

AD-A024 493

RFA-76-U306

OT,  
Burkeltaub

AD

USADACS Technical Library



5 0712 01010869 3

FA-TR-75074

SELF-PHASE MODULATION: A REVIEW

TECHNICAL  
LIBRARY

January 1975

Approved for public release; distribution unlimited.



Pitman-Dunn Laboratory

U.S. ARMY ARMAMENT COMMAND

FRANKFORD ARSENAL

PHILADELPHIA, PENNSYLVANIA 19137

BEST AVAILABLE COPY

BEST AVAILABLE COPY

#### DISPOSITION INSTRUCTIONS

Destroy this report when it is no longer needed. Do not return to the originator.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER FA-TR-75074	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) SELF-PHASE MODULATION: A REVIEW		5. TYPE OF REPORT & PERIOD COVERED Technical Research Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) LLOYD C. BOBB KIMBALL KRAMER		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS FRANKFORD ARSENAL ATTN: SARFA-PDS PHILADELPHIA, PA 19137		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS AMCMS: 611102.11.11D.F1.01 DA PROJ: 1T161102A11D.F1
11. CONTROLLING OFFICE NAME AND ADDRESS US ARMY ELECTRONICS COMMAND ATTN: AMSEL-CT-L FORT MONMOUTH, NJ 07703		12. REPORT DATE FA-TR-75074, January 1975
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 16
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE N/A
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Picosecond pulses Self-Phase modulation Super-broadened continuum		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  Self-phase modulation is described from an experimental and theoretical point of view. Applications for the self-phase modulated continua are given. Recommendations are made for future studies.		

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

## TABLE OF CONTENTS

	<u>PAGE</u>
INTRODUCTION . . . . .	2
BACKGROUND . . . . .	2
THEORETICAL. . . . .	3
EXPERIMENTAL . . . . .	5
APPLICATIONS . . . . .	8
FUTURE STUDIES . . . . .	9
REFERENCES . . . . .	11
DISTRIBUTION . . . . .	13



## INTRODUCTION

In the following paragraphs self-phase modulation (SPM) will be reviewed. A brief background will be given and the process will be described from a theoretical and experimental point of view. The materials studied and the results of the studies will be discussed. The applications of this technique will be explored along with the appropriate experiments. Several future experiments will be proposed.

## BACKGROUND

When a highly intense light pulse propagates through a medium, the electric field of the pulse can alter the index of refraction, which in turn, affects the propagation of the pulse. The time dependent index changes the phase of the wave which changes the temporal and spectral characteristics as well. The spectral broadening which occurs is called self-phase modulation or super broadening. There are a number of mechanisms which can contribute to the index variation: (1) direct electronic cloud distortion, (2) molecular reorientation, (3) molecular redistribution, and (4) librational motion of molecules.

Spectral broadening was first observed in CS<sub>2</sub> by Brewer<sup>1</sup> in 1967. A Q-switched ruby laser with 100 kW peak power was self-focused in the CS<sub>2</sub>. The spectral composition of the self-trapped filaments was observed to not correspond to Raman, Rayleigh, or Brillouin scattering. These experiments were repeated in CS<sub>2</sub> by Shimizu<sup>2</sup> who observed a regular periodic structure superimposed on the frequency broadened spectrum. These results were interpreted in terms of a molecular orientational model. Polloni<sup>3</sup> et al., studied self-focusing and self-phase modulation in CS<sub>2</sub> and interpreted their results in terms of a librational model in which the molecules "rock" in the field of the neighboring molecules.

Brewer and Lee<sup>4</sup> used a mode locked 1.06 $\mu$ m laser to study self-trapping in low viscosity liquids, high viscosity liquids and glass where linear and rotational diffusion modes are frozen out. Their results support a molecular electronic distortion mechanism for the index of refraction change. The importance of the electronic dis-

---

<sup>1</sup> R. G. Brewer, Phys. Rev. Lett. 19, 8 (1967).

<sup>2</sup> F. Shimizu, Phys. Rev. Lett. 19, 1097 (1967).

<sup>3</sup> R. Polloni, C. A. Sacchi, and O. Svelto, Phys. Rev. Lett. 23, 690 (1969).

<sup>4</sup> R. G. Brewer and C. H. Lee, Phys. Rev. Lett. 21, 267 (1968).

tortion mechanism is shown also in several papers by Alfano and Shapiro<sup>5-8</sup>. Self-phase modulation has been investigated recently both experimentally and theoretically near the electronic resonances of a  $\text{PrF}_3$  crystal.<sup>9</sup> Information was obtained on the evolution of the SPM spectrum through and beyond the electronic resonances.

### THEORETICAL

The problem of an intense electromagnetic wave traveling in a medium where the index of refraction depends on the electric field of the light has been studied.<sup>8-14</sup> There are a variety of effects which can occur under the self-action of light waves. Some of these effects are self-phase modulation, self-focusing, self-defocusing, and self-steepening. The following analysis pertains mostly to self-phase modulation:

In looking at picosecond spectra from various media one finds that the light is often self-focused into filaments. This can occur in materials which are homogeneous in the absence of the electromagnetic

- 
- <sup>5</sup> R. R. Alfano and S. L. Shapiro, Phys. Rev. Lett. 24, 1217 (1970).
  - <sup>6</sup> R. R. Alfano and S. L. Shapiro, Phys. Rev. Lett. 24, 592 (1970).
  - <sup>7</sup> R. R. Alfano and S. L. Shapiro, Phys. Rev. Lett. 24, 584 (1970).
  - <sup>8</sup> R. R. Alfano, L. L. Hope, and S. L. Shapiro, Phys. Rev. A 6, 433 (1972).
  - <sup>9</sup> R. R. Alfano, J. I. Gersten, G. A. Zawadzkas, and N. Tzoar, Phys. Rev. A 10, 698 (1974).
  - <sup>10</sup> S. A. Akmanov, R. V. Khokhlov, and A. P. Sukhorukov, Laser Handbook 2, edited by F. T. Arecchi and E. O. Schulz-Dubois (North-Holland Publishing Co., Amsterdam, 1972). Chapter E-3.
  - <sup>11</sup> A. C. Cheung, D. M. Rank, R. Y. Chiao, and C. H. Townes, Phys. Rev. Lett. 20, 786 (1968).
  - <sup>12</sup> R. Y. Chiao, E. Garmire, and C. H. Townes, Phys. Rev. Lett. 13, 479 (1964).
  - <sup>13</sup> T. K. Gustafson, J. P. Taran, H. A. Haus, J. R. Lifstiz, and P. L. Kelley, Phys. Rev. Lett. 177, 306 (1969).
  - <sup>14</sup> F. DeMartini, C. H. Townes, T. K. Gustafson, and P. L. Kelley, Phys. Rev. Lett. 164, 312 (1967).

wave if the dielectric constant increases with field. A phenomenological explanation<sup>12</sup> can be obtained by considering a uniform circular beam of diameter (d) propagating through a medium in which the index of refraction is:

$$n = n_0 + n_2 E^2 + \dots \quad (1)$$

Ordinarily, when all but the first term in the expansion is neglected, the beam would be expected to expand with angular divergence  $\theta \sim 1.22\lambda/n_0 d$ . However, if the term  $n_2 E^2$  is large enough the critical angle for total reflection at the beam edge will be such that all of the energy is confined to the beam. In other words spreading of the beam by diffraction does not occur. The power at which this occurs is:

$$P = \frac{\pi d^2}{4} \frac{n_0 E^2 c}{8\pi} \geq (1.22\lambda)^2 \frac{c}{64n_2} \quad \text{for } \theta \ll 1. \quad (2)$$

Equation (1) can be rewritten as follows in a time dependent form for a single index affecting mechanism of relaxation time  $\tau$ .

$$n(t) = n_0 + \frac{n_2}{\tau} \int_{-\infty}^t e^{-(t-t')/\tau} E^2(t') dt' \quad (3)$$

The electric field of the incident laser pulse is:

$$E(t) = E_0 e^{-t^2/T^2} \cos(\omega_0 t), \quad (4)$$

where T is related to the pulse width at half-maximum. By writing the equation in the above form we have neglected chirping.<sup>15</sup> As the laser pulse propagates through the medium the electric field changes in phase as follows:

$$E(t) = E_0 e^{-t^2/T^2} \left[ \cos \omega_0 t - \phi(t) \right] \quad (5)$$

where

$$\phi(t) = n(t) \omega_0 z / C. \quad (6)$$

This approach ignores dispersion. Dispersion broadens the pulse in time and moves the longer wavelengths to the leading edge of the pulse.

<sup>12</sup> R.Y. Chiao, E. Garmire, and C.H. Townes, Phys. Rev. Lett. 13, 479 (1964).

<sup>15</sup> E.B. Treacy, Phys. Lett. 28A, 34 (1968).



The spectral density of the light which is modulated in phase is given by

$$S(\omega) = (c/4\pi) |E(\omega)|^2 \quad (7)$$

where  $E(\omega)$  is the Fourier transform of  $E(t)$ . Therefore, it can be seen that the spectral density depends on the electric field of the laser pulse in the medium, and the electric field of the laser pulse in the medium depends on how the medium responds to the electric field of the incident laser pulse. To give an example, consider that the  $n_2 E_2$  term arises solely from an electronic mechanism which has a relaxation time  $\tau < 1/\omega_0$ . In other words the index of refraction responds at optical frequencies. In this case the function  $(1/\tau) \exp[-(t - t')/\tau]$  in Equation 3 may be replaced by  $\delta(t - t')$  and Equation 3 becomes

$$n(t) = n_0 + n_2 E_0^2 \exp(-2t^2/T^2) \cos^2(\omega_0 t), \quad (8)$$

and Equation 5 becomes

$$E(t) = E_0 \exp(-t^2/T^2) \cos[\omega_0 t - \omega_0 n_0 z/c - n_2 E_0^2 \omega_0 z/c \exp(-2t^2/T^2) \cos^2(\omega_0 t)] \quad (9)$$

Alfano et al.,<sup>8</sup> Fourier transformed Equation 9, and the spectra for the electronic mechanism were computed numerically for different values of  $n_2 E_0^2 \omega_0 z/c = \beta$  and  $T_f$  which is the pulse full width at half-maximum times  $\sqrt{2}$ . The spectra are symmetric around the input frequency and have a nonperiodic structure of maxima and minima throughout. For  $\beta = 120$  and  $T_f = .4$  psec the spectra extend over  $14000 \text{ cm}^{-1}$ . Going to longer pulses markedly reduces the spectral content.

Using the approach of Shimizu<sup>2</sup> the instantaneous frequency shift may be defined as  $\partial \phi(t)/\partial t$ . This leads to the following relationship

$$\Delta\omega = \omega_0 z n_2 E^2 / c\tau. \quad (10)$$

<sup>2</sup>

F. Shimizu, Phys. Rev. Lett. 19, 1097 (1967).

<sup>8</sup>

R. R. Alfano, L. L. Hope, and S. L. Shapiro, Phys. Rev. A. 6, 433 (1972).

Substituting  $\omega_0 \sim 2 \times 10^4 \text{ cm}^{-1}$ ,  $z \sim 1 \text{ cm}$ ,  $c \sim 3 \times 10^{10} \text{ cm/sec}$ ,  $n_0 E_0^2 \sim 10^{-4} \text{ esu}$  and  $\tau \sim 1 \times 10^{-14} \text{ sec}$ ,  $\Delta\omega \sim 2/3 \times 10^4 \text{ cm}^{-1}$ . This is the amount of broadening expected from an electronic mechanism. From the above equation it would appear that much slower effects ( $\tau$  longer) would have a smaller frequency spread (sweep). However, the value of  $n_2$  for the Kerr effect associated with molecular reorientation is about  $10^3$  times greater than the electronic Kerr effect. Therefore, one can expect a substantial amount of broadening from these slower ( $\sim 10 \text{ psec}$ ) processes associated with molecular reorientation.

### EXPERIMENTAL

A typical experimental arrangement for generating self-phase modulated light is usually comprised of a mode locked Nd or ruby laser, a frequency doubler, a lens for focusing the laser light into a sample cell and a lens for imaging the filaments onto the slits of a spectrograph.

Alfano and Shapiro<sup>5</sup> have demonstrated that significant changes in atomic shape occur under the intense fields of picosecond light pulses in liquid argon and liquid and solid krypton. They focused  $5300\text{\AA}$  mode-locked laser light into a 12 cm sample cell. The beam intensity in the medium was  $\sim 4 \times 10^{11} \text{ W/cm}^2$ . Spectral sweeps of  $1000\text{--}6000 \text{ cm}^{-1}$  were observed on both sides of the laser light. This experiment demonstrated that the electronic mechanism can contribute substantially to SPM.

Frequency broadening was observed in calcite, quartz, sodium chloride, and glass<sup>6</sup> and the mechanism was identified as electronic self-phase modulation. For these studies a Q-switched Nd-glass mode-locked system was used with a KDP doubler. The pulse width was 4 psec and the power was  $\sim 2 \times 10^8 \text{ W}$  at  $5300\text{\AA}$ . The beam was reduced in size by an inverted telescope to 1.2 mm diameter. The filament size in the samples  $\sim 20\mu$ . Typical sweeps were as follows:

<u>MATERIAL</u>	<u>CRYSTAL LENGTH</u>	<u>STOKES SWEEP</u>	<u>ANTI-STOKES SWEEP</u>
Calcite	4 cm	4400 $\text{cm}^{-1}$	6100 $\text{cm}^{-1}$
Quartz	4.5 cm	3900 $\text{cm}^{-1}$	5500 $\text{cm}^{-1}$
Sodium Chloride	4.7 cm	3900 $\text{cm}^{-1}$	7300 $\text{cm}^{-1}$
Dense Flint Glass	7.55 cm	1100 $\text{cm}^{-1}$	-----
Borosilicate Crown	8.9 cm	4200 $\text{cm}^{-1}$	7400 $\text{cm}^{-1}$
Light Barium Crown	8.9 cm	4200 $\text{cm}^{-1}$	7400 $\text{cm}^{-1}$

<sup>5</sup> R. R. Alfano and S. L. Shapiro, Phys. Rev. Lett. **24**, 1217 (1970).

<sup>6</sup> R. R. Alfano and S. L. Shapiro, Phys. Rev. Lett. **24**, 592 (1970).

It was also noted in this paper the SPM was observable within the KDP doubler. The large amount of spectral broadening in these materials indicates relaxation times  $\sim 10^{-15}$  sec, therefore these materials might be useful as a ultrafast light gate.<sup>16</sup>

SPM has been observed in H<sub>2</sub>O and D<sub>2</sub>O,<sup>17,18</sup> The continua generated in these media were recorded by a 3/4 meter spex spectrograph. The Stokes continua was cut-off by the red response of the Polaroid Type 47 film. The anti-Stokes emission extends beyond 3100Å. Sharp inverse Raman absorptions were noted in both media. A measurement of the time width of the continuum pulse shows it to be at least as short as the incident laser pulse.

SPM has been observed in CS<sub>2</sub> by many authors.<sup>1,2,11,19</sup> It was observed that the broadening occurred in discrete bands of frequencies extending to either side of the laser frequency. The bands may be several to tens in number, with a total frequency spread of tens to hundreds of wavenumbers. Cheung et al.,<sup>11</sup> proposed a model which fit their data very well. The model assumes two plane waves of slightly different frequency traveling in a nonlinear medium. The spectral extent of the continua from CS<sub>2</sub>, as well as the degree of symmetry between the Stokes and anti-Stokes light, and the band spacing depend on the time and frequency characteristics of the incident pulse.

The Stokes and anti-Stokes spectra from PrF<sub>3</sub> were investigated using an intense 5300Å picosecond pulse.<sup>9</sup> The peak power was  $\sim 8 \times 10^8$  W and the pulse width was  $\sim 4$  psec. PrF<sub>3</sub> was chosen for this study because of the nearness of the energy of the electronic levels to the energy of the laser light. The continuum extends past the absorptions of the Pr<sup>3+</sup> ion;  $>3000$  cm<sup>-1</sup> on the Stokes side (film limit) and  $>6000$  cm<sup>-1</sup> on the anti-Stokes side. The intensity of the continuum outside the absorptions is

---

<sup>1</sup> R. G. Brewer, Phys. Rev. Lett. **19**, 8 (1967).

<sup>2</sup> F. Shimizu, Phys. Rev. Lett. **19**, 1097 (1967).

<sup>9</sup> R. R. Alfano, J. I. Gersten, G. A. Zawadzkas, and N. Tzoar, Phys. Rev. A **10**, 698 (1974).

<sup>11</sup> A. C. Cheung, D. M. Rank, R. Y. Chiao, and C. H. Townes, Phys. Rev. Lett. **20**, 786 (1968).

<sup>16</sup> M. A. Duguay and J. W. Hansen, App. Phys. Lett. **15**, 192 (1969).

<sup>17</sup> G. E. Busch, R. P. Jones, and P. M. Rentzepis, Chem. Phys. Lett. **18**, 178 (1973).

<sup>18</sup> W. Werncke, A. Lau, M. Pfeiffer, K. Lenz, H. J. Weigmann and C. D. Thuy, Opt. Comm. **4**, 413 (1972).

<sup>19</sup> J. Reintjes, R. L. Carman, and F. Shimizu, Phys. Rev. A **8**, 1486 (1973).



$\sim 10^{-4}$  of the intensity of the central maximum, and the intensity of the continuum inside the absorptions is  $\sim 10^{-2}$  of the intensity of the central maximum.

Additional theoretical and experimental evidence was given supporting the direct electronic distortion model of SPM in calcite, liquid  $\text{CCL}_4$ , liquid argon, solid krypton, and liquid nitrogen.<sup>8</sup> The spectra were characterized by large spectral widths and nonperiodic substructure with an occasional interference structure. The spectral extent on each side of the laser line was the same within 20 percent. The Stokes and anti-Stokes intensities were approximately the same and  $10^2 - 10^3$  less intense than the central frequency.

SPM was observed in  $\text{CS}_2$ , toluene, benzene and nitrobenzene by using a 6 cm cell, a 10 cm focusing lens, a 3/4 m spectrograph and hypersensitized Kodak I-Z spectroscopic plates.<sup>19</sup> The spectra showed interference patterns with the intensity and spacing of the maxima increasing with distance from the central maxima. The average spacing between peaks is  $\sim 50 \text{ cm}^{-1}$ . The extent of the broadening was found to vary considerably from filament to filament. The largest broadening was found in  $\text{CS}_2$  with spectra extending  $500 - 1000 \text{ cm}^{-1}$  on the long and short wavelength sides. The maximum broadening on both sides for toluene was  $300 - 500 \text{ cm}^{-1}$ , and for benzene and nitrobenzene was  $200 - 300 \text{ cm}^{-1}$ . The broadening was found to be fairly symmetrical. The ratio of the energy in the Stokes side to the anti-Stokes side was estimated to be between 1 and 2. The degree of symmetry found here is much greater than that found in spectra generated by Q-switched multi-mode lasers. Although, differences are also found in the spectra generated by different mode-locked lasers.

#### APPLICATIONS

The super-broadened continua arising from self-phase modulation is an extremely valuable research tool because of the frequency extent and the short time frame of the light. A variety of experiments have been performed utilizing these characteristics, and in the following paragraphs a few examples will be given.

---

<sup>8</sup> R. R. Alfano, L. L. Hope, and S. L. Shapiro, Phys. Rev. A, 6, 433 (1972).

<sup>19</sup> J. Reintjes, R. L. Carman, and F. Shimizu, Phys. Rev. A, 8, 1486 (1973).

The inverse Raman spectra has been observed in benzene, carbon disulfide, methanol, liquid nitrogen, and calcite using a 4 psec self-phase modulated continuum.<sup>20</sup> Picosecond pulses at 5300Å were focused into borosilicate BK-7 glass producing light from 4000Å to 7000Å. The low dispersion allows the 5300Å light and the continuum to emerge from the glass simultaneously. The continuum and the laser pulse then enter the sample and are subsequently imaged onto film in a spectrograph. The result is a photograph of the continuum with the Raman absorptions superimposed.

In a recent paper a picosecond flash photolysis and spectroscopy experiment was performed on 3,3'-diethyloxadicarbocyanine iodide.<sup>21</sup> In this experiment the 5300Å light and the continuum are separated and delayed by various amounts up to 4 nsec. One of the interesting features of this experiment is that only the central region of the sample was pumped by the 5300Å pulse and the continuum passed through the entire sample. Therefore, each spectrum has the excited state absorption imaged between the normal absorption, i.e., each spectral shot has its own reference. By introducing suitable delays in the continuum arrival the time dependence of the excited states was established. The excited singlet lifetime is  $1.15 \pm .15$  nsec in ethanol and  $560 \pm 70$  psec in water.

The transient absorption spectra of DTTC was studied using picosecond ruby pulses and a super-broadened continua over the range 400 - 900 nm.<sup>22</sup> A transient absorption band centered at 525 nm with 35 nm width was observed. The dynamical behavior of this absorption was studied utilizing an echelon technique. This echelon delays different segments of the continuum by 13 psec with a total range of 210 spec. The ruby pulse is then timed to be coincident with a given segment of the continuum at the sample. Because segments of the continuum are spread out spatially as well the spectrograph shows the absorption spectra for each segment. In this way the time and frequency characteristics of the transient absorption can be established in a single shot. In this case it was determined that the band at 525 nm has a lifetime of  $90 \pm 30$  psec.

#### FUTURE STUDIES

SPM will be studied in a variety of materials with large electro-optic coefficients which are useful as Q-switches. These materials all have large electric field dependent indices of refraction, with long

---

<sup>20</sup> R. R. Alfano and S. L. Shapiro, Chem. Phys. Lett. 8, 631 (1971).

<sup>21</sup> D. Magde and M. Windsor, Chem. Phys. Lett. 27, 31 (1974).

<sup>22</sup> H. Yashiro and T. Yajima, Chem. Phys. Lett. 25, 582 (1974).



relaxation times. Also, those materials with a reasonably accessible ferroelectric to paraelectric transition will be studied for SPM in the paraelectric state near the transition temperature. If the optical field in these materials can create a local ferroelectric state there will be a substantial change in the index of refraction and a concomitant increase in the SPM. The high fields developed over the short times should allow the examination of the induced polar state in a time and electric field regime never before studied.

In addition to the materials with large electro-optic coefficients a variety of molecules will be studied which are similar but are different in symmetry. For example, various nitrobenzenes and toluences will be compared as well as carbon tetrachloride with chloromethane.

All of the above experiments are designed to aid in the understanding of the SPM process. It is only through the understanding of this effect that it can be either minimized when it is operating as a loss mechanism in high powered lasers or maximized when a highly intense, broad band, short pulsewidth source of radiation is needed. It will be particularly interesting to explore methods for maximizing the SPM in each of the above experiments.

## REFERENCES

1. R. G. Brewer, Phys. Rev. Lett. 19, 8 (1967)
2. F. Shimizu, Phys. Rev. Lett. 19, 1097 (1967).
3. R. Polloni, C. A. Sacchi, and O. Svelto, Phys. Rev. Lett. 23, 690 (1969).
4. R. G. Brewer and C. H. Lee, Phys. Rev. Lett. 21, 267 (1968).
5. R. R. Alfano and S. L. Shapiro, Phys. Rev. Lett. 24, 1217 (1970).
6. R. R. Alfano and S. L. Shapiro, Phys. Rev. Lett. 24, 592 (1970).
7. R. R. Alfano and S. L. Shapiro, Phys. Rev. Lett. 24, 584 (1970).
8. R. R. Alfano, L. L. Hope, and S. L. Shapiro, Phys. Rev. A 6, 433 (1972).
9. R. R. Alfano, J. I. Gersten, G. A. Zawadzkas, and N. Tzoar, Phys. Rev. A 10, 698 (1974).
10. S. A. Akmanov, R. V. Khokhlov, and A. P. Sukhorukov, Laser Handbook 2, edited by F. T. Arecchi and E. O. Schulz-Dubois (North-Holland Publishing Co., Amsterdam, 1972). Chapter E-3.
11. A. C. Cheung, D. M. Rank, R. Y. Chiao, and C. H. Townes, Phys. Rev. Lett. 20, 786 (1968).
12. R. Y. Chiao, E. Garmire, and C. H. Townes, Phys. Rev. Lett. 13, 479 (1964).
13. T. K. Gustafson, J. P. Taran, H. A. Haus, J. R. Lifstiz, and P. L. Kelley, Phys. Rev. Lett. 177, 306 (1969).
14. F. DeMartini, C. H. Townes, T. K. Gustafson, and P. L. Kelley, Phys. Rev. Lett. 164, 312 (1967).
15. E. B. Treacy, Phys. Lett. 28A, 34 (1968).
16. M. A. Duguay and J. W. Hansen, App. Phys. Lett. 15, 192 (1969).
17. G. E. Busch, R. P. Jones, and P. M. Rentzepis, Chem. Phys. Lett. 18, 178 (1973).
18. W. Werncke, A. Lau, M. Pfeiffer, K. Lenz, H. J. Weigmann and C. D. Thuy, Opt. Comm. 4, 413 (1972).
19. J. Reintjes, R. L. Carman, and F. Shimizu, Phys. Rev. A 8, 1486 (1973).

REFERENCES (Cont'd)

20. R. R. Alfano and S. L. Shapiro, Chem. Phys. Lett. 8, 631 (1971).
21. D. Magde and M. Windsor, Chem. Phys. Lett. 27, 31 (1974).
22. H. Yashiro and T. Yajima, Chem. Phys. Lett. 25, 582 (1974).

# DISTRIBUTION

Department of the Army  
Deputy Chief of Staff for  
Research, Development, and  
Acquisition  
Washington, DC 20310

1 Attn: DAMA-ARZ, Rm. 3E364  
Dr. M.E. Lasser  
Chief Scientist

1 Attn: DAMA-ARZ, Rm. 3E365  
Dr. V. Garber

1 Attn: DAMA-ARZ, Rm. 3E365  
Dr. I.R. Hershner, Jr.

1 Attn: DAMA-ARZ, Rm. 3E365  
Dr. R. Watson

1 Attn: DAMA-ARS, Rm. 3E365  
Dr. C.H. Church

1 Attn: DAMA-ARS, Rm. 3E365  
Dr. F. Verderame

Commander  
US Army Materiel, Development and  
Readiness Command  
5001 Eisenhower Avenue  
Alexandria, VA 22333

1 Attn: AMCDL,  
Mr. N. Klein

1 Attn: DRCRD,  
BG H. Griffith

1 Attn: DRCRD-PE,  
Mr. T. Jasczcult

1 Attn: DRCRD-TP,  
Mr. P. Chernoff

1 Attn: DRCRD-BC,  
Mr. Z. Tashjian

1 Attn: DRCRD-MT,  
Mr. E. Sedlak

1 Attn: DRCRD-TC,  
Mr. R. Zentner

Commander  
US Army Armament Command  
Rock Island, IL 61201

1 Attn: DRSAR-CG,  
MG J. Raaen

1 Attn: DRSAR-RD,  
Mr. J. Brinkman

1 Attn: DRSAR-RDT,  
Mr. J. Turkeltaub

1 Attn: DRSAR-RDT,  
Dr. R.L. Moore

1 Attn: DRSAR-RDM,  
Mr. R. Chandler

1 Attn: DRSAR-RDC,  
Mr. E. Vaughan

Commander  
Aberdeen Proving Ground  
Aberdeen, MD 21005

1 Attn: AMSTE-SA-E,  
Mr. J. Bialo

1 Attn: AMSTE-ME,  
Mr. J. Steedman

1 Attn: AMXBR-TD,  
Dr. R. Eichelberger

1 Attn: AMXSY-D,  
Dr. J. Sperrazza

1 Attn: AMXSY-GS,  
Mr. C. Odom

Commander  
Harry Diamond Laboratories  
2800 Powder Mill Road  
Adelphi, MD 20783

1 Attn: AMXDO-RCB,  
Dr. H. Gibson

1 Attn: AMXDO-RCB,  
Dr. T. Gleason

DISTRIBUTION (Cont'd)

Assistant Director  
Engineering Technology  
Pentagon  
Attn: ODDR&E, Room 3D1089  
Mr. J. Persh  
Washington, DC 20310

Dr. R.E. Schwartz  
Pentagon  
Attn: ODDR&E/TWP, Room 3E1025  
(Land Warfare)  
Washington, DC 20310

US Army Foreign Science &  
Technology Center  
Attn: AMXST-BS (Stop 196)  
Munitions Bldg.  
Washington, DC 20315

Headquarters, USAF  
Pentagon  
Attn: AF/RDPA, Room 5D332  
LTC Guest  
Washington, DC 20310

Commander  
US Army Electronics Command  
Fort Monmouth, NJ 07703

1 Attn: AMSEL-CT-L,  
Mr. B. Louis

1 Attn: AMSEL-CT-L,  
Dr. R. Buser

1 Attn: AMSEL-CT-L,  
Mr. V. DeMonte

1 Attn: AMSEL-CT-L,  
Mr. M. Mirachi

Commander  
US Army Electronic Proving Ground  
Attn: STEEP-T-B1  
Fort Huachuca, AZ 85613

Commander  
US Army Missile Command  
Redstone Arsenal, AL 35809

1 Attn: DRSMI-RR,  
Dr. G. Miller

1 Attn: DRSMI-RR,  
MAJ M. O Neill

1 Attn: DRSMI-R,  
Dr. J. McDaniel

1 Attn: DRSMI-REI,  
Mr. John Asbell

1 Attn: DRSMI-RFGA,  
Mr. Fowler

1 Attn: DRSMI-R,  
Dr. R. Conrad

Commander  
White Sands Missile Range  
White Sands, NM 88002

1 Attn: AMSEL-WL-ML,  
Mr. J. Bert

1 Attn: STEWS-ID-A,  
Mr. G. Galos

Commander  
US Army Dugway Proving Ground  
Attn: STEDP-TL, Technical Library  
Dugway, UT 84022

Commander  
Yuma Proving Ground  
Attn: STEYP-AD, Technical Library  
Yuma, AZ 85364

Commander  
US Army Research Office-Durham  
Box CM, Duke Station  
Attn: Dr. R.J. Lontz  
Durham, NC 27706



DISTRIBUTION (Cont'd)

Commander  
US Army Natick Research and  
Development Command  
Attn: AMXRE-PRD, Dr. E. Healy  
Natick, MA 07160

Commander  
Naval Research Laboratory  
Washington, DC 20390

1 Attn: Bldg. 58,  
Dr. R. Andersen

1 Attn: Bldg. 42,  
Dr. A. Schindler

Commander  
Air Force Armament Laboratories  
Attn: DLOS  
Eglin AFB, FL 32542

Commander  
Rocky Mountain Arsenal  
Attn: SARRM-CS, Dr. W. McNeill,  
Chief Scientist  
Denver, CO 80240

President  
US Army Armor & Engineering Board  
Attn: STEBB-CV  
Fort Knox, KY 40121

Director Electronic Warfare  
Electronic Warfare Laboratory  
Fort Monmouth, NJ 07703

1 Attn: AMSEL-WL-D,  
Mr. J. Charlton

1 Attn: AMSEL-WL-D,  
Mr. C. Hardin

Advisory Group on Electron Devices  
Attn: Secretary, Working Group  
on Lasers  
201 Varick St.  
New York, NY 10014

Advanced Research Projects Agency  
Attn: Dr. P. Clark  
Architect Bldg.  
1400 Wilson Blvd.  
Arlington, VA 22209

MG S. Meyer  
Commander  
Attn: MASSTER  
Fort Hood, TX 76544

Dr. M.P. Pastel  
Scientific Advisor-TRADOC  
Attn: ATDC-SI  
Fort Monroe, VA 23651

COL Richard McLean  
Weapons System Evaluation Group  
400 Army/Navy Drive  
Arlington, VA 22202

Institute for Defense Analyses  
400 Army/Navy Drive  
Arlington, VA 22202

1 Attn: Classified Library

1 Attn: Mr. V. Corcoran

Department of the Air Force  
Air Force Avionics Laboratory (AFS)  
Wright Patterson AFB, OH 45433

1 Attn: Mr. R. Firsdon

1 Attn: ASD/RWT

Air Force Weapons Laboratory  
Kirtland Air Force Base  
Attn: CPT M. Kemp, Bldg. 497  
Albuquerque, NM 87116

Mr. Everett Richey  
School of Aerospace Medicine  
Brooks Air Force Base  
San Antonio, TX 78235

DISTRIBUTION (Cont'd)

Defense Documentation Center (12)  
Cameron Station  
Alexandria, VA 22314

Commander  
Frankford Arsenal  
Philadelphia, PA 19137

1 Attn: SARFA-AOA-M/107-B  
1 Attn: SARFA-TD/107-1  
1 Attn: SARFA-GC/40-1  
1 Attn: SARFA-PD/64-4  
1 Attn: SARFA-PDR/64-4  
6 Attn: SARFA-PDS/64-4  
1 Attn: SARFA-PDC/64-3  
1 Attn: SARFA-FC/110-1  
1 Attn: SARFA-FCD-O/201-2,  
Mr. S.C. Novak  
1 Attn: SARFA-QA/219-3  
2 Attn: SARFA-FI/219-3  
1 Attn: SARFA-PA/107-2  
3 Attn: SARFA-TSP-L/51-2  
1 - Reference Copy  
1 - Circulation  
1 - Tech Reports Editing

Printing & Reproduction Division  
FRANKFORD ARSENAL  
Date Printed: 5/7/76