



### **Calhoun: The NPS Institutional Archive**

### **DSpace Repository**

Theses and Dissertations

Thesis and Dissertation Collection

1976

## The effect of rapid raising of the bow seal on early transition of the XR-3 captured air bubble testcraft.

## Moore, Wayne Thomas

Monterey, California. Naval Postgraduate School

http://hdl.handle.net/10945/17742

Downloaded from NPS Archive: Calhoun



Calhoun is a project of the Dudley Knox Library at NPS, furthering the precepts and goals of open government and government transparency. All information contained herein has been approved for release by the NPS Public Affairs Officer.

> Dudley Knox Library / Naval Postgraduate School 411 Dyer Road / 1 University Circle Monterey, California USA 93943

http://www.nps.edu/library

THE EFFECT OF RAPID RAISING OF THE BOW SEAL ON EARLY TRANSITION OF THE XR-3 CAPTURED AIR BUBBLE TESTCRAFT

Wayne Thomas Moore

## NAVAL POSTGRADUATE SCHOOL Monterey, Galifornia



## THESIS

The Effect of Rapid Raising of the Bow Seal on Early Transition of the XR-3 Captured Air Bubble Testcraft

bу

Wayne Thomas Moore

March 1976

Thesis Advisor:

D.M. Layton

Approved for public release; distribution unlimited.

UNCLASSIFIED						
SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)						
REPORT DOCUMENTATION PAGE	BEFORE COMPLETING FORM					
T. REPORT NUMEER 2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER					
TITLE (and Sublille) The Effect of Rapid Raising of the Bow Seal on Early Transition of the XR-3	<ol> <li>TYPE OF REPORT &amp; PERIOD COVERED Master's Thesis March 1976</li> <li>PERFORMING ORG. REPORT NUMBER</li> </ol>					
Laptured Air Buddle lestcraft						
7. AUTHOR() Wayne Thomas Moore	8. CONTRACT OR GRANT NUMBER(s)					
S. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, CA 93940	10. PHOGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS					
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE					
Naval Postgraduate School	March 1976					
Monterey, CA 93940	13. NUMBER OF PAGES					
A MONITORING AGENCY NAME & ADDREEGH different for Constitute Office	39					
Naval Postgraduate School Monterey, CA 93940	UNCLASSIFIED 15. DECLASSIFICATION/DOWNGRADING SCHEDULE					
17. DISTRIBUTION STATEMENT (of the obstract entered in Plack 20, if different fro	an Report)					
16. SUPPLEMENTARY NOTES	·····					
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) XR-3 Air Bubble Testcraft Bow-Seal-Raising Transition	,					
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)						
A series of tests was conducted to de rapid raising of the bow seal on the tran captured air bubble testcraft.	termine the effects of sition of the XR-3					
The report contains a brief description the installed air spring seal, and seal p	on of the testcraft, of osition control					
D FORM 1473 EDITION OF I NOV 65 IS OBSOLETE (Page 1) S/N 0102-014-6601   UN	CLASSIEIED					

SECURITY CLASSIFICATION OF THIS PAGE (When Date Enternd

20. Abstract (continued)

mechanisms. A short description of the data gathering and reduction systems is also included.

The report then presents data in the form of bar graphs showing the thrust and velocity required for normal and bowseal-raising transition. Finally, the conclusions that may be drawn from the data are presented. The Effect of Rapid Raising of the Bow Seal on Early Transition of the XR-3 Captured Air Bubble Testcraft

by

Wayne Thomas Moore Lieutenant, United States Navy B.S., United States Naval Academy, 1969

Submitted in partial fulfillment of the requirements for the degree of

MASTER OF SCIENCE IN AERONAUTICAL ENGINEERING

from the

NAVAL POSTGRADUATE SCHOOL March 1976

NAVAL F. SI ATLA COL

#### ABSTRACT

A series of tests was conducted to determine the effects of rapid raising of the bow seal on the transition of the XR-3 captured air bubbles testcraft.

The report contains a brief description of the testcraft, of the installed air spring seal, and seal position control mechanisms. A short description of the data gathering and reduction systems is also included.

The report then presents data in the form of bar graphs showing the thrust and velocity required for normal and bow-seal-raising transition. Finally, the conclusions that may be drawn from the data are presented.

#### TABLE OF CONTENTS

Ι.	INTI	RODUCT	ION	- 7
	Α.	DESC	RIPTION OF THE XR-3	- 7
	Β.	THE .	AIR SPRING SEAL	- 9
		1.	Description	- 9
		2.	Position Control Mechanism	- 10
	С.	SEAL	SHAPE	- 10
II.	TEST	FING P	ROCEDURES	- 11
	Α.	GENE	RAL	- 11
	Β.	DATA	ACQUISITION	- 11
		1.	Thrust Measurement	- 11
		2.	Velocity Measurement	- 12
		3.	Pitch Angle Measurement	- 12
		4.	Data Recording	- 13
	С.	DATA	REDUCTION	- 13
	D.	TEST	RUNS	- 15
		1.	General	- 15
		2.	Normal Transition Procedure	- 16
		3.	Bow-Seal-Raising Transition Procedure	- 16
III.	RESI	JLTS -		- 18
IV.	CON	CLUSIO	۷۶	- 20
LIST	0F I	REFERE	VCES	- 38
INIT	IAL I	DISTRI	BUTION LIST	- 39

#### LIST OF FIGURES

1.	Normal Configuration of the XR-3	22
2.	Seal Section	23
3.	Bow Seal	24
4.	Bow Seal Height Control	25
5.	Bow Seal Shape (Unpressurized)	26
6.	Bow Seal Shape (Pressure = 20 PSF)	27
7.	Bow Seal Deflection vs. Seal Count	28
8.	Normal Transition (Runs 4501-4505)	29
9.	Bow-Seal-Raising Transition	30
10.	Comparison of Thrust	31
11.	Comparison of Velocity	32
12.	Normal Transition (Runs 4601-4607)	33
13.	Bow-Seal-Raising Transition	34
14.	Comparison of Thrust	35
15.	Comparison of Velocity	36
16.	Pitch Angle	37

#### I. INTRODUCTION

Future development and growth of the United States Navy force the need for high speed surface combatants with the ability to obtain speeds in excess of fifty knots. Conventional displacement hulls, with their inherent high drag, cannot achieve this capability without the use of massive power plants. One particularly attractive alternative to conventional hull design is the surface effect ship. The U.S. Navy presently has an active program of research into the characteristics of this type of vessel. Under the sponsorship of the Surface Effects Ships Project Office (SESPO), the Naval Postgraduate School has operated the XR-3 captured air bubble testcraft in an on-going series of test programs since the summer of 1970.

The focus of this report is on one series of these tests. The purpose of these tests was to determine the effect of bow seal movement during transition upon the performance of the XR-3 testcraft. All tests were performed at the San Antonio Lake test site in California.

#### A. DESCRIPTION OF THE XR-3

The XR-3 testcraft operated by the Naval Postgraduate School is a captured air bubble type of surface effect ship. It has a beam of 12 feet, an overall length of 24 feet, and weighs approximately 6,000 pounds in the test configuration with a crew of two men.

The twin hull construction, similar to that of a catamaran sailing craft, is the most prominent physical feature of the testcraft. Installed between the side hulls at the bow and stern of the testcraft are flexible, inflated air spring seals. These seals, together with the side hulls, form a sealed plenum chamber beneath the testcraft. About 80% of the total testcraft weight is supported by the large aerostatic lift force created by pressurization of the plenum chamber. The remaining testcraft weight is principally supported by the displacement lift of the side hulls. The side hulls draw between two and ten inches of water, contingent upon the testcraft weight and center of gravity. The water level inside the chamber is lower than the external level, due to the pressurization of the plenum.

Five axial fans, each driven by an aircooled, internal combustion engine, pressurize the plenum chamber. The plenum is directly pressurized by two of these engines, while two more selectively pressurize the bow seal. The fifth engine is used to pressurize the rear seal.

A 110 volt, 1,500 watt a.c. generator, located on deck, aft of the lift engine compartment, provides power for the data acquisition systems.

Located on the aft end of the side hulls, outboard of the stern seal, are two 40-horsepower outboard motors that provide the propulsion for the XR-3. In order to reduce propeller side force effects to a minimum, the motors are

configured so that the port and starboard propellers rotate in opposite directions.

There are two crew member positions aboard the XR-3; the pilot controls all maneuvering and data collection functions, while the observer has no specific duties other than observation and safety.

B. THE AIR SPRING SEAL

#### 1. Description

The XR-3 presently uses air spring seals that were installed in the winter season of 1972-73, replacing the semi-rigid seals originally provided with the testcraft. The Naval Ships Research and Development Center, CARDEROCK, Maryland designed and fabricated the new seals.

The construction of the bow and stern seals is identical, the only difference being in the rigging of the position control cables. Each seal is comprised of a two-cell rubberized fabric air bag which is attached to the underside of the plenum chamber (termed "wet deck"). Twelve steel spring stiffeners, measuring 48" x 4" x 1/4", are constructed in the lower surface of the seal to give strength and shape to the seal (see Figure 2). To provide a measure of rate damping of seal motion, the cells of the air bag are divided by a perforated fabric in order to control the rate of airflow from one cell to the other. The seals may be selectively pressurized over a range of pressures in order to obtain various spring constants.

#### 2. Position Control Mechanism

Two downstop rings are attached to each of the steel spring stiffeners; one six inches forward of the trailing edge, and one 30 inches forward of the trailing edge.

On the bow seal, each of the forward downstop rings is connected by a steel shackle to an aluminum bar that runs across the craft's beam the full width of the seal. The aft downstop rings are attached to a second bar in an identical manner. Two steel cables connect each of these bars to an electrically operated winch. The winch capstan is divided into two sections of dissimilar diameter. The capstan section diameters were chosen so that the seal could be raised evenly, rotating about the hinge line, by winding the cables from the more forward downstops on the smaller section and the cables from the aft downstops on the larger section (see Figures 3 and 4).

#### C. SEAL SHAPE

Figures 5 and 6 show the contours of the seals in both the pressurized and unpressurized states. The shapes of the bow and stern seals are identical, being slightly bowed. The bowed shape of both seals becomes much more pronounced under pressurization.

#### II. TESTING PROCEDURE

#### A. GENERAL

The purpose of this series of tests was to investigate the effect of raising the bow seal upon the transition performance of the XR-3 and determine if an early transition (lower thrust and lower velocity) could be obtained. A series of test runs was conducted to determine the thrust (or drag) to velocity relationship at transition that existed with and without raising the seal. These relationships were then graphically compared to determine the effect of raising the bow seal.

#### B. DATA ACQUISITION

The instrumentation aboard the XR-3 is quite extensive. Sensors are installed to measure thrust, velocity, accelerations, angular displacements and rates about all axes, rudder angle, plenum and seal pressures, and height of a reference point above water. In this test series, the parameters of interest were thrust, velocity and pitch angle.

#### 1. Thrust Measurement

To insure only readings of longitudinal forces, the thrust of each outboard motor is transmitted to a balanced-bridge load cell by a parallelogram linkage. The output of the load cell is amplified to a range of 0.0 to

1.0 volts d.c. for compatibility with the onboard tape recorder. The voltage range corresponds to a thrust range of 0 to 500 pounds.

#### Velocity Measurement

The testcraft velocity is measured by a Potter velocity meter located on a supporting strut in the undisturbed water ahead of the testcraft (see Figure 1). The meter consists of a small magnetized free turbine in an axial duct contained in a bomb-shaped probe. The rotating turbine wheel induces a sinusoidal voltage in a pickup coil located in the probe body. The signal frequency is directly proportional to flow through the meter, thus to the testcraft velocity. A velocity conditioning unit consisting of a frequency to voltage converter, provides a signal of 0.0 to 5.0 yolts d.c. that corresponds to testcraft velocities of 0 to 40 knots. This signal is split, one branch being reduced in voltage to 0.0 to 1.0 volts d.c. for compatibility with the data recording equipment. The other signal branch drives a d.c. voltmeter, that has been calibrated in knots, located on the pilot's instrument panel.

#### 3. Pitch Angle Measurement

The Pitch Angle was measured using the Humphrey's Model CF18-0101-1 gyro package which is capable of measuring pitch, roll and yaw displacement and pitch, roll and yaw rates.

#### 4. Data Recording

A Pemco model 120 magnetic tape recorder automatically records all data taken onboard the XR-3. The tape recorder simultaneously records fourteen channels of data from the electronic sensors and, in addition, the comments and observations of the pilot on a voice edge track. Recording accuracy is 1/2% for an input range for each channel of -1.0 to +1.0 volts d.c. The Pemco recorder, located in a compartment aft of the pilot's cockpit, is controlled by means of a remote control system on the pilot's instrument panel. The 26 volt d.c. power required by the recorder is provided by a Pemco power supply which obtains its power from the 110 volt d.c. generator. A digital voltmeter connected to the data inputs through a rotary selector switch enables the pilot to monitor the input to any channel. The Pemco recorder is easily portable, thus it can be taken out of the XR-3 to the Mobile Data Facility, where data may be immediately reduced and analyzed, at the completion of each day's operation. Reference | provides additional information on the data collection and recording system.

#### C. DATA REDUCTION

The XR-3 Mobile Data Facility is contained in a 26-foot Champion motor home. A part of the interior furnishings have been removed and a complete data reduction system has been installed. The motor home also provides berthing and messing for XR-3 personnel during extended operations, in

addition to the data reduction facilities and working space. The mobile facility supplies power for the data systems from a self-contained gasoline-powered 110 volt, 5,000 watt a.c. generator. A Pemco power supply is used to provide power to the tape recorder, while all other equipment uses the 110 volt a.c. power directly.

The data reduction equipment, in addition to the tape recorder, consists of:

- Signal selector and conditioning unit
- Analog to digital converter and calculator interface module
- 3. Monroe model 1880 calculator
- 4. Monroe model PL-4 digital X-Y plotter
- Hewlett-Packard model 7100-B two-channel strip chart recorder

The signal selector and conditioning unit is of major importance to the data reduction system. It conditions the raw analog data from the tape recorder to supply the proper signals to the strip chart recorder and to the Monroe calculator for display on the Monroe X-Y plotter. All fourteen channels of raw analog data on the tape recorder are accepted by the signal conditioning unit. The operator may output any given parameter on any of nine output channels through the use of a selector panel. A summing circuit is also provided which combines the port and starboard thrust signals to provide a total thrust signal. The unit also filters out high-frequency noise from the data and provides

a means for adjusting the null and range of the conditioned output. The strip chart recorder displays any two channels of analog data. For further calculations on the Monroe calculator or plotting on the X-Y plotter, the conditioned analog data may also be converted to digital form. A complete description of the data reduction system may be found in reference 2.

D. TEST RUNS

1. <u>General</u>

The test runs were conducted so as to obtain thrust, velocity and pitch angle during transition both without raising and with raising the bow seal at several seal positions. The weight and center of gravity of the testcraft were held constant as possible during the runs.

Before conducting the test series, the date, crew, data channelization, weight, and center of gravity were annotated on the voice track of the tape recorder. All channels were calibrated to enable accurate setting of the null and range on the data reduction equipment. The thrust load cells had known loads of 0, 250, and 500 pounds applied, and a zero velocity signal was recorded. Once upon the water, a twenty-knot velocity calibration was conducted and recorded.

Prior to each test run, the pilot prefaced the tape with the known data for that run. This included seal

position, weight, center of gravity, and factors that may affect the conduct of the test such as wind and sea conditions.

All tests were conducted in calm water conditions, and, as nearly as possible, in calm wind conditions. Due to the size of the XR-3, aerodynamic drag forces, though unknown, are certainly significant. In order to minimize any variations in aerodynamic drag between upwind and downwind runs, tests were held only under very light wind conditions.

#### 2. Normal Transition Procedure

With the testcraft in a stopped position, engines at idle, both seals were set at minimum pressurization and plenum pressure set at 23.5 pounds per square foot. Power was then added slowly, while maintaining heading with rudder, until transition over the secondary hump occurred. Thrust, velocity and pitch angle were continuously recorded during each run.

#### 3. Bow-Seal-Raising Transition Procedure

Seal and plenum pressure were set as in the normal transition procedure. Power was added slowly until the velocity was just below that for transition. As velocity increases, the air venting under the side walls moves aft and at the transition point this venting is approximately even with the blower engine compartment. The addition of power is halted at this point, prior to transition, and held

steady to ascertain that the testcraft is in fact below transition. Once this is confirmed, the bow seal is raised electrically by means of an "up" switch in the cockpit. Heading is held steady with rudder while the testcraft transitions over the secondary hump.

In runs 4601 through 4607, the trailing edge of the bow seal was raised two inches above the skeg keel, and the position of the forward downstop varied as in runs 4501 through 4505. This was done in an attempt to investigate the effects of the bow raising transition procedure with a more rounded trailing edge shape.

The data from these runs are shown in Table I.

It was desired to make additional runs to validate the data, but this was precluded by a gross failure of the bow seal retraction mechanism in December 1975. Due to the urgency of installing a modified rear seal support system, the XR-3 was removed from service temporarily in January 1976 and no time was available for additional runs.

#### III. RESULTS

Figures 8 through 16 present the data in the form of bar graphs, collected from the test series. Each bar graph relates thrust and velocity during transition for both the normal and bow-seal-raising procedures. Figure 17 shows the pitch angle of the testcraft with time.

Upon examination of the graphs, the following may be observed:

1. In runs 4501 through 4505 (Figures 8 through 11): There is a marked improvement in both thrust and velocity for transition with the bow-seal-raising procedures. No effect is observed with the bow seal in the relaxed position, but as the center downstop position is raised, an increased improvement is observed, in both thrust and velocity, until an optimum is reached around a downstop position of 0.68 inches. After this, the effect of raising the bow seal for transition is decreased and approaches the thrust and velocity levels required for normal transition. 2. In runs 4601 through 4607 (Figures 12 through 16): The thrust required for transition is less than that of the 4500 series runs, yet follows the same general pattern. There is still an improvement by use of the bow-seal-raising procedure, but not as marked as the

4500 series runs. The optimal bow-seal-raising transition occurs at a downstop position of 0.51 inches. Velocity at transition is also less than the normal transition and follows the pattern of thrust improvement.

Qualitative tests with rapid raising and lowering of the bow seal effected transition in the same manner as though the bow seal were raised and not lowered. Approximately 2 seconds are required for the seal to go from full down to full up, and approximately 1.5 seconds from full up to full down positions. The testcraft begins to dip (nose down pitch) at the moment the seal begins to raise, but almost immediately pitches up and transitions.

In general, the bow-seal-raising procedure does effect an early transition provided the seal shape is not flattened beyond the optimal. Reference 4 provides information on seal shape variations. The bow-seal-raising procedure produces more dramatic lowering of thrust and velocity with the bow seal trailing edge in the full down, unrestrained position.

#### IV. CONCLUSIONS

From the data presented, the following conclusions have been drawn:

 It is possible to effect an early transition (lower thrust and lower velocity) by raising the bow seal, provided the seal shape is optimal (see Reference 4).

2. With the bow seal in the relaxed position, raising the bow seal does not permit overriding the bow wave. However, as the seal shape is flattened by pulling up on the center downstop, raising the bow seal effects an early transition. 3. If the bow seal shape is flattened beyond the optimum shape, the early transition is "delayed" and approaches the normal transition as a limit. 4. Positioning of the static seal shape with respect to the sidewall (raising the trailing edge as in the 4600-series runs) although providing a general improvement in thrust required for transition, does not create as dramatic an improvement in the bow-seal-raising mode as it did in the 4500 series runs.

															j	
⊖min (Deg)			2.1	1.4	1.1	1.1	1.4	ssure	1.8	1.6	1.1	1.2	1.8	sput	ty 119	
Velocity# (kts)	ssure		6.0	5.3	5.2	5.2	5.9	Minimum Pre	6.0	5.8	5.3	5.2	5.9	aht 6010 pot	ter of Gravi	
Thrust# (1bs)	Minimum Pre		395	385	375	375	380	Skeg Keel,	330	351	350	320	342	Wei	Cen	
⊖ss (Deg)	Keel,	ssure	2.1	2.1	2.1	2.1	2.2	s Above ssure	1.8	1.9	1.9	1.9	2.0	C)		F
Velocity* (kts)	Edge at Skeg	Minimum Pre:	6.0	5.8	6.0	6.1	6.0	Edge 2 Inche: Minimum Pre:	6.0	6.0	6.0	6.0	6.0	ʻfaximum Valuo	aximum Value	al Transition 30w Seal
Thrust* (1bs)	- Trailing B	- Relaxed,	395	392	510	415	395	- Trailing   - Relaxed,	330	357	368	330	345	ndarv Hump 1	dary Hump Ma	ngle – Norma – Raising I
Center Downstop Position (Inches from relaxed position)	Bow Seal	Rear Seal	0.00	0.25	0.51	0.68	1.00	Bow Seal Rear Seal	0.00	0.25	0.37	0.51	1.00	Transition - Seco	1g Bow Seal - Secon	ceady State Pitch A linimum Pitch Angle
Run N°			4501	4502	4503	4504	4505		4601	4602	4603	4604	4605	* Normal	# Raisin	© <sub>ss</sub> - St ⊙min - M

TABLE I







Figure 2







Figure 4



Figure 5







# SEAL POSITION



THRUST VELOCITY

NORMAL TRANSITION BOW SEAL TRAILING EDGE FULL DOWN





NORMAL

SEAL RAISING

COMPARISON OF VELOCITY BOW SEAL TRAILING EDGE FULL DOWN



FIGURE 11

 $\square$ 

VELOCITY THRUST



FIGURE 12

 $\square$ 

THRUST VELOCITY

> BOW-SEAL-RAISING TRANSITION BOW SEAL TRAILING EDGE UP 2 INCHES

1.00 0.51 0.37 0.25 • 0.0 370 + 360 (S81) ткият 340 340 330 320 6.15 6.0+ 5.7+ 5.9 5.8+ 5.6+ 5.5+ 5.3 5.4 5.2+ 5.1 **NELOCITY (KTS)** 



# SEAL POSITION



тнкизт (гвз)

SEAL RAISING NORMAL COMPARISON OF VELOCITY BOW SEAL TRAILING EDGE UP 2 INCHES

 $\square$ 



AELOCITY (KTS)



#### LIST OF REFERENCES

- Feeney, James Leo, XR-3 Data Acquisition System for <u>Performance Evaluation</u>, M.S. Thesis, Naval Postgraduate School, Monterey, March 1972.
- Dabberi, Peter Vincent Jr., <u>Data Reduction System for</u> the XR-3 Captured Air Bubble Testcraft, M.S. Thesis, Naval Postgraduate School, Monterey, December 1973.
- O'Malley, John Francis, and Belden, William Ellsworth, Jr., Design Modification and Preliminary Performance Evaluation of the XR-3, A Captive Air Bubble Testcraft. M.S. Thesis, Naval Postgraduate School, Monterey, June 1973.
- Moloney, Robert William, <u>The Effect of Seal Shape</u> <u>Variations Upon the Performance of the XR-3 Captured</u> <u>Air Bubble Testcraft</u>, M.S. Thesis, Naval Postgraduate <u>School</u>, Monterey, March 1975.

#### INITIAL DISTRIBUTION LIST

		No.	Copies
1.	Defense Documentation Center Cameron Station Alexandria, VA 22314		2
2.	Library, Code 0212 Naval Postgraduate School Monterey, CA 93940		2
3.	Department Chairman, Code 57Be Department of Aeronautics Naval Postgraduate School Monterey, CA 93940		1
4.	Assoc. Prof. D.M. Layton, Code 57Ln Department of Aeronautics Naval Postgraduate School Monterey, CA 93940		3
5.	LT Wayne Thomas Moore, USN 549 Jefferson Avenue Lake Geneva, WI 53147		1
б.	Naval Sea Systems Command PMS-304-31A Box 34401 Washington, DC 20034		1

