



Calhoun: The NPS Institutional Archive

DSpace Repository

Theses and Dissertations

Thesis and Dissertation Collection

1976

Mathematical model for small arms fire against low-flying aircraft.

Padua, Purwo A.

Monterey, California. Naval Postgraduate School

http://hdl.handle.net/10945/17848

Downloaded from NPS Archive: Calhoun



Calhoun is a project of the Dudley Knox Library at NPS, furthering the precepts and goals of open government and government transparency. All information contained herein has been approved for release by the NPS Public Affairs Officer.

> Dudley Knox Library / Naval Postgraduate School 411 Dyer Road / 1 University Circle Monterey, California USA 93943

http://www.nps.edu/library

MATHEMATICAL MODEL FOR SMALL ARMS FIRE AGAINST LOW-FLYING AIRCRAFT

Purwo A. Padua

NAVAL POSTGRADUATE SCHOOL Monterey, California



THESIS

MATHEMATICAL MODEL FOR SMALL ARMS FIRE AGAINST LOW-FLYING AIRCRAFT

Ъy

Purwo A. Padua

March 1976

Thesis Advisor:

Joseph B. Tysver

Approved for public release; distribution unlimited.

T174027

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered) READ INSTRUCTIONS REPORT DOCUMENTATION PAGE BEFORE COMPLETING FORM . REPORT NUMBER 2. GOVT ACCESSION NO. 3. RECIPIENT'S CATALOG NUMBER 4. TITLE (and Subtitie) 5. TYPE OF REPORT & PERIOD COVERED Master's Thesis Mathematical Model for Small Arms Fire March 1976 Against Low-Flying Aircraft 6. PERFORMING ORG. REPORT NUMBER 8. CONTRACT OR GRANT NUMBER(+) 7. AUTHOR(.) Purwo A. Padua 9. PERFORMING ORGANIZATION NAME AND ADDRESS 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Naval Postgraduate School Monterey, California 93940 11. CONTROLLING OFFICE NAME AND ADDRESS 12. REPORT DATE March 1976 Naval Postgraduate School 13. NUMBER OF PAGES Monterey, California 93940 15. SECURITY CLASS. (of this report) MUNITORING AGENCY NAME & ADDRESS(II different from Controlling Office) Naval Postgraduate School Unclassified Monterey, California 93940 15e. DECLASSIFICATION/DOWNGRADING SCHEDULE 16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited. 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) 18. SUPPLEMENTARY NOTES 19. KEY WORDS (Continue on reverse side if necessary and identify by block number) 20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Mathematical models for hit probabilities of small arms fire against low-flying aircraft are developed with the aid of the impact points. Three techniques of fire are examined. A model for determining appropriate lead angles is developed. Probability of hit for single shot at various ranges and constant altitude are calculated. Repeated shots are then examined when the technique is used of firing multiple rounds at DD 1 JAN 73 1473 EDITION OF 1 NOV 68 IS OBSOLETE (Page 1) S/N 0102-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Dete Entered

20. Abstract (Continued)

a fixed angle. The result shows the probability of one of the shots is high, while for other rounds it declines very sharply. Suggestions for further extensions are included. Mathematical Model for Small Arms Fire Against Low-Flying Aircraft

Ъy

Purwo A. Padua Major, Indonésian Army

Submitted in partial fulfillment of the requirements for the degree of

MASTER OF SCIENCE IN OPERATIONS RESEARCH

from the

NAVAL POSTGRADUATE SCHOOL March 1976

UX LIBRARY POSTGRADUATE SCHOOD VIEREY. CALIFORNIA 93940

ABSTRACT

Mathematical models for hit probabilities of small arms fire against low-flying aircraft are developed with the aid of the impact points. Three techniques of fire are examined. A model for determining appropriate lead angles is developed. Probability of hit for single shot at various ranges and constant altitude are calculated. Repeated shots are then examined when the technique is used of firing multiple rounds at a fixed angle. The result shows the probability of one of the shots is high, while for other rounds it declines very sharply. Suggestions for further extensions are included.

TABLE OF CONTENTS

I.	INTI	RODU	CTION	 8
II.	BAS	ІС М	ODEL	 10
	Α.	BAS	IC MODEL	 10
		1.	Assumptions for the Theoretical Treatment	 10
		2.	Geometry	 10
	В.	FOR	MULATION OF LEAD ANGLE	 12
	С.	OTH	ER GEOMETRY	 19
III.	ONE	DIM	ENSIONAL CASE	 22
	Α.	SIN	GLE SHOT	 22
	в.	EVA	LUATION OF SECOND ROUND OF FIRE	 25
		1.	Pattern of Fire	 25
		2.	Changing Lead	 26
		3.	Fixed Lead	 27
IV.	TWO	DIM	ENSIONAL CASE	 30
V.	CON	CLUS	ION AND RECOMMENDATION	 41
BIBLI	OGRAI	PHY		 43
INITIA	AL DI	ISTR	IBUTION LIST	 44

LIST OF FIGURES

1.	Aircraft Weapon Geometry	10
2.	Lead Angle	12
3.	Lead Angle vs Altitude	16
4.	Lead Angle vs Horizontal Distance	18
5.	Geometry of the Target	19
6.	Chart of ℓ and ∇	21
7.	Geometry of the Target at Single Shot	22
8.	Geometry of the Target for Multiple Shots	24
9.	Probability a Hit at Various Ranges Without Lead Angle	29
10.	Probability a Hit at Various Ranges With Correct Lead Angle	29
L1.	Dynamics of Impact Points	34
12.	Expected Number of Hits with Respect to	40

LIST OF TABLES

1.	The Value of & Correspond to the Velocity and Altitude for an Aircraft	15
2.	The Value of 🖗 Correspond to the Velocity and Horizontal Range	17
3.	Relation between $\mathcal{S}, \mathcal{T}, \mathcal{L}$	21
4.	Probability a Hit at Various Ranges Without Lead Angle	28
5.	Probability a Hit at Various Ranges with Correct Lead Angle	28
6.	Probability of Hit of 4 Rounds in Sequence with kat Increment	38
7.	Expected Value of Hits with Respect to at	39

I. INTRODUCTION

The problem of computation hit probability for fire against aircraft by small arms organic to the infantry is of increased concern, because of recent emphasis on low altitude air assault tactics.

In firing with small arms against aircraft, there are two types of errors: ballistic and aiming.

- Ballistic errors relate to characteristics of the projectile and weapon and are caused by variations in projectile weights, variations in weapon barrels, and variation in muzzle velocities.
- Aiming errors are caused by incorrect pointing of the gun, etc.

For highly time-varying target positions the process of aiming small arms is much more difficult than aiming the gun against stationary targets since the aiming point must be ahead of the target. A model to calculate lead angle at various gun angle of elevation, ballistic and aircraft velocities will be developed in Section II.

These lead angles express the angle by which the gunbore axis must be deflected from the gun-target line at the instant of fire. By selecting the correct lead angles,

the ballistic can intercept the moving target. There are three techniques of engagement: [1]

- Pattern of fire technique. The gunner fires continuously at a fixed point on the target path with a pre-selected and fixed aiming angle.
- 2. Changing lead technique. The gunner extrapolates the target's present line of flight and continuously adjusts his aim point to provide the appropriate lead while firing.
- Fixed lead. This involves establishing an arbitrary but constant lead along the line of flight and firing continuously.

A basic model for the probability of hit for smallarms fire against low-flying aircraft will be developed in Section III. Only flight path at constant altitude with the approaching aircraft flying directly over the gunner will be considered. The general theoretical formulation involves a density function and some basic geometry which will be used for calculating hit probabilities.

II. BASIC MODEL

A. BASIC MODEL

1. Assumptions for the Theoretical Treatment

In order to be able to treat the hit probability, certain assumptions will be made:

- a. The ballistic errors are a random process,
- b. The distribution function of the ballistic error is normal,
- c. The mean value for the ballistic error is $\mathcal{M} = 0$,

d. For the two dimensional case $\sigma_x = \sigma_y = \sigma$,

 The bullet has a flat trajectory along the effective range. (This ignores the effect
 of gravity on the bullet.)

2. Geometry

Figure 1: Aircraft Weapon Geometry

Figure 1 illustrates the general situation for firing at targets under the assumption that the aircraft is flying a straight line, unaccelerated course.

Since we do not account for the effect of gravity, the trajectory of the bullet is a straight line which will intersect with the line of the bullet's trajectory. The angle that the bullet's trajectory makes with the horizontal is the initial angle of inclination of the trajectory and is also called the angle of departure.

If we only consider the projection on the plane (X,Z) containing both aircraft and bullet trajectories the following quantities may be used in developing the model in a one dimensional case:

x = horizontal range to target,

h = altitude of the target (aircraft),

x, g = initial angle of inclination of gun,

GF = slant range (r),

B = velocity of ballistic, and

AC = velocity of the aircraft

and the symbols G for gun, F for target (aircraft). For the two dimensional case the trajectory of the bullet also may have a projection in the (X,Y) plane.

B. FORMULATION OF LEAD ANGLE

In the hit problem, we will be concerned with the problem of successfully aiming the gun so a bullet will intercept a moving target. If the gun is pointed directly at the target at the time the gunner fires, he will make an error because of the target's motion during the projectile's time in flight.

It is important to develop a formula expressing the angle by which the gun-bore axis must be deflected from the gun target line at the instant of fire. This angle is called "the lead angle."

In this model we will only consider the kinematic lead, and ignore the gravity since the ballistics of small arms have an essentially flat trajectory within the effective range of fire.

Suppose the direction of the bullet when fired is GT_f , bullet velocity V_B and time of aircraft flight t_f . From the triangle GT T_f and the law of sines yield:

$$\frac{\sin \theta}{T T_{f}} = \frac{\sin \varphi}{G T_{f}}$$

$$\sin \theta = \frac{T T_{f}}{GT_{f}} \cdot \frac{\sin \varphi}{V_{B} t_{f}} = \frac{V_{A} t_{f}}{V_{B} t_{f}} \cdot \frac{\sin \varphi}{V_{B} t_{f}}$$

$$\sin \varphi = \frac{h}{GT} = \frac{h}{\sqrt{(x^{2} + h^{2})}}$$

$$\sin \theta = \frac{V_{A}}{V_{B}} \cdot \frac{h}{\sqrt{(x^{2} + h^{2})}}$$

$$\theta = \sin^{-1} \frac{V_{A} h}{V_{B} \sqrt{(x^{2} + h^{2})}}$$

or if lead angle is small

$$\Theta = \frac{V_A}{V_B} \cdot \frac{h}{\sqrt{(x^2 + h^2)}} \quad \text{rad}$$
(2)

(1)

For illustration, Table 1 shows the required lead angle 0 in degrees and in radians for an aircraft with velocity 100,200,400 knots with altitude 100m, 150m, 200m, 250m, 300m, 350m, 400m, when a small arm with bullet velocity

2750 ft/sec is fired at a horizontal distance of 350 meters. Table 2 shows the result of θ in degrees and in radians from the same ballistic and the same aircraft as in Table 1, but with altitude constant at 100m.

The horizontal range changes from 0 to 400m with 25m increments.

Figure 3 shows the relationships between θ and altitude, if velocity of the aircraft and the bullet are known.

Figure 4 shows the relationship between θ and the horizontal range, for three velocities of the aircraft at an altitude of 100 meters.

Table 1

The Value of Angle θ Corresponds to the Velocity & Altitude of an Aircraft

		7				and the second se				-
KNOTS	NI E	DEGREES	3.8531	5.5319	6.9844	8.1867	9.1604	9.9739	10.6261	
V _{AC} = 400	ANGLE (RADIANS	.0672	.0964	.1216	.1424	.1592	.1732	.1844	
00 KNOTS	H IN	DEGREES	1.925	2.762	3.485	4.082	4.565	4.968	5.290	
$V_{AC} = 20$	ANGLE	RADIANS	.0336	.0482	.0608	.0712	.0796	.0866	.0922	
0 KNOTS	θ IN	DEGREES	.962	1.383	1.742	2.041	2.286	2.484	2.644	
$V_{AC} = 1($	ANGLE	RADIANS	.0168	.0241	.0304	.0356	.0398	.0433	.0461	V DEO
ALTI - TUDE			100m	150m	200m	250m	300m	350m	400m	NOTE -

 $V_{B} = 2750 FT/sec$

Table 2 The Value of Angle 9 Corresponds to the Velocity and Horizontal Ranges of an Aircraft

DEGREES 4.4276 14.1936 13.7449 9.9739 5.2096 4.7955 4.1288 3.6005 3.3938 12.6620 8.7892 6.9844 6.2922 7.8164 3.8531 11.3031 5.6931 400 KNOTS IN ANGLE 0 RADIANS IL .0836 .0720 2376 .1260 .1096 0592 .1960 .1732 .1529 .1360 .0992 .0908 0772 0672 2452 2192 0628 VAC 2.6021 2.3956 DEGREES 7.0421 2.8430 6.8228 6.2922 4.9680 4.3816 3.1413 2.0630 1.9255 1.7993 1.69625.6240 3.4857 3.8991 2.2121 KNOTS ANGLE 9 IN 200 RADIANS 1226 .0496 .0386 0360 .0336 H .1188 .1096 0980 .0866 .0764 .0680 .0608 .0548 .0454 .0418 .0314 0296 v_{AC} 1.570 1.426 3.514 1.948 1.304 1.200 1.110 3.409 3.143 2.810 2.484 2.194 1.032 905 100 KNOTS RADIANS DEGREES 1.742 .964 851 H IN ANGLE 1 .0209 .0227 0193 0180 .0148 0613 0594 0548 .0490 .0382 .0340 .0304 .0274 .0248 0157 .0433 0168 VAC HORIZ. RANGE 200 225 250 300 0 100 125 150 175 275 325 350 25 50 375 400 (\mathbf{X}) 75

ALTTTUDE: 100mVB + 2750 FT/sec 1 KNOT = 1.85 km/HR

NOTE

OTHER GEOMETRY

Figure 5: Geometry of the Target

1. Aircraft Presented Projection

a. One Dimensional Case

For practical case of firing against aerial cargets we are confronted with complicated target shapes. 4]. In the one dimensional case we consider the aircraft is a two rectangular dimensional target. The impact point of the target is normally distributed on the line perpenlicular to the ballistic trajectory (gun-target line). Let \checkmark be the length of the aircraft and t be the height of the aircraft. From Figure 5 (a), the projection of \checkmark in the projection of t is t cos δ . Then the projection

of the aircraft to the line perpendicular bullet trajectory can be approximately by the equation $\mathcal{L} = \mathcal{A} \sin \mathcal{S} + t \cos \mathcal{S}$. (3)

b. Two Dimensional Case

As in the one dimensional case, the aircraft can be projected to the plane perpendicular to the trajectory.

> Let A_1 be the horizontal area A_2 be the vertical area The projection of A_1 to that plane is $A_1 \sin \delta$ and the projection of A_2 is $A_2 \cos \delta$.

Then the projection of the aircraft to the plane perpendicular to the bullet trajectory can be approximately by the equation

$$A = A_1 \sin \delta + A_2 \cos \delta \tag{4}$$

2. Formulation of Ballistic Dispersion (\mathcal{T})

Let \Leftrightarrow be the dispersion angle of the bullet known for a certain type of gun or bullet. From the triangle GFL as shown in Figure 5 (b), GF perpendicular to FL, then $\frac{\sigma}{\text{GF}}$ = tan \Leftrightarrow or σ = GF tan \Leftrightarrow . From the triangle GFF₁ · GF = h/sin δ then σ = $\frac{h \tan \sigma}{\sin \delta}$ (5) or illustration, Table 3 shows the value of \mathcal{L} and \mathcal{T} for various distance with constant altitude of 100 meters where the length of the aircraft is 8 meters and the width of the aircraft = 2 meters.

Table 3

Relation Between $\mathcal{S}, \mathcal{T}, \mathcal{L}$

III. ONE DIMENSIONAL CASE

Let the impact point of the bullet be a random variable X, normally distributed on the line \mathcal{L} perpendicular to the GUN-TARGET line GF (Figure 7). Assuming the distribution of the point of the bullets intersection of the line is centered at F ($\mathcal{M} = 0$) with standard deviation \mathcal{T}_1 , the density distribution of X is:

$$f(x) = \frac{1}{\sigma_{1} \sqrt{2\pi}} \cdot e^{-x^{2}/2\sigma_{1}^{2}}$$
(6)

The probability of hit in the line l centered at F is:

$$\int_{-\ell_2}^{\ell} f(x) dx$$

Then: Pr (hit) = $P_r \left(-\frac{l}{2} \leq X \leq \frac{l}{2}\right)$ = $\oint \left(\frac{l/2}{\sigma_r}\right) - \oint \left(-\frac{l/2}{\sigma_r}\right)$ = $2\oint \left(\frac{l}{2\sigma_r}\right) - \frac{1}{2}$ (7)

where $\oint (a) = Prob (x \le a)$ can be obtained from standard tables for the normal distribution. Let \neg be the length of the aircraft and t be the height of the aircraft. The projection of the aircraft to the bullet trajectory can be approximated by the equation:

$$l = \int \sin \delta + t \cos \delta \tag{8}$$

Substituting equation (8) into equation (7) yields: Pr (a hit) = $2\oint \left(\frac{s_{SW}\delta + t_{cos}\delta}{2\sigma_{l}}\right) - 1$ (9) as calculated in Section IIC, $\nabla_{1} = \frac{k_{lan}\sigma}{s_{lW}\delta}$

Substituting the value of \mathcal{T}_1 into equation (9) yields: $\Pr(a \text{ hit}) = 2\oint \left\{ \frac{(-JSIN\delta + t\cos\delta)SIN\delta}{2 \ h \ tand} \right\}$ (10)

Example: An aircraft with velocity 100 knots is fired upon by a rifle, the velocity of the bullet $V_B = 2750$ ft/sec = 838.2 meter/sec. The aircraft has a constant altitude 200m and its horizontal distance from aircraft to the firer = 200m let $\ll = 0.5^{\circ}$ be the dispersion angle of the bullet. We have $\oint = \arctan \frac{250}{200} = 51.3401$. lead angle θ as shown in Table 2. For this geometry θ =1.570, then $\delta = \varphi + \varphi = 51.3401 + 1.570 = 52.9101$. Let the length of the aircraft be $\Lambda = 8$ meters and the height of the aircraft be t = 2 meters, then:

Pr (a hit) =
$$2 \oint \left\{ \frac{(\sin \delta + t \cos \delta) \sin \delta}{2 h \tan \alpha} \right\} -1$$

= $2 \oint \left\{ \frac{8 \sin 52.9101 + 2 \cos 52.9101) \sin 52.9101}{2 \times 250 \tan 0.5} \right\}$
= $2 \oint \left(\frac{6.05259}{4.3634} \right) -1$
= $2 \oint 1.38 -1$
= 0.8324

B. MULTIPLE SHOTS

EVALUATION OF THE SECOND ROUND OF FIRE

1. MODE 1: Pattern of Fire

Here the gun has the same position as the first round (see Figure 8). Let the difference time between the first bullet and the second bullet = \triangle t. The first bullet will intersect the line of the aircraft (the line perpendicular to GF at the point F at time t). At time t, the second bullet is at the point S. Suppose the second bullet intersects the line perpendicular to GF at the point H at time t+t₁ and the airplane has moved from F to the point K. The time for the aircraft to travel from F to K must equal time for the second bullet to travel from S to H, FH = FS - SH

$$= V_{B} \Delta t - V_{B} t_{1}$$

$$t_{1} = \frac{V_{B} \Delta t - FH}{V_{B}}$$
(11)
$$FK = V_{AC} \cdot t_{1}$$

$$t_{1} = \frac{FK}{V_{AC}}$$
(12)

accordingly setting (11) equal to (12) is

$$t_1 = \frac{V_B \bigtriangleup t - FH}{V_B} = \frac{FK}{V_{AC}};$$

$$FH = FK \cos \mathcal{S} \text{ so } t_{1} = \frac{V_{B} \cdot \triangle t - FK \cos \mathcal{S}}{V_{B}} = \frac{FK}{V_{AC}}$$
or
$$V_{B} \cdot V_{AC} \cdot \triangle t - FK V_{AC} \cos \mathcal{S} = FK \cdot V_{B}$$

$$FK \cdot V_{B} + FK V_{AC} \cos \mathcal{S} = V_{B} \cdot V_{AC} \cdot \triangle t$$

$$FK (V_{B} + V_{AC} \cos \mathcal{S}) = V_{B} \cdot V_{AC} \cdot \triangle t$$

$$FK = \frac{V_{B} \cdot V_{AC} \cdot \triangle t}{(V_{B} + V_{AC} \cos \mathcal{S})}$$

$$KH = FK \sin \mathcal{S} = \frac{V_{B} \cdot V_{AC} \cdot \triangle t \sin \mathcal{S}}{V_{B} + V_{AC} \cos \mathcal{S}}$$

$$Fr (\text{second hit}) = \int_{f(X)}^{KH + \ell_{2}} \frac{\Phi(\frac{KH + \ell_{2}}{C_{2}}) - \Phi(\frac{KH - \ell_{2}}{C_{2}})}{f(X)}$$

$$(13)$$

where
$$l = 1 \sin \delta + t \cos \delta$$
 and $\overline{C}_{2} = h \tan \alpha$ (14)

sin S

2. MODE 2: Changing Lead

With a changing lead, the direction of the gun moves to the new position with the correct lead angle for the newly positioned target. Let the lead angle for that new position be \mathscr{S} (as calculated at Table 2). Then the new firing angle is $\mathscr{S} + \mathscr{T}$, and

Pr (second hit) =
$$\int_{-\frac{l}{2}}^{\frac{l}{2}} dx = 2 \oint \left(\frac{l}{2\sigma}\right)^{-1}$$

where $l = J\sin(\delta + \delta) + t\cos(\delta + \delta)$ and $T = \frac{h \tan \alpha}{\sin(\delta + \delta)}$

Thus,

Pr (second hit) =

$$2 \oint [\frac{f_{SSin}(S+T) + t \cos(S+T)}{2 k \tan \alpha} - \frac{1}{2} \int (15)$$

Results for probability of hit at various ranges without
lead angle and with correct lead angle are shown in Tables
4 and 5 and the accompanying graphs are shown in Figures 9

and 10.

3. MODE 3: Fixed Lead

Let $\not\in$ be the constant lead angle selected from the set of leads appropriate for target speeds and target gunner distances. Then the new firing angle is $\delta + \not\in$. Pr (second hit) = $\int_{-l/2}^{l/2} f'(x) - \frac{l/2}{2}$ = $2 \oint \left(\frac{l}{20}\right) - 1$

when $l = J\sin(\delta + \xi) + t\cos(\delta + \xi)$ and $T = \frac{h \tan \alpha}{\sin(\delta + \xi)}$

Pr (second hit) = $2 \oint \left[\frac{\{ J \sin (\delta + \hat{F}) + t \cos (\delta + \hat{F}) \} \sin (\delta + \hat{F})}{2 k \tan \alpha} - 1 \right]$ (16)

Table 4

X	б	(= htonx SIN &	l	Pr (Hit)
400	14.0362	3.5981	3.8805	.4038
350	15.9453	3.1766	4.1208	.4778
300	18.4349	2.7596	4.4271	.5762
250	21.8014	2.3497	4.8280	.6922
200	26.5650	1.9513	5.3665	.8354
150	33.6900	1.5732	6.1016	.9464
100	45.	1.2341	7.0710	.9958
50	63.4349	.9756	8.0498	1.
0	90	.8726	8.	1.

Probability A Hit at Various Ranges Without Lead Angle

<u>Table 5</u>

Probability A Hit at Various Ranges With Correct Lead Angle

X	5+0	$G = \frac{h \tan \alpha}{SIN(\delta + \theta)}$	l	Pr (Hit)
400	15.7324	3.2185	4.0942	.4714
350	17.8709	2.8438	4.3585	.5528
300	20.6470	2.4749	4.6924	.6528
250	24.4035	2.1122	5.1265	.7738
200	29.7063	1.7610	5.7015	.8926
150	37.5892	1.4306	6.4647	.9756
100	49.9680	1.1397	7.4119	.9988
50	69.7271	.9303	8.1974	1.0
0	97.0421	.8793	7.6944	1.0

Correct Lead Angle

IV. TWO DIMENSIONAL CASE

Let the impact point of the bullet on a plane which is perpendicular to the bullet trajectory and which coincides with the center of the aircraft be represented by random variables X and Y. It is assumed that X, Y are independently and normally distributed N(X; 0; σ_x^2), N(Y; 0; σ_y^2) and $\sigma_x^2 = \sigma_y^2 = \sigma^2$.

The density functions of X and Y are:

$$f_{x}(x) = \frac{1}{\sigma_{x} \sqrt{2\pi}} e^{-x^{2}/2\sigma_{x}^{2}}$$

$$f_{y}(y) = \frac{1}{\sigma_{y} \sqrt{2\pi}} \cdot e^{-\frac{y^{2}}{2}\sigma_{y}^{2}}$$

The joint density is:

$$\int_{\mathbf{x}\gamma} (\mathbf{x}, \mathbf{y}) = \left(\frac{1}{\sigma_{\mathbf{x}} \sqrt{2\pi}} \cdot e^{-\mathbf{x}^2/2\sigma_{\mathbf{x}}^2}\right) \left(\frac{1}{\sigma_{\mathbf{y}} \sqrt{2\pi}} \cdot e^{-\frac{\gamma^2/2\sigma_{\mathbf{y}}^2}{2\sigma_{\mathbf{y}}^2}}\right)$$

$$f_{XY}^{\prime}(X,Y) = \frac{1}{2\pi\sigma^{2}} \cdot e^{-\frac{\chi^{2}+Y^{2}}{2\sigma^{2}}}$$
(17)

The probability of a hit in an area A is: Pr (a hit) = $\int_{A} \int \frac{1}{2\pi\sigma^{2}} \cdot e^{-\frac{\chi^{2} + \gamma^{2}}{2\sigma^{2}}} dx d\gamma$ Assume that the target is circular with radius R. transforming to the polar coordinates:

$$X = r \cos \theta , \quad Y = r \sin \theta$$

$$X^{2} + \gamma^{2} = r^{2} \cos^{2} \theta + r^{2} \sin^{2} \theta$$

$$= r^{2} (\cos^{2} \theta + \sin^{2} \theta) = r^{2}$$

1 A

$$Pr(a hit) = \frac{1}{2\pi\sigma^2} \int_{0}^{R} \frac{\pi}{r} e^{-\frac{r^2}{2\sigma^2}} d\theta dr$$
$$= \frac{2\pi}{2\pi\sigma^2} \int_{0}^{R} r e^{-\frac{r^2}{2\sigma^2}} dr$$
$$= -\frac{r^2}{2\sigma^2} \int_{0}^{R} r e^{-\frac{r^2}{2\sigma^2}} dr$$

Pr (a hit) = $1 - e^{-R^2/2\sigma^2}$

(18)

Recall the series expansion of $C^{X} = 1 + X + \frac{X^{2}}{2!} + \frac{X^{3}}{3!} + \cdots$ If X is small, the second and higher order terms in the

series can be ignored,

i.e.: $e^X \approx 1 + X$

From the formula (18) if R is small,

$$e^{-\frac{R^{2}}{2\sigma^{2}}} = 1 - \frac{\frac{R^{2}}{2\sigma^{2}}}{-\frac{R^{2}}{2\sigma^{2}}}, \text{ then}$$

Pr (hit) = $1 - e^{-\frac{R^{2}}{2\sigma^{2}}}$
= $1 - \frac{1}{2\sigma^{2}} + \frac{\frac{R^{2}}{2\sigma^{2}}}{-\frac{R^{2}}{2\sigma^{2}}}$

Since the area of the target is πR^2

Pr (a hit) = $\frac{R^2}{2\sigma^2} = \frac{\pi}{\pi} \cdot \frac{R^2}{2\sigma^2} = \frac{A}{2\pi\sigma^2}$ Accordingly for a small target (if $R < \sigma$), then Pr (hit) = $\frac{A}{2\pi\sigma^2}$ (19)

While for the large target $(R > \sigma)$,

Pr (hit) =
$$1 - e^{\frac{A}{2\pi\sigma^2}}$$
 (20)

From section IIC:

 $A = A_1 \cos \delta + A_2 \sin \delta$

$$\sigma = \sigma_1 = \frac{h_{\tan \alpha}}{\sin \delta}$$

Substituting the value of A and \mathcal{O} to the equation (19) yields:

$$\frac{2\pi}{2\pi} \left(\frac{hit}{sins}\right)^{2} \qquad (21)$$

(i.e. the probability of a hit for small target)

and if the target is large:

$$Pr (hit) = 1 - C \qquad \frac{A_1 \cos \delta + A_2 \sin \delta}{2\pi (\frac{h \tan \alpha}{\sin \delta})^2}$$
(22)

For an illustration of the application of these models,

we consider the following example:
Given:
$$V_B = velocity of the bullet = 710m$$

 $h = aircraft altitude = 200m$
 $X = horizontal range from gun to aircraft = 300m$
 $V_{AC} = velocity of aircraft = 300 knots = 154.164 km/sec$
 $G_X = 0.5^{\circ}$
rate of fire = 600 rounds/minutes
 $\Delta t = time between rounds$
 $= .1 second$
 $\Delta = length of the aircraft$
 $= 8m$
 $t = height of the aircraft$
 $= 2m$
 $\Delta = arc tan 200/300 = 33.69$
 $L = 8 sin 33.69 + 2 cos 33.69 = 6.1016$
 $L/2 = 3.050$
 $G = \frac{200 tan 0.5}{33.69} = 3.146$

The values of l and σ are assumed constant for the specified angle δ .

Instead of using the lead angle we shift the position of aircraft $k \Delta t$ forward from the initial hit position (k = 0.1, 0.2, . . 1.0). The result is shown in Table 6.

Figure 11: Dynamics of Impact Points

First Round
FB =
$$2 \Delta t V_{AC}$$

FA = FB cos δ = $2 \Delta t V_{AC} cos \delta$
FA₁ = V_B t₁
A₁A = FA - FA₁ = $2\Delta t V_{AC} cos \delta$ - V_B t

$$A_{1}C = \frac{A_{1}A}{\cos \delta} = \frac{2 \Delta t \ V_{AC} \cos \delta - V_{B} \ t_{1}}{\cos \delta}$$
$$A_{1}C = B_{1}B = V_{AC} \ t_{1}$$
$$t_{1} = \frac{2 \Delta t \ V_{AC} \cos \delta}{V_{AC} \cos \delta + V_{B}}$$

Pr (Hit) =
$$\int_{\Gamma} \frac{(A_1B_1 + l/2)}{\sigma} - \int_{\Gamma} \frac{(A_1B_1 - l/2)}{\sigma}$$

$$A_{2}A_{1} = (\Delta t - t_{2}) V_{B}$$

$$A_{2}C_{1} = \frac{(\Delta t - t_{2}) V_{B}}{\cos \delta} = B_{1}B_{2} = V_{AC} t_{2}$$

$$(\Delta t - t_{2})V_{B} = V_{AC} t_{2} \cos \delta$$

$$V_{AC}t_{2} \cos \delta + V_{B}t_{2} = .V_{B}\Delta t$$

$$t_{2} (V_{AC} \cos \delta + V_{B}) = V_{B} \Delta t$$

$$t_{2} = \frac{V_{B} \Delta t}{V_{B} + V_{AC} \cos \delta}$$

$$P_{B} (V_{AC}) = \sqrt{1} (A_{2}B_{2} + t_{AC})$$

Pr (Hit) =
$$\oint \frac{(A_2B_2 + l/2)}{\sigma} - \oint \frac{(A_2B_2 - l/2)}{\sigma}$$

Third Round

$$A_{3}A_{2} = (\Delta t - t_{3}) V_{B}$$

$$A_{3}C_{2} = \frac{(\Delta t - t_{3})V_{B}}{\cos \delta} = B_{3}B_{2} = V_{AC}t_{3}$$

$$(\Delta t - t_3)V_B = V_{AC} t_3 \cos \delta$$

$$V_B t_3 + V_{AC} t_3 \cos \delta = \Delta t V_B$$

$$t_3 (V_B + V_{AC} \cos \delta) = \Delta t V_B$$

$$t_3 = \Delta t \frac{V_B}{V_B + V_{AC} \cos \delta}$$
Pr (Hit) = $\oint \frac{(A_3B_3 + \ell/2)}{\sigma} - \oint \frac{(A_3B_3 - \ell/2)}{\sigma}$
By putting the numerical example to these calculation we get the results:
 $t_1 = 0.030$
FA₁ = $V_B t_1 = 7.0 \times 0.030 = 21.3$
A₁B₁ = 21.3 tan 33.69 = 14.199
Pr (Hit) = $\oint (15.482) - \oint (3.543)$
 $= .0002$
 $t_2 = 0.084$
FB₂ = $V_{AC} (2\Delta t - t_1 - t_2)$
 $= 13.258$
A₂B₂ = FB₂ sin 33.69 = 7.3542
Pr (Hit) = $\oint 3.3071 - \oint 1.3681$
 $= 0.0864$
 $t_3 = t_2 = 0.084$
FB₃ = FB₁ - $2V_{AC} t_2 = 0.03083$

$$A_{3}B_{3} = FB_{3} \sin 33.69 = .01710$$

$$Pr (Hit) = \oint .9749 - \oint - .9658$$

$$= .6655$$

$$t_{4} = t_{3} = 0.0864$$

$$FB_{4} = FB_{1} - 3V_{AC} t_{2} = -12.64144$$

$$A_{4}B_{4} = -7.0122$$

$$Pr (Hit) = \oint -1.2594 - \oint (-3.1984)$$

$$= .1049$$

From Table 6 we can calculate Pr (n Hits) is

$$Pr(1 Hit) = \sum_{i=1}^{4} P(H_i) \prod_{j \neq i} P(M_j), where P(M_j) = 1 - P(H_j)$$

Then:

Pr (1 Hit) = .5728
Pr (2 Hits) =
$$\sum_{i=1}^{4} \mathcal{P}(\mathcal{H}_i) \underbrace{\mathcal{F}}_{j\neq i} \mathcal{P}(\mathcal{H}_j) \underbrace{\mathcal{T}}_{K\neq i, j} (\mathcal{M}_K)$$
= .1236
Pr (3 Hits) = .00605

Pr(4 Hits) = .000001

Results for probability of his of 4 rounds in sequence with k \triangle t increments are shown in Table 6. The expected value of hits with respect to \triangle t is shown in Table 7 and the accompanying graph is shown in Figure 12. TADLE 0

Probability of Hit of 4 Rounds in Sequence With *k Δt Increment

1.0Åt	PH(10)	.1741	. 6305	.0454	.0001	.8501
0.9Åt	(6)Hd	.1143	. 6628	.0774	.0002	.8547
0.8At	PH(8)	.0705	.6589	.1241	.0003	.8538
0.7 ^Δ t	PH(7)	.0408	.6211	.1897	.0008	.8524
0.6At	PH(6)	.0217	.5551	.2688	.0019	.8475
0.5At	PH(5)	.0110	.4738	.3591	.0047	.8386
0.4 ^Δ t	PH(4)	.0052	.3761	.4534	.0139	.8486
0.3At	PH(3)	.0023	.2848	.5375	.0192	.8438
0.2At	PH(2)	.0010	.2032	.6109	.0358	.8509
0.1At	PH(1)	.0004	.1367	. 6544	.0627	.8542
0.0At	PH(0)	.0002	.0864	. 6655	.1049	.8570
INCREMENT	PROB SHOT #	1	2	3	4	Pr (Hit)

* k = 0.0, 0.1, 0.2, ----- 0.9, 1.0

Table 7

Expected Value of Hits With Respect to Δ t

INCRE-	PROB FXPT	PROB n = NUMBER OF HITS				EXPECTED	
		1	2	3	4	CORRESPOND TO THE INCREMENT	
0.00+	Pr(n)	.5728	.1236	.0061	.000001	0202	
0.041	E(n)	.5728	.2472	.0183	.000004	.0303	
1 4 -	Pr(n)	.5923	.1224	.0057	.000002	05/0	
.140	E(n)	.5923	.2448	.0171	.000080	.0342	
2 1 +	Pr(n)	.5564	.1404	.0046	.000004	9510	
.24t	E(n)	.5564	.2808	.0138	.000016	.8510	
2.4.	Pr(n)	.5121	.1609	.0033	.000007	0/ 20	
.34t	E(n)	.5121	.3218	.0099	.000028	.0430	
	Pr(n)	.4811	.1766	.0033	.000012	0440	
.445	E(n)	.4811	.3532	.0099	.000048	.0442	
5 1 +	Pr(n)	.4895	.1744	.0027	.000009	01.61.	
.54t	E(n)	.4895	.3488	.0081	.000036	.0404	
6 1 +	Pr(n)	.5207	.1581	.0035	.000006	01.71	
.041	E(n)	.5207	.3162	.0105	.000024	.04/4	
7 4 +	Pr(n)	.5640	.1368	.0049	.000004	0522	
./21	E(n)	.5640	.2736	.0147	.000016	.0323	
8 A +	Pr(n)	.5968	.1198	.0058	.000002	0520	
.021	E(n)	.5968	.2396	.0174	.000008	.0330	
$Q \wedge t$	Pr(n)	.6002	.1184	.0059	.000001	85/17	
.941	E(n)	.6002	.2368	.0177	.000004	.0,47	
1 0 A +	Pr(n)	.5723	.1314	.0050	.000005	9501	
1.04E	L.UZE	E(n)	.5723	.2328	.0150	.000020	.0301

NOTE:

Pr(n) : Probability (n Hits)

E(n) : Expected Value (n Hits)

Figure 12: Expected Number of Hits with Respect to t

V. CONCLUSION AND RECOMMENDATION

The model developed in Section III is based on certain assumptions. These create idealized conditions but should still be indicative of real situations and capable of yeilding useful results.

As shown in the last illustration of the model the time intervals between impact bullets are equal since the velocity of the bullet and the aircraft are assumed constant along the trajectory. In a real situation the velocity of the bullet will be decreasing because of air resistence and earth gravitation. Since we are concerned only with small arms which have a short effective range, ignoring the effect of gravity should not give a significantly different result. On the other hand by using the correct lead angle increases the probability of hit relative to that without lead angle. If the gun is reaimed after every round, this reduces the errors.

Another example shows that the hit probability for the first bullet is high while the second and the successive bullet have low probability. These probability depend on the velocities of the aircraft and bullet and the rate of

fire. The extension of the model by taking into account the effect of gravity and wind velocity should produce better results.

Another possible extension of this model would be the generation of hit probability if the aircraft is moving tangentially to a gunner's position.

BIBLIOGRAPHY

- Human Resources Research Organization Report 70-2, <u>Method of Training for the Engagement of Aircraft</u> <u>with Small Arms</u>, by Robert D. Baldwin and Robert J. Faskett, Feburary 1970.
- <u>Introductory Probability and Statistical Application</u>, second edition by: Meyer, Addison Wesley Publishing Company.
- 3. <u>Small Arm Fire Against Fast Low-Flying Aircraft in</u> <u>Southeast Asia</u>, thesis by Miles E. Mixson, Naval Postgraduate School, June 1973.
- 4. <u>Stochastic Error Processes and Hit Probability: A</u> <u>Methodical Survey</u>, by Hans Brandli, PHD, English edition, published by Naval Surface Weapons Center, Dahlgren Laboratory, Dahlgren, Virginia 1975.

INITIAL DISTRIBUTION LIST

		No.	Copies
1.	Defense Documentation Center Cameron Station Alexandria, Virginia 22314		2
2.	Library, Code 0212 Naval Postgraduate School Monterey, California 93940		2
3.	Department of Operations Research and Administrative Sciences Naval Postgraduate School Monterey, California 93940		1
4.	Prof. J. B. Tysver, Code 55 Ty Department of Operations Research and Administrative Sciences Naval Postgraduate School Monterey, California 93940		1
5.	Prof. G. F. Lindsay Department of Operations Research and Administrative Sciences Naval Postgraduate School Monterey, California 93940		1
6.	DAN PUS HUBAD JL. S PARMAN 103 Jakarta, Indonesia		1
7.	MAJOR CHB PURWO A. PADUA JL. MATARAM DN2/160 JOGYAKARTA Indonesia		1

