

NRL Memorandum Report 3426

Efficient Laser Light Absorption by Ion Acoustic Fluctuations

W. M. MANHEIMER, D. G. COLOMBANT, AND B. H. RIPIN

Plasma Dynamics Branch Plasma Dynamics Division

December 1976





NAVAL RESEARCH LABORATORY Washington, D.C.

Approved for public release: distribution unlimited.

READ INSTRUCTIONS BEFORE COMPLETING FORM
3. RECIPIENT'S CATALOG NUMBER
S TYPE OF REPORT & PERIOD COVER
Interim report on a continuing
NRL problem.
6. PERFORMING ORG. REPORT NUMBE
8. CONTRACT OR GRANT NUMBER(.)
10. PROGRAM ELEMENT PROJECT TA
AREA & WORK UNIT NUMBERS
NRL Problem H02-51
Subtask RR011-09-41
12: REPORT DATE
December 1976
13. NUMBER OF PAGES
15 12110
15. SECURITY CLASS. (of this report)
UNCLASSIFIED
15. DECLASSIFICATION DOWNGRADIN
SCHEDULE
TAILOG
ROTIOL
and the second se
N
RØ110941
R Ø 1 1 Ø 9 4 1
R Ø 1 1 Ø 9 4 1
R 0110941
R Ø 1 1 Ø 9 4 1
R Ø 110941
R Ø 11 Ø 9 4 1 a Report) t in plasma resulting from an ion omparisons with experimental
R Ø 11 Ø 9 4 4
Report) a Report) t in plasma resulting from an ion omparisons with experimental
Report) a Report) t in plasma resulting from an ion omparisons with experimental
Report) a Report) t in plasma resulting from an ion omparisons with experimental
Report) a Report) t in plasma resulting from an ion omparisons with experimental
Report) a Report) t in plasma resulting from an ion omparisons with experimental 251.95



EFFICIENT LASER LIGHT ABSORPTION BY ION ACOUSTIC FLUCTUATIONS

This Letter presents a new absorption mechanism which gives efficient absorption of intense light by a laser produced plasma. The basic idea is that in absorption, the laser energy flux is converted into an electron thermal energy flux Q flowing into the plasma. In order for charge neutrality to be maintained, there must be a return current of low velocity electrons flowing toward the laser (in the negative x direction). This return current excites ion acoustic waves, also propagating toward the laser. The laser light then experiences enhanced collisional damping on these ion density fluctuations in the underdense plasma. The absorption of the laser light then creates that very electron thermal energy flux which was required in the first place.^{1,2,3} Values of Q/nmv³_e are small enough that a fluid model (dominated by anomalous transport) is valid. Finally, we show that a magnetized plasma should give both higher absorption and also remove some of the approximations inherent in the calculations presented here for an unmagnetized plasma.

Results of our theory seem to be in good qualitative agreement with many absorption, scattering and x-ray measurements at NRL.⁴⁻⁷ It would be very difficult to explain these measurements by resonant absorption.⁸ The measurements consistently show high fractional absorption (in excess of 50%) which is relatively independent of both polarization and angle of incidence.⁵ In addition, NRL experiments indicate a fairly smooth critical surface for distance scales above about one micron.⁷ Also light absorption by enhanced ion density fluctuations would not tend to strongly produce non thermal electrons. Energy flux is found to be carried principally by electrons at Note: Manuscript submitted November 23, 1976.

about two or three times the thermal speed. This also seems to be in agreement with hard x-ray measurements.^{4,6} Finally, layered target experiments⁴ indicate a value of Q/nmv_e^3 less than 0.2 which is also in agreement with our calculations. We now describe our calculations, and will close by giving more detailed comparisons with experimental results. The relevant steady state fluid equations have been written out and discussed elsewhere.¹ We summarize them here as:

$$\frac{\partial}{\partial x} nT_e + neE + \frac{1}{4} \frac{e^2}{m^2 \Omega^2} \frac{\partial}{\partial x} (E_i^2 + E_r^2) = C_{ve}$$
(a)

$$\frac{\partial Q}{\partial x} = C_{\text{Te}} + v_{\text{an}} \left(\frac{E_{1}^{2} + E_{r}^{2}}{\delta_{T}} \right) - \frac{\omega_{\text{pe}}^{2}}{\Omega^{2}}$$
(b)

$$\frac{3}{2}\frac{\partial}{\partial x}nT_e^2 + \frac{3}{2}\frac{T_e}{m}(neE + \frac{1}{4}\frac{e^2}{m^2\Omega^2}\frac{\partial}{\partial x}[E_i^2 + E_r^2]) = C_{Qe} \quad (c)$$

$$nv = const.$$
 (d)

(1)

$$nMv \frac{\partial v}{\partial x} + \frac{\partial}{\partial x} nT_{i} - neE = -C_{ve}$$
 (e)

$$\frac{\partial}{\partial x}\frac{\beta}{2} nvT_{i} + nT_{i}\frac{\partial v}{\partial x} = -C_{Te}$$
(f)

where E is the ambipolar electric field. $E_{i(r)}^2$ is the intensity of the incident (reflected) laser light, Q is the electron thermal energy flux in the x direction, Ω is the laser light frequency, v_{an} is the anomalous collision frequency, and C_{ve} , C_{Te} , C_{Qe} are quasi-linear collision terms which describe the electron momentum, thermal energy and thermal energy flux loss

due to interactions with unstable waves. In Eq. 1c, the effects of ponderomotive force have been included. All other notation is standard.

Coupled to this fluid system are equations for the incident and reflected laser light and also equations for the unstable ion acoustic waves. These are

where θ is the angle of incidence of the laser light and

$$\frac{d}{dx} \left| \frac{e \omega(k)}{T_{e}} \right|^{2} = 2 \left(\frac{v}{v - (T_{e}/m)^{\frac{1}{2}}} \right) \left| \frac{e \omega(k)}{T_{e}} \right|^{2} , \qquad (3)$$

where v is the growth rate.¹

The final quantities to specify are C_{ve} , C_{Te} , C_{Qe} and v_{an} . The quantity v_{an} depends on the component of <u>k</u> in the direction of <u>E</u>_i (for instance the y direction). Thus the angular spectrum of the ion acoustic fluctuations is needed. We make use of results of many numerical simulations of ion acoustic turbulence in two dimensions,⁹ which show a cone of unstable waves out to an angle of between about 45 and 60 degrees. We use this basic result and assume a three dimensional conical spectrum uniform in angle up to 55° to the x axis and then dropping sharply to zero. Making this assumption, we find¹



$$v_{an} = \Omega \frac{w_{pe}^2}{\Omega^2} \frac{3k_{min}}{k_{max}} \sum_{k=k_{min}}^{k_{max}} \left(\frac{k}{k_{max}}\right)^2 \quad 0.3\pi \quad \left(\frac{w_{pe}}{\Omega}\right)^3 k\lambda_D \quad \cdot \\ \left[\left(1 - \frac{w_{pe}^2}{\Omega^2}\right)^2 + 4\left(\frac{w_{pe}^2}{\Omega}\right)^3 k^2 \lambda_D^2\right]^{-1} \quad \left|\frac{e\omega(k)}{T_e}\right|^2 \quad .$$
(4)

where k_{\min} and k_{\max} are the minimum and maximum wave numbers included in the summation. In our calculations we take $k_{\max} = 0.75 \text{ k}_D$ and $k_{\min} = k_{\max}/9$. The C's are calculated as in Ref. 1, only making the same conical approximation to the wave spectrum.

Now it is worthwhile pointing out that if a transverse magnetic field exists, as is usually the case for laser light focused on a slab¹⁰, the ion acoustic wave no longer propagates parallel to \underline{Q} , but parallel to \underline{E}_i .¹¹ Thus not only would v_{an} increase, but also there would be no need to make any approximations concerning the angular width of the spectrum. In a future publication, we plan to discuss the problem of absorption in a magnetic field.

Equations 1 through 4 are a coupled set of equations which we solve numerically starting at x = 0 and integrating backwards towards the laser. As initial values, we start with parameters characteristic of the low density shelf as explained in Ref. 12, and $\sum \left|\frac{e^{0}}{T_{e}}\right|^{2} = 10^{-5}$. At a given subcritical density, the flow velocity v, and v_{os}/v_{e} are determined.¹² Also $E_{i}^{2} = E_{r}^{2}$ at x = 0. Choosing an electron temperature is then essentially equivalent to choosing an incident laser power. The remaining initial

parameters to be specified are T_i/T_e and Q. The parameter Q(x = 0) is found by iteration so that $Q(x = -\infty) = 0$.

Results are shown in Fig. 1a-d. Figure 1a shows the spatial dependence of T_e , Q, E_i^2 , E_r^2 and $\left[\sum_{r} \left|\frac{e\phi(k)}{T_e}\right|^2\right]^{\frac{1}{2}}$ where T_e (x = 0) = 12 keV, $T_{i}(0)/T_{e}(0) = 1/30, \omega_{pe}^{2}(0)/\Omega^{2} = 0.7, \text{ and } \theta = 0.$ Following E_{i}^{2} back to $-\infty$, we see that the incident laser flux is 10^{15} W/cm^2 , $Q(0)/\text{nmv}_e^3(0) \approx 0.1$, and the absorption efficiency is 664. The unstable wave spectrum peaks at about $k \sim k_p/2$. The electrons which principally absorb the laser light have velocity ~ $\Omega/k \sim \Im v_{a}$ so that an energetic tail is not expected to be substantially produced. Figure 1b shows the absorption efficiency as a function of density on the low density shelf assuming $T_a(0) = 12$ keV and $T_e(0)/T_i(0) = 30$. Figure 1c shows values of $Q(0)/nmv_e^3(0)$, T (0) and absorption efficiency as a function of laser power where $n(0) = 0.5 n_{cr}$ and $T_{i}(0)/T_{i}(0) = 30$. The high temperatures calculated here, of course, exist only in front of the critical surface. At higher densities, the temperature would be much lower. Figure 1d shows the absorption efficiency as a function of angle for $n(0) = 0.5 n_{cr} \cos^2 \theta$ (see Ref. 12), $T_{e}(0)/T_{f}(0) = 30$ and $T_e(0) = 12 \text{ keV}$ (the incident laser flux was in the vicinity of 2 X 10^{15} W/cm^2). The fractional absorption would be substantially increased at higher power and/or with higher density shelves as is apparent from Figs. 1b and 1c.

To summarize, our results show good absorption by the thermal part of the distribution function which is nearly independent of both polarization and angle, and with Q/nmv_e^3 of typically about 0.1. Finally, we wish to point out that similar results results were found by numerical simulations.¹³ We will now discuss more fully some of the related experimental results. Figure le (taken from Ref. 5) shows the reflected light as a function of angle of incidence and polarization, for laser irradiance of 5 X 10^{15} W/cm². Notice that the absorption efficiency is not strongly dependent on either polarization or angle of incidence for tilt angle less than about 60° ; just as predicted in Fig. 1d.

We now discuss the relevance of an experiment in which the transport of energy was studied at an irradiance of 10^{15} W/cm² through a thin layer of polystyrene into an aluminum substrate.⁴ The intensity of aluminum line radiation is shown as a function of polystyrene thickness in Fig. 1f. The absorbed energy flux Q is measured. Assuming a particular value for Q/nmv³_e then allows one to calculate the average electron energy near the critical surface. Since the laser energy must ultimate heat the electrons in the polystyrene to this energy, one can calculate how much laser energy, at given irradiance, is needed to just burn through a given layer of polystyrene (i.e., to cut off the aluminum line radiation).

A value of Q/nmv_e^3 of about 0.1 is consistent with the upper limit of $Q/nmv_e^3 \sim 0.2$ inferred from the dependence of Al x-ray radiation to polystyrene thickness shown in Fig. 1f.⁴

The experimental situation is closely one dimensional. The asymmetry of specularly reflected light indicates that, on the average, the center of the critical surface bulges by only about 1 μ compared to the half energy content focal diameter of 30 μ . However, Fourier analysis of the specularly reflected light does show enhanced density fluctuations near 1 μ ,⁷ which is close to the peak ion fluctuation wavelength.

Finally, we would like to make a few remarks on hard x-ray data. Our own¹⁴ and other theories⁸ have shown that resonant absorption creates electron

distributions having non thermal tails extending from about $3v_e$ to 6 or $7v_e$. If 10^{15} W/cm² is conducted by the electrons and Q/nmv_e³ ~ 0.2 as indicated in Ref. 4, then the thermal energy is about 6 keV. Thus the non thermal tail would extend from about 60 keV to about 300 keV. The layered target experiments and others⁶ show very few hard x-rays above 100 keV. Thus there appears to be no indication of a strong superthermal tail to the electron distribution function.

In summary then, there are good theoretical and experimental indications that light absorption by enhanced ion density fluctuations is a very important process for laser fusion.

	REFERENCES
1.	W. Manheimer, Phys. Fluids, Feb. 1977, also UCRL, 77149 (1975).
2.	R. C. Malone, R. L. McCrory and R. L. Morse, Phys. Rev. Lett 12,
	721, (1975).
3.	S. Bodner, et al., CN-35/F9, presented at the IAEA meeting on Plasma
	Physics and Controlled Nuclear Fusion Research, Oct. 1976, Burchdes-
	Garden, Germany.
4.	F. C. Young, et al., submitted to Appl. Phys. Lett.
5.	B. H. Ripin, submitted to Appl. Phys. Lett. and NRL Memo 3315 (1976)
6.	B. H. Ripin, et al., Phys. Rev. Lett. <u>34</u> , 1313 (1975).
7.	B. H. Ripin, to be published.
8.	J. P. Friedberg, et al., Phys. Rev. Lett. <u>28</u> , 795 (1972) and K. G.
	Estabrook, et al., Phys. Fluids <u>18</u> , 1151 (1975).
9.	M. Lampe, et al., Phys. Fluids 17, 428 (1974) and D. Biskamp and R. Chodura,
	Phys. Rev. Lett. 27, 1553 (1971).
ιο.	J. A. Stamper and B. H. Ripin, Phys. Rev. Lett. <u>34</u> , 138 (1975).
11.	W. Manheimer and C. Max to be published.
12.	K. Lee, D. Forslund, J. Kindel and E. Lindeman, Phys. Fluids, to be
	published, also Los Alamos LA-UR-75-2097.
13.	R. L. Morse and R. C. Malone, Bull. Am. Phys. Soc. 21, 1028 (1976) and
	to be published.
L ⁴ .	W. Manheimer, and H. Klein, Phys. Fluids 18, 1299 (1975).



Fig. 1 - (a) Fluid quantities as a function of x, (b) fractional absorption as function of density, (c) fractional absorption, T_e and f as a function of laser flux, (d) fractional absorption as a function of tilt angle, (e) total reflected and backscattered energy as a function of the angle of incidence. Circles and triangles are for the two incident polarizations, and (f) Al-line radiation (X) and continuum (·) (1-3 keV) versus polystyrene thickness.

DISTRIBUTION LIST

- 1. Los Alamos Scientific Laboratory P. O. Box 1663 Los Alamos, New Mexico 87344 David Forslund Joseph Kindell Eric Lindman Ralph Boyer Rodney Mason Claire Nielson Har: Dricier John Ingraham Donald DuBois
- Lawrence Livermore Laboratory University of California Livermore, California 94551

Bill Kruer Jeffery Thomson John DeGroot Victor George John Nucholls Lowell Wood John Emmett Barbara Lasinsky Bruce Langdon John Shearer K. G. Estabrook K. N. Sinz

 U.C.L.A. Los Angeles, California

> John Dawson Burton Fried Y. C. Lee

 University of California Berkeley, California 94720

> Prof. Allan Kaufman Dept. of Physics

 University of Texas Austin, Texas

William Drummond (Phys)

 Princeton University Princeton, New Jersey 08540

> Marshall Rosenbluth Ernie Valeo Carl Oberman Roscoe White Francis Perkins T. K. Chu Hans Hendel N. Porkolab

H. Okuda

7. Massachusetts Institute of Technology Cambridge, Massachusetts 02139

> Bruno Coppi (Phys) T. H. Dupree (Nuc Eng) Abe Bers (Elec Eng)

James McCune (Aero Eng)

 University of Colorado Boulder, Colorado 80302

Martin Goldman

9. Cornell University Ithaca, New York 14850

> R. N. Sudan (App. Phys.) Edward Ott (E.E.)

 Stevens Institute of Technology Hoboken, New Jersey

George Schmidt

11. NOAA Boulder, Colorado 80302

Jerome Weinstock

 University of California, S.D. LaJolla, California 92037

> J. A. Fejer Thomas O'Neil

 College of William and Mary Williamsburg, Virginia 23185

S. P. Gary

Fred Crownfield Dr. G. Vahala (Dept. of Physics)

 14. University of South Florida Dept. of Physics Tampa, Florida 33620

Robert Flynn

15. Culham Laboratory Abingdon, Berkshire England

> Chris Lashmore Davies Ian Cook

16. Sandia Laboratory Albuquerque, New Mexico 87115

Thomas Wright

17. University of Rochester Rochester, New York

> Moishe Lubin E. B. Goldman

- 12. Defense Nuclear Agency Washington, D. C. 20305 Jonathan Farber Peter Haas
- Max Planck Institute für Plasma Physics 8046 Garching near Münich West Germany

D. Biskamp

20. Naval Research Laboratory Washington, D. C. 20375

> Code 7700 - 25 copies Code 7750 - 150 copies

21. U.S.E.R.D.A. Inertial Confinement Division Washington, D. C. 20545

> Leslie Levine Martin Stickley

22. U. S. Navy Materials Support Activity Washington, D. C. 20360

1

R. N. Keeler

23. University of Arizona Tucson, Arizona

Prof. Richard Morse