# Evaluation of the Harpoon Missile Shock Environment During Ejection Launch by Aircraft Launchers

 $\sim$ 

ADA 03706

by Allan G. Piersol Bolt Barenek and Newman Inc. for the Engineering Department

FEBRUARY 1977

Approved for public release; distribution unlimited,





# Naval Weapons Center

		I I There		
R. G. Freeman, III,	RAdm., USN	• • • • •		 Commander
G. L. Hollingsworth	•••••	· · · · · · ·	•••••	 Technical Director

# FOREWORD

The tests described in this report were performed from July 1973 to November 1975 under AIRTASK AOSP-204/2162/6000/00000 and Work Unit A-05P-204/A/RGM-84-5. It is a final report that analyzes the shock spectra environment of a Harpoon missile at ejection.

This report is released at the working level. Because of the continuing nature of this effort, it is probable that further testing will be conducted.

This report was reviewed for technical accuracy by W. N. Jones.



# NWC Technical Publication 5881

Collation	. Technical Information Department
First printing	Cover, 20 leaves
· · · · · · · · · · · · · · · · · · ·	

<u>UNCLASSIFIED</u> SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered) **READ INSTRUCTIONS** EPORT DOCUMENTATION PAGE BEFORE COMPLETING FORM RECIPIENT'S CATALOG NUMBER 2. GOVT ACCESSION NO AFPOR NWC/UP-5881 t. PE OF ATTONY & PERIOD COVERED TITLE (and Subtitie) Final VJuln 1073 - Nove EVALUATION OF THE HARPOON MISSILE SHOCK ENVIRONMENT 1-DURING EJECTION LAUNCH BY AIRCRAFT LAUNCHERS . PERFORMING ORG. REPORT NUMBER 6. 2950, Project No. 157158 CONTRACT OR GRANT NUMBER(+) AUTHCR( .) Allan G.**J**Piersol N 6Ø530-75-M-563Ø Bolt Barenek and Newman Inc. PERFORMING ORGANIZATION NAME AND ADDRESS PROGRAM ELEMENT, P Bolt Barenck and Newman Inc. 21120 Vanowen Street AIRTASK A05P-204/2162/6000/ Canoga Park, CA 91303 00000 REPORT DATE 1. CONTROLLING OFFICE NAME AND ADDRESS 12. February 1077 Naval Weapons Center NUMBER OF PAGES tā. China Lake, CA 93555 38 18. SECURITY CLASS. (of this report) MONITORING AGENCY NAME & ADDRESS(II dillarent from Controlling Office) Unclassified DECLASSIFICATION DOWNGRADING 16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, If different from Ruport) 18. SUPPLEMENTARY NOTES 19. KEY WURDS (Continue on reverse side if necessary and identify by block number) Harpoon Ejection Snock Environment High- and Low-Force Ejection Cartridges High Frequency (Pyrotechnic Shock) Missile Launch Ejection System Maximax Shock Spectrum Residual Shock Spectrum 20. ABSTRACT (Continue on reverse side if necessary and identify by block number) See back of form. DD 1 JAN 73 1473 ELITION OF I NOV 65 IS OBSOLETE UNCLASSIFIED S/N 0102-014-6601 | SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered) 389655 <B

UNCLASSIFIED

SUMITY CLASSIFICATION OF THIS PAGE (When Data Entered)

(U) Evaluation of the Harboon Missile Snack Environment During Ejection Launch by Aircraft Launchers, by Allan G. Persol, Bolt Barenek and Newman Inc. China Lake, Calif., Naval Weapons Center, February 1977. 38 pp. (NWC TP 5881, publication UNCLASSIFIED.)

 $(U)^{h}A$  series of ground launch ejections of a Harpoon missile were performed to establish and evaluate the Harpoon ejection shock environment. The acceleration response of the missile was measured at 30 locations during various ejections from an MAU-9A/A and an Aero-7A-1 rack. The data were reduced to acceleration shock spectra covering a frequency range from 100 to 10 000 Hz. The results of the study produced considerable information concerning launch ejection shock environments of general interest. For example, the shock spectra of the response at all locations typically displayed a sharp increase in level in the frequency range around 800 Hz, which is well above the estimated frequency of the first flexural hoop mode of the missile shell. This frequency appears to be a significant dividing line for various other response characteristics. Increasing the clearance between the ejector foot and missile increased the response shock spectrum levels at frequencies above 800 Hz, but did not significantly increase the levels at lower frequencies. On the other hand, the response levels along the three orthogonal axes were not significantly different, on the average, at frequencies below 800 Hz, but were significantly different at the higher (requencies, with the highest response occurring in the vertical direction and the lowest in the axial direction. There was no significant difference in the missile response during ejections from the MAU-9A/A and Aero-7A-1 rack. However, increasing the force of the ejection cartridges did significantly increase the shock response of the missile at frequencies below 800 Hz. The shock response of the missile decreased greatly with distance from the point of impact. For example, the peak acceleration levels at locations only 10 inches from the point of impact were less than 20%, on the average, of the levels measured at the point of impact.

#### UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

# CONTENTS

Introduction	3
Test Configurations and Procedures         Test Missile Configuration         Data Transducers         Ejection Racks         Test Facility         Test Procedure         Analysis Procedures	
Experimental Results	9 9 11 11 13
Evaluation of Results         Variations Among Repeated Ejection Tests         Variations With Ejector Foot Instrumentation         Variations With Ejector Foot Clearance         Variations With Q Factor         Variations With Measurement Direction         Variations With Type of Rack         Variations With Size of Cartridges         Variations With Structural Locations	10 16 20 20 20 20 20
Comparisons to Equipment Design Criteria Comparisons Based Upon Shock Spectra Comparisons Based Upon Energy Spectra	27 3( 37
Conclusions	33
Appendix: A. Review of Techniques for Evaluating Transient Data	34

# INTRODUCTION

The dynamic response experienced by externally carried aircraft stores during launch ejection can pose a major reliability hazard to store equipment and structure. For example, the Walleye glide bomb has a history of guidance problems when high-force cartridges are used for launch ejection. As a result, restrictions have been placed on the cartridges used to eject the Walleye missiles. Similar restrictions have been placed on other ejection-launched stores. It follows that the shock environment induced by launch ejection is of considerable interest in current development programs of aircraftlaunched weapons, including the Harpoon missile.

Various test programs have been performed in the past to measure the shock environment for aircraft-launched stores during ejection. In most cases, however, data were collected only at frequencies below 2.5 kHz. There have been two recent test programs involving the Antipersonnel-Antimaterial (APAM) and Mk 83 bombs where data were collected at frequencies up to 10 kHz. In both cases the dynamic response of the test items in the frequency range from 2.5 to 10 kHz was substantially greater than expected. These facts motivated an extensive launch ejection test program on the Harpoon missile that would provide shock response data at frequencies up to 10 kHz. This report summarizes the results of that test program and is believed to be of general interest.

# TEST CONFIGURATIONS AND PROCEDURES

The Harpoon missile (AGM-84A) is an antiship missile designed to be launched from aircraft, surface ships, and submarines. The air-launched missile configuration is shown in Figure 1. The missile has a low-level cruse trajectory, active radar guidance, and terminal maneuvering to ensure maximum weapon effectiveness. During cruise it is powered by a turbojet sustainer engine.

#### TEST MISSILE CONFIGURATION

The missile configuration used for the tests simulated a prototype vehicle in size, weight, and CG. The total weight of the test vehicle was 1137 pounds (516 kg), with a CG located at missile station 83.6. No attempt was made to simulate wire bundles, valves, tubing, and other plumbing components; nor was secondary structure included, except where it was required to mount equipment packages. These items contribute very little mass and stiffness, and hence their absence should not significantly influence the shock response. All major equipment items were included in the test configuration. Some of the major components were structurally and mechanically the same as the real equipment, but not necessarily a functional device. Other major items were simulated, with the same mass, CG, and mounting configuration as the component being represented. A description of each missile section and equipment item included in the test vehicle follows.

3

PRECEDING PACE, BLANK NOT FILMED





FIGURE 1. Harpoon Missile.

Guidance Section. This section consisted of an actual radome structure, battery, and midcourse guidance unit (MGU), and a simulated altimeter. The seeker was a structural and mechanical representation of the actual seeker.

Test and Evaluation Section. The T&E section consisted of actual structure with all appropriate openings, doors, trays, and bulkheads, and simulated components. The T&E section simulated the weight and CG of the warhead section in the Harpoon missile, but not the stiffness. Specifically, the stiffness of the T&E section was in excess of that for the Harpoon integrated ordnance section. The two proximity fuzes were mass-simulated installations.

Sustainer Section. This section was composed of actual structure. The fuel tank was filled with water to simulate fuel weight. A spent real prototype engine was used; it was mounted to a prototype mounting ring and associated structure. A number of components that are normally mounted on the engine were not present. Lead ballast was attached to the engine to obtain the total appropriate weight and CG location.

**Boattail Section.** This section was actual structure with one real and three simulated actuators, and one real and three simulated control fins. The outboard location of each control fin CG from the missile mold line was not represented in the simulated fins.

# **DATA TRANSDUCERS**

All acceleration measurements were made using Endevco Type 2292 and 2225 shock accelerometers in conjunction with Endevco Type 2713, 2718, and 2740 charge amplifiers. The accelerometers were mechanically mounted both externally and internally on the test missue, as shown in Figures 2 and 3 and as summarized in Table 1. In addition to the accelerometers, a pressure transducer was used to measure ejector rack cylinder pressure. Breakwires were used to record the time of rack hook release. The times at which the ejector foot impacted and separated from the missile were monitored by an electrical contact strip.



FIGURE 2. Location of External Accelerometers for Harpoon Ejection Tests.



FIGURE 3. Location of Internal Accelerometers for Harpoon Ejection Tests.

5

A STATE

No	Location	Direction	Station no and orientation, deg	Internal or External	Range (zero to peak gs)
VS01 VS02 VS03 VS04 VS05 VS06 VS07 VS08 VS09 VS10 VS11 VS12 VS13	Seeker bulkhead Seeker bulkhead Seeker bulkhead MGU flight control ring MGU flight control ring MGU flight control ring Guidance sect. structure Guidance sect. structure Proximity fuze Proximity fuze Proximity fuze Forward attach lug	Axial Lataral Vertical Axial Lateral Vertical Lateral Axial Lateral Vertical Axial	24.7 24.7 24.7 37.8 37.8 37.8 37.8,0 37.8,0 37.8,0 37.8,0 78,90 78,90 78,90 78,90 68,0	Internal Internal Internal Internal Internal External External External External External External	900 900 900 1000 1000 1000 1000 1000 10
VS14	Forward attach lug	Lateral	68,0	External	3000
VS15	Forward attach lug	Vertical	68,0	External	3000
VS16	Ejector foot impact	Axial	88,0	External	5000
VS17	Ejector foot impact	Lateral	88,0	External	5000
VS18	Ejector foot impact	Vertical	88,0	External	5000
VS19	T&E sect, structure	Lateral	88,90	External	5000
VS20	T&E sect, structure	Vertical	88,180	External	5000
VS21	Aft attach lug	Axial	98,0	External	5000
VS22	Aft attach lug	Vertical	98,0	External	5000
VS23	Engine sect. structure	Axial	136,0	External	1000
VS24	Engine sect. sturcture	Vertical	136,0	External	1000
VS25	Engine sect. structure	Lateral	136,90	External	1000
VS26	Engine sect. structure	Axial	138,0	External	1000
VS27	Engine sect. structure	Vertical	138,0	External	1000
VS28	Fuel controller	Vertical	Sustainer engine	Internal	1000
VS29 VS30 ₽S01	Control fin actuator Control fin actuator Rack cylinder pressure	Axial Radial	152.8,45 152.8,45 On ejection rack	External External	800 800

TABLE 1. Summary of Transducer Locations for Harpoon Ejection Tests. PS01 used pressure sensor; all others used accelerometers

#### **EJECTION RACKS**

Two different ejection racks were used for the tests, an Aero-7A-1 rack and a MAU-9A/A rack. Both rack assemblies consist of the following: a dual cartridge breech assembly, a hook assembly a star assembly group, and a sway brace assembly. Both racks accept the same cartridge combinations: one Mk 2 Mod 0 and one Mk 1 Mod 2 cartridge (this combination is hereafter referred to as the high-force cartridges) or two Mk 2 Mod 0 cartridges (hereafter referred to as the low-force cartridges). Nominal force-time histories for the two cartridge combinations are shown in Figure 4.



FIGURE 4. Nominal Ejection Force-Time Histories for Aero-7A-1 and MAU-9A/A Ejection Racks.

# **TEST FACILITY**

The ejection tests were conducted at the Ground Ejection Test Facility, Pacific Missile Test Center, Point Mugu, Calif. The missile was allowed to free-fall approximately 6 feet (2 meters) after ejection before being arrested by restraining rope. All of the signal conditioning equipment was adjacent to the stand and hard-wired to the missile. The data were recorded in a data acquisition van located adjacent to the test stand. Figure 5 illustrates the test setup.

# **TEST PROCEDURE**

The missile was installed on the ejection rack to simulate an actual aircraft installation. The cartridges were installed, the rack was armed, and a firing countdown was initiated. The tape recorders were turned on about 5 seconds before the ejection. After each ejection the missile was inspected for damage and was then reinstalled on the ejection rack. The restraining ropes were replaced, the instrumentation was again checked out, precalibrated, etc., and the above sequence was repeated. The first three tests were performed primarily for equipment checkout and calibration. The test sequence was as shown in Table 2.



FIGURE 5. Harpoon Ejection Test Stand and Setup.

Test no.	Rack used	Ejector foot clearance	Ejector foot instrumentation	Cartridges Used
18	MAU-9A/A	Normalb	Yes	Low-force
24	MAU-9A/A	Normal	No	Low-force
38	MAU-9A/A	Normal	No	Low-force
4	MAU-9A/A	Normal	Yes	Low-force
5	MAU-9A/A	Normal	Yes	Low-force
6	MAU-9A/A	1/4 in. (6.4 mm)	res	Low-force
7	Aero-7A-1	Normal	Yes	Low-force
8	Aero-7A-1	Normat	Yes	Low-force
9	Aero-7A-1	Normal <sup>c</sup>	No	Low-force
10	Aero-7A-1	Normal	No	High-force
11	Aero-7A-1	Normal	No	High-force

TABLE 2. Test Sequence for Harpoon Ejection Tests.

<sup>a</sup>Equipment checkout and calibration tests.

bNormal clearance generally less than 1/16 in (1.6 mm) (first detent)

CA repeat of Tests 7 and 8 with the ejector foot instrumentation (electrical contact strip) removed.

## **ANALYSIS PROCLDURES**

The acceleration transients measured at various locations on the Harpoon missile during the simulated ejections were evaluated in terms of significant transient events and peak acceleration levels. The acceleration-time records were reduced to response (shock) spectra for more detailed evaluation using an SD 3.20 analyzer. Selected records were also reduced to energy spectra. (For the benefit of those readers who may not be familiar with these analysis procedures, a brief review and discussion are presented in Appendix A.)

# EXPERIMENTAL RESULTS

The basic results of the Harpoon missile ejection test consist of acceleration-time histories, peak, acceleration values, energy spectra, and shock spectra at the various measurement locations. Peripheral results include measurements of the ejection rack cylinder pressure, the time of contact and separation between the rack ejector foot and the missile, and the time of the rack hook release. Pertinent characteristics of these results are summarized in the following sections.

### ACCELERATION-TIME HISTORIES AND RELATED PARAMETERS

Figure 6 shows a typical time history of an acceleration response that was measured on the Harpoon structure near the point of the ejector foot impact during a low-force ejection from the MAU-9A: A rack. Note that the history displays three distinct transient events, the first initiating at





about 2 ms, the second at about 56 ms, and the third at about 78 ms after cartridge ignition. The first event is due to the initial impact of the ejector foot on the missile. The third event reflects the tinal separation of the missile from contact with the ejector foot.

The source of the second event at about 56 ms is uncertain, but it appears that it may be related to a discontinuity in the ejection rack thrust, or perhaps even a momentary separation between the ejector foot and the missile. The event is present in the histories at all locations during all ejections. It occurs at about 47 ms after cartridge ignition during ejections from the Aero-7A-1 rack with the low-force cartridges, and at about 39 ms with the high-force cartridges. The vertical acceleration-time history for the latter case at the point of ejector foot impact is shown in Figure 7. Although of uncertain origin, this event between the initial impact and final separation is assumed to be physically significant and hence is included in the calculation of shock and energy spectra.

At locations more widely separated from the point of ejector foot impact, the acceleration-time histories are more complex. Figure 8 shows the vertical acceleration response measured on the guidance section structure during the same ejection that produced the data in Figure 6. Note that the same three events seen in Figure 6 are present at this location as well, but the responses have lower peak levels and are more spread in time. In particular, the initial transient starting at about 2 ms appears to maintain its strength up to about 15 ms, and then build up again between 20 and 25 ms. This is believed to represent the influence of flexural waves propagating from the point of impact down the missile shell at their group velocity (estimated to be about 600 ft/s (183 m/s) at the predominant frequency of about 700 Hz). For example, in the forward section of the missile at about 7 ms after impact, and reflect back off the nose past this same position at about 15 ms after impact. This is reasonably consistent with the results shown in Figure 8.



₿ 4 ¶¶

ないないないで、

#### TIME AFTER CARTRIDGE IGNITION, ms

FIGURE 7. Acceleration-Time History at Ejector Foot Location (VS18) During Ejection Test 11 (Aero-7A-1 Rack With High-Force Cartridges).



FIGURE 8. Acceleration-Time History at Guidance Section Location (VS08) During Ejection Test 4 (MAU-9A/A Rack With Low-Force Cartridges).

#### PEAK ACCELERATION RESULTS

The peak values of the acceleration-time histories recorded at the various measurement locations during Tests 4 through 11 are presented in Table 3. Note that the peak acceleration levels vary dramatically with type of rack, cartridge combination, and structural location. In general, the peak accelerations diminish rapidly with distance from the point of ejector foot impact, as will be discussed further in the "Evaluation of Results" section.

#### **ENERGY SPECTRA RESULTS**

A typical energy spectrum of the acceleration response is presented in Figure 9. This particular energy spectrum was computed from the acceleration-time history shown previously in Figure 7, using only that segment covering the separation transient from 55 to 62 ms. Since the separation transient in these tests approximates a unit step input, the energy spectrum at any location is closely related to the square of the frequency response function of the missile structure between that location and the impact location, as suggested by Equation (A-5) in the Appendix A. Hence the various significant peaks in the energy spectrum shown in Figure 9 represent important normal modes of the missile structure. For example, there is a peak at about 1000 Hz, which probably represents a strongly excited hoop mode of the missile shell. The peak at about 3000 Hz undoubtedly represents another strongly excited hoop resonance.

Tests.	
Ejection	cartrid <b>ges</b> .
Harpoon	ligh-force
During I	and 11: h
Measured	Tests 10
Levels	cartridges.
celeration	w-force (
Peak Aci	rough 9: 1
ABLE 3.	Tests 4 th
Ē	

	11 Aero-7A-1	19	8	: 6	45	45	8	<u>8</u> 8	8 9	<u>۽</u> ۽	<u>:</u>	33	ß	240	300	650	970	•	63	:	8	8	8	;	8	:	33	3
	10 Aero-7A-1	15	30	22	55	45	110	8	£ 5	3 5	38	8	8	<b>360</b>	450	625	420	<b>660</b>	110	130	30	65	55	3	20	8	40	
rough 11	9 Aero-7A-1	13 15	:	108	80	55	65	87	8 1		55	35	8	250	280	200	600	400	137	142	33	85	65	4	8	13	•	57
or tests 4 th	8 Aero-7A-1	12	18	្ទំខ្ល	45	35	75	87	42 42	7 8	3 23	35	8	190	160	200	400	220	67	<u>95</u>	13	8	:	8	35	Q	ଛ	33
ation in gs 6	7 Aero-7A-1	23	18		20	45	55	123	:		:	:	:	:	;	:	475	350	115	160	80	97	8	45	8	:	õ	46
Peak acceler	6 MAU-9A/A	12	2 8	83 2)	19	52	2	75	85	DC PPE	8	36	82	248	250	368	576	315	118	150	42	8	100 1	25	8	16	2	108
	5 MAU-9A/A	2 2	: 0	: 8	33	22	8	38	 *	2	5 5	16	Ř	116	152	176	200	224	88	8	3	<b>Ş</b>	\$	35	23	ŋ	24	\$
	4 MAU-9A/A	12	: 2	: 9	8	74	<b>5</b>	8	23	: 8	8 8	19	42	8	140	Z18	248	<b>305</b>	92	92	8	23	8	38	<b>4</b> 8	~	R	8
	Direction	Axial I ateral	Vertical	Axial Lateral	Vertical	Axial	Vertical	Lateral	Axial	Variation	Axial	Lateral	Vertical	Axial	Lateral	Vertical	Lateral	Vertical	Axial	Vertical	Axial	Vertical	Lateral	Axial	Vertical	Vertical	Axial	Radial
	Location	Seeker buikhead Seeker huikhead	Seeker bulkhead	MGU flight control ring MGU flight control ring	MGU flight control ring	Guidance sect. structure	Guidance sect. structure	Guidance sect. structure	Proximity fuze	Proximity luce	Forward attach lug	Forwerd attach lug	Forward attach lug	Ejector foot impact	Ejector foot impact	Ejector foot impact	T&E sect. structure	T&E sect. : tructure	Aft attach ug	Aft attach lug	Engine sect. structure	Fuet controller	Control fin actuator	Control fin actuator				
	No.	VS01	VS03	VS04 VS05	VS06	VS07	VS08	60SA	US10	Liev Versy	VS13	VS14	VS15	VS16	VS17	VS18	VS19	VS20	VS21	<b>VS22</b>	VS23	VS24	VS25	VS26	VS27	VS28	VS29	VS30





FIGURE 9. Energy Spectrum at Ejector Foot Location (VS18) For Separation Transient During Ejection Test 11 (Aero-7A-1 Rack With High-Force Cartridges).

# SHOCK SPECTRA RESULTS

ł

2.1

A typical set of shock spectra for the acceleration response are presented in Figures 10 and 11. The two spectra in Figure 10 are maximax results for two different damping ratios, specifically, Q = 10 and Q = 100. The spectra in Figure 11 represents the positive and negative shock spectra for Q = 100. All of the spectra were computed from the acceleration-time history previously presented in Figure 7.

In Figure 10 it is seen that the shock spectra levels are somewhat higher for the more lightly damped case, as would be expected. In both cases, Q = 10 and Q = 100, the spectra display peaks at about the same frequencies. Furthermore, the frequencies of these significant peaks correspond in many cases to the frequencies of peaks previously observed in the energy spectrum shown in Figure 9. In broad terms, however, the shock spectrum values tend to rise and the energy spectrum values tend to fall with increasing frequency. This observation is consistent with the  $\frac{1}{2}$  is difference in the characteristics of shock and energy spectra, as is discussed in Appendix A.

In Figure 11 it is seen that the positive and negative shock spectra of the transient are similar at frequencies above 600 Hz. At the lower frequencies, however, the positive spectrum levels sometimes exceed the negative levels by a significant amount. This reflects the fact that the basic transient associated with the rack ejector foot striking the missile is in the positive (downward) direction.







FIGURE 11. Positive and Negative Shock Spectra for Q = 100 at Ejector Foot Location (VS18) During Ejection Test 11 (Aero-7A-1 Rack With High-Force Cartridges).

# EVALUATION OF RESULTS

Various aspects of the shock spectra test results are of interest, including variations with repeated ejections, ejector foor instrumentation, foor clearance, rack type, cartridge size, measurement direction, and measurement location. Such variations were investigated using the shock spectra results and the peak acceleration data summarized in Table 3. To permit the evaluations to be performed in an efficient manner, the shock spectra of interest were first converted to average levels in contiguous 1/3-octave bandwidths. Both the shock spectra values and the peak acceleration values were also converted to dB referenced to 1 g (dB = 20 log g). This was done so a given percentage difference in acceleration values would be weighted equally in the statistical studies, independent of the absolute acceleration values. All statistical evaluations were performed using the well-known UCLA biomedical statistical data analysis computer programs.

Many of the evaluations involved comparisons of different cases based upon average shock upectra values. These average spectra were computed separately for each 1/3-octave band by averaging over all locations where data were available for the cases being compared in that plot. Due to the wide dynamic range of the shock spectra data, accurate shock spectra values were not always tetrieved at all locations, particularly in the frequency range below 1000 Hz. Since this problem was most common at those locations displaying relatively low response levels, the average values computed in the frequency range below 1000 Hz often tended to be biased upwards. However, in any given figure to follow, the same locations were used for all cases of interest to compute the average values in a given 1/3-octave band, and hence the results within that figure are directly comparable.

#### VARIATIONS AMONG REPEATED EJECTION TESTS

Referring back to Table 2, the test missile was ejected at least twice from each of the three ejection rack-cartiidge configurations. The rack performance from one test to another for a given configuration was quite consistent, at least as measured by the chamber pressure-time histories. This fact is demonstrated in Figure 12, which shows the pressure-time histories for Tests 4, 5, and 6, all



FIGURE 12. Rack Chamber Pressure-Time Histories for Repeated Ejections During Tests 4, 5, and 6 (MAU-9A/A Rack With Low-Force Cartridges).



17

عاطتها احتليانا

involving the MAU-9A/A rack with the low-force cartridges. Note that the ejector foot clearance was increased for Test 6, which probably explains the less stable result for this test.

The peak acceleration values measured at the various locations during repeated ejections under identical conditions are also in close agreement, on the average, as demonstrated in Table 4. In both comparisons, the difference in the average peak acceleration levels is not sufficient to be considered statistically significant at the a = 1% level of significance, based upon a conventional Student "t" test of differences.

The shock spectra values measured at specific locations on the missile sometimes differ between repeated tests by up to 2:1 (6 dB) at certain frequencies. On the average, however, the shock spectra for repeated tests are in good agreement (within anticipated statistical variations), at least in the frequency range below 4000 Hz, as shown in Figure 13. At frequencies above 4000 Hz, discrepancies are observed between the average shock spectra values up to 3.5 dB. These discrepancies are slightly outside the range of expected statistical variations and may represent the sensitivity of the high frequency response of the missile to the exact manner in which the ejector foot initially strikes the missile structure. In any case the repeatability of the test results is considered acceptable.

Test no.	Test config- uration	Average of peak accelerations dB	Average difference dB	Standard deviation, dB	Sample size	Significant difference at 1% levol, dB
4	10	33.46				
6		32.65	0.81	1.75	28	0.91
6	1	37.10	, c	<b>. C</b>	. C	c
10	20	37.80				
11.	2	36.86	0.94	3.51	23	2.05

TABLE 4. Comparison of Average Peak Acceleration Levels for Repeated Ejection Tests.

#MAU-9A/A rack with low-force cartridges, normal ejector foot clearance, and ejector foot instrumentation

<sup>b</sup>Aero-7A-1 rack with high-force cartridges, normal ejector foot clearance, and no lejector foot instrumentation

©Not analyzed.

### VARIATIONS WITH EJECTOR FOOT INSTRUMENTATION

Some of the ejection tests were performed with an electrical contact strip mounted on the missile to identify the times of foot-missile contact and separation. For Tests 9, 10, and 11 this instrumentation was removed. During the initial checkout tests (1, 2, and 3), it was determined by visual inspection of acceleration-time histories that the ejector foot instrumentation had no significant influence on the resulting missile structural response. However, the peak acceleration data for Tests 7 and 8 versus 9, which were identical ejections except for the ejector foot instrumentation, suggest that the electrical contact strip might have caused a slight reduction in the resulting shock loads, at least as measured by peak acceleration levels on the n'ssile structure. The average of the peak accelerations recorded during Tests 7 and 8 were about 1.5 dB lower, on the average, than the peak accelerations recorded during Test 9. This constitutes a statistically significant difference at the 1% level of significance but not a major difference in physical terms. Nevertheless, the possibility of some minor influence due to the ejector foot instrumentation should be kept in mind when comparing the results of tests performed with and without the instrumentation.

and the sub-state of the





19

MERICANSIN LA CLASSING

فاستحد فالمأساد فبعذك

# VARIATIONS WITH EJECTOR FOOT CLEARANCE

Of the three ejection tests performed with the MAU-9A/A rack using the low-force cartridges (Tests 4, 5, and 6), Test 6 was conducted with the ejector foot-missile clearance increased to 1/4 inch (6.4 mm) from the normal 1/16 inch (1.6 mm) or less. The peak acceleration data in Table 4 indicate a significant increase in levels due to the increased clearance. Specifically, the average of the peak accelerations with the increased clearance is 37.1 dB, as compared to 33.0 dB with normal clearance. However, most of this increased structural response with increased clearance occurs in the frequency range above 800 Hz as illustrated in Figure 14, which presents the average shock spectra of the shock spectrum levels for the increased clearance case are no more than 1.8 dB higher than for the normal clearance case at frequencies below 800 Hz. Above 800 Hz, however, the levels for the increased structure at some frequencies, well beyond the limits of anticipated statistical variations. Therefore, it must be concluded that the shock response of the missile structure at frequencies above 800 Hz is dependent upon the clearance between the ejector foot and the missile.

#### **VAPIATIONS WITH Q FACTOR**

Shock spectra values for any given transient are a function of the damping ratio; a smaller damping ratio (larger Q) will produce larger shock spectra values. This dependence on Q for the Harpoon shock data is illustrated in Figure 15, which presents the average spectra for all locations during Tests 4 and 5 computed for Q = 10 and Q = 100. Note that there is no significant statistical error in the indicated differences between the Q = 10 and Q = 100 curves, since both curves were computed from identical histories. Figure 15 shows that the shock spectrum values for Q = 100 exceed the values for Q = 10 by less than 1.5 dB at frequencies below about 800 Hz. At higher frequencies, however, the difference increases to about 4.5 dB. This result indicates that the Harpoon structure tends to "ring" for a longer period of time at the higher frequencies; i.e., the structural response to the ejection shock tends to decay much more rapidly at the lower frequencies. This reaction is generally characteristic of the response of lightly damped structures to sharp impact loads.

# VARIATIONS WITH MEASUREMENT DIRECTION

Figure 16 shows the differences in the average shock spectra levels for Q = 100 along the three orthogonal axes during Tests 4, 5, and 6. These results indicate that the shock spectrum levels at most frequencies are lowest in the axial direction and highest in the vertical direction, as would be expected for a cylindrical structure subjected to a slock load normal to its axis. However, the differences in the spectral values among the three orthogonal lixes are not dramatic, particularly at the lower frequencies. For example, in the frequency range below 800 Hz, the differences among the three axes are always less than 3 dB, as compared to anticipated statistical variations of about  $\pm 2$  dB for each measurement.

#### VARIATIONS WITH TYPE OF RACK

The average shock spectra values for Q = 10 for ejections from the MAU-9A/A rack with low-force cartridges and similar data from the Aero-7A-1 rack are compared in Figure 17. Note that the general shapes of the average shock spectra for the two cases are similar, but the spectral values





FIGURE 14. Shock Spectra Average Over All Locations for Ejections During Tests 4, 5, and 6 (MAU-9A/A Rack Using Low-Force Cartridges With Normal and Increased Ejector Foot Clearance). Average levels at frequencies below 1000 Hz computed over those locations of most intense response only.

NIVC TP 5881







FIGURE 16. Shock Spectra for Q = 100 Averaged Over All Locations Along Each Orthogonal Axis for Ejections During Tests 4, 5, and 6 (MAU-9/A Rack Using Low-Force Cartridges). Average levels at frequencies below 1000 Hz computed over these locations of most intense response only.



.

ў ( 471) 1

![](_page_26_Figure_2.jpeg)

for the Aero-7A-1 rack ejection are consistently higher by 1 to 3 dB at all frequencies, except for the lowest band at 100 Hz. Although this discrepancy is usually within the range of anticipated statistical variations for any given frequency band, the consistency of the discrepancy over all frequencies suggests that the shock loads were actually higher by a small amount (1.3 dB on the average) for the Aero-7A-1 ejection. It should be noted, however, that the MAU-9A/A ejections (Tests 4 and 5) were performed with the ejector foot instrumentation installed, whereas the Aero-7A-1 ejection was performed without this instrumentation. A possible explanation for the indicated difference in levels is given in a later section called "Comparisons Based Upon Energy Spectra."

On the other hand, the peak acceleration data in Table 4 tend to support the conclusion that the shock response of the missile during ejection from the Aero-7A-1 rack, even with the ejector foot instrumentation, was somewhat more severe than during ejection from the MAU-9A/A rack, at least in the region of the ejector foot impact. Furthermore, the nominal force-time histories for ejections from the two racks, as shown in Figure 4, indicate that the peak ejection force is slightly higher for the Aero-7A-1 rack, which could translate into slightly higher shock response levels. On balance, however, any differences that may exist in the missile shock environment due to ejections from the MAU-9A/A versus the Aero-7A-1 rack do not appear to be sufficiently great to warrant separate consideration of the two racks.

## VARIATIONS WITH SIZE OF CARTRIDGES

Figure 18 compares the average shock spectra values for Q = 10 for an ejection from the Aero-7A-1 rack with the low-force and the high-force cartridges. It should be mentioned that the dynamic range of the analysis for the measurements was quite good, and hence even the low frequency values represent an accurate average of almost all the 30 measurements made on the missile structure.

It is clear from Figure 18 that the missile shock response is more severe for the ejection with the high-force cartridges, particularly in the frequency range below 800 Hz. The average shock spectrum levels are consistently about 4 dB higher in this frequency range when the high-force cartridges are used. Noting that the nominal ejection force with the high-force cartridges is about twice as great as for the low-force cartridges, one might have expected the shock response levels to have doubled, i.e., to have increased by 6 dB. The lack of a full 6-dB increase in levels with the doubling of ejection force probably reflects the influence of nonlinearities in the response of the missile structure to intense shock loads.

#### VARIATIONS WITH STRUCTURAL LOCATIONS

i) i

ł

The 30 mealurements of the missile shock response during the various ejection tests were made at 10 specific structural locations over the length of the missile, as shown in Table 1 and Figures 2 and 3. It is now of interest to evaluate how the missile shock response varied from one location to another. This variation is illustrated in Figure 19 in terms of peak acceleration levels versus the missile station number for the locations. The peak acceleration levels averaged over the available measurements at each location are shown separately for the three basic ejection rack-cartridge configurations tested.

The results in Figure 19 clearly demonstrate that the missile shock response diminishes very rapidly with axial distance from the point of ejection, as would be expected. For example, from the point of ejector foot impact to the proximity fuze, a distance of only 10 inches (8.3 m), the peak

![](_page_28_Figure_0.jpeg)

![](_page_28_Figure_1.jpeg)

![](_page_29_Figure_0.jpeg)

FIGURE 19. Peak Acceleration Response Levels Versus Missile Station Number for Various Ejection Rack and Cartridge Combinations.

acceleration levels during ejections from the Aero-7A-1 rack drop by 16 dB (a ratio of over 6:1). From the ejector foot to the seeker bulkhead, the drop is over 28 dB (a ratio of 25:1). In other words, the seeker section at station 25 sees acceleration peaks that are only 4% as great as those measured at station 88, the point of impact. About 10 dB of this reduction occurs over the last 10 inches (8.3 m) between the guidance section and the seeker section.

This dramatic variation in the shock response with structural location is illustrated by the shock spectra data shown in Figures 20 and 21. Here the shock spectra average of available measurements at each location are shown for ejection from the Aero-7A-1 rack with high-force cartridges. The shock spectra for locations at station 88 (the ejector foot and T&E section structure) far exceed those at all other locations and frequencies. The seeker section at the forward end of the missile displays a uniquely low shock response spectrum at frequencies above 200 Hz. The shock spectra at other locations scatter between these two extremes.

# COMPARISONS TO EQUIPMENT DESIGN CRITERIA

The environmental design criteria for the Harpoon missile 1 specify that the missile equipment should withstand a half-sine-wave shock load with a duration of 0.5 ms and an amplitude of 385 to 1100 g, depending upon the location along the length of the missile. The peak acceleration levels

Ĩ

<sup>1</sup>Naval Air Systems Command. Environmental Design Criteria for the AGM-84A/RGM-84A Missile (Harpoon.) Washington, D.C., 1973. (XAS-2381A.)

![](_page_30_Figure_1.jpeg)

FIGURE 20. Shock Spectra for Q = 10 Averaged Over Three Axes at Various Locations for Ejection (Aero-7A-1 Rack Using High-Force Cartridges).

![](_page_31_Figure_0.jpeg)

FIGURE 21. Shock Spectra for Q = 10 Averaged Over Three Axes at Various Locations for Ejection (Aero-7A-1 Rack Using High-Force Cartridgos).

measured during the test ejections, as summarized in Table 3, are all well below the peak acceleration level of the equipment design criterion for each location. However, as is discussed in Appendix A, the peak accelerations in themselves do not provide a fully definitive comparison between dissimilar transient acceleration-time histories. A comparison based upon a frequency-dependent parameter is generally more meaningful. Such equipment comparisons are now made using both shock and energy spectra for the ejection from the Aero-7A-1 rack using the high-force cartridges. Based upon the evaluations of the equipment comparisons, this case generally represents the most severe launch ejection shock condition tested.

#### COMPARISONS BASED UPON SHOCK SPECTRA

In Figures 22, 23 and 24 shock spectra for the equipment design criteria are compared to the measured shock spectra of the missile response at three key equipment locations. In these figures the measured shock spectrum shown for each location represents the maximum spectral value computed in all directions at that location, independently for each 1/3-octave frequency band, during ejection from the Aero-7A-1 rack with the high-force cartridges.

From Figures 22, 23, and 24 it is seen that the ejection shock response of the Harpoon equipment, as measured in terms of a Q = 10 shock spectrum, falls well below the design requirements at all locations considered. It appears reasonable to conclude that the Harpoon equipment design criteria for ejection shock loads are conservative.

![](_page_32_Figure_5.jpeg)

FIGURE 22. Comparison of Q = 10 Shock Spectrum Levels and Design Criterion for the Midcourse Guidance Unit.

![](_page_33_Figure_0.jpeg)

![](_page_33_Figure_1.jpeg)

![](_page_33_Figure_2.jpeg)

![](_page_33_Figure_3.jpeg)

FIGURE 24. Comparison of Q = 10 Shock Spectrum Levels and Design Criterion for Proximity Fuze.

31

the here and

and an and a second second

1. 1.

المعلكمة أأفاده

# COMPARISONS BASED UPON ENERGY SPECTRA

Figure 25 compares the energy spectrum for the design criteria to the measured energy spectrum of the missile response at the seeker. As before, the measured energy spectrum represents the maximum spectral value computed in all directions at that location, independently for each 1/3-octave band, during ejection from the Aero-7A-1 rack with high-force cartridges. Since the energy spectra for both the design criteria and actual data fall off to insignificant values at the higher frequencies, results are shown for the frequency range up to 2500 Hz only. The energy spectra measured at this location displayed considerable scatter, and the data were heavily smoothed to arrive at the results shown in Figure 25. It is seen, however, that the energy spectrum of the shock response measured on the seeker bulkhead falls surprisingly close to the design requirement at most frequencies. In general, the design requirement appears to be slightly conservative.

Comparing the results in Figure 25 to those previously presented in Figure 23, it is seen that the energy spectrum levels are generally higher relative to the equipment design criterion than the shock spectrum levels at the same equipment location. This observation points out a major deficiency in the use of energy spectra for multiple event data of the type involved in those experiments. Specifically, the missile shock response-time history for any given ejection includes at least three distinct transient events that are rather widely separated in time, as previously detailed in the "Acceleration-Time Histories and Related Parameters" section. The energy spectrum for the entire shock response-time history includes contributions from all of these individual events. Furthermore, the repetition of distinct events with a relatively wide time separation causes a strong low frequency contribution to appear in the overall energy spectrum which is not present in the spectrum of each event taken alone (see Figure 9). These factors are not as influential in a shock spectrum, assuming " reasonable degree of damping. For the case of Q = 10, the hypothetical oscillators producing the shock spectrum values will generally decay to near zero response between the separate events, at least at the higher frequencies. This means that the shock spectrum tends to reflect primarily the most severe of the individual transients, which probably constitutes a more realistic measure of damage potential than that provided by the energy spectrum.

![](_page_34_Figure_4.jpeg)

![](_page_34_Figure_5.jpeg)

#### CONCLUSIONS

The specific conclusions to be drawn from this study of the Harpoon missile response to simulated launch ejection shock loads may be summarized as follows.

1. The response of the missile is sensitive to the clearance between the ejector foot and the missile. Specifically, the average shock spectra of the acceleration response at frequencies above 800 Hz were np to 6 dB (100%) higher when the clearance was increased from normal (less than 1/16 inch (1.6 mm)) to 1/4 inch (6.4 mm).

2. The acceleration response shock spectrum levels computed for Q = 100 exceed those computed for Q = 10 by about 1 dB at frequencies below 800 Hz and about 4 dB at frequencies above 800 Hz.

3. The shock spectra of the acceleration responses are generally highest along the vertical axis of the missile and lowest in the axial direction. However, the differences among the three orthogonal axes are not significant in the frequency range below 800 Hz. At the higher frequencies, the vertical response is up to 4 dB (60%) higher than the axial response.

4. The response of the missile is about the same for ejections from the MAU-9A/A rack and the Aero-7A-1 rack using similar cartridge combinations.

5. The response of the missile is higher when ejection cartridges of greater force are used. When the nominal force of the ejection cartridges was doubled, the average shock spectrum of the acceleration responses increased by about 4 dB (60%) in the frequency range below 800 Hz. At the higher frequencies, the shock spectrum levels increased by less than 2 dB (25%).

6. The response of the missile falls off dramatically with distance from the ejector foot impact location. For example, the peak acceleration levels at a location only 10 inches (8.3 m) from the ejector foot were about 16% of those measured at the ejector foot location. The lowest levels were measured in the seeker section near the nose of the missile, where the peak acceleration was only 4% of that measured at the ejector foot. In terms of shock spectra, the levels in the seeker section were 20 to 30 dB lower than at the ejector foot location, indicating that the ejection shock is strongly attenuated with distance.

7. In terms of shock spectrum levels, the environmental design criteria for the missile ejection shock loads are generally conservative. At some locations the design criteria exceed the measured response levels by up to 20 dB (10:1).

The above specific conclusions apply rigorously to the Harpoon missile only. Yet most of the conclusions could probably be applied to another missile of similar construction, assuming that differences in key structural parameters are properly taken into account. For example, the flexural hoop mode of the missile shell appears to constitute an important parameter in establishing the response characteristics of the missile as measured by a shock spectrum. Hence, conclusions 1, 2, 3 and 6 might be assumed in the preliminary design of a new missile by scaling the shock spectra frequencies with the ratio of the estimated frequency of the first flexural hoop mode of the new missile, relative to the Harpoon missile. This scaling can generally be accomplished using the simple parameter  $t/R^2$  where t is the missile shell thickness and R is the missile radius.

# Appendix A REVIEW OF TECHNIQUES F( : EV/LUATING TRANSIENT DATA

#### BACKGROUND

Simple transients involving only one or a few oscillations that are basically deterministic in character (that is, highly repetitious in detail from one sample record to the next for a repeated experiment) can sometimes be described adequately for desired applications solely in terms of a response-time history, or some pertinent property of the history such as a peak value and duration. For these cases the transient can often be approximated by some classical waveform (for example, an N wave for sonic booms) which can then be used to evaluate the response of any structure of interest, or to simulate the transient for testing purposes.

For transients that are more complex or atochastic in character, a response-time history by itself is generally of only limited value. Properties of a given history, such as the peak value and duration, may vary significantly from one sample record to the next for a repeated experiment, and also may not fully define the dynamic characteristics of the transient. Examples here include many transients originating from ordnance explosions, particularly when the transients represent the response of some point on a complex structure. The acceleration response data measured at various points on the Harpoon missile structure during aircraft ejection fall into this category. In such cases it is generally more convenient to evaluate the transient for both structural analysis and simulation purposes in terms of some statistically pertinent spectral parameter, rather than in terms of direct response-time histories.

The classical random noise theory provides several techniques that are applicable to the analysis of general nonstationary stochastic phenomena, including complex mechanical shocks. In particular, such data can be analyzed in terms of either a generalized power spectrum or an instantaneous power spectrum, if an ensemble of sample records from repeated trials of an experiment is available.<sup>2</sup> The generalized power spectral density function provides a spectral description in a double frequency plane: the instantaneous power spectral density function yields a time-dependent spectrum. The advantage of such descriptions is that they provide rigorous analytical input-output relationships for structural analysis problems. Their principal disadvantage is that they require considerable data from repeated trials of the experiment of interest that can be voluminous, and the resulting spectra are difficult to interpret in qualitative terms.

For the case of transients that have a clearly defined beginning and end, an overall spectral description for the entire transient event, as opposed to a time-dependent spectral description, is usually satisfactory from the applications viewpoint, and much easier to measure and interpret. Two such overall spectral descriptions in common use are the energy spectrum and the shock response spectrum.

#### ENERGY SPECTRA

Consider a transient time history record x(t) which is nonzero only over a finite time interval  $t_0 \le t \le t_0 + T$ . For the problem at hand, x(t) would be an acceleration measurement, although it might be any measurement parameter of interest. This history can be transformed into the frequency domain via its Fourier transform given by

<sup>2</sup>J. S. Bendat, and A. G. Piersol. *Random Data: Analysis and Measurement Procedures*. New York, Wiley-Interscience, 1971, Pp. 360-62.

$$X(f) = \int_{-\infty}^{\infty} x(t) e^{-j2\pi f t} dt = X_R(f) - jX_f(f)$$
 (A-1)

where

$$X_R(f) = \int_{t_0}^{t_0+T} x(t) \cos 2\pi f t \, dt \tag{A-1a}$$

$$X_{f}(f) = \int_{t_{O}}^{t_{O}+T} x(t) \sin 2\pi f t \, dt \tag{A-1b}$$

so long as x(t) = 0 except for  $t_0 \le t \le t_0 + T$ . The real part of the Fourier transform,  $X_R(f)$ , defines the coincident portion of the Fourier spectrum while the imaginary part,  $X_I(f)$ , gives the quadrature portion. The Fourier transform may also be expressed in complex polar notation by

$$X(f) = |X(f)| e^{-f(\theta(f))}$$
(A.2)

where

$$|X(f)| = [X_R^2(f) + X_f^2(f)]^{\nu_1}$$
 (A·2a)

$$\theta(f) = \tan^{-1} \left[ X_f(f) / X_R(f) \right] \tag{A-2b}$$

The absolute value of the transform, X(f) yields its magnitude and the argument,  $\theta(f)$ , defines an associated phase angle.

The Fourier transform given by Equations (A-1) and (A-2) provides a convenient and analytically useful spectral description of a transient, but one that is uniquely related to the exact transient history; i.e., X(f) defines one and only one x(t). Hence, the use of an X(f) computed from the history produced by a single trial of an experiment introduces the same problems associated with the use of x(t); specifically, X(f) will vary from trial to trial of a given experiment if the transient is stochastic in character. However, for many mechanical, shock-type transients, the stochastic character of the transient is more apparent in the argument of the Fourier transform than in its magnitude. To be specific, if an experiment producing a stochastic transient history is repeated many times, the spectral energy of the resulting histories, as given by

$$E_{\mathbf{x}}(f) = |X(f)|^2 = X_{R}^2(f) + X_{I}^2(f)$$
(A-3)

will often be quite consistent from one sample record to the next, even though the associated phase factor,  $\theta$  (f), might vary dramatically. For many applications, the energy spectrum alone will provide adequate information.

The energy spectrum E(f) for a transient is analogous to the power spectrum commonly used to describe the spectral content of stationary random vibrations, and is interpreted and applied in the

same way. When given two statistically independent transients, x(t) and y(t), their energy spectraare additive, i.e.,

 $E_{x+y}(f) = E_{x}(f) + E_{y}(f)$ (A-4)

Furthermore, if y(t) if the response to an excitation x(t), then

$$E_{y}(f) = |H(f)|^{-2} E_{x}(f)$$
(A.5)

where H(f) is the frequency response function of the system between x(t) and y(t). The energy spectrum E(f) is computed in the same way as the power spectrum, except that a division by the analysis time T is not required and the error problems are slightly different. Hence, conventional power spectrum computational procedures and analyzers can be used to calculate E(f) with only minor changes in the calibration procedure

The primary advantage of the energy spectrum as a descriptor of mechanical shock environments lies in the implications of Equations (A-4) and (A-5). The principal disadvantage is that the energy spectrum, like the power spectrum of a stationary vibration, does not yield direct interpretations of the damage potential of the transient. Additional information and analytical effort are needed to translate such spectral representations into a damage potential.<sup>3</sup> On the other hand, the energy spectrum does provide a convenient criterion for simulating shocks in the laboratory.

# SHOCK RESPONSE SPECTRA

Unlike the energy spectrum, which evolves basically from analytical concepts, the shock response spectrum is an engineering function designed to describe transient events in terms directly related to the damaging potential of such events. The concept of the shock spectrum is thoroughly developed in the engineering literature, and has been widely applied to aerospace mechanical shock problems.<sup>4,5</sup> Furthermore, it is commonly used as a criterion for the mechanical shock testing of aerospace hardware.<sup>6</sup>

In general terms, the shock spectrum of an acceleration transient x(t) is defined as the maximum response of a damped spring-mounted mass when x(t) is applied at its foundation. The response is calculated as a function of the natural frequency of the spring mass system. The resulting spectrum of peak response values may be defined in terms of any response parameter of interest. In practice, relative displacement (proportional to stress) is widely used to describe mechanical shocks for load-carrying structures, whereas absolute acceleration is more common for equipment packages. In some cases the shock spectrum is presented in terms of psuedo-velocity parameter, which is defined as  $2 \pi f S_d(f)$ , where  $S_d(f)$  is the relative displacement shock spectrum. In any case, the interpretation of the shock spectrum is as follows: Given any system of interest that behaves like a

<sup>3</sup>S. H. Crandall, and W. D. Mark. *Random Vibration in Mechanical Systems*. New York, Academic Press, 1963. Pp. 103-25.

4S. Rubin. "Concepts — Shock Data Analysis," Shock and Vibration Handbook, ed. by C. M. Harris and C. E. Crede, New York, McGraw Hill, 1961. Chap. 23.

<sup>5</sup>DOD Shock and Vibration Information Center. Principles and Techniques of Shock Data Analysis, by R. D. Kelly and G. Richman, Washington, D.C., SVIC, 1969. (SVM-5.) Pp. 61-79.

<sup>6</sup>Goddard Space Flight Center. General Environmental Test Specifications for Spacecraft and Components. Beltsville, Md., GSFC, 1969. (S-320-G-1.)

linear oscillator, the shock spectrum directly defines the maximum strain, acceleration, or other failure-related parameter value that the system will experience when subjecte<sup>1</sup> to the shock, depending only upon its natural frequency and damping.

One may define and measure more specific types of shock spectra depending upon the application. For example, the maximum response of the hypothetical spring mass system in the positive and negative directions may be separated to arrive at the positive shock spectrum and the negative shock spectrum. Furthermore, the maximum response that occurs during the application of the input transient might be distinguished from the maximum response after the mput transient has terminated. The frequency plot of maximum response during the transient is called the primary shock spectrum, and the plot of maximum response after the transient is called the residual shock spectrum. The plot of maximum values independent of their direction or time of occurrence is often called the maximax shock spectrum.

A key parameter in any type of shock spectrum presentation is the damping ratio assumed for the hypothetical spring mass system. If the shock spectrum concept is to be meaningful, this damping ratio obviously should be similar to the actual damping of the physical system which must survive the shock. For single pulse (nonoscillatory) transients, the damping ratio does not have a major impact on the resulting shock spectrum. However, for oscillatory transients, the damping ratio has a profound impact on the resulting spectrum.

The principal advantage of the shock spectrum lies in its direct interpretation in terms of a failure criterion. It also provides a convenient criterion for simulating shocks in the laboratory. Its disadvantages are associated with the critical assumptions involved in its application, in particular, the assumption that the system of interest will behave as a linear spring mass system with a known damping ratio. For the case of transients that are oscillatory in character, the assumed damping ratio is particularly critical. The Harpoon missile ejection shock data of interest in this study are of the type where the assumed damping ratio significantly influences the resulting shock spectra calculations. To help circumvent this problem, the shock spectra were computed using two damping ratios, 5% (Q = 10) and 0.5% (Q = 100). It is believed that these two damping ratios will bound the actual damping of most structural members and components of the missile.

#### COMPARISONS OF ENERGY AND SHOCK SPECTRA

Energy and shock spectra evolve from totally different concepts and are generally interpreted in different ways. However, the two functions do have one direct analytical relationship. Specifically, given an acceleration time history x(t), the residual shock spectrum of acceleration values computed using zero damping is given by

$$S_{X}(f)_{r} = 2\pi f \left[ E_{X}(f) \right]^{\frac{1}{2}}$$
 (A-6)

where  $E_{X}(f)$  is the energy spectrum of  $x(t)^{4}$ . It is important to note the frequency dependence in Equation (A-6); i.e., shock spectrum values increase relative to the energy spectrum values as frequency increases. Although this relationship is rigorously correct only for undamped residual shock spectra, there is a tendency in practice for damped maximax shock spectra to display a similar frequency dependence. The reason for this is obvious if one remembers that the shock spectrum is related to the response of a linear oscillator excited by the transient. The half-power point bandwidth of a linear oscillator with fixed damping factor Q is approximately proportional to its natural frequency.  $f_{n}$ , i.e.,  $B = f_{n}/Q$ . Hence, the bandwidth of the energy that the oscillator will respond to increases with frequency. Given an acceleration transient with an energy spectrum  $E_{X}(f)$ , it follows that the acceleration shock spectrum  $S_{X}(f)$  will increase relative to  $E_{X}(f)$  as f increases.

# INITIAL DISTRIBUTION

27 Naval Air Systems Command

·\* 65 \* . .

```
AIR-03P(1)
      AIR-30212(2)
      AIR-320(1)
      AIR-330D(1)
      AIR-350(1)
      AIR-5108C(1)
      AIR-5108C1 (1)
     AIR-5109B(1)
     AIR-5109B1 (1)
      AIR-5109E(5)
     AIR-5205(1)
     AIR-53232(1)
     AIR-53321(1)
     AIR-5336(1)
     AIR-5351 (1)
     AIR-5366(1)
     AIR-53662(1)
     AIR-53663(1)
     AIR-53664 (1)
     AIR-954 (2)
     PMA-258(1)
2 Chief of Naval Operations
     OP-703(1)
     OP-722C(1)
1 Chief of Naval Material (MAT-0325B)
6 Naval Sea Systems Command
     SEA-0331(1)
     SEA-0332(1)
     SEA-09G32(2)
     SEA-55211B(1)
     SEA-93(1)
3 Naval Air Development Center, Johnsville
     Code AEHE, F. Smith (1)
     Code AM, J. Seidel (1)
     Technical Library (1)
2 Naval Air Engineering Center, Lakehurst (WESCO, C. R. Osmanski)
2 Naval Avionics Facility, Indianapolis
     Code ESS, H. Stone (1)
     Technical Library (1)
3 Naval Ordnance Station, Indian Head
     Code 3012A1, B. Boudreaux (1)
     Code REBO(1)
     Technical Library (1)
2 Naval Postgraduate School, Monterey
     R. E. Ball (1)
```

38

rituali, Matani in this

L.V. Schmidt (1) 1 Naval Research Liboratory (Technical Library) 1 Naval Ship Missile Systems Engineering Station, Port Hueneme 4 Naval Surface Weapons Center, Dahlgren Laboratory, Dahlgren Code FVR, R. Hudson (1) Code TI, J. E. Hurtt (1) Code WXA, S. H. McEiroy (1) Technical Library (1) 3 Naval Surface Weapons Center, White Oak Jack Gott (1) Vic Yarow (1) Technical Library (1) 1 Naval Undersea Conter. San Diego 2 Naval Weapons Support Center, Crane (ode RD(1) Cal Austin (1) 9 Pacific Missile Test Center, Point Mugu Code 5330 (1) Code 5333, C. V. Ryden (1) Code 5334. Bob Cannon (1) Code 5700, H. Harrison (1) A A. Anderson (1) F J Brennan (1) Technical Library (1) 2 Office Chief of Research and Development Col A. Quinnelly (1) Technical Library (1) 2 Army Materiel Development & Readiness Command AMCRD-TV. Navakin (1) Technical Library (1) 1 Aberdeen Proving Ground (Technical Library) 4 Army Engineer Topographic Laboratories, Fort Belvoir GS-EC, Brierly (3) Technical Library (1) 2 Frankford Arsenal K-3400, D. Askin (1) Technical Library (1) 1 Harry Diamond Laboratories (Technical Library) 1 Picatinny Arsenal (Technical Library) 1 Headquarters, U.S. Air Force (Debuty Chief of Staff. Research and Development) 1 Air Force Armament Laboratory, Eglin Air Force Base 5 Air Force Rocket Propulsion Laboratory, Edwards Air Force Base Plans and Program Office (1) RPMCP(1) L. Meyer (1) Technical Library (1) 2 Armament Development and Test Center, Eglin Air Force Base R. Greene (1) Technical Library (1)

2 Directorate of Armament Development, Eglin Air Force Base Technical Library (1) 3 Wright-Patterson Air Force Base AFAL, AFSC(1) Charles Thomas (1) William Savage (1) 12 Defense Documentation Center 2 Applied Physics Laboratory, JHU, Laurel, MD Bill Caywood (1) 1 Bird Engineering Research Associate, Inc., Vienna, VA 1 Convair Division of General Dynamics. San Diego, CA (R. G. Huntington) 4 General Dynamics Corporation, Pomona Division, Pomona, CA Code 6-42, H. B. Godwin (1) Code 8-101, R. J. Carey (1) D. Underhill (1) Technical Library (1) 1 Honeywell, Inc., Systems and Reasearch Division, Minneapolis, MN (J. D. Brennan) 1 Hughes Aircraft Company, Canoga Park, CA (R. J. Oedy) 1 Lockheed-California Company, Burbank, CA (Code 01-10, W. Hawkins) 4 Lockheed Propulsion Company, Redlands, CA C. J. Barr (1) W. A. Stevenson (1) Engineering Research, John H. Bonin (1) Technical Library (1) 11 McDonnell Douglas Corporation, St. Louis, MO J. H. Bell (9) J. L. Gubser (1) Technical Library (1) 2 Martin Company, Denver, CO F. A. Thompson (1) Technical Library (1) 1 Raytheon Company, Waltham, MA (D. H. Sanders) 2 Rocketdyne, McGregor, TX , Sparrow/Shrike Project Manager (1) Technical Library (1) 2 Sandia Corporation, Albuquerque, NM J. Foley (1) Technical Library (1) 1 Sandia Corporation, Livermore, CA (Technical Library) 2 Teledyne, CAE, Toledo, OH Harpoon Office (1) Technical Library (1) 1 Texas Instruments, Inc., Dallas, TX (Missile & Ordnance Division, J. E. Tepera) 3 The Martin Company, Orlando, FL Code 143, J. A. Roy (1) P. G. Hahn (1) Technical Library (1) 1 Thiokol Chemical Corporation, Wasatch Division, Brigham City, UT (R. Brown) 2 Value Engineering Company, Alexandria, VA John Toomey (1) NWC 805 805 (3/77) 208 Technical Library (1)

... . .... •