

AD A 043912

12

Technical Report

R 855



Sponsored by


NAVAL FACILITIES ENGINEERING COMMAND

July 1977

CIVIL ENGINEERING LABORATORY

Naval Construction Battalion Center

Port Hueneme, California 93043



EXPENDABLE DOPPLER PENETROMETER:
A PERFORMANCE EVALUATION

by R. M. Beard

SEP 9 1977
D

DDC FILE COPY

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER TR-855	2. GOVT ACCESSION NO. DN687021	3. REPORT'S CATALOG NUMBER <i>rept.</i>
4. TITLE (and Subtitle) EXPENDABLE DOPPLER PENETROMETER: A PERFORMANCE EVALUATION.	5. TYPE OF REPORT & PERIOD COVERED Final Jan 1973 - Oct 1976	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) R. M. Beard	8. CONTRACT OR GRANT NUMBER(s) F52556	9. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 627951N: 62751N YF5255699901.106
10. PERFORMING ORGANIZATION NAME AND ADDRESS CIVIL ENGINEERING LABORATORY Naval Construction Battalion Center Port Hueneme, California 93041	11. CONTROLLING OFFICE NAME AND ADDRESS Naval Facilities Engineering Command Alexandria, Virginia 22332	12. REPORT DATE July 1977
13. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) CEL-TR-855	14. SECURITY CLASS. (of this report) Unclassified	15. DECLASSIFICATION DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (for the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Soil testing, shear strength, seafloor soils, penetrometer, Doppler principle, core samples, coring tool.		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) An expendable penetrometer using the Doppler principle has been developed to expediently test seafloor soils to a depth of 9m (30 ft) at water depths to 6,000m (20,000 ft). The velocity of the penetrometer is measured as it penetrates seafloor soils. From the velocity record, soil penetrability and an estimate of the undrained shear strength profile can be calculated. The penetrometer has a mass of 173 kg (12 slugs), is 2.9m (9.5 ft) long, is 90mm (3.5 in.) in diameter, and is easily deployed from a ship. This		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

Unclassified

continued

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

391 111

1B

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

20. (Continued)

report presents data from 11 tests at four locations off the southern California coast. Undrained shear strength profiles determined from penetrometer data are compared to other types of in-situ data and core data. It is concluded that the expendable Doppler penetrometer is reliable and simple to use and that reasonable estimates ($\pm 30\%$ of actual values) of undrained shear strength profiles can be obtained even though the analyzed phenomenon is complex. This tool will be of particular value in surveying potential embedment anchor or foundation locations and can, for some cases, provide information sufficient for design purposes.

ACCESSION NO.	
NTIS	White Section <input checked="" type="checkbox"/>
DDC	Blue Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	AVAIL. CODES OR SPECIAL
A	

Library Card

Civil Engineering Laboratory
EXPENDABLE DOPPLER PENETROMETER: A
PERFORMANCE EVALUATION (Final), by R. M. Beard
TR-855 19 pp illus July 1977 Unclassified

1. Soil sampling 2. Coring tool 1. YF52.556.999.01.106

An expendable penetrometer using the Doppler principle has been developed to expediently test seafloor soils to a depth of 9m (30 ft) at water depths to 6,000m (20,000 ft). The velocity of the penetrometer is measured as it penetrates seafloor soils. From the velocity record, soil penetrability and an estimate of the undrained shear strength profile can be calculated. The penetrometer has a mass of 173 kg (12 slugs), is 2.9m (9.5 ft) long, is 90mm (3.5 in.) in diameter, and is easily deployed from a ship. This report presents data from 11 tests at four locations off the southern California coast. Undrained shear strength profiles determined from penetrometer data are compared to other types of in-situ data and core data. It is concluded that the expendable Doppler penetrometer is reliable and simple to use and that reasonable estimates ($\pm 30\%$ of actual values) of undrained shear strength profiles can be obtained even though the analyzed phenomenon is complex. This tool will be of particular value in surveying potential embedment anchor or foundation locations and can, for some cases, provide information sufficient for design purposes.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

CONTENTS

	page
INTRODUCTION	1
Background	1
Approach and Scope	1
DESCRIPTION OF TEST APPARATUS	2
Penetrometer	2
Hydrophone	2
Receiver	2
THEORY OF OPERATION	4
DETERMINING UNDRAINED SHEAR STRENGTH	4
TEST PROGRAM AND PROCEDURES	6
REST RESULTS	6
180-Meter Site	9
370-Meter Site	10
1700-Meter Site	10
880-Meter Site	12
DISCUSSION	12
CONCLUSIONS	14
RECOMMENDATIONS	14
EPILOGUE	14
ACKNOWLEDGMENTS	15
REFERENCES	15

INTRODUCTION

This report describes an expendable dynamic penetrometer and its associated ship-board electronics. An evaluation of the system's ability to determine seafloor penetrability and undrained shear strength is presented. Seafloor shear strength information derived from penetrometer data is compared to the best in-situ or laboratory shear strength data available. The overall objective in developing the dynamic penetrometer was to provide an expedient means for determining seafloor characteristics and properties relevant to site selection for design of direct embedment anchors.

Background

Installing embedment anchors requires knowledge about seafloor sediment strength, penetrability, thickness, and the occurrence of anomalous conditions (e.g., detritus and small submarine lava flows). These data must cover sediment depths to 9m (30 ft) plus at-water depths to 6000m (20,000 ft). The more data available on these factors, the more likely a successful installation will be made. The mainstays of site surveys to provide the required information are soil coring and acoustic profiling. Both are necessary. However, coring is time consuming, limited to fair weather, and, therefore, costly. Acoustic profiling tends to average the characteristics of large seafloor areas and does not measure engineering properties. To increase the flexibility and success of conducting seafloor surveys with these apparatuses a tool was needed that would decrease coring requirements and allow for better interpretation of acoustic profiling records. An expendable penetrometer could fulfill these requirements.

Penetrometers are expedient, usable in rough weather, and indirectly measure what is probably the most significant engineering property for designing embedment anchors—undrained shear strength. This property is also used when analyz-

ing bearing capacity, breakout, and penetration problems. Penetrometers can be used to estimate this key parameter in conjunction with widely spaced cores, or independently when coring is not feasible because of weather or sea conditions. Penetrometers can also help interpret acoustic profile records where core data are either not available or remote by providing a link to undrained shear strength.

In the application of penetrometers to the design of direct embedment anchors, several factors must be recognized. First, a penetrometer will provide data (undrained shear strength) that are suitable only for estimating short-term holding capacity in cohesive soils. Fortunately, most deep ocean soils are near normally consolidated cohesive deposits in which the short-term holding capacity will govern the design because it is less than the long-term holding capacity. Second, the estimates of short-term capacity will only be as good as the undrained shear strength obtained. Penetrometers are not a way of obtaining ideal shear strength data, but they can provide data accurate enough for selecting fluke size and for making tolerable estimates of penetration and short-term holding capacity.

Sandia Laboratories began development of a seafloor penetrometer in 1970 (Colp et al., 1975), and Scott (1970) reported on a mechanical accelerometer for use with an ocean penetrometer. Delco Electronics developed an expendable soil bearing meter for use in the ocean that was similar to an expendable bathythermograph (Robertson, 1965). None of these devices was found suitable for the requirements outlined above. Their sizes are too small to obtain the required 9m (30 ft) of penetration, and they are not operable to a water depth of 6,000m (20,000 ft). Therefore, a new approach was necessary to obtain the performance required.

Approach and Scope

An expendable penetrometer utilizing the Doppler principle of a sound source moving in relation to the

receiver of the sound emitted was developed to provide the desired penetrometer capability (Thompson, 1977). In addition, a ship-board receiver and hydrophone were developed to monitor the Doppler data from the penetrometer and provide an analog of the velocity of the penetrometer as it embeds into the seafloor. With these data can be recovered at water depths to 6,000m (20,000 ft) with 9m (30 ft) of sediment penetration.

To verify the feasibility of a Doppler penetrometer and to show that satisfactory data can be obtained with it, tests were conducted at four sites off the southern California coast. The reduced data were then compared to the best in-situ or core data available. A performance evaluation of the penetrometer system based on the at-sea work and the data comparisons is presented.

DESCRIPTION OF TEST APPARATUS

The expendable Doppler penetrometer system has the following components: (1) a penetrometer with a constant frequency sound source mounted on it, (2) a hydrophone with a preamplifier, and (3) a receiver for processing the incoming data.

Penetrometer

The penetrometer (Figure 1) has two components: (1) a heavy, hydrodynamically shaped vehicle for speeding the penetrometer to the seafloor and for providing the impetus to penetrate the soil, and (2) an accurately controlled sound source for data measurement.

The vehicle is a lead-filled 2.45-m (8-ft) long, 90-mm (3½-in.) diameter pipe. A steel hemisphere is welded to the nose of the vehicle to provide an efficient hydrodynamic shape. The upper end is capped with a steel plate and center stud for attaching the sound source. Three equally spaced fins at the upper end provide stability for the falling penetrometer. The vehicle has a mass of 161 kg (11 slugs).

The sound source (Figure 2) consists of an acoustic projector, a power supply, electronic circuitry, and a protective pressure-resistant housing. It has a mass of 12 kg (1 slug), is 0.46m (18 in.) long, and is 90 mm (3½ in.) in diameter. The unit is screwed onto

the stud provided at the upper end of the penetrometer vehicle. The acoustic output of the sound source is about 89 db above 0.1 Pa (1 μ bar) at 1m, and this output level can be sustained for about 10 minutes. The frequency is 12,000 Hz \pm 1 Hz. Immersion in water starts the sound source.

When the vehicle and the sound source are assembled, the penetrometer is a 173-kg (12-slug), 2.90-m (9½-ft) long, 90-mm (3½-in.) diameter package. The penetrometer attains a free-fall terminal velocity of 27 to 29 m/s (90 to 95 fps) and penetrates about 9m (30 ft) into soft, normally consolidated seafloor clays.

Hydrophone

The hydrophone used to pick up the signal from the penetrometer can be lowered 30m (100 ft) below the sea surface to reduce ship, wave, and other surface-generated noise. It has a plug-in bandpass preamplifier and an overall sensitivity of -65 db referenced to 1V per 0.1 Pa (1 μ bar) of pressure. Other features include a 0.33-rad (19-deg) beam pattern at 12,000 Hz, and a front-to-back ratio of 20 db. Absolute level calibration facilities are also provided.

Receiver

The receiver is used to process the penetrometer data signal, which is Doppler shifted, that is picked up with the hydrophone. The hard-limiting receiver electronics consists of various bandpass filters and calibration crystals, a frequency converter, and a frequency discriminator. A self-contained sealed lead acid battery pack or line power can be used to operate the receiver. Numerous outputs are provided on the receiver, including raw frequency signal, converted frequency signal, and a voltage analog of the penetrometer's velocity. Time output is also provided with a 1-ms tick and a unique tick every 10 ms. The receiver components are housed in a splashproof aluminum case with appropriate control switches and plug-in jacks.

The high-gain hard limiter takes the incoming signal and amplifies it to saturation levels, thereby maximizing the low-end signal level that can be processed. The frequency converter then shifts the




Figure 1. Expendable Doppler penetrometer.




Figure 2. Sound source for penetrometer.

12,000-Hz signal down to a standard instrumentation frequency of about 3,900 Hz. This magnifies the Doppler shift as a percentage of the total frequency. Next the signal is processed by a frequency-modulated discriminator into a direct current voltage. The amplitude of the direct current voltage is the analog of the Doppler-shifted signal and is readily plotted or recorded.

THEORY OF OPERATION

The Doppler principle can be stated as

$$f' = f \frac{v}{v + v_s} \quad (1)$$

where f' = frequency received

f = frequency transmitted

v = velocity of sound of the immersion medium

v_s = velocity of source (penetrometer)

The 12,000-Hz signal emitted by the penetrometer is received by the hydrophone as a Doppler-shifted frequency and is processed by the receiver to obtain an analog of the penetrometer's kinematics. At the terminal velocity of the penetrometer, which is about 28 m/s (92 fps), and its operating frequency of 12,000 Hz, an 11,775-Hz signal will be received by the hydrophone if one assumes a seawater sound velocity of 1,463 m/s (4,800 fps). This is a frequency shift of 225 Hz or 1.8% of the 12,000 Hz signal of the penetrometer. In the range of velocities from 0 to 30 m/s (0 to 100 fps), the frequency shift is nearly linear at 8.04 Hz/mps of penetrometer velocity. The changes in the received sound are then a linear analog of the kinematics of the penetrometer. This frequency analog can be recorded and processed as is any frequency-modulated telemetry signal.

The required processing is accomplished in the receiver, and the analog signal is then recorded versus time. This recording can then be integrated to determine penetration depth and computer-reduced to estimate undrained shear strength versus depth.

DETERMINING UNDRAINED SHEAR STRENGTH

The soil failure around an advancing penetrometer is complex and difficult to analyze. Consideration of frontal bearing resistance, side resistance, buoyancy, "fluid" drag forces, and added mass need to be made. Analyzing the body motions of a penetrometer produces an undrained shear strength profile of the penetrated soil. This property is probably the most important soil property for anchor and foundation design in seafloor soil mechanics. The derived shear strength data will be more reliable for cohesive seafloors than for noncohesive seafloors. This is because partial drainage and other confounding factors in noncohesive soils multiply the difficulties of analysis.

The method used to analyze the data is that presented by True (1975). His method treats all the factors that were previously mentioned. The basic formulation is:

$$\text{Net Force} = F_D + W' - F_{BE} - F_{AD} - F_H \quad (2)$$

where F_D = externally applied driving force

W' = buoyant weight of penetrometer

F_{BE} = bearing pressure force

F_{AD} = side adhesion force

F_H = "fluid" drag force

The net force is the force causing the penetrator and any added mass to decelerate. The data reported herein gave best correlations when the added mass was ignored. This is a reasonable action based on added mass factors found in fluids for slender penetrators (Wendel, 1950). For the Doppler penetrometer, when treating the soil as a fluid, only about 1.5 kg (0.1 slug) of added mass are involved compared to a penetrometer mass of about 173 kg (12 slugs).

The soil shear strength terms have been formulated by True as:

$$F_{BE} = S_t (S_u N_c A_f) \text{ and } F_{AD} = S_t \left(\frac{S_u \delta A_s}{S_t} \right)$$

ere S_e = soil strength strain rate factor

S_u = soil undrained shear strength

N_c = bearing capacity factor

A_f = penetrometer frontal area

δ = side adhesion factor

A_s = penetrometer side area

S_t = soil sensitivity

Undrained shear strength in cohesive soils is a function of strain rate, hence the application of a strain rate factor. However, the magnitude of the factor is in doubt. True recommends a maximum factor of 4. The work of Prevost (1976, p 1253) suggests that maximum strengths should be about 1.5 times conventional strengths (factor = 1.5) at most strain levels to 10% at maximum strain rates 100 times that of conventional strength tests (or 300% per hour). The strain rates during penetration of the Doppler penetrometer are at least 10,000 times greater than those during conventional strength tests and, therefore, Prevost's maximum would not seem appropriate. Analysis of the Doppler penetrometer data reported herein suggests, based on correlation to other available strength data, that a maximum strain rate factor of 2 is more appropriate than True's maximum value of 4 or Prevost's value of 1.5.

The side adhesion term of Equation 2 includes a side adhesion factor that varies over the length of the penetrator. This factor accounts for separation or reduced lateral pressure between the soil and penetrator. This variable side adhesion factor caused fluctuations in the derived shear strength data. Eliminating the term eliminated the fluctuations; therefore, the term has not been used in obtaining the data presented herein.

The drag force is calculated from the standard fluid drag equation

$$F_H = \frac{1}{2} \rho C_D A_f V^2 \quad (3)$$

where ρ = fluid (soil) mass density

C_D = drag coefficient

V = penetrometer velocity

The drag coefficient is calculated from the terminal velocity of the free-falling penetrometer.

Because the penetrometer is free-falling, there is no externally applied force during penetration, and Equation 2 becomes

$$Ma = W' - S_e \left(S_u N_c A_f + \frac{S_u A_s}{S_t} \right) - \frac{1}{2} \rho C_D A_f V^2 \quad (4)$$

where M = penetrometer mass

a = penetrometer deceleration

This equation is solved on an incremental basis to find undrained shear strength profiles.

To use Equation 4 assumptions must be made for the unit weight of the soil, the sensitivity of the soil, and the sound velocity of the near-bottom water. A parametric study of these parameters was made to assess their effect on derived undrained shear strength values. The unit weight assumption required for calculating the buoyant weight of the penetrometer was found not to be critical. Deviations up to 320 kg/M³ (20 lb/ft³) caused deviations in calculated strengths of 2% or less. Assuming 1,440 and 1,760 kg/m³ (90 and 110 lb/ft³) densities for loose and dense seafloors,* respectively, will usually give errors of 1% or less. The sensitivity of the soil was found to be more critical as it affects a large force term, side adhesion. For the Doppler penetrometer, where the side area is 100 times greater than the nose area, a 50% error in estimating the sensitivity will result in about a 25% error in the estimated strength profile. Usually the sensitivity can be estimated to less than a 50% error from data available on soils of similar geology. The sound velocity estimate is required to determine the velocity of the penetrometer from the Doppler frequency

*Density judged by penetration depth.

shift. These estimates can be made from sound velocity-depth-latitude data, such as those provided by Myers et al. (1969, pp 3-7). Good estimates of the sound velocity of the soil can be made by assuming the sound velocities in soft sediments (deep penetration) are the same as the bottom water, and for stiffer sediments (shallow penetration) that they are 5% higher than the bottom water. In general this will produce errors of less than 2% in the velocity data.

TEST PROGRAM AND PROCEDURES

Initial testing of the Doppler penetrometer was conducted to verify system design and general feasibility and to proof-test components. These tests, which totaled eight were conducted in water less than 30m (100 ft) deep in a sandy seafloor. Consequently, terminal velocity was not obtained, and penetrations were typically less than 1m (3 ft). The test results were presented by Beard (1976). The sound sources for these tests were prototypes of limited acoustic output. Based on the tests it was concluded that the concept of a dynamic penetrometer using the Doppler principle to gather data was workable, and that the instrument concept could accurately describe the velocity of the penetrometer.

To evaluate the penetrometer concept more thoroughly tests were required in a variety of sediments at greater water depths. Sound sources of increased acoustic output were required to conduct these tests. Prototypes of these sound sources were procured. They were pressure-tested at the Civil Engineering Laboratory and acoustically tested at the TRANSDECK facility of the Naval Undersea Center, San Diego.

Field testing of additional units was conducted at four sites off the southern California coast to determine the quality of data that can be obtained using the Doppler penetrometer. These sites ranged in depth from 180 to 1,700m (600 to 5,600 ft). Their locations relative to the coastline and their approximate geographic coordinates are presented in Figure 3.

With the exception of the 880-Meter Site, the engineering properties of the bottom sediment at

these sites are known. Table 1 summarizes the types and quantity of data that have been obtained at each site. All of the data extend to a seafloor depth of 3m (10 ft) except for three cores that were taken at the 370-Meter Site; these are as long as 7.3m (24 ft).

Eleven expendable penetrometer tests were conducted: two each at the 880-Meter Site and three each at the other sites. Table 2 presents a summary of the tests conducted and a general soil classification of each test site.


The general test procedure at each site was the same. The ship was brought on station using LORAC navigation. The hydrophone was placed in the water and lowered below the ship suspended on a bungee cord from a spar buoy. Calibrations were made at frequencies representing zero and about one-half terminal velocity. The sound source was checked for a watertight seal and test-started. The assembled penetrometer was placed over the ship's side and cast free. Raw frequency data, converter frequency data, a frequency shift analog, and time were recorded on magnetic tape. The analog data and time were also recorded on paper.

TEST RESULTS

The prototype sound sources were successfully pressure-vessel-tested to an equivalent water depth of 6,000m (20,000 ft). At TRANSDECK it was learned that the source output was about 89 db above 0.1 Pa (1 μ bar) at 1m, and that this output level can be maintained for over 10 minutes.

About 15 minutes were required to perform an at-sea test that included placing the hydrophone in the water suspended from the spar buoy, making calibrations, placing the penetrometer over the side, recording data as the penetrometer fell, and recovering the hydrophone. Sea conditions were usually good, with a maximum sea state of 3 being experienced when testing at the 880-Meter Site. No difficulties were experienced testing at this sea state.

The field data acquired with the penetrometer were reduced to determine penetration depths and undrained shear strength profiles. Available sound velocity data near each site were used to determine the appropriate sound velocities for calculating a



Designation Site	Location	Latitude (N)	Longitude (W)
180-Meter Site	Santa Barbara Channel	34° 17' 12"	119° 42' 47"
370-Meter Site	Santa Barbara Channel	34° 16' 30"	119° 50' 58"
1700-Meter Site	Santa Cruz Basin	33° 51' 00"	119° 41' 00"
880-Meter Site	Santa Monica Basin	33° 43' 30"	119° 05' 00"

Figure 3. Location of test sites.

**Table 1. Types and Quantity of Engineering Property
Data Available at Each Test Site**

Site	No. of Cores	No. of In-Situ Vane Shear	No. of In-Situ Cone Penetrometer
180-Meter	5	3	5
370-Meter	6	1	3
1700-Meter	1	—	2
880-Meter	—	—	—

Table 2. Penetrometer Testing Program and General Conditions

Test Designation	Site	Soil Characteristics
180-P1 180-P2 180-P3	180-Meter	A nonuniform deposit varying from a sandy, clayey silt (ML) above 1m (3 ft) to a clayey silt (ML-MH) below. Soil appears to be over-consolidated and is strong.
370-P1 370-P2 370-P3	370-Meter	A uniform plastic clayey silt (MH). Plastic limit of 41% and liquid limit of 83%. Appears typical of deep ocean sea-floor sediments.
1700-P1 1700-P2 1700-P3	1700-Meter	A silty clay (MH) with an occasional sand lens. Plastic limit of about 70% and liquid limit of about 120%.
880-P1 880-P2	880-Meter	Uncored sediment thought to be a cohesive deposit based on embedment anchor test result.

calibration velocity corresponding to the calibration frequencies. This information is presented in Table 3. Soil impact time was selected by eye as the point of initial deceleration on a deceleration-time trace. Penetration depths were calculated using the trapezoid rule to integrate the velocity-time curve from the time of impact to the time the penetrometer came to rest. Undrained shear strength profiles were determined using the method outlined in the section on calculating undrained shear strength from penetrometer data. Shear strength data for the last two depth increments of penetration for each test have been omitted because of difficulty in analyzing the data where the available soil resistance was high and the deceleration of the penetrometer was low.

180-Meter Site

Velocity versus depth data for tests conducted at the 180-Meter Site are presented in Figure 4. Penetrations were calculated to be 6.7m (22 ft), 6.4m (21 ft), and 5.8m (19 ft) for tests 180-P1, -P2, and -P3, respectively. The velocities at impact were 29.0, 29.6, and 28.3 m/s (95, 97, and 93 fps), respectively. The three shear strength profiles derived from the data are provided in Figure 5. The results compare favorably to the in-situ vane shear data, and the data from test to test seem to be repeatable. The

average vane shear data are from three tests, with little data scatter from test to test. The penetrometer impact points may have been separated by distances up to 0.8 km (0.5 mi).




Figure 4. Velocity versus depth for 180-Meter Site.

Table 3. Calibration Velocities Corresponding to Calibration Frequencies at Each Site

Site	Sound Velocity at Site		Calibration Frequency (Hz)	Calibration Velocity	
	m/s	fps		m/s	fps
180-Meter	1,490	4,890	11,876	15.6	51.1
370-Meter	1,486	4,875	11,876	15.5	50.9
1700-Meter	1,490	4,890	11,876	15.6	51.1
880-Meter	1,484	4,870	11,876	15.5	50.9




Figure 5. Undrained shear strength versus depth for 180-Meter Site.

370-Meter Site

Data for velocity versus depth of penetration are given in Figure 6 for the tests conducted at the 370-Meter Site. The respective penetrations for tests 370-P1 and -P3 were calculated to be 10.0m (33 ft) and 9.8m (32 ft). The data from test 370-P2 were not reduced because of a signal dropout part way through the penetration phase. Velocities at impact were 29.6 m/s (97 fps) and 28.3 m/s (93 fps), respectively. Figure 7 shows the calculated undrained shear strength profiles for these tests compared to

undrained shear strength data taken on three piston cores recovered from the site. The penetrometer data compare well to the core data. At depths less than 3m (10 ft) there is more scatter in the core data than in the penetrometer data. At depths greater than 4.5m (15 ft) the scatter from core to core is little, and the scatter in the penetrometer tests is equally small. However, at these depths the penetrometer data average about 30% higher than the core data. Test 370-P3 was near the core locations, but test 370-P1 was about 0.8 km (0.5 mi) away.




Figure 6. Velocity versus depth for 370-Meter Site.

1700-Meter Site

Figure 8 presents the velocity versus depth of penetration for tests conducted at the 1700-Meter Site. For tests 1700-P1, -P2, and -P3 respective penetrations were calculated to be 7.0m (23 ft),




Figure 7. Undrained shear strength versus depth for 370-Meter Site.




Figure 8. Velocity versus depth for 1700-Meter Site.

7.3m (24 ft), and 9.4m (31 ft). Velocities at impact were 26.2, 29.3, and 27.4 m/s (86, 96, and 90 fps), respectively. Undrained shear strength profiles were calculated from the test data and are presented in Figure 9. In general these tests do not compare well from one to another. However, each test location was about 1.6 km (1 mi) from the others. Only test 1700-P3 was at the location of existing core data. The penetrometer data from test 1700-P3 and the core data are compared in Figure 10; over the depth of the core the data compare fairly well. In Figure 9 note the high strength calculated at depths over 6m (20 ft) for test 1700-P2. These strengths seem reasonable when the velocity data in Figure 8 for this test are reviewed; i.e., during the last 1m (3 ft) of penetration the velocity dropped about 18 m/s (60 fps).

At this site the strength of the signal being received from each penetrometer was measured after each penetrometer was buried in the seafloor. The length of time the signal lasted was also noted. The excess signal measured was conservatively 20 db, and signals were detected for periods of 1 to 2 hours.




Figure 9. Undrained shear strength versus depth for 1700-Meter Site.

880-Meter Site

Velocity versus depth data are presented in Figure 11 for test 880-P1. The calculated penetration for this test was 6.7m (22 ft). The velocity at impact was 27.3 m/s (90 fps). On test 880-P2 the signal abruptly went from terminal to zero velocity, indicating that the penetrometer had struck something other than soil. The undrained shear strength profile calculated from test 880-P1 is presented in Figure 12. There are no data to compare these data to.

DISCUSSION

In general the expendable Doppler penetrometer performed well. Pressure vessel testing showed that the sound source pressure housing is good to a 6000m (20,000-ft) water depth. Based on the acoustic output




Figure 10. Comparison of undrained shear strength calculated from test 1700-P3 and data from core at the site.




Figure 11. Velocity versus depth for 880-Meter Site.

measured at TRANSDECK the source should be acoustically sufficient to operate to the 6000-m (20,000-ft) design depth. This was substantiated during testing in 1,700 m (5,600 ft) of water where, after the source was buried with 6m (20 ft) of sediment, more than enough signal level remained to detect the penetrometer in 6,000m (20,000 ft) of water. Operationally it has proved to be simple to use, and it takes little ship-time to perform each test. The length of time the signal can be detected was a problem, as another test could not be performed at a given site until the signal was gone (the two signals would interfere). This could be prevented by having a timing circuit that shuts the sound source off after 10 minutes or so. Deployment of the penetrometer has taken place under sea state 3 conditions with no difficulties occurring.

Of the 11 penetrometers dropped, nine provided good data for estimating undrained shear strength profiles. Of the other two, one did not penetrate due to hitting either rock or debris, and the other did provide data that can be analyzed,

but more effort will be required than on the other nine tests. The instrumentation has been shown to be dependable. This can be ascribed to the instrument's simplicity and the fact that it has to work for only a short time.

Penetrations were in the range of the design, which was 9m (30 ft) plus in soft sediments. Tests 370-P1, 370-P3, and 1700-P3, where penetrations were 10.0, 9.8, and 9.4m (33, 32, and 31 ft), respectively, confirm the penetrometer's penetration capability. Calculated penetrations are quite accurate as reported by Beard (1976). Even in soft soils little difficulty was encountered in determining the impact time, which is the most significant factor in determining depth of penetration.

The data obtained with the penetrometer look quite good; see Figures 5, 7, 9, 10, and 12. Correlation to existing undrained shear strength profiles was particularly good at the 180-Meter Site, with satisfactory results at the 370- and 1700-Meter Sites. (No correlation was made at the 880-Meter Site because there were no existing data.) These correlations were

made with the advantage of knowing the soil density, soil sensitivity, and speed of sound parameters. These would normally have to be estimated. However, parametric studies have shown that soil density has little effect on the data, and that a reasonable sound velocity estimate from a source such as Myers et al. (1969, pp 3-7) will be sufficient to limit errors to a few percent. Soil sensitivity can have a large effect, and it is the greatest potential source of error with the slender Doppler penetrometer. A 50% error in the estimated soil sensitivity will result in 25% error in the calculated undrained strength. A shorter penetrometer would result in a lower potential error. For most marine sediment types, an estimate of the soil sensitivity from existing data with less than a 50% error should be possible.




Figure 12. Undrained shear strength versus depth for 880-Meter Site.

CONCLUSIONS

1. The Doppler instrumentation system is a reliable and simple method for monitoring the motion of a free-falling penetrometer. The system described herein is capable of operating to water depths of 6,000m (20,000 ft).
2. The performance of the Doppler penetrometer is sufficient to meet its objective as it will provide data to 9-m (30-ft) soil depths.
3. Undrained shear strengths calculated from Doppler penetrometer data can be reasonable (+30% or less of actual values) even though the penetration phenomenon is complex.
4. Most factors affecting the Doppler signal or the data analysis either lead to small errors in or can be reasonably estimated for calculating the undrained shear strength. This is not true of the soil sensitivity. It must be estimated with care as significant errors (25%) can be induced by a 50% error in soil sensitivity.
5. The expendable Doppler penetrometer is a simple, reliable, and expedient tool for investigating the strength of seafloor deposits.

RECOMMENDATIONS

1. Future penetrometer sound sources should include a timing circuit to shut themselves off after about 10 minutes of operation. They should also have the signal output reduced by about 20 db from the present level to save money on the cost of the projector. This signal strength reduction is possible when the penetrometer is used in conjunction with a hydrophone receiver comparable to the system described in this report.
2. Continued performance evaluation should be made in a range of seafloor sediment types.

EPILOGUE

The expendable Doppler penetrometer has been successfully tested at a water depth of 5430m (17,800 ft). Penetration into a pelagic clay exceeded 8m (26 ft). Excess signal levels measured with the sound source buried 5m (16 ft) were about 20 db.

ACKNOWLEDGMENTS

The author acknowledges the help of Messrs. D. G. True and H. J. Lee who in many discussions gave insight to analyzing the data. A special acknowledgment is in order for Mr. J. R. Thompson. He conceived and developed the Doppler instrumentation system that was the key to obtaining a rapidly deployable, expendable penetrometer. Messrs. True, Lee, and Thompson are employees of the Civil Engineering Laboratory.

REFERENCES

- Colp, J. L., W. N. Caudle, and C. L. Schuster (1975). Penetrometer system for measuring in-situ properties of marine sediments, Ocean 75, combined meeting of 1975 IEEE Conference on Engineering in the Ocean Environment and Eleventh Annual Meeting of the Marine Technology Society, Institute of Electrical and Electronic Engineers, Inc. New York, N.Y., Sep 1975, pp 405-411.
- Myers, J.J., C.H. Holm, and R. F. Mcallister (1969). Handbook of Ocean and Underwater Engineering. McGraw-Hill, New York, N.Y.
- Prevost, J. H., (1976). Undrained stress-strain-time behavior of clays, Proceeding of the American Society of Civil Engineers, Journal of the Geotechnical Engineering Division. New York, N.Y., vol. 102, no. GT12, Dec 1976, pp 1245-1259.
- Robertson, R.M., (1965). Expendable instrumentation, in Marine Sciences Instrumentation, W. C. Knopf, and H. A. Cook, editors, Plenum Press, New York, N.Y. vol. 3.
- Scott, R.F., (1970). In-place ocean soil strength by accelerometer, Proceedings of the American Society of Civil Engineers, Journal of the Soil Mechanics and Foundations Division. New York, N.Y., vol. 96, no. SMI, Jan 1970, pp 199-211.
- True, D.G., (1975). Penetration of projectiles into seafloor soils. Technical Report R-822, Civil Engineering Laboratory, Port Hueneme, Calif., May 1975.
- Beard, R.M., (1976). Expendable Doppler Penetrometer: Interim Report. Technical Note N-1435, Civil Engineering Laboratory, Port Hueneme, Calif., Apr 1976.
- Thompson, J.R., (1977). Method of determining the physical characteristics of a seafloor, U. S. Patent 4,007, 633, Feb 15.
- Wendel, K., (1950). Hydrodynamic masses and hydrodynamic moments of inertia. Translated by E. N. Labouvie and A. Borden, David Taylor Model Basin, Translation 260, Jul 1956.

DISTRIBUTION LIST

ARMY BMDSC-RE (H. McClellan) Huntsville AL
 ARMY COASTAL ENGR RSCH CEN Fort Belvoir VA; R. Jachowski, Fort Belvoir VA
 ARMY CORPS OF ENGINEERS Seattle Dist. Library, Seattle WA
 ARMY CRREL A. Kovacs, Hanover NH
 ARMY ENG WATERWAYS EXP STA Library, Vicksburg MS
 ARMY ENGR DIST. Library, Portland OR
 ARMY MOBIL EQUIP R&D COM Code DRXFB-MR Fort Belvoir VA
 ASST SECRETARY OF THE NAVY Spec. Assist Energy (P. Waterman), Washington DC; Spec. Assist Submarines, Washington DC
 BUREAU OF RECLAMATION Code 1512 (C. Selander) Denver CO; MC 1541 (J. P. Bara), Denver CO
 CINCANT Civil Engr. Supp. Plans. Ofc Norfolk, VA
 CNM Code 03462, Washington DC; Code 043 Washington DC; NMAT 081246 (Dieterle) Wash, DC
 CNO Code NOP-964, Washington DC; Code OP 323, Washington DC; Code OP 405, Washington DC; Code OP 414, Washington DC; Code OP 97 Washington DC; Code OP 987 Washington DC; Code OPNAV 09B24; Code OPNAV 22, Wash DC; Code OPNAV 23, Wash DC; OP987P4 (B. Petrie), Pentagon
 DEFENSE DOCUMENTATION CTR Alexandria, VA
 DEFENSE INTELLIGENCE AGENCY Dir., Washington DC
 DINSRDC Anna Lab (Code 1175) Annapolis MD
 ENERGY R&D ADMIN. Dr. Cohen
 EMILANT CEC Offr, Norfolk VA
 LANTNAVFACENGCOM CONTRACTS Roicc, Keflavik
 NAS PW (J. Maguire), Corpus Christi TX
 NATL OCEAN AND ATMDS. ADMIN. Libraries Div.-D823, Silver Spring MD
 NAVACT PWO, London UK
 NAVAL FACILITY PWO, Barbados
 NAVCOASTSYSLAB CO, Panama City FL; Code 710.5 (J. Mittleman) Panama City, FL; Code 710.5 (J. Quirk) Panama City, FL; Library Panama City, FL
 NAVCONSTRACEN CO (CDR C.L. Neugent), Port Hueneme, CA
 NAVELXSYSCOM Code PME-124-61, Washington DC
 NAVFODFAC Code 605, Indian Head MD
 NAVFACENGCOM CDR L. K. Donovan, Alexandria VA; Code 043 Alexandria, VA; Code 044 Alexandria, VA; Code 0451 Alexandria, VA; Code 0453 (D. Potter) Alexandria, VA; Code 0453C, Alexandria, VA; Code 0454B Alexandria, VA; Code 04B3 Alexandria, VA; Code 04B5 Alexandria, VA; Code 06, Alexandria VA; Code 101 Alexandria, VA; Code 10133 (J. Leimanis) Alexandria, VA; Code 1023 (T. Stevens); Code 104 Alexandria, VA; P W Brewer; PC-22 (E. Spencer) Alexandria, VA; PL-2 Ponce P.R. Alexandria, VA
 NAVFACENGCOM - CHES DIV. Code 402 (R. Morony) Wash, DC; Code 405 Wash, DC; Code FPO-1 (C. Bodey) Wash, DC; Code FPO-1 (Ottisen) Wash, DC; Code FPO-1C2 Wash, DC; Code FPO-1P4 (Gregory); Code FPO-1SP (Dr. Lewis) Wash, DC; Code FPO-1SP13 (T F Sullivan) Wash, DC; Code FPO-1P12 (Mr. Scola), Washington DC
 NAVFACENGCOM - LANT DIV. RDT&ELO 09P2, Norfolk VA
 NAVFACENGCOM - NORTH DIV. (Boretsky); (Boretsky) Philadelphia, PA; Code 09P (LCDR A.J. Stewart); Code 1028, RDT&ELO, Philadelphia PA; Design Div. (R. Masino), Philadelphia PA
 NAVFACENGCOM - PAC DIV. Code 402, RDT&E, Pearl Harbor HI; Commander, Pearl Harbor, HI
 NAVFACENGCOM - SOUTH DIV. Code 90, RDT&ELO, Charleston SC
 NAVFACENGCOM - WEST DIV. Code 04B; Code 2011; 09P/20
 NAVFORCARIB Commander (N42), Puerto Rico
 NAVHOSP LT R. Elsbernd, Puerto Rico
 NAVOCEANO Code 1600 Wash, DC; Code 3408 (J. Kravitz) Bay St. Louis
 NAVOCEANSYSCEN CODE 4099 (E. Hamilton), San Diego CA; Code 3400 San Diego CA; Code 409 (D. G. Moore), San Diego CA; Code 52 (H. Talkington) San Diego CA; Code 6565 (Tech. Lib.), San Diego CA
 NAVPGSCOL Code 2124 (Library), Monterey CA; Code 61WL (O. Wilson) Monterey CA; D. Leipper, Monterey CA; E. Thornton, Monterey CA; LCDR K.C. Kelley Monterey CA
 NAVPHIBASE C O ACB ONE San Diego CA; CO, ACB 2 Norfolk, VA; COMNAVBEACHGRU TWO Norfolk VA; Code 33T, Norfolk VA; OIC, UCT ONE Norfolk, Va; UCT 1 (MacDougal) Norfolk, VA
 NAVSCOLCECOPF C35 Port Hueneme, CA
 NAVSEASYSYSCOM Code SEA OOC Washington, DC
 NAVSHIPYD Code 202.4, Long Beach CA; Code 440.4, Charleston SC; PWD (LT N.B. Hall), Long Beach CA

NAVSTA CO Naval Station, Mayport FL; CO Roosevelt Roads P.R.; PWD (LTJG P.M. Motodlenich), Puerto Rico;
 PWD Engr. Div., Puerto Rico; PWO Midway Island; PWO, Keflavik Iceland; PWO, Mayport FL; PWO, Puerto
 Rico; SCE, Subic Bay, R.P.; Utilities Engr Off. (LTJG A.S. Ritchie), Rota Spain
 NAVFACENGCOM - LANT DIV. Eur. BR Deputy Dir., Naples Italy
 WPNSTA EARLE Code 092, Colts Neck NJ
 NCBC CFI (CAPT N. W. Petersen), Port Hueneme, CA; CFI AOIC Port Hueneme CA; Code 10 Davisville, RI;
 Code 155, Port Hueneme CA
 NCR 20 Code R31; 20, Commander; FWD 30th CDR Diego Garcia Island
 NMCB 5, Operations Dept., 74, CO; One, LT E.P. Digeorge
 NRI, Code 8400 (J. Walsh), Washington DC; Code 8441 (R.A. Skop), Washington DC
 NTC OICC, CBU-401, Great Lakes IL
 NAVOCLANSYSCEN Code 4473 Bayside Library, San Diego, CA; Code 6505 (J. Stachiw), San Diego, CA
 NUSC Code FA123 (R.S. Munn), New London CT; Code S332, B-80 (J. Wilcox); Code TA131 (G. De la Cruz), New
 London CT; Code 131 New London, CT
 OCEANAV Mangmt Info Div., Arlington VA
 OCEANSSYSLANT LT A.R. Giancola, Norfolk VA
 OFFICE SECRETARY OF DEFENSE ASD (I&I) Code CSS/CC Washington, DC
 ONR CDR Harlett, Boston MA
 NORDA Code 440 (Ocean Rsch, off) Bay St. Louis, Ms
 ONR BROFF, CO Boston MA; Code 481, Arlington VA; Code 700F Arlington VA; Dr. A. Laufer, Pasadena CA
 PMTC Pat. Counsel, Point Mugu CA
 PWC ENS J.E. Surash, Pearl Harbor HI; CO, Great Lakes IL; Code 120C (Library) San Diego, CA; OIC CBU-405,
 San Diego CA
 USCG (G-ECV/61) (Burkhart) Washington, DC; (G-MP-3/USP/82) Washington DC; G-EOE-4/61 (T. Dowd), Washington
 DC; MMT-4, Washington DC
 USCG ACADEMY LT N. Stramandi, New London CT
 USCG R&D CENTER CO Groton, CT; D. Motherway, Groton CT; LTJG R. Dair, Groton CT; Tech. Dir., Groton, CT
 USNA Sys. Engr Dept (Dr. Monney), Annapolis MD
 AMERICAN UNIVERSITY Washington DC (M. Norton)
 CALIF. MARITIME ACADEMY Vallejo, CA (Library)
 CALIFORNIA STATE UNIVERSITY LONG BEACH, CA (YEN)
 CORNELL UNIVERSITY Ithaca NY (Serials Dept, Engr Lib.)
 DAMES & MOORE LIBRARY LOS ANGELES, CA
 DUKE UNIV MEDICAL CENTER B. Muga, Durham NC; DURHAM, NC (VESIC)
 FLORIDA ATLANTIC UNIVERSITY BOCA RATON, FL (MC ALLISTER); Boca Raton FL (Ocean Engr Dept., C.
 Lin)
 FLORIDA ATLANTIC UNIVERSITY Boca Raton FL (W. Tessin)
 FLORIDA TECHNOLOGICAL UNIVERSITY ORLANDO, FL (HARTMAN)
 GEORGIA INSTITUTE OF TECHNOLOGY Atlanta GA (B. Mazanti)
 INSTITUTE OF MARINE SCIENCES Morehead City NC (Director)
 IOWA STATE UNIVERSITY Ames IA (CE Dept, Handy)
 LEHIGH UNIVERSITY BETHLEHEM, PA (MARINE GEOTECHNICAL LAB., RICHARDS), Bethlehem PA
 (Linderman Lib. No.30, Flecksteiner)
 LIBRARY OF CONGRESS WASHINGTON, DC (SCIENCES & TECH DIV)
 MAINE MARITIME ACADEMY CASTINE, ME (LIBRARY)
 MASSACHUSETTS INST. OF TECHNOLOGY Cambridge MA (Rm 10-500, Tech. Reports, Engr. Lib.); Cambridge
 MA (Rm 14 E210, Tech. Report Lib.); Cambridge MA (Whitman)
 MICHIGAN TECHNOLOGICAL UNIVERSITY Houghton, MI (Haas)
 MIT Cambridge, MA (Harleman)
 NATL ACADEMY OF ENG. ALEXANDRIA, VA (SEARLE, JR.)
 OREGON STATE UNIVERSITY CORVALLIS, OR (CE DEPT, BELL); Corvallis OR (School of Oceanography)
 PENNSYLVANIA STATE UNIVERSITY STATE COLLEGE, PA (SNYDER); State College PA (Applied Rsch Lab);
 UNIVERSITY PARK, PA (GOTOLSKI)
 PURDUE UNIVERSITY Lafayette IN (Leonards); Lafayette, IN (Altschaeffl); Lafayette, IN (CE Engr. Lib)
 SCRIPPS INSTITUTE OF OCEANOGRAPHY LA JOLLA, CA (ADAMS)
 SOUTHWEST RSCH INST J. Malson, San Antonio TX; R. DeHart, San Antonio TX
 STANFORD UNIVERSITY STANFORD, CA (DOUGLAS)
 STATE UNIV. OF NEW YORK Buffalo, NY; FORT SCHUYLER, NY (LONGOBARDI)
 TEXAS A&M UNIVERSITY COLLEGE STATION, TX (CE DEPT); College TX (CE Dept, Herbich)
 U.S. MERCHANT MARINE ACADEMY KINGS POINT, NY (REPRINT CUSTODIAN)

UNIVERSITY OF CALIFORNIA BERKELEY, CA (CE DEPT, MITCHELL); La Jolla CA (Acq. Dept, Lib. C 075A); Los Angeles CA (Engr I, K. Lee); SAN DIEGO, CA, LA JOLLA, CA (SEROCK)
 UNIVERSITY OF CONNECTICUT Groton CT (Inst. Marine Sci. Library)
 UNIVERSITY OF DELAWARE LEWES, DE (DIR. OF MARINE OPERATIONS, INDERBITZENE; Newark, DE (Dept of Civil Engineering, Chesson)
 UNIVERSITY OF HAWAII HONOLULU, HI (CE DEPT, GRACE); HONOLULU, HI (SCIENCE AND TECH. DIV.); Honolulu HI (Dr. Szilard)
 UNIVERSITY OF ILLINOIS Metz Ref Rm, Urbana IL; URBANA, IL (LIBRARY)
 UNIVERSITY OF MASSACHUSETTS (Heronemus), Amherst MA CE Dept
 UNIVERSITY OF MICHIGAN Ann Arbor MI (Richart)
 UNIVERSITY OF RHODE ISLAND KINGSTON, RI (PAZIS); Narragansett RI (Pell Marine Sci. Lib.)
 UNIVERSITY OF SO. CALIFORNIA Univ So. Calif
 UNIVERSITY OF TEXAS Inst. Marine Sci (Library), Port Aransas TX
 UNIVERSITY OF TEXAS AT AUSTIN Austin TX (R. Olson)
 UNIVERSITY OF WASHINGTON Seattle WA (M. Sheriff); SEATTLE, WA (APPLIED PHYSICS LAB); SEATTLE, WA (OCEAN ENGRSCH LAB, GRAY)
 UNIVERSITY OF WISCONSIN Milwaukee WI (Ctr of Great Lakes Studies)
 URS RESEARCH CO. LIBRARY SAN MATEO, CA
 US DEPT OF COMMERCE NOAA, Pacific Marine Center, Seattle WA
 US GEOLOGICAL SURVEY Off. Marine Geology, Mailstop 915, Reston VA
 ALFRED A. YEE & ASSOC. Honolulu HI
 ATLANTIC RICHFIELD CO. DALLAS, TX (SMITH)
 AUSTRALIA Dept. PW (A. Hicks), Melbourne
 BELGIUM NAECON, N.V., GEN.
 BRITISH EMBASSY Sci. & Tech. Dept. (J. McAuley), Washington DC
 BROWN & ROOT Houston TX (D. Ward)
 CANADA Can-Dive Services (English) North Vancouver; Library, Calgary, Alberta; Lockheed Petrol. Srv. Ltd., New Westminster BC; Mem Univ Newfoundland (Chari), St Johns; Surveyor, Nenninger & Chenevert Inc., Montreal; Warnock Hersey Prof. Srv Ltd, La Sale, Quebec
 DRAVO CORP Pittsburgh PA (Giannino); Pittsburgh PA (Wright)
 NORWAY DET NORSKE VERITAS (Library), Oslo
 EVALUATION ASSOC. INC KING OF PRUSSIA, PA (FEDELE)
 EXXON PRODUCTION RESEARCH CO Houston, TX (Chao)
 FORD, BACON & DAVIS, INC. New York (Library)
 FRANCE Dr. Dutertre, Boulogne; P. Jensen, Boulogne; Roger LaCroix, Paris
 GEOTECHNICAL ENGINEERS INC, Winchester, MA (Paulding)
 GLOBAL MARINE DEVELOPMENT NEWPORT BEACH, CA (HOLLETT)
 GOULD INC, Shady Side MD (Ches. Inst. Div., W. Paul)
 GRUMMAN AEROSPACE CORP, Bethpage NY (Tech. Info. Ctr)
 HALEY & ALDRICH, INC. Cambridge MA (Aldrich, Jr.)
 ITALY M. Caironi, Milan; Sergio Tattoni Milano
 KOREA Korea Rsch Inst. Ship & Ocean (B. Choi), Seoul
 LAMONT-DOHERTY GEOLOGICAL OBSERV, Palisades NY (McCoy)
 LOCKHEED MISSILES & SPACE CO. INC. SUNNYVALE, CA (PHILLIPS); Sunnyvale CA (Rynewicz)
 LOCKHEED OCEAN LABORATORY San Diego CA (F. Simpson)
 MCCLELLAND ENGINEERS INC Houston TX (B. McClelland)
 MEXICO R. Cardenas
 MOBIL PIPE LINE CO. DALLAS, TX MGR OF ENGR (NOACK)
 NORWAY A. Torum, Trondheim; DET NORSKE VERITAS (Roren) Oslo; J. Creed, Ski; Norwegian Tech Univ (Brandzaeg), Trondheim
 OCEAN DATA SYSTEMS, INC. SAN DIEGO, CA (SNODGRASS)
 OCEAN ENGINEERS SAUSALITO, CA (RYNECKI)
 OCEAN RESOURCE ENG. INC. HOUSTON, TX (ANDERSON)
 OFFSHORE DEVELOPMENT ENG. INC, BERKELEY, CA
 PACIFIC MARINE TECHNOLOGY LONG BEACH, CA (WAGNER)
 PRESCON CORP TOWSON, MD (KELLER)
 PUERTO RICO Puerto Rico (Rsch Lib.), Mayaguez P R
 R J BROWN ASSOC (McKeehan), Houston, TX
 RAYMOND INTERNATIONAL INC, CHERRY HILL, NJ (SOILTECH DEPT)
 SANDIA LABORATORIES Library Div., Livermore CA

SCHUPACK ASSOC SO. NORWALK, CT (SCHUPACK)
 SEATECH CORP. MIAMI, FL (PERONI)
 SHELL DEVELOPMENT CO. Houston TX (C. Sellars Jr.); Houston TX (E. Doyle)
 SHELL OIL CO. HOUSTON, TX (MARSHALL)
 SWEDEN GeoTech Inst; VBB (Library), Stockholm
 TIDEWATER CONSTR. CO Norfolk VA (Fowler)
 UNITED KINGDOM British Embassy (Info. Offr), Washington DC; Cement & Concrete Assn. (R Rowe) Wexham
 Springs, Slough Buck; D. New, G. Maunsell & Partners, London; Shaw & Hatton (E. Hansen), London; Taylor,
 Woodrow Constr (014P), Southall, Middlesex; Univ. of Bristol (R. Morgan), Bristol
 USGS MENLO PARK, CA (YOUNG)
 WESTINGHOUSE ELECTRIC CORP. Annapolis MD (Oceanic Div Lib, Bryan)
 WMCI APP LABS - BATTELLE DUXBURY, MA (LIBRARY)
 WOODWARD-CLYDE CONSULTANTS PLYMOUTH MEETING PA (CROSS, III)
 AL SMOOTS Los Angeles, CA
 ANTON TEDESKO Bronxville NY
 BRAHTZ La Jolla, CA
 BULLOCK La Canada
 HAMEED ELNAGGAR Wexford PA
 R.Q. PALMER Kaneohe HI

