AD-AO	SIFIED	BRITI THE DI 1977	SH COLU ESIGN A T R	MBIA UN ND PERF OSBORN	NIV VA	NCOUVER E OF FR	INST EE-FALL	OF OCE MICRO	ANOGRAP STRUCTU N000	HY RE INS 14-67-0	F/G 8 TRUME C-0047 NL	/10 ETC(U)	/	1
	9 _F ADA048 971	and the second s								Lange of States				
							-		ret Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria Territoria T	The second secon		A second		
		1 1									The second secon			
	END DATE FILMED 2 =-78 DDC							ъ						
1											×			~

First DRAFT : VIREVISED AD A 0 4 8 9 7 1 The design and performance of free-fall microstructure instruments at the Institute of Oceanography/ University of British Columbia by COPY T.R./Osborn FILE (Contract No NØØ014-67-C-0047, Date: 1977 6 Vancouver Canada. COPY AVAILABLE TO DOG DOES NOT PERMIT FULLY LEGISLE PRODUCTION DDC JAN 20 1978 DISTRIBUTION STATEMENT A Α Approved for public release Distribution Unlimited 063770

Introduction

This report covers the design, manufacture, and operational characteristics of the different free-fall microstructure instruments developed at the Institute of Oceanography, of the University of British Columbia. The objective is to produce one comprehensive description of the vehicles to be available for reference by readers of material based on the data collected by the instruments. Detailed information about the temperature sensors is available in Lueck et al. (1977) and the velocity probes in Osborn & Crawford (1977).

Gattles the first two instruments were designed -

The first instrument was for studying temperature microstructure only. The second instrument was designed to measure temperature and electrical conductivity fluctuations, γ as well as being the test vehicle for the development of a sensor for turbulent velocity measurements, With the successful development of the velocity probe, we reach a branch point in the study of microstructure where everything that was planned, couldn't be done with just one instrument. K third instrument was built to further the velocity microstructure work. The early temperature microstructure studies with the first two instruments has shown the desirability of a set of simple instruments to look at spatial and temporal variability of the temperature fluctuations. Hence, the fourth design, of which three identical instruments were constructed, was made as simple as possible to allow for multiple drops to study the variation in time and space. While four distinct instrument formats have been developed, the last two are the most important in terms of the data that have been collected. Thus the report describes the first two instruments, but their characteristics are not discussed in as much detail as the latter two designs. Appendix I contains a synopsis of each instrument.

Other free-fall instruments have been described in the literature. For ocean microstructure work the early development was mainly due to C.S. Cox at Scripps Institute of Oceanography (see Osborn and Cox, 1972 and Gregg and Cox, 1971). Williams (1974) and Caldwell et al. (1975) describe free-fall instruments for small-scale profiling. Simpson (1972) and Sandford et al. (1977) use free-fall bodies to look at the velocity profiles with depth, a field now being studied by Williams at Woods Hole Oceanographic Institution, and Rossby and Evans at the University of Rhode Island. Elliot and Oakey (1976) have a sophisticated system doing temperature and electrical conductivity profiling. Mortensen and Lange (1976) discuss the design criterion for wing stabilized free fall instruments.

ACCESSION for White Section Ø 271 2 Butt Secilos 000 UNANKOUNCED BY DISTRIBUTION / AVAILABILITY CODES AVAIL and/or SPESIAL Dist.

...

1

.

Initial Design Considerations

Before discussing the individual instruments it is worthwhile to consider come of the constraints placed on a free-fall instrument. The objective is to have a vehicle which travels through the ocean at a constant rate relative to the local water column, independent of the motion of a surface vessel. Because of frequency limitations on sensor response it is often desirable to have the descent speed less than the 1 m/sec that is common for STD casts. In fact, speeds are usually less than 50 cm/sec and for some workers as low as 3 or 4 cm/sec. The fail speed can be regulated by the excess weight, the drag, or the lift. Cox's instruments use the lift derived from the autorotation of the wings to limit the fall speed. Reducing the excess weight to get a small fall speed is difficult because a fractional change in density of the water produces a change in excess weight that is the same fraction of the total weight. Thus having balanced a 70 kg instrument to .5 kg a change of .1% in density (1 unit in σ_{1}) causes a change of 14% in the excess weight. Another technique is to increase the drag by increasing the cross-sectional area (i.e. form drag) of the instrument. Care must be taken to avoid introducing unfavorable body motions due to large-scale eddies being shed. Thus a parachute or flat plate should not be used. Even blunt ends on vertical measure cases can cause oscillation.

Upon reaching some lower limit for profiling, the instrument must return to the surface. Hence the vehicle must be buoyant at depth as well as at the surface (i.e. the buoyancy must be pressure proof). The problem of making a buoyant pressure case for all depths in the ocean is nontrivial. Brown & Cox (1973) give the information necessary to determine a suitable pressure case designed from aluminum pipe. Our original two instruments use glass spheres for buoyancy and for the electronics housings. While the available buoyancy, volume, and maximum depth characteristics make the glass spheres attractive, we find the problems of access to the inside of the pressure housing exceeds the advantages for development work.

Another major design problem with free fall oceanic microstructure systems is the data recording or transmitting system. Due to the small-scale nature of the phenomenon under study, detailed spatial sampling is required. Velocity fluctuations can reasonably be expected down to the centimetre

scale, hence a spatial resolution of 10² cycles per metre is required and that implies 2×10^{2} numbers for 1000 m profile for each channel If one has two data channels for the velocity and another two sampled. for the temperature gradient and the electrical conductivity gradient, as well as additional storage space for the mean values (which can be digitized at lower densities) of temperature, electrical conductivity, and pressure, then the total amount of data could be 10' bits at 10 bits/ That estimate is probably conservative because of the desirabilnumber. ity of having more than 10 bits per word. Now the data rate depends on the fall speed. Given a fall speed of 10 cm/sec the data rate is 1000 bits/sec. 50 cm/sec implies 5000 bits/sec. The data handling problems are not insurmountable but are a significant difficulty. Cox solved the problem with a hybrid recording that put a digital signal on a multichannel $\frac{1}{2}$ tape in analogue fashion. This system limits the depth range over which data are recorded to about 150 m. We decided to telemeter the information to the surface using expendable wire links manufactured by the Sippican Corporation. These XWLs are essentially the wire portion of an expendable bathythermograph. With one spool located on the instrument and another on the ship there is little drag to affect the motion of the vehicle. The dynamic range of our system is much smaller than that in Cox's system and we have compensated in part for this deficiency with more analog treatment of the data inside the instrument.

4-

The First Two Instruments

The first instrument built at UBC (see Fig. 1) was designed in late 1969 and early 1970 to measure temperature microstructure. The instrument consisted of a cylindrical plastic outer shell 1.05 m in length and .28 m in diameter. Inside the outer housing was a .25 m diameter Corning polar access glass sphere that was used as the pressure housing for the electronics. The electronics were attached to the "endcap". Another sphere and some syntactic foam were also mounted inside the cylindrical housing to provide sufficient floatation of the instrument. An OAR submersible citizen's band radio transmitter was mounted on the top of the instrument for location upon return to the surface. The wire link was also mounted on the upper end. Three wings were mounted to the outer rim of the instrument. These wings were formed from salvaged sonobuoy wings that were extended to .97 m length. The release is a Richardsontype stretched pin release and is mounted at the centre of the lower end of the instrument. The weight is held on with wires that run out to compressed salt blocks mounted on the outside of the lower end of the plastic housing. Thus the weight can be dropped either by the breaking of the pin or the dissolving of the salt blocks. The salt blocks are much preferable to magnesium links as back up releases because they are quicker and more certain, not being coated by their corrosion products and hence protected from decay, as are some magnesium links. If more time is needed (>45 min) we dip them in paint.

The water temperature was sensed by two thermistors; one was mounted on the axis of the instrument housing and the other was mounted $\frac{1}{2}$ m outboard but at the same level as the central probe. The temperature from each thermistor was telemetered to the surface. In addition, the temperature signal was passed through a high pass single pole R-C filter ($\tau = \frac{1}{2}$ sec) in the instrument and then amplified. These amplified signals (one for each thermistor) were then transmitted to the surface. A fifth signal, the pressure, was also telemetered up to the surface so that the fall speed of the instrument could be determined.

This first instrument was essentially the test bed for two new ideas, the glass spheres as instrument housings and the wire links for telemetering

the data. The latter idea worked quite well but the former was not very successful due to the small entry hole into the sphere (63 mm diameter). Data from this instrument were analyzed for two projects, the work in Rupert Inlet (during March 1971) described by Drinkwater (1973) and the measurements in Powell Lake (during Sept. 1971) reported by Osborn (1973). The instrument was lost in Powell Lake. It resurfaced 11 months later, and we recovered it from the local resident who had found it and called the phone number printed on the side of the outer housing just below the word "REWARD". The pressure release pin had broken indicating the instrument hit the bottom shortly after the pin broke or the pin snapped due to the continual high pressure. The previous drop to the one which lost the instrument showed signs of scraping the bottom (there was sediment in the thermistor holder although the thermistor was not broken). The bottom of the lake contins no oxygen but does contain hydrogen sulphide. The orange outer paint had turned a dark green color, the copper wire on the XWL spool had darkened in color, and the potting at the base of the OAR radio transmitter antenna had softened. The potting was replaced and the transmitter has been used many times since the recovery. The vibrotron pressure transducer in the instrument was still good and was used by Galloway (1974) in one of his tide gauges. It has since been lost in the Arctic Ocean.

With the loss of the first instrument in Powell Lake in September of 1971, development of a second instrument which had already begun was hastened. This instrument is shown in Figure 2, in the configuration that it was finally used for the development of the velocity probe. The pressure housing was a 16" polar access glass sphere. The sphere was chosen because it offered sufficient floatation as well as a high maximum pressure rating and a .12m hole for inserting the electronics.

The sphere was mounted inside a PVC frame with the endcap upward. A flashing light and radio (both from OAR) were mounted on the upper end to aid in recovery. The wings were from a sonobuoy, initially .28m long and were shortened from their original size to reduce the rotation rate of the instrument. At their final length of .12m, they produced little lift and so the balancing of the instrument became critical. The

original design of the instrument was with the larger wings and an outboard thermistor again mounted $\frac{1}{2}m$ from the axis of the instrument and on the same level as the central thermistor.

. . . .

A few improvements in the electronics were brought in with this second instrument. The most notable was the modification of the high-pass amplifier of the temperature signal to a straight differentiator. This modification was really just an increase in the frequency of the highpass filtering to something greater than 40 hz from the previous value of approximately 1/3 hz ($\tau = \frac{1}{2}$ sec). This transition was done in steps so that we could see the changing nature of the signal due to the increasing amount of differentiation. Another channel was added in which we tried compensating for the effect of the thermistor attenuation by boosting the measured temperature gradient in the band above 15 hz, by an additional factor of ω to make up for the approximately single pole attenuation of the thermistor's response. A correction of this sort required a detailed understanding of the thermistor attenuation hence the work reported in Lueck et al. (1977) was undertaken to study the thermistor response as a function of frequency.

The rotation rate of the instrument was measured electronically using a technique suggested by T. Sanford of WHOI. A permeable metal core was wrapped with a coil made from an XBT wire and the signal amplified so that as the instrument rotated the changing magnetic flux through the coil generated an essentially sinusoidal curve as a function of time. This device proved very successful for measuring the rotation rate. A similar coil was installed with the axis vertical to look for possible oscillations of the instrument about a vertical axis. We were also experimenting with a series of salinometers during the winter of 1971-1972 but were unable to develop a sensing head with sufficient resolution and low enough noise to be useful.

Development of this second instrument was begun in earnest in the fall of 1971 after the first instrument was lost in Powell Lake. By the spring of 1972 the work with the velocity probe was sufficiently promising that the salinometer work was shelved. The mount for the second thermistor was removed to reduce asymmetries of the body, and from this

time on a considerable amount of our effort was devoted to probe development, manufacture and setting up of the associated electronics. The probe first operated successfully in July 1972, and by the August 1972 sea trip, from which data Osborn (1974) describes the probe, it was apparent that the large glass sphere made it too difficult to service and trouble-shoot the electronics. Additionally, the desire for more static stability made a new instrument housing desirable so the next instrument was designed and operating in December 1972.

0.2

The Camel

Figure 3 shows the "Camel", our third instrument. It was designed primarily for supporting the velocity probe and initially expected to operate no deeper than 300 m. Operations were expected to be limited to the local inlets where the effects of surface waves can be ignored in terms of ship motion, thus handling problems during launch and recovery would be minimal. Due to the success of the velocity prove work, studies were undertaken in the Equatorial Atlantic from the R.V. Atlantis II in the summer of 1974, off the Azores from the W.F.S. Planet in March 1975, and the western Atlantic as part of the Fine and Microstructure Experiment (FAME) organized by Drs. Sanford and Hogg of WHOI on board the R.V. Knorr.

The pressure housing is 6061-t6 shedule 40 aluminum, .168m diameter, 7.1mm thickness and length 2.85m. Maximum operating depth is estimated as 1000m from the work of Brown and Cox. The end caps are cut from 50mm thick aluminum plate, have a diameter of .20m and are attached to the tube with bolts to external lugs that have been welded onto the tube. There is a single O-ring seal to the inside of the tube which has been ground circular by a local marine engine-boring company since no local machine shop could accommodate the length on their lathe and still machine a circular hole. The end caps were machined after the tube was ground so that a proper seal was assured. Electrical penetrations are made via Electro-Oceanics connectors. All the electronics are inside the main case except for the temperature, conductivity, and velocity sensors and the velocity probe preamplifier mounted just above the probe.

The upper and lower ends are faired with fiberglass shells to reduce the wobble due to eddy shedding. The brushes form a drag element that does not shed large eddies so the fall speed can be reduced without reducing the excess weight and causing large variations of fall speed with depth. There are six brushes .17m long and .16m in diameter mounted as an almost continuous ring around the cylinder. The brushes are held away from the body with triangular PVC plates mounted to the housing with large hose clamps. The whole assembly is then wired together to prevent loss in case a sharp blow from the recovery vessel.

An OAR flashing light and citizens band radio (reduced antenna model) are mounted on the upper endcap for aid in location. A Helle PG-06 pinger is used when the bottom is shallower than 1000m. There are two rope hoops that were installed for operations in 1974 from the Atlantis II along the Atlantic Equatorial Undercurrent. The recovery procedure involves snagging these ropes with a hook designed by Williams (1974) on the end of a long pole. The pole is then pulled loose and the instrument hoisted aboard.

The relase system consisted of two Richardson-type stretched pin releases. The weights are mounted in two tubes and wires are stretches between the two releases and across the ends of the tubes. Upon either pin breaking, both weights are released. For safety, salt blocks are inserted into each line. These dissolve in about 45 minutes time and release the weights. The instrument is ballasted so that the release of either weight will allow it to return to the surface. (On our first recovery along the equator in the Atlantic it returned with one weight still attached and a small amount of water in the pressure case.) The only problem with the release system occurred on a cruise in Howe Sound with the bottom at about 200 m. We normally use tin-plated copper wire for holding the weights in. This trip we had brought steel wire which was too stiff and did not work, so we borrowed some copper wire from the ship. This wire was very soft so we had to use a much larger diameter and that in turn reduced the amount the release screw could be threaded into the piston on the release. Thus on one drop the release screw stripped its threads without breaking off its head and the instrument hit bottom and stuck before the salt releases could work. Due to the telemetering system we could identify that the instrument was on the bottom and tell that the case had not flooded. Fortunately the instrument worked its way out of the bottom in a day or so and we picked it up two days later with a small cabin cruiser. We had included the acoustic pinger on the instrument in case of such a problem, and had in fact already made arrangements for a small submersible

to effect the recovery. A further safeguard that has not been instituted in the present instrument would be to modify the releases to drop the weights if the screw strips. This modification could be simply effected by changing the orientation of the release so that the wires are trying to pull the screws out.

The salinometer is a modification of the design of Gregg and Cox (1971). Rather than use a spring mechanism that pulls a piston up a tube to suck water through the sensing port, a bellows is expanded at a constant rate with depth. The system that expands the bellows is a piston and spring combination. The piston has water on one side, the other side being at essentially atmospheric pressure because it is connected to a reservoir. A spring mounted between the reservoir and the bellows balances the force of the water pressure on the piston (Figure 4). Thus the compression of the spring and the expansion of the bellows are essentially dinear functions of the depth. Variations in fall speed are unimportant since the volume of water per unit depth pulled into the bellows through the sensing port, is independent in the fall speed. Further discussion of the conductivity measurements.

...

The mass of the instrument as launched is 75 ± 5 kgm. This mass corresponds to a weight of 740 ± 50 newtons. After the instrument was dropped the first time, changes in the mass became more important than the actual value. The buoyancy of the instrument is estimated by weighing the instrument in the water when fully prepared for a drop. Because of the motion caused by the small waves the value is not very precise and the fine adjustment is done from the fall speed calculated from the pressure records. Experience gained by weighing the instruments just before release, indicates that the fall speed is between 40 and 55 cm/sec when ballasted to be 18 to 27 newtons heavy.

Measurements of the falling and rising speeds at the Camel taken during the field trip to the Azores can be used to estimate the drag coefficient, assuming the fall speed is quadratic in the excess weight and that the relationship is the same for a rising and falling instrument. On drops 5 and 6 the observed fall speeds were .53 and .51m/sec respectively. The rise speeds are also available for portions of these two drops. These values are .85 and .45m/sec respectively. I attribute the difference to the fact that half of the release weight did not fall away immediately on drop 6 (this data is not the first indication that this situation could arise but perhaps it occurs more often than we expected). For this pair of drops the total drop weight is known to be 93.6 newtons (21 lbs) when

weighed in air, 85.3 newtons in water. The following equations can be used to describe the system:

$$B = A (.85 m/sec)^2$$
 (1)

$$B - \frac{85.3}{2} = A (.45m/sec)^2$$
(2)

$$E = A (.52 m/sec)^2$$
 (3)

$$B + E = 85.3$$
 newtons (4)

Where B is the buoyancy of the instrument with both drop weights released, E is the excess weight when falling, A is the drag coefficient, and the average fall speed is taken to be .52m/sec. We have more than sufficient equations for a solution which is:

> $A_1 = 86 \text{ newtons/m}^2/\text{sec}$ $A_2 = 92 \text{ newtons/m}^2/\text{sec}$ B = 62 newtonsE = 23 newtons

Where A_1 is derived from equations 1, 3 and 4 while A_2 is derived from equations 1 and 2. These values are in general agreement with a few crude measurements of excess weight derived with a small hand held scale in sheltered portions of a local inlet.

For the analysis of the behavior of the body in response to large-scale shears and velocity fluctuations in the ocean it is necessary to know the location of the centre of mass and buoyancy of the instrument. The centre of mass can be measured by finding the balance point of the instrument in the laboratory. For the complete instrument except for the drop weights the C of M is 40 cm below the middle of the aluminum tube. The drop weights for the recent cruises have been 9.6 kgm total mass with their centre about 1.1m below the C of M for the unloaded instrument. Thus the C of M for the whole instrument is .14m lower for the loaded instrument or .54m below the centre of the tube. The centre of buoyancy can be estimated in a similar fashion. The instrument housing and endcaps are symmetric in displacement except for the section inserted to contain the salinometer mechanisms. This apparatus weighs 37.5 lbs in air and 22.5 in water, so the buoyancy is 15 lbs. The distance from the centre of the tube is 1.7m. The recovery aids, etc., on the upper end have

9 lbs. buoyancy and a moment arm of 1.6m. A reasonable estimate for the centre of buoyancy is therefore .07m below the centre of the tube or .47m above the centre of mass. The error is probably \pm .10m in the centre of buoyancy and the centre of mass. Measurements of the torque necessary to make the instrument lie horizontal while fully submerged, yield a value of $370\pm8\%$ newton-meters about the calculated centre of buoyancy. The error is predominately due to the problem of measuring small forces in the presence of wave motion. The instrument is so large that the measurements must be performed in the ocean and even small waves in an enclosed yacht basin lead to errors of about 6% in the force measurements. The torque of 370 newton-meters would correspond to a force of 790 newtons at a moment arm of .47m. The calculated and measured stability values are consistent with each other.

4: ..

.

Electronics

The electronics consists of the measuring circuits, the power supply, and the telemetering system (Fig. 5). The power is derived from a set of gel-cell batteries which are regulated to a nominal \pm 15 volts and a set of nickel-cadmium batteries that are regulated to anominal \pm 6.3 volts. The telemetry is performed by a set of Sonex TEX-3075 voltage controlled oscillators specially ordered to be low voltage, (6.3 volts rather than 28 volts). The FM signals from the individual oscillators are summed with an operational amplifier and then transformer coupled to the XWL for transmission to the surface. The only signal that does not use an auxiliary oscillator is the pressure signal which comes from a pressure transducer which has a direct FM output on one of the I.R.I.G. channels.

The temperature sensing thermistor forms one arm of an essentially equal arm Wheatstone Bridge which is linear to + 1% for a temperature deviation of + 8°C from the balance point of the bridge. The bridge output is fed to a preamplifier with a nominal gain of 20 and then to a second amplifier (nominal gain 1.4 to 2.8) for the temperature signal output. The preamplifier output is also fed to a differentiator circuit which produces the signal that is later interpreted as the vertical component of the temperature gradient. The differentiator has a high frequency rolloff consisting of two R-C filters with 3db points at 64 and 79 hertz respectively. The differentiator has a nominal gain at 1 hertz of 18.47 based on the circuit parameters; the measured value is 18.39. Frequency response is -3db relative to a differentiation at 44 hz (measured and calculated). The response of the thermistors is discussed in the paper by Lueck, Hertzman and Osborn (1977). Calibration of the thermistors consists of measuring the resistance at one or more temperatures that are in turn measured with a mercury in glass thermometer. To date no concerted effort has been made to ensure or enhance the accuracy of the temperature measurements. The relative temperature measurements are probably within + .10°, or better depending on the number of calibration points, but the absolute accuracy requires calibration against an STD trace to be within + .2C°. On the Azores and Bermuda cruises we have been bothered by oscillations in the temperature gradient data and to a lesser extent in

15

the electrical conductivity gradient. It has not been possible to locate the source of the problem since on testing cruises in local waters we are not able to reproduce the problem. Hence it may be some interaction of the ships with the instrument or something we cannot recognize that we are doing differently at home and away.

The pressure is measured with a Vibrotron pressure transducer that is calibrated with an Amthor model #452 dead weight tester. The transducer is driven by a United Controls Amplifier. The accuracy and interpretation of the pressure record is discussed in the section dealing with the fall speed of the instrument body.

The electronics associated with the velocity probe are covered extensively in the paper by Osborn and Crawford (1977). The salinometer consists of a modification of the design by Gregg and Cox (1971).

The output of electrical conductivity is treated in a similar fashion to the output of the temperature preamlifier in that the signal and its time derivative are both telemetered to the surface. The details of the circuit and its operation will not be discussed in this paper because the data have not been systematically analyzed yet.

The direction is measured with a flux gate compass purchased from Mr. Neil Brown, who calibrated it at 2^o intervals. The instrument was installed in the Camel to make sure the rotation of the body was slow enough that velocity signals were not being adversely affected. The period of rotation is generally greater than 200 seconds. Nothing was designed into the instrument to make it rotate, and no effort was exerted to stop this slow rotation. Some changes in rotation are seen at the Equator when the instrument enters the high shear region at the top of the undercurrent. Data show variations that range from a tripling of the rate of rotation in the same direction, to a stopping of the rotation and even a reversal.

Data telemetry

Data from our instruments are converted from a time varying voltage to a frequency modulated (f.m.) signals by voltage controlled oscillators (vco's) inside the pressure case. The output of the different oscillators is summed by an operational amplifier and this signal is transformer coupled to the wire link. On board ship another operational amplifier serves as a high impedance load on the wire and outputs the signal to a HP 3960B tape recorder for later analysis, and a set of SONEX S-35 discriminators and a chart recorder for real time data display. Figure 6 is derived from Sippican Development Report R-621 and shows the attenuation as a function of frequency as the wire is unspooled in the water. Our configuration is slightly different as one spool of wire is always in the water. The XWLs we use are 5000 feet long with 1500 feet on the source spool and 3500 feet on the shipboard spool. For deep drops we have interchanged the spools with good success for operations as deep as 800 m. The attenuation of the signal is a problem, especially the differential attenuation as a function of frequencies. We have used the I.R.I.G. ±7.5% deviation channels with center frequencies as low as .73 kHz and as high as 10.5 kHz (see Table 1). The attenuation is accounted for by increasing the gain of the shipboard operational amplifier which loads the XWL. The differential attenuation is fought by setting the vco's up with tapered output amplitudes. Thus the highest frequency has the largest amplitude at the surface. As the instrument sinks, the differential attenuation reverses the relationship and the low frequencies have the largest amplitude. Fortunately, the discriminators can accept a large range of input amplitudes (5 volts to 5 millivolts rms). Also the highest frequency is the Vibrotron pressure gauge and if these data are lost at great depth we can approximate the depth from the last known value and the fall speed.

This telemetering system has worked well. There is the occasional aggravation of a broken wire at the surface or depth. In high current or windy regions there is the problem of the surface wire running out before the instrument starts to return. The advantages of real time display and the ability to recycle without opening the pressure case to change tapes have been appreciated. As mentioned earlier, we lost the Camel once for two days by a release failure which caused it to stick in the bottom of

a local inlet. The real time display allowed us to tell that we had hit bottom and that the case was not flooded. Hence, when it didn't come up long after the salt blocks had dissolved we knew it was worth trying to recover and we made arrangements for a small submersible. Fortunately the tidal currents (or just time and the buoyancy) broke it loose two days later. We have also had the instrument come to rest on the halocline in the local inlets where $\Delta S = 20 \%$. The telemetry identifies this problem and we wait for the salt blocks to dissolve.

Table I gives the vco center frequencies and the band width for $\frac{1}{2}$ db attenuation. The 14.5 kHz channel is used for tape speed compensation (TSC) and is recorded by itself on a separate channel at the tape recorder. Some of the Vibrotron pressure transducers are on the 14.5 kHz channel, in these cases we divided their frequency by two inside the instrument and use the 7.35 kHz data channel. Upon playback the TSC signal is fed to a special discriminator which automatically feeds a correction signal to the data discriminators to correct for fluctuations in the tape speed. The TSC signal is put on a separate channel so that the levels of the f.m. data signal can be adjusted using the recorder's input meter. The noise seems to be lower if the two signals are fed to the discirminator set separately.

Calibration of the oscillators and discriminators are performed with a digital multimeter (Fluke 1000A or Dana 3800A), a counter (HP523CR) and a Wave-Tek oscillator. The center of the band is adjusted to 0 volts and one band edge set to \pm 1.414 volts at \pm 7.5% deviation for the discriminator, or \pm 7.5% deviation at \pm 2.5 v for the oscillators, and the other band edge then checked and recorded. For digitization of the data the IOUBC PDP-12 computer contains a 10-bit digitizer. It was augmented in January 1977 by a 12-bit unit which will be used henceforth.

Fall Speed of the Camel

The pressure gauge in the instrument measures the pressure as a function of time. The data are stored on magnetic tape and digitized. For analysis data are digitized at a rate of 200 or 250 hz, depending on the data set. This high rate is not needed for the pressure data but the system is not designed to digitize different channels at different rates so the rate is determined by the highest rate required. The pressure data are then averaged in blocks of 128 points and then converted to pressure using the calibration of the Vibrotron as determined in the laboratory with the dead-weight tester. The calibration data are fitted with a cubic polynomial and that formula is used to convert the averaged values to pressure.

The resultant profiles of depth as a function of time are plotted on 30 inch paper with 25m/inch and 16sec/inch. The slope of the line is the fail speed. In addition to the plot, the data are fitted to a series of linear polynomials using 16 values for the depth, each separated by .64 or .512 seconds (depending on the digitization rate). These depths correspond to the interval over which the velocity data are analyzed to estimate the local rate of energy dissipation. These estimates of the fall speed scatter quite a bit about the mean. Table II shows the computer printout for Drop 15 in the Azores. The first column is the depth, the second column is the fall speed estimated for the linear fit to 16 successive values of the depth averaged over .64 seconds, the third column is the sum of the fall speed values and the last column is the average fall speed up to that point. It should be remarked that the depth of release is always the surface but sometimes the calculated depth can vary by several meters due to temperature effects; first drop of the day the instrument is at lab temperature, for later drops it's colder; the discriminator calibration, or the transducer hysterisis. One can see the scatter, values as low as 49 cm/sec at 179 m and 562 m. These low values are probably due to noise combined with the least count problems with the digitizer. The least count on the digitizer corresponds to approximately .94 m so the whole time interval of 10.24 seconds corresponds to about 5 m or 5.3 counts. The last bit on the digitizer has been found to have a favored value (there is a 2 to 1 preference in the least significant bit, Crawford, personal communication) and so the 16 values

-18

are not separated enough to average this preference out. The slope of the line fitted by eye gives between 50 m and 380 m depth is 52.5 cm/sec, the average of the estimated velocities eliminating the first three and last value (instrument may have been accelerating during those intervals) is 52.14 cm/sec. The average fall speed derived from dividing the change in depth by the time from the fourth to the second from last depth is 52.05 cm/sec. The average from 60 m depth to 737 m depth is 51.98 cm/sec. The value used for the dissipation calculations was 52 cm/sec based on the fact that the depth versus time curve showed a bit of curvature above the 50 m depth. In order to study the fall speed variation with depth, the depth versus time record for this drop was fitted using a cubic spline routine available on the UBC computer. Essentially, the fit produced has the minimum curvature possible within the allowed variation for each individual point and the profile as a whole. For more details on the technique see Reinsch (1967). The results are given in Table III which show the fitted depth, the slope of the fit (fall speed), and the curvature of the fit (acceleration). There is a minimum in the fall speed around 480 m depth which may be real or a problem with the calibration values which show a peculiar minimum in slope in the 600-700 psi region (Table IVa,b). It seems that .52 m/sec is a reasonable estimate of the average fall speed and the error is $\sim \pm$ 10 mm/sec or \pm 2%. Table III suggests the error could be decreased significantly by adding a linear variation with depth to the fall speed. It is unclear how much of the deeper variation is due to the instrumentation and how much is real.

The error in fall speed contains two parts, the error in the pressure measurement by the Vibrotron and the errors associated with the differencing of the pressure. The errors in the pressure measurement that are constant with depth do not influence the fall speed calculation, it is the depth or time variable errors that are important. One source of error is the temperature sensitivity of the resonant frequency of the Vibrotron pressure transducer. Calibrations of the transducer at 19.8°C and 13°C showed the transducer used in the Azores and the Bermuda Cruises to be much more temperature sensitive at low pressures than at higher pressures. Table IVc shows the difference in the measured frequency between the two temperatures. The difference in measured

19

. . . .

frequency shows a consistent trend, with fluctuations that may be associated with the errors in the calibration technique being amplified by the differencing of the values. A change of three Hertz corresponds to about a 1m depth increment so the effect over the whole water column is about 2 m in 600 m, or less than .5%. The effect is most pronounced near the surface so if we consider the first 50 psi of change we have .5 m in about 30 m or .23%/C°. The fall speed is not all that constant in the first 30 m anyway.

The different methods for calculating the <u>average</u> fail speed from the pressure data all give answers that are within 1% of the value chosen for the mean fall speed over the drop. If one excludes the calculation based on lines drawn by eye the disagreement is less than .5% over the whole drop. The small-scale variability of the fall speed cannot be examined to this accuracy, of course, because of the least count error problem of the digitizer discussed earlier.

There remains the question of stability of the fall speed. What is the length of time, or the depth to which the instrument has sunk, before the fall speed has reached its terminal value? What are the variations with depth after 'terminal velocity' is reached?

The stability of the fall speed has been examined for a drop in a local fjord, Howe Sound. For this drop a 0-500 psi pressure gauge was installed for greater resolution of the depth trace. The initial speed (.54 m/sec) was 97.3% of the terminal value (Table V). The fall speed reaches 98% of its terminal value of .555 m/sec (the average of .553 and .555 m/sec) at a depth of 40 m. This depth is greater than that required for the data collected along the Atlantic Equatorial Undercurrent wherein all the drops that were analyzed by Crawford (1976) reached their terminal velocity by 15 to 20 m depth. The data collected in the Azores show terminal velocity is achieved by 20 m in all but one of the drops which required 29 m to reach the terminal value. The solution to this question requires drops with a pressure transducer with a limited full-scale range or else an internal recording system of great resolution such as developed by Cox for their free-fall system in order to get the reso-

lution in pressure necessary to look at variations in its first derivative, which is the fall speed. Our interest to date has been on the deeper part of the water column below the first 10 to 20 m in general so that the speed up at the start has not been a problem in general. For that portion of this Howe Sound drop below 75 m, the fall speed is a constant $\pm .7$ %.

Some of the fall speeds measured on the Bermuda Cruise show an increase in speed from .30 m/sec to .42 m/sec with depth for the first 50 m (Gargett. personal communication). This extreme situation has not been seen in the other cruises and the explanation is unknown. One possible cause is an air bubble trapped in the salinometer system bellows. The design is such as to make this quite possible. This bubble would compress with depth, hence decreasing the buoyancy and allowing the fall speed to increase. The effect is the opposite of that due to an increase in the density of the water. The estimation of the volume of air necessary must be crude because of the imprecise knowledge of the excess weight on the body as a function of the fall speed. Data analysis for the Bermuda Cruise was also complicated by the fact that below a certain depth the pressure signal faded out, so that deeper depths had to be estimated from the last known pressure and the fall speed. The loss of pressure signal had not been a problem previously although it has typically had the highest centre frequency and hence been attenuated most by the transmission system. The pressure transducer has now been overstressed by operating 25% beyond its full scale and shows a tendency to oscillate unstably at high pressures and low temperatures (θ <13^oC). Thus there may be a decrease in amplitude with decreasing temperature.

Motion of the Camel

Since the Camel is being used to support the velocity probe, it is important to investigate the possible effects of body motions of the vehicle on the velocity measurements of the probe. There are two aspects to this problem. First let's consider the probe so we understand its operating principles. As described in Osborn and Crawford (1977), it is a symmetric airfoil of revolution whose axis is aligned with the axis of the Camel. As the probe moves through the water, the mean velocity vector of the water is axially along the probe, i.e. the velocity vector has zero angle of attack relative to the probe. Any horizontal velocity component in the water relative to the probe leads to a non-zero angle of attack for the total velocity vector, hence a lift force is exerted on the probe tip. The two perpendicular components of this lift force are sensed by two perpendicular piezoceramic transducers inside the prove and the force components are converted to electrical signals. The output of the probe is linear in the cross-stream velocity (U) and the axial velocity (V),

Output = $\frac{1}{2}$ pS UV

where p is the density and S is the sensitivity. We have already considered fluctuations in the mean fall speed of the Camel (which could be considered fluctuations in the mechanical gain of the system). We will now consider fluctuations in the cross stream and the axial velocity due to pendulum-like oscillations of the body about its vertical axis. After that discussion we will discuss constraints due to the probe's limitation that the total angle of attack be less than some maximum critical angle between 10° and 15°. Measurements of the instrument, ballasted for neutral buoyancy, show the natural period of oscillation to be 7 seconds and the motion is highly damped. Let us compare this value to the theoretical calculation based on the known parameters to check on our understanding of the situation.

The question of natural frequency of scillation can be looked at by estimating the oscillation period of the instrument as a pendulum

$\omega = \sqrt{wh/I}$		1.
√ mg•h	√12gh	
1 <u></u> 2	22	
12		

 $T = 2 \frac{\pi}{\omega} = 2\pi \ell / \sqrt{12gh} = \frac{2\pi \cdot 4.2m}{\sqrt{12 \cdot 9.8m/sec^2 \cdot 47m}} = 3.6 secs$

where w is the weight, h the metacentric height, I the moment of inertia, and & the length. Since the instrument is in water the effect of the virtual mass should be included. The virtual mass is the water associated with the cylinder which must move at the same time. The effect is to increase the moment of inertia. For a long prolate spheroid the added mass is equal to the displaced mass (Lamb 1945) so the period would increase by the $\sqrt{2}$ times, to 5 secs. An accelerometer could have been installed to measure this effect but since the frequency is below the range of interest we did not feel the expense was warranted. As a further check we must see if the magnitude of the tip is significant for the interpretation of the data.

For a consideration of the effect of possible tipping of the instrument due to the shear in the water the velocity data collected by Bruce and Katz (1975) along the Atlantic Equatorial Undercurrent can be used. A large value of the mean shear over a vertical distance of 10 meters is .06 sec⁻¹. The mean horizontal acceleration of the Camel, assuming some point on the body remains at rest with the local water column, is

$$a = \frac{\partial u}{\partial t} = \frac{\partial u}{\partial z} \cdot \frac{\partial z}{\partial t} = .06 \cdot v_{fall} = .03 \text{ m/sec}^2$$
,

the force associated with such an acceleration is

$$F = ma = 75 \text{ kgm} \cdot .03 \text{m/sec}^2$$

This force can come from two possible sources. First the aerodynamic lift force on the tapered lower end of the cylinder and secondly the cross stream drag force on the cylinder as a whole. The aerodynamic lift force due to the potential flow from Allen and Perkins (1951) is

$$r_1 = \rho A V u$$
.

A is the cross-sectional area of the body, V is the axial speed, and u is the local cross-stream speed. The force, F, acts at the position of changing cross-sectional area, i.e. the ends of the instrument. From the same source we get the force due to flow separation as

$$F_2 = \int \frac{1}{2} \rho u^2 \cdot c_{d\alpha} = 90^{\circ} \cdot 2r dl$$

 $C_{d\alpha=90^{\circ}}$ is the drag coefficient for a cylinder perpendicular to the flow and r is the radius. This force acts all along the body away from the lower end where C_d is probably reduced due to the axial velocity and the close proximity of the upstream end of the cylinder diminishing the effect of flow separation. In order to estimate the magnitude of these forces one must first estimate the local cross-stream velocity as

a function of position along the cylinder. A reasonable estimate can be derived by assuming the brushes are at rest with respect to the local water velocity. One further assumption is to ignore the forces on the portion of the body above the brushes. Since that portion of the instrument is in the wake of the brushes it is inappropriate to use a potential flow theory to calculate an aerodynamic lift force. The effect of the u^2 drag is limited since the region is close to the brushes and the speed u increases linearly with distance from the point of zero relative velocity. The distance from the brushes to the nose is 3.3m

 $F_1 = \rho Avu = \frac{1000 \text{ kgm}}{\text{m}^3} \cdot 2.2 \times 10^{-2} \text{m}^2 \cdot \frac{5\text{m}}{\text{sec}} \cdot .06 \text{ sec}^{-1} \cdot 3.3\text{m}$

= 2.2 newtons

which is a sufficient force to provide the acceleration required for some point on the body to 'keep up' with increasing horizontal speed. The Torque exerted by this force about the C of M is

 $M_1 = 2.2$ newtons 2.2m = 4.8 newton metres.

For the cross-stream drag force we integrate down to, but not including

the nose

$$F_{2} = \int_{0}^{3m} \frac{1}{2} \cdot 1000 \frac{\text{kgm}}{\text{m}^{3}} \cdot (.06 \cdot \text{k sec}^{-1})^{2} 1.2 \cdot .17 \text{m d} \text{k}$$

= $\frac{1}{2} \cdot 1000 \cdot 3.6 \times 10^{-3} \text{ sec}^{-2} \cdot 1.2 \cdot .17 \text{m} \frac{(3m)^{3}}{3}$
= 3.3 newtons

Again more than enough force to provide the horizontal acceleration. The torque about the level of the brushes is

/ 3m

$$M'_{2} = \begin{cases} F_{2}(l)dl = 3/4 \cdot 3m \cdot F_{2} = 7.43 \text{ newton-meters.} \\ 0 \end{cases}$$

This torque can be transferred to the centre of mass by subtracting F_2 times the distance tetween the brushes and the centre of mass (1.6m). So the torque about the centre of mass due to the u² face is

$$M_2 = M_2' - F_2 \cdot 1.6m = 2.15$$
 newton-meters

The total torque $M_1 + M_2$ is 7newton-meters, what is the angle of tip? The centre of mass is .5m below the centre of buoyancy, equating the torque from the forces to the torque due to the stability of the instrument gives

7 newton-meters = 740 newtons $\cdot .5m \cdot sin\theta$ $\theta = 1.1^{\circ}$

This is probably an overestimate of the tip because the total force is 3 times that necessary to produce the horizontal acceleration. An estimate for the point of zero velocity 1m lower would produce

F
$$(2m) = \left(\frac{2 \cdot 3}{3 \cdot 3}\right)^2 F_1 = 1.53$$
 newtons
 $M_1(2m) = \left(\frac{2 \cdot 3}{3 \cdot 3}\right)^2 M_1 = 2.3$ newton-meters
 $F_2(2m) = \left(\frac{2}{3}\right)^3 F_2(3m) = 1$ newton
 $M_{\frac{1}{2}}(2m) = \left(\frac{2}{3}\right)^4 M_2(3m) - .6m F_2(2m) = .9$ newton-meters

Now the assumption that F'_2 and M'_2 can be calculated without including the contributions from the regions above point of zero velocity relative to the local water, becomes more suspect, in fact one might argue that a) $F'_2 \approx 0$ since we are now near the centre of the body and the force distribution is symmetric and that b) M'_2 should be doubled to 1.8 newtons. The roll of the brushes in the lateral force balance is difficult to assess. Their diameter is comparable to the cylinder but their projected area when viewed from the side is equivalent to .3 m length of the tube. They are designed to be effective drag elements in the vertical direction and not the horizontal. For a torque of 3.3 newton-meters. The tip of the instrument is

$$\theta = .51^{\circ}$$

Hence we can conclude that the tipping of the instrument is probably restricted to less than l^{0} even in the presence of fairly strong values of the local velocity shear.

There is another much more serious aspect of the problem and that is the question of the mean angle of attack of the total velocity vector. The problem arises because the velocity sensor used is a lift force sensor (see Osborn and Crawford 1977) and has a maximum angle of attack limitation somewhere in the 10° to 15° range. For the data collected at the equator the fall speed of the instrument was in the 40 to 45 cm/sec range. If the length scale for the distance between the nose probe and the point at rest with respect to the local water is 2 meters then the relative horizontal velocity at the nose is

$$u = 2 \text{ meters } \cdot \frac{\partial u}{\partial z} = 12 \text{ cm/sec}$$

for a large value of $\frac{\partial u}{\partial z} = .06 \text{ sec}^{-1}$. The mean angle of attack is then

$$\frac{12 \text{cm/sec}}{40 \text{cm/sec}} = \tan \alpha \rightarrow \alpha = 16.7^{\circ}$$

Thus the maximum angle of attack is almost certainly exceeded. The problem of large mean shears is much more serious when viewed in this context rather than the tipping problem. The easiest solution is to increase the

fall speed thereby reducing the angle of attack. Since the force producing the horizontal acceleration of the body is the aerodynamic lift force and that is linear in the fall speed, the body will continue to track the horizontal motion. The tipping will increase with speed since the dominant contributor to the torque is the lift force. Hence there is some middle ground where the relative effects cross over and an increase in speed is no longer any help. Removing the present salinometer, returning to the earlier configurations, would bring the probe closer to the point of no relative motion without significantly reducing the static stability, thereby reducing the effect of a large mean shear.

There is another aspect and that is the contamination of the measured velocity spectrum by the vibrations. The details are covered in Osborn and Crawford. It is sufficient for the discussion at hand to say that the turbulence signal is presently ($f_{vall} = 40$ to 55 cm/sec) in a lower frequency region of the spectrum than the contamination due to vibrations. Increasing the fall speed linearly increases the apparent frequency of the turbulence signals and unless steps are taken to avoid trouble the desired data can become contaminated by the unwanted vibration signal. The Camel was not designed with the vibration problem in mind. Some of the sources of noise have been reduced or eliminated (stiffening has doubled some resonant frequencies). The best solution is to be aware of the problem at the initial design stage and avoid shapes that are prone to vibration, such as weights at the ends of rods. The thermistor mount, the weight holders, and the salinometer system are major sources of noise in the present design.

Pumpkins

Work with the early instruments at the University of British Columbia indicated a need for a set of small, simple instruments to separate the temporal variations of the microstructure fluctuations from the spatial variations. The first instruments had a turn around time on the order of $\frac{1}{2}$ hour between successive drops. A series of drops with one of these instruments was very interesting but it was very difficult to relate fluctuations between profiles. What was needed was a set of instruments that could be dropped simultaneously with a given spatial separation or at different times in the same location. To be useful such a set of instruments should be simple, so that the chances are high that all of them will operate at once. The design problem reduces to the question of what is the 'minimum' instrument necessary to make useful microstructure measurements.

The decision was made to measure the microstructure and not just the fine structure as done by the simple instruments described by Osborn and Cox (1972) and Hacker (1973). The problem under investigation was: What are the time and space scales of thermal microstructure? An initial attempt was made to develop an instrument that telemetered the data up an XWL as a low frequency signal. The electronics in the probe consisted of a bridge and a differentiator, the outputs were added together and applied to the wire link. At the upper surface a set of electronics interpreted the low frequency fluctuations and drift as the temperature profile and the high frequency fluctuations as the temperature derivative. While the system could be made to function in the laboratory it never showed any signs of working in the field. The major problem was noise picked up by the wire link functioning as an antenna. On one trial, this instrument was lost (it is the only free-fall instrument still unrecovered) and the approach was abandoned. The decision was to make a set of electronics that measured temperature and temperature gradient and telemetered the data to the surface using two of the IRIG FM channels. The circuit is essentially the same as the Camel except for the gains and the fact that the bridge is not operated in an equal arm balanced configuration. Thus the output of the temperature channel is not a linear function of

the temperature. The advantage is that the gain of the temperature channel is greater by a factor approaching 2 for the same voltage across the thermistor gradient. The Camel was operatored in a configuration like this for local development work because the water is uniform to within just a few degrees below the thermocline. Therefore more gain was important and the poorer linearity was not a problem because the range was not as large as that seen in the open ocean. Power for the electronics is provided by four Eveready 216 (NEDA 1604) batteries. These are non-rechargeable alkaline cells.

....

Figure 7 shows a schematic drawing of one of the three Pumpkins that we built and operated. The floatation is provided by a Viny 103-12 plastic float. The instrument is designed so that even if the instrument housing floods there will be enough buoyancy (once the weights are released) to return the entire instrument to the surface.

The instrument consists of a float, a set of wings and a pressure case for the electronics. There is an OAR citizens band radio transmitter on the upper end for location on the surface. The wire link spool is mounted next to the radio, an empty spool is mounted on the other side of the radio to provide symmetry. The wings are from sonobuoys and can fold down about 45° for easier handling on deck. The release is a stretched pin Richardson-type, made of aluminum rather than the stainless steel used on the Camel. The acoustic pinger is a disposable model. The pressure case is made of stainless steel arc-welded together with an o-ring seal for the endcap. Steel was chosen for the pressure case because of fear of damage to an aluminum case. The connection to the thermistor is via an Electro-Oceanics bulkhead connector. The composite output telemetry signal is taken through the case with an Electro-Oceanics penetrator. The thermistor is soldered to an Electro-Oceanics male connector and the joint is epoxy encapsulated. The plug is mounted in the tube on the lower endcap and the connector inserted into the bulkhead connector. The design we had was inconvenient to mount and required the connector and thermistor to be potted together which was a time-consuming operation.

The electronics for the Pumpkins do not include a pressure transducer because of the restricted room in the pressure case and the desire to avoid the complexity of the added circuitry. Instead there was one circuit made that consisted of a Vibrotron pressure transducer and a rotation rate circuit - a coil wrapped around a permeable iron core. Drops made with this electronics are used to estimate the fall speed as a function of added weight. The final estimate of the fall speed is made by fitting the temperature profile measured by the Pumpkin against that measured with an STD. Remember the object of the study is to look at the horizontal extent of the microstructure patches so the exact depth is not crucial.

There is one operational problem that arose from this design that was unanticipated. During drops along the Equator in the Atlantic Ocean the current shear was so great that the fine copper wire from the XWLs was pulled sideways and the rotation of the Pumpkin wrapped the wire around the radio antenna, leading to premature breakage. This problem was cured by the addition of a loop at the top of the radio antenna to guide the wire safely above the aerial.

The fall rate and rotation rate of the Pumpkins as measured at the Equator in the Atlantic is summarized in Table VI. The rotation rate values are derived from analysis of the analog data telemetered up the wire. A more detailed digital analysis of the pressure data, including a spline fit as described earlier, was performed to calculate the fall speeds. Only one drop with each instrument using the pressure measuring electronics was performed along the Equator.

REFERENCES

Allen, H.J. and E.W. Perkins (1951) A study of effects of flow over slender inclined bodies of revolution. National Advisory Council for Aeronautics Report No. 1048.

. 2 2 .

- Brown, J.F. and C.S. Cox (1973) Design of light, cylindrical pressure cases. Engineering Journal 35-37.
- Bruce, J.G. and E.J. Katz (1976) Observations in the Equatorial Atlantic during GATE, June and July 1974 from Atlantis II. Woods Hole Oc. Inst. tech. rep. 76-54, 90pp.
- Caldwell, D.R., S.D. Wilcox and M. Matsler (1975) A relatively simple freelyfalling prove for small-scale temperature gradients. Limnology and Oceanography, 20, 1035-1042.
- Crawford, W.R. (1976) Turbulent energy dissipation in the Atlantic Equatorial Undercurrent. Ph. D. Thesis, Inst. of Oceanography, University of British Columbia, 149 pp.
- Drinkwater, K.F. (1973) The role of tidal mixing in Rupert and Holberg Inlets. M. Sc. Thesis, Inst. of Oceanography, University of British Columbia.58p.
- Elliott, J.A. and N.S. Oakey (1976) Spectrum of small-scale oceanic temperature gradients. JFRBC 33:10, 2296-2306.
- Galloway, J.L. (1974) Prototype of a continental shelf tide gauge. M. A. Sc. Thesis, Dept. of Electrical Engineering, Faculty of Applied Science, University of British Columbia, 73 pp.
- Gregg, M.C. and C.S. Cox (1971) Measurements of oceanic microstructure of temperature and electrical conductivity. Deep Sea Res. 18, 925-934.

Hacker, P.W. (1973) The mixing of heat deduced from temperature fine structure measurements in the Pacific Ocean and Lake Tahoe. Ph. D. Dissertation, University of California, San Diego, 121 pp.

Lamb, H. (1945) Hydrodynamics. 6th ed. Dover Publications, New York, N.Y.

Lueck, R.G., O. Hertzman and T.R. Osborn (1977) The spectral response of thermistors. In press Deep Sea Res.

Mortensen, A.C. and R.E. Lange ((1976) Design considerations of wing stabilized free-fall vehicles. Deep Sea Res. 23, 1231-1240.

Osborn, T.R. (1973) Temperature microstructure in Powell Lake. J. Phys. Oc. 3:3 302-307.

Osborn, T.R. (1974) Vertical profiling of velocity microstructure. J. Phys. Oc. 4:109-115.

Osborn T.R. and C.S. Cox (1972) Oceanic fine structure. Geophys. Fluid Dyn. 3:321-345. References (cont'd)

Osborn, T.R. and W.R. Crawford (1977) Turbulent velocity measurements with an airfoil probe. NATO Advanced Study Institute on Instruments and Methods in Air'Sea Interaction.

Reinsch, C.H. (1967) Smoothing by spline functions. Num. Math. 10:177-183.

- Sanford, T.B., R.G. Drever and J.H. Dunlap (1977) The design and performance of a free-fall electromagnetic velocity profiler (EMVP). In press Deep Sea Res.
- Simpson, J.H. (1972) A free fall probe for the measurement of velocity microstructure. Deep Sea Res. 19:331-336.
- Williams, A.J. (1974) Latching hook for instrumental retrieval. Ocean Engng 2:275.
- Williams, A.J. (1974) Free-sinking temperature and salinity profiler for ocean microstructure studies. IEEE International Conf. on Engng. in the Ocean Environment Record, Catalogue No. 74 CH0873-0 OCC 279-283.

APPENDIX I

A

.

...

Q.

2.2

- :

+ . .

First Instrument

Parameters measured:

- 1. Pressure;
- 2. Nose temperature;
- 3. Wing temperature;
- 4. Nose temperatures high pass filtered and amplified;
- 5. Wing temperature high pass filtered and amplified.

Sensors:

<u>Pressure</u>: Vibrotron pressure gauge BJ Electronics serial #5811. 0-500 psi range.

11

Temperature: Veco Z41A40 .058 cm glass probe.

Characteristics:

di la

Fall speed: Nominal 20-25 cm/sec.

Rotation rate: Nominal one revolution per nine seconds.

Second Instrument

1.

5

Parameters measured:

1.	Pressure;	
----	-----------	--

- 2. Nose temperature;
- 3. Wing temperature;
- Nose temperature gradient;
- 5. Wing temperature gradient;
- Electrical conductivity;
- 7. Electrical conductivity gradient;
- 8. Two horizontal velocity components;
- Time variation of the horizontal magnetic field component;
- 10. Time variation of the vertical magnetic field.

Sensors:

Vibrotron pressure gauge no serial number. 0-300 psi range. Pressure: BJ electronics #4193 - 0-1000 psi.

Temperature: Thermistor Veco 43A401C microbead thermistor coated with .016 mm of paralene-C by Sippican later Thermometics beads were used.

Electrical Conductivity: A series of inductive circuits and sensors were tried but none ever operated successfully. The circuitry was finally removed to concentrate on the velocity measurements.

Velocity:

Airfoil probes manufactured at 1.0.U.B.C.

See Osborn (1974) and Osborn & Crawford (1977) for details.

Characteristics: Fall speed: Nominal 20-25 cm/sec.

Rotation rate: Dependent on wings used .Up to 27 second period.

Third Instrument

"The Camel"

Parameters measured:

- 1. Pressure;
- 2. Nose temperature;
- Nose temperature gradient;
- Electrical conductivity;
- 5. Electrical Conductivity gradient;
- 6. Angular orientation of axis;
- 7. Horizontal velocity fluctuations.

Sensors:

1. Pressure: Vibrotron pressure gauges;

- (a) 300 psi gauge with no serial number;
- (b) BJ Electronics serial #4193. 0-1000 psi range;

1

- (c) BJ Electronics #5075. 0-500 psi range.
- Temperature: Microbeads manufactured by Thermometrics Inc. see "pumpkins" for details.
- 3. Electrical Conductivity: Modified Gregg & Cox type salinometer.
- 4. <u>Angular Orientation</u>: Flux gate compass manufactured on special order by N. Brown.
- <u>Velocity</u>: Air foil probes manufactured at 1.0.U.B.C. See Osborn
 & Crawford (1977) for details.

Characteristics:

- 1. Fall speed 40-55 cm/sec.
- 2. Rotation period greater than 200 sec.

Fourth Instrument

2 : .:

Bra

"The Pumpkins"

Parameters measured:

A. For Data:

- 1. Temperature;
- 2. Temperature gradient.
- B. For Calibration:
 - 3. Pressure;
 - 4. Rotation.

Sensors:

Temperature: Thermometrics microbead thermistors #BB05PB853N/A4^oC (special order) with .0007" paralene-C coating by Sippican.

Pressure: Vibrotron pressure gauge BJ Electronics, Serial #4191 0-1000 psi range.

Rotation: Coil wrapped around a permeable iron core.

Characteristics: Fall speed: Nominal 20 cm/sec. Rotation Rate: Nominal .2 hz (see Tabe VI).

LIST OF FIGURES

1. Schematic drawing of the first instrument.

- 2. Schematic drawing of the second instrument in the configuration used during the development of the velocity probe.
- a) Schematic drawing of the Camel before the inclusion of the salinometer mechanism.

b) Drawing of the Camel in its final configuration.

- 4. Schematic drawing of the salinometer mechanism showing the large low pressure air reservoir with the piston, spring, and bellows.
- 5. Block diagram of the Camel electronics.
- Attenuation of the XWL as a function of frequency and the amount of wire in the water.
- 7. Schematic drawing for a Pumpkin.

A Contract and a set

List of Tables

- 1. I.R.I.G. frequencies and band widths.
- Average speed and depth as derived from a series of successive leasts squares linear fit to 10.24 seconds of the pressure data from drop 15 in the Azores.
- Depth and fall speed as derived from the drop 15 pressure data using a cubic spline fit.
- . Calibration data for Vibrotron 4193 at
 - a) 19.8°C (increasing pressure) and 21°C (decreasing pressure); and,
 - b) 13°C (increasing pressure) and 12°C (decreasing pressure).

Table 4c is the frequency difference between the two calibrations as a function of pressure.

Spline fit to the pressure data from drop Spirit 7, Howe Sound, January, 1976.

5. Fall rate and rotation rate information for the three Pumpkins:

Pumpkin 1; b) Pumpkin 2; c) Pumpkin 3.







Figure 3a





Figure 4





Figure 6



Band	-7.5%	Centre Frequency	+7.5%	Modulation Frequency for ½db Attenuation.
1	370	400	430	6
2	518	560	602	8
3	675	730	785	11
4	888	. 960	1,032	14 -
5	1,202	1,300	1,398	20
6	1,572	1,700	1,828	25
7	2,127	2,300	2,473	35
8	2,775	3,000	3,225	45
9	3,607	3,900	4,193	59
10	4,995	5,400	5,805	81
11	6,799	7,350	7,901	110
12	9,712	10,500	11,288	160
13	13,412	14,500	15,588	220

Table 1

5.20922 5.20538	9.205.0	5.20022	1. Cler	5.20535	5.20825	5.21.42	5.212.0	5.21041	171143	5.21135	5.21254	10012.9	1.012.2	5.21104	5.21145	5.20523	5.212.4	22012.6		5+212-5	5.21051	5.2002	5.23645	5.20762	10. 10. 15 S	5.203.5	5.20015	12102.5	91601.6	11251.2	5.1031.5	11.1.6	5.20254	5.20345	5.201.16	5.1 503	19. ·										1
24 485.65521 61 454.86279 18 500.33374	51 505.28125 64 536 52417	30 515-72241	19 520-14 147	64 530.94560	d2 234.44751	50 541.50760 50 547.56420	70110.560 10	36 557.52075	34 902.012.03 31 505.05766	14 573.25171	22 276.59180	19 562.52400	14 565-57545	99 555.20570	10 604.28607	53216-202 94	36 015-12671	CH 2/ 5 . 020 17	14 420-24914	13 635.62018	10 640.65282	15115.319	90 651. J5064	15 656.15967	74 644 11018	16 071.15330	11 076.05750	45 686-35481 CA	81 091.4003	\$1414.353 89	10 761-4-01	00 101. LUICO	10 717.54555	19722.51757	56 726.16284	44 732.53115											
5.167 5.167	145.4 1	5.1.58	200.0	111.2	104.4 0	054.6 0	100.9 0	4.404	201.0	5.154	2 5.340	5.533	-18.4	5.243	5.317	4.925	119.5 5	0.240	1-5-146	151.6 8	5.212	1 5.025	5.153	5.103	2001	5.074	505.5	5.237	975.5	5.020	5.349	5.521	5.340	4.968	5.244	4. 708				ale II	-						
494.0466	12 209 . 07 3 74	520.26489	52.010°	530.0537	241.2605	552.03420	010.105	562.0710	1787.674	574.8347	583.425	269+2+65C	341 10 . 554	634.99341	010.32715	615.67993	623.63316	020.0324	031.402	1935.149	647.10020	055.2450	2061.169	663.13940	508000 12 9 2 9 9 000	679.01445	1255.980	064.84376	700.20343	7.05.4.0.78	710.00382	721.1605	720.00474	732.08658	137, 07768	1421.4 96 83				Tal							
5.20120 5.15847 5.20133	5.19684	5.15300 5.15300	11631.2	5.20603 5	5.20463	5.21413	5.15263	5.19789	5.16207	5.19+35	5.19543	5.19917	05051.6	5.20229	5.20171	5.20234	5-202.59	58102.0	5.20402	5-21:82	5.21361	5.21638	5.215.9	5.21809	5-22016	5.27545	5.22206	5.22690	5.22457	5.22662	5.22607	5.22157	5.2223		5.21621	5.21755	5. 21 60 H	5.21513	5.21500	5.21018	5.21359	5.21428	17612.6	5.21129	04002-5	5.21124	
177.04474 131.94650 187.24797	192.28310	202.55293	237.56401	216.07419	225.80580	224.63570	236.66348	244.30078	254-41168	259.71729	264.90734	270.35609	242242840	266.12022	291.29550	296.53369	301-75000	301.20221	212.0012	323.256.84	326.45776	333.00108	339.00073	344.35429	11400-010	360.56982	365-566-+3	376-34106	381.42261	386.77020	391.95557	24000-140	407.33574	412.5222	417.24680	422.62158	461.14676	+36.07080	443.27466	448.59180	453.58228	626.05009	464.10405	400-000000	470-77943	454.706.05	
5-34304 4-50177 5-30147	51 466. 6	5.02770	5.41183	5.30089	10201.5	5.45279	4.22700	5.45731	100110	5.30508	5.24976	5.30530	5-20010	5.32666	2.16989	5.25793	5.21032	17716-6	01 27 2 . 4 . 10	5-63164	5.20097	14004-5	5-12972	11242.0	000/2-5	5.00044	5.01030	5.30706	62180.5	5.34759	5.16533	24411-6	5.27320	5.18852	4.77467.	5.32473	5-12120	20167.5	10,02.2	5-31729	15055.4	5.27445	21232.0	001/2.5	201100 ···	5.42217	
173.71645 179.22556 164.22443	189.85359	200.53957	19600.007	210.510.12	241.91458	221.23070	258.32425	242.43042	21016119	254-54203	264.07471	269.43372	281-2-1068	245.57573	291.13565	290.42749	201.00066	201111119	01640.516	322.88159	323-56421	333.77000	339.++800	344.72192	87001 · · · · ·	000.01396	360.18462	+0120-110	362.78491	387.98291	343.59229	40041.446	409.26336	414.85138	420.30957	10555.424	430.11664	441.40503	446.62012	452.00024	457.51689	10100.204	401-2208	413.00004	400000000	408.57929	
							1							-			1:	Vfall	4.14941	4-50895	4.61 /58	4.62695	4.88011	4.95963	5.04418	5.00324	5.07850	5.04052	5.12727	5.12117	5.13571	5.15763	5.15242	5.15003	5.16318	5.17549	5. [424]	5.19703	5.20172	5.20205	5.21403	5.21410	5-22-38	5.100	2.20046	5.20105	
						•								•			: 5	ú Vfall	10	16201-6	13. 45273	19.36730	24.40057	24. 751 27	19:02-19	45.50918	50.18563	09414-06	66.45451	71. 69644	77.0300	87.44150	62455.55	04210.35	19500.501	138.6536	114.24451	124-74312	130.64292	135.33144	140-16004	145.446.8	151-151	156.45513	101/2/201	111.101.111	
		•						•										VEALL	m/ sec. x	01850-0	4.65483	10001.0	5.09278	9-35724	5 440.15	5.17658	4. 717 · C	2.15411	5.54830	5.04195	5.33916	2. Le194	2.15604	5.27358	5.64902	5. 42185	91 200 - 0	50100-6	5.29932	5.25852	10344.0	2.61034	84902.4	2.10005	51+15-4	2.44125	
		•	:	•••	1													Jenth m		170921	20100-0	11631.1	0911-11	0921+-23		60349.P	1091200	02001-6	J.4.J262	0.13673	1.39210	0.10101	30901-1		40644.66	30.1.15d55	5010.4	04201-01	00211.0	05051.11	10.40499	12.12000	1.30726	10440.00	000000000	.9.45deb.	

00000		[000]	10000	10000	0002	00001	10002	10000	10101	10000	10000	00000	0.0000	00000	1 01 00	00000	50505	0000			-			•		•	*		•																	
0.51520 -0. 0.51520 -0. 0.51518 0.	0.51521 0.	C.51538 U.	0.51551 0.	0.51504 0.	0.51595 0.	0.51610 0.	0.51425 0.	0.51640 0.	C.51652 U.	0.51662 0.	0. 51676 0	0.51680 0.	0.51682 U.	0.51641 -3.	0.51679 -0.	0.51670 -0.	0-21216-0	0-51667 -0.		all the second s						ble III	•									<u></u>										
6215-92603 621-20215 626-47754	631.75317	642.30615	641.20423	052. d0353	0200 142725	668.71118	613.99683	474.28344	684. 21251	669. 36233	C0761.640	70957-607	711.02808	710.32331	721.61255	120. 104 30	111.4464	742.11134								Ta																				
0.00004 0.00004 0.00003	C.COCO3	C. 00003	C. LCOP3	C. CC002	6-60001	L. CCC3C	-0.0000	-0.60.01	-0.0002	-0.0003	-0 100104	-0-0000	- C. CJJJ7	-0.000.08	-0.10108	- 6. 63 308	-0-10108	-0.00.07	-u.cuuu7	-0.00337	-0-0000	- 4. 600.15	-0.0004	-0.0003	-0.0002	-0.00.02	-0-00000-	C. 60001	0.0001	C.CO002	0.0002	C. CORO3	C. C3003	0.00003	0.00022	0.0002	0.0001	-0.0000	10:000.0-	10.000.0-	-0.0002	-0.0002	-0.1002	-0.0.02		-0.0002
0.52412 6.52450 0.52467	0.52521	0.52586	0.226.15	0.52641	0-52674	0.52661	0.52680	C. 52e71	0.52652	0.52624	0 53530	182429-1	0.52414	0.52339	0. 5258	0.52175	14020-0	0.51452	0.51857	0.51/60	0.51119	0-51604	74510.	61515-0	06415-0	0.51469	0-51453	0.51455	0.51463	0.51477	0.51518	0.51544	17414.0	0-51627	0.51652	0.51674	0.51701	0.51703	0.51659	0.51690	0.51659	0.51638	0.51615	0.51592	0.7214.0	24313.0
. 246.11.153 302.08667 307.45947	312.03509	325.59688	325.94011	324. 31427	345.15418	7262.045	355.94300	301. 34204	306.73402	372.12476	21116-116	HALL VILLE	343.64.209	359.00562	404. 30084	11011.14	62010-014	425.04873	431.01140	436.31836	76/10-144	422.10/75	67614-164	402. 75705	468.33131	413.30249	410.51221	484.11011	494.37939	645.64540	513.19529	515.47314	520. 75269	16400.6.153	147(0.065	541.07019	552.45438	18371.77841	563.C7300	508.36040	578.94171	584.23853	569.54215	62903.494	c00.04131	60110.509
Acceleration		0.0	6.01.02	C.COC03		C. 696.05	6. C C O F		c.couc.c	6. 00004	0.0004	0.0000	0.0001	0° ((()))	- C. 60330	10001-0-		-6-6004	-4.43395	-0.00006	-6. 00007	-6.(0.08	-0-00-04	-0.0036	-0. 6000B	-6.0008	-0.00008	- C. JJJJe	-6.40005	-0.00004	-0.0003	-0.00))2	-0.6002	-0.0001	-0.0000	0.0000	0.0001	0.0003	0.0004	C. (4005	0.03035	(1- bar at	C. CCLOT	6.6005	J. 10.05	6.001 US
Vfall	units.	0132010	C. 52522	0.22547	C100.00	0. 52665	C. 2743	1. 166.73	1.2554	L 503	69675-0	1053C.0	0.014	C. 1 JC33	C. 13:332	L. 1 302 1	0. 5 1005	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0.12458	0.42943	L	1123.0	C457.11	17452.0	U. 22385	9.5259.0	0.52216	17052.0	C.54015	C. 51568	16515-0	0.5166)	0.21862	0.51540	0.51834	0.51432	0-51647	0.51667	00513.0	6.515.3	96514°C	C. 107	0. 164	C /20	9. 473	0
Derth	symaric c	1-24224	C. 12545	12.33629	0100011	23.44319	33. 30.07	34.20245	44.67435	51460 00	BCC10.00	1.1.1.1.1	11.74633	71. 22247	9664336	8. J'sle	06114	104. 40162	100.70015	115.19475	140.00278	111 - 14745	136-12349	142.16069	147.52930	152.005 18	1042-5415	150.11.50	174.24162	179.57140	164.85132	155.54686	64360.002	211-42141	216.72934	222. 00699	234.06318	237.49326	243.33602	244. 54266	12:36.567	104-1 (1-10)	407.9400	275.40711	200.03/21	205.99243

Vibrotron Calibration #4193

Ambient Temperature	19.8°c		Temperature 21.0 ⁰ C
0 PS1 50 100 150 200 250 300 350 400 450 500 550 600 650 700 750 800 850 900 950	f 15.3282 KHz 15.2411 15.1533 15.0653 14.9761 14.8868 14.7970 14.7074 14.6159 14.5233 14.4309 14.3377 14.2436 14.1482 14.0543 13.9585 13.8618 13.7644 13.6665 13.5678 12.5678 13.5678 13.5678	Δf -87.1 -88.8 -88.0 89.2 89.3 89.8 89.6 91.5 92.6 92.4 93.2 94.1 95.4 93.9 95.8 96.7 97.4 97.9 98.7 99.8	Δf 15.3269 15.239587.4 15.151687.9 15.064387.3 14.9754 14.9754 14.9754 14.7959 14.8860 89.4 14.7959 90.1 14.7053 90.6 14.6141 ³ 91.2 14.5223 91.8 14.4297 92.6 14.3361 93.6 14.2421 94.0 14.1468 95.3 14.0529 93.9 13.9573 95.6 13.8610 96.3 13.7637 97.3 13.6660 97.7 13.5672 98.8 12.4679 99.3
1,000	13.4680	JJ.0	13.46/9
Ambient Temperature	Vibrotron Ser 13 ⁰ C	ial #4193	Temperature 12 ⁰ C
•	f	Δf	Δf
0 PS1 50 100 150 200 250 300 350 400 450 550 600 650 700 750 800 850 900 950 1.000	15.3228 KHz 15.2373 15.1498 15.0615 14.9732 14.8843 14.7944 14.7038 14.6129 14.5213 14.4288 14.3361 14.2417 14.1485 14.0558 13.9577 13.8616 13.7648 13.6664 13.5679 13.4687	-85.5 -87.5 -88.3 87.3 88.9 90.6 90.9 91.6 92.5 92.7 94.4 93.2 94.7 97.1 96.1 96.1 96.8 98.4 98.5 99.2	15.3228 15.2357 15.1484 15.0602 14.9716 88.6 14.9716 88.6 14.9716 89.2 14.7927 98.4 14.7023 98.4 14.7023 98.4 14.7023 98.4 14.7023 98.4 14.7023 98.4 14.7023 98.4 14.2397 92.0 14.4277 92.0 14.3340 93.7 14.2394 92.9 14.1465 92.9 14.0517 94.8 13.9563 95.4 13.8602 96.1 13.6661 97.7 13.6661 97.7 13.6677 98.4 13.4688 98.9

Table IVb

. .

.

Pressure	Δf		
Psi	Hz		
0	5.4	580	1.6
50	3.8	600	1.4
100	3.5	680	.3
150	3.8	700	.5
200	2.9	750	.8
250	2.5	800	.2
300	2.6	880	.4
350	3.6	900	.1
400	3.0	950	.1
450	2.0	1000	.7
500	2.1		

5.

1...

Table IVc

•	•					•	•			•										: .*							•	
														!								•						
									-																			
																				Table V	4.5							
			- C. CCC04 - C. CCC04 - C. CCC04		-6.0004	-0.0004	-0.00003	-c.ccc01 c.ccc0	C.CCC01 C.CCC01	C. CCC02	C. CCCC2 C. CCCC2	C.CC002	C. CCCO1 C. CCCO1	C. CC001	0.00001	C. CCC00	C. CCOCO	C.CCUU0				•		•				
		•	0.55534 0.55513 0.55513	0.00	0.55404	C. 55364	10000	0.55312	0.55311	0.555355	0.55345	0.55364	0.55378	0.55383	0.55350	0.55394	0.55395	0.55396										
		- # :	148.32063 151.16338 154.00500	156.025566	165.35079	171.02210	176-65565	182.35441 165.19620	186.02814	192.65263	199.25852	205.02727	207-86206 210-65734	213-53276	\$15-20435	224-57648	227.71274	233.38524										
		ACCEL.	C. CCC00 C. CCC00 C. CC003		C.CCC10	C. CCC14	0.00016	C.CCU18 C.CCC18	C.CCC18 C.CCC18	C. CCC1 7	C. CCU15	C.CC013	C. CCC12 C. CC011	0.0010		0.0000	C.CCUG6	C.CCC4	C. CCCC2	c.ccccl c.ccccl	C.CCCC0	-0.00001	-0.00001	- 6. 60602	-0.0000	-01010-	+0.0000	-6.60004
		SPEEC ks units 0.53566	C.52467 0.53572 D.53572	0.54031	C.54116	0.54235	0.54354	0.54569 C.5466C	0.54152	C.5453C	0.55094	0.55738	C. 55303 O. 55362	0.55417	0.55512		0.55(19	0.55667	C.55695	C.55703	0.55768	C.55707 C.557C3	C-55657	0.55678	0.55050	C.55616	7.25252 7.25257	5111110
		CEPTH 10.03252	12.82562 15.55865 15.355865	23.85256	25.42934	34.57678 34.57678	40.53556	41.11736	51.71458	57-23641	(2.96364	66.61307	71.44252	77.11151	82.79163	£5.49C12	c1.32766	51.02505	102.72694	105.57875	111-29210	114.13535	115.93932	124.54176	11 24162	136 3572	17661 251	11 41676
	-			4 - 4 - 2		,																						

and see before me

CEPTH	SPEED	ACCEL	-
meters	meters/sec	meters/sec ²	
-8.56102	C. 19001	C.C	
-6.04349	0.18973	-C.CCCC6	
-3.14141	0.18776	-0.00020	
-C. 28576	0.18388	-C.CC28	
2.50539	0.17959	-C.CC027	
5.23427	C.175E7	-0.00021	
7.91288	C.173C8	-C.CC15	
10.55629	0.17128	-C.CCCC9	
13.17939	C.17C43	-(.((003	-
15.79596	C.17C38	C.CCC02	1- 2+
18.41602	0.17084	0.00004	
21.04556	0.17159	C.CCC5	
23.68790	0.17249	C.CCC06	
26.34540	0.17357	C. CCCC8	
29.C2054	C.17476	80000.0	
31.71385	0.17594	80000.0	
34.42545	0.17714	C. CCCC8	
37.15634	0.17847	C.CCC09	
35.90504	C.17557	C.CC010	
42.68614	C.18167	C.CCC12	
45.49121	0.18362	C.CC014	
48.32819	C.18583	C.CCC15	
51.20059	0.18826	C. CCC16	
54.11169	0.19073	C.CO016	
57.05952	0.19307	C.CC015	
60.04175	0.19519	C.COC13	
63.05440	0.19701	C.CO010	
66.09138	0.15833	C.CCCC7	
69.14421	0.19911	C.CC0C4	
72.20609	0.19953	C. CCCC2	
75.27298	0.15578	C.CCCC1	
78.34251	0.19989	C.C0000	
81.41316	C. 19992	C. (C C C C O	

Rotation period 5.1seconds

Table Vla

	DEPTH	SPEEC	ACCEL.	
	meters	meters/sec	meters/sec ²	
	-C.7C479	0.17926	C. C	
	2.96830	C.17559	·C.CC0C4	
	6.65870	0.18058	0.0009	
	10.38455	C.18289	C. CCCC8	
	14.14557	0.18422	C.CCCC4	
	17.92438	C.18468	C. CC001	
	21.70630	0.18460	-C.CCCC1	
	25.48738	0.18476	0.0003	
	29.28139	C.18592	C.CCCC8	5
	33.10783	0.18784	C.CC010	,
	36.57670	C.18956	0.00010	
	40.88565	0.15167	C.CCCC7	
	44.82274	0.19270	C.CCC03	
	48.77504	0.15324	C. C0002	
	52.73759	0.15373	C.CCC02	
	56.7(929	0.15408	C.CC001	
	66.68358	0.19392	-C. CCCC3	
	64.64723	0.19304	-C.CCCC6	
	68.58575	0.19146	-C.COO10	
	72.48441	C.18915	-C.CCC13	
	76.32916	0.18624	-C.CCC15	
	80.11241	C.1833C	-0.00013	
	83.84303	C.18124	-C.CCCC7	
	87.54626	0.18666	C.C0001	
	\$1.25273	C.18145	C.CCCC7	
	\$4.58636	0.18321	C. ((C))	
	\$8.75867	0.18517	· C.CCC09	
•	102.569(2	C.18686	C.CCCC7	
	166.40878	0.18801	C.CCCC4	
	110.26616	0.18860	C.C0002	
	114.13089	C.18877	C. CCCCO	
	117.99681	0.18875	-C.CCCCO	
	121.86154	C.1887C	-C.CCCCC	
	125.72600	0.18866	-C.CCCCO	
	129.58965	0.18865	00003.0	

: ;

Rotation period 4.8seconds

Table VIb