

AD-A051 353

AIR FORCE ARMAMENT LAB EGLIN AFB FLA  
THE EFFECTS OF GBU-15 CRUCIFORM WING WEAPON CANARD SIZING ON TH--ETC(U)  
NOV 76



F/G 1/3

UNCLASSIFIED

AFATL-TR-76-140

NL

| OF |  
AD  
A051 353



END  
DATE  
FILMED  
4-78  
DDC



AFATL-TR-76-140


1

Nov 76

AD-A051353

# THE EFFECTS OF GBU-15 CRUCIFORM WING WEAPON CANARD SIZING ON THE DRAG AND LONGITUDINAL STABILITY OF THE F-4 AIRCRAFT

AIRCRAFT COMPATIBILITY BRANCH  
MUNITIONS DIVISION



NOVEMBER 1976

FINAL REPORT: JANUARY 1976-NOVEMBER 1976

Approved for public release; distribution unlimited

## AIR FORCE ARMAMENT LABORATORY

AIR FORCE SYSTEMS COMMAND • UNITED STATES AIR FORCE

EGLIN AIR FORCE BASE, FLORIDA



REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM										
1. REPORT NUMBER AFATL-TR-76-140 <sup>✓</sup>	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER										
4. TITLE (and Subtitle) THE EFFECTS OF GBU-15 CRUCIFORM WING WEAPON CANARD SIZING ON THE DRAG AND LONGITUDINAL STABILITY OF THE F-4 AIRCRAFT		5. TYPE OF REPORT & PERIOD COVERED FINAL REPORT January 1976 - November 1976										
		6. PERFORMING ORG. REPORT NUMBER										
7. AUTHOR(s)		8. CONTRACT OR GRANT NUMBER(s)										
9. PERFORMING ORGANIZATION NAME AND ADDRESS Aircraft Compatibility Branch (DLJC) Munitions Division Air Force Armament Laboratory <sup>✓</sup>		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Program Element 62602F JON 2567-02-16										
11. CONTROLLING OFFICE NAME AND ADDRESS Air Force Armament Laboratory Armament Development and Test Center Eglin Air Force Base FL 32542		12. REPORT DATE November 1976										
		13. NUMBER OF PAGES 30										
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report)  UNCLASSIFIED										
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE										
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited		<table border="1"> <tr> <td colspan="2">ADDITIONAL</td> </tr> <tr> <td>NTIS</td> <td>Write Section <input checked="" type="checkbox"/></td> </tr> <tr> <td>DDI</td> <td>Ref Section <input type="checkbox"/></td> </tr> <tr> <td colspan="2">UNANNOUNCED <input type="checkbox"/></td> </tr> <tr> <td colspan="2">JUSTIFICATION</td> </tr> </table>	ADDITIONAL		NTIS	Write Section <input checked="" type="checkbox"/>	DDI	Ref Section <input type="checkbox"/>	UNANNOUNCED <input type="checkbox"/>		JUSTIFICATION	
ADDITIONAL												
NTIS	Write Section <input checked="" type="checkbox"/>											
DDI	Ref Section <input type="checkbox"/>											
UNANNOUNCED <input type="checkbox"/>												
JUSTIFICATION												
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		<table border="1"> <tr> <td>BY</td> <td colspan="2">DISTRIBUTION/AVAILABILITY CODES</td> </tr> <tr> <td>Dist.</td> <td>AVAIL.</td> <td>and/or SPECIAL</td> </tr> <tr> <td>A</td> <td></td> <td></td> </tr> </table>	BY	DISTRIBUTION/AVAILABILITY CODES		Dist.	AVAIL.	and/or SPECIAL	A			
BY	DISTRIBUTION/AVAILABILITY CODES											
Dist.	AVAIL.	and/or SPECIAL										
A												
18. SUPPLEMENTARY NOTES  Available in DDC.												
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) GBU-15 Cruciform Wing Weapon (CWW) Canards F-4 Aircraft Stability Index Number System												
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) An aerodynamic analysis has been conducted for carriage of two designs of GBU-15 CWW's on the F-4 aircraft. The analysis was to determine the effects of the GBU-15 Cruciform Wing Weapon (CWW) canard sizing on the drag and longitudinal stability of the F-4 aircraft. The GBU-15 CWW canard redesign from a 46-inch span to a 29-inch span canard equated to a Drag Index reduction, per GBU-15 CWW, of 2.6. The Stability Index Number, per GBU-15 CWW, was reduced by approximately 50 percent.												


PREFACE

This report documents the GBU-15 Cruciform Wing Weapon canard sizing effects on the drag and longitudinal stability of the F-4 aircraft. Captain Jack L. Kincart (DLJC) served as project engineer for the study. The study was initiated in June 1976 and was completed in November 1976.

This report has been reviewed by the Information Officer (OI) and is releasable to the National Technical Information Service (NTIS). At NTIS it will be available to the general public, including foreign nations.

This report has been reviewed and is approved for publication.

FOR THE COMMANDER



WILLIAM F. BROCKMAN, Colonel, USAF  
Chief, Munitions Division

TABLE OF CONTENTS

Section	Title	Page
I	INTRODUCTION . . . . .	1
II	DATA ANALYSIS . . . . .	3
III	CONCLUSIONS . . . . .	5
References		6

LIST OF FIGURES

Figure	Title	Page
1	F-4C Model with GBU-15 Cruciform Wing Weapon (Large Canards) and 370-Gallon Fuel Tanks . . . . .	7
2	F-4C Model with GBU-15 Cruciform Wing Weapon (Small Canards) and 370-Gallon Fuel Tanks . . . . .	8
3	Details and Dimensions of the GBU-15 Cruciform Wing Weapon (Large Canard) Wind Tunnel Model . . . . .	9
4	Details and Dimensions of the GBU-15 Cruciform Wing Weapon (Small Canard) Wind Tunnel Model . . . . .	10
5	Incremental Trim Angle of Attack Versus Mach Number, H = Sea Level . . . . .	11
6	Incremental Trim Angle of Attack Versus Mach Number, H = 10,000 Feet . . . . .	12
7	Incremental Trim Angle of Attack Versus Mach Number, H = 20,000 Feet . . . . .	13
8	Incremental Trim Angle of Attack Versus Mach Number, H = 30,000 Feet . . . . .	14
9	Incremental Stabilator Angle to Trim Versus Mach Number, H = Sea Level . . . . .	15
10	Incremental Stabilator Angle to Trim Versus Mach Number, H = 10,000 Feet . . . . .	16
11	Incremental Stabilator Angle to Trim Versus Mach Number, H = 20,000 Feet . . . . .	17
12	Incremental Stabilator Angle to Trim Versus Mach Number, H = 30,000 Feet . . . . .	18
13	Incremental Trim Drag Coefficient Versus Mach Number, H = Sea Level . . . . .	19
14	Incremental Trim Drag Coefficient Versus Mach Number, H = 10,000 Feet . . . . .	20
15	Incremental Trim Drag Coefficient Versus Mach Number, H = 20,000 Feet . . . . .	21
16	Incremental Trim Drag Coefficient Versus Mach Number, H = 30,000 Feet . . . . .	22
17	Neutral Point Versus Mach Number, H = Sea Level . .	23
18	Neutral Point Versus Mach Number, H = 10,000 Feet .	24
19	Neutral Point Versus Mach Number, H = 20,000 Feet .	25
20	Neutral Point Versus Mach Number, H = 30,000 Feet .	26

LIST OF ABBREVIATIONS, ACRONYMS AND SYMBOLS

$C_{D_T}$	Aircraft trim drag coefficient, $\frac{\text{drag}}{q_\infty S}$
cg	Center-of-gravity location, percent MAC
CWW	Cruciform Wing Weapon
DI	Drag Index, $\Delta C_D \times 10 \times S$
Drag Count	Drag Coefficient x 10,000
H	Altitude, feet
M	Free Stream Mach number
MAC	Theoretical Mean Aerodynamic Chord
NP	Neutral Point location, percent MAC
$q_\infty$	Free stream dynamic pressure
S	Wing reference area, 530 square feet
SIN	Stability Index Number
$\alpha_{W_T}$	Wing chord angle of attack at trim conditions, deg
$\delta_{S_T}$	Stabilator angle of attack at trim conditions, deg
$\Delta\alpha_{W_T}$	Incremental trim wing angle of attack, deg
$\Delta\delta_{S_T}$	Incremental trim stabilator angle, deg

## SECTION I

### INTRODUCTION

In recent years, nonnuclear weapon design has evolved from the conventional unguided stores such as dispensers, firebombs, and general purpose bombs to highly sophisticated guided weapon systems. Many of these systems incorporate laser or electro-optical guidance packages, autopilots, and movable wing/canard/tail combinations for free flight maneuvering. Examples of the sophisticated weapon systems are the GBU-15 Planar Wing Weapon (PWW), GBU-15 Cruciform Wing Weapon (CWW) and the Pavestorm I and II.

Many problems have been found with the guided weapons when investigating all aspects of aircraft/store compatibility. Typical problem areas have been with store separation (Reference 1), store mounting, and degradations to aircraft stability. This report will deal with one aspect of the problems that can arise with the new sophisticated guided weapon systems, that is, degradations to performance and stability due to carriage of the GBU-15 CWW on the F-4 aircraft.

The initial design of the GBU-15 CWW was configured with 51-inch span canards and 59-inch span wing assembly in the carriage position. This design of the GBU-15 CWW proved to exhibit unsafe separation characteristics from the F-4 aircraft. A second iteration redesign of the canards and further analysis proved that the 31-inch span canard GBU-15 CWW exhibited safe separation characteristics from the F-4 aircraft (Reference 1).

This report is a subsequent performance and stability analysis of the initial and redesigned GBU-15 CWW on the F-4 aircraft. The purpose of this report is to determine and compare the effects on longitudinal stability and drag characteristics of the F-4 aircraft due to carriage of the large canard GBU-15 CWW (Figure 1) and the small canard GBU-15 CWW (Figure 2). Data were utilized from two separate wind tunnel force tests to determine the degradations in longitudinal stability and drag characteristics. Both tests were conducted in the Aerodynamic Wind Tunnel (4T) of the AEDC Propulsion Wind Tunnel Facility utilizing 0.05 scale models. The 0.05 scale model of the large canard GBU-15 CWW varied from the initial design. The wind tunnel model was scaled for 46-inch span canards and 61-inch span wing assembly (Figure 3). The initial design incorporated 51-inch span canards and 59-inch span wing assembly. The 0.05 scale model of the small canard GBU-15 CWW also varied from the second iteration design. The wind tunnel model was scaled for 29-inch span canards and 61-inch span wing assembly, whereas, the second iteration design had 31-inch span canards and 59-inch span wing assembly (Figure 4). As shown in Figures 1 and 2, the small canard GBU-15 CWW wind tunnel model had faired leading edges of the canards and



wings. The large canard GBU-15 CWW wind tunnel model did not. However, for the purpose of this analysis, and the conclusions that will be discussed later, the differences are not important. Further details of the wind tunnel tests can be found in References 2 and 3.

It should be noted that carriage of the GBU-15 CWW on the F-4C/D aircraft is possible; it has been determined that Stability Index Numbers and Drag Indexes for a particular store are the same on the F-4C/D/E models (References 4 and 5).

## SECTION II

### DATA ANALYSIS

The data analysis assumed a representative F-4 gross weight of 52,300 pounds. The trimmed aerodynamic characteristics were determined for altitudes of sea level, 10,000, 20,000, and 30,000 feet from wind tunnel data referenced to a cg location of 33 percent of the theoretical mean aerodynamic chord (MAC). The Mach numbers range from 0.6 to 1.3. The wind tunnel data in this report are corrected to full scale F-4 aircraft.

Figures 5 through 16 present incremental aerodynamic trim conditions versus Mach number and altitude. The baseline configuration was the F-4 with two 370-gallon wing tanks and two armament pylons. Two sets of data are presented on each figure. One set of data, labeled small canards, are the increments due to the GBU-15 CWW with small canards, and likewise for the set of data labeled large canards. Figures 17 through 20 present total aircraft neutral point location versus Mach number and altitude. Two sets of data are presented on each figure. One set of data, labeled small canards, is the F-4 aircraft with 370-gallon wing tanks on stations 1 and 9 and the GBU-15 CWW (small canards) with MAU-12B/A pylons on stations 2 and 8. All other stations are empty. The second set of data presented, labeled large canards, is the same except that the GBU-15 CWW (large canards) are substituted on stations 2 and 8. Any increments between the two curves in each figure, therefore, are due only to the canard sizing on the GBU-15 CWW.

Figures 5 through 16 are the incremental trim angle of attack, incremental stabilator angle to trim and incremental trim drag coefficient versus Mach number curves. Incremental trim drag coefficient versus Mach number and altitude curves are presented in Figures 13 through 16. As illustrated in these figures, the incremental trim drag coefficient was slightly decreased by the smaller canards. The average decrease in drag was about 10 drag counts for the normal flight envelope of the F-4 aircraft. Ten drag counts equate to a Drag Index of 5.3. As a comparison, the Drag Index of a MK82 LDGP is 1.1.

Figures 17 through 20 present neutral point versus Mach number and altitude. As seen in these figures, the F-4 aircraft is considerably more stable in the longitudinal plane subsonically with the small canard GBU-15 CWW. Depending upon Mach number and altitude, the aircraft neutral point for carriage of the small canard GBU-15 CWW was 1 to 5 percent MAC further aft of the aircraft neutral point for the large canard GBU-15 CWW. In the transonic region, at 10,000 and 20,000 feet, the neutral point of the aircraft with both GBU-15 CWW designs fluctuated such that neither had a clear advantage over the other. It was only at sea level and 30,000 feet altitude that the aircraft neutral point with the small canard GBU-15 CWW was consistently aft (more stable) of the aircraft neutral point with the

large canard GBU-15 CWW. Supersonic data for the smaller canard GBU-15 CWW extended to only  $M = 1.1$ , therefore, a thorough comparison to the large canard GBU-15 CWW could not be made. However, the trends from transonic to  $M = 1.1$  clearly indicate that the aircraft neutral point with the smaller canard GBU-15 CWW is aft of the aircraft neutral point with the large canard GBU-15 CWW.

For an example to relate to the Stability Index Number System (SIN), an F-4 configuration of two 370-gallon wing tanks and two GBU-15 CWW's was investigated. From the data in Figure 19, the aircraft neutral point location with the large canard GBU-15 CWW is 31.3 percent MAC for  $M = 0.85$ . This neutral point equates to a SIN of 277.5 for the total aircraft. Subtracting SIN's for the two armament pylons and two wing tank/pylon combinations from 277.5 and dividing by two, gives a SIN for one large canard GBU-15 CWW of about 102. From the same figure and Mach number, the corresponding aircraft neutral point location with the small canard GBU-15 CWW is 33 percent MAC. Thirty-three percent MAC equates to a total aircraft SIN of 168.8. Following the identical steps explained above, the SIN for one small canard GBU-15 CWW is 47.5. In effect, the redesign of the canards decreased the SIN of the GBU-15 CWW by over 50 percent. For a more thorough examination of the SIN system and Drag Index system, refer to Reference 6.

### SECTION III

#### CONCLUSIONS

The aerodynamic analysis of the effects of the wind tunnel model canard redesign on the drag and longitudinal stability of the F-4 aircraft has resulted in the following conclusions:

(a) The incremental drag of one GBU-15 CWW was improved by a Drag Index of approximately 2.6.

(b) The longitudinal stability of the F-4 was greatly improved by the smaller canards. Depending upon the altitude, the GBU-15 CWW Stability Index Number was reduced by approximately 50 percent at  $M = 0.85$ .

(c) The final, and most important conclusion, is that weapon designers must take into consideration the aircraft/store compatibility problems associated with the various design trends of modern nonnuclear guided weapons. As illustrated in this report, and noted in Reference 4, weapon designs have a very large impact on all aspects of aircraft/store compatibility. Design changes that affect store aerodynamics could significantly affect weapon separation characteristics or aircraft performance, stability or control.

#### REFERENCES

1. Mathews, C. B., Captain Cason, R. D., Captain McGirr, P. G., Lt Carreras, E. M., "A Technique for Investigating the Launch and Separation of Guided Weapons." Paper presented to the Joint Technical Coordinating Group for Munitions Development (JTTCG/ME) Working Party No. 12 Symposium on Aircraft/Stores Compatibility, 2 - 4 September 1975.
2. Whoric, J. M., Effect of Various External Stores on the Aerodynamic Characteristics of the F-4 Aircraft, AEDC-TR-74-75 (AD787657), AFATL-TR-74-113, October 1974.
3. Washington, E. S., Effect of the GBU-15 (Cruciform Wing) and the GBU-15 (Planar Wing) Stores on the Aerodynamic Characteristics of the F-4C Aircraft. AEDC-TR-75-116, AFATL-TR-75-111, November 1975.
4. TO 1F-4C-1, Appendix A, Part 1, 1 December 1975.
5. TO 1F-4E-1, Appendix A, Part 1, 1 December 1975.
6. Pliske, D. R., Hammer, R. A., Hollingsworth, W. B., et al, Model F-4, External Stores Installed Characteristics, McDonnell/Douglas Corporation Report Number MDC A0815, 1 August 1974.




Figure 1. F-4C Model With GBU-15 Cruciform Wing Weapon (Large Canards) and 370-Gallon Fuel Tanks




Figure 2. F-4C Model With GBU-15 Cruciform Wing Weapon  
and 370-Gallon Fuel Tanks




Figure 3. Details and Dimensions of the GBU-15 Cruciform Wing Weapon  
(Large Canard) Wind Tunnel Model






Figure 4. Details and Dimensions of the GBU-15 Cruciform Wing Weapon  
(Small Canards) Wind Tunnel Model




Figure 5. Incremental Trim Angle of Attack Versus Mach Number, H = Sea Level




Figure 6. Incremental Trim Angle of Attack Versus Mach Number, H = 10,000 Feet




Figure 7. Incremental Trim Angle of Attack Versus Mach Number,  $H = 20,000$  Feet




Figure 8. Incremental Trim Angle of Attack Versus Mach Number, H = 30,000 Feet




Figure 9. Incremental Stabilator Angle to Trim Versus Mach Number, H = Sea Level




Figure 10. Incremental Stabilator Angle to Trim Versus Mach Number, H = 10,000 Feet




Figure 11. Incremental Stabilator Angle to Trim Versus Mach Number, H = 20,000 Feet






Figure 12. Incremental Stabilator Angle to Trim Versus Mach Number, H = 30,000 Feet




Figure 13. Incremental Trim Drag Coefficient Versus Mach Number, H = Sea Level




Figure 14. Incremental Trim Drag Coefficient Versus Mach Number, H = 10,000 Feet




Figure 15. Incremental Trim Drag Coefficient Versus Mach Number,  $H = 20,000$  Feet




Figure 16. Incremental Trim Drag Coefficient Versus Mach Number, H = 30,000 Feet

$\Delta C_{D_T}$




Figure 17. Neutral Point Versus Mach Number, H = Sea Level




Figure 18. Neutral Point Versus Mach Number, H = 10,000 Feet




Figure 19. Neutral Point Versus Mach Number, H = 20,000 Feet






Figure 20. Neutral Point Versus Mach Number, H = 30,000 Feet

INITIAL DISTRIBUTION

HQ USAF/SAMI	1
AFIS/INTA	1
ASD/ENFEA	1
OGDEN ALC/MMWM	2
TAWC/TRADOCLO	1
AFATL/DL	1
AFATL/DLOSL	9
AFATL/DLJC	20
TAC/INA	1
ASD/XRP	1
HQ TAC/DRA	1
HQ USAFE/DOQ	1
HQ PACAF/DOO	1