

AD-A051 627

CALIFORNIA UNIV SAN DIEGO LA JOLLA DEPT OF APPLIED M--ETC F/6 20/11  
ON TWO- AND THREE-DIMENSIONAL RESULTS FOR ROTATIONALLY SYMMETRI--ETC(U)  
NOV 77 S NAIR, E REISSNER

N00014-75-C-0158


NL

UNCLASSIFIED

| OF |  
AD  
A051 627



END  
DATE  
FILMED  
4-78  
DDC



MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

10

UNIVERSITY OF CALIFORNIA, SAN DIEGO  
Department of Applied Mechanics and Engineering Sciences  
La Jolla, California 92093

ADA 051627

AU NO. [unclear]  
DDC FILE COPY

6 ON TWO- AND THREE-DIMENSIONAL RESULTS FOR  
ROTATIONALLY SYMMETRIC DEFORMATIONS OF  
CIRCULAR CYLINDRICAL SHELLS

10 by S. Nair and E. Reissner

9 *Interim rept.*



11 Nov 1977

12 34p.

DDC  
RECEIVED  
MAR 23 1978  
B

Prepared for  
OFFICE OF NAVAL RESEARCH  
Washington, D. C.

15 NP44-75-C-0158

DISTRIBUTION STATEMENT A  
Approved for public release;  
Distribution Unlimited

407 513

mt

ON TWO- AND THREE-DIMENSIONAL RESULTS  
FOR ROTATIONALLY SYMMETRIC DEFORMATIONS  
OF CIRCULAR CYLINDRICAL SHELLS

by

S. Nair and E. Reissner

Department of Applied Mechanics and Engineering Sciences  
UNIVERSITY OF CALIFORNIA, SAN DIEGO  
La Jolla, California 92093

ABSTRACT

Previous considerations by asymptotic expansion procedures of the relation between elasticity theory results and thin-shell theory results for the case of rotationally symmetric deformations of an edge-loaded semi-infinite circular cylindrical shell are supplemented by an analysis of this problem for a shell possessing a limiting-type orthotropy, such that transverse normal strains vanish identically. It is shown that assuming this kind of orthotropy has the important benefit of allowing the derivation of exact expressions for the edge zone solution contribution, when such exact expressions are not possible for the problem of the shell with more general properties of the material. —One result of our analysis is an answer to the following question. Given a shell with arbitrarily prescribed edge displacements, what is the asymptotically exact form of the corresponding conditions for this same problem, treated within the framework of two-dimensional thin-shell theory?

---

† A report on work supported by the Office of Naval Research, Washington, D.C.

ON TWO- AND THREE-DIMENSIONAL RESULTS  
FOR ROTATIONALLY SYMMETRIC DEFORMATIONS  
OF CIRCULAR CYLINDRICAL SHELLS

S. Nair and E. Reissner

INTRODUCTION

We return once more to the problem of rotationally symmetric deformations of a semi-infinite circular cylindrical shell as the simplest non-trivial example of the relation between three-dimensional elasticity-theory analysis and two-dimensional thin shell-theory analysis. The first paper on this subject [1] considered the problem of the asymptotic determination of a class of "interior" solutions for the given three-dimensional boundary value problem and the derivation therefrom of a system of two-dimensional shell-theory equations including the formulation of shell-theory boundary condition statements from given three-dimensional elasticity-theory statements of such conditions, for the case that these conditions were stress boundary conditions. A subsequent paper by Reiss [2] extended this work by considering complete asymptotic solutions, including interior solutions and "edge-zone" solution contributions. The results obtained in this manner confirmed the conclusions in [1] in regard to the problem of two-dimensional shell theory, while at the same time supplying significant additional insights in regard to the nature of the relation between two- and three-dimensional theory, with these insights having meanwhile been extended and generalized in important ways by various other workers, in particular by Goldenweiser [3].

One of the difficulties encountered in the use of an edge-zone solution contribution, as done by Reiss [2], consists in the fact that the relevant two-dimensional boundary value problem for a bi-harmonic function defined in a semi-infinite strip cannot, for some important cases including the case of pure traction conditions and of pure displacement conditions be solved in closed form, and to the extent that this is the case the asymptotic results which are obtained remain approximate rather than exact.

BY		
DISTRIBUTION/AVAILABILITY CODES		
Dist.	AVAIL.	and/or SPECIAL
A		

Given the impossibility of a closed-form solution of the relevant bi-harmonic problem, as well as the apparent absence of results for the case of pure displacement edge condition cases, we have recently considered the complete problem by combining interior asymptotic expansions, Rayleigh-Ritz type edge-zone solution contributions, and upper and lower bound formulas through use of the principles of minimum potential and complementary energies [4]. The principal results of this analysis consisted in the derivation of upper and lower bounds for the values of influence coefficients involved in the solution of the semi-infinite circular cylindrical shell problem with prescribed edge tractions or prescribed edge displacements. All of these bound results were such as to imply the determination of exact results for the solution of the three-dimensional problem by means of two-dimensional theory, insofar as the leading terms in an expansion of the solution of the three-dimensional problem in powers of wall thickness  $h$  to shell radius ratio  $a$  were concerned. We also determined supplementary terms for such an expansion, of relative order  $h/a$  (including terms of order  $(h/a)^{\frac{1}{2}}$  which are encountered for some classes of edge conditions), with these supplementary bound terms being such that in some cases there was coincidence between upper and lower bound results so that, in effect, a determination of exact results, up to terms of relative order  $h/a$ , was accomplished.

In order to understand the meaning of these results, as well as the significance of the analysis which follows it is convenient to interpret the leading-term results as exact results for an infinitely-thin shell (that is, for a shell for which  $h/a \rightarrow 0$ ), with the supplementary terms representing the effects of finite thickness. There are altogether three distinct effects of finite thickness. The first of these is a geometrical effect, having to do with the change of width of shell elements with distance from the middle surface (so that this effect is absent for the special case of a flat plate). It is known that this effect is taken account of properly (assuming absence of the other

two) in a refined two-dimensional shell theory associated with the names of Flügge, Lurie and Byrne. The second effect is the effect of transverse normal stress deformability (which is absent for the case of a limiting-type orthotropic material unable to sustain transverse normal strains). It has earlier been shown that this effect is of the same order of magnitude as the geometrical FLB effect [1], and our recent work [4] indicates that for some classes of edge condition this effect comes out to be of relative order  $(h/a)^{\frac{1}{2}}$  (without these terms being of numerical significance, however, in comparison with the co-existing  $h/a$ -order effects).

The third of the effects of finite thickness is the effect of transverse shear deformability. This effect too comes out to be of relative order  $h/a$ . We are not concerned here with the consequences of this effect, in regard to the order of the differential-equation system and to the number of the associated boundary conditions, as discussed most simply in recent work dealing with the subject of plates [5]. Rather, we are concerned with this effect from the point of view of its relative numerical dominance in comparison with the other two, as revealed by our upper and lower bound calculations [4].

Having previously obtained upper and lower bound results for the three effects of geometry, transverse normal stress deformability, and transverse shear deformability, with these three effects being additive up to orders of magnitude which are of primary interest, we now undertake an asymptotic analysis of two of the three effects, these being the effects of transverse shear deformability and of geometry. Our analysis is based on recognition of the fact that it is possible to derive exact solutions for the two-dimensional semi-infinite strip problem governing the edge-zone solution contribution, upon assuming a limiting-type orthotropy in such a manner that transverse normal strains vanish identically.

Having the existence of these exact solutions for the edge-zone contributions involved in the asymptotic expansion procedure, we are now in a position to verify and, in principle, to refine the results of our upper and lower bound analysis. Beyond this, we are able to obtain

results for types of boundary conditions which do not fall within the scope of the indicated bound solutions. To mention a specific example, our analysis permits us to solve a problem which has long been of interest to us but for which until now no rational solution has come to our attention. The problem is as follows. Given a semi-infinite circular cylindrical shell, with arbitrarily prescribed edge displacements as loading conditions. To be determined is the asymptotically exact form of the corresponding conditions of the first-order interior solution contribution, to wit the appropriate form of the corresponding boundary conditions for this same problem, treated within the frame work of standard two-dimensional thin shell theory.

### FORMULATION OF THE PROBLEM

We take as differential equation for symmetrical deformations of circular cylindrical bodies a system consisting of the equilibrium equations

$$r\sigma_{x,x} + (r\tau)_{,r} = 0, \quad r\tau_{,x} + (r\sigma_r)_{,r} - \sigma_\theta = 0, \quad (2.1)$$

in conjunction with stress strain (displacement) relations of the form

$$u_{,x} = \frac{\sigma_x - \nu\sigma_\theta}{E} - \nu_r \frac{\sigma_r}{E_m}, \quad \frac{v}{r} = \frac{\sigma_\theta - \nu\sigma_x}{E} - \nu_r \frac{\sigma_r}{E_m},$$

$$v_{,r} = \frac{\sigma_r}{E_r} - \nu_r \frac{\sigma_x + \sigma_\theta}{E_m}, \quad u_{,r} + v_{,x} = \frac{\tau}{G}, \quad (2.2)$$

where  $E_m = (EE_r)^{\frac{1}{2}}$ , with positive  $E$ ,  $E_r$  and  $G$ , and with the additional strain energy positive-definiteness conditions  $\nu^2 < 1$  and  $2\nu_r^2 < 1 - \nu$ .

The system (2.1) and (2.2) is to be solved in the region  $0 \leq x < \infty$ ,  $a - c \leq r \leq a + c$  subject to face boundary conditions

$$r = a \pm c: \quad \sigma_r = 0, \quad \tau = 0, \quad (2.3)$$

subject to edge boundary conditions "at infinity" which for all cases are taken in the form

$$x \rightarrow \infty: \quad u = 0, \quad v = 0 \quad (2.4)$$

and subject to edge boundary conditions at the loaded edge of the shell, of the form

$$x = 0: \begin{cases} u_{,r} = \bar{u}_{,r} , & \text{or} & \sigma_x = \bar{\sigma}_x , \\ v = \bar{v} , & \text{or} & \tau = \bar{\tau} , \end{cases} \quad (2.5)$$

with the right hand sides in these four relations being prescribed functions of  $r$ , subject only to the restriction that  $\int_{a-c}^{a+c} (r/a) \bar{\sigma}_x dr = 0$ .

Within the frame work of the above class of three-dimensional problems (which because of the assumed absence of any  $\theta$ -dependence of the solutions formally reduce to a class of two-dimensional problems) we are particularly concerned in asymptotic reductions to two-dimensionality (with this reduction here formally to one-dimensionality) for the determination of the weighted stress averages

$$M_x = \int_{a-c}^{a+c} (r/a) \sigma_r (r-a) dr , \quad Q = \int_{a-c}^{a+c} (r/a) \tau dr \quad (2.6)$$

and for the determination of displacement measures such as,

$$V = v(x, 0) , \quad \beta = u_{,r}(x, 0) , \quad (2.7)$$

with these reductions being of technical significance for "sufficiently small" values of the wall thickness-diameter ratio  $c/a$  of the shell.

In association with the derivation of a system of two (here one) -dimensional differential equations for the quantities  $M_x$ ,  $Q$ ,  $V$ ,  $\beta$  it is necessary to also derive a system of suitable edge conditions, involving the functions  $\bar{u}_{,r}$ ,  $\bar{v}$ ,  $\bar{\sigma}_x$ ,  $\bar{\tau}$  which appear in equations (2.5). One expects, and this has been shown to be true in [1] and [2], that insofar as the traction condition portions in (2.5) are concerned the equivalent lower-dimensional edge conditions are of the form

$$x = 0: \quad M_x = \bar{M}_x , \quad Q = \bar{Q} \quad (2.8a)$$

with  $\bar{M}_x$  and  $\bar{Q}$  defined in terms of  $\bar{\sigma}_x$  and  $\bar{\tau}$  in accordance with equations (2.6).

One also expects, and this is generally considered to be correct, that when the displacement condition portions in equations (2.5) are such that  $\bar{u}_{,r}$

as well as  $\bar{v}$  are independent of  $r$ , then the equivalent lower-dimensional edge conditions are of the form

$$x = 0: \quad V = \bar{v}, \quad \beta = \bar{u}_{,r}. \quad (2.8b)$$

We will, in what follows, re-confirm the asymptotic validity of the above expectation, within the frame work of the restrictions associated with the nature of the analysis which is here carried out. Over and above this result, however, we will establish the form of the edge conditions for "effective" measures  $V$  and  $\beta$ , not necessarily identical with these measures as defined in equations (2.7), which are valid in the event that  $\bar{u}_{,r}$  and  $\bar{v}$  are other than independent of  $r$ . An example of this nature which will be considered explicitly is the case where  $\bar{u}$  is assumed to be proportional to  $(r - a)^3$  in place of the usually assumed linear distribution.

#### DIFFERENTIAL EQUATIONS AND BOUNDARY CONDITIONS FOR TRANSVERSELY INEXTENSIONAL DEFORMATIONS

The case of transversely inextensional deformations is given upon setting

$$E_r = \infty \quad (3.1)$$

in the stress strain relations (2.2). These may therewith be written in the form

$$\begin{aligned} E u_{,x} &= \sigma_x - \nu \sigma_\theta, & E r^{-1} v &= \sigma_\theta - \nu \sigma_x, \\ v_{,r} &= 0, & G(u_{,r} + v_{,x}) &= \tau, \end{aligned} \quad (3.2)$$

where it will be assumed from here on that  $E$ ,  $\nu$  and  $G$  are independent of  $x$  and  $r$ .

Our first conclusion is now that the transverse displacement component does not vary across the thickness,

$$v = V(x) \quad (3.3)$$

and that, associated therewith, the transverse normal stress component  $\sigma_r$  assumes the character of a reactive quantity.

In order to solve the remaining boundary value problem, we begin by satisfying the first of the equilibrium equations (2.1) by means of a stress

function  $\Psi$ , in the form

$$r\sigma_x = a\Psi_{,r}, \quad r\tau = -a\Psi_{,x}, \quad (3.4)$$

where the factor  $a$  on the right hand side has been introduced to make the writing of some of the developments which follow somewhat more convenient.

We next use the second of the stress strain relations (3.2), in conjunction with equation (3.3) in order to write for the circumferential normal stress,

$$r\sigma_\theta = \nu a\Psi_{,r} + EV. \quad (3.5)$$

With the above expressions for  $\sigma_\theta$  and  $\tau$ , we obtain from the second equilibrium equation in (2.1) as an expression for the transverse normal stress  $\sigma_r$  which satisfies the condition of vanishing  $\sigma_r$  for  $r = a - c$ ,

$$r\sigma_r = a \int_{a-c}^r (\Psi_{,xx} + \nu r^{-1} \Psi_{,r}) dr + EV \int_{a-c}^r r^{-1} dr. \quad (3.6)$$

The condition that  $\sigma_r$  must also vanish for  $r = a+c$  gives as one of two equations connecting the two functions  $\Psi(x, r)$  and  $V(x)$

$$\int_{a-c}^{a+c} (\Psi_{,xx} + \frac{\nu}{r} \Psi_{,r}) dr + \frac{EV}{a} \ln \frac{a+c}{a-c} = 0. \quad (3.7)$$

A second equation connecting  $\Psi$  and  $V$  follows upon expressing  $u_{,r}$  in terms of  $\Psi$  and  $V$  in accordance with the last relation in (3.2), in conjunction with (3.3) and (3.4), as

$$u_{,r} = -V_{,x} - \frac{a}{r} \frac{\Psi_{,r}}{G}, \quad (3.8)$$

and by combining this result with the first relation in (3.2), written in the form  $Eu_{,xr} = \sigma_{x,r} - \nu\sigma_{\theta,r}$ , with  $\sigma_x$  and  $\sigma_\theta$  taken from equations (3.4) and (3.5). The ensuing differential equation may be written in the form

$$\frac{1 - \nu^2}{E} \left( \Psi_{,rr} - \frac{\Psi_{,r}}{r} \right) + \frac{1}{G} \Psi_{,xx} + \frac{r}{a} V_{,xx} + \frac{\nu}{ra} V = 0. \quad (3.9)$$

Having equations (3.7) and (3.9) it remains to state boundary conditions in terms of  $\Psi$  and  $V$ , in accordance with the remaining face boundary conditions

in (2.3), which concern  $\tau$ , and in accordance with the edge conditions as stated in Eqs. (2.4) and (2.5).

We begin by satisfying the edge condition at infinity by stipulating

$$\Psi(\infty, r) = 0, \quad V(\infty) = 0. \quad (3.10)$$

With this, and with observation of the relation  $\int_{a-c}^{a+c} (r/a)\sigma_x dr = 0$ , the face boundary conditions  $\tau(x, a \pm c) = 0$  take on the form

$$\Psi(x, a \pm c) = 0. \quad (3.11)$$

Finally, the conditions (2.5) for the loaded edge of the shell become

$$x = 0: \left\{ \begin{array}{l} V_{,x} + \frac{a}{G} \frac{\Psi_{,x}}{r} = -\bar{u}_{,r} \quad \text{or} \quad \frac{\Psi_{,r}}{r} = \frac{\bar{\sigma}_x}{a}, \\ \\ V = \bar{V} \quad \text{or} \quad \int_{a-c}^{a+c} \Psi_{,r} dr = -\bar{Q}. \end{array} \right. \quad (3.12)$$

We note that in writing the second set of conditions in (3.12), we have taken account of the fact that the assumed properties of the material require that the prescribed transverse displacement  $\bar{v}$  be independent of  $r$  and so may be written, in consistent fashion, as  $\bar{V}$ , and that at the same time this specialization of properties implies a sensitivity of the medium to the resultant  $\bar{Q}$  of the edge stresses  $\bar{\tau}$  only, rather than to the details of a prescribed  $\bar{\tau}$ -distribution.

#### STIFFNESS AND FLEXIBILITY COEFFICIENTS

In accordance with our earlier work in [4], we define general stiffness coefficients  $K$ , with reference to the problem of prescribed edge displacements, for the case that  $\bar{u}_{,r} = -\beta_0$  and  $\bar{V} = -V_0$ , by means of relations of the form

$$M_x(0) = K_{\beta\beta}\beta_0 - K_{\beta V}V_0, \quad Q(0) = K_{VV}V_0 - K_{V\beta}\beta_0, \quad (4.1)$$

where  $K_{V\beta} = K_{\beta V}$ .

At the same time we define a specialized system of such coefficients for mixed edge condition problems, as follows

$$\begin{aligned}
 M_x(0) &= K_\beta \beta_o \quad (\text{when } \bar{\tau} = 0) \quad , \\
 Q(0) &= K_V V_o \quad (\text{when } \bar{\sigma}_x = 0) \quad .
 \end{aligned}
 \tag{4.2}$$

Insofar as the problem of prescribed edge tractions is concerned, we have earlier [4] defined flexibility coefficients  $C$  with reference to traction distributions  $(r/a)\bar{\sigma}_x = (3M_o/2c^3)(r-a)$  and  $(r/a)\bar{\tau} = (3Q_o/4c)[1 - (r-a)^2/c^2]$ , and weighted edge displacement averages

$$\beta_o^* = -\frac{3}{4c} \int_{a-c}^{a+c} \left[ 1 - \frac{(r-a)^2}{c^2} \right] u_{,r} dr \quad , \quad V_o^* = -\frac{3}{4c} \int_{a-c}^{a+c} \left[ 1 - \frac{(r-a)^2}{c^2} \right] v dr \quad , \tag{4.3}$$

in the form

$$\beta_o^* = C_{MM} M_o + C_{MQ} Q_o \quad , \quad V_o^* = C_{QM} M_o + C_{QQ} Q_o \quad , \tag{4.4}$$

with these relations being "nearly" the inverses of equations (4.1), upon the identifications  $\beta_o^* = \beta_o$ ,  $V_o^* = V_o$ ,  $M_x(0) = M_o$  and  $Q(0) = Q_o$ .

The principal aim in [4] was the deduction of upper and lower bounds for the coefficients  $K$  and  $C$ , with these bounds depending on the geometrical parameter  $c/a$ , as well as on the materials property parameters  $E$ ,  $E/G$ ,  $E/E_r$ ,  $\nu$  and  $\nu_r$ . Among the characteristics of these bound relations the following are noteworthy.

1. In the limit  $c/a \rightarrow 0$ , our upper and lower bound values coincide with each other and with the corresponding values of what may be called first-approximation classical thin shell theory results.

2. For sufficiently small finite values of  $c/a$  our bound values involve additive terms of relative order  $(c/a)^{\frac{1}{2}}$  and of relative order  $c/a$ . The terms of order  $(c/a)^{\frac{1}{2}}$  represent transverse normal strain effects alone, while the terms of order  $c/a$  represent transverse normal strain effects, as well as transverse shearing strain effects, and also geometrical effects of the Flügge-Lurie-Byrne type. The numerically dominant of these three effects is the transverse shearing strain effect, even though this effect does not contain any  $(c/a)^{\frac{1}{2}}$ -contributions.

Insofar as the determination of stiffness and flexibility coefficients is concerned the present analysis enables us to obtain exact values of all

contributions of relative orders  $(c/a)^{\frac{1}{2}}$  and  $c/a$  (as well as exact values of contributions of higher order in  $c/a$  should we so desire) subject only to the restriction  $E_r = \infty$ . While it is possible to do this for the entire set of ten coefficients defined in equations (4.1) to (4.4), the necessary analysis will be carried out in what follows only to the extent of obtaining expressions for  $K_{\beta\beta}$ ,  $K_{V\beta}$  and  $K_{\beta}$ .

#### THE NON-DIMENSIONALIZED BOUNDARY VALUE PROBLEM

We introduce a non-dimensional axial coordinate  $\xi$  and a nondimensional radial coordinate  $\eta$ , measured from the middle surface of the shell, by writing

$$x = b\xi, \quad r = a + c\eta, \quad (5.1)$$

with  $b$  being in the nature of a characteristic length, to be chosen presently.

We further set

$$(1 - \nu^2)\Psi = E\Psi_0 g(\xi, \eta), \quad V = V_0 F(\xi), \quad (5.2)$$

where  $\Psi_0$  and  $V_0$  remain to be chosen, and we define dimensionless parameters  $\rho$  and  $\alpha$  in the form

$$\rho = c/a, \quad (1 - \nu^2)\alpha^2 = E/G. \quad (5.3)$$

Indicating now differentiations with respect to  $\xi$  and  $\eta$  by primes and dots, respectively, the two differential equations (3.7) and (3.9) for  $\Psi$  and  $V$  take on the following form

$$\Psi_0 \int_{-1}^1 \left[ \frac{c^2}{b^2} g'' + \frac{\rho^2}{(1 + \rho\eta)^2} g \right] d\eta + V_0 [(1 - \nu^2)\rho \frac{1 + \rho}{1 - \rho} F] = 0 \quad (5.4)$$

$$\Psi_0 \left[ g'' - \frac{\rho}{1 + \rho\eta} g' + \alpha^2 \frac{c^2}{b^2} g \right] + V_0 \left[ \frac{c^2}{b^2} (1 + \rho\eta) F'' + \frac{\nu\rho^2}{1 + \rho\eta} F \right] = 0. \quad (5.5)$$

At the same time the face boundary conditions (3.11) become

$$g(\xi, \pm 1) = 0, \quad (5.6)$$

and the edge boundary conditions at infinity become

$$g(\infty, \eta) = 0, \quad F(\infty) = 0. \quad (5.7)$$

Insofar as the boundary conditions (3.12) at the loaded edge are concerned, we will limit ourselves in what follows to the consideration of just two of a total of eight possible cases, both of them concerning problems with prescribed axial displacements as expressed in terms of the slope function  $\bar{u}_{,r}$ , with the other condition being the displacement condition of vanishing  $\bar{V}$ , or the traction condition of vanishing  $\bar{Q}$ . Expressed in terms of  $g$  and  $F$  this set of conditions takes on the form

$$\frac{\Psi_0}{b} \frac{\alpha^2}{1 + \rho\eta} g'(0, \eta) + \frac{V_0}{b} F'(0) = -\bar{u}_{,r} \quad (5.8)$$

$$F(0) = 0 \quad \text{or} \quad \int_{-1}^1 g'(0, \eta) d\eta = 0 \quad (5.9)$$

Expressions for the stresses  $\sigma_x$ ,  $\tau$ ,  $\sigma_\theta$ , and for the stress resultant  $Q$  and the stress couple  $M_x$  follow from equations (3.4), (3.5) and (2.6) as

$$\sigma_x = \frac{E}{1 - \nu^2} \frac{\Psi_0}{c} \frac{g'}{1 + \rho\eta} \quad , \quad \tau = -\frac{E}{1 - \nu^2} \frac{\Psi_0}{b} \frac{g'}{1 + \rho\eta} \quad (5.10)$$

$$\sigma_\theta = E \frac{V_0}{a} \frac{F}{1 + \rho\eta} + \frac{E}{1 - \nu^2} \frac{\Psi_0}{c} \frac{\nu g'}{1 + \rho\eta} \quad (5.11)$$

$$M_x = -\frac{E\Psi_0 c}{1 - \nu^2} \int_{-1}^1 g d\eta \quad , \quad Q = -\frac{E}{\nu^2} \frac{\Psi_0 c}{b} \int_{-1}^1 g' d\eta \quad (5.12)$$

We list additionally as expression for the circumferential stress resultant

$$N_\theta = \int_{a-c}^{a+c} \sigma_\theta dr,$$

$$N_\theta = EV_0 \rho \frac{1 + \rho}{1 - \rho} F - \frac{E\Psi_0 \rho}{1 - \nu^2} \int_{-1}^1 \frac{\nu g d\eta}{(1 + \rho\eta)^2} \quad (5.13)$$

and we shall not concern ourselves, in what follows, with the complementary expressions for  $\sigma_r$  and  $M_\theta$ .

#### INTERIOR AND EDGE ZONE SOLUTION CONTRIBUTIONS

We accept as known the fact that the solution to be obtained will, for sufficiently small values of  $\rho$ , be composed of two contributions, one of them

being an "interior" contribution  $g_i, F_i$ , with characteristic length  $b = b_i = (ac)^{\frac{1}{2}}$  and the other an "edge zone" contribution  $g_e, F_e$ , with characteristic length  $b = b_e = c$ . We note that in this way  $F_i = F_i(\xi_i)$  and  $F_e = F_e(\xi_e)$ , etc., but we shall refrain from making the distinction between  $\xi_i$  and  $\xi_e$  explicit, as this will cause no difficulty as the analysis proceeds. With  $\xi_i, \xi_e$  and  $\eta$  defined in this manner, and in view of the form of the differential equations and boundary conditions for  $\Psi$  and  $F$ , we are in a position to stipulate the basic order of magnitude relations

$$g_i, g_e, F_i, F_e, g_i', g_e', g_i'', g_e'', F_i', F_e' = O(1) \quad , \quad (6.1)$$

and we shall write, in place of equations (5.2), so as to make the distinction between the two solution contributions explicit

$$(1 - \nu^2)\Psi = E(\Psi_i g_i + \Psi_e g_e) \quad , \quad V = V_i F_i + V_e F_e \quad , \quad (6.2)$$

with the form of the two differential equations for the set  $g_i, F_i$  and for the set  $g_e, F_e$  being distinct, to the extent that this is required to account for the difference between  $b_i$  and  $b_e$ .

Setting  $b = b_i = (ac)^{\frac{1}{2}}$ , we obtain from equations (5.4) and (5.5)

$$\Psi_i \rho \int_{-1}^1 [g_i'' + \frac{\nu \rho}{(1 + \rho \eta)^2} g_i] d\eta + V_i \rho^2 [\frac{1 - \nu^2}{\rho} \frac{1 + \rho}{1 - \rho} F_i] = 0 \quad , \quad (6.3)$$

$$\Psi_i [g_i'' - \frac{\rho}{1 + \rho \eta} g_i' + \alpha^2 \rho g_i''] + V_i \rho [(1 + \rho \eta) F_i'' + \frac{\nu \rho}{1 + \rho \eta} F_i] = 0 \quad . \quad (6.4)$$

Setting  $b = b_e = c$ , we obtain instead

$$\Psi_e \int_{-1}^1 [g_e'' + \frac{\nu \rho^2}{(1 + \rho \eta)^2} g_e] d\eta + V_e \rho^2 [\frac{1 - \nu^2}{\rho} \frac{1 + \rho}{1 - \rho} F_e] = 0 \quad , \quad (6.5)$$

$$\Psi_e [g_e'' - \frac{\rho}{1 + \rho \eta} g_e' + \alpha^2 g_e''] + V_e [(1 + \rho \eta) F_e'' + \frac{\nu \rho^2}{1 + \rho \eta} F_e] = 0 \quad . \quad (6.6)$$

In view of the difference between  $\xi_i$  and  $\xi_e$ , the functions  $g_i$  and  $g_e$  must

individually satisfy the face boundary conditions

$$\eta = \pm 1: \quad g_i = 0, \quad g_e = 0, \quad (6.7)$$

and for the same reason the edge conditions at infinity (5.7) must be satisfied individually,

$$\xi = \infty: \quad g_i = 0, \quad g_e = 0, \quad F_i = 0, \quad F_e = 0. \quad (6.8)$$

With  $g_i$  and  $F_i$ , and  $g_e$  and  $F_e$ , so far being subject to a system of uncoupled requirements, there remains only the system edge loading conditions (5.8) and (5.9) to accomplish the necessary coupling for the determination of the two sets of functions. We find that equations (5.8), again with  $b_i = (ac)^{\frac{1}{2}}$  and  $b_e = c$ , takes on the form

$$\frac{\alpha^2}{1 + \rho\eta} [\Psi_i \rho^{\frac{1}{2}} g_i'(0, \eta) + \Psi_e g_e'(0, \eta)] + V_i \rho^{\frac{1}{2}} F_i'(0) + V_e F_e'(0) = -c\bar{u}_{,r}, \quad (6.9)$$

and equations (5.9) take on the form

$$V_i F_i(0) + V_e F_e(0) = 0, \quad (6.10a)$$

or

$$\int_{-1}^1 [\Psi_i \rho^{\frac{1}{2}} g_i'(0, \eta) + \Psi_e g_e'(0, \eta)] d\eta = 0. \quad (6.10b)$$

Having the relations (6.2) to (6.10) our next step is an appropriate disposition of the four scale factors  $\Psi_i, \Psi_e, V_i, V_e$ . We begin by observing that in order to be able to satisfy the face boundary conditions (6.7) in such a way that not only the functions  $g_i$  and  $g_e$ , but also the functions  $F_i$  and  $F_e$  are involved it will be necessary to have the terms with  $g''$  in equations (6.4) and (6.6) of the same order of magnitude as the terms with  $F''$  in these equations. Accordingly, we get

$$\Psi_i = \rho V_i, \quad \Psi_e = V_e. \quad (6.11)$$

Introduction of (6.11) into the edge conditions (6.9) and (6.10) then gives further

$$V_i \rho^{\frac{1}{2}} [F_i'(0) + \frac{\alpha^2 \rho}{1 + \rho \eta} g_i'(0, \eta)] + V_e [F_e'(0) + \frac{\alpha^2}{1 + \rho \eta} g_e'(0, \eta)] = -c \bar{u}_{,r} , \quad (6.12)$$

with (6.10a) remaining unchanged, and equation (6.10b) assuming the form

$$\int_{-1}^1 [V_i \rho^{\frac{3}{2}} g_i'(0, \eta) + V_e g_e'(0, \eta)] d\eta = 0 . \quad (6.13)$$

Having equation (6.12), we now impose the requirement that both interior and edge-zone solution contributions participate in the satisfaction of this non-homogeneous edge condition. This means that we must have

$$V_i \rho^{\frac{1}{2}} = V_e . \quad (6.14)$$

Finally, we introduce a weighted average,  $\beta$ , of the variation of edge rotations in thickness direction by writing

$$\bar{u}_{,r} = -\beta s(\eta) , \quad (6.15)$$

with

$$\int_{-1}^1 (1 - \eta^2) s(\eta) d\eta = \frac{4}{3} , \quad \beta = -\frac{3}{4} \int_{-1}^1 (1 - \eta^2) \bar{u}_{,r} d\eta , \quad (6.16)$$

(so that  $\beta = \beta_0$  when  $\bar{u}_{,r} = -\beta_0 = \text{const.}$ ).

With (6.14) and (6.15) and with the further stipulation that

$$V_e = c\beta , \quad (6.17)$$

the nonhomogeneous edge condition appears now in the form

$$F_i'(0) + \frac{\alpha^2 \rho}{1 + \rho \eta} g_i'(0, \eta) + F_e'(0) + \frac{\alpha^2}{1 + \rho \eta} g_e'(0, \eta) = s(\eta) \quad (6.18)$$

and the homogeneous edge conditions (6.13) and (6.10a) become

$$F_i(0) + \rho^{\frac{1}{2}} F_e(0) = 0 , \quad (6.19a)$$

or

$$\int_{-1}^1 [\rho g_i'(0, \eta) + g_e'(0, \eta)] d\eta = 0 . \quad (6.19b)$$

Equations (6.18) and (6.19) are to be used in conjunction with the consequences of introducing (6.11) into equations (6.3) to (6.6), that is in conjunction with two systems which may be written in the form

$$\int_{-1}^1 g_i'' d\eta + \frac{1-\nu^2}{\rho} \ln \frac{1+\rho}{1-\rho} F_i + \rho \int_{-1}^1 \frac{\nu g_i d\eta}{(1+\rho\eta)^2} = 0 \quad (6.20)$$

$$g_i'' + F_i'' + \rho \left[ \alpha^2 g_i'' + \eta F_i'' - \frac{g_i' - \nu F_i'}{1+\rho\eta} \right] = 0 ,$$

and

$$\int_{-1}^1 g_e'' d\eta + \rho^2 \left[ \int_{-1}^1 \frac{\nu g_e d\eta}{(1+\rho\eta)^2} + \frac{1-\nu^2}{\rho} \ln \frac{1+\rho}{1-\rho} F_e \right] = 0 \quad (6.21)$$

$$g_e'' + \alpha^2 g_e'' + F_e'' + \rho \left[ -\frac{g_e'}{1+\rho\eta} + \eta F_e'' + \frac{\rho \nu F_e'}{1+\rho\eta} \right] = 0 .$$

The solution of (6.20) and (6.21), subject to the edge conditions (6.18), (6.19) and (6.8) and subject to the face boundary conditions (6.7) is to be introduced into equations (6.2) for  $\Psi$  and  $V$ . Upon taking account of the relations (6.11), (6.14) and (6.17) we have then

$$(1-\nu^2)\Psi = Ec\beta(g_e + \rho^{\frac{1}{2}}g_i) , \quad V = \sqrt{ca}\beta(F_i + \rho^{\frac{1}{2}}F_e) . \quad (6.22)$$

Furthermore, introduction of  $\Psi$  and  $V$  from equation (6.2) into equations (5.10) to (5.12) gives as expressions for stresses

$$\sigma_x = \frac{E\beta}{1-\nu^2} \frac{g_e' + \rho^{\frac{1}{2}}g_i'}{1+\rho\eta} , \quad \tau = -\frac{E\beta}{1-\nu^2} \frac{g_e' + \rho g_i'}{1+\rho\eta} , \quad (6.23)$$

$$\sigma_\theta = E\beta \left[ \frac{\nu}{1-\nu^2} \frac{g_e' + \rho^{\frac{1}{2}}g_i'}{1+\rho\eta} + \frac{\rho^{\frac{1}{2}}F_i' + \rho F_e'}{1+\rho\eta} \right] , \quad (6.24)$$

and as expressions for the stress couple  $M_x$  and the stress resultant  $Q$  ,

$$M_x = -\frac{E\beta c^2}{1-\nu^2} \int_{-1}^1 (g_e + \rho^{\frac{1}{2}}g_i) d\eta , \quad (6.25)$$

$$Q = -\frac{E\beta c}{1-\nu^2} \int_{-1}^1 (g_e' + \rho g_i') d\eta , \quad (6.26)$$

We note that while the above formulas for  $M_x$  and  $Q$  give the impression that the edge-zone solution contribution  $g_e$  makes a dominant contribution to these quantities—which, if true would detract much from the significance of conventional two-dimensional shell theory—we will find shortly that  $\int_{-1}^1 g_e d\eta$  comes out to be of a smaller order of magnitude in  $\rho$  than  $\rho^{\frac{1}{2}} \int_{-1}^1 g_i d\eta$ , so that no problem of this sort does, in fact, arise.

Beyond this we may also note that the differential equation for  $g_e$  in (6.21) is effectively of second order, in place of a fourth-order bi-harmonic problem which is encountered in the analysis of the corresponding problem for an isotropic homogeneous shell medium. It is this difference in the order of the differential-equation problem for the edge-zone solution contribution which makes possible an exact solution of the complete problem for the case of the transversely inextensional medium.

#### PARAMETRIC EXPANSIONS FOR INTERIOR AND EDGE-ZONE SOLUTION CONTRIBUTIONS

As inspection of the differential equations (6.20) and (6.21), in conjunction with the boundary conditions (6.7), (6.8), (6.18) and (6.19) indicates the possibility of an expansion of the solutions in powers of the parameter  $\rho^{\frac{1}{2}}$ .<sup>†</sup>

$$F = F_0 + \rho^{\frac{1}{2}} F_1 + \rho F_2 + \dots, \quad g = g_0 + \rho^{\frac{1}{2}} g_1 + \rho g_2 + \dots, \quad (7.1)$$

and observing that  $(1/\rho) \ln[(1+\rho)/(1-\rho)] = 2[1 + \rho^2/3 + \dots]$ , we have then from equations (6.20),

$$\int_{-1}^1 g_{in}'' d\eta + 2(1 - \nu^2) F_{in} = 0, \quad g_{in}'' + F_{in}'' = 0; \quad n = 0, 1, \quad (7.2)$$

$$\left. \begin{aligned} \int_{-1}^1 g_{in}'' d\eta + 2(1 - \nu^2) F_{in} &= -\nu \int_{-1}^1 g_{in-2} d\eta; \quad n = 2, 3 \\ g_{in}'' + F_{in}'' &= g_{in-2}' - \alpha^2 g_{in-2}'' - \eta F_{in-2}'' - \nu F_{in-2} \end{aligned} \right\}, \quad (7.3)$$

<sup>†</sup> Except for the form of (6.19a) this expansion would be in powers of  $\rho$ , rather than  $\rho^{\frac{1}{2}}$ . This means that when (6.19b) applies, one-half the terms in our expansion will vanish automatically.

with analogous relations for  $n = 4, 5, \dots$ , which will not be utilized in what follows, and equations (6.21) give in the same manner

$$\int_{-1}^1 g''_{en} d\eta = 0, \quad g''_{en} + \alpha^2 g''_{en} + F''_{en} = 0; \quad n = 0, 1, \quad (7.4)$$

$$\int_{-1}^1 g''_{en} d\eta = 0, \quad g''_{en} + \alpha^2 g''_{en} + F''_{en} = g'_{en-2} - \eta F''_{en-2}; \quad n = 2, 3, \quad (7.5)$$

$$\int_{-1}^1 g''_{en} d\eta = -\nu \int_{-1}^1 g_{en-4} d\eta - 2(1 - \nu^2) F_{en-4}; \quad n = 4, 5. \quad (7.6)^\dagger$$

The associated boundary conditions which follow from (6.7) and (6.8) are

$$\eta = \pm 1: \quad g_{in} = 0, \quad g_{en} = 0, \quad (7.7)$$

$$\xi = \infty: \quad g_{in} = 0, \quad g_{en} = 0, \quad F_{in} = 0, \quad F_{en} = 0. \quad (7.8)$$

The coupling between interior and edge zone contributions will be effected in the process of satisfying the boundary conditions for the loaded edge of the shell which follow from (6.18) and (6.19) in the form

$$F'_{io}(0) + F'_{eo}(0) + \alpha^2 g'_{eo}(0, \eta) = s(\eta), \quad (7.9a)$$

$$F'_{in}(0) + F'_{ei}(0) + \alpha^2 g'_{ei}(0, \eta) = 0, \quad (7.9b)$$

$$F'_{in}(0) + F'_{en}(0) + \alpha^2 g'_{en}(0, \eta) = \alpha^2 \eta g'_{en-2}(0, \eta) - \alpha^2 g'_{in-2}(0, \eta); \quad n = 2, 3, \quad (7.9c)$$

and

$$F_{io}(0) = 0, \quad F_{in}(0) + F_{en-1}(\theta) = 0; \quad n = 1, 2, 3, \dots \quad (7.10)$$

or

$$\int_{-1}^1 g'_{en}(0, \eta) d\eta = 0; \quad n = 0, 1, \quad (7.11a)$$

---

<sup>†</sup> It is in this one place that we require equations for  $n = 4, 5$ , in order to complete the determination of our expansion terms upto  $n = 3$ .

$$\int_{-1}^1 g'_{en}(0, \eta) d\eta = - \int_{-1}^1 g'_{in-2}(0, \eta) d\eta ; \quad n = 2, 3, \dots \quad (7.11b)$$

#### DETERMINATION OF INTERIOR SOLUTION CONTRIBUTION TERMS

We begin by determining the interior solution contribution to the extent that this is possible without bringing in the form of the associated edge zone solution contribution. In doing this we will arrive at a set of ordinary differential equations for the dimensionless deflection functions  $F_{in}$ , with  $F_{i0}$  being equivalent to the corresponding function in accordance with conventional two-dimensional shell theory, with  $F_{i1}$  accounting for the effect of deviating from the "conventional" assumption of an  $\eta$ -independent edge slope function  $s(\eta)$ , and with  $F_{i2}$  accounting for the effects of transverse shear deformation and of element width changes in the same manner as previously found in [1].

We complement these results by the discovery of the complete system of boundary conditions for  $F_{i0}$ , for an arbitrarily prescribed edge slope function  $s(\eta)$ , through use of the differential equations for the edge-zone solution contributions, but without having to determine any part of the edge-zone portion of the solution of the complete problem.

Considering the fact that  $F_{in} = F_{in}(\xi)$ , we find from equations (7.2), in conjunction with the appropriate statement in (7.7) the simple result

$$g_{in} = \frac{1 - \eta^2}{2} F''_{in} , \quad F_{in}^{IV} + 3(1 - \nu^2) F_{in} = 0 ; \quad n = 0, 1 . \quad (8.1)$$

In the same way we find from equations (7.3) and (7.7), and with  $(1 - \nu^2)\alpha^2 = E/G$ ,

$$\left. \begin{aligned} g_{in} &= \frac{1 - \eta^2}{2} F''_{in} + \frac{\eta - \eta^3}{3} F''_{in-2} + \left( \nu \frac{1 - \eta^2}{2} - \frac{E}{G} \frac{5 - 6\eta^2 + \eta^4}{8} \right) F_{in-2} \\ F_{in}^{IV} + 3(1 - \nu^2) F_{in} &= \left( \frac{6E}{5G} - 2\nu \right) F''_{in-2} ; \quad n = 2, 3 . \end{aligned} \right\} \quad (8.2)$$

We now turn to the form of the boundary conditions for the functions  $F_{in}$ . We find from (7.8) the obvious requirements of vanishing  $F_{in}$  (and  $F'_{in}$ ) for  $\xi = \infty$ . As far as conditions for  $\xi = 0$  are concerned, we have as one of the two conditions for  $F_{i0}$ , for one of the two cases considered in (7.10) and (7.11), that

$F_{i0}(0) = 0$ . The other conditions, in accordance with (7.9) to (7.11) all appear to require the simultaneous determination of  $F_{en}$  and  $g_{en}$ . We will show next how to avoid this complication to a significant extent.

#### DERIVATION OF BOUNDARY CONDITIONS FOR $F_{in}$ , WITH OR WITHOUT INVOLVEMENT OF EDGE-ZONE SOLUTION CONTRIBUTION

We begin by observing that equations (7.4) and (7.5), in conjunction with the conditions  $g_{en}(\infty, \eta) = g'_{en}(\infty, \eta) = 0$  imply the relations

$$\int_{-1}^1 g_{en}(\xi, \eta) d\eta = \int_{-1}^1 g'_{en}(\xi, \eta) d\eta = 0, \quad (9.1a)$$

for  $n = 0, 1, 2, 3$ . Furthermore, from (6.21),

$$\int_{-1}^1 g'_{en}(\xi, \eta) d\eta = (1 - \nu^2) \int_{\xi}^{\infty} F_{eo}(\xi) d\xi. \quad (9.1b)$$

With the help of (9.1), and through use of the first relation in (8.1) and (8.2), we may write the set of conditions in (7.10) and (7.11) in the form

$$F_{i0}(0) = 0, \quad \underline{\text{or}} \quad F'''_{i0}(0) = 0, \quad (9.2a)$$

$$F_{i1}(0) = -F_{e0}(0), \quad \underline{\text{or}} \quad F'''_{i1}(0) = 0, \quad (9.2b)$$

$$F_{in}(0) = -F_{en-1}(0) \quad \underline{\text{or}} \quad F'''_{in}(0) = \left( \frac{6E}{5G} - \nu \right) F'_{in}(0) - 3(1 - \nu^2) \int_0^{\infty} F_{en-2}(\xi) d\xi; \quad n = 2, 3. \quad (9.2c)$$

It remains to establish a second condition at  $\xi = 0$  for  $F_{in}$ , through use of equations (7.9), with a view towards letting this condition to be as much as possible a condition for  $F'_{in}(0)$ , in terms of given quantities. In order to accomplish this purpose, we consider an integrated version of the edge-zone differential equations (7.4) and (7.5), with an appropriate weighting function, as follows.

We write, as a consequence of equation (7.4),

$$\int_{-1}^1 (1 - \eta^2)(g''_{en} + \alpha^2 g''_{en} + F''_{en})d\eta = 0 ; \quad n = 0, 1 . \quad (9.4)$$

In this we write first,

$$\int_{-1}^1 (1 - \eta^2)g''_{en} d\eta = [(1 - \eta^2)g'_{en} + 2\eta g_{en}]_{-1}^1 - 2 \int_{-1}^1 g_{en} d\eta ,$$

with the conclusion, which follows from (9.1) and (7.8), that

$$\int_{-1}^1 (1 - \eta^2)g''_{en} d\eta = 0 . \quad (9.5)$$

Introduction of (9.5) into (9.4) and observation of the edge conditions at infinity then gives further

$$\int_{-1}^1 (1 - \eta^2)(\alpha^2 g'_{en} + F'_{en})d\eta = 0 ; \quad n = 0, 1 . \quad (9.6)$$

Upon using (9.6), in conjunction with (7.9a, b), we obtain as conditions for  $F'_{i0}$  and  $F'_{i1}$ ,

$$F'_{i0}(0) = 1 , \quad F'_{i1}(0) = 0 , \quad (9.7a, b)$$

and we see that, in fact, the determination of  $F_{i0}$  may in all cases considered here be carried out without explicit reference to the edge zone contribution to the complete solution of the problem.

It suggests itself to see to what extent application of the same procedure to the differential equations (7.5) may make possible a reduction of the boundary conditions (7.9c) which involve  $F'_{i2}$  and  $F'_{i3}$ . We find first, proceeding in the same way as in going from (9.4) to (9.6), and observing that  $\eta F''_{en-2}$  is an odd function of  $\eta$ , that now

$$\int_{-1}^1 (1 - \eta^2)(\alpha^2 g''_{en} + F''_{en})d\eta = 2 \int_{-1}^1 \eta g_{en-2} d\eta , \quad (9.8)$$

for  $n = 2, 3$ .

Evidently, equation (9.8), together with the edge conditions at infinity, allows us to conclude that

$$\int_{-1}^1 (1 - \eta^2) [\alpha^2 g'_{en}(0, \eta) + F'_{en}(0)] d\eta = -2 \int_{-1}^1 \eta \int_0^{\infty} g_{en-2}(\xi, \eta) d\xi d\eta, \quad (9.9)$$

for  $n = 2, 3$ . Therewith, and with the consequences of the first relation in (8.1), we obtain altogether that

$$F'_{in}(0) = -\frac{2\alpha^2}{5} F'''_{in-2}(0) + \frac{3}{2} \int_{-1}^1 \eta \int_0^{\infty} g_{en-2}(\xi, \eta) d\xi d\eta + \frac{3\alpha^2}{4} \int_{-1}^1 (\eta - \eta^3) g'_{en-2}(0, \eta) d\eta, \quad (9.10)$$

for  $n = 2, 3$ . We note as a very important consequence of (9.10) the fact that when  $g_{eo}$  is an even function of  $\eta$ , which is the case when  $s(\eta)$  is even, then the integral terms on the right vanish for  $n = 2$  and we have a boundary condition for  $F_{i2}$  as well which is free of any reference to the edge-zone solution contribution.

#### EXPANSIONS FOR DEFLECTION, AXIAL BENDING MOMENT AND TRANSVERSE SHEAR STRESS RESULTANT

In order to see the possibility of determining  $M_x$  and  $Q$ , and also  $V$ , for the conventional displacement boundary condition case of an  $\eta$ -independent  $\bar{u}_{,r}$  upto terms of relative order  $\rho$ , solely on the basis of a determination of the interior solution contribution we rewrite our earlier expressions for these quantities as follows.

On the basis of equations (6.22) and (7.1),

$$V = -\beta c^{\frac{1}{2}} a^{\frac{1}{2}} [F_{i0} + \rho^{\frac{1}{2}} (F_{i1} + F_{e0}) + \rho (F_{i2} + F_{e1}) + \dots] \quad (10.1)$$

On the basis of (6.25), (6.26), (7.1), in conjunction with equations (8.1) and (8.2) for the  $g_{in}$  and equations (9.1) for the  $g_{en}$ ,

$$M_x = -\frac{2}{3} \frac{E\beta c^{\frac{5}{2}}}{(1 - \nu^2) a^{\frac{1}{2}}} \left\{ F''_{i0} + \rho^{\frac{1}{2}} F''_{i1} + \rho \left[ F''_{i2} - \left( \frac{6E}{5G} - \nu \right) F_{i0} \right] + \dots \right\} \quad (10.2)$$

$$Q = -\frac{2}{3} \frac{E\beta c^2}{(1-\nu^2)a} \left\{ F_{i0}''' + \rho^{\frac{1}{2}} F_{i1}''' + \rho \left[ F_{i2}''' - \left( \frac{6E}{5G} - \nu \right) F_{i0}' + 3 \frac{1-\nu^2}{2} \int_{\xi}^{\infty} F_{e0} d\xi \right] + \dots \right\} . \quad (10.3)$$

We note that it will be possible to determine  $V$ ,  $M_x$  and  $Q$ , upto terms of relative order  $\rho$ , solely on the basis of a consideration of the interior solution contributions  $F_{i0}$ ,  $F_{i1}$  and  $F_{i2}$ , to the extent that it is possible to determine these functions without explicit consideration of the edge-zone solution portion, as discussed on page 21, and to the extent that  $F_{e0}$  and  $F_{e1}$  turn out to vanish altogether.

The same conclusions apply insofar as the determination of the stiffness coefficients  $K_{\beta\beta}$ ,  $K_{V\beta}$  and  $K_{\beta}$  is concerned, inasmuch as we have that

$$K_{\beta\beta} = M_x(0)/\beta , \quad K_{V\beta} = -Q(0)/\beta , \quad (10.4)$$

when  $V(0) = 0$ , and

$$K_{\beta} = M_x(0)/\beta , \quad (10.5)$$

when  $Q(0) = 0$ .<sup>†</sup>

#### EXPANSIONS FOR STRESSES

Introduction of the series expansions (7.1) into equations (6.23) and (6.24) gives as expansions for the stresses  $\sigma_x$ ,  $\tau$ ,  $\sigma_{\theta}$ , upto terms of relative order  $\rho$ ,

$$\sigma_x = \frac{E\beta}{1-\nu^2} [g_{e0}' + \rho^{\frac{1}{2}}(g_{e1}' + g_{i0}') + \rho(g_{e2}' + g_{i1}' - \eta g_{e0}') + \dots] , \quad (11.1)$$

$$\tau = -\frac{E\beta}{1-\nu^2} [g_{e0}' + \rho^{\frac{1}{2}} g_{e1}' + \rho(g_{e2}' + g_{i0}' - \eta g_{e0}') + \dots] , \quad (11.2)$$

$$\sigma_{\theta} = \nu \sigma_x + E\beta [\rho^{\frac{1}{2}} F_{i0} + \rho(F_{i1} + F_{e0}) + \dots] , \quad (11.3)$$

<sup>†</sup> Note that (10.4) and (10.5) are consistent with (4.1) and (4.2) in the light of the defining relation (6.16) for  $\beta$ .

We note that, in contrast to the results for deflection, axial moment and transverse resultant, the distribution of stress in the shell will, for the general case, be such that edge zone contributions come out to be of a higher order of magnitude than interior region contributions. This is not so for the "exceptional" cases for which  $g_{e0}$  and  $g_{e1}$  vanish identically. The significance of this distinction will become apparent in our discussion of the exceptional case of an  $\eta$ -independent  $\bar{u}_{,r}$ , in comparison with the case where  $\bar{u}_{,r}$  is assumed to be a quadratic function of  $\eta$ .

### SOLUTION OF INTERIOR AND EDGE-ZONE DIFFERENTIAL EQUATIONS

Determination of the interior solution contribution, in accordance with equations (8.1) and (8.2), is the same as in the earlier work concerned with this contribution only [1]. We find, upon taking account once for all of conditions for  $\xi = \infty$ , with  $4m^4 = 3(1 - \nu^2)$ , that

$$F_{in} = (A_n \cos m\xi + B_n \sin m\xi)e^{-m\xi} ; \quad n = 0, 1 , \quad (12.1)$$

and

$$F_{in} = (A_n \cos m\xi + B_n \sin m\xi)e^{-m\xi} - \left(\frac{6E}{5G} - 2\nu\right) \frac{\xi}{16m^4} F_{in-2}'''' ; \quad n = 2, 3 , \quad (12.2)$$

with the associated functions  $g_{in}$  following from the above in accordance with (8.1) and (8.2).

Having  $F_{in}$  and  $g_{in}$ , as indicated above we now turn to the determination of  $F_{en}$  and  $g_{en}$ , for  $n = 0, 1, 2, 3$ , in accordance with equations (7.4) to (7.8). Writing as before as differential equations for  $g_{en}$  and  $F_{en}$ , the set

$$g_{en}'' + \alpha^2 g_{en}'' + F_{en}'' = 0 ; \quad n = 0, 1 , \quad (12.3)$$

$$g_{en}'' + \alpha^2 g_{en}'' + F_{en}'' = g_{en-2}' - \eta F_{en-2}'' ; \quad n = 2, 3 , \quad (12.4)$$

we take account of the first relations in (7.4) and (7.5), in conjunction with the conditions for  $\xi = \infty$ , so as to establish as a system of three boundary conditions

for  $\eta = \pm 1$ ,

$$\int_{-1}^1 g_{en}(\xi, \eta) d\eta = 0, \quad g_{en}(\xi, \pm 1) = 0, \quad (12.5)$$

with the presence of the terms  $F''_{en}(\xi)$  in (12.3) and (12.4) making it possible to satisfy the three conditions in (12.5), when without these terms the first condition (12.5) would rule out significant portions of the solutions of (12.3) and (12.4).

To see that this is in fact so we write (12.3) and (12.4) in the differentiated form

$$g_{en}''' + \alpha^2 g_{en}'' = 0; \quad n = 0, 1, \quad (12.6)$$

$$g_{en}''' + \alpha^2 g_{en}'' = g_{en-2}'' - F''_{en-2}; \quad n = 2, 3, \quad (12.7)$$

and determine first the solution of (12.6).

We find, by separation of variables, that equation (12.6) has particular solutions

$$g_{enp} = (C_1 + C_2 \cos \lambda \eta) e^{-\lambda \xi / \alpha} + (D \sin \mu \eta) e^{-\mu \xi / \alpha} \quad (12.8)$$

where  $C_1, C_2, D, \lambda$  and  $\mu$  are arbitrary constants. Satisfaction of the three boundary conditions (12.5) requires that these arbitrary constants satisfy the relations

$$C_1 + C_2 \lambda^{-1} \sin \lambda = 0, \quad C_1 + C_2 \cos \lambda = 0, \quad D \sin \mu = 0. \quad (12.9)$$

The conditions for non-trivial solutions in (12.9) are

$$\tan \lambda = \lambda, \quad \sin \mu = 0, \quad (12.10)$$

for all positive roots  $\lambda = \lambda_j$  and  $\mu = \mu_k$  for  $j, k = 1, 2, 3, \dots$ . It is evident that the functions  $\sin \mu_k \eta$  form an orthonormal system, such that every integrable odd function of  $\eta$  in the interval  $-1 < \eta < 1$  may be expanded in terms of them. Additionally, it can be shown that the set

$$\varphi_j = \frac{\cos \lambda_j - \cos \lambda_j \eta}{\lambda_j \cos \lambda_j} \quad (12.11)$$

also forms an orthonormal system, in such a way that every integrable even function  $f(\eta)$ , in  $-1 < \eta < 1$ , with the additional property  $\int_{-1}^1 f d\eta = 0$ , can be expanded in terms of them.<sup>†</sup>

We use the above properties to construct the series solution

$$g_{en} = \sum_{j,k=1}^{\infty} C_{jn} \varphi_j(\eta) e^{-\lambda_j \xi / \alpha} + D_{kn} (\sin \mu_k \eta) e^{-\mu_k \xi / \alpha} \quad (12.12)$$

for  $n = 0, 1$ .

Before proceeding to the analogous solution of (12.7) we return to equation (12.3) in order to establish, with the help of the conditions  $F_{en}(\infty) = F'_{en}(\infty) = 0$ , as solution  $F_{en}(\xi)$  which is associated with  $g_{en}$  in (12.12),

$$F_{en} = -\alpha^2 \sum_{j=1}^{\infty} \lambda_j^{-1} C_{jn} e^{-\lambda_j \xi / \alpha}; \quad n = 0, 1. \quad (12.13)$$

We now consider equation (12.4) where it remains to determine the appropriate particular solution corresponding to a right-hand side which can be seen, with the help of (12.11) to (12.13), to be of the form

$$\sum C_{jn-2} \left( \frac{\sin \lambda_j \eta}{\cos \lambda_j} + \lambda_j \eta \right) e^{-\lambda_j \xi / \alpha} + D_{kn-2} (\mu_k \cos \mu_k \eta) e^{-\mu_k \xi / \alpha}.$$

We find that a particular solution of (12.4) with the above expression in place of the original right-hand side, which also satisfies the three boundary conditions (12.5), is such that altogether

$$g_{en} = \sum C_{jn} \varphi_j(\eta) e^{-\lambda_j \xi / \alpha} + D_{kn} (\sin \mu_k \eta) e^{-\mu_k \xi / \alpha} \\ + \sum C_{jn-2} \left( \frac{\eta}{\lambda_j} - \frac{\eta \cos \lambda_j \eta}{2\lambda_j \cos \lambda_j} - \frac{\sin \lambda_j \eta}{2\lambda_j \sin \lambda_j} \right) e^{-\mu_k \xi / \alpha}$$

<sup>†</sup> We note that it is this orthogonality property of the functions  $\varphi_j$  which is responsible for the advantages of the present solution of the general problem, in comparison with the solution of the corresponding problem for the isotropic shell.

$$+ \frac{1}{2} \sum D_{kn-2} \left( \eta \sin \mu_k \eta - \frac{\cos \mu_k \eta - \cos \mu_k}{\mu_k} \right) e^{-\mu_k \xi / \alpha}, \quad (12.14)$$

and

$$F_{en} = -\alpha^2 \sum \lambda_j^{-1} C_{jn} e^{-\lambda_j \xi / \alpha} - \frac{1}{2} \alpha^2 \sum \mu_k^{-1} \cos \mu_k D_{kn-2} e^{-\mu_k \xi / \alpha}, \quad (12.15)$$

for  $n = 2, 3$ .

It now remains to determine the constants of integration  $C_{jn}$  and  $D_{kn}$  in conjunction with, or preferably subsequent to, the determination of the constants  $A_n$  and  $B_n$  in the interior solution portion  $F_{in}$  as given by (12.1) and (12.2).

#### DERIVATION OF BOUNDARY CONDITIONS FOR DETERMINATION OF CONSTANTS IN $g_{en}$

We begin by recalling that the complete system (7.9) to (7.11) of conditions at the edge  $\xi_e = \xi_i = 0$  of the shell had been reduced, insofar as possible, to a system of conditions for the  $F_{in}$  alone, consisting of equations (9.2), (9.3), (9.7) and (9.10). A characteristic of these conditions is that in them the effect of the edge-zone solution contribution manifests itself through the presence of certain definite integrals with respect to  $\eta$  of  $g_{en}(\xi, \eta)$ , but without appearance of the  $g_{en}$  themselves. Consequently, these conditions do not contain those elements of the complete system of edge conditions (7.9) to (7.11) which are required for a determination of the series coefficients  $C_{jn}$  and  $D_{kn}$  in  $g_{en}$ .

A re-inspection of equations (7.9) to (7.11) makes it clear that the remaining supplementation of the boundary conditions (9.2), (9.3), (9.7) and (9.10) must come from equations (7.9), and not from (7.10) and (7.11).

We obtain the first of the remaining transformed conditions by introducing (9.7a) into (7.9a) and by eliminating  $F'_{eo}(0)$  from this relation by considering that  $\int_{-1}^1 g'_{eo} d\eta = 0$ . This gives

$$\alpha^2 g'_{eo}(0, \eta) = s(\eta) - \frac{1}{2} \int_{-1}^1 s(\eta) d\eta. \quad (13.1)$$

We finally introduce  $F'_{in}(0)$  from (9.10) into (7.9c) and consider that here  $\int_{-1}^1 g'_{en} d\eta = 0$ , and  $g'_{in-2}(0, \eta) = \frac{1}{2}(1 - \eta^2)F'''_{in-2}(0)$ . Therewith equation (7.9c) becomes

$$g'_{en}(0, \eta) = \eta g'_{en-2}(0, \eta) - \frac{1}{2} \int_{-1}^1 \eta g'_{en-2}(0, \eta) d\eta - \frac{1}{2} \left( \frac{1}{3} - \eta^2 \right) F'''_{in-2}(0) \quad , \quad (13.3)$$

for  $n = 2, 3$ .

Having equations (13.1) to (13.3), in conjunction with equations (12.12) and (12.13) for  $g_{en}$  and  $F_{en}$ , we are now in a position to arrive at some general conclusions, without additional analysis. To wit

(1) The functions  $g_{e1}$  and  $F_{e1}$  will vanish identically, for all edge conditions cases here under consideration.

(2) The functions  $g_{eo}$  and  $F_{eo}$  will vanish identically for the special case  $s(\eta) = 1$ , but will otherwise have a dominant effect in equations (11.1) to (11.3) for the distribution of stress, and a direct effect of relative order  $\rho^{\frac{1}{2}}$  on the values of the deflection  $V$ , in accordance with equation (10.1), as well as an indirect effect of relative order  $\rho^{\frac{1}{2}}$  on  $M_x$  and  $Q$ , in accordance with equations (10.2), (10.3) and (9.2b).

(3) The functions  $g_{e2}$  and  $F_{e2}$  will make a contribution of relative order  $\rho$  on stresses, in accordance with (11.1) to (11.3) but will make no such contribution to  $V$ ,  $M_x$  and  $Q$ .

#### THE CASE OF A UNIFORM EDGE ROTATION

We assume now, as in [4], an axial-edge displacement  $\bar{u} = -\beta_o(r - a)$ , giving  $\bar{u}_{,r} = -\beta_o$  and, in accordance with (6.16),  $\beta = -(3/4)(-\beta_o)(4/3) = \beta_o$  and therewith, in accordance with (6.15),

$$s = 1 \quad , \quad (14.1)$$

and then, as discussed in the preceding section

$$g_{eo} = 0 \quad , \quad F_{eo} = 0 \quad . \quad (14.2)$$

With (14.2), and with  $g_{e1} = 0$  and  $F_{e1} = 0$ , we have, from (9.2), (9.3), (9.7) and (9.10) as edge conditions for the interior solution contribution

$$F'_{i0}(0) = 1, \quad F'_{i1}(0) = F'_{i2}(0) = F'_{i3}(0), \quad (14.3)$$

together with

$$F_{i0}(0) = F_{i1}(0) = F_{i2}(0) = F_{i3}(0) = 0, \quad (14.4)$$

for the case  $V(0) = 0$ , and

$$F'''_{i0}(0) = F'''_{i1}(0) = F'''_{i2}(0) = F'''_{i3}(0) = 0 \quad (14.5)$$

for the case  $Q(0) = 0$ , with equation (14.3), together with (14.4) or (14.5), to be used for the determination of the constants of integration  $A_n$  and  $B_n$  in (12.1) and (12.2).

We omit the elementary calculations leading to the appropriate values of the  $A_n$  and  $B_n$ . With their help there follows

$$\begin{aligned} V(0) &= -c^{\frac{1}{2}} a^{\frac{1}{2}} \beta [F_{i0}(0) + \rho F_{i2}(0) + \dots] \\ &= \frac{c^{\frac{1}{2}} a^{\frac{1}{2}}}{2m} \beta \left[ 1 - \frac{\rho}{m^2} \left( \frac{3E}{20G} + \frac{\nu}{4} \right) + \dots \right], \end{aligned} \quad (14.6)$$

$$\begin{aligned} M_x(0) &= -\frac{Ec^{\frac{5}{2}}}{2m^4 a^{\frac{1}{2}}} \beta \left\{ F''_{i0}(0) + \rho \left[ F''_{i2}(0) - \left( \frac{6E}{5G} - \nu \right) F_{i0}(0) \right] + \dots \right\} \\ &= \frac{Ec^{\frac{5}{2}}}{2m^3 a^{\frac{1}{2}}} \beta \left[ 1 - \frac{\rho}{m^2} \left( \frac{3E}{20G} - \frac{\nu}{4} \right) + \dots \right], \end{aligned} \quad (14.7)$$

for the case  $Q(0) = 0$ , and

$$M_x(0) = \frac{Ec^{\frac{5}{2}}}{m^3 a^{\frac{1}{2}}} \beta \left[ 1 - \frac{\rho}{m^2} \left( \frac{9E}{20G} + \frac{\nu}{4} \right) + \dots \right], \quad (14.8)$$

$$Q(0) = -\frac{Ec^2}{m^2 a} \beta \left[ 1 - \frac{\rho}{m^2} \left( \frac{3E}{5G} + \frac{\nu}{2} \right) + \dots \right], \quad (14.9)$$

for the case  $V(0) = 0$  where, it is recalled,  $4m^4 = 3(1 - \nu^2)$  and  $\rho = c/a$ .

We note, specifically, that the results in (14.6) to (14.9) have been obtained without determination of any edge-zone solution contribution and that furthermore

the stiffness coefficients  $K_{\beta\beta}$  and  $K_{\nu\beta}$  which are associated with (14.8), in accordance with (10.4), as well as the coefficient  $K_{\beta}$  associated with (14.7) in accordance with (10.5) are consistent with our earlier bound results in [4], upon specializing these so as to correspond to the limiting-type assumption of a medium unable to experience transverse normal strains.

Having determined the  $F_{in}$ , we may now obtain the here leading terms  $g_{e2}$  and  $F_{e2}$  of the edge-zone solution portion of the complete solution of the problem from equations (12.14) and (12.15), with  $C_{jo} = 0$  and  $D_{jo} = 0$ , in conjunction with the boundary condition (13.3) which now reduces to the form

$$g'_{e2}(0, \eta) = \frac{1}{2} \left( \frac{1}{3} - \eta^2 \right) F'''_{io}(0) \quad , \quad (14.10)$$

or, equivalently, to

$$\sum \lambda_j C_{j2} \varphi_j + \mu_k D_{k2} \sin \mu_k \eta = \frac{1}{2} \alpha \left( \eta^2 - \frac{1}{3} \right) F'''_{io}(0) \quad (14.11)$$

in the interval  $-1 < \eta < 1$ . The orthonormality properties of the functions  $\varphi_j$  and  $\sin \mu_k \eta$  then give

$$D_{k2} = 0 \quad , \quad \lambda_j C_{j2} = \frac{\alpha}{2} F'''_{io}(0) \int_{-1}^1 \left( \eta^2 - \frac{1}{3} \right) \varphi_j d\eta = \frac{2\alpha}{3\lambda_j} F'''_{io}(0) \quad (14.12)$$

and therewith,

$$g_{e2} = \frac{2}{3} \alpha \left( \sum \lambda_j^{-2} \varphi_j(\eta) e^{-\lambda_j \xi / \alpha} \right) F'''_{io}(0) \quad . \quad (14.13)$$

A consideration of (14.5) now gives that  $g_{e2}$  vanishes throughout, just as  $g_{e0}$  and  $g_{e1}$ , for the case  $Q(0) = 0$ . For the case  $V(0) = 0$  the function  $F_{io}$ , with  $F'_{io}(0) = 1$  and  $F_{io}(0) = 0$ , gives the relation  $F'''_{io}(0) = 2m^2$ .

Having determined  $g_{e2}$  it becomes possible to evaluate the distribution of stress in the shell, in accordance with equations (11.1) to (11.3), with these equations reducing, for the present problem to the form

$$\sigma_x = \frac{E\beta\rho^{\frac{1}{2}}}{1-\nu^2} [g'_{io} + \rho^{\frac{1}{2}} g'_{e2} + \dots] \quad , \quad \tau = -\frac{E\beta\rho}{1-\nu^2} [g'_{io} + g'_{e2} + \dots] \quad (14.4)$$

with a corresponding expression for  $\sigma_\theta$ . We see once again that the "elementary" interior contribution in  $\sigma_x$  (as well as in  $\sigma_\theta$ ) dominates the supplementary edge zone contribution. At the same time the edge zone contribution is of the same order of magnitude as the interior contribution insofar as the transverse shearing stress  $\tau$  is concerned. We note, in particular, the possibility of writing, on the basis (14.14) and (14.10), as expression for the edge shear distribution for the case  $V(0) = 0$

$$\tau(0, \eta) \approx \frac{E\beta_0}{1-\nu^2} \frac{m^2}{2} \left[ \left(1 - \eta^2\right) - \left(\frac{1}{3} - \eta^2\right) \right] \quad (14.15)$$

with the second term inside the braces representing the edge zone effect, which has the expected property of making no contribution to the shear stress resultant  $Q$ .

#### A CASE OF NON-UNIFORM EDGE ROTATION

We now consider, as an example for which the results of the standard two-dimensional shell theory are complemented in an essential way by three-dimensional considerations, the case for which the axial edge displacement is prescribed in the form

$$\bar{u} = -\beta_0 \left[ (r-a) + \frac{k}{3} \frac{(r-a)^3}{c^2} \right], \quad \bar{u}_{,r} = -\beta_0 [1 + k\eta^2] \quad (15.1)$$

and therewith, in accordance with (6.16) and (6.15),

$$\beta = -\beta_0 \left(1 + \frac{1}{5}k\right), \quad s(\eta) = \frac{1 + k\eta^2}{1 + k/5} \quad (15.2)$$

We can now, as before, determine the first term of the interior solution contribution, with the help of the edge conditions

$$F'_{i0}(0) = 1, \quad F_{i0}(0) = 0 \quad \text{or} \quad F'''_{i0}(0) = 0 \quad (15.3)$$

which follow from (9.2a) and (9.7a), depending on whether  $V(0) = 0$  or  $Q(0) = 0$  is prescribed, and we note that this determination does incorporate information on the nature of the shape functions in (15.1), by way of the defining relation (15.2) for  $\beta$ .

Introduction of  $g_{e0}$  from equation (12.12) into the relation

$$\alpha^2 g'_{eo}(0) = k \frac{\eta^2 - 1/3}{1 + k/5}, \quad (15.4)$$

which follows from (13.1) in conjunction with (15.2) now gives

$$C_{jo} = \frac{4}{\alpha \lambda_j^2} \frac{k/3}{1 + k/5}, \quad D_{ko} = 0. \quad (15.5)$$

Having  $g_{eo}$ , and  $g_{io}$ , and recalling that  $g_{e1} = 0$  for all cases, we now have as expressions for stresses, upto and including terms of relative order  $\rho^{\frac{1}{2}}$ ,

$$\sigma_x = \frac{E\beta}{1 - \nu^2} (g'_{eo} + \rho^{\frac{1}{2}} g'_{io}), \quad \tau = \frac{-E\beta}{1 - \nu^2} g'_{eo}, \quad (15.6)$$

as well as  $\sigma_\theta = \nu \sigma_x + E\beta \rho^{\frac{1}{2}} F_{io}$  where, notably, all components of stress are, within the narrow edge zone, of a higher order of magnitude than the expected stresses associated with the interior solution contributions  $g_{ic}$  and  $F_{io}$ .

We omit listing explicit formulas for stresses, and instead consider equations (10.1) to (10.3) for  $V$ ,  $M_x$  and  $Q$ , where we note that evaluation of the contributions of relative order  $\rho^{\frac{1}{2}}$  and  $\rho$  involves the relations

$$F_{eo}(0) = -\frac{4\alpha k/3}{1 + k/5} \sum \frac{1}{\lambda_j^3}, \quad \int_0^\infty F_{eo} d\xi = -\frac{4\alpha^2 k/3}{1 + k/5} \sum \frac{1}{\lambda_j^4}. \quad (15.7)$$

Upon evaluation of (10.1) to (10.3), we now obtain in generalization of equations (14.6) to (14.9)

$$\frac{V(0)}{\sqrt{ca}} = \frac{\beta}{2m} \left\{ 1 + \frac{\rho^{\frac{1}{2}}}{m} \sqrt{\frac{E}{3G}} \frac{4k}{1 + k/5} \sum \frac{1}{\lambda_j^3} \right. \\ \left. - \frac{\rho}{m^2} \left[ \frac{3E}{20G} \left( 1 + \frac{40k/3}{1 + k/5} \sum \frac{1}{\lambda_j^4} \right) + \frac{\nu}{4} \right] + \dots \right\} \quad (15.8)$$

$$\frac{M_x(0)}{Ec^2} = \frac{\beta}{2m^3} \sqrt{\frac{c}{a}} \left\{ 1 - \frac{\rho}{m^2} \left[ \frac{3E}{20G} \left( 1 - \frac{40k/3}{1 + k/5} \sum \frac{1}{\lambda_j^4} \right) - \frac{\nu}{4} \right] + \dots \right\} \quad (15.9)$$

when  $Q(0) = 0$ , and

$$\frac{M_x(0)}{Ec^2} = \frac{\beta}{m^3} \frac{c}{a} \left\{ 1 + \frac{\rho^{\frac{1}{2}}}{m} \sqrt{\frac{E}{3G}} \frac{2k}{1+k/5} \sum \frac{1}{\lambda_j^3} - \frac{\rho}{m^2} \left( \frac{9E}{20G} + \frac{\nu}{4} \right) + \dots \right\} \quad (5.10)$$

$$\frac{Q(0)}{Ec} = -\frac{\beta}{m^2} \frac{c}{a} \left\{ 1 + \frac{\rho^{\frac{1}{2}}}{m} \sqrt{\frac{E}{3G}} \frac{4k}{1+k/5} \sum \frac{1}{\lambda_j^3} - \frac{\rho}{m^2} \left[ \frac{3E}{5G} \left( 1 + \frac{5k/3}{1+k/5} \sum \frac{1}{\lambda_j^4} \right) + \frac{\nu}{2} \right] + \dots \right\} \quad (15.11)$$

when  $V(0) = 0$ .

In order to evaluate (15.8) to (15.11), we note that with the successive roots  $\lambda_j \approx 4.49, 7.72, 10.90, 14.07, 17.22, 20.37, 23.52, 26.67, 29.81, 32.99, (j + \frac{1}{2})\pi, \dots$  of equation (12.10) the two sums of negative powers of  $\lambda_j$  come out to be

$$\sum \lambda_j^{-3} \approx 0.015 \quad , \quad \sum \lambda_j^{-4} \approx 0.0029 \quad . \quad (15.12)$$

Insofar as the interpretation of equations (15.8) to (15.11) is concerned, it should be noted that the leading terms on the right may be considered as equivalent to the consequences of ordinary thin shell theory, in conjunction with the solution of the problem of how to introduce an appropriate representation of the displacement condition (15.1) into this theory. Additionally, we find that while the effect of transverse shear deformability and of cross-sectional width changes comes out, as expected, to be of relative order  $\rho$ , the effect of  $\eta^3$ -term in  $\bar{u}_r$  comes out to be of order  $\rho^{\frac{1}{2}}$ , with the numerically largest values of these correction terms resulting upon letting  $k$  tend to infinity, with a finite limiting value of  $\beta_0 k$ .

To obtain an impression of the numerical consequences of replacing a linear distribution  $\bar{u} = u_0 (r - a)/c$  by a pure cubic distribution  $\bar{u} = u_0 (r - a)^3/c^3$  we set in equations (15.8) to (15.11)  $k = \infty$  and  $\beta = -\beta_0 k/5 = 3u_0/5c$ . Therewith, and with equations (15.12) there follows

$$\frac{V(0)}{\sqrt{ca}} \approx \frac{\beta}{2m} \left\{ 1 + 0.3 \frac{\rho^{\frac{1}{2}}}{m} \sqrt{\frac{E}{3G}} - \frac{\rho}{m^2} \left[ \frac{3E}{20G} (1 + 0.2) + \frac{\nu}{4} \right] \right\} \quad (15.13)$$

$$\frac{M_x(0)}{Ec^2} \approx \frac{\beta}{2m^3} \sqrt{\frac{c}{a}} \left\{ 1 - \frac{\rho}{m^2} \left[ \frac{3E}{20G} (1 - 0.2) - \frac{\nu}{4} \right] \right\} \quad (15.14)$$

when  $Q(0) = 0$ , and

$$\frac{M_x(0)}{Ec^2} \approx \frac{\beta}{m^3} \sqrt{\frac{c}{a}} \left\{ 1 + 0.15 \frac{\rho^{\frac{1}{2}}}{m} \sqrt{\frac{E}{3G}} - \frac{\rho}{m^2} \left( \frac{9E}{20G} + \frac{\nu}{4} \right) \right\} \quad (15.15)$$

$$\frac{Q(0)}{Ec} \approx -\frac{\beta}{m^2} \frac{c}{a} \left\{ 1 + 0.3 \frac{\rho^{\frac{1}{2}}}{m} \sqrt{\frac{E}{3G}} - \frac{\rho}{m^2} \left[ \frac{3E}{5G} (1 + 0.025) + \frac{\nu}{2} \right] \right\} \quad (15.16)$$

when  $V(0) = 0$ .

As might be expected, the shape correction terms with  $\rho^{\frac{1}{2}}$  come out to be numerically quite significant for moderately thin shells, say for  $\rho = 0.1$ . Additionally, due to the change from a linear to a cubic edge displacement distribution a significant modification of the terms with  $\rho$  is seen to occur in some of the above expressions.

#### REFERENCES

1. M. W. Johnson and E. Reissner, On the Foundations of the Theory Thin Elastic Shells, J. Math. and Phys. 37, 371-392, 1958.
2. E. L. Reiss, A Theory for the Small Rotationally Symmetric Deformations of Cylindrical Shells, Comm. Pure Appl. Math. 13, 531-550, 1960.
3. A. L. Goldenweiser, Derivation of an Approximate Theory of Shells by Means of Asymptotic Integration of the Equations of the Theory of Elasticity, P.M.M. 23, 593-608, 1963.
4. S. Nair and E. Reissner, On Asymptotic Expansions and Error Bounds in the Derivation of Two-Dimensional Shell Theory, Studies Appl. Math. 56, 189-217, 1977.
5. E. Reissner, On the Theory of Transverse Bending of Elastic Plates, Int. J. Solids Structures 12, 545-554, 1976.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) ON TWO- AND THREE-DIMENSIONAL RESULTS FOR ROTATIONALLY SYMMETRIC DEFORMA- TIONS OF CIRCULAR CYLINDRICAL SHELLS		5. TYPE OF REPORT & PERIOD COVERED INTERIM
7. AUTHOR(s) S. Nair and E. Reissner		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Dept. of Applied Mechanics & Engg. Sciences University of California, San Diego La Jolla, California 92093		8. CONTRACT OR GRANT NUMBER(s) N00014-75-C-0158
11. CONTROLLING OFFICE NAME AND ADDRESS Structural Mechanics Branch Office of Naval Research, Code 474 Arlington, VA 22217		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE November 1977
		13. NUMBER OF PAGES 33
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Derivation of 2D-shell theory from 3D-elasticity theory. Circular cylin- drical shells. Asymptotic expansion procedures. Edge zone and interior zone solution contributions. Exact results for midsurface normal inextensible shells.		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Previous considerations by asymptotic expansion procedures of the relation between elasticity theory results and thin-shell theory results for the case of rotationally symmetric deformations of an edge-loaded semi-infinite circular cylin- drical shell are supplemented by an analysis of this problem for a shell possess- ing a limiting-type orthotropy, such that transverse normal strains vanish iden- tically. It is shown that assuming this kind of orthotropy has the important benefit of allowing the derivation of exact expressions for the edge zone solution contribution, when such exact expressions are not possible for the problem of the shell with more general properties of the material.		