

AD-A055 685

ELECTRONICS ENGINEERING GROUP (1842ND) SCOTT AFB IL
PROTOTYPE HIGH FREQUENCY (HF) INTERCEPT CAPABILITY FOR THE TACT--ETC(U)
MAY 78 D H CASEY

F/G 17/2.1

UNCLASSIFIED

1842 EEG/EETD-TR-78-7


NL

1 OF 1
ADA
055685



END
DATE
FILMED
8 -78
DDC





NATIONAL BUREAU OF STANDARDS
MICROCOPY RESOLUTION TEST CHART

AD A 055685



FOR FURTHER TRANSMISSION


2

14

1842 EEG/EETD-TR-78-7

9

AFCS TECHNICAL REPORT



6

PROTOTYPE HIGH FREQUENCY (HF) INTERCEPT CAPABILITY
FOR THE
TACTICAL AIR BASE WEATHER ELEMENT (TABWE).

10

Daniel H./ Casey

This document has been approved
for public release and sale; its
distribution is unlimited.

12

11p.

DIGITAL AND NARROWBAND SYSTEMS BRANCH
1842 ELECTRONICS ENGINEERING GROUP (AFCS)
SCOTT AIR FORCE BASE, ILLINOIS

11

15 MAY 1978

78 06 19 116

409 646 Lue

AD No.

DDC FILE COPY

1842 ELECTRONICS ENGINEERING GROUP

MISSION

The 1842 Electronics Engineering Group (EEG) is organized as an independent group reporting directly to the Commander, Air Force Communications Service (AFCS) with the mission to provide communications-electronics-meteorological (CEM) systems engineering and consultive engineering for AFCS. In this respect, 1842 EEG responsibilities include: Developing engineering and installation standards for use in planning, programming, procuring, engineering, installing and testing CEM systems, facilities and equipment; performance of systems engineering of CEM requirements that must operate as a system or in a system environment; operation of a specialized Digital Network System Facility to analyze and evaluate new digital technology for application to the Defense Communications System (DCS) and other special purpose systems; operation of a facility to prototype systems and equipment configurations to check out and validate engineering-installation standards and new installation techniques; providing consultive CEM engineering assistance to HQ AFCS, AFCS Areas, MAJCOMS, DOD and other government agencies.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 1842 EEG/EETD TR78-7	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) PROTOTYPE HIGH FREQUENCY (HF) INTERCEPT CAPABILITY FOR THE TACTICAL AIR BASE WEATHER ELEMENT (TABWE)		5. TYPE OF REPORT & PERIOD COVERED
7. AUTHOR(s) Capt Daniel H. Casey		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS 1842 EEG/EETD Scott AFB, IL 62225		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS 1842 EEG/EETD Scott AFB, IL 62225		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) 1842 EEG/EEISD Scott AFB, IL 62225		12. REPORT DATE 15 May 1978
		13. NUMBER OF PAGES
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release. Distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Tactical Weather System (TWS), Tactical Air Base Weather Element (TABWE), Weather Intercept		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) <p>The Tactical Weather System (TWS) is a system of ten modules of mobile communications and meteorological equipment. The modules are divided into two components; the Tactical Weather Analysis Center (TWAC) and the Tactical Air Base Weather Element (TABWE). The TWAC receives weather information by HF radio and relays this information to the TABWE. The TABWE does not have its own HF intercept capability and could not perform its mission if deployed without the support of the TWAC. This report describes a prototype installation of HF radio equipment in the TABWE.</p>		

APPROVAL PAGE

This report has been reviewed and is approved for publication and distribution.

Z. J. Bara
 ZYGMUND J. BARA

1842 EEG/EET (AFCS)
 Chief, Command, Control & Defense Communications
 Systems Engineering Division

Jesse J. Tallman
 JESSE J. TALLMAN, P.E.

1842 EEG/EETD (AFCS)
 Chief, Digital/Narrowband Systems Branch

Wilton T. Hataway
 WILTON T. HATAWAY

1842 EEG/EETDN (AFCS)
 Technical Area Manager, Narrowband Systems

Daniel H. Casey
 DANIEL H. CASEY, Capt, USAF

1842 EEG/EETDN (AFCS)
 Electronics Engineer, Author

ACCESSION for	
NTIS	White Section <input checked="" type="checkbox"/>
DDC	Buff Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
D.	SPECIAL
<i>A</i>	

78 06 19 116

TABLE OF CONTENTS

<u>Paragraph</u>		<u>Page</u>
1	Introduction	1
2	Background	1
3	Problem	2
4	Solution	2
5	Conclusions and Recommendations	6

ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
1	Communications Rack in TWAC	2
2	TWAC HF Radio Intercept Configuration	3
3	D Module Equipment Storage Rack	4
4	TABWE D Module Signal Entry Panel	5
5	Prototype HF Intercept Capability for the TABWE	6
6	Proposed HF Intercept Capability for the TABWE	7

TABLES

<u>Table</u>		<u>Page</u>
1	Tactical Weather System (TWS) Van Description	1
2	TWAC and TABWE Module Arrangement	1
3	TWAC Communications Rack Equipment Configuration	4

weather data to the Tactical Air Force Headquarters and the TABWE. The TWAC has the capability to receive weather data from both wire line and radio sources. HF radio equipment is contained in the C Module.

The TABWE is deployed at the tactical air base adjacent to the Tactical Unit Operations Center. The TABWE provides weather data to the local tactical air base agencies and forwards weather observations to the TWAC. The TABWE has no HF radio intercept capability of its own. In some cases, the TWAC and TABWE may not be deployed as a system.

3. THE PROBLEM. The TWAC is normally deployed with the AFCH. The 3CMBTCG does not have an AFCH element and is not authorized the TWAC portion of the TWS. The TABWE has no equipment for receiving weather data sent by HF radio, but depends on information relayed from the TWAC. Without the support of the TWAC, the 3CMBTCG must deploy the antiquated AN/MSQ-10 Weather Intercept Van to provide weather data for the TABWE.

4. THE SOLUTION. The communications rack now contained in the TWAC is shown in Figure 1. It contains nine major items of equipment, which are identified in Table 3.




Figure 1. Communications Rack in TWAC

1. INTRODUCTION. This report describes the engineering and installation of a prototype high frequency (HF) radio receiving capability for the Tactical Air Base Weather Element (TABWE).

2. BACKGROUND. The Tactical Air Base Weather Element (TABWE) and Tactical Weather Analysis Center (TWAC) are configurations of mobile vans which comprise the Tactical Weather System (TWS), a system of communications and meteorological equipment. The nomenclature, function, and quantity of the various vans is shown in Table 1.

Table 1. Tactical Weather System (TWS) Van Description

<u>Module</u>	<u>Nomenclature</u>	<u>Description/Function</u>	<u>Quantity</u>
A	AN/TMQ-28	Meteorological Station/ Forecasting	3
B	AN/TCC-76	Communications Central/ Observing	2
C	AN/TCC-77	Communications Central/ Radio Intercept	1
D	S-517G	Maintenance Shelter	4

The A Module is the work area for the weather forecasters. No radio equipment is contained in the A Module, however the UHF radio in the B Module is operable from the A Module.

The B Module contains equipment to accept readouts from the various meteorological instruments. It contains a UHF transceiver, two facsimile recorders and two automatic send/receive teletype machines.

The C Module is the communications center of the TWS. It contains one send/receive teletype, two receive only printers, two facsimile recorders, one VHF receiver, and three HF receivers.

The D Module is the maintenance shop. It contains two work benches and two empty equipment racks with adjustable shelves for storage of test equipment.

The ten modules of the TWS are commonly configured into a TWAC and TABWE as shown in Table 2.

Table 2. TWAC and TABWE Module Arrangement

<u>Module</u>	<u>TWAC</u>	<u>TABWE</u>
A	2	1
B	1	1
C	1	0
D	2	2

The TWAC is deployed with the Air Force Component Headquarters (AFCH) and is located adjacent to the Tactical Air Control Center, and may be located as far as 100 miles from the TABWE. It provides




Figure 2. TWAC HF Radio Intercept Configuration

Table 3. TWAC Communications Rack Equipment Configuration

1. TTY FSK Convertor, CV-2543P/T
 2. VHF Receiver, AN/SMQ-28
 3. HF Receiver No. 1, Collins 651S-1
 4. HF Receiver No. 2, Collins 651S-1
 5. HF Receiver No.3, Collins 651S-1
 6. Facsimile Convertor, Alden 421C
 7. HF Multicoupler, CU-1382F/FRR
 8. Morse-to-Baudot Convertor, CV-2124/U
 9. Power Frequency Convertor (400-to-60 Hz)
-




Figure 3. D Module Equipment Storage Rack.

The signals from the equipment are distributed through an audio patch panel in an adjacent rack. The VHF receiver, Morse-to-Baudot convertor, and power frequency convertor are not required for a TABWE HF intercept capability. The power frequency convertor is needed in the TWAC since the TWAC is powered by 400 Hz generators and some of the equipment requires 60 Hz power. The TABWE is designed to be powered by 60 Hz generators so no frequency conversion is necessary. Figure 2 is a functional block diagram of the HF intercept portion of the communications rack.

A prototype HF intercept capability was constructed using one of the test equipment storage racks in the D Module of the TABWE and assets from the communications rack in the TWAC. The equipment storage rack, with its removable shelves is shown in Figure 3.

Sufficient space is available elsewhere in the shelter for storage of test equipment displaced by the new communications rack.

Of prime importance in the prototype installation was the avoidance of permanent modifications to the vans, since any operational installation must also be done without modification. Meeting this objective meant avoiding changes in the existing signal entry panel and power distribution system. No changes in the panel or power system are required if existing jacks and receptacles are used for signal lines and power requirements. The TABWE "D" Module signal entry panel is shown in Figure 4. The two jacks on the top row are BNC types, and the two jacks at the bottom left are N types. These four jacks are unused and terminate with similar connectors inside the van. One of the N type connectors could be used for connecting the cable from the antenna. One of the BNC jacks could be used for egress of the signal line from the facsimile convertor. Since the output of the TTY convertor is bipolar, the remaining two jacks could be used for signal egress, however another way which avoids the need for special cables would be to use ordinary field wire for both the facsimile and TTY outputs and route the wire through the drain hole in the van. Power for the new communications rack can be obtained from a 20-amp convenience outlet located just to the right of the rack. Thus, no wiring changes or alterations to the power distribution panel are required.




Figure 4. TABWE D Module Signal Entry Panel

The prototype installation is shown in Figure 5. The prototype occupied only about one-half of the total available rack space, since the VHF receiver, Morse-to-Baudot convertor, and power frequency convertor are not required. A permanent operational installation would include a small audio patch panel. A functional block diagram of the new configuration is shown in Figure 6.

5. CONCLUSIONS AND RECOMMENDATIONS. The prototype installation established that an HF intercept capability can be provided in the D Module of the TABWE with no extensive changes to the van. Equipment for the prototype was mounted on spare equipment shelves. A permanent installation would require that several holes be drilled and tapped in the rack for mounting slide drawers and the supporting metalwork. Finally, the 3CMBTCG would prefer to use a whip antenna similar to the one used in the TWAC, rather than something more complex such as the AN/GRA-4 antenna. Mounting a whip antenna to the exterior of the D Module would require four holes for the mounting bracket.

Considering the minor nature of the required alterations, installing the equipment in the D Module of the TABWE appears to be the easiest and most convenient solution to the problem of providing an HF intercept capability for the TABWE.




Figure 5. Prototype HF Intercept Capability for the TABWE




Figure 6. Proposed HF Intercept Capability for the TABWE

DISTRIBUTION LIST

HQ AFCS
CS
EP
DO
LG

1
3
2
2

ECA/XR
APO New York 09012

2

NCA/EIE
Griffiss AFB, NY 13441

2

PCA/EIE
APO San Francisco 96553

2

SCA/EIE
Oklahoma City AFS, OK 73145

2

3 CMBTCG/LGM
Tinker AFB, OK 73145

2

1839 EIG/EP

2

Defense Documentation Center
Cameron Station
Alexandria, VA 22314

2