

AD-A055 691



AIR FORCE HUMAN RESOURCES LAB BROOKS AFB TEX
EFFECTS OF PLATFORM MOTION, VISUAL AND G-SEAT FACTORS UPON EXPE--ETC(U)
JUN 78 P A IRISH, G H BUCKLAND
AFHRL-TR-78-9

F/G 5/5


UNCLASSIFIED

NL

1 OF 1
ADA
055691



END
DATE
FILMED
8-78
DDC



NATIONAL BUREAU OF STANDARDS
MICROCOPY RESOLUTION TEST CHART

AFHRL-TR-78-9

FOR FURTHER TRAN ⁴¹¹ 2

AIR FORCE



AD A 055691

AD No.
DDC FILE COPY

**HUMAN
RESOURCES**

**EFFECTS OF PLATFORM MOTION, VISUAL AND G-SEAT
FACTORS UPON EXPERIENCED PILOT PERFORMANCE
IN THE FLIGHT SIMULATOR**


By

Philip A. Irish, III, 1st Lt, USAF
George H. Buckland, Capt, USAF

FLYING TRAINING DIVISION
Williams Air Force Base, Arizona 85224

June 1978
Final Report for Period April 1976 - March 1977

Approved for public release; distribution unlimited



78 06 20 020

LABORATORY

AIR FORCE SYSTEMS COMMAND
BROOKS AIR FORCE BASE, TEXAS 78235

NOTICE

When U.S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This final report was submitted by Flying Training Division, Air Force Human Resources Laboratory, Williams Air Force Base, Arizona 85224, under project 1123, with HQ Air Force Human Resources Laboratory (AFSC), Brooks Air Force Base, Texas 78235.

This report has been reviewed and cleared for open publication and/or public release by the appropriate Office of Information (OI) in accordance with AFR 190-17 and DoDD 5230.9. There is no objection to unlimited distribution of this report to the public at large, or by DDC to the National Technical Information Service (NTIS).

This technical report has been reviewed and is approved for publication.

EDWARD E. EDDOWES, Technical Advisor
Flying Training Division

DAN D. FULGHAM, Colonel, USAF
Commander

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 14 AFHRL-TR-78-9	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
6 EFFECTS OF PLATFORM MOTION, VISUAL AND G-SEAT FACTORS UPON EXPERIENCED PILOT PERFORMANCE IN THE FLIGHT SIMULATOR.	9	7. TYPE OF REPORT & PERIOD COVERED Final report Apr 76 - Mar 77
10 Philip A/ Irish, III George H/Buckland	8. CONTRACT OR GRANT NUMBER(s) 12 45p.	6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Flying Training Division Air Force Human Resources Laboratory Williams Air Force Base, Arizona 85224	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62205F 11230325 17 03	11. CONTROLLING OFFICE NAME AND ADDRESS HQ Air Force Human Resources Laboratory (AFSC) Brooks Air Force Base, Texas 78235
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	12. REPORT DATE Jun 78	13. NUMBER OF PAGES 44
	15. SECURITY CLASS. (of this report) Unclassified	15a. DECLASSIFICATION DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) flight simulation visual display G-seat performance measurement pilot performance platform motion		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The objective of this study was to empirically assess the performance of experienced pilots in the Advanced Simulator for Pilot Training (ASPT) under varying platform motion, G-seat, field-of-view and ceiling/visibility conditions. Five experienced T-37 pilots flew five contact and instrument maneuvers in the ASPT under all combinations of the independent variables. Automated performance measures based on system parameters, pilot inputs and derived scores were collected and analyzed. The results indicated that expert performances were affected by the motion, field-of-view and ceiling/visibility variables and were often manifested as changes in control behavior rather than vehicle performance.		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

404 415

Am

DDC
RECEIVED
JUN 22 1978
F

PREFACE

This report covers research conducted by the Flying Training Division of the Air Force Human Resources Laboratory between April 1976 and March 1977. Full support of this project was provided by the 82d Flying Training Wing, Williams AFB, Arizona 85224. The project was conducted in support of project 1123, Flying Training Development, Mr. James F. Smith, project scientist; task 112303, Exploitation of Flight Simulation in Undergraduate Pilot Training (UPT), Mr. Robert R. Woodruff, task scientist; work unit 11230325, Simulator Design Configurations Study 2, Capt George H. Buckland, principal investigator, and Lt Philip A. Irish III, associate investigator.

Special appreciation is extended to the Computational Sciences Division at Brooks AFB for their assistance in the data reduction portion of the project. The authors would also like to extend special thanks to the following individuals for their outstanding contributions to this efforts: Dr. Thomas H. Gray for his critical editorial comments; Lt Paul M. Grunzke for his continuing suggestions; Mr. Thomas Farnan and Capt Richard Dorre for their excellent console operation; Capts Steven Cotterman, John Swofford, Anthony Dennis, Lts Michael Durringer, and Neal Houde for their dedication as subjects.

ACCESSION for	Write Section <input checked="" type="checkbox"/>
NTIS	Gift Section <input type="checkbox"/>
DOC	
UNANNOUNCED	
JUSTIFICATION	
BY	DISTRIBUTION/AVAILABILITY CODES
	SPECIAL
A	

TABLE OF CONTENTS

	Page
I. Introduction	5
Statement of Problem	5
Background	6
Study II Objectives	7
Hypotheses	8
II. Method	8
Subjects	8
Apparatus	8
Experimental Design	9
Independent Variables	10
Dependent Variables	10
Maneuvers	13
Procedures	13
Analysis	13
III. Results of Study II	14
IV. Discussion of Study II	23
V. Discussion of Studies I and II	27
VI. Summary and Conclusions	35
References	37
Appendix A: Description of Performance Measurement Algorithms	39

LIST OF ILLUSTRATIONS

Figure	Page
A1 GCA and landing scoring sequence	39
A2 360° overhead pattern and landing scoring sequence	40
A3 Aileron roll scoring sequence	41
A4 Loop scoring sequence	41
A5 Barrel Roll scoring sequence	42

78 06 20 020

LIST OF TABLES

Table		Page
1	Dependent Measure Listings for All Maneuvers	11
2	Significant Multivariate Effects Across All Maneuvers in Both Designs of Study II	14
3	Univariate Field-of-View Main Effects and Means Across Maneuvers	15
4	Univariate Motion Main Effects and Means Across Maneuvers	18
5	Univariate Ceiling/Visibility Main Effects and Means Across Maneuvers	20
6	Univariate Motion by Ceiling/Visibility Interactions in the Ground Controlled Approach	22
7	Percentages of Nonerror Sums of Squares for the Loop, the Aileron Roll and the Barrel Roll Maneuvers	23
8	Percentages of Nonerror Sums of Squares for the GCA Maneuver	24
9	Percentages of Nonerror Sums of Squares for the Overhead Pattern Maneuver	25
10	Comparison of Significant Multivariate Effects Across Study I and Study II Maneuvers	28
11	Ceiling/Visibility Effects Upon Individual Dependent Measures Common to Studies I and II	30
12	Motion Effects Upon Individual Dependent Measures Common to Studies I and II	31
13	Field-of-View Effects Upon Individual Dependent Measures Common to Studies I and II	32
14	G-Seat Effects Upon Individual Dependent Measures Common to Studies I and II	33

EFFECTS OF PLATFORM MOTION, VISUAL AND G-SEAT FACTORS UPON EXPERIENCED PILOT PERFORMANCE IN THE FLIGHT SIMULATOR

I. INTRODUCTION

Statement of the Problem

For some time, it has been accepted that the more closely the flight simulator approximates the aircraft in terms of the visual, kinesthetic, vestibular, and control loading cues provided to the pilot, the more effective the simulator will be for training. This hypothesis is based on the assumption that maximum training transfer will occur when the training environment and the transfer environment are identical. Recent developments in the art of flight simulation have provided research and training managers a wide variety of aircraft simulator design configuration options. Available options include synergistic or cascaded platform motion systems, pneumatic or hydraulic G-seat/G-suit arrangements and high resolution, multi-channel visual displays. All of these options have been designed and constructed for the sole purpose of increasing or improving the fidelity or realism of the flight simulator. However, assuming that current devices can produce desired levels of fidelity, the direct and associated costs of some of the present fidelity enhancement systems are formidable. Because of increasing economic constraints and extensive procurement projections, future procurement of simulators will have to include only those options which are able to maximize training potential and minimize cost. It is important, therefore, that the nature of the effects of these devices be fully explored, in order not only to describe the effectiveness of these systems but also to provide sufficient information to make informed procurement decisions regarding the selection of hardware design options.

A logical starting point for such investigations is to assess the responses of expert pilots to various configurations of the design options via their performance in the simulator. By monitoring changes in performance, one can objectively observe those design changes which seem to be most important in facilitating or hindering various aspects of pilot performance. Not only may the occurrence of performance changes be noted, but additionally, sufficient measurements may provide insight into the reasons for such changes. Although information on expert pilot performance in the simulator may or may not be related to the training effectiveness of a simulator or simulation in general, it provides a clearer understanding of the underlying psychological, and, to an extent, physiological processes at work within flight simulation. The information generated in this type of investigation is then useful in conducting further studies oriented toward less experienced and naive student behaviors. Such studies could be transfer of training studies which are normally limited to one or two variables due to experimental constraints. A research strategy employing this sequence of investigations provides an economical approach to the exploration and definition of system oriented variables in simulation research and may allow a significant reduction in the number of univariate transfer of training studies which must be conducted in attempting to describe the effects of these variables adequately in follow-on efforts.

The present study was initiated as a follow-on investigation of a previous exploratory effort. The first project, hereinafter referred to as Study I, was entitled "The Effects of System and Environmental Factors Upon Experienced Pilot Performance in the Advanced Simulator for Pilot Training" (AFHRL-TR-77-13). Study I was conducted to provide a "first look" into the main and interactive effects of platform motion, G-seat and visual display factors upon expert pilot performance on five contact and instrument flight maneuvers performed in the simulator. The purpose of this "first look" was to identify those variables and interactions which produce a significant impact upon expert pilot performance. The specific maneuvers studied were: the 360° overhead traffic pattern, ground controlled approach (GCA), takeoff, the aileron roll, and a slow flight exercise. Several types of dependent measures were utilized in Study I, including system output measures, pilot input measures, and derived scores. System output measures were defined for the most part as root mean square (RMS) deviations from specified parameter criteria during a specified

segment of a maneuver or a series of maneuver segments. Pilot input measures were sampled by collecting analogs to pilot induced forces on the control stick and rudder. Derived scores were time-in-tolerance measures reflecting how well the pilot remained within acceptable tolerances on several parameters simultaneously.

Another important aspect of Study I was that an economical approach to the design and analysis of the project was utilized. Briefly, this consisted of using a fractional factorial design which included higher-order (3rd order and above) interaction confounding. Additionally, a very small sample size ($N = 3$) was utilized in this exploratory effort. Due to the nature of the experimental design and the importance of the topic area, it was decided that some of the results of the first study should be validated and extended in a follow-on project. The present report documents the findings of this effort and compares and contrasts the results of both projects.

Background

A considerable amount of research has been performed on one simulator design option: platform motion systems. Studies investigating this issue have been, for the most part, equivocal in terms of the usefulness of platform motion systems. These systems are designed to provide vestibular and kinesthetic cues to the pilot by moving the platform upon which the cockpit rests. These motion systems are designed to provide directional cue information to the pilot, although it is obvious that prolonged directional cue information is physically limited, due to excursion constraints of each motion system. Presumably, the movements are intended to provide alerting information to the pilot; i.e., information indicative of changes in the status of the simulated aircraft.

Many past studies have reported improvements in pilot performance on various tasks when the simulator included platform motion (Borlace, 1967; Brown, Johnson, & Mungall, 1960; Jacobs, Williges, & Roscoe, 1975; Koonce, 1974; Rathert, Creer, & Sadoff, 1961). However, other studies have reported the converse, i.e., that performance remains stable across conditions of the presence and absence of platform motion (Demaree, Norman, & Matheny, 1965). Two recent training studies investigating the platform motion issue (Gray & Fuller, 1977; Woodruff, Smith, Fuller, & Weyer, 1976) have reported no reliable differences between students trained with simulator platform motion and students trained without platform motion. The first study reported no significant differences in training time between motion/no motion groups for any of the tasks investigated. Those tasks represented basic, advanced contact, instrument and navigation maneuvers which are standard in the T-37 phase of undergraduate pilot training. The second study reported no reliable differences due to motion training in pilots' ability to deliver air-to-surface weapons either in the simulator or in the aircraft.

Study I, which dealt with expert performance, revealed statistically significant motion differences in the performance of selected maneuvers. In this study, motion was consistently found to deleteriously affect the subject pilots' performance in the simulator.

Little systematic research has been conducted on pneumatic G-seat/G-suit systems in part because of the relatively small number of those systems available for research in conjunction with advanced platform motion and visual systems. The G-seat was designed essentially to supplement platform motion systems in providing the pilot additional proprioceptive and haptic cueing in order to improve the fidelity of the simulator. This cueing is generated by the systematic inflation and deflation of a series of pneumatic bellows installed in the backrest, seat pan and thigh panels of the pilot's seat. These bellows cause the pilot's weight to be repositioned on his thighs and buttocks in response to the bellows' activity. The cues provided by the G-seat are also of higher frequency and longer duration than those contributed by platform motion systems.

Taylor, Gerber, Allen, Brown, Cohen, Dunbar, Flexman, Hewitt, McElwain, Pancoe, & Simpson (1969), in a project addressing the effectiveness of G-seat cueing systems, reported that improvements in pilot performance accompanied the addition of G-cueing to the simulator dynamics.

Study I of the present series also indicated that performance improvements occurred when ground controlled approach (GCA) and takeoff maneuvers were attempted under conditions of a fully operative G-seat as compared to performance under inoperative G-seat conditions.

Research dealing with visual factors in aircraft simulator performance has been extensive. Many investigators have directed their efforts toward ascertaining the requirements of one particular aspect of the visual domain, field-of-view. Several studies, Armstrong (1970), Reeder and Kolnick (1964), Roscoe (1951), reported adequate pilot landing performances under conditions of restricted fields-of-view. Roscoe, however, reported that as the field-of-view increased, a corresponding improvement in performance occurred. The remaining studies mentioned above did not report this change in performance as a function of the field-of-view.

The results of Study I of this series showed no significant differences in pilot performance as a function of field-of-view (FOV) on four of the five maneuvers which were explored. The general trend of the data, however, suggested improved performance under larger display fields-of-view as compared to performance under restricted FOV conditions. This trend was somewhat substantiated in the analysis of the fifth maneuver in the study, the aileron roll. In this instance, performance was significantly better under conditions of maximum field-of-view as compared to two levels of restricted visual displays.

There has not been a great deal of research directed at examining possible interactions of the simulator design options. Past research addressing interactive effects of motion and visual cueing devices has been directed primarily toward the psychophysiological issues in simulator training. Specifically, problems of simulator sickness, disorientation and nausea have been the focus of this type of research. There has, in the past, been little information generated on the interactive effects of these cueing devices on pilot performance. Study I addressed this issue and reported several significant interactive impacts upon the pilot performance on selected flight tasks. Significant interactions were found to exist between the platform motion and G-seat systems, motion and visual systems as well as interactions between the cueing devices and experimentally constructed environmental variables, such as, wind, turbulence and ceiling/visibility. These findings stimulate additional research questions regarding the selection of sets of simulator design configuration options.

The results of the past research on these simulator design variables also tend to suggest that these results are highly specific to the simulator being investigated. This is due to differences in the inherent capabilities of the simulation devices and to the differences in the manner of computer programming for each simulator. Furthermore, it is probable that the nature of the effects are also specific to the type of aircraft being simulated as well as the experience levels of the subject pilot populations. Finally, the results of the first study tend to substantiate the hypothesis that the effects of a particular cueing device, both alone and in combination with other devices, may be specific to the type of maneuver being attempted.

Study II Objectives

The primary objective of Study II was to assess empirically the performance of experienced T-37 pilots in the Advanced Simulator for Pilot Training (ASPT) under varying platform motion, G-seat, field-of-view, and ceiling/visibility configurations.

Another objective was to further explore the prominent main and interactive effects which were reported in Study I in an attempt to confirm and validate the approach and findings of that study.

Furthermore, it was desired that the investigation of the above-mentioned variables be extended into the area of "higher G-force" maneuvers, representative of a more dynamic flight regime.

Finally, it was desired that additional information regarding the relationships between the system output measures and the pilot input measures as measured by the automated measurement system capability of the ASPT be obtained for various system configurations, flight maneuvers, and simulated environmental conditions.

Hypotheses

As a result of the findings of the previous study, several *a priori* hypotheses were formulated for this investigation. First, since platform motion consistently produced deleterious effects upon the pilot performances in the first study, it was hypothesized that experienced pilot performance in the simulator would be superior across all maneuvers when flown under no-platform-motion conditions than when under either 3- or 6-degree-of-freedom motion conditions.

Second, although the field-of-view variable produced a significant impact only upon the performance of the aileron roll maneuver in the first study, the consistency in the direction of the nonsignificant results in that study warranted the hypothesis that pilot performance under full field-of-view conditions would be superior to performance under restricted field-of-view conditions for all maneuvers excluding the ground controlled approach where the performances would tend to be equal across the field-of-view conditions. This exclusion was formulated, because the most important visual information in this task was concentrated directly in front of the pilot, and thus decrements in peripheral vision information would not seriously affect the pilot's performance.

Third, it was hypothesized that the variation in the G-seat's operation would not differentially affect performance. Although the G-seat was found to impact the performances on the takeoff and GCA maneuvers in the first study, these differences were not consistent across the broad range of dependent variables and did not warrant a directional hypothesis.

Fourth, it was hypothesized that reducing the ceiling/visibility conditions to minimums would substantially reduce performance on the 360° overhead pattern maneuver. However, it was also hypothesized that this environmental deterioration would not adversely affect performance on the GCA.

One of the most powerful and consistent effects evidenced in Study I was the ceiling/visibility variable. Performance on the overhead landing task was consistently degraded when the maneuver was flown under restricted ceiling/visibility conditions. The same trend was found for the ground controlled approach; however, it was not quite as consistent as in the former maneuver. Because the ground controlled approach was designed as an instrument maneuver to be performed under conditions of reduced ceiling/visibility, and because of the insufficient consistency of this variable's effects on performance in the first study, it was felt that variation in ceiling/visibility would not affect performance on this maneuver.

Finally, no directional hypotheses were made regarding interaction effects. Although the substantiation of the presence and/or absence of specific interactions was of major concern in this study, the investigators believed that the results of the first study were insufficient evidence upon which to base directional hypotheses. This was especially the case for an unusually large three-factor interaction which was found in the former study.

II. METHOD

Subjects

Five T-37 instructor pilots (IPs) from Williams Air Force Base were used as subjects for the duration of the effort. Each subject was selected on the basis of flying experience. The flight experience of the subjects ranged from 300 to 2,200 total flying hours, and from 160 to 700 hours in the T-37 aircraft. Each subject was required to be a qualified T-37 IP and to be current in the T-37 at the time of the study.

Apparatus

The Advanced Simulator for Pilot Training (ASPT) located at the Air Force Human Resources Laboratory/Flying Training Division (AFHRL/FT) was used for the duration of the study.

The ASPT consists of two fully instrumented T-37 cockpits which are mounted on two independent platform motion systems. Each platform motion system has six hydraulically-driven legs which are operated

synergistically to provide six degree-of-freedom (DOF) movement. The platform motion system has the capability of approximately 4-feet horizontal and 3-feet vertical travel. The displacement capabilities include: (a) Pitch: -20 degrees to +30 degrees; (b) Roll: ± 22 degrees; and (c) Yaw: ± 32 degrees.

The left seats in both cockpits are configured as 31-bellow pneumatic G-seats with variable tension lap belts. The bellows are located on the seat pan (16 cells), the backrest (9 cells), and thigh panels (6 cells). The G-seat operates by way of the programmed inflation and deflation of individual bellow(s) in response to the requirements of each particular maneuver.

The wraparound visual system of the ASPT is comprised of seven 36-inch monochromatic cathode-ray tubes (CRTs) placed in such a manner as to provide the pilot with a visual field-of-view of +110 degrees to -40 degrees vertical and ± 150 degrees horizontal. The visual environment is constructed by way of computer generated imagery (CGI). Most prominent ground references (mountains, runways, towers, roads, etc.) within a 100 square nautical mile area of Williams Air Force Base have been modeled within the environment. The visual imagery is updated at a 30 times per second rate in response to the aircraft's movement through the simulated environment. In this study, an enhanced visual environment was utilized, which differed from the normal ASPT configuration in the amount of ground image detail presented to the pilot. This image detail was enhanced by providing more ground section lines and by providing additional objects (stationary aircraft, tractor) in the vicinity of the runway. A detailed discussion of the characteristics of this enhanced environment can be found in Monroe, Rife, Cyrus, & Thompson (1976).

Another capability which the ASPT possesses is the ability to record, store and score various pilot performance parameters automatically. These measures are sampled and stored at an iteration rate ranging from 3.75 to 15 times per second, dependent upon the nature of the measure. The computer system also possesses a Cognitronics voice-generation capability for providing ground-controlled approach information.

All systems of ASPT (platform motion, visual display) can be varied, dependent upon experimental requirements to match a wide variety of environmental conditions or aerodynamic characteristics. For a more comprehensive technical discussion of the ASPT capabilities, consult Hagin and Smith (1974), and Rust (1975).

Experimental Design

Two separate designs were utilized in this project. The primary consideration in the construction of these designs was that a more traditional, more conservative approach be employed than was utilized in Study I. It was desired that an increase in the quantity and frequency of observations of performance be accomplished in order to provide more stability in the estimation of the relevant system and environmental effects.

The first design, a mixed effects 3^3 randomized block factorial (Kirk, 1968) included three independent variables each having three levels. The independent variables were: (a) Platform Motion, (b) G-Seat, (c) Field-of-View. Blocking was accomplished upon subjects in order that individual differences could be isolated. Twenty-seven unique treatment combinations were generated by the independent variables. This design was utilized in the investigation of three of the maneuvers studied: the aileron roll, the barrel roll, and the loop.

The second design was an extension of the first design and was used in the investigation of the remaining two maneuvers, the GCA and the 360° overhead pattern. A fourth independent variable, ceiling/visibility (C/V), with two levels was included. The inclusion of this additional variable increased the number of unique treatment combinations to 54. Thus, the second design was a mixed effects $3^3 2^1$ randomized block factorial. Blocking was again performed upon the subject variable in order that estimation of individual differences could be made. The same five subjects took part in both designs of the study. The order of treatment condition presentation was independently and stochastically randomized for each subject within the two designs.

The error terms for both designs were constructed assuming an additive model. That is, all block by treatment interactions were assumed to be zero. Thus, the error term was a linear combination of residual

block by treatment variances. This assumption was made because the subjects who were selected to participate in the study were highly qualified instructor pilots, and, therefore, it was inferred that the effects of learning the tasks would be minimized. Additionally, the treatment conditions were presented in a random fashion thus distributing any minimal learning effects equally between all specific treatments.

Independent Variables

The independent variables selected for study and investigated within the first design (3³) were: Platform Motion, G-Seat, and Field-of-View.

Three levels of platform motion were selected. Those levels were: (a) no motion; (b) 3 DOF motion including movement in roll, pitch, and heave, (c) 6 DOF motion including roll, pitch, yaw, heave, lateral and longitudinal displacements.

The three levels of the G-seat variable included: (a) nonoperational; (b) seat pan bellows operational, backrest and thigh panel bellows nonoperational; and (c) fully operational.

The FOV variable also possessed three levels: (a) 300° horizontal (H) by 150° vertical (V) (full capability of ASPT); (b) 144° H x 36° V; and (c) 48° H x 36° V, representative of many single-channel visual displays.

The fourth variable investigated in this research was ceiling/visibility. This variable was included in part due to the interactive potential with the other independent variables which this factor demonstrated in Study 1 of this series of investigations. Another reason for the inclusion of this variable was that it provided a measuring stick, at least on the basis of face validity, of the reasonability of the effects which occurred and the measurements which were employed. If performance decreased under adverse weather conditions, as was expected, then more confidence in the direction of the effects of the simulator configuration variables would be warranted. The ceiling/visibility variable had two levels: (a) clear visibility and unlimited ceiling, and (b) minimum visibility and a specified ceiling altitude. The minimum ceiling/visibility condition was task specific, dependent upon the nature of the maneuver. For the 360° overhead pattern, the minimum ceiling was set at 1,200 feet above ground level (AGL) and the corresponding visibility was established at 3 miles (1,200 ft/three miles). The minimum condition for the GCA was set at 100 feet AGL/.25 mile. The minima for both maneuvers were established to represent real-world limitations.

The final factor investigated was subject (block) effects. This factor permitted investigation of anticipated individual differences by statistically isolating that portion of the total experimental variance due to subject differences.

Dependent Variables

A large number of dependent measures were collected in this study by way of the Automated Performance Measurement System (APMS) feature of ASPT. A complete listing of the measures collected in this study across all of the maneuvers is provided in Table 1. The measures generally fit into one of three basic categories: (a) system output measures; (b) pilot input measures; and (c) derived scores.

The system output measures reflect deviations using the root mean square technique from specified parameter criteria within particular segments of a maneuver. As such, smaller scores reflect smaller deviations and, hence, better performances. Maneuver segments were defined as non-overlapping portions of maneuvers wherein one or more desired parameter values were stabilized. Specific maneuver segments for each of the maneuvers investigated are illustrated in Appendix A.

The pilot input measures, or smoothness measures, represent an attempt to measure analogs of pilot workload. These measures are normally expressed in the form of elevator, aileron and rudder power for particular maneuver segments. An assumption made in judging the direction of this type of score was that smaller scores reflect less effort expended in controlling the simulator and therefore were more desirable.

The derived scores were composite scores for a segment or combination of segments within a maneuver. These scores were indications of how well the pilot remained within the tolerance limits of

Table 1. Dependent Measure Listings for All Maneuvers

Variable	Units
Aileron Roll	
1. Entry pitch	Degrees
2. An average score of bank in, bank out and roll	Percent
3. Entry and exit pitch score	Percent
4. RMS bank in deviation	Degrees
5. RMS bank out deviation	Degrees
6. Elevator power during bank in	(Lbs-Deg)/Sec
7. Aileron power during bank in	(Lbs-Deg)/Sec
8. RMS pitch rate deviation during bank in	Deg/Sec
9. RMS roll rate deviation during bank in	Deg/Sec
10. RMS roll acceleration deviation during bank in	Deg/Sec ²
11. Elevator power during roll	(Lbs-Deg)/Sec
12. Aileron power during roll	(Lbs-Deg)/Sec
13. RMS pitch rate deviation during roll	Deg/Sec
14. RMS roll rate deviation during roll	Deg/Sec
15. Elevator power during bank out	(Lbs-Deg)/Sec
16. Aileron power during bank out	(Lbs-Deg)/Sec
17. RMS pitch rate deviation during bank out	Deg/Sec
18. RMS roll rate deviation during bank out	Deg/Sec
Barrel Roll	
1. Elevator power	(Lbs-Deg)/Sec
2. Aileron power	(Lbs-Deg)/Sec
3. Rudder power	(Lbs-Deg)/Sec
4. RMS pitch rate deviation	Deg/Sec
5. RMS roll rate deviation	Deg/Sec
6. Total Score	Percent
7. RMS pitch error-top half	Degrees
8. RMS pitch error-bottom half	Degrees
Loop	
1. Elevator power	(Lbs-Deg)/Sec
2. Aileron power	(Lbs-Deg)/Sec
3. RMS pitch rate deviation	Deg/Sec
4. RMS roll rate deviation	Deg/Sec
5. Total score	Percent
6. RMS groundtrack deviation	Feet
7. RMS pitch deviation	Degrees
360° Overhead Pattern	
1. RMS vertical velocity deviation during pitchout	Feet/Sec
2. RMS pitchout bank deviation	Degrees
3. RMS pitchout altitude deviation	Feet
4. Pitchout elevator power	(Lbs-Deg)/Sec
5. Pitchout aileron power	(Lbs-Deg)/Sec
6. RMS pitch rate deviation during pitchout	Deg/Sec
7. RMS roll rate deviation during pitchout	Deg/Sec
8. RMS vertical velocity during downwind	Ft/Min
9. RMS downwind altitude deviation	Feet
10. Downwind elevator power	(Lbs-Deg)/Sec
11. Downwind aileron power	(Lbs-Deg)/Sec

Table 1 (Continued)

Variable	Units
12. RMS downwind pitch rate deviation	Deg/Sec
13. RMS downwind roll rate deviation	Deg/Sec
14. RMS final turn bank deviation	Degrees
15. RMS final turn airspeed deviation	Knots
16. Final turn elevator power	(Lbs-Deg)/Sec
17. Final turn aileron power	(Lbs-Deg)/Sec
18. RMS final turn pitch rate deviation	Deg/Sec
19. RMS final turn roll rate deviation	Deg/Sec
20. RMS final approach glidepath deviation	Degrees
21. RMS final approach course deviation	Feet
22. RMS final approach airspeed deviation	Knots
23. Landing X position	Feet
24. Landing Y position	Feet
25. Landing airspeed	Knots
26. Landing heading	Degrees
27. Landing vertical velocity	Ft/Min
28. Elevator power final through landing	(Lbs-Deg)/Sec
29. Aileron power final through landing	(Lbs-Deg)/Sec
30. Rudder power final through landing	(Lbs-Deg)/Sec
31. RMS pitch rate final through landing	Deg/Sec
32. RMS roll rate final through landing	Deg/Sec
33. RMS vertical velocity final through landing	Ft/Sec
34. Overall pitch score	Percent
35. Overall downwind score	Percent
36. Overall final approach score	Percent
37. Overall landing score	Percent

Ground Controlled Approach (GCA)

1. Total score	Percent
2. Touchdown airspeed	Knots
3. Touchdown heading	Degrees
4. Touchdown vertical velocity	Ft/Sec
5. RMS altitude deviation	Feet
6. RMS airspeed deviation	Knots
7. RMS centerline deviation	Feet
8. RMS glidepath deviation	Degrees
9. Elevator power prior to glideslope interception	(Lbs-Deg)/Sec
10. Aileron power prior to glideslope	(Lbs-Deg)/Sec
11. RMS pitch rate deviation prior to glideslope	Deg/Sec
12. RMS roll rate deviation prior to glideslope	Deg/Sec
13. Elevator power on glideslope	(Lbs-deg)/Sec
14. Aileron power on glideslope	(Lbs-Deg)/Sec
15. Rudder power on glideslope	(Lbs-Deg)/Sec
16. RMS pitch rate deviation on glideslope	Deg/Sec
17. RMS roll rate deviation on glideslope	Deg/Sec

Note. — Lbs = pounds.
 Deg = degrees.
 Sec = second.
 Ft = feet.
 Min = minute.

several criteria simultaneously. These measurements were normally expressed as time-in-tolerance percentages with larger values representing better performances.

For a more comprehensive discourse on the specific derivations of these measures, consult Waag, Eddowes, Fuller, and Fuller (1975).

Although the number of dependent variables investigated in this study is relatively large, it still represents only a fraction of the measures which were available in the APMS system. The inclusion or exclusion of the available measures in this experiment was based upon the recommendations of expert pilots. Only those variables which were considered meaningful, reasonable indications of pilot performance for the particular maneuver under investigation were included.

Maneuvers

Five contact and instrument maneuvers were selected for the purpose of this study: aileron roll, barrel roll, loop, ground controlled approach and 360° overhead pattern. The aileron roll, GCA, and overhead pattern were chosen because they were included in Study I, and these maneuvers were investigated again to determine the constancy and generalizability of the earlier findings through testing with another sample of the subject population. The barrel roll and loop were included in this study to extend the analysis into the domain of higher G-force maneuvers. A complete discussion of the beginning and end points and scoring sequences of each of the maneuvers is included as Appendix A.

Procedures

Prior to data collection, each of the five subjects was provided approximately 4 hours of familiarization with the simulator (and safety factors) and familiarization with the types of simulator design configurations which would be investigated. This was accomplished by initially having the subjects fly the simulator in its normal full capability configuration. Next, the subjects were requested to complete several study maneuvers under a broad range of randomly selected independent variable conditions (e.g., motion, no motion, etc.). This training was constant for all subject pilots.

The data collection procedure was begun by having the pilot strap into the cockpit of the simulator and then having the console operator enter identification and system configuration information into the computer. The simulator was then initialized to one of five randomly selected maneuvers. The pilot was briefed on the task to be completed and all pertinent simulated weather conditions. After completion of this task, another randomly selected maneuver was initialized and the pilot was given the necessary instructions. This process was repeated a total of seven times per mission. The subjects normally flew two to three missions per session lasting approximately 2 hours, with rest periods provided whenever requested. All sorties were flown in cockpit B of the simulator in an attempt to control for possible inter-cockpit differences. In accomplishing the ground controlled approach, all verbal, glideslope, glidepath and distance information was conveyed via the Cognitronics voice generator. All measurements were stored on magnetic disk for subsequent analysis.

Analysis

Multivariate analyses of variance (MANOVA) were performed on each of the five maneuvers. The multivariate analyses were selected as the appropriate omnibus test due to the intercorrelation and interdependencies of the measurement sets. The significance criterion was established at the .05 probability level for all multivariate and univariate tests. Following the MANOVA, in those cases where significant multivariate F's were obtained, traditional stepdown univariate F's were computed in order to ascertain the location of the significance within the measurement set (Harris, 1975). Once the specific variable(s) was found, Tukey's tests were performed to determine the direction of the effect. This analytic procedure was followed for both designs. Finally, an index of the strength of the univariate effects was calculated for each dependent measure where multivariate and univariate significance was obtained. This index was calculated using the ratio of the sums of squares for an effect over the total nonerror sums of squares. This index represents a proportionate reduction in the total nonerror variability due to each specific effect and thus provides a relative measurement of the importance of an effect.

III. RESULTS OF STUDY II

Significant multivariate and univariate effects were discovered in all flight maneuvers. Inspection of Table 2 reveals those specific independent variables producing significant multivariate effects for all of the maneuvers investigated.

Table 2. Significant Multivariate Effects Across All Maneuvers in Both Designs of Study II

Effect	Aileron Roll	Barrel Roll	Loop	GCA	Overhead Pattern
A(FOV)	.047	.000	N/S	.039	.000
B(Motion)	N/S	.096	.027	.023	.000
C(G-seat)	N/S	N/S	N/S	N/S	N/S
D(C/V)	—	—	—	.000	.000
S(Block)	.000	.000	.000	.000	.000
AB(FOVxMOT)	N/S	N/S	.071	N/S	N/S
AC	N/S	N/S	N/S	N/S	N/S
BC	N/S	N/S	N/S	N/S	N/S
AD	—	—	—	N/S	N/S
BD(MOTxC/V)	—	—	—	.026	N/S
CD	—	—	—	N/S	N/S
ABC	N/S	N/S	N/S	N/S	N/S
ABD	—	—	—	N/S	N/S
ACD	—	—	—	N/S	N/S
BCD	—	—	—	N/S	N/S
ABCD	—	—	—	N/S	N/S

Note. — Table entries are probability levels.

N/S = Not Significant.

— = Not Estimated.

FOV = Field-of-View.

C/V = Ceiling/Visibility.

MOT = Motion.

Field-of-View (FOV). The first system variable investigated, field-of-view, produced significant multivariate effects in four of the five maneuvers: the aileron roll, barrel roll, GCA and 360° overhead pattern. Table 3 depicts the univariate analysis of variance and the cell means within each maneuver's measurement set showing those specific dependent variables which contributed toward the overall multivariate significance. In the aileron roll maneuver, three of the 18 total variables collected showed significant field-of-view main effects. In this maneuver, best performance was demonstrated under the full field-of-view condition for the average bank in, out and roll score but under the most restricted FOV conditions for the other measures: elevator power and RMS pitch rate during roll.

In the barrel roll maneuver, four of the eight total measures showed univariate significance ($p < .05$) due to the FOV variable. The general trend in these measures was that superior performance accompanied either the large or the medium FOV levels, and worst performance was normally associated with the most restricted FOV condition. This was true in three of the four measures: aileron power, RMS roll rate and RMS pitch error during the bottom half of the maneuver. The fourth maneuver, elevator power during roll, demonstrated best performance under the most restricted FOV condition and worst performance in the medium FOV setting.

In the overhead pattern maneuver, 12 of the 37 total measures collected demonstrated significant ($p < .05$) FOV main effects with 9 of these showing best performance under the two larger FOV

Table 3. Univariate Field-of-View Main Effects and Means Across Maneuvers

Source	\bar{X} (Full)	\bar{X} (Med)	\bar{X} (Small)	SSB	SSW	F	P
Aileron Roll							
1. Entry pitch	29.386	29.383	28.452	26.09	477.47	2.841	.062
2. Average score on bank in, out and roll	85.847*	84.320	79.305*	1,054.350	13,834.169	3.963	.021*
3. Entry and exit pitch score	-4.734	-4.780	-5.706	27.049	822.93	1.709	.186
4. RMS bank in deviation	1.107	1.092	1.287	1.061	36.49	1.513	.225
5. RMS bank out deviation	2.276	2.928	3.427	29.993	555.94	2.805	.065
6. Elevator power during bank-in	3.465	2.771	2.887	12.457	290.69	2.228	.112
7. Aileron power during bank-in	.212	.135	.182	.135	3.283	2.14	.122
8. RMS pitch rate deviation during bank in	6.418	6.030	6.109	3.791	168.10	1.172	.313
9. RMS roll rate deviation during bank in	1.073	.841	1.056	1.509	48.423	1.621	.202
10. RMS roll acceleration deviation during bank in	3.289	2.307	3.225	27.155	814.75	1.733	.181
11. Elevator power during roll	1.191	1.465*	.887*	7.527	61.996	6.313	.002*
12. Aileron power during roll	5.026	4.467	4.500	8.833	980.33	.468	.627
13. RMS pitch rate during roll	4.333	4.823*	4.268*	8.382	118.210	3.663	.029*
14. RMS roll rate deviation during roll	49.519	47.934	49.367	68.846	4,763.36	.751	.474
15. Elevator power during bank-out	5.139	6.850	5.593	70.773	5,371.09	.685	.506
16. Aileron power during bank-out	2.346	3.417	4.114	71.334	2,352.12	1.577	.211
17. RMS pitch rate deviation during bank-out	1.518	2.021	1.814	5.758	143.12	2.092	.128
18. RMS roll rate deviation during bank-out	5.126	5.459	6.542	49.333	2,991.27	.857	.427

All F-ratios calculated with $df_{2,104}$

Barrel Roll							
1. Elevator power during roll	3.474	4.144*	3.111*	24.754	260.365	4.994	.008*
2. Aileron power	1.191	1.181*	1.564*	4.289	53.085	4.201	.170
3. Rudder power	.377	.307	.343	.110	15.050	.380	.684
4. RMS pitch rate deviation	9.688	10.053	9.310	12.409	410.954	1.570	.212
5. RMS roll rate	18.023	17.532*	21.606*	445.334	2,098.737	11.034	.000*
6. Total score	66.986	58.770	60.487	1,690.40	30,649.79	2.867	.061
7. RMS pitch error-top half	9.591	10.602	9.993	23.297	1,210.15	1.001	.371
8. RMS pitch error during bottom half	10.026*	11.457	12.984*	197.706	2,221.710	4.627	.011*

All F-ratios calculated with $df_{2,104}$

Table 3 (Continued)

Source	$\bar{X}(\text{Full})$	$\bar{X}(\text{Med})$	$\bar{X}(\text{Small})$	SSB	SSW	F	P
Overhead Pattern							
1. RMS vertical velocity deviation during pitchout	262.199	263.954	254.570	4,583.03	3,011.576	.161	.851
2. RMS pitchout bank deviation	4.145*	3.298	3.324*	41.813	578.740	8.544	.000*
3. RMS pitchout altitude deviation	39.652	38.103	38.897	108.024	102,562.5	.116	.894
4. Pitchout elevator power	2.131	2.193	2.179	.185	218.742	.089	.914
5. Pitchout aileron power	1.201	1.229	1.282	.307	100.205	.325	.722
6. RMS pitch rate deviation during pitchout	6.963	7.187	7.219	3.511	140.393	2.651	.072
7. RMS roll rate pitchout	7.740	7.979*	8.340*	16.420	501.958	3.467	.033*
8. RMS vertical velocity during downwind	230.977	253.082	246.492	23,183.7	2,111,276.	1.164	.314
9. RMS downwind altitude	35.505	37.628	35.267	304.091	88,049.6	.366	.693
10. Downwind elevator power	1.076	1.159	1.227	1.032	63.444	1.725	.180
11. Downwind aileron power	.651	.641	.709	.242	32.705	.785	.457
12. RMS downwind pitch rate deviation	1.148	1.167	1.122	.091	19.240	.505	.603
13. RMS downwind roll rate deviation	2.965	2.920	3.154	2.759	303.24	.964	.382
14. RMS final turn bank deviation	6.404*	7.921	9.015*	309.530	1,971.813	16.639	.000*
15. RMS final turn airspeed deviation	3.438	3.827	4.099	19.876	798.587	2.638	.073
16. Elevator power final turn	.966*	.956	.806*	1.444	49.965	3.064	.048*
17. Aileron power final turn	.863*	.759	.732*	.859	28.049	3.247	.040*
18. RMS pitch rate final turn	2.718*	2.874*	2.662	2.181	36.239	6.381	.002*
19. RMS final turn roll rate deviation	3.650	3.548	3.608	.478	200.076	.253	.776
20. RMS final approach glidepath deviation	1.246	1.196	1.382	1.667	81.655	2.164	.117
21. RMS final approach course deviation	23.554*	53.936	90.702*	203,506.14	422.977	15.035	.000*
22. Final approach airspeed RMS deviation	3.815*	3.815*	5.366*	134.58	2,498.08	5.710	.003*
23. Landing X position	7.988	9.923	9.591	192.770	9,712.18	2.103	.124
24. Landing Y position	-708.840	-736.079	-780.244	233,730.	15,617,740.	1.586	.207
25. Landing airspeed	79.497	78.875	79.890	47.176	3,674.43	1.361	.258
26. Landing heading	301.780	301.946	301.690	3.029	171.483	1.872	.150
27. Landing vertical velocity	-273.65	-254.029	-269.970	19,580.4	1,596,654.	1.299	.274
28. Elevator power final through landing	2.398	2.380	2.472	.427	235.690	.192	.825
29. Aileron power final through landing	.903*	1.130	1.261*	5.936	63.653	9.885	.000*
30. Rudder power final through landing	.379*	.420	.505*	.739	19.751	3.967	.020*
31. RMS pitch rate final through landing	1.938*	1.312	1.409*	6.599	46.897	14.917	.000*
32. RMS roll rate final through landing	2.913*	3.661*	4.119	66.711	461.564	15.320	.000*
33. RMS vertical velocity final through landing	16.348	16.523	15.890	19.204	2,318.06	.878	.417

Table 3 (Continued)

Source	\bar{X} (Full)	\bar{X} (Med)	\bar{X} (Small)	SSB	SSW	F	P
34. Overall pitch score	63.890	67.423	66.594	614.36	195,232.	.333	.716
35. Overall downwind score	66.401	63.326	59.737	2,002.69	98,451.0	2.156	.118
36. Overall final approach score	17.329	19.478	14.028	1,356.68	86,661.4	1.659	.192
37. Overall landing	81.334	81.736	80.166	119.613	11,904.77	1.065	.346

All F-ratios calculated with df_{2,212}

Ground Controlled Approach

1. Total score	57.675	58.771	59.36	131.897	51,010.27	.268	.764
2. Touchdown airspeed	74.208	74.486	76.030	173.386	8,103.242	2.268	.106
3. Touchdown heading	301.521	301.580	301.533	.179	177.642	.107	.898
4. Touchdown vertical velocity	-154.916	-153.615	-173.771	22,903.13	1,379,232.5	1.760	.174
5. RMS altitude deviation	24.246	23.500	24.305	36.255	23,342.57	.164	.848
6. RMS airspeed deviation	1.760	1.737	1.668	.416	68.587	.644	.526
7. RMS centerline deviation	61.679	63.093	59.309	657.912	104,070.05	.670	.512
8. RMS glidepath deviation	24.482	25.274	24.438	39.808	13,072.49	.322	.724
9. Elevator power prior to glideslope	.345	.290	.300	.155	9.298	1.772	.172
10. Aileron power prior to glideslope	.373	.353	.381	.036	6.598	.582	.559
11. RMS pitch rate deviation prior to glideslope	.626	.604	.611	.022	6.143	.389	.678
12. RMS roll rate deviation prior to glideslope	1.763	1.739	1.941	2.186	80.185	2.890	.057
13. Elevator power on glideslope	4.459	4.343	3.955	12.571	1,114.639	1.195	.304
14. Aileron power on glideslope	.851	.791	.831	.165	94.535	.186	.830
15. Rudder power on glideslope	1.073	1.048	1.133	.338	122.55	.293	.746
16. RMS pitch rate deviation	1.201	1.222	1.164	.151	13.101	1.226	.295
17. RMS roll rate on glideslope	2.013	1.981*	2.359*	7.919	245.29	3.422	.034*

All F-ratios calculated with df_{2,212}*Indicates significant ($p < .05$) difference found.

conditions. Furthermore, 7 of these 12 measures also showed worst performance under the most restricted FOV condition. Those significant measures demonstrating worst performance in other than the most restricted display condition were: elevator, aileron power and RMS pitch rate in the final turn, and RMS pitch rate in the final through landing segments.

Multivariate significance was also demonstrated for the FOV variable in the GCA maneuver. In this maneuver, however, only one of the 17 dependent variables (RMS roll rate on the glideslope) showed a significant univariate effect. In this measure, best performance was demonstrated in the medium FOV setting followed by somewhat poorer performance under the maximum FOV condition and worst performance in the smallest FOV condition.

Motion. Significant multivariate motion effects were demonstrated in three of the five maneuvers investigated in this study: the loop, overhead pattern and GCA. Additionally, the motion effects

approximated significance ($p < .096$) on another maneuver, the barrel roll. Table 4 illustrates the univariate analyses and means for the dependent measures in the three maneuvers.

Table 4. Univariate Motion Main Effects and Means Across Maneuvers

Source	$\bar{X}(\text{Off})$	$\bar{X}(3 \text{ DOF})$	$\bar{X}(6 \text{ DOF})$	SSB	SSW	F	P
Loop							
1. Elevator power	5.107	5.556	5.829	11.979	562.769	1.106	.334
2. Aileron power	.346	.394	.458	.285	15.393	.965	.384
3. RMS pitch rate deviation	13.150	13.116	13.462	3.263	182.319	.930	.397
4. RMS roll rate deviation	2.278	2.374	2.550	1.703	179.136	.494	.611
5. Total score	41.292*	52.857*	54.880*	1,282.415	48,352.65	1.379	.007*
6. RMS groundtrack deviation	125.143	123.876	120.127	612.324	1,171,658.8	.027	.973
7. RMS pitch deviation	3.310	3.165	3.011	2.011	74.087	1.411	.248
F-ratios calculated with df _{2,104}							
Overhead Pattern							
1. RMS vertical velocity deviation during pitchout	261.191	269.743	249.689	18,228.16	3,011,576.9	.641	.527
2. RMS pitchout bank deviation	3.870	3.600	3.297	14.776	518.740	3.019	.050
3. RMS pitchout altitude deviation	41.382	37.903	37.366	855.888	102,562.55	.884	.414
4. Pitchout elevator power	2.047	2.197	2.260	2.158	218.742	1.045	.353
5. Pitchout aileron power	1.179	1.253	1.281	.492	100.205	.520	.594
6. RMS pitch rate deviation during pitchout	7.099	7.077	7.195	.709	140.393	.535	.586
7. RMS roll rate deviation during pitchout	8.125	7.982	7.952	1.547	501.958	.326	.721
8. RMS vertical velocity during downwind	247.032	235.856	247.663	7,941.54	2,111,276.6	.398	.671
9. RMS downwind altitude deviation	36.559	33.765	38.075	860.371	88,049.663	1.035	.356
10. Downwind elevator power	.944*	1.169	1.349*	7.399	63.444	12.363	.000*
11. Downwind aileron power	.608	.701	.692	.470	1.318	1.525	.219
12. RMS downwind pitch rate	1.085*	1.128	1.224*	.918	19.240	5.062	.007*
13. RMS downwind roll rate deviation	3.084	3.000	2.956	.756	303.241	.264	.767
14. RMS final turn bank deviation	7.668	7.908	7.764	2.623	1,971.813	.141	.868
15. RMS final turn air-speed deviation	3.837	4.012	3.514	11.490	798.587	1.525	.220
16. Final turn elevator power	.772*	.903	1.053*	1.444	49.965	7.522	.000*
17. Final turn aileron power	.614*	.837*	.902	.859	28.049	15.325	.000*
18. RMS final turn pitch rate deviation	2.709	2.739	2.807	.453	36.239	1.326	.267
19. RMS final turn roll rate deviation	3.435	3.666	3.705	3.843	200.076	2.036	.133
20. RMS final approach glidepath deviation	1.325	1.182	1.318	1.157	81.655	1.502	.225
21. RMS final approach course deviation	65.796	54.595	47.801	14,863.35	1,434,750.7	1.098	.335
22. RMS final approach air-speed deviation	4.254	4.563	4.294	5.074	2,498.084	.215	.800
23. Landing X position	8.045	9.273	10.183	207.222	9,712.184	2.261	.106
24. Landing Y position	-733.852	-725.221	-766.090	83,523.27	15,817,740.	.566	.568
25. Landing airspeed	79.651	79.479	79.132	12.590	3,674.431	.363	.695
26. Landing heading	301.584*	302.032*	301.800	3.029	171.483	5.576	.004*
27. Landing vertical	-267.283	-269.269	-261.097	3,269.967	1,596,654.4	.217	.805
28. Final through landing elevator power	2.091*	2.528	2.631*	.427	235.690	6.656	.001*

Table 4 (Continued)

Source	$\bar{X}(\text{Off})$	$\bar{X}(3 \text{ DOF})$	$\bar{X}(6 \text{ DOF})$	SSB	SSW	F	P
29. Aileron power final through landing	1.032	1.187	1.075	1.159	63.653	1.930	.147
30. Rudder power final through landing	.393	.454	.457	.238	19.751	1.278	.280
31. RMS pitch rate final through landing	1.238	1.264	1.264	.034	46.897	.077	.925
32. RMS roll rate final through landing	3.794	3.564	3.335	9.482	461.564	2.177	.115
33. RMS vertical velocity final through landing	116.170	16.331	16.260	1.166	2,318.062	.053	.948
34. Overall pitch score	62.205	69.222	66.479	2,251.185	195,232.78	1.222	.296
35. Overall downwind score	61.356	65.590	62.517	861.623	98,451.057	.927	.397
36. Overall final approach score	18.024	18.061	14.794	650.844	86,661.405	.796	.452
37. Overall landing score	80.075	81.322	81.838	147.884	11,904.779	1.316	.270

All F-ratios calculated with $df_{2,212}$

Ground Controlled Approach

1. Total score	60.763	55.840	59.205	1,139.474	52,010.277	2.322	.100
2. Touchdown airspeed	74.326	75.317	75.080	48.201	8,103.242	.630	.533
3. Touchdown heading	301.575	301.575	301.484	.501	177.642	.299	.741
4. Touchdown vertical velocity	-156.466	-169.122	-156.71	9,424.665	1,379,232.5	.724	.485
5. RMS altitude deviation	23.196	25.317	23.538	233.334	23,342.570	1.059	.348
6. RMS airspeed deviation	1.703	1.784	1.678	.555	68.587	.858	.425
7. RMS centerline	59.53	66.55*	57.98*	3,756.283	104,070.05	3.825	.023*
8. RMS glidepath deviation	24.730	24.406	25.058	19.079	13,072.493	.154	.856
9. Elevator power prior to glideslope	.26*	.32	.34*	.155	9.298	3.484	.032*
10. Aileron power prior to glideslope	.31*	.40*	.38	.443	6.598	7.128	.001*
11. RMS pitch rate prior to glideslope	.57*	.62	.63*	.198	80.185	3.433	.034*
12. RMS roll rate prior to glideslope	1.67*	1.90*	1.86	2.597	80.185	3.433	.034*
13. Elevator power on to glideslope	4.317	4.496	3.944	14.262	1,114.639	1.356	.259
14. Aileron power on glideslope	.61*	.96*	.89	6.144	94.535	6.889	.001*
15. Rudder power on glideslope	1.000	1.175	1.079	1.379	122.555	1.193	.305
16. RMS pitch rate deviation on glideslope	1.180	1.217	1.190	.065	13.101	.531	.588
17. RMS roll rate on glideslope	1.78*	2.28*	2.27	14.749	245.290	6.373	.002*

All F-ratios calculated with $df_{2,212}$

* Indicates significance ($p < .05$).

In the loop, only one of seven total measures, total score, registered significance due to the motion variable. In this case, best performance was demonstrated under full 6 DOF with somewhat poorer performance under 3 DOF motion and worst performance under the no-motion condition. This was the only univariate case in the study where best performance was demonstrated with the full motion condition.

Six dependent measures in the overhead pattern maneuver showed significant effects due to the platform motion variable. Five of these measures showed superior performance under the no-motion condition, and showed corresponding decrements in performance as DOFs were added to the platform motion's operation. The other measure, landing heading showed significant differences in another direction.

Motion main effects in the GCA were exhibited in Seven of the 17 total measures which were collected. Of these seven, six measures demonstrated best performance accompanied by the no-motion condition and poorer performance associated with some form of motion. Those measures were: elevator power, aileron power, RMS pitch rate, RMS roll rate prior to glideslope interception, and aileron power, RMS roll rate after glideslope interception.

G-Seat. The final system variable to be investigated, the G-seat, was conspicuous by the complete absence of significant multivariate effects in any of the maneuvers. This is the only occurrence in the study where a significant main effect did not surface.

Ceiling/Visibility. The only environmental variable evaluated in this study, ceiling/visibility, produced multivariate and univariate significance in the two maneuvers where it was manipulated. Table 5 presents the dependent variables in these two maneuvers, the overhead pattern and the GCA. Nineteen of the measures in the overhead pattern demonstrated a significant ceiling/visibility effect, all of which showed best performance with clear conditions. Similarly, in the GCA maneuver, 14 of the 17 measures collected showed significance on this variable, all with best performance demonstrated under the clear conditions.

Table 5. Univariate Ceiling/Visibility Main Effects and Means Across Maneuvers

Source	\bar{X} (Clear)	\bar{X} (Min)	SSB	SSW	F	P
Overhead Pattern						
1. RMS vertical velocity deviation during pitchout	264.397	256.018	4,739.539	3,011,576.9	.333	.564
2. RMS pitchout bank deviation	3.677	3.501	2.095	518.740	.856	.355
3. RMS pitchout altitude deviation	38.508	39.259	38.114	102,562.55	.078	.779
4. Pitchout elevator power	2.012	2.323	6.559	218.742	6.357	.012*
5. Pitchout aileron power	1.211	1.264	.194	100.205	.410	.522
6. RMS pitch rate deviation during pitchout	7.146	7.101	.139	140.393	.210	.647
7. RMS roll rate deviation during pitchout	7.995	8.044	.165	501.958	.069	.792
8. RMS downwind vertical velocity	209.324	277.710	315,668.38	2,111,276.6	31.697	.000*
9. RMS downwind altitude deviation	30.614	41.652	8,223.804	88,049.663	19.800	.000*
10. Downwind elevator power	.959	1.349	10.290	63.444	34.385	.000*
11. Downwind aileron power	.538	.796	4.503	32.705	29.194	.000*
12. RMS downwind pitch rate deviation	.925	1.367	13.168	19.240	145.090	.000*
13. RMS downwind roll rate deviation	2.687	3.339	28.630	303.241	20.016	.000*
14. RMS final turn bank deviation	7.362	8.198	47.245	1,971.81	5.079	.025*
15. RMS final turn airspeed deviation	3.371	4.199	45.622	798.587	12.111	.000*
16. Final turn airspeed power	.793	1.025	3.642	49.965	15.453	.000*
17. Final turn aileron power	.695	.874	2.150	28.049	16.257	.000*
18. RMS final turn pitch rate deviation	2.681	2.822	1.338	36.239	7.831	.005*
19. RMS final turn roll rate deviation	3.316	3.889	22.132	200.076	23.452	.000*
20. RMS final approach glidepath deviation	1.223	1.326	.719	81.655	1.868	.173
21. RMS final approach course deviation	54.373	57.755	772.027	1,434,750.7	.114	.735
22. RMS final approach airspeed deviation	3.818	4.922	82.207	2,498.084	6.976	.008*

Table 5 (Continued)

Source	\bar{X} (Clear)	\bar{X} (Min)	SSB	SSW	F	P
23. Landing X position	10.518	7.816	492.699	9,712.184	10.754	.001*
24. Landing Y position	-744.206	-739.236	1,667.520	15,617,740.	.022	.880
25. Landing airspeed	79.119	79.723	24.607	3,674.431	1.419	.234
26. Landing heading	301.835	301.835	.244	171.483	.301	.583
27. Landing vertical velocity	-263.609	-268.157	1,396.057	1,596,654.4	.185	.667
28. Elevator power final through landing	2.352	2.481	1.136	235.690	1.022	.313
29. Aileron power final through landing	1.02	1.17	1.639	63.653	5.462	.020*
30. Rudder power final through landing	.419	.450	.066	19.751	.709	.400
31. RMS pitch rate final through landing	1.230	1.276	.140	46.897	.637	.425
32. RMS roll rate final through landing	3.395	3.735	7.794	461.564	3.579	.059
33. RMS vertical velocity acceleration deviation final through landing	15.814	16.694	52.307	2,318.062	4.783	.029*
34. Overall pitch score	66.508	65.429	78.501	195,232.78	.085	.770
35. Overall downwind score	70.069	56.240	12,908.604	98,451.057	27.796	.000*
36. Final approach score	19.571	14.319	2,862.059	86,661.405	4.555	.034*

All F-ratios calculated with df_{1,212}

Ground Controlled Approach

1. Total score	62.975	54.230	5,162.095	52,010.27	21.041	.000*
2. Touchdown airspeed	74.706	75.109	11.001	8,103.242	.287	.592
3. Touchdown heading	301.667	301.422	4.059	177.642	4.845	.028*
4. Touchdown vertical velocity	-159.074	-162.461	774.516	1,379,232.5	.119	.730
5. RMS altitude deviation	22.125	25.909	966.550	23,342.570	8.778	.003*
6. RMS airspeed deviation	1.534	1.909	9.497	68.587	29.357	.000*
7. RMS centerline deviation	54.135	68.586	14,096.321	104,070.05	28.715	.000*
8. RMS glidepath deviation	23.768	25.694	250.369	13,072.493	4.060	.045*
9. Elevator power prior to glideslope	.267	.356	.532	9.298	12.151	.000*
10. Aileron power prior to glideslope	.301	.437	1.240	6.498	39.845	.000*
11. RMS pitch rate prior to glideslope	.521	.707	2.351	6.143	81.148	.000*
12. RMS roll rate prior to glideslope	1.389	2.240	48.806	80.185	129.039	.000*
13. Elevator power on glideslope	3.945	4.559	25.419	1,114.639	4.834	.029*
14. Aileron power on glideslope	.553	1.096	19.870	94.535	44.560	.000*
15. Rudder power on glideslope	.794	1.375	22.748	122.553	39.351	.000*
16. RMS pitch rate deviation on glideslope	1.175	1.216	.114	13.101	1.852	.175
17. RMS roll rate on glideslope	1.523	2.713	95.580	245.290	82.607	.000*

All F-ratios calculated with df_{1,212}

*Indicates significance ($p < .05$).

Interactions. Only one interaction reached the criterion for multivariate significance in any of the five maneuvers. One other interaction, the first order FOV by platform motion interaction in the loop approximated significance ($p < .07$), but did not exceed the selected criterion ($p < .05$). The interaction attaining a significant level was the first order platform motion by ceiling/visibility interaction in the GCA maneuver. Table 6 depicts the univariate analyses and cell means for all of the dependent measures in this maneuver.

Table 6. Univariate Motion by Ceiling/Visibility Interactions in the Ground Controlled Approach

Source	\bar{X} (Clear)			\bar{X} (Minimums)			F	P
	\bar{X} (Off)	\bar{X} (3 DOF)	\bar{X} (6 DOF)	\bar{X} (Off)	\bar{X} (3 DOF)	\bar{X} (6 DOF)		
1. Total score	62.804	62.277	63.844	58.722	49.403	54.566	1.792	.169
2. Touchdown airspeed	74.259	74.498	75.360	74.393	76.135	74.800	.742	.477
3. Touchdown heading	301.15	301.722	301.565	301.435	301.428	301.403	.141	.868
4. Touchdown vertical velocity	-155.782	-155.839	-165.600	-157.151	-182.404	-147.832	1.710	.183
5. RMS altitude deviation	21.768	23.070	21.537	24.625	27.564	25.538	.143	.866
6. RMS airspeed deviation	1.522	2.581	1.500	1.885	1.987	1.856	.048	.952
7. RMS centerline deviation	53.160	56.314	52.930	65.904	76.805	63.048	1.333	.265
8. RMS glidepath deviation	25.347	23.497	22.461	24.144	25.316	27.654	3.768	.024*
9. Elevator power prior to glideslope	.225	.303	.274	.305	.350	.414	1.140	.321
10. Aileron power prior to glideslope	.276	.326	.303	.350	.490	.471	2.039	.132
11. RMS pitch rate deviation prior to glideslope	.485	.551	.526	.667	.705	.750	.956	.385
12. RMS roll rate deviation prior to glideslope	1.327	1.444	1.396	2.027	2.359	2.335	1.016	.363
13. Elevator power on glideslope	4.195	3.813	3.828	4.43	5.179	4.060	1.813	.165
14. Aileron power on glideslope	.456	.551	.654	.775	1.379	1.134	3.418	.034*
15. Rudder power on glideslope	.680	.759	.944	1.320	1.590	1.214	3.162	.004*
16. RMS pitch rate on glideslope	1.162	1.128	1.235	1.198	1.306	1.145	6.528	.001*
17. RMS roll rate deviation	1.343	1.455	1.770	2.231	3.123	2.783	3.413	.034*

All F-ratios calculated at $df_{2,212}$

*Indicates significance ($p < .05$).

Analysis of this interaction shows all of the five measures generally associating superior performance with the clear ceiling/visibility conditions.

Subject Effects. Significant multivariate subject effects were demonstrated in all of the maneuvers studied. These subject differences were also manifested in nearly all of the univariate analyses of the individual dependent measures. No overall performance hierarchy for the subjects was established, because this information was not pertinent to this study.

Effect Strengths. In an attempt to determine the relative strengths of the various independent variable main and interactive effects upon the subjects' performances on the five maneuvers, percentages of nonerror sums of squares were computed for each measure registering univariate significance following a significant multivariate test. Table 7 presents this information for the aerobatic maneuvers: the loop, aileron roll, and the barrel roll. In these maneuvers, the subject effects were most prominent. Consistently, subject differences accounted for the largest portion of the performance variability on each measure. This percentage ranged from 15 to 89 percent of the total variability in the performances of these maneuvers. The percentages for the field-of-view and motion factors were highly variable from measure to measure. The values ranged from 2 to 16 percent for the FOV factor and from .4 to 12 percent for the platform motion factor. The final factor, the G-seat, was considerably more consistent across dependent measures and across maneuvers. The percentage of the performance variability due to the G-seat ranged from .04 to 2 percent, which was dramatically lower than the other factors.

Table 7. Percentages of Nonerror Sums of Squares for the Loop, the Aileron Roll and the Barrel Roll Maneuvers

	Source						
	A(FOV)	B(MOT)	C(G-Seat)	S(Subj)	AB	AC	BC
Loop							
5. Total score	3.28	12.38*	2.78	43.85*	12.17*	2.58	4.69
7. RMS pitch deviation	2.62	6.36	1.69	54.11*	6.29*	4.81	6.08
Aileron Roll							
2. Average score of bankin and bankout	16.34*	8.10	.93	15.17	8.96	8.21	15.57
11. Elevator power during roll	8.94*	5.65	1.45	66.78*	2.83	6.79	3.65
13. RMS pitch rate deviation during roll	3.20*	.40	.42	87.38*	.27	1.59	2.12
Barrel Roll							
1. Elevator power	5.56*	2.18	.04	78.71*	1.95	2.82	3.37
2. Aileron power	2.62*	1.07	.48	89.38*	.89	1.64	1.41
5. RMS roll rate deviation	8.95*	3.64*	.23	75.53*	2.84	2.62	1.59
8. RMS pitch-error bottom half	7.76*	1.58	.30	75.36*	2.73	1.27	3.92

*Indicates univariate significance ($p < .05$) was also present.

Table 8 provides percentage information for the GCA maneuver. Subject effects were again most prominent across the various dependent measures. The subject effect sizes ranged from 15 to 74 percent of the nonerror variability. The ceiling/visibility variable, added in this maneuver, also produced relatively large effect strengths. In this maneuver, the percentage values ranged from .4 to 47 percent of the performance variability. The percentage values for the FOV factor in the GCA were somewhat reduced from the values exhibited in the aerobatic maneuvers. In this maneuver, the FOV percentages ranged from .17 to 6 percent of the nonerror variability. The motion factor recorded similar percentages on this maneuver as in previously reported maneuvers, within the range from .25 to 8 percent. The G-seat percentages were somewhat elevated in this maneuver ranging from .03 to 8 percent, dependent upon the specific measure observed. The motion by ceiling/visibility interaction which was found to be significant in the GCA maneuver also shows some enlargement in the percentages of nonerror variability for the various measures. The values for this index range from .07 to 6 percent.

Table 9 depicts the effect strength information for the overhead pattern maneuver. Again, subject effects were the most prominent effect noted, varying between 4 and 74 percent dependent upon the measure. The ceiling/visibility factor also frequently accounted for a relatively large portion of the nonerror variability, between .03 and 54 percent. The percentages associated with the FOV factor were also highly variable, ranging from .12 to 40 percent. Similarly, the motion factor registered wide variability in its effect strengths (.08 to 17 percent). The G-seat percentages, however, were again very consistent in magnitude, varying between .01 to 3 percent.

IV. DISCUSSION OF STUDY II

Because of the importance of information regarding the effects of simulator design configurations upon pilot performance to the Air Force and other agencies involved in flight simulation, it is appropriate that the results of this study be placed in proper perspective. The results of this study concern only the performance of experienced pilots and cannot be generalized to student pilot behaviors or to the training situation in general. In addition, this effort evaluated the effects of the cueing devices within the context of the ASPT. Other simulators representing different hardware design features or software methods may or may not produce the same sort of results. Finally, the effects of these cue enhancement devices (platform

Table 8. Percentages of Nonerror Sums of Squares for the GCA Maneuver

Variable	Source												
	A (FOV)	B (MOT)	C (G-seat)	D (C/V)	S (Subj)	AB	AC	BC	AD	BD	CD	ABC	ABD
1. Total score	.17	1.49	1.27	6.76*	74.53*	1.70	1.49	1.04	.71	1.15	.77	2.61	1.67
2. Touchdown airspeed	6.25	1.74	.28	.40	61.53*	6.28	2.39	5.28	10.57*	2.05	4.10	19.28	2.64
3. Touchdown heading	.48	1.33	1.20	10.73*	20.17*	4.99	1.95	1.29	1.43	.62	1.47	13.20	1.41
5. RMS altitude deviation	.39	2.49	3.19	10.30*	59.04*	2.72	2.11	1.24	.39	.34	3.65	3.31	3.18
6. RMS airspeed deviation	.98	1.30	6.73*	22.32*	43.02*	1.08	.87	.29	2.58	.07	.09	7.68	2.84
7. RMS centerline deviation	.34	1.92	.86	7.22*	74.91*	2.15	1.99	.74	.11	.67	1.15	2.71	.61
8. RMS glidepath deviation	.52	.25	8.38*	3.26*	44.47*	3.68	4.85	2.05	1.79	6.05*	.62	10.52	3.07
9. Elevator power prior to glideslope	4.19	8.24*	1.48	14.37*	15.43*	2.80	3.20	6.56	.07	2.70	1.13	9.80	4.52
10. Aileron power prior to glideslope	.58	7.12*	.58	19.91*	54.16*	.65	1.76	2.26	1.56	2.04	1.35	2.90	.45
11. RMS pitch rate deviation prior to glideslope	.46	4.03*	.98	47.66*	22.65*	2.06	2.12	2.24	.43	1.12	.03	4.29	.80
12. RMS roll rate deviation prior to glideslope	1.98	2.35	.15	44.13*	38.75*	.68	.39	1.89	2.00	.69	1.28	2.56	1.89
13. Aileron power on glideslope	2.32	2.63	.40	4.69*	25.52*	2.66	5.48	8.52	1.67	3.52	.50	14.15	1.15
14. Aileron power on glideslope	.23	8.69*	.03	28.09*	36.27*	.92	2.94	3.15	1.99	4.31*	.50	3.18	1.67
15. Rudder power on glideslope	.23	.93	.36	15.28*	63.52*	.78	4.14*	.87	.85	2.46*	1.00	1.99	1.73
16. RMS pitch rate deviation on glideslope	1.13	.49	1.55	.85	68.46*	3.20	2.96	2.00	.99	6.03*	.22	4.18	.75
17. RMS roll rate deviation on glideslope	2.84*	5.29*	.24	34.28*	41.92*	1.08	1.61	1.79	.37	2.83*	.52	1.83	1.53
													.44
													.54
													2.90

*Indicates univariate significance ($p < .05$) was also present.

Table 9. Percentages of Nonerror Sums of Squares for the Overhead Pattern Maneuver

Variable	Source															
	A (FOV)	B (MOT)	C (G-seat)	D (C/V)	S (Subj)	AB	AC	BC	AD	BD	CD	ABC	ABD	ACD	BCD	ABCD
2. RMS pitchout bank deviation	7.89*	2.79	.21	.40	70.60*	.54	1.65	.63	1.53	.44	.63	3.93	1.43	2.89	1.27	3.19
4. Pitchout elevator power	.12	1.44	2.53	4.37*	63.25*	1.30	1.52	3.97	.32	3.23	.69	6.83	1.56	2.67	2.03	4.17
7. RMS roll rate deviation during pitchout	3.21*	.30	.10	.03	68.45*	2.32	1.38	.23	.70	1.89	2.82*	4.43	2.21	.78	2.42	8.74*
8. RMS Vertical Velocity during downwind	1.28	.44	1.87	17.46*	46.71*	.44	1.38	.32	2.74	2.92	.41	9.70*	.99	5.46*	2.42	5.46
9. RMS Downwind altitude deviation	.64	1.80	.51	17.19*	33.25*	1.34	1.82	2.21	3.93	1.19	.43	14.17*	3.00	4.75	4.05	9.73
10. Downwind Elevator power	2.21	15.82*	.01	22.00*	36.05*	1.07	5.42	1.09	.24	1.06	.26	4.78	.86	3.01	1.74	4.36
11. Downwind alleron power	.70	1.36	1.25	13.05*	65.76*	1.85	1.37	.84	.54	2.19	.97	2.62	1.81	.42	1.43	3.82
12. RMS downwind pitch rate deviation	.38	3.82*	.44	54.71*	28.86*	.94	1.89	.22	.55	1.52	.17	1.85	.38	2.13	1.06	1.08
13. RMS downwind roll rate deviation	.98	.27	.90	10.22*	62.65*	1.54	1.33	.25	.50	2.98	.12	3.41	2.67	2.35	3.13	6.70
14. RMS final turn bank deviation	36.56*	.31	2.01	5.58*	10.80*	1.12	7.28	1.85	10.71*	.09	.89	3.60	11.05*	4.15	.71	3.29
15. RMS final turn airspeed deviation	4.10	2.37	.46	9.42*	46.97*	2.70	4.31	2.65	.57	.67	1.70	7.02	3.00	5.05	2.06	6.95
16. Final turn elevator power	3.28*	8.06*	1.08	8.28*	53.91*	2.65	1.69	1.17	.77	1.23	1.58	5.21	.97	1.83	4.66	3.62
17. Final turn alleron power	2.98*	14.06*	.16	7.46*	55.71*	.77	.09	1.61	.74	.44	2.50	7.17	2.90	.61	1.42	1.37
18. RMS final turn pitch rate deviation	7.49*	1.56	.17	4.60*	54.47*	.79	1.93	2.13	2.34	2.08	2.79	6.61	.85	.68	1.80	9.73*
19. RMS final turn roll rate deviation	.44	3.55	.13	20.45*	36.91*	1.08	.93	5.10	1.91	2.63	.93	12.44	4.72	3.46	1.80	3.51
21. RMS final approach course deviation	40.72*	2.97*	3.51	.15	17.68*	1.44	3.04	.99	.10	.08	.77	7.13	2.04	1.03	2.21	16.14
22. RMS final approach airspeed deviation	8.09*	.30	1.66	4.94*	44.05*	2.73	.58	1.89	2.26	4.97*	.36	8.87	7.94*	2.48	1.54	7.32
23. Landing X position	7.44	7.99	1.94	19.01*	4.97	.23	3.40	4.04	5.04	1.97	1.75	9.66	6.22	5.06	2.54	18.75
26. Landing Heading	3.30	9.82*	1.24	.27	42.27*	9.40*	2.92	8.55	1.00	.82	1.26	5.69	1.86	1.74	1.41	8.45
28. Elevator power final turn through landing	.57	17.80*	1.45	1.37	23.84*	12.00	3.98	9.04	2.38	3.38	1.55	9.96	.08	5.96	1.41	5.28
29. Alleron power final turn through landing	13.44*	2.62	3.01	3.71*	53.68*	2.39	1.50	1.13	.56	2.33	.18	.77	3.09	2.47	3.70	5.42
30. Rudder power final turn through landing	3.37*	1.08	.72	.30	74.73*	1.43	.56	2.90	.14	3.45*	.76	4.78	1.42	2.01	.22	2.13
31. RMS pitch rate final turn through landing	30.59*	.16	2.35	.65	25.12*	1.59	2.70	4.01	.32	3.47	.60	7.68	2.70	1.78	3.51	12.74
32. RMS roll rate final turn through landing	21.61*	3.07	2.05	2.53	44.22*	.51	.89	1.26	4.08	2.13	.09	2.10	2.30	4.53	2.67	6.95
33. RMS vertical velocity final turn through landing	1.36	.08	.78	3.71*	38.01*	1.75	.89	9.59	.95	6.52	1.66	13.80*	4.35	4.86	1.67	10.03
35. Overall downwind score	2.92	1.26	.86	18.81*	16.54*	3.83	1.11	.53	3.25	4.17*	1.13	14.32*	7.06*	10.61*	2.45	11.15
36. Overall final approach score	2.93	1.41	1.88	4.03*	51.47*	.68	1.33	5.23	2.96	.37	2.70	7.78	1.47	3.70	2.00	10.07

* Indicate univariate significance was also found.

motion, G-seat and visual display) are strictly specific to the types of maneuvers being investigated. It seems reasonable to expect that the devices vary in their effectiveness dependent upon the particular portion of the flight regime of the aircraft being simulated.

System Design Variables. The field-of-view variable was found to significantly impact pilots' performance on four of the five maneuvers in this study. In the aileron roll, the results suggest that the width of the visual display directly affects the pilots' ability to control the simulated aircraft both in pitch and roll dimensions. While the pilots tended to score better on bank in, out and roll control under full FOV conditions, they seemed to demonstrate superior elevator and hence pitch control when under restricted FOV conditions. One possible explanation for this phenomenon is that the additional peripheral information is useful and important for control of the vehicle in the roll dimension but is irrelevant information for pitch control. Thus, when the extraneous information is removed and concentration is directed toward the front of the vehicle, pitch response is improved. This improvement occurs as a decrease in the amount of effort expended and an increase in the smoothness of the effort used in controlling the simulator.

The same trends concerning the FOV appear in the barrel roll where roll performance tends to be poorer under the most restricted FOV when compared to the larger display sizes. Again, the exception lies in the extent of the pilots' inputs to the elevators. Under the most restricted condition, the elevator inputs become smaller, probably in response to the loss in extraneous signals.

In the overhead pattern maneuver, the loss of visual information was manifested particularly within the pitchout, final turn, and final approach segments. In the pitchout and final turn, the pilots again appeared to be making fewer, less extensive inputs to the elevators thereby resulting in smoother pitch rate scores, but less accurate overall aircraft control. Aileron control in these segments generally was degraded as a function of display size reduction. The more restricted the display became, the poorer the performance in those measures reflecting aileron control. However, the results for the final approach suggested a change in the control strategy used. During the final approach, as the runway came into view, the pilot increased his inputs to the elevators and, in effect, worked harder in an attempt to land the aircraft. However, his overall performance tended to remain degraded in spite of his efforts.

Only one of 17 measures was affected by changes in the FOV in the GCA maneuver. Again, this measure reflected the pilots' ability to maintain the proper lateral stability in this case on the glideslope segment. However, no changes were exhibited in pitch control or control strategies.

Motion. The manipulation of the degrees of freedom in the platform motion system resulted in significant performance differences in the loop, the overhead pattern, and the GCA. In the loop, the total score, which was a derived score, exhibited best performance when accompanied by motion. This was the only measure of the seven measures collected which demonstrated any significant differences due to platform motion. Because of this inconsistency, this instance may be an artifact, possibly due to the manner in which the total score was derived. However, other tracking-type studies (Borlace, 1967; Koonce, 1974) have reported enhanced performance with the platform motion operational, and this result may be related to such effects. In these studies, pilot errors were significantly reduced when maneuvers were flown in the simulator with platform motion, as compared to when flown without motion.

The absence of any consistent and reliable motion effect in the two higher G-maneuvers, the loop and the barrel roll, was somewhat surprising. It was initially anticipated that the relatively quick onset and large magnitude of motion cues intrinsic to these maneuvers would tend to highlight any possible performance differences due to motion configurations. Apparently, this was not the case as only the total score variable manifested significance and that in a direction contrary to the vast majority of other measures which were sensitive to platform motion manipulation.

The results of the overhead pattern were considerably more consistent in the trends exhibited. The effects of the motion variable were manifested within the downwind, final turn and final approach segments. In these segments, it appeared that the introduction of motion, either 3 or 6 DOF, fundamentally affected the pilots' pitch control. The amount of pilot input to the elevators in all of these segments was

substantially increased when motion was added. Likewise, pilot inputs to the ailerons were increased in the final turn segment, probably in an attempt to control for the increased instability in the aircraft's movements. The fewer inputs by the pilots under the no-motion condition seemed to result in smoother pilot responses as evidenced by the improved performance on the RMS pitch rate on the downwind segment. In only one case was performance under motion superior to performance without, that being in the landing heading of the vehicle. In this instance, performance with 3 DOF was superior to no-motion performance.

The same general trends were demonstrated in the performance of the GCA. Performance under the no-motion condition was consistently superior to performance under either 3 or 6 DOF motion. Fewer, smoother aileron and elevator inputs were made by the pilots in completing this task when platform motion was absent. However, few reliable differences were found between the 3 and 6 DOF conditions.

Environmental Variable. The ceiling/visibility variable demonstrated consistent significant effects upon the two maneuvers wherein it was manipulated. In the overhead pattern, performance on all segments, pitchout, downwind, final turn and final approach to landing, was deleteriously affected when the ceiling and visibility conditions were reduced. The aircraft performance parameters, the pilot input measures and the derived scores were all affected in this manner. The same performance decrements were exhibited in the GCA analysis. Again, all three types of measures were similarly affected. This consistent demonstration (14 out of 17 measures) provided strong evidence that the algorithms used in generating the environmental variable were valid, in that performance was, as anticipated, degraded when environmental conditions deteriorated.

Interaction. Only one interaction achieved significance in any of the maneuvers investigated in this study. The first-order platform motion by ceiling/visibility interaction demonstrated significance in the GCA. This interaction suggested that the motion and ceiling/visibility variables combined synergistically when used together. In this maneuver, the interaction was illustrated by differential motion effects dependent upon the environmental conditions. Under clear conditions, the subject pilots tended to perform the flight task better with full motion. In these situations, the performance was generally improved by making more extensive inputs to the ailerons and rudder. This increased activity with the controls, thereby resulted in less smooth rate changes, notably pitch rate and roll rate on glideslope. However, when the task was performed under minimum ceiling/visibility conditions, the pilots appeared to have improved performances without motion cueing. In these cases, the pilots also tended to make fewer control inputs to the ailerons and rudder. Under the ceiling/visibility conditions, the pilots were most probably flying completely on their instruments.

V. DISCUSSION OF STUDIES I AND II

Several important differences existed between the two studies. One important variation is that the motion, G-seat, and flight dynamic equations of the ASPT were modified during the intervening time period between the studies. Although these modifications were made as "improvements" to the systems from an engineering standpoint, it is uncertain as to what physiological or psychological impact these changes may have caused.

Secondly, several performance measurement routines had been updated in the time between the studies. Again, although the changes were made in the interest of improvement, it is uncertain as to whether the updated versions have become more or less sensitive to the variables under consideration.

Another difference between the studies arises from the fact that a separate visual environment was utilized in each study. The visual environment utilized in the second study represented superior display capabilities not only in the modeling of the ground area within immediate proximity of the airfield but also in the ability to manipulate visual display dimensions.

These differences in the various capabilities of the ASPT, motion, G-seat, performance measurement, and visual display, could have certainly altered the effects of these devices on the pilots' performances. In

spite of the various uncontrolled changes in the simulator, the results of Study II seem to be in general agreement with the data of the earlier study.

Table 10 illustrates the locations of the significant multivariate effects found across all of the maneuvers in the two studies. Within this table, the hyphenated areas represent effects which were not estimated for various specific reasons. Empty spaces represent nonsignificant effects. Inspection of this

Table 10. Comparison of Significant Multivariate Effects Across Study I and Study II Maneuvers

Effect	Alleron Roll		GCA		Ovhd Ptn		Slo Flt	Takeoff	Barrel Roll	Loop
	II	I	II	I	II	I	I	I	II	II
A(MOT)		*	*	*	*	*	*	*	0	*
B(FOV)	*	*	*		*	*	*		*	*
C(G-Seat)			*	*	*	*		*		
D(C/V)	-	-	*	*	*	*	-	*	-	-
E(Winds)	-	-	-	*	-	*	-	*	-	-
F(Turb)	-	-	-	*	-	*	-	*	-	-
S(Block)	*	*	*	*	*	*	*	*	*	*
AB(MOTxFOV)				*				*		0
AC					*			*		
AD	-	-	*				-		-	-
AE	-	-	-		-		-		-	-
AF	-		-	*	-	*		*	-	-
BC										
BD	-	-		*			-		-	-
BE	-	-	-		-				-	-
BF	-	-	-		-				-	-
CD	-	-		*		0	-		-	-
CF	-	-	-		-				-	-
DE	-	-			-		-		-	-
DF	-	-	-		-		-		-	-
EF	-	-	-	0	-		-		-	-
ABD	-	-	-	0	-		-		-	-
ABE	-	-	-	0	-		-		-	-
ABF	-	0	-		-		-		-	-
ACD	-	-	-		-		-		-	-
ACE	-	-	-		-		-		-	-
ACF	-	-	-		-		-		-	-
ADE	-	-	-		-		-		-	-
ADF	-	-	-		-		-		-	-
AEF	-	-	-		-		-		-	-
BCD	-	-		*		*	-	*	-	-
BCE	-	-	-		-		-		-	-
BDF	-	-	-		-		-		-	-
BEF	-	-	-		-		-		-	-
CDE	-	-	-		-		-		-	-
CDF	-	-	-		-		-	0	-	-
CEF	-	-	-		-		-		-	-
DEF	-	-	-		-		-		-	-
ABC										
ABCD	-	-	-	-	-	-	-	-	-	-

*Denotes significance $p < .05$.

0 Denotes significance $p < .10$.

- Represent effects not estimated.

MOT = Motion.

FOV = Field-of-View.

TURB = Turbulence.

SLO FLT = Slow Flight.

OVHD PTTN = Overhead Pattern.

GCA = Ground Controlled Approach.

table reveals that significant subject differences were present in every maneuver. The consistency in this effect strongly suggests that pilots responses to system and environmental alterations are highly individualistic. It also strongly suggests that no one model of piloting behaviors is generalizable to the population of expert pilots, in that various control strategies are employed.

It is also apparent by viewing the results of the two studies that the algorithms used in generating the environmental effects in the ASPT seem to be properly constructed. The simulated weather factors affected performance in the directions which were anticipated, i.e., increasing winds and turbulence correspondingly decreased performance. Similarly decreasing the C/V conditions caused poorer performances. Table 11 depicts the location of the measures across the two studies, which demonstrated significant univariate C/V effects. Since the environmental variables precipitated results in the expected directions, the environmental factors became benchmarks against which the effects of the system variables were measured.

The system variables showed significant impacts in every maneuver. One system variable, platform motion, demonstrated multivariate significance in 8 of the 10 total maneuvers in the two studies. In only one multivariate case, the loop in the second study, was performance not superior when platform motion was absent. Table 12 presents the motion effects on the specific dependent measures which were common to both studies. These measures represent portions of the measurement sets used in the analyses of the overhead pattern, the GCA, and the aileron roll maneuvers. These three maneuvers are the only maneuvers to have been completed by subjects in both Studies I and II. In this Table, the mean performances on each measure for both studies are listed, including whether or not univariate significance was achieved. Furthermore, the measures are categorized into either a system output, pilot input or derived score classification. This was performed in an attempt to determine which type of variable was most responsive to either environmental or simulator design variations. In the first maneuver of the Table, the overhead pattern, a large majority of the univariate significant differences fell under the category of pilot input scores. In this maneuver, it seems that platform motion causes the greatest impact in the pilots' control strategy, rather than in the criterion-referenced aircraft parameters.

In the ground controlled approach, however, this distinction is not as apparent. Several significant differences were evidenced in all of the categories with the majority of instances in the system output and pilot input categories.

In the aileron roll maneuver, the only significant differences recorded fell into the category of system output measures and then only in the first study.

The second system configuration variable, field-of-view, demonstrated a reliable impact in five of the 10 maneuvers studied as shown in Table 10. A univariate comparison between the two studies is shown in Table 13.

In the overhead pattern portion of this table, no clear-cut difference exists between the incidence of significance in the system output or pilot input categories. The same was true in the aileron maneuver. However, in the GCA, significance occurred more frequently under the pilot input category.

The final system variable, the G-seat evidenced multivariate effects in two of the 10 maneuvers investigated across the two studies (Table 10). In Table 14, univariate comparisons were made between the means of the dependent measures common to the two studies. In the overhead pattern, no immediate distinction is obvious between the sensitivity of system output, or pilot input to variations in the G-seat's operation. In the GCA, however, every case of significant difference was found to occur under the system output classification in both studies. In the aileron roll, no significance due to the G-seat was found either in the first or the second study.

Overall, the results of the two studies showed surprising consistency in terms of the nature and direction of the effects of the system and environmental variables. The results seem to indicate that all of the variables investigated, with the possible exception of the G-seat, directly or indirectly influence expert pilot performances in the variety of maneuvers investigated. However, the data also indicate that in comparison to subject differences and environmental factors the design variables are of lesser importance. This was effectively demonstrated, not only in the frequency of reliable differences found, but also in the relative effect strengths of these factors.

Table 11. Ceiling/Visibility Effects Upon Individual Dependent Measures
Common to Studies I and II

Source	\bar{X} (Clear)		\bar{X} (Minimum)		Significance Found
	I	II	I	II	
360° Overhead Pattern					
System Output					
1. RMS pitchout bank deviation	11.4	3.67	9.95	3.50	
2. RMS pitchout altitude deviation	36.3	38.50	47.3	39.25	0
3. RMS downwind altitude deviation	35.8	30.61	44.6	41.65	*0
4. RMS final turn bank deviation	9.83	7.36	11.20	8.19	*0
5. RMS final turn airspeed deviation	5.07	3.37	6.60	4.19	*0
6. RMS glidepath deviation	1.09	1.22	1.22	1.32	
7. RMS centerline deviation	110	54.37	154	57.75	
8. RMS final approach airspeed deviation	4.23	3.81	5.37	4.92	*0
Pilot Input					
1. Pitchout elevator power	1.81	2.01	1.97	2.32	*
2. Pitchout aileron power	.47	1.21	.60	1.26	0
3. Downwind elevator power	1.71	.95	2.46	1.34	*0
4. Downwind aileron power	1.07	.53	1.36	.79	*0
5. Final turn elevator power	1.47	.79	1.79	1.02	*0
6. Final turn aileron power	.74	.69	.87	.87	*0
7. Final through landing elevator power	2.86	2.35	3.18	2.48	
8. Final through landing aileron power	1.77	1.02	2.14	1.17	*0
9. Final through landing rudder power	3.63	.41	4.35	.45	*0
Derived					
1. Downwind score	70.4	70.06	62.9	56.24	*0
2. Landing score	77.1	81.10	75.8	81.05	
Ground Controlled Approach					
System Output					
1. RMS altitude deviation	40.4	22.12	38.8	25.90	*
2. RMS airspeed deviation	7.59	1.53	2.59	1.90	*
3. RMS centerline deviation	95.0	54.13	108	68.58	*0
4. RMS glidepath deviation	34.7	23.76	37.2	25.69	*
Pilot Input					
1. Elevator power prior to glideslope	.429	.26	.469	.35	*
2. Aileron power prior to glideslope	.46	.30	.46	.43	*
3. Elevator power after glideslope	4.28	3.94	4.11*	4.55	*
4. Aileron power after glideslope	1.54	.55	1.81	1.09	*
Derived					
1. Total Score	76.9	62.97	77.6	54.73	*0

* Indicates significance ($p < .05$). found in second study.

0 Indicates significance ($p < .05$) found in first study.

I, II Relate to Studies I and II, respectively

**Table 12. Motion Effects Upon Individual Dependent Measures
Common to Studies I and II**

Source	$\bar{X}(0 \text{ DOF})$		$\bar{X}(3 \text{ DOF})$		$\bar{X}(6 \text{ DOF})$		Significance Found
	I	II	I	II	I	II	
360° Overhead Pattern							
System Output							
1. RMS pitchout bank deviation	10.1	3.87	11.20	3.60	10.8	3.29	
2. RMS pitchout altitude deviation	36.9	41.38	40.6	37.9	47.8	37.36	
3. RMS downwind altitude deviation	34.0	36.55	41.4	33.76	45.3	38.07	0
4. RMS final turn bank deviation	9.95	7.66	10.6	7.90	11.0	7.76	
5. RMS final turn airspeed deviation	5.68	3.83	6.14	4.01	5.69	3.51	
6. RMS glidepath deviation	1.14	1.32	1.12	1.18	1.20	1.31	
7. RMS centerline deviation	128	65.79	134	54.59	134	47.80	
8. RMS final approach airspeed deviation	4.88	4.25	4.73	4.56	4.79	4.29	
Pilot Input							
1. Pitchout elevator power	2.16	2.04	1.72	2.19	1.79	2.26	
2. Pitchout aileron power	.439	1.17	.513	1.25	.666	1.28	0
3. Downwind elevator power	2.22	.994	1.74	1.169	2.30	1.349	0
4. Downwind aileron power	.895	.608	1.17	.701	1.58	.692	*0
5. Final turn elevator power	1.55	.772	1.47	.903	1.88	1.053	*
6. Final turn aileron power	.605	.615	.830	.837	.987	.902	*0
7. Final through landing elevator power	3.28	2.091	2.74	2.528	3.04	2.631	*
8. Final through landing aileron power	1.70	1.03	2.05	1.18	2.12	1.07	
9. Final through landing rudder power	4.40	.393	3.48	.454	4.09	0.457	
Derived							
1. Downwind score	70.2	61.35	65.5	65.59	64.2	62.51	
2. Landing score	78.1	80.07	76.2	81.32	75.2	81.83	
Ground Controlled Approach							
System Output							
1. RMS altitude deviation	33.2	23.19	41.2	25.31	44.3	23.53	0
2. RMS airspeed deviation	2.40	1.70	2.44	1.78	2.92	1.67	0
3. RMS centerline deviation	96.7	59.53	102	66.55	106	57.98	*
4. RMS glidepath deviation	36.3	24.73	35.6	24.40	36.0	25.05	
Pilot Input							
1. Elevator power prior to glideslope	.091	.26	.113	.32	.123	.34	*
2. Aileron power prior to glideslope	.379	.31	.395	.40	.572	.38	*0
3. Elevator power after glideslope	8.56	4.31	6.83	4.49	9.20	3.94	
4. Aileron power after glideslope	4.29	.61	3.70	.96	4.61	.89	*
Derived							
1. Total score	27.3	60.76	24.3	55.84	22.7	9.20	0
Aileron Roll							
System Output							
1. RMS bank-in deviation	1.54	1.17	2.12	1.01	2.50	1.29	0
2. RMS bank-out deviation	2.86	2.80	3.84	2.73	3.76	3.08	0
3. RMS roll acceleration during bank-in	10.2	2.79	13.7	2.70	14.0	3.32	

Table 12 (Continued)

Source	\bar{X} (0 DOF)		\bar{X} (3 DOF)		\bar{X} (6 DOF)		Significance Found
	I	II	I	II	I	II	
Pilot Input							
1. Aileron power bank-in	1.18	.171	1.92	.181	1.95	.178	
2. Aileron power roll	1.01	5.09	1.43	4.18	1.49	4.70	
3. Aileron power bank-out	.873	4.07	1.18	3.17	1.53	2.63	
Derived							
1. Roll score	38.8	82.98	36.2	85.64	40.5	80.83	

*Indicates significance ($p < .05$) found in second study.⁰Indicates significance ($p < .05$) found in first study.

I,II Relate to Study I and Study II, respectively.

Table 13. Field-of-View Effects Upon Individual Dependent Measures Common to Studies I and II

Source	\bar{X} (Full)		\bar{X} (36x144)		\bar{X} (36x48)		Significance Found
	I	II	I	II	I	II	
360° Overhead Pattern							
System Output							
1. RMS pitchout bank deviation	10.4	4.14	—	3.29	11.0	3.32	*
2. RMS pitchout altitude deviation	39.4	39.650	—	38.10	44.1	38.89	
3. RMS downwind altitude deviation	39.3	35.50	—	37.62	41.1	35.26	*
4. RMS final turn bank deviation	9.62	6.40	—	7.92	11.5	9.01	
5. RMS final turn airspeed deviation	5.92	3.43	—	3.82	5.75	4.09	
6. RMS glidepath deviation	1.04	1.24	—	1.19	1.26	1.38	
7. RMS centerline deviation	99.1	23.55	—	53.93	165	90.70	*
8. RMS final approach airspeed deviation	4.09	3.92	—	3.81	5.51	5.26	*
Pilot Input							
1. Pitchout elevator power	1.91	2.13	—	2.19	1.87	2.17	
2. Pitchout aileron power	.48	1.20	—	1.22	.59	1.28	
3. Downwind elevator power	2.04	1.07	—	1.15	2.13	1.22	
4. Downwind aileron power	1.09	.65	—	.64	1.34	.70	
5. Final elevator power	1.62	.96	—	.95	1.65	.80	*
6. Final aileron power	.72	.86	—	.75	.89	.73	
7. Final through landing elevator power	3.03	2.39	—	2.38	3.02	2.47	*
8. Final through landing elevator power	1.84	.90	—	2.13	2.07	1.26	*
9. Final through landing rudder power	3.96	.37	—	.42	4.02	.50	*
Derived							
1. Downwind score	70.5	66.40	—	63.32	62.9	59.73	
2. Landing score	76.5	81.33	—	81.83	76.4	80.16	
Ground Controlled Approach							
System Output							
1. RMS altitude deviation	37.2	24.24	—	23.50	42.0	24.30	
2. RMS airspeed deviation	24.6	1.76	—	1.75	27.1	1.66	
3. RMS centerline deviation	104	61.67	—	63.09	99.4	59.30	
4. RMS glidepath deviation	37.1	24.48	—	25.27	34.8	24.43	

Table 13 (Continued)

Source	\bar{X} (Full)		\bar{X} (36x144)		\bar{X} (36x48)		Significance Found
	I	II	I	II	I	II	
Pilot Input							
1. Elevator power prior to glideslope	.42	.34	—	.29	.47	.30	
2. Aileron power prior to glideslope	.39	.37	—	.35	.53	.38	0
3. Elevator power after glideslope	4.21	4.45	—	4.34	4.18	3.95	
4. Aileron power after glideslope	1.58	.85	—	.79	1.76	.83	
Aileron Roll							
System Output							
1. RMS bank-in deviation	1.82	1.10	—	1.09	2.11	1.28	
2. RMS bank-out deviation	2.56	2.22	—	2.92	3.18	3.42	
3. RMS roll acceleration during bank-in	9.67	3.28	—	2.30	13.1	3.22	0
Pilot Input							
1. Aileron power bank-in	.99	.21	—	.13	1.92	.18	0
2. Aileron power roll	.79	5.02	—	4.46	1.52	4.50	
3. Aileron power bank-out	1.24	2.34	—	3.41	1.08	4.11	
Derived							
1. Roll score	35.3	85.84	—	84.32	40.5	79.30	*

* Indicates significance ($p < .05$) found in second study.

0 Indicates significance ($p < .05$) found in first study.

— Indicates no data.

I, II Indicates Study I or Study II.

Table 14. G-Seat Effects Upon Individual Dependent Measures Common to Studies I and II

Source	\bar{X} (Off)		\bar{X} (Seat Pan)		\bar{X} (On)		Significance Found
	I	II	I	II	I	II	
360° Overhead Pattern							
System Output							
1. RMS pitchout bank deviation	11.7	3.61	—	3.65	9.67	3.50	0 *
2. RMS pitchout altitude deviation	42.3	38.04	—	35.00	41.3	43.59	
3. RMS downwind altitude deviation	40.8	35.90	—	35.09	39.6	37.39	
4. RMS final turn bank deviation	10.60	7.48	—	8.09	10.50	7.75	
5. RMS final turn air-speed deviation	5.89	3.66	—	3.81	5.78	3.88	
6. RMS glidepath deviation	1.27	1.25	—	1.23	1.03	1.33	
7. RMS centerline deviation	159	52.20	—	67.28	105	48.71	
8. RMS final approach air-speed deviation	4.89	4.01	—	4.29	4.71	4.79	
Pilot Input							
1. Pitchout elevator power	1.68	2.14	—	2.32	2.09	2.03	
2. Pitchout aileron power	.52	1.21	—	1.27	.55	1.22	
3. Downwind elevator power	1.94	1.15	—	1.16	2.23	1.14	
4. Downwind aileron power	1.16	.62	—	.66	1.27	.71	
5. Final turn elevator power	1.52	.85	—	.94	1.74	.92	

Table 14 (Continued)

Source	\bar{X} (Off)		\bar{X} (Seat Pan)		\bar{X} (On)		Significance Found
	I	II	I	II	I	II	
6. Final turn aileron power	.81	.76	—	.80	.79	.78	
7. Final through landing elevator power	2.78	2.34	—	2.50	3.27	2.40	0
8. Final through landing aileron power	2.03	1.03	—	1.06	1.87	1.19	
9. Final through landing rudder power	4.0	.42	—	.41	3.98	.46	
Derived							
1. Downwind score	67.2	63.42	—	64.81	66.1	61.22	
2. Landing score	76.0	81.28	—	81.47	77.0	80.47	
Ground Controlled Approach							
System Output							
1. RMS altitude deviation	44.0	24.48	—	25.01	35.2	22.55	0
2. RMS airspeed deviation	2.70	1.69	—	1.86	2.48	1.61	*
3. RMS centerline deviation	108	64.84	—	59.18	95.3	60.05	0
4. RMS glidepath deviation	37.3	25.20	—	26.34	34.6	22.64	*
Pilot Input							
1. Elevator power prior to glideslope	.42	.30	—	.33	.47	.30	
2. Aileron power prior to glideslope	.48	.36	—	.38	.44	.36	
3. Elevator power after glideslope	3.97	4.13	—	4.26	4.42	4.35	
4. Aileron power after glideslope	1.66	.82	—	.81	1.69	.83	
Derived							
1. Total score	23.5	58.19	—	56.50	26.0	61.10	
Aileron Roll							
System Output							
1. RMS bank-in deviation	2.17	1.18	2.12	1.22	1.87	1.08	
2. RMS bank-out deviation	3.75	2.24	3.39	3.18	3.32	3.19	
3. RMS roll acceleration during bank-in	13.1	3.59	12.9	2.91	12.5	2.32	
Pilot Input							
1. Aileron power bank-in	2.03	.205	1.43	.17	1.60	.15	
2. Aileron power roll	1.49	5.26	1.22	4.49	1.23	4.23	
3. Aileron power bank-out	1.45	2.61	1.16	3.94	.968	3.31	
Derived							
1. Roll score	42.8	83.86	36.3	82.26	36.4	83.34	

*Indicates significance ($p < .05$) found in second study.0 Indicates significance ($p < .05$) found in first study.

— Indicates no data collected.

I, II Relate to Study I and Study II, respectively.

VI. SUMMARY AND CONCLUSIONS

The results of these two investigations (I & II) have provided a substantial amount of information regarding the relative influences of various system design and simulated environmental factors upon expert pilot behaviors in the simulator. Although several differences between the two studies existed, generally the findings were consistent across the investigations.

One of the most important conclusions based upon the findings of these studies regards the apparent hierarchy of the various factors which were manipulated. The largest and most consistent factor affecting performance is that of individual differences. In comparison with this factor, all other variable effects seem small. The fact that people are different is nothing new or surprising; however, it strongly suggests that individual pilots respond to simulator configurations differently and disconfirms the hypothesis that any simple linear model of piloting behaviors is sufficient to describe the processes involved in controlling an aircraft.

The results showed that simulated environmental factors were also demonstrated to be functioning in the anticipated manner, that is, as the simulated weather conditions deteriorated, the flight performances became poorer. This provided some degree of face validity to the construction and implementation of the algorithms used in generating the environmental settings. Additionally, the environmental factors were seen to interact with the system configuration variables in certain instances to cause differential performances on several flight tasks. The effects of the environmental variables were also demonstrated to be relatively large in size when viewed in comparison with the effects of the simulator design configuration variables. The effects of the environmental variables also seemed to be equally dispersed among the several categories of dependent measures which were collected.

The simulator configuration variables also seemed to lend themselves to the establishment of an effect hierarchy. The most frequently occurring effect across the two studies belonged to the platform motion variable. The effects of this variable seemed to be generally consistent in that the addition of platform motion to the flight task normally degraded the performance on that task. However, it was not clear when weighing the results of both studies whether performance was more frequently inferior under the 3 DOF or the 6 DOF situation. The differences caused by the motion variable were often manifested in measurements particularly sensitive to change in pitch control. Furthermore, in some cases, the changes were more frequently recorded within the pilot input category of the dependent measures suggesting that this variable, while often not strong enough to alter the overall performance of the vehicle does, however, cause changes in the pilots' controlling strategy.

The motion variable, while demonstrating more frequent significant impacts than the other two system variables, generally was not larger in size than the effects due to the field-of-view variable. Both factors accounted for approximately 1 to 10 percent of the performance variability. The field-of-view variable manifested consistent significant impacts upon the subjects' performance of four maneuvers in the two studies: the aileron roll (twice), the barrel roll, and portions of the overhead pattern maneuver. The performance measurements which seemed to be most strongly affected by changes in the field-of-view of the visual display represented scores sensitive to changes in the roll dimension of the aircraft. Measures reflecting changes in the pitch status of the simulator were also affected. However, these measures did not seem to be impacted as greatly as the roll-sensitive measures.

The variable pertaining to the G-seat produced extremely surprising results. While the G-seat produced significant effects in the first study on two maneuvers, the takeoff and the GCA, no significance was recorded in the second study. Reevaluation of the consistency of the results of Study I taken in light of Study II results revealed that although multivariate significance was achieved in those two instances only five univariate tests reached criterion significance in 19 total tests for the two maneuvers. This demonstration coupled with the very consistently small contribution of the G-seat in the second study suggests that the G-seat may be the least important variable of the system variables studied in these projects.

The interactive potential that the G-seat demonstrated in the first study was not realized in the second study. One possible explanation for the absence of this and other interactions involving the G-seat in the second study is that the research designs utilized in Study II were considerably more conservative than the research designs employed in the first study. This does not invalidate the former effort because the purpose in that study was to isolate and identify any and all possible sources of variance in an attempt to explore the variable space completely. Apparently, that study was successful in identifying all of the possible sources of variance. However, when these sources were scrutinized more closely, as in the second study, they were found not to be as important as formerly believed.

Another important area to which these studies have contributed substantial information is that of performance measurement. The existence and the nature of the subject effects and the system configuration variable effects have demonstrated the utility and efficacy of a comprehensive performance measurement strategy which addresses not only the traditional system output types of measures but also includes control strategy measures in the form of pilot workloads and input smoothness. The results of the two studies seem to suggest that given different conditions, expert pilots adapt to these conditions often without serious degradation in the vehicle's performance but frequently with radical changes in control strategy and information acquisition. These studies have begun to identify the manner in which these changes seem to occur. Obviously, the area requires more exploration to substantiate and refine the findings of this series of investigations.

REFERENCES

- Armstrong, B.O. *Flight trials to discover whether peripheral vision is needed for landing*. Royal Aircraft Establishment Technical Report 70205, AD-724 009, November 1970.
- Borlace, F. Flight simulator motion, its enhancement and potential for flight crew training. *Proceedings of the Third International Simulation and Training Conference*. New York: 27 April 1967.
- Brown, F.P., Johnson, H.I., & Mungall, R.G. *Simulator motion effects on a pilot's ability to perform a precise longitudinal flying task*. NASA-TN-D-367, AD-236 265, May 1960.
- Demaree, R.G., Norman, D.A., & Matheny, W.G. *An experimental program for relating transfer of training to pilot performance and degree of simulation*. NAVTRADEVCE-TR-1388-1. Naval Training Device Center, June 1965.
- Gray, T.H., & Fuller, R.R. *Effects of simulator training and platform motion on air-to-surface weapons delivery training*. AFHRL-TR-77-29, AD-A043 649. Williams AFB, AZ: Flying Training Division, Air Force Human Resources Laboratory, July 1977.
- Hagin, W.V., & Smith, J.F. *Advanced simulation in undergraduate pilot training (ASUPT) facility utilization plan*. AFHRL-TR-74-43, AD-786 411. Williams AFB, AZ: Flying Training Division, Air Force Human Resources Laboratory, June 1974.
- Harris, R.J. *A primer of multivariate statistics*. New York: Academic Press, Inc., 1975.
- Irish, P.A., III, Grunzke, P.M., Gray, T.H., & Waters, B.K. *The effects of system and environmental factors upon experienced pilot performance in the advanced simulator for pilot training*. AFHRL-TR-77-13, AD-A043 195. Williams AFB, AZ: Flying Training Division, Air Force Human Resources Laboratory, April 1977.
- Jacobs, R.S., Williges, R.C., & Roscoe, S.N. Simulation motion as a factor in flight-director display evaluation. *Human Factors*, December 1973, **15**(6), 569-582.
- Kirk, R.E. *Experimental design: Procedures for the behavioral sciences*. Belmont, CA: Brooks/Cole Publishing Co., 1968.
- Koonce, J.M. *Effects of ground-based aircraft simulator motion conditions upon prediction of pilot proficiency*. AFOSR-TR-74-3. Air Force Office of Scientific Research. Illinois University, April 1974.
- Monroe, E.G., Rife, R.W., Cyrus, M.L., & Thompson, L.C. *ASUPT visual simulation of air-to-surface weapons delivery*. AFHRL-TR-76-40, AD-A034 319. Williams AFB, AZ: Flying Training Division, Air Force Human Resources Laboratory, June 1976.
- Rathert, G.A., Creer, B.Y., & Sadoff, M. *The use of piloted flight simulators in general research*. Report 365. NATO Advisory Group for Aeronautical Research and Development, 1961.
- Reeder, J.P., & Kolnick, J.J. *A brief study of closed-circuit television for aircraft landing*. NASA-TN-D-2185. February 1964.
- Roscoe, S.N. *Flight by periscope*. University of Illinois Bulletin, 1951, **48**, 55.
- Rust, S.K. Flight simulator fidelity assurance. *Proceedings of the Eighth NTEC/Industry Conference*, 18-20 November 1975.
- Taylor, R., Gerber, A., Allen, M., Brown, L., Cohen, E., Dunbar, D., Flexman, R., Hewitt, W., McElwain, D., Pancoe, E., & Simpson, D. *Study to determine requirements for undergraduate pilot training research simulation system (UPTRSS)*. AFHRL-TR-68-11, AD-858 640. Wright-Patterson AFB, OH: Training Research Division, Air Force Human Resources Laboratory, July 1969.
- Waag, W.L., Eddowes, E.E., Fuller, J.H., Jr., & Fuller, R.R. *ASUPT automated objective performance measurement system*. AFHRL-TR-75-3, AD-A014 799. Williams AFB, AZ: Flying Training Division, Air Force Human Resources Laboratory, March 1975.
- Woodruff, R.R., Smith, J.F., Fuller, R.R., & Weyer, D.C. *Full mission simulation in undergraduate pilot training: An exploratory study*. AFHRL-TR-76-84, AD-A039 267. Williams AFB, AZ: Flying Training Division, Air Force Human Resources Laboratory, December 1976.

APPENDIX A: DESCRIPTION OF PERFORMANCE MEASUREMENT ALGORITHMS

The performance measurement algorithms used in this study divided each maneuver into several exercise segments. For each exercise segment, special computer programs, labelled "cases," were developed that determined simulator system conditions and defined the parameters to be measured in that segment. The operation of these cases may be described in the following manner. An initialization case set the simulator at the maneuver starting conditions. Intermediate cases used to sample outputs executed a FORTRAN program with a 3.75 Hertz iteration rate. A special case was provided which measured the pilot outputs at an iteration rate of 15 Hertz. An end-point case froze the simulator when the end conditions for the maneuver were met.

Descriptions of the performance measurement algorithms for the five maneuvers are as follows:

GCA and Landing: The starting condition was 2,400' MSL, 300 degree heading, and 160 knots on an 8-mile final for Runway 30. The pilot maintained starting conditions until the Cognitronics Voice System began giving GCA "controller" instructions. The pilot slowed to 110 knots and lowered the landing gear and flaps at the appropriate airspeeds. He followed the "controller" heading instructions to maintain course. At 4.5 miles, the pilot intercepted the glidepath. The controller then provided information on aircraft position relative to the glidepath (above or below and left or right). When the pilot had the runway in sight, he made appropriate corrections to maintain the extended centerline and glidepath visually. The pilot was instructed to land on the runway centerline, approximately 1,000' down the runway. The maneuver was terminated on landing roll after the airspeed decreased below 50 knots.

GCA and Landing Scoring Sequence




Figure A1. GCA and landing scoring sequence.

360° Overhead Pattern and Landing: The starting condition was 2,500' MSL, 300° heading, and 200 knots on 4-mile initial for RW 30. The pilot flew the initial, maintaining altitude, airspeed, and runway centerline. Approximately halfway down the runway, the pilot pitched out by reducing power to 50-60% rpm and made a steep turn to the left not exceeding 60° bank. After completing a 180° turn, he lowered the speedbrake and landing gear, maintaining 2,500' MSL and 120 knots minimum. Approximately 3/4

mile past the end of the runway, he lowered the flaps and started a descending turn to the left. He maintained 110 knots minimum and adjusted the bank and descent rate so as to roll out on runway centerline at 1,700' MSL.

Once on final approach, the pilot maintained 100 knots minimum and a constant glidepath. He adjusted pitch and power so as to touchdown in the first 1,000' of the runway at an airspeed between 75-80 knots. The maneuver was terminated when airspeed decreased below 50 knots during the rollout.

360° Pattern and Landing




Figure A2. 360° overhead pattern and landing scoring sequence.

Aileron Roll: The initial conditions were established to represent 15,000' MSL, 160 knots indicated airspeed, and 180° heading. The pilot lowered the nose of the aircraft and set the power at 90% in order to accelerate. He then raised the nose, so as to pass through level flight at an airspeed of 200 to 230 knots. He continued to smoothly raise the nose without banking the wings until the nose was approximately 20° to 30° above the horizon. At this point, he started a roll in either direction, adjusting the roll rate as necessary so that the roll was executed smoothly. As the upright wings level attitude was approached, aileron pressure was gradually released to roll out with the nose on the horizon. The exercise was terminated 5 seconds after the roll was complete.




Figure A3. Aileron roll scoring sequence.

1. *Loop*. The starting condition was 15,000' MSL, 160 knots, and 180° heading. The pilot lowered the nose of the aircraft to accelerate while setting power at 100%. He then raised the nose so as to pass through level flight at an airspeed between 240 and 250 knots. He continued to raise the nose vertically with a constant positive 3 "G" force and maintained wings level. At the top of the maneuver, while inverted, stick back pressure was reduced to keep a constant pitch rate change. As airspeed increased on the downward part, stick back pressure was increased to keep the pitch rate constant with the wings level. The maneuver was terminated when straight-and-level flight was reestablished.




Figure A4. Loop scoring sequence.

2. *Barrel Roll*: The starting conditions were 14,000' MSL, 190 knots, 180° heading, and a 12° dive angle. The pilot set the power at 90% and continued the dive until the airspeed was between 200 and 230 knots indicated. He then rolled to a 30° to 45° heading change to either side and raised the nose to wings level. He continued to raise the aircraft nose above the horizon and rolled around a desired reference point. The pilot attempted to keep the reference point in the same relative offset position throughout the roll. He continued the roll checking the offset when the wings level inverted position on the opposite side of the starting point was reached. The maneuver was completed when the pilot arrived at the same position where he initiated the roll with wings level.




Figure A5. Barrel roll scoring sequence.