

AFOSR-TR- 78-1085

AD A 056066

LEVELTM

Q

Portability Techniques for BLISS Programs

Bruce W. Leverett
Paul J. Knueven
Peter G. Hibbard

November, 1977

DEPARTMENT
of
COMPUTER SCIENCE



AD No. _____
DDC FILE COPY

Carnegie-Mellon University

78 06 27 09 6

Approved for public release;
distribution unlimited.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

19) REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
18) GOVT ACCESSION NO. 18) AFCSR/TR-73-1035		3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) (6) PORTABILITY TECHNIQUES FOR BLISS PROGRAMS	5. TYPE OF REPORT & PERIOD COVERED Interim <i>rept.</i>	
7. AUTHOR(s) (10) Bruce W. Leverett, Paul J. Knueven Peter G. Hibbard	8. CONTRACT OR GRANT NUMBER(s) (15) F44626-73-C-0074, //ARPA	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Carnegie-Mellon University Department of Computer Science Pittsburgh, PA 15213 (16) 2466	10. PROGRAM ELEMENT NUMBER, TASK AREA & WORK UNIT NUMBER 61101E AC2466/7 (Order-2466	
11. CONTROLLING OFFICE NAME AND ADDRESS Defense Advanced Research Projects Agency 1400 Wilson Blvd. Arlington, VA 22209 (17) 877	12. REPORT DATE (11) Nov 1977	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Air Force Office of Scientific Research (NM) Bolling AFB, DC 20332	13. NUMBER OF PAGES 79	
15. SECURITY CLASS. (of this report) UNCLASSIFIED		
15a. DECLASSIFICATION/DOWNGRADING SCHEDULE (12) 8PP		
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The problems of writing large systems in BLISS that can be run in more than one environment are described. A method (a set of methods) for attacking these problems is explained, with examples of its use in a particular system (a compiler). Aspects of the BLISS language are discussed with regard to their usefulness or uselessness in solving these problems.		

403 081 *Guu*

LEVEL II

②


Portability Techniques for BLISS Programs

Bruce W. Leverett
Paul J. Knueven
Peter G. Hibbard

November, 1977

Abstract

The problems of writing large systems in BLISS that can be run in more than one environment are described. A method (a set of methods) for attacking these problems is explained, with examples of its use in a particular system (a compiler). Aspects of the BLISS language are discussed with regard to their usefulness or uselessness in solving these problems.



The work described here was supported by the Defense Advanced Research Projects Agency under contract F44620-73-C-0074, monitored by the Air Force Office of Scientific Research.

78 06 27 096

In 1974, the authors undertook to write a compiler for ALGOL 68. The compiler was to run on a PDP-11 and produce code suitable for a PDP-11. The first version was to run on C.mmp[1], a multiprocessor system comprising several (slightly modified) PDP-11 processors and other hardware, under the HYDRA[2] operating system.

The compiler was written in BLISS[3], for the usual variety of reasons, not least of which was that the C.mmp/HYDRA system offers a complete symbolic debugging system (SIX12[4]) and other support for BLISS programs. However, there were some initial problems with building a system in this environment.

- The environment itself was unstable. The hardware and the various levels of the operating system were full of bugs, and subject to frequent redesign as well.
- The environment was completely unfamiliar to the authors, who had never used it before.
- The compiler and linker for BLISS did not run on C.mmp/HYDRA, but on a PDP-10/TOPS-10, with no easily available link between the two. Thus changing the compiler involved loading a linked version onto a DECTape, carrying the tape over to C.mmp, mounting it there, and reading it--a time-consuming process. (This, incidentally, was one of the problems that the ALGOL 68 system was intended to solve, since it was to run entirely under C.mmp/HYDRA.)

Hence, the authors decided to build a preliminary version of the compiler, which would run entirely under PDP-10/TOPS-10 (suffering from none of the above three problems), and do most of the early development work on the preliminary version. To minimize the problems of changing over, from PDP-10 versions to C.mmp versions and vice versa, the preliminary version was also written in BLISS. We wished to be able to switch from using either version to using the other, simply by making a small number of error-proof changes, and then running the appropriate compiler and linker to produce the version to be used. We completely met this goal, and in fact switched from using one version to using the other several times. In addition, we met it in a way that was very easy to maintain: although we had not used the PDP-10 version since April 1976, we used the procedure outlined above to create a PDP-10 version in February 1977, with essentially no problems (e.g. all files compiled correctly, in spite of language differences between BLISS-10 and BLISS-11).

Achieving this level of portability was a non-trivial task. BLISS is not as high-level a language as ALGOL nor as standardized as FORTRAN (though achieving portability even in FORTRAN is not always easy [5]). The machine-dependence of the design of even the simplest data structures is not hidden from the programmer; moreover, I/O and other interactions with the operating system are not part of the language, and must be supplied by the user's program (or at least in separately-compiled programs). Standard packages are available for handling routine problems for both BLISS-10/TOPS-10 and BLISS-11/HYDRA, but there are several problems with using these:

- o They are not compatible with each other.
- o They (especially the BLISS-11/HYDRA package) are inadequate for the needs of large programs such as compilers.

- o There are no packages for any PDP-11 operating systems other than HYDRA, RSX-11, and RT-11, and even these three are not compatible with each other.

This paper describes the techniques we used to achieve portability, i.e. to minimize the work necessary to change over from one version to the other. Chapter 1 describes our system for isolating the differences between the architectures of the PDP-10 and the PDP-11. Chapter 2 describes our treatment of the differences between the BLISS-10 and BLISS-11 languages. Chapter 3 describes the compiler interface with the operating system, i.e. the system for isolating the differences between TOPS-10 and HYDRA. In Chapter 4 we draw some conclusions about the general applicability of our techniques, and about the design of system implementation languages (such as BLISS) with portability in mind. Portions of the compiler are included in the Appendices for illustration.

1. Hardware Differences

By using a high-level language, we were able to avoid having to deal with differences between the instruction sets and instruction formats of the PDP-10 and the PDP-11 (the few exceptions are noted below). However, because of the nature of the BLISS language, we could not avoid dealing with differences between their data formats.

Our method of isolating these differences was to use a "REQUIRE file". BLISS has a declaration similar in purpose to the PL/I %INCLUDE statement, by means of which a program may incorporate several files as part of its source text; this is the REQUIRE declaration. Any particular separately-compiled module of the compiler begins with a series of REQUIRE declarations, each of which names a file containing some set of related definitions. The very first such file is always SYSPRM.REQ, which contains the definitions which hide the differences between the PDP-10/BLISS-10 and the PDP-11/BLISS-11 systems. The 10 version of this file is B10PRM.REQ; the 11 version is B11PRM.REQ. The first step in the changeover from one version to the other, say from the 10 version to the 11 version, is to make sure that SYSPRM.REQ is a copy of the proper version of this file (in this case B11PRM.REQ). This requires a single command to the file system.

Not all of the differences between language/machine systems could be handled by a single file of definitions, however. Those that could not may be characterized as differences between libraries. Neither of the two BLISS compilers generates code to support unsigned division, conversion of strings of characters to fixed- or floating-point numbers (or to BITS values, for ALGOL 68), or the SIGNAL/ENABLE feature of BLISS-11. These must be handled by library subroutines, and the libraries, even those which can be written in BLISS, are of a very low-level, machine-dependent nature. The two libraries are kept as separate groups of source files, and the differences in the interfaces to them are hidden in SYSPRM.REQ.

A few words of explanation of BLISS are in order before we describe the contents of SYSPRM.REQ. The data structures commonly available in other high-level languages, such as records, stacks (except for the control stack), arrays, list cells, and so forth, are not built into BLISS. To use such a structure, a program must define it, by defining

- the layout in memory of each instance of the structure. This includes a list of the parameters (e.g. dimensions) of any declaration of a variable with that structure, and specification of how those parameters are used (if at all) in determining the amount of storage allocated to that variable.
- the method by which the fields of the structure are accessed. A particular field need not be an entire machine word; then it must be specified which group of bits within the word it must be.

For instance, the standard definition of a one-dimensional zero-based array of one-word values (in BLISS-10; it is slightly different in BLISS-11) is as follows:

```
structure Vector [Index] = [Index] (.Vector + .Index) <0, 36>;
```

The first pair of square brackets indicates that both declarations and accesses of Vector variables have one parameter. The expression in the second pair of square brackets indicates how large an array is allocated to such a variable when it is declared; in this case, the number of words allocated is equal to the parameter ("Index") used in the declaration. (For instance, a declaration like

```
local Vector QQQQ [445];
```

causes the array QQQQ to have length 445 words.) The remaining expression indicates how this structure is to be accessed: the location of the base variable and the value of the index are summed to get an address, and the 36 bits starting at bit 0 of the word at that address (that is, the whole word) are referred to.

The Vector structure happens to be predefined, but all other structures must be defined by the user's program. The definition of this structure in BLISS-11 is slightly different from its definition in BLISS-10, because of the different data formats of the two machines: one can declare vectors of bytes or vectors of full words, and thus take advantage of either the byte addressing or the word addressing of the PDP-11.

This background helps to explain the organization of SYSPRM.REQ. The definitions in this file which hide differences between the PDP-10 and the PDP-11 can be grouped into four categories:

1. the definitions of "standard structures". These are:

BYTVECT - array of 8-bit bytes

CHARVECT - array of ASCII (7-bit) characters

HFVECT - array of half words

HFTABLE - array of half words, from which subfields may be accessed

2. the definitions of machine characteristics. These are occasionally useful even outside the definitions of the standard structures. They are:

	PDP-10	PDP-11
QADRINC	1	2

- address increment from one full word
to the next

QCHSWRD	5	2	- # of ASCII characters packed into one full word
QADRSIZ	18	16	- width in bits of a pointer
QWRDSIZ	36	16	- width in bits of a full word
QHFSIZ	18	8	- width in bits of a half word
QSPARE	35	1	- position within a word of a bit which, if the word contains a pointer, is not relevant (by convention) to that pointer. For the PDP-11, this is the lowest order bit of the word, since full words are aligned on even boundaries, and pointers to them always have zero in the lowest bit. For the PDP-10, this may be any of the bits in the high order half of the word, since by convention, pointers are always held in the lower half.

3. the definition of the packed-string data type. This is a set of definitions, primarily of operators, for manipulating strings of characters. What makes these definitions interesting--they are the only section of SYSPRM.REQ which underwent a major design iteration--is the crucial difference between the basic string operations "read (write) a character and step to the next character", on the two machines. On the PDP-10, these operations (the IDPB and ILDB instructions) move to the next character before reading or writing; on the PDP-11, the corresponding operations (the autoincrement addressing mode) cause reading or writing before moving to the next character. This difference cannot be hidden without imposing some restrictions on the operations which may be performed on strings. We therefore divide string pointers into two categories: those for which every access of a character is accompanied by a step from one character to the next ("I-pointers") and those for which stepping to the next character must always be done separately ("N-pointers").
4. the definitions of two "library" routines which happen to be coded as macros, rather than as closed subroutines. These are the routines to clear out a block of core and to copy one block of core into another.

2. Language Differences

Neither BLISS-11 nor BLISS-10 is a proper superset of the other. Generally, however, we did not make much use of features of one language which were not present in the other, and the list of such features for which we put fake definitions in the versions of SYSPRM.REQ is uninteresting. However, three exceptions should be noted:

- The BLISS-11 SIGNAL/ENABLE construct caught our fancy, and we used it for compilation error handling. Therefore, we were obliged to write BLISS-10 constructs to simulate it. We were surprised to find that this was possible. The BLISS-11 library file, SIGENB3.MAC, which is a standard part of the BLISS-11 compiler distribution, corresponds to the BLISS-10 library file, SYSDEP.MAC

(which contains some miscellaneous material not related to SIGNAL/ENABLE as well). The only problem with our simulation of SIGNAL/ENABLE is that some extra code is required on normal termination of a block containing an ENABLE declaration, to pop a frame off the (conceptual) "ENABLE stack". The BLISS-11 compiler outputs this code automatically, but of course the BLISS-10 compiler does not; we put the code in the macro ENABEND, and we enforce the convention that every path to exit of an ENABLEd block must end with an ENABEND, to get around this problem.

- We wished to set up extensive preloaded symbol tables with the BLISS PLIT facility. We stumbled over one characteristic of those symbol tables, namely, that they contained many pointers to themselves and each other. The BLISS-10 NAMES and GLOBALLY NAMES feature allowed us to generate the necessary pointers easily and cleanly, but there is no corresponding feature in BLISS-11. Therefore we wrote a set of iterated and recursive macros which simulated these, as well as the related INDEXES and GLOBALLY INDEXES feature. The simulation is not quite complete, because the iterated/recursive macro processor attempts to update an index into a PLIT that it is building by counting the arguments which fly by it; it doesn't understand other features of the PLIT facility, such as duplication factors and strings. However, we did not need to make use of these features in our symbol tables.
- The BLISS-10 and BLISS-11 macro processors do not expand macro arguments in quite the same way. From our point of view, the problem is this: Let there be a macro A, with a formal parameter FA, and a macro B, with possibly some formal parameters. Suppose there is a call such as

A (B (...))

and the call of B results in a string containing a comma--that is, a comma which is not hidden by being between a matched pair of parentheses or brackets of some sort. The BLISS-11 macro processor completes the expansion of the call of B while setting up the call of A, and since it regards the comma as an argument separator, it concludes that A has (wrongly) been passed two actual parameters, instead of just one. The BLISS-10 macro processor does not do this, treating the entire call of B as a single parameter to A.

In the ordinary course of programming, we did not encounter such problems, because of our generally conservative use of macros. However, the slightly bizarre tricks we used in the set of macros which set up the table of productions tripped across exactly this problem. We solved it by "quoting" the comma which was generated, in the BLISS-11 version, so that the BLISS-11 macro processor would not recognize it as an argument separator; this is the origin of the macro "quoted" which is defined in SYSPRM.REQ.

ACCESSION for	White Section	Buff Section	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
FILE	DOC	MANUFACTURER	INSTITUTION	BY	DEPARTMENT/AGENCY
DATE	NAME	ADDRESS	TEL	TELE	MAIL ADDRESS
REMARKS					

A

3. Operating System Differences

Because more than 20 complete operating systems are in use on PDP-11's and configurations of PDP-11 processors, the problem of isolating the operating system interface (or Operating System Environment, OSE) would have to have been faced even if we had not had to write a PDP-10 version of the compiler. It almost goes without saying that this problem cannot be solved by a single "REQUIRE file" of useful definitions. The TOPS-10 OSE consists of 2K words of code distributed over 2 source files (and some files from a Bliss-10 library), and the HYDRA OSE is about half as large. Thus the OSE constitutes a separate subdivision of the compiler, and, as with other subdivisions, the interface between the OSE and the rest of the compiler has been redefined several times.

Originally we thought of the OSE as a collection of utility subroutines; the compiler at the top level was a system-independent controller consisting, like many compilers and other file processing programs under TOPS-10, of an infinite loop:

```
DO
  <read input/output file specifications>
  <create object file from source file>
OD
```

Eventually we realized that the top level of the compiler must itself be part of the OSE. The system-independent portion of the compiler is, at its top level, a subroutine which compiles a single Algol source program. This seems to be the largest unit of computation which all possible OSE's can deal with, ranging from the simplest paper-tape load-and-go systems for bare PDP-11's to complete operating subsystems with their own text editors, linkers, and version backup systems. Thus the HYDRA OSE consists of:

- (1) A set of utility subroutines, invoked from various points in the system-independent part of the compiler. These are:

- | | |
|-----------------|--|
| (1a) OSEsrcchar | Reads a single character from the source file, and returns the character as its value. End-of-file is denoted by a special character. Note that end-of-file here means end-of-logical-source-program; for instance, in the TOPS-10 OSE (and perhaps in future HYDRA OSE's) the source program compiled in a single compilation may stretch over several of the entities that the operating system knows of as "files". |
| (1b) OSElstline | Sends a single line of text off to be listed. The system-independent portion of the compiler believes that there are two places to which text output may be sent: a "listing device" and a "command device", corresponding in many systems to a line printer and a user's terminal, respectively. Thus one of the arguments to this routine is an indicator of which place(s) the line is to be sent to. |
| (1c) OSEerrmsg | Outputs a single error message. The sole argument to this |

routine is a number indicating which of many compilation errors occurred. In some OSE's, such as that for TOPS-10, this routine consists only of one or more invocations of OSElistline. It is included in the OSE itself because, in general, the method of obtaining the error message text to be output is expected to be system-dependent. For instance, in the HYDRA OSE, the error messages are not normally kept in addressable core; this routine makes them addressable temporarily.

(1d) OSEobjword Outputs a single word of code to the object file. This would be too small a unit of output if the compiler had to deal with different loader formats for such things as fixups, relocatable segments, and overlay structures, but we have avoided those by writing our own loader. OSEobjword is a null routine in the TOPS-10 version.

(2) A "top level". This opens various standard channels for I/O, performs other system-dependent initializations (e.g. initializing the symbolic debugging system), and calls the system-independent compiler. In load-and-go systems, this top level might start the user's program when the system-independent compiler had finished. (Alternatively, this might be more conveniently left to the operating system itself.) The current HYDRA OSE top level also includes

- (2a) A routine to handle aborted compilations. The system-independent compiler may find itself unable to continue due to such things as internal errors, lack of core, or I/O failures; in such cases it returns to its caller, with a result value indicating the cause of failure.
- (2b) Routines to initialize the settings of various compilation options, based on information supplied by the user to the operating system and passed by the operating system to the OSE.
- (2c) A routine to clear out a workspace in core for the compiler; this initialization must be in the OSE, because different versions may have completely different arrangements in memory of the compiler's code, workspace, and internal control stack.

(3) A set of global variables, which serve as an additional means of communication between the compiler and the OSE. They are:

- (3a) GBLerrs Count of ordinary compilation errors.
- (3b) GBLwarns Count of "mild" compilation errors--those which do not prevent the compiler from generating code.
- (3c) GBLfreelo Points to the start of the compiler's workspace.
- (3d) GBLfreehi Points to the end of the compiler's workspace.
- (3e) GBLprogstart An indication of the starting address of the compiled program.
- (3f) GBLpragflags The area (currently a single word) in which all the compilation option settings are kept.

4. Conclusions

There is a natural conflict between, on the one hand, the universal language design goal of portability and, on the other hand, one of the goals of system implementation languages (SIL's) in particular, namely that the programmer should be able to make use of all the facilities of the hardware, such as unusual instructions. The designers of PL/360[6] have resolved this conflict by sacrificing portability altogether. The designers of MARY[7] describe a subset of the language, "safe MARY", and a set of features which extend it to "unsafe MARY"; programs written entirely in the subset are guaranteed to be portable from one computer to another. The compiler can enforce the restriction to the subset, if the programmer desires. The approach taken by BLISS is not quite so strict as this. The designers regarded the various dialects of BLISS as "a class of languages that are similar in philosophy and that mirror a similar concern for the important aspects of systems programming, but each of which is tailored to its host machine[3]."

Usually the requirements of portability cannot be ignored. The more successful SIL's are bound to be implemented on more than one kind of computer, and for all but the lowest-level, most hardware-dependent programs (device handlers, diagnostics, and so forth) it will always be attractive to copy a program already written, even from another computer, rather than to write a new program from scratch. Therefore it is useful to consider what aspects of BLISS we found helpful in constructing a portable program, and what aspects were useless or even harmful.

It is evident that our principal tools, namely the REQUIRE feature and the practice of keeping the two libraries in separate groups of files, are extremely powerful; they could be used, and were used, as a "last resort" in the solution of portability problems, when there was no way to avoid writing two different (machine-dependent) versions of some routine or group of routines. The effectiveness of our techniques is therefore judged by the extent to which we had to use the "last resort", i.e. by the size of the libraries. Indirectly we also judge the suitability of BLISS for writing portable programs by this criterion.

In this respect the STRUCTURE definition facility has been outstandingly successful. The string data-type is an example of what has been done with this. Strings are represented in completely different ways on the two machines: packed 5 characters to a word on the PDP-10, aligned on byte (half word) boundaries on the PDP-11. But by the use of the CHARTECT structure, together with a small set of operations based on the BLISS-10 "special functions" SCANN, REPLACEI, etc., we have made string manipulation completely uniform, so that no library routines whatever had to be written for it. Perhaps an even more striking example is that of the structures PBLOCK and OBLOCK, the standard structures onto which pointers to blocks of packed data are mapped. These did not even have to be defined in SYSPRM.REQ, and thanks to the macros RH, LH, WORDF, ADDR, and SPCF, the definitions of fields in the various types of blocks need not be placed in the machine-dependent REQUIRE file either.

The LINKAGE definition facility should also be mentioned although we have so far made little use of it. By defining a linkage, such as REGO, one imposes special calling

conventions (e.g. special locations for actual parameters) on all routines which are declared with that linkage. It is particularly well designed for portability, in the following respects:

- Code which makes use of LINKAGE definitions and is correct is guaranteed to be correct when the use of special linkages is removed.
- The use of special linkages is particularly easy to remove. That is, the "fake definitions" which one must put in one version, corresponding to the linkage definitions and uses of another version, are extremely simple. The definition of REGO in the BLISS-10 version, our only example, is a null macro.

Two features of BLISS which we had to essentially ignore (except in the construction of libraries) were the ability to descend into machine code (the MACHOP feature of BLISS-10, the OPCODE feature of BLISS-11) and the ability to force local variables to be allocated to the machine's fast registers (the REGISTER declaration). It is worth asking why we could not make use of the second of these.

The alternative to the REGISTER declaration, in both versions of BLISS, is the LOCAL declaration. The choice between these two alternatives is not quite the same in BLISS-10 as it is in BLISS-11. In the former, LOCAL variables are always allocated on the control stack, but in the code that is generated, copies of the variables are often put in registers to allow easier access to them. In the latter, any LOCAL variable may be allocated either to a register or to a location on the stack, depending on the whim of the compiler, which attempts to find an optimal allocation. In both cases, the usefulness of declaring a variable as REGISTER instead of LOCAL in order to make frequent accesses to it less expensive is clouded or even nullified by the actions of the compiler. Thus REGISTER declarations are primarily useful only when they are necessary, e.g. in conjunction with use of the MACHOP (OPCODE) feature.

This paper has not covered two aspects of the question of portability which may be of general interest. The first of these is portability between really different languages. Although a version of the compiler has been produced principally by transcribing the BLISS source code into another (unrelated) higher-level language (PASCAL), we were not sufficiently familiar with that effort to discuss the questions raised by it in this paper.

The second of these is portability of the compiler to installations where BLISS compilers are not available. Since the BLISS-11 compiler produces assemblable PDP-11 code, it is possible to export the PDP-11 version of the compiler in the form of a set of assemblable files. But this leaves little room for the user of the system to make local modifications to it, such as additions of new language features, or modifications to the compiler's pre-initialized symbol tables; it is difficult or impossible in most cases to follow the assembly code produced by the BLISS-11 compiler, since it is, after all, completely uncommented and unformatted, and labels in the assembly code do not correspond in general to labels in the BLISS-11 source code. We have not yet attacked the problems raised by the general unavailability of BLISS-11 compilers at user sites, and so we postpone the discussion of them to future articles.

References

- [1] Wulf, W.A., and Bell, C.G., "C.mmp--a Multi-mini-processor", Proc. AFIPS 1972 FJCC, Vol. 41, AFIPS Press, Montvale, N.J., pp. 765-777.
- [2] Wulf, W.A., Cohen, E., Corwin, W., Jones, A., Levin, R., Pierson, C., and Pollack, F., "HYDRA: The Kernel of a Multiprocessor Operating System", Comm. ACM 17, 6 (June 1974), pp. 337-345.
- [3] Wulf, W.A., Russell, D.B., and Habermann, A.N., "BLISS: A Language for Systems Programming", Comm. ACM 14, 12 (Dec. 1971), pp. 780-790.
- [4] Reiner, A., and Newcomer, J. (eds.), "The HYDRA Users' Manual", technical report, Dept. of Computer Science, Carnegie-Mellon University, August 1977.
- [5] Sabin, M.A., "Portability--Some Experiences with FORTRAN", Software Practice and Experience 6, 3 (July-Sept. 1976), pp. 393-396.
- [6] Wirth, N., "PL360, A Programming Language for the 360 Computers", J. ACM 15, 1 (Jan. 1968), pp. 37-74.
- [7] Conradi, R., and Holager, P., "MARY Textbook", Regnesentret ved Universitetet, Trondheim, Norway, 1974.

Appendix

The following files are included here in their entirety:

B10PRM.REQ - PDP10 version of SYSPRM.REQ

B11PRM.REQ - PDP11 version of SYSPRM.REQ

COMMON.REQ - REQUIRE file used by every module in the compiler

SYSDEP.MAC - support routines for BLISS-10 SIGNAL/ENABLE

SIGENB.MAC - support routines for BLISS-11 SIGNAL/ENABLE

A68S10.B10 - heart of the TOPS-10 OSE

A68S11.B11 - heart of the HYDRA OSE

MOSTRC.REQ - typical REQUIRE file

LEXAN.BLI - representative code module

SRTABS.BLI - representative use of the DATAAREA macros

PAGE 1-1

DBKB:BIOPRM.REQ(L150ALBB)@CMU-10A

21-Feb-77 13:21 10 blocks

! BIOPRM.REQ (must be copied to SYSPRIL.REQ)

!

! Copyright 1977 P. Hibbard and P. Kneaven
! Pittsburgh, Pennsylvania

! System-dependent declarations for the Bliss 10 version.

bind

Qadrinc = 1, ! Increment from word address to next word address
Qdrdsiz = 18, ! Number of bits in an address value (pointer)
Qchard = 5, ! Number of characters per word
Qhfsiz = 18, ! Number of bits per half-word
Qhtab = 1, ! True iff horizontal tabs may be sent to output device
Qspare = 35, ! Must be 0 or Qdrdsiz-1
Qwrdtsiz = 36; ! Number of bits per word

!
! Macros to supply actual names of the Operating System Environment
! routines and globals.
!

macro

GBLerrrs = ?.errs \$,
GBLwarns = ?.warns \$,
GBLprngflags = ?.prngf \$,^
GBLprngstart = ?.prngs \$,
GBLfroochi = ?.frooch \$,
GBLfrooto = ?.froot \$,

OSEsrcchar = ?.SRCch \$,
OSElistline = ?.LSTLI \$,
OSEobjHord = ?.OBJHO \$,
OSEerrmsg = ?.Errms \$;

!
! Macros to smooth over the differences in the Bliss-10 syntax and
! the Bliss-11 syntax.
!

macro signal(e)=

begin external ?.SIGNL;
(.Frag-1)<8,36>-??.SIGNL<8,0>;
return e
end \$,
enable
register R(5); ! Forces all declarable regs to be preserved.
local ?.Frame(4);
external ?.ENABL,Sigval,Sigreg;
Vreg ~ (??.Frame-1)<8,0>;
?.ENABL();
if .Vreg eq 8
then 0
else exitblock select .Sigval of
next \$,

ethanen

PAGE 1-2

DSKB:BIOPMM.REQ(L150AL68)@CMU..16A 21-Feb-77 13:21 10 blocks

```
Otherwise: signal(.Signal)
              teen $,
enabandn:
  Sigreg-0(.Sigreg-2) $,
enableaven:
  enableaven; leave $,           ! The programmer is cautioned against
  enabreturn:                   ! using enableave or enabreturn to
  enabreturn:                   ! exit more than one level of ENABLEd
  enaband; return $,            ! blocks; an extra enabond is required
                                ! for each level.
byte   = $,
quoted = $,
uplit  = plit $,
unates = list $,
stacklocal = local $,
Reg0   = $,
maxl(A,B) = (if (A) geq (B) then (A) else (B)) $,
minl(A,B) = (if (A) leq (B) then (A) else (B)) $,
liss  = iss $, lequ = leq $,
eqiu = eqi $, nequ = neq $,
gequ = geq $, gtr  = gtr $,
rebindit(N,V) =
  bind XXXtmp = V;
  undeclare N;
  bind N = XXXtmp;
  undeclare XXXtmp $,
|
| Handy macro in Bliss-10
|
ID(x) = x$,
|
| Create pointer which consists of the address OR'd with the
| Quare bit. This cannot be done in a straightforward way
| due to a Bliss-10 bug.
|
SpcPtr(x) = (x)<32,0> $,
|
| Cheap non-zero value
|
nonzed = .Sreg $,
|
| Some attempts at solving the problem of declaring data in a
| machine-independent, language-independent way.
| Major obstacles to be surmounted:
| GLOBAL RINNs to symbols are illegal in Bliss-10;
| Bliss-10 does not have initialized RINNs or GLOBALNs;
| Bliss-11 does not have NAMES, INDEXES;
| Bliss-10 does not have iterated or recursive macros.
|
globaldata(strc,nm,sz) = bind strc ID(QQQ)nmsz=plit(nm globally names $,
dataarea(n) = bind Vector ID(QQQ)n = plit( n globally names $,
dataend = ) $,
gbiname(name,d) = name globally names d $,
```

PAGE 1-3

DSKB:B10PRM.REQ[L150AL68]@CMU-10A

21-Feb-77 13:21 10 blocks

```
gbindex(name,d) = name globally indexes d $,
locname(name,d) = name names d $,
locndx(name,d) = name indexes d $,
data(d) = d $,

gibname(x) = x globally names $,
gibbind(x,v) = switches optimize $,

! Support for machine-independent scan and replace operations
! See B11PRM.REQ for more explanation.

Nptrtochars(x) = (x)<29,7> $,
Nptrtobytes(x) = (x)<28,8> $,
Iptrtochars(x) = (x)<36,7> $,
Iptrtobytes(x) = (x)<36,8> $,
NtoIptr(x) = (x) $,
ItoNptr(x) = (x) $,
Iptrndx(x) = ((x)-1) $,

! Perform zero and move operations in best machine-dependent way.

Zerocor(start,cnt)=
begin machop BLT=#251;
register R;
R<(start)+1; R<18,18>-(start);
start=0;
BLT(R,(start)+((cnt)-1));
novalue
end $;

Movcor(s,d,cnt)=
begin machop BLT=#251;
register R;
R<(d); R<18,18>-(s);
BLT(R,(d)+((cnt)-1));
novalue
end $;

! Some structures.

structure Bytevect[] = [(I+3)/4] (.Bytevect+.I/4)<28-8*(.I and 3),8>;
structure Charvect[] = [(I+4)/5] (.Charvect+.I/5)<29-7*(.I mod 5),7>;
structure Hfvect[] = [(I+1)/2] (If .I then (.Hfvect+.I/2)<18,18>
                                else (.Hfvect+.I/2)<0,18>);
structure Hftable[I,J,P,S] = [(I+1)/2] (If .I+.J then (.Hftable+.I+.J)/2)<18+.P,.S>
                                         else (.Hftable+.I+.J)/2)<8+.P,.S>);

! END OF B10PRM.REQ
```

PAGE 1-1

DSKB:BLIPRM.REQ(L150ALGB)@CHU..10A

19-Feb-77 15:30 15 blocks

! BLIPRM.REQ (must be copied to SYSPRM.REQ)

!

! Copyright 1977 P. Hibbard and P. Knueven
! Pittsburgh, Pennsylvania

! System-dependent declarations for the Bliss II version.

bind

Qdrinc = 2, ! Increment from word address to next word address
Qdratiz = 16, ! Number of bits in an address value (pointer)
Ochaurd = 2, ! Number of characters per word
Ohtatz = 8, ! Number of bits per half-word
Ohtab = 0, ! True iff horizontal tabs may be sent to output device
Qspare = 0, ! Must be 0 or Qdratiz-1
Qwrlatz = 16; ! Number of bits per word

!

! Macros to supply actual names of the Operating System Environment
! routines and globals.

!

macro

GBLerrn = \$Errs \$,
GBLwarns = \$Warns \$,
GBLfreeo = \$Freeo \$,
GRLfreehi = \$Freehi \$,
GBLprogrstart = \$Progst \$,
GBLpragflags = \$Pragfl \$,

OSEarchar = \$SRCchar \$,
OSElistline = \$LISTline \$,
OSEobjword = \$OBJword \$,
OSEerrmsg = \$Errmsg \$;

!

! Macros to smooth over the differences in the Bliss-10 syntax and
! the Bliss-II syntax.

!

macro enbband = \$,
enblisave = leave \$,
enbreturn = return \$,
quoted = \$quote \$quote \$,
maxi(A,B) = ((A) max (B)) \$,
mini(A,B) = ((A) min (B)) \$,
semicolon = ; \$,
rebindit(N,V) = rebind N = V \$,

! Create pointer consisting of address OR'd with the Qspare bit.

!

SpcPtr(x) = (x) + 1 \$,

!

! Check non-zero value.

!

nonzed = .PC \$,

```
!
! Some attempts at solving the problem of declaring data in a
! machine-independent, language-independent way.
! Major obstacles to be surmounted:
! GLOBAL BINDs to symbols are illegal in Bliss-10;
! Bliss-10 does not have initialized DHNs or GLOBALs;
! Bliss-11 does not have NAMES, INDEXES;
! Bliss-10 does not have iterated or recursive macros.
! Macros whose names begin with $ ($Makdata, $Setupdata, $Strippers,
! $Setupbinds) are not intended to be used outside B11PRM.REQ .
!

globaldata(strc,nm,sz) = global bind strc nm[sz] = uplit( $,
dataarea(name) = $Makdata(name, $,
dataend = ) $,
gbname(name)[] =
    Squote2 Snamebind, global, name, $Length-1, ($Remaining) $,
gbindex(name)[] =
    Squote2 $indexbind, global, name, $Length-1, ($Remaining) $,
locname(name)[] =
    Squote2 Snamebind, , name, $Length-1, ($Remaining) $,
locindex(name)[] =
    Squote2 $indexbind, , name, $Length-1, ($Remaining) $,
data[] =
    Squote2 $obind, , , $Length , ($Remaining) $,
$Makdata(name)[] =
    external name;
bind SName('.NAME.') = name, SName('.INDEX.') = 0;
$Setupbinds($Remaining);
undeclare name,SName('.NAME.'), SName('.INDEX.');
global bind name = plit $Setupdata($Remaining) $,
Squote2 = quoted quoted quoted $,
Snamebind(name) = bind name = SName('.NAME.') + 2*$Name('.INDEX.') $,
$indexbind(name) = bind name = SName('.INDEX.') $,
$obind(name) = switches optimize $,
$Setupdata(bnd,gbl,name,len,list) = $Strippers(list $,
$Strippers() = $Remaining $,
$Setupbinds(bnd,gbl,name,len,list) =
    gbl bnd(name);
    rebind SName('.INDEX.') = SName('.INDEX.')+len $,
gibname(x) = $,
gibbind(x,v) = global bind x = v $,
!

! Support for machine-independent scan and replace operations
! The goal is to have efficient character/byte scanning operations
! which are machine independent. Bliss-10 provides scan and replace
! operators which allow the programmer to perform PDP-10 byte instructions
! and thus are relatively efficient. An efficient method of scanning on
! the PDP-11 is through the use of auto-increment addressing modes in
! byte instructions. Thus, an obvious approach to reaching the goal is
! to provide Bliss-11 scan and replace macros which cause the generation of
! byte instructions with auto-increment operands. The major difficulty
! in implementing this solution is that the PDP-10 pointer-incrementing
```

Instructions perform the increment before a fetch or store, while the PDP-11 instructions increment afterwards. This difficulty is overcome by forcing the programmer to pay special attention to the way in which pointers are initialized and used.

Pointers may be one of two varieties, I-pointer or N-pointer. N-pointers always refer to a particular byte until an incp is performed. I-pointers increment before each access, i.e. after an access an I-pointer refers to the byte accessed. The rules for using those kinds of pointers may be stated by consistently substituting N or I for X in the following paragraph.

X-pointers must be initialized by assigning a value yielded by an Xptrto... operator. All operations on an X-pointer must be an incp, X-operation (i.e. scanX, replaceX or copyXI) or the appropriate conversion operator.

An I-pointer value may be converted to an N-pointer value by using ItoNptr. The new N-pointer refers to the byte last accessed by the I-pointer. Similarly, NtoIptr may be used to create an I-pointer from an N-pointer. The new I-pointer refers to the same byte as the N-pointer. However, since only I-operations are permissible that byte is not accessible via the I-pointer.

Iptrrndx(n) is used in conjunction with the Bytovect and Charvect structures. When used as the actual parameter in a Bytovect or Charvect structure access, it produces an I-pointer which will access the n-th byte or character in the first I-operation in which it is used.

```

incp(ptr)      = ( (ptr)+, (ptr)+1 ) $,
scanN(ptr)     = ( .,(ptr)<0,8> ) $,
replaceAll(ptr,x) = ( .,(ptr)<0,8>+{x} ) $,
replaceI(ptr,x) = ( .,(ptr)<0,8>+{x}; incp((ptr)); ) $,
copyII(pt,opt) = ( replaceI((opt),scanN((pt))); incp((pt)); ) $,
copyII(plt,opt) = ( replaceI((opt),scanN((plt))); incp((plt)); ) $,
Nptrtochar(x)  = x $,
Nptrtobytes(x) = x $,
Iptrtochar(x)  = x $,
Iptrtobytes(x) = x $,
ItoNptr(x)     = ((x)-1) $,
NtoIptr(x)     = ((x)+1) $,
Iptrrndx(x)   = x $,

```

Perform zero and move operations in best machine-dependent way.

```

Zerocor(adr,cnt)=
begin
register Ptr;
opcode CLR;
Ptr+(adr)+(cnt)*2;
while .Ptr gtru (adr) do
    CLR(A-Ptr);
novalue
end $,

```

```
Movecor(s,d,cnt)=
```

PAGE 1-4

DSKB:B11PRM.REQ(L150NL68)@CMU-10A 19-Feb-77 15:30 15 blocks

```
begin register Src,Dst;
opcode MOV;
Src+=; Dst+=;
decr I from (cnt)-1 to 0 do
    MOV(&+Src,&+Dst);
novalue
end S;

! Some structures.
!
structure
    Bytevect[] = [] (.Bytevect+.I)<0,8>;
    Charvect[] = [] (.Charvect+.I)<0,8>;
    Hfvect[] = [] (.Hfvect+.I)<0,8>;
    Hftable[I,J,P,S] = [] (.Hftable+.I+.J)<.P,.S>;
!

! Some linkages.
!
linkage
    RegD = Bliss(register=0);

!
! END OF B11PRM.REQ
```

PAGE 1-1

OSKB:COMMON.REQ(L150RL68)@CMU-10A 13-Jul-77 12:14 10 blocks

! COMMON.REQ

!

! Copyright 1977 P. Hibbard and P. Knuven
! Pittsburgh, Pennsylvania

! Common definitions included in every module.

! Target machine parameters

bind

Xbase = 8,
Ybase = #100000,

Zadrinc = 2, ! Increment from word address to next word address
Zcharwd = 2, ! Characters per word
Zhfsiz = 8, ! Bits per half-word
Zspare = 1, ! Value to add to make an illegal word address
Zwordsz = 16, ! Bits per word

ZRnizNaked = 2,
ZRnizLENbase = 7,
ZRnizLBbase = 16,
ZRnizBtop = 4+(if ZRnizNaked eqi 1 then 2),
ZRnizDreadad = 2,
ZRTypGenblock = 76,
ZRnizDesctrip = 4;

! Useful keywords

macro

if = then \$,
elif = else if \$,
otherwise = always \$, ! To be used like "T" in a Lisp COND.
repeat = while I do \$,
exitL = leave L with \$,
newValue = .Vreg \$,
bool(s) = if (s) then true \$,
times3(x) = (2*x)+(x) \$,
modulo(L,R) = (if (R) and -(R)) eqi (R)
 then (L) and (R)-1
 else (L) mod (R)) \$,
divide(L,R) = (if (R) eqi 1 then (L)
 elif (R) eqi 2 then (L)†(-1)
 elif (R) eqi 4 then (L)†(-2)
 else (L)/(R)) \$,
Mng(str) = Nptrtocharn(uplft asclz str) \$,
comment = switches optimize; \$;

! Some structures

structure Bitvect(P,S) = (.Bitvect) <.P,.S>;
structure Pblock(I,P,S) = (.Pblock+Qadrincs,I)<.P,.S>;
structure Oblock(I,P,S) = (.Oblock+Qadrincs,I-1)<.P,.S>;
structure Constbv(I,J,K) = (if .K eqi 0

PAGE 1-2

DSKB:COMMON.REQ(L150NL68)@CMU-10A 13-Jul-77 12:14 18 blocks

```
        then .Constbvff(-,I) and IT.J-1  
        else .Constbvff(-,J) and IT.K-1) <8,0>;
```

! More useful definitions

bind

```
true      = 1,  
false     = 0,  
zed       = 0,  
Constbv Minusl = -1,  
HTab      = #11,  
LF        = #12,  
FF        = #16,  
CR        = #15,  
EOFchar   = #200,  
SRPLatKsize = 128,      ! Semantic/Syntax stack size  
Cbufsize= 132;          ! Standard character buffer size
```

! Macros useful in field definitions

macro

```
ZRH      = 0,Zhfsiz $,  
ZLH      = Zhfsiz,Zhfsiz $,  
RH       = 0,Qhfsiz$,  
LH       = Qhfsiz,Qhfsiz$,  
Wordif   = 0,Qwordsz $,  
Addrif   = 0,Qaddrsz $,  
Specf    = Qspare,1 $,  
Clrspare(x) = (x) and not 1#Qspare $,  
Zhwords(Lo,Hi) = ((HI)1Zhfsiz or (Lo)) $,  
Hwords(Lo,Hi) = ((HI)1Qhfsiz or (Lo)) $;
```

! Fatal error codes

bind

```
FatNospace = -1,  
FatBufovfl = -2,  
FatUser    = -3;
```

! Interface to Operating System Environment (OSE)

external

```
GBLerrs, GBLwarns,  
GBLfreeio, GBLfreehi,  
GBLprgstart,  
Bitvect GBLpragflags,  
  
OSEsrcchar,  
RegO OSElistline,  
RegO OSEobjword,  
RegO OSEerrmsg;
```

! Field definitions for GBLpragflags

macro

```
Prgstrop  = RH $,  
Prglist   = Qhfsiz+8,1 $,
```

PAGE 1-3

DSKB:COMMON.REQ(L1580L68)eCMU-10A

13-Jul-77 12:14 10 blocks

Pryobj = Qhtsiz+1,1 \$,
Prgharr = Qhtsiz+2,1 \$,
Prgmach = Qhtsiz+3,1 \$,
Prgnonaked = Qhtsiz+4,1 \$,
Prgnoghost = Qhtsiz+5,1 \$;

END OF COMMON.REQ

PAGE 1-1 OSKB:SYSDEP.MAC(L150AL68)@CMU-10A 22-Feb-77 15:44 5 blocks

; SYSDEP.MAC

;

; Copyright 1977 P. Hibbard and P. Kruiven
; Pittsburgh, Pennsylvania

TITLE SYSDEP ALGOL68 SYSTEM DEPENDENT MACHINE LANGUAGE ROUTINES
TWOSEG

JOBREN#124

LOC JOBREN

XWD 0,REHADR

JOB61#41

LOC JOB61

JFCL ; NOP FOR SIX12 UUO'S

RELOC 400000

; COMPILER CONSTANTS

LSTCHN#1 ; LISTING CHANNEL

; CALLI DEFINITIONS

RESET#8

EXIT#12

; CODE EXECUTED WHEN MONITOR "REENTER" COMMAND IS GIVEN

;

REENTER: CLOSE LSTCHN,0 ; CLOSE LISTING FILE ON REENTRY

CALLI 0,RESET ; DO NOT WRITE OTHER FILES

CALLI 0,EXIT ; GO AWAY

; BLISS 10 SPECIAL REGISTERS

SS#0 ; SREG: STACK POINTER REGISTER

SF#2 ; FREG: POINTS TO CURRENT INVOCATION BLOCK

SV#3 ; VREG: VALUE REGISTER

; DETECT FLOATING-POINT OVERFLOW

;

FLTOVF:

SETO SV,

JFOV .+2

SETZ SV,

POPJ SS,

; ENABLE FRAME FORMAT

; FRAME#0: POINTER TO ENABLE CODE

; FRAME#1: POINTER TO PREVIOUS FRAME#3

; FRAME#2: SAVED FREG

; FRAME#3: SAVED SREG

PAGE 1-2

DSKB:SYSDEP.HAC(L150NL68)@CMU-10A

22-Feb-77 15:44 5 blocks

```
; ROUTINE TO SET UP ENABLE FRAME
;
; INPUTS
;   VREG - POINTER TO NEW 4-WORD FRAME-1
;
; OUTPUTS
;   SIGREG - POINTER TO FRAME+3
;   VREG - ZERO
;
.ENABLE:
    EXCH    $S,1
    PUSH    $V,0(1)
    PUSH    $V,SIGREG
    PUSH    $V,$F
    PUSH    $V,1
    SOS     B($V)
    MOVEM   $V,SIGREG
    SETZ    $V,
    EXCH    $S,1
    POPJ    $S,
;

; ROUTINE TO PERFORM A SIGNAL
;
; INPUTS
;   VREG - SIGNALLED VALUE
;
; OUTPUTS
;   SIGVAL - SIGNALLED VALUE
;   SIGREG - RESTORED TO POINT TO PREVIOUS FRAME
;   VREG - NON-ZERO
;   RETURNS TO MOST RECENT (DYNAMICALLY) ENABLE DECLARATION
;
.SIGNAL:
    MOVEM   $V,SIGVAL
    MOVE    $V,SIGREG
    POP     $V,$S
    POP     $V,$F
    POP     $V,SIGREG
    POPJ    $V,
;

; INITIAL ENABLE CODE
ENABLE: CALLI  1,EXIT

; INITIAL ENABLE FRAME
FRAMEB: EXP    ENABO, FRAMEB+3, B, B

RELOC  8

; VARIABLES USED BY SIGNAL/ENABLE ROUTINES
SIGVAL::      B          ; SIGNALLED VALUE
SIGREG::      FRAMEB+3   ; POINTS TO TOP OF STACK OF ENABLE FRAMES

END
```

PAGE 1-1 DSK:SIGENB.M11(N810HY97) 28-Jul-76 11:40 5 blocks

; File: SIGENB.M11(N810HY97)
;
; This work was supported by the Advanced Research
; Projects Agency of the Office of the Secretary of
; Defense (F44620-73-C-0074) and is monitored by the
; Air Force Office of Scientific Research.

.TITLE SIGENB

.CSECT SIGE.C

; The BLISS-11 out of line routines to handle SIGNAL's and
; ENABLE frame creation.

; 11-Nov-73 P. Knueven
; 26-Jul-76 P. Karlton - change to location of
; SIGREG and SIGVAL to be SAVREG and
; SAVVAL as in STKPAG.REQ(N811HY97)
; Commented out LEV0 and EXIT also.

; The dynamically nested occurrences of ENABLE declarations
; are recorded in the LIFO ENABLE stack. This is implemented
; as a linked list of 3-word stack frames. The current top of
; the stack is pointed to by .SIGREG. An ENABLE frame is
; created each time an ENABLE declaration is "executed".
; It looks like the following:

; Offset Contents
; 0 Pointer to most recent previous frame
; 2 Value of SP for the ENABLE body
; 4 Pointer to the ENABLE body

.GLOBL SSIGNL,SSIGN1
.GLOBL SENABL
.GLOBL SIGVAL,SIGREG

R8=X0
SP=X8
PC=X7

; Calling Sequence
; MOV E,R8
; JMP SSIGNL
;
SSIGNL: MOV R8,SIGVAL
SSIGN1: MOV SIGREG,R8
MOV (R8)+,SIGREG
MOV (R8)+,SP
MOV (R8)+,PC

; Calling Sequence
; MOV #n+6,R8
; JSR PC,SENABL
; .WORD L2-L1
; L1:
; ... ENABLE body ...

PAGE 1-2

DSK:SIGENB.M11(N810NY97)

28-Jul-76 11:40 5 blocks

```
; L2:  
;  
; where n is 2 plus the offset into the stack of the  
; space reserved for the frame  
;  
SENABL: ADD      SP,R0  
        MOV      (SP), (R0)  
        ADD      #2, (R0)  
        MOV      @ (SP), (SP)  
        ADD      (R0), (SP)  
        MOV      SP,-(R0)  
        ADD      #2, (R0)  
        MOV      SIGREG,-(R0)  
        MOV      R0,SIGREG  
        RTS      PC  
  
;SEXIT: HALT  
;  
;SLEV8: .WORD  0,0,SEXIT  
  
SIGREG =      270          ; SAVREG address  
SIGVAL =      272          ; SAVVAL address  
  
.END
```

PAGE 1-1 DSKB:AG8S10.B10(L150AL88)@CHU-10A 3-Oct-77 02:40 38 blocks

```
| AG8S10.B10
|
| Copyright 1977      P. Hibbard and P. Knueven
|                               Pittsburgh, Pennsylvania
module AG8S10(stack(1000)) =
begin
|
|          PDP-11 ALGOL 68S Cross-compiler for PDP-10
|
|
switches nolist;
require DIOPRN.REQ;
require COMMON.REQ;
require IOMACS.REQ;
switches list;

undeclare
OSElistline,
OSEerrmsg,
OSEobjword,
OSEsrcchar;

forward
| Initchnl,
| InitFDB,
| Cmdmsg,
| Cvtfile,
| Reset,
| Getbuf,
| Lkupntr,
| Getcmd,
| Perrmsg,
| Initchna,
| Punt,
| Page,
| Lread;

bind   FatCmdlong = FatUser-0,
       LSTlinesperpage = 50;

own
LSTheadpg,
LSTpage,
LSTcount;

Machine Call = #47;

bind
Critm  = Msg('?M?J'),
Specm  = Msg(' '),
Errm   = Msg('Command error'),
PPNm   = Msg('Invalid PPN');

bind
```

PAGE 1-2 DSKB: A68S10.B10(L150AL68)@CHU-10A 3-Oct-77 02:48 36 blocks

Maxbuf = #203,
IObuf1 = 6*Maxbuf;

external

Buffers,
Close,
Date,
Dayofweek,
Enter,
Filescan,
Lookup,
Open,
Pdate,
Ptime,
Purgeout,
Read,
Writemsg;

own

IObuff[IObuf1],
IObufp,
Srcbufp,
Bitvect Grootem,
FDR(5),
Extseen,
Chnl;

bind

Device = FDR(0),
Filename = FDR(1),
Extension = FDR(2),
PrTlDate = FDR(3), ! Protection, Time, Date
PPN = FDR(4),

LkupBlk = FDR(1),
NtrBlk = FDR(1);

!

! Names of fields in words in the Chnlstat block

!

macro

Specd = 0,1 \$, ! True if channel has been correctly initialized
TTYd = 1,1 \$, ! True if device on channel is a TTY
Binto = 18,1 \$, ! True if channel is for binary I/O,
! False if for ASCII
Inptc = 19,1 \$; ! True if channel is for input,
! False if for output

bind

Cmchn = -2,
Cmochn = -1,
Binchn = 0,
Latchn = 1,
Srcchn = 2,
Hichn = Srcchn;

PAGE 1-3 DSKB:R68S10.B10(L150NL68)@CMU-10A 3-Oct-77 02:48 36 blocks

```
structure Bufhdvec[] = [3e1] (.Bufhdvec+3e.1);
structure Block[I,P,S] = [I+Qadrinc] (.Block+Qadrinc.1)<.P,.S>;

own Bufhdvec Bufhd[Hichn+1];
own Block Chnstatat[Hichn+1];

structure Chnstatwd[P,S] = (Chnstat+.Chnstatwd)<.P,.S>;
map Chnstatwd Chnl;      ! so that .Chnl[Specd] means .Chnstat!.Chnl.Specd

bind Vector Initstat[Hichn+1] = p11(
    Hfwords(0,1),
    Hfwords(0,0),
    Hfwords(0,2));

macro Initchnl(chan,blk) =
begin
| blk is always FDD
| Chnl+(chan);
| Lkupntr()
| end$;

macro InitFDB(dev,file,ext) =
begin
| Device=dev;
| Filenam=file;
| Extension=ext;
| PrTlDate=PPN=0;
| end$;

comment ! Cvtfile
!
! Functions: set up a character string, to be output by the caller,
! that describes a file (device, name, extension).
!
! Locals
! Mngbuf - space to hold the string
! Dstp - a byte pointer to the string
! FDB - the block holding the information about the file
!
! Output
! VALUE - byte pointer to the 1st character of the string
!
routine Cvtfile =
begin
own Mngbuf(4),Dstp;

comment ! Cvtsix(N)
!
! Functions: convert a SIXBIT string to ASCII and append it to
! the current string (DSTP).
!
! Inputs
! N - word containing the SIXBIT string
!
```

PAGE 1-4

DSKB:AB8810.B10(L150NL68)@CMU-10A

3-Oct-77 02:40 38 blocks

```
routine Cvtsix(N) =
begin
local Srcp;
Srcp=N<36,6>;
decr I from 5 to 0 do
  if scanl(Srcp) eq1 0
    then exitloop
    else replacei(Dstp,scann(Srcp)+#40);
novalue
end;

Dstp->ptrtochar(Magbuf);
Cvtsix(.Device);
Replacei(Dstp,":");
Cvtsix(.Filename);
Replacei(Dstp,".");
Cvtsix(.Extension and #7777777Qhtsiz);
Replacei(Dstp,0);
Nptrtochar(Magbuf)
ond;

comment ! Cmdmsg(Str)
!
! Functions: output a message to the user's terminal, ending
! with CRLF, using TTSCALL's.
!
! Inputs
! Str - pointer to a word whose high byte begins the
! string to be output.
!
routine Cmdmsg(Str) =
begin
Writemsg(Cmachn,.Str);
Writemsg(Cmachn,Crlf);
Purgeout(Cmachn);
novalue
end;

comment ! Reset
!
! Functions: do a RESET UUO, and reinitialize the Chnstat words
!
routine Reset =
begin
map Vector Chnstat;
IObufp->IObuff<8,8>;
Movocor(Initstat,Chnstat,Hichn+1);
CallI(0,8);
novalue
end;

comment ! Getbuf
!
! Function: allocate space for I/O buffers for a given channel,
```

PAGE 1-5 DSKB:R68S10.B10(L150AL68)@CHU-10A 3-Oct-77 02:48 38 blocks

```
! calling the BLLIB routine BUFFERS.

! Inputs
! Chnl - a channel number, between Cnchn and Hichn inclusive
! lobuff[lobufi] - a large block of space from which all I/O buffers are taken
! lobufp - a pointer to the beginning of unused space in lobuff

! Outputs
! lobufp - updated
! VALUE - True if buffer space was allocated,
!         false if some error was encountered

routine Gotbuf =
begin
local Size;
if .Chnl eq1 Srechn then Srcbufp-.IObufp;
Size=2*(2+Buffers(.Chnl,0,.Chnl[Inpio],0));
if .IObufp+.Size leq [Obuff[Obufi]<8,0] then
begin
Buffers(.Chnl,2,.Chnl[Inpio],.IObufp);
IObufp+.IObufp+.Size;
True
end
endif;

comment ! Lkupntr

! Function: Initialize a channel for I/O as indicated

! Inputs
! Chnl - the channel number
! FOB - a block containing all necessary information about the
!       current channel, except that contained in
! Chnstat[Hichn] - a vector of words, one for each channel, each
!                   of which contains a few bits of information about
!                   the channel.

! Outputs
! VALUE - True if initialization succeeds, false otherwise

routine Lkupntr =
begin
macro Devchr(dvnm) = (register QQ; QQ=dvnm; call1(QQ,#6))$;
macro Binarymt = 12,1 $,      ! Names of fields in the DEVCHR result word
    Ascimt = 1,1 $,
    TTYdevf = 21,1 $;
bind Binarymode = #14, Ascilinemode = 1;
bind L150 = #25627, L150AL71 = #25627010165;
register Bitvect R;

if not .Chnl[Specd]          ! Is channel already in use?
  thif (R-Devchr(.Device)) neq 0  ! Does device exist?
  thif (if (.Chnl[Binio]
            then .R[Binarymt]
            else .R[Ascimt]))
  thif Open(.Chnl,           ! Does OPEN UOO succeed?
            if .Chnl[Bint])
```

PAGE 1-6

DSKB:R68S16.B10(L150AL68)@CHU-10R 3-Oct-77 02:48 38 blocks

```
then Binarymode
else Ascillinemode,
.Device,
if .Chnl[Inpio]
then Bufhdl(.Chnl)<0,0>
else Bufhdl(.Chnl)<0,0>?Qhfsiz)
thif Getbuff() neq 0           ! Can buffers be gotten?
thif (if .Chnl[Inpio]          ! Does LOOKUP or ENTER UUD succeed?
then begin
local SavPPN;
SavPPN-.PPN;
if Lookup(.Chnl,LkupBlk) then exitblock true;
if not .Extseen then
begin
Extension=0;
if Lookup(.Chnl,LkupBlk) then exitblock true;
Extension=sixbit 'B60';
ends;
if .SavPPN eqi 0 and .Greetem(LH) eqi L150 then
begin
PPN=L150AL71;
if Lookup(.Chnl,LkupBlk) then exitblock true;
ends;
false
end
else Enter(.Chnl,NtrBlk))
then begin                  ! Success
Chnl[TTYd]^.R(TTYdev);
Chnl[Specd]=True;
return True;
ends;
Cmdmsg(Msg('Initialization failure')); ! Failure
Cmdmsg(Cvtfile());
False
ends;

comment ! Getcmd
!
! Functions: input a command from the user's terminal,
! using TTCALL's
!
! Outputs
! Cmdbuf - a block of bytes in which the command is stored as an ASCII string
!
routine Getcmd =
begin
bind Cmdbuf1 = 20;
own Cmdbuf(Cmdbuf1);
register Ptr,N;
Ptr->ptrtochars(Cmdbuf);
N=QchurdoCmdbuf1;
do begin
if (N=N-1) lss 0 then
Punt(FatCmldlong);
replicoi(Ptr,Read(Cmchn));
end
```

PAGE 1-7 DSKB:A68S10.B10(L150AL68)@CMU-10A 3-Oct-77 02:40 38 blocks

```
        until .Vreg eqf Lf;
        lptrtochars(Cmdbuf)
        end;

routine Formsg =
begin
macro GetPPH = (register QQ; QQ=0; CallI(QQ,#24))$;
macro Greet(What,What) = What: exitselect Cmdmsg(Msg(What))$;
bind
    AH20 = #005040,
    AL68 = #010130,
    AL69 = #010131,
    AL70 = #010164,
    AL74 = #010170,
    BL03 = #032013,
    GA10 = #155604,
    PH02 = #427112,
    PK02 = #431202,
    SA20 = #511150,
    TR30 = #547404,
    WH17 = #641573;
if .Greetem neq 0 then return novalue;
Greetem=GetPPH;
select .Greetem(RH) of
  nsat
    Greet(AH20,'Watch me blaze Pascal');
    Greet(AL68,'Let me elaborate on that');
    Greet(AL69,'Let me elaborate on that');
    Greet(AL70,'Let me elaborate on that');
    Greet(AL74,'Where''s the missing link??');
    Greet(BL03,'Hi Bruce');
    Greet(GA10,'Hug Guy');
    Greet(PH02,'Thou art Peter');
    Greet(PK02,'Good luck Paul');
    Greet(SA20,'It''s that crazy Swedo again');
    Greet(TR30,'Give my regards to Cme');
    Greet(WH17,'It''s big daddy Bill')
  teen;
  novalue
end;

comment ! Initchns(Srconly)
!
! Function
! Initialize I/O channels.
!
! If Srconly is neq 0 then get command line from
! user and initialize specified channels.
!
! If Srconly is less 0 then initialize source input channel to read from
! next specified input file. Return False as value iff end-of-data or
! error occurred.
!
routine Initchns(Srconly) =
begin
macro
```

```
Cmddone = return True $,
Cmdfail = return False $,
Cmderr(x) = (Cmdmsg(x); Cmdfail)$;
own Cmdeof,Ptr;
local Bitvect Scanv;
macro Retcode = RH $,           ! Names of fields in the FILESCAN result word
Breakch = LH $;

if .Sreonly eqq 0
then begin
    Reset();
    Pormsg();
    Writelnmsg(Cmochn,Msg('e'));
    Purgeout(Cmochn);
    Cmdeof=False;
    LSTpage=0;
    LSTcount=LSTlinesperpage;
    Ptr=Getcmd();
    Chnl=Latchn;
    end
else begin
    Chnl=Srechn;
    end;
until .Cmdeof do
begin
    InitFDB(sixbit 'DSK', 0,
            case .Chnl-Binchn of set sixbit 'OBJ'; sixbit 'P11'; Zsixbit 'A68' % 0 tes);
    Scanv=Filescan(Ptr,FDB);
    if not (Extseen-.Extension neq 0)
        then Extension=sixbit 'A68';
    case .Scanv(Retcode)+(-1) of
        set
        0;
        Cmderr(Errm);
        Cmderr(PPNn);
        Cmderr(PPNn);
        Cmderr(PPNn);
        Cmderr(Msg("Invalid switch specification"));
        tes;
    if .Scanv(Breakch) eqq "+"
        then Scanv(Breakch)+"="
    else if .Scanv(Breakch) eqq ";"
        then Scanv(Breakch)+Cr;
    select .Scanv(Breakch) of
        nset
        ",":exitselect begin
            if .Chnl eqq Latchn then Cmderr(Errm);
            if .Scanv then
                if not Initchn(.Chnl,FDB) then Cmdfail;
            if .Chnl eqq Binchn
                then Chnl=Latchn
            elseif .Scanv then Cmddone;
        end;
    "=":exitselect begin
        if .Chnl eqq Srechn then Cmderr(Errm);
        if .Scanv then
```

PAGE 1-8

DSKB:A68S10.B10(L150RL68)eCMU-10A 3-Oct-77 02:48 38 blocks

```
    If not Initchn(.Chnl,FDB) then Cmdfail;
    Chnl←Srcchn;
    end;

Cr: exitselect begin
    Cmdeof=True;
    If .Scany
        then (If .Chnl eqi Srcchn then
            If not Initchn(.Chnl,FDB)
                then Cmdfail
                else Cmddone)
        elif .Chnl eqi Binchn then
            Cmdfail;
    Cmderr(Errm);
    end;

    Otherwise Cmderr(Msg('Illegal delimiter'))
    testn;
    end;
end;
false
ond;

routine Punt(N) =
begin
    external JobDDT,Jobsn,Six12;
    doer I from Hichn to 0 do
        If .Chnistat[I,Specd] and not .Chnistat[I,Inpl] then
            Purgeout(I);
    Cmdmsg(Msg('?M?J??PUNT!'));
    If .JobDDT neq 0
        then Six12(-1)
        else (.Jobsn)();
    novalue
    end;

!
! Source Input
!

comment ! Lread
!
! Functions: call the BLILIB routine READ, passing Srcchn as
! argument, and return the result, except that if the character read
! is a character of an SOS line number, return an error code of -3.
!
routine Lread =
begin
    bind Vector Bufhd = Bufhd(Srcchn);
    bind Bytptr = 1;
    If Read(Srcchn) gtr 0 then
        If @Bufhd[Bytptr] then
            Vreg←-3;
    .Vreg
    end;
```

PAGE 1-18

DSKB:R68S10.B10(L150ALG8)eCHU-10A

3-Oct-77 02:48 30 blocks

```
comment ! OSERecchar
!
! Functions: got a character from the input buffer. Process
! line numbers, I/O errors, and end-of-file conditions correctly.
!
global routine OSERecchar =
begin
local Bitvect Char, InSOSno;
InSOSno:=zad;
while (Char=Lread()) lss 0 do
  case .Char+3 of
    set
      ! 0 - Line number character
      InSOSno:=nonzed;

      ! 1 - I/O error
      begin
        Cmdmsg(Msg('Input transmission error'));
        return EOFchar;
      end;

      ! 2 - End-of-file
      begin
        Close(Srcchn);
        Chnstat[Srcchn,Wordf]:=Initstat[Srcchn];
        IObufp^.Srcbufp;
        if not Initchn(-1) then
          return EOFchar;
      end
    tes;
  if .InSOSno neq 0 and .Char eq HTab
    then 0
    else .Char
  endj;

!
! Listing Output
!

routine Lstmsg(Str) =
begin
  Writemsg(Latchn,.Str);
  novalue
endj;

routine Pago =
begin
  external Varsid;
  bind Dayo(7#2) = pltt(
    'Sunday',
    'Monday',
    'Tuesday',
    'Wednesday',
    'Thursday',
    'Friday',
```

PAGE 1-11

DSKB:A68S10.B10(L150AL68)@CHU-10A

3-Oct-77 02:40 30 blocks

```
'Saturday');
local Today;
LSTcount=0;
if not .Chnstat[Latchn,TTYd] then
begin
  Today=Date();
  Lstmsg(Msg('?L;Rigol 68 '));
  Lstmsg(Nptrtochars(Versid));
  Lstmsg(Spcsm);
  Lstmsg(Nptrtochars(Days[2+Dayofweek(.Today)]));
  Lstmsg(Spcsm);
  Pdate(Latchn,.Today);
  Lstmsg(Spcsm);
  Ptime(Latchn,-1);
  Lstmsg(Spcsm);
  Lstmsg(Cvtfile());
  Lstmsg(Msg(' Page '));
  LSTheadpg=0;
  Cvtdecz(Iptrtochar(LSTheadpg),LSTpage-.LSTpage+1,3);
  Lstmsg(Nptrtochars(LSTheadpg));
  Lstmsg(Crlf);
  Lstmsg(Crlf);
  Purgeout(Latchn);
end;
navalue
end;

comment ! OSEIstline(First,Foll,Errdev)
!
! Functions: output a string to the listing device, and possibly to
! the user's terminal as well, appending a CRLF.
!
! Inputs
! First- byte pointer to the first character of the (ASCII) string
! Foll - byte pointer to the character just after the last character
! of the string. This is temporarily set to zero, to make
! the string ASCIZ, before calling Writemsg.
! Errdev - nonzero if the string is also to be output to the terminal
!
global routine OSEIstline(First,Foll,Errdev) =
begin
  if .GBLprngflags[Prglist] or .Errdev neq 0 then
  begin
    local Sav;
    if (LSTcount-.LSTcount+1) gtr LSTlinesperpage then
      Page();
    Sav=scann(Foll);
    replacen(Foll,0);
    if .Chnstat[Latchn,Spcd] then
    begin
      Lstmsg(.First);
      Lstmsg(Crlf);
      if .Chnstat[Latchn,TTYd] then Purgeout(Latchn);
    end;
    if .Errdev neq 0 and not .Chnstat[Latchn,TTYd] then
      Cndmsg(.First);
```

PAGE 1-12 OSKB:068S10.B10(L150AL68)@CHU-10A 3-Oct-77 02:48 30 blocks

```
    replacen(Foll,.Save);
    end;
novalue
end;

! Object Output
!

global routine OSObjword = novalue;

! Error Message Output
!

global routine OSErrorMsg(N) =
begin
  external Errtxt;
  if .Errtxt[N] neq 0 then
    begin
      Out$(' - ');
      Outsz(.Errtxt[N]);
    end;
novalue
end;

! Initialization and Finalization
!

macro Initmem (dum) =
begin
  global GBLfreeLo, GBLfreeHi, Freearea(3000);
  GBLfreeLo = Freearea<0,0>;
  GBLfreeHi = (Freearea+3000)<0,0>;
novalue
end $;

routine Initprags =
begin
  GBLpragFlags=0;
  GBLpragFlags[Prgstrop]=1;
  GBLpragFlags[Prgwarn]=true;
  GBLpragFlags[Prglist]=true;
  GBLpragFlags[Prgobj]=true;
novalue
end;

macro Inittransput(dum) =
begin
  until Initchn(0) do Initprags();
  if .Chnstat(Latchn,TTYd) then
    begin
      external VersId;
```

PAGE 1-13

DSKB:A68S10.B10(L150AL68)@CMU-10A

3-Oct-77 02:48 30 blocks

```
Writemsg(Cmochn,Msg('?LRigol 68 '));
Cmdmsg(Nptrtochars(Versid));
end;
novalue
ends;

macro Fintransput(dum) =
begin
  do cr I from Hichn to 0 do
    if .Chnstat[I,Specd] then
      Close(I);
  novalue
ends;

external Rigol68;

Grootem=0;
repeat
  begin
    local Val;
    global GBLvars,GBLwarns,GBLprogstart,GBLpragflags;
    Initmem();
    ·Initprags();
    Inittransput();
    If (Val=Rigol68()) less 0 then Punt(-.Val);
    Fintransput();
  end;

  novalue
end
*udom
```

PAGE 1-1 DBKB:R68S11.B11(L150NL68)@CHU-10A 27-Sep-77 12:08 20 blocks

| R68S11.B11

|

| Copyright 1977 P. Hibbard and P. Kruveen
| Pittsburgh, Pennsylvania

module R68S11(START = Start, NODEBUG) =
begin

|

Rigel 68 Compiler Hydra Operating System Environment

| This module contains most of the routines which comprise the
| Hydra OSE for the Rigel 68 Compiler. The routine Start is the
| entry point for the Hydra load-and-go compiler system.

Compilation Initialization

| The following functions must be performed:

- Ascertain which output files are to be created. Perform any setup required to make subsequent output actions work correctly. Set \$Pragfl(Prglist) to true iff the listing file is to be written and \$Pragfl(Prgobj) to true iff the object file is to be written.
- Determine what text is to be used as the source input. Make any necessary connections to allow subsequent input actions to work correctly.
- Alter \$Pragfl to reflect any requests for pragmat-controlled actions.
- Do anything else necessary for particular system.
- Set Frooto and Froot1.

Source Input (\$SRCchar)

| The routine \$SRCchar returns the next character from the source input.
| If no more input exists it returns EOFchar. The characters must be
| encoded as 7-bit ASCII.

Listing Output (\$LSTline)

| \$LSTline outputs a single line of text to the listing device and possibly
| to the command output device as well. It takes three parameters, an
| N-pointer to the first character of the line, an N-pointer to the character
| immediately following the last character of the line, and an indication of
| whether the line should be sent to the command output device (0 implies do
| not send it).

Error Reporting (\$Errmsg)

| \$Errmsg(N) is called to output any text message associated with error
| number N.

Object Output (\$OBJword)

| \$OBJword is called to output a word of object code.

Compilation Finalization

|
switches nolists;
require KERKAL.REQ (N811HY97);

```
require CBCODE.REQ [N811HY97];
require STKPAG.REQ [N811HY97];
require RTSSTR.REQ [N811HY97];
require RTS .REQ [N811HY97];
require PHCALL.REQ [N810PH99];
require TTCALL.REQ [N810PH99];
```

```
require B11PRM.REQ;
require COMMON.REQ;
require IOMACS.REQ;
switches list;
```

undeclare

```
$Errmsg,
$LSLine,
$OBJword,
$SRCchar;
```

external

```
Closedev,
I0init,
Opendev,
Outasciz,
Outw,
Outcrlf,
Versid,
```

```
Glotag,
Sixcmd;
```

bind

```
FatHarderr = FatUser-0,
FatSignal = FatUser-1,
FatObjvfl = FatUser-2,
```

```
CM1chan = 0,
CM0chan = 1,
LPTchan = 2,
```

```
RPSdata1 = 4,
RPSdata2 = 5,
RPSdata3 = 6,
RPSid = 7,
```

```
LNSsix12 = 1,
LNSsyn = 2,
LNSuser = 3,
LNSport = 4, % Parameter %
LNSterm = 5, % Parameter %
LNSource = 6, % Parameter %
LNSoptions = 7, % Parameter %
LNSobject = 8, % Parameter %
LNSpagns = 13,
LNSprocdt1 = 16,
LNSprocdt2 = 17,
LNSprocdt3 = 18,
LNSerrmsg = 19,
```

PAGE 1-3

DSKB:R68511.B11(L150NL68)eCHU-10A 27-Sep-77 12:09 20 blocks

```
LNSdata1      = 31,  
LNSdata2      = 32,  
LNSdata3      = 33,  
LNStemp       = 34,  
  
CPSdata1      = 4,  
CPSdata2      = 5,  
CPSdata3      = 6,  
CPSerrmsg     = 7,  
CPSxseg       = 21,  
CPSyseg       = 22,  
CPSsource     = 23,  
  
IOpage        = #20000hRPS10;  
  
own  
Charvect CM0buf[88],  
Charvect LPTbuf[136],  
    Debcom      = 0,  
    IOcurpg     = 0,  
    IOInptr     = IOpage,  
    LSTchan     = CM0chan,  
    LSTcount    = 54,  
    LSTdev,  
Vector LSThead[17] = ASCII '  Rigol 68 on C.mmp    Page XXX',  
    LSTpgno     = 0,  
    SRCpage     = CPSsource;  
  
bind  
LSTheadpg     = LSThead+30;  
  
routine interrupt Herr =  
begin  
Outst('?G?G?G?G!ard Error at Compiler PC#'); Outoct(.OldPC); Eserr();  
Outst('  with ERRCODE#'); Outoct(.SERRCODE); Eserr();  
if .Debcom neq 0 then  
    Sixcmd(#1000);  
signal FatHarderr  
end;  
  
routine interrupt Hsig =  
begin  
local T;  
T-.R0;  
Outst('?G?GSignal #'); Outoct(.T<0,15>); Outst(' at Compiler PC#'); Outoct(.OldPC); Eserr();  
Outst('  with SIGDATA#'); Outoct(.SSIGDATA); Eserr();  
if .Debcom neq 0 then  
    Sixcmd(#1001);  
signal FatSignal  
end;  
  
routine IOload(CPSslot) =  
begin  
if .CPSslot neq .IOcurpg then
```

PAGE 1-4

DSKB:A68S11.B11(L150NL68)@CHU-10A

27-Sep-77 12:09 28 blocks

```
begin
  IOcurpg->.CPSslot;
  SRRLOAD(RPSlo,.CPSslot);
end;
novalue
end;

routine Punt(N) =
begin
  if .Debcom neq 0 then
    Sixcmd(#777);
  Outs('PUNTI '); Outdec(.N);
  Eolerr();
  novalue
end;

!
! Source Input
!

global routine $SRCchar =
begin
  local Val;
  if .IOinptr eqi IOpage+#20000 then      ! ???? This may lose if EOF occurs at boundary
    (SRCpage-.SRCpage+1; IOinptr=IOpage);
  IOload(.SRCpage);
  Val=scanN(IOinptr); incp(IOinptr);
  if .Val eqi 0 then
    if (Val=scanN(IOinptr)) neq 0
      then incp(IOinptr)
      else Val=EOFchar;
  .Val
end;

!
! Listing Output
!

global routine Reg0 $LSTline(First,Foll,Errdev) =
begin
  if .$Pragfl[Prglist] or .Errdev neq 0 then
    begin
      if (LSTcount-.LSTcount+1) gtr 54 then
        begin
          LSTcount+0;
          if .LSTchan neq CM0chan then
            begin
              Outasciz(.LSTchan,Msg('?L'));
              Outasciz(.LSTchan,Versid);
              Cvtdecz(LSTheadpg,LSTpgno-.LSTpgno+1,3);
              Outasciz(.LSTchan,LSThead);
              Outerr(.LSTchan);
              Outerr(.LSTchan);
            end;
        end;
    end;

```

```
        end;
    end;
Outm(.LSTchan,.First,.Foll);
Outcrit(.LSTchan);
if .LSTchan neq CM0chan and .Errdev neq 0 then
begin
Outm(CM0chan,.First,.Foll);
Outcrit(CM0chan);
end;
end;
novalue
end;

!
! Object Output
!

bind
Display      = #2000,
Tranvect     = #100000,
Xpage        = #120000,
Ypage        = #140000;

macro SelectX(dum) = IOload(CPSxseg) $;
macro SelectY(dum) = IOload(CPSyseg) $;

global routine Reg0 $OBJword(Loc,Dtype,Dvalue) =
begin
local Doffset;
bind Vector Basetable = upl1( 0, 0, 0, 0, Xpage, Ypage, Display, Tranvect );
if .Loc geq Ybase
then begin
Loc-.Loc-Ybase;
SelectY();
end
else begin
Loc-.Loc-Xbase;
SelectX();
end;
if .Loc geq #10000 then signal FatObjovf;
Doffset-(case .Dtype of
set
.Dvalue;
.Dvalue;
.Dvalue;
.Dvalue;
.Dvalue;
.Dvalue-Zadrinc - Xbase-Zadrinc;
.Dvalue-Zadrinc - Ybase-Zadrinc;
.Dvalue-Zadrinc;
.Dvalue-Zadrinc
tes);
IOpage(.Loc)-.Basetable(.Dtype) + .Doffset;
novalue
end;
```

PAGE 1-6

DSKB:R68S11.B11[L150ALBB]@CHU-10A

27-Sep-77 12:00 28 blocks

| Error Message Output

```
global routine RegD SErrmsg(N) =
begin
  external Errtxt;
  IOload(CPSerrmsg);
  if .Errtxt[.N] neq 0 then
    begin
      Outs(' - ');
      Outsz(.Errtxt[.N]);
    end;
  novalue
end;
```

| Initialization and Finalization

```
macro Initcusp(dum) =
begin
  local $StrCBERRORTRAPS TrapHandlers;
  local $Rights Restrict;
  TrapHandlers($ERRPC)~Herr;
  TrapHandlers($SIGPC)~Hsig;
  SSETLCB(0,TrapHandlers,SCBERRORTRAPS);
  SCOPY(LNSdata1,LNSprocd1,CPSdata1);
  SCOPY(LNSdata2,LNSprocd2,CPSdata2);
  SCOPY(LNSdata3,LNSprocd3,CPSdata3);
  SRRI.ORD(RPSdata1,CPSdata1);
  SRRI.ORD(RPSdata2,CPSdata2);
  SRRLOAD(RPSdata3,CPSdata3);
  SCPSLOAD<0,
    <CPSSxng,SPATH(LNSobject,1)>,
    <CPSSyng,SPATH(LNSobject,2)>};
  Restrict[SAuxRTS]~not $HritePageRTS;
  Restrict[SGenericRTS]~-1;
  incr I from 1 to SCLENGTH(LNSource) do
    begin
      SCETCAPR(LNRTemp,SPATH(LNSource,.I));
      SPUTCAPR(LNStamp,LNTemp,Restrict);
      SCPSLOAD<0, <CPSSource-I+.I,LNStamp>};
      SDELETE(LNStamp);
    end;
  novalue
ends;
```

```
macro Initmem(dum) =
begin
  exact global='FREE.G';
  global Freearea;
  bind Freeend = 10page;
  $Freehi=Freearea;
  $Freehi=Freeend;
```

PAGE 1-7

DSKB:ABBS11.B11(L150AL68)@CHU-10A 27-Sep-77 12:09 20 blocks

```
novalue
endS;

routine Dosswitches =
begin
stacklocal Lng;
Lang=SDLENGTH(LNOptions);
Incr I from 2 to .Lang do
begin
stacklocal Sw;
SGETDATA(Sw,LNOptions,.I,1);
If I less .Sw and .Sw less 17 then
case .Sw of
    set
        ;
        % DEBUG %      Dobcom-nonzad;
        % GHOST %      SPragfl(Prgnoghost)=false;
        % LISTING %    SPragfl(Prglist)=true;
        % LOWER %      SPragfl(Prgstrop)=3;
        % MACH %       SPragfl(Prgmach)=true;
        % NAKED %      SPragfl(Prgnonakd)=false;
        % NODERUG %    Dobcom-nonzad;
        % NOGHOST %    SPragfl(Prgnoghost)=true;
        % NOLISTING %  SPragfl(Prglist)=false;
        % NOMACH %     SPragfl(Prgmach)=false;
        % NONAKED %    SPragfl(Prgnonakd)=true;
        % NOWARNINGS % SPragfl(Prgwarn)=false;
        % POINT %      SPragfl(Prgstrop)=1;
        % RES %        SPragfl(Prgstrop)=0;
        % UPPER %      SPragfl(Prgstrop)=2;
        % WARNINGS %   SPragfl(Prgwarn)=true
    tes;
end;
novalue
endS;

macro Initprags(dum) =
begin
SPragfl=0;
SPragfl(Prgstrop)=1;
SPragfl(Prgwarn)=true;
SPragfl(Prgobj)=true;
SPragfl(Prglist)=true;
Dosswitches();
novalue
endS;

routine Inittransput =
begin
IOInit(LNSTdev);
Opendev(CHDchan,CHDbuf[0],80,3);
SGETDATA(LSTdev,LNOptions,1,1);
If .LSTdev eqi 0
    then SPragfl(Prglist)=false
elif .LSTdev eqi 2
    then begin
        Opendev(LPTchan,LPTbuf[0],136,6);
    end;
```

PAGE 1-8

DSKB:R68S11.B11[L150AL68]eCHU-10A

27-Sep-77 12:09 28 blocks

```
LSTchan=LPTchan;
end;
Outsciz(CH0chan,Versid);
Outsciz(CMOchan,Msg(" Compiler Starting"));
Outerif(CMOchan);
novalue
end;

routine Fintransput =
begin
  if .LSTchan eq1 LPTchan then
    Closedev(LPTchan);
  Closedev(CMOchan);
  novalue
end;

routine R68 =
begin
  local Val;
  external Algo168;
  Initcusp();
  Initmem();
  Initprags();
  Inittransput();
  if .Dobcom neq 0
    then Sixcmd(0)
    else Glogar-1;
  if (Val-Algo168()) eq1 0
    then Val-Zadrincc.SProgat+Ypage
    else begin
      if .Val iss 0 then Punt(-.Val);
      Val-0;
    end;
  SPUTDATA(LN$object,Val,1,1);
  Fintransput();
  SBREAK(LN$term);
  .Val
end;

routine Start =
begin
  external Init612,Ret612;
  csect global='GLOB.C';
  global $Errs,$Freehi,$Freeeo,$Pragfl,$Progat,$Warns;
  Init612(LN$port,0,0,1,1);
  Ret612(R68(),0,0)
end;
end
eludon
```

PAGE 1-1

DSKB:MDSTRC.REQ(L150AL68) eCHU-10A

19-Jul-77 05:33 18 blocks

! MDSTRC.REQ

!

! Copyright 1977 P. Hibbard and P. Knuoven
! Pittsburgh, Pennsylvania

! required by: CODE, CODESU, DBDEB1, LEXAN, SEMR8, SEMR2, SEMR4, SEMRSU, SRTABS

! Definitions associated with modes.

macro

```
Mode = 0block $,  
XMode = 1 $,  
  
Mdv      = 1,Wordf $,  
MdIO     = 1,RH $,  
Mdseen   = 1,Qwordsize-8,1 $,  
Mddone   = 1,Qwordsize-7,1 $,  
Mdopproc = 1,Qwordsize-6,1 $,  
Mdspecial = 1,Qwordsize-5,1 $,  
Mdrecur   = 1,Qwordsize-4,1 $,  
Mdaddressed = 1,Qwordsize-3,1 $,  
Mdlo     = 1,Qwordsize-2,1 $,  
Mdpile   = 1,Qwordsize-1,1 $,  
  
Mdprofmd = 2,Wordf $,  
  
Mdundisp = 2,Wordf $,  
  
Mdunocnt = 2,Wordf $,  
Mdunond(n) = 3+(n),Wordf $,  
  
Mdprerow = Mdprofmd $,  
Mdprecont = 3,Wordf $,  
Mdpreprms = 4,Wordf $,  
Mdpreprm(n) = 4+(n),Wordf $,  
  
Mdrlenmd = Mdprofmd $,  
  
Mddevtmd = Mdprofmd $,  
  
Mdrownd = 2,Wordf $,  
Mdrowncnt = 3,Wordf $,  
  
MdstrSDB = 2,Wordf $,  
Mdstrlen = 3,Wordf $,  
Mdstrcnt = 4,Wordf $,  
Mdstrfids = 5,Wordf $,  
Mdstrfmd(n) = 5+2*(n),Wordf $,  
Mdstrflex(n) = 6+2*(n),Wordf $;
```

! Definitions of Mdv values for modes.

```
macro Mdval(uniq,pi,dres,spc,lo) =  
    (pi)↑(Qwordsize-1) + (lo)↑(Qwordsize-2) + (dres)↑(Qwordsize-3)  
    + (spc)↑(Qwordsize-5) + (uniq) $;
```

PAGE 1-2

DSKB:MDSTRC.REQ(L150ALG8) eCMU-10A 19-Jul-77 05:33 18 blocks

bind

```
Pile = 1, Simple = 0,  
Dressed = 1, Undressed = 0,  
Special = 1,  
Io = 1, Nolo = 0,
```

```
Doproc = 1†(Qwrdsize-8);
```

bind Constby

Mdvint	= Mdvvall(0, Simple, 0 , 0 , Io);
Mdvlint	= Mdvvall(1, Pile , Undressed, Special, Io);
Mdvreal	= Mdvvall(2, Pile , Undressed, Special, Io);
Mdvireal	= Mdvvall(3, Pile , Undressed, 0 , Io);
Mdvchar	= Mdvvall(4, Simple, 0 , 0 , Io);
Mdvbits	= Mdvvall(5, Simple, 0 , 0 , Io);
Mdvbytes	= Mdvvall(6, Simple, 0 , 0 , Nolo);
Mdvstring	= Mdvvall(7, Pile , Dressed , 0 , Io);
Mdvbool	= Mdvvall(8, Simple, 0 , 0 , Io);
Mdvvoid	= Mdvvall(9, 0 , 0 , 0 , Nolo);
Mdvskip	= Mdvvall(10, 0 , 0 , 0 , Nolo);
Mdvjump	= Mdvvall(11, 0 , 0 , 0 , Nolo);
Mdvnil	= Mdvvall(12, 0 , 0 , 0 , Nolo);
Mdvout	= Mdvvall(13, Pile , Dressed , 0 , 0);
Mdvin	= Mdvvall(14, Pile , Dressed , 0 , 0);
Mdvoutb	= Mdvvall(15, Pile , Dressed , 0 , 0);
Mdvinb	= Mdvvall(16, Pile , Dressed , 0 , 0);
Mdvnumber	= Mdvvall(17, Pile , Dressed , 0 , 0);
Mdvrows	= Mdvvall(18, Pile , Dressed , 0 , 0);
Mdvunionof	= Mdvvall(19, Pile , Dressed , 0 , 0);
Mdvbinds	= Mdvvall(20, Simple, 0 , 0 , Nolo);
Mdvabsent	= Mdvvall(21, Simple, 0 , 0 , 0);
Mdvproc	= Mdvvall(22, Pile , Dressed , 0 , Nolo);
Mdvref	= Mdvvall(23, Pile , Dressed , 0 , Nolo);
Mdvstruct	= Mdvvall(24, Pile , Undressed, 0 , Nolo);
Mdvrow	= Mdvvall(25, Pile , 0 , 0 , Nolo);
Mdvevent	= Mdvvall(26, Pile , Dressed , 0 , Nolo);
Mdvcode	= Mdvvall(27, Simple, 0 , 0 , Nolo);
Mdvnewsimple	= Mdvvall(28, Simple, 0 , 0 , Nolo);
Mdvnewpile	= Mdvvall(29, Pile , Dressed , 0 , Nolo);

Macro

Callmode(M)	= (Tnonplain(M) eqi 1) \$,
Codemode(M)	= (M(MdID) eqi Mdvcode(MdID)) \$,
Eventmode(M)	= (M(MdID) eqi Mdvevent(MdID)) \$,
Hipmode(M)	= (Thip(M) gtr 0) \$,
Intrealmode(M)	= (M(MdID) leq Mdvireal(MdID)) \$,
Neumode(M)	= (M(MdID) gtr Mdvcode(MdID)) \$,
Procmode(M)	= (M(MdID) eqi Mdvproc(MdID)) \$,
Refmode(M)	= (M(MdID) eqi Mdvref(MdID)) \$,
Roundmode(M)	= (M(MdID) eqi Mdvrou(MdID)) \$,
Structmode(M)	= (M(MdID) eqi Mdvstruct(MdID)) \$,
Undefinedmode(M)	= (M(MdID) eqi Mdvabsent(MdID)) \$,
Unionofmode(M)	= (M(MdID) eqi Mdvunionof(MdID)) \$,
Unitedmode(M)	= (Tunited(M) gtr 0) \$,
Widenable(M)	= (M(MdID) leq Mdvstring(MdID)) \$,
Widenatoron(M)	= (M(MdID) geq Mdvbits(MdID)) \$,

! Valid only if Widenable(M) is true

PAGE 1-3

DSKB:MDSTRC.REQ(L150NL68)@CMU-10A 19-Jul-77 05:33 10 blocks

```
SameSize(X1,X2) = ((X1) eqv (X2)) $;

external
  Reg0  ValueLength,
        Reg0  Tarith,
        Reg0  Tchars,
        Reg0  Thip,
        Reg0  Tsize,
        Reg0  Tnonplain,
        Reg0  Tunitd,
        Tunion,
        Reg0  TXsize;

bind
  Xint    = 1,
  Xlnt    = 2,
  Xreal   = 3,
  Xlreal  = 4,
  Xcompl = 5,
  Xlcompl= 6,
  Xmaxsizint = 2,
  Xmaxsizreal = 4,
  Xchar   = 1,
  Xstring = 2,
  Xchars  = (Xchar*2 + Xchar) -2,
  Xskip   = 1,
  Xjump   = 2,
  Xnihil  = 3,
  Xout    = 1,
  Xin     = 2,
  Xoutb  = 3,
  Xinb   = 4,
  Xnumber = 5,
  Xrows   = 6;

! END OF MDSTRC.REQ
```

! LEXAN.BLI

!

! Copyright 1977

P. Hibbard and P. Knuoven
Pittsburgh, Pennsylvania

module Lexan =
begin

!

Lexical Analyzer

! The lexical analyzer converts a stream of characters into a stream of
! lexemes representing tokens of the ALGOL 68S language. The stream of
! characters is the source program and is supplied one character at a time
! by the system-dependant routine OSGetchar. The next lexeme of the program
! is obtained from the analyzer by a call on LxScan. A description of
! the format and possible values of lexemes may be found in LXSTRC.REQ.

! A more specific list of the functions performed by the lexical
! analyzer is the following:

- Recognize tokens in the current stropping convention
- Construct lexemes
- Output program listing
- Ignore comments
- Process pragmatics

! A source program may be represented in any of four
stropping conventions. The current default is the POINT convention
in which bold tokens (i.e. bold-tags and symbols represented
by bold character sequences) are indicated by a prefix strop
character. This strop character may be either a point (.) or an
apostrophe (''). The other conventions available are UPPER, LOWER and
RES. The use of the strop character is permitted in all of these.
The occurrence of a strop followed by an alphabetic character
always forces the following alphanumeric sequence to be bold.

! The UPPER convention uses upper case letters to indicate bold
letters, while LOWER convention uses lower case letters. A strop
may be used to override this as described above.

! In RES convention, typographical display features may no longer
appear between the marks of a tag or the symbols of a denotation.
A sequence of alphanumeric characters surrounded by disjunctors
(non-alphanumeric characters or typographical display features)
represents a bold symbol, if one exists with that particular
spelling; otherwise it represents a tag.
In RES stropping the first occurrence of a user-introduced
bold-tag must be explicitly stropped.

! Known Nonconformance with the Hansen-Boos Report

- There is no intimidation character. In particular, there is no
representation of the worthy character underscore.
- Upper and lower case letters may be intermixed following a strop
in UPPER (and LOWER); thus, .Begin is always allowed.
- PAGE pragmat-item is not implemented.

| - Apostrophe-image symbol is not implemented.
| - The RCS convention is different. It probably does
| not even conform to the Report because of the restriction on the
| use of typographical display features. Also, applied occurrences
| of bold-tags are reserved.
| - \$ is permitted as the first character of a tag.
|

```
switches nolist;
    require SYSPRH.REQ;
    require COMMONI.REQ;
    require IOMACS.REQ;
    require LISPHG.REQ;
    require ERRCOH.REQ;
    require ERRLEK.REQ;
    require LXTABS.REQ;
    require LXSTRC.REQ;
    require MDSTRC.REQ;
    require LXVCOM.REQ;
    require LXVSY.REQ;
    require LXTABL.REQ;
    require MDTABL.REQ;
switches list;

external
    Errchar,
    Errlptr,
    Errnonblank,
    Errptr,
    Lineno,
    Pblock Faptr;           ! Pointer to first location in freearea

forward
    InitLx,                 % global %
    RegR Lxerr,
    Outsrc,
    Nextch,
    RegR Nextch,
    RegR Scanch,
    TlastABC,
    Tbold,
    ! Tbreak,
    Putchr,
    Putcvt,
    Uppercase,
    Hashin,                 % global %
    Doprag,
    Lxscan,                 % global %
    Lx,
    Errorchar,
    Getprimden,
    Getstrgden,
    RegD Scantax,
    Hashbold,
    Gottax,
    Gotbold,
    Endoffile,
```

PAGE 1-3

DSKB:LEXAN.RL11150ALG810CHU-10A

13-May-77 20:29 35 blocks

```
Getoprj;

own
    Char,
    Charvect Errbuf(Cbufsize),
    Index,
    Inpragment,
    Longment,
    Lookahead,
    Charvect Srcbuf(Cbufsize),
    Srcptr,
    Scratch,
    Syment,
    Symptr,
    Bitvect Type;

macro
    Srcstat = Srcbuf(8) $;           | Nptr

bind
    Srcline = Srcbuf(Iptrndx(2)),      | Iptr
    Srctext = Srcbuf(Iptrndx(3)),      | Iptr
    Srcend = Srcbuf(Iptrndx(Cbufsize+1)), | Iptr
    Errtext = Errbuf(Iptrndx(8));      | Iptr

comment ! InitLx
!
! Functions: Perform per-compilation initialization required by
! the Lexical Analyzer.
!
global routine InitLx =
begin
    local Ptr;
    Index=Control;
    Inpragment=zed;
    Lookahead=0;
    Longment=0;

    Ptr=Iptrtochars(Errbuf);
    until .Ptr eqi Errtext do replace(Ptr," ");
    Errptr=Errixptr^.Ptr;
    Errchar=" ";
    Errnonblank=zed;

    Ptr=Iptrtochars(Srcbuf);
    replace(Ptr,";");
    until .Ptr eqi Srctext do replace(Ptr," ");
    Srcptr^.Ptr;

    Lineno=1;
    Zerocor(HT,HTsize);
    Faptr=Lextab<0,0>;
    until .Faptr(Link) eqi Minus1(Link) do
        begin
            if .Faptr(Lxv) eqi Lxvtag then
                Faptr(Lxp)=0;
```

PAGE 1-4 OSKB:LEXAN.RLI(L150NL68)eCHU-10A 13-May-77 20:29 35 blocks

```
Hashin();
  end;
novalue
end;

comment ! Lxerr(N)
!
! Functions: Print error message unless currently processing inside
! a pragmatt.
!
! Value: The Error lexeme.
!
! Inputs
!   N           - Error code
!   Inpragmatt - nonzero iff scanning pragmatt
!
routine Rng0 Lxerr(N) =
begin
  if .Inpragmatt eqi 0 then
    Error(.N);
  Lexerror;
end;

comment ! Outsrc
!
! Functions: Output a line of source listing on the listing device.
! If an error occurred in the line or the line was ignored due to a
! previous error, then a line of error indication is also output.
! If an error occurred in the line, then Errdev will be nonzero and thus
! all output will go to the error device also.
!
routine Outsrc =
begin
  Cvtdec(Sectline,.Lineno,3);
  Lineno-.Lineno;
  Sreptr->toNptr(.Sreptr);
  Incp(Sreptr);
  OSEListLine(Nptrtochars(Srcbuf),.Sreptr,.Errdev);
  Sreptr->SrcText;
  if .Errnonblank neq 0 then
    begin
      Errptr->toNptr(.Errptr);
      Incp(Errptr);
      OSEListLine(Nptrtochars(Errbuf),.Errptr,.Errdev);
      if .Errchar eqi " " then
        Errnonblank=zed;
      Errdev=zed;
    end;
  Errptr->Err1xptr+Errtext;
  Srcstate-.Srcstate;
  novalue
end;

comment ! Newch
```

PAGE 1-5 DSK:B:LEXAN.BLI(L150NLG8)@CHU-10A 13-May-77 20:29 35 blocks

```
!
! Function: Get a non-control character from the input stream.
!

routine Nouch =
begin
local C;
do C:=OSEsrcchar() until .Chartypol(C) neq Cctrl;
.C
end;

bind
Skipnone = EOL,
SkipEOL = Space,
Skipspaces = Errch,
Skipinprag = Letter;

comment ! Nextchr(Level) and Scanchr(Level)
!
! Functions: Get the next acceptable character from the source input.
! Level is used to indicate which characters are acceptable. Nextchr
! always uses a new input character as the first character to consider;
! Scanchr starts with the current character.
!
! Outputs
! Char - the current input character
! Type - character type of current input character
! Index - index of character class of current input character
!

routine RegD Nextchr(Level) =
begin
do begin
if .Index eqi EOL then Outsrc();
if .Lookahead neq 0
then (Char=.Lookahead; Lookahead=0)
else Char=Nouch();
Type=.Chartypol(.Char);
Index=.Type[Tpindex];
if .Index eqi EOF
then (if .Srcptr neq SrcText then Outsrc())
elseif .Index grt EOL
then begin
if .Index eqi Point then
if (Lookahead=Nouch()) neq "A" then
begin
Type=Ctstop;
Index=Stop;
end;
if .Srcptr eqi Scond then Outsrc();
replace1(Srcptr,.Char);
replace1(Erptr,.Errchar);
end;
end
while .Index lss .Level;
novalue
end;
```

PAGE 1-6

DSK:BLLEXAN.BLI(L150AL68)@CHU-10A

13-May-77 20:29 35 blocks

```
routine Ray0 ScanCh(Level) =
begin
  if .Index <= .Level then Nextch(.Level);
  novalue
  end;

comment ! Tdigit,Tletter,Tupper,Tlower,Tdigher,Tdigpor,
! Thexit,TletterR,Tpow10,TletABC,Tbold,
! Tbreak(Bold)

! Values: true if the current character is --
! (Tdigit) a digit
! (Tletter) a letter
! (Tupper) an upper case letter
! (Tlower) a lower case letter
! (Tdigher) a digit or letter
! (Tdigpor) a digit or upper case letter
! (Tdigwar) a digit or lower case letter
! (Thexit) a hexadecimal digit
! (TletterR) a letter R
! (Tpowl0) a power of ten choice
! (TletABC) a non-bold letter symbol
! (Tbold) a possible first character of bold tag
! (Tbreak) not allowed in tag or bold-tag
!

macro
  Tdigit(dum) = (.Type(Tpdigit)) $,
  Tletter(dum) = (.Type(Tpletter) neq 0) $,
  Tupper(dum) = (.Type(Tpupper)) $,
  Tlower(dum) = (.Type(Tplower)) $,
  Tdigher(dum) = (.Type(Tpdigher) neq 0) $,
  Tdigpor(dum) = (.Type(Tpdigpor) neq 0) $,
  Tdigwar(dum) = ((.Type and Tpdighor) neq 0) $,
  Thexit(dum) = (.Type(Tphexit) and (TletABC() or Tdigit())) $,
  TletterR(dum) = (TletABC() and Uppercase() eqi "R") $,
  Tpow10(dum) = (.Char eqi "/" or
                  (TletABC() and Uppercase() eqi "E")) $;

routine TletABC =
  case .GBLpragflags(Prgstrop) of
    set
      boot(Tletter());
      boot(Tletter());
      boot(Tlower());
      boot(Tupper());
    tes;

routine Tbold =
  if .Index eqi StrOp
  then true
  else case .GBLpragflags(Prgstrop) of
    set
      % RES % boot(Tletter());
      % STROP % false;
      % UPPER % boot(Tupper());
```

PAGE 1-7

DSKB:LEXAN.BLI(L150NL68)@CHU-10A

13-May-77 20:29 35 blocks

```
% LOWER % bool(Tlower())
tes;

macro Tbreak(Bold) =
begin
case .GBLpragflags[Prgstrop] of
  set
    % RES % not Tdighter();
    % STROP % not Tdighter();
  ! % UPPER % If (Bold) neq 0 then not Tdigper() else not Tdiguer();
    % LOWER % If (Bold) neq 0 then not Tdiguer() else not Tdigper()
  tes
end$;

comment ! Putchr and Putcvt
!
! Function: Store character in Lexeme Table entry under construction
! at top of freearea. Update character count. Check if there is sufficient
! space left in freearea. Putcvt, in addition, first converts any
! lower case letter to the corresponding upper case letter.
!
! Inputs
! Symptr - Hptr to character string in new Lexeme Table entry
! Symcnt - count of characters in current symbol
! Outputs
! Symptr - updated after character is stored
! Symcnt - incremented by one
!
routine Putchr =
begin
if modulo(.Symcnt,0chhurd) eqi 0 then
  begin
  Storatost(.Symptr<Addrf>);
  (.Symptr)<Wordf>=0;
  end;
replaceN(Symptr,.Char);
incp(Symptr);
Symcnt=.Symcnt+1;
novalue
end;

routine Putcvt =
begin
Char=Uppercase();
Putchr();
novalue
end;

comment ! Uppercase
!
! Function: Compute the upper case equivalent of the current input character.
!
routine Uppercase =
  if Tlower() then .Char and (not #40) else .Char;
```

```
comment ! Hashin
!
! Function: Search Lexeme Table for lexeme sitting at start of freearea.
! If lexeme is already in table, then return pointer to this
! old lexeme. If it is not in the table and Noontor is not set and
! we are not inside a pragment, then enter the lexeme in the table
! and return a pointer to the new lexeme. If lexeme is not found and
! a new entry is not made then return zero.
!
global routine Hashin =
begin
local Total,Ptr;
Total=0;
Ptr=Nptrtochar(Faptr(Lxsym));
decr I from .Faptr(Lxcount)+Qchnurd-1 to 0 do
begin
Total+.Total+scanN(Ptr);
Incp(Ptr);
end;
Total+.Total and HTmask;
do Total-.Total-HTsize until .Total less 0;
Total+.Total+HTsize;
Noontor-.Noontor or .Inprgpragnt;
Find(HT[.Total],HTD(.Faptr(Lxcount)+1)};
ond;

comment ! Doprag(N)
!
! Function: Carry out the semantics of the pragmat specified by N.
!
macro Doprag(N) =
begin
case (N) of
set

    ! RES, POINT, UPPER, LOWER
    Newstrop+(N);
    Newstrop+(N);
    Newstrop+(N);
    Newstrop+(N);

    ! WARNINGS and NOWARNINGS
    GBLpragflags[Prglwarn]=true;
    GBLpragflags[Prglwarn]=false;

    ! LISTING and NOLISTING
    GBLpragflags[Prgllist]=true;
    GBLpragflags[Prgllist]=false;

    ! PAGE
    tes;
    novalue
    ond$;
```

```
comment ! LxScan
!
! Functions: Scan a token from the input and return its lexeme.
! A token consists of an optional fragment (pragmat or comment) followed
! by a symbol.
!
global routine LxScan =
begin
label L;
local Lexeme Lex;
while begin
  Sscratch" ";
  Lex=Lx();
  .Lex[Lxv] eqi 0
  end
do begin
  local Newstrop;
  Inpragmt=Sscratch.Lex(Lxp);
  Newstrop.GBLpragflage(Prgstrop);
  repeat begin
    local Lexeme Lex2;
    ScanCh(SkipInprag);
    Lex2=Lx();
    if .Lex2 neq Lexerror then
      if .Lex2 eqi Lexstop
        then (Error(ELx2); exitloop)
      elseif .Lex2 eqi .Lex
        then exitloop
      elseif .Lex2[Lxv] eqi Lxvprgitem and .Inpragmt eqi "P"
        then Doprags(Lex2[Lxp]);
    end;
    Inpragmt+zed;
    GBLpragflage(Prgstrop)+.Newstrop;
  end;
  L:select .Lex[Lxv] of
  next
    Lxvlong: exitL Longnent+.Longnent+1;
    Lxvshort: exitL Longnent+.Longnent-1;
    Atelse: Longnent+0
  then;
  .Lex
  end;
!
comment ! Lx
!
! Functions: Scan a symbol from the input.
!
! Values: Lexeme for the symbol.
!
routine Lx =
begin
local Pblock Lex;
bind LxRoute = upitl(
  0,           ! Control
  0,           ! EOL
```

PAGE 1-10

DSKB:LEXAN.RLI[L150AL68]@CHU-10A

13-May-77 20:28 35 blocks

```
0,                      ! Space
Errorchar,              ! Errch
Getprimden,              ! Digit
Getprimden,              ! Point
Getstrgden,              ! Quote
Getopr,                  ! Punct
Getopr,                  ! Plsmin
Gettax,                  ! Letter
Gettax,                  ! Dollar
Getbold,                 ! Strop
Endoffile,               ! EOF
Getopr );                ! Prag

do begin
    ScanCh(Skipspaces);
    ErrIptr^.Errptr;
    SyLent=0;
    Syntptr^.Nptrtochars(Faptr[Lxsym]);
    Lex^.LxRnnts^.Index))()
    end;
until .Lex neq Lexerror or .Infragment neq 0;
.Lex
end;

comment ! Errorchar
!
! Functions: Deal with situation where illegal character occurs in the source.
!
! Value: Error lexeme.
!
routine Errorchar = (Exerr(ELxG); Nextch(Skipnone); Lexerror);

comment ! Getprimden
!
! Functions: Scan a primitive denotation from the input.
!
! Value: Lexeme for the denotation.
!
routine Getprimden =
begin
    local State, Mode M;
    external Lengthn, Cvtb,Cvti,CvtII,Cvtr,CvtIR;
    bind Vector Cvtrtn = uplit(Cvtb,Cvti,CvtII,Cvtr,CvtIR);

    State=(if .Index eqi Point then 1 else 0);
repeat
begin
    Putcvt();
    Nextch(if .GBLprngflags(Prgstrop) eqi 0 then Skipnone else Skipspaces);
    case .State of
        set
            ! 0: scan digits
            if .Index eqi Point
            then State=1
            else IfLetterR()
        end
    end
end;
```

```
        then State=6
    elseif Tpow10()
        then (Char="E"; State=3)
    elseif not Tdigit()
        then (M=Mdint; exitloop);

    ! 1: fixed-point-numeral must follow point in fractional-part
    if Tdigit()
        then State=2
    else return Lxerr(ELx4); '


    ! 2: scan digits of fractional-part
    if Tpow10()
        then (Char="E"; State=3)
    elseif not Tdigit()
        then (M=Mdreal; exitloop);

    ! 3: check for plusminus in exponent-part
    if .Index eq1 PIsmin
        then State=4
    elseif Tdigit()
        then State=5
    else return Lxerr(ELx4);

    ! 4: fixed-point-numeral must follow plusminus
    if Tdigit()
        then State=5
    else return Lxerr(ELx4);

    ! 5: scan fixed-point-numeral in exponent-part
    if not Tdigit()
        then (M=Mdreal; exitloop);

    ! 6: digits must follow letter-r in bits-denotation
    if Thexit()
        then State=7
    else return Lxerr(ELx4);

    ! 7: scan digits in bits-denotation
    if not Thexit()
        then (M=Mdbits; exitloop)
    tso;
    end;
M=Length(.M,.Longsent);
replaceM(Symptr,0);
if (.Cvrltn(Tarith(.M)))() gtr 0 then return Lxerr(ELx4);
Faptr[Lxdannd]~.M;
Faptr[Lxv]~Lxvprindm;
Faptr[Lxp]~B;
Faptr[Lxcount]~ValueLength(.M)+1;
Faptr[Lxtoken]~TkDenot;
Hashin();
end;

comment ! Getstrgden
!
```

PAGE 1-12

DSKB:LEXAN.BLI(L150AL68)eCMU-10A

13-May-77 20:29 35 blocks

```
! Function: Scan a string denotation from the input.
!
! Value: Lexname for the string denotation.
!
routine Getstrgden =
begin
  external Cvtstrg;
  Symptr->Nptrtochar(Faptr(Lxstrgrop));
  repeat begin
    Srcatch-#S";
    Nextch(SkipEOL);
    if .Index eq1 EOF
      then return Lxerr(Elxi)
    elif .Index neq Quote
      then Putchr()
    else begin
      Srcatch-# ";
      Nextch(Skipnone);
      if .Index eq1 Quote
        then Putchr()
      else begin
        Scanch(Skipspaces);
        if .Index neq Quote
          then exitloop;
        end
      end
    end;
  end;
  Cvtstrg(.Syment);
  if .Syment eq1 1
    then (Syment-0; Faptr(Lxdennd)->Mdchar; Faptr(Lxdenrop)->Faptr(Lxstrgrop))
    else (Faptr(Lxdennd)->Mdstring; Faptr(Lxdenrop)->.Syment);
  Faptr(Lxv)->Lxvstrgden;
  Faptr(Lxp)->0;
  Faptr(Lxcount)->divide(.Syment+3#Chwrd-1, Chwrd);
  Faptr(Lxtoken)->TkDenot;
  Hashin();
end;

comment ! Scantax(Bold)
!
! Functions: Scan characters contained in a tag or bold-tag.
!
! Inputs
! Bold - nonzero iff scanning bold-tag
!
routine Rng0 Scantax(Bold) =
begin
  do begin
    Putcvt();
    Nextch(if .Bold neq 0 then Skipnone else Skipspaces);
    end
    until Tbreak(.Bold);
  Faptr(Lxp)->0;
  Faptr(Lxcount)->divide(.Syment+0#Chwrd-1, Chwrd);
  novalue
end;
```

```
comment ! Hashbold
!
! Functions: Scan a bold-tag from the input.
!
! Value: Lexeme for the bold-tag.
!
routine Hashbold =
begin
  Scantax(nonzad);
  Faptr[Lxv]~Lxvtab;
  Faptr[Lxtoken]~TkBold;
  Hashin()
end;

comment ! Gettax
!
! Function: Scan a TAX-symbol from the input. In RES convention the
! symbol scanned may be a TAB-symbol, otherwise it is a TAG-symbol.
!
! Value: Lexeme for the symbol.
!
routine Gettax =
begin
  if Tbold()
    then begin
      local Val;
      if .GBLpragflags[Prgstrop] eqi 0 then
        Nonerror=nonzad;
      if (Val=Hashbold()) neq 0 then
        return .Val;
    end
  else
    Scantax(zad);
  Faptr[Lxv]~Lxvtax;
  if .Inpragnont eqi "C"
    then Lexerror
  else begin
    Faptr[Lxtoken]=(if .Inpragnont eqi 0 then TkTag else TkPragitem);
    Hashin()
  end
end;

comment ! Getbold
!
! Functions: Scan a bold-tag from the input.
!
! Value: Lexeme for the bold-tag.
!
routine Getbold =
begin
  local Val,Savstrop;
  Nextch(Skipnone);
  if not Letter() then
```

PAGE 1-14

DSKB:LEXAN.BLI(L150AL68)@CMU-10A

13-May-77 20:29 35 blocks

```
        return Lxerr(ELx5);
Savstrop^.GBLprngflags[Prgstrop];
GBLprngflags[Prgstrop] := 1;
Val:=Hashbold();
GBLprngflags[Prgstrop]:=Savstrop;
.Val
end;

comment ! Endoffile
!
! Function: Return STOP lexeme to indicate source end-of-file has occurred.
!
routine Endoffile = return Lexstop;

comment ! Getopr
!
! Function: Scan an operator from the input.
!
! Value: Lexeme for the operator or Error lexeme.
!
routine Getopr =
begin
local Lxptr,S,OldS;
Lxptr:=Lexerror;
S:=0;
do begin
OldS:=S;
if .Char eqi .Opcthtable[S,0] then
begin
Nextch(Skipnone);
Lxptr^.Opcthtable[S,0]lex;
if .Opcthtable[S,0]next then S:=S+0tronsize;
end
else begin
S:=S+.Opcthtable[S,0]alt;
end;
until .S eqi .OldS;
if .Lxptr eqi Lexerror
then Lxerr(ELx3)
else Opixtable[Lxptr]<0,0>
end;

global routine Lxline =
begin
Scanch(Skipspaces);
novalue
end;

end
studom
```

PAGE 1-1

DSKB:SRTABS.BLI(L150ALD8)@CMU-10A

29-Sep-77 22:18 55 blocks

! SRTABS.BLI

!

! Copyright 1977 P. Hibbard and P. Kneeven
! Pittsburgh, Pennsylvania

module SRtabss
begin

!

Semantic Tables

This module defines the entries initially contained in the
Mode Table, Operator Table and Symbol Table.

Kernel call tables

in - ZX>Z ... Z<KZ
out - ZX>ZZ ... ZZ<KZ

Hydra tables (other than Kernel call)

in - XH>Z ... Z<HZ
out - XH>ZZ ... ZZ<HZ

switches nolist;

require SYSRHN.REQ;
require COMMON.REQ;
require LISPKG.REQ;
require LXVCON.REQ;
require LXVSY.REQ;
require LKPVAL.REQ;
require EMIT.REQ;
require MDSTRC.REQ;
require STSTRC.REQ;
require OPSTRC.REQ;
require LXTRABL.REQ;

switches /list;

macro

empty = 0:0 \$,

Defstdid(offset,md,ix) =
0, Qadrincuplit(0, ix), 0, Hfwords(Stbtype(Stdidty,Stbdefid), 0),
(offset + ZRsizeBbase + ZRsizeLDBbase + 1), 0, md \$,

Defstopri(prio,std,ix) =
0, Qadrincuplit(0,ix), 0, Hfwords(Stbtype(0,Stbdelprio),0),
std, 0, prio \$,

Defstopr2(prio,std) =
0, 0, 0, Hfwords(Stbtype(0,Stbdelprio),0),
std, 0, prio \$,

Defdonint(val) =
Lexm(Lxvprindon, val), Hfwords(2,TkDonot), Mdint, val \$,

Deftag(len,str) =
Lexm(Lxvtag, 0), Hfwords((len+Qchwd-1)/Qchwd, TkTag), str \$,

Defbold(iv,lp,len,str) =

PAGE 1-2

DSKB:SRTABS.BL1(L150NL68)@CHU-10A

29-Sep-77 22:10 55 blocks

```
8, Lexn(lv,lp), Hfwords((len+Qchswrd-1)/Qchswrd, TkBold), str $,
Defpragitem(lp,len,str) =
 8, Lexn(Lxvpriitem,lp), Hfwords((len+Qchswrd-1)/Qchswrd, TkPragitem), str $,
Defopr(len,str) =
  Lexn(Lxvopr,0), Hfwords((len+Qchswrd-1)/Qchswrd, TkBold), str $,
Defcode0(yield) = Mdvcode+Doproc, yield, 0 $,
Defcode1(p1,yield) = Mdvcode, yield, 1, p1 $,
Defcode2(p1,p2,yield) = Mdvcode, yield, 2, p1, p2 $,
Defproc0(yield) = Mdvproc+Doproc, yield, 0 $,
Defproc1(p1,yield) = Mdvproc, yield, 1, p1 $,
Defproc2(p1,p2,yield) = Mdvproc, yield, 2, p1, p2 $,
Defproc3(p1,p2,p3,yield) = Mdvproc, yield, 3, p1, p2, p3 $,
Defproc4(p1,p2,p3,p4,yield) = Mdvproc, yield, 4, p1, p2, p3, p4 $,
Defproc6(p1,p2,p3,p4,p5,p6,yield) = Mdvproc, yield, 6, p1, p2, p3, p4, p5, p6 $,
Defref(md) = Mdvref, md $,
Defrow(md,rent) = Mdvrow, md, rent $,
Defunion2(m1,m2) = Mdvunionof, 2, m1, m2 $,
Defstruct2(m1,l1,m2,l2) = Mdvstruct, 0, 0, 2, m1,l1, m2,l2 $,
Defstruct4(m1,l1,m2,l2,m3,l3,m4,l4) = Mdvstruct, 0, 0, 4, m1,l1, m2,l2, m3,l3, m4,l4 $;
bind dummy = 8;

dataarea(MdnD)
  gblname(Mdint,          Mdvint),
  gblname(Mdilint,         Mdvilint),
  gblname(Mdbits,          Mdvbits),
  gblname(Mdbytes,         Mdvbytes),
  gblname(Mdreal,          Mdvreal),
  gblname(Mdireal,         Mdvireal),
  gblname(Mdbool,          Mdvbool),
  gblname(Mdchan,           Mdvnewsimple),
  gblname(Mdchar,           Mdvchar),
  gblname(Mdstring,         Mdvstring),
  gblname(Mdfile,            Mdvnewsimple),
  gblname(Mdnone,            Mdvnewsimple),
  gblname(Mdvoid,             Mdvvoid),
  gblname(Mdakip,            Mdvakip),
  gblname(Mdjum,              Mdvjump),
  gblname(Mdnii,              Mdvnil),
  gblname(Mdout,              Mdvout),
  gblname(Mdin,                Mdvin),
  gblname(Mdoutb,             Mdvoutb),
  gblname(Mdinh,               Mdvinb),
  gblname(Mdnumber,            Mdvnumber),
  gblname(Mdrown,              Mdvroun),
  gblname(Mdbnds,              Mdvbnis),
  gblname(Mdabsent,             Mdvabsent),
  gblname(Mdrout,              Mdvproc)

dataand;
dataarea(MdnI)
```

```

data(          0),
gblname(Mdcompl, Defstruct2(Mdreal,Lexra,Mdreal,Lexim)),
data(          0),
gblname(Mdcompl, Defstruct2(Mdreal,Lexra,Mdreal,Lexim)),
data(          0),
gblname(Rowbool, Defrow(Mdbool, 1)),
data(          0),
gblname(Rowchar, Defrow(Mdchar, 1)),
data(          0),
locname(Rowout, Defrow(Mdout, 1)),
data(          0),
locname(Rowin, Defrow(Mdin, 1)),
data(          0),
locname(Rownutb, Defrow(Mdnutb, 1)),
data(          0),
locname(Rowinb, Defrow(Mdinb, 1)),
data(          0),
gblname(Prcbndn, Defproc0(Mdbndn)),           ! Rowed mode indicant
data(          0),
locname(Prc2iv, Defproc2(Mdint,Mdint, Mvoid)),
data(          0),
locname(Rofint, Defref(Mdint)),
data(          0),
locname(Roffile, Defref(Mdfile)),
data(          0),
gblname(Rofstring, Defref(Mdstring))
dataend;

dataarr(Mdn2)
data(          0),
gblname(Prcrv, Defproc1(Roffile, Mvoid)),        ! Reset, Close, Scratch
data(          0),
locname(Prcbf, Defproc1(Roffile, Mdbool)),
data(          0),
locname(Prcllibb, Defproc3(Mdint,Mdint,Mdbits, Mdbool)),
data(          0),
locname(Codibtv, Defcode2(Mdint,Mdbits, Mvoid))
dataend;

dataarr(Mdn3)
data(          0),
locname(Prcreal, Defproc0(Mdreal)),                ! Random
data(          0),
locname(Prcrr, Defproc1(Mdreal, Mdreal)),           ! Sin, Cos, etc.
data(          0),
locname(Prcbtrb, Defproc1(Rowbool, Mdbits)),         ! Bits pack
data(          0),
locname(Prcbyst, Defproc1(Mdstring, Mbytes)),        ! Bytes pack
data(          0),
locname(Prcrfir, Defproc1(Rofint, Mdreal)),           ! Next random
data(          0),
locname(Prcif, Defproc1(Roffile, Mdint)),             ! Char number, etc.
data(          0),
locname(Prcchi, Defproc1(Roffile, Mdchan)),           ! Chan
data(          0),
locname(Prevout, Defproc1(Rowout, Mvoid)),            ! Print, Write
data(          0),

```

PAGE 1-4

DSKB:SRTABS.BL1(L150NL68)@CMU-10A 29-Sep-77 22:10 55 blocks

locname(Previn,	Defproc1(Rowin, Mdvoid)),	! Read
data(0),	
locname(Prevob,	Defproc1(Rowoutb, Mdvoid)),	! Write bin
data(0),	
locname(Previb,	Defproc1(Rowinb, Mdvoid)),	! Read bin
data(0),	
locname(Prevfout,	Defproc2(Roffile,Rowout, Mdvoid)),	! Put
data(0),	
locname(Prevfin,	Defproc2(Roffile,Rowin, Mdvoid)),	! Get
data(0),	
locname(Prevfp,	Defproc2(Roffile,Rowoutb, Mdvoid)),	! Putbin
data(0),	
locname(Prevfg,	Defproc2(Roffile,Rowinb, Mdvoid)),	! Getbin
data(0),	
locname(Prevfts,	Defproc2(Roffile,Mdstring, Mdvoid)),	! Make term
data(0),	
locname(Prevrtts,	Defproc2(Roffile,Restring, Mdvoid)),	! Associate
data(0),	
locname(Prcon,	Defproc2(Roffile,Prbf, Mdvoid)),	! On routines
data(0),	
locname(Prcsn1),	Defproc2(Mdnumber,Mdint, Mdstring)),	! Whole
data(0),	
locname(Prcsn2),	Defproc3(Mdnumber,Mdint, Mdint, Mdstring)),	! Fixed
data(0),	
locname(Prcifsc,	Defproc3(Roffile,Mdstring,Mdchan, Mdint)),	! Open
data(0),	
locname(Prcsn3),	Defproc4(Mdnumber,Mdint,Mdint,Mdint, Mdstring)),	! Float
data(0),	
locname(Prcvt3),	Defproc4(Roffile,Mdint,Mdint,Mdint, Mdvoid)),	! Set
data(0),	
locname(Prcest,	Defproc6(Roffile,Mdstring,Mdchan,Mdint,Mdint, Mdint)),	! Establish
data(0),	
locname(Codcibtv,	Defcode0(Codcibtv)),	! Sys trace
data(0),	
locname(Codp2ivv,	Defcode1(Prc2iv, Mdvoid)),	! On tick
data(0),	
locname(Codp1bbv,	Defcode1(Prc1bb, Mdvoid)),	! On error
data(0),	
locname(Codc1btvv,	Defcode1(Codcibtv, Mdvoid)),	! On sys trace
data(0),	
locname(Codiv,	Defcode1(Mdint, Mdvoid))	! Warning level
dataends;		

ZH>%

dataarea(Hyd0)	
gblname(Mdtimel,	Mdvmemfile)
dataends;	
dataarea(Hyd1)	
data(
locname(Roffile,	Defret(Mdtimel))
dataends;	
dataarea(Hyd2)	
data(
locname(Codv,	Defcode0(Mdvoid)),

PAGE 1-5

DSKB:SRTAB.SBLI(L150AL68)@CHU-10A 29-Sep-77 22:10 55 blocks

```
data(          0),
  locname(Codrftv, Defcodel(Reftime, Mdvoid)),
data(          0),
  locname(Codtmrl, Defcodel(Mdtmrl, Mdreal))
dataand;
%<H%
```

ZK>%

```
dataarea(Ker0)
  gblname(Mdnslot, Mdvnonpile),
  gblname(Mdstep, Mdvnonimpl)
dataand;
```

```
dataarea(Ker1)
  data(          0),
  locname(Mdrtsmask, Defstruct4(Mdbits,Lexaux,Mdbits,Lexgen,Mdbool,Lexamp,Mdbool,Lextemp)),
  data(          0),
  locname(Rowint, Defrow(Mdint, 1)),
  data(          0),
  locname(Rowstep, Defrow(Mdstep, 1))
dataand;
```

```
dataarea(Ker2)
  data(          0),
  locname(Mdwalk, Defref(Rowstep))
dataand;
```

```
dataarea(Ker3)
  data(          0),
  locname(Mdpath, Defstruct2(Mdnslot,Lexs,Mdwalk,Lexu))
dataand;
```

```
dataarea(Ker4)
  locname(Mdalyparm, Defunion2(Mdpath,Mdnslot)),
  locname(Mdpnthslot, Defunion2(Mdpath,Mdnslot))
dataand;
```

```
dataarea(Ker5)
  data(          0),
  locname(Mdarylist, Defron(Mdalyparm, 1)),
  data(          0),
  locname(Prestep, Defproc0(Mdintep)),
  data(          0),
  locname(Prepsv, Defproc1(Mdpnthslot, Mdvoid)),
  data(          0),
  locname(Prepub, Defproc1(Mdpnthslot, Mdbool)),
  data(          0),
  locname(Prepsv, Defproc1(Mdpnthslot, Mdintep)),
  data(          0),
  locname(Prepsv, Defproc2(Mdnslot,Mdpnthslot, Mdvoid)),
  data(          0),
  locname(Prepub, Defproc2(Mdpnthslot,Mdnslot, Mdvoid)),
  data(          0),
  locname(Prepub, Defproc2(Mdpnthslot,Mdnslot, Mdbits)),
  data(          0),
  locname(Prebsv, Defproc2(Mdnslot,Mdbits, Mdvoid)),
```

PAGE 1-6

DSKB:SRTAB6.BLI(L150AL68)@CHU-10A 29-Sep-77 22:10 55 blocks

```
data(          0),
  locname(Prcpsrtv, Defproc2(Mdpathslot, Mdrtsmask, Mdvoid)),
  data(          0),
  locname(Prcpsrtv, Defproc3(Mdpathslot, Mdslot, Mdrtsmask, Mdvoid)),
  data(          0),
  locname(Prcpsarts, Defproc3(Mdpathslot, Mdslot, Mdrtsmask, Mdstep)),
  data(          0),
  locname(Prcsspsv, Defproc3(Mdslot, Mdslot, Mdpathslot, Mdvoid)),
  data(          0),
  locname(Code,   Defcode0(Mdslot)),
  data(          0),
  locname(Codist, Defcode1(Mdint, Mdstep)),
  data(          0),
  locname(Codriu, Defcode1(Rowint, Mduink)),
  data(          0),
  locname(Codisl, Defcode1(Mdint, Mdslot))
dataend;

dataarea(Ker6)
  data(          0),
  locname(Prcpsab, Defproc3(Mdslot, Mdpathslot, Mdarglist, Mdbits)),
  data(          0),
  locname(Prcprnah, Defproc4(Mdslot, Mdpathslot, Mduink, Mdarglist, Mdbits))
dataend;
%<K%
```

```
structure Imoda{I,P,S} = (.Imode=Quadrince(.I-1))<.P,.S>;
map Imoda
%H>%  Reftime:Codiv:Codrltv:Codtmrl: Z<K%
%K>%  Mduink:Rowint:Rowstep:Mdarglist:Mdpath:Mdrtsmask:
      Prcpsv:Prcpsrtv:Prcsspsv:Prcpsnah:
      Prcpsv:Prcpsrtv:Prcpsab:Prcpsarts:Prcps:Prcpsab:
      Prcpsb:Prcsv:Prcstep:Prcsspsv:
      Code:Codist:Codriu:Codis: Z<K%
      RefInt:RefFile:RefString:
      Rowhol:Rowchar:Rowout:Rowin:Rowoutb:Rowinb:
      Mdcompl:Mdcompl:
      Prebndn:Precon:Preerr:Prebtrb:Prei:bbs:
      Prelf:Prebf:Prechf:Prevob:Previb:Precon:Preanli:Prebyst:Preffir:
      Prevfl:Prevfrv:Prevout:Previni:Prevfout:Prevfrst:Prevfst:
      Prean2i:Prean3i:Preast:Prevfin:Previp:Previg:Preifsc:Pre2iv:
      Codibtv:Codp2ivv:Codpt:bbvt:Codeibtv:Codeibtvv:Codiv;
```

```
globlidata(Vector, Idata,
  RefL, RefInt[Link], RefFile[Link], RefString[Link],
%H>%  RefTime[Link], Z<K%
%K>%  Mduink[Link], Z<K%
  0,
  RowL, Rowhol[Link], Rowchar[Link], Rowout[Link], Rowin[Link],
  Rowoutb[Link], Rowinb[Link],
%K>%  Rowint[Link], Rowstep[Link], Mdarglist[Link], Z<K%
  0,
  StructL, Mdcompl[Link], Mdcompl[Link],
%K>%  Mdpath[Link], Mdrtsmask[Link], Z<K%
```

PAGE 1-7

DSKB:SRTABS.BLI[L150NL68]@CMU-10A 29-Sep-77 22:16 55 blocks

```
8,
ProcL, Prebndn[Link], Precreat[Link], Preerr[Link],
Prebtrb[Link], Preif[Link], Prebf[Link], Prechf[Link],
Prevf3i[Link], Prerfv[Link], Prevout[Link], Previn[Link],
Prevob[Link], Previb[Link], Prevfs[Link], Prevfrs[Link],
Prevfout[Link], Prevfin[Link], Prevfp[Link], Previg[Link],
Preon[Link], Presn1[Link], Presn2i[Link], Presn3i[Link],
Prcifsc[Link], Preest[Link], Prebyst[Link], Prcfir[Link],
Prc2iv[Link], Prcihb[Link],
ZK>ZK
Prespan1[Link], Prepav[Link], Presav[Link], Prepavr[Link],
Prepanv[Link], Prepartv[Link], Prepah[Link], Prepsarts[Link],
Prepas[Link], Prespanb[Link], Prepanb[Link], Presbv[Link],
Prestap[Link], Presspsv[Link], ZK<ZK
8,
CodeL, Codibtv[Link], Codeibtv[Link], Codp2ivv[Link], Codplibbv[Link],
Codeibtvv[Link], Codiv[Link],
ZH>Z
Codv[Link], Codrftv[Link], Codtmri[Link], ZK<Z
ZK>ZK
Code[Link], Codist[Link], Codriw[Link], Codist[Link], ZK<ZK
8,
EventL, 8,
8);
```

bind ! Indexes into the Xmodes table (see SEMR4.BLI)

```
Mint = 0, MInt = 1, Mreal = 2, Mireal = 3, Mcompl = 4, Micompl = 5,
Mchar = 6, Mstring = 7, Mbool = 8, Mbits = 9,
Msma = 10, Mvoid = 11;
```

bind

Obabs	= upl1(Hwords(Idmon, Pabsi), Hwords(Mint, Mint), Hwords(Idmon, Pabsi), Hwords(MInt, MInt), Hwords(Idmon, Pabsr), Hwords(Mreal, Mreal), Hwords(Idmon, Pabsir), Hwords(Mireal, Mireal), Hwords(Idmon, Pabsc), Hwords(Mcompl, Mreal), Hwords(Idmon, Pabsic), Hwords(Micompl, Mreal), Hwords(Idmon, Pabsb), Hwords(Mbool, Mint), Hwords(Idmon, Pabsbt), Hwords(Mbits, Mint), Hwords(Idmon, Pabsch), Hwords(Mchar, Mint), 8),
Oband	= upl1(Hwords(Idgen, Pandb), Mdbool, Mdbool, Mdbool, Hwords(Idgen, Pandbt), Mdbits, Mdbits, Mdbits, 8),
Obarg	= upl1(Hwords(Idmon, Parq), Hwords(Mcompl, Mreal), Hwords(Idmon, Parq), Hwords(Micompl, Mireal), 8),
Obbin	= upl1(Hwords(Idmon, Pbin), Hwords(Mint, Mbits), 8),
Obeonj	= upl1(Hwords(Idmon, Pconj), Hwords(Mcompl, Mcompl), Hwords(Idmon, Pconj), Hwords(Micompl, Micompl), 8),
Obdiv	= upl1(Hwords(IdIIR, Pdiv), Hwords(IdAAA, Pdiv), 8),
Obdown	= upl1(Hwords(Idmon, Pdownnm), Hwords(Msma, Mvoid), 8),

PAGE 1-8

DSKB:SRTABS.BL1(L150ALG8) eCHU-10A

29-Sep-77 22:18 55 blocks

Obdvab	= uplit(Hfwords(IdRAR, Pdiv), 8),
Obolem	= uplit(Hfwords(Idgen, Polmb), Mdbool, Mdbits,Mdint, Hfwords(Idgen, Polmby), Mdchar, Mdbutes,Mdint, 8),
Obanti	= uplit(Hfwords(Idmon, Penti), Hfwords(Mreal, Mint), Hfwords(Idmon, Pentii),Hfwords(Mireal, Miint), 8),
Oboq	= uplit(Hfwords(IdANNC, Peq), Hfwords(IdSSB, Peqcs), Hfwords(Idgen, Peqb), Mdbool, Mdbool,Mdbool, Hfwords(Idgen, Peqbt), Mdbool, Mdbits,Mdbits, Hfwords(Idgen, Peqby), Mdbool, Mdbutes,Mdbutes, 8),
Obyo	= uplit(Hfwords(IdANNC, Pyo), Hfwords(IdSSB, Pyocs), Hfwords(Idgen, Pyobt), Mdbool, Mdbits,Mdbits, Hfwords(Idgen, Pyoby), Mdbool, Mdbutes,Mdbutes, 8),
Obyt	= uplit(Hfwords(IdANNC, Pgt), Hfwords(IdSSB, Pgts), Hfwords(Idgen, Pgtby), Mdbool, Mdbutes,Mdbutes, 8),
Oble	= uplit(Hfwords(IdANNC, Ple), Hfwords(IdSSB, Plecs), Hfwords(Idgen, Plebt), Mdbool, Mdbits,Mdbits, Hfwords(Idgen, Pleby), Mdbool, Mdbutes,Mdbutes, 8),
Obleng	= uplit(Hfwords(Idmon, Plengi),Hfwords(Mint, Miint), Hfwords(Idmon, Plengr),Hfwords(Mreal, Mireal), Hfwords(Idmon, Plengc),Hfwords(Mcompl, Micompl), 8),
Oblevel	= uplit(Hfwords(Idmon, Plevint),Hfwords(Mint, Msena), Hfwords(Idmon, Plevsem),Hfwords(Msena, Mint), 8),
Obit	= uplit(Hfwords(IdANNC, Pit), Hfwords(IdSSB, Pitcs), Hfwords(Idgen, Pitby), Mdbool, Mdbutes,Mdbutes, 8),
Oblub	= uplit(Hfwords(IdIBR, Plubm), Mdabsent, Hfwords(IdIBR, Pluh), Mdint, Hfwords(Idmon, Plubustr), Hfwords(Mstring,Mint), 8),
Obndab	= uplit(Hfwords(IdIRI, Pmod), 8),
Obanab	= uplit(Hfwords(IdRAR, Psub), Hfwords(IdIRI, Psub), 8),
Obminus	= uplit(Hfwords(IdAAA, Psub), Hfwords(Idmon, Pnegi), Hfwords(Mint, Mint), Hfwords(Idmon, Pnegi),Hfwords(Miint, Miint), Hfwords(Idmon, Pnegr), Hfwords(Mreal, Mreal), Hfwords(Idmon, Pnegir),Hfwords(Mireal, Mireal), Hfwords(Idmon, Pnegc), Hfwords(Mcompl, Mcompl), Hfwords(Idmon, Pnegic),Hfwords(Micompl, Micompl), 8),
Obmod	= uplit(Hfwords(IdIII, Pmod),

Obno	= uplit(8), Hfwords(IdARRNC, Pno), Hfwords(IdSSB, Pnoes), Hfwords(Idgen, Pnob), Mdbool, Mdbool, Mdbool, Hfwords(Idgen, Pnobt), Mdbool, Mdbits, Mdbits, Hfwords(Idgen, Pnoby), Mdbool, Mdbutes, Mdbutes, 8),
Obnot	= uplit(Hfwords(Idmon, Pnotb), Hfwords(Mbool, Mbool), Hfwords(Idmon, Pnotbt), Hfwords(Mbits, Mbits), 8),
Obodd	= uplit(Hfwords(Idmon, Podd), Hfwords(Mint, Mbool), Hfwords(Idmon, Podd1), Hfwords(Mint, Mbool), 8),
Ober	= uplit(Hfwords(Idgen, Porb), Mdbool, Mdbool, Mdbool, Hfwords(Idgen, Porbt), Mdbits, Mdbits, Mdbits, 8),
Obovab	= uplit(Hfwords(IdIRI, Pavar), 8),
Obover	= uplit(Hfwords(IdIII, Pover), 8),
Obplab	= uplit(Hfwords(IdRAR, Padd), Hfwords(IdIRI, Padd), Hfwords(IdSCS, Pcats4), Mdstring, Hfwords(IdSCS, Pcat+3), Mdchar, 8),
Obplto	= uplit(Hfwords(IdCSS, Pplusdocs), 8),
Obplitm	= uplit(Hfwords(IdIIC, Pplitm), 8),
Obplus	= uplit(Hfwords(IdAAA, Padd), Hfwords(IdSSS, Pcat), Hfwords(Idmon, Pnoop), Hfwords(Mint, Mint), Hfwords(Idmon, Pnoop), Hfwords(Mint, Mint), Hfwords(Idmon, Pnoop), Hfwords(Mreal, Mreal), Hfwords(Idmon, Pnoop), Hfwords(Mreal, Mreal), Hfwords(Idmon, Pnoop), Hfwords(Mcompl, Mcompl), Hfwords(Idmon, Pnoop), Hfwords(Mcompl, Mcompl), 8),
Obopr	= uplit(Hfwords(Idmon, Prepr), Hfwords(Mint, Mchar), 8),
Obroun	= uplit(Hfwords(Idmon, Proun), Hfwords(Mreal, Mint), Hfwords(Idmon, Proun), Hfwords(Mreal, Mint), 8),
Obsh1	= uplit(Hfwords(Idgen, Psh1), Mdbits, Mdint, Mdbits, 8),
Obshr	= uplit(Hfwords(Idgen, Pshr), Mdbits, Mdint, Mdbits, 8),
Obshrt	= uplit(Hfwords(Idmon, Pshrt1), Hfwords(Mint, Mint), Hfwords(Idmon, Pshrt2), Hfwords(Mreal, Mreal), Hfwords(Idmon, Pshrtc), Hfwords(Mcompl, Mcompl), 8),
Obsign	= uplit(Hfwords(Idmon, Psign), Hfwords(Mint, Mint), Hfwords(Idmon, Psignl), Hfwords(Mint, Mint), Hfwords(Idmon, Psignr), Hfwords(Mreal, Mint), Hfwords(Idmon, Psignr), Hfwords(Mreal, Mint), 8),
Obtimes	= uplit(Hfwords(IdAAA, Pmul),

```

        Hfwords(Idgon, Pmullc), Mdstring, Mdchar,Mdint,
        Hfwords(Idgon, Pmulcl), Mdstring, Mdint,Mdchar,
        Hfwords(Idgon, Pmulis), Mdstring, Mdstring,Mdint,
        Hfwords(Idgon, Pmulsi), Mdstring, Mdint,Mdstring,
        8 ),
Obtnab = uplit( Hfwords(IdRAR, Pmul),
        Hfwords(IdIRI, Pmul),
        Hfwords(IdSCS, Pmulsi), Mdint,
        8 ),
Obup = uplit( Hfwords(Idmon, Pupsen),Hfwords(Nesema, Mvoid),
        8 ),
Obup1 = uplit( Hfwords(IdAIR, Pexp),
        8 ),
Obup2 = uplit( Hfwords(IdAIR, Pexp),
        8 ),
Obupb = uplit( Hfwords(IdIBR, Pupbn), Mdabsent,
        Hfwords(IdIBR, Pupb), Mdint,
        Hfwords(Idmon, Pupbnstr), Hfwords(Matring, Mint),
        8 );

```

datanrea(Syntab)

! Environment enquiries

```

data( Defstid( 0, Mdint, quoted Dofftag( 6, 'MAXINT'))),
data( Defstid( 1, Mdreal, quoted Dofftag( 7, 'MAXREAL'))),
data( Defstid( 2, Mdreal, quoted Dofftag( 9, 'SMALLREAL'))),
data( Defstid( 3, Mdint, quoted Dofftag(10, 'MAXRSCHAR'))),

```

! Operations associated with BITS values

```

data( Defstid( 4, Prcbtrb, quoted Dofftag( 8, 'BITSPACK'))),

```

! Operations associated with BYTES values

```

data( Defstid( 5, Prcbyt, quoted Dofftag( 9, 'BYTESPACK'))),

```

! Standard mathematical constants and functions

```

data( Defstid( 6, Mdreal, quoted Dofftag( 2, 'PI'))),
data( Defstid( 7, Prerr, quoted Dofftag( 4, 'SQRT'))),
data( Defstid( 8, Prerr, quoted Dofftag( 3, 'EXP'))),
data( Defstid( 9, Prerr, quoted Dofftag( 2, 'LN'))),
data( Defstid(10, Prerr, quoted Dofftag( 3, 'COS'))),
data( Defstid(11, Prerr, quoted Dofftag( 6, 'ARCCOS'))),
data( Defstid(12, Prerr, quoted Dofftag( 3, 'SIN'))),
data( Defstid(13, Prerr, quoted Dofftag( 6, 'ARCSIN'))),
data( Defstid(14, Prerr, quoted Dofftag( 3, 'TAN'))),
data( Defstid(15, Prerr, quoted Dofftag( 6, 'ARCTAN'))),
data( Defstid(16, Prerfir, quoted Dofftag(10, 'NEXTRANDOM'))),

```

! Channels

```

data( Defstid(17, Mdchan, quoted Dofftag(14, 'STANDINGCHANNEL'))),
data( Defstid(18, Mdchan, quoted Dofftag(15, 'STANDOUTCHANNEL'))),
data( Defstid(19, Mdchan, quoted Dofftag(16, 'STANDARDCHANNEL'))),

```

! Files and associated operations

```

data( Defstid(20, Prechf, quoted Dofftag( 4, 'CHAN'))),
data( Defstid(21, Prevts, quoted Dofftag( 8, 'MAKETERM'))),
data( Defstid(22, Preon, quoted Dofftag(16, 'DNLOGICALFILEEND'))),

```

```

data( Defstid(23, Prcon, quoted Doftag(17, 'ONPHYSICALFILEEND'))),
data( Defstid(24, Prcon, quoted Doftag( 9, 'ONPAGEEND'))),
data( Defstid(25, Prcon, quoted Doftag( 9, 'ONLINEEND'))),
data( Defstid(26, Prcest, quoted Doftag( 9, 'ESTABLISH'))),
data( Defstid(27, Prcifsc, quoted Doftag( 4, 'OPEN'))),
data( Defstid(28, Prcvfrs, quoted Doftag( 9, 'ASSOCIATE'))),
data( Defstid(29, Prcrvf, quoted Doftag( 5, 'CLOSE'))),
data( Defstid(30, Prcrvf, quoted Doftag( 7, 'SCRATCH'))),
data( Defstid(31, Prcif, quoted Doftag(10, 'CHARNUMBER'))),
data( Defstid(32, Prcif, quoted Doftag(10, 'LINENUMBER'))),
data( Defstid(33, Prcif, quoted Doftag(10, 'PAGENUMBER'))),
data( Defstid(34, Prcrvf, quoted Doftag( 5, 'SPACE'))),
data( Defstid(35, Prcrvf, quoted Doftag( 7, 'NEWLINE'))),
data( Defstid(36, Prcrvf, quoted Doftag( 7, 'NEWPAGE'))),
data( Defstid(37, Prevf31, quoted Doftag( 3, 'SET'))),
data( Defstid(38, Prcrvf, quoted Doftag( 5, 'RESET'))),

```

! Conversion routines

```

data( Defstid(39, Prcsn1i, quoted Doftag( 5, 'WHOLE'))),
data( Defstid(40, Prcsn2i, quoted Doftag( 5, 'FIXED'))),
data( Defstid(41, Prcsn3i, quoted Doftag( 5, 'FLOAT'))),

```

! Formatless transput

```

data( Defstid(42, Prevfout, quoted Doftag( 3, 'PUT'))),
data( Defstid(43, Prevfin, quoted Doftag( 3, 'GET'))),

```

! Binary transput

```

data( Defstid(44, Prcvfp, quoted Doftag( 6, 'PUTBIN'))),
data( Defstid(45, Prcvfg, quoted Doftag( 6, 'GETBIN'))),

```

! Particular prologue

```

data( Defstid(46, Rofint, quoted Doftag(10, 'LASTRANDON'))),
data( Defstid(47, Prcral, quoted Doftag( 6, 'RANDOM'))),
data( Defstid(48, Roffile, quoted Doftag( 7, 'STANDIN'))),
data( Defstid(49, Roffile, quoted Doftag( 8, 'STANDOUT'))),
data( Defstid(50, Roffile, quoted Doftag( 9, 'STANDRACK'))),
data( Defstid(51, Prcvout, quoted Doftag( 5, 'PRINT'))),
data( Defstid(51, Prevout, quoted Doftag( 5, 'WRITE'))),
data( Defstid(52, Prcvin, quoted Doftag( 4, 'READ'))),
data( Defstid(53, Prcvob, quoted Doftag( 8, 'WRITERIN'))),
data( Defstid(54, Previb, quoted Doftag( 7, 'READRIN'))),

data( Defstid(55, Cdp2ivv, quoted Doftag( 6, 'ONTICK'))),
data( Defstid(56, Cdpibbv, quoted Doftag( 7, 'ONERROR'))),
data( Defstid(57, Cdcibtvv, quoted Doftag(10, 'ONSYSTRACE'))),
data( Defstid(58, Cdcibtv, quoted Doftag( 8, 'SYSTRACE'))),
data( Defstid(59, Cadiv, quoted Doftag(12, 'WARNINGLEVEL'))),

```

ZH>Z

```

data( Defstid(60, Mdchan, quoted Doftag(13, 'CONSINCHANNEL'))),
data( Defstid(61, Mdchan, quoted Doftag(14, 'CONSOUTCHANNEL'))),
data( Defstid(62, Mdchan, quoted Doftag(16, 'FIXEDPAGECHANNEL'))),
data( Defstid(63, Mdchan, quoted Doftag(14, 'VARPAGECHANNEL'))),
data( Defstid(64, Codiv, quoted Doftag( 7, 'SUTRACE'))),
data( Defstid(65, Codrvf, quoted Doftag(11, 'GETPROCTIME'))),
data( Defstid(66, Codv, quoted Doftag(13, 'STARTPROCTIME'))),
data( Defstid(67, Codimrl, quoted Doftag( 6, 'MUSECS'))),
data( Defstid(68, Mdchan, quoted Doftag(14, 'SOSFILECHANNEL'))),

```

PAGE 1-12

DSKB:SRTABS.BLI(L150AL68)eCHU-10A 29-Sep-77 22:18 55 blocks

X<HZ

ZK>ZZ

```

data( Defstid(69, Prepsarts, quoted Doftag(11, '$APPENDCAPA'))),
data( Defstid(70, Prepsab, quoted Doftag( 5, '$CALL'))),
data( Defstid(71, Prepsa, quoted Doftag( 8, '$LENGTH'))),
data( Defstid(72, Prepsbb, quoted Doftag( 8, '$COMPARE'))),
data( Defstid(73, Prepsbv, quoted Doftag( 8, '$CONTROL'))),
data( Defstid(74, Prepsv, quoted Doftag( 7, '$DELETE'))),
data( Defstid(75, Prepspv, quoted Doftag( 8, '$GETCAPA'))),
data( Defstid(76, Prepsrtv, quoted Doftag(12, '$INTERCHANGE'))),
data( Defstid(77, Prestep, quoted Doftag(18, '$LN LENGTH'))),
data( Defstid(78, Prepsv, quoted Doftag( 9, '$MAKEPAGE'))),
data( Defstid(79, Prepsv, quoted Doftag(14, '$MAKE(UNIVERSAL'))),
data( Defstid(80, Prepspv, quoted Doftag( 6, '$MERGE'))),
data( Defstid(81, Prepsv, quoted Doftag( 2, '$P'))),
data( Defstid(82, Prepsrtv, quoted Doftag(5, '$PSS'))),
data( Defstid(83, Prepsarts, quoted Doftag(11, '$PSSAPPEND'))),
data( Defstid(84, Prepsb, quoted Doftag(13, '$PCONDITIONAL'))),
data( Defstid(85, Prepsrtv, quoted Doftag(8, '$PUTCAPA'))),
data( Defstid(86, Preprtiv, quoted Doftag(13, '$SETCHKRIGHTS'))),
data( Defstid(87, Prepsv, quoted Doftag( 7, '$SWITCH'))),
data( Defstid(88, Prepsv, quoted Doftag( 5, '$TAKE'))),
data( Defstid(89, Prepsnat, quoted Doftag(9, '$TYPECALL'))),
data( Defstid(90, Prepsv, quoted Doftag( 7, '$UPDATE'))),
data( Defstid(91, Prepsv, quoted Doftag( 2, '$V'))),
data( Defstid(92, Prepsv, quoted Doftag( 7, '$VACATE'))),
data( Defstid(93, Prepsv, quoted Doftag( 5, '$VALL'))),
data( Defstid(94, Coda, quoted Doftag( 8, '$GETSLOT'))),
data( Defstid(95, Codist, quoted Doftag( 9, '$MAKESTEP'))),
data( Defstid(96, Codrw, quoted Doftag( 9, '$MAKEWALK'))),
data( Defstid(97, Codsl, quoted Doftag( 8, '$USESLOT'))),
data( Defstid(98, Codpiibbv, quoted Doftag(8, '$ONSIGNAL'))),
data( Defstid(99, Mdslot, quoted Doftag( 8, '$NULLSLOT'))),

```

ZZ<HZ

I Operators

```

data( Defstopr( 0, Obabs, quoted Dofopr( 3, 'ABS'))),
data( Defstopr( 0, Obarg, quoted Dofopr( 3, 'ARG'))),
data( Defstopr( 0, Obbin, quoted Dofopr( 3, 'BIN'))),
data( Defstopr( 0, Obconj, quoted Dofopr( 4, 'CONJ'))),
data( Defstopr( 0, Obdown, quoted Dofopr( 4, 'DOIN'))),
data( Defstopr( 0, Obonti, quoted Dofopr( 6, 'ENTIER'))),
data( Defstopr( 0, Oblong, quoted Dofopr( 4, 'LENG'))),
data( Defstopr( 0, Oblevel, quoted Dofopr( 5, 'LEVEL'))),
data( Defstopr( 0, Obnot, quoted Dofopr( 3, 'NOT'))),
data( Defstopr( 0, Obodd, quoted Dofopr( 3, 'ODD'))),
data( Defstopr( 0, Obrepr, quoted Dofopr( 4, 'REPR'))),
data( Defstopr( 0, Obroun, quoted Dofopr( 5, 'ROUND'))),
data( Defstopr( 0, Obshrt, quoted Dofopr( 7, 'SHORTEN'))),
data( Defstopr( 0, Obsign, quoted Dofopr( 4, 'SIGN'))),
data( Defstopr( 0, Obup, quoted Dofopr( 2, 'UP'))),
data( Defstopr( 1, Obdvab, quoted Dofopr( 5, 'DIVAB'))),
gbinamol Oprdvab,
data( Defstopr2( 1, Obdvab)),
gbinamol Oprmnab,
data( Defstopr2( 1, Obmnab)),
data( Defstopr2( 1, Obmdab), quoted Dofopr( 5, 'MODAB'))),

```

PAGE 1-13

DSKB: SRTABS.BLI (L150UL68) eCMU-100

29-Sep-77 22:18 55 blocks

```

gbinname( Oprmidab,
    data(
gbinname( Oprovab,
    data(
gbinname( Oprplab,
    data(
gbinname( Oprpito,
    data(
gbinname( Oprtmab,
    data(
        data(
        data(
gbinname( Oreq,
    data(
gbinname( Oprne,
    data(
gbinname( Oprge,
    data(
gbinname( Oprgt,
    data(
gbinname( Oprle,
    data(
gbinname( Oprlt,
gbinname( Oprplus,
gbinname( Oprminus,
    data(
gbinname( Oprtimes,
gbinname( Oprdiv,
    data(
gbinname( Oprmod,
    data(
gbinname( Oprovor,
gbinname( Oprup1,
gbinname( Oprup2,
    data(
        data(
        data(
        data(
gbinname( Oprplitm,
    data(
        -1)
dataend;

```

Defstopr2(1, Obmdab)),
 Defstopr1(1, Obovab),
 Defstopr2(1, Obovab)),
 Defstopr1(1, Obplab,
 Defstopr2(1, Obplab)),
 Defstopr1(1, Obpito,
 Defstopr2(1, Obpito)),
 Defstopr1(1, Obtmab,
 Defstopr2(1, Obtmab)),
 Defstopr1(2, Obor,
 Defstopr1(3, Oband,
 Defstopr1(4, Oboq,
 Defstopr2(4, Oboq)),
 Defstopr1(4, Obne,
 Defstopr2(4, Obne)),
 Defstopr1(5, Obyo,
 Defstopr2(5, Obyo)),
 Defstopr1(5, Obgt,
 Defstopr2(5, Obgt)),
 Defstopr1(5, Obie,
 Defstopr2(5, Obie)),
 Defstopr1(5, Obit,
 Defstopr2(5, Obit)),
 Defstopr2(6, Obplus)),
 Defstopr2(6, Obminus)),
 Defstopr1(7, Obolem,
 Defstopr2(7, Obtimes)),
 Defstopr2(7, Obdiv)),
 Defstopr1(7, Obmod,
 Defstopr2(7, Obmod)),
 Defstopr1(7, Obovor,
 Defstopr2(7, Obovor)),
 Defstopr2(8, Obup1)),
 Defstopr2(8, Obup2)),
 Defstopr1(8, Oblwib,
 Defstopr1(8, Obupb,
 Defstopr1(8, Obshi,
 Defstopr1(8, Obshr,
 Defstopr2(9, Obplitm)),
 quoted Defopr(6, 'OVERAB'))),
 quoted Defopr(6, 'PLUSAB'))),
 quoted Defopr(6, 'PLUSTO'))),
 quoted Defopr(7, 'TIMESAB'))),
 quoted Defopr(2, 'OR'))),
 quoted Defopr(3, 'AND'))),
 quoted Defopr(2, 'EQ'))),
 quoted Defopr(2, 'NE'))),
 quoted Defopr(2, 'GE'))),
 quoted Defopr(2, 'GT'))),
 quoted Defopr(2, 'LE'))),
 quoted Defopr(2, 'LT'))),
 quoted Defopr(4, 'ELEM'))),
 quoted Defopr(3, 'MOD'))),
 quoted Defopr(4, 'OVER'))),
 quoted Defopr(3, 'UPB'))),
 quoted Defopr(3, 'SHL'))),
 quoted Defopr(3, 'SHR'))),

! Think about doing IM and RE

```

undeclare Lexstop, Lexstart, Lextab;

globnldata(,Lexstart,)  Lexn(Lxvstart,empty));
globnldata(,Lexstop,)   Lexn(Lxvstop,empty));

globnldata(,Lextab,)

0, Deftag( 8, empty),
8, Deftag( 2, 'IM'),
0, Deftag( 2, 'RE'),

```

```

0, Deftag( 4, 'STOP'),
0, Defdoinit( 1),
%K>Z%
0, Deftag( 1, 'S'),
0, Deftag( 1, 'W'),
0, Deftag( 7, 'SAUXRTS'),
0, Deftag(11, 'SGENERICRTS'),
0, Deftag(12, 'SAMPLIFYFLAG'),
0, Deftag(13, 'STEMPLATEFLAG'),
%K<Z%

```

Defbold(Lxvat,	0,	2, 'AT'),
Defbold(Lxvbogin,	0,	5, 'BEGIN'),
Defbold(Lxvprimdr,	Mubits,	4, 'BITS'),
Defbold(Lxvothdr,	Mdbool,	4, 'BOOL'),
Defbold(Lxvby,	0,	2, 'BY'),
Defbold(Lxvprimdr,	Mdbytes,	5, 'BYTES'),
Defbold(Lxvcare,	0,	4, 'CASE'),
Defbold(Lxvothdr,	Mdchan,	7, 'CHANNEL'),
Defbold(Lxvothdr,	Mdchar,	4, 'CHAR'),
Defbold(Lxvpco,	"C",	2, 'CO'),
Defbold(Lxvcode,	0,	4, 'CODE'),
Defbold(Lxvcodeop,	0,	6, 'CODEOP'),
Defbold(Lxvpco,	"C",	7, 'COMMENT'),
Defbold(Lxvprimdr,	Mdcompl,	5, 'COMPL'),
Defbold(Lxvdo,	0,	2, 'DO'),
Defbold(Lxveilit,	0,	4, 'ELIF'),
Defbold(Lxveise,	0,	4, 'ELSE'),
Defbold(Lxvend,	0,	3, 'END'),
Defbold(Lxvesac,	0,	4, 'ESAC'),
Defbold(Lxvevent,	0,	5, 'EVENT'),
Defbold(Lxvexit,	0,	4, 'EXIT'),
Defbold(Lxvext,	0,	3, 'EXT'),
Defbold(Lxvboiden,	A68false,	6, 'FALSE'),
Defbold(Lxvfi,	0,	2, 'FI'),
Defbold(Lxvothdr,	Mdfile,	4, 'FILE'),
Defbold(Lxvfor,	0,	3, 'FOR'),
Defbold(Lxvfrom,	0,	4, 'FROM'),
Defbold(Lxvgo,	MdjumP,	2, 'GO'),
Defbold(Lxvgoto,	MdjumP,	4, 'GOTO'),
Defbold(Lxvheap,	Genheap,	4, 'HEAP'),
Defbold(Lxvit,	0,	2, 'IF'),
Defbold(Lxvin,	0,	2, 'IN'),
Defbold(Lxvprimdr,	Mdint,	3, 'INT'),
Defbold(Lxvidty,	Idtyis,	2, 'IS'),
Defbold(Lxvidty,	Idtyisnt,	4, 'ISNT'),
Defbold(Lxvioc,	Gensecret,	3, 'LOC'),
Defbold(Lxvlong,	0,	4, 'LONG'),
Defbold(Lxvmoda,	0,	4, 'MODE'),
Defbold(Lxvmodule,	0,	6, 'MODULE'),
Defbold(Lxvnunmoda,	Mdvnunfile,	7, 'NEWFILE'),
Defbold(Lxvnunmoda,	Mdvnunsimple,	9, 'NEWSIMPLE'),
Defbold(Lxvnill,	Mdnll,	3, 'NIL'),
Defbold(Lxvod,	0,	2, 'OD'),
Defbold(Lxvof,	0,	2, 'OF'),
Defbold(Lxvop,	0,	2, 'OP'),
Defbold(Lxvouse,	0,	4, 'OUSE'),

PAGE 1-15

DSKB:SRTABS.BLI(L150NL68)eCHU-10A

29-Sep-77 22:18 55 blocks

```
Defbold(Lxvout,      8,      3, 'OUT'),
Defbold(Lxvpar,      8,      3, 'PAR'),
Defbold(Lxvpco,      "P",     2, 'PR'),
Defbold(Lxvpco,      "P",     7, 'PRACINT'),
Defbold(Lxvprio,     8,      4, 'PRIO'),
Defbold(Lxvproc,     8,      4, 'PROC'),
Defbold(Lxvprimdr,   Mdreal,  4, 'REAL'),
Defbold(Lxvref,       8,      3, 'REF'),
Defbold(Lxvhosp,     Conseloc, 6, 'SECLOC'),
Defbold(Lxvothdr,    Mdsema,   4, 'SEMA'),
Defbold(Lxvshort,    8,      5, 'SHORT'),
Defbold(Lxvskip,     Mdskip,   4, 'SKIP'),
Defbold(Lxvothdr,    Mdstring, 6, 'STRING'),
Defbold(Lxvstruct,   8,      6, 'STRUCT'),
Defbold(Lxvthan,     8,      4, 'THEN'),
Defbold(Lxvto,        8,      2, 'TO'),
Defbold(Lxvboolden,  A68true, 4, 'TRUE'),
Defbold(Lxvvoid,     Mdvoid,   4, 'VOID'),
Defbold(Lxvwhile,    8,      5, 'WHILE'),
```

%H>%

```
Defbold(Lxvothdr,   Mdtime,   8, 'PROCTIME'),
```

%<H%

%K>%

```
Defbold(Lxvothdr,   Mdpath,   4, 'PATH'),
Defbold(Lxvothdr,   Mdrtmask, 10, 'RIGHTSMASK'),
Defbold(Lxvothdr,   Mdslot,   4, 'SLOT'),
Defbold(Lxvothdr,   Mdstep,   4, 'STEP'),
Defbold(Lxvothdr,   Mdwalk,   4, 'WALK'),
```

ZZ<K%

```
Defpragitem(0, 3, 'RES'),
Defpragitem(1, 5, 'POINT'),
Defpragitem(2, 5, 'UPPER'),
Defpragitem(3, 5, 'LOWER'),
Defpragitem(4, 8, 'WARNINGS'),
Defpragitem(5, 10, 'NOWARNINGS'),
Defpragitem(6, 7, 'LISTING'),
Defpragitem(7, 9, 'NOLISTING'),
Defpragitem(8, 4, 'PAGE'),
-1 );
```

end

studom