

AD-A056 320

SYSTEMS SCIENCE AND SOFTWARE LA JOLLA CALIF
COMMENTS ON THE STRENGTH OF AREA 12 TUFF.(U)
FEB 78 R E DUFF


F/G 8/7


UNCLASSIFIED

DNA-4526T

DNA001-77-C-0099
NL

| OF |
AD
A056320





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AD A 056320

②

LEVEL II

AD-E300 244

DNA 4526T

COMMENTS ON THE STRENGTH OF AREA 12 TUFF

Systems, Science and Software
P.O. Box 1620
La Jolla, California 92038

February 1978

Topical Report for Period November 1977—February 1978

CONTRACT No. DNA 001-77-C-0099

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

THIS WORK SPONSORED BY THE DEFENSE NUCLEAR AGENCY
UNDER RDT&E RMSS CODE B345077462 J24AAXYX98349 H2590D.

Prepared for
Director
DEFENSE NUCLEAR AGENCY
Washington, D. C. 20305

DDC
RECEIVED
JUL 17 1978
B

AD NU.
DDC FILE COPY

Destroy this report when it is no longer
needed. Do not return to sender.



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER DNA 4526T	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) COMMENTS ON THE STRENGTH OF AREA 12 TUFF.	5. TYPE OF REPORT & PERIOD COVERED Topical Report, For Period Nov 77-Feb 78	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Russell E. Duff	8. CONTRACT OR GRANT NUMBER(s) DNA 001-77-C-0099	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Systems, Science and Software P.O. Box 1620 La Jolla, California 92038	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NWET Subtask J24AAXYX983-49	
11. CONTROLLING OFFICE NAME AND ADDRESS Director Defense Nuclear Agency Washington, D.C. 20305	12. REPORT DATE February 1978	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) DNA, SBIE	13. NUMBER OF PAGES 30p.	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.	15. SECURITY CLASS (of this report) UNCLASSIFIED	
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
18. SUPPLEMENTARY NOTES This work sponsored by the Defense Nuclear Agency under RDT&E RMSS Code B345077462 J24AAXYX98349 H2590D.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Material Strength Material Properties		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) An effort is described to find a relation between measured stress difference at 4 Kbar as determined by uniaxial strain tests and other material properties for NTS area 12 tuff. No useful relationship was found.		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

388507

CL

Table of Contents

	<u>Page</u>
1. INTRODUCTION.....	3
2. TECHNICAL DISCUSSION.....	5
3. CONCLUSIONS.....	24
REFERENCES.....	26

✓	
INSTRUMENTAL ANALYSIS	
Dist.	AVAIL 6/7/68
A	

1. INTRODUCTION

One of the most interesting developments in the recent history of containment research has involved the realization of the importance of the residual stress field as a significant feature of the containment of an underground nuclear explosion. This stress field is the result of the plastic deformation of the geologic material during the formation of the explosive cavity and its subsequent relaxation to an equilibrium state.

Rimer^[1] showed the dependence of the stress field on several relevant material parameters, and his results have been confirmed and extended by App,^[2] Terhune,^[3] and Allen.^[4]

All investigators have shown that material strength is an important determinant of residual stress magnitude for a given initial condition. Relatively little information is available about the strength of geological materials of interest, and such information is difficult to obtain. Therefore, an interesting question involves the extent to which strengths are determined by other measurable material properties. Specifically, if it could be shown that the strengths could be estimated reasonably well as a function of, let us say, water content, sound speed, and grain density, such a relation could significantly extend our knowledge of material strengths and our ability to estimate residual stress magnitude at the site of future contemplated tests.

An effort has been made to seek such a relation by what might best be called a brute-force, least-squares fitting approach. No preconceived relationships were assumed in the process.

PRECEDING PAGE BLANK-NOT FILMED

The numerical work was done by a least-square fitting program written at the UCLA medical school entitled "BMD02R, Stepwise Regression." This code generates least-squares fits of a set of dependent variables as a function of a practically unlimited set of possible independent parameters. The code examines the correlation between the dependent and independent variables and chooses the most significant parameter to be used in generating a least-squares fit. After that fit is performed, the remaining independent parameters are again examined and the second most significant is chosen, and a two-parameter fit is generated. This sequence is continued until further fitting becomes statistically insignificant. During the course of a fitting cycle, parameters can be either introduced or removed from the fit.

2. TECHNICAL DISCUSSION

Material properties information, determined by TerraTek for area 12 tuff samples, was used exclusively in this investigation. The strength parameter used is the stress difference at 4 Kb from uniaxial strain tests as scaled from data published in a series of recent TerraTek reports.^[5-9] These strength parameters were determined for the 48 drill holes in E, N and T tunnels of area 12, listed in Table I. A total of 471 data points were found in which stress difference at 4 Kb as well as a complete suite of other material properties information was available. The other information included as-received and grain densities, water contents, and longitudinal and shear-sound speeds determined from ultrasonic tests. Porosity and saturation values were derived from these. For purposes of this exercise, porosity and saturation were treated as independent parameters even though they were derived from other measurements.

Figures 1-7 show "strength" plotted as a function of the seven "measured" quantities. It is interesting to note in every case that the relations can best be described as shotgun patterns. In no case is a clear relationship evident. Figure 1 shows the relation between strength and water content. It is quite true that the field of data can be limited on the upper right hand side by a line which indicates that strength goes to zero at roughly 32 wt. percent of water in tuff. Such a relationship has been used in some calculations of event parameters. However, that is only one limit to the data and can hardly be called a representation of the information available.

This set of 471 strength determinations was fit by linear least-squares techniques to an optimum choice from 113 possible parameters. Specifically, the fit used the measured parameters themselves, various moduli derived from them,

Table I

Sources for 471 Data Points Used in a Study of the Influence
of Material Properties on Strength

<u>E Tunnel</u>	<u>N Tunnel</u>	<u>N Tunnel</u>	<u>N Tunnel</u>
UE12E#1	UE12N#8	U12N09U69SA#1	U12N101SS#1
UE12E#3	UE12N#9	U12N09UG9SA#2	U12N10ADNRE#1
U12E14UG#3	UE12N#10	U12N09UG9Misc	U12N10ADNHF#3
U12E14UG#10	U12N05UG#4	U12N10UG#1	U12N10AGSCH#1
U12E18GZ#1	U12N05UG#8	U12N10UG#2	U12N10AGSCH#2
	U12N07UG#10	U12N10UG#5	U12N10AGSCH#3
<u>T Tunnel</u>	U12N07UG#11	U12N10UG#7	U12N10AGSCH#4
U312T#3	U12N07UG#12	U12N10A	U12N10AGSHF#3
U12T01UG#1	U12N08UG#9	U12N10B	U12N10AGSHF#4
U12T03UG#2	U12N08UG#9a	U12N10C	U12N10AGSHF#6
U12T03UG#3	U12N08UG#10	U12N10HF#2	U12N10AGSHF#8
U12T04UG#1	U12N08UG#11	U12N10HF#4	U12N10AGSHF#9
			U12N10AIFRE#2
			U12N10ALLCI#1

ROCK STRENGTH IN RELATION TO OTHER RHEOLOGICAL PROPERTIES




Figure 1.

ROCK STRENGTH IN RELATION TO OTHER RHEOLOGICAL PROPERTIES




Figure 2.

ROCK STRENGTH IN RELATION TO OTHER RHEOLOGICAL PROPERTIES




Figure 3.

ROCK STRENGTH IN RELATION TO OTHER RHEOLOGICAL PROPERTIES




Figure 4.

ROCK STRENGTH IN RELATION TO OTHER RHEOLOGICAL PROPERTIES




Figure 5.

ROCK STRENGTH IN RELATION TO OTHER RHEOLOGICAL PROPERTIES




Figure 6.

ROCK STRENGTH IN RELATION TO OTHER RHEOLOGICAL PROPERTIES




Figure 7.

miscellaneous ratios of these moduli, and the squares and inverses of these variables. It must be admitted that some pretty wild functions were generated, as will be evident from the actual fit developed which will be presented below. Table II lists the important parameters and moduli used to generate the 113 potential independent variables used.

The simplest, two-term fit to the strength data is:

$$S = 0.08278 + 0.64020 \frac{v^2}{\phi}$$

Table III shows the most complex, linear, least-squares fit which could be constructed. It contains 33 terms. Insofar as the standard deviation is a good indication of the quality of a fit, the fits obtained in this effort are quite poor. At the limit of statistical significance, the standard deviation could be reduced from 0.29 to 0.20 Kb, only about 30 percent as shown in Table IV.

The quality and characteristics of the fits are indicated in the following figures. Figure 8 plots the measured strength against the simple, two-term fit shown above. Note that that fit does not explicitly involve the water content or saturation. The influence of saturation is shown in Figures 9 and 10 and water content is examined in Figures 11 and 12. Finally, Figure 13 shows the best fit found to this strength data. It does not differ noticeably from the simple fit of Figure 8.

Table II
Table of Variables Used to Construct Independent Fit Parameters

S	=	stress difference at 4Kb in uniaxial strain, kbar
ρ_G	=	grain density, mg/m^3
ρ	=	as received density, mg/m^3
ϕ	=	porosity
F	=	saturation
V_L	=	longitudinal sound speed, $\text{ft}/\text{sec} \times 10^{-4}$
V_S	=	transverse sound speed, $\text{ft}/\text{sec} \times 10^{-4}$
G	=	ρV_S^2 , shear modulus
L	=	ρV_L^2
K	=	$L - \frac{4}{3} G$, Bulk modulus
σ	=	$\frac{V_L^2 - 2V_S^2}{2(V_L^2 - V_S^2)}$, Poisson's Ratio
E	=	$\frac{9 GK}{G+3K}$, Young's modulus

Table III


"Best" Linear, Least-Squares Fit of Strength Data
for Area 12 Tuff

$S = - 18.7831$	$+ 2.7240 \frac{V_S^2}{\phi}$	$+ 0.08121 \frac{K^2}{\phi}$	$- 1.4970 KL$
$+ 33.260 \frac{1}{\rho}$	$- 18.542 L\phi$	$- 10.280 \left(\frac{G^2}{L^2 - G^2} \right)^2$	$+ 0.07688 \left(\frac{G}{H} \right)^2$
$- 0.11905 \left(\frac{L}{\phi} \right)^2$	$- 26.865 V_S$	$- 0.25480 \frac{1}{H\phi}$	$+ 1.9262 \frac{H}{G}$
$+ 7.6831 \frac{\rho_G G}{\rho(1-\phi)^{2/3}}$	$+ 2.1037 \frac{L}{\phi}$	$+ 8.9504 (K\phi)^2$	$+ 0.07808 (KL)^2$
$- 0.23785 \frac{1}{KH}$	$+ 0.9499 F^2$	$- 37.326 (\phi - H\rho)$	$- 36.153 \left(\frac{H}{\phi} \right)^2$
$+ 0.57805 \frac{1}{K\phi}$	$+ 0.79272 \rho_G^2$	$+ 0.05004 \frac{1}{\sigma}$	$+ 3.4115 \frac{1}{L}$
$+ 23.744 LH$	$- 10.898 (LH)^2$	$- 3.5394 \frac{1}{E}$	$+ 0.01990 \frac{1}{HG\phi}$
$+ 20.7470 \frac{1}{\rho_G}$	$+ 0.01957 \frac{G V_S^2}{(V_L^2 - V_S^2)}$	$- 4.4764 \frac{H}{K}$	$+ 3.9760 \frac{1}{F}$
$+ 35.491 (GH)^2$			

Table IV
Standard Deviation of Strength Data
From Several Specific Fits to it

Simple average	S = 0.45251 Kb
	σ = 0.2921
Simple fit	(2 terms)
	σ = 0.2159
Best fit	(33 terms)
	σ = 0.1970


ROCK STRENGTH IN RELATION TO OTHER RHEOLOGICAL PROPERTIES



SIMPLE FIT OF ALL DATA

Figure 8.


ROCK STRENGTH IN RELATION TO OTHER RHEOLOGICAL PROPERTIES



SIMPLE FIT OF DATA WITH GREATER THAN .95 OF COMPLETE SATURATION

Figure 9.


ROCK STRENGTH IN RELATION TO OTHER RHEOLOGICAL PROPERTIES



SIMPLE FIT OF DATA WITH LESS THAN .95 OF COMPLETE SATURATION

Figure 10.


ROCK STRENGTH IN RELATION TO OTHER RHEOLOGICAL PROPERTIES



SIMPLE FIT OF DATA WITH MASS FRACTION OF H2O GREATER THAN .23

Figure 11.

ROCK STRENGTH IN RELATION TO OTHER RHEOLOGICAL PROPERTIES



SIMPLE FIT OF DATA WITH MASS FRACTION OF H2O LESS THAN .17

Figure 12.

ROCK STRENGTH IN RELATION TO OTHER RHEOLOGICAL PROPERTIES




Figure 13.

3. CONCLUSIONS

This analysis of area 12 material properties and measured strengths indicates that the strength as represented by stress difference at 4 Kb in uniaxial strain tests is not strongly correlated with any other measured material property. In particular, the correlation with water content is weak. One can conclude from this work that if strength values are desired for some purpose, they must be measured or deduced by an independent technique. They cannot be estimated reliably for tuff on the basis of other, conventionally-determined properties.

A strong caveat is certainly appropriate. We all recognize that the statement that the dependence of material strength on water content is weak must be viewed in context. Without question, if one had a tuff in which the water content exceeded, say, 50 percent, it would be a very strange material indeed and would probably have no strength at all. Four hundred and seventy-one independent sets of material property data on real materials were used in this study. For those real materials an effort was made to find a good relation between this definition of strength and other parameters. None was found. That much is true. One should be careful in drawing further conclusions from this work.

Another class of questions should be addressed in the context of material properties, residual stresses and containment.

(1) How meaningful is stress difference at 4 kbar from uniaxial strain tests as a fundamental measure of material strength? The uniaxial constraint is appropriate for a shock process, but not for unloading phenomena. The 4 kbar value is of interest near the shot point, but residual stresses involve stress states closer to 1.0 kbar.

Hopefully an answer to this basic question will be found in the future.

(2) Assuming this stress difference is the value of interest, is it reliably measured? This question involves aspects of intrinsic in-situ material variability and experimental technique. The question is asked because a monumental effort on Mighty Epic apparently led us to a wrong qualitative and quantitative understanding of the strength of that material. Again, this question deserves our attention.

REFERENCES

1. N. Rimer, "The Influence of Material Properties on the Magnitude of Residual Stresses Around a Nuclear Cavity," Systems, Science and Software Report SSS-R-75-2658, June, 1975.
2. F. App, "A Calculational Study of the Influence of Rock Compressive Strength Upon Cavity and Residual Stress Formation about a Contained Underground Explosion," LASL Draft Report, September 1977.
3. R. Terhune, "Analysis of Depth of Burial Criteria for Containment," UCRL to be published.
4. R. Allen, et al, "Parametric Study of Ground Motion Effects Related to Stemming," PT-077-0111 to be published.
5. S. Butters, et al, "Material Properties in Support of the Nevada Test Site Nuclear Test Program," Volume I, DNA 3870F-1, October 1975.
6. S. Butters, et al, "Material Properties in Support of the Nevada Test Site Nuclear Test Program," Volume II, Supplement, DNA 3870F-2, October 1975.
7. S. Butters, et al, "Material Properties of Nevada Test Site Tuff and Grout - With Emphasis on the Mighty Epic Event, DNA 4235F, November 1976.
8. D. Gardiner and S. Butters, "Material Properties for the Diablo Hawk Event," TErraTek report TR-77-43, June, 1977.
9. Material Properties Data Bank Listing, TerraTek, no name, no date.

DISTRIBUTION LIST

DEPARTMENT OF DEFENSE

Defense Documentation Center
Cameron Station
2 cy ATTN: TC

Director
Defense Nuclear Agency
3 cy ATTN: TITL
ATTN: TISI
ATTN: DDST
ATTN: SPTD, Capt W. Summa

Commander
Field Command, DNA
ATTN: FCPR
ATTN: FCTMC, Carl Keller

Chief
Livermore Div., Fld. Command, DNA
Lawrence Livermore Laboratory
ATTN: FCPRL
ATTN: Dr. David Oakley
ATTN: Dr. Billy Hudson
ATTN: Mr. Terhune

Chief
Test Construction Div.
Field Command, Test Directorate, DNA
ATTN: Mr. Joe LaComb

Under Secretary of Def. for Rsch. & Engrg.
Department of Defense
ATTN: S&SS (OS)
ATTN: AE

DEPARTMENT OF THE ARMY

Commander Harry Diamond Laboratories
ATTN: DELHD-NP

DEPARTMENT OF THE NAVY

Officer-in-Charge
Naval Surface Weapons Center
ATTN: Code WA501, Navy Nuc. Prgms. Off.

DEPARTMENT OF THE AIR FORCE

AF Weapons Laboratory, AFSC
ATTN: SUL

DEPARTMENT OF ENERGY

Los Alamos Scientific Laboratory
ATTN: Dr. Robert Brownlee
ATTN: Mr. Fred App

Department of Energy
Nevada Operations Office
ATTN: Dr. Robert Newman

Sandia Laboratories
ATTN: Wendell Weart/Lynn Tyler

OTHER GOVERNMENT AGENCY

Department of commerce
U.S. Geological Survey
Special Projects Branch
ATTN: Rod Carroll, MS 954

DEPARTMENT OF DEFENSE CONTRACTORS

Pacifica Technology
ATTN: G. I. Kent

Physics International Company
ATTN: E. T. Moore

SRI International
ATTN: Alex Florence

Systems, Science & Software, Inc.
ATTN: Russell E. Duff

Terra Tek, Inc.
ATTN: Sidney Green

General Electric Company
TEMPO-Center for Advanced Studies
ATTN: DASIAC