

Unclassified SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered) **READ INSTRUCTIONS** 9 REPORT DOCUMENTATION PAGE BEFORE COMPLETING FORM . REPORT NUMBER 2. GOVT ACCESSION NO. 3. RECIPIENT'S CATALOG NUMBER 18 NSWC/DL TR-3830 5. TYPE OF REPORT & PERIOD COVERED Contractor Report 4. TITLE (and Subtitle) IMPROVED TRANSONIC NOSE DRAG ESTIMATES 3/4/77 - 10/4/77 FOR THE NSWC MISSILE AERODYNAMIC COMPUTED SERFORMING ORG. REPORT NUMBER PROGRAM . NEAR-TR-153 4 CONTRACTOR GRANT NUMBER(S) Denny S. Chaussee N60921-77-C-A085 9. PERFORMING ORGANIZATION NAME AND ADDRESS 10. PROGRAM ELEMENT, PROJECT, TASK Nielsen Engineering & Research, Inc. 11 510 Clyde Avenue Mountain View, CA 94043 11. CONTROLLING OFFICE NAME AND ADDRESS 12. REPORT DATE Naval Surface Weapons Center (K21) -November 197 Dahlgren Laboratory 13. NUMBER OF Dahlgren, Virginia 22448 MONITORING AGENCY NAME & ADDRESS(II different from Controlling Office) 15. SECURITY CLASS. e rest. 4 Mar- 4 Oct 7 Unclassified DECLASSIFICATION DOWNGRADING NA 16. DISTRIBUTION STATEMENT (of this Report) Approved for public release - distribution unlimited. DIST RIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) 3239 SUPPLEMENTARY NOTES SR\$23\$2 \$\$ 19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Transonic Flow Computational Fluid Dynamics Sphere-ogive-cylinder Configuration Inviscid Nose Drag 6 01 = STRACT (Continue on reverse side If necessary and identify by block number) An axisymmetric implicit unsteady Euler equation solver has been applied to the transonic flow past sphere-ogive-cylinder bodies. This paper documents this method and shows results that were obtained for the full range of transonic Mach numbers, 0.7 SM 3 1.2. The present numerical results are compared to the experiments of Hsieh for $M_{\infty} = 0.7, 0.95, 1.0, 1.05, 1.1$ flow A /rather extensive parametric study over hemisphere cylinders. DD 1 JAN 73 1473 EDITION OF I NOV 65 IS OBSOLETE Unclassified CLASSIFICATION OF THIS PAGE (When Date Entered

Unclassified

4

SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered)

of sphere-ogive-cylinders was performed over the transonic Mach number range. Nose pressure drag values were calculated and are presented for varying nose radii, 0 to 1.0, varying nose length, 1.0 to 10.0 and varying Mach numbers, 0.7 to 1.2, where all geometric quantities are normalized with respect to the maximum body radius. These results have been included in the NSWC Missile Aerodynamic Computer program to improve transonic nose drag estimates.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

FOREWORD

This technical report covers the work performed under Contract N60921-77-C-A085 from 4 March 1977 to 4 October 1977. The program is sponsored by the Naval Surface Weapons Center, Dahlgren Laboratory (NSWC/DL), Dahlgren, Virginia.

The funding support was provided by the Naval Sea Systems Command (NAVSEA) SEATASKS <u>SF 32399-592/18450</u> and <u>SR02302-001-18635</u>, Naval Air Systems Command (NAVAIR) NIF, and Army Missile Research and Development Command, Research Element No. 62303A.

This report was reviewed for technical accuracy by Dr. J. Sun and Dr. L. Devan and approved by Dr. F. G. Moore, Head, Aeromechanics Branch and H. P. Caster, Head, Exterior Ballistics Division.

Released by:

Gazl. a Heman

R. A. NIEMANN, Head Strategic Systems Department

61153N



ACKNOWLEDGMENT

The author would like to express his appreciation to Dr. P. Kutler, Dr. T. Pulliam, both of NASA/Ames and to Dr. M. Hemsch of NEAR, Inc. for their consultation and helpful suggestions during this study and to the Computational Fluid Dynamics Branch at NASA/Ames Research Center, Moffett Field, California, for the allocation of computer time throughout the study.

This technical report covers the work performed under Contract N60921-77-C-A085 from 4 March 1977 to 4 October 1977. The program is sponsored by the Naval Surface Weapons Center, Dahlgren Laboratory (NSWC/DL), Dahlgren, Virginia.

CEDING PAGE BLANK-NOT FILMED

Dr. J. Sun and Dr. L. Devan, Dahlgren Laboratory were the contract monitors for this study.

CONTENTS

	Page
INTRODUCTION	1
ANALYSIS	2
Implicit Unsteady Euler Equation Method	2
Drag Calculation	8
Body Geometry	10
Table Lookup Method	12
RESULTS AND DISCUSSION	13
Comparison of Pressure Prediction Methods	13
Drag Predictions and Comparisons	26
Computer Program Alterations	42
CONCLUSIONS AND RECOMMENDATIONS	43
REFERENCES	50
GLOSSARY OF TERMS	52
DISTRIBUTION	

vii

TECEDING PAGE BLANK-NOT FILMED

LIST OF ILLUSTRATIONS

Figure		Page
1	Transformation of Physical Plane to Computational Plane for a Single Solver	4
2	Nomenclature for Drag Calculation	9
3	Ogive Body Geometry Definition	11
4	Typical Example of Computational Grid	14
5	Pressure Distribution on Hemisphere-Cylinder	16
6	Hemisphere-Cylinder Drag Variation with ${\tt M}_{_{\infty}}$	18
7	Embedded Supersonic Region at $M_{\infty} = 0.95$ for Flow Over a Hemisphere Cylinder	19
8	Comparison of Theoretical and Experimental Location of Shock Angle for $M_{\infty} = 1.1$ for Flow Over a Hemisphere Cylinder	20
9	Shock Wave and Sonic Line Location for $M_{\infty} = 1.1$ Flow Over a Hemisphere Cylinder	21
10	Evolution of Drag Solution for Hemisphere Cylinder	22
11	Comparison Between Experiment and Theory for $M_{\infty} = 0.95$ Flow Past a 4 Caliber Tangent Ogíve Body	23
12	Calculated Body Pressure on Sphere-Ogive-Cylinders for Varying Nose Bluntnesses, Nose Lengths, and Mach Numbers	24
13	Calculated Values of Nose Pressure Drag Presented as a Function of Nose Length and Nose Bluntness for Varying Mach Numbers	29
14	Transonic Wave Drag of Pointed Tangent Ogives for Various Nose Lengths in Calibers	33
15	Total and Forebody Drag Comparisons of the Present and Previous Theoretical Results with Experiment	35
16	Total and Forebody Drag Comparisons of the Present and Previous Theoretical Results with Experiment	37
17	Total and Forebody Drag Comparisons of the Present and Previous Theoretical Results with Experiment	39
18	Sample Input Data for a Typical Tangent Ogive Configuration	47
19	Sample Output for Tangent Ogive Configuration of Figure 18	48

PECEDING PAGE BLANK-NOT FILMED

INTRODUCTION

Accurate drag predictions are essential for optimum missile design. For Mach numbers in the transonic regime, the NSWC code¹ is currently applicable to missiles with pointed or slightly blunted noses. This restriction results from the use of methods based on small perturbation theory such as Wu and Aoyoma.² When bluntness effects become large, it is necessary to account for radial flow velocities comparable to free stream velocities over a sizable region of the flow field. A fundamental failing of small-disturbance theory is that it cannot do this.

A precise calculation of nose wave drag depends upon the accurate determination of surface pressures both in the stagnation region and the shoulder region. This is because the overpressure in the stagnation region creates a large drag force which is partially or wholly counterbalanced by the flow expansion in the shoulder region. In subsonic flows, the balance is exact for the nose itself, while in transonic flows, one is attempting to find the difference of two large, nearly equal quantities in order to compute the nose wave drag. Consequently, a method is required which can maintain the required accuracy in these regions.

The computation of nose wave drag, then, for the transonic speed range requires an accurate code capable of properly treating the inviscid flow physics. The exact governing equations are the Euler equations. In the present report an implicit Euler equation solver^{3,4,5} is used to calculate the flow field around the bodies and pressures on the bodies. These pressures are then integrated to obtain the nose drag coefficient for a set of Mach numbers, nose bluntnesses and nose lengths. The resulting table of transonic drag coefficients which is necessarily restricted to sphere-tangent ogive-noses is incorporated into the NSWC computer code.¹

ANALYSIS

Implicit Unsteady Euler Equation Method

The partial differential equations governing the two-dimensional planar or axisymmetric flow of an unsteady inviscid, non-heat-conducting, ideal gas are written in conservation-law form under the generalized independent variable transformation

$$\tau = t,$$

 $\xi = \xi(t, x, y),$
 $\eta = \eta(t, x, y)$

as follows:

 $(U/J)_{\tau} + [(\xi_{t}U + \xi_{x}E + \xi_{y}F)/J]_{\xi} + [\eta_{t}U + \eta_{x}E + \eta_{y}F)/J]_{\eta} + jH = 0 \quad (1)$

where

$$\mathbf{U} = \begin{bmatrix} \rho \\ \rho \mathbf{u} \\ \rho \mathbf{v} \\ \mathbf{e} \end{bmatrix} \quad \mathbf{E} = \begin{bmatrix} \rho \mathbf{v} \\ p + \rho \mathbf{u}^{2} \\ \rho \mathbf{u} \mathbf{v} \\ (\mathbf{e} + p) \mathbf{u} \end{bmatrix} \quad \mathbf{F} = \begin{bmatrix} \rho \mathbf{v} \\ \rho \mathbf{u} \mathbf{v} \\ p + \rho \mathbf{v}^{2} \\ (\mathbf{e} + p) \mathbf{v} \end{bmatrix} \quad \mathbf{H} = \frac{1}{\mathbf{y} \mathbf{J}} \begin{bmatrix} \rho \mathbf{v} \\ \rho \mathbf{u} \mathbf{v} \\ \rho \mathbf{v}^{2} \\ (\mathbf{e} + p) \mathbf{v} \end{bmatrix}$$

and the Jacobian

$$J = \xi_x \eta_y - \xi_y \eta_x$$

In eq. (1), j = 0 for two-dimensional flow; j = 1 for axisymmetric flow (where y becomes the cylindrical radius); p represents the pressure, ρ , the density; u and v, the velocity components in the x and y directions, respectively; and e, the total energy per unit volume. The following equation relates the pressure, density, and velocity components to the energy for an ideal gas

$$e = p/(\gamma - 1) + \rho(u^{2} + v^{2})/2$$
(2)

The equations represented by eq. (1) were solved using an implicit Euler equation method.

Using the above independent variable transformation, the physical plane with boundaries 1-4 in x, y, and t space is mapped into the rectangular computational plane ξ , η , and τ space as shown in figure 1. The metrics (geometric factors) that are required by eq. (1) are defined as follows:

$$\xi_{t} = (x_{\eta}y_{\tau} - y_{\eta}x_{\tau})/I \qquad n_{t} = (y_{\xi}x_{\tau} - x_{\xi}y_{\tau})/I$$

$$\xi_{x} = y_{\eta}/I \qquad n_{x} = -y_{\xi}/I \qquad (3)$$

$$\xi_{y} = -x_{\eta}/I \qquad n_{y} = x_{\xi}/I$$

where

$$I = 1/J = x_{\xi} y_{\eta} - x_{\eta} y_{\xi}.$$

Generally at each time step the metrics of eq. (3) are not known analytically and they must be determined numerically.

The basic numerical algorithm used in the IMP code was developed by Beam and Warming.⁴ It is second-order accurate, noniterative, and is in a spatially factored form. In particular, the "delta-form" with Euler time differencing is used, and when applied to eq. (1), it assumes the following form

$$(\mathbf{I} + \Delta t \delta_{\xi} \mathbf{A}^{\mathbf{n}}) (\mathbf{I} + \Delta t \delta_{\eta} \mathbf{B}^{\mathbf{n}}) (\mathbf{U}^{\mathbf{n}+1} - \mathbf{U}^{\mathbf{n}}) = -\Delta t (\delta_{\xi} \mathbf{E}^{\mathbf{n}} + \delta_{\eta} \mathbf{F}^{\mathbf{n}} + \mathbf{H}\mathbf{j})$$
(4)

where A and B are the Jacobian matrices $A = \partial \hat{E}/\partial \hat{u}$ and $B = \partial \hat{F}/\partial \hat{u}$ with $\hat{u} = U/J$; $\hat{E} = (\xi_t U + \xi_x E + \xi_y F)/J$, and $\hat{F} = (n_t U + n_x E + n_y F)/J$. The A matrix is given below. The B matrix, which has the same form except that ξ_t , ξ_x , and ξ_y are replaced by n_t , n_x , and n_y , is not presented. I is the identity matrix, δ_{ξ} and δ_{η} are second-order, central difference operators, $\hat{U}^{n+1} = \hat{U}(n\Delta t)$ and Δt is the integration stepsize.





$$A = \begin{cases} \xi_{t} & (\gamma-1)q^{2}\xi_{x}/2 & (\gamma-1)q^{2}\xi_{y}/2 & [(\gamma-1)q^{2}-\gamma e/\rho] \cdot \\ & -u(\xi_{x}u+\xi_{y}v) & -v(\xi_{x}u+\xi_{y}v) & \cdot(\xi_{x}u+\xi_{y}v) \\ \xi_{x} & \xi_{t}-(\gamma-2)u\xi_{x} & \xi_{x}v-\xi_{y}(\gamma-1)u & [\gamma e/\rho - (\gamma-1)q^{2}/2]\xi_{x}-(\gamma-1)u \cdot \\ & +\xi_{x}u+\xi_{y}v & & \cdot(u\xi_{x}+v\xi_{y}) \\ \xi_{y} & -\xi_{x}(\gamma-1)v & \xi_{t}-(\gamma-2)v\xi_{y} & [\gamma e/\rho - (\gamma-1)q^{2}/2]\xi_{y}-(\gamma-1)v \cdot \\ & +\xi_{y}u & +\xi_{x}u+\xi_{y}v & \cdot(u\xi_{x}+v\xi_{y}) \\ 0 & (\gamma-1)\xi_{y} & (\gamma-1)\xi_{y} & \xi_{t}+\gamma(\xi_{x}u+\xi_{y}v) \end{cases}$$
(5)

Equation (4) is solved at the interior points only. It requires two block 4×4 , tridiagonal inversions at each time step of the integration. The solution procedure is as follows:

1. Define $\Delta \hat{U} = \hat{U}^{n+1} - \hat{U}^n$;

- 2. Form the right-hand side of (4) and store results in the \hat{U}^{n+1} array;
- 3. Apply smoothing $\hat{U}^{n+1} = \hat{U}^{n+1} \epsilon/8$ S/J where the smoothing term is defined below;
- 4. Define $\overline{U} = (I + \Delta t \delta_n B^n)$ U and solve the matrix equation $(I + \Delta t \delta_{\xi} A^n) \overline{U} = U^{n+1}$ for \overline{U} and again store the result in the \hat{U}^{n+1} array;

5. Solve the matrix equation $(I + \Delta t \delta_n B^n) \Delta \hat{U} = \hat{U}^{n+1}$ for $\Delta \hat{U}$;

6. Obtain the new values of \hat{U}^{n+1} from the equation $\hat{U}^{n+1} = \Delta \hat{U} + \hat{U}^n$.

A fourth order smoothing term is needed to eliminate nonlinear instabilities³ which arise since the use of central differences in the spatial directions results in a neutrally stable algorithm. The smoothing term S is

$$S_{jk} = (\hat{U}J)_{j+2,k}^{n+1} - 4[(\hat{U}J)_{j+1,k}^{n+1} + (\hat{U}J)_{j-1,k}^{n+1}] + 12(\hat{U}J)_{j,k}^{n+1} + (\hat{U}J)_{j-2,k}^{n+1} + (\hat{U}J)_{j,k+2}^{n+1} - 4[(\hat{U}J)_{j,k+1}^{n+1} + (\hat{U}J)_{j,k-1}^{n+1}] + (\hat{U}J)_{j,k-2}^{n+1}$$

and ξ is the smoothing coefficient chosen from the range $0 \le \varepsilon \le 0.4$ depending upon the size of the time step. The j and k indices correspond to the ξ and η directions, respectively. At the points adjacent to the boundaries a special form of the smoothing term is used.

The solution of initial value problems using finite difference procedures requires an integration step size. The value of this step size is a function of the eigenvalues of the coefficient matrices, \overline{A} and \overline{B} , of the governing pde's (equation 1) when written in the form:

$$u_{\tau} + \overline{A}u_{\varepsilon} + \overline{B}u_{n} + j\hat{H} = 0$$
 (7a)

The eigenvalues of the coefficient matrices \overline{A} and \overline{B} are

$$\sigma_{A_{1,2}} = \xi_{t} + u\xi_{x} + v\xi_{y} \pm c(\xi_{x}^{2} + \xi_{y}^{2})^{1/2}$$

$$\sigma_{A_{3}} = \xi_{t} + u\xi_{x} + v\xi_{y}$$

$$\sigma_{B_{1,2}} = \eta_{t} + u\eta_{x} + v\eta_{y} \pm c(\eta_{x}^{2} + \eta_{y}^{2})^{1/2}$$

$$\sigma_{B_{2}} = \eta_{t} + u\eta_{x} + v\eta_{y}$$
(7b)

where \hat{H} is the modified source term and

(6)

where c, the speed of sound is equal to $(\gamma p/\rho)^{1/2}$. The σ terms in Eq. (7b) can be recognized as the slopes of the characteristics and streamlines in the t- ξ and t- η planes.

The stability theory for explicit methods, at least for (t,ξ) space in unsteady flow, requires that

$$\frac{\Delta t}{\Delta \xi} \leq \frac{1}{|(\sigma_{A_{\ell}})|} \qquad \ell = 1,3$$

where $(\sigma_{A_{\ell}})$ is the maxima of the local eigenvalues of all the points at a particular constant t or ξ plane. Similar relations can be obtained for the (t,η) plane:

$$\frac{\Delta \tau}{\Delta \eta} \leq \frac{1}{|(\sigma_{B_{\ell}})|} \qquad \ell = 1,3$$
(8c)

(8b)

This planar analysis has been shown to give a good bound on the step size in multidimensional problems if the right hand side of Eqs. (8b) and (8c) are multiplied by a constant C. In explicit methods, $C \leq 1$ and is usually assigned a value of 0.9 whereas in implicit methods C is only restricted by the accuracy of the solution since implicit methods are unconditionally stable. Typically these values are on the order of 5 to 10 for inviscid flow computations.

It is convenient to consider two types of boundaries in inviscid computational fluid dynamics - those which are impermeable (no mass flow across) and those which are permeable (mass flow across). The impermeable boundaries consist of such surfaces as solid walls, symmetry planes and slip surfaces, while the permeable boundaries consist of such things as supersonic inflow or outflow boundaries and shock waves. In the transonic flow about projectiles, the four boundaries of figure 1 can be characterized as follows: boundary 1 is either a shock wave ($M_{\infty} > 1.00$) or a fixed outer boundary ($M_{\infty} < 1.0$), boundary 2 is an outflow plane, boundary 3 is the solid body, and boundary 4 the plane of symmetry.

The body boundary is treated by using the tangency condition which is incorporated through the use of Kentzer's scheme,⁶ and at the symmetry plane, the variables are reflected according to whether they are odd or even. The outflow boundary is placed far enough down the aft body such that the pressure can be approximated by its value at infinity and the rest of the variables are extrapolated. At the outer boundary, there are two possibilities: (1) if shock fitting is used and the flow is supersonic, the sharp discontinuity approach of Thomas⁷ is used or (2) if shock capturing is used, the flow can be either subsonic or low supersonic and the outer boundary is chosen such that its influence on the flow field surrounding the body is negligible.

The initial conditions are determined by first guessing a shock wave shape or outer boundary shape for the particular obstacle at hand. Second, a Newtonian pressure distribution is prescribed on the body. Using the fact that there is no flow through the body and that the maximum entropy streamline wets the body, the remainder of the properties can be prescribed on the body. Finally, a linear variation for the properties is prescribed between boundary 1 and the body. This gives an initial guess for the flow field which is integrated forward in time until a steady state is reached.

In all cases, the resulting flow field between the body and the outermost boundary is treated in shock capturing fashion and, therefore, allows for the correct formation of secondary internal shocks.

Applying the algorithm, boundary conditions and initial conditions to Eq. (1) and solving Eq. (1) in a time asymptotic fashion with interest only in the steady state, a complete set of flow field data results out of which the nose drag is calculated by integrating the surface pressures over the surface area of the body.

Drag Calculation

The wave or pressure drag for a sphere-ogive-cylinder body at zero angle of attack is

$$D = \int_{0}^{2\pi} \int_{0}^{Y_{b}} (p-p_{\infty}) y \, dy \, d\phi$$

(see figure 2). Note that $p-p_{\infty}$ is the differential pressure along the surface and $yd\phi \cdot dy$ is the surface area over which the pressure is acting for drag considerations. Since the body is axisymmetric and at zero angle of attack, the pressure is not a function of the meridional angle, ϕ . Integrating the above equation (9) and using the fact that $p-p_{\infty} = f(y)$ gives

$$D = 2\pi \int_{0}^{Y_{b}} (p-p_{\infty}) y dy .$$



Figure 2. Nomenclature for Drag Calculation

9

By using the following approximation for total drag

$$D \approx \sum_{i=0}^{i} D_{i}$$

(10b)

(10a)

equation (10) can be integrated using the mean value theorem for each geometric segment i. This can be written as a form of the trapezoidal rule

$$D \approx 2\pi \sum_{i=1}^{I} (\overline{p-p_{\infty}}) \frac{(y_i^2 - y_{i-1}^2)}{2}$$

where

$$(\overline{p-p_{\infty}}) = \frac{(p-p_{\infty})_{i} + (p-p_{\infty})_{i-1}}{2}$$

Thus the total drag is the summation of each geometric increment of drag.

The drag coefficient is defined as

$$C_{\rm D} = \frac{\rm D}{\rm qS_{\rm ref}}$$
(11a)

(10c)

where

q is the dynamic pressure $\frac{1}{2}\rho_{\infty}V_{\infty}^2$ S_{ref} is the reference area πr_b^2

Finally, the total drag coefficient is

$$C_{\rm D} = \frac{1}{r_{\rm b}^2} \sum_{i=1}^{\rm Imax} \frac{\left(C_{\rm p_i} + C_{\rm p_{i-1}}\right)}{2} (y_{\rm i}^2 - y_{\rm i-1}^2)$$
(11b)

where

$$C_{p} = \frac{p - p_{\infty}}{q}$$

Body Geometry

A large number of ogive body shapes are considered in this report. They are characterized by bluntness ratios from 0 to 1 and fineness ratios from 5 to 0.5.

From figure 3, the bluntness ratio is defined as the nose radius divided by the cylindrical body radius

Bluntness =
$$\frac{R_n}{R_b}$$



Figure 3. Ogive body geometry definition

where a bluntness of 0 is a pointed ogive and a bluntness of 1 is a hemisphere. The fineness ratio is defined as the sphere ogive body length divided by the diameter of the attached cylinder:

Fineness =
$$\frac{L_n}{2R_b}$$

where a fineness ratio of 0.5 is a hemisphere cylinder.

Geometrically, the sphere ogive cylinder configuration is defined by using one algebraic equation in y and x to define each of the three segments which are shown in figure 3. This general equation is written

$$Ay^{2} + Byx + Cx^{2} + Dy + Ex + F = 0$$

where the coefficients vary depending upon which segment of the body is being defined. Body segment 1 is input as the arc of a circle of radius R_n with the origin at $(R_n, 0)$ and it satisfies the equation

$$y^{2} + (x-R_{n})^{2} = R_{n}^{2}$$
.

Similarly, body segment 2 is also an arc of a circle of radius R_2 with the origin at $[L_n, (R_b-R_2)]$, and satisfies the equation

$$[y - (R_b - R_2)]^2 + (x - L_n)^2 = R_2^2$$
.

The third segment is a straight line parallel to the x axis and is given by

$$y = R_b$$
.

In the computer solution, all of the geometric quantities are normalized with respect to the cylindrical radius $R_{\rm h}$.

Table Lookup Method

The wave or pressure drag coefficient has been calculated as a function of three variables,

$$C_{\rm D} = f(M_{\infty}, R_{\rm n}/R_{\rm b}, L_{\rm n}/R_{\rm b})$$
.

The problem is one of interpolation for the drag coefficient given the three independent variables. This can be done by three onedimensional interpolations. To keep within the framework of the previous program usage and for the ease of understanding, the following approach was taken. In this process, the table of drag coefficients consists of 10 nose bluntnesses, 8 nose lengths, and 4 Mach numbers. The procedure is as follows:

1. For a single value of bluntness, load up a new set of 8 nose length arrays each consisting of drag values for the four corresponding Mach numbers; i.e. $L_i = L_i(C_D(M_{\infty}))$ i = 1, 2, ..., 8.

- 2. For a given Mach number, a three point Lagrangian interpolation is used to obtain a value of the drag coefficient from each of the 8 new nose length arrays of step 1. Each interpolated value is stored in a new array corresponding to one of the 8 nose lengths.
- 3. For a given nose length, a five point Lagrangian interpolation is used on the new arrays created in step 2 to find the final value of drag which is stored in a new array.
- 4. Steps 1 through 3 yield the drag coefficient for a single value of bluntness in the drag table and for the given Mach number and nose length. Repeating steps 1 through 3 for each value of nose bluntness, a value for the drag coefficient is obtained for each bluntness.
- 5. A five point Lagrangian interpolation is performed on the drag coefficient array of step 3 which consists of a value for each of the 10 bluntness in the table. This gives the final value of the drag coefficient for a specified Mach number, nose length, and nose bluntness.

Two subroutines not available in the NSWC parent code were needed in this solution procedure. They are documented in a later section.

RESULTS AND DISCUSSION

Comparison of Pressure Prediction Methods

Since there is experimental data⁸ readily available through the transonic range for hemisphere cylinders, the present technique was initially applied to that limiting case. These results are presented in figures 4-10.

Figure 4 shows the typical grid network used. By numerical experimentation, it was found that locating the outer boundary at 10 body diameters and the outflow boundary at 4 body diameters was sufficient to obtain a solution uninfluenced by the choice of boundaries. It was also found useful to stretch the mesh in the outer regions and compress it near the body.





Figure 5 shows numerical results from the present method compared to the experiments performed by Hsieh for $M_{\infty} = .7, .95$, 1.0, 1.05, 1.1. In all cases, the comparison is very good with experiment. This establishes confidence in the present method.

Figure 6 compares numerical computations of the drag for a hemisphere-cylinder with Hsieh's experimental results. The drag calculation by the present method gives good agreement with the previous numerical and experimental results of Hsieh.⁸

The flow field of a highly supercritical flow is presented in figure 7. The typical transonic flow pattern is observed with an acceleration of flow over the hemisphere nose to sonic velocity and downstream compression on the cylinder via a normal shock wave.

Figures 8 and 9 show, respectively, the shock angle which is measured from the horizontal, δ , and the shock wave and sonic line for low supersonic flow, $M_{\infty} = 1.1$ flow over a hemisphere-cylinder. In figure 9, one of the more interesting features of the flow field is the bending back of the sonic line past the vertical axis.

Figure 10 shows the drag (pressure) evolution for transonic flows over a hemisphere-cylinder. Note that in general the limiting value for drag is reached by the time 1200 iterations have been performed.

The results presented above have established the accuracy and versatility of the present code. The next step is to apply it to transonic flow over sphere-ogive-cylinders. Previous researchers² have used an inviscid transonic approximation theory to calculate the entire flow field around nonlifting slender ogive bodies. The transonic flow fields are essentially the same for these shapes which include the hemisphere cylinders as a special case. Figures 11 and 12 give some results for different sphere-ogive-cylinder bodies. The calculated pressure distribution along the body for $M_{\infty} = 0.95$, 4 caliber tangent ogive body is presented in figure 11 along with available experimental data. The final mesh point distribution used in calculating the pressure distribution was used in the remaining calculations based on its ability to capture the essentials of a flow field surrounding sphere-ogive-cylinders.



Figure 5. Pressure Distribution on Hemisphere-Cylinder







Figure 7. Embedded Supersonic Region at $M_{\infty} = 0.95$ for Flow Over a Hemisphere Cylinder





the state of the second st







Figure 10. Evolution of Drag Solution for Hemisphere Cylinder











Figure 12. Concluded

Typical results for transonic flow about sphere-ogive-cylinders are presented in figure 12. Figures 12a and 12b show the effect of nose bluntness and nose length on the body pressure distribution for a $M_{\infty} = 1.05$. The major change in the low supersonic flow regime takes place near the nose of the vehicle. In figure 12c at a high subsonic Mach number, $M_{m} = 0.95$, there occurs two major changes, one aft of the ogive-cylinder juncture and one in the region of the nose as in the low supersonic case. The major change aft of the ogive-cylinder juncture is due to the termination of the supersonic embedded region by a normal shock wave which produces a steepening of the pressure gradient. In figure 12c, this phenomena occurs at about 1.5 calibers downstream of the nose. For decreasing nose bluntness, the location of the normal shock is located more aft on the body. It should be understood that in figure 12c the curve for $R_n/R_h = 1.0$ was obtained by placing more points on the afterbody where the terminator shock wave strikes the body. This in no way reflects upon the accuracy of the drag calculation since those were done by maximizing the number of points in the nose region where the resolution of the pressure is important for the calculation of drag.

Drag Predictions and Comparisons

The purpose of this study was the calculation of the nose drag coefficients for a family of sphere-ogive-noses through the transonic Mach number range. A table was constructed (Table I) for these coefficients as a function of nose bluntness, nose length, and Mach number. This table was incorporated into the NSWC computer code. As a first step in obtaining the aforementioned table, nose drag coefficients are presented in figures 13 as a function of nose bluntness and nose length for the transonic Mach numbers 0.8, 0.95, 1.05, and 1.2. To reduce the overall computation time of this study, a minimum matrix of variables was necessarily calculated. These computations are represented by the symbols in figures 13.

In figures 13a, c, e, g, the nose drag coefficient versus nose length with nose bluntness as a variable is presented. For all bluntnesses and for all Mach numbers, the nose drag coefficient

TABLE I. $C_D = f(R_n/R_b, L_n/R_b, M_{\infty})$ for Sphere-Ogive-Cylinders.

1.0		. 08	.08	.08	08	. 08	.08	.08	.08		.278	278	278	278	278	278	278	278		410	410	410	410	410	410	410	410
8.		.060	.055	.042	.042	.042	.042	.042	.042		.184	.150	.121	.108	.108	. 108	.108	.108		. 300	.240	.200	.175	.175 .	.175 .	.175 .	175
۲.		.058	.045	.031	.031	.031	.031	.031	.031		.180	.238	160.	.065	.065	.065	.065	.065		.285	.223	.170	.130	.121	.120	.120	120
.6		.060	.040	.022	.022	.020	.020	.020	.020		.180	.123	.081	.048	.048	.048	.048	.048		.291	.229	.170	.135	.100	.082	.077	020
.5		.065	.040	.020	.018	.010	.010	.010	.010		.190	.130	.080	.047	.031	.031	.031	.031		.310	.240	.180	.145	.095	.061	.050	070
. 4		.089	.051	.030	.020	.010	.006	.006	.006		.211	.144	.091	.055	.040	.031	.028	.021		.335	.260	.202	.160	.100	.051	.038	100
.3		.130	.081	.051	.035	020	.007	.007	.007		.250	.175	.115	.075	.042	.032	.028	.020		.365	.290	.230	.180	.115	.055	.030	100
.2	æ.	.198	.130	.088	.065	.040	.020	.012	.008	= .95	.311	.223	.150	.110	.061	.038	.021	.015	= 1.05	.441	.339	.270	.210	.140	.067	.030	300
	× ⁸	.290	.200	.140	.101	.070	.041	.029	.020	× ×	.400	. 295	.200	.150	160.	.049	.031	.020		.541	.409	.321	.250	.175	.085	.035	0.05
٥.		.422	.290	.210	.151	.100	.068	.050	.041		.518	. 395	.262	.198	.130	.080	.040	.025		.67	.505	.390	.302	.211	.105	.040	0.05
Ln/Rb		1.5	2.0	2.5	3.0	4.0	6.0	8.0	10.0		1.5	2.0	2.5	3.0	4.0	6.0	8.0	10.0		1.5	2.0	2.5	3.0	4.0	6.0	8.0	10 0

TABLE I. Concluded.

				T	T			
1.0		.565	.565	292	.565	.565	.565	. 565
.8		.435	.355	. 320	.290	.290	.290	. 290
۲.		.425	.333	087.	.211	.205	.204	.204
9.		.435	. 335	012.	.180	.151	.145	.140
.5		.451	.350	187.	.170	.121	.105	. 095
4.		.470	. 374	. 302	.170	.109	.070	.055
.3		.497	.404	. 333	.175	.100	.060	.041
.2	= 1.2	.552	.450	015.	.190	.095	.050	.030
.1	μ ⁸	.652	.521	319	.205	.092	.040	.025
0.		.820	.640	. 350	.225	.095	.040	, 025
Rn/Rb	q	1.5	2.0	0.2	4.0	6.0	8.0	10.0
							I	





Figure 13. Calculated Values of Nose Pressure Drag Presented as a Function of Nose Length and Nose Bluntness for Varying Mach Numbers



Figure 13. Continued







Figure 13. Concluded



Nose Drag Coefficient, CA

rapidly increases with decreasing nose lengths when these lengths are less than 1.5 calibers. As the body becomes more blunt, the flow expands more rapidly and a larger pocket of supercritical flow is formed. It is this phenomena which causes the nose drag increase with decreasing nose length.

The nose drag coefficient versus nose radius with nose length as a parameter is presented in figures 13b, d, f, h. These results for each Mach number are obtained by plotting the results of the faired curves in figures 13a, c, e, g for a constant length. This method enables the smoothest set of curves from the least amount of calculated data to be obtained. The final coefficient values from these figures are presented in Table I. This table is then incorporated into subroutine TRANS of the NSWC computer code.

Figure 14 gives the wave drag obtained by solving the transonic perturbation equation and the wave drag obtained by solving the full Euler equations for various tangent ogive nose lengths throughout the transonic Mach number range. The new results extend the lower end of the nose length curves from 1.5 calibers to 0.75 calibers.

To test the accuracy of the new method for calculating the nose drag, a suitable set of test cases were run and compared with an available experiment.⁹ These cases involved variations in nose bluntness, nose length, and transonic Mach numbers and are presented in figures 15-17.

In all three test configurations the afterbody is 10 calibers in length and the nose bluntnesses (R_n/R_b) were 0.0, 0.250, .50, and .750 calibers.

The following observations can be made:

1. For the pointed tangent ogive body the revised computer program results compare more favorably with experiment than the previous computer program results. This improvement is as high as 39 percent over the previous result for a pointed 2 caliber nose length projectile at a free stream $M_{\infty} = 0.8$.







b) Two caliber tangent ogive body with a nose bluntness of .125.









d) Two caliber tangent ogive body with a nose bluntness of 0.375

Figure 15. Concluded



b) Three caliber tangent ogive body with a nose bluntness of 0.125







Figure 16. Concluded



















Figure 17. Concluded

- 2. For the larger nose bluntnesses the revised computer program results again compare more favorably with experiment than the previous results. The maximum improvement of 27 percent occurs at a free stream $M_{\infty} = 0.8$, a nose bluntness, $R_n/R_b = .375$, and a nose length $L_n/2R_b = 4$.
- 3. For transonic Mach numbers less than 0.85 the revised computer program gives results which are closer to experiment.
- 4. The experimental points were obtained in laminar flow whereas the calculations are performed assuming turbulent flow. This could explain the discrepancy between the theory and the experiment.

Computer Program Alterations

There have been no changes in the input/output portions of the NSWC code. The changes in TRANS and MAIN, and the additional subroutines necessary are documented below.

INTERD, INTER3

These subroutines are used to interpolate for the value of a function at a given point. Three point Lagrange interpolation is used.

SUBROUTINE INTER	{D(TX, TY, X, Y, N, J)	
DIMENSION TALLOU	1),14(100)	
	and the second	
	160 TO 1	
IFIT GT (Nall)		
CALL INTERSILATE	(I-1), TY(T), TY(I+1), TY(I-1), TY(T), TY(TA	
RETURN		
END		
The second s		
	· ·	
SUBROUTINE	E INTERS(X, X1, X2, X3, F1, F2, F3, F)	
C S POINT I	LAGRANGE INTERPOLATION FORMULA	
CXI .LE. 1	X .LE. X3	
Ais(X=X2)	*(X=X3)	
A2=(X=X1):	*(X=X3)	
A3=(X=X1):	*(X=X2)	
01=(X1=X2))*(X1=X5)	
11x=2x)=20)*(X2=X3)	
D3=[X3=X1)*(x3=x2)	
any and a proper state of the second s		
C1=A1/01		
C1=A1/01 C2=A2/02	·	
C1=A1/D1 C2=A2/D2 C3=A3/D3		
C1=A1/D1 C2=A2/D2 C3=A3/D3 F=C1=F1+C2	2*F2+C3*F3	
C1=A1/D1 C2=A2/D2 C3=A3/D3 F=C1=F1+C2 RETURN	2*F2+C3*F3	

THIS PAGE IS BEST QUALITY PRACTICABLE FROM COPY FURNISHED TO DDC The changes in TRANS are shown by a solid line down the left hand margin. A sample input data sheet is shown in figure 18 where an accompanying sketch with the geometric parameters describing the configuration is also given. Figure 19 gives the sample output for the test case. C_D for $0.5 < M_{\infty} < 0.8$ is reduced quadratically to zero from a table value at $M_{\infty} = 0.8$. This and other improved modifications to program changes in the original NEAR TR 153 were made by L. Devan at NSWC.

CONCLUSIONS AND RECOMMENDATIONS

 An accurate implicit axisymmetric Euler equation solver has been used to obtain nose drag coefficients for transonic flow over sphere ogive cylinders.

2. A matrix of drag values was calculated for the following parameters

$$0.8 \le M_{\infty} \le 1.2$$
$$0 \le R_n/D \le .5$$
$$.75 \le L_n/D \le 10$$

3. The computed matrix was incorporated into the NSWC computer code as a table lookup. Several test cases were run and compared with experiment.

4. It is recommended the Euler equation solver be used to calculate drag coefficients for bodies with surface discontinuities, and be used to calculate drag coefficients for sphere-ogive bodies in the Mach number range 0.5 to 0.8.

```
CHANGE OCCURS AT MAIN.8
     CONNON/CEO4/KyFyRR
      COMMON/GEO4/K.F.RR.RREF.TH1
CHANGE OCCURS AT MAIN. 326
     -OA-I-J-J
     -00 10-5
      GO TO 2
   51 CA4= 0.012*(THE1-10.)
     -60 TO 5
      GO TO 2
   19 IF(VOVS. LT. 1.19) GO TO 2
      CALL HYBRID
      GO TO 5
      CALL TRANS
    2 IF(VOVS. LE. .5160 TO 5
      CALL TRANS
CHANGE OCCURS AT BASEP.6
     -COMMON/SEO4/K,F,RR,RREF
      COMMON/GEO4/K,F,RR,RREF,TH1
CHANGE OCCURS AT BLUNT.6
     COMMON/SEO4/K.F. RR. RREF
      COMMON/GEO4/K.F.RR.RRFF.TH1
CHANGE OCCURS AT GEOM.6
     GONMON/GEOU/K.F.RR.RREF
      COMMON/GEO4/K, F, RR, RREF, TH1
CHANGE OCCURS AT HYBRID.5
     -COMMON/GEO4/K.F.RR.RREF
      COMMON/GE04/K,F,RR,RREF,TH1
CHANGE OCCUPS AT NEWT.6
      CONMON/GEOW/K.F. BR. RREF
      COMMON/GEO4/K, F, RR, RREF, TH1
CHANGE OCCURS AT NORMEC.6
     CONTON/GEO4/K,F,RR, REF
      COMMON/GEO4/K.F.RR.RREF.TH1
CHANGE OCCURS AT SIMP.6
     COMMON/GEO4/K,F,RR,RREF,TH1
CHANGE OCCURS AT SKINF.6
      CONMON/GEO4/K.F.RR.RREF
      COMMON/GF04/K.F.RR.RREF.TH1
      SUBROUTINE TRANS
      CUMMON/GEOM/RP(6), X(30), R(30), C2, N, NSHAPE, N1, N2, X9(225), RB(225)
      COMMON/GEO1/ RBP(225), PETA
      COMMON/GEO2/NN1,NN2,NN3,NN4,NFL,NB_JNT,NN,NNI, IPRINT,NN1A
      COMMON/GEO3/VOVS, AL. XM, YM. XINT, YINT, NNIA
      COMMON/CPY/ CPV(225.7), JA. JB
    COMMON/GEO4/K,F,RR,RREF,TH1
      COMMON / 152/ SUM1. SUM2. SUM3. SUM4. SJ45. SU46. CABLH
      COMMON/LENG/ BL . ANL . ALA
      COMMON/WAVE/CABL, CN3L. CMBL, CAW, SNW, SMW
      DIMENSION CA15(4.10), CA2(4,10), CA25(4.10), CA3(4.10), CA4(4.1)).
                 CAE (4, 10), CAB(4,10), CA10(4, 10), CA15R(4), CA2 R(4), AM(4),
                 CA3 R(4), CA4 R(4), CA6 R(4), CA8 P(4), CA10R(4), CD(10).
                 A0(10), A1(10), A2(10), A3(10), A4(10), A5(10), A6(10), A7(10)
      DIMENSION CA25R(4)
      DATA (AM(T), I=1,4)
                                      1.8,.35,1.05,1.2/
      DATA((CA15(I.J), I=1.4), J=1,10)/. 422..518.67.82.29.4.541.652.
     1.198..311..441..552..130..250..365..497..089..211..335..47..065.
     1.19..31..451..36..18..291..435..059..18..285..425..06..184..3..435
     ),.38,.278,.41,.565/
      DATA((CA2 (I,J),I=1,4),J=1,16)/.29,.395,.505,.64,.2,.295,.409,.521
     1..13..223..339..45..081..175..29..434..051..144..26..374..04..13.
```

44

1.24..35..04..123..229..335..045..128..223..333..055..15..24..355.

```
1.68..278..41..565/
  DATA ((CA25(I,J),I=1.4),J=1.10)/.21).262..39.468.14.2.321.411
 1,.088,.15,.27,.37,.051,.115,.23,.333..03..091,.202,.302,.02,.08,
 1.18..281..022..081..17..27..031..091..17..28..042..121..2..32..08.
 1.278..41..505/
  DATA((CA3 (1,J), I=1,4). J=1,10)/.151..198..302..350..101..15..25.
 1.319,.065,.11,.21,.29,.035,.075,.19,.253,.02,.055,.16,.245,.018,
 1.047..145..231..022.049..135..23..031..065..13..24.042..108.
 1.175..302..08..278..41..565/
  DATA((CA4 (I,J),I=1,4),J=1,10)/.1,.130,.211,.225,.070,.091,.175.
 1.205..04..361..14..19..02..042..115..175..01..04..1..01..01..031,
 1.035..17..02..048..1..18.031..065..121..211.042..108..175..29.
 1. 18 . . 278 . . 41 . . 565/
 DATA((CA6 (I,J), I=1,4), J=1,1))/.068,.080,.105,.095,.041,.049,.085,
).092,.02,.038,.067,.095,.007,.032,.055,.1,.006,.031,.051,.109,.01,
  1.031,.061,.121,.02,.048,.082,.151,.031,.065,.12,.205,.042,.108,
 1.175..29..08..278..41..565/
  DATA ( (CA8 (I.J), I=1,4), J=1, 10)/.05,.04,.04,.04,.029,.031..035.04,
 1.012,.021,.03,.05,.007,.028,.03,.06,.006,.028,.038,.07,.01,.031,.05,
 1.105..02..048..07.145..031..065..12..204..042..108..175..29..08.
 1.279..41..555/
   DATA((CA13(I,J), I=1.4), J=1.1)/ .041,.025,.025,.025,.02,.020,.025,.025,
  1.008,.015,.025,.03,.007,.020,.025,.041,.006,.021,.025,.055,.01,.031,
 1.04,.095,.02,.048,.07,.14..031,.065,.12,.204,.042,.108,.175,.29,
 1.08..278..41..565/
  C83=3.
   IF(RSP(NN).LT.-C.0001) GO TO 87
   GO TO 58
87 VOV=VOV5-.0498
   IF(VOV.LT.1.) GO TO 89
  AREF=3.14159*RREF**2
   IF (NSHAPE.LT.4) GO TO SA
   IF(NN1A.EG.2) GO TO 1
   IF(N3LUNT.E7.2) GO TO 1
   1=NN2+1
  GO TO 2
  J= NN3+1
2 00 13 L= J. W
   XX=XB(L)-XB(J)
   DELTA= ATAN(1./(2.*ANL))
   IF(R3P(J-3).LT.R3P(1)) DELTA=ATAN(.2/ANL)
  GA44=1.4
  C1=1.+GAMA
   CU=SQPT(C1)
   C3=VOV ++2
   C4=1.-C3
  C5=C4/(C1*C3)
   66=3.*9ELTA/ (2.*CG)
  C7=25.*C1*VOV **(2./3.)
   C8=.5*C4/(C1*C3)
   C9=1.25*C5**2
  C1J=2.*C5/(VOV **(2./3.))*C6**(2./3.)
  C11=(C6/VOV )**(4./3.)
  CS2=C7+(C8+(C9+C10+C11)++(.5))
   C=SORT (CSO)
  Y=2. *ALA +2. *XX
           =.4*(Y-C)/SORT(C1*VOV **(2./3.))*(.04*(Y-C)**2/(C1*VOV **
  CP1
 1(2./3.)) -C4/(C1*C3))**.5
   IF(Y.GT.C) SP1=6.
  DELTA=-RBP(L)
  GA44=1.4
  C1=1.+GAMA
  CU=SOFT(C1)
  C3=VOV **2
  C4=1.-C3
  C5=C4/(C1*C3)
```

```
C6=3.*DEL 14/ (2.*CU)
     C7=25.*C1*VOV **(2./3.)
     C8=.5*C4/(C1*C3)
     C9=1.25*C5**2
     C10=2. *C5/(VOV **(2./3.))*C6**(2./3.)
     C11=(C6/VOV )**(4./3.)
     CSQ=C7+(C8+(C9+C10+C11) ++(.5))
      C=SORT (CSQ)
     Y=XX#2.
     CPV(L, 1)=.4*(Y-C)/SQRT(C1*VOV **(2./3.))*(.04*(Y-C)**2/(C1*VOV **
    1(2./3.)) -C4/(C1*C3))** .5-DELTA**2+3-1
     IF (Y.GT.C) CPV(L,1)=CP1
 15
     00 10 K1=1,7
     CPV(L, K1)=CPV(L,1)
   10 CONTINUE
     JA=J
      JB=NN
      SUM1=0.
      SU42=0.
      SU43=0.
      CALL SIMP
     CBD=2. *SUM1/AREF
     V0=V0V-1.
      IF(VO.LE.0.06) C91=C90
     V1=VOVS
 89
     CONTINUE
      IF(VOVS.GT.0.95) GO TO 90
     C83=0.
     GO TO 88
     CB0=CB1* (VOVS-.95)/ (V1-.95)
 90
     CONTINUE
 88
C .... TABLE LOOKUP IS BASED ON LN/RB. RN/28
      ANL1=ANL
      ANL = ANL + RR* (-1.+1./(1.+SIN(TH1)))
      ANL=2. #ANL
      VV=VOVS
      IF(VOVS. LT. .8)VOVS=.8
C
C+++
              С
      DETERMINE RNORB, THE CORRECT RADIUS OF THE NOSE, TO
C
C
     BE USED IN TABLE LOOKUP.
C
      RNORB=2.0*R(1)/COS(TH1)
C
C
      WRITE (6.200) VOVS.ANL. RNORB
  200 FORMAT (* *, * MACH NO., NOSE LENGTH, RN/23*, 3F15.10.///
           . AS AND DRAG !!
    1
     IF (ANL.GT.10.) ANL=10.
      IF (ANL. LT. 1.5) ANL=1.5
      IF(RNORB.GE.0.4) GO TO 21
      J1=1
      J2=5
   GO TO 22
21 IF(RNORB.LE.0.5) GO TO 23
      J1=5
      J2=10
      GO TO 22
   23 J1=4
      J2=8
   22 DO 14 J=J1,J2
DO 13 I=1,4
      IF (ANL .GT.4.) GO TO 24
      CA15R(I)=CA15(I,J)
```

```
GA2 R(1)=GA2 (1. J)
      CA25R(I)=CA25(I,J)
   24 CA3R(I)=CA3(I,J)
      CA4 R(I)=CA4 (I,J)
      IF(ANL.LE.4.) GO TO 13
CA6 R(I)=CA6 (I,J)
      CA8 R(I)=CA8 (I.J)
      CALOR(I)=CALD(I.J)
      CONTINUE
13
      IFIANL .GT.4.) GO TO 26
      CALL INTERS(RNOR9,.3..4,.5,.6,.7,C)(4),CD(5),CD(6),CD(7),C)(8),
 19
                   CAN)
      CALL INTERDIAM, CA15R, VOVS, AD(J), 4, 21
      CALL INTERDIAM, CA2 R. VOVS. A1 (J) . 4,2)
      CALL INTERDIAM, CA25R, VOVS, A2(J), 4, 2)
   26 CALL INTERDIAM, CA3 R. VOVS, A3(J) . 4. 2)
      CALL INTERDIAM, CA4 R. VOVS. A4(J), 4,2)
      IF (ANL.LE.4.) GO TO 25
      CALL INTERDIAM, CA6 R. VOVS, A5(J), 4,2)
      CALL INTERDIAM. CA8 R. VOVS. A6(J) . 4. 2)
      CALL INTERD(AM, CA10R, VOVS, A7(J), 4.2)
      GO TO 12
   25 CALL INTERSIANL.1.5.2..2.5,3.... ADIJI.A1(J).A2(J).A3(J).A4(J).
     )
                   CO(J))
      GO TO 14
      CALL INTERS(ANL, 3., 4., 6., 8., 10., A3(J), A4(J), A5(J), A6(J), A7(J),
12
     1
                   ((1)00
 14
      CONTINUE
      IF (RNOR9 .GE. 0.4)60 TO 16
      CALL INTERS(RNOR8,0...1..2,.3,.4,C)(1),C)(2),CD(3),CD(4),CD(5),
     )
                   CAN)
      GO TO 17
16
      IFIRNORB .LE. 0.5) GO TO 19
      CALL INTERS(RNOR8,.5,.6..7,.8,1.,C)(6), 30(7), CD(8), CD(9), C)(10),
     )
                   CAN)
      GO TO 17
   17 IF(VV .GE .. 8)GO TO 18
      CAN=CAN* ( (VV -. 51/.31**2
      VOVS=VV
   18 CAW=CAN+CBO+CAW
      WPITE(6,215) CAN, CAW
  215 FORMAT (* *, *NOSE DRAG AND WAVE DRAG*, 2F15.10)
      ANL = ANL1
  99 RETURN
      END
CHANGE OCCURS AT WAVE.8
      CONTON/SEOW/KAF, RR, RREF
      COMMON/GEO4/K, F, RR, RREF, TH1
```





000FT
and the second
1673
LB-SEC/FT2
NOSE TIP
and the second
The second second
and the second second
- marine
and the second s
al martine prove
A State of the second

Figure 19. Sample Output for Tangent Ogive Configuration of Figure 18

THIS PAGE IS BEST QUALITY PRACTICABLE

			DODY ANI	L FORCE CONT	RIBUTIONS		
MACH NO.	KIN FRIC	TION BASE	PRESSU	RE	PRESSURE	PROTRUSIONS	TOTAL
					all a second	i de la ser .	a Aria de Maria
1.500	.003.	3	.1910		-1504	0.0000	.4046
1.200	.068	1	.2180		.1524	0.0000	4384
1.050	070	8	.2190	and an and a start	.1151	0.0000	4048
1.000	.071	7	.2090		.0963	0.0000	.3770
.950	.072	5	.1844		.0660	0.0000	.3231
.800	.075	5	.1350		.0767	3.0000	.2872
.000	.079		.1285		.0085	0.0000	.2168
			TOTAL	STATIC AERO	DÝNAMICS(F	ORCE/ALPHA)	
MACH NO.	ÇD	ÇN	CL	CM	CNAL	CM	AL XCP/D
1,500 .	4046	0.0000	0.0000	0.000	0.000	0.	0000.000
1.200 .	4384	0.0000	0.0000	0.000	0.000	0.	000.000
1.050 .	4048	0.0000	0.0000	0.000	0.000	0.	000.000
1,000 .	3770	0.0000	0.0000	0.000	0.000	0.	0000.000
.950 .	3231	0.0000	0.0000	0.000	0.000	0.	000.000
.800 .	2872	0.0000	0.0000	0.000	0.000	0.1	000.000
.600 .	2083	0.0000	0.0000	0.000	0.000	0.	000.000
		CONF	IGURATIC	IN DYNAMIC DE	RIVATIVES		
MACH ND	CLP	time and		CHQ+CMAD		CNPA1	CNPA5
1.50	042			-369,240		0.000	0.000
1.20	042			-369.240 .		0.000	1 0.000
1.05	043			-369,240	a Standard C	0.000	0.000
1.00	044		and the state of the	-369,240		0.000	0.000
.95	046	- Andrews and a	And the second of the	-369,240	and an and the second second	0.000	0.000
.80	-,066			-369.240	With the state of the state	0.000	0-000
. 60		M. T. A. C. M. C. M. C.		-369.240	and the state of the	0.000	

Figure 19. Concluded

REFERENCES

- F. G. Moore and R. C. Swanson, Aerodynamics of Tactical Weapons to Mach Number 3 and Angle of Attack 15°. Part I - Theory and Application, NSWC/DL TR-3584, Feb. 1977. Part II - Computer Program and Usage, NSWC/DL TR-3600, Mar. 1977.
- K. Aoyoma and J. M. Wu, On Transonic Flow Field Around Tangent Ogive Bodies, AIAA Paper 70-189, presented at AIAA 8th Aerospace Sciences Meeting, New York, N.Y., Jan. 19-21, 1970.
- 3. D. S. Chaussee, S. S. Stahara, and J. R. Spreiter, Application of an Axisymmetric Implicit Blunt Body Procedure: "Computation of Solar Wind Flows Past Terrestrial Planets," AIAA Paper 77-700 presented at the AIAA 10th Fluid and Plasma Dynamics Conference, Albuquerque, New Mexico, June 27-29, 1977.
- R. M. Beam and R. F. Warming, An Implicit Finite-Difference Algorithm for Hyperbolic Systems in Conservation-Law Form, J. Comp. Phys., Vol. 22, no. 1, Sept. 1976.
- 5. D. S. Chaussee, On the Transonic Flow Field Surrounding Tangent-Ogive Bodies with Emphasis on Nose Drag Calculations, AIAA Paper 78-212, to be presented at AIAA 16th Aerospace Sciences Meeting, Huntsville, AL, January 16-18, 1978.
- C. P. Kentzer, Discretization of Boundary Conditions on Moving Discontinuities, Proceedings of the Second International Conference on Numerical Methods in Fluid Dynamics, Lecture Notes in Physics, Vol. 8, edited by M. Holt, Berkeley, CA, September 15-19, 1970, pp. 108-113.
- P. D. Thomas, M. Vinokur, R. Bastionon, and R. J. Conti, Numerical Solution for the Three-Dimensional Hypersonic Flow Field of a Blunt Delta Body, AIAA Journal, Vol. 10, no. 7, July 1972, pp. 887-894.
- T. Hsieh, Flow Field Study About a Hemisphere Cylinder in Transonic and Supersonic Mach Number Range, AIAA Paper 75-83, presented at AIAA 13th Aerospace Sciences Meeting, Pasadena, CA, January 20-22, 1975.

9. C. B. Butler, E. Sears, and S. G. Pallas, Aerodynamic Characteristics of 2, 3 and 4-Caliber Tangent-Ogive Cylinders with Nose Bluntnesses of 0.00, 0.25, 0.50 and 0.75, at Mach Numbers from 0.6 to 4.0, AFATL TR 77-8, January 1977.

GLOSSARY OF TERMS

A	Jacobian matrix defined in Equation 4, = $\frac{\partial \hat{E}}{\partial \hat{u}}$	
в	Jacobian matrix defined in Equation 4, = $\frac{\partial \hat{\mathbf{F}}}{\partial \hat{\mathbf{F}}}$	
с	speed of sound = $(\gamma p/\rho)^{1/2}$ ∂u	
C	drag coefficient	
C_	pressure coefficient	
P dy	space increment	
dt	time increment	
D	drag	
	energy per unit volume	
F	matrix of conservative variables defined in Equation 1	
ê	$\frac{1}{12} \frac{1}{12} \frac$	
-	$(\xi_t) + \xi_x + \xi_y)/3$	
r ≏	matrix of conservative variables defined in Equation 1	
F	$(\eta_t U + \eta_x E + \eta_y F)/J$	
н	source matrix defined in Equation 1	
I	identity matrix	
j	$j = 0$ 2-D flow; $j \approx 1$ axisymmetric flow	
J	Jacobian	
^L n	length of nose	
м	free stream Mach number	
P	pressure	
q	dynamic pressure = $\frac{1}{2}\rho_{\infty}q_{\infty}^2$	
q ²	total velocity vector squared	
r _b ,R _b	radius of the cylindrical afterbody	
r _n ,R _n	radius of the spherical nose	
S	smoothing term defined by Equation 7	
Sref	reference area = πr_b^2	

t	time
u	velocity component in x-direction
U	matrix defined in Equation 1
û	U/J
v	velocity component in y-direction
x	coordinate direction in physical plane
У	coordinate direction in physical plane
Уb	radius of the body
Y	term included in source term, H of Equation 1
Ŷ	ratio of specific heats, 1.4 in this study
δ	central difference operator in Equation 6; shock angle in figure 8
ε	smoothing coefficient, $0 \le \varepsilon \le 0.4$
n	coordinate direction in computational plane
ξ	coordinate direction in computational plane
ρ	density
σ	eigenvalue defined in Equation 5
τ	time
φ	meridional angle defined in figure 2
Subscr	ipt
ъ	body
i	increment
j	ξ-direction
k	n-direction
n,N	nose
Supers	cript
n	time direction
()	averaging

DISTRIBUTION

Commander Naval Sea Systems Command Washington, DC 20360 ATTN: SEA-03 (Mr. Lionel Pasiuk) Library Commander Naval Air Systems Command Washington, DC 20361 ATTN: AIR-320 (Mr. Bill Volz) AIR-320 (Dr. H. Mueller) AIR-532 Library Chief of Naval Research Arlington, VA 22217 ATTN: Mr. Lawrence E. McCullough Mr. Dave Seigel Dr. Bob Whitehead Dr. R. J. Lundegard Mr. Mort Cooper Mr. Ralph Cooper Library Chief of Naval Operations Pentagon Washington, DC 20350 ATTN: OP-098 Library Commander Naval Material Command Washington, DC 20360 ATTN: MAT-032 (Mr. Sid Jacobson) Dr. John Huth Library Commander Naval Weapons Center China Lake, CA 93555 ATTN: Mr. Ray Van Aken Mr. D. Meeker Mr. Kinge-Okauchi

Library

(2)

(2)

(2)

(2)

(2)

Commander Pacific Missile Test Center Point Mugu, CA 93041 ATTN: Mr. Joe Rom Library

Commander David W. Taylor Naval Ship Research and Development Center Bethesda, MD 20084 ATTN: Dr. T. C. Tai Library

Commander Naval Air Development Center Warminster, PA 18974 ATTN: Mr. Bill Langen Library

Commanding Officer Naval Ordnance Station Indian Head, MD 20640

Commandant of the Marine Corps Headquarters, Marine Corps Washington, DC 20380

Commander Naval Air Engineering Center Aeronautical Structures Department Lakehurst, NJ 19112

Commander Naval Air Test Center Patuxent River, MD 20670 ATTN: Mr. Ron Wilson Library

Commander Naval Coastal Systems Laboratory Panama City, FL 32401

Commander Naval Ocean Systems Center San Diego, CA 92135

Commander Naval Underwater Systems Center Newport, RI 02480 (2)

(2)

(2)

(2)

(2)

(2)

Naval Research Laboratory Washington, DC 20375 Superintendent U. S. Naval Academy Annapolis, MD 21402 ATTN: Head, Weapons Department Head, Science Department Library Superintendent U. S. Naval Postgraduate School Monterey, CA 95076 ATTN: Head, Mechanical Engineering Department Head, Department of Aeronautics Library Chief of Naval Research Department of the Navy Washington, DC 20360 Director Naval Strategic Systems Projects Office (PM-1) Department of the Navy Washington, DC 20360 Officer in Charge U. S. Naval Scientific and Technical Intelligence Center U. S. Naval Observatory Washington, DC 20360 Commander Marine Corps Development and Education Command Quantico, VA 22134 ATTN: Director, Development Center S&R Division Air Operations Division Ground Operations Division Library U. S. Army Armament Research and Development Command Dover, NJ 07801 ATTN: Mr. E. F. Friedman Mr. Henry Hudgins Mr. M. Cline Mr. A. Loeb Mr. Mertz Library

(2)

(2)

(2)

(2)

(2)

Director, U. S. Army Ballistic Research Laboratory Aberdeen Proving Ground, MD 21005 ATTN: Dr. C. H. Murphy Mr. L. McAllister Mr. A. Platou Mr. B. McCoy Library

President U. S. Army Field Artillery Board Fort Sill, OK 73503 ATTN: Marine Corps Liaison Officer Library

Commander U. S. Army Material Development and Readiness Command 5001 Eisenhower Avenue Alexandria, VA 22333

Commander Frankford Arsenal Philadelphia, PA 19137 ATTN: Mr. W. Gadomski Library

Commander Harry Diamond Laboratories 2800 Powder Mill Road Adelphi, MD 20783 ATTN: Technical Library

Commander U. S. Army Combat Development Command Field Artillery Agency Fort Sill,OK 73503

Commander U. S. Army Missile Command Redstone Aresenal, AL 35809 ATTN: DRSMI (Mr. Ray Deep) DRSMI (Dr. D. J. Spring) Library

AF Office of Scientific Research Washington, DC 20330 ATTN: Library (2)

(2)

(2)

(2)

(2)

(2)

Headquarters Air Force Systems Command Andrews Air Force Base, MD 20331 Headquarters, USAF Washington, DC 20330 U. S. Air Force Systems Command Regional Offices c/o Department of the Navy Washington, DC 20360 Air Force Armament Laboratory Eglin Air Force Base, FL 32542 ATTN: Dr. D. Daniel Dr. S. G. Pallas Mr. C. Butler Dr. Lijewski Mr. C. Mathews Mr. K. Cobb Mr. E. Sears (2) Library **USAF** Academy Colorado Springs, CO 80912 (2)Air Development and Test Center (2) 7 Eglin Air Force Base, FL 32542 Arnold Engineering Development Center USAF Tullahoma, TN 37389 ATTN: Mr. J. Usselton Mr. W. B. Baker, Jr. (2) Library Edwards Air Force Base Edwards, CA 93523 ATTN: Flight Research Center Rocket Propulsion Laboratory (Maj. Washburn) (2) Library Wright Patterson Air Force Base Dayton, OH 45433 ATTN: Aeronautical Systems Division (2) Aeronautical Research Laboratory Air Force Flight Dynamics Laboratory FGC (Mr. E. Flinn) (Dr. G. Kurylowich) (Dr. V. Hoehne) FX (Mr. Mel Buck) (2) Library

Advanced Research Projects Agency Department of Defense Washington, DC 20305

Director Defense Research and Engineering Department of Defense Washington, DC 20305 ATTN: R&AT Office (Mr. B. Osborne) Library

Headquarters, NASA Washington, DC 20546

NASA George C. Marshal Flight Center Huntsville, AL 35804

NASA Goddard Space Center Greenbelt, MD 20771

NASA Lewis Research Center Cleveland, OH 44101

NASA Ames Research Center Moffett Field, CA 94035 ATTN: Mr. Vic Peterson Mr. John Rakich Library

NASA Langley Research Center Langley Station Hampton, VA 23365 ATTN: Dr. Roy C. Swanson, Jr. Mr. Bud Bobbitt Mr. Jerry South Mr. Leroy Spearman Mr. C. M. Jackson, Jr. Mr. W. C. Sawyer Library

Applied Physics Laboratory Johns-Hopkins University 8621 Georgia Avenue Silver Spring, MD 20910 ATTN: Dr. L. L. Cronvich Mr. Edward T. Marley Dr. Gordon Dugger Library (2)

(2)

(2)

(2)

ARO Inc. Arnold Air Force Station, TN 37389 ATTN: Dr. Tsuying Hsieh

Sandia Laboratories Albuquerque, NM 87115 ATTN: Division 1331 (Mr. Robert LaFarge) Library

Sandia Laboratories Box 969 Livermore, CA 94550 ATTN: Division 8158 Library

The Rand Corporation 1600 Main Street Santa Monica, CA 90406

Stanford Research Institute Menlo Park, CA 94025 ATTN: Dr. Milton Van Dyke Library

(2)

Raytheon Company Spencer Laboratory Burlington, MA 01803 ATTN: BOX SL 7162 (Mr. Steve Pearlsing)

McDonnell Douglas Astronautics Co. (West) 5301 Bolsa Avenue Hunington Beach, CA 92647 ATTN: Mail Station 13-2 (Dr. Jim Zerikos)

Vought Corporation P. O. Box 5907 Dallas, TX 75222 ATTN: Dr. W. B. Brooks Mr. F. Prilliman

Boeing Computer Services, Inc. P. O. Box 24346, M/S 8F-37 Seattle, WA 98124 ATTN: Mr. Roger Wyrick

Lockheed Missiles and Space Co., Inc. P. O. Box 1103, W. Street Huntsville, AL 35807 ATTN: Mr. B. H. Shirley

Lockheed Missiles and Space Co., Inc. Department 81-10, Bldg. 154 Sunnyvale, CA 94088 ATTN: Dr. Lars E. Ericson Mr. P. Reding Nielsen Engineering and Research, Inc. 510 Clyde Avenue Mountain View, CA 94043 ATTN: Dr. Jack Nielsen (10) Mr. V. L. Pianta P. O. Box 1201 San Jose, CA 95108 Virginia Polytechnic Institute and State University Department of Aerospace Engineering Blacksburg, VA 24060 ATTN: Prof. J. A. Schetz Prof. A. H. Nayfeh (2) Library North Carolina State University Department of Mechanical and Aerospace Engineering Box 5246 Raleigh, NC 27607 ATTN: Prof. F. R. DeJarnette (2) Library University of Tennessee Space Institute Tullahoma, TN 37388 ATTN: Dr. J. M. Wu Library (2) Defense Documentation Center Cameron Station Alexandria, VA 22314 (12)Library of Congress Washington, DC 20390 ATTN: Gift and Exchange Division (4) Defense Printing Service Washington Navy Yard Washington, DC 20374

LOCA	<u>т</u>			
E41 G G20 G23 G30 G40				
G41	(Mr.	в.	Piper, Mr. G. Graff)	
K				
K02				
K04				
K05				
K20				
K21	(Dr.	J.	Sun, Dr. F. G. Moore)	(20)
K22				
K23	(Mr.	J.	Mitchell)	
K50		-		
K80	(Mr.	S.	Hastings)	101
K81	(Dr.	м.	Krumins)	(2)
K81	(Mr.	r.	Baltakis)	
K82	(Dr.	J.	Goeller, Dr. N. Sheets,	
	Mr.	F.	Regan)	
R	1-	-		
R44	(Dr.	J.	SOLOMON)	(2)
X210	,			(2)