| 1 | AD-A05          | 3 271<br>SIFIED | WESTIN<br>EVALUA<br>MAY 78 | GHOUSE<br>TION OF<br>F J G | ELECTRI<br>FRICTI<br>URNEY, | C CORP<br>ON PROP<br>A M ADA | PITTSBU<br>ERTIES  | AFML-TR-   | ADVANCE<br>T FORM | ED ENE-<br>ING LUB<br>F33615 | -ETC F<br>RICANTS<br>-77-C-5   | /G 11/6<br>BETC<br>099<br>NL | ່ເບາ   |   | /        |
|---|-----------------|-----------------|----------------------------|----------------------------|-----------------------------|------------------------------|--|--|-------------------|------------------------------|--|------------------------------|--|---|----------|
| - | OF  <br>A058271 |                 |                            |                            |                             |                              | enstime.<br>etcaso   |  |                   |                              | and an and a second sec |                              | Artentorian<br>Martinetta<br>Martinetta<br>Martinetta<br>Martinetta<br>Martinetta<br>Martinetta<br>Martinetta<br>Martinetta  | TORNESSE<br>STREET                                  |          |
|   |                 |                 |                            | pontoone.                  |                             |                              | Thermotory<br>Thermotory<br>Statematics<br>Statematics<br>Statematics<br>Statematics | An on the New York Street Stre |                   |                              |  |                              |  |   |          |
|   |                 | A               |                            |                            | Sh-                         |                              |  | X  | X                 |                              |  |                              | Transfer and the second | Para Di Pristr<br>Para Li Pristr<br>- di Statistica |          |
| 1 |                 |                 |                            |                            |                             |                              |  |  |                   |                              |  |                              |  |   |          |
|   | Tee White       |                 |                            |                            | far Öffitt                  | Par Dimin                    | END<br>DATE<br>FILMED<br>10-78<br>DDC  |  |                   |                              |  |                              |  |   | O hydron |
|   |                 |                 |                            |                            |                             |                              |  |  |                   |                              |  |                              |  |   |          |
| - |                 |                 |                            |                            |                             |                              |  |  |                   |                              |  |                              |  |   | /        |





AFML-TR-78-66

1

2

ADA 0 582

COPV

AD 1

# EVALUATION OF FRICTION PROPERTIES OF SHEET FORMING LUBRICANTS BY TENSILE DRAWING AND BY RING COMPRESSION

WESTINGHOUSE ELECTRIC CORPORATION ADVANCED ENERGY SYSTEMS DIVISION PITTSBURGH, PENNSYLVANIA 15236

**TECHNICAL REPORT AFML-TR-78-66** 

MAY 1978

Approved for public release; distribution unlimited.

78 08 29

AIR FORCE MATERIALS LABORATORY AIR FORCE WRIGHT-AERONAUTICAL LABORATORIES AIR FORCE SYSTEMS COMMAND WRIGHT-PATTERSON AIR FORCE BASE, OHIO 45433

Summary Report for Period 1 May 1977 to 15 February 1978

#### NOTICE

When government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

This report has been reviewed by the Information Office (OI) and is releasable to the National Technical Information Service (NTIS). At NTIS it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication.

Hunt M. Adain

ÁTTWELL M. ADAIR Project Engineer Metals Processing Group

FOR THE COMMANDER Henry G. GRAHAM

HENRY M. GRAHAM Acting Chief, Processing and High Temperature Materials Branch Metals and Ceramics Division Air Force Materials Laboratory

Copies of this report should not be returned unless return is required by security considerations, contractual obligations, or notice on a specific document.

AIR FORCE/56780/10 August 1978 - 300

Unclassified SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered) READ INSTRUCTIONS BEFORE COMPLETING FORM 9) REPORT DOCUMENTATION PAGE 2. GOVT ACCESSION NO. 3. RECIPIENT'S CATALOG NUMBER REPO AFML-TR-78-66 ERIOD COVERED EVALUATION OF FRICTION PROPERTIES OF SHEET ( Final Technical Report\* 1 May 1977 + 15 Feb 178, FORMING LUBRICANTS BY TENSILE DRAWING AND BY RING COMPRESSION -UMBE 15 AUTHOR(s) TRACT OR GRANT NUMBER(S) F. J. Gurney, Advanced Energy Systems Division F33615-77-C-5099 Westinghouse Electric Corporation, A. M. /Adair, Air Force Materials Laboratory (LLM) PERFORMING ORGANIZATION NAME AND ADDRESS PROGRAM ELEMENT, PROJECT, TASK Westinghouse Electric Corporation 73510817 Advanced Energy Systems Division 62102F Pittsburgh, PA 15236 11. CONTROLLING OFFICE NAME AND ADDRESS REPORT DAT May 1078 Air Force Materials Laboratory NUMBER OF PAGES Wright-Patterson AFB, OH 45433 52 MONLIORING AGENCY NAME & ADDRESS(if different from Controlling Office) 15. SECURITY CLASS. (of this report) Unclassified 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE DISTRIBUTION ST Adain 0 Celease; Distribution Unlimited Approv '7. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) 18. SUPPLEMENTARY NOTES 19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Sheet forming Ring test Lubricants Sheet friction Metalworking 0. ABSTRACT (Continue on reverse side if necessary and identify by block number) Experimental and selected commercially available sheet forming lubricants were evaluated by two friction testing techniques; 1) strip-drawing with only elastic workpiece loads and 2) ring compression testing where plastic deformation of the workpiece occurred. Material and test variables examined were; 1) two workpiece materials A1-7075 and Ti-6A1-4V, 2) eight lubricants coatings, 3) three levels of hold-down pressure and deformation amount, 4) two die roughness conditions, 5) two drawing speeds and 6) two lubricant dryness conditions. The tests were performed at room temperature. DD 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE Unclassified SECURITY CLASSIFICATION OF THIS PAGE (When Date Entere 410 110

### Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered)

Results indicate that the lubricant dryness condition can be a significant factor in friction characteristics of the lubricant. Of the other variables, the lubricant type caused the most influence on the resultant friction characteristics. Quantitative ratings of each lubricants was obtained as a function of the test variables.

> Unclassified SECURITY CLASSIFICATION OF THIS PAGE(When Dete Entered)

#### FOREWORD

This report was prepared by the Westinghouse Electric Corporation, Advanced Energy Systems Division, Pittsburgh, Pennsylvania, under USAF Contract No. F33615-77-C-5099. The project was initiated under Project No. 7351, "Metallic Materials", Task No. 735108, "Processing of Metals", and was administered under the direction of the Air Force Materials Laboratory, Wright-Patterson Air Force Base, Ohio, with Mr. A. M. Adair (AFML/LLM) as Project Engineer.

The work described in this report was carried out between 1 May 1977 and 15 February 1978. Technical support was provided by Westinghouse personnel, T. E. Jones, M. M. Myers, and R. A. Sweeney. Contributions by AFML personnel have been made by A. M. Adair and V. DePierre\*. The various parts of this effort were compiled by Ms. Faye Hickman who also edited and typed the report.

This report was submitted by the author on 15 March 1978.

|                                | na Sala C<br>Sal Salar C<br>Salar C |
|--------------------------------|-------------------------------------|
|                                | Contraction of the original         |
| DV .                           |                                     |
| BY                             | NAL TRUTY LUES                      |
| BY<br>INSTRIBUTION<br>Dist. AV |                                     |

\*Deceased

### TABLE OF CONTENTS

| SECTION |                                   | PAGE |
|---------|-----------------------------------|------|
| I       | INTRODUCTION                      | 1    |
| II      | BACKGROUND AND APPROACH           | 2    |
| III     | EXPERIMENTAL PROGRAM              | 4    |
| IV      | RESULTS                           | 6    |
| v       | DISCUSSION                        | 9    |
| VI      | CONCLUSIONS                       | 11   |
|         | REFERENCES                        | 12   |
|         | APPENDIX APPLIED METAL PROCESSING | 29   |

### LIST OF ILLUSTRATIONS

| FIGURE |  | PAGE |
|--------|--|------|
| 1      | Reduction in peak strain at a critical region in stamping of an automobile hood.   | 19   |
| 2      | Photograph of the variable-die-pressure strip-<br>drawing apparatus.   | 20   |
| 3      | Illustrative sketch indicating features of the variable-die-pressure strip-drawing apparatus.  | 21   |
| 4      | Photograph of the strip-draw specimen and the dove-<br>tailed locked interchangeable dies used in the<br>evaluation.                             | 22   |
| 5      | Photograph of test set-up for lubricant evaluation in strip-drawing.   | 23   |
| 6      | Effect of hold-down pressure on friction ratio during<br>strip-drawing where the lubricant was applied just<br>before testing.                   | 24   |
| 7      | Effect of hold-down pressure on friction ratio during strip-drawing where lubricant was cured before testing.                                    | 25   |
| 8      | Effect of very high hold-down pressures on friction ratio of selected lubricants at selected conditions.   | 26   |
| 9      | Effect of variation in die surface condition, lubri-<br>cant curing time and draw speed on the resulting<br>friction ratio of dry film graphite. | 27   |
| 10     | Interface friction factor from various lubricants<br>when deformed plasticity during the ring forge<br>test.                                     | 28   |

ví

### LIST OF TABLES

DACE

| TABLE |   | PAGE |
|-------|---|------|
| 1     | Chemical Composition of Test Material   | 13   |
| 2     | Lubricants Used in the Evaluation   | 14   |
| 3     | Friction Ratios of Sheet Forming Lubricants in<br>Elastic Drawing at Low to Moderate Hold-Down<br>Pressures | 15   |
| 4     | Friction Ratios of Sheet Forming Lubricants in<br>Elastic Drawing at High Hold-Down Pressures               | 16   |
| 5     | Friction Evaluation of Sheet Forming Lubricants<br>from Ring Compression Testing of A1-7075                 | 17   |

vii

#### SECTION I

#### INTRODUCTION

Recent interest in improved production efficiency has resulted in consideration of computer-aided techniques for both design and manufacturing processes. In metalworking operations, a considerable portion of this interest is directed at sheet metal forming operations. The wide scale usage of sheet metal products in common items such as automobiles, stoves, furnaces, air conditioners, etc. attest to the large number of manufacturing organizations involved with this metalworking operation. The large majority of these applications is almost exclusively concerned with the ability to produce style effects without gross fracture and without aesthetically non-pleasing deformation effects such as non-uniform thinning, orange peeling, gathering or buckling. The material for the majority of these sheet metal forming processes is low alloy steels or low alloy aluminums, and the fabrication is almost exclusively conducted at room temperature.

This technology for the forming processes in these common usage items is mostly based on trial and error experiences of the individual sheet metal forming shops(1). Because of this, the ability to transfer experience from one material to another within the same shop or from one shop to another for the same material often results in only limited success. The limited ability to transfer skill capability is the most serious deficiency with this "experience based" technology. The development of a sound scientific or engineering "knowledge base" for this technology is required to alleviate this deficiency.

Development of an engineering "knowledge base" for sheet forming processes is especially desirable for aerospace applications. In aerospace applications, component weight considerations frequently require the sheet product to have load transfer characteristics. Thus, reproducibility of service properties is critically important. The development of an engineering "knowledge base" for these forming processes is also an essential prerequisite to the establishment of a computer-aided and computer-controlled design and manufacturing process for sheet metal forming.

#### SECTION II

#### BACKGROUND AND APPROACH

One of the critical factors limiting the development of a "knowledge base" for sheet forming is the interface condition. The importance of the interface condition in sheet forming operations is well recognized (2-5) and has been shown by Goodwin<sup>(5)</sup> to be a factor which can influence the production of sound or fractured product (see Figure 1). However, despite its importance, the most generally accepted view of the effects of interface friction in these processes is that it can only be determined by trial and error techniques<sup>(6)</sup>.

The use of bench-type evaluations of lubricants has generally been considered to be of only marginal usefulness(6). It was only very recently that any success has been reported in quantifying the effects of friction in sheet forming operations. This initial effort by  $Ghosh^{(4)}$  was directed primarily at materials and lubricants for use during room temperature stamping for automotive industry applications. The applicability of this initial effort to computer-aided processing is yet to be determined, but it is significant in that an attempt to quantify the role and effects of the interface condition is now underway.

The use of the ring compression test for evaluating friction under bulk forming operation is well documented in the literature (7-9). This test has been shown to allow the simultaneous determination of friction stresses(7)of lubricants and the flow stress-deformation strain relationships(8) of materials under bulk deformation operations. Even though specific application of the ring test to sheet forming operations has been shown by Pope, Robins, and Berry(10), some question exists as to the validity of results from a bulk deformation operation when applied to sheet forming processes where lower tooling pressures frequently occur. Some of the concern of the various friction test methods is related to test techniques. Other concern is related to basic considerations of friction itself.

The basic aspect of evaluation of friction characteristics of lubricants on which this study is based is that quantitative characterization of the lubricant should be independent of the process system in which it is utilized. This idea of characterizing lubricants by their intrinsic shear resistance or shear strength is also argued by Schey(11) in comparison of friction results from ring compression testing and from twist compression testing. In this study, Schey points out that several lubricants are not only sensitive to pressure, but some are sensitive to the velocity at which shearing is accomplished. Schey suggests that at lower pressures, those at or below the compressive flow strength of the material, the shear restraint of the interface substance can be represented by an Amonton's Law relationship. This is represented by the following relation,

 $\tau = \mu P$ 

(1)

where  $\tau$  is the shear restraint of the interface substance,  $\mu$  is the assumed constant friction coefficient and P is the pressure applied normal to the surface. This concept of friction implies that the shear resistance of the interface substance is directly related to the applied pressure.

At higher pressure , those above the compressive flow strength of the material, the use of the interface shear factor concept has been argued to be a more realistic characterization of friction both by Schey(11) and also by Male and DePierre(12). The interface shear factor concept of friction implies that the only meaningful values of frictional shear resistance are those in the range from zero frictional restraint up to the values of the shear strength of the workpiece material. Interface substances which have shear restraint greater than the shear strength of the workpiece material will not allow metal flow at the interface, rather sub-surface shearing of the workpiece occurs. This concept is illustrated by the following relation.

$$\tau = m \frac{\sigma}{\sqrt{3}}$$
(2)

where  $\tau$  is the shear restraint of the interface substance  $\sigma/\sqrt{3}$  is the von Mises shear strength of the material and m is the interface shear factor. The value of m can vary from 0 for a frictionless case to a value of 1 for the maximum meaningful friction case.

When fluid-like lubricants are employed in thickness sufficient to create a hydrodynamic film, they are sometimes considered as Newtonian fluids as suggested by  $Vdovin^{(13)}$ . The frictional shear resistance of the film would then be related as shown below:

$$\tau = \eta \frac{\Delta v}{t}$$
(3)

where  $\tau$  is the frictional shear resistance of the interface film,  $\eta$  is the viscosity of the interface film,  $\Delta v$  is the velocity gradient within the film and t is the film thickness. The treatment of lubricants by this method gives an indication of the effects of pressure and temperature on the film shear strength through its direct relation to viscosity effect. For most materials, viscosity increases with increasing pressure and with decreasing temperature.

Consideration of these three views of friction illustrates some of the concern of lubricant evaluation and the applicability of the evaluation techniques to other conditions. The effort of this study will give attention to the application of the different views. The approach of this study was to examine the applicability of the interface shear approach to quantifying the interface condition in comparison with the coefficient of friction approach used by Ghosh<sup>(4)</sup>. The approach proposed for this task is to utilize the results from the ring compression test in combination with the results from a variable die-pressure strip-draw test.

#### SECTION III

#### EXPERIMENTAL PROGRAM

#### Material

Two sheet materials were investigated in this study, 7075 Al and Ti-6A1-4V. Both were procured in the form of 100 mil sheet. The chemical composition of these materials is given in Table 1.

#### Lubricants

The lubricants used in this evaluation were a combination of experimental and commercially available types. Since almost no information on quantitative evaluation of lubricants for sheet forming is available in the literature, the lubricants selected were deemed to be appropriate for the first round evaluation. Information from this first round evaluation would be used as the basis for classifying the lubricants and making the second round selection and evaluation. No attempt was made to select representative lubricants from the number of manufacturers, nor was any attempt made to evaluate the lubricants in their manufacturer's recommended use condition. Those lubricants used in this evaluation are given in Table 2.

#### Sheet Friction Test Equipment and Evaluation Procedures

The sliding friction resistance of the lubricants was evaluated through use of a specially constructed variable-die-pressure strip-drawing apparatus shown pictorially in Figure 2 and schematically in Figure 3.

The apparatus incorporates two particular features which allow data to be assimilated easily. The first of these features is the use of an air cylinder which together with bottled nitrogen gas and regulator can allow quick setting or quick change of the die hold-down pressures between 0 psi and 200 psi. The second feature is the dove-tailed die locking arrangement which allows quick interchange of the dies. The dies were made of H-12 tool steel and are shown in Figure 4 together with a sheet specimen used during testing. Two die surface conditions were used in the evaluation. One condition was as-ground with a roughness of approximately 32 RMS and the other was a lapped condition with a finish smoother than 1.0 micro-inch.

The sheet draw specimens, Figure 4, were produced with a strip area of width 1.0 inch and a length of 6.0 inches. The thickness surfaces of the specimen is the as-rolled thickness of the sheet. The lubricants were applied to the sheet specimens by either dipping or spraying, whichever was found to be more convenient. The lubricant was applied to attain a film thickness of approximately 0.005 inches. The lubricants were tested in two different conditions. One condition was the "just applied" condition where the test was performed within 30 seconds of application. The second condition was the dry condition where the lubricants were allowed to dry from 24 to 48 hours prior to testing.

Actual testing was accomplished with the strip-drawing apparatus fixed to a Tinius Olsen Testing Machine, Figure 5. Two cross-head speeds were utilized in the testing 1.5 ips and 15 ips. The tensile drawing load was monitored and recorded for each set of test conditions.

#### Ring Test Equipment and Evaluation Procedure

----

The ring compression test evaluation used in this program was performed on the 500 Ton Hydraulic Forge Press located at the Air Force Materials Laboratory. The basic characteristics of this test equipment and procedure has been described in the literature (7-9). For these tests, an interchangeable die system was utilized which allowed the test series for each lubricant to be performed on dies which were free of contamination from previous lubricants. Each set of dies was lapped with 3 micron diamond polish prior to use in the ring forging evaluations.

The ring test specimens used were machined from the 100 mil sheet. Rings of 24:8:1 geometry (0. D., I. D., Thickness) were used where the ring thickness was the as-rolled sheet thickness. All machining and testing was done at room temperature in the as-received condition. The lubricants were applied to the rings by either spraying or dipping, whichever technique was found to be more convenient. An approximate lubricant thickness of 0.005 inches was applied to the rings and these coated rings were held at room temperature for 24 hours prior to testing for the cured condition but tested within 30 seconds of application for the "just applied" condition. Ring compression tests were performed at 10, 20 and 30 percent reduction in height. Analysis of the ring compression tests were accomplished as described in an earlier publication (9).

#### SECTION IV

#### RESULTS

The results from the variable-die-pressure drawing tests are presented in Table 3 and 4. The frictional restraint of each lubricant film is presented in terms of the friction ratio. This term is calculated as the ratio of the drawing stress to the clamping or hold-down stress. Both the initial and maximum value of this ratio were recorded. Trends in the values of the friction ratio are plotted in Figures 6-9. The results from the plastic ring compression test are presented in Table 5 with the results shown graphically in Figure 10.

#### Effects of Lubricant Curing Times

Results from lubricants which are tested within 30 seconds of application are shown in Figure 6 for the Al-7075 workpieces. Also shown on this figure in bold lines are three theoretical constant interface friction curves. The fit of the maximum friction ratios from the C-300 and DGF lubricants to the theoretical curve is seen to be almost exact over the range of hold-down pressures. The results from G-231 and G-203A indicate a somewhat close fit with the theoretical curves at hold-down pressures of 305 psi and 610 psi, but show significant deviation when the hold-down pressures is increased to 915 psi.

When the time period between application and testing of the lubricants is extended to 24 hours with all other parameters identical, the friction ratio results are significantly different. These results are shown in Figure 7. A relation yielding a constant value of friction ratio with increasing hold-down pressure indicates that the frictional restraint increases almost in proportion to the load normal to the lubricant film, i.e. a constant coefficient of friction. However, results from some of the lubricants show that the friction ratio increases with increasing hold-down pressure, indicating that the anti-friction characteristics of the lubricant itself are adversely affected by pressure.

The principal difference between the lubricants in the "just applied" condition and the dry condition is that a significant amount of the lubricant carrier is retained in the "just applied" condition. Almost none of this carrier remains after the coating has dried for 24 hours. For the majority of tests, the effect of this retained carrier was to reduce the friction condition. However, in one of the lubricants (Hydro), this retained carrier resulted in an increase in friction when tested on both aluminum and titanium workpiece material, Table 3.

#### Effects of High Hold-Down Pressures

The testing of three of the lubricants was continued to high hold-down pressures. Two of these lubricants were applied to the workpiece 24 hours prior to testing and one was applied just prior to testing. Results from these tests are given in Figure 8. The trends from the two lubricants which were allowed to cure before testing showed almost constant coefficient-offriction type response for hold-down pressures as high as 2135 psi. The lack of significant variation between the initial and maximum values at any value of hold-down pressure indicates a very consistent response of the lubricants.

The results from the lubricant which was applied to the workpiece just prior to testing indicate that the low initial friction ratio is maintained up to the highest hold-down pressures tested, 2135 psi. A significant increase in the maximum value of the friction ratio begins to occur after hold-down pressures of 1220 psi indicating the breakdown of the favorable anti-friction characteristics as the drawing process continues. Galling between the aluminum workpiece and the tool steel die is associated with this breakdown.

#### Effect of Die Surface Finish

The effects of die finish were investigated for several lubricants applied to the A1-7075 workpieces. One die finish was 32 micro-inch RMS and the other was lapped smoother than 1 micro-inch. Except for the DGF lubricant, no significant differences in the two die finishes were noted. In the case of the DGF lubricant, the lapped finish resulted in significantly higher friction ratios, Table 3.

#### Effect of Drawing Speed

Drawing speed variations were investigated for three test series using lubricants applied to aluminum specimens only. Two draw speeds, 15 ips and 1.5 ips were investigated but no significant variations in friction resulted.

### Effect of Workpiece Material

When tests were performed with lubricants in the dried condition, no effects of material were observed. When the "just applied" lubricants condition is compared, the results are less consistent, but generally slightly higher friction ratios resulted from tests on titanium specimens.

#### Comparison of Test Variables on Lubricant Response

A comparison of the effects of test variables is shown in Figure 9 for the DGF lubricant applied to 7075 Al. The results show an amount of scatter, with most variables but a clear effect of the retained carrier in reducing the sliding friction as the hold-down pressures are increased.

### Interface Friction Factors from the Ring Compression Test

Since the initial testing of sheet forming lubricants were to be investigated for room temperature properties only, the ring forging tests were limited to the 7075 Al workpiece material. The higher flow stress of the Ti-6Al-4V and the thin ring specimens required forging loads which were too high to allow significant results to be obtained. The ring tests are presented in Table 5 and shown in Figure 10. These results show that the friction factors fall in a range between 0.10 and 0.22 for the majority of the lubricants tested for the cured condition. Results from the J-Wax and the MS-122 lubricants show definite trends with low values of friction factors.

#### SECTION V

#### DISCUSSION

The results of this study tend to show that none of three methods of characterizing lubricants outlined by the equations in Section II is completely suitable for evaluating frictional characteristics of lubricants for sheet drawing operations. Results from the variable die friction strip-draw test presented in Figure 6 show that a constant interface friction analysis is somewhat realistic if the lubricant contains some fluid components; this is particularly so for hold-down pressures between 300 psi and 600 psi. However, if testing is performed after these same lubricants have been cured to remove the fluids, then the constant coefficient of friction approach appears more realistic as can be seen in Figure 7. Considerable variation can occur for any lubricant depending on the conditions of the test as shown in Figure 9 for dry film graphite. The essential consideration of lubricants which is brought out by the data of Figures 6-9, is that the intrinsic properties of the lubricants are not completely characterized by the three basic equations discussed earlier. The frictional restraint offered by the lubricants must include a careful documentation of the manner of testing and the assumption included in the analysis.

When lubricant evaluation is performed for a specific process, certain simplifying assumptions are frequently made in the analysis. Generalization of the results based on those assumptions can cause significant difficulties when the same lubricants are used in different processes. An example of this condition can be made with the analysis of punch stretching by  $Gosh^{(4)}$  in which it is carefully stated that a pressure dependence of friction coefficient generally occurs. In his analysis, however, Gosh reasons that the pressure changes experienced in punch stretching are small and that simplification of the analysis could be achieved if the friction coefficient were assumed constant and that Amonton's Law holds, Equation 1. Examination of the data presented in Figure 6 of this report shows that significant errors would result when Gosh's data or equations, based on no pressure effect, are used to predict friction when large pressure variations occur.

Further consideration must be given to the film breakdown condition which most frequently occurs when the lubricant is used at significantly higher deformation pressures or when it is used in sliding conditions where no replinishment is possible. The film breakdown condition is shown in Figure 6 to occur for the variable-die-pressure strip draw test with the lubricant in the "just applied" condition as the hold-down pressure is increased from 600 to 900 psi. A part of this effect is associated with the lubricant depletion as the sliding process occurs. It is interesting to note, however, that no film breakdown occurred when the "just applied" condition of these lubricants was evaluated by the ring forging test, even though significantly higher normal pressure were experienced, Figure 10 and Table 5. The reason for this effect is not readily apparent and perhaps should be investigated more thoroughly by testing at intermediate pressure conditions. The condition of film breakdown occurrence because of continued sliding without lubricant replinishment is found to occur in a lubricant when very high hold-down pressures are used Figure 8. While the hold-down pressures used in these data are considerably in excess of those normally encountered in practical sheet forming operations, the results illustrate the greater stability and more consistent response when the lubricants are cured prior to use.

A direct comparison of the quantitative results from the two lubricant evaluation techniques cannot be made because of the large difference in the normal load each imposes on the lubricant film. Normal pressures from the strip drawing apparatus were in general varied between 305 psi and 915 psi. The normal pressures resultant from ring forging generally range between 40 ksi and 100 ksi. It is possible that the interface shear stress of the lubricant film is pressure dependent and the wide differences found in these tests are attributable to this effect. Because of the lack of data at intermediate pressures, when such a correlation was found it could not be established whether it was real or coincidental. Attempts to establish this pressure dependence with the results of these tests were abandoned because of this lack of intermediate pressure data.

Further comparison of the results of the two test techniques must consider the differences in the mode of testing. In the strip draw test, a new section of the coated workpiece is continuously drawn in between the dies as the test proceeds. If the lubricant is poorly adhered to the workpiece, the effect of the dies would be to scrapeoff the lubricant coating and thereby cause large increases in the friction as the test proceeds. If the lubricant is tightly adhered to the workpiece, then consistent friction results should be obtained as the test proceeds. It would also be possible that the initial portion of the drawing operations conditions the die to allow an effective reduction in the friction as the test proceeds.

For the ring test, the only newly coated workpiece material that can be brought in between the dies would result from the fold over of the axial surface of the ring. This new surface is more probably offset by exposure of new uncoated surface from the plastic deformation process. In addition to this difference, the high deformation pressures associated with the ring test can either cause squeezing out of more fluidish lubricants or cause dishing of the ring surface which effectively entraps the lubricant. When a comparison is made of lubricants evaluated in the "just applied" condition versus the cured condition, Table 4 and 5, it can be seen that both tests indicate the friction stresses of cured lubricants are about twice the value of the "just applied" condition. Some variation is evident, however.

The results from either test in the evaluation of dry graphite films do not show significant variations. For two of the non-graphite type lubricants, J-Wax and MS-122, results from the ring test showed definite lower values of friction. The exact explanation of this effect is not known, but is probably attributable to these lubricants being entrapped as the ring surfaces become dished.

#### SECTION VI

#### CONCLUSIONS

The results of this study allow the following conclusion to be made:

- The anti-friction characteristics of lubricants for sheet forming operations are strongly dependent upon the amount of fluid carrier substance remaining in the lubricant at time of test.
- 2. Fluid containing lubricants show constant interface shear response in lightly boaded applications. The frictional shear resistance stresses are almost constant and the ratio of the frictional restraint to the normal applied pressure decreases with increasing normal pressure.
- Lubricants without retained fluids show a constant coefficient of friction response in lightly loaded test conditions. The frictional restraint stress increases with increasing normal applied stress.
- 4. Lubricants evaluated in the cured or dried conditions gave a more consistent response in testing, but in general indicated higher frictional shear resistance.
- 5. Drawing speed variations evaluated at 15 ips and 1.5 ips did not indicate a significant effect on frictional response of the lubricant.
- 6. Die surface finish as measured by peak to valley roughness did not cause a significant effect on the frictional response of the lubricant between roughness values of 1.0 micro-inch and 32 micro-inches.
- 7.. The results from the ring compression test indicated approximately the same trend in lubricant response as did the results from the variable-die-pressure strip draw test. The effect of the large pressure differences between these two tests could not be correlated with the resultant frictional shear of the film because of the lack of intermediate pressure data.

#### REFERENCES

- Eary, D. F. and E. A. Read, <u>Techniques of Pressworking Sheet Metal</u>, 2nd Ed., Prentice Hall, Englewood Cliffs, N. J., 1974.
- Keeler, S. P., "Understanding Sheet Metal Formability", A series of 6 articles, Sheet Met., Ind., <u>48</u>, Nos. 5-10, (1971).
- Hecker, S. S., "Formability of HSLA Steel Sheets", Metal Engineering Quarterly, <u>13</u>, (3), August 1973, pp. 42-8.
- Ghosh, A., "A Method for Determining the Coefficient of Friction in Punch Stretching of Sheet Metals", General Motors Research Laboratories Research Publication, GMR-2311, December 1976.
- 5. Goodwin, G. M., "Application of Strain Analysis to Sheet Metal Forming Problems in the Press Shop", SAE Paper 680093, pp. 1-12 (Reference cited by Keeler in Reference 2).
- 6. Keeler, S. P., (Part V of Reference 2, "Die Design and Lubrication").
- Male, A. T. and V. DePierre, "The Validity of Mathematical Solutions for Determining Friction from the Ring Compression Test", TRANS ASME, Journal of Lubrication Technology, 1970, pp. 389-397.
- Saul, G., A. T. Male, and V. DePierre, "A New Method for the Determination of Material Flow Stress Values Under Metalworking Conditions", Metal Forming: Interrelation Between Theory and Practice, Ed., A. L. Hoffmanner, 1971, Plenum Press.
- 9. DePierre, V. and F. Gurney, "A Method for Determination of Constant and Varying Friction Factors During Ring Compression Testing", Journal of Lubrication Technology, TRANS ASME, 1974, 96, Series F, (3), p. 482.
- Pope, M. H., L. Robins, and J. T. Barry, "Lubrication Aspects of the Deep Drawing of Stainless Steel, Titanium and Nickel-Base Alloys at Elevated Temperatures", ASLE Paper No. 69LC-1.
- Schey, J. A., "The Validity of Various Friction Concepts in Deformation Processing", <u>Proceedings NAMRC-IV Fourth North American Metalworking</u> <u>Research Conference</u>, May 1976, p. 108.
- Male, A. T., and V. DePierre, "The Relative Validity of the Concepts of Coefficient of Friction and Interface Friction Shear Factor for Use in Metal Deformation Studies", ASLE Transactions, 16, (3), p. 177.
- Vdovin, V. F., "Technological Properties of Glass-Base Lubricants Used in Extrusion", pp. 220-222 from Dnepropetrovsk, Scientific Transactions No. 53, 1967, English Translation by Foreign Technology Division, USAF, FTD-MT-24-318-69, 31 December 1969.

TABLE 1

Chemical Composition of Test Material

|       |     |     | Сот | position |     |      |     |      |
|-------|-----|-----|-----|----------|-----|------|-----|------|
| ial   | Zn  | Mg  | ЧЧ  | Cu       | Cr  | Si   | Fe  | IA   |
| AI    | 5.8 | 2.9 | .03 | .1.7     | .34 | .02  | .02 | Bal. |
|       | TA  | Λ   | Fe  | U        | 0   | Ti   |     |      |
| 14-14 | 6.6 | 4.2 | .16 | .015     | .15 | Bal. |     |      |

TABLE 2

Lubricants used in the Evaluation\*

| C-300  | A spray mixture of graphite and $M_OS_2$ with a carrier   |
|--------|---|
| DGF    | A graphite spray with a carrier   |
| MS-122 | A fluorocarbon spray in a carrier   |
| F-33   | A silicon spray in a carrier  |
| J-WAX  | A commercial paste wax polish   |
| IC-665 | A commercial sheet forming lubricant  |
| G-203A | A commercial sheet forming lubricant composed<br>of graphite dispersed in water, oils or solvents |
| G-231  | A commercial sheet forming lubricant composed of graphite dispersed in water oils or solvents     |
| HYDRO  | A commercial sheet forming lubricant composed<br>of graphite dispersed in water oils or solvents  |

\*The lubricants listed on this table were applied and tested in a manner to obtain significant test variations. No attempt was made to utilize these lubricants in the manner recommended by the manufacturer. Results from the evaluation are not meant to refute nor to endorse the characteristics of the particular lubricant.

| TAR | IF | 3 |
|-----|----|---|
| TUD | 25 | - |

### Friction Ratios of Sheet Forming Lubricants in Elastic Drawing at Low to Moderate Hold Down Pressures

|          |        | Conditi                          | .on                          | Draw<br>Speed         | Initial/<br>Indicate                             | Maximum Frict<br>d Hold Down P                   | ion Ratio At<br>ressure                          |
|----------|--------|----------------------------------|------------------------------|-----------------------|--|--|--|
| Material | Lube   | Lube †                           | Die <sup>*</sup>             | (ipm)                 | 305 psi  | 610 psi  | 915 psi  |
| 7075 A1  | C-300  | J.A.<br>DRY                      | A.G.<br>A.G.                 | 15<br>15              | .086/.182  | .070/.075  | .059/.066  |
|          |        | DRY<br>DRY                       | L.P.<br>A.G.                 | 1.5                   | .165/.175  | .248/.261  | .269/.281  |
| 7075     | DGF    | J.A.<br>DRY<br>DRY<br>DRY        | A.G.<br>A.G<br>L.P.<br>A.G.  | 15<br>15<br>15<br>1.5 | .140/.186<br>.204/.259<br>.267/.309<br>.172/.214 | .077/.093<br>.175/.235<br>.350/.380<br>.198/.257 | .038/.062<br>.176/.223<br>.263/.289<br>.199/.315 |
| 7075     | J-WAX  | J.A.<br>DRY<br>DRY<br>DRY<br>DRY | A.G.<br>A.G.<br>L.P.<br>A.G. | 15<br>15<br>15<br>1.5 | .089/.125<br>N.D.<br>.140/.151<br>.092/.092      | .079/.135<br>N.D.<br>.159/.163<br>.150/.151      | .053/.160<br>N.D.<br>.180/.186<br>.159/.159      |
| 7075     | HYDRO  | J.A.<br>DRY<br>DRY               | A.G.<br>A.G.<br>L.P.         | 15<br>15<br>15        | .229/lost<br>.138/.136<br>.118/.128              | .194/lost<br>.128/.143<br>.132/.151              | .276/lost<br>.125/.135<br>.135/.158              |
| 7075     | G-231  | J.A.<br>DRY<br>DRY               | A.G.<br>A.G.<br>L.P.         | 15<br>15<br>15        | .289/.289<br>.153/.162<br>.149/.149              | .168/.168<br>.165/.175<br>.172/.182              | .161/.161<br>.181/.207<br>.195/.196              |
| 7075     | G-203A | J.A.<br>DRY<br>DRY               | A.G.<br>A.G.<br>L.P.         | 15<br>15<br>15        | .051/.099<br>.149/.153<br>lost                   | .051/.095<br>.168/.185<br>lost                   | .041/.053<br>.163/.173<br>lost                   |
| 7075     | IC-665 | J.A.<br>DRY<br>DRY               | A.G.<br>A.G,<br>L.P.         | 15<br>15<br>15        | .049/.058<br>.157/.159<br>lost                   | .045/.067<br>.168/.177<br>lost                   | .038/.049<br>.171/.191<br>lost                   |
| T1-6-4   | HYDRO  | DRY<br>J.A.                      | A.G.<br>A.G.                 | 15<br>15              | .147/.176<br>.121/.1°3                           | .134/.139<br>.258/.271                           | .115/.126<br>.233/.254                           |
| TI-6A1   | G-231  | DRY<br>J.A.                      | A.G.<br>A.G.                 | 15<br>15              | .147/.176<br>.153/.191                           | .163/.205<br>.242/.291                           | .106/.113<br>.237/.257                           |
| T1-6A1   | IC-665 | DRY<br>J.A.                      | A.G.<br>A.G.                 | 15<br>15              | N.D.<br>.051/.091                                | .156/.165<br>.051/.070                           | .174/.176<br>.129/.161                           |
| Ti-6Al   | G-203A | DRY<br>J.A.                      | A.G.<br>A.G.                 | 15<br>15              | N.D.<br>.051/.058                                | .163/.174<br>.032/.041                           | .149/.164<br>.051/.077                           |
| T1-6A1   | DGF    | J.A.                             | A.G.                         | 15                    | .172/.181  | .210/.217  | .221/.226  |
| TI-6A1   | J-WAX  | J.A.                             | A.C.                         | 15                    | .191/.212  | .267/.274  | .289/.301  |

L. P. - Lapped smoother than 1 micro-inch finish; \*A. G. - As ground approximately 32 micro-inch finish; †J. A. - Just-applied within 30 secs. of testing; †DRY - Applied at least 24 hours prior to testing; N. D. - Not Determined; Lost - Data lost because of test situations. TABLE 4

Friction Ratios of Sheet Forming Lubricants in Elastic Drawing at High Hold-Down Pressures

|                                | 2135 psi | 111./60   | 18/.132   | 49/.240   |  |
|--------------------------------|----------|-----------|-----------|-----------|--|
| tio At<br>e                    | si 2     | 35 .10    | 11. 72    | 45 .04    |  |
| iction Rat<br>n Pressure       | 1830 ps  | .130/.1   | .115/.1   | .053/.24  |  |
| 1/Maximum Fr.<br>ted Hold-Down | 1525 psi | .135/.142 | .112/.125 | .032/.178 |  |
| Initia<br>Indica               | 1220 psi | .133/.137 | .115/.119 | .051/.069 |  |
| Draw<br>Speed                  | (ipm)    | 15        | 15        | 15        |  |
| ition                          | Die      | A.G.      | A.G.      | A.G.      |  |
| Condi                          | Lube     | DRY       | DRY       | J.A.      |  |
|                                | Lube     | J-WAX     | HYDRO     | IC-665    |  |
|                                | Material | 7075      | 7075      | 7075      |  |

| TA | RI | E | 5 |
|----|----|---|---|
|    |    | - | - |

Interface Friction of Lubricants During Ring Forging of Sheet

| Forge<br>Number | Lube<br>Type | ∆ID<br>(%) | ∆H<br>(%) | Condition | m   | c<br>(ksi) |
|-----------------|--------------|------------|-----------|-----------|-----|------------|
| 4691            | C-300        | 14.5       | 11        | Cured     | .19 | 3.06       |
| 4693            | C-300        | 22.2       | 15        | Cured     | .22 | 3.50       |
| 4692            | C-300        | 34.9       | 26        | Cured     | .10 | 2.72       |
| 4694            | DGF          | 19.6       | 16        | Cured     | .12 | 2.47       |
| 4695            | DGF          | 26.8       | 18        | Cured     | .18 | 4.22       |
| 4696            | DGF          | 38.3       | 23        | Cured     | .19 | 3.82       |
| 4698            | J-WAX        | 9.6        | 11        | Cured     | .07 | 1.34       |
| 4697            | J-WAX        | 13.4       | 18        | Cured     | .05 | 1.09       |
| 4699            | J-WAX        | 23.1       | 28        | Cured     | .05 | 1.28       |
| 5033            | J-WAX        | 2.1        | 14        | J-APP     | .02 | .48        |
| 5034            | J-WAX        | 13.8       | 31        | J-APP     | .03 | .89        |
| 5035            | J-WAX        | 21.0       | 33        | J-APP     | .03 | 1.02       |
| 5036            | J-WAX        | 7.1        | 12        | Cured     | .05 | 1.02       |
| 5037            | J-WAX        | 21.4       | 26        | Cured     | .05 | 1.31       |
| 5038            | J-WAX        | 30.7       | 36        | Cured     | .04 | 1.63       |
| 4701            | MS-122       | 1.4        | 10        | Cured     | .19 | 3.08       |
| 4700            | MS-122       | 5.2        | 17        | Cured     | .14 | 2.17       |
| 4702            | MS-122       | 10.3       | 22        | Cured     | .14 | 3.26       |
| 4703            | IC-665       | 4.3        | 4         | Cured     | .14 | 2.17       |
| 4704            | IC-665       | 16.2       | 12        | Cured     | .19 | 3.08       |
| 4705            | IC-665       | 42.2       | 26        | Cured     | .14 | 3.26       |
| 5025            | IC-665       | 23.0       | 18        | Cured     | .12 | 2.85       |
| 5021            | IC-665       | 1.6        | 5         | J-APP     | .03 | .48        |
| 5022            | IC-665       | 4.1        | 15        | J-APP     | .03 | .65        |
| 5023            | IC-665       | 14.2       | 25        | J-APP     | .04 | 1.26       |
|                 |              |            |           |           |     |            |

The second second second

## TABLE 5 (CON'T)

| 1               | <u></u>      |                                     | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | r   | r          |
|-----------------|--------------|-------------------------------------|---------------------------------------|---------------------------------------|-----|------------|
| Forge<br>Number | Lube<br>Type | ∆ID<br>(%)                          | ∆H<br>(%)                             | Condition                             | m   | c<br>(ksi) |
| 4706            | HYDRO        | 10.4                                | 8                                     | Cured                                 | .21 | 2.99       |
| 4707            | HYDRO        | 20.5                                | 16                                    | Cured                                 | .14 | 2.57       |
| 4708            | HYDRO        | 36.0                                | 23                                    | Cured                                 | .16 | 3.36       |
| 5027            | HYDRO        | 1.5                                 | 3                                     | J-APP                                 | .04 | .62        |
| 5028            | HYDRO        | 5.1                                 | 13                                    | J-APP                                 | .03 | .67        |
| 5029            | HYDRO        | 22.9                                | 32                                    | J-APP                                 | .05 | 1.62       |
| 5030            | HYDRO        | 7.8                                 | 9                                     | Cured                                 | .08 | 1.76       |
| 5031            | HYDRO        | 23.2                                | 20                                    | Cured                                 | .10 | 2.54       |
| 5032            | HYDRO        | 38.9                                | 26                                    | Cured                                 | .12 | 3.77       |
| 5008            | G-231        | 0.0                                 | 5                                     | J-APP                                 | .02 | .35        |
| 5009            | G-231        | 1.9                                 | 25                                    | J-APP                                 | .01 | .22        |
| 5010            | G-231        | 4.8                                 | 38                                    | J-APP                                 | .02 | .56        |
| 5011            | G-231        | 2.4                                 | 4                                     | Cured                                 | .05 | .92        |
| 5012            | G-231        | 9.1                                 | 7                                     | Cured                                 | .22 | 3.40       |
| 5013            | G-231        | 29.1                                | 23                                    | Cured                                 | .10 | 2.69       |
| 4713            | G-203A       | 28.9                                | 19                                    | Cured                                 | .18 | 3.56       |
| 4714            | G-203A       | 53.2                                | 27                                    | Cured                                 | .23 | 4.37       |
| 5014            | G-203A       | -1.5                                | 14                                    | J-APP                                 | .02 | .36        |
| 5016            | G-203A       | 0.0                                 | 19                                    | J-APP                                 | .02 | .48        |
| 5015            | G-203A       | 2.4                                 | 20                                    | J-APP                                 | .02 | .49        |
| 5017            | G-203A       | 12.0                                | 34                                    | J-APP                                 | .02 | .47        |
| 5019            | G-203A       | 30.8                                | 24                                    | Cured                                 | .10 | 2.56       |
| 5020            | G-203A       | 53.3                                | 36                                    | Cured                                 | .08 | 3.18       |
| 4715            | F-33         | 9.3                                 | 10                                    | Cured                                 | .09 | 1.81       |
| 4716            | F-33         | 15.3                                | 13                                    | Cured                                 | .12 | 3.42       |
| 4717            | F-33         | 19.9                                | 20                                    | Cured                                 | .07 | 3.16       |
|                 |              | and the second second second second |                                       |                                       |     |            |

Interface Friction of Lubricants During Ring Forging of Sheet



Figure 1. Reduction in Peak Strain at a Critical Region in Stamping of an Automobile Hood. The reduction was achieved by changing one "good" lubricant for another.











Figure 6. Effect of hold-down pressure on friction ratio during strip-drawing where the lubricant was applied just before testing.



Figure 7. Effect of hold-down pressure on friction ratio during strip-drawing where lubricant was cured before testing.









Figure 10. Interface friction factor from various lubricants when deformed plasticity during the ring forge test.

## APPENDIX APPLIED METAL PROCESSING

100

## TITANIUM BASE

| Extrusion<br>Number | Agency             | Alloy                            | Temp.<br>°F | Red. I<br>Ratio | Billet<br>Lube | Die<br>Angle    | P <sub>t</sub><br>(ksi) | V <sub>ex</sub><br>(ips) | Surface   |
|---------------------|--------------------|----------------------------------|-------------|-----------------|----------------|-----------------|-------------------------|--------------------------|-----------|
| 6754                | AFML/LLS           | Ti-8V-4Cr-<br>2Mo-2Fe-<br>3A1    | 1500        | 5.3:1           | 8871           | 60 <sup>0</sup> | 97                      | 1.8                      | Good      |
| 6755                | AFML/LLS           | Ti-8V-4Cr-<br>2Fe-3A1            | 1500        | 5.3:1           | 8871           | 60 <sup>0</sup> | 108                     | 1.8                      | Good      |
| 6756                | AFML/LLS           | T1-15V-3Cr-<br>3A1-3Sn           | 1500        | 5.3:1           | 8871           | 600             | 111                     | 1.8                      | Good      |
| 6757                | AFML/LLS           | Ti-15V-3Cr-<br>3A1-3Sn           | 1500        | 5.3:1           | 8871           | 60°             | 109                     | 1.8                      | Good      |
| 6764                | Pratt &<br>Whitney | Ti-32.5A1-<br>4.6Nb5W            | 2550        | 6:1             | 7740           | 60°             | 120                     | 1.4                      | Good      |
| 6765                | Pratt &<br>Whitney | Ti-32.5A1-<br>4.6Nb5W            | 2550        | 6:1             | 7740           | 60°             | 140                     | 1.4                      | Good      |
| 6766                | Pratt &<br>Whitney | Ti-32.5A1-<br>4.6Nb5W            | 2550        | 6:1             | 7740           | 60 <sup>0</sup> | 120                     | 1.4                      | Good      |
| 6767                | Pratt &<br>Whitney | Ti-32.5A1-<br>4.6Nb5W            | 2550        | 6:1             | 7740           | 60 <sup>0</sup> | 120                     | 1.4                      | Good      |
| 6768                | AFML/LLS           | Ti-5A1-5Sn<br>-2Zr-2Mo-<br>.25Si | 1600        | 6:1             | 0010           | 60 <sup>0</sup> | 157                     | 2.1                      | Good      |
| 6769                | AFML/LLS           | Ti-5A1-5Sn<br>2Zr-2Mo-<br>.25Si  | 1900        | 6:1             | 0010           | 60 <sup>0</sup> | 59                      | 2.6                      | Excellent |
| 6770                | AFML/LLS           | Ti-5A1-5Sn<br>-2Zr-2Mo-<br>.25Si | 1900        | 6:1             | 0010           | 60°             | 68                      | 2.6                      | Excellent |
| 6788                | AFML/LLM-1         | Ti-36.3Al<br>Powder              | 2575        | 10:1            | 7740           | 90°R            | 51                      | 1.3                      | Good      |
| 6790                | AFML/LLM-1         | Ti-28.6Al<br>Powder              | 2575        |                 | 7740           | 90°R            | 42                      | 1.5                      | Good      |

## TITANIUM BASE

| Extrusion<br>Number | Agency               | Alloy                  | Temp.<br>oF | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle      | P <sub>t</sub><br>(ksi) | V <sub>ex</sub><br>(ips) | Surface |
|---------------------|----------------------|------------------------|-------------|---------------|----------------|-------------------|-------------------------|--------------------------|---------|
| 6791                | AFML/LLM-1           | Ti-30.5A1              | 2575        |               | 7740           | 90 <sup>0</sup> R | 40                      | 1.5                      | Good    |
| 6792                | AFML/LLM-1           | Ti-32.5A1              | 2575        |               | 7740           | 90 <sup>0</sup> r | 44                      | 1.5                      | Good    |
| 6793                | AFML/LLM-1           | Ti-34.25A1             | 2575        |               | 7740           | 90°R              | 43                      | 1.4                      | Good    |
| 6821                | Pratt &<br>Whitney   | Ti-32.5A1-<br>4.6Nb-5W | 2550        | 6:1           | 7740           | 60 <sup>0</sup>   | 38                      | 1.5                      | Good    |
| 6822                | Pratt & ·<br>Whitney | Ti-32.5A1-<br>4.6Nb-5W | 2550        | 6:1           | 7740           | 60 <sup>0</sup>   | 39                      | 1.5                      | Good    |
| 6823                | Pratt &<br>Whitney   | Ti-32.5A1-<br>4.6Nb-5W | 2550        | 6:1           | 7740           | 60°               | 38                      | 1.4                      | Good    |
| 6833                | AFML/LLM             | Ti-10V-<br>2Fe-3A1     | 1150        | 5.8:1         | 8871           | 90 <sup>0</sup>   | 185                     | .3                       |         |
| 6837                | AFML/LLM             | Ti-10V-<br>2Fe-3A1     | 1150        | 5.9:1         | 8871           | 60 <sup>0</sup>   | 178                     | 0.5                      | Good    |
| 6859                | AFML/LLM             | Ti-10V-<br>2Fe-3A1     | 1150        | 5.8:1         | 8871           | 60°               | 173                     | 1.2                      | Good    |
| 6860                | AFML/LLM-1           | Ti-32.5A1-<br>4.6Nb-5W | 2550        | 15.92<br>:1   | 7740           | 60 <sup>0</sup>   | 55                      | 1.5                      | Good    |
| 6861                | AFML/LLM-1           | T1-28.6A1              | 2550        | 26:1          | 7740           | 60 <sup>0</sup>   | 62                      | 1.5                      |         |
| 6862                | AFML/LLM-1           | T1-14.6A<br>10Nb-4W    | 2200        | 26:1          | 0010           | 60°               | 65                      | 1.4                      |         |
| 6872                | AFML/LLS             | Ti-31%A1               | 2550        | 20:1          | 7740           | 90°R              | 43                      | 1.5                      | Good    |
| 6874                | AFML/LLM-1           | Ti-51%A1               | 2575        | 26:1          | 7740           | 60 <sup>0</sup>   | 76                      |                          | Good    |
| 6912                | AFML/LLM-1           | Ti-27%A1               | 2200        | 26:1          | 0010           | 60 <sup>0</sup>   | 54                      | 1.6                      | Good    |
| 6913                | AFML/LLM-1           | T1-27%A1               | 2200        | 26:1          | 0010           | 60 <sup>0</sup>   | 57                      | 1.6                      | Good    |
| 6914                | AFML/LLM-1           | Ti-24%A1-<br>11%Nb     | 2200        | 26:1          | 0010           | 60 <sup>0</sup>   | 54                      | 1.6                      | Good    |

## TITANIUM BASE

| Extrusion<br>Number | Agency     | <u>A11oy</u>             | Temp.<br>oF | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle     | Pt<br>(ksi) | Vex<br>(ips) | Surface |
|---------------------|------------|--------------------------|-------------|---------------|----------------|------------------|-------------|--------------|---------|
| 6915                | AFML/LLM-1 | Ti-24%A1-<br>11%Nb       | 2200        | 26:1          | 0010           | 60 <sup>0</sup>  | 54          | 1.6          | Good    |
| 6923                | AFML/LLM-1 | T1-25%A1-<br>8%Nb        | 2575        | 26:1          | 7740           | 60 <sup>0</sup>  | 81          | 1.6          | Good    |
| 6924                | AFML/LLM-1 | Ti-25%Al-<br>8%Nb-5%W    | 2575        | 26:1          | 7740           | 60 <sup>0</sup>  | 70          | 1.6          | Good    |
| 6926                | AFML/LLM-1 | Ti-26.5W/o<br>-Al        | 2575        | 26:1          | 7810           | 60 <sup>0</sup>  | 70          | 1.6          | Good    |
| 6927                | AFML/LLM-1 | Ti-34.3W/o<br>-Al        | 2575        | 26:1          | 7810           | 60 <sup>0</sup>  | 97          | 1.5          | Good    |
| 6928                | AFML/LLM-1 | Ti-34W/o-<br>Al-4.5W/o-W | 2575        | 26:1          | 7810           | 60 <sup>0</sup>  | 127         | 1.5          | Good    |
| 6929                | AFML/LLM-1 | Ti-36W/o-A1              | 2575        | 26:1          | 7810           | 60 <sup>0</sup>  | 89          | 1.6          | Good    |
| 6930                | AFML/LLM-1 | Ti-32W/o-Al<br>-9W/o-W   | 2575        | 26:1          | 7810           | 60 <sup>0</sup>  | 81          | 1.6          | Good    |
| 6931                | AFML/LLM-1 | Ti331W/o-<br>Al-14W/o-C  | 2575        | 6:1           | 7810           | 60 <sup>0</sup>  |             |              |         |
| 6932                | GE         | T1-6A1-4V                | 1800        | 44:1          | 0010           | 120 <sup>0</sup> | 105         | 2.8          | Good    |
| 6933                | GE         | Ti-6A1-4V                | 1800        | 44:1          | 0010           | 120 <sup>0</sup> | 108         | 2.7          | Good    |
| 6934                | GE         | Ti-6A1-4V                | 1800        | 44:1          | 0010           | 120 <sup>0</sup> | 105         | 2.8          | Good    |
| 6935                | GE         | Ti-6A1-4V                | 1800        | 44:1          | 0010           | 120 <sup>0</sup> | 105         | 2.7          | Good    |
| 6936                | GE         | Ti-6A1-4V                | 1800        | 44:1          | 0010           | 120 <sup>0</sup> |             |              |         |
| 6937                | GE         | Ti-6A1-4V                | 1800        | 44:1          | 0010           | 120 <sup>0</sup> |             |              | Good    |
| 7052                | AFML/LLM   | 2Ti-10V-<br>2Fe-3A1      | 1150        | 10:1          | 8871           | 60 <sup>0</sup>  | 192         | 1.1          | Good    |

## TITANIUM BASE

| Extrusion<br>Number | Agency   | Alloy                             | Temp.<br><sup>o</sup> F | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle    | P <sub>t</sub><br>(ksi) | Ve <sub>x</sub><br>(ips) | Surface |
|---------------------|----------|-----------------------------------|-------------------------|---------------|----------------|-----------------|-------------------------|--------------------------|---------|
| 7053                | AFML/LLM | Ti-10V-<br>2Fe-3A1                | 1150                    | 10:1          | 8871           | 60 <sup>0</sup> | 193                     | 1.1                      | Good    |
| 7068                | AFML/LLS | Ti-5Al-<br>5Sn-2Zr-<br>2Mo-0.25Si | 1600                    | 6:1           | 0010           | 60 <sup>0</sup> | 135                     | 2.7                      | Good    |
| 7069                | AFML/LLS | Ti-5A1-5Sn<br>2Zr-2Mo-0.2         | 1900<br>5Si             | 6:1           | 0010           | 60 <sup>0</sup> | 43                      | 3.1                      | Good    |

## NICKEL BASE

| Extrusion<br>Number | Agency             | Alloy   | Temp.<br>oF | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle    | P<br>(ksi) | Vex<br>(ips) | Surface |
|---------------------|--------------------|---|-------------|---------------|----------------|-----------------|------------|--------------|---------|
| 6761                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 0 <sub>3</sub> | 1900        | 16:1          | Poly           | 90 <sup>0</sup> | 140        | 1.8          | Good    |
| 6762                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 03             | 1900        | 16:1          | Poly           | 90 <sup>0</sup> | 134        | 2.0          | Good    |
| 6763                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 03             | 1900        | 16:1          | Poly           | 90 <sup>0</sup> | 138        | 2.0          | Good    |
| 6772                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 03             | 1900        | 16.3:1        | Poly           | 90 <sup>0</sup> | 130        | 2.0          | Good    |
| 6773                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 0 <sub>3</sub> | 1900        | 16.3:1        | Poly           | 90 <sup>0</sup> | 130        | 2.0          | Good    |
| 6774                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 03             | 1900        | 20.5:1        | Poly           | 90°             | 140        | 1.6          | Good    |
| 6775                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 0 <sub>3</sub> | 1900        | 20.5:1        | Poly           | 90 <sup>0</sup> | 140        | 1.7          | Good    |
| 6776                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 0 <sub>3</sub> | 1900        | 20.5:1        | Poly           | 90 <sup>0</sup> | 153        | 6.0          | Good    |
| 6777                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 0 <sub>3</sub> | 1900        | 20.5:1        | Poly           | 90 <sup>0</sup> | 154        | 5.2          | Good    |
| 6778                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 03             | 1900        | 16:1          | Poly           | 90 <sup>0</sup> | 130        | 2.0          | Good    |
| 6779                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 03             | 1900        | 16:1          | Poly           | 90 <sup>0</sup> | 134        | 2.1          | Good    |
| 6780                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 0 <sub>3</sub> | 1900        | 20:1          | Poly           | 90 <sup>0</sup> | 159        | 5.5          | Good    |
| 6781                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 0 <sub>3</sub> | 1900        | 20:1          | Poly           | 90 <sup>0</sup> | 161        | 6.0          | Good    |
| 6782                | Pratt &<br>Whitney | IN-100  | 1950        | 8:1           | 0010           | 60 <sup>0</sup> | 135        | 1.2          | Good    |

## NICKEL BASE

| Extrusion<br>Number | Agency             | Alloy  | Temp.<br>oF | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle    | P <sub>t</sub><br>(ksi) | Ve <sub>x</sub><br>(ips) | Surface |
|---------------------|--------------------|--------|-------------|---------------|----------------|-----------------|-------------------------|--------------------------|---------|
| 6783                | Pratt &<br>Whitney | IN-100 | 2000        | 8:1           | 0010           | 60 <sup>0</sup> | 147                     | 1.2                      | Good    |
| 6784                | Pratt &<br>Whitney | IN-100 | 1950        | 2:1           | 0010           | 60 <sup>0</sup> | 70                      | 1.5                      | Good    |
| 6785                | Pratt &<br>Whitney | IN-100 | 1900        | 2:1           | 0010           | 60 <sup>0</sup> | 81                      | 1.1                      | Good    |
| 6786                | Pratt &<br>Whitney | IN-100 | 1850        | 2:1           | 0010           | 60 <sup>0</sup> | 100                     | 1.1                      | Good    |
| 6787                | Pratt &<br>Whitney | IN-100 | 1800        | 2:1           | 0010           | 60 <sup>0</sup> | 124                     | .9                       | Good    |
| 6794                | Battelle           | 718    | 1900        | Blank         | Poly           | 90 <sup>0</sup> | 200                     | 1.0                      | Good    |
| 6795                | Battelle           | 718    | 1900        | Blank         | Poly           | 90 <sup>0</sup> | 200                     | 1.0                      | Good    |
| 6796                | Battelle           | 718    | 1900        | Blank         | Poly           | 90 <sup>0</sup> | 200                     | 1.0                      | Good    |
| 6797                | Battelle           | 718    | 1900        | Blank         | Poly           | 90 <sup>0</sup> | 194                     | 1.0                      | Good    |
| 6798                | Battelle           | 718    | 1900        | Blank         | Poly           | 90 <sup>0</sup> | 197                     | 1.0                      | Good    |
| 6799                | Battelle           | 718    | 1900        | Blank         | Poly           | 90 <sup>0</sup> | 192                     | 1.0                      | Good    |
| 6800                | Battelle           | 718    | 1900        | Blank         | Poly           | 90 <sup>0</sup> | 194                     | 1.0                      | Good    |
| 6801                | Battelle           | 718    | 1900        | Blank         | Poly           | 90 <sup>0</sup> | 200                     | 1.0                      | Good    |
| 6802                | Battelle           | 718    | 1900        | Blank         | Poly           | 90 <sup>0</sup> | 194                     | 1.0                      | Good    |
| 6803                | Battelle           | 718    | 1900        | Blank         | Poly           | 90 <sup>0</sup> | 197                     | 1.0                      | Good    |
| 6804                | Battelle           | 718    | 1900        | Blank         | Poly           | 90 <sup>0</sup> | 194                     | 1.0                      | Good    |
| 6805                | Battelle           | 718    | 1900        | Blank         | Poly           | 90 <sup>0</sup> | 194                     | 1.0                      | Good    |
| 6806                | Battelle           | 718    | 1900        | 10:1          | 0010           | 90 <sup>0</sup> | 184                     | .5                       | Good    |
| 6807                | Battelle           | 718    | 2000        | 10:1          | 0010           | 90 <sup>0</sup> | 178                     | .5                       | Good    |

## NICKEL BASE

| Extrusion<br>Number | Agency              | Alloy   | Temp.<br>oF   | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle      | P <sub>t</sub><br>(ksi) | V <sub>ex</sub><br>(ips) | Surface |
|---------------------|---------------------|---------|---------------|---------------|----------------|-------------------|-------------------------|--------------------------|---------|
| 6808                | Battelle            | 718     | 20 <b>0</b> 0 | 10:1          | 0010           | 90 <sup>0</sup>   | 178                     | 1.4                      | Good    |
| 6809                | Battelle            | 718     | 2000          | 10:1          | 0010           | 90 <sup>0</sup>   | 167                     | 2.0                      | Good    |
| 6810                | Battelle            | 718     | 2000          | 10:1          | 0010           | 90 <sup>0</sup>   | 173                     | 2.0                      | Good    |
| 6811                | Battelle            | 718     | 2000          | 10:1          | 0010           | 90 <sup>0</sup>   | 170                     | 2.1                      | Good    |
| 6812                | Battelle            | 718     | 2000          | 10:1          | 0010           | 90 <sup>0</sup>   | 167                     | 2.1                      | Good    |
| 6813                | Battelle            | 718     | 2000          | 10:1          | 0010           | 900               | 173                     | 1.9                      | Good    |
| 6814                | Battelle            | 718     | 2000          | 10:1          | 0010           | 90 <sup>0</sup>   | 173                     | 2.0                      | Good    |
| 6815                | Battelle            | 718     | 2000          | 10:1          | 0010           | 90 <sup>0</sup>   | 170                     | 2.0                      | Good    |
| 6816                | Battelle            | 718     | 2000          | 10:1          | 0010           | 90 <sup>0</sup>   | 173                     | 2.0                      | Good    |
| 6817                | Battelle            | 718     | 2000          | 10:1          | 0010           | 90 <sup>0</sup>   | 170                     | 1.9                      | Good    |
| 6819                | Polymet             |         | 2000          | 9:1           | Poly           | 60 <sup>0</sup>   | 178                     | .7                       | Bad     |
| 6824                | Sherritt<br>Gordon  | Ni-Base | 1800          | 9.6:1         | Poly           | 90 <sup>0</sup> R | 116                     | 1.2                      | Good    |
| 6825                | Sherritt-<br>Gordon | Ni-Base | 1800          | 10:1          | Poly           | 90 <sup>0</sup> R | 113                     | 1.1                      | Good    |
| 6826                | Sherritt-<br>Gordon | Ni-Base | 1800          | 10:1          | Poly           | 90 <sup>0</sup> R | 116                     | 1.1                      | Good    |
| 6827                | Sherritt-<br>Gordon | Ni-Base | 1900          | 10:1          | Poly           | 90°R              | 113                     | 1.1                      | Good    |
| 6828                | Sherritt-<br>Gordon | Ni-Base | 1900          | 10:1          | Poly           | 90°R              | 119                     | 1.0                      | Good    |
| 6829                | Sherritt-<br>Gordon | Ni-Base | 1900          | 10:1          | Poly           | 90 <sup>0</sup> R | 111                     | 1.0                      | Good    |
| 6830                | Sherritt-<br>Gordon | Ni-Base | 2000          | 10:1          | Poly           | 90 <sup>0</sup> R | 97                      | 1.2                      | Good    |

NICKEL BASE

| Extrusion<br>Number | Agency              | Alloy                             | Temp.<br>oF | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle      | Pt<br>(ksi) | V <sub>ex</sub><br>(ips) | Surface |
|---------------------|---------------------|-----------------------------------|-------------|---------------|----------------|-------------------|-------------|--------------------------|---------|
| 6831                | Sherritt-<br>Gordon | Ni-Base                           | 2000        | 10:1          | Poly           | 90 <sup>0</sup> R | 103         | 1.2                      | Good    |
| 6832                | Sherritt-<br>Gordon | Ni-Base                           | 2000        | 10:1          | Poly           | 90° R             | 104         | 1.1                      | Good    |
| 6840                | Pratt &<br>Whitney  | IN-100                            | 1750        | 2:1           | 0010           | 60°               | 126         | 1.5                      |         |
| 6841                | Pratt &<br>Whitney  | IN-100                            | 1700        | 2:1           | 0010           | 60 <sup>0</sup>   | 135         | .8                       |         |
| 6847                | Stellite            | Ni-16Cr-<br>4A1-Y <sub>2</sub> 03 | 1900        | 16.3:1        | Poly           | 90 <sup>0</sup>   | 132         | 2.2                      | Good    |
| 6848                | Stellite            | Ni-16Cr-<br>4A1-Y <sub>2</sub> 03 | 1900        | 16.3:1        | Poly           | 900               | 138         | 1.9                      | Good    |
| 6849                | Stellite            | Ni-16Cr-<br>4A1-Y <sub>2</sub> 03 | 1900        | 16.3:1        | Poly           | 90 <sup>0</sup>   | 138         | 1.9                      | Good    |
| 6850                | Stellite            | Ni-16Cr-<br>4A1-Y <sub>2</sub> 03 | 1900        | 20.5:1        | Poly           | 90 <sup>0</sup>   | 154         | 4.5                      | Good    |
| 6851                | Stellite            | Ni-16Cr-<br>4A1-Y <sub>2</sub> 03 | 1900        | 20.5:1        | Poly           | 90 <sup>0</sup>   | 156         | 4.5                      | Good    |
| 6852                | Stellite            | Ni-16Cr-<br>4A1-Y <sub>2</sub> 03 | 1900        | 20.5:1        | Poly           | 90 <sup>0</sup>   | 156         | 4.5                      | Good    |
| 6853                | Pratt &<br>Whitney  | IN-100 Mod.                       | 2050        | 8:1           | 0010           | 60 <sup>0</sup>   | 117         | 1.1                      | Good    |
| 6854                | Pratt &<br>Whitney  | MARM-200                          | 2050        | 8:1           | 0010           | 60 <sup>0</sup>   | 123         | 1.0                      | Good    |
| 6855                | Pratt &<br>Whitney  | MARM-200                          | 2150        | 20:1          | 0010           | 60 <sup>0</sup>   | 119         | 1.2                      | Good    |
| 6856                | Pratt &<br>Whitney  | Ni-Mo-Al                          | 2150        | 20:1          | 0010           | 60 <sup>0</sup>   | 135         | 1.0                      | Good    |

NICKEL BASE

| Extrusion<br>Number | Agency             | Alloy                             | Temp.<br>oF  | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle     | P <sub>t</sub><br>(ksi) | V <sub>ex</sub><br>(ips) | Surface |
|---------------------|--------------------|-----------------------------------|--------------|---------------|----------------|------------------|-------------------------|--------------------------|---------|
| 6857                | Pratt &<br>Whitney | B-1950                            | 2100         | 8:1           | 0010           | 60°              | 105                     | 1.2                      | Good    |
| 6858                | Pratt &<br>Whitney | Monoloy                           | 2100         | 8:1           | 0010           | 60 <sup>0</sup>  | 122                     | 1.1                      | Good    |
| 6864                | Polymet            | Ni-Base                           | 1700         | 12.5:1        | Poly           | 90 <sup>0</sup>  | 122                     | 2.0                      | Good    |
| 6866                | Pratt &<br>Whitney | MARM-200<br>Mod.                  | 2150         | 43:1          | 7052           | 120 <sup>0</sup> | 152                     | .9                       | Good    |
| 6867                | Pratt &<br>Whitney | MARM-200                          | 2150         | 43:1          | 7052           | 120 <sup>0</sup> | 159                     | .7                       | Good    |
| 6868                | Pratt &<br>Whitney | Ni-Mo-Al                          | 2200         | 43:1          | 7052           | 120 <sup>0</sup> | 167                     | .8                       | Good    |
| 6875                | Pratt &<br>Whitney | IN-100                            | 1600         | 2:1           | 0010           | 60 <sup>0</sup>  | 154                     | 0.7                      | Fair    |
| 6876                | Pratt &<br>Whitney | IN-100                            | 1650         | 2:1           | 0010           | 60 <sup>0</sup>  | 154                     | 0.7                      | Fair    |
| 6778                | Stellite           | Ni-16Cr-<br>4A1-Y <sub>2</sub> 03 | 1900         | 16:1          | Poly           | 90 <sup>0</sup>  | 130                     | 2.0                      | Good    |
| 6879                | Pratt &<br>Whitney | Ni-Mo-Al                          | 2200         | 43:1          | 7052           | 1200             | 155                     | 0.5                      | Good    |
| 6880                | Pratt &<br>Whitney | Ni-Mo-Al                          | 2200         | 43:1          | 7052           | 120 <sup>0</sup> | 165                     |                          | Good    |
| 6881                | Pratt &<br>Whitney | Ni-Mo-Al                          | 2200         | 43:1          | 7052           | 120 <sup>0</sup> | 147                     | 0.5                      | Good    |
| 6882                | Pratt &<br>Whitney | MARM-200<br>Mod.                  | 2200         | 43:1          | 7052           | 120 <sup>0</sup> | 148                     | 0.5                      | Good    |
| 6883                | Pratt &<br>Whitney | Ni-Cr-Al-<br>N-γ                  | <b>220</b> 0 | 43:1          | 7052           | 120 <sup>0</sup> | 139                     | 0.5                      | Good    |
| 6884                | Pratt &<br>Whitney | Ni-Cr-Al-<br>Ni-Y                 | 2200         | 43:1          | 7052           | 120 <sup>0</sup> | 140                     | 0.5                      | Good    |

37

# APPLIED METAL PROCESSING NICKEL BASE

| Extrusion<br>Number | Agency             | Alloy                            | Temp.<br>oF | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle     | P <sub>t</sub><br>(ksi) | Vex<br>(ips) | Surface |
|---------------------|--------------------|----------------------------------|-------------|---------------|----------------|------------------|-------------------------|--------------|---------|
| 6886                | Pratt &<br>Whitney | Ni-Cr-Al-<br>γ+WC                | 2200        | 43:1          | 7052           | 120 <sup>0</sup> |                         | .7           | Good    |
| 6887                | Pratt &<br>Whitney | Ni-Cr-Al-<br>y+WC                | 2200        | 43:1          | 7052           | 120 <sup>0</sup> | 157                     | 1.0          | Good    |
| 6888                | Pratt &<br>Whitney | Ni-Cr-Al-γ<br>TiC+W              | 2200        | 43:1          | 7052           | 120 <sup>0</sup> | 159                     | 1.0          | Good    |
| 6889                | Pratt &<br>Whitney | Ni-Cr-Al-<br>γ-Ti-B              | 2200        | 43:1          | 7052           | 120 <sup>0</sup> | 154                     | 1.0          | Good    |
| 6890                | Pratt &<br>Whitney | Ni-Cr-Al-<br>γ+Ti-C <sup>2</sup> | 2200        | 43:1          | 7052           | 120 <sup>0</sup> | 147                     | 1.1          | Good    |
| 6891                | Pratt &<br>Whitney | Ni-Cr-Al-<br>y+Cb-C              | 2200        | 43:1          | 7052           | 120 <sup>0</sup> | 157                     | .9           | Good    |
| 6892                | Pratt &<br>Whitney | Ni-Cr-Al-<br>γ+Ti-C-Cb           | 2200        | 43:1          | 7052           | 120 <sup>0</sup> | 165                     | .9           | Good    |
| 6893                | Pratt &<br>Whitney | Ni-Mo-Al                         | 2200        | 43:1          | 7052           | 120 <sup>0</sup> | 178                     | .8           | Good    |
| 6894                | Pratt &<br>Whitney | Ni-Mo-Al                         | 2200        | 43:1          | 7052           | 120 <sup>0</sup> | 177                     | 1.0          | Good    |
| 6895                | Pratt &<br>Whitney | Hi-C Mod.<br>AF2-1DA             | 2200        | 43:1          | 7052           | 120 <sup>0</sup> | 140                     | 1.1          | Good    |
| 6896                | Pratt &<br>Whitney | C. Mod.<br>AF2-1DA               | 2200        | 43:1          | 7052           | 120 <sup>0</sup> | 132                     | 1.3          | Good    |
| 6897                | Pratt &<br>Whitney | C+B Mod.<br>AF2-1DA              | 2200        | 43:1          | 7052           | 120 <sup>0</sup> | 135                     | 1.2          | Good    |
| 6898                | Pratt &<br>Whitney | B. Mod.<br>MARM-200              | 2200        | 43:1          | 7052           | 120 <sup>0</sup> | 146                     | 1.0          | Good    |
| 6916                | Pratt &<br>Whitney | MARM-200                         | 2200        | 44.6:1        | 0010           | 120 <sup>0</sup> | 146                     | 1.0          | Good    |

## NICKEL BASE

| Extrusion<br>Number | Agency                | Alloy                             | Temp.<br>°F | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle     | P<br>(ksi) | V <sub>ex</sub><br>(ips) | Surface   |
|---------------------|-----------------------|-----------------------------------|-------------|---------------|----------------|------------------|------------|--------------------------|-----------|
| 6917                | Pratt &<br>Whitney    | MARM-200                          | 2250        | 44.6:1        | 7052           | 120 <sup>0</sup> | 130        | 1.2                      | Excellent |
| 6918                | Pratt &<br>Whitney    | Monoloy-<br>555                   | 2250        | 44.6:1        | 7052           | 120 <sup>0</sup> | 154        | 1.0                      | Excellent |
| 6919                | Pratt &<br>Whitney    | MARM-200                          | 2300        | 44.6:1        | 7052           | 120 <sup>0</sup> | 151        | 1.2                      | Good      |
| 6920                | Pratt &<br>Whitney    | Ni-15Mo-<br>8A1                   | 2300        | 44.6:1        | 7052           | 120 <sup>0</sup> | 140        | 1.0                      | Good      |
| 6921                | Pratt &<br>Whitney    | Ni-18Mo-<br>8A1                   | 2300        | 44.6:1        | 7052           | 120 <sup>0</sup> | 146        | 1.0                      | Good      |
| 6944                | Pratt &<br>Whitney    | MARM-247                          | 2250        | 44:1          | 0010           | 120 <sup>0</sup> | 146        | 1.1                      | Good      |
| 6945                | Pratt &<br>Whitney    | MARM-247                          | 2250        | 44:1          | 0010           | 120 <sup>0</sup> | 146        | 1.1                      | Good      |
| 6946                | AiResearch<br>Arizona | MARM-247                          | 2200        | 43:1          | 0010           | 120 <sup>0</sup> | 155        | 1.0                      | Good      |
| 6947                | AiResearch<br>Arizona | MARM-247                          | 2200        | 43:1          | 0010           | 120 <sup>0</sup> | 151        | 1.1                      | Good      |
| 6948                | Pratt &<br>Whitney    | Ni-72.76Cr<br>-2.4-(+)            | 1850        | Blank         | Poly           | 120 <sup>0</sup> | 192        | 1.0                      | Excellent |
| 6949                | Pratt &<br>Whitney    | Ni-72.76Cr<br>-12.4-(+)           | 1850        | Blank         | Poly           | 120 <sup>0</sup> | 190        | 1.0                      | Excellent |
| 6950                | Pratt &<br>Whitney    | Ni-63.7-<br>12.4Cr-(+)            | 1850        | Blank         | Poly           | 120 <sup>0</sup> | 193        | 1.0                      | Excellent |
| 6951                | Pratt &<br>Whitney    | Ni-63.76Cr<br>-12.4-(+)           | 1850        | Blank         | Poly           | 120 <sup>0</sup> | 189        | 1.0                      | Excellent |
| 6952                | Pratt &<br>Whitney    | Ni-50.2Cr-<br>12.4Co-<br>22.5-(+) | 1850        | Blank         | Poly           | 120 <sup>0</sup> | 192        | 1.0                      | Excellent |

## NICKEL BASE

| Extrusion |                    |                                    | Temp.          | Red.  | Billet | Die              | Pt    | Vex   | A DEPARTMENT |
|-----------|--------------------|------------------------------------|----------------|-------|--------|------------------|-------|-------|--------------|
| Number    | Agency             | Alloy                              |                | Ratio | Lube   | Angle            | (ks1) | (ips) | Surface      |
| 6953      | Pratt &<br>Whitney | Ni-50.26Cr<br>-12.4Co-<br>9.0- (+) | 1850           | Blank | Poly   | 120 <sup>0</sup> | 192   | 1.0   | Excellent    |
| 6954      | Pratt &<br>Whitney | Ni-55.00Cr<br>-12.4Co-18-          | 1850<br>(+)    | Blank | Poly   | 120°             | 194   | 1.0   | Excellent    |
| 6955      | Pratt &<br>Whitney | N1-55.00Cr<br>-12.4Co-<br>18-(+)   | 1850           | Blank | Poly   | 120 <sup>0</sup> | 192   | 1.0   | Excellent    |
| 6956      | Pratt &<br>Whitney | N1-64.09-<br>12.4Cr-<br>22.5Co(+)  | 1850           | Blank | Poly   | 120 <sup>0</sup> | 192   | 1.0   | Excellent    |
| 6957      | Pratt &<br>Whitney | Ni-64.09Cr<br>-12.4-9.0Co          | 1850<br>(+)    | Blank | Poly   | 120 <sup>0</sup> | 190   | 1.0   | Excellent    |
| 6958      | Pratt &<br>Whitney | Ni-53.34-<br>12.4Cr-22.50          | 1850<br>Co (+) | Blank | Poly   | 120 <sup>0</sup> | 192   | 1.0   | Excellent    |
| 6959      | Pratt &<br>Whitney | Ni-53.34-<br>12.4Cr-<br>18.0Co(+)  | 1850           | Blank | Poly   | 120 <sup>0</sup> | 194   | 1.0   | Excellent    |
| 6960      | Pratt &<br>Whitney | N1-60.62-<br>12.4Cr-<br>9.0Co-(+)  | 1850           | Blank | Poly   | 120 <sup>0</sup> | 196   | 1.0   | Excellent    |
| 6961      | Pratt &<br>Whitney | N1-60.09-<br>12.4Cr-<br>9.0Co-(+)  | 1850           | Blank | Poly   | 120 <sup>0</sup> | 196   | 1.0   | Excellent    |
| 6962      | Pratt &<br>Whitney | N1-62.34-<br>12.4Cr-<br>9.0Co-(+)  | 1850           | Blank | Poly   | 120 <sup>0</sup> | 194   | 1.0   | Excellent    |
| 6963      | Pratt &<br>Whitney | Ni-62.34-<br>12.4Cr-<br>9.0Co-(+)  | 1850           | Blank | Poly   | 120 <sup>0</sup> | 194   | 1.0   | Excellent    |

## NICKEL BASE

| Extrusion<br>Number | Agency             | Alloy                                | Temp.<br>°F | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle     | Pt<br>(ksi) | V <sub>ex</sub><br>(ips) | Surface   |
|---------------------|--------------------|--------------------------------------|-------------|---------------|----------------|------------------|-------------|--------------------------|-----------|
| 6964                | Pratt &<br>Whitney | N1-57.99Cr<br>-12.15Co-<br>13.9-(+)  | 1850        | Blank         | Poly           | 120 <sup>0</sup> | 194         | 1.0                      | Excellent |
| 6965                | Pratt &<br>Whitney | N1-58.05Cr<br>-12.16Co-<br>13.9-(+)  | 1850        | Blank         | Poly           | 120 <sup>0</sup> | 192         | 1.0                      | Excellent |
| 6966                | Pratt &<br>Whitney | Ni-58.5Cr-<br>12.16Co-<br>13.9-(+)   | 1850        | Blank         | Poly           | 120 <sup>0</sup> | 194         | 1.0                      | Excellent |
| 6967                | Pratt &<br>Whitney | Ni-58.53Cr<br>-12.16Co-<br>13.9-(+)  | 1850        | Blank         | Poly           | 120 <sup>0</sup> | 194         | 1.0                      | Excellent |
| 6968                | Pratt &<br>Whitney | N1-58.34Cr<br>-12.17Co-<br>13.9-(+)  | 1850        | Blank         | Poly           | 120 <sup>0</sup> | 196         | 1.0                      | Excellent |
| 6969                | Pratt &<br>Whitney | N1-58.34Cr<br>-12.17Co-<br>13.9-(+)  | 1850        | Blank         | Poly           | 120 <sup>0</sup> | 197         | 1.0                      | Excellent |
| 6970                | Pratt &<br>Whitney | N1-58.2Cr<br>-12.14Co-<br>13.90-(+)  | 1850        | Blank         | Poly           | 120 <sup>0</sup> | 194         | 1.0                      | Excellent |
| 6971                | Pratt &<br>Whitney | N1-57.99Cr<br>-12.10Co-<br>13.85-(+) | 1850        | Blank         | Poly           | 120 <sup>0</sup> | 194         | 1.0                      | Excellent |
| 6972                | Pratt &<br>Whitney | Ni-72.76Cr<br>-12.4-(+)              | 2000        | 6:1           | 0010           | 60 <sup>0</sup>  | 97          | 1.5                      | Good      |
| 6973                | Pratt &<br>Whitney | Ni-72.76Cr<br>-12.4-(+)              | 2000        | 6:1           | 0010           | 60 <sup>0</sup>  | 100         | 1.4                      | Good      |
| 6974                | Pratt &<br>Whitney | Ni-63.76Cr<br>12.4Co-<br>9.0-(+)     | 2000        | 6:1           | 0010           | 60 <sup>0</sup>  | 97          | 1.4                      | Good      |

## NICKEL BASE

| Extrusion<br>Number | Agency             | Alloy                              | Temp.<br><sup>O</sup> F | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle    | P <sub>t</sub><br>(ksi) | V <sub>ex</sub><br>(ips) | Surface |
|---------------------|--------------------|------------------------------------|-------------------------|---------------|----------------|-----------------|-------------------------|--------------------------|---------|
| 6975                | Pratt &<br>Whitney | Ni-63.76Cr<br>12.4Co-<br>9.0-(+)   | 2000                    | 6:1           | 0010           | 60 <sup>0</sup> | 96                      | 1.4                      | Good    |
| 6976                | Pratt &<br>Whitney | Ni-50.26Cr<br>-12.4Co-<br>22.5-(+) | 2000                    | 6:1           | 0010           | 60 <sup>0</sup> | 97                      | 1.4                      | Good    |
| 6977                | Pratt &<br>Whitney | Ni-50.26Cr<br>-12.4Co-<br>22.5-(+) | 2000                    | 6:1           | 0010           | 60 <sup>0</sup> | 81                      | 1.5                      | Good    |
| 6978                | Pratt &<br>Whitney | Ni-55.00Cr<br>-12.4Co-<br>18.0-(+) | 2000                    | 6:1           | 0010           | 60 <sup>0</sup> | 92                      | 1.4                      | Good    |
| 6979                | Pratt &<br>Whitney | Ni-55.00Cr<br>-12.4Co-<br>18.0-(+) | 2000                    | 6:1           | 0010           | 60°             | 92                      | 1.4                      | Good    |
| 6980                | Pratt &<br>Whitney | Ni-64.09Cr<br>-12.4Co-<br>9.0-(+)  | 2000                    | 6:1           | 0010           | 60 <sup>0</sup> | 97                      | 1.4                      | Good    |
| 6981                | Pratt &<br>Whitney | Ni-64.09Cr<br>-12.4Co-<br>9.0-(+)  | 2000                    | 6:1           | 0010           | 60 <sup>0</sup> | 100                     | 1.4                      | Good    |
| 6982                | Pratt &<br>Whitney | Ni-53.34Cr<br>-12.4Co-<br>18.0-(+) | 2000                    | 6:1           | 0010           | 60 <sup>0</sup> | 86                      | 1.4                      | Good    |
| 6983                | Pratt &<br>Whitney | Ni-53.34Cr<br>12.4Co-<br>18.0-(+)  | 2000                    | 6:1           | 0010           | 60°             | 86                      | 1.5                      | Good    |
| 6984                | Pratt &<br>Whitney | N1-60.62Cr<br>-12.4Co-<br>9.0-(+)  | 2000                    | 6:1           | 0010           | 60 <sup>0</sup> | 92                      | 1.3                      | Good    |

## NICKEL BASE

| Extrusion<br>Number | Agency             | Alloy                                | Temp.<br>oF | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle    | P <sub>t</sub><br>(ksi) | V <sub>ex</sub><br>(ips) | Surface |
|---------------------|--------------------|--------------------------------------|-------------|---------------|----------------|-----------------|-------------------------|--------------------------|---------|
| 6985                | Pratt &<br>Whitney | N1-60.62Cr<br>12.4Co-<br>9.0-(+)     | 2000        | 6:1           | 0010           | 60 <sup>0</sup> | 96                      | 1.3                      | Good    |
| 6986                | Pratt &<br>Whitney | Ni-62.34Cr<br>-12.4Co-<br>9.0-(+)    | 2000        | 6:1           | 0010           | 60 <sup>0</sup> | 92                      | 1.4                      | Good    |
| 6987                | Pratt &<br>Whitney | Ni-62.34Cr<br>-12.4Co-<br>9.0-(+)    | 2000        | 6:1           | 0010           | 600             | 97                      | 1.3                      | Good    |
| 6988                | Pratt &<br>Whitney | Ni-57.99Cr<br>12.15Co-<br>13.90-(+)  | 2000        | 6:1           | 0010           | 60 <sup>0</sup> | 108                     | 1.2                      | Good    |
| 6989                | Pratt &<br>Whitney | Ni-58.05Cr<br>-12.16Co-<br>13.92-(+) | 2000        | 6:1           | 0010           | 60 <sup>0</sup> | 103                     | 1.2                      | Good    |
| 6990                | Pratt &<br>Whitney | Ni-58.53Cr-<br>12.16Co-<br>13.92-(+) | 2000        | 6:1           | 0010           | 60 <sup>0</sup> | 97                      | 1.2                      | Good    |
| 6991                | Pratt &<br>Whitney | Ni-58.53Cr<br>-12.16Co-<br>13.92-(+) | 2000        | 6:1           | 0010           | 60°             | 107                     | 1.1                      | Good    |
| 6992                | Pratt &<br>Whitney | Ni-58.34Cr<br>12.17Co-<br>13.93-(+)  | 2000        | 6:1           | 0010           | 60 <sup>0</sup> | 92                      | 1.3                      | Good    |
| 6993                | Pratt &<br>Whitney | Ni-58.34Cr<br>-12.17Co-<br>13.93-(+) | 2000        | 6:1           | 0010           | 60 <sup>0</sup> | 92                      | 1.3                      | Good    |
| 6994                | Pratt &<br>Whitney | N1-58.2Cr-<br>12.14Co-<br>13.90-(+)  | 2000        | 6:1           | 0010           | 60°             | 89                      | 1.2                      | Good    |

# NICKEL BASE

| Extrusion<br>Number | Agency              | Alloy  | Temp.<br>oF | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle      | P <sub>t</sub><br>(ksi) | V <sub>ex</sub><br>(ips) | Surface |
|---------------------|---------------------|--|-------------|---------------|----------------|-------------------|-------------------------|--------------------------|---------|
| 6995                | Pratt &<br>Whitney  | N1-57.99Cr<br>-12.10Co-<br>13.85-(+)                   | 2000        | 6:1           | 0010           | 60 <sup>0</sup>   | 86                      | 1.3                      | Good    |
| 6998                | Pratt &<br>Whitney  | MARM-200   | 2150        | 43:1          | 7052           | 120 <sup>0</sup>  | 162                     | .5                       | Good    |
| 6999                | Pratt &<br>Whitney  | AF2-1DA  | 2150        | 43:1          | 7052           | 120 <sup>0</sup>  | 165                     | .5                       | Good    |
| 7000                | Pratt &<br>Whitney  | MARM-247   | 2200        | 43:1          | 7052           | 120 <sup>0</sup>  | 140                     | .5                       | Good    |
| 7001                | Pratt &<br>Whitney  | Monoloy<br>444   | 2250        | 43:1          | 7052           | 120 <sup>0</sup>  | 151                     | .6                       | Good    |
| 7002                | Pratt &<br>Whitney  | MARM-200   | 2250        | 20:1          | 7052           | 60 <sup>0</sup>   | 124                     | 1.4                      | Good    |
| 7003                | Pratt &<br>Whitney  | AF2-1DA  | 2250        | 43:1          | 7052           | 120 <sup>0</sup>  | 154                     | 1.3                      | Good    |
| 7004                | Pratt &<br>Whitney  | Ni-18Mo-8A1  | 2300        | 43:1          | 7052           | 120 <sup>0</sup>  | 140                     | 1.4                      | Good    |
| 70 <b>05</b>        | Pratt &<br>Whitney  | Ni-21Mo-8A1  | 2300        | 43:1          | 7052           | 120 <sup>0</sup>  | 138                     | 1.3                      | Good    |
| 7006                | Pratt &<br>Whitney  | N1-9Cr-8A1-<br>9W2C                                    | 2300        | 43:1          | 7052           | 120 <sup>0</sup>  | 136                     | 1.4                      | Good    |
| 7007                | Sherritt-<br>Gordon | Ni-16Cr-<br>4.5A1-<br>0.5Y <sub>2</sub> 0 <sub>3</sub> | 1832        | 10:1          | Poly           | 90 <sup>0</sup> R | 116                     | 1.3                      | Good    |
| 7008                | Sherritt-<br>Gordon | Ni-16Cr-<br>4.5A1-<br>0.5Y <sub>2</sub> 0 <sub>3</sub> | 1832        | 10:1          | Poly           | 90 <sup>0</sup> R | 117                     | 1.3                      | Good    |

## NICKEL BASE

| Extrusion<br>Number | Agency              | Alloy  | Temp.<br><sup>o</sup> F | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle      | Pt<br>(ksi) | V <sub>ex</sub><br>(ips) | Surface |
|---------------------|---------------------|--|-------------------------|---------------|----------------|-------------------|-------------|--------------------------|---------|
| 7009                | Sherritt-<br>Gordon | N1-16Cr-<br>4.5A1-<br>0.5Y <sub>2</sub> 03             | 1832                    | 12.5:1        | Poly           | 90 <sup>0</sup> R | 140         | 1.1                      | Good    |
| 7010                | Sherritt-<br>Gordon | Ni-16Cr-<br>4.5A1-<br>0.5Y <sub>2</sub> 0 <sub>3</sub> | 1832                    | 12.5:1        | Poly           | 90 <sup>0</sup> R | 146         | 1.1                      | Good    |
| 7011                | Sherritt-<br>Gordon | Ni-16Cr-<br>4.5A1-<br>0.5Y <sub>2</sub> 0 <sub>3</sub> | 1922                    | 10:1          | Poly           | 90 <sup>0</sup> r | 116         | 1.3                      | Good    |
| 7012                | Sherritt-<br>Gordon | Ni-16Cr-<br>4.5A1-<br>0.5Y203                          | 1922                    | 10:1          | Poly           | 90° <sub>R</sub>  | 116         | 1.2                      | Good    |
| 7013                | Sherritt-<br>Gordon | Ni-16Cr-<br>4.5A1-<br>0.5Y <sub>2</sub> 0 <sub>3</sub> | 1922                    | 12.5:1        | Poly           | 90° <sub>R</sub>  | 136         | 1.2                      | Good    |
| 7014                | Sherritt-<br>Gordon | Ni-16Cr-<br>4.5A1-<br>0.5Y203                          | 1922                    | 12.5:1        | Poly           | 90°R              | 138         | 1.2                      | Good    |
| 7015                | Sherritt-<br>Gordon | Ni-16Cr-<br>4.5A1-<br>0.5Y <sub>2</sub> 0 <sub>3</sub> | 1922                    | 12.5:1        | Poly           | 90 <sup>0</sup> r | 132         | 1.3                      | Good    |
| 7016                | Sherritt-<br>Gordon | Ni-16Cr-<br>5A1-2Th0 <sub>2</sub>                      | 1922                    | 12.5:1        | Poly           | 90 <sup>0</sup> r | 143         | 1.1                      | Good    |
| <br>7017            | Sherritt-<br>Gordon | Ni-16Cr-<br>4.5A1-<br>0.5Y <sub>2</sub> 0 <sub>3</sub> | 2012                    | 10:1          | Poly           | 90 <sup>0</sup> R | 103         | 1.4                      | Good    |
| 7018                | Sherritt-<br>Gordon | Ni-16Cr-<br>4.5A1-<br>0.5Y <sub>2</sub> 0 <sub>3</sub> | 2012                    | 10:1          | Poly           | 90 <sup>0</sup> R | 108         | 1.3                      | Good    |
| 7019                | Sherritt-<br>Gordon | N1-16Cr-<br>4.5A1-<br>0.5Y203                          | 2012                    | 12.5:1        | Poly           | 90° <sub>R</sub>  | 124         | 1.3                      | Good    |

## NICKEL BASE

| Extrusion<br>Number | Agency                       | Alloy                                      | Temp.<br>°F | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle      | P <sub>t</sub><br>(ksi) | V <sub>ex</sub><br>(ips) | Surface |
|---------------------|------------------------------|--|-------------|---------------|----------------|-------------------|-------------------------|--------------------------|---------|
| 7020                | She <b>r</b> ritt-<br>Gordon | Ni-16Cr-<br>4.5A1-<br>0.5Y <sub>2</sub> 03 | 2012        | 12.5:1        | Poly           | 90 <sup>0</sup> r | 124                     | 1.3                      | Good    |
| 7054                | Pratt &<br>Whitney           | AF2-1DA<br>Mod.                            | 2250        | 43:1          | .7052          | 120 <sup>0</sup>  | 130                     | 1.1                      | Good    |
| 7055                | Pratt &<br>Whitney           | AF2-1DA<br>Mod.                            | 2250        | 43:1          | 7052           | 120 <sup>0</sup>  | 130                     | 1.2                      | Good    |
| 7056                | Pratt &<br>Whitney           | Ni-18Mo-<br>6A1                            | 2250        | 20:1          | 7052           | 120 <sup>0</sup>  | 119                     | 1.2                      | Good    |
| 7057                | Pratt &<br>Whitney           | Ni-16Cr-<br>4A1-15Cb                       | 2250        | 43:1          | 7052           | 120 <sup>0</sup>  | 151                     | .7                       | Good    |
| 7058                | Pratt &<br>Whitney           | Ni-14Mo-<br>6A1-6Ta                        | 2300        | 43:1          | 7052           | 120 <sup>0</sup>  | 162                     | .8                       | Good    |
| 7059                | Pratt &<br>Whitney           | Ni-15Mo-<br>7Al-3Ta                        | 2300        | 43:1          | 7052           | 120 <sup>0</sup>  | 162                     | .7                       | Good    |
| 7060                | Pratt &<br>Whitney           | Ni-18Mo-<br>7A1-3Ta                        | 2300        | 43:1          | 7052           | 120 <sup>0</sup>  | 151                     | .9                       | Good    |
| 7061                | Pratt &<br>Whitney           | Ni-6Cr-2.5<br>Al-20Cb                      | 2300        | 43:1          | 7052           | 120 <sup>0</sup>  |                         |                          |         |
| 7062                | Pratt &<br>Whitney           | Ni-Cr-<br>Al+Tac                           | 2300        | 43:1          | 7052           | 120 <sup>0</sup>  | 135                     | 1.1                      | Good    |
| 7063                | Pratt &<br>Whitney           | Ni-Tac-<br>Low-C                           | 2300        | 43:1          | 7052           | 120 <sup>0</sup>  | 127                     | 1.2                      | Good    |
| 7064                | Pratt &<br>Whitney           | Ni-6Cr-<br>6A1-10Cb                        | 2300        | 43:1          | 7052           | 120 <sup>0</sup>  | 108                     | 1.2                      | Good    |
| 7065                | Pratt &<br>Whitney           | Ni-13Cb-<br>8A1                            | 2300        | 43:1          | 7052           | 120 <sup>0</sup>  | 119                     | 1.1                      | Good    |

## NICKEL BASE

| Extrusion<br>Number | Agency             | Alloy              | Temp. | Red.<br>Ratio | Billet<br>Lube | Die<br><u>Angle</u> | P <sub>t</sub><br>(ksi) | Ve <sub>x</sub><br>(ips) | Surface |
|---------------------|--------------------|--------------------|-------|---------------|----------------|---------------------|-------------------------|--------------------------|---------|
| 7066                | Pratt &<br>Whitney | Ni-18Mo-<br>8A1    | 2300  | 43:1          | 7052           | 120 <sup>0</sup>    | 140                     | 1.0                      | Good    |
| 7067                | Pratt &<br>Whitney | Ni-18Mo-<br>8A1+Zr | 2360  | 43:1          | 7052           | 120 <sup>0</sup>    | 130                     | 1.2                      | Good    |

## IRON BASE

| Extrusion<br>Number | Agency             | Alloy             | Temp.<br>oF | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle     | P <sub>t</sub><br>(ksi) | V <sub>ex</sub><br>(ips) | Surface |
|---------------------|--------------------|-------------------|-------------|---------------|----------------|------------------|-------------------------|--------------------------|---------|
| 6938                | Pratt &<br>Whitney | Mild Steel        | 1600        | 8:1           | 0010           | 120 <sup>0</sup> | 163                     | 1.3                      | Good    |
| 6939                | Pratt &<br>Whitney | Mild Steel        | 1600        | 8:1           | 0010           | 120 <sup>0</sup> | 154                     | 1.4                      | Good    |
| 6940                | Pratt &<br>Whitney | Mild Steel        | 1600        | 8:1           | 0010           | 120 <sup>0</sup> | 161                     | 1.4                      | Good    |
| 6941                | Pratt &<br>Whitney | Mild Steel        | 1600        | 8:1           | 0010           | 120 <sup>0</sup> | 155                     | 1.4                      | Good    |
| 6942                | Pratt &<br>Whitney | Mild Steel        | 1600        | 8:1           | 0010           | 120 <sup>0</sup> | 154                     | 1.4                      | Good    |
| 6943                | Pratt &<br>Whitney | Mild Steel        | 1600        | 8:1           | 0010           | 120 <sup>0</sup> | 157                     | 1.4                      | Good    |
| 6996                | Pratt &<br>Whitney | Fe-9Ni-4Co-<br>2C | 1500        | 12:1          | 8871           | 60 <sup>0</sup>  | 134                     | 1.5                      | Good    |
| 6997                | Pratt &<br>Whitney | Fe-9Ni-4Co-<br>2C | 1400        | 12:1          | 8871           | 60 <sup>0</sup>  | 144                     | 1.3                      | Good    |
| <b>7</b> 021        | Pratt &<br>Whitney | Mild Steel        | 1600        | 8:1           | 0010           | 900              | 153                     | 1.4                      | Good    |
| 7022                | Pratt &<br>Whitney | Mild Steel        | 1600        | 7.8:1         | 0010           | 90 <sup>0</sup>  | 167                     | 1.4                      | Good    |
| 7023                | Pratt &<br>Whitney | Mild Steel        | 1600        | 7.8:1         | 0010           | 90 <sup>0</sup>  | 157                     | 1.4                      | Good    |
| 7024                | Pratt &<br>Whitney | Mild Steel        | 1600        | 7.8:1         | 0010           | 90 <sup>0</sup>  | 165                     | 1.4                      | Good    |
| 7025                | Pratt &<br>Whitney | Mild Steel        | 1600        | 7.8:1         | 0010           | 90 <sup>0</sup>  | 170                     | 1.4                      | Good    |
| 7026                | Pratt &<br>Whitney | Mild Steel        | 1600        | 7.8:1         | 0010           | 90 <sup>0</sup>  | 171                     | 1.4                      | Good    |

COBALT BASE

| Extrusion<br>Number | Agency             | Alloy               | Temp.<br>oF | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle     | Pt<br>(ksi) | Vex<br>(ips) | Surface |
|---------------------|--------------------|---------------------|-------------|---------------|----------------|------------------|-------------|--------------|---------|
| 6758                | Polymet            | Co-18Cr-<br>5Mo-2B  | 1750        | 16:1          | Poly           | 90 <sup>0</sup>  | 113         | 2.0          | Good    |
| 6759                | Polymet            | Co-20W-<br>28Cr     | 2000        | 9:1           | Poly           | 90 <sup>0</sup>  | 100         | 2.0          | Good    |
| 6760                | Polymet            | Co-20W-<br>28Cr     | 2000        | 9:1           | Poly           | 900              | 103         | 2.0          | Good    |
| 6863                | Polymet            | Co-Base             | 2000        | 16:1          | Poly           | 90 <sup>0</sup>  | 97          | 2.1          | Good    |
| 6871                | Polymet            | Co-Base             | 2000        | 9:1           | Poly           | 900              | 73          | 2.5          | Good    |
| 6877                | Pratt &<br>Whitney | Co-Tac 741          | 2200        | 43.73<br>:1   | 7052           | 1200             | 132         | 0.5          | Good    |
| 6878                | Pratt &<br>Whitney | Co-Tac 741          | 2200        | 43:1          | 7 <b>0</b> 52  | 120 <sup>0</sup> | 142         |              | Good    |
| 6905                | Polymet            | Co-30Cr-<br>W/o-20W | 2000        | 16.3:1        | Poly           | 90 <sup>0</sup>  | 151         | 1.7          | Good    |
| 6906                | Polymet            | Co-30Cr-<br>W/o-20W | 2000        | 8.9:1         | Poly           | 90 <sup>0</sup>  | 143         | 1.9          | Good    |
| 6907                | Polymet            | Co-30Cr-<br>W/o-20W | 2200        | 8.9:1         | Poly           | 90 <sup>0</sup>  | 143         | 2.0          | Good    |
| 6908                | Polymet            | Co-30Cr-<br>20W     | 2000        | 16.34<br>:1   | Poly           | 90 <sup>0</sup>  | 167         | 2.0          | Good    |

49

.

## ALUMINUM BASE

| Extrusion<br>Number | n<br>Agency        | Alloy            | Temp.<br><sup>o</sup> F | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle    | P <sub>t</sub><br>(ksi) | V <sub>ex</sub><br>(ips) | Surface |
|---------------------|--------------------|------------------|-------------------------|---------------|----------------|-----------------|-------------------------|--------------------------|---------|
| 6789                | AFML/LLM-1         | 17 Al<br>Powder  | 2575                    |               | 7740           | 90 <sup>0</sup> | 43                      | 1.5                      | Good    |
| 6835                | AFML/LLM           | 7075-A1          | 900                     | 10:1          | Poly           | 90 <sup>0</sup> | 157                     | .8                       | Good    |
| 6865                | Pratt &<br>Whitney | 7057-A1<br>Allov | 850                     | Blank         | Poly           | 90 <sup>0</sup> |                         | .5                       | Good    |

## COPPER BASE

| Extrusion<br>Number | Agency   | Alloy | Temp.<br>oF | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle    | Pt<br>(ksi) | Vex<br>(ips) | Surface |
|---------------------|----------|-------|-------------|---------------|----------------|-----------------|-------------|--------------|---------|
| 6834                | AFML/LLM | Cu.   | 900         | 10:1          | Poly           | 90 <sup>0</sup> | 146         | 1.0          | Good    |
| 6869                | AFML/LLM | Cu.   | 900         | 10:1          | Poly           | 90 <sup>0</sup> | 148         | 1.1          | Good    |
| 6870                | AFML/LLM | Cu.   | 900         | 10:1          | Poly           | 90 <sup>0</sup> | 159         | 1.1          | Good    |

### TANTALUM BASE

| Extrusion<br>Number | Agency                  | Alloy   | Temp.<br>°F | Red.<br>Ratio | Billet<br>Lube | Die<br>Angle    | P <sub>t</sub><br>(ksi) | V <sub>ex</sub><br>(ips) | Surface   |
|---------------------|-------------------------|---------|-------------|---------------|----------------|-----------------|-------------------------|--------------------------|-----------|
| 6771                | University<br>of Calif. | Ta-20Hf | 3000        | 2.5:1         | Bare           | 60 <sup>0</sup> | 97                      | 4.5                      | Excellent |

. . ≎U.S.Government Printing Office: 1978 — 757-080/50