

AD-A059 854

ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND ABERD--ETC F/G 19/1
SIMULATION OF LOW LEVEL EXPLOSIVES BLAST LOADINGS AT FULL SCALE--ETC(U)
JUL 78 E J GION

UNCLASSIFIED

ARBRL-MR-02853

SBIE-AD-E430 104

NL

| OF |

AD
A069854



END

DATE

FILMED

12-78

DDC

AD A0 59 854

DDC FILE COPY

12
NW
LEVEL II
AD-E430104

MEMORANDUM REPORT ARBRL-MR-02853

SIMULATION OF LOW LEVEL EXPLOSIVES BLAST
LOADINGS AT FULL SCALE BY MODIFICATIONS
TO BRL DUAL SHOCK TUBE FACILITY

Edmund J. Gion

July 1978

DDC
RECEIVED
OCT 16 1978
B



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

78 09 12 017

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report by originating
or sponsoring activity is prohibited.

Additional copies of this report may be obtained
from the National Technical Information Service,
U.S. Department of Commerce, Springfield, Virginia
22161.

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

*The use of trade names or manufacturers' names in this report
does not constitute indorsement of any commercial product.*

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MEMORANDUM REPORT ARBRL-MR-02855	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) SIMULATION OF LOW LEVEL EXPLOSIVES BLAST LOADINGS AT FULL SCALE BY MODIFICATIONS TO BRL DUAL SHOCK TUBE FACILITY.	5. TYPE OF REPORT & PERIOD COVERED Final rept.	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Edmund J. Gion	8. CONTRACT OR GRANT NUMBER(s)	9. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS J.S. Army Armament Research & Development Command J.S. Army Ballistic Research Laboratory ATTN: DRDAR-BL Aberdeen Proving Ground, MD 21005	12. REPORT DATE JULY 1978	13. NUMBER OF PAGES 42
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) 1244p.	15. SECURITY CLASS. (of this report) UNCLASSIFIED	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited. 18 SBIE 19 AD-E430 104		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Shock Tubes Blast Waves Simulated Blast Waves Blast from Explosives		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A concept is described permitting full scale testing of walls, of 3.7m (12 ft) height under simulated explosive blast loadings with pressures of 70 kPa (10 psi), 50ms positive duration. The existing BRL 2.4m (8 ft) diameter shock tube with modification was the hardware motivating the inquiry; and this hardware is used by way of example in the calculation of numbers and graphs. An enlarged 3.7m test or		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

393 471

LB

next page

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

cont.

→ driven section is added to the 2.4m driver section to accommodate full scale test dimensions. The normal straight shock tube operating cycle is then extended by testing at a location where the reflected expansion waves from the breech overtake and weaken the shock. The resulting pressure loading is a decaying pulse (i.e., blast-wave type) with determinable duration.

↳ A requirement on the loading duration may conversely be used to specify the appropriate tube lengths involved. The methods are described which account for the differences in operation between a straight and an area-changed shock tube, which apparently have not been done before for the sub-sonic conditions encountered here.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

TABLE OF CONTENTS

	Page
LIST OF FIGURES.	5
LIST OF TABLES	7
I. INTRODUCTION	9
II. DETERMINATION OF DRIVER PRESSURE	10
III. DETERMINATION OF POSITIVE PULSE DURATION	16
A. Wave Advance in the Straight Shock Tube	16
B. Determination of Wave Speeds	17
C. Sample Calculated Wave Speeds and Results	21
IV. CONCLUSIONS	24
ACKNOWLEDGMENT	25
LIST OF REFERENCES	29
DISTRIBUTION LIST.	31

ACCESSION for		
NTIS	White Section	<input checked="" type="checkbox"/>
DDC	Buff Section	<input type="checkbox"/>
UNANNOUNCED		<input type="checkbox"/>
JUSTIFICATION _____		
BY _____		
DISTRIBUTION/AVAILABILITY CODES		
Dist.	AVAIL.	and/or SPECIAL
A		

78 09 12 017

LIST OF FIGURES

Figure		Page
1.	BRL Dual Shock Tube Facility	26
2.	Wave Diagram of Idealized Shock Tube with Area Change at Diaphragm	26
3.	Graphical Solution to Equation (8): Curves Z_{3a} and Z_3 as a function of Mach number	27
4.	Driver Pressure - Testing Pressure for 2.4m: 3.7m (8':12') Area Changed Shock Tube	27
5.	Wave Interactions and Pressures at Stations x: Straight Shock Tube.	28
6.	Wave Diagram Illustrating Driver Tube Lengths Relationship	28

1. INTRODUCTION

Recently, the Army has shown interest in minimizing "collateral damage" to civilian areas and to friendly troops. This interest has created a need for facilities to permit "full scale" testing under simulated low-level blast loadings caused by explosive charges. ("Full scale" walls would be of realistic sizes wherein regular construction materials and methods are useable.) The need for such facilities apparently has not been met satisfactorily. Facilities exist, e.g. the DASACON conical tube at Dahlgren, Virginia, permitting full scale testing; yet operationally they may have shortcomings: expense of operation in terms of manpower and/or energy requirements or, inadequate simulation of the waveform characteristics of conventional explosive blast waves. In response to an Army request involving such full scale testing, we have studied a possible modification of the 2.4m (8') tube portion of the existing BRL Dual Shock Tube Facility^{1,2}, Figure 1 from Reference 1, to give the desired testing parameters - acceptance of walls to 3.7m (12') height, subjected to peaked pressure pulses up to 70 kPa (10 psi) of ~ 50 ms positive duration.

Testing beyond the open end was not considered because of the jet-like characteristics of the flow emitted. Close in, pressures are uneven across a planar surface immersed normal to the flow, a result predicted from a simple model, and found in early experiments by Bertrand². Farther away, when the shock is more planar, the desired pressure levels are not assured under the tube's operating limits.

The modification considered is basically an adjustment on the driver/driven tube lengths and test station location to give the desired pressure wave form, and is a somewhat natural extension of the classical shock tube operation cycle, but with an area change. The peaked pressure waveform is obtained by testing at stations within a distance interval defined by the intersection of the leading and trailing waves of the breech-reflected expansion fan with the primary shock. The interaction of the expansion waves with the shock weakens it, thereby giving the desired decaying pressure pulse. The flow in an equivalent straight shock tube is used to follow the wave processes. Specifying the desired positive duration of the peaked wave then determines the appropriate tube lengths, for the straight tube; then, by imposing a simple physical requirement, these tube lengths can be carried over to determine the desired area-changed tube lengths.

1. B. P. Bertrand, "BRL Dual Shock Tube Facility," BRL MR 2001, U. S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, August 1969. AD 693264.
2. B. P. Bertrand, "Proposed Improvement of BRL Dual Shock Tube Facility," BRL Technical Note No. 1733, U. S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, April 1970. AD 871736.

The driving pressures for the area-changed shock tube are computed following the methods of Alpher and White,³ who also treated area-changed shock tubes but whose interests were in stronger shocks, with the driver tube looking into a smaller area driven tube. The principal features of our calculations apparently have not previously been done explicitly for the subsonic flows occurring here and up to the wave interaction regions involved. Results are presented of calculations for the driver pressures for the 2.4m tube for several test conditions, involving two different (larger) areas of driven tube.

II. DETERMINATION OF DRIVER PRESSURE

The flow situation for the area-changed tube is depicted in Figure 2, along with its wave diagram or x-t plot. Following Alpher and White, we may write the expression for the diaphragm pressure ratio p_{4c}/p_1 , after the diaphragm is broken and flow processes are established, as (ideal, one-dimensional flow throughout)

$$\frac{p_{4c}}{p_1} = \frac{p_{4c}}{p_{3a}} \frac{p_{3a}}{p_3} \frac{p_3}{p_2} \frac{p_2}{p_1} \quad (1)$$

The pressure ratios in the expression are interpreted to be

- p_{4c}/p_{3a} - the pressure (ratio) required to expand unsteadily the gas in region 4 from rest to a Mach number M_{3a} ;
- p_{3a}/p_3 - the pressure required to expand steadily the gas from M_{3a} to M_3^* ;
- p_3/p_2 - the pressure across the contact surface separating driver- from driven-gas, with $p_3 = p_2$;
- p_2/p_1 - the pressure required to compress the test gas in region 1 through the shock of strength M_1 or M_s .

Assuming the processes are isentropic and accounting for the steady or unsteady nature, we may write Equation (1) as

3. R. A. Alpher and D. R. White, "Flow in Shock Tubes with Area Change at the Diaphragm Section," *J. Fluid Mech* 3, 457-70 (1958).

*For subsonic flow $M < 1$, a steady expansion is more efficient in the conversion of thermal to kinetic energy than an unsteady expansion.⁴

4. E. L. Resler, Shao-Chi Lin, and Arthur Kantrowitz, "The Production of High Temperature Gases in Shock Tubes," *J. Appl. Phys.* 23, 1390-99 (1952).

LIST OF TABLES

Table		Page
IA	Parameters for Test Flows	13
IB	Calculated Nozzle Mach Numbers and Driver Pressures	13
II	Calculated (Absolute) Driver Pressures for 1.7m(5½) Diameter Tube Operating in Tailored-Interface Mode	15

$$\frac{p_{4c}}{p_1} = \left\{ \left(1 + \frac{\gamma_4 - 1}{2} M_{3a}^2\right) \left[\frac{2 + (\gamma_4 - 1) M_3^2}{2 + (\gamma_4 - 1) M_{3a}^2} \right]^{\frac{1}{2}} \right\}^{\frac{2\gamma_4}{\gamma_4 - 1}} \frac{p_2}{p_1} \quad (2)$$

In regular shock tube testing, the gases in regions 1 and 4 are usually specified, as is the desired test overpressure; thus a driver pressure can be determined. In the area-changed tube the unknowns are p_{4c} as well as M_3 and M_{3a} . Equations to connect these are the expression for isentropic nozzle flow in terms of the nozzle areas:

$$\frac{A_4}{A_1} = \frac{M_3}{M_{3a}} \left[\frac{2 + (\gamma_4 - 1) M_{3a}^2}{2 + (\gamma_4 - 1) M_3^2} \right]^{\frac{1}{2} \frac{\gamma_4 + 1}{\gamma_4 - 1}} \quad (3)$$

and an expression connecting M_3 with the driven gas:

$$M_3 \equiv \frac{u_3}{a_3} = \frac{u_3/a_1}{a_3/a_1} = \frac{u_2/a_1}{(a_3/a_1) (a_3/a_2) (a_2/a_4) (a_4/a_1)} \quad (4)$$

where a similar decomposition into steady-unsteady processes as in Equation (1) is made, and results in:

$$M_3 = \frac{(u_2/a_1)(a_1/a_4)}{\left[\frac{2 + (\gamma_4 - 1) M_{3a}^2}{2 + (\gamma_4 - 1) M_3^2} \right]^{\frac{1}{2}} \frac{2}{2 + (\gamma_4 - 1) M_{3a}^2}} \quad (5)$$

We now combine Equation (5) with Equation (2) and rewrite (2) as

$$\frac{p_{4c}}{p_1} = \left[\frac{(u_2/a_1)(a_1/a_4)}{M_3} \right]^{\frac{2\gamma_4}{\gamma_4 - 1}} \frac{p_2}{p_1} \quad (6)$$

Equations (5), (6) and (3) may then be used to determine the required driver pressure p_{4c} , knowing the desired testing pressure p_2/p_1 and the nozzle area ratio A_4/A_1 . Solution techniques - e.g. the Newton-Raphson method or iteration - may be used on this system of equations.

We have used a graphical procedure offering some simplicity and utility to the worker at the site. This is now illustrated. From Equation (3) we have

$$\left(\frac{A_4}{A_1} \frac{M_{3a}}{M_3} \right)^{\frac{\gamma_4-1}{\gamma_4+1}} = \left[\frac{2 + (\gamma_4-1) M_{3a}^2}{2 + (\gamma_4-1) M_3^2} \right]^{1/2},$$

which, on substituting into Equation (5), gives

$$M_3 = \frac{(u_2/a_1) (a_1/a_4)}{\frac{\gamma_4-1}{\gamma_4+1} \left(\frac{A_4}{A_1} \frac{M_{3a}}{M_3} \right)^{\frac{\gamma_4+1}{\gamma_4-1}} \frac{2}{2 + (\gamma_4-1) M_{3a}^2}} \quad (7)$$

Or rearranging

$$2 \frac{(A_4/A_1)^{\frac{\gamma_4-1}{\gamma_4+1}}}{(u_2/a_1) (a_1/a_4)} M_3^{\frac{2}{\gamma_4+1}} = \frac{2 + (\gamma_4-1) M_{3a}^2}{\frac{\gamma_4-1}{\gamma_4+1} M_{3a}^2} \quad (8)$$

The right hand side of Equation (8) determines a curve Z_{3a} plotted vs Mach number; similarly, the left hand side determines a curve Z_3 (a straight line on a log-log plot). Thus for given p_2/p_1 - or $(u_2/a_1) (a_1/a_4)$ - and A_4/A_1 , the points $Z_3 = Z_{3a}$ determine the Mach numbers M_{3a} and M_3 upstream and downstream, respectively, of the nozzle, and in particular M_3 of Equation (6) and, thereby, the required driver pressure p_{4c} .

Some sample values have been calculated for their specific interest and to illustrate the procedure. An attractive feature is that different area ratios and test pressures are reflected only in a change in (straight line) intercept (for the same gases) of the Z_3 curve. The area ratios considered were for 2.4m (8') diameter driver tube and Case (a)-3.7m (12') and Case (b) - 4.6m (15')

diameter driven tubes, with a test overpressure $p_{2g} = 73 \text{ kPa (10.6 psi)}$. Gases had

$$\gamma_4 = \gamma_1 = 7/5; a_4 = a_1$$

Case (c) is similar to (a) but $p_{2g} = 34.5 \text{ kPa (5.0 psi)}$. The values for the various quantities entering into the construction of the graph are tabulated in Table IA.

TABLE IA - PARAMETERS FOR TEST FLOWS

Case	(A_4/A_1)	u_2/a_1	M_1	$2(A_4/A_1)^{1/6}(u_2/a_1)$	p_2/p_1
a	0.444	0.4022	1.27	4.346	1.72
b	0.284	0.4022	1.27	4.033	1.72
c	0.444	0.219	1.14	7.982	1.34

The graphs for these cases are plotted in Figure 3 as functions of Mach number.

For the three cases the Mach numbers determined are tabulated in Table IB as well as the driver pressures (absolute) as determined from Equation (6).

TABLE IB - CALCULATED NOZZLE MACH NUMBERS AND DRIVER PRESSURES

Case	(kPa)	p_{4c} (psi)	$\sim M_{3a}$	$\sim M_3$
a	800	116	0.6	0.50
b	1564	227	0.68	0.55
c	252	37	0.40	0.25

From these sample cases, it is seen that a 2.4m diameter driver section coupled to a 3.7m diameter driven section to give test overpressures up to 70 kPa (10 psi) is well within the 1100 kPa operating limits of the present TBD 2.4m shock tube. A 4.6m driven section at this overpressure could not be accommodated, however. For reference we have considered a range of test overpressures p_{2g} and their required driver pressures p_{4c} for the 2.4m: 3.7m (8':12')

area-changed tube. Results are plotted as Figure 4.* Maximum p_{2g} is seen to be ~ 93 kPa (13.5 psi) for the 1100 kPa driver operating limit.

In addition, some cases have also been treated involving the 1.7m (5 1/2") diameter tube of the BRL Dual Shock Tube Facility, to illustrate the obtainable test pressures, along with associated driver pressures. Wave durations were not worked out. The 1.7m tube has provision for heating of the driver gas to eliminate the contact surface discontinuity, i.e. for tailoring of the interface.

For small disturbances, identity of the acoustic impedance ρa across the interface assures that waves are transmitted without change. For the same gas on either side of the interface, the requirement reduces to identity of the sound speeds. Hence, also, in the tailored-interface mode

$$u_2/a_2 = u_3/a_3 = M_3.$$

With the desired test condition (hence M_3) known, one may enter the plot of Figure 3 to select a particular pair (there is a range) M_3, M_{3a} for which $Z_3 = Z_{3a}$, as required by Equation (8) in the solution for p_{4c} . Through this point (M_3, Z_3) is passed a straight line paralleling previously computed straight-line Z_3 curves for other conditions; and this gives the intercept value, from which the driver sound speed ratio a_4/a_1 is determinable. Consequently, the driver gas temperature or the heating may be determined. Then the driver pressure including the heating is again determined from Equation (6). Three sample cases are given in the following Table II, for the 1.7m tube coupled to a 3.7m diameter driven tube, with $T_1 = 300^\circ$ K.

**Because of the relatively large exponent occurring in Equation (6), small rounding errors in the early stages of calculations can yield variations from our final results. The accuracy conforms to the approximate nature of the inquiry, and does not appear to be the limiting feature in the tube modification.*

TABLE II. CALCULATED (ABSOLUTE) DRIVER PRESSURES FOR 1.7m (5½') DIAMETER TUBE OPERATING IN TAILORED-INTERFACE MODE

Case	p_{2g} (kPa)	M_1 (psi)	ρ_2/p_1	a_2/a_1	u_2/a_1	M_3	M_{3a}	Intercept value	a_4/a_1	T_4^0	K	p_{4c}/p_1	p_{4c} (kPa)	p_{4c} (psi)
1	73.0	10.6	1.27	1.72	1.083	0.4022	0.3714	0.43	5.62	1.466	645	13.95	1413	205
2	34.5	5.0	1.136	1.34	1.043	0.213	0.2043	0.25	9.55	1.319	522	6.96	703	102
3	51.7	7.5	1.199	1.510	1.062	0.3041	0.2864	0.39	7.1	1.400	588	10.47	1061	154

III. DETERMINATION OF POSITIVE PULSE DURATION

A. Wave Advance in the Straight Shock Tube

We turn now to questions on the positive duration of the desired peaked wave. As mentioned in the Introduction, we rely on the interaction between the incident shock S_{\rightarrow} and the reflected rarefaction wave R_{\leftarrow} from the breech to weaken the shock pressure, thus giving the peaked pressure wave form. The wave diagram of Figure 5, for a straight shock tube, illustrates a possible set of events and the pressures at various stations x . For sufficiently strong rarefaction waves the shock reduces to one of the characteristics of the rarefaction wave exiting from the interaction region; for weak rarefaction waves overtaking the shock, a weakened shock with lowered shock pressures emerges⁵. In both instances we may take the peaked wave's positive duration as the interaction time of the shock with the reflected expansion fan from the driver breech. The problem, therefore, is to determine this time from the operation cycle of our area-changed shock tube.

As a point of departure, we make use of calculations involving a straight shock tube chosen to give the same downstream conditions as the area-changed tube. The interaction problem and the relevant times will be solved for the straight tube. Then asking for a simple physical requirement enables a transforming of the computed numbers to the actual tube.

Most of the features of the wave interaction problem in the straight shock tube are well known. The interactions delineate in the (x,t) - plane a number of regions of shock tube flow. These have been labeled in the Figure 5 according to standard practice. We focus on the interactions involving the reflected leading and trailing waves of the expansion fan connecting straight shock tube regions 4 and 3. Where and when these overtake the incident shock wave tell a) where a test wall should be placed to experience a peaked pressure pulse and b) what positive duration is to be expected. Conversely, if the positive duration is specified, the problem formulation allows driver and driven lengths to be determined.

Thus, considering the propagation of the forward-facing, reflected rarefaction waves R , we note that they will first interact at the contact surface K . This interaction may lead to weak reflected rarefaction or compression waves, but always to a transmitted rarefaction wave. The transmitted rarefaction wave thus continues onward, overtakes and interacts with the primary shock. This interaction gives rise to four possibilities depending on relative strengths of the

5. *I. I. Glass and J. G. Hall, Handbook of Supersonic Aerodynamics, Section 18, Shock Tubes, NAVORD Report 1488 (Vol. 6) 1959.*

interacting waves: strong rarefaction wave relative to shock gives 1) reflected rarefaction or 2) compression waves and a transmitted rarefaction wave; or weak rarefaction wave relative to shock gives 3) reflected rarefaction or 4) compression waves and a transmitted (weakened) shock. The different initial conditions required to achieve these cases could be a means of achieving different pressure pulses with changed wave slopes, if desirable. For this study it turns out that the last-named interactions did not have to be considered in such detail.

B. Determination of Wave Speeds

The progress of the R_{\rightarrow} wave* from the breach after reflection requires knowledge of its wave speed C through the various uniform regions. The wave speed is obtained from the Riemann invariants governing the simple flow. Across the backward facing R_{\leftarrow} wave connecting regions 3 and 4:

$$\frac{2}{\gamma_4 - 1} a_4 = u_3 + \frac{2}{\gamma_4 - 1} a_3 = a_3 \left(M_3 + \frac{2}{\gamma_4 - 1} \right)$$

$$u_4 = 0$$

$$\frac{a_4}{a_3} = \frac{\gamma_4 - 1}{2} M_3 + 1 \quad ,$$

$$u_3 = \frac{2}{\gamma_4 - 1} (a_4 - a_3) \quad ,$$

$$\frac{p_4}{p_3} = \left(\frac{a_4}{a_3} \right)^{\frac{2\gamma_4}{\gamma_4 - 1}} \quad ;$$

Wave Speeds: $C_{-3} = u_3 - a_3, C_{-4} = -a_4$

Across the forward-facing R_{\rightarrow} wave connecting 3 with 5:

*The notation is R = rarefaction, S = shock, and arrows indicate direction; and C_{-4} = wave speed of backward-facing wave in region 4.

$$u_5 - \frac{2}{\gamma_4 - 1} a_5 = u_3 - \frac{2}{\gamma_4 - 1} a_3 = a_3 \left(M_3 - \frac{2}{\gamma_4 - 1} \right)$$

$$a_5/a_3 = 1 - \frac{\gamma_4 - 1}{2} M_3$$

$$u_5 = 0$$

$$\frac{p_5}{p_3} = \left(\frac{a_5}{a_3} \right)^{\frac{2\gamma_4}{\gamma_4 - 1}}$$

Wave speeds: $C_{+3} = u_3 + a_3$; $C_{+5} = + a_5$

Farther along, the interaction $R_{\rightarrow} K \rightarrow$ $\left\{ \begin{array}{l} \text{weak } R_{\leftarrow} KR_{\rightarrow} \\ \text{or} \\ \text{weak} \\ \text{compress. wave, } S_{\leftarrow} KR_{\rightarrow} \end{array} \right.$

If we assume the result $R_{\leftarrow} KR_{\rightarrow}$, our calculations lead to a contradiction in the pressures across the wave as well as in the slopes of leading and trailing wave. In this regard, the criteria and outcome for this interaction, as stated by Courant and Friedrichs,⁶ page 180, give an incorrect result here, whereas those by Glass and Hall,⁵ page 95-6, and Landau and Lifshitz⁷ (for acoustic waves) page 255-6, predict the results we indeed find.

The interaction results, then, in reflected compression waves coalescing to a shock and a transmitted rarefaction wave. For the weak waves expected here, the compression waves have the same properties as weak shocks.⁵ Hence we assume the shock wave equations are applicable and also that entropy changes across the "forming shock" may be neglected, i.e., the process is also assumed to be isentropic.

With these assumptions, regions 5 and 6 are connected by

6. R. Courant and K. D. Friedrichs, Supersonic Flow and Shock Waves, Interscience Publishers, Inc., New York (1948).

7. L. D. Landau and E. M. Lifshitz, Fluid Mechanics, Pergamon Press Ltd., London, 1959.

$$u_6 = u_5 - a_5 \left(\frac{p_6}{p_5} - 1 \right) \sqrt{\frac{2/\gamma_4}{(\gamma_4+1) (p_6/p_5) + (\gamma_4-1)}}$$

and

$$\frac{p_6}{p_5} = \left(\frac{a_6}{a_5} \right)^{\frac{2\gamma_4}{\gamma_4-1}}$$

using the isentropic assumption.

On the other side of the contact surface, across the transmitted forward-facing R_{\rightarrow} connecting regions 2 and 7, one has

$$u_2 - \frac{2}{\gamma_1-1} a_2 = u_7 - \frac{2}{\gamma_1-1} a_7$$

and

$$\frac{p_7}{p_2} = \left(\frac{a_7}{a_2} \right)^{\frac{2\gamma_1}{\gamma_1-1}}$$

where the known conditions for region 2 are obtained from the shock strength p_2/p_1 or M_s , i.e., from tables of straight shock tube properties.

The first equation is recast into more useful form:

$$u_7 = u_2 + \frac{2}{\gamma_1-1} a_2 \left[\left(\frac{p_7}{p_2} \right)^{\frac{\gamma_1-1}{2\gamma_1}} - 1 \right],$$

and making use of equalities across the contact surface

$$u_6 = u_7, p_6 = p_7; p_3 = p_2$$

results in

$$u_7 = u_2 + \frac{2}{\gamma_1 - 1} a_2 \left[\left(\frac{p_7}{p_5} \cdot \frac{p_5}{p_3} \right)^{\frac{\gamma_1 - 1}{2\gamma_1}} - 1 \right] = u_6$$

$$= u_5 - a_5 \left(\frac{p_7}{p_5} - 1 \right) \sqrt{\frac{2/\gamma_4}{(\gamma_4 + 1) (p_7/p_5) + (\gamma_4 - 1)}},$$

yielding a single equation for p_7/p_5 in terms of previously determined quantities. Solution then permits the calculation of particle and sound speeds u_6 , a_6 and u_7 , a_7 applicable for these regions.

The transmitted leading and trailing waves of the expansion then propagate onward with velocities $(u_2 + a_2)$ and $(u_7 + a_7)$, respectively, to interact with the shock giving the locations within which one may expect a peaked wave, and also determining its duration. Specific cases of test conditions must now be entered to obtain actual numbers. The problem formulation is usually done in non-dimensional coordinates

$\chi = \frac{x}{L}$, $\tau = \frac{at}{L}$ where L and a are convenient reference length and sound speed, respectively. The non-dimensional time interval between intersection of leading and trailing waves of the expansion with the shock thus yields the reference length, if we set the real time interval equal to the pulse duration. The numbers as yet apply to a straight shock tube, chosen to give the desired equivalent downstream conditions.

In converting over to the area-changed shock tube, we recognize that the driver lengths should not in general be equal, since different **pressure ratios** are involved across the diaphragm. Thus, velocities and wave speeds must be different; and, the wave speed in the area-changed tube must slow down in the steady, subsonic expansion to match the downstream conditions set for the equivalent straight shock tube.

The wave diagram in Figure 6 shows a possible wave-speed comparison (as seen from numbers to be given later) and illustrates how a simple conversion of tube lengths may be made: we demand that the real times be equal, for both straight and area-changed shock tubes, for the leading wave of expansion to be reflected from breech and to travel back to the diaphragm station. The flows to the leading waves are then identical beyond, neglecting the time required in traversing the short transition piece (which implies an assumption on the length of this piece).

This particular calculation may be done analytically for the intersection point of leading with trailing wave of the reflected expansion⁸ and wave progress then continued at constant speed to the diaphragm station $X = 0$ at τ_0 .

From the nondimensional times

$$\Delta\tau = \frac{a_4 \Delta t}{L_4}$$

the real times for the arrival at $X = 0$ are equated

$$\Delta t = \left(\frac{L_4 \Delta\tau}{a_4} \right)_{\text{str}} = \left(\frac{L_4 \Delta\tau}{a_4} \right)_{\text{c}}$$

to arrive at driver length conversion.

C. Sample Calculated Wave Speeds and Results

The actual test conditions are used in the calculations outlined. As a specific example, we choose the test condition $p_{2g} = 73$ kPa (10.6 psi). For this case the previously obtained flow parameters are given to an equivalent straight shock tube:

$$M_1 = 1.27 \qquad \gamma_1 = \gamma_4 = 7/5$$

$$p_2/p_1 = 1.72$$

$$u_2 = 0.4022a_1 = u_3$$

$$M_3 = u_3/a_3 \doteq 0.5 \quad (M_{3a} = 0.6 \text{ for } A_4/A_1 = 0.444)$$

$$a_3 = 0.8044a_1$$

With these conditions, the driver sound speed is

$$a_4 = 0.88484a_1$$

8. R. K. Lobb, "On the Length of a Shock Tube," UTIA Report 5, Institute of Aerophysics, University of Toronto, 1950.

Then the wave speeds for the reflected expansion are

$$C_{+3} \equiv u_3 + a_3 = (0.4022 + 0.8044)a_1 = 1.2066a_1$$

$$C_{+5} \equiv u_5 + a_5 = 0.72396 a_1$$

$$C_{+2} \equiv u_2 + a_2 = (0.4022 + 1.083)a_1 = 1.4852a_1$$

$$C_{+7} \equiv u_7 + a_7 = (-0.0610 + 0.9911)a_1 = 0.9301 a_1$$

$$(C_{-4} \equiv u_4 - a_4 = -0.88484 a_1)$$

$$(C_{-3} \equiv u_3 - a_3 = -0.4022a_1)$$

With these results, one is in position to follow the rarefaction wave from diaphragm break to its interaction with the primary shock.

A characteristics calculation with desk calculator yields the extent of the breech reflection, for leading (ℓ) and trailing (t) waves:

$$X = -1.0, \quad \begin{array}{l} \tau_\ell = 1.1301 \\ \tau_t = 2.15147 \end{array} \quad \left(\tau \equiv \frac{a_1 t}{L_4} \text{ here} \right) .$$

The intersection point X_3 of reflected leading wave with trailing wave is found to be

$$X_3 = -0.6094; \quad \tau_3 = 1.5151.$$

Continuing, the reflected leading and trailing waves moving with velocities C_{+3} and C_{+5} , respectively, overtake the contact surface K moving with velocity u_2 . We have bypassed a detailed (but more accurate) characteristics calculation, and have followed both waves' arrival only up to the leading wave's intersection with K , at X_K :

$$\begin{array}{l} \tau_{K,\ell} = 3.0302 \\ X_K = 1.21876, \\ \tau_{K,t} = 5.21607 \end{array}$$

This procedure, as seen by inspection of the wave diagram, Figure 5,

should give a lower estimate on the actual trailing wave's intersection point with K and hence an upper estimate to be made on the tube lengths.

Beyond the contact surface K, the transmitted leading and trailing waves of the rarefaction move to intersection with the shock, with velocities C_{+2} and C_{+7} , respectively. The procedure for this interaction is again to follow the rarefaction waves only up to the leading wave's intersection X_s with shock. Here also a detailed characteristics calculation is bypassed in the interest of simplicity. Similarly, a lower estimate on actual intersection position and time is expected for the trailing wave. The results then are

$$\tau_{s, \ell} = 15.2495$$

$$X_s = 19.367,$$

$$\tau_{s, t} = 24.728$$

The (nondimensional) interaction time

$$\Delta\tau = \tau_{s, t} - \tau_{s, \ell} \equiv \frac{a_1 \Delta t}{L_4}$$

thus fixes the desired peaked wave's duration (which may be transmitted with some positive pressure, depending on conditions, nevertheless). Choosing the wave duration $\Delta t = 50$ ms then determines the required (straight tube) driver length:

$$L_{4 \text{ str}} = \frac{a_1 50 (10^{-3})}{\Delta\tau}$$

$$L_{4 \text{ str}} = 1.77\text{m} (5.80 \text{ ft.}) (a_1 = 335 \text{ m/s or } 1100 \text{ ft/s})$$

The test wall is placed at X_s , where the leading wave of the rarefaction intersects the primary shock and determines the driven tube length L_1 :

$$L_1 = X_s L_4 = 19.367 (1.77\text{m})$$

$$L_1 = 34.3\text{m} (112.3 \text{ ft.}) ;$$

as we have remarked earlier, L_1 as determined is probably an upper estimate.

These numbers are as yet based on the straight shock tube with downstream conditions identical to the desired conditions. To maintain this identity through wave speeds and interaction points in the wave diagram, we asked that the real times be equal after diaphragm break - for straight and for area-changed tube - for the leading waves of the expansions to travel back to the diaphragm station. Thus, using the numbers appropriate for the straight tube and for the area-changed tube for the case considered in the beginning of this section and following the procedure outlined earlier, we arrive at

$$\Delta t = L_{4c} \frac{\Delta \tau_c}{a_{4c}} = L_{4 \text{ str}} \frac{\Delta \tau_{\text{str}}}{a_{4 \text{ str}}}$$

and with numbers inserted

$$\Delta t = L_{4c} \frac{1.756}{a_1} = L_{4 \text{ str}} \frac{1.7747}{0.88484 a_1}$$

or
$$L_{4c} = 1.142 L_{4 \text{ str}}$$

For $L_{4 \text{ str}} = 1.77\text{m}$ (5.80 ft),

$$L_{4c} = 2.02\text{m} \text{ (6.62 ft)}$$

Then, having forced this partial simultaneity on driver wave motions, we are assured that the downstream behavior in the two shock tubes will be reasonably matched. Hence the driven tube length is as computed- 34.3m (112 ft).

IV. CONCLUSIONS

Using an extension of the normal straight shock tube operating cycle, we have determined appropriate tube lengths and driver pressures for requisite operation/modification of an existing BRL 2.4m (8') shock tube to permit full scale testing. Walls and structures of 3.7m (12') height are acceptable for simulated blast loadings of ~70 kPa (10 psi) having pulse durations of 50 ms. Other loadings and the appropriate tube lengths are derivable without difficulty using the procedures developed.

The results are based on idealized shock tube operation, with approximations introduced to obviate the need for an extensive computer program. In an actual design to the full sized tube, one

should expect departures from such ideal operation due to boundary layer growth and imperfect diaphragm effects such as non-instantaneous opening and loss of energy to the opening process.

Due to the relatively short length of driver required, a much smaller prototype tube with required area change ratio could be constructed from BRL existing shock tubes, and the wave characteristics determined empirically and compared with calculations, to see what modifications should be incorporated into the full sized facility.

ACKNOWLEDGMENT

The author thanks Dr. K. S. Fansler for helpful discussion and clarification of ideas.




Figure 1. BRL Dual Shock Tube Facility




Figure 2. Wave Diagram of Idealized Shock Tube with Area Change at Diaphragm




Figure 3. Graphical Solution to Equation (8): Curves Z_{3a} and Z_3 as a Function of Mach Number




Figure 4. Driver Pressure - Testing Pressure for 2.4m: 3.7m (8':12') Area Changed Shock Tube




Figure 5. Wave Interactions and Pressures at Stations x :
Straight Shock Tube




Figure 6. Wave Diagram Illustrating Driver Tube Lengths
Relationship

REFERENCES

1. B. P. Bertrand, "BRL Dual Shock Tube Facility," BRL MR 2001, U. S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, August 1969. AD 693264.
2. B. P. Bertrand, "Proposed Improvement of BRL Dual Shock Tube Facility," BRL Technical Note No. 1733, U. S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, April 1970. AD 871736.
3. R. A. Alpher and D. R. White, "Flow in Shock Tubes with Area Change at the Diaphragm Section," J. Fluid Mech 3, 457-70 (1958).
4. E. L. Resler, Shao-Chi Lin, and Arthur Kantrowitz, "The Production of High Temperature Gases in Shock Tubes," J. Appl. Phys. 23, 1390-99, (1952).
5. I. I. Glass and J. G. Hall, Handbook of Supersonic Aerodynamics, Section 18, Shock Tubes, NAVORD Report 1488 (Vol. 6) 1959.
6. R. Courant and K. D. Friedrichs, Supersonic Flow and Shock Waves, Interscience Publishers, Inc., New York (1948).
7. L. D. Landau and E. M. Lifshitz, Fluid Mechanics, Pergamon Press Ltd., London, 1959.
8. R. K. Lobb, "On the Length of a Shock Tube," UTIA Report 5, Institute of Aerophysics, University of Toronto, 1950.

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
12	Commander Defense Documentation Center ATTN: DDC-TCA Cameron Station Alexandria, VA 22314	5	Director Defense Intelligence Agency ATTN: DT-1C DT-7D/E. O. Farrell DT-2/Wpns & Sys Div Technical Library DI-7E Washington, DC 20301
3	Director Defense Advanced Research Projects Agency ATTN: Tech Lib NMRO PMO 1400 Wilson Boulevard Arlington, VA 22209	6	Director Defense Nuclear Agency ATTN: SPTD/Mr. J. Kelso STSI/Archives SPAS/Mr. J. Moulton STSP STVL/Dr. La Vier RATN/Cdr Alderson Washington, DC 20305
4	Director of Defense Research and Engineering ATTN: DD/TWP DD/S&SS DD/I&SS AD/SW Washington, DC 20301	6	Director Defense Nuclear Agency ATTN: DDST/Mr. P. Haas DDST/Mr. M. Atkins STTL/Tech Lib (2 cys) SPSS (2 cys) Washington, DC 20305
1	Director Weapons Systems Evaluation Gp ATTN: Document Control Washington, DC 20305	2	Commander Field Command, DNA ATTN: FCPR FCTMOF Kirtland AFB, NM 87115
1	Director Institute for Defense Analyses ATTN: IDA Librarian, Ruth S. Smith 400 Army-Navy Drive Arlington, VA 22202	1	Chief Las Vegas Liaison Office Field Command TD, DNA ATTN: Document Control P.O. Box 2702 Las Vegas, NV 89104
2	Asst. to the Secretary of Defense (Atomic Energy) ATTN: Document Control Donald R. Cotter Washington, DC 20301	1	Commander Field Command, DNA Livermore Branch ATTN: FCPRL P.O. Box 808 Livermore, CA 94550

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Director Defense Communications Agency ATTN: Code 930 Washington, DC 20305	1	Commander US Army Aviation Research and Development Command ATTN: DRSAV-E 12th and Spruce Streets St. Louis, MO 63166
3	Director Joint Strategic Target Planning Staff JCS ATTN: Sci & Tech Info Lib JLTW-2 DOXT Offutt AFB, Omaha, NB 68113	1	Director US Army Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035
1	Director National Security Agency ATTN: E. F. Butala, R15 Fort George G. Meade, MD 20755	6	Commander US Army Electronics Research and Development Command ATTN: DELSD-L DRDEL-SA, W.S. McAfee R. Freiberg DELS-D-EI, J. Roma DELS-D-EM, A. Sigismondi C. Goldy Fort Monmouth, NJ 07703
2	Director Defense Civil Preparedness Agency ATTN: Mr. George Sisson/RF-SR Technical Library Washington, DC 20301	1	Commander US Army Communications Rsch and Development Command ATTN: DRDCO-SGS Fort Monmouth, NJ 07703
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDMD-ST, N. Klein 5001 Eisenhower Avenue Alexandria, VA 22333	1	Commander US Army Missile Research and Development Command ATTN: DRDMI-R Redstone Arsenal, AL 35809
1	Commander US Army Materiel Development and Readiness Command ATTN: Technical Library 5001 Eisenhower Avenue Alexandria, VA 22333	2	Commander US Army Missile Materiel Readiness Command ATTN: DRSMI-AOM DRSMI-XS, Ch Scientist Redstone Arsenal, AL 35809
1	Commander US Army Materiel Development and Readiness Command ATTN: W. H. Hubbard 5001 Eisenhower Avenue Alexandria, VA 22333		

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Commander US Army Tank Automotive Research & Development Cmd ATTN: DRDTA-UL Warren, MI 48090	5	Commander US Army Harry Diamond Lab ATTN: DRXDO-TI DRXDO-TI/012 DRXDO-NP DRXDO-RBH Mr. P. A. Caldwell DELHD-RBA, J. Rosado 2800 Powder Mill Road Adelphi, MD 20783
1	Commander US Army Mobility Equipment Research & Development Cmd ATTN: DRXFB-RT/Dr. K. Oscar Fort Belvoir, VA 22060	3	Commander US Army Materials and Mechanics Research Center ATTN: Technical Library John Mescall Richard Shea Watertown, MA 02172
5	Commander US Army Armament Research and Development Command ATTN: DRDAR-LCN-F Mr. Warren Reiner DRDAR-TSS (2 cys) P. Angelotti (2 cys) Dover, NJ 07801	2	Commander US Army Natick Research and Development Command ATTN: DRXRE, Dr. D. Sieling DRXNM-UE Arthur Johnson Natick, MA 01762
1	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L, Tech Lib Rock Island, IL 61299	1	Commander US Army Foreign Science and Technology Center ATTN: Rsch & Concepts Branch 220 Seventh Street, NE Charlottesville, VA 22901
1	Commander US Army Watervliet Arsenal Watervliet, NY 12189	1	Commander US Army Training and Doctrine Command ATTN: ATCD-SA, Mr. Oscar Wells Fort Monroe, VA 23651
5	Commander US Army Harry Diamond Labs ATTN: Mr. James Gaul Mr. L. Belliveau Mr. J. Gwaltney Mr. F. N. Wimenitz Mr. Bill Vault 2800 Powder Mill Road Adelphi, MD 20783		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	Director US Army TRADOC Systems Analysis Activity ATTN: LTC John Hesse ATAA-SL, Tech Lib White Sands Missile Range NM 88002	2	Deputy Chief of Staff for Operations and Plans ATTN: Technical Library Dir of Chemical and Nuclear Operations Department of the Army Washington, DC 20310
2	Commander US Army Nuclear Agency ATTN: ACTA-NAW Technical Library 7500 Backlick Rd, Bldg 2073 Springfield, VA 22150	2	Director US Army BMD Advanced Technology Center ATTN: CRDABH-X CRDABH-S Huntsville, AL 35807
1	Commander Combined Arms Combat Developments Activity ATTN: ATCA-CO, L. C. Pleger Fort Leavenworth, KS 66027	1	Program Manager US Army BMD Program Office ATTN: John Shea 5001 Eisenhower Avenue Alexandria, VA 22333
1	Commander US Army Engineering Center ATTN: ATSEN-SY-L Fort Belvoir, VA 22060	1	Commander US Army BMD Systems Command ATTN: BMDSC-TFN, N. J. Hurst P. O. Box 1500 Huntsville, AL 35807
1	Commander US Army Logistics Center ATTN: ATCL-SCA Mr. Robert Cameron Fort Lee, VA 23801	1	Commander US Army Research Office P. O. Box 12211 Research Triangle Park NC 27709
1	Interservice Nuclear Weapons School ATTN: Tech Lib Kirtland AFB, NM 87115	2	Office, Chief of Engineers Department of the Army ATTN: DAEN-MCE-D DAEN-RDM 890 S. Pickett Street Alexandria, VA 22304
2	HQDA (DAMA-AR; NCL Div) Washington, DC 20310		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
5	Commander US Army Engineer Waterways Experiment Station ATTN: Tech Library William Flathau John N. Strange Guy Jackson Leo Ingram P. O. Box 631 Vicksburg, MS 39180	3	Commander Naval Facilities Engineering Command ATTN: Code 03A Code 04B Technical Library Washington, DC 20360
1	Division Engineer US Army Engineering Division Ohio River ATTN: Docu Cen P. O. Box 1159 Cincinnati, OH 45201	2	Commander Naval Sea Systems Command ATTN: ORD-91313 Library Code 03511 Department of the Navy Washington, DC 20362
1	Division Engineer US Army Engineering Division ATTN: HNDSE-R, M. M. Dembo Huntsville Box 1600 Huntsville, AL 35804	2	Commander Naval Ship Engineering Center ATTN: Technical Library NSEC 6105G Hyattsville, MD 20782
1	Chief of Naval Material ATTN: MAT 0323 Department of the Navy Arlington, VA 22217	1	Commander David W. Taylor Naval Ship Research & Development Ctr ATTN: L42-3 Library Bethesda, MD 20084
2	Chief of Naval Operations ATTN: OP-03EG OP-985F Department of the Navy Washington, DC 20350	2	Commander Naval Ship Research and Development Ctr Facility Underwater Explosions Rsch Div ATTN: Code 17, W.W. Murray Technical Library Portsmouth, VA 23709
1	Chief of Naval Research ATTN: N. Perrone Department of the Navy Washington, DC 20360	1	Commander Naval Surface Weapons Ctr ATTN: DX-21, Library Br. Dahlgren, VA 22448
1	Commander Naval Electronic Systems Cmd ATTN: PME 117-21A Washington, DC 20360		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
3	Commander Naval Surface Weapons Center ATTN: Code WA501/Navy Nuclear Programs Office Code WX21, Tech Lib Code 240, C.J. Aronson Silver Spring, MD 20910	1	Superintendent Naval Postgraduate School ATTN: Code 2124, Tech Rpts Lib Monterey, CA 93940
1	Commander Naval Weapons Center ATTN: Code 533, Tech Lib China Lake, CA 93555	1	HQ USAF (IN) Washington, DC 20330
2	Commander Naval Weapons Evaluation Facility ATTN: Document Control R. Hughes Kirtland AFB Albuquerque, NM 87117	1	HQ USAF (PRE) Washington, DC 20330
		2	AFSC (DLCAW; Tech Lib) Andrews AFB Washington, DC 20331
		2	ADTC (ADBRL-2; Tech Lib) Eglin AFB, FL 32542
		2	AFATL (ATRD, R. Brandt) Eglin AFB, FL 32542
4	Officer-in-Charge Civil Engineering Laboratory Naval Construction Battalion Center ATTN: Stan Takahashi R. J. Odello John Crawford Technical Library Port Hueme, CA 93041	2	RADC (EMTLD, Docu Lib; EMREC, R. W. Mair) Griffiss AFB, NY 13340
		1	AFWL/SUL Kirtland AFB, NM 87117
		1	AFWL/DE-I Kirtland AFB, NM 87117
2	Commander Naval Research Laboratory ATTN: Code 2027, Tech Lib Code 8440, F. Rosenthal Washington, DC 20375	1	AFWL/DEX Kirtland AFB, NM 87117
		1	AFWL/Robert Port Kirtland AFB, NM 87117
3	Director Strategic Systems Projects Ofc ATTN: NSP-43, Tech Lib NSP-273 NSP-272 Department of the Navy Washington, DC 20360	1	AFWL/DEV (Jimmie L. Bratton) Kirtland AFB, NM 87117
		1	AFWL (R. Henny) Kirtland AFB, NM 87117
		1	AFWL/DEV (M. A. Plamondon) Kirtland AFB, NM 87117

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	Commander-in-Chief Strategic Air Command ATTN: NRI-STINFO Lib XPFS Offut AFB, NB 68113	1	US Energy Research and Development Administration Albuquerque Operations Office ATTN: Doc Control for Tech Lib P.O. Box 5400 Albuquerque, NM 87115
2	ADC (XP; XPQDQ) Wright-Patterson AFB, OH 45433	1	US Energy Research and Development Administration Nevada Operations Office ATTN: Doc Control for Tech Lib P.O. Box 14100 Las Vegas, NV 89114
1	AFIT (Lib Bldg. 640, Area B) Wright-Patterson AFB, OH 45433		
1	AFML (MAMD/Dr. T. Nicholas) Wright-Patterson AFB, OH 45433		
1	ASD (Tech Lib) Wright-Patterson AFB OH 45433	5	Director Lawrence Livermore Laboratory ATTN: L. W. Woodruff/L-96 Tech Info Dept L-3 D. M. Norris/L-90 Ted Butkovich/L-200 J. R. Hearst/L-205 P.O. Box 808 Livermore, CA 94550
4	FTD (TDFBD; TDPMG; ETET/ CPT R. C. Husemann; TD-BTA/Lib) Wright-Patterson AFB OH 45433		
1	Director US Bureau of Mines ATTN: Tech Lib Denver Federal Center Denver, CO 80225	4	Director Lawrence Livermore Laboratory ATTN: Jack Kahn/L-7 J. Carothers/L-7 Robert Schock/L-437 R. G. Dong/L-90 P.O. Box 808 Livermore, CA 94550
1	Director US Bureau of Mines Twin Cities Research Center ATTN: Technical Library P. O. Box 1660 Minneapolis, MN 55111		
1	US Energy Research and Development Administration Division of Headquarters Svcs ATTN: Docu Control for Classified Technical Lib Library Branch G-043 Washington, DC 20545	4	Director Los Alamos Scientific Laboratory ATTN: Doc Control for Rpts Lib R. A. Gentry G. R. Spillman Al Davis P.O. Box 1663 Los Alamos, NM 87544

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Director National Aeronautics and Space Administration Scientific and Technical Information Facility P.O. Box 8757 Baltimore/Washington International Airport, MD	1	The BDM Corporation ATTN: Richard Hensley P.O. Box 9274 Albuquerque International Albuquerque, NM 87119
		21240	
5	Aerospace Corporation ATTN: Tech Info Services (2 cys) P. N. Mathur P.O. Box 92957 Los Angeles, CA 90009	2	The Boeing Company ATTN: Aerospace Library R. H. Carlson P.O. Box 3707 Seattle, WA 98124
1	Agbabian Associates ATTN: M. Agbabian 250 North Nash Street El Segundo, CA 90245	1	Brown Engineering Co., Inc. ATTN: Manu Patel Cummings Research Park Huntsville, AL 35807
1	Analytic Services, Inc. ATTN: George Hesselracher 5613 Leesburg Pike Falls Church, VA 22041	2	California Research and Technology, Inc. ATTN: Ken Kreyenhagen Technical Library 6269 Variel Avenue Woodland Hills, CS 91364
1	Applied Theory, Inc. ATTN: John G. Trulio 1010 Westwood Blvd. Los Angeles, CA 90024	1	Calspan Corporation ATTN: Technical Library P.O. Box 235 Buffalo, NY 14221
1	Artec Associates, Inc. ATTN: Steven Gill 26046 Eden Landing Road Hayward, CA 94545	1	Civil/Nuclear Systems Corporation ATTN: Robert Crawford 1200 University N.E. Albuquerque, NM 87102
1	AVCO Corporation ATTN: Res Lib A830, Rm 7201 201 Lowell Street Wilmington, MA 01887	1	EG&G, Incorporated Albuquerque Division ATTN: Technical Library P.O. Box 10218 Albuquerque, NM 87114
2	The BDM Corporation ATTN: Technical Library A. Lavagnino 1920 Aline Avenue Vienna, VA 22180	1	The Franklin Institute ATTN: Zemons Zudans 20th Street and Parkway Philadelphia, PA 19103

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	General American Trans Corporation General American Research Division ATTN: G. L. NEIDHARDT 7449 N. Natchez Avenue Niles, IL 60648	2	Martin Marietta Aerospace Orlando Division ATTN: G. Fotieo Mail Point 505, Craig Luongo P.O. Box 5837 Orlando, FL 32805
1	General Electric Company-TEMPO ATTN: DASIAC P.O. Drawer QQ Santa Barbara, CA 93102	3	McDonnell Douglas Astronautics Corporation ATTN: Robert W. Halprin Mr. C. Gardiner Dr. P. Lewis 5301 Bolsa Avenue Huntington Beach, CA 92647
2	Hazeltine Corp. ATTN: Carl Meinen Greenlawn, NY 11740	2	Merrity Cases, Inc. ATTN: J. L. Merritt Technical Library P.O. Box 1206 Redlands, CA 92373
1	J. H. Wiggins Co., Inc. ATTN: John Collins 1650 South Pacific Cost Highway Redondo Beach, CA 90277	1	Meteorology Research, Inc. ATTN: W. D. Green 454 West Woodbury Road Altadena, CA 91001
6	Kaman Avidyne ATTN: Dr. N. P. Hobbs (4 cys) Mr. S. Criscione Mr. John Calligeros 83 Second Avenue Northwest Industrial Park Burlington, MA 01830	1	The Mitre Corporation ATTN: Library P.O. Box 208 Bedford, MA 01730
3	Kaman Sciences Corporation ATTN: Library P. A. Ellis F. H. Shelton 1500 Garden of the Gods Road Colorado Springs, CO 80907	2	Pacifica Technology ATTN: G. Kent R. Bjork P.O. Box 148 Del Mar, CA 92014
1	Lockheed Missiles & Space Co. ATTN: Technical Library P.O. Box 504 Sunnyvale, CA 94088	4	Physics International Corp. ATTN: E. T. Moore Dennis Orphal Coye Vincent F. M. Sauer 2700 Merced Street San Leandro, CA 94577

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
4	Physics International Corp ATTN: Robert Swift Charles Godfrey Larry Behrmann Technical Library 2700 Merced Street San Leandro, CA 94577	1	Science Applications, Inc. ATTN: Technical Library P.O. Box 3507 Albuquerque, NM 87110
5	R&D Associates ATTN: Dr. H. L. Brode Dr. Albert L. Latter C. P. Knowles William B. Wright Henry Cooper P.O. Box 9695 Marina del Rey, CA 90291	2	Science Applications, Inc. ATTN: R. Seebaugh John Mansfield 1651 Old Meadow Road McLean, VA 22101
4	R&D Associates ATTN: Jerry Carpenter Sheldon Schuster J. G. Lewis Technical Library P.O. Box 9695 Marina del Rey, CA 90291	1	Science Applications, Inc. 8201 Capwell Drive Oakland, CA 94621
1	The Rand Corporation ATTN: C. C. Mow 1700 Main Street Santa Monica, CA 90406	2	Science Applications, Inc. ATTN: Technical Library Michael McKay P.O. Box 2351 La Jolla, CA 92038
6	Sandia Laboratories ATTN: Doc Control for 3141 Sandia Rpt Collection A. J. Chaban M. L. Merritt L. J. Vortman W. Roherty L. Hill Albuquerque, NM 87115	4	Systems, Science & Software ATTN: Donald R. Grine Ted Cherry Thomas D. Riney Technical Library P.O. Box 1620 La Jolla, CA 92037
1	Sandia Laboratories Livermore Laboratory ATTN: Doc Control for Tech Lib P. O. Box 969 Livermore, CA 94550	3	Terra Tek, Inc. ATTN: Sidney Green Technical Library A. H. Jones 420 Wakara Way Salt Lake City, UT 84108
		2	Tetra Tech, Inc. ATTN: Li-San Hwang Technical Library 630 North Rosemead Blvd. Pasadena, CA 91107

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
7	TRW Systems Group ATTN: Paul Lieberman Benjamin Sussholtz Norm Lipner William Rowan Jack Farrell Pravin Bhutta Tech Info Ctr/S-1930 One Space Park Redondo Beach, CA 92078	2	Battelle Memorial Institute ATTN: Technical Library R. W. Klingsmith 505 King Avenue Columbus, OH 43201
1	TRW Systems Group ATTN: Greg Hulcher San Bernardino Operations P.O. Box 1310 San Bernardina, CA 92402	1	California Institute of Technology ATTN: T. J. Ahrens 1201 E. California Blvd. Pasadena, CA 91109
2	Union Carbide Corporation Holifield National Laboratory ATTN: Doc Control for Tech Lib Civil Defense Research Proj P.O. Box X Oak Ridge, TN 37830	2	COSMIC ATTN: L. C. Gadol 112 Barrow Hall University of Georgia Athens, GA 30602
1	Universal Analytics, Inc. ATTN: E. I. Field 7740 W. Manchester Blvd. Playa del Rey, CA 90291	2	Denver Research Institute University of Denver ATTN: Mr. J. Wisotski Technical Library P.O. Box 10127 Denver, CO 80210
1	Weidlinger Assoc. Consulting Engineers ATTN: M. L. Baron 110 East 59th Street New York, NY 10022	3	IIT Research Institute ATTN: Milton R. Johnson R. E. Welch Technical Library 10 West 35th Street Chicago, IL 60616
1	Westinghouse Electric Company Marine Division ATTN: W. A. Votz Hendy Avenue Sunnyvale, CA 94008	2	Lovelace Foundation for Medical Education ATTN: Asst. Dir. of Research/ Robert K. Jones Technical Library 5200 Gibson Blvd., SE Albuquerque, NM 87108
		1	Massachusetts Institute of Technology Aeroelastic and Structures Research Laboratory ATTN: Dr. E. A. Witmer Cambridge, MA 02139

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
2	Southwest Research Institute ATTN: Dr. W. E. Baker A. B. Wenzel 8500 Culebra Road San Antonio, TX 78206		<u>Aberdeen Proving Ground</u> Dir, USAMSAA ATTN: Dr. J. Sperrazza Mr. R. Norman, GWD Cdr, USATECOM ATTN: DRSTE-SG-H
2	Stanford Research Institute ATTN: Dr. G. R. Abrahamson Carl Peterson 333 Ravenswood Avenue Menlo Park, CA 94025		
1	University of Dayton Industrial Security Super. KL-505 ATTN: H. F. Swift 300 College Park Avenue Dayton, OH 45409		
1	University of Illinois Consulting Engineering Services ATTN: Nathan M. Newmark 1211 Civil Engineering Building Urbana, IL 61801		
2	The University of New Mexico The Eric H. Wang Civil Engineering Research Facility ATTN: Larry Bickle Neal Baum University Station Box 188 Albuquerque, NM 87131		
2	Washington State University Administration Office ATTN: Arthur Miles Hohorf George Duval Pullman, WA 99163		