



WTIS DDC UNANNOUNCED JUSTIFICATION	White Section			
BY DISTRIBUTION/AVAILABILITY CODES				
DISTRIBUTION/A	ALABILIT	CODES		
DISTRIBUTION/A	AILABILIT	CODES SPECIAL		

FTD -ID(RS)T-0887-78

EDITED TRANSLATION

FTD-ID(RS)T-0887-78 31 October 1978

MICROFICHE NR: 24D - 78-C-001463

CSI76152080

"THE EFFECT OF TURBULENCE PARAMETERS ON THE TRANSFER OF HEAT BY FLOW AROUND A SPHERE"

By: Czeslaw Strumillo, Adam Markowski, Stefan Grabowski

English pages: 17

Source: Inzynieria Chemiczna, Vol. 5, Nr. 4, 1975, pp. 889-902

Country of Origin: Poland Translated by: LINGUISTIC SYSTEMS, INC. F33675-78-D-0618 Anthony M. Angiletta Requester: FTD/TQTA Approved for public release; distribution unlimited.

THIS TRANSLATION IS A RENDITION OF THE ORIGI-NAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DI-VISION.

PREPARED BY:

TRANSLATION DIVISION FOREIGN TECHNOLOGY DIVISION WP-AFB, OHIO.

FTD _ID (RS)T_0887-78

Date 31 Oct 19 78

"The Effect of Turbulence Parameters on the Transfer of Heat by Flow Around a Sphere" by Czeslaw Strumillo, Adam Markowski, and Stefan Grabowski

Chemical Engineering Istitute of Lodz Polytechnical

Submitted January 25, 1975.

Polish, Russian, and English Abstracts

Praca niniojsza dotyczy wpływa parametrów buraliwości na ruch ciepla przy opływie tali. Doświadczenia wykonano przy użyciu kul metalowych o średniench 50,6 i 41,4 mm, ogrzewanych od wewnątrz. Liczbę Roynoldsa zmieniano w zakresie $3 \cdot 10^3 \cdot 3 \cdot 10^4$, natomiast zakros zmian parametrów burzliwości wynosił: stopień burzliwości s – od 3 do 24% i bezwymiarowa skala burzliwości L_0/d – od 0,07 do 0,75. W wyniku interpretacji danych doświadczalnych stwierdzono przydztność dla ciał osiowo-symetrycznych simpleksa β saproponowanego dla przepływu w rurze przez Mościoką [9]. Analize statystyczna otrzymanych wyników pozwoliła na otrzymanie następującej zależności dla średnich współczynników wnikania ciepla:

Работа касается вляяния параметров турбулентности на теллоперенос при обтекания шара. Опыты проведены при исплользовании металлических шаров диаметром 59,6 и 41,4 км, с внутреними обогревом. Число Рейбольдса каменили в интернале $3 \cdot 10^3 - 3 \cdot 10^3$, а пределы каменений параистров турбулентности были равны: степень турбулентности в -- 3-24% в безмерный насштаб турбулентности $L_g/d = 0.07 \cdot 0.75$. В результате интерпратация экспериментальных дациых обивружена пригодность для осевосимметрических тел симплекса β , предложенного Мосыцицкой [9] одя точения в трубе. Статистический анализ полученных результатов позволил получить следующую зависимость для средних козфециентов теплоотдами:

The work deals with the influence of the turbulent parameters on heat transfer coefficients by flow of air stream past single sphere.

The inside heated metallic spheres of 59,6 and 41,4 mm dismeter placed in a vertical wind tunel were used. The variable parametres varied as follows: Reynolds number: $R_{0} = 3 \cdot 10^{3} \cdot 3 \cdot 10^{4}$, level of turbulence: $\epsilon = 3 \cdot 24\%$, aimensionless scale of turbulence: $L_{0}/d = 4,07 \cdot 0,75$.

It was found that number β proposed by Mościcka [9] for flow in the pipe, is witable for the correlation of heat transfer data for the sphere.

On the basis of the statistical analysis the results of the experiments were correlated by the dimensionless equation :

Nu - 0,142 Rob. 40 / - 0,34 (Bd) -0.16.

L

Introduction

The transfer of heat and mass from spherical particles to a stream of liquid appears in many industrial problems. We can here number the processes of the dispersive drying up of solid bodies, the moistening of the air, the chemical processes occuring in catalytic layers, the problems of spherical exchanges of heat as well as of dissolution, sublimation and barbotage.

In a majority of the applica tions mentioned here, we have to deal with turbulent flow. In these conditions one of the most useful methods of intensifying the transfer of heat and mass is the artificial increase of turbulence of a liquid flow. This is realized through the introduction to the flowing liquid of a different kind of turbulence generators which induce a change in the parameters determining the core turbulence. This is confirmed in many of the works devoted to this problem [1-57.

The development of measuring techniques, especially thermoanemometry [6,7] allowed for an accurate determination of the parameters of core turbulence. The obtaining of correlation equations of heat and mass transfer was made possible in these cases by an artificially increased turbulence. Analysis of the experiments permit confirmation of the divergence between the various authors' results. An additional inference resulting from analysis of the literature is the confirmation of the need for the resolution of this problem on the theoretical level.

In light of these considerations it appears that the appropriate conduct of further experimental work, having the goal of explanation of the mentioned differences, and at the same time the acquisition of generalized methods calculated for

this process should take place.

The object of the present work was the experimental determination of the influence of the basic parameters describing the isotropic fields of liquid flow trubulence, that is to say, the degrees and scale of turbulence in heat transfer from a single metallic sphere located in an air stream.

The Current State of the Problem

The transfer of heat and mass during flow around a body is strictly connected to the hydrodynamic conditions of a flowing liquid. These conditions are usually defined by Reynolds numbers. For a stratified flow the determination of the Reynolds number by use of the velocity of the liquid flow allows the synonymous determination of the hydrodynamic conditions of flow. It is not sufficient in the area of turbulent motion, where we have to deal with a continual change of values and the direction of the vector of velocity. The speed of the liquid's flow refers to that averaged over time.

For these conditions a Reynolds number is not a sufficient criterion of hydrodynmaic similarity, and it is necessary for the completion of this description that we have the aid of interdependent parameters of turbulence: the degree and scale of turbulence. This fact is confirmed in the works of Hinze [87, Moscicki [97, as well as by Boulous and others [107.

Consideration of these parameters allows the obtaining of various hydrodynamic conditions, and at the same time of various intensities of exchange processes by the same Reynolds number.

The problem presented until this time was not subject to full theoretical solution. This results mainly from the lack of

an accurate theory of turbulence, and particularly the difficulty of defining the phenomenon of turbulent exchange momentum, of heat and mass in the boundary layer. This is connected to the indefinite knowledge of the parameters of turbulent transfer: turbulent viscosity, turbulent conductivity and turbulent diffusion, which are necessary for the solution of the generalized differential equations describing this process. The parameters are not functions of the state and depend upon the situation. One of the most direct methods of determining these parameters is based on knowledge of the velocity distribution as well as the Prandtl concept, until this time the mixing length. Other methods described are in the works of McEligot [11] and Bankston [12].

The solutions mentioned were obtained for a fluid flow in a pipe or for the flow around two-dimensional plates, where the velocity distribution is accurately described. This problem is remarkably complicated in the case of flow around rotary bodies, i.e., a sphere or a cylinder, where we have to deal with the mixed character of the movement and with the phenomenon of the separation of the boundary layer. For these conditions there was not obtained thus far a complete theoretical solution of differenctial equations and recently the published work of Galloway [13] concerns only the fron-half of a sphere. This author as a result of the numerical solution of differential equations describing the motion of heat in the flow around a sphere, using the mentioned conception of centrifugal viscosity based on the Prandtldefined mixing length, obtained the following relationship

$$F_{4} = 1,47(1 - A_{4}\xi^{2} - A_{4}\xi^{4}) \frac{1}{1 + \phi_{4}(Pr)}$$

where

 $F_{s} = \frac{Nu - 2}{ke^{0.5} P_{7}^{0.34}},$ (2)

(1)

$$\Psi_{2}(Pr) = \frac{0,0840}{Pr^{0.33}} - \frac{0,0079}{Pr^{0.67}} + \frac{0,001325}{Pr} - \frac{0,00406}{Pr^{1.38}} + \frac{0,00317}{Pr^{1.67}}, \quad (3)$$

$$\zeta = \int_{-\infty}^{\infty} \left[\frac{U_{1}(\omega)}{U_{\infty}} \right] \left[\frac{r(\omega)}{d} \right]^{16} d\left(\frac{\omega}{d} \right) \quad (4)$$

(for flow around a sphere k = 1).

A comparison of the derived solution with the experimental results indicate its utility only for low ranges of turbulence degrees. This connected to the imperfection of the turbulence model based on the Prandtl concept as well as with the simplified description of the velocity profile of Ruckenstein and Berbente [14] used in this work. There appears to be an appropriate reception in this area of the modified conception of Deissler, Van Driest or others [11, 12]

Great difficulties in the analytic description of heat transfer in conditions of turbulent flow caused the need for the undertaking of a series of experimental works. From the analysis of these works [15,16] it results that bodies flowed around (spheres, cylinders) the intensifica tion of heat transfer by an increase of turbulence of the inflowing system is connected with the appearance on the boundary layer of the following phenomena:

1. A later passing from a laminar to a turbulent boundary layer (by lower angles of substitution).

2. Interactions of the vortices of the main stream on the flow in the laminar and turbulent boundary layer.

3. Displacements of the point of separation and development of changes in the track behind the body discussed.

Quantitative analysis regarding the evaluation of

the influence of separate effects on the intensification of the exchange processes is not possible at the moment.

The principal criterial equation used by various authors, defining the movement of heat in flows around a body and accounting for the parameters of trubulence is the relationship

$$Nu = f(Re, Pr, \varepsilon, \frac{L}{d}), \qquad (5)$$

where ε - degree of turbulence, L/d - simplex formulating the relation of the scale of turbulence to a linear dimension.

A significant number of the authors (17,18,19) restrict their investigations solely to the effect of the degree of turbulence adding the assumption that the effect of the scale of turbulence is insignificant. Such data are represented appropriately in figure 1, where there are represented the results of Venezjan's work (20). There is observed an increase in the intensifica tion of heat transfer Nu at approximately 50% in the result of the increase ε from 2 to 15% as well as the relationship of this increase upon the Reynolds number range.

Another group of authors [9, 21, 22] account in their work as well for the scale of turbulence, however their views on the effect of this parameter are contradictory. One can observe as well great differences vis-a-vis the definition of the size of the effect of the degree of core turbulence on the intensity of heat transfer. This is shown in figure 2 where the results of various experimental works are shown, The nonuniform opinions pertain as well to the influence exerted by core turbulence on the front-half as well as the back-half of a sphere, and also the effect of the degree of turbulence in the area of lower and higher values of this parameter [21,22,25]. A certain test of the interpretation of these divergences is given in work [9].



The current state of the problem as stated indicates that there is a lack of accurate, certain analytic methods, permitting a definition of the effect of core turbulence on the intensity of heat transfer from axial-symmetrical bodies (sphere, cylinder). Numerous experimental undertakings conclude with contradictory opinions via-a-vis the quantitative grasp of the process considered. They indicated as well the great possibilities of an intensification of these processes by the application of artificial promoters of turbulence.

Experimental Portion

Experimental tests took place in a vertical wind tunnel of the closed type at an altitude of 7 m, and with an internal diameter of 228 mm. The neasuring section was positioned at the upper part of the tunnel, in which there was installed a test sphere. The intensity of the air flow was measured by the use of a Prandtl pipe connected with an inclined manometer.

Metallic spheres were used for the test with diameters of 59.6mm and 41.4mm. They were fabricated from copper sheeting, and then, after the installation of thermal elements on its surface as well as on the heating coil, the interior of the spheres were executed in fluid zinc. Liquid was supplied to the coil from a pump at a regula ted rate. The amount of the flowing liquid was recorded and the temperature at the intake and outlet of the coil which permitted the achievement of a balance of heat, and then a determination of the coefficient of heat penetration. Tests accounted for the following range of parameter changes:

- Reynolds number = $3 \cdot 10^3 30 \cdot 10^3$,
- degree of turbulence $\varepsilon = 3 24\%$
- scale of turbulence expressed in the form of simplex L/d = 0.07 0.75

The special construction of the research apparatus as well as construction of the spheres are represented in work [26].

As the promoters of turbulence there are used perforated plates as well as woven nets from ferrous bronze wire. Such a solution has assured the finding of a wide range of variations of turbulence parameters. Some structural parameters of several turbulence promoters are compared in Table 1.

Measurement of the turbulence parameters of the airstream flow was obtained with the aid of the constant temperature thermometric DISA D 61. Employed for the measurements were sensors of the heating wire type 55 E 20. The gradation of these sensors were provided in the aerodynamic tunnel DISA 55 D 41/42. The shift of the sensors to the radius of the tunnel was accomplished with the aid of the shifting system DISA 55 E 40 with an accuracy of O.lmm. The measures of the trubulence parameters as well as the determined dimensions of the heat transfer were provided in separate time intervals with the aim of avoiding the deformation of the boundary layer developed by the presence of the sensor. In the result of the tests there was used a velocity distribution in a section of the tunnel (figure 3), which was used for the determination of the average speed. A comparison in this way of the results obtained with the indica tors of the Prandtl pipe demonstrate a deviation not exceeding 4%. Moreover, analysis of the obtained velocity profiles without a net and in its presence (figure 3) point to a deformation of the velocity profiles obtained by a net. Hence, the corollary resutls that with the aim of enabling the comparability of results, the Reynolds number should be defined by the use of volumetric velocity, which was used in the present work.

The degree of airstream trubulence defined by the described method in works [8,27], and the dimension of the integral

Lp. No.	Rodzaj promo- tora King of promo- tør	Materiał Material	Grubość blachy Plate thick- uces	Średni- ca otwo- rów Hole diame- ter [mm]	Podział- ka otwo- rów Hole pitch [mm]	Ilość otworów Hole number	Stopień zaję- cią powierz- chni przekro- ju Degree of fil- ling of cross- sectional area	
1	Piyta perforo- wana	aluminium	5	14	17	127	0,485	
2	perforated plate	stal steel	10	13	19	109	0,619	
з	Siatka tkana o kwadratowych oczkach Woven net with square mesh	žolazobrąs ferrobrons	érednice drutu wiré dismeter d = 1 mm		Liczba oozek cm ^a = 4 mesh number aq·cm = 4			

Tabela I - Table I









scale of turbulence was calculated by the graphic method (figure 4) in the manner presented in works [8,9]. As a result of the analysis of the obtained measurement results, the values ε and L_g depend on the geometry of the turbulence promoters used. Another corollary emerging from these tests is confirmation that with an increase of a sphere's distance from a promoter of turbulence the degree of turbulence diminishes as well as does not undergo changes due to changes in the airstream flow. A similar confirmation can be found in works [3,29].

Interpretation of the Results

The initial point of interpretation of the experimental results was the determination of the relationship of the Nusselt number to the Reynolds number. Such data is represented in figure 5. Analysis of the graph indicates that the measurement points were arranged on several straight lines at close values of the directivity coefficient but at other constants. Each of the represented relationships correspond to a different value of the airstream turbulence parameters. With an increase in flow turbulence defined equally as the degree of turbulence ε , and as in the scale of turbulence \mathbf{L}_g/d , the heat transfer rises until the maximum effect of intensification reaches approximately 60%. From this graph one can observe as well that this effect is greater for the higher range of Reynolds numbers.



Bys. 4. Zależność $g(r) \rightarrow f(r)$ Fig. 4. Relationship $g(r) \rightarrow f(r)$ v - net ur i. 7 - net ur s. 0 - net ar s. 40 - usee



Similar results to this effect are here mentioned in the turbulence parameters used by Lavender and Pei [19], Venezjan et al [20] as well as Galloway and Sage [24]. Higher values of heat transfer intensification (over 70%) were confirmed by Endoh et al [22], and lower (approx. 40%) by Isatajew and Zanawajew [17].

Because many of the authors interpret the results of their tests with the aid of the introduction for general criterial equation of the Reynolds turbulence number Re_T , their own results were converted similarly and in this way were used in the graph represented in figure 6. One should remark here upon a certain spread of experimental points which results from the disregard in this type of interpretation of the effect of the scale of turbulence. Additionally, in this figure there are included the data used by other authors. In this sense one can acknowledge the position of one's own data with satisfaction.





Further quantitative analysis of the experimental results obtained are carried out on the basis formulated by Moscicka [9] of the hydrodynamic criteria of similarity of turbulent flow fields in a pipe. From the equations put forth in this work, there results that the degree and scale of turbulence cannot be treated as independent hydrodynamic criteria defining the core turbulence. For one cannot experimentally separate their effect on the intensity of the processes of heat transfer and mass. Also, an authoress proposed the introduction to the general criterial equation of heat transfer or mass a simplex tying both the mentioned parameters, so defined as

$$\boldsymbol{\beta}_{\mathrm{R}} = \frac{\mathrm{L}_{\mathrm{g}}}{\mathrm{R}} \, \epsilon^2 \tag{6}$$

Because in the present work the aim of test was heat transfer about a sphere there necessarily appears the consideration in simplex definition (6) of a characteristic dimension, such as is the diameter of the sphere [28] instead of the radius of the research tunnel. This fact has equally confirmation in a number of the experimental works currently under discussion.

Considering the remark above, we obtain the following criterial equation of heat transfer:

$$Nu = f(Re, Pr, Pd).$$
(7)

Utilization of equation (7) for interpreting the experimental results with the aid of methods of statistical analysis (Gauss multiplier method [29] is accomplished on the digital computer ODRA 1204) allowed for use the following correlation equation:

$$Nu = 0.142 \text{Re}^{0.6} \text{Pr}^{0.33} (\textbf{p}_d)^{-0.16}.$$
 (8)

The corresponding statistical parameters amount to:

$$R_y = 0.954, \beta_y = 0.046, D_y^2 = 0.0098.$$

A graphic illustration of equation (8) is given in figure 7.



In the obtained equation (8) the Nusselt number depends on the non-dimensional simplex β_d to the power (-0.16). For flow bodies which have not used a parameter of this type, immediately for a heat exchange during flow through a pipe, Moscicka [9] obtained the equation

$$Nu = 0.005 \text{Re}^{0.8} \text{Pr}^{0.33} (\mathbf{P}_{R})^{-0.25}.$$
(9)

Differences of indexes for simplexes expressing the turbulence of a flow can result here from the distinct geometry of systems.

In equation (8) the index according to the Reynolds number amounts to 0.6. This value appears to be completely explained in light of the work of Rowe and Claxton [32], which discusses for a similar range the number Re given in work [26].

Corollaries

1. On the basis of a critical survey of the literature up to this time on the effect of turbulence parameters on heat transfer on the flow around a sphere, there was confirmed:

-the possibility of the intensification of the process by the use of turbulence promoters;

-the lack of analytic and experimental methods, allowing for the synonymous evaluation of the effect of artificially induced turbulence;

-the lack of a synonymous opinion of the hitherto choice of corresponding parameters determining the effect mentioned.

2. There is confirmed the suitability of the simplex β proposed by Moscicka [91], considering as well the scale and the degree of turbulence for the interpretation of the data obtained in the result of the tests of the process of heat transfer for rotary bodies. 3. Interpretation of one's own experimental material (120 measurement points) by the use of simplex β allowed the formulating of the following criterial relationship:

.

 $Nu = 0.142 Re^{0.6} Pr^{0.33} (pd)^{-0.16}$.

OZNACZENIA - SYMBOLS

	Analasian kuli	
	- srounds sun	
a(r)	- wanólezvanik korelacji predkości	
	coefficient of correlation of velocity	
,	- promień	ш
	radius	
4 , v	– składowe pulsácyjne w kierunku z, y	w/s
	fluctuating velocities in a, y direction	
A1, A4	- stale w rozwiązaniu GALLOWAYA [13]	
	constants in GALLOWAY's solution [13]	
D ² ,	- wariancja resztkowa	
	residual variance	
L	- calkowa skala burzliwości	m
1 11	integral turbulence scale	
$L_g = \frac{1}{R} \int g(t)$	r)dr – poprzezna skala burzliwości	m
	transverse scale of turbulence	
R	- promień tunclu powietrznego	ţ,
	radius of air tunnel	
K _V	- współczynnik korelacji	
	correlation coefficient	
0,7	- threattons w cause produced w klorunku z, y	tri /e
	winte-storegou telepicy in s, y circewon	
1		
+	- współczynnik wnikania ciepta	W/mit.day
1	heat transfer coefficient	
20	– poziom istotności korelacji	
1	significance level of correlation	
1	- stopisú burzliwości	
;	integnity of turbulenco	1
i	LICEBY BEZWYNIAROWE - DIMENSIONI HER CONT	a is
1 - (NH - 2)/	1:40,5 / -0.33 Lington Definition	
	Weinsting and be	and the second sec
Iva antis	lingha Number	a start and a start and a start
and and a	Numelt number	
Pr - culà	- liceha Brandtla	
1	Prandtl number	
Ko - Ud/v	- liczha Revnolden	
	Reynolds number	
Ker - Kee .	- burzliwa licsba Reynoldus	
(Bie) - (Ly/K)e2	- krytorium podobieństwa bursliwych udl prest	WH W# [9]
	criterion of the similarity of turbulent flow field	de after (9)
(Jd) - (Lg/d) e*	- kryterium podobiedstwa bursliwych pół przenty	vu liesone wagledom
:	drudnicy kuli	
A State State	eritories of the similarity of turbulest floy f	diry botelucios alla

INDEKAY - BUMBCRIPTS

- wartość średnia dla przekroju poprzecznego tunelu averago valuo for tunnel cross-section
- w bezpośrednim sąsiedztwie warstwy granicznoj
- in immediate vicinity of boundary layer » — w głównym strumieniu płytu
 - in the bulk of fluid

CITED SOURCES

[1] Ju. A. IWANOW, Int. Fiz. Zurn., 19, 818 (1970).

[2] D. G. THOMAS, Ind. Eng. Chem., Proc. Design and Devel., 6, 385 (1967).

[3] I. Mościcka, Przem. Chom., 48, 422 (1969).

[4] M. E. CHARLES, C. H.S. CHEN, L. H.L. CHU, Can. J. Chem. Eng., 49, 737 (1973).

[5] A. SCHACK, Industrial Heat Transfer, J. Willey, New York (1965).

[6] S. GOLDSTEIN, Modorn Developments in Muid, Dover Publ., New York 1905.

[7] W. K. GEORGE, J. Fluid Moch., 66, 11 (1974).

[8] I. O. HINZE, Turbulentność, tl. z ang., Gonud. Izd. Fiz. Mat. Lit., Moskwa 1963.

[9] I. Mościcka, Chem. Stos., 1B, VII, 85, 105, 130 (1070).

[10] J. M. BOULOS, D. C. T. PEJ, Can. J. Chem. Eng., 52, 637 (1973).

[11] D. M. MCELIGOT, S. B. SMITH, C. A. BANKSTON, Tr. ASME, J. Heat Tr., 92, 642 (1970).

[12] C. A. BANKSTON, D. M. MCELIGOT, Int. J. Heat Mass Tr., 13, 319 (1970).

(13) T. R. GALLOWAY, AICHEJ, 3, 608 (1978).

[14] E. RUCKENSTEIN, C. BERNENTE, Chem. Eng. Sci., 25, 475 (1970).

[15] A. CLAMEN, W. H. GAUVIN, Cun. J. Chem., Eng., 46, 223 (1968).

[16] T. R. GALLOWAY, B. H. BAGE, AIChEJ., 18, 287 (1972).

[17] B. J. JEATAJEW, Z. Z. ZANAWAJEW, Int. Fiz. Zurn., 16, 586 (1972).

- [18] L. B. NEWMAN, E. M. SPARROW, E. R. G. EOKERT, Tr. ASME, J. Heat Tr., 94, 7 (1973).
- [19] W. J. LAVENDER, D. C. T. PEI, Int. J. Heat Muss Tr., 10, 529 (1967).
- [20] E. VENEZIAN, M. J. CRESPO, B. H. SAGE, AJChEJ., 8, 883 (1962).
- [21] G. D. RAJTHBY, E. R. G. ECKERT, Int. J. Heat Mass Tr., 11, 1233 (1968).
- [22] K. ENDOH, H. TSURUGA, H. MIRANO, M. MORIHIBA, J. Heat Transfer-Japanese Res., 1, 113 (1972).
- [23] W. S. BROWN, K. SATO, B. H. SAGE, Chem. Eng. Data Ser., 3, 263 (1958).
- [24] T. R. GALLOWAY, B. H. SAGE, Int. J. Heat Muss Tr., 7, 283 (1964).
- [25] V. J. GOSTKOWSKI, F. A. COSTELLO, Int. J. Heat Mass Tr., 13, 1383 (1970).
- [26] A. MARKOWSKI, Cz. STRUMILLO, Int. Chem., III, 3, 565 (1978).
- [27] DISA, Aebraucheanweisung und Servicekandbuch für Termianom.
- [28] Cz. STRUMILLO, A. MARKOWSKI, B. GRABOWSKI, Zeszyty Nuuk. Polit. Lódzkiej, Chomis, 26, 93 (1972).
- [29] W. VOLK, Statystyka stosowana dla intynierów, WNT, Warszawa 1973.
- [30] T. R. GALLOWAY, B. H. SAGE, AJChEJ, 10, 1195 (1967).
- [31] I. J. BIBZOZJUTKO, B. M. SMOLSKIJ, W. K. SZCZITNIKOW, Tieplo i massobmien pri facewych i chimicocchich provrazoconiach, Izd. Nauka i Technika, Mińsk 1961, 220.
- [35] P. M. Rows, K. P. CLARTON, Trans. Inst. Chem. Kuges., 10, 801 (1966).

DISTRIBUTION LIST

DISTRIBUTION DIRECT TO RECIPIENT

ORGAN	IZATION	MICROFICHE	ORGAN	IZATION	MICROFICHE
A205	DMATC	1	E053	AF/INAKA	1
A210	DMAAC	2	E017	AF/RDXTR-W	1
B344	DIA/RDS-3C	9	E403	AFSC/INA	1
C043	USAMIIA	ī	E404	AEDC	1
C509	BALLISTIC RES LABS	ī	E408	AFWL	1
C510	AIR MOBILITY R&D LAB/FIO	. ī	E410	ADTC	1
C513	PICATINNY ARSENAL	1		FTD	
C535	AVIATION SYS COMD	1		CCN	1
C591	FSTC	5		ASD/FTD/ NIIS	5 3
C619	MIA REDSTONE	1		NIA/PHS	1
D008	NISC	ī		NIIS	2
H300	USAICE (USAREUR)	ī			
P005	DOE	ī			
P050	CIA/CRB/ADD/SD	ī			
NAVOR	DSTA (50L)	ī			
NASA /	KSI	ī			
AFIT/	LD	ī			
LLL/C	ode L-389	ī			

. "

Y. .