

AD-A064 837

GEORGE WASHINGTON UNIV WASHINGTON D C SCHOOL OF ENGI--ETC F/6 21/2  
MULTIANGULAR SCANNING ABSORPTION-EMISSION TECHNIQUES FOR THREE --ETC(U)  
DEC 78 R GOULARD AFOSR-77-3439

UNCLASSIFIED

AFOSR-TR-79-0056

NL

| OF |  
AD  
A064837



END  
DATE  
FILMED  
4-79  
DDC

AFOSR-TR- 79 - 0056

③ LEVEL II  
SC

MULTIANGULAR SCANNING ABSORPTION-EMISSION  
TECHNIQUES FOR  
THREE DIMENSIONAL  
COMBUSTION DIAGNOSTICS

AFOSR 77-3439  
Annual Technical Report

prepared for:

AFOSR, Bolling AFB


Attn: Dr. B.T. Wolfson

ADA064837


DDC FILE COPY

R. Goulard

December 1978



School of Engineering and Applied Science  
The George Washington University  
Washington, DC 20052



Approved for public release;  
distribution unlimited.

79 02 16 061

AIR FORCE OFFICE OF SCIENTIFIC RESEARCH (AFSC)  
NOTICE OF TRANSMITTAL TO DDC  
This technical report has been reviewed and is  
approved for public release IAW AFR 190-12 (7b).  
Distribution is unlimited.  
A. D. BLOSE  
Technical Information Officer

# LIST OF CONTENTS

	Page
TECHNICAL OBJECTIVES	1
CURRENT STATUS	2
ABSORPTION TECHNIQUES IN 3-DIMENSIONAL DIAGNOSTICS	4
DEVELOPMENT OF THE TECHNIQUE	11
CONCLUSION	13
LIST OF REFERENCES	14

ACCESSION for		
NTIS	White Section	<input checked="" type="checkbox"/>
DDC	Buff Section	<input type="checkbox"/>
UNANNOUNCED		<input type="checkbox"/>
JUSTIFICATION _____		
BY _____		
DISTRIBUTION/AVAILABILITY CODES		
Dist.	AVAIL. and/or	SPECIAL
A		

79 02 16 061



## TECHNICAL OBJECTIVES

As better measurement techniques become available, new ranges of combustion phenomena can be studied with the accuracy necessary for meaningful interpretation. In particular, the potential of optical methods as compared to that of classical probes should be evaluated in the context of the phenomenology needed for the design of current and future combustors. Specifically, it is proposed to extend the absorption-emission methods previously limited to one-dimensional and axisymmetrical flows ("onion-peeling"), to the more realistic 3-dimensional flow fields found in actual combustion devices.

The relevance of such a study to the research needs of the Air Force is supported by the constant need expressed in propulsion design groups, for a combustion phenomenology verified realistically by accurate diagnostics. Since current measurement techniques are for the most part constrained to point measurements with little flexibility for the recording of time- or space- histories (i.e., correlations or profiles), the proposed technique would answer a serious need in real, 3-dimensional and often unsteady systems.

## CURRENT STATUS

a. Typical pollutant/radical distribution in flames have been simulated by summation of Gaussian curves and also by uniform areas of concentration inside a flame cross section.

b. Two distinct multiangular algorithms are being tested on these synthetic profiles: one based on two-dimensional Fourier transforms, the other on an iteration (back-projection) method. Work is proceeding satisfactorily, with some partial results available. It is reviewed in Part II of this technical report. Substantial support (mostly advice) has been given by the Washington medical research community (X-Ray Tomography) and by interferometry specialists (Dr. Sweeney).

c. As we move towards a practical design for pollution/radical diagnostics by the end of this grant, we have also explored the use of multiangular techniques in X-Ray applications. Following a visit to Dr. McGregor at AFRPL (January 1978), several applications of X-Ray techniques to Air Force needs have been evaluated (a report co-authored by Dr. Geskin is in preparation).

d. A continuing assessment is being made of the various competing diagnostics techniques susceptible of application in Air Force present programs and future research plans, especially in air breathing propulsion. In this very active field, expectations and risks are difficult to assess, especially when novel techniques (CARS, fluorescence) are proposed. A review paper is being prepared.

e. Three seminars on this current work have been given in the last 8 months (Howard U., NASA-Langley and AFRPL). A paper was presented

at the 1978 Central State Section Meeting of the Combustion Institute. A review of the absorption diagnostics has been prepared for the AIAA Aerospace Sciences meeting in January 1979 (Paper 79-0085).

f. The personnel involved in this research have been:

R. Goulard, principal investigator (3 man-months)

E. Geskin (1½ man-months)

P. Emmerman (2 man-months)

## ABSORPTION TECHNIQUES IN 3-DIMENSIONAL DIAGNOSTICS

In three dimensional diagnostics of concentrations and temperature, point measurement techniques, such as Raman scattering for instance, suffer from very small cross sections and are therefore limited in their threshold and accuracy. Path measurement techniques (interferometry, absorption) correspond to much larger cross sections and are therefore more accurate. However, these measurements are path-integrated and it is necessary to treat them by suitable mathematical algorithms in order to obtain properties at every point in the medium.

There exists (Goulard 1976) two ways to generate the information necessary to obtain the profile of a property along a line ( $n$  points) or for a planar cross section ( $m \times n$  grid). One is frequency-scanning where  $n$  frequencies are measured along a given line of sight. This method has been evolved with great success in satellite meteorology and stellar atmospheres (Wark et al. 1966, Chahine 1970, Jeffries 1968). The other is multiangular scanning where the absorption of  $m$  equally-spaced parallel beams is measured in a given direction  $\theta$  ( $m$  measurements); the procedure is then repeated for  $n$  other angles (see Fig. 1). From the resulting set of  $m \times n$  data, it is possible to retrieve a  $m \times n$  grid of properties.

The frequency-scanning method has been used in the case of combustion (Chao and Goulard, 1974), but the inherent difficulty of converting optical lengths (i.e., density  $\times$  length) to physical lengths, makes it cumbersome, except for those cases where additional information is available (e.g. known mixing ratio, density law, etc. (Goulard, 1977a)). The multiangular method has been applied to interferometry (Sweeney and Vest 1974) and X-Ray diagnostics (the latter with great commercial success (Brooks and diChiro, 1976; Gordon et al., 1975)). The procedure is outlined below.






Fig. 1. Typical Scanner. 180 values of  $\theta$  are used and 160 parallel beams for each value of  $\theta$  (Delta Scanner, Ohio Nuclear, Inc.).




Fig. 2. Cartesian and Scanning Coordinates.



### The Multiangular Scanning Procedure

The multiangular scanning technique is based (Fig. 2) on the image reconstruction of a property field  $f(x,y)$  from its projection in the  $\theta$  direction:

$$f_{\theta}(r) = \int_{-\infty}^{+\infty} f(r,s) ds \quad (1)$$

where:  $r = x \cos \theta + y \sin \theta$

$$s = -x \sin \theta + y \cos \theta$$

There exists a number of mathematical methods which use the set of  $(m \times n)$  values of  $f_{\theta}(r)$  obtained experimentally (by scanning the field of interest for  $m$  values of  $\theta$  and  $n$  values of  $r$ ), and then convert this data into a  $(m \times n)$  grid of  $f(x,y)$  values. At the limit, an infinite number of measurements would give an exact map of  $f(x,y)$ . Once the map  $f(x,y)$  has been established for a section  $z$ , measurements are performed at other sections  $z$  and eventually the three dimensional map  $f(x,y,z)$  is obtained.

In the case of flame absorption data, if a beam of initial intensity  $I_0$  emerges from the flame with an intensity  $I$ , the absorption equation takes the form:

$$\frac{I}{I_0} = \exp \left[ - \int_{-\infty}^{+\infty} (N_i Q_i ds) \right] \quad (2)$$

where the product (cross section  $Q_i$  x concentration  $N_i$ ) for the component  $i$  can be considered as a local function  $f(r,s)$  of the thermodynamic properties and concentration of  $i$  at the point  $(r,s)$  or  $(x,y)$ . Since the ratio  $I/I_0$  can be measured experimentally, it is seen that by writing Eq. 2 in the form

$$- \log \frac{I}{I_0} = \int_{-\infty}^{+\infty} (N_i Q_i) ds \quad , \quad (3)$$

the techniques developed in other fields of application to solve Eq. 1 can be readily extended to the 3-dimensional measurement of  $(N_i Q_i)$  in flames.

If this measurement is made at the frequencies of two excited states of the same band, the ratio of the two retrieved values yields the temperature  $T$  through a Boltzmann relationship (see Chen and Goulard 1976). The knowledge of the  $(x,y)$  maps of  $N_i Q_i$  and  $T$  yields in turn the concentration  $N_i$ , since  $Q_i$  is available from the literature as a function of  $T$ .

In practice, except for the "generalized onion peeling" method proposed by Chen et al (1976), the multiple angular scanning method has not been applied to absorption. However, it has been used successfully in interferometry and X-Ray tomography. Since "onion peeling" methods amplify experimental errors, the available algorithms developed for interferometry and tomography are worth closer inspection in terms of possible use in absorption experiments. They fall in three general categories which have been evaluated and compared, especially in both contexts of X-Ray tomography (Brooks and diChiro 1976) and interferometry (Sweeney and Vest 1974, Radulovic and Vest 1976).

1. Two-dimensional Fourier transforms. This method is based on the fact that by taking the Fourier transform of Eq. 1, one obtains a "spectrum"  $F_\theta(\rho)$  of the experimentally available function  $f_\theta(r)$ :

$$F_\theta(\rho) \equiv \int_{-\infty}^{+\infty} f_\theta(r) e^{-2\pi i \rho r} dr,$$

where  $\rho$  is an integer which can take any number of values:  $1, 2, \dots$ . It is possible also to construct a function  $(\theta, \rho)$ :

$$\mathcal{F}(\theta, \rho) \equiv \int_{-\infty}^{+\infty} F_\theta(\rho) e^{-2\pi i \theta s} ds,$$

where  $\theta$  is another integer, which in this application is the measurement

angle  $\theta$ . The function  $\mathcal{F}$  can be written then:

$$\mathcal{F}(\theta, \rho) = \int_{-\infty}^{+\infty} \int_{-\infty}^{+\infty} f(r, s) e^{-2\pi i(\rho r + \theta s)} dr ds \quad (4)$$

which is clearly a two-dimensional Fourier transform of the function  $f$ . Therefore, its inverse Fourier transform is the unknown function  $f$ . Numerical methods, using finite series rather than integrals, have been adapted to this case. Their accuracy improves with the number of measurements and they tend to be successful mostly for situations where access is free from all angles.

However, it should be noted that Fourier transform calculations can be initiated only after all the data ( $\theta$ ) has been collected (Eq. 4). Fast Fourier Transform techniques (FFT) have accelerated this process substantially (Bendat 1971, Thomson 1976), but still faster procedures have been evolved. In the convolution methods developed by Ramachandran (1974), the profiles  $f_{\theta}(r)$  collected for each  $\theta$  are immediately "back projected" on the beam ( $\theta, r$ ). The picture matrix is thus constructed in cumulative fashion as the angular scanning proceeds over  $\theta$ . Typically (Ledley 1976), an ACTA-scanner will deliver a 64,000 element map of  $(N_i, Q_i)$  in  $4\frac{1}{2}$  minutes or less. This method has been extremely successful in detecting lesions and abnormalities in brain or limb cross sections, based only on the absorption characteristics of such tissues in the X-Ray range.

2. Series expansions. This approach relies on the properties of certain series expansions to match by their first terms the main features of the property profiles. For instance, the Hermitian polynomials  $H_{mn}(x, y)$  have been shown to be well suited to near-Gaussian density profiles by Matulka and Collins (1971).

3. Iterative techniques are based on straight forward algorithms

which repeatedly adjust the estimated  $f(x,y)$  map until convergence is accomplished. This is done by comparing for each beam  $(\theta, r)$ , the value of  $f_{\theta}(r)$  calculated on the basis of the estimated values of  $f(x,y)$ , with the actual measurement of  $f_{\theta}(r)$ . An algorithm increases then the estimated  $f(s,y)$  values along the beam  $(r, \theta)$  by the same increment, in such a way as to reduce the difference between measured and calculated  $f_{\theta}(r)$  to zero. The procedure is repeated until the predicted values of  $f_{\theta}(r)$  coincide with actual measurements for all  $\theta$ 's. Obviously, a clever choice of mathematical "filters" is essential to this approach. Often called "Algebraic Reconstruction Techniques (ART)", they have been found to be very successful in a number of early applications, in particular when no a-priori knowledge of the profile existed. Their convergence can be accelerated by smoothing techniques (Chen and Goulard 1976, Baba and Murata 1977). Such methods can handle also highly non-linear cases, as it has been demonstrated in frequency-scanning techniques (Chao and Goulard 1974). However, such methods are "brute force" and convergence can be laborious. Most commercial scanners use a variation of the Fourier transform approach.

#### APPLICATION TO COMBUSTION PROBLEMS

The applicability of multiangular methods to absorption techniques is tied to the existence of absorption bands which can be matched by existing light sources. Such combinations have been exploited for years by combustion experimentalists. Listed below are typical species found in flames and their absorption cross section  $Q_i$ :

CO	$\lambda = 4.74 \mu$	$Q_i = 1.7 \times 10^{-18} \text{ cm}^2$
NO	$= 0.22$	$= .5 \times 10^{-17}$
C <sub>6</sub> H <sub>6</sub>	$= 0.25$	$= 1.3 \times 10^{-18}$



OH	$\lambda = 0.31 \mu$	$Q_1 = 5.1 \times 10^{-17} \text{ cm}^2$
NO <sub>2</sub>	= 0.4	= $1.1 \times 10^{-17}$
CO <sub>2</sub>	= 4.3	= $1.8 \times 10^{-17}$
H <sub>2</sub> O	= 2.7	= $6.1 \times 10^{-18}$
SO <sub>2</sub>	= 8.8	= $5 \times 10^{-20}$
C <sub>2</sub> H <sub>4</sub>	= 10.54	= $1 \times 10^{-18}$

For samples a few inches deep, the effective detection threshold corresponds to a transmittance which is equal to about  $10^{-2}$  with ordinary light sources (Goulard 1976). However, the advent of tunable lasers (see Fig. 3) combined with differential absorption techniques, have led to thresholds of the order of  $10^{-4}$  (Patel 1978). Therefore, the values of  $Q_1$  listed above allow for a concentration threshold of the order of 100 ppm with ordinary sources and 1ppm with laser sources. Hence the great promise of the absorption multiangular scanning method.

In practical combustion systems, a very important question is the kind of optical access which is available to the experimentalist. In interferometry, the effect of the reduction of the view angle from  $180^\circ$  to  $90^\circ$  or to  $45^\circ$  has been evaluated by Sweeney and Vest (1973) from the standpoint of error increase and computer time gains. Similarly, Rachamandran (1971) has estimated the loss of accuracy incurred when the number of viewing angles  $\theta$  is reduced to twelve or three. There again, the conclusions seem to depend very much on the particular field and especially on the profiles being measured.

The effect of such constraints on the optimal choice and number of viewing angles would be a critical factor in the design of an absorption diagnostics device for combustion applications. In medical tomography, such devices as fan-shaped beams (see Fig. 4) are an important practical improvement over the basic parallel-beam concept for both standpoints of access and rapid








Fig. 4. Fan-Shaped Beams in absorption (ACTA-scanner).

completion.

Finally, the availability of instantaneous 3-D measurements would be a major improvement on current scanning techniques in such applications as turbulent combustion, for instance. A cluster of simultaneously fired sources has been tested in heart tomography (Wood 1977). Also, and less expensively, a single laser source combined with beam-splitting mirrors was used successfully in interferometry (Matulka 1971). It should be investigated for accuracy and resolution in flame mapping.

The purpose of our work is to develop a technique suited to combustion diagnostics. The following section describes our results in exploring optimal algorithms and number of viewing angles. An experimental design is also proposed.


## DEVELOPMENT OF THE TECHNIQUE

The search for an optimal 3-D absorption device suitable to flames should emphasize the need for dependable measurements under conditions of limited access and short time response.


A reduction of the number of angles from which measurements are made is a first step towards overcoming access limitation problems. However, the accuracy obtained when many viewing angles are available (180 for instance) is compromised when such a reduction occurs. The theoretical part of this report will describe our search for an acceptable trade-off on the number of viewing angles.

To be able to investigate experimentally the evolution of a combustion process, time resolutions of the order of 20 KHz may be required. Therefore a source illuminating the flame should produce a set of absorption signals to be emitted and collected within 50 microsec. Such a device - assuming five viewing angles, for instance - could be constructed as shown on Fig. 5. The light source could be either a laser beam extended to encompass the full extent of the flame, or else a thin beam which could be made to scan the area of interest by means of a fast piezo electric raster system (60 MHz devices are available). In both cases, continuous recording is possible. The design and construction of this device is being considered by the National Bureau of Standards' Thermal Processes Division, in conjunction with this study.

The determination of the optimum number of viewing angles is the goal of our current theoretical effort. The convolution algorithm was chosen as the primary means to analyze the reconstruction of a variety of symmetric and non-symmetric, continuous and discontinuous functions. This algorithm, which is representative of the class of Fourier based reconstruction techniques,



LIGHT SOURCE



BEAM SPLITTERS B

MIRRORS M

SENSOR ARRAYS S

Figure 5 - Instantaneous Multiangular Scanning (5 x 100).



has the advantages of speed of implementation and of being analytically tractable. A comparison is made between the Fourier based algorithms and the iterative algebraic reconstruction techniques. Test functions composed of three dimensional Gaussian fields (Fig. 6) represent the anticipated distribution in an unconstrained combustion process. Constrained combustion processes are approximated by a summation of cylindrical and Gaussian functions.

A rough qualitative evaluation of Gaussian functions can be obtained with as few as three equally spaced functions. To ascertain an accurate reproduction of these functions (error in the order of 1%), ten equally spaced projections are sufficient. If a reconstruction error in the order of 10% (particularly in the periphery of the spatial domain) can be tolerated, as few as six projections are sufficient (Figs. 6,7,8,9). It can be seen that most errors occur at the edge of the flame, where it is easy to substitute our a-priori physical knowledge of field (uniform). Such filtering is common practice in image reconstruction and it is hoped that it will reduce the rms error shown on Fig. 10 to the point where good accuracy will be obtained for five viewing angles only.

As would be expected, functions which have discontinuities are much more difficult to reconstruct, although proper filtering has a large effect on the accuracy of the reproduction. Small amplitude Gaussian distributions easily become obscured by the ringing caused by these discontinuities (Figs. 11 and 12). To be able to limit the number of projections necessary for a reasonably accurate reconstruction, significant preprocessing of the data shall be required.


## CONCLUSION

Therefore, in terms of practical flame applications, there seem to be two areas of useful absorption diagnostics. One is for three-dimensional real time measurements of low concentrations from a laser-beam splitters-sensors combination, operating from a few viewing angles. This will be satisfactory provided the profiles are relatively smooth (e.g. a set of Gaussians (Fig. 6), or at least representable by a model depending on a few parameters only). Many flames correspond to this description.

The other is for three-dimensional measurements of arbitrarily complicated and discontinuous maps of low concentrations. Such applications require many viewing angles (Fig. 11). If such open access is available (e.g. in X-Ray applications), extremely fine resolution is expected, as has been demonstrated in medical and material testing tomography. It does require, however, expensive multiple sources or, (more cheaply), the time-averaging of sequential measurements. Solid propellants, fluidized beds, etc... could be investigated in that fashion.




SUMMATION OF GAUSSIAN DISTRIBUTIONS



TRUE FUNCTION

Figure 6


SUMMATION OF GAUSSIAN DISTRIBUTIONS



20 SCANS

Figure 7


SUMMATION OF GAUSSIAN DISTRIBUTIONS



10 SCANS

Figure 8


SUMMATION OF GAUSSIAN DISTRIBUTIONS



6 SCANS


Figure 9





1.000  
0.500  
0.000

Figure 10




TRUE FUNCTION

Figure 11



SUMMATION OF GAUSSIAN AND CYLINDRICAL DISTRIBUTIONS



20 SCANS FILTERED

Figure 12

#### LIST OF REFERENCES

- AGARD (1976) - "Applications of Non-Intrusive Instrumentation in Fluid Research" AGARD Conference Proceedings CP-193, May 1976.
- Baba N. and Murata K. (1977) - "Filtering for Image Reconstruction from Projections" Journal of the Optical Society of America, Vol. 67, No. 5, pp. 662-668, May 1977.
- Bailly R., Pealat M. and Taran, J.P. (1976) - "Raman Investigation of a Subsonic Jet" Optics Communications, 17, No. 1, pp. 68-73, April 1976.
- Baronovski A.P. and McDonald J.R. (1977) - "The Application of Saturation Spectroscopy to the Measurement of  $C_2$  Concentrations in Oxy-Acetylene Flames" Chemistry Division, Naval Research Laboratory, Washington, 1977.
- Bendat J.S. and Piersol A.G. (1971) - "Random Data: Analysis and Measurement Procedures" Wiley Interscience, New York.
- Blazowski W.S., Rosfjord T.S. and Roquemore W.M. (1976) - "Air Force Needs in Turbopropulsion Combustion" Eastern States Section of the Combustion Institute, November 1976.
- Brooks R.A. and di Chiro G. (1976) - "Principles of Computer Assisted Tomography (CAT) in Radiographic and Radioisotopic Imaging" Physics in Medicine and Biology, 21, No. 5, September, 1976.
- Chahine M.T. (1970) - "Inverse Problems in Radiative Transfer: Determination of Atmospheric Parameters" Journal of Atmospheric Sciences, Vol. 27, No. 6, pp. 960-967, September, 1970.
- Chao C.M. and Goulard R. (1974) - "Nonlinear Inversion Techniques in Flame Temperature Measurements" from Heat Transfer in Flames, Afgan and Beer, Editors, Scripta Book Co., Washington, D.C., pp. 295-337.
- Chen F.P. and Goulard R. (1976) - "Retrieval of Arbitrary Concentration and Temperature Fields by Multiangular Scanning Techniques" JQSRT, 16, pp. 819-827, October 1976.
- Coleman H.W. et al (1977) - "Interim Report: Diagnostics Assessment for Advanced Power Systems" Sandia Laboratory Energy Report SAND 77-8216, March 1977.
- Daily J.W. (1977) - "Saturation Effects in Laser Induced Fluorescence Spectroscopy" Applied Optics, 16, pp. 568-571, March 1977.
- Druet S. (1976) - "Resonant Coherent Anti-Stokes Scattering in Gases" 5th International Conference on Raman Spectroscopy, Freiburg, DFR, September, 1976.

Eckbreth A.C. (1977) - "Review of Laser Raman and Fluorescence Techniques for Practical Combustion Diagnostics" United Technologies Research Center, Rept. UTRC R77-952665-6, May, 1977.

Gordon R., Herman G.T. and Johnson S.A. (1975) - "Image Reconstruction from Projections" Scientific American, pp. 56-68, October, 1975.

Goulard R. (1976) ed. - "Combustion Measurements" Academic Press.

Goulard R. (1977a) in "Proceedings of the Interactive Workshop on Inversion Methods in Atmospheric Soundings" (A. Deepak ed.), Williamsburg, VA, December, 1976, to appear.

Goulard R. (1977b) - "A Report on Recent Advances in Combustion Optical Diagnostics" March 1977 (unpublished).

Hartley D.L. (1974) - "Raman Gas Mixing Measurements and Ramanography", from "Laser Raman Gas Diagnostics" (Lapp and Penney, eds.), pp. 311-313.

Jeffries, J.T. (1968) - "Spectral Line Formation" Blaisdell Publishing Co., 1968.

Klug, E.P. and Slusher, G.R. (1974) - "Exhaust Emission Probe Investigation of a Mixed Flow Turbofan Engine" Society of Automotive Engineers, Paper No. 74-636.

Lapp M. and Penney C.M., eds., (1974) - "Laser Raman Gas Diagnostics", Plenum Press, New York, 1974.

Ledley R.S., Di Chiro G., Luessenhop A.J., Twigg H.L. (1974) - "Computerized Transaxial X-Ray Tomography of the Human Body" Science, 186, pp. 207-212.

Ledley R.S. (1976) - "Introduction to Computer Assisted Tomography" Comp. Biol. Medic. 6, pp. 239-246.

Lynch, Jr., R.T., Kramer S.D., Lotem H. and Bloembergen N. (1976) - "Double Resonance Interference in Third Order Light Mixing" Optics Communications, 16, No. 3, pp. 372-375, March 1976.

Marble F.E. and Broadwell J.E. (1977) - "The Coherent Flame Model for Turbulent Chemical Reactions" Project Squid Report TRW-9-PU, January, 1977. (See also: Spalding's AIAA Paper 77-141).

Matulka R.D. and Collins D.J. (1971) - "Determination of Three Dimensional Density Fields from Holographic Interferograms" Journal of Applied Physics, Vol. 12, pp. 1109-1119.

Minerbo, G.N. and Sanderson J.G. (1977) - "Reconstruction of a Source from a few (2 or 3) projections," Los Alamos Scientific Laboratory, LA-6747-MS, March 1977.

Patel C.K.N. (1978) - "Laser Detection of Pollution" Science, 202, pp. 157-173, 13 Oct. 1978.

Ramachandran G.N. and Lakshminarayanan A.V. (1971) - "Three Dimensional Reconstruction for Radiographs and Electron Micrographs: Application of Convolutions Instead of Fourier Transforms" Proceedings of the National Academy of Sciences, 68, pp. 2236-2240.

Setchell R.E. (1976) - "Time-Averaged Measurements in Turbulent Flames Using Raman Spectroscopy" AIAA Paper 76-28, January 1976.

Song J.J., Easley G.L. and Levenson M.D. (1976) - "Background Suppression in Coherent Raman Spectroscopy", Applied Physics Letters, 29, No. 9, pp. 567-569, November 1976.

Spalding D.B. (1975) - "Turbulence Modeling: Solved and Unsolved Problems" pp. 85-130, from "Turbulent Mixing and Non Reactive Flows" Murthy S.N.B., ed., Plenum Press, 1975.

Stuck B.W. (1977) - "A New Proposal for Estimating the Spatial Concentration of Certain Types of Air Pollutants" Journal of the Optical Society of America, Vol. 67, No. 5, pp. 668-678, May, 1977.

Sulzmann K.G.P., Lowder J.E.L. and Penner S.P. (1973) - "Estimates of Possible Detection Limits for Combustion Intermediates and Products with Line Center Absorption and Derivation Spectroscopy Using Tunable Laser," Comb. and Flame 20, pp. 177-191.

Thomson J.A.L. (1976) - "Design Concepts for Remote Atmospheric Sensing Systems" Internal Report, Physical Dynamics, Sept. 1976.

Wark D.Q. and Flemming H.E. (1966) - "Indirect Measurements of Atmospheric Temperature Profile from Satellites: 1. Introduction" Monthly Weather Review, Vol. 94, No. 6, June 1966.

Williams W.D., Power H.M., McGuire R.L., Jones J.H., Price L.L. and Lewis J.W.L. (1977) - "Laser Raman Diagnostics..." AIAA Paper 77-211, January 1977.

Williams W.D. and Lewis J.W.L. (1975) - "Rotational Temperature and Number Density Measurements of  $N_2$ ,  $O_2$ , CO and  $CO_2$ , in Hypersonic Flow Fields, Using Laser Raman Spectroscopy, AEDC-TR-75-37, July 1975.

Wood E.H. et al (1977) - from "Proceedings of the 1975 Workshop on Reconstruction Tomography in Diagnostic Radiology and Nuclear Medicine (San Juan, Puerto Rico), University Park, Baltimore.

Yule A.J., Chigier N.A., Thomson D. (1977) - "Coherent Structures in Combustion" Symposium on Turbulent Shear Flows" Pennsylvania State University, April 1977.



18 19 REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM																					
1. REPORT NUMBER <b>AFOSR-TR-79-0056</b>		2. GOVT ACCESSION NO.																					
3. RECIPIENT'S CATALOG NUMBER		5. TYPE OF REPORT & PERIOD COVERED INTERIM 1 Sep 77 - 30 Aug 78																					
4. TITLE (and Subtitle) <b>MULTIANGULAR SCANNING ABSORPTION-EMISSION TECHNIQUES FOR THREE DIMENSIONAL COMBUSTION DIAGNOSTICS</b>		6. PERFORMING ORG. REPORT NUMBER																					
7. AUTHOR(s) <b>ROBERT COULARD</b>		8. CONTRACT OR GRANT NUMBER(s) <b>AFOSR-77-3439</b>																					
9. PERFORMING ORGANIZATION NAME AND ADDRESS GEORGE WASHINGTON UNIVERSITY SCHOOL OF ENGINEERING & APPLIED SCIENCE WASHINGTON, DC 20052		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS <b>2308A2</b> <b>61102F</b>																					
11. CONTROLLING OFFICE NAME AND ADDRESS AIR FORCE OFFICE OF SCIENTIFIC RESEARCH/NA BLDG 410 BOLLING AIR FORCE BASE, D C 20332		12. REPORT DATE <b>Dec 78</b>																					
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) <b>Annual technical rept. 1 Sep 77 - 30 Aug 78</b>		13. NUMBER OF PAGES <b>30</b>																					
		15. SECURITY CLASS. (of this report) UNCLASSIFIED																					
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE																					
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.																							
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)																							
18. SUPPLEMENTARY NOTES																							
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) <table border="0"> <tr> <td>ABSORPTION</td> <td>COMBUSTION</td> <td>SCANNING</td> <td>RECONSTRUCTION</td> </tr> <tr> <td>SPECTROSCOPY</td> <td>FLAMES</td> <td>X-RAY</td> <td>IMAGING</td> </tr> <tr> <td>POLLUTION</td> <td>LASERS</td> <td>ACCURACY</td> <td>SENSORS</td> </tr> <tr> <td>RADICALS</td> <td>ALGORITHM</td> <td>FILTERING</td> <td>TOMOGRAPHY</td> </tr> <tr> <td>TIME-CONTINUOUS</td> <td></td> <td></td> <td>THREE-DIMENSIONAL</td> </tr> </table>				ABSORPTION	COMBUSTION	SCANNING	RECONSTRUCTION	SPECTROSCOPY	FLAMES	X-RAY	IMAGING	POLLUTION	LASERS	ACCURACY	SENSORS	RADICALS	ALGORITHM	FILTERING	TOMOGRAPHY	TIME-CONTINUOUS			THREE-DIMENSIONAL
ABSORPTION	COMBUSTION	SCANNING	RECONSTRUCTION																				
SPECTROSCOPY	FLAMES	X-RAY	IMAGING																				
POLLUTION	LASERS	ACCURACY	SENSORS																				
RADICALS	ALGORITHM	FILTERING	TOMOGRAPHY																				
TIME-CONTINUOUS			THREE-DIMENSIONAL																				
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) <p>Absorption techniques are being applied to three-dimensional combustion diagnostics. By using multiangular scanning, the traditional 'onion-peeling' method can be extended from axisymmetrical flows to arbitrary distributions of radicals and pollutants in the flow. Since Scattering 'point' techniques are limited by their very small cross section, such an extension would be a step improvement in sensitivity, down to low radical concentrations. Convolution Fourier transforms and iterative algorithms have already been proven in X-Ray absorption tomography and interferometric application. They are currently tested and compared and</p>																							



radical concentration as they appear in flames or exhausts. The effect of the number of scans (viewing angle limitation), of the instrument noise are analyzed for parallel beams. The results show that a trade-off exists between accuracy and the number of viewing angles. A five-angle procedure gives 10% accuracy with a moderately filtered convolution algorithm. An experiment feasibility study shows that time-continuous three-dimensional maps of low concentrations (1 ppm) can be obtained up to 20 KHz.

UNCLASSIFIED