

AD-A066 166

FOREIGN TECHNOLOGY DIV WRIGHT-PATTERSON AFB OHIO
CHARACTERISTICS OF THE ELECTRO-OPTICAL EFFECT IN CUBIC CRYSTALS--ETC(U)
JUL 78 A A BEREXHNOY
FTD-ID(RS)T-1121-78

F/G 7/2

UNCLASSIFIED

NL


| OF |

AD
A066 166



END
DATE
FILMED

'5--79
DDC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

1

AD-A066166


FOREIGN TECHNOLOGY DIVISION



CHARACTERISTICS OF THE ELECTRO-OPTICAL EFFECT IN CUBIC
CRYSTALS OF LEAD MAGNONIOBATE AND ZINC SELENIDE AND
THEIR USE FOR THE CONTROL OF LASER EMISSION

By

A. A. Berexhnoy



Approved for public release;
distribution unlimited.

78 12 22 232

EDITED TRANSLATION

FTD-ID(RS)T-1121-78

17 July 1978

MICROFICHE NR: *FTD-78-C-000982*

CHARACTERISTICS OF THE ELECTRO-OPTICAL EFFECT
IN CUBIC CRYSTALS OF LEAD MAGNONIOPATE AND ZINC
SELENIDE AND THEIR USE FOR THE CONTROL OF LASER
EMISSION

By: A. A. Berexhnoy

English pages: 3

Source: Materialy II Resp. Kongress Molodykh
Uchenykh Po Fiziki Institut Fiziki
ANBSSR, Minsk, Vol 2, 1972, pp. 83-84

Country of Origin: USSR
Translated by: Robert D. Hill
Requester: FTD/TQTD
Approved for public release;
distribution unlimited.

ACCESSION for	
NTIS	White Section <input checked="" type="checkbox"/>
DDC	Buff Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION _____	
BY _____	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	Avail. and/or SPECIAL
A	

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:
TRANSLATION DIVISION
FOREIGN TECHNOLOGY DIVISION
WP-AFB, OHIO.

U. S. BOARD ON GEOGRAPHIC NAMES TRANSLITERATION SYSTEM

Block	Italic	Transliteration	Block	Italic	Transliteration
А а	А а	A, a	Р р	Р р	R, r
Б б	Б б	B, b	С с	С с	S, s
В в	В в	V, v	Т т	Т т	T, t
Г г	Г г	G, g	У у	У у	U, u
Д д	Д д	D, d	Ф ф	Ф ф	F, f
Е е	Е е	Ye, ye; E, e*	Х х	Х х	Kh, kh
Ж ж	Ж ж	Zh, zh	Ц ц	Ц ц	Ts, ts
З з	З з	Z, z	Ч ч	Ч ч	Ch, ch
И и	И и	I, i	Ш ш	Ш ш	Sh, sh
Й й	Й й	Y, y	Щ щ	Щ щ	Shch, shch
К к	К к	K, k	Ъ ъ	Ъ ъ	"
Л л	Л л	L, l	Ы ы	Ы ы	Y, y
М м	М м	M, m	Ь ь	Ь ь	'
Н н	Н н	N, n	Э э	Э э	E, e
О о	О о	O, o	Ю ю	Ю ю	Yu, yu
П п	П п	P, p	Я я	Я я	Ya, ya

*ye initially, after vowels, and after ъ, ь; e elsewhere.
When written as ë in Russian, transliterate as yë or ë.

RUSSIAN AND ENGLISH TRIGONOMETRIC FUNCTIONS

Russian	English	Russian	English	Russian	English
sin	sin	sh	sinh	arc sh	sinh ⁻¹
cos	cos	ch	cosh	arc ch	cosh ⁻¹
tg	tan	th	tanh	arc th	tanh ⁻¹
ctg	cot	cth	coth	arc cth	coth ⁻¹
sec	sec	sch	sech	arc sch	sech ⁻¹
cosec	csc	csch	csch	arc csch	csch ⁻¹

Russian English

rot curl
lg log

FIRST LINE OF TEXT

CHARACTERISTICS OF THE ELECTRO-OPTICAL EFFECT IN CUBIC CRYSTALS OF LEAD MAGNONIOBATE AND ZINC SELENIDE AND THEIR USE FOR THE CONTROL OF LASER EMISSION

A.A. Berexhnoy

The characteristics of the electro-optical effect (EOE) in crystals of lead magnoniobate $/PbMg_{1/2}Nb_{1/2}O_3/$ and zinc selenide $/ZnSe/$ are examined. Crystals of the lead magnoniobate belong to the cubic centrally symmetric class of symmetry $m\bar{3}m$, and crystals of zinc selenide, to the cubic noncentrally symmetric class $\bar{4}3m$. Observed in the first crystals is the quadratic EOE and in the second crystals, the linear EOE. The optical isotropy and considerable EOE make it possible to use them effectively for the control of laser emission. Crystals of lead magnoniobate are ferroelectric and have a diffused phase transition. The diffusion of the phase transition in these crystals determines the characteristics of their EOE properties. It is revealed that under the effect of the electrical field E , linearization of the EOE in crystals $PbMg_{1/2}Nb_{1/2}O_3$ occurs. When $E > E_0 = 4$ kV/cm, the crystals of lead magnoniobate behave as piezoelectrics, i.e., they possess piezoelectric resonance and linear EOE. When E is applied along $[001]$, it goes over into a tetragonal class of symmetry $4mm$, and when it is applied along $[011]$ it goes over to the rhombohedral class of symmetry $mm\bar{2}$. The characteristic of the EOE in crystals of lead magnoniobate is discussed from the viewpoint of concepts on the dispersion of the phase transition in

ferroelectric crystals.

The longitudinal EOE is examined. The combination of the EO [Electro-optical] coefficients, which determine the longitudinal effect at room temperature and $\lambda = 0.63 \mu\text{m}$, proved to be equal to $(R_2 - R_3 \cdot R_4) = 6.4 \cdot 10^{-13} \text{ cm/V}^2$. Such a large longitudinal quadratic effect is connected with the disruption of the oxygen octahedron owing to the dispersion of the phase transition. The magnitude of EO coefficients and half-wave voltages for crystals of lead magnoniobate at room temperature and $\lambda = 0.63 \mu\text{m}$ are given in the table:

$R_{ij} \cdot 10^{12} \text{ cm/V}^2$ 1)	$r_{ij} \cdot 10^8 \text{ cm/V}$ 2)	$V_{1/2} \text{ , kv}$ 3)
$R_2 = 1.40$	Для симметрии $6mm2$ 4) $r_{23} = 187,0$	Для поперечного эффекта 5) при $E < E_0$ $V_{1/2} = 3,2$
$R_3 = 0,09$	$r_{33} = 8,2$	при $E > E_0$ $V_{1/2} = (0,11 \frac{d}{l} + 3,4 \text{ d})$
$R_4 = 0,67$	Для симметрии $mm2$ 4) $r_{31} = 69,0$	Для продольного эффекта 5) при $E < E_0$ $V_{1/2} = 3,4 \text{ d/l}$
	$r_{32} = 3,8$	при $E > E_0$ $V_{1/2} = (0,32 + 4,9 \text{ d})$

KEY: 1) cm/V^2 ; 2) cm/V ; 3) kV ; 4) For symmetry; 5) For transverse effect; 6) when; 7) For longitudinal effect.

where R_{ij} is the quadratic EO coefficients, r_{ij} - linear EO coefficients, l - dimension of the crystal in the direction of the light propagation, d - dimension of the crystal in the direction of the application of the field.

Possibilities are discussed concerning the use of the EOE in lead magnoniobate crystals for the deflection and modulation of laser emission.

Characteristics of the EOE in crystals Pb_2Ni_2 are connected with a large photoeffect, which is observed in these crystals. The dependence of the EO parameters on the intensity of the light passing through the crystal is investigated. It is revealed that with an increase in the light intensity by two orders, the magnitude of $V_{1/2}$ is increased by almost one order. The time charac-

characteristics of the photoelectric parameters are studied. In conclusion, the possibilities of the practical use of the discovered effect are discussed.

FIRST LINE OF TITLE

5
4
3
2
1
0

5
4
3
2
1
0

STOP HERE

STOP HERE

DISTRIBUTION LIST

DISTRIBUTION DIRECT TO RECIPIENT

<u>ORGANIZATION</u>	<u>MICROFICHE</u>	<u>ORGANIZATION</u>	<u>MICROFICHE</u>
A205 DMATC	1	E053 AF/INAKA	1
A210 DMAAC	2	E017 AF/RDXTR-W	1
B344 DIA/RDS-3C	9	E403 AFSC/INA	1
C043 USAMIIA	1	E404 AEDC	1
C509 BALLISTIC RES LABS	1	E408 AFWL	1
C510 AIR MOBILITY R&D	1	E410 ADTC	1
LAB/FIO		E413 ESD	2
C513 PICATINNY ARSENAL	1	FTD	
C535 AVIATION SYS COMD	1	CCN	1
C591 FSTC	5	ASD/FTD/NICD	3
C619 MIA REDSTONE	1	NIA/PHS	1
D008 NISC	1	NICD	2
H300 USAICE (USAREUR)	1		
P005 ERDA	1		
P005 CIA/CRS/ADB/SD	1		
NAVORDSTA (50L)	1		
NASA/KSI	1		
AFIT/LD	1		