AD-	A066 58	B2 ARI BAS FEI	MY MOBI SELINE B 79 E MER	LITY EQ TESTS O J DOWG	UIPMEN F THE	T RESEA SEBRING C E BA	RCH AND CITI-V ILEY DOE	DEVELO	TRIC D	COMME ELIVERY C-77-A-	TC F/G TRUCK	13/6 (U)	,	/
	0F AD A066582		galetter		Ē							THE FUEL		
a statistical and a statistica								Mar Jan						
														1
							ALL STREET		Harris Mar			12-11 12-11		
		e dikis Kuchata L <mark>ektanataolek</mark>	, alu ia, dit dit ju , alu ia, dit dit ju , alu ia, dit dit ju ia	aban nan Kula abatan nan Kula	dilbhaadsh hasibaksad	विषय्वत्र स्थित् । विषय्वत्र स्थित् ।	initiation of the second se	เลี้ยงส่วนของส่ว เสียงสายสล้า	all the set		END DATE FILMED 5-79 DDC			-
	.7													
								÷.					.,	1



LEVEL 12 AD AD AO 66582 Report 2268 **BASELINE TESTS OF THE SEBRING CITI-VAN** ELECTRIC DELIVERY TRUCK NAR 30 1979 MAR 30 1979 MAR C by A05692 Edward J. Dowgiallo, Jr. Cornelius E. Bailey, Jr. DDC FILE COPY Ivan R. Snellings and William H. Blake February 1979 Approved for public release; distribution unlimited. **U.S. ARMY MOBILITY EQUIPMENT RESEARCH AND DEVELOPMENT COMMAND** FORT BELVOIR, VIRGINIA 79 03 29 065

Destroy this report when it is no longer needed. Do not return it to the originator.

The citation in this report of trade names of commercially available products does not constitute official endorsement or approval of the use of such products.

This report was prepared to document work sponsored by the United States Government. Neither the United States nor its agent, the United States Department of Energy, nor any Federal employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights.

UNCLASSIFIED CURITY CLASSIFICATION OF THIS PAGE (When Date Entered) READ INSTRUCTIONS BEFORE COMPLETING FORM Dr. REPORT DOCUMENTATION PAGE ON MBER 2. GOVT ACCESSION NO. 3. RECIPIENT'S CATALOG NUMBER REPORT NU 2268 ERIOD COVERED BASELINE TESTS OF THE SEBRING CITI-VAN Test Reper **ELECTRIC DELIVERY TRUCK** • ER ERFOR MINGOR CONS/Ø421-4 NUMBER(.) Edward J Dowgiallo, Jr.; Cornelius E. Bailey, Jr. Interagency Agreement Ivan R./Snellings William H./Blake EC-77-A-31-1942 PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS PERFORMING ORGANIZATION NAME AND ADDRESS Electro Chem Div, Elec Pwr Lab US Army Mobility Equipment Research and Development Command, Fort Belvoir, VA 22060 11. CONTROLLING OFFICE NAME AND ADDRESS y 1079 US Army Mobility Equipment Research and Development Febr Command, ATTN: DRDME-EC NUMBER OF PAGE Fort Belvoir, VA 22060 66 4. MONITORING AGENCY NAME & ADDRESS(II different from Controlling Office) 15. SECURITY CLASS. (of this report) Prepared for Dept of Energy; Elec & Hybrid Highway Unclassified Vehicle Systems Program Div of Transportation Energy 15. DECLASSIFICATION DOWNGRADING SCHEDULE Conservation 16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited. 4 17. DISTRIBUTION STATEMENT (of the abetract entered in Block 20, 11 different from Report) 18. SUPPLEMENTARY NOTES 19. KEY WORDS (Continue on reverse side if necessary and identify by block number) **Electric Vehicle Traction Battery** RACT (Continue on provide of the fit necessary and identify by block number) The Citi-Van Model 611N0003, an electric two-passenger multipurpose van, was tested at the US Army Aberdeen Proving Ground test facilities in Aberdeen, Maryland, as part of a Department of Energy (DOE) project to characterize the state-of-the-art of electric vehicles. The Citi-Van is manufactured in Sebring, Florida, by Sebring Vanguard, Inc. It is powered by eight 6-volt batteries that are connected to the motor through a contactor control actuated by a foot pedal to control motor speed. The 6-horsepower motor drives the rear wheels through a direct drive to the differential. No regenerative braking was provided. DD , FORM 1473 EDITION OF I NOV 65 IS OBSOLETE UNCLASSIFIED 403160 79 SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered) 03 29 06

## PREFACE

The Electric and Hybrid Vehicle Program was conducted under the guidance of the (then) Energy Research and Development Administration (ERDA), now part of the Department of Energy (DOE).

The assistance and cooperation of US Postal Service is greatly appreciated. The Department of Energy provided funding support and guidance during this project.

NTIS DOC UNANMOUNCED JUSTI-ICATION	White Section C Buff Section C
BY Distingtion/Ava	ABILITY CODES
0	SPECIAL

iii

# CONTENTS

Section	Title	Page
	PREFACE	iii
	ILLUSTRATIONS	vi
	TABLES	viii
1	SUMMARY	1
11	INTRODUCTION	1
ш	OBJECTIVES	3
IV	TEST VEHICLE	
	1. Description	3
	2. Operating Characteristics	3
v	INSTRUMENTATION	3
VI	TEST PROCEDURES	
	1. Range Test at Constant Speed	8
	2. Range Test Under Driving Schedules	8
	3. Acceleration and Coast-Down Tests	8
VII	TEST RESULTS	
	1. Maximum Speed	11
	2. Maximum Acceleration	11
	3. Gradeability	15
	4. Road Energy Consumption	15
	5. Road Power Requirements	22
	6. Indicated Energy Consumption	28
VIII	COMPONENT PERFORMANCE AND EFFICIENCY	
	1. Battery Characteristics	28
	a. Manufacturer's Data	28
	b. Battery Acceptance	28

And the second second second

# CONTENTS (CONT'D)

Section		Title	Page
	2.	Constant Vehicle Speed Battery Performance	30
	3.	Battery Performance - Maximum Acceleration	30
	4.	Battery Performance – Driving Cycle	30
	5.	General Battery Performance	30
	6.	Braking Tests	30
	7.	Driver Reaction	30
	AP	PENDICES	
	A.	VEHICLE SUMMARY DATA SHEET	39
	B.	DESCRIPTION OF VEHICLE TEST TRACK	42
	C.	VEHICLE PREPARATION AND TEST PROCEDURES	46

v

tion and contraction of the second

# ILLUSTRATIONS

Figure	Title	Page
ı	Partial Side and Front View of the Sebring Citi-Van	5
2	Schematic Diagram of Vehicle Electric Propulsion System Showing Instrumentation Monitors	7
3A	Speed as a Function of Time (English Units)	9
3B	Speed as a Function of Time (Metric Units)	10
4A	Speed as a Function of Time During Acceleration (English Units)	12
4B	Speed as a Function of Time During Acceleration (Metric Units)	13
5A	Acceleration as a Function of Speed (English Units)	16
5B	Acceleration as a Function of Speed (Metric Units)	17
6A	Gradeability as a Function of Speed (English Units)	19
6B	Gradeability as a Function of Speed (Metric Units)	20
7A	Road Energy as a Function of Speed (English Units)	23
7B	Road Energy as a Function of Speed (Metric Units)	24
7C	Road Energy as a Function of Speed (Metric Units)	25
8A	Road Power as a Function of Speed (English Units)	26
8B	Road Power as a Function of Speed (Metric Units)	27
9	Battery Voltage as a Function of Capacity Removed	29
10A	Constant Speed Battery Performance (First 25% of Range)	31
10B	Constant Speed Battery Performance (Last 25% of Range)	31

1

vi

# ILLUSTRATIONS (CONT'D)

Figure	Title	Page
11A	Average Battery Current	34
11B	Average Battery Voltage	35
11C	Average Battery Power	36
11D	Speed as a Function of Time	37
BI	Plan View of Slopes	42
B2	Eight of the Standard Gradeability Slopes	43
B3	Aerial View of Mile Loop	43
B4	Dynamometer Course	44
B5	Aerial View of Perryman Test Area	45

ADDRESS AND A DESCRIPTION OF A DESCRIPTI

# TABLES

able	Title	Page
1	Summary of Test Results for Citi-Van	2
2	Parameters, Symbols, Units, and Unit Abbreviations	4
3	Speed Versus Time During Coasting	11
4	Acceleration Test Results at Three States of Charge	14
5	Acceleration Characteristics	18
6	Gradeability at Speed as a Function of Battery State of Charge	21
7	Road Energy Consumption	22
8	Road Power Requirements	28
9	Constant Speed Battery Data	32
10	Battery Performance – Maximum Acceleration	33
11	Driving Cycle Performance	38

A STATE OF THE STA

# BASELINE TESTS OF THE SEBRING CITI-VAN ELECTRIC DELIVERY TRUCK

#### I. SUMMARY

The Citi-Van, a multipurpose electric vehicle manufactured in Sebring, Florida, by Sebring-Vanguard, Inc., was tested at the US Army Aberdeen Proving Ground test facilities in Aberdeen, Maryland, between 14 June and 13 July 1977. The tests are part of a Department of Energy (DOE) project to characterize the state-of-the-art of electric vehicles. This report presents the performance of the Sebring Citi-Van.

The Sebring Citi-Van is a two-passenger delivery truck with a cycolac plastic body and powered by eight 6-volt batteries. The batteries are connected to a motor through a contactor controller actuated by a foot pedal to control motor speed. The 6-horsepower motor drives the rear wheels through a direct drive to the differential. No regenerative braking was provided on this vehicle.

All tests were run at the gross vehicle weight of 884 kilograms (1949 lbm). The Citi-Van accelerated from 0 to 48.3 kilometers per hour (0 to 30 mi/h) in 21.5 seconds.

The results of the tests are summarized in Table 1.

#### II. INTRODUCTION

The vehicle tests and the data presented in this report are in support of Public Law 94-413 enacted by Congress on 17 September 1976. The Law requires the Energy Research and Development Administration (ERDA), now DOE, to develop data characterizing the state-of-the-art of electric and hybrid vehicles. The data so developed are to serve as a baseline (1) to compare improvements in electric and hybrid vehicle technologies, (2) to assist in establishing performance standards for electric and hybrid vehicles, and (3) to help guide future research and development activities.

The US Army Mobility Equipment Research and Development Command (MERADCOM) under the direction of the Electric and Hybrid Research Development and Demonstration Office of the Division of Transportation Energy Conservation of DOE has conducted track tests of electric vehicles to measure their performance characteristics and vehicle component efficiencies. Table 1. Summary of Test Results for Citi-Van

			(a) SI Units				
	Test Condition					Energy	Indicated
	(Constant Speed)	Wind			Number	into	Energy
	(km/h); or Driving	Velocity	Temperature	Range	of	Charger	Consumption
Test Date	Schedule	(km/h)	(°C)	(km)	Cycles	(M))	(MJ/km)
29 Jun 77	48.0	17.7	28.9	43.9	1	55.8	1.27
30 Jun 77	48.0	12.9	26.7	46.0	1	55.8	1.21
1 Jul 77	40.0	8.0	26.4	56.8	1	57.6	1.01
5 Jul 77	40.0	6.4	29.4	55.2	1	55.8	1.01
12 Jul 77	В	0	25.6	42.2	120	61.2	1.45
13 Jul 77	В	6.4	22.2	47.0	130	59.4	1.26
Acceleration 0 to 30 km/h (20 mi/h 0 to 48 km/h (30 mi/h	) in 7 seconds ) in 22 seconds						
		(q)	US Customary	Units			
	Test Condition					Energy	Indicated
	(Constant Speed)	Wind			Number	into	Energy
	(mi/h); or Driving	Velocity	Temperature	Range	of	Charger	Consumption
Test Date	Schedule	(mi/h)	(°F)	(mi)	Cycles	(kWh)	(kWh/mi)
29 Jun 77	30	11	84	27.3	1	15.5	0.57
30 Jun 77	30	8	80	28.6	1	15.5	0.54
1 Jul 77	25	5	79.5	35.3	I	16	0.45
5 Jul 77	25	4	85	34.3	1	15.5	0.45
12 Jul 77	В	0	78	26.2	120	17	0.65
13 Jul 77	В	4	72	29.2	130	16.5	0.57

The tests were conducted according to DOE Electric and Hybrid Vehicle Test and Evaluation Procedures, described in Appendix A of MERADCOM Report 2244.<sup>1</sup>

US customary units were used in the collection and reduction of data. The units were converted to the International System of Units (Systeme International, SI) for presentation in this report. US customary units are presented in parentheses. The parameters, symbols, units, and unit abbreviations used in this report are given in Table 2 for the convenience of the reader.

#### III. OBJECTIVES

The characteristics of interest for the Citi-Van are vehicle speed, range at constant speed, range over stop-and-go driving schedules, maximum acceleration, gradeability, road energy consumption, road power, indicated energy consumption, and battery characteristics.

#### IV. TEST VEHICLE

1. Description. The Citi-Van, an electric delivery truck, Model 611N0003, is a minivan in the 200-pound payload class. The compact vehicle has bench-type seating in front for a driver and one passenger. The body is composed of an all-aluminum frame and an ABS cycolac plastic shell. The vehicle is powered by eight 6-volt batteries that are located under the bench-type seat. The batteries are connected to the series motor through a contactor controller actuated from a foot pedal. The motor is connected directly to the differential. The battery, contactor controller, and 4.5-killowatt d.c. motor are connected in series. The vehicle is shown in Figure 1 and described in detail in Appendix A. A single-phase, 115-volt on-board battery charger is used to charge the traction batteries. No regenerative braking was provided on this vehicle.

2. Operating Characteristics. A key switch is used to close the main switch which enables the contactor controller, which is actuated by a foot throttle, to change the voltage applied to the 4.5-kw motor.

#### V. INSTRUMENTATION

The Citi-Van was instrumented to measure vehicle speed and range, battery voltage, current, instantaneous power, and averaged power. The battery charger input in a.c. kilowatt-hours and output in d.c. amperes were also measured. Battery

<sup>1</sup> E. J. Dowgiallo, Jr.; C. E. Bailey, Jr.; I. R. Snellings; and W. H. Blake; "Baseline Tests of the EVA Metro Electric Passenger Vehicle," MERADCOM Report 2244 (July 1978).

ilen.		SI Ur	nits	U.S. Custor	nary Units
Parameter	Symbol	Unit	Abbreviation	Unit	Abbreviation
Acceleration	a	meter per second squared	m/s²	mile per hour per second	mi/h/s
Area	-	square meter	m²	square foot; square inch	ft <sup>2</sup> ; in. <sup>2</sup>
Energy	-	megajoule	MJ	kilowatt hour	kWh
Energy Consumption	Е	megajoule per kilometer	MJ/km	kilowatt hour per mile	kWh/mi
Energy Economy	-	megajoule per kilometer	MJ/km	kilowatt hour per mile	kWh/mi
Force	F	newton	N	pound force	lbf
Integrated current	-	ampere hour	Ah	ampere hour	Ah
Length	-	meter	m	inch; foot; mile	in.; ft; mi
Mass; weight	w	kilogram	kg	pound mass	lbm
Power	Р	kilowatt	kW	horsepower	hp
Pressure	-	kilopascal	kPa	pound force per square inch	lbf/in²
Range	-	kilometer	km	mile	mi
Specific energy	- 1 - 1 1-2 - 1 - 1	megajoule per kilogram	MJ/kg	watt hour per pound mass	Wh/lbm
Specific power	-	kilowatt per kilogram	kW/kg	kilowatt per pound mass	kW/lbm
Speed	v	kilometer per hour	km/h	mile per hour	mi/h
Volume	-	cubic meter	m <sup>3</sup>	cubic inch; cubic foot	in. <sup>3</sup> ; ft <sup>3</sup>

Table 2. Parameters, Symbols, Units, and Unit Abbreviations



Figure 1. Partial Side and Front View of the Sebring Citi-Van.

electrolyte temperatures were measured with thermometers. A brief description of the instrumentation system is given below. Details on the recorder are given in Appendix B of MERADCOM Report 2244.<sup>2</sup>

Instrumentation consisted of signal conditioning circuits and a magnetic tape recorder for recording analog signals of electrical parameters. The magnetic tape recorder was operated in the frequency modulation mode at 4.763 cm (1.875 inches) per second. The signal conditioning circuitry to the recorder consisted of a main battery voltage divider, a shunt-voltage amplifier for current monitor, an analog multiplier, and averager circuits for averaging power and current since the recorder response was less than 0.3 db down at 500 Hertz. A voltage proportional to battery power was produced by the instantaneous multiplication of voltages proportional to battery voltage and current. Voltages proportional to current and power were recorded both raw and electronically averaged. The raw values include the rapid switching transients associated with the solid state controller. An estimation of the overall d.c. measurement error is less than  $\pm 1.8\%$  for power. This includes digitization from the field recorded analog magnetic tape to a computer compatible digitized magnetic tape. The measurement error of the various conditioning circuits can be broken down as follows: current shunt ( $\pm 0.25\%$ ), current amplifier ( $\pm 1\%$ ), multiplier ( $\pm 0.25\%$ ), and magnetic tape recorder  $(\pm 1\%)$ . In addition to these errors, phase deterioration starts to be significant above 3 kilohertz when the multiplier is combined with an averager (± 1%); and, finally, the analog-to-digital converter at 16 bits and 100 conversions per second did not introduce any significant error.

A schematic diagram of the electric propulsion system with the instrumentation sensors is shown in Figure 2. A Laboratory Equipment Corporation, Tracktest Fifth Wheel with the Model DD1.1, Electronics Digital Speed Meter and the Model DD2.1, Electronic Digital Distance Meter were used during the track tests. A tachometer generator was connected to the fifth wheel to record velocity and calculate distance traveled. The fifth wheel and auxiliaries weighed about 18.6 kilograms (41 lb). The fifth wheel was calibrated by rotating the wheel on a constant-speed fifth-wheel calibrator drum mounted on the shaft of a synchronous AC motor. The accuracies of the velocity readings were within  $\pm \frac{1}{2}$ % of reading. Velocity was recorded on a Lockheed Store 7 Magnetic Tape Recorder.

Battery electrolyte temperatures and specific gravities were measured manually before and after the tests.

Power for the fifth wheel instruments was provided by a vehicle auxiliary 12-volt SLI battery. The power for the magnetic tape recorder and signal conditioning instrument package was supplied from a battery pack.

<sup>&</sup>lt;sup>2</sup> E. J. Dowgiałło, Jr.; C. E. Bailey, Jr.; I. R. Snellings; and W. H. Blake; "Baseline Tests of the EVA Metro Electric Passenger Vehicle," MERADCOM Report 2244 (July 1978).



All instruments were calibrated periodically with checks before each test.

The current into the battery and the energy into the battery charger were measured while the battery was recharged after each test. The current to the battery was recorded on a Hewlett Packard 7100 B Strip Chart Recorder. The current measurement used a 100 amperes-100 milivolts current shunt. The energy delivered to the charger was measured with a Sangamo Electric Type J4S 30TA Single-Phase Residential Watt-Hour Meter.

#### VI. TEST PROCEDURES

The tests decribed in this report were performed at three different test locations at the Aberbeen Proving Ground (APG) test facilities. A complete description of the track is given in Appendix B. When the vehicle was delivered to MERADCOM, the pretest checks described in Appendix C were conducted. Then the vehicle was shipped to Aberdeen Proving Ground and the checks described in Appendix C were performed before the first test run. There was a shakedown run to familiarize the driver with the operating characteristics of the vehicle and to verify proper operation of all instrumentation systems. All tests were run in accordance with the DOE Electric and Hybrid Vehicle Test and Evaluation Procedure, Appendix A of MERADCOM Report 2244.<sup>3</sup>

1. Range Test at Constant Speed. Range tests at constant speed were carried out at 40 km/h (25 mi/h) and 48 km/h (30 mi/h); speeds were held constant within  $\pm$  1.6 km/h (1 mi/h) and the test was terminated when the vehicle could no longer maintain 95% of the designated test speed. The range tests were run two times at 40 km/h and two times at 48.0 km/h.

2. Range Tests Under Driving Schedules. The 32.2 kilometer-per-hour (20 mi/h), schedule B, was run two times with this vehicle. Complete descriptions of the cycle test procedures are given in Appendix A of MERADCOM Report 2244.<sup>4</sup>

3. Acceleration and Coast-Down Tests. The acceleration coast-down tests were performed continuously until the battery was discharged. The vehicle was operated in this manner two times. Data were recorded on an analog magnetic tape recorder and, later, digitized and calculations were performed on a computer. Data were tabulated for three states of charge. These tests were conducted on the Dynamometer Course at APG (see Appendix B for description of the course). Coast-down data were taken following each maximum acceleration run with the transmission in neutral. The speed versus time relationships are shown in Figures 3A and 3B and Table 3.

<sup>&</sup>lt;sup>3</sup> E. J. Dowgiałło, Jr.; C. E. Bailey, Jr.; I. R. Snellings; and W. H. Blake; "Baseline Tests of the EVA Metro Electric Passenger Vehicle," MERADCOM Report 2244 (July 1978).

<sup>4</sup> Ibid.





Time	Vehicle	Speed	
<u>(s)</u>	<u>(</u> km/h)	(mi/h)	
0	52.6	32.7	
9.6	41.6	25.8	
21.6	30.6	19.0	
33.6	21.2	13.2	
42.6	15.2	9.4	
51.6	10.1	6.3	
57.6	6.6	4.1	

#### VII. TEST RESULTS

The data collected from all the range tests are summarized in Table 1. Shown in the table are the test data, type of test, environmental conditions, the range test results, the temperature of the battery, and the energy into the charger. These data are used to determine vehicle range and energy economy.

1. Maximum Speed. The maximum speed of the vehicle was measured during the acceleration tests. The measured maximum speed was 52.5 km/h (32.6 mi/h) for this vehicle.

2. Maximum Acceleration. The maximum acceleration of the vehicle was measured with the batteries fully charged, 40% discharged, and 80% discharged. The results of the tests are shown in the curves of Figures 4A and 4B and are tabulated in Table 4. The average acceleration,  $\overline{a}_n$ , was calculated for the time period  $t_{n-1}$  to  $t_n$  where the vehicle speed increased from  $V_{n-1}$  to  $V_n$  from the equation:

$$a_n = \frac{V_n - V_{n-1}}{t_n - t_{n-1}}$$

and the average speed of the vehicle,  $\overline{V}$ , was calculated from the equation:

$$\overline{\mathbf{V}} = \frac{\mathbf{V}_{n} + \mathbf{V}_{n-1}}{2}$$



Figure 4A. Speed as a Function of Time During Acceleration (English Units).



-

	Table	4. Acceleration	Test Results at	Three States of	Charge	
			Vehicle	Speed		
Time	0% Dis	charge	40% Dis	scharge	80% Di	scharge
(s)	(km/h)	(mi/h)	(km/h)	(mi/h)	(km/h)	(mi/h)
0.6			1.6	1.0	3.6	2.2
1.2	6.4	4.0			5.8	3.6
1.8			3.5	2.2		
2.4	14.7	9.1	8.1	5.0	9.7	6.0
3.0	18.3	11.4	12.0	7.5	11.4	1.7
4.2	23.5	14.6			. 12.2	7.6
4.8			21.1	13.1		
5.4	28.4	17.6				
6.0	30.4	18.9	25.9	16.1	16.8	10.4
6.6	31.9	19.8				
6.7	32.2	20.0				
8.2			32.2	20.0		
8.4	36.1	22.4				
9.0	37.3	23.2	34.0	21.1	17.5	10.9
12.0	41.5	25.8	40.0	24.9	19.4	12.1
15.0	43.6	27.1	42.5	26.4	24.8	15.4
18.0	46.6	29.0	45.0	28.0	29.7	18.5
21.0	47.9	29.8	47.0	29.2	35.7	22.2
24.0	49.0	30.4	48.0	29.8		
27.0	50.3	31.3	49.0	30.4	41.6	25.8
30.0	50.6	31.4	49.4	30.7	43.5	27.0
39.0	51.9	32.3	50.8	31.6	46.7	29.0
45.0	52.1	32.4	51.3	31.9	47.8	29.7
54.0	52.6	32.7	51.6	32.1	48.1	29.9
60.0	575	376	1 63	27.4	40.0	30.4

Average acceleration as a function of speed is shown in Figures 5A and 5B and Table 5. These tests were run consecutively and the percent of discharge was determined by computer calculation. Discharging the battery by continuous start-stop vehicle operation rather than allowing a cool-off period while the battery was discharged to each state of charge was considered more realistic.

3. Gradeability. The maximum vehicle speed on a specific grade is determined from maximum acceleration tests by using the equations:

Gradeability, G, at a speed  $\overline{V}$ , in km/h:

 $G = 100 \tan (\sin^{-1} 0.1026 \,\overline{a}_n) \%$ 

or in English units at a speed  $\overline{V}$  in mi/h:

 $G = 100 \tan(\sin^{-1} 0.0455 \,\overline{a_n}) \%$ 

where:

 $\overline{a}_n$  = acceleration in meters per second squared (mi/h/s).

The resulting maximum grade the Citi-Van can negotiate as a function of speed is shown in Figures 6A and 6B and Table 6.

4. Road Energy Consumption. Road energy is a measure of the energy consumed in overcoming the vehicle's aerodynamic and rolling resistance plus the energy consumed in the differential drive shaft and the portion of the transmission rotating when in neutral. Road energy is obtained during coast-down with the differential being driven only by the wheels.

The road energy consumed by the vehicle at various speeds and the losses in the differential were determined from coast-down tests. Road energy consumption  $(E_n)$  is calculated as megajoules per kilometer from the following equation:

$$E_n = 2.78 \times 10^{-4} W \frac{V_{n-1} - V_n}{t_n - t_{n-1}}, \frac{MJ}{km}$$

or in English units:

 $E_n = 9.07 \times 10^{-5} W \frac{V_{n-1} - V_n}{t_n - t_{n-1}}, \frac{kWh}{mi}$ 

VEHICLE PERFORMANCE OF SEBRING-VANGUARD CITIVAN

1

Contraction and Contraction





		I abi	e 5. Accelera	tion Characte	Instics			1
Vehicle	Speed	0% Dis	scharge	40% Di	scharge	80% Di	scharge	
km/h	mi/h	m/s <sup>2</sup>	ft/s <sup>2</sup>	m/s <sup>2</sup>	ft/s <sup>2</sup>	m/s <sup>2</sup>	ft/s <sup>2</sup>	
2	1.2			6.3	2.07	1.39	4.56	
4	2.5			1.17	3.84	0.97	3.18	
9	3.7	1.38	4.53	2.09	6.86	0.89	2.92	
80	5.0	1.65	5.41	1.99	6.53	0.82	2.69	
10	6.2	1.86	6.10	1.88	6.17	0.19	0.62	
12	7.5	1.87	6.14	1.73	5.68	0.35	1.15	
16	9.9	1.72	5.64	1.43	4.69	0.31	1.02	
20	12.4	1.31	4.30	1.25	4.10	0.48	1.57	
24	14.9	1.15	3.77	1.09	3.58	0.46	1.51	
28	17.4	1.04	3.41	0.86	2.82	0.52	1.71	
32	19.9	0.66	2.17	0.68	2.23	0.39	1.28	
36	22.4	0.59	1.94	0.59	1.94	0.24	0.79	
40	24.9	0.36	1.18	0.34	1.12	0.13	0.43	
44	27.3	0.23	0.75	0.22	0.72	0.03	0.10	
48	29.8	0.11	0.36	0.09	0.30	0	0	
48.9	30.4					0	0	
52	32.3	0.02	0.07	0	0	0	0	
52.1	32.4			0	0	0	0	
52.5	32.6	0	0	0	0	0	0	







ORCOM HE LWR OWEH

Charge	1	80% Discharge		26			14.3	6.6	0.6	8.4	2.0	3.6	3.1	4.9	4.6	5.3	4.0	2.4	1.3	3	0	
nction of Battery State of	ballery State of Unarge	40% Discharge	Gradeability Percent	26		6.5	12.0	21.8	20.6	19.5	17.9	14.7	12.8	11.2	8.8	6.9	6.1	3.4	2.2	0.9		0
leability at Speed as a Fu		0% Discharge		26				14.2	17.0	19.3	19.4	17.8	13.5	11.8	10.6	6.7	6.1	3.7	2.4	1.1		2
Table 6. Grade			Speed	mi/h		1.24	2.5	3.7	5.0	6.2	7.5	6.6	12.4	14.9	17.4	19.9	22.4	24.9	27.3	29.8	30.4	32.3
			Vehicle	km/h	0	2	4	9	90	10	12	16	20	24	28	32	36	40	44	48	48.9	52

where:

V = vehicle speed in kilometers per hour (mi/h).

t = time, sec.

The results for the road energy determination are shown in Figures 7A, B, and C and Table 7.

Vehicle	Speed		Road Energy	
km/h	mi/h	MJ/km	kWh/km	kWh/mi
47.14	29.3	0.29	0.08	0.13
36.04	22.4	0.23	0.063	0.10
25.90	16.1	0.20	0.056	0.09
18.18	11.3	0.16	0.045	0.075
12.71	7.9	0.14	0.039	0.061
8.36	5.2	0.14	0.039	0.060

5. Road Power Requirements. The road power is a measure of vehicle aerodynamic and rolling resistance plus the differential, drive shaft, and a portion of the transmission's power loss.

The road power,  $P_n$ , required to propel a vehicle at various speeds is also determined from the coast-down tests. The following equations are used:

$$P_n = 3.86 \times 10^{-5} W - \frac{V_{n-1}^2 - V_n^2}{t_n - t_{n-1}}, kW$$

or in English units

$$P_n = 6.08 \times 10^{-5} W - \frac{V_{n-1}^2 - V_n^2}{t_n - t_{n-1}}$$
, hp

The results of road power calculations are shown in Figures 8A and 8B and Table 8.



Contraction of the second









Vehicle	Speed	Road Powe	r Required	
km/h	mi/h	kW	hp	
47.14	29.3	3.68	5.0	
36.04	22.4	2.26	3.0	
25.90	16.1	1.38	1.85	
18.18	11.3	0.83	1.13	
12.71	7.9	0.49	0.64	
8.36	5.2	0.33	0.45	

Indicated Energy Consumption. The vehicle indicated energy consumption 6. is defined as the energy required to recharge the battery after a test divided by the vehicle range achieved during the test, where the energy is measured as the input to the battery charger.

The energy input to the battery charger was measured with a residential kilowatt-hour meter following each range test. Some overcharge of the batteries was usually required in order to assure that all cells of the battery were fully charged and the pack was equalized. The energy usage reported in Table 1 was based on field data acquired with a Sorensen Power Supply Model DCR-150-10A which was used because the charger supplied with the van was incapable of recharging the batteries overnight.

#### VIII. COMPONENT PERFORMANCE AND EFFICIENCY

#### 1. Battery Characteristics.

Manufacturer's Data. The batteries supplied with the Sebing Citi-Van a. were eight 6-volt lead-acid modules, rated 132 amp-hours at 75 amperes, from Gould Battery Co.

b. Battery Acceptance. Prior to initiation of road tests, the batteries supplied by the vehicle manufacturer were tested for battery capacity and terminal integrity as specified in Appendix A of MERADCOM Report 2244.<sup>5</sup> The capacity check was performed on the batteries using a thyristor-controlled discharge unit.<sup>6</sup> Since the measured capacity was 119 ampere-hours at a discharge rate of 75 amperes to 1.70 volts per ceil, more than 80% of the manufacturer's rated capacity, the battery was acceptable. As shown in Figure 9, the battery voltage at the initiation of discharge was 46.2 volts and decayed gradually to 40.8 volts at the end of the test.

<sup>5</sup> E. J. Dowgiallo, Jr.; C. E. Bailey, Jr.; I. R. Snellings; and W. H. Blake; "Baseline Tests of the EVA Metro Electric Passenger Vehicle," MERADCOM Report 2244 (July 1978).

E. J. Dowgiallo, Jr.; J. B. O'Sullivan; I. R. Snellings; and R. B. Anderson; "High Power Facility for Testing Electrochemical Power Sources," Princeton, New Jersey; Journal of the Electrochemical Society, Vol. 121, No. 9, Sep 74.



In lieu of the 5-minute terminal integrity test, all terminals and terminal connections were cleaned and inspected.

2. Constant Vehicle Speed Battery Performance. During the road tests, battery current was monitored constantly. Presented in Figures 10A and 10B and Table 9 are the battery characteristics during the 40 kilometers per hour (25 mi/h) and the 48 kilometers per hour (30 mi/h) range tests. The average battery current, voltage, and power during the first 25% of the vehicle's range are shown in Figure 10A. Similar battery performance data during the last 25% of the vehicle's range are shown in Figure 10B. Required battery power decreases during the test, probably due to the reduced power requirements as the temperature of the mechanical drive train components and associated lubricants increases and the tire rolling resistance decreases.

3. Battery Performance-Maximum Acceleration. Battery performance data at selected times during the maximum acceleration test for three depths of battery discharge are presented in Table 10.

**4. Battery Performance-Driving Cycle.** The battery current, voltage, and power and the vehicle speed for the third and next-to-last cycle of the SAE "B" (start/stop) schedules are shown in Figures 11A-D. The total number of start/stops, distance traveled and other data on the battery and drive cycles are given in Table 11.

5. General Battery Performance. The fully charged (temperature corrected) battery electrolyte specific gravities during the driving tests ranged from 1.250 to 1.270 and the fully discharged specific gravities from 1.110 to 1.115. The battery temperature had a tendency to increase from ambient at the start of the test to about  $7^{\circ}C$  (13°F) above ambient at the end of the test.

6. Braking Tests. Four braking tests were performed from a speed of 52.8 km/h (32.8 mi/h). The required stopping distance criterion of 17.4 m (57 ft) was complied with.

7. Driver Reaction. Performance was fair in general. The vehicle rode roughly compared to most electric vehicles. The foot brake is in a poor location and required use of the left foot which is not normal to the average driver. The steering is positive.







Figure 10B. Constant Speed Battery Performance (Last 25% of Range).

	313	
	BATTERV	( same
	Speed	
Constant	CONSTANT	
c	2.	
- Ho	AUIC	

		1			
) mi/h) Test	I act 750	111	44.2	4.91	W-h
48-km/h (30	First 25%	113	46.8	5.29	4.75 k
mi/h) Test	Last 25%	67.2	33.1	2.22	W-h
40-km/h (25	First 25%	83.5	37.1	3.09	3.69 k
	Parameter	$\overline{T}_{B}$ Average Battery Current (amps)	$\overline{V}_{B}$ Average Battery Voltage (volts)	P <sub>B</sub> Average Battery Power (kW)	Total Energy Removed from Battery

	Ta	able 10. Battel	ry Pertormance	- Maximum Acc	eleration	
Time	Speed	km/h	Current	Voltage	Power	Discharged
(3)	(mi/h)		(Amp)	(v)	(KW)	(%)
3	11.4	18.3	497	37.9	18.8	0
10	24.0	38.7	206	44.3	9.1	0
20	29.5	47.5	135	46.0	6.2	0
30	31.4	50.6	117	46.6	5.5	0
40	32.3	51.7	110	46.8	5.1	0
60	32.6	52.5	105	47.0	4.9	0
3	7.5	12.0	543	35.1	19.1	40
10	22.4	36.0	228	42.9	9.8	40
20	28.8	46.3	136	45.0	6.1	40
30	30.7	49.4	115	45.6	5.2	40
40	31.6	50.9	108	45.7	4.9	40
60	32.4	51.1	105	45.8	4.8	40
3	7.1	11.4	524	32.4	17.0	80
10	11.3	18.1	366	35.4	13.0	80
20	20.9	33.7	183	41.5	7.6	80
30	27.0	43.5	136	42.8	5.8	80
40	29.1	46.9	115	43.3	5.0	80
09	30.4	49.0	104	43.7	4.5	80



Service and Service



WHLOC ZH MODHLOC



COBMA HE AB



and the constant of the left o

Parameter	Schedule B
Total Start/Stop Cycles	125
Distance Traveled During Test	27.7 km/h (44.32 mi/h)
Test Period	2.55 h
Kilowatt-Hours Used During Test	6,052
Average Watt-Hours Used Per Cycle	48.40
Average Cycle Duration	73.4 s
Average Time Battery is Loaded Per Cycle	39.6 s
Percent of Power Used for Acceleration to Cruising Speed	68.0%

### **APPENDIX A**

# VEHICLE SUMMARY DATA SHEET

- 1. Vehicle Manufacturer: Sebring-Vanguard, Inc. Sebring, Florida 33871
- 2. Vehicle Description: Name: Citi-Van

Model: 611SN0003 Price: \$3,988.00

Passengers Wt: 84.44 kg (186 lb)

Payload Wt: 50.85 kg (112 lb)

Length: 2.74 m (108 in.)

Headroom: 0.91 m (36 in.)

3. Vehicle Weight: Curb Wt: 660.57 kg (1,455 lb) Driver Wt: 88.98 kg (196 lb) Gross Wt: 884.85 kg (1,949 lb)

4. Vehicle Size: Wheelbase: 1.93 m (76 in.) Width: 1.42 m (56 in.) Legroom: 0.56 m (22 in.)

5. Auxiliaries & Options: No. Lights: 16

- 2 Head Lamps a.
- b. 8 Parking Lamps
- c. **4 Signal Lamps**
- d. 1 Back-Up Lamp

e. 1 D

Yes	Windshield Washam	v
Yes	Heater.	Yes
No	Fuel C	Yes
No	Fuel Gage:	Yes
NO	lachometer:	Yes
res	Odometer:	Yes
One	Power Steering:	No
No		
rect Pinion D	rive	
	Yes Yes No No Yes One No irect Pinion Di	Yes Windshield Washers: Yes Heater: No Fuel Gage: No Tachometer: Yes Odometer: One Power Steering: No irect Pinion Drive

- 6. Propulsion Batteries: Type: Lead Acid No. of Modules: 8 No. Cells: 24 AH Capacity: 132.5 Battery Wt: 210.6 kg (464 lb) Battery Rate: 75 A
- Auxiliary Battery: Type: Power Breed No. Cells: 6 AH Capacity: 4 Battery Rate: 20 h

 Controller: Type: Multi-Voltage Resistive Relay Size: 400 mm x 160 mm x 190 mm (16 in. x 6.5 in. x 7.5 in.)

 Propulsion Motor: Type: Series Wound Insulation Class: Fon Plate Current Rating: 130 A Weight: 21.56 kg (47.5 lb) Rated Speed: 4100 r/min

10. Body: Type: Cyolac No. Doors: 3 No. Windows: 6 No. Seats: 1 Cargo Volume: 1.36 m<sup>3</sup>

11. Chassis:

Type Frame: Boxed Rectangular Type Material: Aluminum Type Springs: Leaf Axle Type Front: Pipe Axle Manufacturer: Sebring-Vanguard Manufacturer: Globe Union S/N: None Battery Voltage: 24 - 48 Battery Size: 180 mm x 250 mm x 240 mm (7 in. x 10 in. x 9.5 in.)

Manufacturer: Gould Battery Voltage: 12 Battery Wt: 19.07 kg (42 lb)

Manufacturer: Vanguard Current Rating: 150A Weight: 8.17 kg (18 lb)

Manufacturer: GE Voltage Rating: 48 V HP Rating: 6 Size: 270 mm L, 16 mm dia (10.75 in. L, 6.5 in. dia)

Manufacturer: ABS Type: Hinge Type: 4 glass, 2 plastic Type: Bench Cargo Dimensions: 610 mm x 810 mm x 910 mm (24 in. x 32 in. x 36 in.)

Manufacturer: Sebring-Vanguard Modifications: None Type Shocks: Standard Axle Type Rear: Direct Gear Drive Drive Line Ratio: 7.1 : 1 Type Brake Front: Drum Type Brakes Rear: Drum Regenerative Brakes: No Tire Type: Radial Size: 125SR12 Rolling Radius: 244 mm (9.8 in.)

12. Battery Charger: On or Off Board: On Automatic Turn Off: No Manufacturer: MICHELIN Pressure: 32 lb/in.<sup>2</sup>

Manufacturer: Symons Input Voltage: 115 Recharger Timer: No

#### **APPENDIX B**

#### DESCRIPTION OF VEHICLE TEST TRACK

The test site used to conduct the tests described in this report is located at Aberdeen, Maryland. The track is owned and operated by the US Army. Three test sites were used.

1. Gradeability Slopes. Gradeability of vehicles is a basic characteristic usually given in design specifications of military vehicles. The Munson gradeability slopes (Figures B1 and B2) cover a range of 5 to 60 percent. They are used to determine optimum drive ratios and maximum attainable speeds on each slope, as well as brakeholding ability and adequacy of angles of approach and departure. With the test vehicle in both ascending and descending attitudes, functions such as lubrication, fuel flow, and carburetion are investigated. The effect of unbalance on turret traversing efforts and functioning of turret drive systems may also be studied on the slopes. The 5, 10, 15 and 20 percent slopes, approximately 14 feet wide, are paved with asphalt; the 30, 40, 45, 50 and 60 percent slopes, with concrete.



Figure B1. Plan View of Slopes.



### Figure B2. Eight of the Standard Gradeability Slopes.

2. Mile Loop. The Mile Loop (Figure B3) was originally constructed in 1933 as a level concrete course of oval shape for continuous high speed operating tests of vehicles. Near the headquarters area of the post, the course consists essentially of two straight sections, each one-quarter-mile long, joined at each end by quarter-mile sections of regular curvature to form an oval of 1 mile total circumference.



Figure B3. Aerial View of Mile Loop.

The course has been modified by covering and maintaining the surface with hot-mixed bituminous concrete and by the addition of a gravel surface parallel to and outside the oval. Several facilities also have been added in the area: a winch test facility, a "pothole-crosstie" course for forklift truck testing, and a 1-inch bump course for mobility testing of towed vehicles.

Winch Test Facility (Mile Loop). This winch facility has a restraining capability of 100,000 pounds and is used primarily as an anchor during winch endurance testing.

3. Dynamometer Course. The Dynamometer Course (Figure B4) is located in the Michaelsville section of the proving ground, 4 miles from the headquarters area. Constructed of reinforced concrete, with a hot-mixed bituminous surface, it is suitable for the operation of the heaviest tracklaying vehicles.

The course has a total gradient of less than 0.1 percent in its l-mile length, and turnarounds are provided at each end. It is used for closely controlled engineering tests such as drawbar pull and tractive resistance measurements, acceleration and braking tests, and fuel consumption measurements.



#### Figure B4. Dynamometer Course.



- 2 No. 2 Cross-Country

a bat a constant

- 3 No. 3 Cross-Country 4 - No. 4 Cross-Country
- 5 Secondary Road A
- 6 Secondary Road B
- 7 3-Mile, High Speed Road
- 9 Mud Mobility Course
- 10 Mobile Bridge Test Facility 11 Deep Water Fording Facility
- 12 Swamp Quarter Mobility Area
- 13 Crash Barrier
- 14 Shop Area

Figure B5. Aerial View of Perryman Test Area.

#### APPENDIX C

#### VEHICLE PREPARATION AND TEST PROCEDURE

When a vehicle was first received at MERADCOM, a number of checks were made to assure that it was ready for performance tests. These checks were recorded on a vehicle preparation check sheet. The vehicle was examined for physical damage upon arrival. Before operating the vehicle, a complete visual check was made of the entire vehicle. The battery was charged and specific gravities taken to determine if the batteries were equalized. If not, an equalizing charge was applied to the batteries. The integrity of the internal interconnections and the battery terminals were checked by drawing 300 amps or the vehicle manufacturer's maximum allowed current from the battery for 5 minutes; if the battery terminals or interconnections temperature rose more than 60°C above ambient, the test was terminated and the terminals cleaned or battery replaced. The batteries were recharged and a battery capacity check was made. This test was made in accordance with the battery manufacturer's recommendations. To pass this test, the capacity had to be within 20% of manufacturer's published capacity at the published rate.

When a vehicle arrived at a test site (APG), a number of checks were performed to assure that it was ready for performance testing. The wheel alignment was checked, compared, and corrected to the manufacturer's recommended alignment values. The vehicle was weighed and compared with the manufacturer's specified curb weight. The gross vehicle weight was determined by manufacturer's rated payload.

#### TEST PROCEDURE

Each day, before a test, a number of pretest checks were made and entered on the vehicle data sheet. These data included:

- 1. Average specific gravity before and after test.
- 2. Tire pressures.
- Fifth-wheel tire pressures.
- 4. Weather information.
- 5. Battery temperatures.
- 6. Test start time.
- 7. Test termination time.
- 8. Amp hours out of the battery.
- 9. Fifth-wheel distance count.

10. Odometer reading before and after each test.

11. A.C. kW used for recharge.

12. D.C. amp hours into battery on recharge.

To prepare for a test, the specific gravities are first measured and recorded. The tire pressures are measured. The instrumentation is connected and power from the instrumentation battery is applied. All instruments are turned on and warmed up and all data channels are calibrated. The vehicle is towed to the starting point on the track. Weather data are recorded; odometer reading taken. The test is started and is carried out in accordance with the DOE test and evaluation procedure. When the test is terminated, the test team makes all the proper checks and records all data on data test sheet for the day's test. After all checks are made, vehicle is towed back to the charge station and placed on charge for next day's test.

#### WEATHER DATA

Measurements of wind velocity and direction and ambient temperatures were taken at the beginning and at the end of each day's testing. The APG Airport weather station was used for all weather data.

# DISTRIBUTION FOR MERADCOM REPORT 2268

No. Copies	Addressee	No. Copies	Addressee
	Department of Defense		
1	Director, Technical Information Defense Advanced Research Projects Agency 1400 Wilson Blvd Arlington, VA 22209	1	Technical Library Chemical Systems Lab Aberdeen Proving Ground, MD 21010
12	Defense Documentation Center Cameron Station Alexandria, VA 22314 Department of the Army	1	Commander US Army Aberdeen Proving Ground ATTN: STEAP-MT-U (GE Branch) Aberdeen Proving Ground, MD 21005
1	Commander, HQ TRADOC ATTN: ATEN-ME Fort Monroe, VA 23651	Canco <sup>1</sup>	Director US Army Materiel Systems Analysis Agency
1	HQDA (DAMA-AOA-M) Washington, DC 20310		Aberdeen Proving Ground, MD 21005
1	HQDA (DALO-TS M-P) Washington, DC 20310	1	Director US Army Ballistic Research Lab ATTN: DRDAR-TSB-S
1	HQDA (DAEN-RDL) Washington, DC 20314		(STINFO) Aberdeen Proving Ground, MD 21005
1	HQDA (DAEN-MCE-D) Washington, DC 20314	1	Director
1	Commander US Army Missile Research and Development Command ATTN: DRSMI-RR Redstone Arsenal, AL 35809		Experiment Station ATTN: Chief, Library Branch Technical Info Ctr Vicksburg, MS 39180
1	Chief, Engineer Division DCSLOG ATTN: AFKC-LG-E HQ Sixth US Army Presidio of San Francisco, CA 94129	1	Commander US Army Troop Support & Aviation Materiel Readiness Command ATTN: DRSTS-KTE 4300 Goodfellow Blvd St. Louis, MO 63120
1	Director Army Materials and Mechanics Research Center ATTN: DRXMR-STL	2	Director Petrol & Fld Svc Dept US Army Quartermaster School Fort Lee, VA 23801
1	Technical Library Watertown, MA 02172 US Army Ballistic Research Labs Technical Library DRXBR-LB (Bldg 305) Aberdeeen Proving Ground, MD 21005	1	Commander US Army Electronics Research & Development Command ATTN: DRSEL-GG-TD Fort Monmouth, NJ 07703

#### No. Copies Addressee

1

1

1

1

1

- 1 President US Army Aviation Test Board ATTN: STEBG-PO Fort Rucker, AL 36360
- 1 US Army Aviation School Library P.O. Drawer O Fort Rucker, AL 36360
- 1 HQ, 193D Infantry Brigade (CZ) Directorate of Facilities Engineering Fort Amador, Canal Zone
  - Commander Special Forces Detachment (Airborne), Europe APO New York 09050
- 1 HQ, USAREUR & Seventh Army DCSENGR, ATTN: AEAEN-MO ATTN: Mil Ops Div APO New York 09403
- 2 Engineer Representative US Army Standardization Group, UK Box 65, FPO New York 09510
  - Commander Rock Island Arsenal ATTN: SARRI-LPL Rock Island, IL 61201
  - Commander Frankford Arsenal ATTN: Library, K2400, B1 51-2 Philadelphia, PA 19137
- 1 Learning Resources Center US Army Engineer School Bldg 270 Fort Belvoir, VA 22060
- 1 President US Army Airborne, Communications and Electronics ATTN: STEBF-ABTD Fort Bragg, NC 28307
  - Commander Headquarters, 39th Engineer Battalion (Cbt) Fort Devens, MA 01433
  - President US Army Armor and Engineer Board ATTN: ATZK-AT-TD-E Fort Knox, KY 40121

#### No. Copies Addressee

1

1

1

1

- Commander 2nd Engineer Group ATTN: S4 APO San Francisco 96301
- 1 Commander and Director USAFESA ATTN: FESA-RTD Fort Belvoir, VA 22060
  - Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL (Tech Lib) White Sands Missile Range, NM 88002

#### MERADCOM

- Commander, DRDME-Z Technical Director, DRDME-ZT Assoc Tech Dir/R&D, DRDME-ZN Assoc Tech Dir/Engrg & Acq, DRDME-ZE Spec Asst/Matl Asmt, DRDME-ZG Spec Asst/Tech Asmt, DRDME-ZK CIRCULATE
- C, Ctrmine Lab, DRDME-N C, Engy & Wtr Res Lab, DRDME-G C, Cam & Topo Lab, DRDME-R C, Mar & Br Lab, DRDME-M C, Mech & Constr Eqpt Lab, DRDME-H C, Ctr Intrus Lab, DRDME-X C, Matl Tech Lab, DRDME-V Director, Product A&T Directorate, DRDME-T CIRCULATE
- 10 Elec Pwr Lab, DRDME-E Electrochem Div, DRDME-EC 200 Tech Reports Ofc, DRDME-WP 3 3 Security Ofc (for liaison officers), DRDME-S 2 Tech Library, DRDME-WC Plans, Programs & Ops Ofc, DRDME-U 1 Pub Affairs Ofc, DRDME-I Ofc of Chief Counsel, DRDME-L 1

#### Department of the Navy

Director Naval Research Laboratory ATTN: Code 2627 Washington, DC 20375

#### No. Copies Addressee

1

1

1

1

1

1

1

1

- Commander, Naval Facilities Engineering Command
- Engineering Command Department of the Navy ATTN: Code 032-A 200 Stovall Street Alexandria, VA 22332
- 1 US Naval Oceanographic Office Library (Code 1600) Washington, DC 20373
  - Officer-in-Charge (Code L31) Civil Engineering Lab Naval Construction Battalion Ctr Port Hueneme, CA 93043
  - Naval Training Equipment Ctr ATTN: Technical Library Orlando, FL 32813

#### Department of the Air Force

- 1 HQ USAF/RDPS (Mr. Allan Eaffy) Washington, DC 20330
  - Mr. William J. Engle Chief, Utilities Branch HQ USAF/PREEU Washington, DC 20332
- 1 AFSC/INJ Andrews AFB, MD 20334
  - AFCEC/XR/21 Tyndall AFB, FL 32401
  - HQ USAF/PREES ATTN: Mr. Edwin B. Mixon Bolling AFB – Bldg 626 Washington, DC 20332
- 1 AFAPL/SFL Wright-Patterson, AFB, OH 45433
  - Department of Transportation Library, FOB 10A, TAD – 494.6 800 Independence Avenue, SW Washington, DC 20591

#### Others

A. D. Little ATTN: Brad Underhill 15 Acorn Park Cambridge, MA 02140

#### No. Copies Addressee

1

1

1

1

1

1

1

1

1

- Advanced Ground Systems Eng ATTN: Dr. George Gelb 3270 E. 70th Street Long Beach, CA 90805
- Airesearch Manufacturing Co. ATTN: Bob Rowlett Program Manager 2525 W. 190th Street Torrance, CA 90509
  - AM General Corporation ATTN: H. H. Crist, Sales Manager 32500 Van Born Road Wayne, MI 48184
  - Amectran ATTN: Mr. Ed Ramirez President 1545 West Mockingbird Suite 4020 Dallas, TX 75235
- Argonne National Labs ATTN: Al Chilenskas 9700 South Cass Avenue Argonne, IL 60439
- B&Z Electric Car Robert McCoy 1418 West 17th Street Long Beach, CA 90813
- Battronic Truck Corporation ATTN: Mr. Harry Yoder President 3rd and Walnut Streets Boyertown, PA 19512
- Billings Energy Corporation ATTN: Mr. Hadden P.O. Box 555 Provo, UT 84601
  - Booz, Allen & Hamilton, Inc. John F. Wing Transportation Consulting Div 4330 East West Highway Bethesda, MD 20014
  - Borrisoff Engineering Co. 7726 Burnet Avenue Van Nuys, CA 91405

#### No. Copies Addres

1

1

1

1

50

CONTRACTOR NOT

- Addressee
- C. H. Waterman Industries ATTN: C. H. Waterman President White Pond Road Athol, MA 01331
- 1 Chloride America James A. Gilchrist, President 5200 W. Kennedy Blvd P.O. Box 24598 Tampa, FL 33623
- 1 Compass Industries, Inc. Richard J. Barkley 715 25th Street Hermosa Beach, CA 90254
- 1 Cooper Development Association ATTN: Donald K. Miner, Manager 430 N. Woodward Avenue Birmingham, MI 48011
  - Cornell University Joe Rosson, Associate Director School of Engineering Phillips Hall Ithaca, NY 14853
  - Creative Automotive Research ATTN: Erwin A. Ulbrich Chief Engineer 8136 Byron Road, Suite G Whittier, CA 90606
- 1 Creative Research Corp. ATTN: Larry Nalley, President P.O. Box 186 Roebuck, SC 29376
  - Daihatsu Morto Co., Ltd. ATTN: Shoji Honda General Manager Electric Vehicle Department 1-1 Daihatsu – Cho Ikeda City, Osaka Prefecture, Japan

Department of Energy ATTN: Dr. Robert S. Kirk Transporation Energy Conservation 20 Massachusetts Avenue, NW Washington, DC 20545

#### No. Copies Addressee

1

- Department of Energy ATTN: Walter J. Dippold Electric & Hybrid Vehicle Systems 20 Massachusetts Avenue, NW Washington, DC 20545
- 1 Department of Industry, Trade & Commerce Fred Johnson, Special Vehicle Div Transportation Industries Branch Ottawa, Canada, KIA 085
- 1 Department of Transportation Transportation Systems Center ATTN: Dr. Norman Rosenburg Cambridge, MA 02142
- 1 Derl Manufacturing Company ATTN: Mr. Erwin Meeks 2730 N. Slater Avenue Compton, CA 90222
- 1 Die Mesh Corporation ATTN: Mr. Domenic Borello President 629 Fifth Avenue Pelham, NY 10803
- 1 Dimension V. Inc. James H. Muir, President 598 Sea Breeze Drive Indialantic, FL 32903
- 1 Douglas Dow Consulting Engineer P.O. Box 14078 Detroit, MI 48214
- 1 Dynamic Science ATTN: Mr. B. Enserik 1850 W. Pinnacle Peak Road Phoenix, AZ 85027
- 1 Edward Harding & Co. c/o W. W. Craig 1411 North State Parkway Chicago, IL 60610
  - Elcar Corporation ATTN: Leon Shahnasarian President 2118 Bypass Road P.O. Box 937 Elkhart, IN 46514

1

1

1

1

1

1

1

1

1

ElecTraction Limited ATTN: R. D Haynes Heybridge Basin Maldon Essex, England

Electric Dynamics Corp. James C. Boylan, Presidnet 607 North Main Street Plainwell, MI 49080

Electric Fuel Propulsion Corp. ATTN: Robert Aronson President 2237 Elliott Avenue Troy, MI 48084

Electric Passenger Cars, Inc. ATTN: P. H. Rubie, President 5127 Galt Way San Diego, CA 92117

Electric Power Research Institute ATTN: Dr. Fritz R. Kalhammer 3412 Hillview Avenue P.O. Box 10412 Palo Alto, CA 94304

Electric Vehicle Associates ATTN: Warren Harhay President 9100 Bank Street Cleveland, OH 44125

Electric Vehicle Council ATTN: Mr. Edward Campbell 90 Park Avenue New York, NY 10016

Electric Vehicle Engineering Wayne Goldman, President P.O. Box 1 Lexington, MA 02173

Energy Research and Development Corporation ATTN: R. Childs, President 9135 Fernwood Drive Omsted Falls, OH 44138

ESB, Inc. ATTN: Jim Norberg 5 Penn Center Plaza Philadelphia, PA 19013

1 EVE Electric Motor Car, Inc. ATTN: Alan D. Brown 723 Forest Street East Lansing, MI 48823 No. Copies Addressee

1

1

- Fiat ATTN: Dennis Hanify, Manager IIT Research Institute 10 West 35th Street Chicago, IL 60616
- Fluid Drive Engineering Co. ATTN: Joseph Seliber, President 313 Hibbard Road Wilmette, IL 60091

1 General Electric Corporate Research & Development ATTN: Gene Rowland Program Manager P.O. Box 8 Schenectady, NY 12301

- 1 General Research Corporation ATTN: John Brennand 5383 Hollister Avenue Santa Barbara, CA 93105
- 1 General Services Administration Federal Supply Service ATTN: Mel Globerman Washington, DC 20406
- I General Services Administration Federal Supply Service ATTN: R. L. Ullrich Washington, DC 20406

1 Jet Industries, Inc. ATTN: William Bales, President 4201 South Congress Austin, TX 78745

- 1 Jet Propulsion Laboratory ATTN: T. Barber 4800 Oak Grove Drive Pasadena, CA 91103
  - Jet Propulsion Laboratory ATTN: Donald W. Ritchie 198-220 4800 Oak Grove Drive Pasadena, CA 91103
  - Kaylor Energy Products ATTN: Roy Kaylor, President 1918 Menalto Avenue Menlo Park, CA 94025
  - Kinergy Research & Development ATTN: Laura Omohundro P.O. Box 1124 Wake Forest, NC 27587

3

1

1

1

1

1

- Lavelle Aircraft Co. ATTN: R. Wilks Sterling Street Newtown, PA 18940
- 1 Lawrence Livermore Laboratory ATTN: Douglas Davis-MS-L-216 P.O. Box 808 Livermore, CA 94550
  - Lectran ATTN: Ray L. Boeger 5452 Business Drive Huntington Beach, CA 92649
- 1 Linear Alpha, Inc. ATTN: Dr. E. H. Wakefield 1927 Sherman Avenue Evanston, IL 60201
- 1 Los Alamos Scientific Labs Byron McCormick P.O. Box 1663 Los Alamos, NM 87545
- Joseph Lucas, Ltd. ATTN: Dr. Brian Phillips Special Projects
  17 Evelyn Road Sparkhill, Birmingham B 11 3JR England
- 1 Lucas Industries N.A., Inc. ATTN: Tony Burgess Two Northfield Plaza Troy, MI 48098
  - Marathon Electric Vehicles, Limited ATTN: Howard Candlish 8305 LeCreusot Street Ville St. Leonard, P.Q. Montreal, Quebec, H1P 2A2 Canada
    - Maxon Industries, Inc. ATTN: Murray Lugash 1960 E. Slavson Avenue Huntington Park, CA 90255
    - McKee Engineering Corporation ATTN: Robert McKee, President 411 West Colfax Street Palatine, IL 60067

#### No. Copies Addressee

1

1

1

1

1

1

1

1

1

- Meteor Research Limited ATTN: W. H. Fengler, President 29440 Calahan Avenue Roseville, MI 48066
- Minicars, Inc. ATTN: Mr. Donald Friedman 35 La Patera Lane Goleta, CA 93017
- NASA Lewis Research Center ATTN: J. S. Fordyce MS: 309-1 21000 Brookpark Road Cleveland, OH 44135
- NASA Lewis Research Center ATTN: Mort Krasner MS: 500-210 21000 Brookpark Road Cleveland, OH 44135
- 20 NASA Lewis Research Center ATTN: H. J. Schwartz MS: 500-215 21000 Brookpark Road Cleveland, OH 44135
  - NASA ATTN: NE/E. E. VanLandingham Washington, DC 20546
  - National Motors Corporation ATTN: Barryl Kane, President P.O. Box 1523 Lancaster, PA 17604
  - Newton Engineering Co. ATTN: John S. Newton, President 22 W. 450 Ahlstrand Drive Glen Ellyn, IL 60137
  - Northwestern University ATTN: Dr. Gordon Murphy Electric Engineering Dept 2145 Sheridan Road Evanston, IL 60201
  - Onan Corporation ATTN: David Burns 1400 73rd Avenue, NE Minneapolis, MN 55432
  - Packaged Promotions, Inc. ATTN: Al Masters 549 W. Randolph Chicago, IL 60606

#### No. Copies Addressee

1

I

1

1

1

1

1

1

1

- Petro-Electric Motors, Ltd. ATTN: Victor Wouk, Consultant 342 Madison Avenue, Suite 831 New York, NY 10017
- Powertrain, Inc. ATTN: Mr. Alfred Blackerby 3665 S. 300 West Salt Lake City, UT 84115
- **Purdue University** 1 IIES A. A. Potter Engineering Center ATTN: Dr. R. E. Goodson W. Lafayette, IN 47907
  - REI ATTN: E. Papandreas 1209 Lake Avenue Lake Worth, FL 33460
  - Sandia Laboratories **Richard Bassett** Division 2354 P.O. Box 5800 **Kirkland Base East** Albuquerque, NM 87115
  - Sebring-Vanguard, Inc. ATTN: Robert Beaumont President 9130 Red Branch Road Columbia, MD 21045
  - Society of Automotive Engineers, Inc. William Toth, Staff Engineer 400 Commonwealth Warrendale, PA 15096
  - Solargen Electronics, Ltd. Steven J. Romer 562 Fifth Avenue New York, NY 10036
  - South Coast Technology, Inc. ATTN: Robert Schwarz P.O. Box 3265 Santa Barbara, CA 93105
- 1 Structural Plastics, Inc. ATTN: William Gillespie, President 1133 S. 120th East Avenue Tulsa, OK 74128-

**Transportation Research Center** of Ohio ATTN: Mr. C. Glassburn East Liberty, OH 43319

#### No. Copies Addressee

1

1

1

- 1 Triad Services, Inc. ATTN: Michael Pocabello, President 10611 Haggerty Street Dearborn, MI 48126
  - TurElec, Inc. ATTN: Harry Grepke, President 1915 29th Avenue, West Bradenton, FL 33505
- 1 Unique Mobility, Inc. ATTN: John Gould 3730 South Jason Englewood, CO 80110
- United States Postal Service: 1 ATTN: Dick Bowman Office of Fleet Mgmt **Delivery Services Dept** Washington, DC 20260
  - United States Postal Service ATTN: Donn Crane, Director Office of Fleet Mgmt **Delivery Services Dept** Washington, DC 20260
- United States Postal Service Research and Development Lab ATTN: Lewis J. Gerlach Program Manager 11711 Park Lawn Drive Rockville, MD 20852
- United States Postal Service 1 ATTN: Thomas W. Martin, Manager Vehicle Services Branch Western Region San Bruno, CA 94099
- 1 University of California Jack Bolger Lawrence Berkeley Labs Berkeley, CA 94720
- Volkswagen of America, Inc. ATTN: Tom Turnure 1 Englewood Cliffs, NJ 07632
- Volkswagen of America, Inc. ATTN: Rudy Schmidt c/o Tom Turnure Englewood Cliffs, NJ 07632

1

1

Western Research Industries ATTN: G. Hayes Turney 3013 West Sahara Avenue Las Vegas, NV 89102

Westinghouse R&D Center ATTN: G. Frank Pittman, Jr. 1310 Beulah Road Pittsburgh, PA 15235

Wolverine Diesel Power Co. ATTN: J. F. Corcoran, President 2880 Aero Park Drive Traverse City, MI 49684 1

Wood-Ivey Systems Corporation ATTN: Mr. Ivey P.O. Box 4609 1 Winterpark, FL 32793

Paul Zanoni 820 Tenth Street Boulder, CO 80302

Zeonics Corporation ATTN: Mr. Ai Long 4085 Chain Bridge Road Fairfax, VA 22030 1

Addressee

# DEPARTMENT OF THE ARMY

U. S. ARMY MOBILITY EQUIPMENT RESEARCH AND DEVELOPMENT COMMAND FORT BELVOIR, VIRGINIA 22060

> OFFICIAL BUSINESS PENALTY FOR PRIVATE USE, \$300

POSTAGE AND FEES PAID U. S. DEPARTMENT OF THE ARMY DOD-314



CONTRACTOR OF

THIRD CLASS MAIL