





ſ	REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
1		N NO. 3. RECIPIENT'S CATALOG NUMBER
4	4 SAI-Ø11-79-633-LJ	
1	T. TITLE (and Subilio)	Annual Report & PERIOD COVERED
ļ	Satellite Measurements of Atmospheric Aerosol	s, to March 31, 1979.
-		6. PERFORMING ORG. REPORT NUMBER
L		SAI-011-79-633-LJ
1	7. AUTHOR(a)	6. CONTRACT OR GRANT NUMBER(a)
F	M./Griggs	(15 NO0014-77-C-0489)
Ľ		U di
ľ	Science Applications, Inc.	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
	P. 0. Box 2351	(II) 31 Mar 79
L	La Jolla, CA 92037	A comparison of the second strange with the second strange
1	0ffice of Naval Research, Code 465	March 31, 1979
I	800 North Quincy Street	13. NUMBER OF PAGES
	Arlington, VA 22217	16 (12) I/p.
Г	14. MONITORING AGENCY NAME & ADDRESS(I different from Controlling Of	ice) 18. SECURITY CLASS (attile report)
	(g)Annual rept.	UNCLASSIFIED
	(9) Annual rept. 1 Apr 78-31 Mar 79)	154. DECLASSIFICATION/DOWNGRADING
	1 Apr 78-31 Mar 79 16. DISTRIBUTION STATEMENT (of the Report) Approved for public release; distribution unl 17. DISTRIBUTION STATEMENT (of the obstract entered in Block 20, 11 difference Same as report.	
	16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unl 17. DISTRIBUTION STATEMENT (of the obstract entered in Block 20, 11 dillor	imited
	16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unl 17. DISTRIBUTION STATEMENT (of the obstract entered in Block 20, 11 dillor Same as report. 18. SUPPLEMENTARY NOTES 19. KEY WORDS (Continue on reverse aide if necessary and identify by block m Maritime Aerosols EOMET Cr	imited
	 16. DISTRIBUTION STATEMENT (of the Report) Approved for public release; distribution unl 17. DISTRIBUTION STATEMENT (of the obstract entered in Block 20, If different Same as report. 18. SUPPLEMENTARY NOTES 19. KEY WORDS (Continue on reverse elde if necessory and identify by block me Maritime Aerosols EOMET Cr Satellite Measurements Sun Photo Ocean Radiance Aerosol Scattering 30. AustRACT (Continue on reverse elde if necessory and identify by block me Measurements of the atmospheric aerosol of during the 1977 EOMET cruise across the Atlan Sea. These data were obtained at the same ti radiance measurements in the vicinity of the between the upwelling radiance and the aerosol for each satellite, confirming earlier Landsa relationships for each satellite are attribut	imited imited int from Report) inter int
	 14. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unl 17. DISTRIBUTION STATEMENT (of the ebstreet entered in Block 20, if difference and in Block 20, if difference and in Block 20, if difference and its and	imited imited int from Report) inter int

ABSTRACT

0

0

Õ

8

-

0

0

D

0

Measurements of the atmospheric aerosol optical thickness were made during the 1977 EOMET cruise across the Atlantic Ocean and the Mediterranean Sea. These data were obtained at the same time as NOAA-5 and GOES visible radiance measurements in the vicinity of the ship. Linear relationships between the upwelling radiance and the aerosol optical thickness were found for each satellite, confirming earlier Landsat results. Differences in the relationships for each satellite are attributed to differences in the radiometric calibrations of the satellite sensors.

ESSION	for	Section	X
IS		Section	6
r		30000	
In Sheren	NCED	-	-
SILICA	rioa		
BA	PTICHINE	NE! ITY	JULS
	i lined use	- 1	SPECIN
SID FAID			
(IDIAID			
BEDIAD	T	1	
	X		
BIDINIS	XI		

ACKNOWLEDGMENTS

O

0

0

Ô

\$

8

0

0

0

0

The author would like to thank Dr. L. Ruhnke for providing the sun photometer data, and for his encouragement in this investigation.

- Carl program burger

TABLE OF CONTENTS

Section		Page
	REPORT DOCUMENTATION PAGE	i
	ABSTRACT	ii
	ACKNOWLEDGEMENTS	iii
1.	INTRODUCTION	1
2.	PREVIOUS LANDSAT RESULTS	2
3.	APPROACH	3
4.	DATA ANALYSIS	4
5.	RESULTS	6
6.	CONCLUSIONS	8
	FIGURE 1	9
	FIGURE 2	10
	FIGURE 3	11
	REFERENCES	12

and the second second

1. INTRODUCTION

The atmospheric marine boundary layer is of considerable importance to Navy operations. Of particular interest, with the increasing use of electro-optical systems, is the nature and distribution of aerosols over the oceans. In order to provide further information about the aerosols, and other meteorological parameters in the marine boundary layer, the Naval Research Laboratory conducted an Electro-Optical Meteorology (EOMET) cruise, May 15 to June 6, 1977, across the North Atlantic Ocean and Mediterranean Sea. This cruise offered a good opportunity to further investigate the satellite technique, developed by Griggs (1975, 1977) to measure the atmospheric aerosol content over oceans. This technique relates the upwelling visible radiance measured by the satellite to the atmospheric aerosol optical thickness. Since 60% of the aerosols are typically in the lowest 1 km, and 90% in the lowest 3 km, it is clear that the satellite measurements can provide information of considerable importance to Navy operations. The previous studies were based on Landsat data, but for this investigation the NOAA and GOES satellites were used.

Õ

8

0

0

0

0

0

a the sector of a sector of the

2. PREVIOUS LANDSAT RESULTS

0

3

3

0

0

8

0

0

Previous results using Landsat 1 data (Griggs, 1975) and Landsat 2 data (Griggs, 1977) have shown that a linear relationship exists between the upwelling radiance in the visible region and the aerosol content. Data have been obtained at several sites, the largest data set being for the Pacific Ocean at San Diego for Landsat 2 overpasses. These results are shown in Figure 1. The radiances are determined from the Landsat digital data (densitometry of the black and white imagery is not accurate enough for intercomparison of different images), and the aerosol content values are determined with ground-based Volz sun photometer measurements at the time of the Landsat overpass. The aerosol content is defined in terms of the Elterman (1965) model vertical aerosol optical thickness; i.e., the aerosol content is given by the ratio (measured aerosol optical thickness at wavelength λ to a model aerosol optical thickness at wavelength λ) x N: i.e., a value of 2N for the aerosol content indicates that the optical thickness is twice that of the Elterman model. In the results reported here, measurements of the aerosol optical thickness were available only at 0.5 µm, so that all radiances measured by the different radiometers are plotted against aerosol content where N indicates an aerosol optical thickness of 0.213 (the Elterman model value) measured at 0.5 µm.

The relationships appear best for multispectral scanner (MSS) channels MSS 5 and MSS 6; this is probably due to the fact that the radiance in MSS 4 is affected by suspended matter in the water. Figure 1 does not show MSS 7 data, since the digital data for this channel are uncertain owing to NASA procedures for producing Landsat 2 computer compatible tapes.

2

- - Level a tradicional and a tradicional

3. APPROACH

Arrangements were made for sun photometer measurements of the atmospheric aerosol optical thickness to be taken daily, weather permitting, on board the U.S.N.S. Hayes (EOMET cruise vessel) at times as nearly coincident as possible with the overpasses of NOAA-5 (0800-1000 local standard time) and at 1600 GMT, when GOES-1 digital data are routinely recorded and stored. The radiances measured by the satellites must be modified in order to compare them with the Landsat values shown in Figure 1. The Landsat radiances are for the multispectral scanner (MSS) spectral bandpasses and for nadir viewing. The NOAA-5 and GOES-1 have slightly different bandpasses, and in general the radiances of interest are not obtained in the nadir direction. These radiances are normalized to the Landsat viewing and sun angle conditions by means of theoretical calculations with an atmospheric scattering code (Dave and Gazdag, 1970), which was previously used in support of the Landsat study.

0

8

0

4. DATA ANALYSIS

The sun photometer data had to be carefully reviewed since measurements are difficult to make on board ship due to the motion of the ship. This is especially true for the measurement of the airmass; fortunately this can be precisely calculated from knowledge of the location of the ship and the time.

The location of the ship as a function of time, and the orbital parameters of the NOAA-5, which is in a polar orbit, are used to determine the respective locations of the ship and the satellite at the time the satellite radiance measurement is acquired. Then, using spherical trigonometry, the sun zenith (θ_0) and azimuth (ϕ) angles and the viewing angle (θ) from the satellite to the ship are calculated. For the geosynchronous GOES-1, which is at a fixed location, the required angles are similarly calculated. These angles are used as input to the Dave code which is used to normalize the measured radiance to the standard conditions used for the Landsat data, viz. $\theta_0 = 63.3^0$, $\phi = 0$, $\theta = 0$. The calculations are made for each pair of satellite radiance and aerosol content observations, using the measured aerosol content as input to the code. The aerosol model used in the code is one that gave good agreement with the Landsat-2 data, i.e., a Junge size distribution with v = 4.0 and refractive index n = 1.5. Thus, the normalized radiance (I) is given by

I = I_m ×
$$\frac{I_c(0,63.3^{\circ},0,N_m)}{I_c(0,0,0,N_m)}$$

where

0

0

.

0

0

 I_m is the measured radiance I_c is the calculated radiance N_m is the measured aerosol content. The calculations are performed at 0.67 μ m for the NOAA-5 Scanning Radiometer (SR) and at 0.64 μ m for the GOES Visible Infrared Spin Scan Radiometer (VISSR).

The satellite data were obtained in digital form from the National Environmental Satellite Service (NESS) of NOAA. The SR data were available only in the mapped format (with 20 km resolution) for this investigation, and did not provide all the resolution elements actually measured during the satellite overpasses. Another shortcoming of the SR data is the fact that the SR output is subject to a non-random noise which cannot be readily eliminated. In an attempt to minimize these effects, each SR radiance reported here is the mean of 5 x 5 block of pixels centered on the calculated ship location. The VISSR radiances (with 6 km resolution) reported here are also the means of 5 x 5 blocks of pixels. The radiances are given in units of $mw/cm^2/um/sr$, and are based on calibration data obtained from NESS, converting digital counts to Foot-Lamberts, in the case of the SR, and directly into radiance units in the case of the VISSR.

2

2

0

Stand Stranger and Stand Strate

5. RESULTS

0

3

۰

8

0

The weather during the cruise was generally quite good, enabling coincident sun photometer and satellite measurements to be obtained on several occasions. The GOES coverage of the Atlantic Ocean is good only to about 25° W longitude, which was reached by the U.S.N.S. Hayes on May 24, 1977. In these first ten days, sets of data were obtained on six occasions for the GOES. During the same time period, six sets of data were also obtained for NOAA-5 overpasses. However, after May 24, 1977, ten more days were spent at sea, but only three more sets of data were obtained for the NOAA-5 overpasses.

The GOES VISSR data, plotted in Figure 2, show an excellent linear relationship, as anticipated from the Landsat results, and shows that normalization procedures with the Dave code are satisfactory.

The NOAA-5 data were not expected to be very useful due to their format and noise problems, as described above. However, in spite of these shortcomings, the relationship shown for the SR radiances in Figure 3 is remarkably good. A linear relationship can probably be inferred. The x-points show an enhanced radiance due to sun-glitter, and demonstrate that observations should be made away from the sun, except close to the nadir as illustrated by the o-point.

In comparing these results with those of Landsat 2, taking into account the wavelength differences, it is found that for the SR data, the radiance value for N = O is as expected (this value is independent of the aerosol properties, and represents a pure molecular atmosphere), but that the other radiances are lower than expected. This can be due to the aerosol properties being different from those of the Landsat San Diego data, or can be due to uncertainties in the radiometric calibrations in each satellite. However, in the Landsat Study, data obtained at Adrigole, Ireland, for Atlantic Ocean aerosols showed good agreement with the San Diego data. The same study showed that differences also existed

between the Landsat 1 and Landsat 2 results at San Diego, and it was concluded that they were due to differences in the radiometric calibrations of the two satellites. It is believed that similar calibration problems are responsible for the SR and Landsat differences. Indeed, in examining the VISSR results in Figure 2, it is found that both the intercept and slope of the line are significantly different from those predicted from the Landsat data, suggesting again that the reason is due to the radiometric calibrations.

It should be understood that the upwelling radiance depends on the aerosol optical properties, such as size distribution and refractive index, and on other parameters such as surface reflectivity, wavelength, sun angles and satellite viewing angles. It was shown earlier (Griggs, 1975) that the vertical distribution of aerosols does not significantly affect the upwelling radiance. The effect of varying surface reflectivity is minimized by avoiding observations in areas of sun glitter. Thus, some scatter in the radiance values shown in the results is expected, mainly from variations in the size distribution and refractive index; these effects are currently being examined theoretically and will be the subject of a future publication. Of course, some scatter is due to experimental error both in the radiances and in the sun photometer, as discussed earlier by Griggs (1975). The aerosol content can be measured with an accuracy of $\pm 5 - 10\%$, and the MSS radiance can probably be determined with an accuracy of about ± 0.06 mw cm⁻²µm⁻¹sr⁻¹.

0

-

-

0

6. CONCLUSIONS

O

0

0

0

0

0

A linear relationship between the upwelling visible radiance, as observed by the Landsat MSS, and the atmospheric aerosol content, has also been found for the GOES-VISSR and the NOAA-5 SR. The relationships are slightly different for each satellite. These differences are attributed to differences in the radiometric calibrations of the satellites, and points to the necessity of precise radiometric calibrations of satellite radiometers if they are to be used in the future for aerosol measurements. Without precise calibration each satellite would have to be empirically calibrated with lengthy periods of ground truth measurements.





Figure 2. GOES Ocean Radiances Versus Aerosol Content. The Radiances are Normalized to Nadir Viewing with a Sun Zenith Angle of 63°.





REFERENCES

- J. V. Dave & J. Gazdag, "A Modified Fourier Transform Method for Multiple Scattering Calculations in a Plane Parallel Mie Atmosphere," Appl. Optics <u>9</u>, 1457 - 1466, (1970).
- 2. L. Elterman, Atmospheric Optics, in <u>Handbook of Geophysics and Space</u> <u>Environments</u>, edited by S. Valley, McGraw-Hill, New York 1965.
- 3. M. Griggs, "Measurements of Atmospheric Aerosol Optical Thickness over Water Using ERTS-1 Data," J. Air. Poll. Contr. Assoc. <u>25</u>, 622 -626 (1975).
- 4. M. Griggs, "Comment on Relative Atmospheric Aerosol Content from ERTS Observations," J. Geophys. Res. <u>82</u>, 4972 (1977).

0

.