

K2176

Contract No. N123(953)54996A
TRACOR Project No. 002-009-26
Document No. SD-68-003-C

~~CONFIDENTIAL~~

Copy #5

MON 21. MAR 1968

LEVEL II

UNCLASSIFIED

DDC LIBRARY COPY

MOST Project-3

①

Good of 00264

ADAO 66894

DDC FILE COPY

TECHNICAL NOTE

RECONFIGURATION OF THE
HORIZONTAL BEAMFORMER (U)

Submitted to

U. S. Naval Undersea Warfare Center
San Diego, California 92152

Attention: Code D551

8 March 1968

DDC
RECEIVED
APR 4 1979
F

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

SCIENCES AND SYSTEMS DIVISION • SAN DIEGO LABORATORY

3065 Rosecrans Place, San Diego, California 92110, AC 714/222-6692
Home Office: TRACOR Inc., 6400 Tracor Lane, Austin, Texas 78721, AC 512-926-2800



UNCLASSIFIED

~~CONFIDENTIAL~~

GROUP - 4
DOWNGRADED AT 3 YEAR INTERVALS;
DECLASSIFIED AFTER 12 YEARS.

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, United States Code, Sections 793 and 794, and the transmission or revelation of its contents in any manner to an unauthorized person is prohibited by law.

UNCLASSIFIED
CONFIDENTIAL

Copy #5



3065 ROSECRANS PLACE, SAN DIEGO, CALIFORNIA 92110

Contract No. N123(953)54996A
TRACOR Project No. 002-009-26
Document No. SD-68-003-C

14 TRACOR

9

TECHNICAL NOTE

6

RECONFIGURATION OF THE
HORIZONTAL BEAMFORMER. (U)

Submitted to

U. S. Naval Undersea Warfare Center
San Diego, California 92152

ATTENTION: Code D551

11 8 March 1968

12 8p.

ADDITIONAL TO	
NTS	White Section <input checked="" type="checkbox"/>
DOC	Buff Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	AVAIL. and/or SPECIAL
A	

Approved:

D. V. Holliday
D. V. Holliday
Project Director

Prepared by:

David B. Doan
David B. Doan
Assistant Project
Director

411120

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sections 793 and 794, and the transmission or revelation of its contents in any manner to an unauthorized person is prohibited by law.

UNCLASSIFIED
CONFIDENTIAL

GROUP - 4
DOWNGRADED AT 3 YEAR INTERVALS;
DECLASSIFIED AFTER 12 YEARS.

UNCLASSIFIED
~~CONFIDENTIAL~~



3055 ROSECRANS PLACE, SAN DIEGO, CALIFORNIA 92110

RECONFIGURATION OF THE HORIZONTAL BEAMFORMER

(C) The baseline implementation for the horizontal beamformer involves a change in the sampling rate. The new sampling rate and the mean propagation delay vary with beam steering. The resampling involved has been shown¹ to produce spurious responses which may fall anywhere in the band. The change in delay with steering produces a discontinuity in the signal which must be corrected prior to the correlator. It may be possible to sufficiently reduce the spurious responses by providing adequate interpolation in the resampling process. It may also be possible to satisfactorily compensate for the delay discontinuity.

(C) However, if it is technically and economically feasible, it would be preferable to eliminate the problems at the source. This means that the horizontal beamformer should be redesigned in such a way as to have a constant sampling rate (equal to the sampling rate in the vertical and sub-array beamformers) and a fixed mean delay. The constant output sampling rate would also make consideration of an all-digital interface to the digital signal processor more feasible.

(C) One such technique has been studied by GD/E.² The basic concept is shown in Fig. 1. Each sub-array output is delayed in a delay channel similar to those used in the vertical and sub-array beamformers. The delayed sub-array outputs are selected and summed to produce the desired horizontal beams.

¹ Memo to Grant Yee, Naval Undersea Warfare Center, Code D551, dated 15 September 1967, "Resampling in the Horizontal Beamformer (U), "TRACOR Document No. 354-C, CONFIDENTIAL.

² "GD/E Monthly Progress Report A026-20233 covering 1 November 1967-30 November 1967 (U)," CONFIDENTIAL.

~~CONFIDENTIAL~~
UNCLASSIFIED

CONFIDENTIAL




Fig. 1
Delay-and-Sum Horizontal Beamformer

CONFIDENTIAL

CONFIDENTIAL



3065 ROSECRANS PLACE, SAN DIEGO, CALIFORNIA 92110

The horizontal beamformer thus follows the same design philosophy as the vertical and sub-array beamformers--the individual inputs are delayed and then summed. This is considerably more expensive than the sum and delay baseline approach.

(C) The alternate method shown in Fig. 2 should be considered for feasibility and cost. The sum and then delay method is an economical method of forming horizontal beams. The principal problem in the present application of this technique is the use of a variable sampling rate. Any given horizontal beam can be readily formed using a sum and delay technique at a fixed sampling rate. If a family of horizontal beams is formed covering 180° at a given depression angle and spaced in such a way that the peak of one beam coincides with the first null of the beam on either side, then any intermediate beam can be formed by interpolation. This would require about 180 beams at 3000 Hz with the baseline array.

(C) The storage required to form 180 fixed beams is not greatly different from that required to form the present 150 beams. The present design requires that any beam be steerable in any direction. Thus, the delay storage is a total of about 30 ms for each beam. In the proposed configuration, the full 30 ms delay would be required only for those fixed beams near endfire. Beams near broadside would need only about 15 ms total delay. (A broadside beam can, of course, be formed with no delay at all. However, the mean delay for all beams must be the same for the interpolation process to work properly.). Thus, the increased storage for the 30 additional beams is offset by the reduced storage requirement for beams away from endfire.

CONFIDENTIAL

CONFIDENTIAL




Fig. 2
Sun-and-Delay Fixed-Beam Beamformers with Output Interpolation

CONFIDENTIAL

CONFIDENTIAL




3065 ROSECRANS PLACE, SAN DIEGO, CALIFORNIA 92110

(C) Note also, that the switching in the interface between the fixed beam HBF's and the SBF's is eliminated as is the equipment for programming changes in τ_{α} . All horizontal steering and stabilization is now done by switching and interpolating at the output of the fixed beam HBF's.

(C) It is the design of this switch that poses the greatest problem of feasibility. Assuming that the switch is feasible, the incremental cost of adding additional output beams is just the cost of the switch.

(C) One possible method for implementing the switch and associated interpolator is shown in Fig. 3. The composite horizontal steering control is a twelve-bit digital signal. Eight bits control a two-pole switch to provide outputs consisting of the beams on either side of the desired direction. The remaining four bits control the interpolator. This is shown as a pair of hardware multipliers. If the binary value of the interpolation code is a , then one beam is multiplied by a and the other by $16-a$. The two weighted beams are then added. All of the bits generated by the multipliers should be carried into the adder. The adder output can be truncated to the number of bits which are present at the beamformer output. Note that 360° coverage can be obtained by adding an additional bit to the switch control and the 180 beam inputs from the other array. This requires that the two beamformers have a common clock.



~~CONFIDENTIAL~~

uml.

FIG. 3

6
~~CONFIDENTIAL~~

uml.