

AD-A071 229

NAVAL OCEANOGRAPHIC OFFICE NSTL STATION MS
OCEANOGRAPHY FOR LONG RANGE SONAR IN ATLANTIC AREA B FOR MAY. (U)
APR 63



F/G 20/1

UNCLASSIFIED


N00-IM-0-105-63

NL

| OF |
ADA
071229



END
DATE
FILMED
8-79
DDC



MICROCOPY RESOLUTION TEST CHART

NATIONAL BUREAU OF STANDARDS-1963-A

UNCLASSIFIED
~~CONFIDENTIAL~~

9
INFORMAL
MANUSCRIPT
REPORT.
NO. O-105-63

LEVEL *II good*

1

TITLE

IE MOST Project -2

6 OCEANOGRAPHY FOR LONG RANGE SONAR IN ATLANTIC AREA B FOR MAY.

AD A 071 229

AUTHOR

OCEANOGRAPHIC DEVELOPMENT DIVISION

14 NOO-IM-φ-1φ5-63

DDC
RECEIVED
JUL 16 1979
F

DATE

11 APR 1963
12 16p.

Reproduction of this document in any form by other than naval activities is not authorized except by special approval of the Secretary of the Navy or the Chief of Naval Operations as appropriate. This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Section 793 and 794. The transmission or revelation of its contents in any manner to an unauthorized person is prohibited by law.

DDC FILE COPY

This manuscript has a limited distribution, therefore in citing it in a bibliography, the reference should be followed by the phrase UNPUBLISHED MANUSCRIPT.

250 450

DOWNGRADED AT 3-YEAR INTERVALS
DECLASSIFIED AFTER 12 YEARS
DOD DIR 5200.10

MARINE SCIENCES DEPARTMENT
U. S. NAVAL OCEANOGRAPHIC OFFICE
WASHINGTON 25, D. C.

UNCLASSIFIED
CONFIDENTIAL

DISTRIBUTION STATEMENT A
Approved for public release;
Distribution Unlimited

LB

~~CONFIDENTIAL~~
UNCLASSIFIED

I AREA: One-degree quadrangle 25°-26°N 72°-73°W

II PREDICTED VALUES FOR QUADRANGLE FOR MAY

Sound Speed at Sonar	5035 ft/sec
Layer Depth	15 ft
Layer Depth Sound Speed	5035 ft/sec

Convergence Zone (For a depth of approximately 3000 fathoms)

Speed at Bottom (Fig 4)	5090 ft/sec
Minimum Refracted Angle (Fig 6)	0°
Maximum Refracted Angle (Fig 6)	8.4°
Average Angle	4.2°
Best Equipment Tilt (D/E) Angle	5.0°
Mean Horizontal Speed for Best Tilt (D/E) Angle (Fig 8)	4910 ft/sec
Initial Range (Fig 7)	70.8 kyds
Reswept Surface Zone Width (Fig 2)	1.4 kyds
Slant Path Velocity	4982 ft/sec

Bottom Bounce (For a depth of approximately 3000 fathoms)

Minimum useful Inclination Angle = Maximum Refracted Angle of Convergence + 3° =	11.4°
Predicted Detection Range (Fig 7)	53.2 kyds
Mean Horizontal Speed (Fig 8)	4870 ft/sec

Near Surface Path Detection

Range (Table I) (12-Knot Figure of Merit + Target Strength = 215 db)	11.6 kyds
----------------------------------------------------------------------	-----------

Accession For	
NTIS GRA&I	
DDC TAB	
Unannounced	
Justification <i>ON FILE AND LATER</i>	
By _____	
Distribution/	
Availability Codes	
Dist.	Avail and/or special
A	

DISTRIBUTION STATEMENT A
Approved for public release;
Distribution Unlimited

UNCLASSIFIED
~~CONFIDENTIAL~~

"B" MAY

UNCLASSIFIED

~~CONFIDENTIAL~~

III USE OF GRAPHS FOR PARTICULAR CONDITIONS

1. From BT temperature trace, determine and tabulate sound speed at sonar depth (V_1) and at layer depth (V_2) from Figure 5. Tabulate bottom (V_3) from Figure 4.

2. Convergence zone

a. Determine if convergence zone is possible. The difference between the bottom speed (V_3) and speed at sonar depth (V_1) will give a qualitative indication of convergence zone existence according to the table below.

$V_3 - V_1$ (ft/sec)	Convergence Zone Existence
Negative	None
0-30	Borderline
>30	Strong

b. To determine angular width and midpoint of totally refracted rays usable in convergence zone:

- (1) Determine minimum angle for totally refracted ray from Figure 6 using sound speed at sonar depth (V_1) and sound speed at layer depth (V_2) (first vertexing speed). With no layer, the minimum angle is 0° .
- (2) Determine maximum angle for totally refracted ray from Figure 6 using sound speed at sonar depth and bottom sound speed (V_3) (second vertexing speed) from Figure 4. (Bottom sound speed may also be obtained from sound speed profile in Figure 1).
- (3) Best tilt (D/E) angle for convergence zone will be that equipment tilt nearest the average of the minimum and maximum angles.

3. Bottom Bounce

a. Refracted ray angle (to the nearest degree) tangent to the bottom [item 2 B (2), above] plus 3° determines the minimum useful bottom bounce Ray angle.

b. Use the equipment tilt (D/E) angle nearest to the minimum useful bottom bounce Ray angle as computed in item III 3 a.

4. Near surface path detection range

a. Use Table 1.

TABLE 1 MEAN SURFACE PATH DETECTION RANGE (KYDS)
OF A SHALLOW TARGET

LAYER DEPTH (FEET)	FIGURE OF MERIT PLUS TARGET STRENGTH (ALLOWABLE TWO-WAY LOSS IN DB)										
	170	175	180	185	190	195	200	205	210	215	220
0	3	3	4	4	5	5	6	7	8	8	9
50	7	8	10	11	12	14	15	17	19	20	22
100	10	11	13	16	17	19	22	24	26	29	31
400	13	17	19	23	27	30	34	38	41	45	49

~~CONFIDENTIAL~~

UNCLASSIFIED

CONFIDENTIAL




FIGURE I TYPICAL SOUND SPEED PROFILE FOR MAY

CONFIDENTIAL

5 MAY

CONFIDENTIAL





FIGURE 2 RAY DIAGRAM FOR MAY COMPUTED FROM

RANGE (KILOYARDS)

32 34 36 38 40 42 44 46 48 50 52 54 56 58 60 62 64 66 68 70



SOURCE DEPTH = 25 FEET


Equipment Tilt
0°
-15° (Down)
-30° (Down)
-45° (Down)
-15° (Up)

BOTTOM

9°
2.7°

2 FROM TYPICAL SOUND SPEED PROFILE FOR CROSS SECTION A-B SHOWN ON FIGURE 4

2



SOUND SPEED PROFILE FOR CROSS SECTION A-B SHOWN ON FIGURE 4

CONFIDENTIAL




FIGURE 3 CORRECTION TO ECHO-SOUNDER DEPTH TO OBTAIN TRUE DEPTH FOR MAY






FIGURE 4 SOUND SPEED (FT/SEC) IN WATER AT BOTTOM AND CONVERGENCE ZONE PROBABILITY OF OCCURRENCE.

"B" MAY

CONFIDENTIAL

CONFIDENTIAL



NORMAL SALINITY CORRECTION FOR THIS AREA AND SEASON IS + 4 FT/SEC

FIGURE 5 SOUND SPEED NOMOGRAM




FIGURE 6 INCLINATION ANGLE VS SOURCE SOUND SPEED AND VERTEXING SOUND SPEED

CONFIDENTIAL

CONFIDENTIAL




FIGURE 7 MEAN HORIZONTAL RANGE VS INITIAL ANGLE AND WATER DEPTH FOR MAY




FIGURE 8 MEAN HORIZONTAL SOUND SPEED VS INITIAL ANGLE AND WATER DEPTH FOR MAY

B MAY

CONFIDENTIAL

CONFIDENTIAL




FIGURE 9 NOMINAL BOTTOM LOSS





FIGURE 10 WAVES FOR APRIL, MAY, AND JUNE
AREA (24°-26°N, 72°-74°W)



SEA CODE	0	1	2	3	4	5	6	7	8	9	TOTAL OBS
SEA HEIGHT (FT)	CALM	<1	1-3	3-5	5-8	8-12	12-20	20-40	\leq 40	CONFUSED	
PERCENT	6.1	21.8	37.0	27.3	6.1	1.8	-	-	-	-	165

SEA TABULATIONS IN PERCENT OF OBSERVATIONS FOR MAY
AREA (24°-26°N, 72°-74°W)

CONFIDENTIAL

"B" MAY

CONFIDENTIAL




FIGURE II BATHYMETRIC PROFILES

CONFIDENTIAL

01 AREA B - ALL MOUNTAINS

CONFIDENTIAL




FIGURE 12 BATHYMETRY

CONFIDENTIAL

CONFIDENTIAL




FIGURE 13 BOTTOM CORE LOCATIONS AND LENGTH OF CORE OBTAINED




FIGURE 14 12-KC NORMAL INCIDENCE BOTTOM LOSS MEASUREMENTS IN db

CONFIDENTIAL

AREA 3 ALL RIGHTS - EXCEPT FEB

CONFIDENTIAL




FIGURE 15 SURFACE SEDIMENT TYPE AND MEDIAN DIAMETER (MICRONS)

"B" MAY ALL MONTHS EXCEPT FEB

CONFIDENTIAL

CONFIDENTIAL

BOTTOM TOPOGRAPHY

The area is situated on the southwest edge of the Hatteras Abyssal Plain where the ocean bottom is flat with a slope of less than 1:1000. Depths in this area range from 2,780 to greater than 2,900 fathoms with a seamount on the southern edge rising to a depth of 2,532 fathoms. Bottom profiles were constructed from data from the USS RHODES in 1961.

The depth profiles, which were recorded in an east-west direction, indicate slope gradients of less than 1 degree. This was determined by generalizing the slopes of several randomly selected profiles. The seamount in the vicinity of 25°07'N, 73°30'W has a slope of greater than 2 degrees. No gradients were determined in the north-south direction because the positions could not be repeated with sufficient precision.

Positions of this survey were obtained with Loran A. These positions have been corrected and adjusted to give a best fit. Position errors average 3 miles, and vary between 1 and 7 miles.

BIOLOGY

During May there is probably less than one whale per 1,000 square miles. Some whale sharks (to 45 feet long) and bluefin tunas (to 10 feet long) may be present, but their concentration is unknown.

B - MAY

CONFIDENTIAL

UNCLASSIFIED
~~CONFIDENTIAL~~

BOTTOM ACOUSTIC PROPERTIES

The cores taken in this area vary in length to a maximum of almost 9 feet and consisted of yellow brown clay interbedded with distinct thin layers of silt and, in some instances, very thin sand layers. The high porosity (70 to 80 %), low density, and fine-grained clay sediment present in this area indicates possible low velocity sediments having a low acoustic impedance. However, increased grain size and density and decreased porosity in the silt layers indicates an increase in the acoustic impedance of these layers. The presence of low velocity and low acoustic impedance sediments generally provides poor reflectivity; however, the presence of silt and sand layers in the short cores and the possible presence of additional silt and sand layers, known to occur in abyssal plain regions, indicates that this area could provide good reflectivity.

The normal incidence 12-kc reflection loss ranges from a low of 10 db to a high of 18 db and shows that anomalously high losses are not found at this high frequency and grazing angle. Assuming that reflection loss decreases with decreasing frequency and grazing angle it would appear, on the basis of 12-kc normal incidence reflection loss and from the core analysis as well as from the accessibility of the area to turbidity currents, that this area would be one of good reflectivity.

UNCLASSIFIED

~~CONFIDENTIAL~~

B ALL 1965