

~~CONFIDENTIAL~~

MOST Project

INFORMAL
MANUSCRIPT
REPORT
NO. 102-65

1

14

NOO-IM-0-102-65

TITLE

Good
LEVEL II

BOTTOM REFLECTION LOSS IN AN AREA IN THE HATTERAS ABYSSAL PLAIN.

AUTHOR

10
ROBERT S. WINOKUR

DATE

11
OCTOBER 1965

12 17p.

DDC
RECEIVED
JUL 16 1979
F

Reproduction of this document in any form by other than naval activities is not authorized except by special approval of the Secretary of the Navy or the Chief of Naval Operations as appropriate.
This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Section 793 and 794. The transmission or revelation of its contents in any manner to an unauthorized person is prohibited by law.

This manuscript has a limited distribution, therefore in citing it in a bibliography, the reference should be followed by the phrase UNPUBLISHED MANUSCRIPT.

DISTRIBUTION STATEMENT A

Approved for public release
Distribution Unlimited

DOWNGRADED AT 3 YEAR INTERVALS;
DECLASSIFIED AFTER 12 YEARS.
DOD DIR 5200.10

MARINE SCIENCES DEPARTMENT
U. S. NAVAL OCEANOGRAPHIC OFFICE
WASHINGTON, D. C. 20390

660720-067

250 450

~~CONFIDENTIAL~~

LB

AD A 071232

DDC FILE COPY

CONFIDENTIAL

ABSTRACT

W

Bottom reflection loss measurements were made along three tracks in a 1 degree quadrangle, designated Area C, extending from 33°00' to 34°00'N and 71°00' to 72°00'W. The area lies along the northwestern edge of the Hatteras Abyssal Plain. Explosive sound sources were used and, based on peak pressure, bottom reflection loss values were computed. Bottom loss at 1 and 3.5 kc for grazing angles between 20 and 60 degrees are reported. The results indicate that the bottom is frequency selective, which is suggested by the frequency crossings or inverse relationship between bottom loss and frequency exhibited by the data along one track. A uniform dependence of bottom loss on grazing angle is not observed.

Accession For	
NTIS GML&I	
DDC TAB	
Unannounced	
Justification <i>Per Letter</i>	
<i>DA FILE</i>	
By _____	
Distribution/	
Availability Codes	
Dist.	Avail and/or special
<i>A</i>	

660720-067

DISTRIBUTION STATEMENT A
Approved for public release;
Distribution Unlimited

CONFIDENTIAL

CONFIDENTIAL

ACKNOWLEDGEMENTS

The author gratefully acknowledges the assistance of Mr. Paul Dunlap for his help in analyzing the field data and Mr. Laurence Breaker and the scientific team he led in collecting the field data.

650720-0067

CONFIDENTIAL

CONFIDENTIAL

TABLE OF CONTENTS

	Page
Introduction	1
Field Procedures	1
Data Reduction and Analysis	1
Discussion of Results	5
Comparison with other Data	8
Conclusion	11
References	13

FIGURES

1 Location of Bottom Reflection Loss Measurements (A, B, C Designate Receiving Ship and Arrow Indicates Direction of Moving Source Ship)	2
2 ALPINE Bottom Reflection Loss vs Grazing Angle (Average of 25 Stations)	4
3 Bottom Reflection Loss vs Grazing Angle Determined by Eq. 1 (Arrow Indicates Direction of Source Ship Relative to Receiving Ship)	6
4 Bottom Reflection Loss vs Grazing Angle Determined by Equations 4 and 5 (Arrow Indicates Direction of Source Ship Relative to Receiving Ship)	9
5 Composite of True Bottom Loss (Figure 4) and ALPINE Average Bottom Loss	10
6 Composite of True Bottom Loss and AMOS Bottom Loss	12

CONFIDENTIAL

CONFIDENTIAL

BOTTOM REFLECTION LOSS IN AN AREA IN THE HATTERAS ABYSSAL AREA

INTRODUCTION

During August 1964, bottom reflection loss data were obtained in the central section of the 1 degree quadrangle, designated Area C, extending from 33°00' to 34°00'N and 71°00' to 72°00'W. The data were collected along three lines at first bottom bounce grazing angles of about 20, 30, and 42 degrees. Mark 50 explosive sound sources were used with the USS WILLIS A LEE acting as the source ship. The USS BRATTLEBORO was used as the receiving ship. Frequency analyses were made at 1 and 3.5 kc and bottom reflection loss values for both first and second bottom reflection angles were determined.

FIELD PROCEDURES

The reflection loss measurements were made along three lines as shown in Figure 1. All measurements were made with the receiving ship lying to at positions A, B, and C as the source ship proceeded along the indicated tracks. At ranges from the receiving ship corresponding to first bottom reflection angles of about 20, 30, and 42 degrees, four or five Mark 50 sound signals were dropped to a detonation depth of 50 feet. Geographic position was determined by Loran-C while the distance between the ships was monitored by radar.

The bottom reflected signals were received by an LC-32 hydrophone at a depth of 50 feet. Signals from the hydrophone were passed through three amplifiers and recorded broad-band on three tracks of a multi-channel magnetic tape recorder. The magnetic tape recordings were made at 7 1/2 inches per second.

DATA REDUCTION AND ANALYSIS

The tape recordings were played back at either 7 1/2 or 1 7/8 inches per second through Allison band pass filters centered at equivalent frequencies of 1 and 3.5 kc in third octave bandwidths. The bottom reflected signals were displayed on a Sanborn logarithmic strip chart recorder.

Bottom reflection loss was determined by first computing the difference between the peak pressure level of the first and second bottom reflection arrivals read on the Sanborn paper tape. That is, the relative amplitude of the bottom-surface-bottom arrival (BSB) was subtracted from the relative amplitude of the first bottom arrival (B). By assuming spherical spreading, straight line ray geometry, and

CONFIDENTIAL

CONFIDENTIAL




FIGURE 1 LOCATION OF BOTTOM REFLECTION LOSS MEASUREMENTS (A, B, C DESIGNATE RECEIVING SHIP AND ARROW INDICATES DIRECTION OF MOVING SOURCE SHIP)

0-102-65

CONFIDENTIAL

CONFIDENTIAL

perfect reflection at the sea surface this difference was then corrected for the difference in path length of the two arrivals. Bottom reflection loss is then given by:

$$B. L. = L_B (\theta_1) - L_{BSB} (\theta_2) - [N_{BSB} - N_B] \quad (1)$$

where: B.L. = bottom reflection loss,
 $L_B (\theta_1)$ = peak level of bottom arrival,
 $L_{BSB} (\theta_2)$ = peak level of bottom-surface-bottom arrival,
 N = propagation loss = $20 \log R + \alpha R$,
 R = slant range in yards,
 σ = $0.0093f^2$ db kyd, and
 f = frequency in kilocycles.

The advantage of this method is that it is independent of source level and system calibration. The main shortcoming of this method is that the grazing angle is not constant for the two arrivals used. Therefore, the computed bottom loss is treated as an apparent bottom loss for the average angle of the two arrivals. The apparent loss determined by using equation 1 is actually the loss at the second grazing angle plus the difference between the loss of the two grazing angles. The apparent loss can be expressed as:

$$\overline{B.L.} = B (\theta_2) + [B (\theta_2) - B (\theta_1)] \quad (2)$$

where: $\overline{B.L.}$ = apparent bottom loss,
 $B (\theta_2)$ = loss at second angle corresponding to BSB arrival, and
 $B (\theta_1)$ = loss at first angle corresponding to B arrival.

It can be seen that the apparent bottom loss values determined by the above method will equal true bottom loss in those areas where bottom loss does not vary with grazing angle. The average bottom loss of 25 locations in Area C, obtained by Alpine Geophysical Associates (1964) for the U. S. Naval Oceanographic Office, indicates that there is no appreciable dependence of bottom loss on grazing angle (Figure 2); however, substantial variations do exist at each location and from location to location. In an attempt to minimize or average the errors present in the computed apparent loss, a second method, based on the results of equation 1, was utilized. In this instance bottom loss can be computed as follows:

$$B. L. = S - N - L \quad (3)$$

where: B. L. = bottom reflection loss,
 S = source level,
 N = propagation loss = $20 \log R + \alpha R$, and
 L = peak level of bottom reflected arrival after system calibrations.

CONFIDENTIAL




FIGURE 2 ALPINE BOTTOM REFLECTION LOSS VS GRAZING ANGLE (AVERAGE OF 25 STATIONS)

CONFIDENTIAL

0-102-65

This equation requires that the source level of the explosive be known or calibrated. Assuming that the average bottom loss in this area is independent of grazing angle, the apparent losses determined by equation 1 can be used in conjunction with equation 3 to yield an apparent source level.

$$\begin{aligned} S_A &= \overline{B. L.} + N_B + L_B \\ S_A &= 2 \overline{B. L.} + N_{BSB} + L_{BSB} \end{aligned} \quad (4)$$

where: S_A = apparent source level and
 $\overline{B. L.}$ = apparent bottom loss determined from equation 1.

A value of S_A , at 1 and 3.5 kc, was computed for each shot and then all values were averaged to arrive at an apparent average source level for each frequency. The average source levels were then used to determine bottom loss values for each B and BSB arrival as follows:

$$\begin{aligned} B. L. (\theta_1) &= \overline{S}_A - N_B - L_B \\ 2B. L. (\theta_2) &= \overline{S}_A - N_{BSB} - L_{BSB} \end{aligned} \quad (5)$$

where: \overline{S}_A = apparent average source level.

For the purposes of this report the bottom loss values determined by the above method will be referred to as true bottom loss.

For comparison purposes a source level, equivalent to 1.8 pounds of TNT for a Mark 50 sound signal, was determined from Weston (1960). The source level, based on Weston, agreed within 3 db of the average source level determined by equation 4. Considering the assumptions made in arriving at the average source level, this agreement is extremely good.

DISCUSSION OF RESULTS

Figure 3 illustrates apparent bottom reflection loss versus grazing angle, as determined by equation 1, along the three tracks. For tracks 4 and 8 at the lower grazing angles the 1 kc losses are greater than the 3.5 kc losses, while at the higher angles a frequency crossing occurs which produces an increase in bottom loss with increasing frequency. Along track 6 the 3.5 kc loss is everywhere about 1 db greater than the 1 kc values. Data collected by Alpine Geophysical Associates (1964) in Area A (36°00' to 37°00'N, 66°00' to 67°00'W) for the U. S. Naval Oceanographic Office exhibit similar frequency crossings; however, it is believed that the results illustrated in Figure 3 do not result from the character of the ocean bottom, but are, in part, a result of the method of analysis employed. The frequency crossings can be partially explained by equation 2 and Table 1. Table 1 is a summary of the bottom loss data

CONFIDENTIAL




FIGURE 3 BOTTOM REFLECTION LOSS VS GRAZING ANGLE DETERMINED BY EQ. 1 (ARROW INDICATES DIRECTION OF SOURCE SHIP RELATIVE TO RECEIVING SHIP)

CONFIDENTIAL

0-102-65

CONFIDENTIAL

TABLE 1
SUMMARY OF BOTTOM LOSS DATA

Track- station	Bottom Angle (θ_1)	True Loss ¹ (db)		BSB Angle (θ_2)	True Loss ¹ (db)		Average Angle	Apparent Loss ² (db)	
		1 kc	3.5 kc		1 kc	3.5 kc		1 kc	3.5 kc
8-1	20°	9.1	15.2	36°	10.1	11.3	28	11.1	9.4
8-2	27	11.2	14.0	45	10.1	12.9	36	8.9	12.0
8-3	42	13.2	14.2	62	11.1	14.2	52	9.9	14.2
8-4	41	12.9	12.8	60	11.4	12.1	50.5	9.8	11.4
8-5	20	11.0	14.0	36	12.3	17.0	28	13.6	6.8
6-1	20	7.2	9.5	37	10.2	11.2	28.5	13.2	14.2
6-2	28	7.2	13.5	47	9.0	12.6	37.5	10.8	12.0
6-3	41	11.2	13.4	60	11.2	13.0	50.5	10.6	12.8
4-1	19	10.2	14.6	34	13.8	11.4	26.5	15.3	11.2
4-2	24	8.2	10.2	41	11.6	12.0	32.5	15.0	13.8
4-3	33	12.9	12.8	53	10.2	12.5	43	7.7	12.2
4-4	43	12.2	14.4	62	10.3	12.7	52.5	8.5	11.0
4-5	42	14.1	11.5	61	10.8	12.7	51.5	7.4	13.8
4-6	27	13.0	8.1	47	11.0	10.0	37	8.9	12.2
4-7	20	9.9	9.7	36	11.0	9.9	28	12.0	10.1

(1) Determined from equations 4 and 5

(2) Determined from equation 1

CONFIDENTIAL

Illustrated in Figures 3 and 4. For example, the frequency crossing at the 32 degree angle of track 4, in Figure 3, can be examined by referring to the computed true losses associated with the bottom and bottom-surface-bottom arrival angles used in determining the apparent loss. Data for station 4-2, in Table 1, show that the 3.5 kc loss values are greater than those for 1 kc; however, by substituting these values in equation 2 we get apparent losses of 13.8 db at 3.5 kc and 15 db at 1 kc and, consequently, a frequency inversion. It is evident that when the true bottom loss is a function of grazing angle the apparent losses arrived at by using equation 1 are either greater than or less than the true values. It then follows that the source levels attained by equation 4 will also be in error; however, by averaging all apparent source levels to arrive at one value, it is assumed that the errors are minimized.

The dependence of true bottom loss on frequency and grazing angle can be seen in Figure 4. Two types of variations can be seen along the individual tracks. The first type involves changes in bottom loss that are not uniform with frequency and results in frequency crossings. This can be seen along track 4 where the 1 kc losses are sometimes higher than the 3.5 kc losses. Tracks 6 and 8 illustrate the expected frequency dependence of increasing bottom loss with increasing frequency illustrated by Marsh and Schulkin (1955) in the results of Project AMOS.

A second type of variation involves changes in bottom loss with grazing angle. A uniform dependence on grazing angle is not observed as 1 to 4 db fluctuations are seen to occur from one grazing angle to the next. In addition, these fluctuations do not equally effect both frequencies.

Since the measurements were made with the source ship opening or closing range on the receiving ship it is not known if the variations in bottom loss as a function of grazing angle are real or if they result from lateral variations in the bottom as the point of reflection changes. No attempt will be made in this report to explain theoretically the results illustrated in Figure 4, but it should be noted that a multi-layered bottom, consisting of sand and silt layers, can produce theoretical frequency crossings. Area C lies within the Hatteras Abyssal Plain and the presence of sand and silt layers in cored sediments in abyssal plain regions has been established by Ericson et al. (1952, 1955).

COMPARISON WITH OTHER DATA

Figure 5 is a comparison of the average Alpine bottom loss for Area C with a composite of the data presented in this report (Figure 4). For 3.5 kc the Alpine average curve appears to be an approximate mean of the composite, while the Alpine 1 kc average appears to be the lower limit of the composite.

CONFIDENTIAL




FIGURE 4 BOTTOM REFLECTION LOSS VS GRAZING ANGLE DETERMINED BY EQUATIONS 4 and 5 (ARROW INDICATES DIRECTION OF SOURCE SHIP RELATIVE TO RECEIVING SHIP)

CONFIDENTIAL

0-102-65

CONFIDENTIAL





FIGURE 5 COMPOSITE OF TRUE BOTTOM LOSS (FIGURE 4) AND ALPINE AVERAGE BOTTOM LOSS

CONFIDENTIAL

0-102-65 FIG 5

CONFIDENTIAL

Although the Alpine average bottom loss does not exhibit an appreciable dependence on grazing angle an examination of their 25 individual stations shows variations in bottom loss similar to those illustrated in this report.

Figure 6 is a comparison of the AMOS bottom loss curve, as modified by Bell (1959), with the composite of Figure 5. For 3.5 kc the AMOS curve shows general agreement at 20 degrees, but everywhere else tends to be about 3 to 4 db higher. The 1 kc AMOS curve appears to form the upper limit of the composite from 20 to 35 degrees and from 35 to 60 degrees the AMOS curve appears to be the mean of the composite.

CONCLUSION

Apparent bottom reflection loss values were computed by a method independent of source level and system calibration. The apparent loss values were used to compute an apparent source level and finally to arrive at true bottom loss. The errors introduced by the method employed appear to be no larger than the errors introduced by assuming a source level.

The data indicate that there are variations in bottom loss from one angle to the next and from track to track. Generally, the results are in overall agreement with the Alpine bottom loss data for this area.

The bottom loss data suggest that the bottom is frequency selective in that the 1 kc loss values can be greater than those for 3.5 kc. This is in contrast to the uniform increase in bottom loss with increasing frequency suggested by the AMOS results.

CONFIDENTIAL





FIGURE 6 COMPOSITE OF TRUE BOTTOM LOSS AND AMOS BOTTOM LOSS

CONFIDENTIAL

0-102-65 FIG 6

~~CONFIDENTIAL~~

REFERENCES

- Alpine Geophysical Associates. 1964 Acoustic and geophysical survey of bottom and subbottom reflectivity Area C. Prepared for U. S. Naval Oceanographic Office under contract N62306-1341, CONFIDENTIAL.
- - - 1964 Acoustic and geophysical survey of bottom and subbottom reflection loss Area A. Prepared for U. S. Naval Oceanographic Office under contract N62306-1442, CONFIDENTIAL.
- Bull, T. G. 1959 A theoretical comparison of the bottom bounce capabilities of AN/SQS-23 versus AN/SQS-26 surface ship sonars. Underwater Sound Laboratory Report 449, CONFIDENTIAL.
- Ericson, D. B., Ewing, M., and B. C. Heezen. 1952 Turbidity currents and sediments in North Atlantic. Bulletin of the American Association of Petroleum Geologists, v. 36, no. 3, pp. 389-511.
- - - and G. Woolin. 1955 Sediment deposition in deep Atlantic. Geological Society of America, Special Paper 62, pp. 205-220.
- Marsh, H. W. and M. Schulkin. 1955 Report on the status of project AMOS. U. S. Navy Underwater Sound Laboratory, Research Report 255, CONFIDENTIAL.
- Weston, D. E. 1960 Underwater explosions as acoustic sources. Proceedings Physical Society of London, v. 76, part 2, pp. 232-249.