# AAE AERONAUTICAL AND ASTRONAUTICAL ENGINEERING DEPARTMENT

AFOSR-TR. 80 -0308

## THE BLAST WAVE FROM DEFLAGRATIVE EXPLOSIONS, AN ACOUSTIC APPROACH

by

Roger A. Strehlow

Approved for public release; distribution unlimited Grant No. AFOSR 77-3336 December 1979 Interim Technical Report

APR 23 1980

Ε

095



3

ADA 0 8378

ENGINEERING EXPERIMENT STATION, COLLEGE OF ENGINEERING, UNIVERSITY OF ILLINOIS, URBANA

#### Conditions of Reproduction

Reproduction, translation, publication, use and disposal in whole or n part by or for the United States Government is permitted. Aeronautical and Astronautical Engineering Department University of Illinois at Urbana-Champaign Technical Report AAE 79-8 UILU-Eng 79 0508

#### Prepared for

Air Force Office of Scientific Research Aerospace Sciences Directorate Bolling Air Force Base, D.C.

### THE BLAST WAVE FROM DEFLAGRATIVE EXPLOSIONS, AN ACOUSTIC APPROACH

by

Roger A. Strehlow

Approved for public release; distribution unlimited Grant No. AFOSR 77-3336 December 1979 Interim Technical Report AFOSR-TR

#### Conditions of Reproduction

Reproduction, translation, publication, use and disposal in whole or in part by or for the United States Government is permitted. AIR FORCE OFFICE OF SCIENTIFIC RESEARCH (AFSC)

NOTICE OF TRANSMITTAL TO DDC This technical report has been reviewed and is approved for public release IAW AFR 190-18 (7b). A. D. BLOSE Technical Information Officer

READ INSTRUCTIONS BEFORE COMPLETING FOR REPORT DOCUMENTATION PAGE REPORT NUMBER 3. RECIPIENT'S CATALOG NUMBER AFOSR, TR. 80 - 0308 400え りのえ TITLE (and Subtitle) TYPE OF RE INTERIM POPT THE BLAST WAVE FROM DEFLAGRATIVE EXPLOSIONS, Jun 78 - 31 May 79, AN ACOUSTIC APPROACH DEMING ODE Tech Report AAE 79-8 CONTRACT OF GRANT NUM AUTHOR(s) MUMBER/A 15 10 AFOSR-77-3336/ ROGER A STREHLOW PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 2309A2 REORMING ORGANIZATION NAME AND ADDRESS UNIVERSITY OF ILLINOIS AT CHAMPAIGN-URBANA 16 U BA A, ILLINOIS 61801 61102F 11. CONTROLLING OFFICE NAME AND ADDRESS REPORT DATE AIR FORCE OFFICE OF SCIENTIFIC RESEARCH/NA Dec **BUILDING 410** HURER OF PAGES BOLLING AFB, DC 20332 25 14. MONITORING AGENCY NAME & ADDRESS(il dillerent from Controlling Office) 15. SECURITY CLASS. (of this report) AAE-19-8, UNCLASSIFIED 154. DECLASSIFICATION/DOWNGRADING SCHEDULE 1 2 IL2-ENG-19-0508 Approved for public release; distribution unlimited 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) AFOSR < 19 } TR-80-0308 18. SUPPLEMENTARY NOTES 19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Acoustics Blast Waves Nonideal Explosions Explosions, nonspherical ABSTRACT (Continue on reverse side if necessary and identify by block number) Simple acoustic source theory has been applied to determine the maximum overpressure obtainable by the deflagration of nonspherical clouds. In three dimensions overpressure is generated not by the rate of energy addition but by the first time derivative of the rate. Because of this, deflagrative combustion of edge-ignited clouds produces markedly less overpressure than central, spherical ignition. Examples are presented for three nonspherical cloud and igniter geometries. The implication is that even high velocity, -> DD 1 JAN 72 1473 EDITION OF I NOV 65 IS OBSOLETE UNCLASSIFIED SECURITY CLASSIFICATION OF THIS PAGE (When Date & مها يهما الما المان المان المحالي المحالي المحالية المحالية المحالية المحالي المحالية المحالية المحالية المحالي

# AFOSR-TR. 80-0808

#### ABSTRACT

Simple acoustic source theory has been applied to determine the maximum overpressure obtainable by the deflagration of nonspherical clouds. In three dimensions overpressure is generated not by the rate of energy addition but by the first time derivative of the rate. Because of this, deflagrative combustion of edge-ignited clouds produces markedly less overpressure than central, spherical ignition. Examples are presented for three nonspherical cloud and igniter geometries. The implication is that even high velocity, subsonic combustion waves cannot produce damaging blast waves and that some type of supersonic combustion or massive flame acceleration is required if a damaging blast wave is to be produced.

Acces	<b>sion</b> For		].
NTIS GRAAI DDC TAB Unsumounced Justification			
By		•	1.
Distri	1	rdes_	
Dist		/or	

#### INTRODUCT ION

The determination of the blast wave produced in free space by the nonspherical combustion of a nonspherical vapor cloud has not been examined in any detail, either analytically or numerically. The problem is important because at the present time spherical theory is being used to estimate the overpressure for clouds of arbitrary shape and no one knows how conservative this approach is. This paper applies simple acoustic source theory to the deflagrative combustion of a few simple free cloud shapes to determine a first cut estimate of the maximum overpressure that one could expect as a function of cloud size and shape.

#### THE SIMPLE ACOUSTIC SOURCE

Stokes<sup>(1)</sup> first showed that a simple source of mass at a point  $\dot{m}(t)$  (Units: Kg/sec) generates a sound wave in three dimensions which has an overpressure which is proportional to  $\ddot{m}(t)$ . Specifically, as Lighthill<sup>(2)</sup> states,

$$P - P_{o} = \ddot{m} \left[ t - \frac{r}{a_{o}} \right] / 4\pi r \qquad (1)$$

where  $t - \frac{r}{a_0}$  replaces t because the wave is propagating away from the source region at the velocity of sound,  $a_0$ . Lighthill also states that at some distance from the source the sound will appear to emanate from a point (i.e., the wave will be very close to spherical) if the quantity  $(\omega r/a_0)^2 \ll 1$ . Here,  $\omega$  is the circular frequency of the source of sound and r is a characteristic radius of the source region. Finally, for a source which has a finite duration  $f\ddot{m}(t)dt = 0$ , and therefore  $f(P-P_0)dt = 0$  in the wave. This means that the acoustic pulse from a source of finite duration must have a negative phase impulse equal to the positive phase impulse. This should be contrasted to the pulse emitted by a finite duration source in a strictly one-dimensional channel. In this case the acoustic overpressure is proportional to  $\dot{m}(t)$  and the overpressure in the pulse is always positive everywhere. <sup>(1)</sup>

Now consider the deflagrative combustion of an unconfined cloud of arbitrary shape. For simple source acoustic behavior the effective rate of mass addition  $\dot{m}(t)$  may be replaced by an effective rate of volume addition multiplied by the initial gas density, that is,  $\dot{m}(t) = \rho_0 \dot{v}(t)$ .

However, for deflagrative combustion

$$\dot{\mathbf{m}}(t) = \rho_0 \dot{\mathbf{v}}(t) = \rho_0 \left( \frac{\mathbf{V}_b - \mathbf{V}_u}{\mathbf{V}_u} \right) \frac{d}{dt} \left( \mathbf{S}_u(t) \cdot \mathbf{A}_f(t) \right)$$
(2)

where  $S_u(t)$  is the effective normal burning velocity,  $\Lambda_f(t)$  is the effective frontal area of the flame and the ratio  $(V_b - V_u)/V_u$  is the new volume produced per unit volume of gas burned at constant pressure. Using the notation of Strehlow <u>et al.</u> <sup>(3)</sup>  $(V_b - V_u)/V_u = \hat{q}/\gamma_0$ . Here,  $\hat{q}$  is an effective dimensionless heat addition. Its relation to the  $\tilde{q}$  of Strehlow <u>et al.</u> is given in Appendix A. Therefore, using the definition of the velocity of sound in an ideal gas and

2

ŧ.:

combining Eqs. (1) and (2) yields

$$\overline{P} = \frac{\hat{q}}{4\pi a_o^2 r} \frac{d}{dt} \left[ S_u(t) \cdot A_f(t) \right]$$

where  $\overline{P}$  is the acoustic overpressure. Equation (3) is a significant relationship. It states that the acoustic overpressure generated by deflagrative combustion in three dimensions is given by the <u>time rate of change</u> of the <u>rate</u> of energy addition rather than the rate of energy addition as it is in strictly one-D flow.

The deflagrative combustion of a cloud generates a sound wave of very low frequency. The period of the sound source in this case is given by  $\tau = 2\pi/\omega$  where  $\tau$  is the burn time. Thus the requirement that the source region is acoustically simple becomes

 $[2\pi (r_m/\tau)/a_o]^2 << 1$ 

where  $r_m$  is a major dimension of the cloud and approximates the distance traversed by the deflagration wave. Even with distortion and motion due to flame propagation  $r/T \approx S_u$  and the simple source requirement becomes  $4\pi^2 M_{Su}^2 \ll 1$ . If the quantity is to be less than 0.1 for no blast wave distortion  $S_u$  will be about 17.5 m/sec before deflagrative behavior produces significant distortion of the blast wave. Even for significantly higher values of  $S_u$  the first effect will be only to distort the shape of the blast wave. Higher overpressures than estimated here will not occur until  $S_u$ becomes quite large. This limitation of the theory has not been quantified as yet.

Ż

#### APPLICATION IN SPHERICAL GEOMETRY

Two classical problems have been treated in spherical geometry. These are the centrally-ignited, constant-velocity flame (3,4) and the Taylor piston problem. (5) For a constant-velocity flame Eq. (3) reduces to the relation

$$\overline{P} = \frac{\hat{q}S_u}{4\pi a_0^2 r} \frac{dA_f}{dt}$$
(4)

where r is the distance from the source to the observer. For a growing spherical flame ball

$$A_f = 4\pi r_f^2$$

and

$$\frac{dr_{f}}{dt} = S_{S} = S_{u} \frac{V_{b}}{V_{u}}$$

Substituting yields

$$\overline{P} = \frac{2\widehat{q}S_{u}^{2}r}{a_{o}^{2}r} \begin{pmatrix} V_{b} \\ V_{u} \end{pmatrix}$$

where the r in the denominator must be equal to or greater than  $r_f$ . If we let it be equal to  $r_f$ , and if we substitute the definition of  $\hat{q}$  given above, we obtain an expression for the acoustic pressure on the unburned side of the flame

$$\overline{P}_{f} = 2\gamma \left(1 - \frac{V_{u}}{V_{b}}\right) \left(\frac{V_{b}}{V_{u}}\right)^{2} M_{Su}^{2}$$
(6)

which is identical to Eq. (19) of Strehlow <u>et al.</u> (3)

If we write  $r_f = S_s t$  for the flame propagation in Eq. (5) and recall that away from the flame t becomes  $\left(t - \frac{r}{a_0}\right)$  Eq. (5) may be written

$$\overline{P} = 2\gamma \left(1 - \frac{V_u}{V_b}\right) \left(\frac{V_b}{V_u}\right)^3 M_{Su}^3 \left(\frac{a_o t}{r} - 1\right)$$
(7)

However, the transformation from a flame to a Taylor spherical piston is

$$M_{p} = \left(1 - \frac{V_{u}}{V_{b}}\right)^{1/3} \frac{V_{u}}{V_{b}} M_{Su}$$

Therefore, Eq. (7) reduces to

$$\overline{P} = 2\gamma_0 M_p^3 \left( \frac{a_0 t}{r} - 1 \right)$$
(8)

where the range on r is  $S_p t < r < a_0 t$ . Equation (8) is identical to the Taylor solution for a spherical piston as  $M_p \neq 0$  (Eq. (13), Strehlow <u>et al.</u><sup>(3)</sup>).

We note that in these equations the rate of flame area growth is proportional to r and the rate of decay of a spherical acoustic pulse is proportional to  $r^{-1}$ . Thus, for the spherical case the acoustic pressure remains constant at the flame front and the wave that is generated during flame motion is self-similar in r/t. This is a fundamental acoustic property of a constant-velocity flame that is completely surrounded by combustible material when it burns. It has been verified by numerous theoretical and numerical investigations. <sup>(3,4)</sup>

#### APPLICATION TO FREE CLOUDS

We restrict ourselves to clouds of arbitrary shape in free space. To simplify the treatment, we will consider free clouds which have a horizontal plane of symmetry for cloud shape, cloud distortion during deflagration and deflagration wave shape. Since we now wish to simply examine the implications of Eq. (3) for general geometries, we for the moment restrict ourselves to considering only constant velocity flames. This means that Eq. (3) reduces to Eq. (4) where  $S_u$  is an effective normal burning velocity and r is the distance of an observer from the cloud center.

In general the evaluation of the  $dA_f/dt$  term in Eq. (4) is complicated because during deflagrative combustion the cloud ahead of the flame will move and distort with time. This distortion will cause  $A_f$  to be a different function of time than that calculated from purely geometric considerations using a constant velocity flame propagating through a stationary cloud.

In order to determine how to best approximate the effect of such distortion for arbitrary ignition of an arbitrary cloud one must first examine flow behavior in two simple limit geometries; strictly one-dimensional flow caused by deflagration and volumetric heat addition in three dimensions.

The wave diagram for a strictly one-D flow driven by a constant-velocity deflagration wave is shown in Fig. 1. If we model the combustion of a stoichiometric methane-air mixture as proposed in Strehlow et al.,  $^{(3)}$  the gas to the right of the flame and to the

left of the contact surface (regions 0, 1 & 3) can be assumed to have a heat capacity ratio  $\gamma_0 = \gamma_1 = \gamma_3 = 1.4$ , while the gas in region 2 has a  $\gamma_2 = 1.202$ . Additionally, the effective value of dimensionless energy addition is  $\tilde{q} = 8.430$ . This means (from Appendix A) that  $\hat{q} = 9.242$  and that  $V_b/V_u = 7.602$  for constant pressure combustion. Furthermore, for this system the Chapman-Jouguet deflagration Mach number is 0.16631.

The properties of the wave system of Fig. 1 were calculated using the shock relationships from Liepman and Roshko<sup>(6)</sup> for the shocks S<sub>1</sub> and S<sub>3</sub>, the deflagration relationship from Strehlow <u>et</u> <u>al.</u><sup>(3)</sup> for the flame and the contact surface requirement that  $U_{p_2} = U_{p_3}$  and  $P_2 = P_3$ . The results of this calculation that are important to this paper are summarized in Fig. 2.

Figure 2 shows that particle velocities generated by flame propagation are relatively high and that the apparent flame speed relative to an observer is from 4.3 to 9.3 times the actual normal burning velocity. Also it is less than the space velocity of a spherical flame if the one-dimensional flame is traveling at less than about 0.9 of its maximum (CJ) velocity. Furthermore, the ratio  $|U_{p_3}/U_{p_1}|$  lies between 1.0 and 1.4 in this same velocity range. This last observation simply means that even relatively high speed flame propagation from a free surface in one-dimensional space displaces the gas rather uniformly to the front and back. This is to be contrasted to the behavior of a one-dimensional CJ detonation, which displaces the gas primarily in the direction of detonation propagation.

We now wish to determine what happens if we relax the confinement normal to the flame propagation direction for the case of deflagrative combustion. To estimate this effect we assume that if energy is added relatively slowly to a gaseous volume, the volume will expand an equal <u>distance</u> in all directions. During flame propagation through a cloud the flame can be assumed to be a relatively thin sheet of energy addition when compared to the cloud dimensions. In other words the flame can be assumed to occupy a volume AAL when  $\Delta L \ll \sqrt{A}$ . Under these circumstances one would expect the major expansion to occur in a direction normal to the local orientation of the flame even though the pressure is propagating almost equally in all three dimensions.

This assumption has been qualitatively verified experimentally by observing flame propagation in a propane-air elongated pancake cloud above a flat plate of about 50 mm height and 0.6 m x 0.3 m, edge ignited at the center of the 0.3 m edge.  $(^{7})$  The flame's apparent propagation speed was about 3.5 times the normal burning velocity, and its luminous height was about equal to the initial cloud height. Furthermore the flame flashed to encompass an area considerably larger than the original lateral extent of the cloud. The assumption has also been reasonably well verified by numerical calculations made by Dr. Len Hazelman<sup>(8)</sup> at Lawrence Livermore Laboratories using a 2 D hydrocode. He calculated flow and flame propagation in an open 2 D channel. His calculations yielded a flame height almost twice the initial cloud height and an

apparent flame speed about three times the normal burning velocity. However, his numerical flame had a thickness only one-third of the cloud height and this should lead to more vertical distortion.

These results indicate that for any arbitrary free cloud and igniter geometry in which the flame is not completely surrounded by a combustible mixture one may make the following conservative assumptions about flame-induced distortion.

1. The burning velocity that should be used is  $S_u$ . This is because, irrespective of the motion of the flame induced by the flow, the entire cloud will burn in a time,  $\tau$ , given by  $S_u \tau = r_m$  where  $r_m$ is the distance from the igniter to the farthest point in the initially quiescent cloud.

2. The increase of flame area in a free cloud due to distortion of the cloud by flame-induced flow will never exceed the value  $V_b/V_u$  calculated for isoboric combustion. This is because this is the value of distortion of the unburned material produced during combustion of a completely surrounded (spherical) flame, and relief due to product gas motion away from the flame can only reduce this factor.

Thus the general procedure for determining a first conservative approximation to the effect of cloud shape and igniter location on the overpressure-time behavior in the blast wave when the igniter is not completely surrounded by the cloud is as follows:

1. Assume a value of  $S_{\mu}$ .

- 2. Assume a cloud geometry and igniter location.
- 3. Calculate  $dA_f/dt$  for a flame traveling at velocity S<sub>11</sub> through the quiescent cloud.
- 4. Correct for distortion by multiplying by  $V_b/V_u$ .

#### Examples for Specific Geometries

a. Central (line) ignition of a pancake cloud.

The flame area is given by

$$A_f = 2\pi r_f H$$

where  $r_f$  is the flame radius and H is the height of the pancake. Therefore

$$\frac{dA_{f}}{dt} = 2\pi H \frac{dr_{f}}{dt} = 2\pi H S_{u}$$

and

$$\overline{P}_{max} = \frac{\widehat{q}S_{u}^{2}H}{2a_{o}^{2}R_{obs}} \begin{bmatrix} V_{b} \\ V_{u} \end{bmatrix}$$
(9)

where  $R_{obs}$  is the distance of an observer from the center of the cloud.

b. Edge (line) ignition of a pancake cloud.

The area of a flame propagating from an edge of a cloud of radius R is given in terms of the distance propagated by the formula

$$A_{f} = 2Hr_{f} \cos^{-1} \frac{r_{f}}{2R}$$

Now

$$\frac{dA_{f}}{dt} = \frac{dA_{f}}{dr_{f}} \cdot \frac{dr_{f}}{dt} = \frac{dA_{f}}{dr_{f}} \cdot S_{u}$$

Therefore

$$\overline{P} = \frac{\widehat{q}S^{2}H}{2\pi a_{o}^{2}r} \left[ \cos^{-1}\frac{r}{2R} - \frac{\frac{r}{2R}}{\sqrt{1 - \left(\frac{r}{2R}\right)^{2}}} \right] \left[ \frac{V_{b}}{V_{u}} \right]$$

or

$$\overline{P}_{max} = \frac{\widehat{q}S_{u}^{2}H}{4a_{o}^{2}R_{obs}} \begin{pmatrix} V_{b} \\ \overline{V}_{u} \end{pmatrix}$$
(10)

which is exactly half that predicted for a centrally-ignited pancake.

c. End (point) ignition of an ellipsoid (cigar-shaped) cloud.

Assume a flat flame of location  $r_f$  propagates from one end of a long cloud with a minor radius of rotation d and major radius b.

Flame area is therefore

$$A_{f} = \pi d^{2} \left[ 1 - \frac{r_{f}^{2}}{b^{2}} \right]$$

or

$${}^{\mathrm{dA}}\mathrm{f} = -2\pi\mathrm{r}_{\mathrm{f}} \frac{\mathrm{d}^2}{\mathrm{b}^2}$$

Now let

 $-b = -L/2 \leq r \leq L/2 = b$  and D = 2d

where L is the length of the ellipsoid.

Therefore

$$\overline{P} = \frac{-\hat{q}S_u^2D^2}{2a_o^2rL^2}r_f\left(\frac{V_b}{V_u}\right)$$

and

$$\overline{P}_{\max} = \frac{\widehat{q}S_{u}^{2}}{4a_{o}^{2}} \cdot \frac{D}{R_{obs}} \cdot \frac{D}{L} \begin{pmatrix} V_{b} \\ \overline{V}_{u} \end{pmatrix}$$
(11)

Now assume that  $\hat{q}$ ,  $S_u$ ,  $a_o$  and  $(V_b/V_u)$  are independent of cloud shape and that the observer is at a fixed distance from the center of a cloud of fixed volume but of these different shapes. Call the volumes  $V_s = V_p = V_c$ , where the subscripts s, p and c refer to spherical, pancake and cigar shaped clouds, respectively. Also define the aspect ratio of the cloud  $\mathcal{R}$  as  $\mathcal{R}_p = 2\mathcal{R}_p/\mathcal{H}_p$  and  $\mathcal{R}_c = D_c/L_c$ . Using this notation we obtain

$$H_{p} = D \sqrt[3]{\frac{2}{3 R^{2}}}$$
 (12)

and

$$D_{c} = \frac{D_{s}}{\sqrt{R}}$$
(13)

Combining Eqs. (5), (9), (10) and (11) with Eqs. (12) and (13) yields

$$\frac{\overline{P}}{\overline{P}}_{s}_{max} = \frac{1}{\left[12\left(\frac{\hat{q}}{\gamma_{0}} + 1\right)\mathcal{A}^{2}\right]^{1/3}}$$
(14)

and

$$\frac{\overline{P}_{c}}{\overline{P}_{s}}_{max} = \left[\frac{2}{3\left(\frac{\overline{q}}{\gamma_{o}} + 1\right)}\right]^{1/3}$$
(15)

where the factor  $\frac{\hat{q}}{\gamma_0} + 1 = V_b/V_u$  arises because we are considering the initial cloud diameter and Eq. (5) is written in terms of the final radius. Eq. (14) is for central-line ignition of a pancake: for edge-line ignition  $(\overline{P}_c/\overline{P}_s)_{max}$  is one half of this value.

Figure 3 is a plot of Eqs. (13) and (14). It shows that the deflagration, after edge ignition of a large aspect-ratio cloud, produces much lower overpressures than central ignition of a spherical cloud. It should be pointed out that point ignition of the edge of a free spherical cloud  $\mathcal{R}_c = 1$  would yield a higher overpressure than calculated with Eq. (14) because the derivation of Eq. (11) assumed a flat flame. In reality one would expect a flame of roughly spherical shape to propagate away from a point source and the initial rate of flame area increase would be larger in this case than for a flat flame.

#### EFFECT OF CLOUD SIZE

Equation (3) can be used to give an order of magnitude estimate of flame areas and accelerations that are necessary for a deflagration to produce a damaging blast wave. If we define the threshold of damage to be 0.1 Bar and assume that this level of overpressure is to be produced 100 m from the cloud center in an atmosphere with a velocity of sound of 350 m/s, Eq. (3) reduces to

1.6 x 10<sup>7</sup> = 
$$A_f \frac{dS_u}{dt} + S_u \frac{dA_f}{dt}$$
 (16)

Table I was constructed from Eq. (16) under the two limit assumptions that (1)  $dS_u/dt = 0$  and (2)  $dA_f/dt = 0$ .

(1) $dS_u/dt = 0$		(2) $dA_f/dt = 0$	
S <sub>u</sub> , m/s	$\frac{dA_f}{dt}$ , $m^2/s$	A <sub>f</sub> , m <sup>2</sup>	$\frac{dS}{dt}, m/s^2$
1	1.7 x 10 <sup>7</sup>	100	$1.7 \times 10^{5}$
10	$1.7 \times 10^{6}$	10,000	$1.7 \times 10^3$
100	1.7 x 10 <sup>5</sup>	1,000,000	17

T/	<b>BLE</b>	I
		- 4

Notice from Table I that even for very high flame velocities the rate of flame area increase must also be very high if even a weak blast wave is to be generated. On the other hand, only extremely large initial flame areas, exhibiting very large flame acceleration over their entire frontal area are necessary to produce a weak blast wave from deflagrative combustion. Both of these observations imply that extremely large clouds are required if one is to produce significant overpressure by deflagrative combustion alone.

14

W)

#### DISCUSSION AND CONCLUSIONS

The application of simple source acoustic theory to deflagrative combustion of an unconfined cloud shows that:

1) It is very difficult to produce a damaging blast wave by deflagrative combustion once the flame is not completely surrounded by a combustible mixture.

2) The maximum overpressure produced, other circumstances being equal, is proportional to the ratio of the minor dimension of the cloud to the distance to the observer.

3) Blast pressure is rather uniformly distributed in all directions, i.e., the blast is roughly spherical.

4) The cloud must be very large if a damaging blast wave is to be produced.

5) Spherical flame propagation calculations such as those of Kuhl <u>et al.</u> and Strehlow <u>et al.</u> greatly overestimate blast pressures from deflagrative combustion following edge ignition of clouds with large aspect ratios.

From various accident accounts of the sequence of events that led to the production of a damaging blast wave after delayed ignition of a massive spill of combustible material it appears that:

1. There is a threshold spill size below which blast damage does not occur. Gugan's <sup>(9)</sup> documentation of incidents shows that blast damage has been observed for spills of less than 2000 Kg but more than 100 Kg only for the fuels  $H_2$ ,  $H_2$ -CO mixture,  $CH_4$  and  $C_2H_4$ . Blast damage has been recorded only for spills greater than

2000 Kg for all other fuels.

2. In the majority of cases where blast damage occurred, fire was present for a considerable period before the blast occurred.

3. In many cases damage is highly directional.

These observations when coupled with the results of simple source acoustic theory for deflagrative combustion lead to the following conclusions.

1. There should be a size threshold below which blast will not occur as long as ignition is "soft", i.e., does not directly trigger detonation.

2. The fact that fire is present early after ignition indicates that massive flame accelerations are necessary to lead to blast wave formation. Since the flame must have burned through the cloud edge by the time the blast is produced, simple acoustic source theory must be operative for even high deflagration velocities. Thus, the blast must arise from some sort of effectively supersonic combustion process or from <u>very</u> rapid increases in effective surface area of the flame.

3. Simple acoustic source theory for deflagrative combustion shows that deflagrative processes per se cannot produce highly directional effects. However, it is well known that detonative combustion of a cloud does produce highly directional blast wave effects.

Literature cited

٢

- 1. Stokes, Phil. Mag. XXXIV, Ser. 3, p. 52.
- Lighthill, J., <u>Waves in Fluids</u>, Chapter 1, Cambridge Univ.
   Press, Cambridge (1978).
- Strehlow, R. A., Luckritz, R. T., Adamczyk, A. A., and Shimpi,
   S. A., "The Blast Wave Generated by Spherical Flames", Combustion and Flame 35, 297-310 (1979).
- Kuhl, A. L., Kamel, M. M., and Oppenheim, A. K., <u>Fourteenth</u> <u>Symposium (International) on Combustion</u>, The Combustion Institute, Pittsburgh, 1973, pp. 1201-1215.
- 5. Taylor, G. I., Proc. Roy. Soc. A 186, 273-292 (1946).
- Liepman, H. W. and Roshko, A., <u>Elements of Gas Dynamics</u>, Chapter 3, p. 62, Wiley, New York, (1957).
- 7. Huseman, P., Private communication, Urbana, IL (1979).
- 8. Hazelman, L., Private communication, Livermore, CA (1979).
- 9. Gugan, K., Unconfined Vapour Cloud Explosions, The Institute of Chemical Engineers, London (1979), pp. 28-35, 39.

#### ACKNOWLEDGMENTS

The author wishes to thank Dr. Len Hazelman of Lawrence Livermore Laboratory, Livermore, California, for performing some 2 D hydrocode calculations. He also wishes to thank Mr. Peter Huseman for performing a few critical experiments and Dr. Harold O. Barthel for a number of helpful discussions.

This work was supported by Arthur D. Little, Inc. and by AFOSR Grant 77-3336, Dr. B. T. Wolfson, Technical Monitor.

#### APPENDIX A

#### THE GENERALIZED HEAT ADDITION HUGONIOT

Strehlow <u>et al</u>.<sup>(3)</sup> have shown that a generalized heat addition Hugoniot quite accurately fits the real Hugoniot for hydrocarbonair combustion over the range of interest for vapor cloud explosions. Briefly they assume that

$$H_o = C_p T_o$$

and

$$h_1 = C_{p_1} T - \tilde{Q}$$

where  $\tilde{Q}$  is the energy added at the deflagrative/detonative discontinuity and C and C are different heat capacities for the re- $P_0$   $P_1$  active and product gases respectively.

Using this approach they define a dimensionless energy addition as

$$\tilde{q} = (\gamma_1 - 1)\tilde{Q}/P_0 V_0$$

Thus the volume change for constant pressure combustion is given by the expression

$$\frac{V_{b}}{V_{u}} = \frac{\gamma_{o}(\gamma_{1}^{-1})}{\gamma_{1}(\gamma_{o}^{-1})} + \frac{\tilde{q}}{\gamma_{1}}$$

therefore

$$\frac{V_b - V_u}{V_u} = \frac{(\gamma_1 - \gamma_o)}{\gamma_1(\gamma_o^{-1})} + \frac{\tilde{q}}{\gamma_1}$$

Now define

for ease of nondimensionlizing the acoustic problem. This yields

$$\hat{q} = \frac{\gamma_o(\gamma_1 - \gamma_o)}{\gamma_1(\gamma_o^{-1})} + \frac{\gamma_o}{\gamma_1} \tilde{q}$$

For stoichiometric methane-air mixtures<sup>(3)</sup>

$$\gamma_0 = 1.4$$
  $\gamma_1 = 1.202$  and  $\tilde{q} = 8.430$ 

Therefore

$$\frac{V_b - V_u}{V_u} = \frac{\hat{q}}{\gamma_o} = 6.6015$$

Thus

and

وسيطو كالمعاط عطاقا بالمتحاط والمتحاط المراجع التلامات

$$\frac{v_b}{v_u} = 7.6015$$

for a stoichiometric methane cloud.

20





•



Figure 2. Flow velocities and apparent speeds associated with the strictly one-dimensional deflagration combustion illustrated in Figure 1.



