

AD-A089 112

HARRY DIAMOND LABS ADELPHI MD
NUCLEAR RADIATION EFFECTS DATA ON LARGE SCALE INTEGRATED CIRCUITS--ETC(U)
JUL 80 R POLINADEI, H EISEN, K PINERO
HDL-DS-80-1


F/G 9/5

NL

UNCLASSIFIED

1 of 1
All
Access

END
DATE
FILMED
10-80
DTIC



HDL-DS-80-1 ✓
July 1980

AD A089112

LEVEL II


2

Nuclear Radiation Effects Data on Large Scale Integrated Circuits

by Roland Polimadei, Harvey Eisen,
and Kelvin Pinero

DTIC
ELECTE
SEP 11 1980

E



U.S. Army Electronics Research
and Development Command
Harry Diamond Laboratories
Adelphi, MD 20783

Approved for public release; distribution unlimited.

2098021

DDC FILE COPY

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM	
1. REPORT NUMBER HDL-DS-88-1	2. GOVT ACCESSION NO. D-AC89 112	3. RECIPIENT'S CATALOG NUMBER	
4. TITLE (and Subtitle) Nuclear Radiation Effects Data on Large Scale Integrated Circuits		5. TYPE OF REPORT & PERIOD COVERED Data Summary	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR Roland Pollimadei / Harvey Eisen and Kelvin Pinciro	8. CONTRACT OR GRANT NUMBER(s) DA Proj 11162129AH25		
9. PERFORMING ORGANIZATION NAME AND ADDRESS Harry Diamond Laboratories 2800 Powder Mill Road Adelphi, MD 20783		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Prog. El.: 6.21.20.A	
11. CONTROLLING OFFICE NAME AND ADDRESS U.S. Army Materiel Development and Readiness Command Alexandria, VA 22333		12. REPORT DATE July 1980	
13. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13a. DATE OF MONITORING 88	
14. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		15. SECURITY CLASS. (of this report) UNCLASSIFIED	16. DECLASSIFICATION/DOWNGRADING SCHEDULE
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)			
18. SUPPLEMENTARY NOTES HDL Project: X75086 DRCMS Code: 612120H250011			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Nuclear radiation effects Integrated circuits LSI Large scale integrated circuits			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This summary tabulates nuclear radiation effects on large scale integrated circuits. This reference can help engineers select components for systems that must survive a given radiation level or evaluate the radiation hardness of previously designed systems. The tables list microprocessors, random access memories, read only memories, programmable read only memories, shift registers, and miscellaneous devices. The data came from government, industry, and IEEE Nuclear and Space Radiation Effects Conference reports.			

DO FORM 1 JAN 79

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

024

11-1-80

FOREWORD

This summary tabulates nuclear radiation effects data on large scale integrated (LSI) circuits. It is intended to be a handy reference to help engineers select components for systems that must survive a given radiation level or evaluate the radiation hardness of previously designed systems. Most of the data in this report were compiled from papers presented at the Annual IEEE Conference on Nuclear and Space Radiation Effects (1971 through 1979). The remainder came from a variety of government and industry reports.

Due to the complexity of testing procedures of LSI devices and the space constraints of a tabular format, not all pertinent data can be presented in this summary. We have attempted to give most of the data needed for assessing the hardness of a given component. The balance of the information can be found in the references. X

This summary is divided into an index, six tables of device data, and the references. The index lists the devices in numerical order and cites the tables in which they are listed. The six tables are microprocessors (μ P's), random access memories (RAM's), read only memories (ROM's), programmable read only memories (PROM's), shift registers, and miscellaneous devices. Within each table, the devices are arranged numerically. In addition, the μ P and RAM tables are subdivided by technology: transistor-transistor logic (TTL), integrated injection logic (I^2L), N-channel metal oxide semiconductor (NMOS), and complementary metal oxide semiconductor (CMOS).

The device technology and the radiation source are described. The number of samples (Smpl size) tested in that radiation source and the results are given next. Because of the complexity of LSI devices, most investigators make functional rather than parametric measurements. For that reason, the results are most often stated here as "functional failure." This is the radiation level at which the first failures (such as loss of stored data, incorrect processing of data, or failure to respond to a command) occurred in the samples tested. When a range of radiation levels is available for the samples tested, that range is given. The terms "transient upset" and "permanent upset" also are used. "Transient upset" means the radiation level at which there was a transient output signal possibly large enough to look like a change of state. "Permanent upset" means the radiation level at which there was a permanent change in some stored data resulting in an incorrect output. Thus, "permanent upset" does not mean that the device was no longer able to function; it means only that some state was changed and had to be reset before correct outputs could be obtained. The seventh column gives the test conditions (such as bias during irradiation or time between irradiation and measurement) and any other pertinent information. The last column lists published (numbered) and unpublished (symbol) references.

We plan to update this compilation. Please put us on your distribution list for pertinent reports or reprints. Please send reports, data, and comments to Harvey Eisen, U.S. Army ERADCOM Harry Diamond Laboratories, 2800 Powder Mill Road, Adelphi, MD 20783.

CONTENTS

	Page
FOREWORD.....	3
INDEX.....	7

TABLES

1a	CMOS μ P's.....	9
1b	NMOS μ P's.....	13
1c	TTL μ P's.....	20
1d	I ² L μ P's.....	25
2a	CMOS RAM's.....	29
2b	NMOS RAM's.....	46
2c	TTL RAM's.....	54
2d	PMOS RAM's.....	58
2e	I ² L RAM's.....	59
2f	NMOS RAM's.....	60
3	ROM's.....	62
4	PROM's.....	63
5	Shift Registers.....	66
6	Miscellaneous Devices.....	69
REFERENCES.....		74
SYMBOLS.....		77
DISTRIBUTION.....		79

ACCESSION for	
NTUS	White Section ☒
DDC	Buff Section ☐
UNANNOUNCED	☐
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	AVAIL. and/or SPECIAL
A	-

PROCESSING PAGE BLANK-NOT FILMED

INDEX

Generic No.	Family	Table	Generic No.	Family	Table
8	NMOS μ P	1b	2901	TTL μ P	1c
010	CMOS μ P	1a	2909	TTL microprogram sequencer	6
54C200	CMOS RAM	2a	2910	TTL microprogram controller	6
54S181	Arithmetic logic unit	6	3000	Microcomputer system	6
074	CMOS μ P	1a	3001	Microprogram control unit	6
74C200	CMOS RAM	2a	3002	TTL μ P	1c
74C920	CMOS RAM	2a	3003	MOS shift register	5
74C929	CMOS RAM	2a	3003	Look-ahead carrier generator	6
74S481	TTL μ P	1c	3101	TTL RAM	2c
82S11	TTL RAM	2c	3300	PMOS shift register	5
82S100	Field prog. logic array	6	3303	PMOS shift register	5
100	I ² L μ P	1d	3400	MNOS PROM (EAROM)	4
0400	I ² L μ P	1d	3601	TTL PROM	4
410	NMOS RAM	2b	3624	TTL PROM	4
416	NMOS RAM	2b	4027	NMOS RAM	2b
1101	PMOS RAM	2d	4030	NMOS RAM	2b
1402	PMOS shift register	5	4035	NMOS RAM	2b
1406	PMOS shift register	5	4050	NMOS RAM	2b
1802	CMOS μ P	1a	4060	NMOS RAM	2b
1821	CMOS RAM	2a	4061	CMOS RAM	2a
1822	CMOS RAM	2a	4096	NMOS RAM	2b
1833	CMOS ROM	3	4102	NMOS RAM	2b
2001	TTL shift register	5	4104	NMOS RAM	2b
2102	NMOS RAM	2b	4116	NMOS RAM	2b
2107	NMOS RAM	2b	4200	NMOS RAM	2b
2114	NMOS RAM	2b	4512	CMOS data selector	6
2116	NMOS RAM	2b	5001	CMOS RAM	2a
2147	NMOS RAM	2b	5101	CMOS RAM	2a
2222	CMOS RAM	2a	5501	CMOS RAM	2a
2256	MNOS RAM	2f	5533	TTL RAM	2c
2812	PMOS shift register	5	5625	TTL ROM	3

INDEX (Cont'd)

<u>Generic No.</u>	<u>Family</u>	<u>Table</u>
6312	CMOS ROM	3
6340	TTL PROM	4
6402	Univ. asynch. rec.-trans.	6
6504	CMOS RAM	2a
6508	CMOS RAM	2a
6518	CMOS RAM	2a
6604	NMOS RAM	2b
6605	NMOS RAM	2b
6701	TTL μ P	1c
6800	NMOS μ P	1b
7040	NMOS PROM (EAROM)	4
8008	NMOS μ P	1b
8080	NMOS μ P	1b
8085	NMOS μ P	1b
8228	TTL ROM	3
9060	NMOS RAM	2b
9080	NMOS μ P	1b
9102	NMOS RAM	2b
9140	NMOS RAM	2b
9404	Microprogram sequencer	6
9408	I ² L μ P	6
9900	I ² L μ P	1d
14512	CMOS data selector	6
14559	CMOS succ. approx. register	6
93425	TTL RAM	2c
93481	I ² L RAM	2e
4K RAM	NMOS RAM	2b

TABLE 1a. CMOS μ P'S

Device No.	Technology	Mfr	Smpl size	Radiation source	Results	Test conditions and comments	Ref
TCS010	Si-gate SOS 8-bit CPU	RCA	6	LINAC 50 ns pulse	Transient upset: 5×10^9 rad(Si)/s	Test performed was "register" to "data-in" addition, with fixed input word of alternating ones and zeros. Test began within 30 s after end of irradiation.	1
			6	^{60}Co 5 rad(Si)/s	Functional failure: 2.2×10^4 rad(Si)	Failure to operate.	
TCS074	Si-gate SOS 8-bit CPU	RCA	4	LINAC 40 ns pulse	Transient upset: 8.8×10^9 rad(Si)/s	Test performed was "register" to "data-in" addition, with fixed input word of alternating ones and zeros.	1
			2	1 μ s pulse	2.4×10^9 rad(Si)/s	Test began within 30 s after end of irradiation.	
			4	^{60}Co 5 rad(Si)/s	Dose: 4.9×10^3 rad(Si)	Output voltage decreased by 5%.	
					1.3×10^4 rad(Si)	Would not operate.	
1802	Si-gate Bulk 8-bit CPU	RCA	3	^{60}Co 13 to 180 rad (Si)/s	Functional failure: $V_{DD} = 5$ V. All signal and control inputs were connected to logic one or logic zero. Devices were tested after irradiation by placement into development system. (3.7 to 6.5×10^3 rad(Si)		2
			1		3.5×10^4 rad(Si)	Unbiased. Tested as above.	

TABLE 1a. CMOS μ P'S (Cont'd)

Device No.	Technology	Mfr size	Radiation source	Results	Test conditions and comments	Ref
1802	Si-gate Bulk 8-bit CPU	HUG	^{60}Co		During irradiation, devices were biased clocked, or executing program as noted.	3
				Functional failure: 8×10^3 rad(Si)	Executing program, $V_{DD} = 5$ V. Clock = 100 kHz.	
				(0.8 to 1.5×10^4 rad(Si)	Clocked at 1 MHz and cleared every 400 μ s, or executing program. $V_{DD} = 5$ V.	
				1.2×10^4 rad(Si)	Developmental SOS, $V_{DD} = 5$ V, executing program.	
				7×10^3 rad(Si)	Clock = 1 MHz or 10 Vdc. Cleared every 400 μ s. $V_{DD} = 10$ V.	
1802DK	Si-gate Bulk 8-bit CPU	RCA	^{60}Co	(2 to 5×10^5 rad(Si)	Specially hardened, $V_{DD} = 5$ V; clocked at 1 MHz and cleared every 400 μ s or registers initialized and μ P executing program.	4
				Functional failure: 7×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 10$ V. All devices were cleared periodically, and either 1 MHz 10 V square wave or 10 Vdc was applied at clock input.	
CDP1802CD	Si-gate Bulk 8-bit CPU	RCA	Flash x-ray 3 ns pulse		Devices were monitored for latchup while being irradiated. Control lines and input and output flags were alternately tied to V_{DD} and then to ground. Biased in static state; $V_{CC} = 5$ V and 10 V.	5

CDP1802CD CDP1802D	Si-gate Bulk 8-bit CPU	RCA	LINAC 10 MeV 18 ns pulse	1	Latchup: Observed at $\sim 1.6 \times 10^9$ rad(Si)/s Total dose: 5 rad(Si)	During irradiation, devices were biased at $V_{CC} = 10$ V. Latchup was not observed for $V_{CC} = 5$ V.	*
					Transient upset: 1.2×10^8 rad(Si)/s	During irradiation, devices were biased at $V_{DD} = 5$ V. Devices were exercised by RCA COSMAC evaluation kit.	
					(0.98 to 1.1×10^8 rad(Si)/s	Static mode program during irradiation.	
					Latchup: (2.3 to 3×10^8 rad(Si)/s	Latchup current = 400 mA. Static mode program during irradiation.	
					Failure: (1.5 to 2×10^4 rad(Si)	Static mode program during irradiation. Full recovery after annealing several hours at 125°C .	
CDP1802CD	Si-gate Bulk 8-bit CPU	RCA	^{60}Co 5 rad(Si)/s	2		During irradiation, devices were operated at $V_{DD} = 10$ V and clocked at 10 V, 2.3 MHz. Functional test is simple addition, and results are compared with known programmed data.	1
						Functional failure: Failure to add. Supply current 9.4×10^3 rad(Si) I_{DD} doubled.	

TABLE 1a. CMOS μ P'S (Cont'd)

Device No.	Technology	Mfr size	Smpl size	Radiation source	Results	Test conditions and comments	Ref
CDP1802D-21	Si-gate Bulk 8-bit CPU	RCA				During irradiation, devices were at nominal bias and performing programmed routines consisting of many different types of instructions. All devices were from single diffusion lot.	†
5	⁶⁰ Co				Functional failure: 8.9×10 ³ rad(Si)/s	Failure to execute instruction set. Devices were tested during irradiation.	
18	LINAC			150 ns pulse 37 MeV	Functional failure: 1.8×10 ⁴ rad(Si)	Total dose accumulated in single pulse. LINAC pulse was triggered at same instant as initiation of instruction set routine. Testing was initiated within 54 μ s after LINAC pulse trigger and completed in next 100 ms.	
					Latchup: 19 rad(Si) 1.2×10 ⁸ rad(Si)/s		
7	LINAC			1 μ s pulse 37 MeV	Functional failure: 2.5×10 ⁴ rad(Si)	(Same as above.)	

TABLE 1b. NMOS μ P'S

Device No.	Technology	Mfr size	Smpl size	Radiation source	Results	Test conditions and comments	Ref
F-8	CPU	MOS	10	60 Co	Functional failure: inability to function or respond to command. 1.7×10^3 rad(Si)	Failure criterion: inability to function or respond to command. Devices were kept in dry ice between irradiation and measurement.	6
F-8	PSU	MOS	10	60 Co	1.7×10^3 rad(Si)	$V_{DD} = 5\text{ V. } V_{GG} = 12\text{ V.}$	
F-8	CPU (3850)	FAI	10	60 Co	1.7×10^3 rad(Si)	$V_{DD} = 5\text{ V. } V_{GG} = 12\text{ V.}$	
			10	60 Co	No failure at 1×10^4 rad(Si)	Unbiased.	
F-8	PSU (3851)	FAI	10	60 Co	1×10^3 rad(Si)	$V_{DD} = 5\text{ V. } V_{GG} = 12\text{ V.}$	
			10	60 Co	No failure at 1×10^4 rad(Si)	Unbiased.	
F-8	PSU Special radiation- hardened version of 3851	FAI	10	60 Co	1×10^4 rad(Si)	$V_{DD} = 5\text{ V. } V_{GG} = 12\text{ V.}$	
6800		MOT	3	60 Co 13 to 180 rad(Si)/s	Functional failure: $V_{CC} = 5\text{ V.}$ All signal and control inputs were connected to either logic one or logic zero. Devices were tested after irradiation by placement into equipment designed to use them.		2

TABLE 1b. NMOS μ P'S (Cont'd)

Device No.	Technology	Mfr size	Smpl size	Radiation source	Results	Test conditions and comments	Ref
6800	MOT	3	LINAC	1 μ s pulse	Functional failure: (7.7 to 9) 10^3 rad(Si)	Devices were irradiated once in active state. After irradiation, data outputs and addresses of test device were compared with those of reference device.	7
6800	NAT	10	^{60}Co		Functional failure: 1×10^3 rad(Si)	Failure criterion: inability to function or respond to command. During irradiation, devices were biased at manufacturer's prescribed burn-in condition.	6
6800P	MOT	10	^{60}Co		Functional failure: $V_{CC} = 5$ V. 1×10^3 rad(Si)		†
	MOT					During irradiation, $V_{CC} = 5$ V and programmed routines consisted of many different types of instructions. All devices were from single diffusion lot.	
		7	^{60}Co	100 rad(Si)/s	Functional failure: 1.8×10^3 rad(Si)	Failure to execute instruction set. Devices were tested during irradiation.	
		11	LINAC	150 ns pulse	Functional failure: 1.9×10^4 rad(Si)	Total dose accumulated in single pulse. LINAC pulse was triggered at same instant as initiation of instruction set routine. Testing was initiated within 54 μ s after LINAC pulse trigger and completed in next 100 ms.	

8008-1	11	LINAC	1 μ s pulse	Functional failure: Total dose accumulated in single pulse triggered at same instant as initiation of instruction set routine. Testing was initiated within 54 μ s after LINAC pulse trigger and completed in next 100 ms.	4
	INT	6	^{60}Co	Functional failure: During irradiation, devices were clocked and biased according to manufacturer's specifications. Reset and clear signals were applied at 400 μ s intervals.	4
8080	INT		^{60}Co 13 to 180 rad(Si)/s	$V_{BB} = 5 \text{ V}$. $V_{CC} = 5 \text{ V}$. $V_{DD} = 12 \text{ V}$. All signal and control inputs were connected to either logic one or logic zero.	2
	3			Functional failure: Biased during irradiation.	
	1		1.5×10^4 rad(Si)	Unbiased during irradiation.	
	1		$> 3.5 \times 10^4$ rad(Si)	Unbiased during irradiation.	
MIL	1		840 rad(Si)	Biased during irradiation.	
AMD	2		$(2 \text{ to } 2.5) \times 10^3$ rad(Si)	Biased during irradiation.	
	1		2×10^3 rad(Si)	Biased during irradiation.	
	1		$> 5 \times 10^4$ rad(Si)	Unbiased during irradiation.	
TII	2		1.9×10^3 rad(Si)	Biased during irradiation.	2
	1		2.5×10^4 rad(Si)	Unbiased during irradiation.	
	1		$> 5 \times 10^4$ rad(Si)	Unbiased during irradiation.	

TABLE 1b. NMOS μ P'S (Cont'd)

Device No.	Technology	Mfr size	Radiation source	Results	Test conditions and comments	Ref
8080		NAT 2		610 to 840 rad(Si)	Biased during irradiation.	2
		2		$>5 \times 10^4$ rad(Si)	Unbiased during irradiation.	
8080A			^{60}Co	Functional failure:	During irradiation, devices were biased and clocked and then reset and cleared periodically, typically at 400 μ s intervals.	4
		NAT 2		700 rad(Si)	Supply current increased by 10% to 3 mA.	
		INT 3		700 rad(Si)	Supply current increased by 10% to 3 mA.	
		AMD 2		3×10^3 rad(Si)	Supply current increased by 10% to 4 mA.	
		NEC 3		5×10^3 rad(Si)		
		TII 2		7×10^3 rad(Si)	Supply current increased by 41% to 22 mA.	
8080A		INT 10	^{60}Co	Functional failure:	Failure criterion: inability to function or respond to command. $V_{\text{BB}} = 5 \text{ V}$. $V_{\text{CC}} = 5 \text{ V}$. $V_{\text{DD}} = 12 \text{ V}$.	6
		10		1×10^4 rad(Si)	Unbiased during irradiation.	
C8080A		INT	LINAC 1 μ s pulse		Devices were irradiated in active state. Starting 40 μ s after irradiation, data outputs and addresses of test device were compared with those of reference device.	7

2					Functional failure: Recovered after 6 and 14 min. (2.1 to 2.4) 10 ⁴ rad(Si)	
D8080A	INT	4	LINAC 1 μ s pulse	Functional failure: Devices were irradiated in active state. Starting 40 μ s after irradiation, data outputs and addresses of test device were compared with those of reference device.	7	
D8080A	INT			During irradiation, devices were at nominal bias and performed programmed routine consisting of many types of instructions.	†	
6			60Co 100 rad(Si)/s	Functional failure: Failure criterion: failure to execute instruction set. Devices were tested during irradiation. All devices were from one diffusion lot.		
8			LINAC 150 ns pulse	Functional failure: Total dose accumulated in single pulse LINAC pulse was triggered at same instant as initiation of instruction set routine. Testing was initiated within 54 μ s after LINAC pulse trigger and completed in next 100 ms.		
TMS8080A	TII		LINAC	Cumulative functional failure: Devices were powered during irradiation, but were not exercised.	#	
1				945 rad(Si) (one shot)		
2				(1.6 to 1.9) 10 ³ rad(Si) (two shots each)		
2				(3.2 to 3.8) 10 ³ rad(Si) (three shots each)		

TABLE 1b. NMOS μ P'S (Cont'd)

Device No.	Technology	Mfr size	Radiation source	Results	Test conditions and comments	Ref
TMS8080A		TII 1		No functional failure: 3×10^3 rad(Si)		#
8080B		INT 1	LINAC 5 μ s pulse	Upset: 1.8×10^5 rad(Si)/s Functional failure: 1.5×10^3 rad(Si)	Device was functionally exercised by simple add and compare program, which was recycled until program error occurred or until external reset signal was applied. HALT instructions were placed in all unused memory locations.	8
			200 ns pulse	Latchup: Not observed to 1.8×10^9 rad(Si)/s (no higher tests)		
D8085A		INT			During irradiation, devices were at nominal bias and performed programmed routines consisting of many different types of instructions. All devices were from one diffusion lot.	†
		5	^{60}Co 100 rad(Si)/s	Functional failure: 4.2×10^3 rad(Si)	Failure to execute instruction set. Devices were tested during irradiation.	
		9	LINAC 37 MeV 150 ns pulse	1.7×10^4 rad(Si)	Total dose accumulated in single pulse. LINAC pulse was triggered at same instant as initiation of instruction set routine. Testing was initiated within 54 μ s after pulse trigger and completed in next 100 ms.	

9080	AMD	10	⁶⁰ Co	13	LINAC 37 Mev 1 μ s pulse	Functional failure: Total dose accumulated in single pulse. LINAC pulse was triggered at same instant as initiation of instruction set routine. Testing was initiated within 54 μ s after trigger and completed in next 100 ms.	6
						Functional failure: inability to function or respond to command. $V_{BB} = -5$ V. $V_{CC} = 5$ V. $V_{DD} = 12$ V.	
AM9080ADMB	AMD					$V_{BB} = -5$ V. $V_{CC} = 5$ V. $V_{DD} = 12$ V. Performing programmed routines consisted of many different types of instructions.	†
		6	⁶⁰ Co 100 rad(Si)/s			Functional failure: Failure to execute instruction set. Devices were tested during irradiation.	
		3	LINAC 150 ns pulse			Functional failure: Total dose accumulated in single pulse. LINAC pulse was triggered at same instant as initiation of instruction set routine. Testing was initiated within 54 μ s after LINAC pulse trigger and completed in next 100 ms.	

TABLE 1c. TTL pp'S

Device No.	Technology	Mfr size	Radiation source	Results	Test conditions and comments	Ref
74S481	4-bit slice STTL	TII			Fifteen test vectors of device under test were compared serially with those for reference device. During irradiation, devices were in static operation at 5 V bias.	9
		5	LINAC 1.4 μ s pulse	Transient upset: 1.6×10^7 rad(Si)/s	Failure criterion: decrease in magnitude of V_{OH} by 0.3 V, such as at Y/AG output.	
				2.4×10^7 rad(Si)/s	Failure criterion: increase in magnitude of V_{OL} by 0.05 V, such as at D_2 output. At 3×10^7 rad(Si)/s output, breakup occurs for output levels of 30 to 80 mV. At higher levels, immediate transitions to opposite state occur.	
				Permanent upset: $\sim 6 \times 10^7$ rad(Si)/s		
			Flash x-ray 25 ns pulse	Transient upset: (0.8 to 1.1×10^8 rad(Si)/s	Criterion: switching latch.	
				Permanent upset: (1.0 to 1.3×10^8 rad(Si)/s		

AM2901	4-bit slice STTL	AMD	Nominal bias and executing ADD instruction so that output data lines consisted of alternating ones and zeros.	8
		3 LINAC 4 μ s pulse	Transient upset: (0.9 to 1.2×10^7 rad(Si))/s	
		3	Latchup: Not observed at 1.1×10^{10} rad(Si)/s	
		3	Total dose: 2×10^7 rad(Si)	All devices remained operable.
		3 LINAC 30 ns pulse	Transient upset: (1 to 1.4×10^8 rad(Si))/s	
AM2901A	4-bit slice STTL	AMD	Flash x-ray 20 ns pulse	10
		5	Transient upset: 3.5×10^{10} rad(Si)/s Latchup: Not observed at this level.	$V_{CC} = 5$ to 5.5 V. Functionally tested by comparison to known good device; 294 different input combinations were used to exercise each logic cell in both logic one and logic zero conditions at least once. Peak photocurrent: ~ 10 A.
AM2901A	4-bit slice STTL	AMD	Sandia reactor	§
		10		Passive during irradiation. Tested by manufacturer's functional test for proper operation.
			1×10^{14} n/cm ²	None failed.
			4×10^{14} n/cm ²	Seven failed RAM galloping logic ones and zeros test.

TABLE 1c. TTL μ P'S (Cont'd)

Device No.	Technology	Mfr size	Radiation source	Results	Test conditions and comments	Ref
AM2901A	4-bit slice STTL	AMD	3	^{60}Co	Devices executed shift instructions at 2 MHz while being irradiated and then were tested according to manufacturer's functional test.	§
				Total dose: 3×10^6 rad(Si)	None failed.	
				6×10^6 rad(Si)	Two failed RAM galloping logic ones and zeros test.	
		3	^{60}Co	Total dose: 9×10^6 rad(Si)	Devices were unbiased during irradiation and then tested as above. None failed.	
AM2901A	4-bit slice LSTTL	AMD	5		Fifteen test vectors of device under test were compared serially with those for reference device. During irradiation, devices were in static operation at bias of 5 V.	9
			LINAC 1.4 μ s pulse	Permanent upset: (0.95 to 1.17×10^7) rad(Si)/s	Most sensitive test vector was OR operation on contents of internal RAM.	
				Transient upset: $\sim 4 \times 10^7$ rad(Si)/s		
			Flash x-ray 25 ns pulse	Permanent upset: (5.6 to 9.5×10^7) rad(Si)/s		

TABLE 1c. TTL μ P'S (Cont'd)

Device No.	Technology	Mfr size	Smpl size	Radiation source	Results	Test conditions and comments	Ref
MM16701D	4-bit slice STTL	MMI	1		Latchup: 3.9×10^8 rad(Si)/s (one device)	I_{CC} increased from 200 to 300 mA, but was restored by interrupting power. Effect was repeatable.	8
			1	LINAC	Cumulative dose: 7×10^5 rad(Si)	Dose rate used: $< 5 \times 10^6$ rad(Si)/s. Sink current I_{OL} degraded by 5%. No change for data-out delay, dc power supply current, output source current, and output voltage levels. Device remained functional.	
			1	WSMR or Sandia reactor	Neutron fluence: 1.5×10^{14} n/cm ²	During irradiation, device was passive and leads were open. Parameter changes: I_{CC} : -6%. I_{OL} : -22%. I_{OH} : -20%. Delay time changes: Output 1: +5%. Output 2: +22%. Output 3: +13%. Output 4: +23%. Device remained functional.	

TABLE 1d. I^2L μP 'S

Device No.	Technology	Mfr size	Smpl size	Radiation source	Results	Test conditions and comments	Ref
F100-L	16-bit CPU	FER	2	LINAC 1 μ s pulse	Transient upset: 5×10^6 rad(Si)/s Latchup: $> 5 \times 10^9$ rad(Si)/s	Tested dynamically during exposure. $V_{CC} = 5$ V. Test consisted of multiplying two numbers and monitoring for correct output.	12
			2			Functional failure: Program was stored in ROM. Clock rate: 1 kHz. 5×10^5 rad(Si)	
			2	VIPER reactor	Functional failure: Passive device irradiation. 1×10^{14} n/cm ²		
SBP0400	4-bit CPU	TII	-	LINAC 1 to 5 μ s pulses	Transient upset: 2×10^7 rad(Si)/s	Injector current was varied over operating range of device.	13
X0400	Prototype of SBP0400 4-bit parallel binary processor	TII				During irradiation, devices were under nominal bias and executing ADD instruction so that output data lines comprised alternating ones and zeros.	8
			1	LINAC 4 μ s pulse	Transient upset: 2.1×10^7 rad(Si)/s Latchup: Not observed to 3.7×10^8 rad(Si)/s	Proper switching sequence resumed within 2 μ s after radiation pulse. Sequence resumed at 3 μ s after 3.7×10^8 rad(Si)/s. No measurable output response occurred below 2×10^7 rad(Si)/s. No surge currents were observed.	

TABLE 1d. I^2L μP 'S (Cont'd)

Device No.	Technology	Mfr	Smpl size	Radiation source	Results	Test conditions and comments	Ref
X0400	Prototype of SBP0400 4-bit parallel binary processor	TII	1	LINAC	Functional failure: Device output levels did not degrade, but had improper logic states. No cumulative dose: 1.4×10^6 rad(Si)	Device output levels did not degrade, but had improper logic states. No room temp recovery 50 min after 2×10^6 rad(Si). After 48 hr anneal at 200°C, output levels recovered to those measured after irradiation to 3×10^5 rad(Si).	8
			1	WSMR or Sandia reactor	Neutron fluence: 5×10^{11} n/cm ²	I _{OL} degraded by 10%.	
					Functional failure: 1×10^{13} n/cm ²	Nonfunctional for injector current below 5.6 mA.	
					4×10^{13} n/cm ²	Nonfunctional for injector current between 3.2 and 150 mA.	
SBP9900	16-bit CPU	TII	-	LINAC 1 to 5 μ s pulses 2.5 Mev	Transient upset: 1×10^8 rad(Si)/s	Injector current was varied over operating range of device.	13
			-	LINAC 20 to 100 ns pulses	4×10^8 rad(Si)/s		
SBP9900	16-bit CPU	TII	2	2.5 Mev	Total dose failure level: 1.2×10^{14} e/cm ² 3×10^6 rad(Si)	Tested on EVM 9900 evaluation board. Injector current level = 523 mA. Clock frequency: 2 MHz. One device had inputs grounded and never recovered. Other device had inputs high and annealed in 45 min.	14

SBP9900	16-bit CPU	TII	-	LINAC 30 ns pulse GaAs laser $\lambda = 0.904 \mu\text{m}$ 35 to 40 ns pulses	1	Total dose failure: Device was irradiated with inputs $1.2 \times 10^{14} \text{ e/cm}^2$ $3 \times 10^6 \text{ rad(Si)}$ Transient upset: $8.5 \times 10^8 \text{ rad(Si)/s}$ Transient upset: $8.7 \times 10^8 \text{ rad(Si)/s}$	Corresponding outputs of device under test and reference device were compared by logic analyzer. Lack of agreement between outputs indicated failure. Two short-looped programs were repeatedly executed during irradiation until failure was observed.	15
SBP9900A	16-bit CPU	TII	3	WSMR fast burst reactor	2	Functional failure: Maximum clock frequency (at $I_I = 500 \text{ mA}$) decreased by 10 to 20%. Functional failure was for ac test at frequency = 1 MHz and $I_I = 500 \text{ mA}$. No significant change in dc parameters except for degradation in V_{OL}. Transient upset: $2.5 \times 10^9 \text{ rad(Si)/s}$ (1.4 to $1.8) 10^9 \text{ rad(Si)/s}$ $1.0 \times 10^9 \text{ rad(Si)/s}$	Direct and alternating current and functional measurements were made. Device was passive during irradiation.	16

TABLE 1d. I^2L μP 'S (Cont'd)

Device No.	Technology	Mfr size	Smpl size	Radiation source	Results	Test conditions and comments	Ref
SBP9900A	16-bit CPU	TII	4	FX-75 Flash x-ray 25 ns pulse	Survivability test: During irradiation, devices were > 1×10^{12} rad(Si)/s Each device was irradiated five times at this level.	biased at 5 V. I_{OL} decreased by 10 to 20%. All devices passed functional test.	16
			2	^{60}Co 200 rad(Si)/s	Functional failure: Device operated during irradiation (3 to 5) 10^6 rad(Si)	and was measured immediately after irradiation. No significant change in dc parameters except for degradation of V_{OL} .	

TABLE 2a. CMOS RAM'S

Device No.	Technology & size (bits)	Mfr size	Smpl size	Radiation source	Results	Test conditions and comments	Ref
MM54C200	Metal-gate 256x1 Radiation hardened	NAT	7	60Co	Change in I_{SS} : 2.5 μA preirradiation 15 μA at 10 ⁵ rad(Si) 20 μA at 10 ⁶ rad(Si) Change in t_{pd} : 220 ns preirradiation 230 ns at 10 ⁵ rad(Si) 255 ns at 10 ⁶ rad(Si)	$V_{DD} = V_{IN} = 10 V.$ $V_{SS} = 0 V.$ $V_{DD} = V_{IN} = 10 V.$ $V_{SS} = 0 V.$ $C_L = 50 pF.$	17
MM54C200	256x1	NAT		Flash x-ray 3 ns pulse		During irradiation, devices were biased at normal voltage levels (3 to 14 V) and operated in READ or WRITE mode. No latchup was observed for $V_{CC} < 10 V.$	5
		1		Latchup: 1x10 ¹⁰ rad(Si)/s Total dose: 30 rad(Si)		$V_{CC} = 14 V.$ Latchup susceptibility was independent of operating mode and input and output logic levels. Latchup current: ~250 mA.	
		1		Transient upset: 1x10 ⁹ rad(Si)/s Total dose: 3 rad(Si)		Lowest total dose level used in this test.	

TABLE 2a. CMOS RAM'S (Cont'd)

Device No.	Technology & size (bits)	Mfr size	Radiation source	Results	Test conditions and comments	Ref
MM54C200	256x1	NAT	4 Selfert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 1.1×10^{14} rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
MM54C200	Al-gate radiation-hardened process 256x1	NAT	^{60}Co		$V_{DD} = 5$ V. Devices were in READ mode during irradiation. Stored data were all logic ones or zeros and were read out at 10 kHz during irradiation.	19
		2		Total dose: 1×10^6 rad(Si)	No difference for stored zeros or ones. Quiescent current increased by one or two orders of magnitude. Access time degraded 5 to 10%.	
MM54C200D	Al-gate radiation hardened process 256x1	NAT	- Flash x-ray 18 ns pulse	Latchup: None at 2.2×10^{11} rad(Si)/s	During irradiation, devices were biased at $V_{DD} = 5$ V.	20
				Latchup: None at 8.8×10^{11} rad(Si)/s	Before flash x-ray exposure, devices received 1×10^{14} n/cm ² .	
				Transient upset: 1.8×10^8 rad(Si)/s	Devices operated at $V_{DD} = 5$ V and with memory enabled. No previous neutron irradiation.	
				2.0×10^8 rad(Si)/s	Previous neutron irradiation at 1×10^{14} n/cm ² .	

MM54C929D	1024x1	NAT	4	Febetron 705 Flash x-ray 2 MeV 20 ns pulse	5.0x10 ⁸ rad(Si)/s	Previous neutron irradiation at 1x10 ¹⁵ n/cm ² . I _{CC} increased by 2 μA. t _{pd} increased by 10%.	21
					1.2x10 ⁹ rad(Si)/s	Previous neutron irradiation at 1x10 ¹⁶ n/cm ² . I _{CC} increased by 25 μA. t _{pd} nearly doubled.	
					Transient upset: (3.4 to 5)10 ⁷ rad(Si)/s	Exercised using Macrodata. Tested in READ, WRITE, and PAUSE modes. All devices latched up at 5x10 ⁷ rad(Si)/s in all modes.	
			4		Permanent upset: (3.5 to 5)10 ⁷ rad(Si)/s		
	4		4	Febetron 705 2 MeV 50 ns pulse	Functional survivability: 4.7x10 ¹¹ rad(Si)/s		
	10			⁶⁰ Co 5 rad(Si)/s	Failure dose: 3x10 ³ rad(Si)	V _{CC} = 5 V. Five devices had all inputs held high; five had all inputs grounded. Substantial increase in standby current at 1x10 ³ rad(Si). Less than 1 hr between irradiation and measurement.	
MM74C200	256x1	NAT	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 1.3x10 ⁴ rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by 2 μs cycle time. Failure criterion was first occurrence of bit error.	18

TABLE 2a. CMOS RAM'S (Cont'd)

Device No.	Technology & size (bits)	Mfr size	Radiation source	Results	Test conditions and comments	Ref
MM74C920	Si-gate 256x4	NAT	Flash x-ray 3 ns pulse	1 Latchup level: 1x10⁹ rad(Si)/s Total dose: 3 rad(Si)	During irradiation, devices were biased at V _{CC} = 5 V and operated in READ or WRITE mode.	5
MM74C929	1024x1	NAT	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	4 Functional failure: 3.7x10³ rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error. Standby power dissipation increased by one order of magnitude.	18
CDP1821SCD	SOS 1024x1	RCA	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	4 Functional failure: 4x10³ rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern having 2 μ s cycle time. Failure criterion was first occurrence of bit error. Quiescent current began rapid increase at 1x10 ³ rad(Si).	18
CDP1821SD	SOS 1024x1	RCA		3 Flash x-ray 20 ns pulse	During irradiation, devices were biased at V _{CC} = 5 V and operated in READ mode.	†
				Transient upset: (2.3 to 2.6)10⁶ rad(Si)/s	Single state change occurred for all devices.	

1822	SOS Al-gate 256x4	HUG	4	LINAC 150 ns pulse	Transient upset: (0.83 to 1.0)10 ¹⁰ rad(Si)/s	Single state change occurred for one device.	5
			2	LINAC 50 ns pulse	Upset: >3.5x10 ¹⁰ rad(Si)/s	During irradiation, devices were biased at V _{DD} = 5 V and operated in various static states. Data were retained. Above 1x10 ⁴ rad(Si) accumulated dose, data were lost at 2x10 ¹⁰ rad(Si)/s.	
		RCA	4	LINAC 50 ns pulse	Transient upset: (2.5 to 3)10 ¹⁰ rad(Si)/s	During irradiation, devices were biased at V _{DD} = 5 V and operated in various static states.	
					Permanent upset: 4x10 ¹⁰ rad(Si)/s		
					Functional failure: Will not write: ~10 ⁴ rad(Si).		
			2	Flash x-ray 3 ns pulse	Dose rate: 3x10 ¹⁰ rad(Si)/s	No upset was observed for 10 pulses up to this dose rate.	
CDP1822SCD	SOS 256x4	RCA	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 1.1x10 ⁴ rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
S2222	Si-gate 512x1	MFA	9	⁶⁰ Co	Functional failure: (3 to 4)10 ³ rad(Si)	During irradiation, devices were biased at V _{CC} = 10 V. After irradiation, devices were taken to measurement facilities within 15 to 30 min with no bias.	22

TABLE 2a. CMOS RAM'S (Cont'd)

Device No.	Technology & size (bits)	Mfr size	Radiation source	Results	Test conditions and comments	Ref
S2222	Si-gate 512x1	MFB 5	60 Co	Functional failure: (3 to 4)10 ³ rad(Si)	During irradiation, devices were biased at V _{CC} = 10 V. After irradiation, devices were taken to measurement facilities within 15 to 30 min with no bias.	22
CD4061	CMOS 256x1	RCA 8	60 Co	Functional failure: 1.5x10 ⁴ rad(Si)	During irradiation, devices were biased at V _{DD} = 10 V. After each irradiation, bias was removed while devices were transported to FAJ 5000 IC tester. Devices were tested within 15 to 30 min after each irradiation. (Devices were made after 1973 by high temp gate anneal process.)	22
CD4061	Special Al-gate process 256x1	RCA	60 Co		During irradiation, devices were biased at V _{DD} = 5 V and were in READ mode. Stored data were either all ones or all zeros and were read out at 10 kHz during irradiation.	19
		2		Functional failure: 3x10 ⁵ rad(Si)	Stored zeros were read out during irradiation. Quiescent current consumption increased by one order of magnitude. Access time degraded by 25%.	
		2		Functional failure: 1x10 ⁶ rad(Si)	Stored ones were read out during irradiation. Quiescent current increased by two to five orders of magnitude. Access time degraded by 17%.	

CD4061	Si-gate 256x1	RCA	7	⁶⁰ Co	Functional failure: $V_{DD} = 10$ V. Inputs were in various combinations of HIGH and LOW during irradiation. After irradiation, devices were transported to testing within 30 min without bias.	22
CD4061	Si-gate 256x1	RCA		LINAC 10 MeV 18 ns pulse	During irradiation, devices were biased at $V_{DD} = 5$ V. Test results were independent of test pattern stored and operational mode.	23
			5		Permanent upset: 2.5×10^8 rad(Si)/s	
			5		5.2×10^8 rad(Si)/s	High reliability devices in standby mode.
			5		2.2×10^8 rad(Si)/s	Commercial devices in active READ mode.
					4.5×10^8 rad(Si)/s	Commercial devices in standby mode.
			5		4.3×10^8 rad(Si)/s	Hardened devices in active READ mode.
			5		3.9×10^8 rad(Si)/s	Hardened devices in standby mode.
			15		Latchup threshold: 4×10^9 rad(Si)/s	Only 1 sample out of 15 tested latched up below max dose rate (1.4×10^{10} rad(Si)/s) for $V_{DD} = 5$ V.
			5	100 ns pulse	Latchup threshold: 1.3×10^{11} rad(Si)/s	High reliability devices. $V_{DD} = 5$ V.
			5		1.9×10^9 rad(Si)/s	High reliability devices. $V_{DD} = 10$ V.

TABLE 2a. CMOS RAM'S (Cont'd)

Device No.	Technology & size (bits)	Mfr size	Radiation source	Results	Test conditions and comments	Ref
CD4061	Si-gate 256x1	RCA 5	100 ns pulse	Latchup threshold: 2.1×10^{10} rad(Si)/s	Commercial devices. $V_{DD} = 5$ V.	23
				1.4×10^9 rad(Si)/s	Commercial devices. $V_{DD} = 10$ V.	
				$> 1.8 \times 10^{11}$ rad(Si)/s	Hardened devices. $V_{DD} = 5$ V.	
				3.1×10^9 rad(Si)/s	Hardened devices. $V_{DD} = 10$ V.	
CD4061	Si-gate 256x1	RCA 4	Flash x-ray 20 ns pulse		Devices were irradiated under bias. Several addresses with various input patterns were used.	10
CD4061A	256x1 Radiation-hardened version	RCA 20	60Co	Latchup threshold: 1.8×10^{10} rad(Si)/s Minimum dose: 1.4×10^3 rad(Si)	$V_{CC} = 7$ V. Peak photocurrent: ~ 0.5 A. Accompanied by memory upset.	24
				Functional failure: 1×10^6 rad(Si)	Wet-oxide process using 850°C gate-oxide anneal temp. Before and after irradiation, devices were subjected to truth table test sequence. All postirradiation tests were completed within 1 hr after irradiation. $V_{DD} = 15$ V.	

TABLE 2a. CMOS RAM'S (Cont'd)

Device No.	Technology & size (bits)	Smpl size	Radiation source	Results	Test conditions and comments	Ref
CD4061A	256x1	RCA 4	⁶⁰ Co	Irradiation 1: 5x10³ rad(Si) Irradiation 2: 2.5x10⁴ rad(Si) Latchup and permanent upset: 4x10⁸ rad(Si)/s	During irradiation, devices were in WRITE mode, CHIP-ENABLE input at 0 V and WRITE/READ input at 10 V. Parameter measurements: Power supply current (increased by 11%). Sink current (no change) Source current (increased by 11%). Read access time (changed by ±10%) Three devices failed in READ mode. Failure mechanism for three devices: radiation-induced latchup. No latchup was observed when 50 ohm resistor was used for current limiting. Failure mechanism for three other devices: data loss in internal memory cells. Failure mechanism for remaining two devices: transient upset at data output terminal.	11
CD4061A	Wet-oxide 256x1	RCA 20	⁶⁰ Co	Functional failure: 1x10⁶ rad(Si) 2x10⁶ rad(Si)	Devices were subjected to truth table test sequence, which exercised each transistor in both ON and OFF states. Functional testing was within 1 hr of irradiation. One device failed. One device failed.	24

Functional failure: During irradiation, devices were biased at $V_{DD} = 10$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.

Functional failure: During irradiation, devices operated at $V_{DD} = 5$ V and clock (1 MHz) = 5 V. Functional exerciser could write and read ones, zeros, or pattern of ones and zeros for each of addressable 1024 bits, in one 2 ms cycle. Input WRITE waveform was compared with output READ waveform. Failure mode: some ones going to zeros observed for alternating logic one and zero data pattern.

Functional failure: During irradiation, device was passive. $V_{DD} = 0$ V. Clock = 0 V. Failure mode: a few hundred logic ones going to zeros.

During irradiation, devices were biased at $V_{DD} = 5$ V. Ones and zeros were loaded into two different addresses and then data were read out. Little room temp annealing at 1000 min for both biased and unbiased devices.

Transient upset:
 9×10^8 rad(Si)/s
 6.6×10^9 rad(Si)/s
 No transient upset observed at
 3×10^9 rad(Si)/s

TABLE 2a. CMOS RAM'S (Cont'd)

Device No.	Technology & size (bits)	Mfr	Smpl size	Radiation source	Results	Test conditions and comments	Ref
MMS5001D	SOS 1024x1	RCA		LINAC 1 μ s pulse		All devices were powered during irradiation; $V_{CC} = 5V$. All functional tests made within minutes of irradiation.	25
			1		3x10 ⁸ rad(Si)/s Cumulative dose: 900 rad(Si)	All logic ones were stored. No bit errors, but device did not function. Supply current = 20 mA.	
			1		3x10 ⁸ rad(Si)/s Cumulative dose: 1.1x10 ³ rad(Si)	All logic ones were stored. Bit errors. Device no longer functioned.	
			1		3x10 ⁸ rad(Si)/s Cumulative dose: 994 rad(Si)	All logic ones were stored. Upset occurred, but device operated after being reset. Continued even after irradiation to 3x10 ⁹ rad(Si)/s. Dose = 6400 rad(Si).	
			1		3.5x10 ⁹ rad(Si)/s Cumulative dose: 4.5x10 ³ rad(Si)	All logic ones were stored. Bit error.	
			1		2.5x10 ⁸ rad(Si)/s Cumulative dose: >750 rad(Si)	All logic zeros were stored. Device did not load logic ones. Supply current = 10 mA.	
			1		3x10 ⁹ rad(Si)/s Cumulative dose: 6.2x10 ³ rad(Si)	All logic zeros were stored. No bit errors occurred.	

MWS500 1D	SI-gate	RCA	LINAC	23	No distinction was made between these two RAM's. Test results indicate no dependence on pattern type stored.
MWS550 1D	SOS		10 MeV		
	1024x1		18 ns pulse		
					Dose rate:
					1x10 ¹¹ rad(Si)/s
					No permanent upset.
					6.5x10 ¹⁰ rad(Si)/s
					No permanent upset.
					2x10 ¹⁰ rad(Si)/s
					No permanent upset.
					During irradiation, devices were in either static or active mode at V _{DD} = 2.5 V.
PD5101	256x4	NEC	Seifert x-ray 150 kVp	18	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error. Power dissipation increased by three orders of magnitude.
					Functional failure: 3.5x10 ³ rad(Si)
MWS550 1D	SOS	RCA	Febetron 705 Flash x-ray 2 MeV 20 ns pulse	21	Exercised using Macrodata. Tested in READ, WRITE, and PAUSE modes.
	1024x1				
					Transient or permanent upset: (6 to 7)10 ¹⁰ rad(Si)/s
					Functional survivability: 4.7x10 ¹¹ rad(Si)/s
					7 Febetron 705 2 MeV Electron beam 50 ns pulse
					10 ⁶⁰ Co 27 rad(Si)/s rad(Si)
					Functional failure: V _{CC} = 10 V. Five devices had all inputs held high; five had them all grounded. Substantial standby current increase at 5x10 ³ rad(Si). Less than 1 hr between irradiation and measurement.

TABLE 2a. CMOS RAM'S (Cont'd)

Device No.	Technology & size (bits)	Mfr	Smpl size	Radiation source	Results	Test conditions and comments	Ref
MMS5501D	SOS 1024x1	RCA		LINAC 1 μ s pulse		All devices were powered during irradiation; $V_{CC} = 5$ V. All functional tests made within minutes of irradiation.	26
			1		Permanent upset: 1×10^9 rad(Si)/s Cumulative dose: 1.1×10^3 rad(Si)	All logic ones were stored. Latchup but resettable by cycling power.	
			1		9×10^9 rad(Si)/s Cumulative dose: 1.7×10^4 rad(Si)	No readout. Device was destroyed. $I_{pp} = 40$ mA.	
			1		1.2×10^9 rad(Si)/s Cumulative dose: 2.1×10^3 rad(Si)	All logic ones were stored. Device did not reset.	
			1		1.2×10^9 rad(Si)/s Cumulative dose: 1.5×10^3 rad(Si)	All logic zeros were stored. Device did not reset.	
HM6504	4096x1	HAR	4	Seifert x-ray 1.3 to 50 rad(Si)/s	Permanent upset: 7×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
6508-2	Si-gate 1024x1	HAR		^{60}Co		During irradiation, devices were biased at $V_{DD} = 5$ V and were in READ mode. Stored data were either all ones or all zeros and were read out at 10 kHz clock rate during irradiation. Devices were in dry ice ~40 min between irradiation and measurement.	19

Part Number	Test Condition	Dose / Exposure	Failure Mode	Notes
6508-5 6508-9	Si-gate 1024x1 Static	HAR - Febetron 706 3 ns pulse	1	Total dose: 5x10 ³ rad(Si) Stored zeros. Quiescent current increased to 10 mA. Access time increased by 5%.
6508	1024x1 Total dose Radiation-hardened version	HAR - Febetron 706 3 ns pulse	1	Total dose: 2x10 ³ rad(Si) Stored ones. Quiescent current increased to 300 μA. Access time increased by 17%.
6508-8	Si-gate 1024x1	HAR 4 60Co 5 rad(Si)/s	1	V _{CC} = 5 V. Two lots were examined. V _{CC} = 5 V. No burnout. During irradiation, devices were operated at V _{CC} = 5 V and clock (1 MHz) = 5 V.
HM6508	Si-gate 1024x1	HAR 4 Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	1	Functional failure: Failure modes: ones going to zeros and zeros going to ones. I _{DD} increased by factor of 9. During irradiation, device was biased at V _{CC} = 0 V. Clock = 0 V.
			1	Functional failure: Failure mode: zeros going to ones 6.1x10 ⁴ rad(Si)
			18	Functional failure: During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern having 2 μs cycle time. Failure criterion was first occurrence of bit error.

TABLE 2a. CMOS RAM'S (Cont'd)

Device No.	Technology & size (bits)	Mfr size	Radiation source	Results	Test conditions and comments	Ref
HMI6508	Si-gate 1024x1	HAR 6	LINAC 10 MeV 18 ns pulse	Latchup and permanent upset: 6×10^7 rad(Si)/s	During irradiation, devices were biased at $V_{DD} = 5$ V. Test results were independent of operational mode.	23
IM6508	Si-gate 1024x1	ISL 4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 2.3×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
IM6508	Si-gate 1024x1	ISL 4	LINAC 10 MeV 18 ns pulse	Latchup and permanent upset: 8×10^7 rad(Si)/s	During irradiation, devices were biased at $V_{DD} = 5$ V.	23
IM6508IDE	Si-gate 1024x1	ISL 2	^{60}Co 5 rad(Si)/s	Functional failure: 1.5×10^3 rad(Si)	During irradiation, devices were biased at $V_{CC} = 10$ V. Clock (1 MHz) = 10 V. Failure mode: wrong bits. I_{DD} increased by factor of 10.	1
		1		Functional failure: 2.1×10^4 rad(Si)	During irradiation, device was biased at $V_{CC} = 1.5$ V. Clock (1 MHz) = 1.5 V. Almost complete functional recovery after 46 hr of room temp anneal.	
		2		Functional failure: 3.0×10^4 rad(Si)	During irradiation, devices were passive. $V_{CC} = 0$ V. Clock = 0 V. Devices were tested immediately after irradiation.	

IM6508MDE	Si-gate 1024x1	ISL	⁶⁰ Co	1	During irradiation, devices were biased at $V_{CC} = 5$ V. Clock (1 MHz) = 5 V.
				3	Functional failure: Failure mode: zeros going to ones. 2.7×10^3 rad(Si) Failures occurred suddenly. Supply current increased by factor of 7. Significant annealing when devices were irradiated under zero bias.
				1	Dose: During irradiation, device was passive. 7.9×10^4 rad(Si) $V_{CC} = 0$ V. Clock = 0 V. No bit failures were observed. I_{DD} increased by factor of 4.
IM6518	Si-gate 1024x1	ISL	Flash x-ray 3 ns pulse	5	$V_{CC} = 5$ V. Various logic levels were applied to inputs so that device was biased in READ, WRITE, or intermediate mode during irradiation.
				1	Latchup: Latchup was observed in all states. (1 to 2×10^9 rad(Si))/s During latchup, device currents range from 150 to 250 mA. Total dose: 3 to 6 rad(Si)

TABLE 2b. NMOS RAM'S

Device No.	Technology & size(bits)	Mfr	Smpl size	Radiation source	Results	Test conditions and comments	Ref
μ PD410D	4096x1	NEC	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Failure dose: 1.7×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
μ PD416D	16384x1	NEC	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Failure dose: 1.7×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
2102A	1024x1	INT	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Failure dose: 3×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
2102B	1024x1	SIG	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Failure dose: 4.5×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
MM2102-2MD	1024x1	NAT	4	Pebetron 705 Flash x-ray 2 MVp 20 ns pulse	Transient or permanent upset: (0.95 to 1.6×10^8 rad(Si)/s	Exercised using Macrodata. Tested in READ, WRITE, and PAUSE modes.	21
			5		Functional survivability: 1.6×10^{11} rad(Si)/s		

2107B	Si-gate 4096x1 Dynamic	INT	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Failure dose: 1500 rad(Si)	10	⁶⁰ Co 1 rad(Si)/s	V _{CC} = 5 V. Five devices had all inputs high; five had them all grounded. All survived 500 rad(Si). Less than 1 hr between irradiation and measurement.
								During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μs cycle time. Failure criterion was first occurrence of bit error.
2107B	4096x1	INT	5	Febetron 705 Flash x-ray 20 ns pulse				V _{DD} = 12 V. V _{CC} = 5 V. V _{BB} = -5 V. Real-time monitoring.
					Permanent upset range: (5 to 8)10 ⁶ rad(Si)/s Corresponding dose: 0.15 to 0.24 rad(Si)			Clock = 32 kHz.
					Permanent upset range: (0.5 to 2)10 ⁸ rad(Si)/s Corresponding dose: 1.5 to 5.8 rad(Si)			Clock = 2.5 MHz.
			9	⁶⁰ Co	Functional failure: 360 to 1100 rad(Si)			Functional failure: Clock = 32 kHz.

TABLE 2b. NMOS RAM'S (Cont'd)

Device No.	Technology & size (bits)	Mfr size	Smpl Radiation source	Results	Test conditions and comments	Ref
2114	Si-gate 1024x4 Static	EM4	4 Febetron 706 3 ns pulse	Permanent upset: (0.5 to 1)10 ⁸ rad(Si)/s	V _{CC} = 5 V. All ones or all zeros stored. Irradiated in standby state.	27
2116	16384x1	INT	4 Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 900 rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
2147	HMOS 4096x1 Static	INT	5 Febetron 705 Flash x-ray 2 MVp 20 ns pulse	Permanent upset: 1.3x10 ⁷ rad(Si)/s	Exercised by Macrodata. Irradiated in READ, WRITE, and PAUSE cycles.	29
			Febetron 705 Electron beam 50 ns pulse	Functional survivability: >2.7x10 ¹¹ rad(Si)/s		
			5 ⁶⁰ Co 5 rad(Si)/s	Functional failure: 1500 rad(Si)	Incremental irradiations of 500 rad(Si) were done. Functional and parametric measurements were made within 1 hr of irradiation.	
C2147	HMOS 4096x1 Static	INT			During irradiation, devices were biased at V _{CC} = 5 V and operated in READ mode.	†
		3	Flash x-ray 20 ns pulse	Transient upset: 1.0x10 ⁹ rad(Si)/s	Single state change occurred for one device.	

MK4027N	4096x1	MOS	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 850 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
			4	^{60}Co 4×10^3 rad(Si)/min	Functional failure: 1.5×10^3 rad(Si)		
			4	1.5 MeV Van De Graaff accelerator	Functional failure: 1.2×10^3 rad(Si)		
TMS4030	4096x1	TII	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 4.1×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
			4	^{60}Co 4×10^3 rad (Si)/min	Functional failure: 3×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
			4	1.5 MeV Van de Graaff accelerator 400×10^3 rad (Si)/min	Functional failure: 1.7×10^3 rad(Si)		
TMS4035	1024x1	TII	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 3×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
			4	^{60}Co 4×10^3 rad (Si)/min	Functional failure: 3.2×10^3 rad(Si)		
			4	1.5 MeV Van de Graaff accelerator 400×10^3 rad (Si)/min	Functional failure: 1.7×10^3 rad(Si)		
TMS4050	4096x1	TII	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 6.2×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18

TABLE 2b. NMOS RAM'S (Cont'd)

Device No.	Technology & size (bits)	Mfr size	Radiation source	Results	Test conditions and comments	Ref
HYB4060	4096x1	SIE	4 Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 2.5×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
4096	4096x1	FAI	4 Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 800 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
MK4096P	4096x1	MOS	4 Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 1.1×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
MK4102N	1024x1	MOS	4 Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 2.8×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
MK4104P	4096x1	MOS	4 Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 1.3×10^3 rad(Si)	During irradiation, devices were biased at $V_{DD} = 5$ V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18

HYB4116	16384x1	SIE	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 2x10 ³ rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μs cycle time. Failure criterion was first occurrence of bit error.	18
MCM4116	16384x1	MOT	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 1.3x10 ³ rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μs cycle time. Failure criterion was first occurrence of bit error.	18
TMS4116	16384x1	TII	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 2.2x10 ³ rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μs cycle time. Failure criterion was first occurrence of bit error.	18
MK4116P	16384x1	MOS	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 2x10 ³ rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μs cycle time. Failure criterion was first occurrence of bit error.	18
SEMI4200	4096x1	EMM	5			Devices were biased at V _{DD} = 12 V, V _{CC} = 5 V, and V _{BB} = -5 V. Inputs were tied to V _{CC} or ground. Memory was placed in READ, WRITE, or standby state during exposure. Latchup was not observed.	5
			5	Flash x-ray 3 ns pulse	Transient upset: 1x10 ⁹ rad(Si)/s Total dose: 3 rad(Si)	Independent of whether logic one or zero was stored in addressed cell. Upset susceptibility was greatest when voltage level stored on DI line was opposite polarity and level to those in contents of addressed cell.	

TABLE 2b. NMOS RAM'S (Cont'd)

Device No.	Technology & size (bits)	Mfr	Smpl size	Radiation source	Results	Test conditions and comments	Ref
SEMI4200	4096x1	EMM	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 1.2x10 ³ rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
MCM6604L	4096x1	MOT	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 1.2x10 ³ rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
MCM6605AL	4096x1	MOT	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 2.3x10 ³ rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
AM9060	4096x1	AMD	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 800 rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18
AM9102	1024x1	AMD	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 800 rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit error.	18

AM9140	4096x1	AMD	4	Selfert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 1x10 ³ rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μs cycle time. Failure criterion was first occurrence of bit error.	18
4K RAM	4096x1			60Co		During irradiation, devices had either zero gate bias (gate, source, and drain connected together) or gate biased at 12 V with respect to drain and source (connected together). After each irradiation, dry ice was used to minimize annealing. Failures were attributed to threshold voltage shifts in decoder access transistors, causing decoders to be stuck in logic one state.	30
				60Co	Functional failure:		
	A ¹	10			2.7x10 ³ rad(Si)	Devices failed: 5	
	B ¹	10			1.7x10 ³ rad(Si)	Devices failed: 1	
	C ¹	10			2.7x10 ³ rad(Si)	Devices failed: 5	
	D ¹	10			1.7x10 ³ rad(Si)	Devices failed: 1	
	E ¹	10			1.7x10 ³ rad(Si)	Devices failed: 1	
	F ¹	10			2.7x10 ³ rad(Si)	Devices failed: 4	
	G ¹	10			2.7x10 ³ rad(Si)	Devices failed: 4	

¹Reference 30 conceals identities of these manufacturers: AMD, FAI INT, MOS, MOT, NAT, and TII (ordered alphabetically here).

TABLE 2c. TTL RAM'S

Device No.	Technology & size (bits)	Smpl Mfr size	Radiation source	Results	Test conditions and comments	Ref
S82S11F	STTL 1024x1	SIG	Febetron 705 2 MVp 20 ns pulse		During irradiation, devices were exercised by Macrodata MD-104.	21
		5		Transient upset: (2 to 4)10 ⁷ rad(Si)/s	Devices were irradiated in READ mode. Logic upset is defined to occur when tester TTL input could not sense correct memory output. Stored data may not be scrambled.	
		5		Permanent upset: (2 to 4)10 ⁸ rad(Si)/s	Devices were irradiated in READ, WRITE or PAUSE mode. Memory data were lost during radiation pulse. Most susceptible when irradiated during active READ/WRITE portion of WRITE cycle.	
		16		Latchup: 2x10 ¹⁰ rad(Si)/s	Only two devices latched up. Power supply current increased from 80 to 500 mA. After power was cycled, devices were functional.	
		15	Flash x-ray 2 MeV 50 ns pulse	Functional survivability: >3x10 ¹² rad(Si)/s		
		10	⁶⁰ Co 195 rad(Si)/s	Functional failure: 1x10 ⁵ rad(Si)	During irradiation, devices were biased at V _{CC} = 5 V and all inputs were grounded. One device failed.	
		10	Sandia pulsed reactor	Functional failure: 3x10 ¹⁴ n/cm ²	During irradiation, devices had no electrical bias. One device failed. Output drive current decreased by about 30% before functional failure.	

I3101	STTL 16x4	INT	-	Flash x-ray 29 ns pulse	Transient upset: 1.9x10 ⁸ rad(Si)/s	During irradiation, device was operated under normal voltage; all ones, all zeros, or alternating ones and zeros stored in memory. Monitored during exposure.	28
-------	--------------	-----	---	----------------------------	---	---	----

I3101	STTL 16x4	INT	Northrop TRIGA	Permanent damage: 1.1×10^{15} n/cm ²	During irradiation, devices were biased at $V_{CC} = 5$ V and functionally tested and compared with unirradiated devices.	31
-------	--------------	-----	-------------------	---	---	----

3	TRIGA reactor	Permanent damage: 7×10^{14} n/cm ²	No latchup was observed at highest test dose rate, 5×10^{10} rad(Si)/s.
2	Flash x-ray 2 Mvp 30 ns pulse	Transient upset: 1.9×10^8 rad(Si)/s	

2	LINAC	Transient upset: 4 μ s pulse	1.7 $\times 10^7$ rad(Si)/s test dose rate, 5 $\times 10^{10}$ rad(Si)/s.	No latchup was observed at highest
---	-------	-------------------------------------	--	------------------------------------

I3101A	STTL	INT	
	16x4		During irradiation, devices were biased at $V_{CC} = 5$ V and functionally tested and compared with unirradiated devices.

3	TRIGA reactor	Permanent damage: 1.4×10^{14} n/cm ²	No latchup was observed at highest test dose rate, 5×10^{10} rad(Si)/s.
2	Flash x-ray 2 MVp 30 ns pulse	Transient upset: 1.9×10^8 rad(Si)/s	

2	LINAC	Transient upset: No latchup was observed at highest test dose rate, 5×10^{10} rad(Si)/s.
	4 μ s pulse	

TABLE 2c. TTL RAM'S (Cont'd)

Device No.	Technology & size (bits)	Mfr	Smpl size	Radiation source	Results	Test conditions and comments	Ref
IM5533A	Au-doped 256x1	ISL	5	LINAC	Transient upset: 1.7×10^8 rad(Si)/s	Tested during irradiation by μ P controlled test facility.	8
			2		Total dose: $> 3 \times 10^7$ rad(Si) Neutron fluence: 1.3×10^{14} n/cm ²	No operational failure. Output transistors suffered factor-of-five gain loss. (This is considered marginal for proper operation.)	
93425-DM	1024x1 Isoplanar Static	FAI		Febetron 705		During irradiation, devices were exercised by Macrodata MD-104.	21
				2 MVP 20 ns pulse			
			5		Transient upset: (0.8 to 2×10^8 rad(Si))/s	Devices were irradiated in READ mode. Logic upset is defined to occur when tester TTL input could not sense correct memory output. Memory may not be lost.	
			5		Permanent upset: (0.8 to 4×10^8 rad(Si))/s	Devices were irradiated in READ, WRITE, or PAUSE mode. Memory data were lost during radiation pulse. Most susceptible when irradiated during active READ/WRITE portion of WRITE cycle.	
			5	Flash x-ray 2 MVP 50 ns pulse	Functional survivability: $> 3 \times 10^{12}$ rad(Si)/s	Memory was scrambled, but could be rewritten, and devices functionally operated after irradiation.	

- 10 ^{60}Co Functional failure: During irradiation, devices were biased at $V_{CC} = 5\text{ V}$ and all inputs were grounded. Seven devices failed.
195 rad(Si)/s 1×10^6 rad(Si)
- 10 Sandia pulsed reactor 3×10^{14} n/cm² Functional failure: During irradiation, devices had no electrical bias. Output drive currents decreased by about 30% before functional failure. One device failed.
-

TABLE 2d. PMOS RAM'S

Device No.	Technology & size(bits)	Smpl size	Radiation source	Results	Test conditions and comments	Ref
I1101	Si-gate PMOS 256x1 Static	INT			During irradiation, devices were biased at normal operating voltage, and two randomly selected bits were monitored. All address lines but one were dc wired.	32
			- LINAC 50 ns to 4.5 μ s	Dose rate: 1.7×10^7 to 2×10^9 rad(Si)/s	No radiation-induced change of state observed.	
			6 Flash x-ray 2 Mev 30 ns pulse		An alternating logic one and zero pattern was loaded into entire array. Single bit was monitored during exposure while device was in READ mode. After irradiation, entire memory was scanned and compared with preirradiation pattern.	
I1101	Si-gate PMOS 256x1 Static	INT				31
				Dose rate: 1×10^{11} rad(Si)/s	No radiation-induced change of state was observed for single-bit test.	
				2.5×10^8 rad(Si)/s	All bits were scanned. All six devices had lost some stored information.	
			^{60}Co 1×10^5 rad(Si)/hr	Functional failure: 2×10^4 rad(Si)	During irradiation, devices were biased and tested at $V_{DD} = -10$ V and $V_{CC} = 5$ V. Tested during irradiation.	
			- Flash x-ray 2 MVP 30 ns pulse	Transient upset: 2×10^8 rad(Si)/s	Latchup was not observed at highest test dose rate, 5×10^{10} rad(Si)/s.	
			- LINAC 4 μ s pulse	Transient upset: 1.1×10^8 rad(Si)/s	Latchup was not observed at highest test dose rate, 5×10^{10} rad(Si)/s.	

TABLE 2e. I²L RAM'S

Device No.	Technology & size(bits)	Mfr	Smpl size	Radiation source	Results	Test conditions and comments	Ref
93481	4096x1	FAI	4	Seifert x-ray 150 kVp 80 to 3000 rad(Si)/min	Functional failure: 1.5x10 ⁴ rad(Si)	During irradiation, devices were biased at V _{DD} = 5 V and exercised by test pattern generator having 2 μ s cycle time. Failure criterion was first occurrence of bit failure. Standby power dissipation began to increase at 2.0x10 ⁴ rad(Si).	18
			4	⁶⁰ Co 4x10 ³ rad(Si)/min	Functional failure: 2.0x10 ⁴ rad(Si)		
			4	1.5 MeV Van de Graaff accelerator 4x10 ⁵ rad(Si)/min	Functional failure: 1.9x10 ⁴ rad(Si)		

TABLE 2f. MNOS RAM'S

Device No.	Technology & size(bits)	Smpl Mfr size	Radiation source	Results	Test conditions and comments	Ref
SR2256	Si-bulk MNOS 64x4 Static Electrically alterable Nonvolatile	SPR 15	Febetron 705 Flash x-ray 50 ns pulse		During irradiation, devices were biased at ± 15 V and were exercised by Macrodata MD-104 LSI test system. Flash x-ray burst was synchronized to any point within operational cycle.	33
				Transient upset: 4×10^8 rad(Si)/s	Device in READ mode. Flash x-ray pulse was applied 1 μ s before start of logic one or logic zero data output signal. Recovery time was one READ cycle.	
				2.4×10^{11} rad(Si)/s	Device was in CLEAR/WRITE mode. Radiation pulse was applied at start of memory enable signal (most sensitive condition for upset). Errors observed in following READ period were result of decreased peak output voltage levels of data output signals. No false data were written into or out of memory.	
				1.0×10^{12} rad(Si)/s	Device operated in PAUSE mode during irradiation. Minimum recovery time was 80 μ s. No loss of preirradiation memory data.	
		1		1.3×10^{12} rad(Si)/s	Memory electrical timing parameters were adjusted to obtain proper post-irradiation operation. No memory loss.	
		1		2.0×10^{12} rad(Si)/s	Device was destroyed.	

6 ⁶⁰Co

77 rad(Si)/s

During irradiation, devices operated in (1) CLEAR/WRITE/READ cycle, where memory was continuously cycled through all operating modes at max cycle rate, (2) PAUSE or WAIT mode, or (3) passive state (no power applied).

Dose:

2.0×10^5 rad(Si)

Read-access time degraded. Timing signals were adjusted to maintain proper device operation. Test results were independent of device operation during irradiation.

Functional failure: All devices failed because of radiation-induced gate threshold shifts in PMOS peripherals.

TABLE 3. ROM'S

Device No.	Technology & size (bits)	Mfr size	Radiation source	Results	Test conditions and comments	Ref
1833	CMOS 1024x8	RCA 2	⁶⁰ Co 13 to 180 rad(Si)/s	Functional failure: 5.5x10 ³ rad(Si)	During irradiation, devices were powered by Duracell batteries. All signal and control inputs were connected to logic one or logic zero. Devices were tested after irradiation by placement into development system.	2
IM5625	TTL 512x8	ISL 5	Flash x-ray 20 ns pulse	Dose rate: 2.5x10 ¹⁰ rad(Si)/s Latchup and upset: Not observed	During irradiation, devices were biased at V _{CC} = 5 V, and results were compared with those of unirradiated device. Peak photocurrent: ~0.5 A.	10
IM6312	Si-gate CMOS 1024x12	ISL	⁶⁰ Co 5 rad(Si)/s	Functional test was to monitor five 12-bit words stored at specific addresses. Words could comprise all ones, all zeros, or alternating ones and zeros.		1
SMS8228	STTL 1024x4	SMS 10	TRIGA reactor	Functional failure: 2.0x10 ⁴ rad(Si)	During irradiation, device was passive (V _{CC} = 0 V).	31
				Functional failure: 2.4x10 ³ rad(Si)	During irradiation, devices were biased at V _{CC} = 10 V and clock (1 MHz) = 10 V.	
				Permanent damage fluence: 2x10 ¹⁴ n/cm ²	During irradiation at room temp, devices were biased at V _{CC} = 5 V and functionally tested, and results were compared with those of unirradiated device. Performance of internal cells was measured in groups of 4-bit words.	
				Transient upset: 2x10 ⁷ rad(Si)/s	Latchup was not observed at highest test dose rate, 5x10 ¹⁰ rad(Si)/s	
		-	Flash x-ray 2 MeV 30 ns pulse	Transient upset: 2x10 ⁶ rad(Si)/s	Latchup was not observed at highest test dose rate, 5x10 ¹⁰ rad(Si)/s.	
				Transient upset: 4 μs pulse		

TABLE 4. PROM'S

Device No.	Technology & size (bits)	Mfr size	Radiation source	Results	Test conditions and comments	Ref
ER3400	MNOS EAROM 4096x1	GEN	Febetron 705	Transient upset:	Radiation was applied 200 ns before start of data output pulse in READ mode and at start of write setup time in WRITE mode. $V_{GG} = -30$ V. $V_{SS} = 5$ V. $V_{DD} = -12$ V.	34
			Flash x-ray	READ mode:		
			20 ns pulse	1.1×10^8 rad(Si)/s		
				WRITE mode:		
				3.1×10^8 rad(Si)/s		
			2 MeV	Functional failure:	Device was in PAUSE mode. No functional failure. No loss of data, but increase in READ access time.	
			Electron beam	$>9.0 \times 10^{11}$ rad(Si)/s		
			50 ns pulse			
		24	^{60}Co	Functional failure:	Devices were tested under following conditions: (2 to 4) 10^4 rad(Si) Continuous READ, continuous PAUSE, or cycling through CLEAR/WRITE/READ mode. (4 to 6) 10^4 rad(Si) Unbiased (no power applied).	
			22 rad(Si)/s			
I3601	STTL 256x4	INT	Flash x-ray	Transient upset:	During irradiation, each device had different stored pattern (all ones, all zeros, or alternating ones and zeros). All open-collector outputs were tied to 5 V supply by 1 kilohm resistor. Address inputs were driven by 8-bit binary counter.	28
			30 ns pulse	1×10^7 rad(Si)/s		

TABLE 4. PROM'S (Cont'd)

Device No.	Technology & size (bits)	Mfr size	Radiation source	Results	Test conditions and comments	Ref
I3624	STTL 512x8	INT	1 LINAC 4 μ s pulse		During and after irradiation, devices were exercised by programming two different words into two different memory locations and then cycling between these locations to monitor for correct data output.	8
				Transient upset: 2.3×10^7 rad(Si)/s		
				6.1×10^7 rad(Si)/s	Outputs saturated in zero state.	
6340D	STTL 512x8	MMI	1 LINAC	Latchup: Not observed at 1.1×10^{10} rad(Si)/s	No internal data were altered up to 1.1×10^{10} rad(Si)/s.	8
				Cumulative dose: 1×10^7 rad(Si)	Device remained functional. I_{OL} decreased by 15%, and address-to-output delay decreased by 14%.	
					Exercised during and after radiation pulse by programming two different words into two different memory locations and then cycling between these locations to monitor for correct data output.	
		1	LINAC 4 μ s pulse	Transient upset: 9.2×10^6 rad(Si)/s	Three of four outputs did not switch properly during radiation pulse. Recovery occurred in $\sim 1 \mu$ s.	
				1×10^8 rad(Si)/s	All outputs saturated in zero state.	

NCM7040	MNOS EAROM 256x1	NIT	7	Febetron 705 Flash x-ray 20 ns pulse	1	LINAC	Latchup: Not observed at 4×10^8 rad(Si)/s	Recovery time = 8 μ s. No internal data were altered over range 5×10^6 to 4×10^8 rad(Si)/s.
							Cumulative dose: 1×10^6 rad(Si)	No measurable degradation in electrical parameters.
							Neutron fluence: 1.5×10^{14} n/cm ²	Device was passive and leads were open. Device remained functional. IOL decreased by 72%, which is barely adequate to drive one gate.
							Transient upset: 2×10^7 rad(Si)/s	Radiation was applied at start of data output pulse in READ mode or at start of write setup time in WRITE mode. WRITE mode threshold was slightly higher. Device recovery time (for READ mode) ranged from 0.2 to 25 μ s. $V_{SS} = \pm 15$ and 5 V.
							Functional failure: $> 7 \times 10^{11}$ rad(Si)/s	Devices were irradiated while in PAUSE or WAIT period. Devices still functioned after recovery period.
							Functional failure: 1.7×10^4 rad(Si)	Device was either cycling through all of its operational modes or in READ mode.
							3.8×10^4 rad(Si)	Device was operating in PAUSE mode only.

TABLE 5. SHIFT REGISTERS

Device No.	Technology & size (bits)	Mfr	Smpl size	Radiation source	Results	Test conditions and comments	Ref
1402	PMOS Si-gate 256x4 Dynamic	INT	5	60Co 30 rad(Si)/s	Permanent damage: (1.4 to 15)10 ⁴ rad(Si)	During irradiation, V _{DD} = -10 V, and V _{CC} = 5 V. Clock rate = 40 kHz.	31, 35
1402	PMOS 256x4 Dynamic	INT	5	LINAC 50 ns pulse	Permanent upset: 3 rad(Si)	Bias during irradiation was not given. Upset depended on clock rate and dose received.	32
					Permanent upset: 1.0 rad(Si)	During irradiation, device was operated by inputting alternate ones and zeros.	
					1.7 to 4.5 rad(Si)	Device was continuously monitored for transient response and permanent upset.	
1405	PMOS 100x2 Dynamic	INT	-	Flash x-ray 2 MeV 30 ns pulse	Permanent upset: 1.2 rad(Si)	During irradiation, device was operated by inputting alternate ones and zeros. Device was continuously monitored for transient response and permanent upset.	32
					1.5 to 1.9 rad(Si)		
DRA2001	TTL 256x2	TII	3	TRIGA reactor 10 ms pulse	Permanent upset: 2.2 rad(Si)	During irradiation, devices were biased at V _{BB} = 2.5 V and V _{CC} = 5 V. Devices were tested after irradiation by being compared with control device.	31
					Permanent damage: 5x10 ¹⁴ n/cm ²		

2812	PMOS 32x8 FIFO	AMD	2	Flash x-ray 2 MeV 30 ns pulse	5	Transient upset: 2×10^8 rad(Si)/s	During irradiation, devices were biased and tested at $V_{BB} = 2.5$ V and $V_{CC} = 5$ V and tested as function of various stored data patterns.
				LINAC 4 μ s pulse	5	Transient upset: 2×10^8 rad(Si)/s	
				^{60}Co 13 to 180 rad(Si)	2	Functional failure: $> 8 \times 10^3$ rad(Si)	2 Devices were unbiased during exposure. Devices were tested after irradiation by placement into equipment that had been designed to use this register.
			2			Functional failure: 4×10^3 rad(Si)	Devices were biased at operating voltage during exposure and tested as above.
TMS3003	MOS 100x2 Dynamic	TII	-	Flash x-ray 30 ns pulse		Permanent upset: 1.5 rad(Si)	32 During irradiation, device was operated by inputting ones and zeros. Device was continuously monitored for transient response and permanent upset.
				LINAC 0.05 to 4 μ s pulses		0.7 to 2.2 rad(Si)	
				TRIGA 10 ms pulse		2.1 rad(Si)	
3300	PMOS 25x1 Static	FAI	-	Flash x-ray 2 MeV 30 ns pulse		Permanent upset: 1×10^9 rad(Si)/s	32 During irradiation, device was operated and continuously monitored for transient response and permanent upset.
				TRIGA reactor 20 ms pulse		Permanent upset: 1×10^6 rad(Si)/s	Peak output photoresponse was 2 V. Loss of stored information. Loss of stored information.

TABLE 5. SHIFT REGISTERS (Cont'd)

Device No.	Technology & size (bits)	Mfr	Smpl size	Radiation source	Results	Test conditions and comments	Ref
3303	MOS 25x2 Dynamic	FAI	-	Flash x-ray 2 MeV 30 ns pulse	Permanent upset: 3.0 rad(Si)	During irradiation, device was operated by inputting ones and zeros. Device was continuously monitored for transient response and permanent upset.	32
				LINAC 0.05 to 4 μ s pulses	4.0 to 7.0 rad(Si)		
				TRIGA reactor 10 ms pulse	6.0 rad(Si)		

TABLE 6. MISCELLANEOUS DEVICES

Device No.	Technology	Mfr	Smpl size	Radiation source	Results	Test conditions and comments	Ref
SN54S181	STTL	TII	6	TRIGA reactor	Permanent damage: 2.1×10^{14} n/cm ²	Arithmetic logic unit. During irradiation, devices were biased at $V_{CC} = 5$ V. After irradiation, devices were tested at maximum fanout and results were compared with those of control device.	31
		-		Flash x-ray 2 MeV 30 ns pulse	Transient upset: 1.5×10^8 rad(Si)/s		
		-		LINAC 4 μ s pulse	Transient upset: 2×10^7 rad(Si)/s		
82S100	STTL	MMI	4	Flash x-ray 20 ns pulse	Latchup: 2×10^9 rad(Si)/s No transient upset at this level	Field programmable logic array (FPLA). During irradiation, devices were biased at $V_{CC} = 4.5$ to 6.6 V. Immediately after irradiation, devices were tested for 44 different input combinations and results were compared with those of control device.	10
AM2909	STTL	AMD	5	Flash x-ray 20 ns pulse	Transient upset: 2.5×10^{10} rad(Si)/s Latchup: Not observed	Microprogram sequencer. During irradiation, devices were biased at $V_{CC} = 5$ V. Devices were functionally tested for 300 different input combinations immediately after pulse, and results were compared with control device.	10

TABLE 6. MISCELLANEOUS DEVICES (Cont'd)

Device No.	Technology	Mfr size	Radiation source	Results	Test conditions and comments	Ref
AM2910	LSTTL	AMD			Microprogram controller. Fifteen test vectors of devices under test were compared serially with those for reference device. During irradiation, devices were in static operation at 5 V bias.	9
		5	LINAC 1.4 μ s pulse	Permanent upset: 1.2×10^7 rad(Si)/s	One word of 5x12 stack register ended up with wrong bit.	
		5	Flash x-ray 25 ns pulse	Transient upset: 7×10^7 rad(Si)/s		
				Permanent upset: 1.4×10^8 rad(Si)/s		
S3000	TTL	INT			Two-bit slice microcomputer system. During irradiation, device was executing low-pass digital filter algorithm.	28
		1	Febetron 705 Flash x-ray 29 ns pulse	Functional failure: 1×10^8 rad(Si)/s	Failure to execute digital function properly.	
		1	TRIGA Mark F reactor	Failure fluence: 3×10^{14} n/cm ² Gamma dose: 1.1×10^5 rad(Si)	Computation error: all data output was zero. Four minutes after irradiation, device began to respond, and at 5 min device was computing without error.	

3001	TTL	INT	2	Febetron 705 Flash x-ray 29 ns pulse	Transient upset: 8×10^7 rad(Si)/s	Microprogram control unit. Internal registers were set to various patterns. Most susceptible state was HIGH condition with clock LOW during pulse. Devices were monitored during exposure.	28
3003	STTL	INT		Febetron 705 Flash x-ray 50 ns pulse		Look-ahead carry generator. During irradiation, devices were biased in static condition with outputs either HIGH or LOW. Devices were tested immediately after irradiation. Failure was defined as change of at least 1.4 V for output voltage.	36
IM6402	Si-gate CMOS	ISL	2	^{60}Co 5 rad(Si)/s	Transient upset: 7×10^8 rad(Si)/s	Logic one state failure level.	
					6×10^8 rad(Si)/s	Logic zero state failure level.	
						Universal asynchronous receiver-transmitter (UART). During irradiation, devices were passive, and all inputs were grounded. Functional test comprised inputting eight words and transmitting converted data through UART to comparator.	1
9404	I ² L	FAI	1	LINAC 30 ns pulse	Degradation dose: 4×10^4 rad(Si)	Supply current increased by factor of 10. Threshold voltage decreased by 40%.	
					Functional failure: $> 5 \times 10^4$ rad(Si)		
					Transient upset: 6×10^8 rad(Si)/s	Microprogram sequencer. Device was exercised through sequence test that checked integrity of data in all internal registers during and after radiation pulse. Certain bits of program counter register changed to logic zero during pulse.	15
			1	GaAs laser $\lambda = 0.904 \mu\text{m}$ 35 ns pulse	Transient upset: 6×10^8 rad(Si)/s		

TABLE 6. MISCELLANEOUS DEVICES (Cont'd)

Device No.	Technology	Mfr	Smpl size	Radiation source	Results	Test conditions and comments	Ref
9408	I^2L	FAI	1	LINAC 30 ns pulse or GaAs laser $\lambda = 0.904 \mu m$ 35 ns pulse	Transient upset: $6 \times 10^8 \text{ rad(Si)}/s$	Microprogram sequencer. Device was exercised through sequence of tests that checked integrity of data in all internal registers during and after radiation pulse. First upsets were change of certain bits of program counter register to logic zero.	15
9408	I^2L	FAI	2	WSMR fast burst reactor	Failure fluence: 10^{14} n/cm^2	Microprogram sequencer. Functionally tested by using microcomputer or functional and dc parametric tests with Tektronix S3260. Both devices survived $3 \times 10^{13} \text{ n/cm}^2$.	37
			3	^{60}Co	Functional failure: $3 \times 10^5 \text{ rad(Si)}$	Functional and dc parametric tests done with Tektronix S3260. All devices survived $1 \times 10^5 \text{ rad(Si)}$.	
			2	LINAC 30 ns pulse	Permanent upset: $6 \times 10^8 \text{ rad(Si)}/s$	Program counter data were scrambled. Cause was upset of master reset input buffer.	
			2	LINAC 100 ns pulse	$2.9 \times 10^8 \text{ rad(Si)}/s$		

MCM14512	CMOS 8-channel	MOT 1	⁶⁰ Co	Functional failure: Data selector. During irradiation, device was biased at $V_{DD} = 10$ V. Bias was removed after irradiation while device was transported to FAI 5000 IC tester. Tests were performed within 15 to 30 min after irradiation. (Device was made after 1973, and high temp gate anneal process was used.)	22
SCL14512	CMOS 8-channel	SOL 1	⁶⁰ Co	Functional failure: Data selector. During irradiation, device was biased at $V_{DD} = 10$ V. Bias was removed after irradiation while device was transported to FAI 5000 IC tester. Tests were performed within 15 to 30 min after irradiation. (Device was made after 1973, and high temp gate anneal process was used.)	22
MC14559	CMOS 512x1	MOT 5	⁶⁰ Co	Functional failure: Successive approximation register. During irradiation, devices were biased at $V_{DD} = 10$ V. Bias was removed while devices were transported to FAI 5000 IC tester. Tests were performed within 15 to 30 min after irradiation.	22

REFERENCES

- (1) L. L. Sivo and P. R. Measel, Radiation Hardness of CMOS LSI Circuits, *IEEE Trans. Nucl. Sci.*, NS-24 (1977), 2219.
- (2) C. M. Clarke, Radiation Effects on Microprocessors, Project Ptarmigan, Plessey Electronic Systems LTD., Romsey, U.K., Single Channel Radio Access Subsystem, Technical Note SCRA/042 (November 1978).
- (3) E. E. King and R. L. Martin, Effects of Ionizing Radiation on the CDP1802 Microprocessor, *IEEE Trans. Nucl. Sci.*, NS-24 (1977), 2172.
- (4) E. E. King, Total Dose Testing of Several Types of MOS Microprocessors, *IEEE Trans. Nucl. Sci.*, NS-25 (1978), 1649.
- (5) M. Simons, Radiation Effects in MOS Integrated Circuits, Research Triangle Institute, Research Triangle Park, NC, Report RTI/0991/00-03F (1978).
- (6) D. K. Myers, Ionizing Radiation Effects on Various Commercial NMOS Microprocessors, *IEEE Trans. Nucl. Sci.*, NS-24 (1977), 2169.
- (7) T. L. Pruitt, H. E. Boesch, Jr., and H. Eisen, A Technique to Measure Short-Term Annealing in MOS Microprocessors, *IEEE Trans. Nucl. Sci.*, NS-25 (1978), 1205.
- (8) P. R. Measel, L. L. Sivo, W. E. Quilitz, and T. K. Davidson, Development of a Hardened Microcontroller, *IEEE Trans. Nucl. Sci.*, NS-23 (1976), 1738.
- (9) L. L. Sivo, J. L. Andrews, L. C. Jeffers, and H. W. Mathers, Upset Testing of LSI Devices, *IEEE Trans. Nucl. Sci.*, NS-26 (1979), 4778.
- (10) L. L. Sivo, F. Rosen, and L. C. Jeffers, Latchup Screening of LSI Devices, *IEEE Trans. Nucl. Sci.*, NS-25 (1978), 1534.
- (11) J. P. Raymond, M. G. Krebs, J. E. Ashe, and C. W. Perkins, Radiation Effects on MSI/LSI Electronic Components (U), Defense Nuclear Agency DNA 4178F (August 1977). (CONFIDENTIAL)
- (12) P. W. Williamson, Radiation Effects on the Ferranti F100-L Microprocessor, Plessey Electronic Systems LTD., Romsey, U.K., Weapon Effects Co-ordination Committee Paper 112 (October 1978).
- (13) J. R. Raymond and R. L. Pease, A Comparative Evaluation of Integrated Injection Logic, *IEEE Trans. Nucl. Sci.*, NS-24 (1977), 2327.
- (14) A. G. Stanley, W. Mallen, and P. Springer, Ionizing Radiation Effects on the Microprocessor, *IEEE Trans. Nucl. Sci.*, NS-24 (1977), 1977.
- (15) T. D. Ellis and Y. D. Kim, Use of a Pulsed Laser as an Aid to Transient Upset Testing of 1^2L LSI Microcircuits, *IEEE Trans. Nucl. Sci.*, NS-25 (1978), 1489.
- (16) T. D. Ellis, Radiation Effects Characterization of the SBP9900A 16-Bit Microprocessor, *IEEE Trans. Nucl. Sci.*, NS-26 (1979), 4735.

REFERENCES (Cont'd)

- (17) A. London, D. Matteucci, and R. Wang, Establishment of a Radiation Hardened CMOS Manufacturing Process, *IEEE Trans. Nucl. Sci.*, NS-24 (1977), 2056.
- (18) M. Schlenker, D. Braeunig, M. Gaertner, and F. Glien, In Situ Radiation Tolerance Tests of MOS RAMs, *IEEE Trans. Nucl. Sci.*, NS-25 (1978), 1209.
- (19) G. P. Nelson and E. E. King, Methods for Radiation Testing Random Access Memories and LSI Circuits, *IEEE Trans. Nucl. Sci.*, NS-24 (1977), 2341.
- (20) A. London and R. C. Wang, Dose Rate and Extended Total Dose Characterization of Radiation Hardened Metal Gate CMOS Integrated Circuits, *IEEE Trans. Nucl. Sci.*, NS-25 (1978), 1172.
- (21) G. Dinger and M. G. Knoll, Radiation Evaluation Study of LSI RAM Technology, Air Force Weapons Laboratory, Kirtland Air Force Base, NM, AFWL-79-118 (1980).
- (22) D. Matteucci and M. Schneider, Radiation Testing Complementary (Symmetry) Metal Oxide Semiconductor (CMOS) Arrays for Satellites, *IEEE Trans. Nucl. Sci.*, NS-24 (1977), 2285.
- (23) G. J. Brucker, Characteristics of CMOS/Bulk and SOS Memories in a Transient Environment, *IEEE Trans. Nucl. Sci.*, NS-24 (1977), 2209.
- (24) A. Pikor and E. Reiss, Technology Advances in the Manufacture of Radiation Hardened CMOS Integrated Circuits, *IEEE Trans. Nucl. Sci.*, NS-24 (1977), 2047.
- (25) M. D. Wheeler, Gamma-Rate Testing of the RCA MWS5001D SOS 1024 Bit CMOS RAM, Plessey Electronic Systems LTD, Romsey, U.K., Working Paper PNH57 (November 1977).
- (26) M. D. Wheeler, Gamma-Rate Testing of the RCA MWS501D SOS 1024 Bit CMOS RAM, Plessey Electronic Systems LTD, Romsey, U.K., Working Paper PNH42 (November 1976).
- (27) M. Simons, Transient Radiation Effects in Silicon and Gallium Arsenide Devices, Research Triangle Institute, Research Triangle Park, NC, RTI/0991/00-04F (November 1979).
- (28) M. G. Krebs, J. R. Srour, et al, Radiation Effects on MSI/LSI Electronic Components (U), Defense Nuclear Agency DNA 4286F (August 1977). (CONFIDENTIAL)
- (29) G. L. Dinger, Radiation Characterization of the Intel 4K HMOS Static RAM (D2147-3), Air Force Weapons Laboratory Technical Memorandum (1980).
- (30) D. K. Myers, Radiation Effects on Commercial Semiconductor 4-Kilobit NMOS Memories, *IEEE Trans. Nucl. Sci.*, NS-23 (1976), 1732.
- (31) J. P. Raymond, MSI/LSI Radiation Response, Characterization and Testing, *IEEE Trans. Nucl. Sci.*, NS-21, No. 6 (1974), 308.
- (32) J. P. Raymond and D. N. Pocock, Transient Ionizing Radiation Effects in MOS/LSI, *IEEE Trans. Nucl. Sci.*, NS-18, No. 6 (1971), 288.
- (33) R. W. Tallon, Ionizing Radiation Effects on the Sperry Rand Nonvolatile 256-Bit MNOS RAM Array (SR2256), *IEEE Trans. Nucl. Sci.*, NS-25 (1978), 1176.

REFERENCES (Cont'd)

- (34) R. Tallon, Metal Nitride Oxide Semiconductor Radiation Characterization Studies, Air Force Weapons Laboratory, Kirtland Air Force Base, NM, AFWL-TR-79-39 (1979).
- (35) J. Raymond et al, Study of Radiation Effects in MSI/LSI Technologies, Defense Nuclear Agency DNA-3517 (1974).
- (36) M. Krebs, Logic-Cell-Coverage Technique for Transient Ionizing Radiation Characterization of Microcircuits, IEEE Trans. Nucl. Sci., NS-24 (1977), 2347.
- (37) T. Ellis, Radiation Effects Characterization Results on the Fairchild 9408A Microprogram Sequencer, Naval Weapons Support Center, Crane IN (1978).
- (*) G. J. Brucker, Transient Test of a CMOS/Bulk Microprocessor, RCA Astro Electronics, Princeton, NJ (1977) (draft).
- (†) N. Wilkin and C. T. Self, Radiation Effects Data, Harry Diamond Laboratories (July 1979) (draft).
- (‡) H. R. Chester, Preliminary Results of Total Gamma Test on the TMS8080 Microprocessor Using the Harwell LINAC, Letter of Transmittal, Ptarmigan Project Office, Plessey Electronic Systems LTD., Romsey, U.K., to W. H. Sellek, Ministry of Defence, Whitehall, London, U.K. (8 February 1979).
- (§) B. Deve, Characterization of AMD 2901A Microprocessor, Air Force Weapons Laboratory, Kirtland Air Force Base, NM (1980) (draft).

SYMBOLS

Technology

Manufacturer (Cont'd)

CMOS Complementary metal oxide semiconductor
 CPU Central processing unit
 EAPOM Electrically alterable read only memory
 FPLA Field programmable logic array
 HMOS High density metal oxide semiconductor
 IC Integrated circuit
 I²L Integrated injection logic
 LSTTL Low power Schottky transistor-transistor logic
 MNOS Metal nitride oxide semiconductor
 MOS Metal oxide semiconductor
 NMOS N-channel metal oxide semiconductor
 PMOS P-channel metal oxide semiconductor
 PSU Programmable storage unit
 SOS Silicon on sapphire
 STTL Schottky transistor-transistor logic
 TTL Transistor-transistor logic
 UART Universal asynchronous receiver-transmitter

NBC Nippon Electric Co., Ltd.
 NIT Nitron
 SIE Siemens
 SIG Signetics
 SMS Scientific Microsystems
 SOL Solid State
 SPR Sperry Rand
 TII Texas Instruments, Inc.
 kVp Kilovolts peak
 LINAC Linear accelerator
 MVp Megavolts peak
 WSMR White Sands Missile Range, NM

Source

Test conditions

Manufacturer

AMD Advanced Micro Devices
 EMM EMM/SEMI, Inc.
 FAI Fairchild
 FER Ferranti
 GEN General Instruments
 HAR Harris
 HUG Hughes
 INT Intel Corp.
 ISL Intersil, Inc.
 MFA Manufacturer A
 MPB Manufacturer B
 MIL Military version
 MMI Monolithic Memories, Inc.
 MOS Mostek Corp.
 MOT Motorola
 NAT National Semiconductor

C_L Load capacitance
 DI Dielectric isolation
 FIFO First in, first out
 I_{CC} Quiescent supply current
 I_{DD} Supply current
 I_I Input current
 I_{OH} Current of output in HIGH state
 I_{OL} Current of output in LOW state
 I_{pp} Primary photocurrent
 t_{pd} Propagation delay time
 V_{BB} Supply voltage to base
 V_{CC} Supply voltage to collector
 V_{DD} Supply voltage to drain
 V_{GG} Supply voltage to gate
 V_{IN} Input voltage
 V_{OH} Voltage of output in HIGH state
 V_{OL} Voltage of output in LOW state
 V_{SS} Supply voltage to source

DISTRIBUTION

SICILIAPIAT
AGED
 201 YADICK ST., STM FLOUN
 HAN YORE, NY 10014
 ATTN RALPH MADILL

ASSISTANT TO THE SECRETARY OF DEFENSE
ATOMIC ENERGY
 WASHINGTON, DC 20301
 ATTN DOCUMENT CONTROL

DIRECTOR
DEFENSE COMMUNICATIONS AGENCY
 WASHINGTON, DC 20305
 ATTN TECHNICAL LIBRARY

DEFENSE COMMUNICATION ENGINEER CENTER
 1860 WHEEL AVENUE
 BOSTON, VA 22060
 ATTN CODE 8720, C. STANSBERRY
 ATTN CODE 8320, C. W. BERNHARD
 ATTN CODE 8124C, TICH LID

NATIONAL COMMUNICATIONS SYSTEM
OFFICE OF THE MANAGER
 WASHINGTON, DC 20305
 ATTN MCS-TS C. BODMAN

DIRECTOR
DEFENSE RESEARCH & ENGINEERING
 DEPARTMENT OF DEFENSE
 WASHINGTON, DC 20301
 ATTN DD/SSS
 ATTN L. SHUREY, 68PG

DIRECTOR
DEFENSE ADVANCED RESEARCH PROJ AGENCY
 ARCHITECT BUILDING
 1400 WILSON BLVD.
 ARLINGTON, VA 22209
 ATTN TECHNICAL LIBRARY
 ATTN DR. F. A. REYNOLDS

INSTITUTE FOR DEFENSE ANALYSIS
 400 ARMY-WAY DRIVE
 ARLINGTON, VA 22202
 ATTN 10, LIBRARIAN, RUTH S. SMITH

DEFENSE TECHNICAL INFORMATION CENTER
 CANTON STATION, BUILDING 5
 ALEXANDRIA, VA 22304
 ATTN DDA-TCA (11 COMBIS)
 ATTN TC-TCA

COMMANDER
DEFENSE ELECTRONIC SUPPLY CENTER
 DARTON, VA 45444
 ATTN DISC-113, JOE DENNIS

DIRECTOR
DEFENSE INTELLIGENCE AGENCY
 WASHINGTON, DC 20301
 ATTN DA-AC2, MR. EDWARD OFARRELL
 ATTN TECHNICAL LIBRARY

LAWRENCE LIVERMORE LABORATORY
 PO BOX 808
 LIVERMORE, CA 94550
 ATTN DOCUMENT CONTROL FOR L-365
 ATTN DE HAROLD MATH
 ATTN TECH INFO DEPT, L-3
 ATTN DOC CON FOR D. HEDDER L-645 (CLASS)
 ATTN DOC CON FOR E. OTT L-389
 ATTN R. CAMATAN L-156
 ATTN LEROY C. MARTIN

DIRECTOR
DEFENSE NUCLEAR AGENCY
 WASHINGTON, DC 20305
 ATTN DDT/DB. CONRAD/DB-OSWALD
 ATTN RATH
 ATTN STIL TECH LIBRARY
 ATTN STVL
 ATTN RALV/CMDR. R. MOHR
 ATTN SPID/LT CDR RONALD S. BISHOP

DIRECTOR
INTERSERVICE NUCLEAR WEAPONS SCHOOL
 FORTLAND AFB, TX 77115
 ATTN TECH LIB

DIRECTOR
NATIONAL SECURITY AGENCY
 FT. GEORGE G. MEAD, MD 20785
 ATTN O. O. VAN GUNTER-R-52
 ATTN K. SHAFER, S-232
 ATTN P. DENOT, R-1
 ATTN TECHNICAL LIBRARY

DEPT OF ARMY
DEPUTY CHIEF OF STAFF
FOR OPERATIONS & PLANS
 WASHINGTON, DC 20310
 ATTN DAMO-SSW, NUCLEAR PLANS AND
 POLICY

COMMANDER
ARMADCON
 DUBLIN, NJ 07001
 ATTN DEDAR-LCS-V

PN
ADVANCED ATTACK HELICOPTER
 12TH & SPRUCE STS
 ST LOUIS, MO 63106
 ATTN DRCPM-AAH/WR ROMANO

COMMANDER
USA AFVALCON

PO BOX 209
 ST. LOUIS, MO 63106
 ATTN DEDAV-RPV

DIRECTOR
US ARMY BALLISTICS RESEARCH LABORATORY
 ABERDEEN PROVING GROUND, MD 21005
 ATTN DEDAK-TSB-S (STIMPD)

DIRECTOR
USA MATERIAL TESTING DIRECTORATE
 ABERDEEN PROVING GROUND, MD 21005
 ATTN SILAR-MT-F
 ATTN DEER-VL ROBERT L. HARRISON

DIRECTOR
US ARMY AMSAA
 ABERDEEN PROVING GROUND, MD 21005
 ATTN DEIST-MP

DIRECTOR
BRD ADVANCED TECH CTR
 HUNTSVILLE OFFICE
 PO BOX 1500
 HUNTSVILLE, AL 35807
 ATTN TECH LIB
 ATTN BMDATC-O, F. MOKE
 ATTN BMDATC-M, R. KELLEY
 ATTN BMDATC-W, W. GIBSON
 ATTN BMDATC-R, S. MASSEY
 ATTN BMDATC-P, R. DACE

DIRECTOR
BRD SYSTEMS COMMAND
 ATTN: R. DEKALB
 P.O. BOX 1500
 HUNTSVILLE, AL 35807

PN
CANNON ARTILLERY WEAPONS SYSTEMS
US ARMY ARMAMENT COMMAND
 ROCK ISLAND, IL 61201

COMMANDER/DIRECTOR
USA ERADCON CSVAL
 FORT MONMOUTH, NJ 07703
 ATTN PM BSTAR DELCS-P-C, W. VANDERMEER
 ATTN PM PAMAS DELCS-S, R. ROBBIANI
 ATTN PM NICHES DELCS-IR, ED WESTHOVEN

COMMANDER
US ARMY COMMUNICATIONS COMMAND
 FT. HUACHUCA, AZ 85613
 ATTN TECHNICAL LIBRARY

COMANDIAF
US ARMY MISSILE COMMAND
REDSTONE AFB, AL 35809
ATTN DESI-NGP, NUGO GREEN
ATTN DESI-LCS, EDWARD H. MENRIKEM
ATTN DESI-PG-SA, WALLACE O. BACHEN
ATTN TECHNICAL LIBRARY
ATTN DESI-RGP, VICTOR W. ROWE
ATTN DESI-DGO
ATTN DESI-MDTI, CPT JOE A. SINS
ATTN DESI-BRR
ATTN ATSM-CDF

US ARMY MISSILE & MUNITIONS
CENTER & SCHOOL
REDSTONE ARSENAL, AL 35809
ATTN A1SK-CID-P

COMMANDER
US ARMY MOBILITY EQUIP. R&D CTR
FORT BELVOIR, VA 22060
ATTN DROME-E J. BOND JR.

BOJ MGR
INVESTIGATION CONTROL SYSTEMS
ESA ELECTRONICS COMMAND
LDC 2525
T. MONMOUTH, NJ 07703

COMMANDER
S ARMY NUCLEAR AGENCY
500 BACKLICK ROAD
PRINCETON, VA 22150
ATTN MAJALAN LIND

FOJ MGR
ERSHING SYSTEM
EDSTONE ARSENAL, AL 35809
ITN DCFM-PH/MP. J. PETTIT

COMMANDER
REDSTONE SCIENTIFIC INFORMATION CTR
U S ARMY MISSILE COMMAND
REDSTONE ARSENAL, AL 35809
ATTN DEDMI-TED, CLARA T. ROGERS

COMMUNICATIONS
SECTION
MILITARY AIRCRAFT
DIVISION, NJ 07801

COMMANDER
 US ARMY S. TILLITE COMM AGENCY
 FT. MONMOUTH, NJ 07703
 ATTN DCPM-SC-5 /MR. P. ELMHEDY
 ATTN DCPM-SC-5 MR. MARSCA
 ATTN DCPM-SC-5 CHASEY
 ATTN DCPM-SC-5 CAULFIELD
 ATTN DCPM-SC-56 P. WELER
 PM
 SELECTED AMMUNITION
 PICAINTY ARSENAL
 DOVER, NJ 07801
 PM
 SINGLE CHANNEL GROUND AND AIRBORNE
 RADIO SUBSYSTEM
 US ARMY ELECTRONICS COMMAND
 FT. MONMOUTH, NJ 07703
 ATTN CANT FISHER
 DIRECTOR
 SIGNALS WARFARE LABORATORY
 VINT HILL FARM STATION
 WARRENTON, VA 22166
 ATTN DMSEL-RD-C
 ATTN DELSR-MS
 ATTN DELSW-OS
 PROJ MGR
 US ARMY TACTICAL COMM SYS
 FT. MONMOUTH, NJ 07703
 ATTN DCPM-ATC
 PROJECT MANAGER
 US ARMY TACTICAL DATA SYSTEMS
 FT. MONMOUTH, NJ 07703
 ATTN TECH LIE
 ATTN DRANE P. HUEBL
 ATTN DCPM-TDS/ MR. S. PILLORI
 PROGRAM MANAGER
 XM-1 TAME SYS
 WARREN, MI 48090
 ATTN DCPM-GM-SB/MR. BOULCOT
 ATTN DCPM-GM-SB/P. SLAUGHTER
 PROGRAM MANAGER
 FIGHTING VEHICLE SYSTEMS
 WARREN, MICHIGAN 48090
 ATTN DCPM-PVS-SELV
 ATTN DCPM-PVS-PA
 ATTN DCPM-PVS-U
 ATTN DCPM-IV
 COMMANDER
 US ARMY TEST AND EVALUATION COMMAND
 ARMYDEV PROVING GROUND, MD 21005
 ATTN DEFT-LL, P. L. KOLCHIN
 ATTN DESIF-PA, P. E. CALASSO
 ATTN TECHNICAL LIBRARY
 ATTN COL GREGORY

OFFICE OF NAVAL RESEARCH/CODES 221
 800 N. QUINCY STREET
 ARLINGTON, VA 22217
 ATTN DR. DAVID C. LEWIS
 DIRECTOR
 NAVAL RESEARCH LABORATORY
 WASHINGTON, DC 20375
 ATTN CODE 6624, JAMES C. RITTER
 ATTN CODE 6620, B. FARADAY
 ATTN CODE 6601, E. POLICKI
 ATTN CODE 6627, C. S. GUENZER
 ATTN CODE 6623, DR. GEORGE McLANE
 ATTN CODE 5262 NELSON SAKS
 ATTN CODE 5216, MR. HAROLD L. HUGHES
 DIRECTOR
 STRATEGIC SYSTEMS PROJECT OFFICE
 NAVY DEPARTMENT
 WASHINGTON, DC 20376
 ATTN SP2701, JOHN W. PITSBERGER
 ATTN MSP-2342, RICHARD L. COLEMAN
 ATTN MSP-43, TECH LIE
 ATTN MSP-230, DAVID GOLD
 ATTN MSP-2703, PHIL SPECTOR
 COMMANDING OFFICER
 NAVAL WEAPON SUPPORT CENTER
 CRANE, IN 47522
 ATTN CODE 7024, JAMES L. RAMSEY
 NAVAL WEAPONS EVALUATION FACILITY
 NUCLEAR SURVIVABILITY DEPT.
 KIRTLAND AIR FORCE BASE
 ALBUQUERQUE, NM 87117
 ATTN RALPH CARROLL, JR.
 COMMANDER
 NAVAL SURFACE WEAPONS CENTER
 WHITE OAK, SILVER SPRING, MD 20910
 ATTN CODE P-32, MR. JAMES E. PARTAR
 ATTN RICHARD SANFORD PM. 132-207
 ATTN VAN KENYON, 132-204
 ATTN KUPT ENKENS, 130-107
 COMMANDER
 NAVAL SURFACE WEAPONS CENTER
 DARLIGREN LABORATORY
 DARLIGREN, VA 22446
 ATTN CODE P54, ROBERT A. AMADORI
 ATTN L. H. LUESSEN
 USAFA/DEP
 USAF ACADEMY, COLORADO 80840
 ATTN CAPT. P. FRAASS
 COMMANDER
 AERONAUTICAL SYSTEMS DIVISION, AFSC
 WRIGHT-PATTERSON AFB, OH 45433
 ATTN ASD/TEPT
 ATTN ASD-ENFTV, WARGRICE P.O.

US ARMY TRADOC SYSTEMS
 ANALYSIS ACTIVITY
 WHITE SANDS MISSILE RANGE, NM 88002
 ATTN ATAA-TDC, MR. BERGLUND
 ATTN ATAA-TFC, OTIS E. MILLER
 COMMANDER
 US ARMY TRAINING AND DOCTRINE COMD.
 FORT MONROE, VA 23661
 ATTN ATORI-OP-58
 ATTN LTC R. S. CHISSMAN
 WEAPONS SYSTEMS EVALUATION GROUP
 400 ARMY NAVY DRIVE
 ARLINGTON, VA 22402
 ATTN DOCUMENT CONTROL
 COMMANDER
 WHITE SANDS MISSILE RANGE
 WHITE SANDS MISSILE RANGE, NM 88002
 ATTN TECHNICAL LIBRARY
 ATTN STERS-TE-ST/J. OKOUMA
 ATTN STERS-TE-AN/MS. A DELAPAZ
 COMMANDER
 NAVAL AIR SYSTEMS COMMAND
 HEADQUARTERS
 WASHINGTON, DC 21360
 ATTN LCDR WUO RANDY (AIR-350-F)
 NAVAL SURFACE WEAPONS CENTER
 DARLIGREN, VA 22446
 ATTN L. H. LUESSEN
 COMMANDER
 NAVAL ELECTRONIC SYSTEMS COMMAND
 HEADQUARTERS
 WASHINGTON, DC 20360
 ATTN PH117-115A, GUNTIP BRUNHART
 ATTN PH1 117-21
 COMMANDING OFFICER
 NAVAL INTELLIGENCE SUPPORT CTR.
 4501 SUTLAND ROAD, BLDG. 5
 WASHINGTON, DC 20360
 ATTN NISC LIBRARY
 CHIEF OF NAVAL OPERATIONS
 NAVY DEPARTMENT
 WASHINGTON, DC 20360
 ATTN CODE 604C3, ROBERT FIACCI
 SUPERINTENDENT (CODE 1424)
 NAVAL POSTGRADUATE SCHOOL
 MONTELE, CA 93940
 ATTN CODE 3124 TECH RPTS. LINEARIAN

DISTRIBUTION (Cont'd)

COMMANDER
 USAF BALLISTIC MISSILE ORGAN.
 POST OFFICE BOX 92460
 GILBERT POSTAL CENTER
 LOS ANGELES, CA 90009
 ATTN TMC, LT. G. DIAZ
 ATTN CAPT. EDWARD B. NERZ
 ATTN SFC. PETER H. STADLER
 ATTN TSN, CAPT. E. NERZ
 ATTN S2J/ MAJ R. DAVIS
 ATTN YA
 SPARK DIV./WN
 NORTON AFB, CA 92406
 ATTN WING, MAJ. RONALD JONES
 HEADQUARTERS
 AIR FORCE SYSTEMS COMMAND
 ANDREWS AFB
 WASHINGTON, DC 20331
 ATTN AFCS/SDUE/ CAPT B. HOCKERSMITH
 AF WEAPONS LABORATORY, AFSC
 KIRTLAND AFB, NM 87117
 ATTN NTC, CPT SHERSON
 ATTN NTC, J. PERRY
 ATTN NTC, E. SIMON
 ATTN NTC, RICHARD J. OLSON
 ATTN NTC, RUE J. MAIER
 ATTN NTC, JOHN L. MULLIS
 ATTN NTC, ROGER W. TALLON
 CENTRAL INTELLIGENCE AGENCY
 ATTN TECHNICAL LIBRARY
 ATTN OCE/ADD/ED CONTROL
 DEPARTMENT OF COMMERCE
 NATIONAL BUREAU OF STANDARDS
 WASHINGTON, DC 20234
 ATTN TECHNICAL LIBRARY
 ATTN KENNETH F. GALLOWAY, BLDG. 225
 ATTN ROBERT I. SCACE BLDG. 225
 MINISTRY OF DEFENSE
 OLD WAR OFFICE BLDG.
 WHITEHALL
 LONDON WC1A 2EY ENGLAND
 ATTN WILLIAM SELLER, ARDC
 NASA/GODDARD SPACE FLIGHT CENTER
 GREENBELT, MD 20771
 ATTN WILLIAM COLLIER, CODE 755/BLDG. 7
 ATTN J.W. ADOLPHSEN, CODE 311
 ATTN JULE FIRSFELD, CODE 755
 ATTN CODE 490
 NATIONAL ACADEMY OF SCIENCES
 2101 CONSTITUTION AVE, NW
 WASHINGTON, DC 20418
 ATTN R. S. SHANE NAT MATERIALS ADRESY
 COMMANDER
 MAIL STOP 30
 WANSWORTH AFB, NM 87131
 ATTN JOHN C. GARTH
 ATTN A. M. FREDERICKSON
 COMMANDER
 WIDEN AIR LOGISTICS CENTER
 HILL AFB, UT 84401
 ATTN CO/WETH MAJ. B. BLACBURN
 COMMANDER
 SACRAMENTO AIR LOGISTICS CENTER)
 MCLELLAN AFB, CA 95652
 ATTN TECHNICAL LIBRARY
 AIR FORCE AVIONICS LABORATORY, AFSC
 WRIGHT-PATTERSON AFB, OH 45433
 ATTN TECH LIB
 ATTN AFAL-TLA, MAJ. J. HEMMECKE
 ATTN AFAL/AAA
 ATTN DIE
 ATTN AFALD/PTEL
 ATTN AAD-3, D. ZANN
 HEADQUARTERS
 ELECTRONIC SYSTEMS DIVISION, (AFSC)
 L. G. HANSCOM FIELD
 BEDFORD, MA 01730
 ATTN YVEL
 ATTN TREV, LTC DAVID C. SPARKS
 ATTN DCS LARIS STAPLES
 ATTN IPT, LTC JOHN M. JASINSKI
 AF DEPUTY FOR ELEC TECHNOLOGY
 L. G. HANSCOM FIELD
 BEDFORD, MA 01731
 ATTN SHERY UPRIN
 ATTN MAJ. A. BILLOREBY
 ATTN LT. JAY JOLLY, M.S. 53
 ATTN ROBERT HUGHMAN, ETSU
 ATTN BALT SHEDD, ETSU
 ATTN PAT VAIL, ETSU
 COMMANDER
 FOREIGN TECHNOLOGY DIVISION, AFSC
 WRIGHT-PATTERSON AFB, OH 45433
 ATTN LTI
 ATTN PID/TOTR, LT. GERALD MARSHALL
 MAJ. ROMY E. GREEN
 ATTN UC-ALC/NEAP
 COMMANDER
 OFFUTT AFB
 OMAHA, NE 68113
 ATTN RUPO, LT MERRILL
 DEPARTMENT OF TRANSPORTATION
 FEDERAL AVIATION ADMINISTRATION
 HEADQUARTERS BLDG. ASE-300
 400 INDEPENDENCE AVENUE, SW
 WASHINGTON, DC 20591
 ATTN ASD-JSU
 AEROMET ELECTRO-SYSTEMS CO. DIV.
 AEROMET-GENERAL CORPORATION
 P.O. BOX 286
 AZUSA, CA 91702
 ATTN TECH LIBRARY
 ATTN DENNIS D. RUPPMAN (160-6441)
 AERONAUTIC FORD CORPORATION
 AEROSPACE & COMMUNICATIONS OPS
 AERONAUTIC DIVISION
 FORD 6 JAMHORE ROAD
 NEWPORT BEACH, CA 92663
 ATTN E. W. PONCELET, JR.
 ATTN EEN C. ATTINGER
 AEROMUTONIC FORD CORPORATION
 WESTERN DEVELOPMENT LABORATORIES DIV
 3834 FABIAN WAY
 PALO ALTO, CA 94303
 ATTN LIBRARY
 ATTN D. NESELL, GRU
 AEROSPACE CORPORATION
 PO BOX 92857
 LOS ANGELES, CA 90009
 ATTN C. B. PEARLSTON
 ATTN JULIAN PEIRREINER
 ATTN KCUC
 ATTN A.J. HOFORSKY
 ATTN A.J. LABLAN
 ATTN PALTIEL BUCHMAN
 AVCO SYSTEMS DIVISION
 201 LORELL STREET, RM. 3269
 WILMINGTON, MA 01827
 ATTN RESEARCH LIBRARY, RM 2201
 ATTN LLOYD BRUCE
 ATTN DAVID SHEARER
 ATTN ERNEST N. ASHLEY, RM 3260
 ATTN PETER ANDERSON
 HALL AEROSPACE SYSTEMS
 BOULDER INDUSTRIAL PARK
 BOX 1062
 BOULDER, CO 80306
 ATTN RICHARD L. GREENWALL WS-1-J
 BARNES ENGINEERING COMPANY
 30 COMMERCE ROAD
 STANFORD, CT 06904
 ATTN J. HANPT

THE BDN CORPORATION
7815 JONES BRANCH DRIVE
MCLAN VA 22101
ATTN: FAN EMMETT 4929
ATTN: E. M. REIGHERS
ATTN: P. DITERS
ATTN: C. SOMERS WMA
ATTN: TECHNICAL LIBRARY
ATTN: JOSEPH BRADDOCK
ATTN: G. LOPI
ATTN: V. SENESE

THE BDN CORPORATION
2000 YALE BLVD. SE
ALBUQUERQUE INTERNATIONAL
ALBUQUERQUE, NM 87106
ATTN: E.J. ARTIMONE
ATTN: BARBARA W. TOBRES
ATTN: D. C. FOWSCH
ATTN: E. L. BUTCHINS
ATTN: JIM DUBAN

BENDIX AEROSPACE SYSTEMS OPERATIONS
1919 GREEN ROAD
ANN ARBOR, MI 48107
ATTN: EARL BELTING
ATTN: J. BEIMER

BENDIX CORPORATION, THE
BOX 1150
KANSAS CITY, MO 64141
ATTN: TECH LIBRARY

BENDIX CORPORATION, THE
EPID
1400 TAYLOR AVE
BALTIMORE, MD 21204
ATTN: W. S. MCQUAY

BENDIX CORPORATION, THE
THE RESEARCH LABORATORIES DIV
BENDIX CENTER
SOUTHFIELD, MI 48075
ATTN: MAX FRANK

BENDIX CORPORATION, THE
COMMUNICATION DIVISION
EAST JOPPA ROAD - TOWSON
BALTIMORE, MD 21204
ATTN: DOCUMENT CONTROL
ATTN: ED GILFILLER

BENDIX CORPORATION, THE
717 W. RESULL DR.
SOUTH BEND, IN 46620
ATTN: RICK PARADISE - DEPT 862

BENDIX CORPORATION, THE
GUIDANCE SYSTEMS DIVISION
YERGENRO, NJ 07008
ATTN: DEPT. 6401
ATTN: W. GALLU
ATTN: G. CORLETT
ATTN: G. RESETER
ATTN: J. ROSENBERG

BOEING COMPANY, THE
BOX 3896 MS 2R-00
SEATTLE, WA 98124
ATTN: HOWARD W. WICHELIN, MS 43-75
ATTN: E. L. SMITH
ATTN: AEROSPACE LIBRARY
ATTN: ITSU ARINDRA, MS 2R-00
ATTN: ALAN JOHNSTON MS-2R-00
ATTN: CARL ROSENBERG, MS-2R-00
ATTN: LEROY SMITH

BOEING WICHITA CO.
J801 S. OLIVER ST.
WICHITA, KANSAS 67210
ATTN: MS 31-28
ATTN: JOHN D. FOSTER E 16-84

BOOZ-ALLEN AND HAMILTON, INC
776 SHREWSBURY AVE
TINTON FALLS, NJ 07724
ATTN: W. J. CHRISLER

BOOZ-ALLEN APPLIED RESEARCH
4320 EAST WEST HIGHWAY
BETHESDA, MD 20014
ATTN: DR. H. GLISSE

BURROUGHS CORPORATION
FEDERAL AND SPECIAL SYSTEMS GROUP
CENTRAL AVE AND ROUTE 252
PO BOX 517
PAOLI, PA 20301
ATTN: P. ELAZ

BURRANO ASSOCIATES, INC.
P.O. BOX 236
HARRINGTON PARK, NJ 07640
ATTN: S. BURRANO

CHARLES STARK DRAPER LABORATORY INC.
555 TECHNOLOGY SQUARE
CAMBRIDGE, MA 02139
ATTN: KENNETH FEITIG
ATTN: TECH LIB
ATTN: PAUL E. KELLEY
ATTN: KENNETH FEITIG-W.S.#54
ATTN: JENNIFER SOMM-W.S.#55
ATTN: PAUL KELLEY-W.S.#62
ATTN: ALLEN SCHUTZ-W.S.#11
ATTN: ROBERT PEDINGFIELD #51
ATTN: JAYNE PARTIDGE #62

CHRYSLER CORPORATION
DEFENSE ENGINEERING DIVISION
ATTN: MR. R.M. O'NEILL 424-01-74

CINCINNATI ELECTRONICS CORPORATION
2640 GLENDALE - HILFORD ROAD
CINCINNATI, OH 45241
ATTN: C. P. STUMP
ATTN: CARL EMOCHELMANN

COMPUTER SCIENCES CORP.
1400 SAN MATLO BLVD. SE
ALBUQUERQUE, NM 87108
ATTN: A. SCRIPP

CONTROL DATA CORPORATION
P.O. BOX 1249
MINNEAPOLIS, MN 55440
ATTN: DR. ROBERT L. CASSOLA
ATTN: THOMAS H. PREY
ATTN: E. L. HUMERTY

EATON CORPORATION
AIL DIVISION
COMAC ROAD
DEER PARK, NY 11729
ATTN: ROY BRYANT

DATAPRODUCT NLR ENGLAND
HARRIS PARK NORTH
BILLINGSFORD, CONNECTICUT 06492
ATTN: JOHN GAILLARD

DELCO ELECTRONICS DIVISION
MAIL STOP: W/S L-104
6767 HOLLISTER AVE
GULLITA, CA 93017
ATTN: JOHN MERISA
ATTN: B. PRITCHARD

DIKEWOOD CORPORATION, THE
1009 BRADBURY DRIVE, SE
UNIVERSITY RESEARCH PARK
ALBUQUERQUE, NM 87106
ATTN: L. WAYNE DAVIS

E-SYSTEMS, INC.
GREENVILLE DIVISION
PO BOX 1056
GREENVILLE, TX 75401
ATTN: LINNARY B-6160UC

E-SYSTEMS, INC.
BC1 DIVISION
1501 72ND STREET NORTH
ST. PETERSBURG, FL 34703
ATTN: W. FRENCH M S 19
ATTN: MARCEL J. GUERIN

EPPICTUS TECHNOLOGY, INC.
5303 HOLISTER AVENUE
SANTA RAPHAEL, CA 94305
ATTN: EDWARD JOHN STEELE
ATTN: ALLAN HUNT

DISTRIBUTION (Cont'd)

BUSCO, INC.
LOS ALAMOS DIVISION
PO BOX 4008
LOS ALAMOS, NM 87544
ATTN TECH LIF

ELECTROSPACE SYSTEMS INC.
PO BOX 1369
RICHARDSON, TX 75080
ATTN D. WANDENBURG
ATTN M. SWYDER

ENGINEERING EXPERIMENT STATION
GEORGIA INSTITUTE OF TECHNOLOGY
ATLANTA, GA 30332
ATTN DR. ROBERT MCILLAN

FAIRCHILD SEMICONDUCTOR
404 ELLIS STREET
MOUNTAIN VIEW, CA 94040
ATTN 2-233, MR. DAVID E. MYERS

FAIRCHILD INDUSTRIES, INC
SHERMAN FAIRCHILD TECHNOLOGY CENTER
20301 CENTURY BOULEVARD
GERMANTOWN, MD 20767
ATTN DOCUMENTATION SPECIALIST

GARRETT CORPORATION
2625 W. 190TH STREET
TOMBALL, CALIFORNIA 90509
ATTN ROBERT WEIN, DEPT. 93-9
ATTN TECH LIF

ATTN RALPH ICHIKAWA DEPT. 93-9
ATTN R. WEIL, 93-38/142

GENERAL DYNAMICS CORPORATION
ELECTRONICS DIVISION
P.O. BOX 81127
SAN DIEGO, CA 92138
ATTN J. G. MARLINGS, DEPT. 647
ATTN G. E. BOLDMAN
ATTN B. TEMPLEN
ATTN JOHN B. NAPIER

GENERAL DYNAMICS CORPORATION
POMONA OPERATION
PO BOX 2507
POMONA, CA 91766
ATTN R. B. HOWLAND

GENERAL DYNAMICS
17800 S. 141 COURT
CERRITOS, CA 90701
ATTN TED T. SHIMIZU

GENERAL DYNAMICS/CONVAIR
PO BOX 80847
SAN DIEGO, CA 92138
ATTN DR. JOHN VALEBIO M255-6200
ATTN M.B. COMB

GENERAL ELECTRIC COMPANY
SPACE DIVISION
VALLEY FORGE SPACE CENTER
PO BOX 8555
PHILADELPHIA, PA 19101
ATTN LARRY I. CHASEM, LIBRARY, MGR.
ATTN JOHN ANDRIS
ATTN LOUIS SIVO
ATTN LARRY JEFFERS

GENERAL ELECTRIC COMPANY
RE-ENTRY & ENVIRONMENTAL SYSTEMS DIV
PO BOX 7722
3184 CHELSEA STREET
PHILADELPHIA, PA 19101
ATTN LOU SULFSTED
ATTN JOHN B. GREENBAUM
ATTN G. J. PATTERSON, ROOM 5433

GENERAL ELECTRIC COMPANY
ORDNANCE SYSTEMS
100 PLASTICS AVENUE
PITTSFIELD, MA 01201
ATTN JOSEPH J. WEIDL

GENERAL ELECTRIC COMPANY
ALEXANDRIA OFFICE
2560 HUNTINGTON AVE
ALEXANDRIA, VA 22303
ATTN DASIAC, WILLIAM ALFONTE

GENERAL ELECTRIC COMPANY
TEMPO-CENTER FOR ADVANCED STUDIES
816 STATE STREET (PO DRAWER QO)
SANTA BARBARA, CA 93102
ATTN DASIAC/M. ESPIG
ATTN DASIAC/J. ROSENFELD

GENERAL ELECTRIC COMPANY
AIRCRAFT ENGINE GROUP
EVENDALE PLANT
CINCINNATI, OH 45215
ATTN JOHN A. ELLEFMOEST, E2

GENERAL ELECTRIC COMPANY
AEROSPACE ELECTRONICS SYSTEMS
PLENCH ROAD
ULICA, NY 13503
ATTN CHARLES M. REVISION, DROP 624

GENERAL MOTORS CORPORATION
7629 S. HOWELL
MILWAUKEE, WI 53219
ATTN D. BROZNIARSKI

CHURMAN AEROSPACE CORPORATION
BLTHPAOL, NY 11714
ATTN JERRY ROGERS, PLANT 35 N-27
ATTN TECHNICAL LIBRARY LOI-35

GTE SYLVANIA, INC.
164 B STREET
MILFORD, MA 02194
ATTN LEON LESINSKI

ATTN CHARLES A. THORNHILL, LIBRARIAN
ATTN JAMES A. WALDON
ATTN GEORGE M. COWEN
ATTN DAVID P. FLOOD
ATTN CHARLES H. RANESOTTUM
ATTN COM SYST DIV, EMIL P. NOTCOWE

GTE SYLVANIA, INC.
ELECTRONIC SYSTEMS GROUP
P.O. BOX 188
MT. VERN, CA 94042
ATTN PAUL JEFFRIES
ATTN DEL EVANS

HARRIS CORPORATION
GOVERNMENT INFORMATION
SYSTEM DIVISION P.O. BOX 37
MELBOURNE, FL 32901
ATTN WAYNE E. ABARR, MS TB 15/3
ATTN CHARLES ANDERSON

HARRIS SEMICONDUCTOR
P.O. BOX 883
MELBOURNE, FL 32901
ATTN TONY FITZPATRICK, LIBRARY
ATTN THOMAS J. SANDERS
ATTN KEN A. PORTS

HAZELTINE CORPORATION
CHINA HILL ROAD
GREEN LAWN, NY 11740
ATTN TECH INFO CTR, M. WAITE
ATTN C. W. NELSEN

HONEYWELL INCORPORATED
GOVERNMENT AND AERONAUTICAL
PRODUCTS DIVISION
2600 RIDGEWAY PARKWAY
MINNEAPOLIS, MN 55413
ATTN RONALD R. JOHNSON, A1622

HONEYWELL INCORPORATED
AEROSPACE DIVISION
13350 US HIGHWAY 19
ST. PETERSBURG, FL 33733
ATTN HARRISON H. NOBLE, MS 725-5A
ATTN JOHN P. SCHOEPF MS 725-5

HONEYWELL ELECTRO-OPTICS CENTER
2 FORNES ROAD
LEXINGTON, MA 02173
ATTN TECHNICAL LIBRARY
ATTN DR. J. A. BOLZER, MS-43

HUGHES AIRCRAFT COMPANY
 CERRITOS AVENUE & TEALE STREET
 CULVER CITY, CA 90230
 ATTN KEN WALLER, MS D157
 ATTN JOHN B. SINGLETARY, MS 6-D129
 ATTN L.O. DUNNIN, M.S. D129, BLDG 6
 ATTN DAN BINDER 6/D 129
 ATTN VINCENT WORMOLD 6/D 129
 ATTN L.D. MCCARTER
 ATTN M. L. PACIARD

 HUGHES AIRCRAFT CO.
 P.O. BOX 90515
 LOS ANGELES, CA 90009
 ATTN MIER FANGETT BLDG. 114 MS 7

 HUGHES AIRCRAFT COMPANY
 P.O. BOX 4310
 FULLERTON, CA 92634
 ATTN M.S. EATON, MS 100, BLDG 614

 HUGHES AIRCRAFT COMPANY
 S S CG
 P.O. BOX 62019, AIRPORT STATION
 LOS ANGELES, CA 90009
 ATTN EDWARD C. SMITH, 666/V347
 ATTN ROBERT A. GLICKMAN
 ATTN JAMES R. HALL
 ATTN DR. JERRY CORNELICK, BLDG. 373/MS A3
 ATTN E. Y. KURO, BLDG. 384 M.S. C314

 HUGHES AIRCRAFT COMPANY
 INDUSTRIAL PRODUCTS DIVISION
 6155 EL CAMINO REAL
 CARLSBAD, CA 94008
 ATTN GEORGE REFSHMAN
 ATTN CHRIS FISCHAP
 ATTN DAVE ROBINSON
 ATTN RODMAN

 IBM CORPORATION
 ROUTE 17C
 OREGO, NY 13527
 ATTN FRANK FRANKONSKY
 ATTN TECHNICAL LIBRARY

 IIT RESEARCH INSTITUTE
 ELECTROMAGNETIC COMPATIBILITY
 ANALYSIS CENTER
 FORT SEVEN
 ANNAPOLIS, MD 21402
 ATTN TECH LIA

 IIT RESEARCH INSTITUTE
 10 WEST JSTN STREET
 CHICAGO, IL 60616
 ATTN VINCE PARMANN
 ATTN J. N. MINDEL
 ATTN T. A. MARTIN

 INTEL CORPORATION
 3045 BORDEN AVE. DEPT. 268
 SANTA CLARA, CA 85050
 ATTN TIMOTHY MAY MS 2-40
 ATTN ROCKY EVANS, BIL- B170

 ION PHYSICS CORPORATION
 SOUTH BROADWAY STREET
 DUBLINGTON, MA 01803
 ATTN ROBERT D. EVANS
 ATTN N. W. HARRIS

 IRT CORPORATION
 P.O. BOX 80817
 SAN DIEGO, CA 92138
 ATTN JOHN HARRITY
 ATTN LARRY L. LONGDEN
 ATTN HENRY J. LAY
 ATTN MARION A. ROSE
 ATTN LLOYD DORCAN
 ATTN SHELTON L. JUBIST

 INTERNATIONAL TELEPHONE AND
 TELEGRAPH CORPORATION
 380 WASHINGTON AVENUE
 NUTLEY, NJ 07110
 ATTN ALEXANDER L. RICHARDSON

 ITT DCD
 492 RIVER ROAD
 NUTLEY, NJ 07110
 ATTN DICK SCHULMAN
 ATTN DAVID GRAY

 ITT AEROSPACE/OPTICAL DIV.
 3700 EAST PONTIAC ST.
 FT. WAYNE IND 46803
 ATTN L.W. RICKETS

 JAYCOM CORPORATION
 1401 CAMINO DEL MAR
 DEL MAR, CA 92014
 ATTN DR. RALPH STABL
 ATTN DR. LARRY SCOTT
 ATTN WILLIAM A. SEIDLER
 ATTN THOMAS A. TRODILLO

 JET PROPULSION LAB
 4800 OAK GROVE DR W/S T-1180
 PASADENA, CA 91103
 ATTN B. PRICE
 ATTN MICHAEL E. GAUTHIER
 ATTN ELITH MARTIN

 JOHNS HOPKINS UNIVERSITY
 APPLIED PHYSICS LABORATORY
 JOHNS HOPKINS ROAD
 LAUREL, MD 20810
 ATTN PETER E. PARTIDGE
 ATTN N. E. GIBSON — LIBRARY (NACIS)

 KAMAN SCIENCES CORPORATION
 PO BOX 7483
 COLORADO SPRINGS, CO 80933
 ATTN W. POSTER RICE
 ATTN J. ERSKINE
 ATTN J. STEARNS
 ATTN J. LUBELL
 ATTN MERLE L. LESOLING
 ATTN WERNER STARK

 LEAR SIEGLER, INC.
 POWER EQUIP. DIV.
 17600 BROADWAY AVE.
 MAPLE HEIGHTS, OHIO 44137
 ATTN A. C. OIENEC, MGR. MAIN. & REL.
 ATTN M. SCOTT BRACKETT/ TECH LIA

 LEAR SIEGLER INC.
 INSTRUMENT DIV.
 4141 EASLEIGH AVE. SE
 GRAND RAPIDS MI 49508
 ATTN STAN TITLICK M/S 113
 ATTN JOHN SIEGEL MS-103
 ATTN P. FABER MS-113

 DIALOG/LITTON SYSTEMS
 1770 WALT WHITMAN ROAD
 MILLVILLE, NY 11744
 ATTN LHMARIAN
 ATTN REL./MAINT. ENGINEERING

 LITTON SYSTEMS, INC.
 DATA SYSTEMS DIVISION
 8000 WOODLEY AVENUE M.S. 45-37
 VAN NUYS, CA 91409
 ATTN D. FREDERICK
 ATTN ERIC EUSTIS

 LITTON SYSTEMS, INC.
 GUIDANCE & CONTROL SYSTEMS DIVISION
 5500 CANOGA AVENUE
 WOODLAND HILLS, CA 91365 MAIL ZONE 79
 ATTN MARK S. COOPER
 ATTN JOHN P. REITLER
 ATTN G.E. BLOOM
 ATTN GEROLD S. ROLLAMP
 ATTN JOHN S. BUCK

DISTRIBUTION (Cont'd)

LOCKHEED MISSILES AND SPACE COMPANY
P. O. BOX 504
BIRMINGHAM, CA 35400
ATTN D. ROBERT PHILLIPS LMSC-SND DEPT.
ATTN TIMOTHY STULTZ
ATTN SAMUEL L. TAINUTY D / NS-45
ATTN MR. E. A. SMITH, BLDG. 151
ATTN DR. D. G. GIBSON BLDG. 151
ATTN DR. J. C. IER BLDG. 151
ATTN J. CAYOT BLDG. 153
ATTN S. L. KIMURA, D/81-14
ATTN L-386 DEPT 81-03 BLDG. 153
ATTN W. D. LOMLEY
ATTN W. A. THORNTON
ATTN L. J. MABEL DEPT 85-05
ATTN G. P. MANCHESTER

LOS ALAMOS SCIENTIFIC LABORATORY
P.O. BOX 1663
LOS ALAMOS, NM 87544
ATTN S.A. BROWN

MAGNAVOX COMPANY
2131 COLISEUM BLVD.
FT. WATNE, INDIANA 46803
ATTN L. PERALTA
ATTN E. E. RICHARDSON

MAGNAVOX GOVT. AND INDUS. ELEC. CO.
46 INDUSTRIAL AVENUE
MANNAN, NJ 07430
ATTN: BLT NESTLER

MARTIN MARETTA AEROSPACE
ORLANDO DIVISION
PO BOX 5437
ORLANDO, FL 3281
ATTN HAROLD CATES
ATTN P. POUSE
ATTN J.G. SIMMONS MP 163
ATTN J. HENDERSON, MP156
ATTN DR. C. WHITESCARTER MP 246

MARTIN MARETTA CORPORATION
RAVIER DIVISION
PO BOX 179
DENVER, CO 80201
ATTN PAUL G. EASE, MAIL DB350
ATTN BEN T. GRAMM, MS P-0504
ATTN GEORGE HARMOND MS E0530
ATTN PARTS ENGINEERING B0540

MATTELL LABORATORIES, INC.
9444 BALBOA AVENUE
SAN DIEGO, CA 92123
ATTN JOHN E. RAUCH

MC DONNELL DOUGLAS CORPORATION
5301 BOLMA AVENUE
BIRMINGHAM BEACH, CA 92647
ATTN B. P. SPARE, MS 13-3
ATTN P. ALPHRETT, MS 13-3
ATTN BRIAN P. TRIGGS
GEORGE C. MESSEMER
3111 BEL AIR DR, 7P
LAS VEGAS, NV 89109
MISSION RESEARCH CORPORATION
PO BOX 669J, STATION C
ALBUQUERQUE, NM 87108
ATTN LARRY D. SCOTT
ATTN HAROLD PRICE
ATTN JOHN SCHNEIDER
MISSION RESEARCH CORPORATION
BOX 1209
LA JOLLA, CA 92038
ATTN V. A. J. VAN LINT
ATTN JAMES RAYMOND
ATTN DR. J. AZARWICZ
ATTN ROBERT BERGER
ATTN DONALD R. NEMOROS
M.I.T. LINCOLN LABORATORY
PO BOX 73
LEXINGTON, MA 02173
ATTN LIONA LOUGHLIN, LIBRARIAN A-062
ATTN MICHAEL GILMORE
MOTOROLA GOVERNMENT ELECTRONICS
8201 E. McDOWELL ROAD
SCOTTSDALE, AZ 85252
ATTN G. GARDNER, M.D. 204J
ATTN CHARLES VOLE
ATTN DR. TET FANG
ATTN GREGORY JARCZYK
NATIONAL SEMICONDUCTOR
2800 SEMICONDUCTOR DRIVE
SANTA CLARA, CA 95051
ATTN APATIE LUNDON
ATTN TONY CARA MS C2350
NORTHROP CORPORATION
ELECTRONIC DIVISION
1 RESEARCH PARK
PALOS VERDES PENINSULA, CA 92074
ATTN BOYCE T. AHLPORT
NORTHROP CORPORATION
NORTHROP RESEARCH AND
TECHNOLOGY CENTER
1 RESEARCH PARK
PALOS VERDES PENINSULA, CA 90274
ATTN J. REND

NORTHROP CORPORATION
ELECTRONIC DIVISION
2201 WEST 120TH STREET
MATHURNE, CA 90250
ATTN STANLEY W. STEWART
ATTN DAVID J. STROBEL
ATTN P. E. GARDNER
NOVATECHNICS, INC.
PO BOX 878
POMPANO BEACH, FLA 33061
ATTN WM. J. RIGERD
ATTN MR. JACK DETNER
PHYSICS INTERNATIONAL COMPANY
2700 MERCED STREET
SAN LEANDRO, CA 94577
ATTN TECH LIR
ATTN LEN VANNUCKI
ATTN JOE KUCULY
QUESTRON CORP.
101 CONTINENTAL BLVD SUITE 500
EL SEGUNDO, CA 90246
ATTN JAMES P. SPRATT
R & D ASSOCIATES
PO BOX 8695
MARINA DEL REY, CA 90291
ATTN ROBERT A. ROLL
ATTN CHARLES MO
ATTN HYRON GAGE
R & D ASSOCIATES
1401 WILSON BLVD, #500
ARLINGTON, VA 22209
ATTN JOHN BONDARDI
RAND CORPORATION, THE
1700 MAIN STREET
SANTA MONICA, CA 90406
ATTN TECHNICAL LINEART
RAYTHEON COMPANY
HARTWELL ROAD
BEDFORD, MA 01730
ATTN CAJANAN R. JOSHI, RADAR SYS LAB
RAYTHEON COMPANY
528 BOSTON POST ROAD
SOUTHURY, MA 01776
ATTN HAROLD L. FLEISCHER
ATTN JAMES P. WICKRACK
ATTN ROBERT N. DILLIER, 4-NS 1NS
ATTN GERALD L. MARION
ATTN GEORGE V. RUSSUTH
ATTN B. W. SCRUFF

RCA RESEARCH LABORATORY
PO BOX 800, LOCUST CORNER
PRINCETON, NJ 08540
ATTN GEORGE J. BRUCKER
ATTN TECH LIB
ATTN SUBINDER S. SEENRA

RCA CORPORATION
SOLID STATE TECHNOLOGY CENTER
RT 202
SOMERVILLE, NJ 08876
ATTN HAROLD BOREAN
ATTN ST COHEN
ATTN WILLIAM ALLEN
ATTN BILL SCHILP

MAIL LOCATION JA

RCA CORPORATION
GOVERNMENT & COMMERCIAL SYSTEMS
MISSILE & SURFACE RADAR DIVISION
MARINE BOUTWAT & BORTON LANDING RD
MOONSTOWN, NJ 08057
ATTN ANDREW L. WAPREN

RCA CORPORATION
BLDG. 10-6
FRONT & COOPER STREETS
GARDEN, NJ 08012
ATTN A. VAN KEEFEN, 13-5-2
ATTN W.P. MARGRETT
ATTN HENRY W. RAISNP
ATTN LEBETH A. WHITEACRE
ATTN ROBERT P. MAGTARICS
ATTN MURDOX ROVELL

RESEARCH TRIANGLE INSTITUTE
PO BOX 12194
RESEARCH TRIANGLE PARK, NC 27709
ATTN DR. NATHAN SIMONE

ROCKWELL/COLLINS
855 35TH STREET N.E.
CEDAR RAPIDS, IOWA 52402
ATTN A.B. LANGENFELD 137-13K
ATTN DON VINCENT

ROCKWELL INTERNATIONAL CORPORATION
3370 MIRMALOMA AVENUE
ANARHEIN, CA 92803
ATTN E. P. ROLL
ATTN V. E. DEMARTINO
ATTN J. BLANDFORD
ATTN P. E. HAFROCK

ROCKWELL INTERNATIONAL CORPORATION
SATELLITE SYSTEMS DIVISION
12214 SOUTH LAKEWOOD BOULEVARD
DUNSMY, CA 90241
ATTN JAMES W. HAPPEY
ATTN RICHARD J. HENPNEY MS 5871

ROCKWELL INTERNATIONAL CORPORATION
TECHNICAL INFORMATION CENTER
P. O. BOX 92089 90009
LOS ANGELES, CA 90009
ATTN T. B. YATES

SANDERS ASSOCIATES, INC.
95 CANAL STREET
NASHUA, NH 03060
ATTN L. STOMMES MAIL STOP: NCAL-6270

SANDIA LABORATORIES
LIVERMORE LABORATORY
PO BOX 1649
LIVERMORE, CA 94550
ATTN TECHNICAL LIBRARY

SANDIA LABORATORIES
PO BOX 5800
ALBUQUERQUE, NM 87185
ATTN ERM FLOYD, 2332
ATTN J. A. MOURD, 4360
ATTN RAY GREGORY, 2140
ATTN FLOYD COFFAGE, 4362
ATTN C. GUTH, 2110
ATTN E. D. KINNEY, 2326
ATTN E. L. SCHWELBEL, 5110
ATTN JOHN R. STICHMAN, 2167
ATTN W. R. DAVES, JR., 2144
ATTN GRANT J. LOCKWOOD, 4332
ATTN LAWRENCE D. POSEY, 4450
ATTN STANLEY B. POSKE, 1242
ATTN HOWARD H. SANDER

SANTA BARBARA RESEARCH CORPORATION
75 CORUMAR DRIVE
GOLETA, CA 93017
ATTN P. MALEK

BEERS ASSOCIATES
P. O. BOX 2549
RISTON, VA 22096
ATTN PREM SETTY, SCIENTIST

SCIENCE APPLICATIONS, INC.
PO BOX 2351
LA JOLLA, CA 92038
ATTN J. ROBERT BLYSTER
ATTN DAVID LONG
ATTN STEVE DALICH
ATTN RUGER FITZBILSON
ATTN RON RAMKINSON
ATTN EDWARD E. O'DONNELL

SCIENCE APPLICATIONS, INC.
BUNTSVILLE DIVISION
2108 W. CLINTON AVENUE
SUIITE 700
BUNTSVILLE, AL 35805
ATTN TECH LIB
ATTN JOHN BRJPCZYNSKI

SCIENCE APPLICATIONS, INC.
8300 OLD COURTHOUSE ROAD
VILNNA, VA 22180
ATTN RICHARD SUTTON, SENIOR SCIENTIST

SCIENCE APPLICATIONS, INC.
J564 LINCOLN AVE, SUITE 5
OGDEN, UT 84401
ATTN D. BILLWARD

SELCO SYSTEMS INC.
65 MARCUS DR.
MELVILLE, L.I. NY 11747
ATTN MYRON GOLDFEDER
ATTN B. GABRIELI

SINCLAIR COMPANY, THE
150 JOTURA ROAD
WATNL, NJ 07470
ATTN NIKOLAI KLINKOSKY
ATTN TECH INFO CENTER 12BJ3
ATTN J. BRINERAN, MS 12B67

SPIERRY RAND CORPORATION
UNIVAC DIVISION
DEFENSE SYSTEMS DIVISION
PO BOX 3525 MAIL STATION 19J1
ST. PAUL, MN 55116
ATTN JAMES A. INDA, MSV2125
ATTN TECH LHM
ATTN M. S. ASP MSV0516

SPIERRY RAND CORPORATION
GYRUSCOPE DIVISION
ONEAT NECK, NY 11020
ATTN FRANK V. SCARAVAGLIONE C-7

SPIERRY RAND CORPORATION
SPIERRY FLIGHT SYSTEMS DIVISION
PO BOX 21111
PHOENIX, AZ 85036
ATTN D. A. SCHOR, ROOM 114C
ATTN TECH LHM

SPIRE CORP.
PATRIOTS PARK
BEDFORD, MA 01730
ATTN ROGER G. LITTLE

SRI INTERNATIONAL-JJ027
333 PAVENWOOD AVE
MENLO PARK, CA 94025
ATTN BURT W. GASTEN

SYSTEMS SCIENCE AND SOFTWARE
PO BOX 4803
MAYFORD, CA 94540
ATTN TECH LIB

DISTRIBUTION (Cont'd)

TELETYPE BROWN ENGINEERING
CUMMINGS RESEARCH PARK
HUNTSVILLE, AL 35897
ATTN MELVIN PRICE, MS 44
ATTN FRED O. LEOPARD

TELETYPE SYSTEMS CO.
19401 MUNDROFF ST.
NORTHridge, CA 91324
ATTN JOSEPH SWART MS 46

TELEPHONICS
770 PARK AVE
HUNTINGTON, NY 11743
ATTN ED WUPPHY

TEXAS INSTRUMENTS, INC.
PO BOX 226015
DALLAS, TX 75226
ATTN DONALD J. MANUS, MS 72
ATTN TECH LIB MS 212
ATTN MOU YOUNG NAM
ATTN FRANK W. FORLENZ

TRACOR
4500 TRACOR LANE
AUSTIN, TX 78721
ATTN P. WILSON

TW9 DEFENSE & SPACE SYS GROUP
ONE SPACE PARK
BURNING WEAVER, CA 90278
ATTN O. E. ADAMS R1/2144
ATTN TECH INFO CENTER/S-1930
ATTN D. M. CLEMENT, R1-2146
ATTN GORDON H. MENSTER, R1-2062
ATTN A. WITTELES, R1-2144
ATTN RUDER DUFF, R1-2062
ATTN FRANK C. FRIEDT, R1-2062
ATTN T. LUNN R4/1002
ATTN E. MORGAN R1/2154
ATTN W. WILLIS R1-2078

TW9 DEFENSE & SPACE SYS GROUP
2423 TELLER ROAD
MERRITT PARK, CA 94320
ATTN HOWARD M. KATZJEN
TW9 DEFENSE & SPACE SYS GROUP
P.O. BOX 1310
SAN BERNARDINO, CA 92402
ATTN P. R. FAY
ATTN E. KETTER 527/712
ATTN E. L. RUSSELL MS 527/712

TW9 SYSTEMS AND ENERGY
DEFENSE AND SYSTEMS GROUP
P.O. BOX 364
CLEARFIELD, UT 84015
ATTN A. B. CORSENA
ATTN B. G. GILLAND

UNITED AIRCRAFT CORPORATION
HAMILTON STANDARD DIVISION
BRADLEY INTERNATIONAL AIRPORT
WINDSOR LOCKS, CT 06098
ATTN RAYMOND G. GIGUEBE

UNITED TECHNOLOGY CORPORATION
NORDEN SYSTEMS DIVISION
100 WELYN ST
NORWALL, CT 06856
ATTN DENNIS LUNGO, MS 1151
ATTN DAVID N. STURTEVANT MS L012

VOUGHT CORPORATION
ADVANCED TECHNOLOGY CENTER
PO BOX 226144
DALLAS, TX 75266
ATTN DR. W. L. LANCE

WESTINGHOUSE ELECTRIC CORPORATION
ASTRONUCLEAR LABORATORY
PO BOX 10864
PITTSBURGH, PA 15236
ATTN TECH LIB

WESTINGHOUSE ELECTRIC CORPORATION
DEFENSE AND ELECTRONIC SYSTEMS CENTER
PO BOX 1521
BALTIMORE, MD 21203
ATTN HENRY P. KALAPACA, MS3330

WESTINGHOUSE ELECTRIC CORPORATION
RESEARCH AND DEVELOPMENT CENTER
1310 BRULAR ROAD, CHURCHILL BOROUGH
PITTSBURGH, PA 15235
ATTN TECH LIB BLDG-302 ROOM 104
ATTN NICHOLAS NUSON

WETEX
ATTN H. ZAGORITES

ROCKWELL INTERNATIONAL CORP.
1370 MINERAL AVE.
ANAHEIM, CA 92801
ATTN HARRY TENOVAN
ATTN ROBERT SCHREIDER
ATTN M. BEGUMALA, MS HB15
ATTN TECHNICAL LIBRARY

US ARMY ELECTRONICS RESEARCH
AND DEVELOPMENT COMMAND
ATTN TECHNICAL DIRECTOR, DBDEL-CI
HARRY DIAMOND LABORATORIES
ATTN CO/TO/TSO/DIVISION DIRECTORS
ATTN RECORD COPY, R1200
ATTN EDL LIBRARY, (3 COPIES) R1100
ATTN EDL LIBRARY, (WOODBRIDGE) R1100
ATTN TECHNICAL REPORTS BRANCH, R1300
ATTN CHAIRMAN, EDITORIAL COMMITTEE
ATTN CHIEF, 10000
ATTN CHIEF, 11000
ATTN CHIEF, 11400
ATTN CHIEF, 11500
ATTN CHIEF, 13000
ATTN CHIEF, 13500
ATTN CHIEF, 15000
ATTN CHIEF, 15200
ATTN CHIEF, 15300
ATTN CHIEF, 21000
ATTN CHIEF, 21100
ATTN CHIEF, 21200
ATTN CHIEF, 21300
ATTN CHIEF, 21500
ATTN CHIEF, 22000
ATTN CHIEF, 22100
ATTN CHIEF, 22300
ATTN CHIEF, 22800
ATTN CHIEF, 22900
ATTN CHIEF, 24000
ATTN CHIEF, 24600
ATTN CHIEF, 24300
ATTN CHIEF, 24500
ATTN CHIEF, 24800
ATTN CHIEF, 26000
ATTN CHIEF, 26100
ATTN CHIEF, 26200
ATTN CHIEF, 26400
ATTN JOHN CORFICAN, 20240
ATTN FRED RALICKI, 20240
ATTN PAUL REIMER, 22100
ATTN C. T. SELF, 22800
ATTN NEIL WILKIN, 22800
ATTN SID RAYNER, 22800
ATTN CHRIS MOYKIN, 22800
ATTN MARE RUMBAUGH, 22800
ATTN R. POLIMADEL, 21 COPIES
ATTN H. EISEN, 10 COPIES
ATTN K. PINERO 2 COPIES