

MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

9) Final report, 1 Feb 79 - 31 Jan 80

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO. A089 716	3. RECIPIENT'S CATALOG NUMBER
6 4. TITLE (and Subtitle) Nearshore Wave Characteristics Generated by Variable Winds	7. AUTHOR(s) 10 M. Aziz/Tayfun	5. TYPE OF REPORT & PERIOD COVERED Final-February 1, 1979 to January 31, 1980
		6. PERFORMING ORG. REPORT NUMBER NCSU-79-7
9. PERFORMING ORGANIZATION NAME AND ADDRESS Dept. of Marine Science and Engineering ✓ North Carolina State University P.O. Box 5923, Raleigh, NC 27650	11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research, Geography Programs Code 462 Arlington, Virginia 22217	8. CONTRACT OR GRANT NUMBER(s) 15 N00014-79-C-0287
		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS PE 61153N NR 388150 12/45
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Office of Naval Research Resident Representative Georgia Institute of Technology, Rm. 325, Hirman Research Building, Atlanta, GA 30332	15. SECURITY CLASS. (of this report) Unclassified	12. REPORT DATE January 1980
		13. NUMBER OF PAGES 36
16. DISTRIBUTION STATEMENT (of this Report)  Distribution of this report is unlimited.		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Bottom Friction; Coastal Waves; Equilibrium Spectrum; Frictional Dissipation; Radiative Transport; Refraction; Significant Wave Height; Wave Forecasting; Wave Period; Wind Duration; Wind Fetch, Wind Waves.		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) → The prediction of wave characteristics generated by variable winds under fetch-and duration-limited conditions is considered by using a parametric approach and a simplified form of the radiative transport equation. The wind-generated sea surface is characterized in terms of an equilibrium range spectrum with a well-defined low wave number cut-off. By relating the local wind velocity to the rate of increase in wave energy and incorporating the refractive and frictional effects of transitional water -		

DTIC ELECTE SEP 3 0 1980

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE  
S/N 0102- LF-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

395078 S/C

JCE

Abstract Cont'd

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

depths into the formulation, governing equations are derived to predict the development of a wind-wave field in terms of integral properties of the spectrum such as mean period, direction, and significant wave height. Under deep water conditions, governing equations admit simple closed form solutions which are shown to compare very favorably with observational data as well as various wind-wave prediction formulae currently available. Consequently, they are numerically solved first for the case of wind-waves in uniform water depth and then for a circular basin with variable bathymetry as an illustrative general case.

Accession	
DTIC Card	<input checked="" type="checkbox"/>
DDC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution	
Availability	
Dist.	Avail. or Special
A	

S/N 0102-LF-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

Department of Marine Science and Engineering  
North Carolina State University

NEARSHORE WAVE CHARACTERISTICS GENERATED  
BY VARIABLE WINDS

By

M. Aziz Tayfun

Technical Report No. 79-7  
Contract No. N00014-79-C-0287  
with the OFFICE OF NAVAL RESEARCH GEOGRAPHY PROGRAMS

January, 1980

## CONTENTS

	Page
List of Figures.....	ii
Abstract.....	iii
Introduction.....	1
Assumptions and Formulation.....	4
Governing Equations.....	8
Comparison with Existing Theories in Deep Water.....	11
Forecasting in Finite Water Depth.....	16
Summary and Concluding Remarks.....	21
References.....	32

## LIST OF FIGURES

Figure		Page
1	Comparison of Observational Data of Wind-Wave Parameters with Various Forecasting Theories for Conditions of Unlimited Duration in Deep Water.	24
2	Comparison of Observational Data of Wind-Wave Parameters with Various Forecasting Theories for Conditions of Unlimited Fetch in Deep Water.	25
3	Forecasting of Wind-Wave Parameters for Conditions of Unlimited Duration in Uniform Water Depths: A Comparison of SPM Theory with the Present Study.	26
4	Forecasting of Wind-Wave Parameters for Conditions of Unlimited Fetch in Uniform Water Depths Based on the Present Study.	27
5	Forecasting of Duration-and Fetch-Limited Wind-Wave Parameters in Uniform Water Depth ( $d = 0.3$ ) Based on the Present Study.	28
6	Forecasting of Wind-Wave Parameters for Conditions of Unlimited Duration in a Circular Basin with Variable Bathymetry: Diagram Illustrating Depth Contours, Wind Direction, and Computed Wave Rays.	29
7	Contours of Scaled Wave Period $T$ .	30
8	Contours of Scaled Significant Wave Height $H$ .	31

## ABSTRACT

The prediction of wave characteristics generated by variable winds under fetch-and duration-limited conditions is considered by using a parametric approach and a simplified form of the radiative transport equation. The wind-generated sea surface is characterized in terms of an equilibrium range spectrum with a well-defined low wave number cut-off. By relating the local wind velocity to the rate of increase in wave energy and incorporating the refractive and frictional effects of transitional water depths into the formulation, governing equations are derived to predict the development of a wind-wave field in terms of integral properties of the spectrum such as mean period, direction, and significant wave height. Under deep water conditions, governing equations admit simple closed form solutions which are shown to compare very favorably with observational data as well as various wind-wave prediction formulae currently available. Consequently, they are numerically solved first for the case of wind-waves in uniform water depth and then for a circular basin with variable bathymetry as an illustrative general case.



## INTRODUCTION

The field of wind-generated waves has been the subject of intensive research effort over the last three decades and, as a natural consequence, a great deal of progress has been made on various aspects relevant to understanding the physics of wind waves, their generation, propagation and dissipation. An excellent review of recent advances in the theory of wind waves, their observation, measurement and prediction is given by Barnett and Kenyon (2). It appears that, in spite of these advances achieved, the present state of knowledge is still in need of considerable improvement, and various gaps in theory, observation and instrumentation remain to be filled through future research.

One of the primary applications of wind wave research is wave forecasting. The complete problem is a field radiation problem in which the directional energy spectrum of a wave field is governed spatially and temporally by an energy balance or, radiative transfer equation (1,2,3,10,11,21,22,23). The solution of the radiative transfer equation requires integration of various non-linear source terms representing the action of local winds, wave-wave interactions, dissipative forces, etc. along wave rays which are the propagation paths given by the Hamilton-Jacobian equations. However, the integration is not straightforward, since the source terms are non-linear. This means that different rays are coupled, making the solution of the problem quite difficult and impractical under general conditions. As a

result, most of the explicit applications such as those demonstrated by Hasselmann and Collins (11), Resio and Vincent (22, 23), and others (1,2,3,7,14,19) are either based on simplified approximations of various source terms or consider deep water conditions. At present, there is a large number of such computer-based discrete spectral models for forecasting waves (see, e.g., Refs. 7,14,19).

A second approach which avoids the intricate complexity of discrete spectral models requiring large computers and complex programming is the parametric specification and forecasting of wind waves. This approach is based on one-dimensional generation models which parameterize some integral property of the wave spectrum such as wave height, or wave period in terms of wind speed, fetch and wind duration. Included in this group are the original Sverdrup and Munk model (28), and its subsequent versions improved by Bretschneider (4, 25), and Ijima and Tang (12,25) based on quasi-empirical, quasi-theoretical arguments, and the methods developed by Pierson, Neuman and James (20) and Wilson (30). More recently, Hasselmann et al. (10) have proposed a parametric model based on the assumption of the invariant spectral shape of the JONSWAP spectrum. The validity of this model depends on the dominance of the self-stabilizing effects of wave-wave interactions as compared to external sources of energy. A comparison of various parametric models is given by Resio and Vincent (22).

Parametric and discrete spectral models have been experimented with mostly under open ocean conditions. Except for the recent applications of discrete spectral models to the Great Lakes

by Resio and Vincent (22,23), and the parametric procedures developed by Bretshneider (4,25), and Ijima and Tang (12,25) for conditions of unlimited wind duration in uniform water depth, there has been a lack of effort to extend either of these approaches to wave field predictions involving variable winds in areas bounded by irregular shorelines. Various pragmatic procedures and definitions of effective fetch and effective duration have been used to incorporate such effects into the nearshore applications (see e.g., Ref. 24).

The principal motivation here is to develop a method of forecasting nearshore wave characteristics generated by variable winds under fetch-and duration-limited conditions by using a parametric approach and a simplified form of the radiative transfer equation. It is assumed that the wind sea is characterized in terms of an equilibrium range spectrum with a well-defined low wave number cut-off. By relating the local wind velocity to the rate of increase in wave energy and incorporating the refractive and frictional effects of transitional water depths into the formulation, governing equations are derived to predict the development of a wind-wave field in terms of the integral properties of the spectrum such as mean period and significant wave height. Various incompletely understood or complex mechanisms such as wave-wave interactions, turbulent dissipation due to wave breaking, wave-current interactions, percolation, etc. are neglected. Under deep water conditions, governing equations admit simple closed form solutions which

are shown to compare very favorably with observational data as well as various wind-wave prediction formulae currently available. Consequently, they are numerically solved first for the case of wind-waves in uniform water depth and then for a circular basin with variable bathymetry as an illustrative general case.

#### ASSUMPTIONS AND FORMULATION

With the neglect of current-wave interactions, the energy balance of wind generated waves can be expressed as (see, e.g., Ref. 21, page 147)

$$d\Psi/dt = (\partial/\partial t + \vec{V} \cdot \vec{\nabla}) \Psi = \Gamma \quad (1)$$

where  $\Psi(\vec{k})$  = directional spectral density over a two-dimensional wave number space  $\vec{k} = (k_1, k_2)$ ;  $\vec{V}$  = group velocity associated with the spectral component with wave number vector  $\vec{k}$ ;  $\vec{\nabla}$  = horizontal gradient operator; and,  $\Gamma$  represents various source terms from any process that transfers energy into and out of the spectral component  $\Psi(\vec{k})$ . For a detailed discussion of the general form of  $\Gamma$ , the reader is referred to Refs 10 and 23. Eq. (1) implies that the rate of change of spectral density along the propagation path of a wave group is  $\Gamma$ , which is in general a complex non-linear function of the local wind and the spectral density  $\Psi$  itself. The propagation path is given by the Hamilton-Jacobian equations

$$dx_i/dt = \partial\sigma/\partial k_i = V_i \quad (2)$$

$$dk_i/dt = -\partial\sigma/\partial x_i \quad (3)$$

where  $x_i$  ( $i=1,2$ ) represents a horizontal coordinate system in the still water plane;

$$\sigma = (gk \tanh kd)^{\frac{1}{2}} \quad (4)$$

is the radian frequency with  $g$  = gravitational constant; and,  $d$  = local still water depth. Eqs. 2 and 3 describe, respectively, the wave ray associated with the spectral component  $\Psi(\vec{k})$  and the variation of  $\vec{k}$  along that ray. Therefore, assuming that the functional form of  $\Gamma$  is known, the solution of the wind-wave problem involves solving first the refraction problem, i.e., Eqs. 2 and 3. Once the rays are determined, Eq. 1 is integrated along each ray. As previously mentioned in the introduction, the integration is not straightforward, since  $\Gamma$  is non-linear and wave rays are coupled. Consequently, in order to overcome some of these difficulties, we will appeal to various simplifying approximations as follows.

Functional Form of  $\Psi(\vec{k})$ . - For wind generated waves, the spectral density function  $\Psi$  is observed to have an equilibrium range with a well-defined low-wave-number cut-off (13,21,29). Combining the dimensional reasonings of Phillips (21), Kitaigorodskii et al. (13), and Thornton (29), it can be shown that

$$\Psi(\vec{k}) = (\beta/2\pi) n k^{-4} ; \quad k \geq k_m, \quad |\alpha| \leq \pi$$

where  $\beta \approx 1.31 \times 10^{-2}$ ;  $\alpha$  = direction of the saturated components;  $k_m$  = low-wave-number cut-off; and,

$$n = \frac{1}{2} \{1 + (2kd/\sinh 2kd)\} \quad (5)$$

The spectral density as a function of wave number moduli or, the distribution of the mean square surface displacement  $\overline{\eta^2}$ , regardless of direction, is given by

$$F(k) = \int_{-\pi}^{\pi} \Psi(\vec{k}) k \, d\alpha = \beta n k^{-3} ; k \geq k_m \quad (6)$$

If it is assumed that the spectral density  $\Psi$  is mostly concentrated in the direction of the spectral peak wave number  $\vec{k}_m$ ,  $F(k)$  is approximately equal to the integral of  $\Psi(\vec{k})$  along lines perpendicular to the direction of  $\vec{k}_m$  (see, e.g., Ref. 21, page 130).

One-Dimensional Form of Energy Balance. - Considering the direction of the spectral peak wave number  $\vec{k}_m$  as a reference, a contracted form of the energy balance equation can be obtained by integrating Eq. 1 along lines perpendicular to  $\vec{k}_m$ . Provided that  $\Psi(\vec{k})$  is mostly concentrated around  $\vec{k}_m$ , the contracted form can be approximated as

$$dF/dt = (\partial/\partial t + \vec{v} \cdot \vec{\nabla}) F(k) = S \quad (7)$$

Functional Form of Source Term S. - Among various possible processes that contribute to the source term, most of the discussion will be centered on the generative action of overwater winds and the dissipative effects of turbulent bottom friction. Guided by previous studies by Miles (17), Snyder and Cox (26),

Manton (15,16), Barnett (1), Barnett and Wilkerson (3), and Hasselmann and Collins (11), the functional form of S is taken as

$$S = F(k_m) (\Omega - \phi_f) \quad (8)$$

where

$$\Omega = \gamma (\rho_a/\rho_w) (\vec{k}_m \cdot \vec{W} - \sigma_m) \quad (9)$$

with  $(\rho_a/\rho_w)$  = ratio of air to water density;  $\vec{W}$  = wind velocity at 10 m above still water; and  $\gamma$  = a constant ( $<1$ ) representing the fraction of wind input energy that is transferred down the spectrum to build up the lower wave number end of the spectrum  $F(k)$ . Hence, it is assumed that an equilibrium exists such that wind input balances the energy losses due to breaking away from the spectral peak towards higher wave numbers. The function  $\phi_f$  represents the dissipative effect of turbulent bottom friction. For a Gaussian sea state in which the spectrum is narrow-beam centered around  $\vec{k}_m$ , the general form of this term (see, e.g., Refs. 11 and 23) can be replaced with the unidirectional approximation

$$\phi_f = 2 C_f (g k_m^2 / \sigma_m^2 \cosh^2 k_m d) \langle |\vec{u}| \rangle \quad (10)$$

where  $C_f$  = an empirical drag or friction coefficient; and,

$$\langle |\vec{u}| \rangle = \left\{ (2/\pi) \int (gk/\sigma \cosh kd)^2 F(k) dk \right\}^{1/2} \quad (11)$$

## GOVERNING EQUATIONS

Substituting Eq. 6 into the left hand side of Eq. 7, we obtain

$$dF/dt = \beta n k_m^{-3} \{-3k_m^{-1} dk_m/dt + n^{-1}(\partial n/\partial k_m) (dk_m/dt) + n^{-1}(\partial n/\partial d) (dd/dt)\} \quad (12)$$

where

$$\partial n/\partial k_m = d(1-2k_m d \operatorname{ctnh} 2k_m d) / \sinh 2k_m d \quad (13)$$

$$\partial n/\partial d = k_m(1-2k_m d \operatorname{ctnh} 2k_m d) / \sinh 2k_m d \quad (14)$$

Similarly, substitutions of Eqs. 4 and 6 into Eqs. 6, 10, and 11 yield

$$\Omega = \gamma(\rho_a/\rho_w) k_m W_0 \{w \cos(\theta-\theta_w) - (\sigma_m/k_m W_0)\} \quad (15)$$

$$\phi_f = (8C_f k_m/\sinh 2k_m d) \{\beta g d \pi^{-1} \int_{2k_m d}^{\infty} (\sinh v + v) (v \sinh v)^{-2} dv\}^{\frac{1}{2}} \quad (16)$$

where  $W_0$  = a reference 10 m - wind speed at a fixed  $\vec{x}$  and  $t$ ;  
 $w = W/W_0$ , a dimensionless function representing spatial and temporal variation of wind field; and,  $\theta, \theta_w$  = directions of  $\vec{k}_m$  and  $\vec{W}$ , respectively, relative to a fixed reference axis.



We can now introduce the dimensionless variables

$$\begin{aligned}\underline{k} &= k_m W_0^2 / g \\ \underline{\sigma} &= \sigma_m W_0 / g \\ \underline{t} &= gt / W_0 \\ \underline{\dot{x}} &= g \dot{x} / W_0^2 \\ \underline{d} &= gd / W_0^2\end{aligned}\tag{17}$$

so that

$$\underline{c} = C_m / W_0 = \sigma_m / k_m W_0 = (\tanh \underline{k} \underline{d} / \underline{k})^{\frac{1}{2}}\tag{18}$$

and

$$\underline{T} = g T_m / 2\pi W_0 = (\underline{k} \tanh \underline{k} \underline{d})^{-\frac{1}{2}}\tag{19}$$

represent, respectively, the dimensionless wave speed and period associated with the spectral peak. Likewise, the dimensionless significant wave height can be shown to be

$$\underline{H} = g H_s / W_0^2 = 4 \left( \int_{\underline{k}}^{\infty} F(v) dv \right)^{\frac{1}{2}}\tag{20}$$

Finally, by substituting Eqs. 12 through 17 into Eq. 7 and solving for  $d\underline{k}/dt$ , we obtain

$$d\underline{k}/dt = (\partial/\partial t + \underline{\nabla} \cdot \underline{\nabla}) \underline{k} = (S_1 - S_2 - S_3) S_4^{-1} \quad (21)$$

where  $\underline{\nabla} =$  dimensionless horizontal gradient operator;

$$\underline{\nabla} = n \underline{c} \underline{\hat{k}} \quad (22)$$

with  $\underline{\hat{k}} = \underline{\hat{k}}/k = (\cos \theta, \sin \theta)$ ; and,

$$S_1 = \gamma(\rho_a/\rho_w) n \underline{k}^2 \{w \cos(\theta - \theta_w) - (\tanh \underline{k} \underline{d}/\underline{k})^{\frac{1}{2}}\} \\ \sinh 2 \underline{k} \underline{d} \quad (23)$$

$$S_2 = 8 C_f n \underline{k}^2 \{\beta \underline{d} \pi^{-1} \int_{2\underline{k} \underline{d}}^{\infty} (\sinh v + v) \\ (v \sinh v)^{-2} dv\}^{\frac{1}{2}} \quad (24)$$

$$S_3 = \underline{k}^2 (1 - 2 \underline{k} \underline{d} \operatorname{ctnh} 2 \underline{k} \underline{d}) d(\underline{d})/dt \quad (25)$$

$$S_4 = \underline{k} \underline{d} (1 - 2 \underline{k} \underline{d} \operatorname{ctnh} 2 \underline{k} \underline{d}) - 3n \sinh 2 \underline{k} \underline{d} \quad (26)$$

Hence, the variation of the modulus  $\underline{k}$  is described by Eq. 21 along the wave ray given by

$$d\underline{\hat{x}}/dt = \underline{\nabla} = n \underline{c} \underline{\hat{k}} \quad (27)$$

What remains, therefore, is the derivation of an expression which will describe the variation of  $\underline{\hat{k}}$  or  $\theta$  along the same ray

due to refraction. This easily follows if we note from Eqs. 3,4 and 17 that

$$d\hat{\underline{k}}/d\underline{t} = d(\underline{k} \hat{\underline{k}})/d\underline{t} = - (\underline{\sigma} \underline{k} / \sinh 2 \underline{k} \underline{d}) \hat{\underline{v}} \underline{d} \quad (28)$$

Solving this for  $d\hat{\underline{k}}/d\underline{t}$  and taking the dot product of the resulting expression with  $\hat{\underline{m}} = (-\sin \theta, \cos \theta)$  immediately gives

$$d\theta/d\underline{t} = -(\underline{\sigma} / \sinh 2 \underline{k} \underline{d}) \hat{\underline{m}} \cdot \underline{\nabla} \underline{d} \quad (29)$$

In summary, the complete problem requires the solution of the system of Eqs. 21,27, and 29 for a specified wind field, i.e.,  $W_0$ ,  $w$ , and  $\theta_w$ , with appropriate initial and boundary conditions on  $\hat{\underline{k}}$ . Then, the estimation of wind-wave parameters  $\underline{C}$ ,  $\underline{T}$  and  $\underline{H}$  follows immediately from Eqs. 18,19, and 20, respectively.

#### COMPARISON WITH EXISTING THEORIES IN DEEP WATER

Under deep water conditions with constant wind direction  $\theta_w$ ,  $\theta = \theta_w$ , and no refraction, it can be verified that Eqs. 21 and 27 become, respectively

$$d\underline{C}/d\underline{t} = \gamma_0 \underline{C}^{-1} [w(\underline{x}, \underline{t}) - \underline{C}] \quad (30)$$

$$d\underline{x}/d\underline{t} = \frac{1}{2} \underline{C} \quad (31)$$

where  $\gamma_0 = (1/6) \gamma (\rho_a / \rho_w)$ ; and use has been made of  $\underline{k} = \underline{C}^{-2}$ . In this special case, the reduced Eqs. 30 and 31 are

identical with the deep water relations previously obtained by Manton (15).

The dimensionless significant wave height follows readily from Eq. 20 as

$$\underline{H} = 2 \beta^{\frac{1}{2}} \underline{C}^2 \quad (32)$$

Hence, by specifying functional form of  $w(x,t)$ , various special cases can be examined and compared with other available parametric forecasting theories and observational data. In particular,

$$w(\underline{x}, \underline{t}) = \theta(\underline{x}) \theta(\underline{t}) \quad (33)$$

where  $\theta(\cdot)$  = Heaviside unit step function, corresponds to a duration-and fetch-limited generation case with the invariant solution

$$\underline{C} + \ln(1-\underline{C}) = \underline{C}_0 + \ln(1-\underline{C}_0) - \gamma_0 (\underline{t} - \underline{t}_0) \quad (34)$$

$$\underline{x} = \underline{x}_0 + \frac{1}{2} \int_{\underline{t}_0}^{\underline{t}} \underline{C}(\underline{x}, \tau) d\tau \quad (35)$$

where

$$\underline{x} \geq \underline{x}_0 ; \underline{t} \geq \underline{t}_0 ; \text{ and, } \underline{C}_0 = \underline{C}(\underline{x}_0, \underline{t}_0) < 1 \quad (36)$$

Wind-wave generation under conditions of uniform wind with unlimited fetch, i.e.,  $w(\underline{t}) = \theta(\underline{t})$ , is represented by the solution

of Eq. 30 with  $d/d\underline{t} = \partial/\partial\underline{t}$

$$\underline{C} + \ln (1 - \underline{C}) = \underline{C}_0 + \ln (1 - \underline{C}_0) - \gamma_0 (\underline{t} - \underline{t}_0) \quad (37)$$

where

$$\underline{t} \geq \underline{t}_0 ; \quad \text{and, } \underline{C}_0 = \underline{C} (\underline{t}_0) < 1 \quad (38)$$

Finally, the solution under conditions of uniform wind with unlimited duration, i.e.,  $w(\underline{x}) = U(\underline{x})$ , also follows easily from Eq. 30 with  $d/d\underline{t} = (\underline{C}/2) d/d\underline{x}$  as

$$\begin{aligned} \underline{C} (1 + \frac{1}{2} \underline{C}) + \ln (1 - \underline{C}) &= \underline{C}_0 (1 + \frac{1}{2} \underline{C}_0) \\ &+ \ln (1 - \underline{C}_0) - 2\gamma_0 (\underline{x} - \underline{x}_0) \end{aligned} \quad (39)$$

where

$$\underline{x} \geq \underline{x}_0 ; \quad \text{and, } \underline{C}_0 = \underline{C} (\underline{x}_0) < 1 \quad (40)$$

Noting that all of these solutions are identical to Manton's (15), we can proceed now to compare them with various other forecasting theories and observational data readily available in the literature. First, the fetch-limited case with the null boundary condition  $\underline{C}_0 = 0$ , i.e.,

$$\underline{C} (1 + \frac{1}{2} \underline{C}) + \ln (1 - \underline{C}) = -2\gamma_0 \underline{x} \quad (\underline{x} \geq 0) \quad (41)$$

$$\underline{H} = 2 \beta^{\frac{1}{2}} \underline{C}^2 \quad (42)$$

where, following Manton (15),  $\beta \approx 1.31 \times 10^{-2}$  and  $\gamma_0 \approx 2.5 \times 10^{-5}$ , will be compared with the parametric relations of Hasselmann et al. (10):

$$\underline{C} = 5.5 \times 10^{-2} \underline{x}^{0.3} \quad (43)$$

$$\underline{H} = 1.54 \times 10^{-3} \underline{x}^{0.5} \quad (44)$$

the Sverdrup-Munk-Bretschneider (SMB) formulae in the Shore Protection Manual (SPM) (25):

$$\underline{C} = 1.2 \tanh (0.077 \underline{x}^{0.25}) \quad (45)$$

$$\underline{H} = 0.283 \tanh (0.0125 \underline{x}^{0.42}) \quad (46)$$

and the relations by Wilson (30):

$$\underline{C} = 5.7 \times 10^{-3} \underline{x}^{0.3} \quad (47)$$

$$\underline{H} = 2.5 \times 10^{-3} \underline{x}^{0.4} \quad (48)$$

The wind-wave parameters represented by Eqs. 41 through 48 are shown in Figure 1 together with the region of field data

obtained from Figure 15 of Wilson (30). Evidently, the general character of the results generated here compares favorably with the field data and other theories or empirical curves in question. So far as the principal purpose of any parametric approach is concerned, apparent differences observed between various forecasting relations can be considered to be within acceptable limits. There are, however, certain points of concern about each forecasting relation. Specifically, the equations of the present study provide estimates with inherent upper bounds such that  $\underline{C} \leq 1$ , and  $\underline{H} \leq 0.229$ . These bounds appear to be slightly underestimated as compared to some field data. On the other hand, parametric relations of Hasselmann et al. (10) and Wilson's (30) empirical curves are likely to overestimate the wind-wave parameters at large fetches; and, SMB curves overestimate the same parameters at small fetches.

The duration-limited case with the null initial condition  $\underline{C}_0 = 0$ , i.e.,

$$\underline{C} + \ln(1 - \underline{C}) = -\gamma_0 \underline{t} \quad (t \geq 0) \quad (49)$$

$$\underline{H} = 2 \beta^{\frac{1}{2}} \underline{C}^2 \quad (50)$$

can also be compared with the relations based on the parametric approach of Hasselmann et al. (10):

$$\underline{C} = 9.17 \times 10^{-3} \underline{t}^{0.43} \quad (51)$$

$$\underline{H} = 7.77 \times 10^{-5} \underline{t}^{5/7} \quad (52)$$

and the forecasting curves of Sverdrup and Munk (28), which are reproduced here in Figure 2 together with the region of data given in Figure 7 of Ref. 28. Also shown in Figure 2 are the wind-wave predictions based on Eqs. 49 through 52. Again, the overall comparison is favorable. Particular differences observed are of the same nature as those just mentioned in the fetch-limited case, i.e.,  $\underline{C} \leq 1$ ,  $\underline{H} \leq 0.229$  for the predictions of the present study, which are likely to be underestimates for long durations; the parametric relations of Hasselmann et al. (10) overpredict  $\underline{C}$  and  $\underline{H}$  for long durations; and, the Sverdrup and Munk theory is likely to overestimate the same parameters for short durations.

#### FORECASTING IN FINITE WATER DEPTH

Uniform Depth Case. - Letting  $S_3 = 0$ , corresponding to a uniform water depth  $\underline{d} = \text{const.}$ , and with  $\theta = \theta_w$ , being coincident with one of the reference axes, the governing equations take the form

$$d\underline{k}/d\underline{t} = (\partial/\partial\underline{t} + \underline{v} \partial/\partial\underline{x}) \underline{k} = (S_1 - S_2) S_4^{-1} \quad (53)$$

$$d\underline{x}/d\underline{t} = \underline{v} = n \underline{C} \quad (54)$$

where  $S_1$ ,  $S_2$ ,  $S_4$ , and  $\underline{C}$  are defined as before. The wind-wave parameters follow from Eqs. 19 and 20 as

$$\underline{T} = (\underline{k} \tanh \underline{k} \underline{d})^{-\frac{1}{2}} \quad (55)$$

$$\underline{H} = 4 \left( \beta \int_{\underline{k}}^{\infty} n v^{-3} dv \right)^{\frac{1}{2}} \quad (56)$$



We can now proceed to consider the numerical simulation of a set of three wind-wave generation situations corresponding, respectively, to fetch-, duration-, and fetch- and duration-limited wind fields with invariant direction. In all these simulations, we take  $C_f = 0.01$  as a characteristic value which allows us to compare the results generated, in particular, under fetch-limited conditions with those presented in SPM (25). For the remaining cases here and in the following section where we will examine the more general case of a variable bathymetry, there is no parametric results available for comparison.

The fetch-limited situation corresponds to setting  $d/d\underline{t} = \underline{V} d/d\underline{x}$  in Eq. 53. Hence, the equation to be solved becomes

$$d\underline{k}/d\underline{x} = (S_1 - S_2) / (n \underline{C} S_4) \quad (57)$$

where  $w(\underline{x}) = \underline{\psi}(\underline{x})$ ; and,  $\underline{T}$  and  $\underline{H}$  are given by Eqs. 55 and 56. In this case and in all subsequent simulations, null boundary and/or initial conditions will be employed so that  $\underline{C}_0 (= \underline{k}_0^{-\frac{1}{2}})$ ,  $\underline{T}_0$ , and  $\underline{H}_0$  are all zero at  $\underline{x}$  and/or  $\underline{t} = 0$ . Hence, the duration-limited case with  $w(\underline{t}) = \underline{\psi}(\underline{t})$  corresponds to the solution of

$$d\underline{k}/d\underline{t} = (S_1 - S_2) S_4^{-1} \quad (58)$$

and the duration-and fetch-limited case with  $w(\underline{x}, \underline{t}) = \underline{\psi}(\underline{x}) \underline{\psi}(\underline{t})$  is given by the solution of the full set of Eqs. 53 and 54. The latter can also be expressed in terms of the integral quadratures

$$\underline{k} = \underline{k}_0 + \int_{\underline{t}_0}^{\underline{t}} (S_1 - S_2) S_4^{-1} d\tau \quad (59)$$

$$\underline{x} = \underline{x}_0 + \int_{\underline{t}_0}^{\underline{t}} n(\underline{k}, \tau; \underline{d}) \underline{C}(\underline{k}, \tau; \underline{d}) d\tau \quad (60)$$

Many sophisticated numerical algorithms exist for the numerical simulation of these nonlinear ordinary differential equations. However, the results to be discussed in the following were generated with the simplest possible scheme by approximating the left-hand sides by forward finite differences, and the right-hand sides with the values of variables  $\underline{k}$ ,  $\underline{x}$ ,  $\underline{t}$ , evaluated at a preceding step. Illustrating this with Eq. (58) as an example, we have then

$$\underline{k}_{i+1} = \underline{k}_i + \left[ (S_1 - S_2) S_4^{-1} \right]_i \Delta \underline{t} \quad (61)$$

Since the null initial and/or boundary conditions imply that  $\underline{k}_0 \rightarrow \infty$  (or,  $\underline{C}_0 = 0$ ), each case is initiated with the corresponding closed-form solution in deep water, i.e., Eqs. 34 through 40 whichever is applicable, and the computation via closed-form solutions are continued until the parameter  $\underline{k} \underline{d}$  becomes small enough for the effects of transitional water depths to be accounted for. In all cases here, the transitional criterion used is  $\underline{k} \underline{d} = 10\pi$ , after which the solution is continued numerically. It is noted that for the duration- and fetch-limited case described by Eqs. 53 and 54 or, Eqs. 59 and 60, it is expected that the local field is initially duration-limited and hence grows until it becomes fetch-limited. The boundary between the fetch-limited region and the duration-limited region is given by Eqs. 59 and 60

with  $\underline{x}_0 = \underline{t}_0 = 0$  or, equivalently, from a comparison of the solutions corresponding to the fetch-limited and duration-limited cases. In other words, once the solutions under fetch-limited and duration-limited conditions are obtained, the fetch- and duration-limited case follows from the combination of the two separate cases by patching them together in a straightforward manner.

The computations for the fetch-limited case for various  $\underline{d}$  values are shown in Figure 3 together with the corresponding results obtained from Eqs. 3-25 and 3-26 of SPM (25). The general agreement between the two sets of predictions is favorable except for short fetches where, just as mentioned previously, the SPM curves tend to overestimate the parameters  $\underline{T}$  and  $\underline{H}$ . Illustrated in the subsequent Figures 4 and 5 are the computations for the duration-limited case for various  $\underline{d}$  values and the fetch- and duration-limited case for  $\underline{d} = 0.3$ , respectively. There is no readily available observational data or parametric theories with which these latter results could be compared.

Variable Depth Case. - In order to illustrate the application of the proposed scheme to a more general situation, consider an artificial example of wind-wave generation over a circular basin with variable depth

$$\underline{d} = 1 + 10^{-2} (\underline{x}^2 + \underline{y}^2)^{\frac{1}{2}} \quad (\underline{x}^2 + \underline{y}^2 \leq 95) \quad (62)$$

Under conditions of unlimited wind-duration with  $w(\underline{x}) = \theta(\underline{x})$  and invariant wind direction  $\theta_w = 0$  with respect to  $+\underline{x}$  - axis, the governing equations follow from Eqs. 21, 27, and 29 as

$$d\underline{k}/d\underline{t} = \underline{\nabla} \cdot \underline{\nabla} \underline{k} = (S_1 - S_2 - S_3) S_4^{-1} \quad (63)$$

$$d\theta/d\underline{t} = - (\underline{\sigma}/\sinh 2 \underline{k} \underline{d}) \underline{\hat{m}} \cdot \underline{\nabla} \underline{d} \quad (64)$$

$$d\underline{x}/d\underline{t} = \underline{\nabla} = n \underline{C} \underline{\hat{k}} \quad (65)$$

where  $S_1$ ,  $S_2$ ,  $S_4$  are defined by Eqs. 23, 24, 26, respectively;  $S_3$  is as in Eq. 25 with  $d(\underline{d})/d\underline{t} = \underline{\nabla} \cdot \underline{\nabla} \underline{d}$ ; and

$$\underline{\hat{k}} = (\cos \theta, \sin \theta) \quad (66)$$

$$\underline{\hat{m}} = (-\sin \theta, \cos \theta) \quad (67)$$

$$\underline{\sigma} = \underline{T}^{-1} = (\underline{k} \tanh \underline{k} \underline{d})^{\frac{1}{2}} \quad (68)$$

The parameters  $\underline{T}$  and  $\underline{H}$  are given by Eqs. 19 and 20 as before, and  $\theta$  is with respect to the  $+x$  - axis.

The solution in this case proceeds by integrating Eqs. 63 and 64 along the rays described by (65). Hence, using forward differences and setting  $\Delta s = n\underline{C} \Delta \underline{t}$  as a stepsize along a ray, the computation is performed in the following order:

$$\theta_{i+1} = \theta_i - (\underline{\sigma} \underline{\hat{m}} \cdot \underline{\nabla} \underline{d} / n \underline{C} \sinh 2 \underline{k} \underline{d})_i \Delta s \quad (69)$$

$$\underline{x}_{i+1} = \underline{x}_i + \frac{1}{2} (\cos \theta_i + \cos \theta_{i+1}) \Delta s \quad (70)$$

$$\underline{y}_{i+1} = \underline{y}_i + \frac{1}{2} (\sin \theta_i + \sin \theta_{i+1}) \Delta s \quad (71)$$

$$\underline{k}_{i+1} = \underline{k}_i + \frac{1}{2} \{ (S_1 - S_2 - S_3)_i (n \underline{C} S_4)_i^{-1} + (S_1 - S_2 - S_3)_{i+1} (n \underline{C} S_4)_{i+1}^{-1} \} \Delta s \quad (72)$$

The boundary conditions consist of the null values, i.e.,  $\theta = \underline{H} = \underline{T} = 0$  for any ray originating along the semicircular arc  $\underline{x}^2 + \underline{y}^2 = 95$  ( $\underline{x} \leq 0$ ) corresponding to the  $\underline{d} = 0.05$  depth contour. As in the previous uniform depth situations, the computation is initiated through the closed-form solution under fetch-limited conditions, i.e., Eqs. 41 and 42, until  $\underline{k} \underline{d} \approx 10\pi$ , after which the solution proceeds numerically via Eqs. 69-72. The results obtained in the manner just described with  $\Delta s = 0.2$  are presented in Figure 6 through 8. In particular, Figure 6 illustrates the geometry of the basin, depth contours, wind direction, and computed wave rays, which remain indifferent to refraction over most of the basin except towards the fetch-end shoreline. The contours of constant  $\underline{T}$  and  $\underline{H}$  are shown in Figures 7 and 8, respectively.

#### SUMMARY AND CONCLUDING REMARKS

Prediction of nearshore wave characteristics generated by variable winds was considered by using a parametric approach based on a contracted form of the radiative transport equation. It was assumed that the wind-disturbed sea surface can be described in terms of a depth-dependent equilibrium range spectrum with a well-defined low wave number cut-off. Among all possible processes at work in wind-wave generation, propagation, and dissipation, only the generative effect of winds and the dissipative

influence of turbulent bottom friction were taken into account, and governing equations were derived to describe the development of a wind-wave field in terms of the integral properties of its surface spectrum such as significant wave height and characteristic period. The governing equations were solved first for various simple cases under deep water conditions, obtaining results which compare very favorably with other parametric theories and observational data available. Consequently, the solutions were numerically extended first to the case of wind-waves in uniform water depth and then to the more general case of a circular basin with variable bathymetry. Except for the case of wind-waves generated under fetch-limited conditions in uniform water depths, where the solutions of the present study compare well with those referenced in SPM (25), there is no other corresponding theory or readily available field data to verify the validity of the remaining set of numerical results presented in Figures 4 through 8. Hence, these results are of a theoretical nature and remain to be substantiated with observational data or, by generating the corresponding integral properties through the application of a proven discrete spectral model to the same cases.

Finally, it is emphasized that the proposed parametric approach is an approximate one involving various inherent simplifying assumptions as to processes which operate in wind-wave generation. Therefore, the proposed approach is intended for operational uses and engineering design purposes to forecast or hindcast the wind-wave climatology in a nearshore zone for short-

or long-term applications or, to fill gaps in wave data base for extreme value statistics. Its application to complex situations such as hurricanes involving wind fields with rapidly varying directions and magnitudes should be considered only with extreme caution.




Figure 1. Comparison of Observational Data of Wind-Wave Parameters with Various Forecasting Theories for Conditions of Unlimited Duration in Deep Water.






Figure 2. Comparison of Observational Data of Wind-Wave Parameters with Various Forecasting Theories for Conditions of Unlimited Fetch in Deep Water.




Figure 3. Forecasting of Wind-Wave Parameters for Conditions of Unlimited Duration in Uniform Water Depths: a Comparison of SPM Theory with the Present Study.




Figure 4. Forecasting of Wind-Wave Parameters for Conditions of Unlimited Fetch in Uniform Water Depths in Uniform Water Depths Based on the Present Study.




Figure 5. Forecasting of Duration and Fetch-Limited Wind-Wave Parameters in Uniform Water Depth ( $\bar{d} = 0.3$ ) Based on the Present Study.




Figure 6. Forecasting of Wind-Wave Parameters for Conditions of Unlimited Duration in a Circular Basin with Variable Bathymetry: Diagram illustrating Depth Contours, Wind Direction, and Computed Wave Rays.




Figure 7. Contours of Scaled Wave Period  $I$ .




Figure 8. Contours of Scaled Significant Wave Height  $\bar{H}$ .

## REFERENCES

1. Barnett, T.P., "On the Generation, Dissipation, and Prediction of Ocean Wind Waves," Journal of Geophysical Research, Vol. 73, No. 1, January, 1968, pp 513-529.
2. Barnett, T.P., and Kenyon, K.E., "Recent Advances in the Study of Wind Waves," Reports on Progress in Physics, Vol. 38, 1975, pp 667-729.
3. Barnett, T.P. and Wilkerson, J.C., "On the Generation of Ocean Waves as Inferred from Airborne Radar Measurements of Fetch-Limited Spectra," Journal of Marine Research, Vol. 25, 1967, p 292.
4. Bretschneider, C.L., "Revisions in Wave Forecasting; Deep and Shallow Water," Proceedings, Sixth Conference on Coastal Engineering, ASCE, Council on Wave Research, 1958.
5. Dobson, F.W., "Observation of Normal Pressure on Wind-Generated Sea Waves," Ph.D. Thesis, University of British Columbia, 1969.
6. Ewing, J.A., Weare, T.J., and Worthington, B.A., "A Hindcast Study of Extreme Wave Conditions in the North Sea," Journal of Geophysical Research, Vol. 84, No. C9, September 1979, pp 5739-5747.
7. Ewing, J.A., "A Numerical Wave Prediction Model for the Atlantic Ocean," Deutsche Hydrographische Feitschrift, Vol. 24, 1971, pp 241-261.
8. Gunther, H., Rosenthal, W., and Richter, K., "Application of the Parametrical Surface Wave Prediction Model to Rapidly Varying Wind Fields," Journal of Geophysical Research, Vol. 84, No. C8, August 1979, pp 4855-4864.
9. Gunther, H., Rosenthal, W., Weare, T.J., Worthington, B. A., Hasselmann, K., and Ewing, J.A., "A Hybrid Parametrical Wave Prediction Model," Journal of Geophysical Research, Vol. 84, No. C9, September 1979, pp 5727-5738.
10. Hasselmann, K., Ross, D.B., Miller, P., and Sell, W., "A Parametric Wave Prediction Model," Journal of Physical Oceanography, Vol. 6, 1976, pp 200-228.
11. Hasselmann, K., and Collins, J.I., "Spectral Dissipation of Finite Depth Gravity Waves due to Turbulent Bottom Friction," Journal of Marine Research, Vol. 26, 1968, pp 1-12.



12. Ijima, T., and Tang, F.L.W., "Numerical Calculation of Wind Waves in Shallow Water," Proceedings, Tenth Conference on Coastal Engineering, ASCE, Tokyo, Vol. 2, 1966, pp 38-45.
13. Kitaigorodskii, S.A., Krasitskii, V.P., and Zaslavskii, M. M., "On Phillips' Theory of Equilibrium Range in the Spectra of Wind-Generated Gravity Waves," Journal of Physical Oceanography, Vol. 5, 1975, pp 410-420.
14. Lazanoff, S.M., Stevenson, N.M., and Cardone, V.J., "A Mediterranean Sea Wave Spectral Model," Technical Note No. 73-1, Fleet Numerical Weather Central, Monterey, Ca, 1973.
15. Manton, M.J., "On the Wave Field Generated by a Variable Wind," Geophysical Fluid Dynamics, Vol. 3, 1972, pp 91-104.
16. Manton, M.J., "Wave Generation on the Air-Sea Interface" Boundary Layer Meteorology, Vol. 2, 1972, pp 348-364.
17. Miles, J.W., "On the Generation of Surface Waves by Shear Flows," Journal of Fluid Mechanics, Vol. 3, 1957, p 185.
18. Mitsuyasu, H., and Rikiishi, K., "The Growth of Duration-Limited Wind Waves," Journal of Fluid Mechanics, Vol. 85, No. 4, 1978, pp 705-730.
19. Pierson, W.J., Jr., "Comments on a Parametric Wave Prediction Model," Journal of Physical Oceanography, Vol. 7, January, 1977, pp 127-134.
20. Pierson, W.J., Jr., Neumann, G., and James, R.W., "Observing and Forecasting Ocean Waves by Means of Wave Spectra and Statistics," Hydrographic Publication No. 603, U.S. Department of the Navy, 1955.
21. Phillips, O.M., The Dynamics of the Upper Ocean, Cambridge University Press, 1966.
22. Resio, D.T., and Vincent, C.L., "A Numerical Hindcast Model for Wave Spectra on Water Bodies with Irregular Shoreline Geometry," Miscellaneous Paper H-77-9, Hydraulics Lab., U.S. Army Engineer Waterways Experiment Station, Vicksburg, Miss, 39180, August 1977.
23. Resio, D.T. and Vincent, C.L., "Design Wave Information for the Great Lakes," Tech. Rep. H-76-1, Hydraulics Lab., U.S. Army Engineer Waterways Experiment Station, Vicksburg, Miss, 39180, June 1978.

24. Seymour, R.J., "Estimating Wave Generation on Restricted Fetches," Journal of the Waterway, Port, Coastal, and Ocean Division, ASCE, Vol. 103, No. WW2, Proc. Paper 12924, May, 1977, pp 251-264.
25. Shore Protection Manual, Coastal Engineering Research Center, U.S. Army Engineers, Washington, D.C., Vol. 1, 1977.
26. Snyder, R.L. and Cox, C.S., "A Field Study of the Wind Generation of Ocean Waves," Journal of Marine Research, Vol. 24, 1966, pp 141-178.
27. Stewart, R.W., "The Wave Drag of Wind over Water," Journal of Fluid Mechanics, Vol. 10, 1961, p 189.
28. Sverdrup, H.U., and Munk, W.H., "Wind, Sea, and Swell: Theory of Relations for Forecasting," Hydrographic Office Publication No. 601. U.S. Navy Department, March 1947.
29. Thornton, E.B., "Rederivation of the Saturation Range in the Frequency Spectrum of Wind-Generated Gravity Waves," Journal of Physical Oceanography, Vol. 7, No. 1, January, 1977, pp 137-140.
30. Wilson, B.W., "Numerical Prediction of Ocean Waves in the North Atlantic for December 1959," Technical Report NR 083-163, National Engineering Science Co., June 1963.

PUBLICATIONS PUBLISHED BY THE  
DEPARTMENT OF MARINE SCIENCE AND ENGINEERING  
(PREVIOUSLY THE CENTER FOR MARINE AND COASTAL STUDIES)

- Wave-Current Force Spectra, C. C. Tung and N. E. Huang, Report No. 72-2,  
December, 1972.
- A Survey of North Carolina Beach Erosion by Air Photo Methods, H. E.  
Wahls, Report No. 73-1, May, 1973.
- Sediment Movement in Tubbs Inlet, North Carolina, Robert P. Masterson,  
Jr., Jerry L. Machemehl and Victor V. Cavaroc, Jr., Report No. 73-2,  
June, 1973.
- Influence of Current On Some Statistical Properties of Waves, C. C.  
Tung and N. E. Huang, Report No. 73-3, December, 1973.
- CTD Sensors, Specific Conductance and the Determination of Salinity,  
C. E. Knowles, Report No. 73-3, August, 1973.
- Planning for North Carolina's Coastal Inlets - An Analysis of the Pre-  
sent Process and Recommendations for the Future, William S. Tilley,  
Report No. 73-4, September, 1973.
- A Preliminary Study of Storm-Induced Beach Erosion for North Carolina,  
C. E. Knowles and Jay Langfelder and Richard McDonald, Report No.  
73-5, October, 1973.
- A Historical Review of Some of North Carolina's Coastal Inlets, Jay  
Langfelder, Tom French, Richard McDonald and Richard Ledbetter,  
Report No. 74-1, January, 1974.
- Statistical Properties of Kinematics and Dynamics of a Random Gravity  
Wave Field, C. C. Tung, Report No. 74-2, June, 1974.
- A New Technique of Beach Erosion Control, Tom French, Jerry L.  
Machemehl and N. E. Huang, Report No. 74-3, June, 1974.
- Citizen Participation in North Carolina's Coastal Area Management  
Program, Steve Tilley, Report No. 74-4, June, 1974.
- An Experimental Study of Scour Around Marine Foundations Due to  
Oscillatory Waves and Unidirectional Currents, Greg N. Abad and  
Jerry L. Machemehl, Report No. 74-5, September, 1974.
- Proceedings of A Conference on Coastal Management, Report No. 74-6,  
September, 1974.
- Statistical Properties of Fluid Motion and Fluid Force in A Random  
Wave Field, Keikhosrow Pajouhi and C. C. Tung, Report No. 75-1,  
May, 1975.

A Numerical Method for Solutions of Systems of Non-Linear Algebraic Equations, John M. Klinck and Leonard J. Pietrafesa, Report No. 75-2, July, 1975.

Wave-Current Interactions in Water of Variable Depths, A. M. Radwan, C. C. Tung and N. E. Huang, Report No. 75-3, August, 1975.

Conference Proceedings Energy From The Oceans Fact or Fantasy?, Jerome Kohl, Report No. 76-1, UNC-SG-76-04, January, 1976.

Long Waves Trapped by the Cape Fear Continental Shelf Topography: A Model Study of Their Propagation Characteristics and Circulation Patterns, David A. Brooks, Report No. 76-2, July, 1976.

A Comparative Study of Three Methods of Inhibiting Scour Around A Vertical Circular Cylinder, David M. Rooney and Jerry L. Machemehl, Report No. 76-3, September, 1976.

A Flow Study of Drum Inlet, North Carolina, Paul R. Blankinship, Report No. 76-4, UNC-SG-76-13, November, 1976.

Dune Stabilization With Panicum amarum Along the North Carolina Coast, E. D. Seneca, W. W. Woodhouse, Jr., and S. W. Broome, Report. 77-1, UNC-SG-77-03, February, 1977.

A Mathematical Model of Nutrient Distribution In Coastal Waters, Eileen E. Hofmann, Leonard J. Pietrafesa, Larry P. Atkinson, Gustav-A. Paffenhöfer and William M. Dunstan, Report No. 77-2, February, 1977.

An Experimental Investigation of Some Combined Flow Sediment Transport Phenomena, Larry Bliven, Norden E. Huang and Gerald S. Janowitz, Report No. 77-3, UNC-SG-77-04, February, 1977.

Thermal Effluent Transport Pathways In Coastal Waters Near The Mouth Of The Cape Fear River Estuary, Leonard J. Pietrafesa, Paul Blankinship and Richard D'Amato, Report No. 77-4, CP&L No. 77-04, March, 1977.

Onslow Bay Physical/Dynamical Experiments Summer-Fall, 1975 Data Report, L. J. Pietrafesa, D. A. Brooks, R. D'Amato and L. P. Atkinson, Report No. 77-5, ERDA Contract No. E(38-1)-902, UNC-SG-77-07, March, 1977.

Sea Level Fluctuations Off The Carolina Coast And Their Relation To Atmospheric Forcing, David A. Brooks, Report No. 77-6, May, 1977.

An Experimental Study Of A Nearshore Erosion Control Structure, Herschel R. Cuzts and Jerry L. Machemehl, Report No. 77-7, May, 1977.

Application of a Radiation - Type Boundary Condition to the Wave - Porous Bed Problem, Charles McClain, Norden Huang and Leonard J. Pietrafesa, UNC-SG-77-10, Report No. 77-8, May, 1977.

An Analysis of Beach Overwash Along North Carolina's Coast, Stanley J. Boc and Jay Langfelder, Report No. 77-9, June, 1977.

Flow Dynamics and Sediment Movement In Lockwoods Folly Inlet, N. C., Jerry L. Machemehl, Mike Chambers and Neale Bird, UNC-SG-77-11, Report No. 77-10, June, 1977.

Numerical Flow Model for an Atlantic Coast Barrier Island Tidal Inlet, T. C. Gopalakrishnan and Jerry L. Machemehl, UNC-SG-78-02, Report No. 78-1, February, 1978.

Continental Margin Atmospheric Climatology and Sea Level, (Historical Setting, 1974, 1975) L. J. Pietrafesa, Rich D'Amato, C. Gabriel, R. J. Sawyer, Jr., UNC-SG-78-09, Report No. 78-2.

Oceanographic Observations Across the Northern Gulf Stream, Thomas B. Curtin, Leonard J. Pietrafesa, NASA Contract No. 62617, Report No. 78-3.

Concurrent Satellite and Ship Observations Across the Gulf Stream North of Cape Hatteras, Thomas B. Curtin, Leonard J. Pietrafesa and Norden E. Huang, NASA Contract No. 62617, Report No. 78-4.

Onslow Bay Physical/Dynamical Experiment-Summer 1976-Data Report, L. J. Pietrafesa, R. D'Amato, C. Gabriel, R. J. Sawyer, Jr., D. A. Brooks, P. Blankinship and R. W. Weisberg, UNC-SG-78-16, Report No. 78-5.

Deterioration of Asbestos Cement Sheet Material in the Marine Environment., Jerry Machemehl, Larry Watson and Bobby Barnes, Report No. 78-6 - UNC-SG, December, 1978.

Sediment Dynamics and Shoreline Response at Drum Inlet, North Carolina. James Forman and Jerry Machemehl, Report No. 78-7. - December, 1978.

Ocean Outfall Wastewater Disposal Feasibility and Planning, prepared by investigators from NCSU and ECU and UNC, Dept of Marine Science and Engineering, Institute for Coastal and Marine Resources East Carolina University, Report No. 79-1, Report No. 5, April 30, 1979

Oceanographic Field Observations off North Carolina Summer  
Survey 2-12 August 1977, Report No. 79-2, By Tom Curtin.

Oceanographic Field Observations off North Carolina Winter  
Survey 2-12 February 1978, Report No. 79-3, By Tom Curtin.

Oceanographic Field Observations off North Carolina Spring  
Survey 12-22 May 1978, Report No. 79-4, By Tom Curtin.

Oceanographic Field Observations off North Carolina Fall  
Survey 1-11 November 1977, Report No. 79-5, By Tom Curtin.

Onslow Bay Dynamical Tidal Experiments - Winter 1976 Data  
Report. Report No. 79-6. By Rich D'Amato, Charles Gabriel,  
Paul Blankinship, Robert Sawyer, Jr. and L. Pietrafesa.

Nearshore Wave Characteristics Generated By Variable Winds,  
Report No. 79-7, By N. Aziz Tayfun.