



UNIVERSITY OF MARYLAND

COMPUTER SCIENCE CENTER

COLLEGE PARK, MARYLAND 20742

80 10 3 112

DISTRIBUTION STATEMENT A

COPY

FILE

33

Approved for public release; Distribution Unlimited

97: marshart TR-885 Mare DAAG-53-76C-0138 (TWO NOTES ON DIGITAL EDGES AND LINES, Alan Broder Azriel/Rosenfeld Computer Vision Laboratory Computer Science Center University of Maryland College Park, MD 20742 (b) DANGES ME DALTER, DARFA ORI 1- FARG

This report consists of two independent parts. The first is entitled "Non-maximum suppression of gradient magnitudes makes them easier to threshold"; it shows that, besides reducing thick responses to thin, the application of non-maximum suppression to digital gradient magnitudes also improves the form of the edge response histogram, making the choice of thresholds easier. In the second, entitled "A note on collinearity merit", measures of collinearity merit based on distance and angle are defined. They yield reasonable results for edges extracted from an aerial photograph.

The support of the Defense Advanced Research Projects Agency and the U.S. Army Night Vision Laboratory under Contract DAAG-53-76C-0138 (DARPA Order 3206) is gratefully acknowledged, as is the help of Kathryn Riley in preparing this paper.

S. A. S. A.



DETRINE)

111074

NON-MAXIMUM SUPPRESSION OF GRADIENT MAGNITUDES MAKES THEM EASIER TO THRESHOLD

Les Kitchen Azriel Rosenfeld Computer Vision Laboratory Computer Science Center University of Maryland

ABSTRACT

Besides reducing thick responses to thin, the application of non-maximum suppression to digital gradient magnitudes also improves the form of the edge response histogram, making the choice of thresholds easier.

Accession For NTIS GRA&I DTIC TAB Unannounced Justification By_ Distribution/ Availability Codes Avril and/or Dist Spacial

One problem with derivative-based edge detectors is that their response is blurred, or spread out rather than sharp. (For the response of a Sobel detector taking horizontal differences, see Figures 1b, 2b, 3b.) This occurs both because the edges themselves may be unsharp, and because the edge detector itself may involve some averaging of gray levels. Nonmaximum suppression is a commonly-used technique for overcoming this difficulty, reducing thick edge detector responses to thin lines (Rosenfeld and Kak, 1976). See Figures 1c, 2c, 3c.

Another problem with such edge detectors is that the histogram of edge response values is virtually featureless, making it very difficult to choose a good threshold for separating valid edges from noise. (See Figures 1e, 2e, 3e.) It seems not to have been previously remarked that non-maximum suppression can be helpful here as well. Histograms of edge responses <u>after</u> non-maximum suppression have a much better form, often showing pronounced bimodality, or at least an inflection, when the original histogram had no such properties. (See Figures 1e, 2e.) This makes the selection of thresholds a much simpler and more reliable process. Figures 1d and 2d show the results of thresholding edge detector responses after non-maximum suppression, using threshold levels chosen by examining their histograms. As seen, the results appear quite good. This effect occurs because the non-maximum suppression removes a whole sub-population of near-edge points, thus making it easier to separate valid edge responses from noise. Of course, such technique will not work as well with pictures which have many different types of edges, for example, Figure 3. However, it is still possible to pick the strongest edges, those which separate house roofs from shadows.

Reference

A. Rosenfeld and A.C. Kak, Digital Picture Processing, Academic Press, New York, 1976, p. 275.



Figures la - ld. (Photomicrograph of chromosomes) Clockwise from top left: (a) Original gray level. (b) Absolute value of Sobel detector (horizontal differences). (c) Same as b, but with non-maxima along horizontal direction suppressed. (d) Same as c, but thresholded at level 6.



Figure le. Comparison of histograms of 1b (upper) and 1c (lower), for levels greater than 1.



5.

Figures 2a - 2d. (Aerial photograph of an airfield). Captions analogous to Figure 1, but 2c is thresholded at level 12.



Figure 2e. Comparison of histograms of 2b (upper) and 1c (lower), for levels greater than 1.



.

Figures 3a - 3d. (Aerial photograph of suburban houses). Captions analogous to Figure 1, but 2c is thresholded at level 12.



Figure 3e. Comparison of histograms of 3b (upper) and 3c (lower), for levels greater than 1.

A NOTE ON COLLINEARITY MERIT

Alan Broder Azriel Rosenfeld Computer Vision Laboratory Computer Science Center University of Maryland

ABSTRACT

Measures of collinearity merit based on distance and angle are defined. They yield resonable results for edges extracted from an aerial photograph.

1. Introduction

Straight edge and line features are often important in the description of an image. Local operators of various types can be employed to detect edge and line segments [1], but it is still necessary to determine sets of these local features that are globally straight, i.e., collinear. Hough transforms [2], in principle, map sets of collinear segments into single points in Hough space; but in practice, due to inherent errors in estimating the slopes and distances from the origin of the segments, the Hough transform of a collinear set will generally be a cluster of points, and it is necessary to examine the original segments in order to establish their collinearity.

This note presents a simple approach to finding sets of collinear segments based on computing a figure of merit for the collinearity of each pair of segments. The pairs whose collinearity merit exceeds a given threshold define an equiavalence relation on the segments. For suitable choices of the threshold, the resulting equivalence classes are in good correspondence with subjective judgments of collinearity.

The figure of merit described here is similar to that used by VanderBrug [3] for linking curve segments based on the smoothness with which their ends can be connected; but it is applied here to straight line segments, rather than to arc ends. On other line segment grouping tasks (linking antiparallel pairs; clustering collinear segments on the basis of proximity) see Scher [4,5].

1

2. Collinearity merit

Our measure of collinearity merit depends on two factors: distance and angular difference.

It seems evident that the distance factor, m_d , should depend on the lengths of the segments. For example, the segments in Figure la have a higher merit than those in Figure 1b, even though the distance in each case is exactly the same. To provide for this dependence, we define

$$m_{d} = \frac{L_{1} + L_{2}}{L_{1} + D + L_{2}}$$

where $L_{1,2}$ are the segment lengths and D is the distance between their nearest endpoints. In this formula, when D=0 we have $m_d=1$, and as D increases, m_d decreases.

The angular difference factor can be measured in two ways. One approach is to use the product of cosines

 $m_a = \cos\theta_1 \cdot \cos\theta_2$

take the collinearity merit to be zero.

where θ_1 and θ_2 are the angles that the segments make with the line joining their nearest end points (see Figure 2). This product is 1 when the segments are exactly collinear, and decreases as one or both of them deviate from collinearity.*

The m_a factor, however, has some undesirable properties; for example, it has the same value for the cases in Figures 3a and 3b, whereas intuitively, Figure 3b should have a higher rating. A factor that has higher values for 3b than for 3a is *This assumes that θ_1 and θ_2 are less than 90°; if they are greater, it may no longer be obvious which are the closer ends, and we

2

$$m'_a = \frac{D'}{L_1 + D + L_2}$$

where D' is the distance between the farthest endpoints of the segments. However, this factor alone would not yield the desired results, since it gives a high score to a pair of segments that are parallel but offset (Figure 4). For this reason, we used the product of m_a and m'_a as the measure of angular difference merit. Our final figure of collinearity merit is

3. Examples and concluding remarks

The figure of merit just defined was measured for pairs of line segments extracted from two portions of an aerial photograph (Figure 5). To simplify the computation, m was computed only for those pairs of segments that map into nearby points in Hough space (distances from origin within 20% of picture size; slopes within 45°).

Figure 6 shows the line segments in the two images, with pairs of segments for which $m \ge t$ joined by lines, for t = 1.0, .8,.6,.4,.2, and 0. We see that for high values our composite figure of merit seems to provide a reasonable basis for linking pairs of segments that are approximately collinear.

References

- 1. A: Rosenfeld and A. C. Kak, <u>Digital Picture Processing</u>, Academic Press, New York, 1976, Sections 8.2-3.
- 2. A. Iannino and S. D. Shapiro, A survey of the Hough transform and its extension to curve detection, Proc. PRIP-78, 32-38.
- 3. G. J. VanderBrug and A. Rosenfeld, Linear feature mapping, IEEETSMC-8, 1978, 548-555.
- 4. A. Scher, M. Shneier, and A. Rosenfeld, A method for finding pairs of anti-parallel straight lines, TR-845, Computer Science Center, University of Maryland, College Park, MD, Dec. 1979.

5. _____, in progress.





Figure 5a



Figure 5b





















Figure 6b

REPORT DOCUME	INTATION PAGE	READ INSTRUCTIONS
REPORT HUMBER	2. GOVT ACCESSION NO.	1. AECIPIENT'S CATALOG NUMBER
	AD-A0902	44
TITLE (and Subsisio)		S. TYPE OF REPORT & PERIOD COVERED
TWO NOTES ON DIGIT	TAL EDGES AND LINES	Technical
•		4. PERFORMING ORG. REPORT NUMBER TR-885
Les Kitchen		S. CONTRACT OR GRANT NUMBER()
Alan Broder Azriel Rosenfeld		DAAG-53-76C-0138
Computer Vision La Science Center, Un College Park, MD	AND ACCORESS LOGRATORY, Computer Liversity of Maryland, 20742	16. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
CONTROLLING OFFICE NAME AND A	OCRES	12. ASPORT DATE March 1980
U.S. Army Night V: Ft. Belvoir, VA	22060 Laboratory	13. NUMBER OF PAGES
MONITONING AGENCY NAME & ADDI	ALEB(I different from Controlling Office)	18. SECURITY CLASS. (of this report)
	·	Unclassified
		15- OFFI ASSIELCATION/COMMERADING
OISTROUTION STATEMENT (of the a	Report) .C release; distribution destroot concord in Block 30, 11 different fre	on unlimited.
GISTREUTION STATEMENT (of the A Approved for publi DISTREUTION STATEMENT (of the a	Report) .C release; distribution Actual anticed in Stock 36, 11 different for	on unlimited.
CISTRIBUTION STATEMENT (of the A Approved for publi DISTRIBUTION STATEMENT (of the a SUPPLEMENTARY NOTES	Report) .C release; distribution betreast catered in Block 30, 11 different fro	on unlimited.
Approved for publi Approved for publi ORSTROUTION STATEMENT (of the o SUPPLEMENTARY NOTES XEY WORDS (Continue on reverse of the Image processing Pattern recogniti Edge Detection Nonmaximum suppre Line detection	Report) .C release; distribution bourses entered in Slock 38, 11 different for 11 necessary and (dentity by block engine Collinearity .on ession	on unlimited.
Approved for publi Approved for publi OUSTIMENTION STATEMENT (of the o SUPPLEMENTARY NOTES XEY VOROS (Continue on reverse side Image processing Pattern recogniti Edge Detection Nonmaximum suppre Line detection ASSTRACT (Continue on reverse side his report consists o Non-maximum suppressi hreshold"; it shows th he application of non ides also improves th he choice of threshol publication.	Report) .C release; distribution between entered in Slock 36, 11 different for Collinearity .Con ession If necessary and identify by block master, .Collinearity .on ession If necessary and identify by block master, .on of gradient magnit that, besides reducing 	ts. The first is entitle udes makes them easier t thick responses to thin to digital gradient magn sponse histogram, making cond, entitled "A note o ty merit based on distan le results for edges
Approved for publi Approved for publi DISTRIBUTION STATEMENT (of the o SUPPLEMENTARY HOTES XEY MORES (Continue on reverse of the Image processing Pattern recogniti Edge Detection Nonmaximum suppres Line detection ASSTRACT (Continue on reverse of the his report consists of Non-maximum suppressing hreshold"; it shows the application of non ides also improves the he choice of threshol Dilinearity merit", mod angle are defined.	Report) .C release; distribution detross entered in Block 30, 11 different for Collinearity .Collinearity .On ession 11 necessary and identify by block marker Collinearity .On ession 11 necessary and identify by block marker .on of gradient magnit that, besides reducing 	The first is entitle udes makes them easier to thick responses to thin to digital gradient magn sponse histogram, making cond, entitled "A note of ty merit based on distan le results for edges ASSIFIED