

AD-A093 277

GENERAL MOTORS CORP INDIANAPOLIS IN DETROIT DIESEL A--ETC F/6 21/5
MARITIME PATROL AIRCRAFT (MPA) CONCEPT FORMULATION. ALLISON PD3--ETC(U)
FEB 79 P STOLP N62269-78-C-0415
DDA-EDR-9775A

UNCLASSIFIED

NADC-80181-C-60

NL

101

101



END

DATE

FILED

1-81

DTIC

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

19) REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 18 NADC-80181-C-60	2. GOVT ACCESSION NO. AD-A093	3. RECIPIENT'S CATALOG NUMBER 277
4. TITLE (and Subtitle) Maritime Patrol Aircraft (MPA) Concept Formulation, Allison PD570-40. T102 Derivative Turboprop Engine.	5. TYPE OF REPORT & PERIOD COVERED 9 Final Report, Oct 1978 - Feb 1979,	6. PERFORMING ORG. REPORT NUMBER DDA -EDR-9775A
7. AUTHOR(s) 10 P./Stolp	8. CONTRACT OR GRANT NUMBER(s) 14 15 N62269-78-C-0415	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Detroit Diesel Allison Division of General Motors Corporation, Box 894 Indianapolis, IN 46206	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 65152N A03P-03PA/001E/7W0880-001 Work Unit XM201	
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Air Development Center Warminster, PA 18974 13 37	12. REPORT DATE 11 February 1979	13. NUMBER OF PAGES 35
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) 16 WD 882 17 WD 880002	15. SECURITY CLASS. (of this report) UNCLASSIFIED	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Aircraft Propulsion Turbofan Engine Derivative Engine Turboshift Engine Maritime Patrol Aircraft Turboprop Engine		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This study developed data on Detroit Diesel Allison (DDA) common core derivative engines for use in Maritime Patrol Aircraft (MPA) concept formulation studies. The study included the screening of potential DDA turboprop/turboshaft engines and the preparation of technical and planning information on three of the most promising engine candidates plus an all new engine. Screening of DDA derivative candidates was performed utilizing an analytical MPA model using synthesized mission profiles to rank the candidates in terms		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 68 IS OBSOLETE
S/N 0102-LF-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

of fuel consumption, weight, cost and complexity. The three turboprop engines selected for further study were as follows: a derivative of the unity size T701-AD-700 shaft power engine with rematched turbine (PD 370-37), an advanced T701 turboprop derivative with 25:1 overall pressure ratio and a scaled ATEGG demonstrated compressor (PD 370-40), an advanced T701 turboprop derivative with 17.7:1 overall pressure ratio and a scaled ATEGG demonstrated compressor (PD 370-41). Data is also presented on a new advanced turboprop engine with 30:1 overall pressure ratio which incorporates compressor, combustor, turbine, and cooling technology now under development and demonstration at DDA. The documentation consists of six separate reports prepared in the following manner. One report summarizes the engine screening analysis and describes the approach to, and the conclusions of the study. A separate report for each of the three derivative engines and for the new turboprop present estimates of performance, weight, and dimensional data. The engineering budgetary estimates of the development, acquisition, and service costs for each of the four engines are presented in a separate report.

Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Avail and/or	
Special	
A	

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)



Detroit Diesel Allison
Division of General Motors Corporation
Indianapolis, Indiana 46206

TABLE OF CONTENTS

	<u>Page</u>
I. INTRODUCTION-----	1
II. ENGINE DESCRIPTION-----	2
III. WEIGHTS-----	6
IV. STEADY STATE PERFORMANCE -----	7



Detroit Diesel Allison

Division of General Motors Corporation

Indianapolis, Indiana 46206

REVISIONS

<u>Letter</u>	<u>Page</u>	<u>Revision</u>
A	4	Gearbox and total weight
A	6	Gearbox, interconnecting struts and shaft, and total weight
A	9	Scaling factors
A	10	Additional matrix points at 0 and 25,000 feet
A	13	Additional performance
A	18	Additional performance
A	23	Additional performance
A	28	Additional performance



Detroit Diesel Allison
Division of General Motors Corporation
Indianapolis, Indiana 46206

I. INTRODUCTION

This report presents estimates of performance, weight, and dimensional data for the PD 370-40 turboprop engine. The PD 370-40 represents an advanced T701 turboprop derivative engine with 25:1 overall pressure ratio. It incorporates a scaled ATEGG demonstrated compressor with basic shaft, bearing and turbine arrangements from the new T701 turboshaft engine. The engine is in the 12,000 to 13,000 SHP class, but scaling data is included to provide for studies down to 6000 SHP. The data is submitted for use in preliminary design type studies in the evaluation of turboprop systems.

The basic T701 engine is a free turbine turboshaft engine that was developed through safety demonstration testing, for the U.S. Army's HLH program. The model 570, a commercial industrial version of the T701, has undergone additional development testing, and is now in production.

The reduction gearbox for speed reduction to the prop-fan is a new simplified design, compared to the DDA T56 series of gearboxes. The new design is based upon a study into the reliability and maintenance cost history of past turboprop systems, and follows the recommendations of that study for a gearbox with high reliability, easy maintainability, and low maintenance costs.



Detroit Diesel Allison

Division of General Motors Corporation

Indianapolis, Indiana 46206

II. ENGINE DESCRIPTION

The Model PD 370-40 is an axial flow engine, having a single spool core and a free power turbine connected by shafting, and supporting structure to an offset reduction gear assembly. The general arrangement and external features of the engine are shown in Figure II-1, with principle physical characteristics listed in Table II-I. Output speed of the engine is constant at 9545 RPM. The reduction gearbox shown in Figure II-1 has an overall gear ratio of 7.52:1, providing a propfan speed of 1270 rpm at 9545 engine rpm. Parametric weight data is shown in Section III so that other propfan rotational speeds, and gear ratios can be analyzed. An aircraft accessory drive pad is provided on the back of the gearbox to drive an aircraft mounted accessory drive box. Power available at this pad is 500 HP at 8000 rpm. The primary engine mounts are on the gearbox with a hang mount at the rear of the engine. Engine accessories are driven by a bevel drive from the high pressure spool. The control system is integral with the prop-fan and is digital electronic. The oil system is integral to the engine and also supplies the prop-fan and reduction gearbox, but is separately filtered and monitored to isolate fault detection in each of these major modules. Engine torque is measured hydraulically from the gear thrust of the power train idler gears in the reduction gearbox.

The gearbox is shown offset, based upon DDA's experience with large turboprop engines. It is offset-up to be consistent with current studies showing a preference to under-the-wing engine mounting. It can also be supplied in the offset-down position.

Performance ratings, sea level static, are listed in Table II-II.

For preliminary design studies, the PD 370-40 engine configuration can be scaled to other power ratings. Scaling information is included for dimensions, weight, and performance.



Detroit Diesel Allison
Division of General Motors Corporation
Indianapolis, Indiana 46206




Figure II-1. PD370-40 General Arrangement.



Detroit Diesel Allison

Division of General Motors Corporation

Indianapolis, Indiana 46206

TABLE II-I

PD 370-40 PHYSICAL CHARACTERISTICS

(Includes Gearbox)

Length (in)	132.46
Max. Engine Diameter (in)	34.20
Max. Gearbox Offset, upward (in)	27.32
Dry Weight, lbs	
Engine	1566
Gearbox, including interconnecting struts and shaft	848
Total	2414

For scaling dimensions the following formulae may be used for SHP's down to 6000, and for other reduction gear ratios than 7.52:1.

Engine

$$\text{Axial dimensions} = \text{Base dim.} \times \left(\frac{\text{SHP}}{13,386} \right)^{0.4}$$

$$\text{Diameters} = \text{Base dia.} \times \left(\frac{\text{SHP}}{13,386} \right)^{0.5}$$

Reduction Gearbox

$$\text{Dimensions} = \text{Base dim.} \times \left(\frac{\text{SHP}}{13,386} \right)^{0.5} \times \left(\frac{\text{GR}}{7.52} \right)^{0.33}$$

Shaft length remains unchanged.



Detroit Diesel Allison
Division of General Motors Corporation
Indianapolis, Indiana 46206

TABLE II-II

PD370-40 PERFORMANCE SUMMARY

Sea Level, 0 kts

	<u>Standard Day</u>			<u>Hot Day, 89.8°F</u>		
	SHP	SFC	F _N	SHP	SFC	F _N
Take-Off	13,386	0.373	1,540	13,351	0.379	1,491
Max. Continuous	9,770	0.393	1,105	7,934	0.418	871



Detroit Diesel Allison
Division of General Motors Corporation
Indianapolis, Indiana 46206

III. WEIGHTS

The weight of the basic 13,386 SHP engine, gearbox, and the interconnecting struts and shaft are given in Table III-I. The gearbox weight is based upon a gear ratio of 7.52:1 which provides a propfan speed of 1270 rpm.

TABLE III-I

PD 370-40 WEIGHTS

	<u>Dry</u>	<u>Wet</u> *	<u>Installed</u>
Basic Engine, lbs	1566	1589	1589
Gearbox, lbs	800	849	849
Interconnecting Struts and Shaft, lbs	48	48	48
	—	—	—
Total, lbs	2414	2486	2486

* Includes total amount of oil required for engine and gearbox operation.

For scaling weights to engine sizes down to 6000 SHP, and for other reduction gear ratios, the following formulae may be used:

$$\text{Engine weight} = 1566 \times \left(\frac{\text{HP}}{13,386} \right)^{1.01}$$

$$\text{Gearbox weight} = 800 \times \left(\frac{\text{HP}}{13,386} \right)^{1.5} \times \left(\frac{\text{GR}}{7.52} \right)^{0.4}$$

Interconnecting strut and shaft weight = 6.0% of dry gearbox weight



Detroit Diesel Allison
Division of General Motors Corporation

Indianapolis, Indiana 46206

IV. STEADY STATE PERFORMANCE

Steady state performance data is tabulated in this section for all points shown in Figure IV-1. Basic engine data is shown for the following assumptions:

- o Uninstalled engine
- o ICAO standard atmosphere except for takeoff which in addition includes an ambient temperature of 89.8°F at standard atmosphere
- o 100% inlet recovery
- o Zero accessory horsepower extraction
- o Zero customer bleed extraction
- o Zero losses due to reduction gear
- o Fuel heating value - 18,400 Btu/lb
- o Estimated average engine performance - No SHP or fuel flow guarantee factors

Sensitivity data is provided for each point so that bleed and duct losses may be estimated as required.

Nomenclature

Nomenclature used in the tabulation of performance is as follows:

MACH	Mach number
SHP	Shaft horsepower
SFC	Specific fuel consumption, lbs/hr/hp
WF	Engine fuel flow, lbs/hr
FN	Net jet thrust, lbs (jet gross thrust - ram drag)
ESHP	Equivalent shaft horsepower (energy in jet stream converted ideally to horsepower and added to SHP)
WCIN	Total inlet corrected airflow, $W\sqrt{\theta_1}/\delta_1$

where: θ_1 = Engine inlet total temp, °R
 $\frac{518.688}{}$



Detroit Diesel Allison
Division of General Motors Corporation

Indianapolis, Indiana 46206

$$\delta_1 = \frac{\text{Engine inlet total pressure, psi}}{14.696}$$

TNOZ Jet nozzle total temperature, °R
PNOZ Jet nozzle total pressure, psi
RC Compressor pressure ratio
BOT Burner outlet temperature, °R
NO Point number

Sensitivity Data

Bleed:

$$\text{SHP, with bleed} = \text{SHP, no bleed} - (\text{DEL SHP})(\% \text{ bleed})$$

$$\text{WF, with bleed} = \text{WF, no bleed} - (\text{DEL WF})(\% \text{ bleed})$$

$$\text{FN, with bleed} = \text{FN, no bleed} - (\text{DEL FN})(\% \text{ bleed})$$

Inlet Recovery:

$$\eta_R = \text{Total pressure actual/Total pressure ideal}$$

$$\text{SHP, with recovery} = \text{SHP, ideal recovery} - (\text{DEL SHP})(1 - \eta_R)(100)$$

$$\text{WF, with recovery} = \text{WF, ideal recovery} (\eta_R)$$

$$\text{FN, with recovery} = \text{FN, ideal recovery} - (\text{DEL FN})(1 - \eta_R)(100)$$

Jet Nozzle Duct Loss:

To estimate thrust loss due to additional duct loss prior to the jet nozzle, use the following equation:

$$\text{FN, with loss} = \text{FN, without loss} - \text{FN, without loss} (K) \left(\frac{\Delta P}{P} \right)$$

where,

o K is obtained for each point from sensitivity data

$$o \frac{\Delta P}{P} = \frac{\text{PTOT, no loss} - \text{PTOT, total loss}}{\text{PTOT, no loss}}$$



Detroit Diesel Allison
Division of General Motors Corporation

Indianapolis, Indiana 46206

Reduction Gear Loss:

Reduction gear is 99 percent efficient.

Accessory Drive Losses:

Accessory drive power extraction is directly from the accessory drive pad on the reduction gearbox. Reduce SHP to prop-fan by amount of accessory power extraction at each point.

Scale Effect on SHP and SFC:

The engine performance is scaleable for purposes of studying other engine sizes. However, component performance will vary, dependent upon the amount of scale. A correction to scale factor for SHP and SFC was formulated for component performance changes and the effects on SHP, SFC, and FN are as follows:

$$\text{Scaled SHP} = \text{Unscaled SHP} \times \left(1 - \frac{A}{100}\right) \times \text{Scale Factor}$$

$$\text{Scaled FN} = \text{Unscaled FN} \times \text{Scale Factor}$$

$$\text{Scaled SFC} = \text{Unscaled SFC} \times \left(1 + \frac{B}{100}\right)$$

where:

$$\text{Scale Factor} = \frac{\text{Desired Rating}}{\text{Unity Rating}} \left(\text{limited from 1.2 to 0.6} \right)$$

$$A = \text{Sizing effect on SHP}$$

$$= 27.29 \times \text{Scale factor} - 11.90 \times (\text{Scale factor})^2 - 15.39$$

$$B = \text{Sizing effect on SFC}$$

$$= 7.15 \times (\text{Scale factor})^2 - 17.70 \times \text{Scale factor} + 10.54$$

Nozzle Throat Area

The effective nozzle throat area is constant for all conditions at 491.4 in².



Detroit Diesel Allison

Division of General Motors Corporation

Indianapolis, Indiana 46206

Standard and Hot Day; Takeoff and Maximum Continuous

Altitude (Ft $\times 10^{-3}$)	MACH Number			
	0	.1	.2	.3
0	X	X	X	X

Standard Day; Maximum Climb, Maximum Continuous and Part Power to Idle

Altitude (Ft $\times 10^{-3}$)	MACH Number							
	.2	.3	.4	.5	.6	.7	.75	.8
0	X	X	X	X	X	X	X	X
5	X	X	X	X	X			
10	X	X	X	X	X	X	X	X
15		X	X	X	X	X	X	X
20			X	X	X	X	X	X
25			X	X	X	X	X	X
30				X	X	X	X	X
35				X	X	X	X	X
40				X	X	X	X	X
45				X	X	X	X	X

Figure IV-1. Matrix of flight conditions for performance data

DETROIT DIESEL ALLISON DIVISION

EDR 9775

GENERAL MOTORS CORPORATION

PO170-40 TURBOPROP

ZERO BLEED

LCC PERCENT RECOVERY

STD DAY

ZERO POWER EXTRACTION

POWER	NACH	SHP	SFC	WF	FN	ESHP	WCIN	TNOZ	PNOZ	AC	NO
TO	0.0	1337.0	0.0	99.0	1539.6	1440.2	9.0	11.5	15.388	25.0	0001
M.C.	0.0	1347.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0002
M.C.	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0003
M.C.	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0004
M.C.	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0005
M.C.	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0006
M.C.	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0007
M.C.	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0008

T AMBIENT - 89.8°F

POWER	NACH	SHP	SFC	WF	FN	ESHP	WCIN	TNOZ	PNOZ	AC	NO
TO	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0009
M.C.	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0010
M.C.	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0011
M.C.	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0012
M.C.	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0013
M.C.	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0014
M.C.	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0015
M.C.	0.0	1351.0	0.0	99.7	1540.0	1440.0	9.7	11.5	15.388	25.0	0016

DETROIT DIESEL ALLISON DIVISION

EDR 9775

PD370-40 TURBOPROP

SENSITIVITY DATA FOR BLEED, INLET RECOVERY, AND EXHAUST DUCT LOSS

0 FEET ALTITUDE

POWER	MACH	DEL-SUP	INLET	DEL-FR	DEL-SHP	PER	DEL	BLEED	DEL-FR	K	NO
TO	0.0	202.0	29.0	0.2	308.0	0.0	0.0	0.0	1.0	4.0	0001
N.C.	0.1	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0002
N.C.	0.2	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0003
N.C.	0.3	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0004
N.C.	0.4	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0005
N.C.	0.5	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0006
N.C.	0.6	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0007
N.C.	0.7	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0008

T AMBIENT = 89.8°F

0 FEET ALTITUDE

POWER	MACH	DEL-SUP	INLET	DEL-FR	DEL-SHP	PER	DEL	BLEED	DEL-FR	K	NO
TO	0.0	202.0	29.0	0.2	308.0	0.0	0.0	0.0	1.0	4.0	0009
N.C.	0.1	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0010
N.C.	0.2	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0011
N.C.	0.3	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0012
N.C.	0.4	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0013
N.C.	0.5	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0014
N.C.	0.6	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0015
N.C.	0.7	167.0	27.0	0.2	271.0	0.0	0.0	0.0	1.0	4.0	0016

GENERAL MOTORS CORPORATION
ZERO POWER EXTRACTION

EDR 9775
P0370-40 TURBOPROP
100 PERCENT RECOVERY
STD DAY
0 FEET ALTITUDE

DETROIT DIESEL ALLISON DIVISION
ZERO BLEED

[illegible]

GENERAL MILK'S CORPORATION
ZENO POWER EXTRACTION

LUK 9775
PDJ10-40 JMBWPHUP
100 PERCENT RELUVENY
SIU UAY

DETAILED DIESEL ALLISON DIVISION
ZAKARYAH

[illegible]

DETROIT DIESEL ALLISON DIVISION
ZERO BLEED

14

GENERAL MUTUALS CORPORATION

ZERO POWER EXTRACTION

9775 JK 216

RU 370-40 IUKBPKJP

100 PERCENT KLUVER

THIS WAY

4,000 FEET ALTITUDE

DEIRK J. DIESEL ALLISON DIVISION

ZERU BLEED

[illegible]

EDR 9775

PD370-40 TURBOPROP

GENERAL MOTORS CORPORATION

SENSITIVITY DATA FOR BLEED, INLET RECOVERY, AND EXHAUST DUCT LOSS

0 FEET ALTITUDE

[illegible]

GENERAL MOTORS CORPORATION

LUR 9/75

DETROIT DIESEL ALLISON DIVISION

P0370-40 TURBOPROP

SENSITIVITY DATA FOR BLEED, INLET RECOVERY, AND EXHAUST DUCT LOSS

5000 FEET ALTITUDE

PLWLR	MACH	PER-SHP-INLET-DEL-FN	DEL-SHP	PER-DEL-WP	DEL-FN	K	NO
CLIMB M.C.	0.00	1.17	2.20	4.50	5.37	2.33	00490
	0.01	1.16	2.20	4.50	5.37	2.33	00501
	0.02	1.13	2.20	4.50	5.37	2.33	00512
	0.03	1.13	2.20	4.50	5.37	2.33	00523
	0.04	1.13	2.20	4.50	5.37	2.33	00534
	0.05	1.13	2.20	4.50	5.37	2.33	00545
	0.06	1.13	2.20	4.50	5.37	2.33	00556
	0.07	1.13	2.20	4.50	5.37	2.33	00567
	0.08	1.13	2.20	4.50	5.37	2.33	00578
	0.09	1.13	2.20	4.50	5.37	2.33	00589
	0.10	1.13	2.20	4.50	5.37	2.33	00600
	0.11	1.13	2.20	4.50	5.37	2.33	00611
	0.12	1.13	2.20	4.50	5.37	2.33	00622
	0.13	1.13	2.20	4.50	5.37	2.33	00633
	0.14	1.13	2.20	4.50	5.37	2.33	00644
	0.15	1.13	2.20	4.50	5.37	2.33	00655
	0.16	1.13	2.20	4.50	5.37	2.33	00666
	0.17	1.13	2.20	4.50	5.37	2.33	00677
	0.18	1.13	2.20	4.50	5.37	2.33	00688
	0.19	1.13	2.20	4.50	5.37	2.33	00699
	0.20	1.13	2.20	4.50	5.37	2.33	00710
	0.21	1.13	2.20	4.50	5.37	2.33	00721
	0.22	1.13	2.20	4.50	5.37	2.33	00732
	0.23	1.13	2.20	4.50	5.37	2.33	00743
	0.24	1.13	2.20	4.50	5.37	2.33	00754
	0.25	1.13	2.20	4.50	5.37	2.33	00765
	0.26	1.13	2.20	4.50	5.37	2.33	00776
	0.27	1.13	2.20	4.50	5.37	2.33	00787
	0.28	1.13	2.20	4.50	5.37	2.33	00798
	0.29	1.13	2.20	4.50	5.37	2.33	00809
	0.30	1.13	2.20	4.50	5.37	2.33	00820
	0.31	1.13	2.20	4.50	5.37	2.33	00831
	0.32	1.13	2.20	4.50	5.37	2.33	00842
	0.33	1.13	2.20	4.50	5.37	2.33	00853
	0.34	1.13	2.20	4.50	5.37	2.33	00864
	0.35	1.13	2.20	4.50	5.37	2.33	00875
	0.36	1.13	2.20	4.50	5.37	2.33	00886
	0.37	1.13	2.20	4.50	5.37	2.33	00897
	0.38	1.13	2.20	4.50	5.37	2.33	00908
	0.39	1.13	2.20	4.50	5.37	2.33	00919
	0.40	1.13	2.20	4.50	5.37	2.33	00930
	0.41	1.13	2.20	4.50	5.37	2.33	00941
	0.42	1.13	2.20	4.50	5.37	2.33	00952
	0.43	1.13	2.20	4.50	5.37	2.33	00963
	0.44	1.13	2.20	4.50	5.37	2.33	00974
	0.45	1.13	2.20	4.50	5.37	2.33	00985
	0.46	1.13	2.20	4.50	5.37	2.33	00996
	0.47	1.13	2.20	4.50	5.37	2.33	01007
	0.48	1.13	2.20	4.50	5.37	2.33	01018
	0.49	1.13	2.20	4.50	5.37	2.33	01029
	0.50	1.13	2.20	4.50	5.37	2.33	01040
	0.51	1.13	2.20	4.50	5.37	2.33	01051
	0.52	1.13	2.20	4.50	5.37	2.33	01062
	0.53	1.13	2.20	4.50	5.37	2.33	01073
	0.54	1.13	2.20	4.50	5.37	2.33	01084
	0.55	1.13	2.20	4.50	5.37	2.33	01095
	0.56	1.13	2.20	4.50	5.37	2.33	01106
	0.57	1.13	2.20	4.50	5.37	2.33	01117
	0.58	1.13	2.20	4.50	5.37	2.33	01128
	0.59	1.13	2.20	4.50	5.37	2.33	01139
	0.60	1.13	2.20	4.50	5.37	2.33	01150
	0.61	1.13	2.20	4.50	5.37	2.33	01161
	0.62	1.13	2.20	4.50	5.37	2.33	01172
	0.63	1.13	2.20	4.50	5.37	2.33	01183
	0.64	1.13	2.20	4.50	5.37	2.33	01194
	0.65	1.13	2.20	4.50	5.37	2.33	01205
	0.66	1.13	2.20	4.50	5.37	2.33	01216
	0.67	1.13	2.20	4.50	5.37	2.33	01227
	0.68	1.13	2.20	4.50	5.37	2.33	01238
	0.69	1.13	2.20	4.50	5.37	2.33	01249
	0.70	1.13	2.20	4.50	5.37	2.33	01260
	0.71	1.13	2.20	4.50	5.37	2.33	01271
	0.72	1.13	2.20	4.50	5.37	2.33	01282
	0.73	1.13	2.20	4.50	5.37	2.33	01293
	0.74	1.13	2.20	4.50	5.37	2.33	01304
	0.75	1.13	2.20	4.50	5.37	2.33	01315
	0.76	1.13	2.20	4.50	5.37	2.33	01326
	0.77	1.13	2.20	4.50	5.37	2.33	01337
	0.78	1.13	2.20	4.50	5.37	2.33	01348
	0.79	1.13	2.20	4.50	5.37	2.33	01359
	0.80	1.13	2.20	4.50	5.37	2.33	01370
	0.81	1.13	2.20	4.50	5.37	2.33	01381
	0.82	1.13	2.20	4.50	5.37	2.33	01392
	0.83	1.13	2.20	4.50	5.37	2.33	01403
	0.84	1.13	2.20	4.50	5.37	2.33	01414
	0.85	1.13	2.20	4.50	5.37	2.33	01425
	0.86	1.13	2.20	4.50	5.37	2.33	01436
	0.87	1.13	2.20	4.50	5.37	2.33	01447
	0.88	1.13	2.20	4.50	5.37	2.33	01458
	0.89	1.13	2.20	4.50	5.37	2.33	01469
	0.90	1.13	2.20	4.50	5.37	2.33	01480
	0.91	1.13	2.20	4.50	5.37	2.33	01491
	0.92	1.13	2.20	4.50	5.37	2.33	01502
	0.93	1.13	2.20	4.50	5.37	2.33	01513
	0.94	1.13	2.20	4.50	5.37	2.33	01524
	0.95	1.13	2.20	4.50	5.37	2.33	01535
	0.96	1.13	2.20	4.50	5.37	2.33	01546
	0.97	1.13	2.20	4.50	5.37	2.33	01557
	0.98	1.13	2.20	4.50	5.37	2.33	01568
	0.99	1.13	2.20	4.50	5.37	2.33	01579
	1.00	1.13	2.20	4.50	5.37	2.33	01590

GENERAL MOTORS CORPORATION

LUK 5775

PJ370-40 TURBO-PUMP

DEERE DIESEL ALLISON DIVISION

SENSITIVITY DATA FOR BLEED, INLET RELAY, AND EXHAUST WULI LUSS

10000 FEET ALTITUDE

POWER	MACH	REF SHIP DEL SHIP	INLET-REF DEL IN	BLEED-REF DEL BP	EXHAUST-REF DEL EX	K	NO
LLIMB M.C.	0.20	14.0	15.4	44.3	28.3	0.97	0089
	0.22	13.1	14.5	41.3	25.2	0.93	0090
	0.24	12.2	13.6	38.3	22.1	0.89	0091
	0.26	11.3	12.7	35.3	19.0	0.85	0092
	0.28	10.4	11.8	32.3	16.0	0.81	0093
	0.30	9.5	10.9	29.3	13.0	0.77	0094
	0.32	8.6	10.0	26.3	10.0	0.73	0095
	0.34	7.7	9.1	23.3	7.0	0.69	0096
	0.36	6.8	8.2	20.3	4.0	0.65	0097
	0.38	5.9	7.3	17.3	1.0	0.61	0098
	0.40	5.0	6.4	14.3		0.57	0099
	0.42	4.1	5.5	11.3		0.53	0100
	0.44	3.2	4.6	8.3		0.49	0101
	0.46	2.3	3.7	5.3		0.45	0102
	0.48	1.4	2.8	2.3		0.41	0103
	0.50	0.5	1.9			0.37	0104
	0.52		1.0			0.33	0105
	0.54		0.1			0.29	0106
	0.56					0.25	0107
	0.58					0.21	0108
	0.60					0.17	0109
	0.62					0.13	0110
	0.64					0.09	0111
	0.66					0.05	0112
	0.68					0.01	0113
	0.70						0114
	0.72						0115
	0.74						0116
	0.76						0117
	0.78						0118
	0.80						0119
	0.82						0120
	0.84						0121
	0.86						0122
	0.88						0123
	0.90						0124
	0.92						0125
	0.94						0126
	0.96						0127
	0.98						0128
	1.00						0129

GENERAL MOTORS CORPORATION

15000 FEET ALTITUDE

4.7.4.

DEVELOPMENTAL DIESEL ALLIANCE DIVISION

PU37U-40 TUKBUPKLP

SENSITIVITY DATA FOR BLEED, INLT RECOVERY, AND EXHAUST DUCT LOSS

20000 FEET ALTITUDE

[illegible]

AMERICAN ALLIANCE FOR THE ABOLITION OF SLAVERY

LUK 5775

PL 10-40 10450PKUP

GENERAL AUTUMS CORPORATION

SENSITIVITY DATA FOR BLEED, INLET RECOVERY, AND EXHAUST DUCT LOSS
30000 FEET ALTITUDE

[illegible]

UNIVERSITY MICROFILMS

4715

80-01570-40 1 JAN 1964

GENERAL MUTUALS COMPUTATION

SENSITIVITY DATA FOR BLEED, INLET RECOVERY, AND EXHAUST DUCT LOSS

35000 FEET ALTITUDE

[illegible]

GENERAL MATHEMATICS COMPUTATION

SENSITIVITY DATA FOR BLEED, INLET RECOVERY, AND EXHAUST DUCT LOSS

45000 FEET ALTITUDE

32