

AD-A101 244

D'APOLONIA CONSULTING ENGINEERS INC PITTSBURGH PA  
NATIONAL DAM INSPECTION PROGRAM, PA-RC & D-105 DAM (NOI I.D. PA-ETC(U)  
1981 L D ANDERSEN DACW31-81-C-0014


F/8 13/13

DACW31-81-C-0014

NL

UNCLASSIFIED

1 OF  
AD-A101 244



END  
DATE  
FILMED  
8-81  
DTIC

PA 701244

SUSQUEHANNA RIVER BASIN  
THOMAS CREEK, SUSQUEHANNA COUNTY

1

PENNSYLVANIA

LEVEL II

6

National Dam Inspection Program,

PA-RC & D-105 DAM

(NDLID: PA-0979,  
DER I.D. 058-138)

Susquehanna River


~~OWNER: SUSQUEHANNA COUNTY COMMISSIONERS~~

Basin, Thomas Creek, Susquehanna County,  
Pennsylvania. PHASE I INSPECTION REPORT,

NATIONAL DAM INSPECTION PROGRAM

10 Lawrence D. Andersen

11 1981  
12 71



DTIC  
ELECTE  
S JUL 13 1981 D  
E

\*Original contains color  
plates: All DTIC reproductions  
will be in black and  
white\*

PREPARED FOR 15 DACW31-81-C-0014

DEPARTMENT OF THE ARMY  
BALTIMORE DISTRICT, CORPS OF ENGINEERS  
BALTIMORE, MARYLAND 21203

BY

D'APPOLONIA CONSULTING ENGINEERS  
10 DUFF ROAD  
PITTSBURGH, PA. 15235

NOT A COPY

DISTRIBUTION STATEMENT A  
Approved for public release  
Distribution Unlimited

81 7 10 01

## PREFACE

This report is prepared under guidance contained in the Recommended Guidelines for Safety Inspection of Dams, for Phase I Investigations. Copies of these guidelines may be obtained from the Department of the Army, Office of Chief of Engineers, Washington, D.C. 20314.

↓ The purpose of a Phase I investigation is to identify expeditiously those dams which may pose hazards to human life or property. The assessment of the general condition of the dam is based upon visual observations and review of available data. Detailed investigations and analyses involving topographic mapping, subsurface investigations, material testing, and detailed computational evaluations are beyond the scope of a Phase I investigation; however, the inspection is intended to identify any need for such studies which should be performed by the owner.

In reviewing this report, it should be realized that the reported condition of the dam is based on observations of field conditions at the time of inspection along with data available to the inspection team. In cases where the reservoir was lowered or drained prior to inspection, such action, while improving the stability of the dam, removes the normal load on the structure and may obscure certain conditions which might otherwise be detectable if inspected under the normal operating environment of the structure.

↖ It is important to note that the condition of the dam depends on numerous and constantly changing internal and external factors which are evolutionary in nature. It would be incorrect to assume that the present condition of the dam will continue to represent the condition of the dam at some point in the future. Only through frequent inspections can unsafe conditions be detected and only through continued care and maintenance can these conditions be prevented or corrected.

Phase I inspections are not intended to provide detailed hydrologic and hydraulic analyses. In accordance with the established Guidelines, the spillway design flood is based on the estimated "Probable Maximum Flood" for the region (greatest reasonably possible storm runoff), or fractions thereof. The spillway design flood provides a measure of relative spillway capacity and serves as an aid in determining the need for more detailed hydrologic and hydraulic studies, considering the size of the dam, its general condition and the downstream damage potential.

The assessment of the conditions and recommendations was made by the consulting engineer in accordance with generally and currently accepted engineering principles and practices.

PHASE I REPORT  
NATIONAL DAM INSPECTION PROGRAM

NAME OF DAM: PA-RC&D-105 Dam  
 STATE LOCATED: Pennsylvania  
 COUNTY LOCATED: Susquehanna  
 STREAM: Thomas Creek, a secondary tributary of the Susquehanna River  
 SIZE CLASSIFICATION: Small  
 HAZARD CLASSIFICATION: High  
 OWNER: Susquehanna County Commissioners  
 DATE OF INSPECTION: November 13, 1980 and February 5, 1981

ASSESSMENT: Based on the evaluation of the existing conditions, the condition of PA-RC&D-105 Dam is considered to be good.


The flood discharge capacity was evaluated according to the recommended criteria and was found to pass full PMF without overtopping the embankment. Therefore, the spillway capacity is rated to be adequate.

The following recommendations should be implemented on a continuing basis.

1. Around-the-clock surveillance should be provided during unusually heavy runoff and a formal warning system should be developed to alert the downstream residents in the event of emergencies.
2. The dam and appurtenant structures should continue to be inspected regularly and necessary maintenance performed.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
<i>form 50 per</i>	
By _____	
Distribution/	
Availability Codes	
Avail and/or	
Dist	Special
<b>A</b>	

Assessment - PA-RC&D-105 Dam



*Lawrence D. Anderson*

Lawrence D. Anderson, P.E.  
Vice President

June 1, 1981  
Date

Approved by:

*James W. Peck*

JAMES W. PECK  
Colonel, Corps of Engineers  
Commander and District Engineer

17 Jun 1981  
Date:

PA-RC&D-105 DAN  
NDI I.D. PA-0979  
DER I.D. 058-138  
NOVEMBER 13, 1980



Upstream Face



Downstream Face

## TABLE OF CONTENTS

	<u>PAGE</u>
<b>SECTION 1 - PROJECT INFORMATION</b>	1
1.1 General	1
1.2 Description of Project	1
1.3 Pertiaent Data	2
<b>SECTION 2 - DESIGN DATA</b>	4
2.1 Design	4
2.2 Construction	5
2.3 Operation	5
2.4 Other Investigations	5
2.5 Evaluation	5
<b>SECTION 3 - VISUAL INSPECTION</b>	7
3.1 Findings	7
3.2 Evaluation	7
<b>SECTION 4 - OPERATIONAL FEATURES</b>	8
4.1 Procedure	8
4.2 Maintenance of the Dam	8
4.3 Maintenance of Operating Facilities	8
4.4 Warning System	8
4.5 Evaluation	8
<b>SECTION 5 - HYDRAULICS AND HYDROLOGY</b>	9
5.1 Evaluation of Features	9
<b>SECTION 6 - STRUCTURAL STABILITY</b>	10
6.1 Evaluation of Structural Stability	10
<b>SECTION 7 - ASSESSMENT AND RECOMMENDATIONS/ PROPOSED REMEDIAL MEASURES</b>	11
7.1 Dam Assessment	11
7.2 Recommendations/Remedial Measures	11

TABLE OF CONTENTS  
(Continued)

- APPENDIX A - CHECKLIST, VISUAL INSPECTION, PHASE I
- APPENDIX B - CHECKLIST, ENGINEERING DATA, DESIGN, CONSTRUCTION,  
OPERATION, AND HYDROLOGIC AND HYDRAULIC, PHASE I
- APPENDIX C - PHOTOGRAPHS
- APPENDIX D - HYDROLOGY AND HYDRAULICS ANALYSES
- APPENDIX E - PLATES
- APPENDIX F - REGIONAL GEOLOGY

PHASE I REPORT  
NATIONAL DAM INSPECTION PROGRAM  
PA-RC&D-105 DAM  
NDI I.D. PA-0979  
DER I.D. 058-138

SECTION 1  
PROJECT INFORMATION

1.1 General

a. Authority. The inspection was performed pursuant to the authority granted by The National Dam Inspection Act, Public Law 92-367, to the Secretary of the Army, through the Corps of Engineers, to conduct inspections of dams throughout the United States.

b. Purpose. The purpose of this inspection is to determine if the dam constitutes a hazard to human life or property.

1.2 Description of Project

a. Dam and Appurtenances. PA-RC&D-105 Dam is a part of the Springville Flood Prevention Project. The dam consists of an earth embankment approximately 200 feet long with a maximum height of 24 feet from the downstream toe and a crest width of 12 feet. Both the upstream and downstream slopes of the dam are covered with grass and have slopes of 3H:1V with a 12-foot berm on the upstream slope near normal pool level.

The flood discharge facilities of the dam consist of a drop inlet primary spillway located near the center of the embankment and an emergency spillway located on the right abutment. The primary spillway is a drop inlet structure consisting of a two-stage reinforced concrete riser and a 30-inch-diameter reinforced concrete conduit, terminating at a reinforced concrete impact basin energy dissipating structure at the downstream toe of the dam. The outlet pipe is supported on a concrete cradle equipped with five antiseepage collars spaced at 20-foot intervals along the upstream two-thirds of the pipe. The emergency spillway is a grass-lined trapezoidal channel with a base width of 60 feet. A 30-foot-wide level section extending across the emergency spillway channel constitutes the overflow section.

b. Location. PA-RC&D-105 Dam is located across Thomas Creek approximately one-quarter mile upstream from Springville, in Springville Township, Susquehanna County, Pennsylvania (N41° 42.1', W75° 55.5'). Plate 1 illustrates the location of the dam.

c. Size Classification. Small (based on 24-foot height and 342 acre-feet maximum storage capacity).

d. Hazard Classification. The dam is classified to be in the high hazard category. Below the dam, Thomas Creek flows under a highway (LR57012) approximately 1,000 feet downstream from the dam and shortly thereafter flows through the urban residential area of Springville. It is estimated that failure of the dam under maximum pool level would cause loss of more than a few lives and property damage in the downstream residential areas.

e. Ownership. Susquehanna County Commissioners (address: Mr. James Adams, Chairman, Susquehanna County Commissioners, Court House, Montrose, Pennsylvania 18801).

f. Purpose of Dam. Flood control.

g. Design and Construction History. The dam was designed by the U.S. Department of Agriculture, Soil Conservation Service, during 1974. Construction of the dam was completed in 1978.

h. Normal Operating Procedure. The reservoir is normally maintained at Elevation 1254.9, the crest level of a two-foot-high and one-foot-wide orifice on the upstream face of the drop inlet structure. The crest level of the primary spillway is at Elevation 1260.6. The crest of the emergency spillway is at Elevation 1260.8. Depending on the rate of inflow, the flood would be discharged through the orifice in combination with the primary and emergency spillways.

### 1.3 Pertinent Data

a. <u>Drainage Area</u>	0.6 square mile
b. <u>Discharge at Dam Site (cfs)</u>	
Maximum known flood at dam site	Unknown
Outlet conduit at maximum pool	118
Gated spillway capacity at maximum pool	Not applicable
Ungated spillway capacity at maximum pool	3580
Total spillway capacity at maximum pool	3580
c. <u>Elevation (USGS Datum) (feet)</u>	
Top of dam	1267.2 (as measured)
	1266.8 (as designed)
Maximum pool	1266.8
Normal pool	1254.9
Upstream invert outlet works	1249.1
Downstream invert outlet works	1242.9
Streambed at center line of dam	1243 <sup>+</sup>
Maximum tailwater	Unknown
d. <u>Reservoir Length (feet)</u>	
Normal pool level	1400 <sup>+</sup>
Maximum pool level	1500 <sup>+</sup>

e. Storage (acre-feet)

Normal pool level	50 (estimated)
Maximum pool level	342

f. Reservoir Surface (acres)

Normal pool level	16±
Maximum pool level	30±

g. Dam

Type	Earth
Length	200 feet
Height	24 feet
Top width	12 feet
Side slopes	Downstream: 3H:1V Upstream: 3H:1V
Zoning	No
Impervious core	No
Cutoff	Yes
Grout curtain	No

h. Regulating Outlet

Type	18-inch reinforced concrete pipe
Length	20 feet to drop inlet
Closure	Sluice gate at drop inlet structure
Access	Drop inlet structure
Regulating facilities	Sluice gate

i. Spillway

Primary: (1)

Emergency:

Type	Drop inlet	Trapezoidal earth channel
Width	15 feet	60 feet
Crest elevation	1260.6	1260.8
Gates	None	None
Upstream channel	Lake	Trapezoidal earth channel
Downstream channel	30-inch outlet reinforced concrete conduit	Trapezoidal earth channel

(1) Normal pool is maintained at the crest level of a two-foot-wide and one-foot-high orifice on the drop inlet at Elevation 1254.9.

SECTION 2  
DESIGN DATA

2.1 Design

a. Data Available. The available information was provided by the Pennsylvania Department of Environmental Resources (PennDER), and includes design drawings, reports, and correspondence.

(1) Hydrology and Hydraulics. The available information consists of principal, freeboard, and emergency spillway inflow hydrographs and the results of associated flood routings.

(2) Embankment. The available information consists of design drawings, geology and soils reports, laboratory soils test results, and the results of slope stability and seepage analyses.

(3) Appurtenant Structures. The available information includes design drawings.

b. Design Features

(1) Embankment. Plates 2 and 3 illustrate the plan of the embankment and the appurtenant structures. As shown in Plate 4, the dam consists of a homogeneous earth embankment with a trench drain located beneath the downstream slope.

The dam was designed to have a 3:1 (horizontal to vertical) slope downstream and upstream. A 12-foot-wide berm on the upstream slope is located at approximately the midheight of the dam.

The subsurface investigation conducted for the dam consisted of numerous borings and test pits. The locations of these borings are shown in Plate 3. Plate 5 shows the typical subsurface profile. The typical subsurface profile consists of 20 feet of medium stiff to hard sandy clayey silts on the valley sides and about 15 feet of loose to dense sand and gravel and clayey sands in the valley bottom. The rock beneath the site includes siltstone and sandstones. In the valley bottom, sandstone was encountered to a depth of approximately 15 feet. It is reported that the permeability of the sandy clayey silt was found to be low, ranging from 0.1 to 0.9 foot per day ( $4 \times 10^{-5}$  cm/sec to  $3 \times 10^{-4}$  cm/sec). These permeabilities were measured at depths ranging from 4 to 22 feet. Details of the downstream slope trench drain are included in Plate 6.

(2) Appurtenant Structures. The appurtenant structures of the dam consist of a drop inlet primary spillway and an emergency spillway. The primary spillway structures include a two-stage reinforced concrete riser and a 30-inch-diameter reinforced concrete conduit through the embankment terminating at a reinforced concrete impact basin at the downstream toe of the dam (Plates 7, 8, and 9). An 18-inch reinforced concrete pipe

from the upstream toe of the dam, discharging into the drop inlet structure, constitutes the reservoir outlet facilities. Flow through the reservoir outlet pipe is controlled by a sluice gate located in the drop inlet structure. The outlet conduit is supported on a continuous concrete cradle with five reinforced concrete cutoff collars.

The emergency spillway is a trapezoidal earth channel excavated into the right abutment (Plate 2). The bottom width of the trapezoidal channel is 60 feet with side slopes of 3H:1V. A 30-foot-wide level section located at Elevation 1206.8 constitutes the control section of the spillway.

c. Design Data

(1) Hydrology and Hydraulics. Available information indicates that the emergency spillway was designed to pass a freeboard hydrograph with a peak of 4647 cfs, corresponding to 24.3 inches of precipitation in six hours without overtopping the embankment. This hydrograph was routed through the reservoir starting at normal pool (Elevation 1254.9), producing a maximum pool level at Elevation 1266.8 with a peak emergency spillway outflow of 2719 cfs. The top of the dam was established at Elevation 1266.8.

(2) Embankment. Available information indicates that the design of the embankment was based on the evaluation of site geology, subsurface conditions, and laboratory index and strength tests.

(3) Appurtenant Structures. The available information indicates that the appurtenant structures were standard Soil Conservation Service (SCS) designs.

2.2 Construction. As-built drawings and construction progress reports were available for review. To the extent that can be determined, the construction of the dam was in conformance with SCS specifications. No unusual construction difficulties were reported. The dam was constructed under the supervision of an SCS field representative. It is reported that the earthwork was monitored by field density tests. However, the results were not available for review.

Available information indicates no postconstruction changes.

2.3 Operation. No records of operation are kept.

2.4 Other Investigations. None reported.

2.5 Evaluation

a. Availability. Available information was obtained from PennDER.

b. Adequacy

(1) Hydrology and Hydraulics. The available information is considered to be adequate to assess the conformity of the design to the current spillway design criteria.

(2) Embankment. Review of the geotechnical aspects of the design indicates that the design generally followed currently accepted practice for subsurface investigation, laboratory testing, analysis, and construction.

(3) Appurtenant Structures. Review of the design drawings indicates that the appurtenant structures were designed and constructed in conformance with currently accepted engineering practices.

SECTION 3  
VISUAL INSPECTION

3.1 Findings

a. General. The onsite inspection of PA-RC&D-105 Dam consisted of:

1. Visual inspection of the embankment, abutments, and embankment toe.
2. Visual examination of the emergency spillway and visible portions of the primary spillway.
3. Evaluation of downstream area hazard potential.

The specific observations are illustrated in Plate 10.

b. Embankment. The general inspection of the embankment consisted of searching for indications of structural distress, such as cracks, subsidence, bulging, wet areas, seeps and boils, and observing general maintenance conditions, vegetative cover, erosion, and other surficial features.

In general, the condition of the dam is considered to be good. No seepage or other signs of distress were observed during inspection. Some minor erosion scars were found on the upstream and downstream faces of the dam.

The top of the dam was surveyed relative to the emergency spillway crest elevation and was found to be within 0.2 foot of the design elevation with camber. Plate 11 shows the dam crest profile.

c. Appurtenant Structures. The appurtenant structures were examined for deterioration or other signs of distress and obstructions that would limit flow. The structures were found to be in good condition. No deficiencies were noted at this time.

d. Reservoir Area. A map review indicates that the watershed is predominantly covered with woodlands. A review of the regional geology is included in Appendix F.

e. Downstream Channel. Downstream from the dam, Thomas Creek flows approximately 2,000 feet southeast where it passes through residential areas of Springville. Further description of downstream conditions is included in Section 1.2 d.

3.2 Evaluation. The dam was found to be in good condition and adequately monitored.

SECTION 4  
OPERATIONAL FEATURES

4.1 Procedure. The reservoir is normally maintained at the primary spillway orifice level with excess inflow discharging through the orifice. The reservoir outlet pipe can be used to draw down the permanent pool when required. The reservoir outlet pipe gate is normally closed.

4.2 Maintenance of the Dam. The maintenance of the dam is considered to be good. The downstream and upstream faces of the dam are covered with grass and appear to be annually mowed.

4.3 Maintenance of Operating Facilities. The only operational feature of the dam is the reservoir outlet pipe sluice gate operated by a hoist located on the primary spillway drop inlet structure. Since the top of the drop inlet structure was not accessible, this facility could not be closely examined.

4.4 Warning System. No formal warning system exists for the dam. Telephone communication facilities are available via residences at the dam site.

4.5 Evaluation. The maintenance condition of the dam is considered to be good.

SECTION 5  
HYDRAULICS AND HYDROLOGY

5.1 Evaluation of Features

a. Design Data. PA-RC&D-105 Dam has a watershed of 0.6 square mile and impounds a reservoir with a surface area of 16 acres at normal pool level. The emergency spillway of the dam is located on the right abutment. The capacity of the emergency spillway is calculated to be 3580 cfs with no freeboard.

b. Experience Data. As previously stated, PA-RC&D-105 Dam is classified as a small dam in the high hazard category. Under the recommended criteria for evaluating emergency spillway discharge capacity, such impoundments are required to pass one-half to full Probable Maximum Flood (PMF). In view of the high downstream drainage potential, full PMF was selected as the spillway design flood.

The PMF inflow hydrograph for the reservoir was determined using the Dam Safety Version of the HEC-1 computer program developed by the Hydrologic Engineering Center of the U.S. Army, Corps of Engineers. The data used for the computer input are presented in Appendix D. The PMF inflow hydrograph was found to have a peak flow of 1590 cfs. The computer outputs are included in Appendix D.

c. Visual Observations. On the dates of inspection, no conditions were observed that would indicate that the emergency spillway capacity would be significantly reduced in the event of a flood.

d. Overtopping Potential. PMF inflow hydrograph was routed through the reservoir and it was found that the dam can pass 100 percent PMF without overtopping.

e. Spillway Adequacy. The spillway can pass the recommended spillway design flood of full PMF without overtopping the embankment; therefore, the spillway capacity is classified to be adequate according to the recommended criteria.

SECTION 6  
STRUCTURAL STABILITY

6.1 Evaluation of Structural Stability

a. Visual Observations

(1) Embankment. As discussed in Section 3, the field observations did not reveal any signs of distress that would significantly affect the stability of the embankment at this time. However, it should be understood that since the dam is a flood control facility and was at normal (low level) pool at the time of inspection, it was not under maximum loading conditions. Maximum loading occurs only during the passage of major floods.

(2) Appurtenant Structures. Performance of the appurtenant structures is considered to be satisfactory.

b. Design and Construction Data

(1) Embankment. Available information indicates that the stability of the embankment was analyzed for steady seepage and rapid drawdown conditions using the modified Swedish circle and sliding block slope stability analysis procedures. The minimum factor of safety was reported to be 2.1 for the steady-state seepage stability of the downstream slope and 1.4 for the rapid drawdown condition of the upstream slope. Strength parameters for the core material were obtained from consolidated-undrained triaxial shear tests with pore pressure measurements. Assumed strength parameter values were used for the shell materials. Construction progress reports indicate that the dam was constructed under the supervision of an SCS field representative, and the earthwork was monitored by field density tests.

(2) Appurtenant Structures. Review of the design drawings indicates that there are no apparent structural deficiencies that would significantly affect the performance of the appurtenant structures.

c. Operating Records. There are no operating records kept for the dam.

d. Postconstruction Changes. None reported.

e. Seismic Stability. The dam is located in Seismic Zone 1, and based on visual observations, the static stability of the dam is considered to be adequate. Therefore, based on the recommended criteria for evaluation of seismic stability of dams, the structure is presumed to present no hazard from earthquakes.

SECTION 7  
ASSESSMENT AND RECOMMENDATIONS/PROPOSED REMEDIAL MEASURES

7.1 Dam Assessment

a. Assessment. The visual observations indicate that PA-RC&D-105 Dam is in good condition. No conditions were observed that would significantly affect the overall performance of the structure at this time. However, as previously noted, the dam was not inspected under its maximum loading condition, which would occur when the reservoir is filled during major storms.

The spillway can pass the required spillway design flood and is, therefore, classified to be adequate according to the recommended criteria.

b. Adequacy of Information. Available information, in conjunction with the visual observations, is considered to be sufficient to make a Phase I evaluation.

c. Urgency. The following recommendations should be implemented on a continuing basis.

d. Necessity for Additional Investigation. No additional investigation is considered to be required at this time.

7.2 Recommendations/Remedial Measures. It is recommended that:

1. Around-the-clock surveillance should be provided during unusually heavy runoff and a formal warning system should be developed to alert the downstream residents in the event of emergencies.
2. The dam and appurtenant structures should continue to be inspected regularly and necessary maintenance performed.

APPENDIX A  
CHECKLIST  
VISUAL INSPECTION  
PHASE I

APPENDIX A

CHECKLIST  
VISUAL INSPECTION  
PHASE I

NAME OF DAM PA-RC&D-105 COUNTY Susquehanna STATE Pennsylvania NDI: PA-0979  
ID# 058-138

TYPE OF DAM Earth HAZARD CATEGORY High

DATE(S) INSPECTION November 13, 1980 WEATHER Sunny TEMPERATURE 50's

POOL ELEVATION AT TIME OF INSPECTION 1254.6 M.S.L. TAILWATER AT TIME OF INSPECTION 1243 ± M.S.L.

INSPECTION PERSONNEL:

REVIEW INSPECTION PERSONNEL:  
(February 5, 1981)

Douglas Cosler Lawrence D. Andersen  
Arthur Smith James H. Poellot  
Bilgin Erel Bilgin Erel

Owner's Representative:

None

Bilgin Erel RECORDER

VISUAL INSPECTION  
 PHASE I  
 EMBANKMENT

VISUAL EXAMINATION OF	OBSERVATIONS	REMARKS OR RECOMMENDATIONS
SURFACE CRACKS	None found.	
UNUSUAL MOVEMENT OR CRACKING AT OR BEYOND THE TOE	None found.	
SLOUGHING OR EROSION OF EMBANKMENT AND ABUTMENT SLOPES	None found.	
VERTICAL AND HORIZONTAL ALIGNMENT OF THE CREST	See Plate 2 for dam crest profile. No perceivable horizontal misalignment.	
RIPRAP FAILURES	None	

VISUAL INSPECTION  
PHASE I  
EMBANKMENT

VISUAL EXAMINATION OF	OBSERVATIONS	REMARKS OR RECOMMENDATIONS
JUNCTION OF EMBANKMENT AND ABUTMENT, SPILLWAY AND DAM	No signs of distress.	
ANY NOTICEABLE SEEPAGE	None	
STAFF GAGE AND RECORDER	None	
DRAINS	Toe drains discharging to outlet pipe impact basin are dry.	

VISUAL INSPECTION  
 PHASE I  
 OUTLET WORKS

VISUAL EXAMINATION OF	OBSERVATIONS	REMARKS OR RECOMMENDATIONS
CRACKING AND SPALLING OF CONCRETE SURFACES IN OUTLET CONDUIT	Not accessible for inspection.	
INTAKE STRUCTURE	In good condition.	
OUTLET STRUCTURE	In good condition.	
OUTLET CHANNEL	No problems observed.	
EMERGENCY GATE (Reservoir Drainpipe Gate)	Equipment in good condition. Operational condition not observed.	Reservoir drainpipe gate should be periodically observed.

VISUAL INSPECTION  
 PHASE I  
 UNGATED SPILLWAY

VISUAL EXAMINATION OF	OBSERVATIONS	REMARKS OR RECOMMENDATIONS
CONCRETE WEIR	Primary Spillway: In good condition. Emergency spillway: No concrete overflow structure.	
APPROACH CHANNEL	Primary Spillway: Lake Emergency Spillway: Lake	
DISCHARGE CHANNEL	Primary Spillway: Concrete pipe. (Not accessible for inspection.) Emergency Spillway: Earth channel in good condition.	
BRIDGE AND PIERS	None	

VISUAL INSPECTION  
 PHASE I  
 GATED SPILLWAY

VISUAL EXAMINATION OF	OBSERVATIONS	REMARKS OR RECOMMENDATIONS
CONCRETE SILL	The dam has no gated spillway.	
APPROACH CHANNEL	N/A	
DISCHARGE CHANNEL	N/A	
BRIDGE PIERS	N/A	
GATES AND OPERATION EQUIPMENT	N/A	

VISUAL INSPECTION  
 PHASE I  
 INSTRUMENTATION

VISUAL EXAMINATION OF	OBSERVATIONS	REMARKS OR RECOMMENDATIONS
MONUMENTATION/SURVEYS	None	
OBSERVATION WELLS	None	
WEIRS	None	
PIEZOMETERS	None	
OTHER	None	

VISUAL INSPECTION  
 PHASE I  
 RESERVOIR

VISUAL EXAMINATION OF	OBSERVATIONS	REMARKS OR RECOMMENDATIONS
SLOPES	No problems observed.	
SEDIMENTATION	Unknown	
UPSTREAM RESERVOIRS	None	

VISUAL INSPECTION  
 PHASE I  
 DOWNSTREAM CHANNEL

VISUAL EXAMINATION OF	OBSERVATIONS	REMARKS OR RECOMMENDATIONS
CONDITION (OBSTRUCTIONS, DEBRIS, ETC.)	No problems observed.	
SLOPES	No problems observed.	
APPROXIMATE NUMBER OF HOMES AND POPULATION	Residential areas of Springville - approximately five to ten houses on floodplain. Population: Approximately 50.	

APPENDIX B  
CHECKLIST  
ENGINEERING DATA  
DESIGN, CONSTRUCTION, OPERATION  
AND HYDROLOGIC AND HYDRAULIC  
PHASE I

APPENDIX B

CHECKLIST

ENGINEERING DATA

DESIGN, CONSTRUCTION, OPERATION

PHASE I

NAME OF DAM PA-RC&D-105

ID# NDI: PA-0979

DER: 058-138

ITEM	REMARKS
AS-BUILT DRAWINGS	Available in Commonwealth of Pennsylvania files.
REGIONAL VICINITY MAP	See Plate 1.
CONSTRUCTION HISTORY	The dam was designed by the Soil Conservation Service. The construction of the dam was completed in 1978.
TYPICAL SECTIONS OF DAM	See Plate 4.
OUTLETS - PLAN - DETAILS - CONSTRAINTS - DISCHARGE RATINGS	See Plates 7, 8, and 9.

CHECKLIST  
ENGINEERING DATA  
DESIGN, CONSTRUCTION, OPERATION  
PHASE I

ITEM	REMARKS
RAINFALL/RESERVOIR RECORDS	Not maintained.
DESIGN REPORTS	Available in Commonwealth of Pennsylvania files.
GEOLOGY REPORTS	Available in Commonwealth of Pennsylvania files.
DESIGN COMPUTATIONS HYDROLOGY & HYDRAULICS DAM STABILITY SEEPAGE STUDIES	Available in Commonwealth of Pennsylvania files.
MATERIALS INVESTIGATIONS BORING RECORDS LABORATORY FIELD	Available in Commonwealth of Pennsylvania files.

CHECKLIST  
 ENGINEERING DATA  
 DESIGN, CONSTRUCTION, OPERATION  
 PHASE I

ITEM	REMARKS
POST CONSTRUCTION SURVEYS OF DAM	None reported.
BORROW SOURCES	Unknown
MONITORING SYSTEMS	None
MODIFICATIONS	None reported.
HIGH POOL RECORDS	Not recorded.

**CHECKLIST**  
**ENGINEERING DATA**  
**DESIGN, CONSTRUCTION, OPERATION**  
**PHASE I**

ITEM	REMARKS
POST CONSTRUCTION ENGINEERING STUDIES AND REPORTS	None reported.
PRIOR ACCIDENTS OR FAILURE OF DAM DESCRIPTION REPORTS	None reported.
MAINTENANCE OPERATION RECORDS	Not maintained.
SPILLWAY PLAN SECTIONS DETAILS	See Plate 3.
OPERATING EQUIPMENT PLANS AND DETAILS	Included in design drawings.

CHECKLIST  
ENGINEERING DATA  
HYDROLOGIC AND HYDRAULIC

DRAINAGE AREA CHARACTERISTICS: 0.6 square mile (woodlands)  
ELEVATION, TOP OF NORMAL POOL AND STORAGE CAPACITY: 1254.9 (50 acre-feet)  
ELEVATION, TOP OF FLOOD CONTROL POOL AND STORAGE CAPACITY: 1266.8 (342 acre-feet)  
ELEVATION, MAXIMUM DESIGN POOL: 1266.8  
ELEVATION, TOP OF DAM: 1266.8

SPILLWAY: (Emergency)

- a. Elevation 1260.8
- b. Type Open channel
- c. Width 60 feet (base width)
- d. Length N/A
- e. Location Spillover Adjacent to spillway
- f. Number and Type of Gates None

OUTLET WORKS:

- a. Type 18-inch reservoir drainpipe
- b. Location Discharges into primary spillway riser
- c. Entrance Inverts 1245.1
- d. Exit Inverts 1245.1
- e. Emergency Drawdown Facilities 18-inch reservoir drainpipe

HYDROMETEOROLOGICAL GAGES:

- a. Type None
- b. Location None
- c. Records None


MAXIMUM NONDAMAGING DISCHARGE: 3600 cfs (capacity of emergency spillway)

**APPENDIX C**

**PHOTOGRAPHS**

LIST OF PHOTOGRAPHS  
PA-RC&D-105 DAM  
NDI I.D. NO. PA-0979  
NOVEMBER 13, 1980

<u>PHOTOGRAPH NO.</u>	<u>DESCRIPTION</u>
1	Crest (looking southeast).
2	Primary discharge channel (looking downstream).
3	Emergency spillway channel.
4	Primary intake structure.
5	Primary outlet structure.
6	Normal pool orifice.
7 & 8	Houses along Thomas Creek (approximately 0.2 mile downstream from dam).



LEGEND:



INDICATES DIRECTION IN WHICH PHOTOGRAPH WAS TAKEN

PA-RC & D-105  
 KEY PLAN OF PHOTOGRAPHS  
 FIELD INSPECTION DATE: NOV. 13, 1980

**D'APOLONIA**




PHOTOGRAPH NO. 2



PHOTOGRAPH NO. 4




PHOTOGRAPH NO. 1



PHOTOGRAPH NO. 3



PHOTOGRAPH NO 5



PHOTOGRAPH NO. 6



PHOTOGRAPH NO 7



PHOTOGRAPH NO 8

**APPENDIX D**

**HYDROLOGY AND HYDRAULICS ANALYSES**

HYDROLOGY AND HYDRAULIC ANALYSIS  
DATA BASE

NAME OF DAM: PA-RC&D-105 Dam

PROBABLE MAXIMUM PRECIPITATION (PMP) = 22.2 INCHES/24 HOURS(1)

STATION	1	2	3	4	5
Station Description	Thomas Creek	PA-RC&D-105 Dam			
Drainage Area (square miles)	0.61	—			
Cumulative Drainage Area (square miles)	0.61	0.61			
Adjustment of PMF for Drainage Area (%) <sup>(1)</sup>	94%				
6 Hours	117				
12 Hours	127				
24 Hours	136				
48 Hours	142				
72 Hours	145				
Snyder Hydrograph Parameters Zone <sup>(2)</sup>	11				
C <sub>p</sub> /C <sub>t</sub> <sup>(3)</sup>	0.62/1.50				
L (miles) <sup>(4)</sup>	1.14				
L <sub>ca</sub> (miles) <sup>(4)</sup>	0.66				
t <sub>p</sub> = C <sub>t</sub> (L·L <sub>ca</sub> ) <sup>0.3</sup> (hours)	1.38				
Spillway Data		Primary Emergency			
Crest Length (ft)		15.0	60.0		
Freeboard (ft)		6.2	6.0		
Discharge Coefficient		3.2	2.65		
Exponent		1.5	1.5		

(1) Hydrometeorological Report 40, U.S. Weather Bureau, 1965.

(2) Hydrological zone defined by Corps of Engineers, Baltimore District, for determining Snyder's Coefficients (C<sub>p</sub> and C<sub>t</sub>).

(3) Snyder's Coefficients.

(4) L = Length of longest water course from outlet to basin divide.

L<sub>ca</sub> = Length of water course from outlet to point opposite the centroid of drainage area.

STORAGE VS. ELEVATION

ELEVATION	ΔH, FEET	AREA (1) (acres)	ΔVOLUME (1) (acre-feet)	STORAGE (acre-feet)
1267.8		30.5		360.1
	8.0		215.1	
1259.8		23.0		145.0
	5.0		97.1	
1254.8		15.8		47.9
	5.0		47.9	
1249.8		0.32		0

(1) From DER files. SCS calculations.



PEAK FLOW AND STORAGE (END OF PERIOD) SUMMARY FOR MULTIPLE PLAN-RATIO ECONOMIC COMPUTATIONS  
 FLOWS IN CUBIC FEET PER SECOND (CUBIC METERS PER SECOND)  
 AREA IN SQUARE MILES (SQUARE KILOMETERS)

OPERATION	STATION	AREA	PLAN	RATIOS APPLIED TO FLOWS										
				RATIO 1	RATIO 2	RATIO 3	RATIO 4	RATIO 5	RATIO 6	RATIO 7	RATIO 8	RATIO 9		
				.20	.30	.40	.50	.60	.70	.80	.90	1.00		
HYDROGRAPH AT	1	.61	1	319.	478.	637.	797.	956.	1114.	1275.	1414.	1594.		
	(	1.58)	(	9.03)	13.54)	18.05)	22.56)	27.08)	31.59)	36.10)	40.61)	45.13)		
ROUTED TO	2	.61	1	20.	125.	308.	486.	656.	827.	1002.	1170.	1339.		
	(	1.58)	(	.56)	3.53)	8.72)	13.76)	18.57)	23.41)	28.36)	33.14)	37.91)		

SUMMARY OF DAM SAFETY ANALYSIS

PLAN 1 .....	ELEVATION STORAGE OUTFLOW	INITIAL VALUE 1254.90 50. 0.	SPILLWAY CREST 1254.90 50. 0.	TOP OF DAM 1267.20 362. 3786.	MAXIMUM RESERVOIR W.S.ELEV	MAXIMUM DEPTH OVER DAM	MAXIMUM STORAGE AC-FT	MAXIMUM OUTFLOW CFS	DURATION OVER TOP HOURS	TIME OF MAX OUTFLOW HOURS	TIME OF FAILURE HOURS
RATIO OF PMF	MAXIMUM RESERVOIR W.S.ELEV	MAXIMUM DEPTH OVER DAM	MAXIMUM STORAGE AC-FT	MAXIMUM OUTFLOW CFS	DURATION OVER TOP HOURS	TIME OF MAX OUTFLOW HOURS	TIME OF FAILURE HOURS				
.20	1259.72	0.00	143.	20.	0.00	45.75	0.00				
.30	1261.24	0.00	179.	125.	0.00	44.00	0.00				
.40	1261.86	0.00	195.	308.	0.00	43.00	0.00				
.50	1262.34	0.00	207.	486.	0.00	42.50	0.00				
.60	1262.75	0.00	218.	656.	0.00	42.25	0.00				
.70	1263.13	0.00	228.	827.	0.00	42.00	0.00				
.80	1263.47	0.00	236.	1002.	0.00	42.00	0.00				
.90	1263.78	0.00	245.	1170.	0.00	41.75	0.00				
1.00	1264.08	0.00	253.	1339.	0.00	41.75	0.00				


# D'APPOLONIA

CONSULTING ENGINEERS, INC.

By WTC Date 1-19-81 Subject PA, RC&D 105 Sheet No. 1 of 2  
 Chkd. By CMB Date 1/29/81 Proj. No. 80-556-0

## PRINCIPAL SPILLWAY CAPACITY

## AS BUILT PLANS



FOR ORIFICE FLOW

$$Q_o = C_d A \sqrt{2gh} = (0.6)(2 \times 1)(6.4)^{1/2} \sqrt{h} = 9.63 \sqrt{\text{LAKE EL.} - 1255.4} \quad (\text{EQ-1})$$

↑ CENTER OF ORIFICE

FOR WEIR FLOW OF RISER

$$Q_w = C L H^{1.5} = (3.22) (15) (H)^{1.5} = 48.3 (\text{LAKE EL.} - 1260.6)^{1.5} \quad (\text{EQ-2})$$

Sharp Crested Weir

PIPE FLOW OF RISER (REF. DESIGN OF SMALL DAM, 2<sup>ND</sup> EDITION, P. 567)

$$H_T = \left[ \frac{(2.5204)(1+K_e)}{D^5} + \frac{(466.18)(n)^2(L)}{D^{16/5}} \right] \left( \frac{Q_p}{10} \right)^2 = \left[ \frac{(2.5204)(1.5)}{(2.5)^5} + \frac{(466.18)(0.012)^2(108)}{(2.5)^{16/5}} \right] \left( \frac{Q_p}{10} \right)^2$$

$$Q_p = 25.69 \sqrt{H_T} = 25.69 \sqrt{\text{LAKE EL.} - 1242.9 - \text{TAILWATER}} = 25.69 \sqrt{\text{LAKE EL.} - 1246} \quad (\text{EQ-3})$$

↑ ASSUMED

LAKE LEVEL ELEVATION	EQ 1	EQ 2	Q <sub>o</sub> +Q <sub>w</sub>	EQ-3	PRIMARY SPILLWAY Q <sub>s</sub>	LAKE LEVEL ELEVATION	PRIMARY SPILLWAY Q <sub>s</sub> =Q <sub>o</sub>
	Q <sub>o</sub>	Q <sub>w</sub>		Q <sub>p</sub>			
	cfs	cfs	cfs	cfs	cfs		cfs
1254.9	0				0	1264.0	109.0
1256.0	7.5				7.5	1265.0	112.0
1258.0	15.5				15.5	1266.0	115
1260.6	22.0	0			22.0	1267.0	118
1260.8	22.4	4.3	26.7	98.8	26.7	1268.0	120
1261.0	22.8	12.2	35.0	99.5	35.0		
1261.98	24.7	78.0	102.7	102.7	102.7		
1263	26.5	179.6	206.1	105.9	105.9		

# D'APPOLONIA

CONSULTING ENGINEERS, INC.

By WTC Date 1-19-81 Subject PA RC&D 105

Sheet No. 2 of 2

Chkd. By MS Date 1/29/81

Proj. No. 80-556-09

## EMERGENCY SPILLWAY CAPACITY

REFERENCE "DESIGN OF SMALL DAM" 2<sup>nd</sup> ED. PSS3

$$V_c = \sqrt{\frac{b+z d_c}{b+2z d_c}} d_c g \quad (EQ-1)$$



$$H_E = d_c + \frac{V_c^2}{2g} = d_c + \left(\frac{b+z d_c}{b+2z d_c}\right) (d_c g) \left(\frac{1}{2g}\right)$$

$$= \frac{(3b+5z d_c) d_c}{2b+4z d_c}$$

$$d_c = \frac{-(3b-4H_E z) + \sqrt{(3b-4H_E z)^2 + (4H_E z)(10b)}}{10z} \quad (EQ-2)$$

$$A_c = (z d_c + b) d_c \quad (EQ-3)$$

$$Q_c = (A_c)(V_c) \quad (EQ-4)$$



LAKE LEVEL ELEVATION	H <sub>E</sub> FT	EQ-2	EQ-3	EQ-1	EMERGENCY SPILLWAY	PRIMARY SPILLWAY	COMBINED SPILLWAY
		d <sub>c</sub> FT	A <sub>c</sub> ft <sup>2</sup>	V <sub>c</sub> fps	Q <sub>c</sub> cfs	Q <sub>s</sub> cfs	Q <sub>c</sub> + Q <sub>s</sub> cfs
1254.9						0	0
1256.0						7.5	7.5
1258.0						15.5	15.5
1260.6						22.0	22.0
1260.8	0	0	0	0	0	26.7	26.7
1261.0	0.2	0.1	8.1	2.1	16.7	35.0	51.7
1261.98 <sup>(H)</sup>	1.18	0.8	49.7	5.0	247.0	102.7	349.7
1263.0	2.2	1.5	96.7	6.7	649.6	105.9	755.5
1264.0	3.2	2.2	146.5	8.0	1175.8	109.0	1284.8
1265.0	4.2	2.9	199.9	9.1	1823.0	112.0	1935.0
1266.0	5.2	3.6	257.1	10.1	2587.5	115.0	2702.5
1267.0	6.2	4.4	318.1	10.9	3468.5	118.0	3586.5
1268.0	7.2	5.1	382.7	11.7	4466.1	120.0	4586.1


Say EL 1262.

← TOP/DAM 1267.2


**APPENDIX E**

**PLATES**


DRAWN BY ACS 12-2-80 CHECKED BY S-1-81 DRAWING 80-556-B30 APPROVED BY S-1-81 NUMBER



KEY PLAN




REFERENCE:  
 U. S. G. S. SPRINGVILLE, PA. QUADRANGLE  
 PHOTOREVISED 1969, SCALE 1:24000



12



DRAWN BY	ACS	CHECKED BY	BE	DRAWING NUMBER	80-556-B31
BY	4-30-81	APPROVED BY	STP	5-1-81	



**LEGEND**

○ Debris Trap

≡≡≡ Stream Crossing




THIS PAGE IS OF POOR QUALITY PRACTICALLY FROM COPY FURNISHED TO DDC

**CONSTRUCTION NOTE**

- Locations of stream crossings and debris traps are approximate. Final locations to be determined by the Engineer. Details see Sheet 5.

**AS BUILT PLANS**




**SPRINGVILLE FLOOD PREVENTION PROJECT**  
 FLOODWATER RETARDING DAM PA-RC 8 D-108  
 SUSQUEHANNA COUNTY, PENNSYLVANIA  
 PLAN OF STORAGE AREA  
 U. S. DEPARTMENT OF AGRICULTURE  
 SOIL CONSERVATION SERVICE  
 S. B. DUNN 6-73  
 PA-RC 8 D-108-2


PLATE 2

**D'APPOLONIA**

1 2

DRAWN BY JCS  
 CHECKED BY BE  
 APPROVED BY JHC  
 5-7-87  
 5 1 81  
 DRAWING NUMBER 80-556-832






Diversion  
Final line & grade to  
be determined by the  
Engineer

Rock Lined Waterway  
Length = 590' approx  
Details sh. 5

**CONSTRUCTION NOTES**

- 1 Existing fences within constr. or work area limits & in permanent pool to be removed as directed by the Engineer
- 2 Ingress & egress road to be constructed and maintained by the contractor
- 3 All structure areas to be cleared & grubbed
- 4 Class of clearing in spoil areas to be determined by the Engineer



**E DAM LAYOUT**  
NOT TO SCALE

**EM SW CURVE DATA**  
 I = 90°  
 R = 40'  
 E = 16.57'  
 M = 11.72'  
 C = 56.57'  
 L = 62.83'  
 T = 40.00'  
 PC = 3+37.18  
 PT = 4+00.00


**AS BUILT PLANS**

30 15 0 30  
SCALE IN FEET

**SPRINGVILLE FLOOD PREVENTION PROJECT**  
 FLOODWATER RETARDING DAM PA-RC&D-105  
 SUSQUEHANNA COUNTY, PENNSYLVANIA  
**PLAN OF STRUCTURAL WORKS**  
 U. S. DEPARTMENT OF AGRICULTURE  
 SOIL CONSERVATION SERVICE  
 CRISE 6-73  
 PA-RC&D-105-P

12

DRAWN BY ACS CHECKED BY BE DRAWING NUMBER 80-556-B33  
 BY A.S.P. APPROVED BY JHP NUMBER 5 1-91




ZONE	MATERIAL	MAX ROCK SIZE	MAX LIFT	REQ'D WATER CONTENT	COMPACTION	
					CLASS	DEFINITION
I	Material as represented by TP-201, depth 3' - 6', classified as SM, SC, TP-204, depth 6' - 10', classified as SM	6"	9'	± 2% of optimum	A	95% max density by ASTM, D-698, Method C


⊥ Max permissible lift thickness before compaction


TYPICAL SECTION OF DAM  
 SCALE IN FEET  
 0 5 10 20

COMPACTION CURVE



COMPACTION CURVE






TYPICAL SECTION OF DAM



CONSTRUCTION NOTES

- 1 Constructed Slopes are 2:90 1 upstream and downstream
- 2 For constructed fill elevations see sheet 6.

COMPACTION CURVE




AS BUILT PLANS


SPRINGVILLE FLOOD PREVENTION PROJECT  
 FLOODWATER RETARDING DAM PA-RC B D-105  
 SUSQUEHANNA COUNTY, PENNSYLVANIA  
 FILL PLACEMENT  
 U.S. DEPARTMENT OF AGRICULTURE  
 SOIL CONSERVATION SERVICE  
 S B Dunn 7-73  
 PA-RC B D-105-P

12


DRAWN BY: ACS  
 CHECKED BY: JFC  
 APPROVED BY: JFC  
 DATE: 4-20-87  
 DRAWING NUMBER: 80-556-B34




PROFILE ALONG E



PLAN VIEW  
 SCALE IN FEET



THIS PAGE IS BEST QUALITY PRACTICALLY  
 FROM COPY FURNISHED TO DDC



TYPICAL SECTION

CONSTRUCTION NOTES

1. E. Dam = E. Cutoff Trench
2. For logs of test holes see sheets 27 & 28.

**AS BUILT PLANS**

<b>SPRINGVILLE FLOOD PREVENTION PROJECT</b> FLOODWATER RETARDING DAM PA-RC-0-105 SUSQUEHANNA COUNTY, PENNSYLVANIA <b>CUTOFF TRENCH</b>	
11 S. DEPARTMENT OF AGRICULTURE SOIL CONSERVATION SERVICE	
Date: 8/75 Drawn: CR 54 Project:	Scale: 1" = 20' Title:

PLATE 5

**D'APPOLONIA**

1 2

DRAWING NUMBER 80-556-B35


CHECKED BY JCF


APPROVED BY JJK

DATE 4-30-81


SCALE 1" = 30'

DRAWN BY





PROFILE ALONG & DRAIN TRENCH



PLAN VIEW  
SCALE IN FEET  
0 10 20 40

THIS CASE IS BEST QUALITY PRACTICABLE  
FROM COPY FURNISHED TO DDC

**AS BUILT PLANS**



<b>SPRINGVILLE FLOOD PREVENTION PROJECT</b> FLOODWATER RETARDING DAM PA-800-105 SUSQUEHANNA COUNTY, PENNSYLVANIA <b>DRAINAGE (PLAN - PROFILE)</b>	
<b>U. S. DEPARTMENT OF AGRICULTURE</b> <b>SOIL CONSERVATION SERVICE</b>	
Designer: <i>H. W. Hall</i> Check: <b>W.L. POOLE JR.</b> Date: 2-75	Approved by: _____ Title: _____ Date: 3-75 Drawn: <i>John R. ...</i> Date: 4-75

PLATE 6

**D'APPOLONIA**

12

DRAWN BY ACS  
 CHECKED BY JAC  
 APPROVED BY JAC  
 DRAWING NUMBER 80-556-B36





Field Book  
 (As Built)  
 PIPE JOINT DATA

JOINT	DIST FROM RISER WALL	INVERT EL.
1	0.0'	1295.40
2	2.7'	1293.27
3	4.6'	1292.38
4	6.7'	1291.19
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		

(As Built)  
 ANTI-SEEP COLLAR DATA

COLLAR	DIST FROM RISER WALL	INVERT EL.
1	2.7'	1293.27
2	4.6'	1292.38
3	6.7'	1291.19
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		

18" ID Reinforced Concrete Pressure Pipe  
 Steel Cylinder Type, Spec 541 (AWWA  
 C-300 or C-301)  
 20' - Straight Sections  
 1 - Ball & Flange Wall Fitting (for 10" dia)  
 20' - Total



THIS PAGE IS JUST QUALITY PRACTICE  
 FROM THE FUTURE OF THE PAST

**CONSTRUCTION NOTES**

1. Outlet end of 30" pipe and inlet end of 10" pipe to be finished so that no metal is exposed
2. Pipe layout data to be furnished by the Engineer
3. Riprap bedding shall meet gradation limits for fine drain fill. sht. 8
4. For logs of test holes see shts. 27 & 28
5. For excavation details see sht. 10

**AS BUILT PLANS**

108.33' - 30" ID Reinforced Concrete Pressure Pipe  
 Steel Cylinder Type, Spec 541 (AWWA C-300 or C-301)  
 108' - Straight Sections  
 1 - Ball & Flange Wall Fitting (for 10" wall)  
 108' - Total

30" ID. Reinforced Concrete Pressure Pipe  
 Steel Cylinder Type, Spec 541 (AWWA C-300 or C-301)  
 108' - Straight Sections  
 1 - Spigot Ring Wall Fitting (for 10" wall)  
 108.33' - Total

**SPRINGVILLE FLOOD PREVENTION PROJECT**  
 FLOODWATER RETARDING DAM PA-RC&D-105  
 SUSQUEHANNA COUNTY, PENNSYLVANIA  
**PRINCIPAL SPILLWAY**  
 U. S. DEPARTMENT OF AGRICULTURE  
 SOIL CONSERVATION SERVICE


Drawn: *M. A. Hall* Date: 5-15  
 Check: CRIBE 7-75  
 Scale: 1" = 10'-0"  
 Project No: 68-RC&D-105-2

PLATE 7


**D'APPOLONIA**

12




DRAWN BY ACS 4.31.81 CHECKED BY JTK 5-1-81 APPROVED BY JTK 5-1-81 DRAWING 80-556-B37



THIS PAGE IS BEST QUALITY PRACTICABLE FROM COPY FURNISHED TO DDC



PROFILE ALONG E. PRINCIPAL SPILLWAY



PRINCIPAL SPILLWAY SECTIONS  
As Directed by the Engineer



STATION	S-S
7+28 to 7+50	1 1
7+50 to 7+70	Transition
7+70 to 8+30	2 1
8+30 to 8+50	Transition
8+50 to 8+64	1 1

### AS BUILT PLANS

SPRINGVILLE FLOOD PREVENTION PROJECT  
 FLOODWATER RETARDING DAM PA-RC&D-105  
 SUSQUEHANNA COUNTY, PENNSYLVANIA  
 SPILLWAY EXCAVATION  
 U. S. DEPARTMENT OF AGRICULTURE  
 SOIL CONSERVATION SERVICE  
 CRISE 7-73  
 PA-RC & D-105-P

12

DRAWN BY ACS 4-30-51 CHECKED BY JBE 5-1-51 APPROVED BY JHR 5-1-51 DRAWING NO. 80-556-B38



1/4 x 6 Carbon  
 to conform to  
 Continuous The  
 Splices Shall  
 1 Butt Welded  
 2 Lapped 3"  
 3 Lapped 3"  
 4






PLATE CONSTR. J

CONSTR. J

STANDARD COVERED RISER	
DESIGN CONSTANTS	$f'_c = 4000$ psi $f'_s = 1600$ psi
	$n = 8$ $f_s = 20,000$ psi
STANDARD DIM. NO.	ES-3030-15E
DATE	7-65
SHEET	1 OF 4

Steel	Quantity	Unit	Length	Weight
#4 Bars	353-6	Lin. Ft.		205
#5 Bars	1000-9	Lin. Ft.		4301
#6 Bars	962-9	Lin. Ft.		623
#7 Bars	206-0	Lin. Ft.		600
				666
				65
				65
Length of #5 Bars = (1,887-9) + (Length of Bars 21, 23, 24, 25 and 26)				
Length of #6 Bars = (413-6) + (Length of Bar 22)				
Total Concrete = (20.33) + (0.721) =				21.05

DETAIL OF FLANGE WALL FITTING  
SEE SHEET 12



Spigot Wall Fitting

1/4 x 6 Carbon steel plate,  
to conform to Spec 581  
Continuous Thru Constr Joint  
Splices Shall Be Either:  
1 Bolted  
2 Lapped 3" And Bolted  
3 Lapped 3" And Fillet Welded




PLATE  
CONSTR JOINT


CONSTR. JOINT

STEEL SCHEDULE


Mark	Size	Quantity	Length	Type	B	C	Total Length
A1	#4	1	6-9				72-3
B1	#4	1	3-3				18-0
B3	#4	21	3-0	21	3-0	6-0	306-0
B4	#4	1	3-9				78-0
B5	#4	1	3-3				67-6
B6	#4	1	3-3				5-6
B7	#4	21	7-0	21	1-1	5-11	35-2
B8	#4	3	7-0	21	1-1	5-11	21-0
B9	#4	14	7-0	21	1-1	5-11	98-0
B10	#4	1	8-3				82-0
B11	#4	1	3-3				13-1
B12	#4	3	3-3				6-9
B13	#4	3	3-3				6-9
B14	#4	10	5-3	21	0-6	5-3	57-6
B15	#4	18	4-3	21	2-9	5-3	144-0
B16	#4	8	2-9	1			22-0
T1	#5	18	6-0	1			108-0
T2	#5	6	8-0	1			48-0
T3	#5	4	4-9	1			19-0
T4	#5	4	3-6	1			14-0
T5	#5	4	2-3	1			9-0
T6	#5	4	3-0	5	2-0	7-0	36-0
T7	#5	12	8-3	1			99-0
T8	#5	2	3-3	1			6-6
T9	#5	2	5-9	1			11-6
T10	#5	2	10-9	1			21-6
T11	#5	2	13-3	1			26-6
T12	#5	14	6-3	1			87-6
T13	#5	6	8-0	1			48-0
T14	#5	4	6-0	1			24-0
T15	#5	4	4-9	1			19-0
T16	#5	4	3-6	1			14-0
T17	#5	4	2-3	1			9-0
T18	#5	4	9-0	19	2-0	7-0	36-0
T19	#5	24	4-0	21	2-9	5-3	192-0
T20	#5	2	3-3	1			6-6
T21	#5	2	5-9	1			11-6
T22	#5	2	8-3	1			16-6
T23	#5	2	10-9	1			21-6
T24	#5	2	13-3	1			26-6
T25	#5	4	13-9	1			55-0
T26	#5	4	13-9	1			55-0
T27	#4	14	8-3	1			115-6
T28	#4	2	4-9	1			9-6
T29	#4	7	13-9	1			96-3
T30	#4	4	5-3	1			21-0
T31	#5	24	6-9	21	1-6	5-3	162-0
T32	#5	2	6-6	21	1-6	5-0	13-0
T33	#5	2	2-6	21	1-6	1-0	5-0
T34	#5	7	13-9	1			96-3
T35	#4	4	5-3	1			21-0

A1	#4	20	8-3	1			174-0
A2	#4	6	8-3	1			49-8
R1	#5	4	3-3	1			13-0
R4	#5	20	8-3	1			174-0
R5	#5	16	9-0	21	2-9	5-3	180-0
R6	#5	10	8-3	1			82-6
R7	#5	8	3-3	1			26-0
R8	#5	28	8-0	21	2-9	5-3	224-0

BAR TYPES



1. All dimensions are out to out of bar
2. Radius of bends equals 3 bar diameters for sizes equal to or less than #7.
3. The 2" and 3" dimensions from face of concrete to steel are clear distances.
4. Portland cement Type I or II with an air-retaining admixture shall be used.
5. All exposed edges of concrete to have a 1" chamfer, unless otherwise noted.



- 100 - CS
- 130 - L.D.
- 150 - L.D.S.
- 170 - CS
- 190 - CS
- 21, 23, A1, A5 and B16 (R2)
- 220 - C.D.

AS BUILT PLANS

SPRINGVILLE FLOOD PREVENTION PROJECT  
 FLOODWATER RETARDING DAM PA-RC&D-105  
 SUSQUEHANNA COUNTY, PENNSYLVANIA

RISER


U. S. DEPARTMENT OF AGRICULTURE  
 SOIL CONSERVATION SERVICE

ADOPTED BY: H. L. Hall Date: 8/13  
 AUTHORIZED BY: J. L. ... Date: 4-78

PA-RC & D-105-P

12

DRAWN BY: sh  
 12/31/80  
 CHECKED BY: BE  
 APPROVED BY: JRP  
 S-1-B  
 5-1-81  
 DRAWING NUMBER 80-556-A 33




NO COMMENTS

NOTE:  
 DAM CREST AT DATE OF INSPECTION  
 WATER LEVEL ~4" BELOW ORIFICE.

PLATE 10  
 PA-RC & D-105  
 GENERAL PLAN  
 FIELD INSPECTION NOTES  
 FIELD INSPECTION DATE: NOV. 13, 1980

**D'APPOLONIA**

DRAWN BY	MBM	CHECKED BY	DRAWING NUMBER
12-23-80	12-23-80	BC	80-556-A34
		APPROVED BY	
		STP	5-1-81



DATUM: PRIMARY SPILLWAY CREST EL. 1254.9

**DAM CREST PROFILE**  
(LOOKING DOWNSTREAM)

NOTES

1. DAM CREST WAS SURVEYED RELATIVE TO SPILLWAY CREST LEVEL
2. DATUM ELEVATION PER U.S.G.S. MAP

PLATE II

PA-RC& D-105  
DAM CREST SURVEY  
FIELD INSPECTION DATE: NOV. 13, 1980

**D'APPOLONIA**

APPENDIX F  
REGIONAL GEOLOGY

REGIONAL GEOLOGY  
PA-RC&D-105 DAM

The PA-RC&D-105 Dam is located in the glaciated low plateaus section of the Appalachian Plateau physiographic province, characterized as a mature glaciated plateau of moderate relief.

The geologic structure consists of a series of northeast trending folds (approximately N70°E) which plunge gently to the southwest. The dip of the limbs of the folds in the vicinity of the PA-RC&D-105 Dam is less than two degrees, with the southeast limb steeper than the northwest limb. The dam is located on the axis of the Wilmot Anticline. In general, the discontinuity trends are northeast and northwest.

The stratigraphy consists of glacial till which will range in thickness from very thin to approximately 200 feet. The glacial till is underlain by the Devonian Catskill Formation, which is approximately 1,800 feet thick in this area. The Catskill Formation is continental in origin, consisting of red shale, cross-bedded red and green sandstone and siltstone. The shale strata tend to weather rapidly when exposed.

DRAWING 80-556-A2  
 2-17-81  
 2-17-81  
 CHECKED BY JHP  
 APPROVED BY JHP  
 DRAWN BY ACS  
 1-2-81



GEOLOGY MAP

**REFERENCE:**  
 GEOLOGIC MAP OF PENNSYLVANIA PREPARED  
 BY COMMONWEALTH OF PENNA., DEPARTMENT OF  
 ENVIRONMENTAL RESOURCES, DATED: 1960  
 SCALE 1:250,000

**D'APPOLONIA**

DRAWING NUMBER 80-556-A4  
 2-17-81  
 2/17/81  
 CHECKED BY ACS  
 APPROVED BY JHG  
 1-2-81  
 DRAWN BY

**PENNSYLVANIAN**  
**APPALACHIAN PLATEAU**

 **Allegheny Group**  
*Cyclic sequences of sandstone, shale, limestone and coal, numerous commercial coals, limestones thicken westward; Vanport Limestone in lower part of section; includes Freeport, Kittanning, and Clarion Formations.*

 **Pottsville Group**  
*Predominantly sandstones and conglomerates with thin shales and coals; some coals mineable locally.*

**ANTHRACITE REGION**

 **Post-Pottsville Formations**  
*Brown or gray sandstones and shales with some conglomerate and numerous mineable coals.*

 **Pottsville Group**  
*Light gray to white, coarse grained sandstones and conglomerates with some mineable coal; includes Sharp Mountain, Schuylkill, and Tumbling Run Formations.*

**MISSISSIPPIAN**

 **Mauch Chunk Formation**  
*Red shales with brown to greenish gray flaggy sandstones, includes Greenbrier Limestone in Fayette, Westmoreland, and Somerset counties; Loyalhanna Limestone at the base in southwestern Pennsylvania.*

 **Pocono Group**  
*Predominantly gray, hard, massive, cross-bedded conglomerate and sandstone with some shale; includes in the Appalachian Plateau Burgoon, Shenango, Cusacko, Cussewago, Curry, and Koapp Formations; includes part of "Onaway" of M. L. Fuller in Potter and Tioga counties.*


**DEVONIAN**  
**UPPER**

**CENTRAL AND EASTERN PENNSYLVANIA**

 **Oswayo Formation**  
*Brownish and greenish gray, fine and medium grained sandstones with some shales and scattered calcareous lenses; includes red shales which become more numerous eastward. Relation to type Oswayo not proved.*

 **Catskill Formation**  
*Chiefly red to brownish shales and sandstones, includes gray and greenish sandstone tongues named Elk Mountain, Honesdale, Shohola, and Delaware River in the east.*

 **Marine beds**  
*Gray to olive brown shales, graywackes, and sandstones; contains "Chemung" beds and "Portage" beds including Hurket, Bralier, Harrell, and Trimmers Rock; Tully Limestone at base.*

 **Susquehanna Group**  
*Barbed line in "Chemung-Catskill" contact of Second Pennsylvania Survey County reports; barbs on "Chemung" side of line.*

**GEOLOGY MAP LEGEND**

**REFERENCE:**  
 GEOLOGIC MAP OF PENNSYLVANIA PREPARED BY COMMONWEALTH OF PENNA., DEPARTMENT OF ENVIRONMENTAL RESOURCES, DATED: 1980  
 SCALE 1 : 250,000

**D'APPOLONIA**

**DAT  
FILM**