

AD-A101 26

RIA-81-U459

TECHNICAL LIBRARY

AD *A101 268*

TECHNICAL REPORT ARLCB-TR-81022

A RATIONAL FUNCTION APPROXIMATION FOR THE INTEGRATION POINT IN EXPONENTIALLY WEIGHTED FINITE ELEMENT METHODS

J. E. Flaherty

June 1981



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
LARGE CALIBER WEAPON SYSTEMS LABORATORY
BENÉT WEAPONS LABORATORY
WATERVLIET, N. Y. 12189

AMCMS No. 611102H5710011

DA Project No. 1L161102BH57

PRON No. 1A1235821A1A

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The use of trade name(s) and/or manufacturer(s) does not constitute an official indorsement or approval.

DISPOSITION

Destroy this report when it is no longer needed. Do not return it to the originator.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ARLCB-TR-81022	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) A RATIONAL FUNCTION APPROXIMATION FOR THE INTEGRATION POINT IN EXPONENTIALLY WEIGHTED FINITE ELEMENT METHODS		5. TYPE OF REPORT & PERIOD COVERED
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Joseph E. Flaherty		8. CONTRACT OR GRANT NUMBER(s) Grant No. AFOSR 80-0192.
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Armament Research & Development Command Benet Weapons Laboratory, DRDAR-LCB-TL Watervliet, NY 12189		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS AMCMS No. 611102H5710011 DA Project No. 1L161102BH57 PRON No. 1A1235821A1A
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Armament Research & Development Command Large Caliber Weapon Systems Laboratory Dover, NJ 07801		12. REPORT DATE June 1981
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 18
		15. SECURITY CLASS. (of this report) UNCLASSIFIED 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES To be published in the International Journal for Numerical Methods in Engineering. This research was partially sponsored by the U.S. Air Force Office of Scientific Research, Air Force Systems Command, U.S.A.F. The U.S. (CONT'D ON REVERSE)		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Convection-Diffusion Problems Exponential-Weights Finite Element Method Rational Approximations		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A rational function is presented for approximating the function $f(z) = \coth z - 1/z$ that appears in several exponentially fitted or weighted finite difference and finite element methods for convection-diffusion problems. The approximation is less expensive to evaluate than $f(z)$ and provides greater accuracy than the doubly asymptotic approximation when $z = O(1)$.		

18. SUPPLEMENTARY NOTES (Cont'D)

Government is authorized to reproduce and distribute reprints not withstanding any copyright notation thereon.

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	1
RATIONAL FUNCTION APPROXIMATION	3
NUMERICAL RESULTS	9
CONCLUSIONS	16
REFERENCES	17

LIST OF ILLUSTRATIONS

1. Optimal, doubly asymptotic, rational, and critical choices of $\xi = f(z)$ given by equations (1), (6), (8), and $\xi = 1 - 1/z$, respectively.	4
2. Region of acceptable values of α and β (shaded) that satisfies equations (9) and (10).	8

TABLES

1. RELATIVE COMPUTER TIMES TO EVALUATE THE APPROXIMATIONS $f_A(z)$ AND $f_R(z)$ AND THE EXACT FUNCTION $f(z)$ FOR 1000 VALUES OF z ON $0 \leq z \leq 100$.	10
2. MAXIMUM ERRORS AT STEADY STATE FOR EXAMPLE 1.	10
3. MAXIMUM ERRORS AT STEADY STATE FOR EXAMPLE 2.	14
4. MAXIMUM ERRORS AT STEADY STATE FOR EXAMPLE 2 WITH $\epsilon = 1/128$. AN * DENOTES THAT $\lambda = 0.48$ FOR THIS CASE.	14
5. ERRORS AT $x = 0.875$ AND 0.9375 AT STEADY STATE FOR EXAMPLE 2 WITH $\epsilon = 1/128$. AN * DENOTES THAT $\lambda = 0.48$ FOR THIS CASE.	15

INTRODUCTION

Exponentially weighted Galerkin-finite element,^{2,5,6} collocation,⁴ and exponentially fitted finite difference^{1,5,7} schemes have become popular and effective numerical methods for solving convection dominated convection-diffusion problems. They avoid the spurious mesh oscillations found in centered schemes at high values of the cell Reynolds or Peclet numbers and reduce the effects of numerical diffusion found in upwind finite difference schemes.

The exponential schemes all require evaluating the function

$$\xi = f(z) := \coth z - 1/z$$

in order to obtain their optimal accuracy. For example, the exponentially fitted Galerkin-finite element method for the two-point boundary value problem

$$\varepsilon \frac{d^2 u}{dx^2} - c(x) \frac{du}{dx} = 0, \quad 0 < x < 1, \quad u(0) = A, \quad u(1) = B \quad (2)$$

on a uniform grid of spacing $h = 1/N$ is given by, (cf, e.g., Hughes⁶)

$$\begin{aligned} (\varepsilon/h^2)(U_{i-1} - 2U_i + U_{i+1}) - (1/2h)[(1+\xi_i)c(\bar{x}_i)(U_i - U_{i-1}) \\ + (1-\xi_i)c(\bar{x}_{i+1})(U_{i+1} - U_i)] = 0, \quad i = 1, 2, \dots, N-1 \end{aligned} \quad (3a)$$

$$U_0 = A, \quad U_N = B \quad (3b,c)$$

Here U_i denotes the numerical approximation of $u(ih)$, $i = 0, 1, \dots, N$, \bar{x}_i is some point on (x_{i-1}, x_i) , e.g., the center of the subinterval, and ξ_i can be

*References are listed at the end of this report.

interpreted as a function evaluation point in a one-point quadrature rule (cf. Hughes⁶). The choice

$$\xi_i = f(\rho_i/2) \quad (4)$$

where ρ_i is the cell Reynolds or Peclet number

$$\rho_i = c(\bar{x}_i)h/\epsilon \quad (5)$$

is known to give the exact solution of Eq. (2) for all ρ_i when c is a constant (cf. Christie et al.²).

The function $f(z)$ is relatively expensive to evaluate because of the exponential functions and is usually replaced by the "doubly asymptotic" approximation

$$\xi = f_A(z) := \begin{cases} z/3, & |z| < 3 \\ \text{sgn}(z), & |z| > 3 \end{cases} \quad (6)$$

The function $f_A(z)$ provides an $O(z^3)$ approximation to $f(z)$ when $|z| \ll 1$ and an $O(1/z)$ approximation when $|z| \gg 1$. Furthermore, when Eq. (6) is used in Eq. (3) and $c(x)$ is smooth, U_i provides an $O(\rho^4)$ approximation when

$$\rho := \max_{1 \leq i \leq N} |\rho_i| \quad (7)$$

is small and an $O(1/\rho)$ approximation when ρ is large.

Thus, $f_A(z)$ provides a good approximation of $f(z)$ when z is either small or large, but has large errors when $z = O(1)$ (cf. Figure 1). The largest difference between $f(z)$ and $f_A(z)$ is 0.328 and it occurs at $z = 3$. This corresponds to a value of $\rho = 6$ and since cell Reynolds numbers in this vicinity are reasonably common in computation it behooves us to find a better approximation for $f(z)$ than $f_A(z)$ when $z = O(1)$.

In this note, we consider rational function approximations having the form

$$\xi = f_R(z) := \frac{z(1 + \alpha|z|)}{3 + \beta|z| + \alpha z^2} \quad (8)$$

for appropriate choices of α and β . This approximation will be considered successful if it provides better accuracy than $f_A(z)$ and is still less expensive to evaluate than $f(z)$.

Like $f_A(z)$, we see that $f_R(z)$ correctly approximates $f(z)$ as $z \rightarrow 0$ and as $|z| \rightarrow \infty$ for all values of β and all $\alpha \neq 0$. The maximum difference between $f(z)$ and $f_R(z)$ is about 0.0115 for the nearly optimal values of $\alpha = 0.6$ and $\beta = 1.38$ (cf. Figure 1). Furthermore, when f , f_A , and f_R were evaluated for 1000 values of $z \in [0,100]$ we found that f_R took 35 percent less time to evaluate than f while f_A took 49 percent less time than f . The approximation f_R also provided greater accuracy than f_A for the computed solution U_i , $i = 0,1,\dots,N$, of two model problems. The savings in time and improvement in accuracy are significant and may be especially important in multi-dimensional problems. As previously noted, the greatest gains occur when $\rho_1 = O(1)$ and $c(x)$ is smooth.

RATIONAL FUNCTION APPROXIMATION

We will want to restrict α and β in Eq. (8) so that our approximation $f_R(z)$ satisfies the following three conditions:

- i. $f_R(z)$ should be a good approximation of $f(z)$ when z is small and large, although not necessarily as good as $f_A(z)$.




Figure 1. Optimal, doubly asymptotic, rational, and critical choices of $\xi = f(z)$ given by equations (1), (6), (8), and $\xi = 1 - 1/z$, respectively.

ii. The solution U_i of Eq. (3) should be oscillation free. Christie et al.² have shown that this will be the case when

$$\begin{aligned} z > 0 & , \quad \xi > 1 - 1/z \\ z < 0 & , \quad \xi < -(1 - 1/z) \\ z = 0 & , \quad \text{all } \xi \end{aligned} \quad (9)$$

iii. Since $f(z)$ is a monotonically increasing function of z we ask that

$$\frac{df_R(z)}{dz} > 0 \quad , \quad \text{all } z \quad (10)$$

Since both $f(z)$ and $f_R(z)$ are odd functions of z it suffices to enforce these conditions for $z \geq 0$. We shall see that enough flexibility remains for us to select α and β to improve accuracy when $z = O(1)$.

The functions $f(z)$ and $f_R(z)$ have the following asymptotic behavior for small and large values of z :

$$\frac{z}{3} - \frac{z^3}{45} + \frac{2z^5}{945} + O(z^7) \quad , \quad z \ll 1 \quad (11a)$$

$$f(z) = \begin{aligned} & 1 - \frac{1}{z} + O(e^{-2z}) \quad , \quad z \gg 1 \end{aligned} \quad (11b)$$

$$\frac{z}{3} \left[1 + \left(\alpha - \frac{1}{3}\beta \right) z + \frac{1}{3} \left(-\beta^2 - \alpha\beta - \alpha \right) z^2 + O(z^3) \right] \quad , \quad z \ll 1 \quad (12a)$$

$$f_R(z) = 1 - \frac{\beta-1}{\alpha z} + \frac{\beta^2-\beta-3\alpha}{\alpha^2 z^2} + O\left(\frac{1}{z^3}\right) \quad , \quad z \gg 1 \quad , \quad \alpha \neq 0 \quad (12b)$$

$$\frac{1}{\beta} \left[1 - \frac{3}{\beta z} + \frac{9}{\beta^2 z^2} + O\left(\frac{1}{z^3}\right) \right] \quad , \quad z \gg 1 \quad , \quad \alpha = 0 \quad , \quad \beta \neq 0 \quad (12c)$$

Equation (12c) only gives the correct limiting value of $f(z)$ as $z \rightarrow \infty$ when $\beta = 1$ and this value of β does not satisfy Eq. (9); hence, we will no longer consider approximations with $\alpha = 0$.

Let

$$e(z) := f_R(z) - f(z) \quad (13)$$

denote the pointwise error and use Eqs. (11) and (12) to obtain

$$e(z) = \left(\alpha - \frac{1}{3}\beta \right) \frac{z^2}{3} + \left(\frac{1}{3}\beta^2 - \alpha\beta - \alpha + \frac{1}{5} \right) \frac{z^3}{9} + O(z^4) \quad , \quad z \ll 1$$

$$\left(1 - \frac{\beta-1}{\alpha} \right) \frac{1}{z} + \frac{\beta^2 - \beta - 3\alpha}{\alpha^2 z^2} + O\left(\frac{1}{z^3}\right) \quad , \quad z \gg 1 \quad (14)$$

We see that the rate of convergence as $z \rightarrow 0$ can be improved from $O(z^2)$ to $O(z^3)$ by selecting

$$\beta = 3\alpha \quad (15)$$

while the rate of convergence as $z \rightarrow \infty$ can be improved from $O(1/z)$ to $O(1/z^2)$ by selecting

$$\beta = 1 + \alpha \quad (16)$$

Both Eqs. (15) and (16) can be satisfied simultaneously by selecting $\alpha = 1/2$ and $\beta = 3/2$.

Before deciding on either or both of Eqs. (15) and (16) we still must find bounds on α and β so that Eqs. (9) and (10) are satisfied. It is slightly simpler to consider Eq. (10) first; thus, we differentiate Eq. (8) to obtain

$$\frac{df_R}{dz} = \frac{3 + 6\alpha z + \alpha z^2(\beta-1)}{(3+\beta z+\alpha z^2)^2} \quad , \quad z > 0 \quad (17)$$

For $df_R/dz > 0$, the polynomial

$$p(z) = 3 + 6\alpha z + \alpha z^2(\beta-1) \quad (18)$$

should not have any positive roots. It will have two negative roots if $\alpha > 0$ and $\beta > 1$ and two complex roots if $\alpha > 0$ and $\beta > 1+3\alpha$ or $\alpha < 0$ and $\beta < 1+3\alpha$. For the reasons of accuracy expressed by Eqs. (15) and (16) we would like to be as close to $\alpha = 1/2$ and $\beta = 3/2$ as possible. Hence, we will not consider the region where $\alpha < 0$ and confine our attention to choices satisfying $\alpha > 0$ and $\beta > 1$.

Finally using Eq. (8), condition (9) will be satisfied if

$$f_R(z) - \left(1 - \frac{1}{z}\right) = \frac{3 + (\beta-3)z + (1+\alpha-\beta)z^2}{z^2(3+\beta z+\alpha z^2)} > 0, \quad z > 0 \quad (19)$$

Since α and β are positive we want the polynomial

$$p(z) = 3 + (\beta-3)z + (1+\alpha-\beta)z^2 \quad (20)$$

to have no positive roots. $p(z)$ will have two negative roots if $3 < \beta < 1+\alpha$ and two complex roots if

$$\beta < -3 + 2\sqrt{3(1+\alpha)} \quad (21)$$

The values of α and β that satisfy both Eqs. (9) and (10) are

$$\begin{aligned} \frac{1}{3} < \alpha < 3, \quad 1 < \beta < -3 + 2\sqrt{3(1+\alpha)} \\ \alpha > 3, \quad 1 < \beta < 1+\alpha \end{aligned} \quad (22)$$

This region is shown shaded in Figure 2. Note that the point $\alpha = 1/2, \beta = 3/2$, which improves accuracy for small and large values of z , fails to satisfy condition (10). However, Figure 2 suggests that an effective alternative might be to pick the point on the curve $\beta = -3 + 2\sqrt{3(1+\alpha)}$ that is closest to $\alpha = 1/2, \beta = 3/2$. This point is $\alpha = 0.5931, \beta = 1.3723$ and a search shows that it is near the point which minimizes the maximum value of $|e(z)|$, for all z .




Figure 2. Region of acceptable values of α and β (shaded) that satisfies equations (9) and (10).

In the examples of the next section we used $\alpha = 0.6$ and $\beta = 1.38$ for which the maximum value of $|e(z)|$ is 0.0115.

NUMERICAL RESULTS

The approximations $f_A(z)$ and $f_R(z)$ and the exact function $f(z)$ given by Eqs. (6), (8), and (1), respectively, were coded in FORTRAN and used in the series of numerical experiments described below.

Equation (1) cannot be used for $f(z)$ when z is near zero and it was replaced by the expansion (11a) for $|z| \leq 0.01$. The FORTRAN Library function for $\tanh(z)$ was used in Eq. (1) when z was not small. All calculations were performed in double precision arithmetic on either an IBM 3033 at the Rensselaer Polytechnic Institute or an IBM 4341 at the Benet Weapons Laboratory.

In our first experiment, we evaluated $f(z)$, $f_A(z)$, and $f_R(z)$ for 1000 values of $z \in [0,100]$ and timed the results. The normalized times recorded in Table 1 were averaged over several runs and include only the times to evaluate the functions and neither input/output nor supervisor state times. Variations in times from run to run were less than two percent. The results indicate that f_R took 35 percent and f_A took 49 percent less time to evaluate than f . The relative timing figures can be expected to vary significantly from computer to computer and even from compiler to compiler; however, the differences between the times to evaluate f_R and f are large enough so that savings should be achieved in most environments.

TABLE 1. RELATIVE COMPUTER TIMES TO EVALUATE THE APPROXIMATIONS $f_A(z)$ AND $f_R(z)$ AND THE EXACT FUNCTION $f(z)$ FOR 1000 VALUES OF z ON $0 \leq z \leq 100$.

Method	Time
Doubly Asymptotic Approximation, Eq. (6)	0.508
Rational Approximation, Eq. (8)	0.654
Exact, Eqs. (1), (11a)	1.000

TABLE 2. MAXIMUM ERRORS AT STEADY STATE FOR EXAMPLE 1.

ρ	λ	Doubly Asymptotic	Lax Wendroff	Rational	Optimal
6	0.75	0.204×10^{-1}	0.159×10^{-2}	0.866×10^{-3}	0.250×10^{-13}
500	0.95	0.200×10^{-2}	0.235×10^{-1}	0.705×10^{-3}	0.208×10^{-11}

In order to study variations in the computed solutions when the different approximations of $f(z)$ are used we consider two boundary value problems having the form

$$\epsilon \frac{d^2 u}{dx^2} - \frac{dF(u)}{dx} = 0, \quad 0 < x < 1, \quad u(0) = A, \quad u(1) = 0 \quad (23)$$

Since our motivation for performing the work described in this note is to study exponentially weighted finite element schemes for transient problems³ we do not use the numerical method (3) but rather, we follow Osher⁸ and consider the solution of (23) as the steady state limit of the following initial-boundary value problem

$$\frac{\partial u}{\partial t} + \frac{\partial F(u)}{\partial x} = \epsilon \frac{\partial^2 u}{\partial x^2}, \quad 0 < x < 1, \quad t > 0 \quad (24a)$$

$$u(0,t) = A, \quad u(1,t) = 0, \quad u(x,0) = \begin{cases} A, & x = 0 \\ 0, & 0 < x < 1 \end{cases} \quad (24b,c,d)$$

Equations (24) are approximated by the following explicit difference scheme

$$U_i^{n+1} = U_i^n - \lambda [(1+\xi_i)(F_i^n - F_{i-1}^n) + (1-\xi_i)(F_{i+1}^n - F_i^n) + (\epsilon\lambda/h)(U_{i-1}^n - 2U_i^n + U_{i+1}^n)], \quad i = 1, 2, \dots, N-1 \quad (25a)$$

$$U_0^n = A, \quad U_N^n = 0, \quad U_i^0 = \begin{cases} 1, & i = 0 \\ 0, & i = 1, 2, \dots, N \end{cases} \quad (25b,c,d)$$

where U_i^n denotes the numerical approximation of $u(ih, n\Delta t)$, Δt is the time step, and

$$\lambda = \Delta t/h \quad (26)$$

The cell Reynolds number is still given by Eq. (5) with c defined as

$$c(x,t) = \frac{dF(u(x,t))}{du} \quad (27a)$$

and

$$x_i \quad , \quad U_{i-1}^n + U_i^n < 0$$

$$\bar{x}_i = (x_{i-1} + x_i)/2 \quad , \quad U_{i-1}^n + U_i^n = 0 \quad (27b)$$

$$x_{i-1} \quad , \quad (U_{i-1}^n + U_i^n) > 0$$

For reasons discussed in Flaherty and Mathon⁴ these choices of \bar{x}_i might be better than always using the center of the subinterval (x_{i-1}, x_i) .

The explicit difference scheme will be stable to linear perturbations provided that (cf. Osher⁸ or Flaherty³)

$$\lambda[c(\bar{x}_i, n\Delta t) + 2\epsilon/h] < 1 \quad , \quad i = 1, 2, \dots, N, \quad n > 0 \quad (28)$$

We use

$$E := \max_{1 \leq i \leq N} |u(ih, n\Delta t) - U_i^n| \quad (29)$$

with n chosen large enough so that steady state has been reached, to measure errors.

Example 1: Consider the constant coefficient problem for Eq. (23) with $F(u) = u$, $c = 1$, $A = 1$, which has the exact solution

$$u(x) = \frac{1 - e^{-(1-x)/\epsilon}}{1 - e^{-1/\epsilon}} \quad (30)$$

The results of calculations when ξ_1 in Eq. (25) was evaluated by the doubly asymptotic approximation (6), the rational approximation (8), the Lax-Wendroff scheme ($\xi_1 = \lambda$), and the optimal scheme (1) are presented in Table 2 for $N = 20$, $\rho = 6$, $\lambda = 0.75$, and $N = 20$, $\rho = 500$, $\lambda = 0.95$. The optimal scheme (1) is exact for this example. The small errors reported in Table 2 are due to the combined effects of roundoff and our failure to reach the steady state limit. As expected the rational approximation improves upon the results of the doubly asymptotic approximation and the improvement is greatest for $\rho = 6$. The Lax-Wendroff solution oscillates when x is near unity.

Example 2. We consider the nonlinear Burgers' equation, $F(u) = u^2/2$
 $c = u$, $A = \tanh 1/2\epsilon$, for which the exact solution of Eq. (23) is

$$u(x) = \tanh(1-x)/2\epsilon \quad (31)$$

Results comparing the doubly asymptotic, rational, and optimal choices of ξ_1 are shown in Table 3 for $N = 20$, $\rho = h/\epsilon = 6$, $\lambda = 0.75$, and $N = 20$, $\rho = 500$, $\lambda = 0.95$, and in Table 4 for $\epsilon = 1/128$, $\rho = 1, 2, 4, 8, 16$. In Table 5 we show results for the error $|U_1^n - u(1h, n\Delta t)|$ at steady state and $x = 1h = 0.875$, 0.9375 for $\epsilon = 1/128$ and $\rho = 1, 2, 4, 8, 16$. The solution obtained using the doubly asymptotic approximation had mesh oscillations for $\rho = 8$ and $\lambda = 0.96$ so this calculation was rerun with $\lambda = 0.48$.

Although accuracy is not as good for this nonlinear example, the results generally parallel our findings for the linear problem. Table 5 shows that the rational and optimal choices of ξ_1 are better than the doubly asymptotic choice at reducing the effects of numerical diffusion for cell Reynolds numbers in the range of 2 to 16.

TABLE 3. MAXIMUM ERRORS AT STEADY STATE FOR EXAMPLE 2.

ρ	λ	Doubly Asymptotic	Rational	Optimal
6	0.75	0.124	0.761×10^{-1}	0.766×10^{-1}
500	0.95	0.200×10^{-2}	0.135×10^{-2}	0.100×10^{-2}

TABLE 4. MAXIMUM ERRORS AT STEADY STATE FOR EXAMPLE 2 WITH $\varepsilon = 1/128$.

AN * DENOTES THAT $\lambda = 0.48$ FOR THIS CASE.

ρ	λ	Doubly Asymptotic	Rational	Optimal
16	0.96	0.605×10^{-1}	0.330×10^{-1}	0.308×10^{-1}
8	0.96	0.117*	0.599×10^{-1}	0.601×10^{-1}
4	0.96	0.110	0.940×10^{-1}	0.932×10^{-1}
2	0.6912	0.627×10^{-1}	0.627×10^{-1}	0.618×10^{-1}
1	0.4608	0.156×10^{-1}	0.157×10^{-1}	0.156×10^{-1}

TABLE 5. ERRORS AT $x = 0.875$ AND 0.9375 AT STEADY STATE FOR EXAMPLE 2 WITH $\epsilon = 1/128$.

AN * DENOTES THAT $\lambda = 0.48$ FOR THIS CASE.

		$x = 0.875$			$x = 0.9375$		
ρ	λ	Doubly Asymptotic	Rational	Optimal	Doubly Asymptotic	Rational	Optimal
16	0.96	0.605×10^{-1}	0.330×10^{-1}	0.308×10^{-1}			
8	0.96	0.131×10^{-1} *	0.244×10^{-3}	0.249×10^{-3}	0.117	0.599×10^{-1}	0.601×10^{-1}
4	0.96	0.741×10^{-4}	0.142×10^{-3}	0.122×10^{-5}	0.118×10^{-1}	0.366×10^{-2}	0.351×10^{-2}
2	0.6912	0.273×10^{-6}	0.182×10^{-6}	0.125×10^{-6}	0.523×10^{-3}	0.438×10^{-3}	0.372×10^{-3}
1	0.4608	0.288×10^{-7}	0.340×10^{-7}	0.238×10^{-7}	0.769×10^{-4}	0.835×10^{-4}	0.709×10^{-4}

CONCLUSION

We have shown that the rational function approximation (8) is an alternative to the doubly asymptotic approximation (6) of $f(z)$ that offers greater accuracy for about a 30 percent increase in cost. The approximation is most useful for cell Reynolds numbers in the range of one to ten.

REFERENCES

1. A. E. Berger, J. M. Solomon, and M. Ciment, "Uniformly Accurate Difference Methods for a Singular Perturbation Problem," in J. J. H. Miller (Ed.), *Boundary and Interior Layers - Computational and Asymptotic Methods*, Boole Press, Dublin, 1980.
2. I. Christie, D. F. Griffiths, A. R. Mitchell, and O. C. Zienkiewicz, "Finite Element Methods for Second Order Differential Equations With Significant First Derivatives," *Int. J. Num. Meth. Engng.*, 10, 1389-1396 (1976).
3. J. E. Flaherty, "Explicit Difference Schemes for Wave Propagation and Impact Problems," to appear in *Trans. Twenty-Seventh Conference of Army Mathematicians*, 1981.
4. J. E. Flaherty and W. Mathon, "Collocation With Polynomial and Tension Splines for Singularly Perturbed Boundary Value Problems," *SIAM J. Sci., Stat. Comput.*, 1, 260-289, (1980).
5. P. W. Hemker, "A Numerical Study of Stiff Two-Point Boundary Problems;" Ph.D. dissertation, Mathematisch Centrum, Amsterdam, 1977.
6. T. J. R. Hughes, "A Simple Scheme For Developing Upwind Finite Elements," *Int. J. Num. Meth. Engng.*, 12, 1359-1365, (1978).
7. A. M. Il'in, "Differencing Scheme For a Differential Equation With a Small Parameter Affecting the Highest Derivative," *Math. Notes Acad. Sci., USSR*, 6, 569-602 (1969).
8. S. Osher, "Nonlinear Singular Perturbation Problems and One Sided Difference Schemes," to appear.

TECHNICAL REPORT INTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>
COMMANDER	1
CHIEF, DEVELOPMENT ENGINEERING BRANCH	1
ATTN: DRDAR-LCB-DA	1
-DM	1
-DP	1
-DR	1
-DS	1
-DC	1
CHIEF, ENGINEERING SUPPORT BRANCH	1
ATTN: DRDAR-LCB-SE	1
-SA	1
CHIEF, RESEARCH BRANCH	2
ATTN: DRDAR-LCB-RA	1
-RC	1
-RM	1
-RP	1
CHIEF, LMC MORTAR SYS. OFC.	1
ATTN: DRDAR-LCB-M	
CHIEF, IMP. 81MM MORTAR OFC.	1
ATTN: DRDAR-LCB-I	
TECHNICAL LIBRARY	5
ATTN: DRDAR-LCB-TL	
TECHNICAL PUBLICATIONS & EDITING UNIT	2
ATTN: DRDAR-LCB-TL	
DIRECTOR, OPERATIONS DIRECTORATE	1
DIRECTOR, PROCUREMENT DIRECTORATE	1
DIRECTOR, PRODUCT ASSURANCE DIRECTORATE	1

NOTE: PLEASE NOTIFY ASSOC. DIRECTOR, BENET WEAPONS LABORATORY, ATTN:
DRDAR-LCB-TL, OF ANY REQUIRED CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST (CONT)

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
COMMANDER US ARMY RESEARCH OFFICE. P.O. BOX 12211 RESEARCH TRIANGLE PARK, NC 27709	1	COMMANDER DEFENSE TECHNICAL INFO CENTER ATTN: DTIA-TCA CAMERON STATION ALEXANDRIA, VA 22314	12
COMMANDER US ARMY HARRY DIAMOND LAB ATTN: TECH LIB 2800 POWDER MILL ROAD ADELPHIA, ME 20783	1	METALS & CERAMICS INFO CEN BATTELLE COLUMBUS LAB 505 KING AVE COLUMBUS, OHIO 43201	1
DIRECTOR US ARMY INDUSTRIAL BASE ENG ACT ATTN: DRXPE-MT ROCK ISLAND, IL 61201	1	MECHANICAL PROPERTIES DATA CTR BATTELLE COLUMBUS LAB 505 KING AVE COLUMBUS, OHIO 43201	1
CHIEF, MATERIALS BRANCH US ARMY R&S GROUP, EUR BOX 65, FPO N.Y. 09510	1	MATERIEL SYSTEMS ANALYSIS ACTV ATTN: DRXSY-MP ABERDEEN PROVING GROUND MARYLAND 21005	1
COMMANDER NAVAL SURFACE WEAPONS CEN ATTN: CHIEF, MAT SCIENCE DIV DAHLGREN, VA 22448	1		
DIRECTOR US NAVAL RESEARCH LAB ATTN: DIR, MECH DIV CODE 26-27 (DOC LIB) WASHINGTON, D. C. 20375	1 1		
NASA SCIENTIFIC & TECH INFO FAC. P. O. BOX 3757, ATTN: ACQ BR BALTIMORE/WASHINGTON INTL AIRPORT MARYLAND 21240	1		

NOTE: PLEASE NOTIFY COMMANDER, ARRADCOM, ATTN: BENET WEAPONS LABORATORY, DRDAF-LCB-TL, WATERVLIET ARSENAL, WATERVLIET, N.Y. 12189, OF ANY REQUIRED CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
ASST SEC OF THE ARMY RESEARCH & DEVELOPMENT ATTN: DEP FOR SCI & TECH THE PENTAGON WASHINGTON, D.C. 20315	1	COMMANDER US ARMY TANK-AUTMV R&D COMD ATTN: TECH LIB - DRDTA-UL MAT LAB - DRDTA-RK WARREN, MICHIGAN 48090	1 I
COMMANDER US ARMY MAT DEV & READ. COMD ATTN: DRCDE 5001 EISENHOWER AVE ALEXANDRIA, VA 22333	1	COMMANDER US MILITARY ACADEMY ATTN: CHMN, MECH ENGR DEPT WEST POINT, NY 10996	I
COMMANDER US ARMY ARRADCOM ATTN: DRDAR-LC -LCA (PLASTICS TECH EVAL CEN) -LCE -LCM -LCS -LCW -TSS (STINFO) DOVER, NJ 07801	I 1 I 1 1 1 2	US ARMY MISSILE COMD REDSTONE SCIENTIFIC INFO CEN ATTN: DOCUMENTS SECT, BLDG 4484 REDSTONE ARSENAL, AL 35898 COMMANDER REDSTONE ARSENAL ATTN: DRSMI-RRS -RSM ALABAMA 35809	2 I I
COMMANDER US ARMY ARRCOM ATTN: DRSAR-LEP-L ROCK ISLAND ARSENAL ROCK ISLAND, IL 61299	I	COMMANDER ROCK ISLAND ARSENAL ATTN: SARRI-ENM (MAT SCI DIV) ROCK ISLAND, IL 61202	I
DIRECTOR US ARMY BALLISTIC RESEARCH LABORATORY ATTN: DRDAR-TSB-S (STINFO) ABERDEEN PROVING GROUND, MD 21005	1	COMMANDER HQ, US ARMY AVN SCH ATTN: OFC OF THE LIBRARIAN FT RUCKER, ALABAMA 36362	1
COMMANDER US ARMY ELECTRONICS COMD ATTN: TECH LIB FT MONMOUTH, NJ 07703	I	COMMANDER US ARMY FGN SCIENCE & TECH CEN ATTN: DRXST-SD 220 7TH STREET, N.E. CHARLOTTESVILLE, VA 22901	I
COMMANDER US ARMY MOBILITY EQUIP R&D COMD ATTN: TECH LIB FT BELVOIR, VA 22060	1	COMMANDER US ARMY MATERIALS & MECHANICS RESEARCH CENTER ATTN: TECH LIB - DRXMR-PL WATERTOWN, MASS 02172	2

NOTE: PLEASE NOTIFY COMMANDER, ARRADCOM, ATTN: BENET WEAPONS LABORATORY, DRDAR-LCB-TL, WATERVLIET ARSENAL, WATERVLIET, N.Y. 12189, OF ANY REQUIRED CHANGES.