

Technical Report 490

LEVEL II C

AD A101475

THE FILE COPY

F,'

SIMULATOR FIDELITY: A CONCEPT PAPER

Robert T. Hays

SIMULATION SYSTEMS TECHNICAL AREA





U. S. Army

Research Institute for the Behavioral and Social Sciences

November 1980

Approved for public release; distribution unlimited.

81 7

16

- Mr. Blind & Hickory

and the second of

U. S. ARMY RESEARCH INSTITUTE FOR THE BEHAVIORAL AND SOCIAL SCIENCES

2

A Field Operating Agency under the Jurisdiction of the Deputy Chief of Staff for Personnel

	FRANKLIN A. HART
JOSEPH ZEIDNER	Colonel, US Army
Technical Director	Commander

NOTICES

DISTRIBUTION Primary distribution of this report has been made by ARI. Please address correspondence concerning distribution of reports to U.S. Army Research Institute for the Bishavioral and Social Sciences, ATTN: PERI-TP, 5001 Eisenhover Avenue, Alexandria, Virginia 22333.

FINAL DISPOSITION: This report may be destroyed when it is no longer readed. Please do not return it to the U.S. Army Research Institute for the Behavioral and Social Sciences.

NOTE. The findings in this report are not to be construed as an official Department of the Army position, unless to designated by other authorized documents.

DEDADT DACHMENTAT		READ INSTRUCTIONS
REFORT DUCUMENTAT	IUN FAUE	BEFORE COMPLETING FORM
Technical ten St. 190	AN - 441	1-47-
TTT: E fond debuties	VID AL	5. TYPE OF REPORT & PERIOD COVERED
SIMULATOR FIDELITY: A CONCEPT	PAPER.	
	5	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(a)		B. CONTRACT OR GRANT NUMBER(+)
Dohowh m Nour		- 12 42
inducter tryindys		(14) 307
U.S. Army Research Institute (mess for the Behavioral	10. PROGRAM ELEMENT, PROJECT, TASK
and Social Sciences (PERI-OL	J)	(16)
5001 Eisenhower Avenue, Alexar	ndria, VA 22333	20162717A79Ø
I. CONTROLLING OFFICE NAME AND ADDIES		A REPORT DATE
and Social Sciences (DEPT-0)	for the Behavioral	W NOVERDER 1980
5001 Eisenhower Avenue, Alexar	ndria, VA 22333	31
14. MONITORING AGENCY NAME & ADDRESS	illerent free Cantrolling Office,) 18. SECURITY CLASS. (of this report)
(14) ART_TR_	Han	Unclassified
(1)//// //6-	1 / 50	154. DECLASSIFICATION/DOWNGRADING SCHEDULE
IA. SUPPLEMENTARY NOTES		
18. SUPPLEMENTARY NOTES	very and identify by block numb	 (*)
18. SUPPLEMENTARY NOTES 19. KEY WORDE (Continue on covince side if names Simulation training Simulators	very and identify by block numb	(√)
18. SUPPLEMENTARY NOTES 19. KEY WORDE (Continue on resurce side if necess Simulation training Simulators Simulator fidelity	very and identify by block numb	<i>⊶</i> ()
 SUPPLEMENTARY NOTES 18. SUPPLEMENTARY NOTES 19. KEY WORDE (Continue on covaries olds if neases) Simulation training Simulation training Simulators Simulator fidelity Fidelity requirements 	nery and identify by block numb	<i>∞</i>)
 18. SUPPLEMENTARY NOTES 19. KEY WORDE (Continue on correct olde if noscent Simulation training Simulators Simulator fidelity Fidelity requirements 20. Add JRACT (Continue on reverse olde if anores) 	wary and identify by block numb	(er)
 18. SUPPLEMENTARY NOTES 19. KEY WORDE (Continue on revurse side if nearest Simulation training Simulators Simulator fidelity Fidelity requirements 29. AMETRACT (Continue on means ship if another This report reviews the 1 	wary and identify by block numb ary and identify by block number Literature on simul	w) ator fidelity and shows that
 18. SUPPLEMENTARY NOTES 19. KEY WORDE (Continue on covere olds if names Simulation training Simulators Simulator fidelity Fidelity requirements 20. AMOTRACT (Continue on reverse other if names This report reviews the 1 there is a great deal of confit aspect definition of fidelity 	ary and identify by block numb ary and identify by block numb literature on simul ision in the usage is proposed which	w) ator fidelity and shows that of the term fidelity. A two- focuses on the physical and
 18. SUPPLEMENTARY NOTES 19. KEY WOADE (Continue on revorce olds if necession in the second state of the second second	ary and identify by block numb literature on simul sion in the usage is proposed which raining device to	w) ator fidelity and shows that of the term fidelity. A two- focuses on the physical and the actual equipment for
 18. SUPPLEMENTARY NOTES 19. KEY WORDE (Centinue on correct olds if nearest Simulation training Simulators Simulator fidelity Fidelity requirements 28. AMETRACT (Continue on means other Management This report reviews the 1 there is a great deal of confu aspect definition of fidelity functional similarity of the to which training is undertaken. 	ary and identify by block mumb literature on simul ssion in the usage is proposed which :raining device to This definition i	w) Nator fidelity and shows that of the term fidelity. A two- focuses on the physical and the actual equipment for a discussed as it applies to
 18. SUPPLEMENTARY NOTES 19. KEY WORDE (Continue on coverce olds if necession in the second simulation training Simulators Simulator fidelity Fidelity requirements 20. Any TRACT (Continue on reverse other if another is a great deal of confut aspect definition of fidelity functional similarity of the test which training is undertaken. several parameters of the training is the test of test of the test of te	ary and identify by block numb literature on simul sion in the usage is proposed which :raining device to This definition i ining situation, su	w) ator fidelity and shows that of the term fidelity. It two- focuses on the physical and the actual equipment for is discussed as it applies to ach as type of task, trainee's
 18. SUPPLEMENTARY NOTES 19. KEY WORDE (Centinue on covere olds if necession in the second simulation training Simulators Simulator fidelity Fidelity requirements 20. ANTIFACT (Centinue on neares othe N measure of the second similarity of the the which training is undertaken. several parameters of the trais stage of learning, or total to the second sec	ary and identify by block must literature on simul ision in the usage is proposed which craining device to This definition i ining situation, su caining context, to	w) ator fidelity and shows that of the term fidelity. in two- focuses on the physical and the actual equipment for is discussed as it applies to ach as type of task, trainee's o determine training (Continued)
 18. SUPPLEMENTARY NOTES 19. KEY WORDE (Continue on covere olds if necession in the second simulation training Simulators Simulator fidelity Fidelity requirements 29. AMATRACT (Continue on reverse other Management of the second second	ary and identify by block numb literature on simul ssion in the usage is proposed which training device to This definition i ining situation, su caining context, to	w) ator fidelity and shows that of the term fidelity. In two- focuses on the physical and the actual equipment for is discussed as it applies to ach as type of task, trainee's o determine training (Continued) Unclassified 4ARA

11-12-5-1-70

ł

1 --

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)	Unclassified	
	SECURITY CLASSIFICATION OF THIS PAGE	han Dats Entered

Item 20 (Continued)

Yeffectiveness. Methodological issues in the empirical determination of fidelity requirements are discussed. A pilot research strategy to begin the empirical study of fidelity requirements is outlined.

ii Unclassified SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

11.

s and the

Robert T. Hays	Accession For NTIS GRARI
Submitted by: Frank J. Harris, Chief SIMULATION SYSTEMS TECHNICAL AREA	Justification By Distribution/ Availability Codos Avail and/or Dist Special
Appro Edgar ORGA RESE	Wed by: M. Johnson, Director INIZATIONS AND SYSTEMS ARCH LABORATORY
U.S. ARMY RESEARCH INSTITUTE FOR THE BEHAVIORAL ANI 5001 Eisenhower Avenue, Alexandria, Virginia 223 Office, Deputy Chief of Staff for Personnel Department of the Army	D SOCIAL SCIENCES
November 1980	

Army Project Number 20162717A790

Simulation Systems

Approved for public releast distribution unlimited.

۲

ARI Research Reports and Technical Reports are intended for sponsors of R&D tasks and for other research and military agencies. Any findings ready for implementation at the time of publication are presented in the last part of the Brief. Upon completion of a major phase of the task, formal recommendations for official action normally are conveyed to appropriate military agencies by briefing or Disposition Form.

The Simulation Systems Technical Area of the Army Research Institute for the Behavioral and Social Sciences (ARI) performs research and development in areas that include training simulation with applicability to military training. Of special interest is research in the area of simulation fidelity requirements. It is necessary to determine the necessary levels of simulator fidelity before any training system may be developed and procured for use in the Army training community.

This report surveys the relevant literature on simulator fidelity and recommends a workable definition of simulator fidelity as well as outlining an approach to the empirical determination of simulator fidelity requirements.

This report is responsive to the requirement of the Office of the Project Manager for Training Devices (PM TRADE) and to the Army's Project 2Q162717A790, "Defining Simulation Fidelity Requirements."

v

Soseph Zildner Rochnical Director

BRIEF

Requirement:

To review the relevant literature on simulator fidelity in order to determine how the term fidelity has been used. From this review, to recommend a workable definition of fidelity and outline a course of empirical investigation to determine the necessary levels of simulator fidelity to insure adequate training effectiveness.

Procedure:

An extensive review of literature on simulator fidelity was conducted. It was shown that there is much confusion in the usage of the term "fidelity." A two-aspect definition of fidelity was proposed which focuses on the physical and functional similarity of the training device to the actual equipment for which training is undertaken. This definition is discussed as it applies to several parameters of the training situation, such as type of task, trainee's stage of learning, or total training context, to determine training effectiveness. Methodological issues in the empirical determination of fidelity requirements are discussed and a pilot research strategy is outlined.

Findings:

Confusion surrounding the use of the term "midelity" may be substantially reduced if we limit the use of the term and let fidelity refer only to the degree of similarity, both physical and functional, between a training device and the actual equipment for which the training was undertaken.

Utilization of Findings:

This report can be used by researchers in determining how they may design empirical studies to determine necessary levels of simulator fidelity and by the military training community to determine the nature of training devices, which must be designed and procured.

vii

CONTENTS

DEFINITIONS	OF	FIDEL	ITY	•	•••	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	2
General Specific	Appro Bre	oache akdow	s to ns c	o ti of I	he Fid	Def eli	in ty	it:	ion	1 O	f.	Fi •	de: •	lit •	·Y	•	•	•	•	•	•	•	•	•	2 2
RECOMMENDED	APP	ROACH	TO	FI	DEL	ITY	č	•	• •	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	6
REASONS FOF	DEP	ARTUR	E FF	ROM	HI	GH	FI	DEI	LIJ	Y		•	•	•	•	•	•	•	•	•	•	•	•	٠	9
FIDELITY AN	D TR	AININ	G EF	FEC	CTI	VEN	IES	S	•••	-		•	•	•	•	•	•	•	•	•	•	•	•	•	10
Fidelity Fidelity Fidelity Fidelity Fidelity Training	and and and and and and Eff	the Type Stag Task the Psyc ectiv	Trai of e of Ana Trai holc enes	inin Tas E La alys inea ogio SS a	ng sk ear sis e's cal as	Cor nir Ak Pr Det	nte ng	xt	ies ple	s . es	of	F	id	eli						• • •		•	• • • •		11 11 12 14 14
METHODOLCG	CAL	ISSUE	s.	•	••		•	•	• •	•		•	•	•	•	•	-	•	•	•	•	•	٠	•	15
CONCLUSIONS	AND	RECO	MMEN	1DA	TIO	NS	•	•	• •		•	•	•	•	•	•	•	•	•	•	•	•	•	•	18
REFERENCES		• •	• •	•		•	•	•	• •			•	•	•	•	•	•	•	•	•	•	•	•	•	19
DISTRIBUTIO	DN .	•••	• •	•	••	•	•	•	• •		•	•	•	•	•	•	•	•	•	•	•	•	•	•	23

LIST OF TABLES

Table	1.	Varieties of fidelity terms	7
	2.	Overlapping fidelity concepts	8
	3.	General relationship between stages of learning, training objectives, and types of training devices	13
	4.	Types of training devices associated with stages of learning	13

LIST OF FIGURES

Figure 1. Sample design for a pilot study to determine the "best" combination of fidelity levels for a given task 17

Page

Today's Army is faced with training problems like none previously encountered in that the high technology of its advanced weapons systems requires correspondingly sophisticated operators and maintainers. This requirement places a heavy burden on training, particularly given the prevalence of large numbers of Category IV enlistees. The traditional approach of training personnel on actual equipment is becoming more and more prohibitive because of the cost of these systems. To cope with this prohibitive expense and to improve the effectiveness of its training, the Army has and will continue to turn increasingly toward the use of simulators. This movement is being paralleled by the other armed services (Miller, 1974; Spangenberg, 1976; Fink & Shriver, 1978; Furifoy & Benson, 1979; Malec, 1980). Apart from potential cost savings, simulators have several unique instructional advantages over the use of either the classroom or actual equipment for training.

Spangenberg (1976) discusses seven unique advantages of simulation for training. Simulators can (1) provide immediate feedback, (2) increase the number of crises, conflicts, equipment malfunctions, and emergencies to provide the trainee with experience which would be unavailable on actual equipment, (3) compress time so a complex sequence of tasks may be accomplished in the time it would take to run through only one or two tasks on the actual equipment, (4) vary the sequence of tasks to maximize training efficiency, (5) provide guidance and stimulus support to the trainee in the form of prompts and feedback, (6) vary the difficulty level to match the skill level of each individual trainee, and (7) provide the trainee with an overview from which the trainee may form an overall understanding of the whole situation. These advantages, in addition to their potential cost-effectiveness have led the Army (PM TRADE) to the conclusion that simulators should be utilized to greater advantage in its training program. But though they are intended to reduce training costs, training simulators may not be cost effective if they duplicate the physical and functional characteristics of operational equipment more precisely than is required for effective transfer of training, i.e., if simulation fidelity exceeds training requirements. However, designing the appropriate level of fidelity is not an easy task. At the very least, a set of consistently used operational definitions of fidelity is required. The term fidelity has been used with a variety of meanings and it is vital that we agree on a workable definition if we are to develop user-oriented guidance in the design, acquisition, and deployment of training simulators. This paper attempts to develop such a definition of fidelity by reviewing and synthesizing the relevant literature. The paper then attempts to place the concept in the proper context of the Army's training needs. Finally, it outlines a variety of strategies for implementing further research to determine specific fidelity requirements for the wide range of tasks carried out by the modern Army.

DEFINITIONS OF FIDELITY

The literature on simulation for training discusses the problem of the necessary levels of fidelity in simulators. The concept of fidelity is unclear because it has been used in a wide variety of ways with a wide variety of meanings. This section surveys the relevant literature and delineates the most widely used definitions of fidelity. Some definitions are very general while others tend to be more specific.

General Approaches to the Definition of Fidelity

Several recent discussions of training simulation have taken a general approach to the definition of fidelity. Two instances will serve as exemplars of this approach. Miller (1974) states that fidelity refers to the accuracy of reproduction of the actual equipment by the simulator; it is the degree to which a simulator resembles the real operational equipment or situation. An even more general approach is taken by Malec (1980). He states that fidelity has been achieved if activity on the simulator is "sufficiently like exercising the actual equipment" (Malec, 1980, p. 16). Neither of these definitions is sufficiently precise or operational to be useful in the development of guidance for simulator designers. We must know what "similar" means or what to be "sufficiently like" the actual equipment entails. There have been other definitions of fidelity which are much more specific than those above.

Specific Breakdowns of Fidelity

One of the most frequently cited breakdowns of the concept of fidelity was provided by Kinkade and Wheaton (1972). They detail three types of fidelity: equipment, environmental, and psychological.

- Equipment fidelity is the degree to which the simulator duplicates the appearance and "feel" of the operational equipment.
- Environmental fidelity is the degree to which the simulator duplicates the sensory stimulation (excluding control feel) which is received from the task situation.
- Psychological fidelity is the degree to which the simulator is perceived by the trained as being a duplicate of the operational equipment and the task situation.

(Kinkade & Wheaton, 1972, p. 679)

Kinkade and Wheaton provide examples of each of these types of fidelity. Equipment fidelity would be high for a driver trainer designed to teach driving if "an actual automobile cab, with steering wheel, steering wheel feedback dynamics, speedometer, fuel gauge, etc." (Kinkade & Whencon, 1972, p. 679) were included. Environmental fidelity would be high if the trainer provided "motion cues and a three-dimensional, dynamic visual presentation of the external world (i.e., the road, trees, sky, etc.)" (Kinkade & Wheaton, 1972, p. 679). Finally, the level of psychological fidelity would be high if the trainee perceives the simulator as being highly realistic, even though it might deviate substantially from the actual equipment it is supposed to represent. These three types of fidelity do not cover all aspects of the concept.

A series of four papers (Wheaton, Mirabella, & Farina, 1971; Wheaton & Mirabella, 1972; Mirabella & Wheaton, 1974; Prophet & Boyd, 1970) discuss task fidelity. Task fidelity refers to the correspondence between tasks performed on the actual equipment and tasks performed on the training simulator. A similar behavioral approach to fidelity is taken by Matheny (1978). We thus have four facets to the concept of fidelity so far. One facet deals with the physical configuration of the simulator (equipment fidelity), one deals with the total context which the simulator tries to duplicate (environmental fidelity), one takes a perceptual viewpoint (psychological fidelity). Some approaches do not break the concept of fidelity down quite so much.

Fink and Shriver (1978) discuss only two types of fidelity--functional and physical fidelity. Functional fidelity is the attempt to represent faithfully the stimulus and response options provided by all or portions of a piece of equipment. The previous example of the motion and visual cues in a driver trainer would also be an example of functional fidelity. Physical fidelity is the attempt to represent accurately the appearance and "feel" of the actual equipment. The example of the parts included in the driver trainer is also an example of physical fidelity. Fink and Shriver's designations of functional and physical fidelity correspond to Kinkade and Wheaton's designations of environmental and equipment fidelity respectively. The term "psychological fidelity" is not used by Fink and Shriver. This may be because they consider it a function of the other two types of fidelity.

Slenker and Cream (1977) not only leave out psychological fidelity bu' physical fidelity as well. They discuss only functional fidelity. This they define as the attempt to duplicate all of the stimulus conditions of the actual equipment. They apparently consider functional fidelity to encompass physical fidelity. This approach would therefore be guided by precise stimulus analysis to ensure that the simulator provided the same cuss as provided by the actual equipment.

Freda (1979) defines fidelity as having two aspects. Physical fidelity is the "engineering (hardware) representation of features in the operational equipment" and psychological fidelity is the "behavioral (functional) representation of the information processing demands of the operational equipment" (Freda, 1979, p. 2). This approach approximates that of Fink and Shriver (1978). Freda's physical fidelity agrees with physical fidelity, as defined by Fink and Shriver. Freda's psychological fidelity is very close to Fink and Shriver's functional fidelity. Any differences between these two approaches are those of emphasic. Freda appears to focus more closely on the trainee through the behavioral aspects of "psychological" fidelity while Fink and Shriver focus on the hardware through the stimulus and response aspects of "functional" fidelity. Since one may define behavior as stimuli and responses, it is not difficult to see the parallel between these two approaches.

It can be easily seen that the term fidelity has been used in a variety of contexts. Hardware, environmental, perceptual, and behavioral applications of the term fidelity tend to obscure one's understanding of the term. In addition, different "types" of fidelity are used to label the same concept, such as equipment and physical fidelity or environmental and functional fidelity. The application of the term "fidelity" in so many contexts and in so many variations constitutes an overextension of the term and negates the usefulness of the concept. We need more consistency and clarity in our definitions of fidelity concepts if they are to be useful in the design of training simulators. Perhaps fidelity concepts have been developed too academically and our efforts should be directed to other areas that are oriented more toward applications.

Often it is possible to gain greater understanding of a concept if we study the way it is used by practitioners as opposed to researchers. In other words, let us now change the direction of our focus from the academic side to the more pragmatic approach taken by contractors who actually attempt to build simulators and by the armed services which attempt to provide user guidance in evaluating and procuring the devices that the contractors build.

Simulator developers have not been much more successful in consistently conceptualizing fidelity. Consider for example the work of four potential contractors who submitted designs for a proposed maintenance training simulator, the Army Maintenance Training and Evaluation Simulation System (AMTESS).

Hughes Aircraft Corporation (1980) takes a two-factor approach to the definition of fidelity. They define physical fidelity as the degree of realism presented in every sonsory mode. This seems to be a combination of both of Fink and Shriver's distinctions, physical and functional fidelity. Realism of simulator controls as well as realism in the way the controls are displayed and the total environment in which the simulator is used would be indicat rs of physical fidelity, as the term is used by Hughes. Hughes also uses the term "psychological fidelity" in a new sense. It is defined as how fully the training environment exercises the mental skills required in performing the job tasks. Other distinctions of fidelity are also made, such as behavioral fidelity, engineering fidelity, and equipment fidelity, but it is not clear (at least to this reviewer) how these terms are used by Hughes.

Seville Research Corporation (1980) defines fidelity as the details of the characteristics of the equipment or item which are represented in the simulation and the "mode" in which those details are represented, and which are specifically included for training purposes. This approach analyzes fidelity in terms of the entire training context. The equipment characteristics may need to be modified to deal with different tasks or stages in the training process. They emphasize, however, that the question of fidelity only concerns those characteristics which need to be included to enhance training effectiveness and not those related to maintainability, reliability, or ccst.

Grumman Aerospace Corporation (1980) does not specifically define fidelity. They do allude to its definition by stating that fidelity requirements analysis specifies the degree or extent of physical and functional equipment similarity required to achieve satisfaction of the training objectives. They thus focus on physical and functional similarities of the simulator to the actual equipment in defining fidelity. They emphasize the need to analyze behavioral tasks in terms of the necessary cues which the simulator must provide to enable the trainee to discriminate among the cues provided by the actual equipment.

Honeywall Corporation (1980) does not attempt to define fidelity. They simply assume that it means the similarity of the simulator to the actual equipment. They state that it is important to determine the minumum level of fidelity necessary to train required tasks.

It can be easily seen that these practitioners are more concerned with the development of equipment rather than the development of conceptual definitions. They are willing to assume that fidelity somehow deals with the physical and functional similarity between the simulator and the actual equipment and then to design their equipment to be as similar as necessary to train to criterion levels. This approach works for the construction of simulators.

It is more difficult for the individuals who are responsible for procuring these devices because they must be able to judge the output of the contractor before they invest huge sums of money to develop the proposed training simulators. It is therefore important that they determine their fidelity requirements before attempting to evaluate proposed training simulators. There are several guidance aids which attempt to assist in this process.

Although several documents have been developed to provide guidance to the individuals responsible for procuring training devices, the limited progress in conceptualizing fidelity is still seen. For example, in Training Device Requirements Guide (1979), the concept of fidelity is discussed only in terms of the physical similarity of the displays (cues) and controls (responses) between the samulator and the actual equipment (pp. 153-160). In this case, the term fidelity is not used. Functional similarity, which compares the operator's behavior in terms of information flow from each display to the operator and from the operator to each control, is also emphasized but again without the use of the term fidelity. This document makes it very clear that the nost important factor is not the physical similarity of the .imulator "but whether the operator acts on the same amount of information in the same way in both operational and training situations" (p. 157). A simulator might be physically dissimilar to the actual equipment (i.e., a flat panel device) and still provide the information the trainee requires to perform in the operational setting. This document provides guidelines for the analysis of tasks to be trained and also for the analysis and evaluation of the simulator in terms of physical and functional similarity.

A similar approach is taken by Interservice Procedures (1975), a TRADOC procedures pamphlet. Although this publication uses the term "fidelity" in a different context than discussed previously (here it refers to how well

the actions, conditions, cues, and standards of the Job Performance Measures approximate these of the tasks), it nevertheless acknowledges the importance of task analysis in the development of training devices. This pamphlet provides guidelines for the analysis of physical characteristics and behavioral requirements.

An approach which avoids the use of the concept of fidelity in the selection of training devices is the TRAINVICE II model (Swezey & Evans, 1980). This model incorporates techniques from both of the previous publications to analyze the physical and functional characteristics of the training devices and also the behavioral requirements which must be trained. As with both of the other guidebooks discussed, this model focuses upon the importance of both the physical and the functional characteristics of the simulator or other training device. The term "fidelity" is not employed in this discussion and it is not a comparison of simulator characteristics with operational equipment characteristics but rather a comparison of simulator characteristics with learning guidelines.

An additional guidebook for training device design was developed by Honeywell for the Air Force Human Resources Laboratory (Miller, McAleese, & Erickson, 1977). This guidebook defines fidelity as "the degree of correspondence between operational and simulation devices in terms of cues, responses, and actions that can be performed" (pp. 51-52). According to this guidebook, the level of fidelity may be determined by task analysis. Tasks are analyzed in terms of criticality, frequency, and difficulty. Task statements are developed and subsequently used to determine the necessary level of fidelity for the device designed to train the tasks.

One other publication which addresses this issue is provided by the Air Force Human Resources Laboratory (Purifoy & Benson, 1979). This model discusses four considerations which must be evaluated when discussing the appropriate levels of simulator fidelity. They are environmental conditions, stimuli, response situations, and control-display relationships. In this guidebook, fidelity is viewed in the whole training context. It is assumed that fidelity cannot be isolated but must be incorporated into an overall training requirements analysis. Here we must not only deal with physical and functional similarity but also how similarity levels interact with other variables in the training situation. A similar conclusion is reached by Eddowes & Waag (1980). They define fidelity as the physical similarity of the learning environment to the performance environment and feel that a simulator must be incorporated into the total training context if it is to be effective.

RECOMMENDED APPROACH TO FIDELITY

Table 1 shows the variety of fidelity terms that were discussed previously. It can easily be seen that many terms have been used in connection with the term "fidelity." Not only have many different terms been used, but various fidelity concepts have been described with different labels. Table 2 shows how several of the same concepts have been labeled with various terms. Variations in terminology and multiple labeling of concepts tend to confuse the issue, so it is important to realize that the

A CONTRACT STREET

Table 1

.

Varieties of Fidelity Terms

Author/publication	Fidelity terms used
Kinkade & Wheaton (1972)	Equipment fidelity Environmental fidelity Psychological fidelity
Wheaton, Mirabella, & Farina (1971)	Task fidelity
Matheny (1978)	Sehavioral fidelity
Fink & Shriver (1978)	Physical fidelity Functional fidelity
Slenker & Cream (1977)	Functional fidelity
Freda (1979)	Physical fidelity Psychological fidelity
Seville (1980)	Fidelity (total context)
Grumman (1980)	Physical fidelity requirements Functional fidelity requirements
Honeywell (1980)	Similarity
Training Device Requirements Guide (1979)	Physical similarity Functional similarity
Interservice Procedures (1975)	Fidelity of job performance measures
Miller, McAleese, & Erickson (1977)	Degree of correspondence (cues, responses, actions)
Purifoy & Benson (1979)	Fidelity (total context)
Eddowes & Waag (1980)	Physical similarity

.....

.

Table 2

Overlapping Fidelity Concepts

Concept	Fidelity terms used	Author/publication
Physical	Physical	Fink & Shriver (1978)
fidelity	Equipment	Kinkade & Wheaton (1972)
	Functional	Slenker & Cream (1977)
	Physical	Freda (1979)
	Physical	Hughes (1980)
	Fidelity (context)	Seville (1980); Purifoy & Benson (1979)
	Physical requirements	Grumman (1980)
	Physical similarity	Honeywell (1980); Training De- vice Requirements Guide (1979); Eddowes & Waag (1980)
	Physical correspondence	Miller, McAleese, & Erickson (1977)
Functional	Functional	Fink & Shriver (1978)
fidelity	Environmental	Kinkade & Wheaton (1972)
	Functional	Slenker & Cream (1977)
	Psychological	Freda (1979)
	Fidelity (context)	Seville (1980); Purifoy & Benson (1979)
	Functional requirements	Grumman (1980)
	Functional similarity	Honeywell (1980); Training De- vice Requirements Guide (1979)
	Functional correspondence	Miller, McAleese, & Erickson (1977)
Behavioral	Task fidelity	Wheaton, Mirabella, & Farina (1971)
	Behavioral fidelity	Matheny (1978)
	Psychological fidelity	Hughes (1980)
	Job performance measure	Interservice Procedures (1975)
Perceptual	Psychological	Kinkade & Wheaton (1972)

•

.

issue is the acquisition by the trainees of skills which they may use on the actual equipment. We are thus concerned with behavior, and it is important that we not confuse fidelity with this. Fidelity has been defined in terms that cover the entire gamut from physical characteristics of the training simulator to the perception of the trainees and their behaviors. In the opinion of this author, the term "fidelity" should be restricted to descriptions of the configuration of the equipment and not be used when discussing behaviors. We must ultimately measure and evaluate behaviors, but there are many concepts already available such as sensation, perception, learning, retention, or reinforcement to deal with these. The issue of fidelity only becomes muddled if we attempt to use the same term to cover all the various aspects of the training situation. This is not to say we should throw out the remainder of the gamut. Rather, we should use labels for these concepts that do not confuse them with fidelity.

Of the approaches discussed above, the one which best isol/ites the equipment characteristics from the behaviors of trainees on the equipment is the approach of Fank and Shriver (1978). As was stated proviously, Fink and Shriver only discuss functional and physical fidelity. In both functional and physical fidelity we are concerned with the equipment on which training is to proceed. The following definition of fidelity is therefore proposed:

Fidelity is the degree of similarity between the simulator and the equipment which is simulated. It is a measurement of the physical characteristics of the simulator (physical fidelity) and the informational or stimulus and response options of the equipment (functional fidelity).

With this restricted use of the term fidelity in mind, let us now discuss why the level of simulator fidelity need not necessarily be as high as possible.

RE'SONS FOR DEPARTURE FROM HIGH FIDELITY

In his considerations for the designs of simulators, Miller (1974) states that studies have never shown that high fidelity is associated with poorer training. This statement may not be true. In a study by the Air Force (Martin & Waag, 1978), it was shown that flight simulators with very high fidelity (6 degrees of motion) provided too much information for novice trainees and actually detracted from simulator efficiency. There are also other considerations which force the designers and procurers of training simulators to desire lower levels of fidelity.

Cox et al. (1965) studied the effects of a wide variety of fidelity levels on the training of fixed-procedures tasks. They concluded that the requirements for fidelity are really quite low as long as the controls and displays of the device remain clearly visible to the individual trainee and as long as the functional relations between parts are maintained. They are careful to state that these conclusions apply only in a fixed-procedures task paradigm. It is probably safe to conclude that at least some departures from high fidelity will not produce detrimental effects in the training effectiveness of a simulator on other types of tasks. Since high fidelity is associated with higher simulator cost;, it is prudent to determine just how much fidelity is necessary in a training simulator.

Blaiwes et al. (1973) state four reasons for departure from perfect physical fidelity. The first deals with training effectiveness. It has been shown (Martin & Waag, 1980) that it is contrary to good urgining practice to make training an exact duplicate of certain real jobs. The training situation affords the opportunity for immediate feedback and enhanced stimulus cues which aid in training but which may not be available on actual equipment. When these features are incorporated in a simulator, the level of fidelity is lowered.

A second reason is the cost effectiveness of lower fidelity simulators. A simulator may be less costly than the actual equipment and if it can be designed with a lower level of fidelity and still provide adequate transfer of training, even more money can be saved.

The third reason for departure from perfect fidelity is the safety of the training. It may be too dangerous to train people on the actual equipment. Not only could individuals be injured but the actual equipment may be damaged if certain malfunctions are induced for the purposes of training.

The final reason given by Blaiwes et al. is the technological barriers to duplicating the operational environment. It may not always be possible to produce a training simulator that exhibits perfect fidelity. The level of fidelity necessary to produce trained personnel must be determined by accounting not only for the previous considerations but also for considerations inherent in the training context. Training context is defined as the way in which a training simulator is incorporated into a specific program of instruction. Although we may see fidelity as a central question in any attempt to design or evaluate a training simulator, it is not. The central question is not its Fidelity but its training effectiveness. As we shall see, fidelity interacts with several parameters to determine training effectiveness.

FIDELITY AND TRAINING EFFECTIVENESS

The question of the necessary level of fidelity has been asked ever since simulators began to be used in training. Not much progress was made in determining fidelity requirements until it was realized that fidelity is not really the question at all. Bunker (1978) states that progress was made only when "instead of pondering how to achieve realism, we should ask how to achieve training" (p. 291).

The same point was made by Kinkade and Wheaton (1972) several years earlier. "The overall level of fidelity required in a training device is partially determined by the desired amount of transfer of training" (p. 679).

What these statements tell us is that fidelity is not a concept that may be discussed in isolation. The effect of fidelity on training effectiveness is not simple. It is modified by the total context in which the equipment is used.

10

a ta Manazar sa Parta a Arg

E

Fidelity and the Training Context

Micheli (1972) makes the point that it may be more important how a device is used than how it is designed. Montemerlo (1977) states that the training effectiveness of a simulator is a function of the total training environment and not just the characteristics of a particular piece of equipment. Wheaton et al. (1976) concluded after an extensive review of fidelity literature that fidelity per se is not sufficient to predict device effectiveness and that the effect of fidelity varies as a function of the type of task to be trained. It becomes increasingly clear that we cannot productively deal with the concept of fidelity in isolation but rather as a function of total training context--which includes the training tasks, the stage of learning of the trainees, and the instructional system designed to train the tasks. Training effectiveness (i.e., the amount of transfer of training from the simulator to the actual equipment in a specific context) may be used to determine necessary simulator fidelity levels.

Fidelity and Type of Task

Several authors have made the point that we must define necessary fidelity levels in terms of the tasks which must be trained. Different tasks may require different levels of fidelity. Fink and Shriver (1978) distinguish between the necessary instruction for maintenance tasks versus that needed for operational tasks. Maintenance training should entail "instruction in decision processes to a greater degree than operations training. This instruction must include formulation of decision rules, identification of decision alternatives, and actual decision making" (p. 5). The fidelity level necessary for decision making may be very different that that necessary for operating the controls on a piece of equipment. The important point here is that we are attempting to train individuals to behave in certain ways and that the ultimate behaviors must guide our choice of fidelity levels. Miller (1980) states the point in this way:

While physical identity of operational and training equipment does facilitate transfer, the controlling factor is not physical congruence but the (sometimes subtle) cues that guide the behavior involved in the performance of a task. Careful analysis and exploitation of these cue/behavior patterns is the basis of all synthetic or simulation-based approaches to training (p. 5).

Stated another way, "The important point is that the behavioral requirements dictate the physical characteristics rather than some perceived physical fidelity dictating behavior" (Matheny, 1978, p. 4).

What is necessary is for us to bridge the gap between the output behaviors which we desire and the input behaviors which the trainees arrive with.

Fidelity and Stage of Learning

An important consideration in determining the fidelity levels necessary to build this "behavioral bridge" is the stage of learning in which we find

the traines. Fink and Shriver (1978) discuss four stages of learning of which each has different general training objectives and which lend themselves to the use of different types of training devices with different levels of fidelity. Table 3 shows these stages of learning and their relationship to training objectives and types of training devices. Fink and Shriver are of the opinion that "no one class of training aid or devices need carry the entire training load" (p. 22). They feel it is more cost effective to train the first stages of learning on low fidelity devices before switching to more expensive simulators required in later learning stages. Kinkade and Wheaton (1972) make the same point. They delineate five stages of training for which different training devices are appropriate. Table 4 shows the types of training devices associated with these five stages of training.

Fidelity and Task Analysis

こう いん、 大学の対応時代になってい

We can see that fidelity levels cannot be determined outside of the training context. The determination of the necessary fidelity becomes a repetitive process with the analysis of tasks and behavior objectives as its guiding principles. "The major decisions in this process are selection of the subset of tasks that will actually be trained in the device and determination of the degree of fidelity necessary to train each of the tasks in the subset" (Eggemeir & Cream, 1978, p. 18). Task analysis therefore is the important first step in determining not only fidelity requirements but also whether a simulator is necessary at all.

Tasks have been analyzed in various ways. Smode (1971) analyzes tasks as training objectives: what is to be trained, under what conditions the training will occur, and the standard of performance desired at the end of training. For each objective, tasks are stated in terms of performance elements, how these will be measured and the conditions under which performance occurs. Smode provides a detailed strategy for developing these training objectives. Similar strategies are provided in the guidebooks which were discussed above (Interservice Procedures, 1975; Lenzychi & Finley, 1980; Training Device Requirements Guide, 1979).

Another approach to task analysis is to rank each task in terms of its criticality, frequency, and difficulty (CFD) (Slenker & Cream, 1977; Eggemeir & Cream, 1978; Freda, 1979). Tasks that are rated high on these dimensions would be included in the training device with the fidelity level determined by a repetitive process. Freda (1979) also uses the CFD approach to provice a framework for analyzing learning tasks in terms of the information processing demands on the individual in the operational setting. "These information processing demands can be viewed as a sequential flow of three information processing stages" (p. 6).

The first stage is sensory input and "refers to the degree of CFD involved in the apprehension of operational stimulus parameters for suprathreshold input processing" (p. 9). The second stage is central processing and "refers to the degree of CFD involved in using cognitive skills and strategies for selecting the appropriate psychomotor output based on the sensory input" (p. 9). The third stage is psychomotor output and "refers

ų,

In the output in the light

General Relationship Between Stages of Learning, Training Objectives, and Types of Training Devices (Fink & Shriver, 1970, p. 23)

Table 3

Stages of learning	General training objectives	Types of training devices					
lst stage	Acquire enabling skills and knowledges	Demonstratorswall charts, films, TV, mock-ups, etc. Nomenclature & parts location Trainers					
2nd stage	Acquire uncoordinated skills and unapplied knowledges	Part-task trainers Procedures trainers					
3rd stage	Acquire coordinated skills and ability to apply knowledges	Troubleshooting logic trainers Job segment trainers Skills trainers					
4th stage	Acquire job proficiency in job setting	Operational equipment Actual equipment trainers					

Table 4

.

Types of Training Devices Associated with Stages of Learning (adapted from Kinkade & Wheaton, 1972, p. 673)

Stages of learning	Types of training devices
Indoctrination	Films, TV, mockup
Procedural training	Photographs, nonfunctional mockup, functional mockup
Familiarization training	Functional equipment Part-task trainer
Skill training	Functional with man-machine dynamics Represented Part-task trainer
Transition training	Part-task simulator

to the degree of CFD involved in the expression of the appropriate behavioral response" (p. 9).

Depending upon the stage of the information processing demands in which a given task is classified and depending upon its CFD rating, the fidelity requirements of a simulator to train that task may be determined (Freda, 1979; Lenzychi & Finley, 1980).

An alternative (or perhaps complementary) approach to task analysis is to analyze the behavioral cues which stimulate the required performance (Pearson & Moore, 1978; Grumman, 1980). In this approach, the degree of fidelity necessary in the simulator is determined on the basis of the amount of information the students must derive from the cue to make the cue worthwhile. "The desired fidelity of a given cue is that level which will enable a trainee discrimination equivalent to that which he could obtain from that cue and similar cues provided by the operational equipment" (Grumman, 1980, p. 128). This approach would make a useful addition to the approach discussed above where tasks are analyzed in terms of CFD. Once it is determined that a given task is above the criterion level on CFD, it may then be analyzed in terms of its behavioral cues to determine the necessary level of fidelity to train the task.

Fidelity and the Trainee's Abilities

An important area of research which relates to task analysis is the determination of how the skills which are necessary for a given task relate to general abilities. This relationship has been utilized in rating tasks on CFD (Freda, 1979). Tasks have been organized into 11 general categories which are very close to general abilities (Aagard & Braby, 1976). Not only can these general learning categories be used to evaluate tasks in determining necessary fidelity levels, but it is also possible to use the output from such evaluations to determine which individuals should be selected for training in the first place. By testing individuals on basic abilities prior to their inclusion in training programs, it should be possible to screen out those trainees who do not possess the required abilities to benefit from a given training program. Again, we must keep in mind that the issue of fidelity should be secondary to the real issue, which is the production of well trained personnel. The "best" training course with perfect fidelity levels will not be productive if the trainees selected for the course do not have the requisite abilities to master the tasks trained in the course.

Fidelity and Psychological Principles

ς.

The determination of the necessary fidelity level for a training simulator may be facilitated if we are guided by established psychological principles in the design of the simulator. Adams (1979) discusses five psychological principles which should underlie the design and use of any simulator. These principles are (1) human learning is dependent on knowledge of results (KOR) so any simulator should incorporate KOR, (2) perceptual learning or the ability to extract information from stimulus patterns increases as a result of experience which may be provided on a simulator,

(3) if a response is to be made to a stimulus, then the stimulus and the control for response to it must be in the simulator, (4) transfer is highest when the similarity between the simulator and the actual equipment is high although transfer is possible with low similarity, and (5) the trainae must be motivated if learning is to occur. One additional principle (Grumman, 1980) is relevant. It is the phenomenon of perceptual constancy. This phenomenon occurs when familiar objects are perceived as maintaining their perceived characteristics almost independent of changes in stimulus conditions. This principle allows reduced fidelity in simulators to a certain point. Each of these principles should be taken into account when the fidelity levels of a simulator are determined.

Training Effectiveness as Determinant of Fidelity Requirements

As was stated previously, training, rather than fidelity, is the real issue. We are in the business of training individuals in specific tasks and all the hardware and software are simply aids in this training process. The necessary fidelity level becomes easier to determine by using training effectiveness as our criterion. The necessary fidelity level for a given simulator may be empirically determined by the training effectiveness of the simulator. As stated previously, training effectiveness may be operationalized as the amount of transfer of training from the simulator to the actual equipment. However, this method has problems as pointed out by Adams (1979). The most critical problem is the cost of transfer of training experiments. It would be very costly to design several simulators with different levels of fidelity, train individuals on them, and then evaluate the trainee's performance on actual equipment. However, this is the only method that will provide us with the empirical data necessary to determine fidelity requirements. It may be possible to make this method more cost effective by limiting the number of fidelity levels evaluated and by beginning our investigations with lower levels of fidelity. As Fink and Shriver (1978) wrote: "The answer to maintenance training lies not in how much but how little simulation to use. This is not to say that fewer simulators should be used, merely that low-cost, low-fidelity simulators should be employed where they can be made effective" (p. 26). Eddowes (1978) also said: "As soon as the capabilities of a simulator support practice of a set of training tasks, stop adding to it. Everything else the simulator does will cost more, and while it may not detract from training effectiveness, it probably won't add to it" (p. 53). Once we have determined that a lower fidelity level is adequate for a given simulator, it will not be necessary to evaluate simulators which incorporate higher fidelity levels. Let us now discuss some of the methodological issues involved in empirically determining necessary levels of simulator fidelity.

METHODOLOGICAL ISSUES

Several methodological issues arise when we attempt to empirically determine the necessary fidelity level for a simulator to train a given task. As was discussed earlier, various tasks will require different levels of fidelity as will different stages of the learning process. It is important that general guidelines be established for required fidelity levels and the only way to establish these guidelines is through empirical investigations of the relationship between level of fidelity and training effectiveness. These empirical investigations should begin at a general level and proceed to a more specific level. The studies at the general level may be considered pilot studies which will direct later investigations focusing on specific tasks and specific configurations of training simulators.

The first step in the empirical investigation of the relationship between level of fidelity and training effectiveness is to develop a scale to measure level of fidelity. If we follow the definition of fidelity that was developed previously, we will have two factors to measure: the physical characteristics of the simulator (physical fidelity) and the informational or stimulus and response options of the equipment (functional fidelity).

We therefore need to measure the physical and functional aspects of fidelity before we can attempt to empirically determine how these factors relate to the training effectiveness of the simulator. An example of this two-factor approach to the measurement of fidelity is the work of Wheaton, Mirabella, and Farina (1971), Wheaton and Mirabella (1972), and Mirabella and Wheaton (1974). In these three investigations, two scales were used to measure the characteristics of training simulators. Panel lay-out indexes developed by Fowler, Williams, Fowler, and Young (1968) were used to measure the physical fidelity of the simulators. Another scale which was assumed to vary independently with the above scale was used to measure the functional fidelity of the simulators. This scale, called the Display Evaluative Index (DEI) was developed by Siegel, Miehle, and Federman (1962) and is a measure of the effectiveness with which information flows from displays to corresponding controls via the operator. This approach yields two fidelity measures which define the two aspects of fidelity. Depending on other parameters such as task type and level of training, these aspects would interact and lead to a given level of training effectiveness.

An example of the design for one of these pilot studies is shown in Figure 1. Here we see the two aspects of fidelity (physical and functional) being treated as factors in a 3 x 3 factoral design. Depending on how a fidelity factor fell on the measurement scale chosen for the experiment, each factor would be represented as low, medium, or high. Values in the cells of the design would be derived from measures of proficiency on the actual equipment.

The measurement of training effectiveness is another problem which must be solved if our empirical investigations are to be meaningful. While there are a variety of methodologies and measures that have been used to measure the training effectiveness of simulators, the transfer of training experiment is the most useful for experimental purposes (Adams, 1979). Of the various measures of training effectiveness that may be derived from a transfer of training experiment, the transfer effectiveness ratio (Provenmire & Roscoe, 1971) may be best adapted for this research. It has been used successfully in Army simulator effectiveness research (Holman, 1979). The transfer of a training type of study would have to be applied to each training task to determine the "best" combination of physical and functional fidelity for that task. A review of theories and models of transfer of training is provided by Wheaton et al. (1976).

Physical fidelity

		Lo./ (control absent)	Medium (drawing)	High (3-D)
	Low (dcesn't work mechanically)			
Functional fidelity	Medium (works with no effect)			
	High (works with effect)			

Figure 1. Sample design for a pilot study to determine the "best" combination of fidelity levels for a given task.

۰.

Once such pilot studies have narrowed our focus down to a few testable concepts, we may develop training programs which actually use simulators to train individuals. Then we can measure the level of training effectiveness on a given task. Our research efforts should determine the training effectiveness of every type of fidelity configuration. Data from these efforts may then be used to determine which configuration is most cost effective to produce the highest level of training effectiveness on a given task. If lower levels of fidelity produce adequate training effectiveness, then there is no necessity to produce simulators with higher fidelity. As was stated previously, more fidelity than is necessary may not reduce the efficiency of a simulator but it will probably not improve it either. Just enough fidelity to motivate the trainee while providing him or her with the necessary skills on the actual equipment is the goal to which we should strive. In this way we still provide the most cost effective training for the Army's personnel.

CONCLUSIONS AND RECOMMENDATIONS

Confusion surrounding the use of the term "fidelity" may be substantially reduced if we limit the use of the term and let fidelity refer only to the degree of similarity, both physical and functional, between a training device and the actual equipment for which the training was undertaken. By dealing with the configuration of the equipment itself, we have something concrete which we can manipulate to change the trainee's behaviors. Other concepts which have been discussed under the label "fidelity" are still useful but should be separated from the concept of fidelity by the use of other labels. We may then ask how fidelity interacts with these concepts. Many researchers have concluded that fidelity, as defined in this paper, interacts with at least four factors: the stage of learning of the trainee, the type of task to be trained and the way the simulator is used and accepted by students and instructors, and the individual sensory and perceptual differences among subpopulations of trainees. Further research needs to be conducted to at least generally determine how the above factors actually interact with the physical and functional configuration of training simulators in producing given amounts of transfer of training. Knowledge about the interaction of these factors with physical and functional fidelity will allow us to determine the principles of simulator training which produce the most effective training program for any given task. Once these principles are quantified we will then be able to determine not only the most effective simulator configuration but also the training context in which the simulator may be used most effectively.

The proposed definition of fidelity and the research strategy which uses this definition should enable us to quantify the concept of simulator fidelity for any given task. We may then use this data as one source of input to our efforts to prescribe simulator device characteristics for devices not yet produced and also to predict the training effectiveness of devices that already exist. Our efforts will pay off in more cost effective programs of instruction which better train individuals for the needs of the Army.

- Aagard, J.A. & Braby, R.B. Learning guidelines and algorithms for types of training objectives, TAEG Report No. 23, March, 1976.
- Adams, J.A. On the evaluation of training devices. <u>Human Factors</u>, 1979, <u>21</u>(6), 711-720.
- Blaiwes, A.S., Puig, J.A., & Regan, J.J. Transfer of training and the measurement of training effectiveness. <u>Human Factors</u>, 1973, <u>15</u>(6), 523-533.
- Bunker, W.M. Training effectiveness versus simulation realism. In the <u>Eleventh NTEX/Industry Comprence Proceedings</u>. Naval Training Equipment <u>Center:</u> Orlando, Florida, 1978.
- Cox, J.A., Wood, R.O., Boren, L.N. & Thorne, H.W. Functional and appearance fidelity of training devices for fixed-procedures tasks. Technical Report: 65-4, Alexandria, VA: Human Resources Research Organization, 1965.
- Crawford, M.P. Simulation in training and education. Professional Paper: 40-67, Alexandria, VA, HumRRO, 1967.
- Eddowes, E.E. Flight simulator fidelity and flying training effectiveness. In Proceedings of a Symposium at the Annual Meeting of the American Psychological Association, August, 1978, Toronto, Canada.
- Eddowes, E.E. & Waag, W.L. The Use of simulators for training in-flight and emergency procedures. NATO advisory Group for Aerospace Research and Development (AGARD), June 1980.
- Eggemeir, F.T., & Cream, B.W. Some considerations in development of team training devices. In D.E. Erwin (Ed.), <u>Psychological Fidelity in</u> <u>Simulated Work Environments: Proceedings of a Symposium at the Annual</u> <u>Meeting of the American Psychological Symposium at the Annual Meeting</u> of the American Psychological Ausociation, August, 1978, Toronto, Canada.
- Fink, C.D. & Shriver, E.L. Simulators for maintenance training; some issues, problems and areas for future research. Technical Report: AFHRL-TR-78-27, July, 1978. Air Force Human Resources Laboratory, Technical Training Division, Lowry Air Force Base, Colorado.
- Fowler, R.L., Williams, W.E., Fowler, M.G., & Young, D.D. An Investigation of the relationship between operator performance and operator panel layout fc⁻ continuous tasks. Report No. AMRL-TR-68-]70. Aerospace Medical Essearch Laboratory, Wright-Patte son Air Force Base, Ohio, 1968.
- Freda, J.S. Fidelity in Training simulation. Unpublished paper: Army Research Institute, 1979.

Gilbert, T.F. <u>Human Competence</u>; <u>Engineering Worthy Performance</u>. New York: McGraw-Hill, 1978

Grumman Aerospace Corporation. AMTESS-1 Final Report. April, 1980.

Holman, G.L. Training effectiveness of the CH-47 flight simulator. ARI Research Repport 1209, May 1979

Honeywell Corporation. AMTESS-1 Final Report. March, 1980

Hughes Aircraft Company. AMTESS-1 Final Report. March, 1980.

Interservice Procedures for Instructional Systems Development. TRADOC Pamphlet 350-40. 1 August, 1975.

- Kinkade, R.G. & Wheaton, G.R. Training device design. In H.P. VanCott & R.G. Kinkade. (*Eds.), <u>Human Engineering Guide to</u> <u>Equipment Design</u>. Washington, D.C.: American Institutes for Research, 1972.
- Lenzychi, H.P. & Finley, D.L. How to determine training device requirements and characteristics: A handbook for training developers. Draft Technical Report TR-80. U.S. Army Research Institute, Alexandria, Va., May 1980.
- Malec, V.M. Simulation in maintenance training. Unpublished paper: Navy Personnel Research and Development Center, San Diego, CA, 1980
- Martin, E.L. & Waag, W.L. Contributions of platform motion to simulator effectiveness: Study 1-Basic contact. Interim Report: AFHRL-TR-78-15. Air Force Human Resources Laboratory, June 1978.
- Matheny, W.G. The concept of performance equivalence in training systems. In D.E. Erwin (Eds.) <u>Psychological Fidelity in</u> <u>Simulated Work Environments; Proceedings of Symposium at the</u> <u>Annual Meeting of the American Psychological Association,</u> August, 1978, Toronto, Canada.
- Micheli, G.S. Analysis of the transfer of training, substitution and fidelity of simulation of transfer equipment. Training Analysis and Evaluation Group. Naval Training Equipment Center, Orlando, Florida, 1972.
- Miller, G.G. Some considerations in the design and utilization of simulators for technical training. Technical Report: AFHRL-TR-74-65. Air Force Human Resources Laboratory, August, 1974.
- Miller, K.E. Simulation in maintenance training. Unpublished paper: Naval Training Equipment Center, Orlando, Florida, 1980.

Miller, L.A., McAleese, K.J. & Erickson, J.M. <u>Training Device Design</u> <u>Guide</u>; The Use of Training Requirements in Simulation Design. Air Force Human Resources Laboratory. Contract F33615-76-C-0050, June 1977

- Mirabella, A. & Wheaton, G.R. Effects of task index variations on transfer of training criteria. Technical Report: NAVTRAEQUIPCEN 72-C-0126-1. Navy Training Equipment Center, Orlando, Florida, January, 1974.
- Montemerlo, M.D. Training device design: The simulators versus stimulation controversy. Technical Report: NAVTRAEQUIPCEN IH-287. Navy Training Equipment Center, Orlando, Florida, July, 1977.
- Narva, M.A. Development of a systematic methodology for the application of judgement data to the assessment of training device concepts. Research Memorandum 79-7. US Army Research Institute, Alexandria, Virginia, May 1979
- Pearson, T.E. & Moore, E.O. Analysis of software simulation in computer-based electronic equipment maintenance trainers. TAEG Report No. 57. Training Analysis and Evaluation Group, Orlando, Florida, Sept. 1978.
- Prophet, W.W. & Boyd, H.A. Device task fidelity and transfer of training: Aircraft cockpit procedures training. Alexandria, Virginia: Human Resources Research Organization, Technical Report 70-10, July 1970.
- Provenmire, H.K. & Roscoe, S.N. An evaluation of ground based flight trainers in routine primary flight training. <u>Human Factors</u>, 1971, 13 (2), 109-116.
- Purifoy, G.R. & Benson, E.W. Maintenance Train imulators Design and Acquistion: Summary of current proc: Technical Report: AFHRL-TR-79-23. Air Force Hu rces Laboratory, November, 1979.

Seville Research Corporation. AMTESS-1 Final Report. March, 1980.

- Siegel, A.I., Miehle, W. & Federman, P. Information transfer in display control systems. VI. A manual for the use and application of the display evaluative index (Sixth Quarterly Report). Wayne, PA: Applied Psychological Services, 1962.
- Slenker, K. & Cream, B.W. Part-task trainer for the F106 A MA-1 Radar/infared fire control system: Design, specification, and operation. Technical Report: AFHRO-TR-77-52, September 1977. Air Force Human Resources Laboratory, Advanced Systems Division, Wright-Patterson Air Force Base, Ohio
- Smode, A.F. Human factors inputs to the training device design process. Technical Report; NAVTRADEVICENT 69-C-0298-1. September, 1971. Navy Training Equipment Center, Orlando, Florida.

and the second second second and the second s

- Spangenberg, R.W. Selection of simulation as an instructional medium. From <u>Proceedings - Volume IV.</u> <u>Future of simulators</u> <u>in skills training.</u> First International Learning Technology Conference & Exposition on Applied Learning Technology, Society for Applied Learning Technology, July 21-23, 1976, p. 65.
- Swezey, R.W. & Evans, R.A. <u>Guidebook for Users of TRAINVICE</u> <u>II. Alexandria, Virginia: US Army Research, Contract No.</u> <u>MDA-903-79-C-0428</u>, May, 1980.
- Training Device Requirments Guide. Orlando, Florida: PM TRADE and Ft. Eustis, VA: Army Training Support Center, 5 January, 1979.
- Wheaton, G.R., Mirabella, A., & Farina, A.J. Trainee and instructor task quantification: Development of quantitative indices and a predictive methodology. Technical Report: NAVTRADEVCEN 69-C-0728-1. Naval Training Device Center, Orlando, Florida, January, 1971.
- Wheaton, G.R. & Mirabella, A. Effects of task index variations on training effectiveness criteria. Technial Report: NAVTRAEQUIPCEN 71-C-0059-1. Navy Training Equipment Center, Orlando, Florida, October, 1972.
- Wheaton, G.R., Rose, A.M., Fingerman, P.W., Korotkin, A.L. & Holding, D.H. <u>Evaluation of the effectiveness of training</u> devices; <u>Literature Review and Preliminary Model.</u> Research Memorandum 76-6. US Army Research Institute for the Behavioral and Social Sciences, Arpil, 1976. Contract No. DAHC <u>19-73-C-0049</u>.

DISTRIBUTION
T US ANNY WESTERN COMMAND ATTNI APPL
T DEPARTMENT OF THE NAVY TRAINING ANALYSIS AND EVALUATION GROUP
T HOA ATTNY DAAG-ED
) HQ. ICATA ATTN: ATCAT-OP-U
7 HODA RESEARCH AND STUDIES DFC
1 MILITARY OCCUPATIONAL DEVELOPMENT DIV DAPC-MSP-D, RM 852C HOFFMAN BLDG 1
4 OASD (MRA AND L)
1 HUDA ATTN: DAMU-RUR
I HU TCATA TECHNICAL LIBRARY
1 HQUA OUCSPER
T USRAJCO - STC
1 HQDA ATTN: DAMI-15I
TUSA AVIATION SYSTEMS COND ATTNT DRSAV-200
I USA CORADCOM ATTN: AMSEL-PA-RH
T USA WRRADCOM ATTY ATFE-LO-AC
1 HEADHUARTERS, US MARINE CURPS ATTN: CULF MP1-20
Z US ARMY EUROPE AND SEVENTH ARMY
1 1ST INFANTRY DIVISION AND FT. RILEY ATTN: AFZN-UPT-T
T USA INTELLIGENCE AND SECURITY COMMAND ATTNI IAOPSATNGAT
2 HQ THADOC TECHNICAL LIBRARY
T NAVAL TRAINING EQUIPMENT CEN ATTN: TECHNICAL LIBRARY
3 MILITARY OCCUPATIONAL DEVELOPMENT DIRECTORATE ATTN: ATZI-NCR-MS-M. R4 3N33 HOFFMAN BLDG TT
T DATA ANALYSIS DIVISION ATTN: ATZI-NCR-MD. HOFPMAN BLDG II
1 USA MILPERCEN ATTN: DAPC-POO-T
TUSAFACFA CHIEF, ORGANIZATIONAL EFFECTIVENESS WRANCH
1 ATH INFANTRY DIVISION
THODA ARHY FURCE HODERNIZATION CUORDIVATION OFFICE
1 NAVAL AIR SYSTEM COMMAND /
DCSOPS (DIST 4) ATTN: DAMO-RUI
1 123D USARCOM RESERVE CENTER
T US ARMY SOLDIER SUPPORT CENTER ATTN: ATSG-HUD (DR. CAVINESS)
1 DIRECTORATE OF ARMOR AVIATION ATTN: ATZK-AAD
T USAAHMC + FT. KNOX AVIATION DIVISION
1 USA FORCES COMMAND AFIN - DEPUTY C OF S FOR INTELLIGENCE
T USA FORCES COMMAND AFUP - DEPUTY CHIEF OF STAFF FOR OPERATIONS
US ANMY AIR DEFENSE SCHOOL ATTN: ATSA-DTD
TOTRECTORATE OF TRAINING ATTN: ATZQ-T
1 DIRECTORATE OF CUMBAT DEVELOPMENTS ATTN: ATZU-D
1 HODANCOM MARINE CORPS LIAISON OFC
1 DEPANTMENT OF THE ARMY US ARMY INTELLIGENCE + SECURITY COMMAND
TUS ARMY SAFETY CENTER ATTN: LIBRARIAN, HLDG 4905
1 USA MISSILE COMMAND ATTN: DRSMI-NTN
1 ARTAUS AITN: DRCPM-IDS-TU
1 USA FORCES COMMAND
1 PM INAUE /
1 US MILITARY DISTRICT OF WASHINGTON OFC OF EQUAL OPPORTUNITY
I NAVAI CIVILIAN PERSONNEL COMU SOUTHERN FLU DIV
22 ARI I TAISON OFFICE
I 7TH WENT IRAINING COMMAND
1 HQ UNAREUM ATINI DESOPS
I NUDRE UCS STOLY OFFICE
1 0.50 MATT TRAINING ANALTSIS EVALUATION GROUP
I USAUJEG ALINI ALEGEREE HUMAN FACIONS
I USAFAGUS/IAU SENIUK ARMT AUSUK
1 INTER-UNIV SEMINAR ON ARMED FORCES + SUC
1 USA FLECIKONIC PHOVING GHUUNU AITN: STEEP_MT-ES
I UASA (RUA) DEPUTY FUR SCIENCE AND TECHNOLOGY
1 OFG UF NAVAL RESEARCH /
1 AFHR, /LNLG
I AIM FUNCE HUMAN RESOURCES LAB ATTNI AFHRL/TSR

1 FEDERAL AVIATION ADMINISTRATION CENTRAL REGION LIBRARY, ACE-66 1 AFAMML/BB 1 AFAMHL/HE T NAVAL PERSONNEL & AND D CENTER COMMAND AND SUPPORT SYSTEMS I NAVY PERSONNEL R AND D CENTER I NAVY PERSONNEL & AND D CENTER UINECTOR OF PROGRAMS I NAVY PERSONNEL & AND D CENTER 1 US AHMY AVN ENGINEERING FLIGHT ALTIVITY ATTHE DAVTE-TO P OFC OF NAVAL RESEARCH PERSONNEL AND THAINING RESEARCH PROGRAMS 1 NAVAL PERSONNEL R + O CENTER 1 OFC OF NAVAL RESEARCH PRUJECT OFFICER. ENVIRONMENTAL PHYSIOLOGY 1 DEPT. OF NATIONAL DEFENCE DEFENCE AND CIVIL INSTITUTE OF ENVIR MED I NAVAL AEROSPACE MEDICAL HOLH LAB AEROSPACE PSYCHOLOGY DEPARTMENT I USA TRADOC SYSTEMS ANALYSIS ACTIVITY ATTN: ATAA-TCA 1 HEADWUARTERS. COAST GUARU CHIFF. PSYCHULOGICAL HSCH HR 1 USA RESEARCH AND TECHNOLOGY LAR ATTN: DAVOL-AS (DR. R. S. DUNN) 1 USA +NGINEER TUPUGRAPHIC LABS AITN: EIL-GSL 1 USA FNGINEER TUPOGRAPHIC LABS ATTN: STINFO CENTER 1 USA FNGINEFR TUPUSRAPHIC LABS ATTN: EIL-TD-S I USA HOBILITY EQUIPMENT & AND U COMU ATTN: DRUME-TQ (SCHOOL) 1 NIGHI VISION LAH ATTN: URSEL-NV-SUD 1 USA IRAINING BOARD ATTN: ATTG-ATU-TA 1 USA HUMAN ENGINEERING LAD 1 USAHEL LIAISON HEP. USAAVNC I USA MATERIEL SYSTEMS ANALYSIS ACTIVITY ATTN: DRXSY-C 1 USA RESEARCH OFC / I NAFEL HUMAN ENGINEERING BRANCH T HATTFLLE-COLUMBUS LABORATORIES TACTICAL TECHNICAL OFC J USA "RCIIC TESI CEN ATTN: AMSTE-PL-TS 1 USA COLD REGIONS TEST CEN ATTN: STECR-UP 1 USA CUNCEPTS ANALYSIS AGLY ATTNE USCA-ROP 1 USA CONCEPTS ANALYSIS AGCY ATTNI CSCA-JF 1 HU WHAIR DIV OF NEUROPSYCHIATRY 1 USACACDA ATTN: ATZL-JAC-10 1 USACHCDA ATTN: ATZL-CAC-IM 1 USACAC ATTNE ATZE-CAC-IA 1 USACACDA ATTN: AT71-CACHA I USA FLECTRONIC WARFARE LAB CHIEF. INTELLIGENCE MATER DEVEL + SUPP OFF 1 USA ASCH DEVEL + STANDAHUIZA GP. U.K. 1 AFWAI /FIGR (CDLC) I USA RESEARCH AND DEVELOPMENT LABS CHIEF. BEHAV SCIENCES DIV. FOOD SCI LAB 1 TRAJANA ATTNI SAJS-OR I NAVAL AIR SYSTEMS COMMANU AITH: AIR-5313 1 ECOM ATTN: AMSEL_CT-0 1 USACHEC TECHNICK INFURMALIUN CENTER T USAARL LIBRARY 1 HUHAN RESOURCES RSCH URG (HUMPRO) 1 1 SEVILLE RESEARCH CORPORATION 1 USA IRAUOC SYSTEMS ANALYSIS ACTIVITY ATTN: ATAA-SL (TECH LIBRARY) I UNIFORMED SERVICES UNIT OF THE HEALTH SCI DEPARTMENT OF PSYCHIATRY I USA COMPUTER SYSTEMS COMMAND ATTN: COMMAND TECHNICAL LIBRARY H-9 1 HUMAN RESOURCES RSCH ORG (HUMRRO) 1 HUMRHU LIBRARY 1 EUSTIS DIRECTONATE, USAAMHUL TECHNICAL LIHRARY 1 RAND CORPURATION 1 RAND CURPURATION ATTN: LIBRARY U 1 FEDERAL AVIATION ADMINISTRATION ATTN: CAMI LINRARY ACC-4401 1 NAFEC LIBRARY, ANA-64 1 GRONINGER LIBRARY ATTN: ATZF-HS-L BLOG 1313 I CENTER FOR NAVAL ANALYSIS 1 NAVAL HEALTH RSCH CEN LIDHARY 1 NAVAL ELECTRONICS LAB ATTN: RESEARCH LIBRARY

24

and the second second

I NAVAL PERSONNEL & AND & CEN LIMHARY ATTN: COUE PIOS 1 AIR FORCE HUMAN RESOURCES LAB ATTN: AFHRL/UIS 1 HQ. FI. HUACHULA ATTN: TELH REF DIV I USA MCADEMY OF HEALTH SCIENCES STIMSON LIBRARY (DOCUMENTS) SCHOUL OF SYSTEMS AND LUGISTICS / 1 USAMERDC TECHNICAL LIBRARY DEPARTMENT OF THE NAVY TRAINING ANALYSIS AND EVALUATION OP 1 1 NATIONAL CENTER FOR HEALTH STATISTICS USMA DEPT OF BEHAVIOHAL SUI AND LEADERSHIP 1 1 OLD DOMINION UNIVERSITY PERFORMANCE ASSESSMENT LABORATORY T USA COMMAND AND GENERAL STAFF CULLEGE "ATTNE LIBRARY" USA (RANSPOR)ATION SCHOOL USA THANSP TECH INFO AND RSCH CEN ۲. NASA HU 1 1 NMRDI. PROGRAM MANAGER FUN HUMAN PERFURMANCE NAVAL MEDICAL & AND D CUMMAND (44) T USA "UNTNEEN TECHNICAL RESEARCH BRANCH LIBRARY 2 HQUA - USA MËD NSCH AND DEVEL COMMAND USA FIELD ARTY HU NAT CLEARINGHOUSE FOR MENTAL HEALTH INFU PARKLAWN BLOG 1 U OF TEXAS CEN FOR COMMUNICATION RSCH INSTITUTE FOR ULFENSE ANALYSES ٦. 1 USA IRAINING SUPPORT CENTER ATINI ATIC-NST-PA 1 AFHRI TECHNOLOGY DEC (H) I PURDUE UNIV DEPT OF PSYCHULUGICAL SCIENCES I USA MUBILITY EQUIPMENT & AND U CUMMANU ATTN: DRUME-ZG 1 HQ. USA MUN ATTN: ANPE-UE I DA UN ARMY RETRAINING BUE BESEARCH + EVALUATION DIVISION I CALSMAN HUMAN FACTORS AND THAINING CENTER 1 USA MEROMEDICAL RESPARCH LAB SCLENTIFIC INFORMATION CENTER 1 USAF SCHOOL OF AEROSPACE MEDICINE AEROMEDICAL LIHRARY (TSK-4) I US MILITARY ACADEMY DEPT. OF HISTORY, HUDG 601 1 USA INTELLIGENCE CEN AND SCH ATTN: SCHOOL LINNARY I USA INTELLIGENCE CEN AND SCH ATTNI ATSI-OP) MANINE COMPS INSTITUTE NAVAL SAFETY CENTER - 1 I USAAVNO AND FT. HUCKER AITNE ALGHES I US ANMY AVN THE LIBRARY AITH: CHIEF LIBRARIAN I USAAVNO ATTN: ATZU-U 1 US MILITARY ACADEMY DIRECTOR OF INSTITUTIONAL RSCH 1 USA LIR DEFENSE SCHOUL ALIN: A (SA-CU-MS 1 USAANS-LIBRARY-DUCUMENTS 1 USA LIR DEFENSE BOARD ATTN: FILLS REPUSITORY 1 USA INFANTRY BUAHD ATTN: ATZD-10-AL I USA INTELLIGENCE CEN AND SCH ATTNE ATSI-DT-SFL USA UNDNANCE CEN AND SCH ATTNE ATSL-TU-TAC USA ARMOR SCHOOL ATTN: ATZK+TI) USA ARMOR CENTER DIRECTORATE OF COMBAT DEVELOPMENTS 1 í 1 NAVAL POSTGRADUATE SCH ATTN: JUULEY KNUX LIBHART (CODE 1424) I USA TRANSPORTATION SCHOOL DEPITY ASST. COMMANDANT EULCA. TECHNOLOGY 1 USA SIGNAL SCHOUL AND FT. GORDON ATTN: ATZH-ET I USA WHOR CENTER + FT. KNUX UFFICE OF ARMOR FORCE MGT + STANDARDIZATION 1 CHIEF OF NAVAL EDUCATION AND ING 1 USA SIGNAL SCHUUL + FT. GURDON EUUCAIIUNAL TECHNOLÜGY DIVISION 1 HQ AIC/XPT() THAINING SYSTEMS DEVELOPMENT 5 USA INTELLIGENCE CEN AND SCH ATTNE ATSI-ERM 1 US ANMY ARMOR CENTER ATTN: ATZN-TU-PHU 1 USA HUARTERMASTER SCHOUL DIRECTURATE OF TRAINING DEVELOPMENTS 1 US CUAST GUARD ACAUEMY / 1 USA IRANSPORTATION SCHOOL DIRECTORATE OF TRAINING + DOCTRINE 1 USA INFANTRY SCHUDL LIHRARY / 1 USA INFANTRY SCHUOL ATTN: ATSH-1-V 1 US ANMY INFANTRY SCHOOL AITN: AISH_CU

```
I USA INFANTRY SCHUDL ATTN: ATSH-UOT-LRU
 I USA INFANTRY SCHUDL ATTN: ATSH-EV
 1 USA MP + CHEM SCHITNG CEN + FT. MCCLELLAN ATTN: ATZN-PTS
 1 USA MP + CHEM SCHITNE CEN + FT. MCCLELLAN DIR. COMBAT DEVELOPMENT
 I USA MP + CHEM SCHITNG CEN + FT. MCCLELLAN UIR. TRAINING DEVELOPMENT
 1 USA MP + CHEM SCHITNG CEN + FT. MCCLELLAN ATTHE ATZN-MP-ACE
 1 USA INSTITUTE OF AUMINISIRATION ATTN: RESIDENT TRAINING MANAGEMENT
 I USA FIELD ARTILLERY SCHOOL MORRIS SWETT LIBRARY
   USA INSTITUTE OF ADMINISTRATION ACADEMIC LIBRARY
 1
 1 USA WAR COLLEGE ATTN: LIDHARY
 1 USA FNGINEER SCHUDL LIHHARY AND LEARNING RESOURCES CENTER
 1 USA ARMOR SCHOUL (USARMS) ATTN: LIBRARY
 + ORGANIZATIONAL EFFECTIVENESS CEN + SCH ATTN: LIBRARIAN
 ) US ARMY INTELLIGENCE CENTER + SCHOOL ATTN: ATSI-TP
 1 US ANMY INTELLIGENCE CENTER + SCHOUL ATTN: ATSI-RM-M
 1 TIS ANMY INTELLIGENCE CENTER + SCHOOL ATTN: ATSI-TU-PM
                                                               ومرضورة والمتعمي
 1 US ARMY INTELLIGENCE CENTER + SCHOOL ATTN: ATSI-CD-CS
1 US ARMY INTELLIGENCE CENTER + SCHOOL ATTN: ATSI-ES
 1 DEPARTMENT OF THE AIR FORCE. AIR UNIVERSITY LIBRARY (ATC)
 1 HQ THADOC TRAINING DEVELOPMENT INSTITUTE
 P BRITISH EMHASSY BRITISH DEFENCE STAFF
 2 CANADIAN JOINT STAFF
 I COLS (W) LIBRARY
 I FRENCH ARMY ATTACHE
 1 AUSTHIAN EMBASSY DEFENSE, MILITARY AND ATR ATTACHE
 3 CANADIAN DEFENCE LIAISON STAFF ATTN: CUINSELLOR, DEFENCE & AND D
  ROYAL NETHERLANDS EMBASSY MILLIARY ATTACHE
 T CANADIAN FORCES BASE CORNWALLIS ATTNE PERSONNEL SELECTION
 2 CANADIAN FORCES PERSONNEL APPL RSCH UNIT
 1 ARMY PERSONNEL RESEARCH ESTABLISHMENT
 1 NETHFREANDS EMBASSY OFFICE OF THE AIR ATTACHE
 6 LINRARY OF CONGRESS "EXCHANGE AND GIFT DIV
  1 DEFENSE LECHNICAL INFORMATION CEN ATTN: DTIC-DDA-2
140 LINRARY OF CONVRESS UNIT DOCUMENTS EXPEDITING PROJECT
  1 US GOVERNMENT PRINTING OFC. LIARARY, PUBLIC DOCUMENTS DEPARTMENT.
  I US GOVERNMENT PRINTING OFC LINRARY AND STATUTORY, LIH DIV (SLL)
  1 THE WHMY LIBRARY ATTN: ARMY STUDIES SEC
  3 RUYAL ARMY EDUCATIONAL CORPS CENTRE ARMY SCHOOL OF TRAINING SUPPORT
                       and a set of the set of
                                   the second s
NUMBER OF ADDRESSERS 223
                                         TOTAL NUMBER OF CUPIES 407
```

26

. .

.

1 10-