

I

I

I

I

I

I

I

I

# DCW INDUSTRIES

DISTRIBUTION STATEMENT A Approved for public release; Distribution Unlimited

17 1981

LEVEL () - 70

3535 VENTURA BLVD., SUITE 207, SHERMAN OAKS, CALIF. 91423

817 13 008

Justinia rept. 1 apri- 30 July 757 AFOSR-TR-75-1398 DCW-R-03-03 EFFECTS OF SURFACE HEAT TRANSFER ON BOUNDARY-LAYER TRANSITION . by Thomas 10 Wilcox and 🗛 L. Chambers D.C. Van d July 1975 Prepared for AIR FORCE OFFICE OF SCIENTIFIC RESEARCH/NA 22209 Arlington, Virginia 9781 Sponsored by ADVANCED RESEARCH PROJECTS AGENCY V ARPA Order No 2980 Contract No.: | F44620-74-C-0048 (200003) Amount of Contract: \$15,609.00 Program Code: 5G10 Effective Date of Contract: April 1, 1975 Contract Expiration Date: July 30, 1975 Principal Investigator/Program Manager: David C. Wilcox, (213) 990-2682 DCW Industries DISTRIBUTION STATEMENT A 13535 Ventura Boulevard, Suite 207 Approved for public release; Sherman Oaks, California 91423 Distribution Unlimited (213) 990-2682 391224

#### ABSTRACT

Effects of surface heat transfer on boundary-layer transition are analyzed in a three-part study using the Saffman-Wilcox transition model. In the first part of the study, model predictions are compared with experimental data for cooled and heated aerodynamic boundary layers on smooth flat surfaces and for cooled aerodynamic boundary layers near the stagnation point of a roughened blunt body. Consistent with measurements, the model predicts, on the one hand, that heating destabilizes a smooth-surface aerodynamic boundary layer and, on the other hand, that cooling destabilizes a roughsurface aerodynamic boundary layer. Differences between predicted and measured transition-point locations are within experimental error bounds. Then, incipient transition conditions are determined for a small, heated hydrodynamic body. Again model predictions agree with measurements which indicate that relatively small amounts of surface heating have a strong stabilizing effect on hydrodynamic boundary layers. In the final part of the study, transition location is determined for a large hydrodynamic body; results indicate that large surface heating rates are not substantially more effective than smaller rates.,



# CONTENTS

PAGE

	ABSTRACT i CONTENTS i NOTATION i	i ii v
1.	INTRODUCTION	1
2.	FORMULATION 2.1 Equations of Motion 2.2 Neutral Stability Considerations	3 3 6
3.	<ul> <li>APPLICATIONS</li></ul>	10 10 14 19
4.	APPENDIX A: THERMODYNAMIC PROPERTIES	23 24
	APPENDIX B: HYDRODYNAMIC BODY SHAPE PARAMETERS	26
	REFERENCES	27

# SECTION

Γ

# NOTATION

SYMBOL

Ī.

I.

I.

I

E

T

Ī

- -

# DEFINITION

C,	Pressure coefficient, $(p-p_{\infty})/(1/2\rho U_{\infty}^2)$
c	Specific heat at constant pressure
e e	Specific turbulent energy
f	Parsons-Goodson-Goldschmied shape parameter
Γ F(η)	Nondimensional self-similar velocity profile
j	0 for two-dimensional flow; 1 for axisymmetric flow
k	Roughness height
k.	Parsons-Goodson-Goldschmied shape parameter
p	Pressure
Pr <sub>I</sub> , Pr <sub>T</sub>	Laminar and turbulent Prandtl numbers
$q_w, \overline{q}_w$	Surface heating rate; average value of q <sub>w</sub>
r	Radial distance from symmetry axis
r <sub>1</sub> , r <sub>n</sub>	Parson-Goodson-Goldschmied shape parameters
R	Empirical constant
Res, Rex	Reynolds number based on arclength, plate length
Ree	Reynolds number based on momentum thickness
Rev	Incipient transition Reynolds number based on $V^{1/3}$
S	Arclength
S	Parsons-Goodson-Goldschmied shape parameter
t	Parsons-Goodson-Goldschmied shape parameter
Т	Temperature
T <sub>t</sub>	Freestream total temperature
т <sup>ĭ°°</sup>	Freestream turbulence intensity
u,v	Velocity component in x,y direction
U	Boundary-layer-edge velocity
U	Freestream velocity
v	Body volume

iv

# NOTATION (cont.)

SYMBOL

I

[

[

# DEFINITION

Distance parallel to, normal to body surface
Parsons-Goodson-Goldschmied shape parameter
Empirical parameters
Empirical constants
Similarity variable
Momentum thickness
Karman's constant; thermal conductivity
Empirical parameters
Modified Polhausen pressure gradient parameter
Molecular viscosity
Kinematic viscosity
Fluid density
Empirical constants
Specific dissipation rate

# Subscripts

е	Boundary layer edge
t	Transition point
W	Surface
8	Freestream

#### 1. INTRODUCTION

In recent years, substantial progress has been made toward maintaining laminar flow, and hence low drag, over aerodynamic/ hydrodynamic bodies at practical flow speeds. In the case of aerodynamic bodies, the use of carefully designed airfoil shapes (e.g. to provide strong favorable pressure gradient) and the use of boundary-layer-control techniques (e.g. suction) has successfully delayed transition to chordlength Reynolds numbers,  $\text{Re}_{s_t}$ , of the order of 10 million. Even larger values of  $\text{Re}_{s_t}$  have been achieved for small hydrodynamic bodies through the use of surface heating and pressure gradient. For hydrodynamic bodies, extrapolations based on linear stability theory indicate that, with practicable amounts of surface heating, values of  $\text{Re}_{s_t}$  in excess of 200 million may be possible on relatively large hydrodynamic bodies<sup>1</sup>.

The reduction in drag which can be achieved by maintaining laminar flow over <u>any</u> vehicle is attractive because of the reduced power requirements to move the vehicle. However, a penalty is generally paid in maintaining laminar flow on <u>lifting</u> bodies in that a laminar boundary layer separates much more easily than does a turbulent boundary layer, resulting in a significant reduction in lift. Hence, maintaining laminar flow is practical mainly for <u>nonlifting</u> bodies. Submarines and torpedos or, more generally, hydrodynamic bodies fall into the latter class.

This study focuses on the observed pronounced effects of surface heat transfer on boundary layer transition. Most importantly, this report includes transition predictions based on a relatively new transition theory for small and large heated hydrodynamic bodies.

Section 2 presents the transition equations, including a modification needed to improve transition-prediction accuracy when surface heat transfer is present. Included in Section 3 are transition computations for various aerodynamic and hydrodynamic boundary layers. The concluding section summarizes results and conclusions.

1

1

## 2. FORMULATION

# 2.1 EQUATIONS OF MOTION

1

The Saffman-Wilcox transition model<sup>2-4</sup> is the basic tool used in this study to analyze effects of surface heat transfer on boundary-layer transition. The model's accuracy has previously been demonstrated for a wide variety of flows ranging from incompressible boundary layers to hypersonic blunt-body flows. These applications have tested the model's ability to predict transition sensitivity to effects of freestream turbulence, suction, surface roughness and pressure gradient. In all cases, accuracy acceptable for most engineering purposes has been obtained.

For incompressible boundary layers (i.e., for very small Mach numbers), the equations of motion which constitute the transition model are:

Mass Conservation

$$\frac{\partial}{\partial x}(r^{j}u) + \frac{\partial}{\partial y}(r^{j}v) = 0 \qquad (1)$$

Momentum Conservation

$$\rho u \frac{\partial u}{\partial x} + \rho v \frac{\partial u}{\partial y} = -\frac{dp}{dx} + \frac{1}{r^{j}} \frac{\partial}{\partial y} \left[ r^{j} \left( \mu + \frac{e}{\Omega} \right) \frac{\partial u}{\partial y} \right]$$
(2)

Energy Conservation

$$\rho u \frac{\partial (C_{p}T)}{\partial x} + \rho v \frac{\partial (C_{p}T)}{\partial y} = u \frac{dp}{dx} + \frac{1}{r^{j}} \frac{\partial}{\partial y} \left[ r^{j} \left( \frac{\mu}{Pr_{L}} + \frac{e/\Omega}{Pr_{T}} \right) \frac{\partial (C_{p}T)}{\partial y} \right] (3)$$

## Turbulent Energy

T

$$\rho u \frac{\partial e}{\partial x} + \rho v \frac{\partial e}{\partial y} = \left[ \alpha^* \left| \frac{\partial u}{\partial y} \right| - \beta^* \rho \Omega \right] \rho e + \frac{1}{r^j} \frac{\partial}{\partial y} \left[ r^j \left( \mu + \sigma^* \frac{e}{\Omega} \right) \frac{\partial e}{\partial y} \right]$$
(4)

Turbulent Dissipation Rate

$$\rho u \frac{\partial \Omega^{2}}{\partial x} + \rho v \frac{\partial \Omega^{2}}{\partial y} = \left[ \alpha \left| \frac{\partial u}{\partial y} \right| - \beta \rho \Omega \right] \rho \Omega^{2} + \frac{1}{r^{j}} \frac{\partial}{\partial y} \left[ r^{j} \left( \mu + \sigma \frac{e}{\Omega} \right) \frac{\partial \Omega^{2}}{\partial y^{2}} \right]$$
(5)

In Equations 1-5, x and y are orthogonal coordinates parallel to and normal to a body surface. The quantity r is the radial coordinate from the body's symmetry axis while j=0 for two dimensional flow and j=l for axisymmetric flow. The velocity components in the x and y directions are denoted by u and v; fluid density, temperature, pressure, specific heat, and viscosity are denoted by  $\rho$ , T, p, C<sub>p</sub>, and  $\mu$  respectively. The quantities e and  $\Omega$  are specific turbulent energy and specific turbulent dissipation rate; their ratio,  $e/\Omega$ , is the turbulent eddy viscosity.

Both air and water are considered in this study. The various thermodynamic properties for air are related through the perfect gas law and the Sutherland viscosity law. Appendix A lists the pertinent thermodynamic properties of water.

Several empirical parameters appear in Equations 1-5. For transitional flows, past studies  $^{2-4}$  have established the following values:

 $Pr_{T} = 0.89$   $\beta = 0.15$  ,  $\beta^{*} = 0.09$  $\sigma = 0.50$  ,  $\sigma^{*} = 0.50$ 

(6)

$$\alpha^* = 0.30 \left[ 1 - (1 - \lambda^*) (1 - \text{Re}_{\text{T}}/\text{R}_{\text{o}}) \right] \left[ (1 - \text{Re}_{\text{T}}/\text{R}_{\text{o}}) \right]$$
(7)

$$\alpha = .1638 \left[ 1 - (1 - \lambda)(1 - \text{Re}_{\text{T}}/\text{R}_{\text{O}}) H (1 - \text{Re}_{\text{T}}/\text{R}_{\text{O}}) \right]$$
(8)

where H(x) is the Heaviside stepfunction and  $\text{Re}_{\mathrm{T}}$  is turbulent Reynolds number defined by

$$Re_{\rm m} = e/\Omega\mu \tag{9}$$

Finally, the parameters  $\lambda^{\boldsymbol{*}}$  and  $\boldsymbol{R}_{O}$  are constants whose values are

$$\lambda^* = 0.105 , \mathbb{R}_{2} = 0.10 \tag{10}$$

The quantity  $\lambda$  depends upon the freestream turbulence level, T', and pressure gradient parameter,  $\Lambda$ , defined by

$$T' = 100 \sqrt{\frac{2}{3} \frac{e}{U_e^2}}$$
(11)

and

$$\Lambda = \frac{\rho_{\rm e}}{\rho_{\rm w}} \frac{\theta^2}{\nu_{\rm e}} \frac{dU_{\rm e}}{dx}$$
(12)

The functional dependence of  $\lambda$  upon  $\Lambda$  and T' is

$$\lambda = .105 (1 + 2H(\Lambda) ) = \exp [-40\Lambda] \exp [-3T^{2}]$$
 (13)

Equations 1-3 are the time-averaged conservation equations with classical eddy-viscosity and eddy-heat-diffusivity closure approximations. Equations 4 and 5 are ronlinear diffusion equations for e and  $\Omega$  which provide a description of the growth of disturbances in a laminar flow up to, through, and beyond transition. Wilcox<sup>2</sup> presents a thorough discussion of the way in which the model equations are used to predict boundary-layer transition. Boundary conditions suitable for flow over both smooth and rough surfaces are given by Wilcox and Chambers<sup>4</sup>.

## 2.2 NEUTRAL STABILITY CONSIDERATIONS

Qualitative features of model-predicted transition can be conveniently determined by dropping the convection and diffusion terms in the turbulent-energy equation (Equation 4). In doing this we can determine the neutral-stability point which is defined as the point in a boundary layer where turbulent energy generation,  $\alpha^* \rho e |\partial u / \partial y|$ , just balances turbulent energy dissipation,  $\beta^* \rho^2 \Omega e$ . Hence, neutral stability is defined by the following condition:

$$\max_{\mathbf{y}} \frac{\alpha^*}{\beta^*} \frac{|\partial u/\partial y|}{\rho \Omega} = 1$$
(14)

Then, noting for laminar boundary layers that  $\Omega$  and  $\alpha^{\textbf{*}}$  are approximately

$$\Omega \stackrel{*}{=} \frac{20}{\beta} \frac{\mu}{\rho^2 y^2}$$
(15)

$$\alpha^{*=} 0.30\lambda^{*} \tag{16}$$

Equation 14 simplifies to

$$\max_{\mathbf{y}} \frac{\mathbf{y}^2}{\nu} \left| \frac{\partial \mathbf{u}}{\partial \mathbf{y}} \right| = \frac{40}{\lambda^*}$$
(17)

For zero-pressure-gradient boundary layers in air, the velocity distribution can be written as

$$u = U_{\rho}F(\eta) \tag{18}$$

where

 $n \equiv y \sqrt{\frac{U_{e}}{v_{W}x}}$ (19)

Using Equations 18 and 19, Equation 17 simplifies to the following:

$$\sqrt{\frac{U_{ex}}{v_{w}}} = \frac{40/\lambda^{*}}{\max_{\eta} \eta^{2} |\frac{\partial F}{\partial \eta}|}$$
(20)

Now for incompressible flow,  $F(\eta)$  is only weakly dependent upon surface heat transfer. Hence, Equation 20 implies that the neutral stability Reynolds number,  $U_e x/v_w$ , varies inversely as  $\lambda^{*2}$ . Experiments<sup>5</sup> indicate that transition Reynolds number,  $U_e x_t/v_w$ , is inversely proportional to  $(T_w/T_e)^2$ . Assuming that the transition Reynolds number is proportional to the neutral stability Reynolds number (as it often is) implies that  $\lambda^*$ should be proportional to  $T_w/T_e$ .

Computations with  $\lambda^*$  independent of  $T_w/T_e$  verified that such a dependence is needed. The unmodified model predicted that heating (cooling) has a stabilizing (destabilizing) effect on aerodynamic boundary layers, in contrast to the measured destabilizing (stabilizing) effect. These predictions were unsurprising as Shamroth and McDonald<sup>5</sup> find a similar reversal in predicted transition sensitivity to heating and cooling with their turbulence-model transition method. Shamroth and McDonald resolve the problem by making a parameter similar to

 $\lambda^*$  an increasing function of  $T_W/T_e$ . While this model revision is sufficient to yield accurate transition location for aerodynamic boundary layers, it is inadequate for the hydrodynamic case. That is, according to Equation 20, transition location,  $x_t$ , is proportional to  $\mu_W/\lambda^{*2}$ . For a liquid,  $\mu_W$  varies as  $T_W^{-8}$  near room temperature (see Appendix A. hence, assuming  $\lambda^*$  is proportional to  $T_W$  would imply that  $x_t$  varies as  $T_W^{-10}$ . Therefore, increasing surface temperature would decrease  $x_t$ , i.e., heating would destabilize a hydrodynamic boundary layer. Since heating stabilizes such a boundary layer, a different modification is clearly needed.

The parameter  $\lambda^*$  should more appropriately depend upon  $\mu_W/\mu_e$ . On the one hand,  $\mu_W/\mu_e$  increases as  $T_W/T_e$  increases for air, while, on the other hand,  $\mu_W/\mu_e$  decreases as  $T_W/T_e$  increases for water. Thus, if  $\lambda^*$  were proportional to some power of  $\mu_W/\mu_e$ , the model could accurately predict effects of surface heat transfer on both aerodynamic and hydrodynamic boundary layer transition. Since  $\mu \sqrt{T^{3/4}}$  for air, the following revised form of Equation .0 is proposed:

$$\lambda^* = 0.105 \left( \mu_w / \mu_e \right)^{4/3}$$
 (10a)

An additional, less obvious, modification is needed. Note that the parameter  $\lambda$  partially controls the rate at which disturbances are amplified beyond the neutral stability point. Furthermore, if  $\lambda$  ever becomes sufficiently large (relative to  $\lambda^*$ ) so that dissipation-rate production,  $\alpha\rho\Omega^2 |\partial u/\partial y|$ , overtakes dissipation-rate dissipation,  $\beta\rho^2\Omega^3$ , (see Equation 5) before the neutral stability point is reached, transition may never occur. Thus, if  $\lambda$  remains

unaltered, the possibility exists that a finite amount of cooling (heating) will cause an aerodynamic (hydrodynamic) boundary layer to forever remain laminar, a physically unrealistic prediction. Hence, Equation 13 must be replaced by:

$$\lambda = .105(\mu_{W}/\mu_{e})^{4/3} \left\{ 1 + 2H(\Lambda)[1 - \exp(-40\Lambda)]\exp(-3T'^{2}) \right\}$$
(13a)

All of the computations presented in the next section have been performed using the transition model defined by Equations 1 through 9, 10a, 11, 12, and 13a; as noted earlier, appropriate surface boundary conditions are given by Wilcox and Chambers<sup>4</sup>.

# 3. APPLICATIONS

In the first part of this section, the transition model is used to predict transition sensitivity to sur?ace heat transfer for smooth- and rough-surface aerodynamic boundary layers; computed transition-point locations are compared with corresponding experimental data. Then, effects of surface heating on a small hydrodynamic body are computed; qualitative comparisons are made with experimental data. Finally, transition location is predicted on a large hydrodynamic body.

# 3.1. HEATED AND COOLED AERODYNAMIC BOUNDARY LAYERS

One of the easiest of all flows to analyze is the incompressible flat-plate boundary layer (FPBL). Furthermore, analyzing this flow provides a good test of the transition model as detailed measurements have been made<sup>6</sup> to determine transition sensitivity to surface heat transfer. Using an incompressible version of DCW Industries' EDDYBL computer code<sup>2</sup>, transition computations were performed for an incompressible FPBL with

$$0.5 < T_{\rm u}/T_{\rm c} < 3.0$$
 (21)

As in all computations in this study, the value of  $\Omega$  at the boundary-layer edge,  $\Omega_{\rm e},$  was given by

$$\Omega_{0} = .0185 U_{0}^{2} / \mu_{0}$$
(22)

a value generally used in EDDYBL transition calculations. Results of the computations are shown in Figure 1; experimental



Figure 1. Computed and measured effects of surface heating and cooling on boundary layer transition in air;  $(\text{Re}_{x_t})_w$  = plate-length transition Reynolds number based on surface conditions;  $(\text{Re}_{x_t})_o$  = the value of  $\text{Re}_{x_t}$  without surface heat transfer.

data of Zysina-Molozhen and Kuznetsova<sup>6</sup> are included in the figure for comparison.

Because the freestream turbulence level in the experiments was not available, computations were done for a relatively high level (T'=1.25%) and for a relatively low level (T'=.03%). As shown in the figure, freestream turbulence level has only a slight effect on transition Reynolds number based on surface conditions,  $(\text{Re}_{xt})_w \equiv U_e x_t / v_w$ . Consistent with the measurements, computed  $(\text{Re}_{xt})_w$  is approximately inversely proportional to  $(T_w/T_e)^2$ ; computed values of  $(\text{Re}_{xt})_w$  generally are within about 20% of corresponding measured values.

A second, more subtle, test of the theory is to apply the equations to rough-wall aerodynamic boundary layers. Surface cooling can actually reverse its stabilizing role to one of destabilization when the surface is rough. The explanation for this phenomenon is well understood. The destabilization occurs because cooling thins the boundary layer, thus making the roughness look larger relative to a boundary-layer thickness such as momentum thickness,  $\theta$ . Hence, the surface looks rougher, whereby transition occurs earlier.

To test the model's ability to predict this phenomenon, computations were performed for Mach 5 airflow past a roughened spherical body with nose radius of 2.5 inches; roughness heights, k, between 1.5 mils and 10 mils were used in the computations. Freestream unit Reynolds number ranged from 3 to 10 million per foot. (The compressible version of the model equations<sup>4</sup> was used for these calculations). The ratio of surface temperature to freestream total temperature,  $T_{t_n}$ ,

was varied from 0.2 to 0.8. Figure 2 compares results of the computations with a correlation of experimental data<sup>7</sup>. Consistent with the measured effect, momentum thickness Reynolds number at transition,  $\operatorname{Re}_{\theta_t}$  increases with decreasing surface temperature.





# 3.2 HEATED HYDRODYNAMIC BOUNDARY LAYERS ON SMALL BODIES

The second round of applications is to a small heated hydrodynamic body. The body, shown in Figure 3, is a Parsons-Goodson-Goldschmied<sup>8</sup> (PPG) minimum-drag hull shape which will be referred to as the H-2 body; the PPG body parameters are given in Appendix B. The objective of the computations was to determine incipient transition conditions for various surface temperatures. By definition, incipient transition occurs when the transition point is located at the maximum body radius.

All computations were performed with the following conditions specified:

Ambient Temperature, T <sub>e</sub>	$= 71^{\circ} F$
Roughness Height, k	= 16 µin
Freestream Turbulence, T'	= .01%
Freestream Dissipation Rate, $\Omega_{ m e}$	$= .0185 U_{e}^{2}/\mu_{e}$

The pressure distribution was obtained from the Douglas-Neumann<sup>9</sup> potential flow program; Figure 4 shows the computed pressure coefficient,  $c_p$ , defined by

$$c_{\rm p} = (p - p_{\rm m}) / (1/2\rho U_{\rm m}^2)$$
 (23)

In the figure, z is axial distance from the stagnation point. Three series of computations were performed in which surface temperature was held constant at values of 71°F, 76°F, and 81°F. Incipient transition Reynolds number,  $\text{Re}_V$  (based on freestream flow conditions and V<sup>1/3</sup> where V is body volume), was computed for each value of  $T_w$ . Results of the calculations are summarized in Table 1; in addition to  $\text{Re}_V$ , the table gives freestream velocity,  $U_\infty$ , transition Reynolds number based on





arclength,  $\text{Re}_{s_t}$ , and average heating rate,  $\overline{q}_w$ , defined by

$$\bar{q}_{w} = \frac{1}{s_{t}} \int_{0}^{s_{t}} q_{w}(s) ds \qquad (24)$$

In Equation 24,  $s_t = 4$  feet (the maximum radius point), and  $q_w(s)$  is the local heat transfer. Figure 5 shows computed  $\text{Re}_V$  as a function of  $T_w - T_e$  and  $\overline{q}_w$ . As can be seen from the figure, heating stabilizes the boundary layer and hence increases the value of  $\text{Re}_V$ . This prediction is qualitatively consistent with the observed stabilizing effect of surface heating when the fluid is a liquid. The magnitude of the effect is also realistic<sup>1</sup>.



T <sub>w</sub> -T <sub>e</sub> (°F)	$\overline{q}_{W}(\frac{kwatts}{ft^{2}})$	$U_{\infty}(knots)$	10 <sup>-6</sup> Re <sub>V</sub>	10 <sup>-6</sup> Re <sub>st</sub>
0	0.00	25.3	9.4	18.2
5	0.31	35.0	13.0	24.5
10	1.30	47.4	17.6	33.8

An interesting feature of the predictions is revealed in Figure 5. Specifically,  $\text{Re}_V$  increases approximately linearly with  $\text{T}_w$ -T<sub>e</sub> for the range of temperatures considered. However,  $\text{Re}_V$  increases much less rapidly with  $\overline{q}_w$ . Hence, increasing the heating rate beyond about 2 kwatts/ft<sup>2</sup> may not yield substantial increases in  $\text{Re}_V$ .



# 3.3 HEATED HYDRODYNAMIC BOUNDARY LAYERS ON LARGE BODIES

The final application of the transition model is to a large heated hydrodynamic body. Again, a PPG hull shape, referred to as the R-9a body, is used (see Appendix B). The objective of these computations was to determine transition point location for specified flow conditions.

Two computations were performed; in one, the freestream flow speed,  $U_{\infty}$ , was 35 knots and in the other  $U_{\infty}$  was 30 knots. In both computations, the following conditions were imposed:

Ambient Temperature, T	= 55°F
Surface Temperature, T.	= 85°F
Roughness Height, k	= 16 µin
Freestream Turbulence, T'	= .01%
Freestream Dissipation Rate, $\Omega_{a}$	= .0185 $U_e^2/\mu_e$

Figure 6 shows the Douglas-Neumann-computed pressure distribution.

Table 2 and Figure 7 summarize results of the computations. For both flow speeds, transiton occurs well upstream of the maximum radius. Computed arclength transition Reynolds numbers,  $\text{Re}_{s_t}$ , are not much larger than the value achieved on the H-2 body with  $\overline{q}_w = 1.30$  kwatts/ft<sup>2</sup> (see Table 1). Noting the heating rates involved, the predictions are consistent with results of the preceding subsection.



$U_{\infty}$ (knots)	$\overline{q}_{w}(\frac{kwatts}{ft^{2}})$	s <sub>t</sub> (ft)	10 <sup>-6</sup> Rest
30 35	1.40 2.08	13.9 11.3	49.1 46.1

Table 2. Computed Transition Conditions for the R-9a Body.

<sup>\*</sup>To facilitate comparison with the H-2 body heating rates, the value of  $\overline{q}_{W}$  has been computed by integrating from s=0 to s=4 feet (see Equation 24).



#### 4. SUMMARY AND CONCLUSIONS

Results reported in Section 3 demonstrate the transition model's accuracy for boundary layers with surface heat transfer, provided nonuniform viscosity effects are taken into account (Subsection 2.2). With no parameter adjustment, the model accurately predicts transition Reynolds number for (a) incompressible smooth-wall aerodynamic boundary layers with surface heating and cooling, (b) cooled roughwall boundary layers on blunt bodies in a hypersonic airstream, and (c) heated hydrodynamic boundary layers on small bodies.

Results of the hydrodynamic computations agree with the measured strong boundary-layer stabilization attending small amounts of surface heating. The model also predicts that large amounts of heating are not significantly more effective in delaying transition than the smaller rates considered in the H-2 body computations of Subsection 3.2. The larger R-9a body computations support this prediction.

#### APPENDIX A THERMODYNAMIC PROPERTIES OF WATER

The following thermodynamic properties of water are pertinent to boundary layer transition: mass density ( $\rho$ ), specific heat ( $C_p$ ), thermal conductivity, ( $\kappa$ ), molecular viscosity ( $\mu$ ), and laminar Prandtl number ( $Pr_L$ ). Values used in this study for these quantities have been obtained from Schlichting<sup>10</sup> and are valid for temperatures ranging from about 40°F. to 110°F.

Mass density, specific heat, and thermal conductivity are approximately constant and have the following values:

$$\rho = 1.936 \quad lbf \cdot sec^2/ft^4 \qquad (A1)$$

$$C_p = 1 \qquad Btu/lbf \cdot \circ F \qquad (A2)$$

$$\kappa = 0.35 \qquad Btu/ft \cdot hr \cdot \circ F \qquad (A3)$$

Viscosity and Prandtl number, by contrast, are strongly temperature dependent over this range of temperatures. An approximate polynomial fit to the Schlichting data was used to calculate  $\mu$  in the computations of Section 3, i.e.,

 $\mu = 7.943 \cdot 10 \quad (T/600) \quad 1bf \cdot sec/ft^2 \quad (A4)$ 

with temperature, T, in degrees Rankine. Finally, the laminar Prandtl number follows from its definition, namely,  $Pr_L = \mu C_p / \kappa$ , wherefore,

$$Pr_{T} = 2.51(T/600)^{-8}$$
(A5)

Figure Al compares Equations A4 and A5 with the measured dependences of  $\mu$  and  $\text{Pr}_{\rm L}$  upon temperature.



#### APPENDIX B HYDRODYNAMIC BODY SHAPE PARAMETERS

The two hydrodynamic bodies analyzed in this study are specified in terms of the eight dimensionless parameters used by Parsons, Goodson, and Goldschmied<sup>8</sup>. The values of these parameters are as follows:

Parameter	H-2 Body	R-9a Body
f	4.450	5.000
x	0.427	0.600
k,	2.715	4.000
r	0.260	0.050
r	0.740	0.700
S,	1.650	1.750
x,	0.595	0.800
t	0.180	0.150

Additionally, the H-2 body is 9.457 feet long and has a volume of 14.5 cubic feet; the R-9a body is 55 feet long and has a volume of 2500 cubic feet.

#### REFERENCES

- Personal communication between D.C. Wilcox of DCW Industries and C. Gazley of the RAND Corp (May 1975).
- 2. Wilcox, D. C., "Turbulence-Model Transition Predictions for Blunt-Body Flows," AFOSR-TR-74-1714 (July 1974).
- Wilcox, D.C., "Turbulence Model Transition Predictions," AIAA Journal, Vol 13, No 2, pp 241-243 (1975).
- Wilcox, D.C. and Chambers, T.L. "Further Refinement of the Turbulence-Model Transition-Prediction Technique," DCW-R-03-02 (July 1975).
- Shamroth, S.J. and McDonald, H., "Assessment of a Transitional Boundary Layer Theory at Low Hypersonic Mach Numbers," NASA CR-2131 (November 1972).
- Zysina-Molozhen, L.M. and Kuznetsova, V.M., "Investigation of Turbulent Conditions in a Boundary Layer," Thermal Engineering (Teploenergetika), Vol 16, No 7, pp 16-20 (1969).
- 7. Anderson, A.D., "Interim Report Passive Nosetip Technology (PANT) Program, Volume 2, Summary of Experimental Results," Appendix A, Aerotherm Report 74-100 (1975).
- Parsons, J.S., Goodson, R.E. and Goldschmied, F.R., "Shaping of Axisymmetric Bodies for Minimum Drag in Incompressible Flow," Journal of Hydronautics, Vol 8, No 3 (July 1974).
- Smith, A.M.O. and Pierce, J., "Exact Solution of the Neumann Problem. Calculation of Non-Circulatory Plane and Axially Symmetric Flows about or within Arbitrary Boundaries," Report ES26988, Douglas Aircraft Co, Long Beach, CA (April 1958).
- 10. Schlichting, H., <u>Boundary Layer Theory</u>, Fourth Edition, McGraw-Hill, p 8 and p 294 (1960).

#### DISTRIBUTION

Air Force Office of Scientific Research General Electric 1400 Wilson Blvd. 3198 Chestnut St Arlington, Virginia 22209 Philadelphia, Pe

Prototype Development Associates, Inc. 1740 Garry Avenue, Suite 201 Santa Ana, California 92705 Attn: J. Dunn

et Propulsion Laboratory Gas Dynamics Section 4800 Oak Grove Drive Pasadena, California 91109 Attn: J. Kendall L. Mack

University of Southern California Dept. of Aerospace Engineering University Park Los Angeles, California 90007 Attn: J. Laufer

Lockheed Missiles & Space Co. Continental Building, Suite 445 101 Continental Blvd. El Segundo, California 90245 Attn: T. Fortune

AEDC AFSC, USAF Arnold Air Force Station Tennessee 97389 Attn: J. Miller

Flow Research, Inc. 5959 West Century Boulevard, Suite 912 Los Angeles, California 90045 Attn: D. Ko

Calspan Corporation P.O. Box 235 Buffalo, New York 14221 Attn: M. Holden

Philco-Ford Corporation Space & Reentry Systems Ford Road Newport Beach, California 92663 Attn: A. Demetriades C. White

Avco Corporation 201 Lowell Street Wilmington, Massachusetts 01887 Attn: A. Pallone V. DiCristina General Electric 3198 Chestnut Street Philadelphia, Pennsylvania 19101 Attn: A. Martellucci

McDonnell-Douglas Corporation 5301 Bolsa Avenue Huntington Beach, California 92647 Attn: K. Kratsch

Physical Sciences, Inc. 18 Lakeside Office Park Wakefield, Massachusetts 01880 Attn: M. Finson

Director of Defense Research and Engineering (Strategic Weapons) The Pentagon Washington, D.C. 20330 Attn: R. Ruffine

Department of Aerospace & Mechanical Engineering Sciences University of California P.O. Box 109 La Jolla, California 92038 Attn: S. Penner

Defense Documentation Center Cameron Station Alexandria, Virginia 22314

Applied Physics Laboratories Johns Hopkins University Silver Spring, Maryland 20390 Attn: Dr. Stone

Defense Advanced Research Projects Agency 1400 Wilson Boulevard Arlington, Virginia 22209 Attn: TIO K. Kresa R. Moore Air University Library

Maxwell Air Force Base Alabama 36112 Attn: AUL 3T-64-316

Acurex Corporation 485 Clyde Avenue Mountain View, California 94040 Attn: R. Kendall R. Rindal

# DISTRIBUTION (continued)

Avco Everett Research Laboratory 2385 Revere Beach Parkway Everett, Massachusetts 02149 Attn: K. Wray

Boeing Company Seattle, Washington 98124 Attn: R. Montgomery

Battelle Memorial Institute 505 King Avenue Columbus, Ohio 43201 Attn: Defender (E. Unger)

Commanding Officer Ballistics Research Laboratories Aberdeen Proving Ground, Maryland 21005 Wright-Patterson Air Force Base Attn: C. Murphy

Arnold Engineering Development Center Von Karman Gas Dynamics Facility Tullahoma, Tennessee 37389 Attn: J. Hahn

Office of Naval Research Department of the Navy Washington, D.C. 20360 Attn: Phys, Br. (Code 421) Dr. Isakson

TRW Systems, Inc. One Space Park Redondo Beach, California 92078 Attn: L. Hromas

U.S. Army Advanced Ballistic Missile Defense Agency Commonwealth Building 1320 Wilson Boulevard Arlington, Virginia 22209 Attn: CRDABM-RD (Street G) RP (Rep) DT (Rep)

Massachusetts Institute of Technology Lincoln Laboratory 244 Wood Street Lexington, Massachusetts 02173 Attn: BMRS Project

Facility P.O. Box 33 College Page, Maryland 20740 Attn: Acquisitions ER(S-AK-DL)

California Institute of Technology Pasadena, California 91109 Attn: L. Lees H. Liepmann P. Saffman Arnold Engineering Development Center Tullahoma, Tennessee 97389 Attn: J. Miller AF Cambridge Research Laboratory Lawrence G. Hanscom Field Bedford, Massachusetts 01730 Attn: CRMXLR, STOP 29 Air Force Flight Dynamics Laboratory Ohio 45433 Attn: M. Buck W. Hankey J. Shang **r**. Knight Air Force Materials Laboratory Wright-Patterson Air Force Base Ohio 45433 Attn: G. Jumper K. Stetson Air Force Weapons Laboratory Kirtland Air Force Base Albuquerque, New Mexico 87115 Attn: WLRA/Capt. Koziol J. Ortwerth Commanding General U.S. Army Safeguard Systems Command P.O. Box 1500 Huntsville, Alabama 35807 Attn: SENSC-Y U.S. Naval Surface Weapons Center White Oak, Silver Springs, Maryland 20910 Attn: Librarian D. Reda C. Lyons R. Phinney Institute for Defense Analysis Science and Technology Division NASA Scientific & Technical Information 400 Army-Navy Drive Arlington, Virginia Attn: H. Liepmann 22202

#### DISTRIBUTION (continued)

Case Western Reserve University Cleveland, Ohio Attn: E. Reshotko NASA Langley Research Center Hampton, Virginia 23665 Attn: I. Beckwith J. Harris D. Bushnell
C. Anderson RAND Corporation 1700 Main Street Santa Monica, California 90406 Attn: C. Gazley NASA Ames Research Center Moffett Field, California 94035 Attn: M. Rubesin J. Marvin B. Baldwin

Space & Missile Systems Organization P.O. Box 92960 Worldway Postal Center Los Angeles, California 90009 Attn: T. Hopkins E. Taylor

The Aerospace Corporation P.O. Box 92957 Los Angeles, California 90009 Attn: W. Portenier

Naval Underwater Systems Center Newport, Rhode Island 02840 Attn: G. Christoph

Lawrence Livermore Laboratories P.O. Box 808 Livermore, California 94550 Attn: A. Buckingham

DCAS 14450 Erwin Street Van Nuys, California 91408 Attn: H. Moses U.S. Naval Weapons Laboratory Dahlgren, Virginia 22448 Attn: Ccde KRT (MODE)

Los Alamos Scientific Laboratory Group T-3, Mail Stop 216 P.O. Box 1663 Los Alamos, New Mexico 87544 Attn: J. Ramshaw

University of California, Berkeley College of Engineering Berkeley, California 94720 Attn: S. Berger

Stanford University Department of Mechanical Engineering Palo Alto, California 94305 Attn: W. Reynolds

DEDADT MACHINENTATION	PAGE	READ INSTRUCTIONS
REFORT DOCUMENTATION	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
AFOSR-TR-75-1398	_ADA015938	AD+A101624
TITLE (and Subittie)		S. TYPE OF REPORT & PERIOD COVERED
EFFECTS OF SURFACE HEAT	TRANSFER ON	INTERIM
BOUNDARY-LAYER TRANSITION	N	6. PERFORMING ORG. REPORT NUMBER
		DCW-R-03-03 -
AUTHOR(.)		8. CONTRACT OR GRANT NUMBER(#)
DAVID C. WILCOX THOMAS L. CHAMBERS		F44620-74-0-0048 🗸
PERFORMING ORGANIZATION NAME AND ADORES	S	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
DCW INDUSTRIES		681307
13535 VENTURA BOULEVARD,	SUITE 207	9781-02 61102F
SHERMAN OAKS, CALIFORNIA	91425	12. REPORT OATE
AIR FORCE OFFICE OF SCIENTIFIC	C RESEARCH/NA	July 1975
1400 WILSON BOULEVARD		13. NUMBER OF PAGES
ARLINGTON, VIRGINIA 22209	ant from Controlling Office)	15. SECURITY CLASS. (of this report)
MONITORING AGENCY NAME & ADDRESS(17 differ		UNCLASSIFIED
		15. OECLASSIFICATION/OOWNGRADING SCHEDULE
. DISTRIBUTION STATEMENT (of the abstract enter	ed in Block 20, 11 dillerent fr	om Report)
8. SUPPLEMENTARY NOTES		
BOUNDARY LAYER TRANSITION TURBULENCE PREDICTION TRANSITION PREDICTION BLUNT-BODY FLOWS SURFACE HEATING	and identify by block numbe DN	r)
0. ABSTRACT (Continue on reverse side II necessery	and identify by block number	n 
Effects of surface heat to are analyzed in a three-part tion model. In the first part compared with experimental of boundary layers on smooth fi boundary layers near the sta body. Consistent with measu	transfer on bou t study using t art of the stud data for cooled lat surfaces ar agnation point urements, the r	Indary-layer transition the Saffman-Wilcox transi- dy, model predictions are d and heated aerodynamic nd for cooled aerodynamic of a roughened blunt model predicts, on the or
D FORM 1473 EDITION OF 1 NOV 65 IS DE	SOLETE	
I JAN 73 14/ J CONTON OF NOT COTS OF		UNULADDIFIED

## UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered)

hand, that heating destabilizes a smooth-surface aerodynamic boundary layer and, on the other hand, that cooling destabilizes a rough-surface aerodynamic boundary layer. Differences between predicted and measured transition-point locations are within experimental error bounds. Then, incipient transition conditions are determined for a small, heated hydrodynamic body. Again model predictions agree with measurements which indicate that relatively small amounts of surface heating have a strong stabilizing effect on hydrodynamic boundary layers. In the final part of the study, transition location is determined for a large hydrodynamic body; results indicate that large surface heating rates are not substantially more effective than smaller rates.

