UNCLAS	SSIFIED	SEP 6	1	 		301766			NL.	10107	
	0F2 4064.84	, ,									
						and the second sec		1			
				1. S.				No.		37	
	€_2 1	4) 1	V.								
							·				

- Version Pol 1. 5 AD-A106484 Metropolitan Washington Airports Pelic: supplement to The August 1900 environmental impact statement, finsl. **7**7 X Revense i gar zar ar vore and Audreas Department of Transportation 4 Federal Aviation Administration 6 Washington, D. C. 20590 Y24 21 8.2 C 12 Section to agence have and Apprets Department of Transportation (A.M.M. Federal Aviation Administration A 800 Independence Avenue, S. W. Washington, D. C. 20591 A 15. Supplementary hotes 16. Abstract This Final Supplement to the August 1980 Environmental Impact Statement considers 2 the potential environmental impacts of additional policy alternatives that are being added to the five alternatives previously assessed. A revised policy is being adopted, reflecting the Department's objective for establishing how Washington National and Dulles International Airports will contribute to meeting the overall aviation needs of the Metropolitan area in the 1980s and beyond. The revised policy considers: Passenger limit; Operating hours; Scheduling limitations; Noise limitations; Aircraft limitations; Nonstop limitations. A Metropolitan Washington Airport Policy will be selected from. within the range of these alternatives. 17. Kay Words 18. Distribution Statement Document is available to the U.S. Public Environmental Impact Statements; throught the National Technical Information Washington National Airport; Dulles Service, Springfield, Virginia 22161 International Airport; Airports; Noise; Emissions; Policies. 20. Security Class." ini this page 21. No. of Peyes 12. Frite 19 Security Classif of this report 118 Unclassified Unclassified Reproduction of completed | 37 DESTRIBUTION STATEMENT A Form DOT F 1700.7 (8-72) Approved for public release; 11 - 11 Distribution Unlimited



¥

U.S. Department of Transportation Federal Aviation Administration

Metropolitan Washington Airports Policy Supplement to the August 1980 Environmental Impact

Final

Statement

September 1981

81 10 27 268

TABLE OF CONTENTS

		Page
Table	e of Contents	i
List	of Figures	ii
List	of Tables	iii
Sect	ion	
I.	Summary	I-1
II.	Description and Purpose of Federal Actions	II-1
	Purpose	II-1
	Revised Policy	11-1
	Background	II-3
	Basic Principles	II-11
	Need for Supplement	II-13
III.	Present Conditions and Impacts of Policy Alternatives	III-1
	Introduction	III-1
	Noise	111-1
	Air Quality	III-41
	Surface Access	111-50
	Energy	III-51
IV.	Unavoidable Adverse Effects and Actions Taken to Minimize Harm	IV-1
v.	Relationship Between Short-Term Uses of Man's Environment and the Maintenance and Enhancement of Long-Term Productivity	V-1
VI.	Irreversible and Irretrievable Commitments of Resources	VI-1
VII.	List of Preparers	VII-1
VIII	Responses to Substantive Comments on Draft Supplement to the August 1980 Environmental Impact Statement	IX-1
IX.	Comments received on Draft Supplement to the August 1980 Environmental Impact Statement	X-1

i

List of Figures

Ľ.

	Page
Figure 1 - National Airport 1981 Ldn Contours, Existing Conditions (Base Case)	111-6
Figure 2 - National Airport 1981 Ldn Contours, Controlled Activity with Noise Restrictions-No Widebody Aircraft	III-14
Figure 3 - Washington National Airport, 1981 Ldn Contours, Based on Level of Operations on July 31, 1981	III-16
Figure 4 - National Airport 1990 Ldn Contours, Controlled Activity with Noise Restrictions-80 dBA Single Event Limit	III-18
Figure 5 - Washington National Airport, Twin-Engine Piston Aircraft 72 dBA Single Event Noise Contours, North and South Departures	111-24
Figure 6 - Washington National Airport, Twin-Engine Piston Aircraft 72 dBA Single Event Noise Contour, Anacostia River Departure	111-25
Figure 7 - Washington National Airport, Medium Twin-Engine Turboprop Transport 72 dBA Single Event Noise	111-34

Contour, North and South Arrivals

ii

List of Tables

				Page
Table I	-	Additional Alternative Policies for National Airport		III-3
Table II	-	Washington National Airport Aircraft Operations Forecasts		III - 5
Table III	-	Noise Impacts at Washington National	Airport	111-7
Table IV	-	General Aviation Nighttime Operations Washington National Airport	,	III-21
Table V	-	Comparative Noise Levels		111-26
Table VI	-	Estimated Maximum A-Weighted Sound Le Airplanes at Part 36 Appendic C Locat Takeoff	vels for ions,	111-28
Table VII	-	Estimated Maximum A-Weighted Sound Le Airplanes at Part 36, Appendix C Loca Takeoff	vels for tions,	111-29
Table VIII	-	Estimated Maximum A-Weighted Sound Le Airplanes at Part 36, Appendix C Loca Approach	vels for tions,	111-35
Table IX	-	Estimated Maximum A-Weighted Sound Le Airplanes at Part 36, Appendix C Loca Approach	vels for tions,	111-37
Table X	-	Total Emissions Inventory		111-44
Table XI	-	Forecast of Air Carrier Operations at Washington National Airport		III - 58
Table XII	-	Air Carrier Fuel Consumption at Washin National Airport (gallons per day)	ngton	111-59
Table XIII	-	Index of Air Carrier Fuel Consumption Washington National Airport	at	111-60
			Accession NTIS GR DTIC TAB Unannoum Justific By Distribu	A%I 2 ced 2 ation 4 ation/
		iii	Availa Dist	Social Social Social Social

205

DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION

Metropolitan Washington Airports

Final

Supplement to the Environmental Impact Statement

Metropolitan Washington Airports

Policy Statement

September 1981

SECTION I: SUMMARY

This final supplement to the August 1980 Environmental Impact Statement is submitted for review pursuant to the following public law requirements: Section 102(2)(C) of the National Environmental Policy Act of 1969 (42 U.S.C. 4332(2)(C)).

Summary

() Draft EIS

(X) Final Supplement to EIS

Department of Transportation, Federal Aviation Administration, John E. Wesler, Director of Environment and Energy, 800 Independence Avenue, S.W., Washington, District of Columbia 20591 (telephone: 202-426-8406).

() Legislative

-:--

(X) Administrative

The Washington-Baltimore region is served by three air carrier airports, two of which, Washington National and Dulles International Airports, are operated by the Federal Government. The two Federal airports have been operating over the past decade without a formalized, comprehensive policy defining their respective roles and guiding their day-to-day operations. Significant technical, regulatory, and social changes have occurred over this period of time along with the recognition of some significant facility and environmental problems that have developed at Washington National Airport.

These problems at Washington National Airport, along with the other changes that have occurred over the past decade, suggest the need for a policy which will guide the two Federal airports in serving the air transportation needs of the Nation's Capital. It is clear that operating, planning, and investment decisions at the two Federal airports cannot logically be made without an underlying policy which sets forth the manner in which each of the two facilities is to contribute to meeting the region's overall aviation needs.

In August 1980, the Department of Transportation (DOT) issued a formal Metropolitan Washington Airports Policy, supported in part by an Environmental Impact Statement. That policy was then issued as an

operating rule on September 15, 1980, by the Administrator of the Federal Aviation Administration (FAA). That rule was to have become effective on January 5, 1981. The Congress, in the DOT and Related Agency's Appropriation Act of 1981, mandated a delay in certain aspects of the policy. The effective date of the entire policy was then postponed until April 26, 1981.

On February 27, 1981, the Secretary of Transportation proposed a further delay in the effective date of the Metropolitan Washington Airports Policy and its implementing regulations. The delay in the effective date was necessary in order to allow time for a thorough review of the policy and its implications, especially in view of Executive Order 12291, which provided new government-wide standards for the promulgation of regulations. Therefore, on March 24, 1981, in order to provide adequate time to review the Metropolitan Washington Airports Policy, the effective date of its implementing regulations was postponed until October 25, 1981.

On July 8, 1981, the Secretary of Transportation announced the results of his review of the Metropolitan Washington Airports Policy, and proposed a revised policy for public review and comment. A Draft Supplement to the August 1980 Environmental Impact Statement, and a Preliminary Regulatory Evaluation were also issued to complement that proposal. Comments on these documents were received through August 31, 1981. This Final Supplement to the August 1980 Environmental Impact Statement forms a part of the final Metropolitan Washington Airports Policy.

POLICY ALTERNATIVES

Ĺ

The Environmental Impact Statement, dated August 1980, analyzed five alternative policies for the operation of the Metropolitan Washington Airports. Those alternatives were:

- No Policy Change (Base Case) at Washington National and Dulles International Airports.
- * Expanded Growth Policy at Washington National Airport
- Controlled Growth Policy to 18,000,000 Passengers Annually at
 Washington National Airport
- Controlled Growth Policy to 16,000,000 Passengers Annually at
 Washington National Airport
- * Reduced Activity Policy at Washington National Airport

This Final Supplement to the August 1980 Environmental Impact Statement addresses three additional alternative policies for the operation of the Metropolitan Washington Airports:

Controlled Activity Policy with Noise Limitations at
 Washington National Airport

- * Unconstrained Activity Policy with Noise Limitations at
 Washington National Airport
- Controlled Activity Policy with Noise Limitations at Washington National Airport, modified by Wilson Amendment to H.R. 4209, FY-1982 DOT Appropriations Act.

The Controlled Activity Policy with Noise Limitations would impose hourly scheduling limitations on operations at Washington National Airport, would impose annual passenger limitations there, and would also impose noise limitations on the types of aircraft permitted to operate there, with more stringent noise criteria for nighttime hours.

The Unconstrained Activity Policy with Noise Limitations would impose no hourly scheduling limitations on any class of operators, and would impose no annual passenger limitations, but would impose noise limitations on the aircraft permitted to operate at Washington National Airport. Those noise limitation criteria would be more stringent during nighttime hours.

On September 10, 1981, the House of Representatives adopted the following amendment to H.R. 4209, the Fiscal Year 1982 DOT Appropriations Act:

1-5

"Section 324. No funds appropriated by this Act shall be used to pay any salary or other expense for the purpose of putting into effect or enforcing any rule or order which requires any reduction in the total daily number of flights by (a) air carriers except air taxis, or (b) air taxis, at Washington National Airport below the number operated on July 31, 1981; except that this limitation shall not apply to Special Federal Aviation Regulation 44, amendments thereto or orders issued thereunder."

Airport records indicate that 808 air carrier and air taxi operations actually occurred on July 31, 1981, including 12 extra sections. The Official Airline Guide schedules for that day indicate that 615 operations were scheduled that day by aircraft with 56 or more seats, and 186 operations were scheduled by aircraft with less than 56 seats, for a total scheduled operations of 801. Therefore, it appears that the amendments noted above would be satisfied if scheduling limitations were imposed as follows for the period from 7:00 am through 9:59 pm:

air carriers 41 per hour (615 per day) plus extra sections commuters 13 per hour (195 per day) plus extra sections General Aviation 12 per hour (180 per day)

Accordingly, a third new alternative, the Controlled Activity Policy with Noise Limitations, modified to comply with the September 10, 1981, amendment to H.R. 4209, would impose hourly scheduling limitations on operations at Washington National Airport, would impose noise limitations on the aircraft permitted to operate there, and would impose no passenger limitations only through Fiscal Year 1982. Effective October 1, 1982, scheduling limitations would be imposed at 37 air carrier operations per hour, 17 commuter operations per hour, and 12 General Aviation operations per hour. At that time, an annual passenger limitation of 16,000,000 would also become effective. The noise limitations would be more stringent during nightime hours.

All of these alternative policies include the more stringent daytime noise limitation criterion in five years, the 1,000-statute-mile nonstop operating limitation, and the possible introduction of "widebody" aircraft.

ENVIRONMENTAL CONSEQUENCES

The environmental consequences associated with the five alternative policies addressed in the August 1980 Environmental Impact Statement remain valid, and are described adequately in that document. The environmental consequences associated with the three new alternative policies are addressed in this Final Supplement to the Environmental Impact Statement. In addition, measures which would be taken to mitigate adverse environmental consequences have been incorporated in each of the policy alternatives.

The analyses of the noise impacts of the two new policy alternatives, compared to those of the five alternatives analyzed earlier, indicate that by 1990, all of the three new policy alternatives would be as effective in reducing noise levels around Washington National Airport as would the Reduced Activity Policy alternative assessed in the August 1980 Environmental Impact Statement. The residents impacted by the eight policy alternatives are as follows:

Noise Impacted Population Within Ldn 65 Contours

				Regional
	National	Dulles	BWI	Total
Existing 1979*	75,500	4,500	30,000	109,500
No Policy Change				
1990*	116,000	3,500	22,900	142,400
Expanded Growth				
1990*	82,000	3,700	22,900	108,600
Controlled Growth				
to 18,000,000				
1990*	24,000	5,100	23,500	52 , 600
Controlled Growth				
to 16,000,000				
1990*	21,000	5,200	24,100	50,300
Reduced Activity				
1990*	1,200	6,000	25,700	32,900
Controlled Activity				
with Noise Restriction	ons			
1990	1,200	3,800	23,000	28,000
Unconstrained Activi	ty			
with Noise Limitatio	ns			
1990	1,200	3,200	22,500	26,900
Controlled Activity	with			
Noise Limitations Mo	lified			
1990	1,200	3,800	23,000	28,000

E

*Taken from August 1980 Environmental Impact Statement

Air quality impacts were compared against the five alternative policies assessed in the August 1980 Environmental Impact Statement, on the basis of total emissions inventory at the three Washington-area airports. Total emissions loading for the three additional alternative policies evaluated in this Final Supplement will increase at Washington National Airport and in the National Capital Interstate Air Quality Control Region, but will remain relatively unchanged within the bi-regional area if Baltimore-Washington International Airport is included.

For the three new alternative policies, the only serious impact on surface access would occur under the Unconstrained Activity Policy, which would be approximately the same as that forecast for the Expanded Growth Policy alternative, assessed in the August 1980 Environmental Impact Statement.

Energy impacts depend greatly on the details of the alternative policy assessed. Energy efficiency will improve with the use of new technology aircraft, required in order to meet proposed noise limitations, and with longer stage lengths permitted by the 1,000-statute-mile nonstop operating limitation. For the Unconstrained Activity Policy alternative, increased delays at Washington National Airport could decrease energy efficiency.

The impacts in the remaining environmental disciplines, including parklands and historical sites, social and economic conditions, and

natural systems, are contained within the range of impacts assessed in the August 1980 Environmental Impact Statement.

AREAS OF CONTROVERSY AND ISSUES TO BE RESOLVED

The primary area of controversy with the Metropolitan Washington Airports Policy centers around the conflicting and competing interests that have historically influenced the use of the two Federal airports. Clearly, this controversy can only be resolved by the policy selection of the Secretary of Transportation.

POLICY DECISION

This Final Supplement to the Environmental Impact Statement assesses three additional alternative policies, in addition to the five assessed in the August 1980 Environmental Impact Statement. A Metropolitan Washington Airport Policy will be selected from within the range of these alternatives.

This Final Supplement was made available to EPA and the public on: September 22, 1981.

Director of Environment and Energy

9-22-81

Date

SECTION II: DESCRIPTION AND PURPOSE

PURPOSE

This Final Supplement to the August 1980 Environmental Impact Statement considers the potential environmental impacts of additional policy alternatives that are being added to the five alternatives previously assessed. Together they consider and support a new policy action to replace the August 1980 Metropolitan Washington Airports Policy. The Department of Transportation deferred the August 1980 policy in response to Congressional action. Implementation of that August 1980 policy was further delayed in early 1981 pending review by the Secretary of Transportation and the Administrator of the Federal Aviation Administration.

As a result of that review, a revised policy is being adopted, reflecting the Department's objective for establishing how Washington National and Dulles International Airports will contribute to meeting the overall aviation needs of the Metropolitan Washington Area in the 1980s and beyond. This preferred alternative is summarized below.*

REVISED POLICY

<u>Passenger Limit</u>. There will be a limit of 16,000,000 per year specified on the number of passengers at Washington National

*This preferred alternative will be amended as necessary to comply with any changes enacted by the Congress.

Airport. There will be no passenger limit at Dulles International Airport.

<u>Operating Hours</u>. Washington National Airport and Dulles International Airport will be operated 24 hours per day.

Scheduling Limitations. Air carriers may schedule no more than 37 operations per hour, and commuter air carriers (defined as those using aircraft having fewer than 56 seats) may schedule no more than 17 operations per hour at Washington National Airport during the period from 7:00 a.m. through 9:59 p.m., subject to the noise limitations noted below. Extra sections will not be included in these limitations. During Instrument Flight Rule conditions, general aviation will be limited to no more than 12 operations per hour at Washington National Airport. There will be no scheduling limitations at Dulles International Airport.

<u>Noise Limitations</u>. For all daytime operations (7:00 a.m. through 9:59 p.m.) at Washington National Airport, there will be a noise limitation criterion of 86 dBA, as generated on takeoff using the standardized test conditions specified in Part 36 of the Federal Aviation Regulations (14 CFR 36); for nighttime departures (10:00 p.m. through 6:59 a.m.), a noise limitation criterion of 72 dBA as generated on takeoff; and for nighttime arrivals, a noise limitation criterion of 85 dBA as generated on approach. Effective October 1, 1986, the daytime noise limitation criterion

will drop to 80 dBA, as generated on takeoff. The nighttime noise limitations will remain at 72 dBA on takeoff and 85 dBA on approach. There will be no noise limitations at Dulles International Airport.

<u>Aircraft Limitations</u>. The operation of additional models of aircraft not now operated at Washington National Airport will be allowed if that operation is found to be safe by the Administrator of the FAA, based on his model-by-model examination, and is found to be operationally acceptable by the Director, Metropolitan Airports. There will be no new aircraft limitations at Dulles International Airport.

Nonstop Limitation. There will be a 1,000-statute-mile nonstop operating limitation for flights to and from Washington National Airport. There will be no nonstop operating limitations for flights at Dulles International Airport.

BACKGROUND

The Washington-Baltimore region is served by three air carrier airports, two of which, Washington National and Dulles International Airports, are operated by the Federal Government. The two Federal airports have been operating over the past decade without a formalized, comprehensive policy defining their respective roles and guiding their

day-to-day operations. Significant technical, regulatory and social changes have occurred over this period of time, along with the recognition of some significant facility and environmental problems that have developed at Washington National Airport.

These problems at Washington National Airport, along with the other changes that have occurred over the past decade, have created the need for a policy which will guide the two Federal airports in serving the air transportation needs of the Nation's Capital. It is clear that operating, planning and investment decisions at the two Federal airports should be made in conjunction with an underlying policy which sets forth the manner in which each of the two facilities is to contribute to meeting the region's overall aviation needs.

In March 1978, the Department of Transportation (DOT) issued a proposed policy and a Draft Environmental Impact Statement (DEIS) for Metropolicy Washington Airports. A wide range of policy options was presented in the analysis, including an evaluation of 32 policy alternatives. Comments on the policy options were received at public hearings held in May 1978 and written comments were received from Members of Congress, Federal agencies, state, municipal and local agencies, public and private organizations, and from interested individuals.

11-4

The comments revealed sharp differences of opinion on a policy for the two Federal airports. Many of the county and municipal governments of the Metropolitan Washington Area, along with local citizens, expressed the strong view that with two other air carrier airports available in the region the concentration of air carrier activity at Washington National Airport is an unwarranted and unnecessary burden on the airport neighbors who are subject to the impacts of aircraft noise. Other interests, many of which are outside the Washington area, expressed an equally strong national view and believe Washington National Airport's uniquely convenient location should be made available to air travelers who want direct access to downtown Washington. Those supporting this national interest argue that Washington National Airport, as a Federally owned and operated airport serving the Nation's Capital, necessarily serves more of a national role than a local one.

The DOT then elected to modify the 1978 policy proposal, given the changes brought about by the deregulation of the air transportation industry, and to issue a revised policy proposal, a Notice of Proposed Rulemaking, and a Supplement to the Draft Environmental Impact Statement. The supplement was issued in January 1980 and another set of public hearings was conducted in March 1980. A Metropolitan Washington Airports Policy and an Environmental Impact Statement were issued in August 1980.

This policy was to become effective on January 5, 1981. The Congress, in the DOT and Related Agency's Appropriation Act of 1981, Pub. L. 96-400, however, mandated a delay in certain aspects of the policy. The effective date of the entire policy, including the perimeter, was postponed until April 26, 1981, because the policy components are interrelated and should be treated as a package and not in a piecemeal fashion.

On February 27, 1981, the Secretary of Transportation proposed a further delay of the effective date for the Metropolitan Washington Airports Policy and implementing regulations. The proposed change in the effective date was necessary to ensure compliance with Executive Order 12291 (46 FR 13193; February 19, 1981), which provided new government-wide standards for the promulgation of rules. In addition, the change in the effective date was necessary to consider the Department's permanent rulemaking on slot allocations at Washington National Airport, and was consistent both with a request by the Senate Commerce Committee to the Secretary that the policy be reviewed and with Congressional concerns expressed in the action that led to the initial delay of the policy until April 26, 1981.

Therefore, on March 24, 1981, in order to provide adequate time to review the Metropolitan Washington Airports Policy, the effective date

of the regulation was postponed by the Secretary until October 25, 1981.

Following a comprehensive review, the Secretary of Transportation on July 8, 1981, proposed a revised Metropolitan Washington Airports Policy, in the form of a Notice of Proposed Rulemaking (46 FR 36068, July 13, 1981), supported by a Draft Supplement to the August 1980 Environmental Impact Statement, and later by a Preliminary Regulatory Evaluation. A public hearing was held on July 28-29, 1981, and written comments were received through August 31, 1981. Following a careful review and analysis of those comments, a final policy was developed.

Review of Policy Objectives

The Department of Transportation's consideration of policy alternatives for Washington National and Dulles International Airports has always been undertaken with the following objectives in mind:

- To rationalize the role and use of the two airports from an overall transportation viewpoint;
- To achieve optimum utilization of existing and planned capacity at the airports;
- 3. To eliminate unnecessary constraints on the use of aircraft

11-7

at the airports, consistent with safety requirements and operational acceptability;

- 4. To ensure that the growth, uses, and roles of the airports are as compatible as possible with the changing demands and expectations of the community, especially with respect to environmental impacts; and
- 5. To permit planning for and implementation of improvements at Washington National and Dulles International Airports, consistent with the designated role of each facility.

Alternative Policy Considerations

The August 1980 Environmental Impact Statement for the Metropolitan Washington Airports Policy considered five alternative policies. These alternatives covered a range of options from a significant reduction in activity at Washington National Airport to an expanded role for the airport. Included were the consequences of making no change in the current operating practice at Washington National Airport.

Although the Federal Aviation Administration does not establish operational policies at Baltimore-Washington International Airport, policy decisions at Washington National and Dulles International Airports will affect air traffic activity at Baltimore-Washington

International Airport and, therefore, impacts associated with each alternative were also analyzed for that airport.

The five alternatives were developed as a result of the FAA's study into options available at each of the airports and also as a direct result of comments provided throughout the environmental review process. Initially, 32 preliminary alternatives or cases were studied by the FAA in a report entitled <u>Metropolitan Washington Airport Policy</u> <u>Analysis</u>. Based on this work, a wide range of policy options defining various roles for the airports was evaluated in the Draft Environmental Impact Statement for the Metropolitan Washington Airports Policy published in March 1978. Quotas, curfews and possible widebody aircraft service at Washington National Airport were examined for potential policy impacts on regional air travelers, community residents, and airport investment requirements. Subsequent to this study, a Supplement to the Draft Environmental Impact Statement was published in January 1980. That supplement considered three basic alternatives plus a proposed policy for the operation of the airports.

The August 1980 Environmental Impact Statement refined these alternatives and expanded the alternatives under consideration as a result of continued FAA study and comments received from various Federal, state and local agencies, community groups, the aviation industry and the general public. The alternatives considered in that analysis included:

- o No Policy Change (Base Case)
- o Expanded Growth policy at Washington National Airport
- Controlled Growth Policy to 16,000,000 Passengers
 Annually at Washington National Airport
- Controlled Growth Policy to 18,000,000 Passengers
 Annually at Washington National Airport
- o Reduced Activity Policy at Washington National Airport

Each alternative was defined on the basis of passenger limits, operating and scheduling hours, the allocation of slots among the classes of aircraft activity, the type of aircraft permitted to use the airport, and a maximum nonstop operating limitation.

The policy that was adopted in August 1980 placed a 17 million annual passenger limit on Washington National Airport; specified operating and scheduling hours; allocated slots among the classes of aircraft activity; considered use of new types of aircraft permitted at Washington National Airport; and defined a maximum nonstop operating limitation for Washington National Airport.

BASIC PRINCIPLES

This revised policy addresses a controversy over the proper uses of Washington National Airport and Dulles International Airport that has now existed for more than a decade. No action can be taken which would eliminate that controversy. A piecemeal approach to the issues of the proper roles and uses of these airports is inappropriate. There have been extensive studies related to this controversy, including environmental, economic, community impact, and policy alternative analyses. This revised comprehensive policy is adopted after considering these studies and the arguments presented by each protagonist, and after taking all of them into consideration. The resultant policy is not likely to be acceptable to all factions, but it represents the Department's views of the proper role and best use of these two airports in the public interest.

Certain basic principles, along with the environmental consequences, guided the development of the new policy for the Washington Metropolitan Airports. They need to be understood by all sides to the controversy, hopefully to gain their enthusiastic support. They are:

 The principal local objection to Washington National Airport is noise, with a secondary objection being ground congestion. Therefore, any rational solution must be noise responsive and congestion sensitive.

- (2) Washington National Airport is a <u>national</u> asset that belong: to all of the people, and should be used to its optimum capability commensurate with noise and congestion considerations, with an efficient balancing of air traffic among the other Washington area airports, Dulles and Baltimore-Washington International Airports.
- (3) The development, production, and procurement of new, quieter aircraft is a time-consuming process, requiring several years at a minimum to accomplish; therefore, to respond to principle (1) and meet the needs of principle (2) above, a long-term policy must be established that affords each affected group the opportunity to make meaningful future plans.
- (4) Fleet composition of most air carriers is currently undergoing considerable change, and with proper incentives can be oriented to the procurement of quieter aircraft at an accelerated rate. However, the Nation cannot afford the unwarranted immediate loss of over \$7 billion in fleet inventory.
- (5) Airside and landside constraints limit capacity at WashingtonNational Airport; therefore, the policy for Metropolitan

Washington Airports should extend sufficiently into the future to reflect forecasts of new technology and operating efficiencies which will be important factors in optimizing the use of the available airport acreage. Accordingly, the policy adopted needs to be made applicable at least through the end of this century, while at the same time recognizing that modifications may result within that period as new technology or operating efficiencies permit.

- (6) Air carriers in making their fleet plans and purchases of new aircraft have long known the runway, terminal, and landside limitations at Washington National Airport; but, similarly, citizens who bought homes near the airport or near its flight paths also knew that the National Airport existed and there was no likelihood of it being abandoned.
- (7) Satisfactory ground transportation will not exist between Dulles International Airport and the center of Washington, D.C., until completion of the I-66 bypass in 1984. The next generation of quieter aircraft also will not be in significant use until that same timeframe.
- (8) The Federal Government should take no action that unreasonably inhibits our free enterprise system or the

II-13

3

ability to compete, and should regulate only to the degree necessary for air safety and implementation of the principles outlined above. Stated simply, the Federal Government should control, not constrain.

This revised policy for the Metropolitan Washington Airports precedes publication by the Federal Aviation Administration of an environmental study required under Section 105 of the Aviation Safety and Noise Abatement Act of 1979 (Public Law 96-193, February 18, 1980), as implemented by its Federal Aviation Regulation (FAR) Part 150. The Act requires publication of a noise exposure map and a noise compatibility program for each of the two Federal airports, Washington National Airport and Dulles International Airport, before March 1, 1982. However, the policy adopted for Metropolitan Washington Airports provides the framework within which the Section 105 study will be accomplished.

NEED FOR SUPPLEMENT

Council on Environmental Quality (CEQ) Regulations in 42 CFR 1502.9(c), requires the preparation of supplemental analyses if the agency makes substantial changes in the proposed action (revised policy for Metropolitan Washington Airports) that are relevant to environmental concerns. FAA Order 1050.1C, Appendix 6, paragraph 104, which implements 42 CFR 1502.9(c), requires a supplement if a reasonable alternative is significantly different from alternatives previously considered.

SECTION III: PRESENT CONDITIONS AND IMPACTS OF POLICY ALTERNATIVES

INTRODUCTION

This section of the Final Supplement to the Environmental Impact Statement presents a brief summary of the existing conditions at Washington National Airport, and the likely changes that would result from either of three additional policy alternatives, which are evaluated here. These changes are also related to the analyses of the five policy alternatives presented in the August 1980 Environmental Impact Statement. Those earlier results are not repeated here, except where convenient for direct comparisons.

NOISE

The noise analysis in this Final Supplement to the Environmental Impact Statement is based on, and extends the analysis presented in the August 1980 Environmental Impact Statement. The assumptions regarding aircraft noise, listed on Page III-5 of that statement, remain valid for this analysis, except as listed on Page III-11 of this document.

Base Case (Existing Conditions, No Policy Change)

The base case as defined in the August 1980 Environmental Impact Statement, page III-5, has been re-calculated and included in this text for convenience of comparison. The base case was re-calculated using

III-1

the Average Day-Night Sound Level (Idn)¹ noise unit, as required by Federal Aviation Regulation, Part 150, which has been issued since the August 1980 analysis, and sets forth Ldn as the standard system for evaluating noise around airports. Noise Exposure Forecast (NEF) was used for the noise analysis presented in the August 1980 Environmental Impact Statement.

The base case operating limitations and assumptions are described in Table I, and are based on the operating practices currently in use. The re-calculated base case utilizes the May 1981 actual operations at Washington National Airport, and a revised 1970 census which has included projected 1980 population distributions and demographics. This computer-based demographic data base provided the population and housing information presented for the present analysis. The results presented in the August 1980 Environmental Impact Statement, while using the same operational assumptions and operating practices, were based on 1979 operations and an earlier population data base.

III-2

¹ Average Day-Night Sound Level is the equivalent A-Weighted Sound Level over a 24-hour period, with the sound levels from 2200 through 0659 local time increased by 10 decibels. As an approximation, Average Day-Night Sound Level is equal to Noise Exposure Forecast (NEF) plus 35 decibels. Ldn = NEF + 35. Thus, the Ldn 65 noise exposure contour approximates the NEF 30 contour, for comparison.

TABLE 1

Magazine .

ADDITIONAL ALTERNATIVE POLICIES FOR NATIONAL AIRPORT

OPTIONS	EXISTING CONDITIONS (Base Case)	CONTROLLED ACTIVITY W/MOISE RESTRICTIONS 1981	CONTROLLED ACTIVITY W/NOISE RESTRICTIONS 1986	WNOISE RESTRICTIONS WNOISE RESTRICTIONS 1981	UNCONSTRAINED ACTIVITY W/NOISE RESTRICTIONS 1986	CONTROLLED ACTIVITY W/NOISE RESTRICTIONS, MODIFIED 1981	CONTROLLED ACTIVITY W/NOISE RESTRICTIONS, MODIFIED 1986
PASSENCER LIMITATION	No limit on total annual passengers at National.	16,000,000	16,000,000	No Limit	No Limit	No Limit	16,000,000
SCHEDULINC	Air carrier - 40 per hour (plus extra sections) extra sections) Commuters 8/hr. Commuters 8/hr. Commuter 8/hr. Scheduling hours for air carrier lets: 7:00 a.m. until 10:00 p.m. commuter props: any time within scheduling limits.	Air carrier - 37/hr. (plus extra sec- tions); Commuters - 17/hr.; General Aviation - 12/hr.; 7:00 a.m. through 9:59 p.m.	Air Carrier - 37/hr. (plus extra sec- tions); Commuters - 17/hr.; General Aviation - 12/hr.; 7:00 a.m. through 9:59 p.m.	No hourly limitations.	No hourly limitations.	Air carrier - 41/hr. (plus extra sections); Commuters - 13/hr.; General Aviation - 12/hr.; 7:00 a.m. through 9:59 p.m.	Air carrier - 37/hr. (plus extra sec- tions; Commuters - 17/hr.; General Aviation - 12/hr.; 7:00 a.m. through 9:59 p.m.
NOISE LIMITATIONS	Informual agree- ment, no general aviation jers between 11:00 pm and 7:00 am.	From 7:00 am thru 9:59 pm: noise limit of 86 dBA on takeofi from 10:00 p.m. thru 6:59 a.m.: noise limit of 72 dBA on limit of 72 dBA on takeoff and 85 dBA on approach.	From 7:00 am thru 9:59 pm: noise limit of 80 dRA on takeoff; from 10:00 pm thru 6:59 am: noise limit of 72 dBA on takeoff and 85 dBA on takeoff	From 7:00 am thru 9:59 pm: noise limit of 86 dBA on takeoff; from 10:00 p.m. thru 6:59 a.m.: noise limit of 72 dBA ^n takeoff and 85 dBA on approach.	From 7:00 am thru 9:59 p.m.: noise limit; of 80 dBA on takeoff; from 10:00 pm thru 6:59 am: noise limit of 72 dBA on takeoff and 85 dBA on approach.	From 7:00 a.m. thru 9:59 p.m.: noise limit of 80 dBA on takeoff; from 10:00 p.m. thru 6:59 a.m.: noise limit of 72 dBA on takeoff and 85 dBA on approach.	From 7:00 a.m. thru 9:59 pm.: noise limi of 80 dBA on takeoff; from 10:00 p.m. thru 6:59 a.m.: noise limit of 72 dBA on takeoff and 85 dBA on approach
AI RCRAFT LLMITATION	Maximum size permitted 727-200 (No 4 eng. jets, 2 or 3 eng.	All models found to be safe and opera- tionally acceptable.	All models found to be safe and opera- tionally acceptable.	All models found to be safe and opera- tionally acceptable.	All models found to be safe and operation- ally acceptable.	All models found to be safe and operationally acceptable.	All models found to be safe and operationally acceptable.
NONSTOP LIMITATION	650 statute mi. Plus 7 "grand∽ father cities".	1000 statute miles nonstop.	1000 statute miles nonstop.	1000 statute miles nonstop.	1000 statute miles nonstop.	1000 statute mìles nonstop.	1000 statue miles nonstop.

3

III-3

The August 1980 Environmental Impact Statement used August 1979 operations at Washington National Airport as the base case for comparison of the five alternative policies analyzed. For the present analysis, May 1981 operations at Washington National Airport were used for comparison with the three new policy alternatives. Air carrier jet operations decreased approximately 5% between August 1979 and May 1981. Thus, essentially, the two sets of analyses are interchangeable regarding comparative noise impacts.

Because of the nationwide air traffic controllers' walkout on August 3, 1981, the actual level of operations at Washington National Airport, and many other larger airports in the United States, is somewhat below the level of operations in May 1981, and will probably remain below that level for a year or more, until sufficient trained controllers become available to permit safe operations at higher levels. This is considered a temporary aberration, however, and has been disregarded for purposes of this evaluation.

Table II lists the air carrier aircraft operations for May 1981. The associated noise impacts at Washington National Airport are shown in Figure 1, and in Table III. Figure 1 indicates that the present Average Day-Night Sound Level (Ldn) 65 contour extends approximately 7.7 miles northwest along the Potomac River corridor from Washington National Airport. Downriver from the airport, the Ldn contour extends about 5.6 miles south. The Ldn 75 contour extends approximately 2.6 miles south of the Runway 36 threshold, and about 2.5 miles northwest

III-4

TARLE II

R

ŀ

WASHINGTON NATIONAL AIRPORT AIRCRAFT OPERATIONS FORECASTS

.....

	Existing Conditions*	Contro No Wid	lled Ac	tivity"	- ইা	Uncons No Wid	trained	Activ W/Wide	ity** body	Contro No Wid	billed A	ctivity w/Wide	. Modified** bo <u>dy*</u>
AIR CARRIER	May 1981	1981	1990	1981	1990	1981	1990	1981	1990	1981	1990	1981	1990
Operations per day:*													
2 Engine Narrow Body	224	223	558	230	294	246	676	240	362	270	589	230	294
3 Engine Narrow Body	316	335		228		350		292		352		228	
2 Engine Wide Body				14	264			14	314			14	264
3 Engine Wide Body				26				26				26	
Total Air Carrier Ops.	560	558	558	558	558	596	676	572	676	622	589	558	558

*Includes Extra Sections **With Noise Restrictions .

and the second second








EP	RESENTATIVE SENSITIVE SITES	PARKS AND RECREATION AREAS
1	ST. MARY'S CHURCH	40 WATERFOWL SANCTUARY
2.	FORT FOOTE PARK	41, GRAVELLY POINT PARK
з.	FT, FOOTE BAPTIST CHURCH	42. POTOMAC RIVER
4	INDIAN QUEEN SCHOOL	41, MARINA
5.	SROOKMONT SCHOOL	44. DAINGERFIELD ISLAND
6.	SIBILEY HOSPITAL	45 SAST POTOMAC PARK
7	AMERICAN UNIVERSITY	46 JONES POINT PARK
	ST. JOHN'S CHILD	47 NEST POTOMAC PARK
	JEVELOPMENT CENTER	18 POTOMAC VIEW PANK
9.	GEORGETOWN UNIVERSITY	49 THE MAL
0	WOODMONT SCHOOL	30 BOUG CREEK AND POTOMAC
1	COLUMBIA HOSPITAL	PARKWAY
2	LINCOLN MEMORIAL	ST C & O CANAL
3	JEFFERSON NEMORIAL	52 ARCHINGLO PARKWAY
4	ST. MARY'S SCHOOL	51 POTOMAC PALISACES PAPEWA
5	SYPHAR SCHOOL	54 SECREE NASHINGTON
8.	HADLEY HOSPITAL	MEMORIAL PARKWAY
7	ST. THOMAS MORE SCHOOL	15. ABLINGTON HOUSE
8.	GRAY HUGH SCHUCL	56 INC IMA MEMORIAL
9	ST JOSEPH'S SCHOOL	17 LADY SIRD , DHNSON PARA
		SH ATHEAN VIRGINIA
		SEGIONAL PARK
		C.

IDGE

NL NCT

a

METROPOLITAN WASHINGTON AIRPORTS FINAL SUPPLEMENT TO THE AUGUST 1980 ENVIRONMENTAL IMPACT STATEMENT

NATIONAL AIRPORT 1981 Ldn Contours Existing Conditions (Base Case)

FIGURE 1

	<u>Area</u> (sq. mi.)*		Population*		
Existing Conditions (May 1981)	25		93,000		
	1981	1990	1981	1990	
Controlled Activity**					
No Widebody Aircraft	26	4.9	97,000	1200	
With Widebody Aircraft	24	4.9	97,000	1200	
Unconstrained Activity**					
No Widebody Aircraft	28	5.0	102,000	1200	
With Widebody Aircraft	24	4.9	97,000	1200	
Controlled Activity, Modified**					
No Widebody Aircraft	27	4.9	102,000	1200	
With Widebody Aircraft	24	4.9	97,000	1200	

*Within Ldn 65 Contour **With Noise Restrictions

III-7

TABLE III

NOISE IMPACT AT WASHINGTON NATIONAL AIRPORT

of the Runway 18 threshold. The total area encompassed by the Ldn 65 contour is approximately 25 square miles, while the Ldn 75 contour covers about 5.7 square miles.

As presented in Table III, the present base case analysis estimates that 93,000 people (42,000 households) reside within the Ldn 65 (NEF 30 equivalent) noise exposure contour, and 6,000 people (2,950 households) reside within the Ldn 75 (NEF 40 equivalent) contour. These figures represent approximately a 30% increase over the number estimated within the equivalent contours in the August 1980 Environmental Impact Statement. Since the noise exposure contours are approximately the same size, the increase in affected population apparently is due to the use of a different demographic analysis procedure and revised data base.

It should be mentioned that the baseline noise impact contours reflect the use of a number of noise abatement measures presently employed at Washington National Airport:

- * The scheduling of turbojet air carrier aircraft only during the period from 7:00 a.m. through 10:00 p.m.
- The limited number of scheduled air carrier and commuter operations each day—40 per hour for air carriers and 8 per hour for commuters.

- * The prohibition on certain types of aircraft--specifically four-engine jet aircraft.
- * Noise abatement operational procedures--thrust reductions after takeoff and reduced flaps on approach.
- * The preferential approach and departure paths over the Potomac River corridors.

The noise abatement steps already taken at Washington National Airport have served to reduce noise impacts near the airport. As newer, less noisy aircraft come into service, and older fleets are modified to comply with Federal regulations, overall noise impacts will gradually be reduced. Nevertheless, there remains a noise problem under present conditions. There are residential areas, parks, historic, and institutional activities existing within the Ldn 65 contour. In addition, there are many residential areas outside the Ldn 65 contour where residents complain that the level of aircraft noise and frequency of overflight is intrusive and annoying.

In general, increasing levels of cumulative noise exposure result in increased annoyance in a larger percentage of the population. In other words, a greater percentage of the population will be annoyed when exposed to a cumulative noise level of Ldn 65 as compared to Ldn 60 or Ldn 55. Although Ldn 65 is normally considered acceptable, there will always be citizens who consider a cumulative noise level of less

than Ldn 65 as unacceptable. In any case, one should never conclude that the Ldn 65 contour represents a boundary outside of which no aircraft noise impacts occur. Many experts believe that noise impact information is best used to compare the relative differences in noise impact among the different policy alternatives, rather than attempting to determine what level of noise should be considered acceptable or unacceptable. In other words, noise contours are best used to compare the relative changes in levels of public annoyance which should result from policy or operating alternatives, rather than to predict the absolute level of annoyance associated with any given policy or operating procedure. It should be emphasized that noise impact contours are calculated and presented for average yearly operating conditions, in order to allow reliable and consistent comparisons. On any given day, actual noise impact contours may vary, depending on operating conditions (e.g.: wind direction and the associated direction of traffic movements). The relative changes in noise impact for each policy alternative as depicted by the noise model will also occur for areas farther from the airport and outside of the noise contours.

Impacts of Policy Alternatives²

The noise impacts of the various policy alternatives result from the combination of policy provisions, including aircraft scheduling restrictions, introduction of new technology aircraft, the amount of reduction of nighttime aircraft operations, and aircraft noise limitations.

For future conditions, 1986 and beyond, all air carrier aircraft operating at Washington National Airport are assumed to be new models or older models re-engined with new engines, in order to comply with the required noise limitation criterion of 80 dBA, as measured for

² The Metropolitan Washington Council of Governments (COG) and the FAA are engaged in a cooperative effort to evaluate and test alternative flight path configurations that may further reduce the impacts of aircraft noise on citizens in the Washington area. Through this effort, considerations will be given to changing existing flight paths and procedures. These tests of alternative flight paths have <u>not</u> been included in this analysis.

takeoff under conditions specified in 14 CFR 36. For the noise analysis, the following air carrier aircraft models are examples of those assumed to be capable of meeting this requirement:

DC-9-80 737-300 727-200 re-engined with two CFM-56 or similar engines 757 767

Note: This assumption does not imply any finding by the Administrator as to the approved use of these models at Washington National Airport. These models of aircraft are cited purely to illustrate the expected performance characteristics of aircraft for environmental analysis purposes.

The alternatives assessed for the near term (1981) and the longer term (1990) include:

- Controlled activity at Washington National Airport with noise restrictions.
- * Unconstrained activity at Washington National Airport with noise restrictions.

* Controlled activity at Washington National Airport with noise restrictions, modified by the September 10, 1981, House of Representatives amendment to the Fiscal Year 1982 DOT Appropriations Act.

Both the near term and the longer term assessments considered the introduction of widebody aircraft and their exclusion.

Controlled Activity with Noise Restrictions, Near Term Impacts: Figure 2 shows the noise impact of imposing a limitation of 37 air carrier operations per hour from 7:00 a.m. through 9:59 p.m. with no widebody aircraft and with the noise restrictions shown in Table I. Since the actual May 1981 activity at Washington National Airport did not utilize all of the slots then available (40 per hour for 16 hours), the Controlled Activity alternative has slightly more impact than the May 1981 base case. There is a 4% increase in the population impacted between this policy alternative and the May 1981 base case. When widebody aircraft are included in this alternative, the area encompassed by the Ldn 65 contour decreases by approximately two square miles but includes about the same number of people as this alternative without widebody aircraft.

Unconstrained Activity with Noise Restrictions, Near Term

<u>Impacts</u>: There is an increase in area and population (two square mile and about 5000 more people within the Ldn 65 contour) impacted for the October 1981 case with no scheduling limitations, no widebody aircraft









· • • • • • • •

 \overline{f}

but with noise restrictions. Since there is no difference in the number of forecast operations between the Controlled Activity alternative with widebodies and the Unconstrained Activity alternative with widebodies, the noise impacts of these alternatives are the same.

<u>Controlled Activity with Noise Reductions, Modified, Near Term</u> <u>Impacts</u>: If the level of operations on Friday, July 31, 1981, were to be sustained throughtout the year, the areas and population impacted is approximately the same as the unconstrained case above. The Ldn 65 contour shown in Figure 3 encompasses 27 square miles within which 102,000 people reside.

In summary, in the near term there will be no significant change in contour areas or population impacted upon implementation of an operating policy with or without the 37 per hour air carrier scheduling limitation, and with or without the introduction of widebody aircraft.

Controlled Activity with Noise Restrictions, Long Term Impact:

The imposition on October 1, 1986, of the 80 dBA noise restriction for all aircraft operating at Washington National Airport during the period from 7:00 a.m. through 9:59 p.m. would change significantly the noise impact. The noise restriction would, in general, allow only new generation (or re-engined) aircraft to operate at Washington National Airport. These aircraft would replace the noisier aircraft currently in use. For example, the noise level from the new generation of 757, 767, and DC-9-80 aircraft are expected to be ten decibels quieter on takeoff than a 727. Most people will perceive the takeoff of one of these new generation aircraft as half as noisy as the 727 aircraft currently operating at Washington National Airport. Figure 4 shows that the 1990 Ldn 65 contour for the alternative of controlled activity with noise restrictions extends 2.4 miles northwest from the Runway 18









threshold and 3.0 miles south of the Runway 36 threshold, encompasses 4.9 square miles and impacts about 1,200 people (734 households). The smaller Ldn 75 contour extends about one-half mile up and down the river from the airport and does not impact any residences. The contours remain the same whether or not widebody aircraft are permitted to operate.

Unconstrained Activity with Noise Restrictions, Long Term Impact: This alternative would not significantly change the area, or the number of people within the Ldn 65 contour as compared with the controlled activity alternative. Table III summarizes the noise impact of all the alternatives assessed in this Supplement.

In summary, both the controlled activity and the unconstrained activity alternatives significantly reduce the number of people impacted within the Ldn 65 noise contour from 93,000 in 1981 to 1,200 by 1990.

NIGHTTIME NOISE LIMITATIONS

The August 1980 policy would have instituted a nighttime curfew on all aircraft departures from Washington National Airport between the hours of 10:30 p.m. and 7:00 a.m., and on all arrivals between 11:00 p.m. and 7:00 a.m. The decision to implement a curfew was based on a need to control the noise impacts associated with aircraft operations. The August 1980 Environmental Impact Statement predicted an improvement in the cumulative noise impact on the surrounding community due in part to the establishment of a curfew.

111-17









Many commenters on the curfew portion of the August 1980 policy urged that, in lieu of closing Washington National Airport to all traffic, smaller aircraft that are substantially quieter should be permitted to operate past the 10:30 or 11:00 p.m. closing hours. In response to these comments, the Secretary directed the FAA to analyze further the curfew and, if appropriate, to propose a modification of the curfew.

Three alternative approaches to the curfew are assessed in this Final Supplement:

- Prohibit all aircraft departures including General Aviation (GA) from 10:30 p.m. through 6:59 a.m., and all aircraft arrivals from 11:00 p.m. through 6:59 a.m. Under the regulations issued to implement the August 1980 policy, this curfew would become effective on October 26, 1981.
- 2. Amend the regulations to prohibit air carrier and general aviation jet operations only, and impose no restrictions on propeller-driven aircraft activity at Washington National Airport during the nighttime hours. This would closely resemble the current operating policy. At present, general aviation activity is unrestricted at night except that the operators of jet aircraft are requested not to operate after 11:00 p.m. and before 7:00 a.m. Under this alternative, the jet restriction would be regulatory, not voluntary.

3. Amend the regulations to adopt a nighttime noise limitation on aircraft, that would allow no significant increase in the cumulative noise over that which would result from the August 1980 policy (Alternative 1), and which would not cause undue intrusions upon residents during nighttime hours. Only aircraft that can meet the limitations when flown under FAA noise certification conditions would be allowed to operate.

Discussion of Alternatives

- The long range environmental effects of a nighttime curfew on all aircraft are discussed in the August 1980 Environmental Impact Statement issued on the policy.
- 2. To examine the environmental impact of maintaining the current policy with respect to general aviation night operations (Alternative 2), operational and noise data were obtained on four typical nights in the month of October 1980. These data show an average of 52 general aviation operations (including an average of 14 helicopter operations) at Washington National Airport between the hours of 10:00 p.m. and 7:00 a.m. This is an average of six per hour. There was an average of 1.75 general aviation jet operations per night due to the voluntary "curfew." Table IV contains a summary of these operations.

111-20

TABLE IV

GENERAL AVIATION NIGHTTIME OPERATIONS

WASHINGTON NATIONAL AIRPORT 2200-0700 - October 1980

	Number of Operations				Noise Leve	Noise Level** (dBA)	
Aircraft Type	<u>Oct. 2</u>	<u>Oct. 21</u>	Oct. 28	Oct. 29	Takeoff	Approach	
Piper Navajo	11	13	11	12	74.0/71.0*	77.0/76.0*	
Piper Aztec	4	9	4	5	69.0	74.0	
Beech 99	7	4	3	5	66.0	74.0	
Beech 100	1				62.0	74.0	
Cessna 310	2	2	3	1	71.0	75.0	
Nord 262	1	2	2	2	78.3	88.0	
NAMC YS-11	1		2	2	81.0	90.0	
Piper Senneca	1		1	3	67.0	73.0	
Smith Aerostor 600	3	3		2	70.0	75.0	
Shorts SD3-30	2		2	2	76.0	85.0	
Falcon Fan Jet	1	1		1	67.6	86.2	
Cessna 500 Jet	1				61.1	77.4	
Gulfstream II Jet	1				80.1	91.1	
Lear 35 Jet	1			2	72.0	83.1	
Lear 25 Jet			2		79.7	88.2	
Cessna 402		4	2		69.0	75.0	
Mitsubishi MU-2		2			66.0	76.0	
Beech Baron		2			67.0	75.0	
Cessna 421	<u> </u>	 .	_2		62.0	75.0	
Fixed Wing Subtotal	37	42	34	37	Avg. 38		
Helicopter	_5	<u>20</u>	<u>14</u>	<u>19</u>			
Total	42	62	48	56	Avg. 52		

*The PA-31-350 Navajo at 7000 # T.O.G.W. is 74.0 dBA whereas the PA-31-310 at 6500 # T.O.G.W. is 71.0 dBA.

**The noise levels were estimated for each airplane as they might occur during type certification tests conducted under Appendices A, B, and C of FAR Part 36. The levels are listed in Advisory Circular 36-3A issued June 11, 1980, entitled "Estimated Airplane Noise Levels in A-Weighted Decibels."

9.2

If these operations occurred in the daytime, they would have no measurable effect on the cumulative noise contours. Due to the nighttime weighting penalty (10 decibels) included in the Ldn metric, these relatively few general aviation nighttime operations will cause the Ldn 65 noise contour to cover slightly more area than if a complete curfew were imposed on all night operations. Since the population density in this area is high, a slight increase in area means a significant number of people would be impacted, or more accurately, would remain impacted. In addition, the single event noise levels of certain louder general aviation aircraft operations at night also intrude into residential areas.

3. In order to achieve the goal of Alternative 3 of not altering the predicted cumulative noise exposure contours, a sufficiently low noise limitation is necessary that would, in effect, offset the 10 dB penalty imposed on night aircraft operations in calculating Ldn.

Since the takeoff noise level of many of the two-engine air carrier jet aircraft which operate daily at National is at least 82 dBA at 6,500 meters from start of takeoff roll (the FAR Part 36, Appendix C takeoff measurement point), aircraft with a takeoff noise level 10 decibels lower, or 72 dBA at the FAR 36 measuring point, would not measurably increase the

Ldn noise contours if operated at Washington National Airport during the nighttime hours. The noise energy from approximately 600 air carrier jet aircraft operations (including over 300 Boeing 727 operations at noise levels several decibels higher than 82 dBA) would dominate, thus causing the impact of around 50 night operations limited to 72 dBA to be insignificant. This conclusion would remain valid even if the number of night operations were doubled.

Since aircraft measuring 72 dBA at the takeoff noise measurement point would not measurably increase the cumulative noise level, this noise level was examined to determine the single event impact of such aircraft and to determine if it would intrude into residences during the night. Figures 5 and 6 show the 72 dBA single-event contours of a typical airplane with a maximum noise level of 72 dBA at 6,500 meters from start to takeoff role as tested under standardized FAR 36 conditions. If the aircraft flies over the center of the Potomac River or up the Anacostia River, the 72 dBA single-event contour does not reach any residential area. Assuming a 15-20 decibel attenuation of sound through a typical residential structure, people inside their homes just outside the contour would be exposed to approximately 50-55 dBA. As can be seen from Table V, which describes typical values of noise level commonly experienced by people, this is below the level which would interfere with most activity, including sleep. Tests have shown that about 10 percent of people sleeping in a laboratory environment who were exposed to a noise level of 50 dBA were awakened.











TABLE V

COMPARATIVE NOISE LEVELS

Typical Decibel (dBA) Values Encountered in Daily Life and Industry

d	BA
_	_

£ -3

Rustling leaves	20
Room in a quiet dwelling at midnight	32
Soft whispers at 5 feet	34
Average residence	50
Men's clothing department of large store	53
Window air conditioner	55
Conversational speech	60
Household department of large store	62
Busy restaurant	65
Typing pool (9 typewriters in use)	65
Vacuum cleaner in private residence (at 10 feet)	69
Ringing alarm clock (at 2 feet)	80
Loudly reproduced orchestral music in large room	82

Over 85 dBA, Beginning of Hearing Damage if Prolonged

Printing press plant (medium size automatic)	86
Heavy city traffic	92
Heavy diesel-propelled vehicle (about 25 feet away)	92
Air grinder	95
Cut-off saw	97
Home lawn mower	98
Turbine condenser	98
150 cubic foot air compressor	100
Banging of steel plate	104
Air hammer	107
Jet airliner (500 feet overhead)	115

Most residences have ambient noise levels that are higher than might be expected in a laboratory. Due to this higher background noise level, fewer than 10 percent of those exposed to 50-55 dBA from the aircraft would be expected to be awakened. Of course, at distances farther from the flight track, single-event noise levels will be even lower so that there would be even less intrusion into households.

A takeoff noise limit of 72 dBA would allow the aircraft listed in Table VI, including some newer technology jet aircraft, to operate at Washington National Airport throughout the night. Table VII contains the balance of the aircraft fleet for which FAA has estimated dBA levels. The aircraft in Table VII exceed the 72 dBA noise level and would not be permitted to depart from Washington National Airport during nighttime hours. Several of the aircraft which currently operate at Washington National during the night (Table IV) will be excluded by this alternative. The noise levels were estimated for each airplane as they might occur during type certification tests conducted under Appendices A, B, and C of FAR Part 36, Amendment 8. However, it should be specifically noted that the reported levels are estimates and do not represent actual certified values. This is because certification data are reported to the FAA in units of Effective Perceived Noise Level (EPNdB) for large transport category airplanes and turbojet powered aircraft. Where possible, the dBA values were estimated from certification data. Propeller-driven aircraft below 12,500 pounds gross weight are certificated in units of dBA, but the tests were conducted in level flight and do not include takeoffs and
TABLE VI ESTIMATED MAXIMUM A-WEIGHTED SOUND LEVELS FOR AIRPLANES AT PART 36 APPENDIX C LOCATIONS ***TAKEOFF***

1111

Manufacturer	Airplane	Engine	Gr. Weight 1000 Lbs	Est. dBA	Flaps
Grumman	Gulfstream I	Dart MK 529	35.1	72.0	
Beech	V 35B	10-520-в	3.4	72.0	
Beech	35-C33A	10-520-B	3.3	72.0	
Beech	F33A	10-520-B	3.4	72.0	
Gates Learjet	Learjet 35	TFE731-2	17.0	72.0	20
Gates Learjet	Learjet 36	TFE731-2	17.0	72.0	20
Gates Learjet	Learjet 35A	TFE731-2	18.0	71.6	08
Gates Learjet	Learjet 36A	TFE731-2	18.0	71.6	30
Gates Learjet	Learjet 36	188/31-2	17.0	/1.4	80
Cocone	T2101	1FE/31-2 TC10 520 P	17.0	71.4	08
Cecena	340	TS10-520-K	5.0	71.0	
Cessna	3100	10-470-VO	5.2	71.0	
Embraer	EMB 110-P2	PT6A-34	12.5	71 0	
Piper	PA-31-310	T10-540-A2C	6.5	71 0	
Piner	PA32KT-300	10-540-K1C-5D	3.6	71 0	
Swearingen	SA226-T	TPE-331-3U-303G	12.5	71.0	
Swearingen	SA226-TC	TPE-331-3UW-303G	12.5	71.0	
Swearingen	SA226-A1	TPE-331-3U-303G	12.5	71.0	
Beech	B 80	IGS0-540-AID	8.8	70.0	
Cessna	T 310R	TS10-520-B	5.5	70.0	
Piper	PA-32-300	10-540-K1A5	3.4	70.0	
Ted Smith	601	10-540-S1A5	6.0	70.0	
Beech	B6U	T10-541-E1C4	6.8	69.0	
Cessna	TU206G	TS10-520-M	3.6	69.0	
Cessna	T210M	TS10-520-K	3.8	69.0	
Cessna	185F	10-520-L	3.4	69.0	
Cessna	401	TS10-520-E	6.3	69.0	
Cessna	414	1510-520-N	6.8	69.0	
DeHavilland	DHC=7	P16A-50	43.5	69.0	
Piper	PA-23-230 PA-28P-235	10-540-CIA	2.2	69.0	
Coccere	1820	0-470-1	2.9	69.0	
Decesult Broquet	Falcon 10	TEF731-2	18 7	67 6	15
Beech	ESS	10-520-0	5.3	67.0	15
Cessna	180	0-470-1	2.8	67.0	
DeHavilland	DHC-6	PT6A-27	12.5	67.0	
Piper	PA-34-200T	TS10-360-E	4.8	67.0	
Rockwell Int'l	680FL	IGSO-540-B1A	8.5	67.0	
Beech	99A	PT6A-27	10.4	66.0	
Beech	58	10-520-C	5.4	66.0	
Cessna	177RG	IO-360-A186	2.8	66.0	
Mitsubishi	MU-2B-36A	TPE-331-5-252M	11.0	66.0	
Piper	PA-42	PT6A-41	10.5	66.0	
Beech	A24R	IO-360-A1B6	2.8	65.0	
Bellanca	17-30A	10-540-T4B50	3.3	65.0	
Beech	C90	PT6A-21	9.7	64.0	
Mitsubishi	MU-28-26A	TPE-331-5-252M	10.0	64.0	
Mooney	M200	0-360-A10	2.6	64.0	
ROCKWEII INC'I	IIZ	10-300-0100	2.0	64.0	15
Cocopaciale	ANA COIVELLE	GTC10, 520-M	13.9	63.0	12
Crumman American	404 CA-7	0 = 320 = 010	3.9	63.0	
Piner	PA-24-260	10-540-6145	3.0	63.0	
Piper	PA-28-200	10-360-010	2.7	63.0	
Beech	A100	PT6A-28	11.5	62.0	
Cessna	421B	GTS10-520-L	7.5	62.0	
Piper	PAJIT	PT6A-28	9.0	62.0	
Cessna	500	JT150-1	11.5	61.1	15
Beech	C23	0-360-A4K	2.5	60.0	
Cessna	170B	0-300-A	2.2	60.0	
Grumman American	AA-5	0-320-F2G	2.2	60.0	
Piper	PA-28-140	0-320-E2A	2.2	60.0	
Bellanca	SGCBC	0-360-C2E	2.2	59.0	
Cessna	172	0-320-A	2.3	58.0	
Mooney	MOJ	10-360-A1B6D	2.7	58.0	
Grumman American	AA-1A	0-235-62C	1.6	57.0	
Cessna	152	0-200-L20	1.7	55.0	
Cessna	150	0~200-A	1.6	55.0	
Piper	FA-18-15V	UT 32UTA28	1.8	54.0	
Rockwell Int'l	090B 700AA	(re-331-3-431K 0-320-438	10.3	54.0	
Dellanca	/GGAM	0- 120-A2D	1./	21.0	

III-28

ş.,

TABLE VII

ESTIMATED MAXIMUM A-WEIGHTED SOUND LEVELS FOR AIRPLANES AT PART 36, APPENDIX C LOCATIONS ***TAKEOFF***

Manufacturer	Airplane	Engine	Gr. Weight 1,000 Lbs.	Est. dBA	Flaps
Concorde	Concorde	0-593/M-602	400.0	112.9	
General Dynamics	CV-880-22M	CJ-805-36	193.0	107.8	
General Dynamics	CV-880-22	CJ-805-3	184.0	105.8	
Boeing	B-747-100	JT9D-3	710.0	105.7	10
McDonnell Douglas	DC8-55	JT3D-3B	328.0	105.2	
McDonnell Douglas	DC8-61	JT3D-3B	328.0	105.2	
Boeing	B-707-120	JT3C-6	258.0	104.6	
Boeing	B-/4/-200	JT9D-JA	/6/.0	104.2	10
McDonnell Douglas	DC8-50	JIJD-1 1730-38	300.0	104.2	
Mebonnell Douglas	DC8-62	173D-3B	350.0	104.2	
Roeing	8-707-420	BCO MK508	316.0	103.8	
McOoppell Douglas	DC8-40	RC0, 12	315.0	103.8	
McDonnell Douglas	DC-8-10	JT3C-6	273.0	103.8	
McDonnell Douglas	bc8-50	JT3D-3B	315.0	103.2	
Boeing	B-747-100	JT9D-JAWET	735.0	103.1	10
Boeing	B-747-200	JT9D-3A	773.0	102.8	10
Boeing	8-747-200	JT9D-7	770.0	102.6	10
McDonnell Douglas	DC8-30	JT4A-9	315.0	102.2	
Boeing	B-747-100	JT9D-7	710.0	101.5	10
Boeing	B- 747-200	JT9D-7WET	775.0	101.5	10
Boeing	B-747-100	JT9D-7WET	735.0	101.4	10
Boeing	B-707-320C	JT3D-3B	332.0	101.2	
McDonnell Douglas	DC8-62	JT3D-3B	335.0	101.2	
McDonnell Douglas	DC8-62	JT3D-7	350.0	101.2	
McDonnell Douglas	DC8-63	JT3D-7	355.0	101.2	
Boeing	B-707~320B	JT3D-3B	328.0	100.8	10
Boeing	B-747-100	JIGD 7E	750.0	100.5	10
Boeing	B-747-100	140D- 3V	750.0	100.5	10
Boeing	B=747=200 B=747=100	1705-74 1705-7457	750 0	100.3	10
Boeing	B = 747 = 100 B = 747 = 200	IT9D-7FWFT	805.0	90.5	10
Hawker Siddeley	TRIDENT IE	RB163 MK511-5	130.0	99.8	10
Hawker Siddeley	TRIDENT 2E	RE163 MK512-5	143.5	99.8	
Boeing	B-720	JT3C-7	230.0	99.6	
Boeing	B-747-200	JT9D-3AWET	773.0	99.6	10
Boeing	B-747-200	JT9D-7	770.0	99.4	10
Boeing	B-747-200	JT9D-7WET	785.0	99.3	10
Boeing	B-747-100	JT 9 D-7	710.0	99.1	10
Boeing	B-747-200	JT9D-7F	775.0	99.1	10
Lockheed	1329 JETSTAR	JT12A-B	42.0	99.1	
Boeing	B-707-320	JT4A-11	316.0	98.6	
Boeing	B-747-200	CF6-50E	820.0	97.3	10
General Dynamics	CV-990A	CJ-805-23	253.0	97.2	
Boeing	B-707-220	JT4A-3	248.0	96.6	
Boeing	B-747-200	CF6-50E	800.0	96.6	10
Boeing	B-/4/-SP	JT9D-/FWET	695.0	96.2	10
Boeing	B-/4/-SP	JT90~/A	690.0	96.1	10
Boeing	B-/4/-200 D 707 100D	KB211-524B	800.0	90.0	10
Boeing	B-707-120B B-767, 200	J I J D-J CF6-50F	238.0	93.0 05 9	10
Boeing Natikor Siddalau	D-747-200 TRIDENT 38	DB162 M2512-5	150.0	93.0	10
McDonnell Douglas	DC8-20	IT4A-3	276.0	95.8	
McDonnell Douglas	DC-10-30	CF6-50C1	590.0	95.4	06
Roeing	B-747-SP	JT9D-7A	660.0	94.9	10
Boeing	B-747-SP	JT9D-7F	660.0	94.9	10
McDonnell Douglas	DC-10-30	CF6-50C	565.0	94.5	10
McDonnell Douglas	DC-10-30	CF6-50C1	572.0	94.5	10
Boeing	B-727-200	JT8D-15	190.5	94.1	05
Boeing	B-747-200	JT9D-70A	820.0	94.1	10
McDonnell Douglas	DC-10-30	CF6-50C1	562.0	94.1	10
McDonnell Douglas	DC-10-30	CF6-50C	550.0	93.9	10
McDonnell Douglas	DC-10-30	CF6-50A	550.0	93.8	08
McDonnell Douglas	DC-10-30	CF6-50C	534.4	93.4	10
McDonnell Douglas	DC-10-30	CF6-50C1	534.4	93.1	10
Boeing	B-747-SR	JT9D-7A	610.0	92.9	10
McDonnell Douglas	DC-10-40	JT9D-59B	590.0	92.7	10
Boeing	B-/2/-200	JT8D-17RQN	208.0	92.6	05

111-29

.

IABLE VII
(Continued)ESTIMATED MAXIMUM A-WEIGHTED SOUND LEVELSFOR AIRPLANES AT PART 36, APPENDIX C LOCATIONS
TAKEOFF

		Thickort	Co. Dodaho	F	
Manufacturer	Airplane	Engine	1,000 Lbs.	dBA	Flaps
McDonnell Douglas	DC-10-40	JT9D-59A	590.0	92.4	10
Boeing	B-727-200	JT8D-17QN	203.1	92.2	05
McDonnell Douglas	DC-10-30	CF6-50A	519.6	92.2	08
Boeing	B-727-200	JT8D-9	172.5	92.1	15
Boeing	B-720B	JT3D-1	235.0	91.8	
Hawker Siddeley	TRIDENT 1	RB163 MK505-5	115.0	91.8	
McDonnell Douglas	DC-10-40	JT9D-59B	555.0	91.2	10
Boeine	B-727-100	JT8D-1	161.0	90.8	05
McDonnell Douglas	DC-10-40	JT9D-59A	555.0	90.6	10
BAC	1-11-500	SPEY MK512	104.5	90.5	
McDonnell Douglas	DC-10-40	JT9D-20	530.0	90.5	10
Boeing	B-727-200	JT8D-17RON	197.0	90.4	05
Boeing	B-727-200	JT8D-90N	184.8	90.4	15
McDonnell Douglas	DC-10-30	CF6-50C	440.0	90.4	10
McDonnell Douglas	DC-10-30	CF6-50C	440.0	90.3	10
Reging	8-727-200	1780-150N	190 5	90.2	05
Boeing	B-747-SR	JT9D-7A	570.0	90.0	10
Bockwell International	SARRE 40A	IT124-8	19.6	90.0	10
ROCKWEII INCEINALIONAI	1-11-500	SPEV MES12	99.7	80.0	
BAC	B-727-200	IT8D-170N	190.5	80.9	05
Boeing	1121 COMMODORE	C1610-5	190.5	90.7	05
	1121 CONTODORE	C1610-9	20.7	80 7	
IAI Magaabadaa Polkey	UED. 220 UANCA	C1610-5	20.7	PO 7	
Restrict Bolkow	nro-320 nansa	179D 1ECD	160.5	07./ 90.2	05
Boeing	B-727-100 B-727-200	J10D-11CD	109.5	07.J	05
Boeing	B-727-200	JIOD-IJQN	104.2	09.0	15
Boeing	B-727-200	J10D-70N	1/2.5	00.7	10
McDonnell Douglas	DC-10-10 p 727 100	1790 7FCD	440.0	00.9	05
Boeing	B-727-100	JIOD-/FCD	103.3	00./	05
Boeing	B-727-100	J10D-9FCD	169.5	00.0	15
Boeing	B-727-200	J10D-/QN	109.3	00.2	15
McDonnell Douglas	DC-10-40	J19D-20	404.0	00.4	10
McDonnell Douglas	DC-10-10		430.0	00.1	00
McDonnell Douglas	DC-10-10		440.0	88.1	80
Boeing	B-/2/-200	J18D-90N	1/2.5	87.9	15
Boeing	B-/2/-100	JT8D-IFCD	160.5	87.4	0.1
Boeing	B-/3/-200	J180-90N	117.0	8/.3	C.
Boeing	B-/27-100C	JT8D-/	160.5	87.3	05
McDonnell Douglas	DC-10-10	CF6-6D1	430.0	87.3	11
Lockheed	L-1011-1	RB211-22C	430.0	8/.1	10
Boeing	B-/3/-200	JT8D-9QN	115.5	86.9	01
Boeing	B-/37-200	JT8D-1/QN	122.5	86.9	01
Lockheed	L-1011-1	RB211-22C	422.0	86.9	10
McDonnell Douglas	DC-10-10	CF6-6D	410.0	86.9	14
Boeing	B-737-200	JT8D-9QN	114.5	86.8	01
Boeing	B-727-100	JT8D-7FCD	160.5	86.8	05
Boeing	B-737-200	JT8D-15QN	117.0	86.6	01
Boeing	B-737-200C	JT8D-15	115.5	86.5	01
Boeing	B-737-200	JT8D-7QN	109.0	86.4	01
Boeing	B-727-100	JT8D-9FCD	160.5	86.4	05
Boeing	B-/37-100	JT8D-9	111.0	86.1	
Boeing	B-/37-200	JT8D-15QN	115.5	86.1	01
Boeing	B-737-200	JT8D-9QN	115.5	86.1	01
McDonnell Douglas	DC-10-40	JT9D-20	430.0	85.6	10
Boeing	B-737-200	JT8D-9	110.7	85.5	01
McDonnell Douglas	DC-9-50	JT8D-17	121.0	85.4	
Boeing	B-737-200	JT8D-17QN	115.5	85.3	01
Lockheed	L-1011-1	RB211-22C	416.0	85.3	10
McDonnell Douglas	DC-9-30	JT8D-17	121.0	85.3	
Lockheed	L-1011-1	RB211-22C	396.0	85.2	10
Lockheed	L-1011	RB211-22B	430.0	85.1	14
McDonnell Douglas	DC-9-50	JT8D-15	121.0	85.1	
Boeing	B-737-200	JT8D-9QN	109.0	84.9	01
Gates Learjet	LEARJET 23	CJ-610-1	12.5	84.7	
Rockwell International	SABRE 60	JT12A-8	20.0	84.7	
McDonnell Douglas	DC-10-10	CF6-6D	377.5	84.5	14
McDonnell Douglas	DC-10-10	CF6-6D1	386.5	84.5	15
McDonnell Douglas	DC-9-50	JT8D-17	118.0	84.5	
McDonnell Douglas	DC9-30	JT8D-9	114.0	84.3	
-					

ļ

TABLE VIL (Continued) ESTIMATED MAXIMUM A-WEIGHTED SOUND LEVELS FOR ATEPTAND: AT PART 36, APPENDIX C LOCATIONS ***TAKEOFF***

Many, is furer	λ irj Lug	Lngine	Gr. Weight 1,000 Lbs.	Lst. dBA	Flaps
Grumnan Arerican	GULESTRIA" II	SPER MKSTI-8	65.5	84.2	20
McDonnell Deaglas	DC -9-40	.0181-11	114.0	84.1	
Boeine	B-237-200	Jico-7QN	100.5	83.8	01
McDonnell Desiglias	Du - 9- 50	JTF1/-17	115.0	83.7	
McDonnell Douglas	10 -9-30	1180-17	115.0	83.6	
McConnel, Desglas	110-9-111	13.50 -9	110.0	83.4	
Nebonneli Douglas	D(-9-50	F180-15	115.0	83.4	
Manuell Douglas	14 -9-41	1180-15	114.0	63.1	
Cortos Dans et	11 - 9- 50 11 - 12 - 14 - 15 - 15 - 15 - 15 - 15 - 15 - 15	1100-13 C1630-6	114.0	82 5	26
nation Lean Set	EEAD HE 250	C1010-6	15.0	82.6	20
Themps D. Southis	14 = 4 = 3(1)	.1180-9	108.0	82.8	2.,
Ma Donnell' Detail	D(-9-4)	JT80-11	107.0	82.5	
"Ocine 10 2	Se La ga	JT8D-7A	108.0	82.4	
5	1-1 1400	SPEY MK512	98.9	82.3	
Lockheed	1329-25 JETSTAR II	TFE731-3-1E	43.8	82.3	20
McConnell Conglas	0(-9-50	JT8D-17	110.0	82.3	
McDonnell Douglas	DC-9-30	JT8D-11	114.0	82.3	
Melonnell Dourlas	DC-9-30	JT8D-17	110.0	82.2	
McDonnell Douglas	DC-9-30	JT8D-15	110.0	82.0	
M. Lonne 11, Dr. 11	100 - 9 - 2 m	JT8D-15	110.0	82.0	
Malentier, stylias	DC-9-30	JT8D-9	103.0	81.6	
McDonnell Douglas	DC-9-30	JT8D-15	108.0	81.5	
Lockheed	L-188	501-D13	116.0	81.3	
Gates Learget	LEARJET 24D	CJ610-6	13.5	80.6	20
McDonnell Douglas	DC-9-40	JT8D-15	105.0	80.6	
McDonnell Douglas	11 9-30	JT8D-7	108.0	80.3	
Grumman American	GULFSTREAM II	SPEV MK511-8	62.0	80.1	20
Gates learjet	LEARJET 25D	C.1610-6	15.0	79.7	08
Gales Learjel Naukow Ciddalau	LEARJEL LOT	CJ01C~0	15.0	79.7	08
hawker Siddeley	A=30081=20	CF6-50C	23.5	79 /	
Alfons 171 Fokker	F=28=%1000	SPEY MK555-15	65 0	79.2	06
VEW FORSET	F-25 MK 2000	SPEY MK555-15	65.0	79.2	06
Airbus	A-300B	CF6-50A	302.0	79.1	
McDonnell Douglas	DC-9-30	JT8D-7A	94.0	79.0	
Hawker Siddeley	HS-125-3	VIPER 522	21.0	78.7	
Hawker Siddeley	HS-125-600	VIPER 601-22	25.0	78.7	
Airbus	A-30084-2C	CF6-50C	336.6	78.5	
McDonnell Douglas	bC-9-30	JT8D-15	98.0	78.5	
Aerospatiale	NORD-262C	BASIAN VIIA	22.9	78.3	
Airbus	A-300B2-1A	CF6-50A	312.4	78.3	
McDonnell Douglas	DC9-30	JT8D-1	98.0	78.3	
McDonnell Douglas	009-80	JT8D-109	140.0	/8.1	
Rockwell International	DRUE 20	GU-4BU-G166	6.5	78.0	
Altous Neukum Cildelou	A=300B4+2C	UTDED 501	330.0	77.9	
Rockwell International	CADUE 75A	CE700.2D 2	19.0	77.7	15
Ceneral Dynamics	CV=560	ALLISON 501-0130	54.6	77 3	15
McDonnell Douglas	DC9-20	IT8D-9	98.0	77.3	
McDonnell Douglas	DC9-10	JT8D-5	86.3	77.3	
McDonnell Douglas	DC9-10	JT8D-1	90.7	77.3	
McDonnell Douglas	DC9-10	JT8D-7	90.7	77.3	
Airbus	A-300B2+1C	CF6-50C	312.4	77.1	
Dassault Breguet	FALCON 2D	CF700-2D-2	28.6	77.0	10
Airbus	A-300B2-1A	CF6-50A	301.4	76.8	
Airbus	A-300B1	CF6-50A	302.0	76.8	
Airbus	A-300B2-1A	CF6-50A	302.4	76.8	
Airbus	A-300B2-1C	CF6-50C	302.0	76.0	
Airbus	A-300B2-10	CF6-50C	302.1	76.0	
Mohawk	29B	PT6A-45A	23.4	/6.0	
SHOTLS Airbuc	ע ארצעטטע אראטטעניאר	F 10A-43A	22.4	75.0	
Catos Leariet	1 FAR 1FT 26F	C 1610-500)14.4 12 E	71. 4	20
Piner	PA=31=350	T10-540-1780	7 0	74.0	20
Gates Leariet	1.FAR 1FT 94F	C 161 0=6	12 0	73 1	20
Beech	A36 (2 BL)	T0-520-B	3.6	73.0	20
Beech	35-B33	10-470-K	3.0	73.0	
Cessna	320C	TS10-470-D	5.2	73.0	
Cessna	337н	10-360-G	4 6	73 0	
		· · · · · · ·			

111-31 i

landings; therefore, these values were also estimated. While these listings provide data on a wide variety of airplane types and models within types, other specific model designations may not be shown. Operators of aircraft not listed in Table VI or VII must demonstrate, either analytically or by flight tests, that their type of airplane do not exceed the 72 dBA noise limit under certification conditions.

Since the noise levels are estimated as they might occur during type certification tests conducted under Appendix C of Part 36, these values are intended to provide a consistent basis for comparison of noise levels of major aircraft models rather than of individual aircraft. The noise levels of individual aircraft may also differ due to variations in weight and operating procedures from those used during certification. For instance, takeoff noise levels are reduced substantially as aircraft takeoff weight is reduced. Takeoff weights during normal in-service operations are often less than the maximum certificated weight. In general, for equal noise control technology, the lower the maximum weight of an airplane the lower the noise level. Conversely, those aircraft normally associated with high weight, long range operation and, therefore, greater productivity, have higher noise levels. This aspect of increasing noise levels with increasing weight is embodied in the noise certification requirements of Part 36. The takeoff noise level is also dependent on operating procedures applied. The takeoff noise level estimates may represent full thrust conditions for some aircraft and a reduced thrust condition, as permitted by FAR Part 36, for other aircraft. Neither of these conditions may be

representative of the in-service operation of a particular aircraft at a particular airport. Variations from the values of the noise estimates presented for individual flights at actual airports under the same nominal conditions could range within plus or minus 3 dBA for airplanes certificated in accordance with Part 36, and somewhat more for those airplanes not noise certificated. Additional variations in absolute value occur when aircraft operating conditions do not conform with those corresponding to noise certification. However, the relative ranking of aircraft noise levels that occur under uniform certification conditions provides the best information currently available on the relative noisiness of airplanes over a wide variety of conditions.

The same rationale applied to aircraft departing Washington National Airport at night was applied to aircraft landing at National during nighttime hours. A noise level of 85 dBA at the FAR Part 36 approach measurement point (2,000 meters from the runway threshold) produces the 72 dBA single event noise contours shown in Figure 6. As can be seen in Figure 7, the contour for the Shorts twin turboprop on an approach to runway 18 extends up the Potomac River nearly to but not extending into the densely populated area of Georgetown. Aircraft which are louder than 85 dBA at the Part 36 measurement point will produce a 72 dBA contour that would extend into populated areas, thus intruding upon residents during nighttime hours. An approach noise limit of 85 dBA (to the nearest decibel) would allow the aircraft listed in Table VIII to land at National throughout the night. Table IX contains the balance of the aircraft fleet for which FAA has









TABLE VIII

and the second second

• • • • • • • • • • • • • • • • •

ESTIMATED MAXIMUM A-WEIGHTED SOUND LEVELS FOR AIRPLANES AT PART 36, APPENDIX C LOCATIONS ***APPROACH***

			Gr. Weight	Est.	
Manufacturer	Airplane	Engine	1,000 Lbs.	dBA	Flaps
Shorts	3-30	Рт6А-45А	22.4	85.0	
DeHavilland	DHC-7	PT6A-50	43.5	84.0	
Gates Learjet	LEARJET 36	TFE731-2	17.0	83.1	40
Gates Learjet	LEARJET 35	TFE731-2	17.0	83.1	40
Gates Learjet	LEARJET 35A	TFE731-2	18.0	82.2	40
Gates Learjet	LEARJET 36A	TFE731-2	18.0	82.2	40
Rockwell International	560E	GO-480-G186	6.5	80.0	
IAI	1124 WESTWIND	TFE731-3-1G	22.9	7 9. 3	20
Aerospatiale	SN601 CORVETTE	JT15D-4	13.9	79.1	35
DeHavilland	DHC-6	PT6A-27	12.5	78.0	
Cessna	500	JT15D-1	11.5	77.4	40
Beech	B80	IGS0-540-A1D	8.8	77.0	
Piper	PA-31-350	TIO-540-J2BD	7.0	77.0	
Cessna	3200	TS10-470-D	5.2	76.0	
Embraer	EMB 110-P2	PT6A-34	12.5	76.0	
Mitsubishi	MU-2B-36A	TPE-331-5-252M	11.0	76.0	
Mitsubishi Di au	MU-2B-20A	TPE-331-5-252M	10.0	/0.0	
Piper	PA-42	P16A-41	10.5	/6.0	
riper Reskuell International	FA-31-310	110-340-A2C	0.5	76.0	
Rockwell International	690E	IPE-331-3-251K	9./	76.0	
Swaringen	000FL 61726 AT	TUSU-340-81A	0.5	76.0	
Suearingen	SA220-A1	TPE = 331 - 30 - 303G	12.5	76.0	
Swearingen	SA220-1 SA226_TC	TPE-331-30W-303C	12.5	76.0	
Beech	E55	10-520-0	5.3	75 0	
Beech	B60	TI0-541-E1C4	6.8	75.0	
Cessna	3100	10-470-V0	5.2	75.0	
Cessna	421B	GTS10-520-L	7.5	75.0	
Cessna	T310R	TS10-520-B	5.5	75.0	
Cessna	401	TS10-520-E	6.3	75.0	
Cessna	404	GTS10-520-M	8.4	75.0	
Cessna	414	TS10-520-N	6.8	75.0	
Cessna	340	TS10-520-K	6.0	75.0	
Ted Smith	601	10-540-S1A5	6.0	75.0	
Beech	C90	PT6A-21	9.7	74.0	
Beech	99A	PT6A-27	10.4	74.0	
Beech	A100	PT6A-28	11.5	74.0	
Beech	58	10-520-C	5.4	74.0	
Cessna	337H	10-360-C	4.6	74.0	
Piper	PA-23-250	10-540-C1A	5.2	74.0	
Piper	PA31T	PT6A-28	9.0	74.0	
Piper	PA-34-2001	TS10-360-E	4.8	/3.0	
Grumman American	GA-/		3.8	/2.0	
Dellanca Dinor	17-30A	10-540-14850	3.3	64.0	
riper Boach	25 022	10-540-KIG-5D	3.0	64.0	
Beech	V35p	10-470-K	3.0	62 0	
Beech	35-0334	10-520-B	33	63.0	
Beech	F334	10-520-B	3.4	63.0	
Beech	A36 (2 BL.)	10-520-B	3.6	63.0	
Cessna	T210M	TS10-520-8	3.8	63.0	
Cessna	185F	10-520-D	3.4	63.0	
Cessna	T210L	TS10-520-R	3.8	63.0	
Cessna	TU206G	TS10-520-M	3.6	63.0	
Piper	PA-28B-235	0-540-B485	2.9	63.0	
Piper	PA-32-300	10-540-K1A5	3.4	63.0	
Cessna	182Q	0-470-U	3.0	62.0	
Cessna	180	0-470-U	2.8	62.0	
Mooney	M2OJ	10-360-A1B6D	2.7	62.0	
Piper	PA-24-260	10-540-R1A5	3.2	62.0	
Beech	C23	0-360-A4K	2.5	61.0	

111-35

TABLE VIII

(Continued) ESTIMATED MAXIMUM A-WEIGHTED SOUND LEVELS FOR AIRPLANES AT PART 36, APPENDIX C LOCATIONS ***APPROACH***

Airplane	Engine	Gr. Weight 1,000 Lbs.	Est. dBA	Flaps
A24R	10-360-A1B6	2.8	61.0	
8GCBC	0-360-C2E	2.2	61.0	
177RG	10-360-A1B6	2.8	61.0	
M20C	0-360-A1D	2.6	61.0	
PA-28-200	10-360-C1C	2.7	61.0	
112	10-360-C1D6	2.6	61.0	
7GCAA	0-320-A2B	1.7	60.0	
172	0-320-A	2.3	60.0	
170B	0-300-A	2.2	60.0	
AA-5	0-320-E2G	2.2	60.0	
PA-28-140	0-320-E2A	2.2	60.0	
PA-18-150	0-320-A2B	1.8	60.0	
152	0-235-L2C	1.7	59.0	
AA-1A	0-235-62C	1.6	59.0	
150	0-200-A	1.6	58.0	
	Airplane A24R 8GCBC 177RG M20C PA-28-200 112 7GCAA 172 170B AA-5 PA-28-140 PA-18-150 152 AA-1A 150	Airplane Engine A24R IO-360-A1B6 8GCBC O-360-C2E 177RG IO-360-A1B6 M20C O-360-A1D PA-28-200 IO-360-C1D 112 IØ-360-C1D6 7GCAA O-320-A2B 172 O-320-A 170B O-320-E2G PA-28-140 O-320-E2A PA-18-150 O-320-A2B 152 O-235-L2C AA-1A O-235-62C 150 O-200-A	AirplaneEngineCr. WeightA24R10-360-A1B62.88GCBC0-360-C2E2.2177RG10-360-A1B62.8M20C0-360-A1B62.8M20C0-360-C1C2.711219-360-C1C2.711219-360-C1D62.67GCAA0-320-A2B1.71720-320-A2.3170B0-300-A2.2AA-50-320-E2G2.2PA-28-1400-320-E2A2.2PA-18-1500-320-A2B1.81520-235-L2C1.7AA-1A0-235-62C1.61500-200-A1.6	AirplaneEngineCr. WeightEst.A24RIO-360-A1B62.861.08CCBCO-360-C2E2.261.0177RGIO-360-A1B62.861.0M20CO-360-A1D2.661.0PA-28-200IO-360-C1C2.761.0112IP-360-C1D62.661.07GCAAO-320-A2B1.760.0172O-320-A2.360.0170BO-300-A2.260.0PA-28-140O-320-E2G2.260.0PA-28-140O-320-E2A2.260.0152O-235-L2C1.759.0150O-200-A1.658.0

III-36

.

K

TABLE IX

ESTIMATED MAXIMUM A-WEIGHTED SOUND LEVELS FOR AIRPLANES AT PART 36, APPENDIX C LOCATIONS ***APPROACH***

			Gr. Weight	Est.	
Manufacturer	Airplane	Engine	1,000 Lbs.	dBA	Flaps
Concorde	CONCORDE	0-593/M-602	400.0	109.5	
Boeing	B-707-320C	JT3D-38	332.0	107.8	
Boeing	B-707-320B	JT 3D-3B	328.0	106.8	
McDonnell Douglas	DC8-55	JI JU- 3B	313.0	106.8	
McDonnell Douglas	DC8-61	JT 3D- 3B	328.0	106.8	
Boeing	B-707-120B	JT30-3	258.0	105.8	
Boeing	B-747-100	JT9D-3AWET	735.0	105.8	30
Boeing	B-747-100	JT9D-7WET	735.0	105.6	30
Boeing	B-747-100	JT9D-7	710.0	105.3	30
Boeing	в-720в	JT3D-1	235.0	104.8	
McDonnell Douglas	DC8-50	JT3D-1	300.0	104.8	
Boeing	B-747-160	JT9D-3	710.0	104.6	30
McDonnell Douglas	DC8-62	JT 3D-7	350.0	103.8	
McDonnell Douglas	D(8-63	JT 3D-/	355.0	103.8	
Reging	DC6-40 R.747 200	RCU. 12	315.0	103.0	20
Boeing	B=747=200 B=747=200	JI JD- 3A IT9D- 3A	767 0	103.4	30
Boeing	B-747-200	JT9D-7WFT	775 0	103.0	30
Hawker Siddelev	TRIDENT 3B	RB163 MK512-5	150.0	102.9	50
McDonnell Louglas	DC9-3.:	JT8D-7	108.0	102.9	50
McDonnell Douglas	DC9-30	JT8D-9	114.0	102.9	50
Boeing	B-747-200	JT9D-7	770.0	102.5	30
Hawker Siddeley	TRIDENI 1E	RB163 MK511-5	130.0	101.9	
Hawker Siddeley	TRIDENT 2E	RB163 MK512-5	143.5	101.9	
McDonnell Douglas	DC9-10	JT8D-5	86.3	101.9	
McDonnell Douglas	DC9-10	JT8D-7	90.7	101.9	
McDonnell Douglas	DC9-10	JT8D-1	90.7	101.9	
McDonnell Douglas	DC9-20	JT8D-9	98.0	101.9	
McDonnell Douglas	D(9-30	J18D-1	98.0	101.9	50
Boeing	B=737=200	JI00-11 JT8D-9	114.0	101.9	20
Boeing	B-737-2000	JT8D-15	115.5	101.6	40
Boeing	B-707-120	JT3C-6	258.0	101.0	40
Lockheed	1329 JETSTAR	JT12A-8	42.0	101.0	50
Hawker Siddeley	TRIDENT 1	RB163 MK505-5	115.0	100.9	
McDonnell Douglas	DC8-63	JT 3D- 3B	350.0	100.8	
McDonnell Douglas	DC8-62	JT3D-3B	350.0	100.8	
McDonnell Douglas	DC8-62	JT3D-3B	335.0	100.8	
Boeing	B-707-220	JT4A-3	248.0	100.6	
Boeing	8~727-100	JT8D-1	161.0	100.2	40
Soeing	8-727-100C	JT8D-7	160.5	100.2	40
TAT	B-/3/-100	JT8D~9	111.0	100.0	40
McDonnell Douglas	DC8-20	CJ010-3	276 0	100.0	
McDonnell Douglas	DC8-10	J14A-J IT3C-6	270.0	97.0 00 8	
McDonnell Douglas	DC8-30	JT44-9	315.0	99.8	
Boeing	B727-200	JT8D-9	172.5	99.7	40
Boeing	B-727-200	JT8D-15	190.5	99.7	40
McDonnell Douglas	DC-10-30	CF6-50C1	590.0	99.2	50
IAI	1123 WESTWIDN	CJ610-9	20.7	99.0	
Messerschmitt-Bolkow	HFB-320 HANSA	CJ610-5	20.2	99.0	
BAC	1-11-500	SPEY MK512	99.7	98.6	
Boeing	I-JJ-300 B 707 130	SPEY MKS12	104.5	98.6	
Boeing	B-707-320 B-720	J14A-11 1T2C 7	316.0	98.6	
Hawker Siddelev	HS-125-600	JIJC-7 VIDED 601 22	230.0	98.0 09 F	
McDonnell Douglas	DC-10-30	CF6-50C	550 D	90.3	50
McDonnell Douglas	DC-10-30	CF6-50C	565.0	98.0	50
McDonnell Douglas	DC-10-30	CF6-50A	550.0	98.0	50
Boeing	B-707-420	RCO. MK508	316.0	97.8	
Boeing	B-747-100	JT9D-7FWET	750.0	97.8	30
Boeing	B-747-100	JT9D-7F	750.0	97.8	30
McDonnell Douglas	DC-10-30	CF6-50A	519.6	97.8	50
McDonnell Douglas	DC-10-30	CF6-50C	440.0	97.6	50
Nawker Siddeley	HS-125-3	VIPER 522	21.0	97.5	
nawker Siddeley	HS-125-400	VIPER 522	23.3	97.5	
Boeing	B-747-100	JT9D-7WET	750.0	9 7.3	30
DOCING	B=74200	RB211-524B	800.0	97.2	30

34

TABLE IX (Continued) ESTIMATED MAXIMUM A-WEIGHTED SOUND LEVELS FOR AIRPLANES AT PART 36, APPENDIX C LOCATIONS ***APPROACH***

Manufacturer	Airplane	Freine	Gr. Weight	Est. dBA	Flans
manuracturer	Allplane	Lingine	1,000 108.	<u>un</u>	11495
Boeing	B-747-100	JT9D-7	710.0	97.2	30
Boeing	B = 747 = 200 B = 747 = 200	JT9D-7WET	785.0 775 D	96.7	30
Hawker Siddeley	HS-125-1A	VIPER 521	19.6	96.5	
McDonnell Douglas	DC-10-40	JT9D-59A	590.0	96.5	50
McDonnell Douglas	DC-10-40	JT9D-59B	590.0	96.5	50
Boeing	B-747-SR	JT9D-7A	610.0	96.1	30
Boeing	B-747-200 B-747-200	JI90-7 JT90-3AWET	773.0	96.1	30
Boeing	B-727-100	JT8D-9FCD	160.5	96.0	40
Boeing	B-727-100	JT8D-9FCD	169.5	96.0	40
Boeing	B-747-200	JT9D-3A	767.0	95.9	30
Gates Learjet	LEARJET 25D	CJ610-6	15.0	95.7	40
McDonnell Douglas	DC-10-40	JT9D-59A	555.0	95.6	35
McDonnell Douglas	DC-10-40	JT9D-59B	555.0	95.6	35
Boeing	B-747-200	CF6-50E	800.0	95.5	30
Boeing	B = 747 = 200	CF6-50E	820.0	95.5	30
McDonnell Douglas	DC-10-10	CF6-6D	440.0	95.3	50
McDonnell Douglas	DC-10-10	CF6-6D1	440.0	95.3	50
McDonnell Douglas	DC-10-40	JT9D-20	530.0	95.3	50
Boeing	B-747-200	JT9D-70A	820.0	95.2	30
General Dynamics	CV-880-22 CV-880-22M	C1-805-3B	184.0	94.8	
McDonnell Douglas	DC-9-30	JT8D-17	121.0	94.8	5ü
McIonnell Douglas	DC-9-50	JT8D-15	121.0	94.8	50
McDonnell Douglas	DC-9-50	JT8D-17	121.0	94.8	50
Gates Learjet	LEARJET 24D	CJ610-6	13.5	94.7	40
McDonnell Douglas	DC-10-10	CF6-6D1	430.0	94.6	50
McDonnell Douglas	DC-10-10	CF6-6D	430.0	94.6	50
Boeing	B-727-100	JT8D-1FCD	160.5	94.5	40
Boeing	B-727-100	JT8D-7FCD	160.5	94.5	40
Boeing	B = 727 = 100 B = 727 = 100	JISD-/FCD	169.5	94.5	40 40
McDonnell Douglas	DC-10-40	JT9D-20	484.0	94.5	se
Boeing	B-747-200	CF6-50E	775.0	94.4	30
McDonnell Douglas	DC-10-10	CF6-6D1	386.5	94.1	50
VFW Fokker	F-28 MK1000	SPFY MK555-15	410.0	94.1	20 42
McDonnell Douglas	DC-9-50	JT8D-17	118.0	94.0	40
McDonnell Douglas	DC-9-50	JT8D-15	115.0	94.0	40
Gates Learjet	LEARJET 25C	CJ610-6	15.0	93.8	40
McDonnell Douglas	DC-10-30 DC-10-40	UT9D-20	572.0	93.8	35 50
Boeing	B-747-SP	JT9D-7FWET	695.0	93.5	30
Boeing	B-747-SP	JT9D-7F	660.0	93.1	30
Boeing	B-747-SP	J19D-7A	690.0	93.1	30
Boeing	R-747-SP	.IT9D-7A	20.0 660 0	93.1	40
McDonnell Douglas	DC-10-30	CF6-50C	534.4	92.8	35
Lockheed	L-1011-1	RB211-22C	430.0	92.7	42
McDonnell Douglas	DC-10-30	CF6-50A	550.0	92.6	35
McDonnell Douglas McDonnell Douglas	DC-9-40 DC-9-40	JT8D-15 JT8D-11	114.0	92.3	50 50
Boeing	B-727-100	JT8D-9FCD	169.5	92.2	30
McDonnell Douglas	DC-10-30	CF6-50C	440.0	92.2	35
McDonnell Douglas	DC-10-30	CF6-50A	519.6	92.2	35
poeing Lockbeed	B-/3/-200	JT8D-15QN RB211-22B	115.0	92.1	40 42
Boeing	B-737-200	JTED-90N	117.0	92.0	40
McDonnell Douglas	DC-9-30	JT8D-9	110.0	92.0	50
Rockwell International	SABRE 60	JT12A-8	20.0	92.0	24
Rockwell International Rocies	SABRE 40A	JT12A-8	19.6	92.0	
Boeing	B-737-200 B-737-200	лу р- А йм Тавр - В им	114.5	01 0 91.9	40 40
Boeing	B-737-200	JT8D-150N	117.0	91.9	40
McDonnell Douglas	DC-9-30	JT8D-15	114.0	91.9	50
McDonnell Douglas	DC-9-30	JT8D-9	114.0	91.9	50
ncuonnell Douglas	DC-9-80	JT8D-109	108.0	91. 7	50

III-38

TABLE IX (Continued) ESTIMATED MAXIMUM A-WEIGHTED SOUND LEVELS FOR AIRPLANES AT PART 36, APPENDIX C LOCATIONS ***APPROACH*** -

	AITKOACI		Gr. Weight	Est.	
Manufacturer	Airplane	Engine	1,000 Lbs.	dBA	Flaps
	NG 0 20	1700 15	110.6	01 7	50
McDonnell Douglas	DC-9-30 p 727 200	J180-13	110.0	91./	50
Airbus	A = 300B4 = 200	CF6-50C	330 0	91.0	25
Airbus	A-300B4-2C	CF6-50C	336.6	91.5	25
Airbus	A-30084-2C	CF6-50C	346.5	91.5	25
Airbus	A-300B1	CF6-50A	302.0	91.4	15
Airbus	A-300B2-1A	CF6-50A	302.4	91.4	15
Lockheed	1-1011-1	RB211-22C	416.0	91.4	33
Lockheed	L-1011-1	RB211-22C	422.0	91.4	33
Airbus	A-300B2-K-3C	CF6-50C	312.4	91.3	25
Lockheed	L-1011	RB211-228	430.0	91.3	33
McDonnell Douglas	DU-9-30	JT8D-15	108.0	91.3	20
Grumman American Bouing	B-737-200	TRD-170N	122 5	91.1	40
Airbus	A=300B	CF6-504	302 0	90.9	25
Airbus	A-300B2-1A	CF6-50A	312.4	90.9	25
Airbus	A-300B2-1C	CF6-50C	312.4	90.9	25
Boeing	B-737-200	JT8D-9QN	109.0	90.8	40
Lockheed	L-1011-1	RB211-22C	416.0	90.8	33
Airbus	A-300B2-1A	CF6-50A	301.4	90.7	25
Airbus	A-300B1	CF6-50A	302.0	90.7	25
Airbus	A-300B2-K-3C	CF6-50C	312.4	90.7	15
Airbus	A-30082-1C	CF6-50C	302.1	90.7	25
Boeing	B-727-200	J180-/UN	109.5	90.0	40
Airbue	$4 = 300B^2 = 1C$	JI0D-/UN CR6-50C	1/2.5	90.0	40
Airhus	A-300B2-10	CF6=504	312.4	90.4	15
Airbus	A = 300B2 = 1C	CF6-50C	302.0	90.4	15
McDonnell Douglas	DC-10-40	JT9D-20	530.0	90.3	35
Rockwell International	SABRE 75A	CF700-2D-2	23.0	90.3	25
McDonnell Douglas	DC-9-30	JT8D-7A	108.0	90.2	50
McDonnell Douglas	DC-10-10	CF6-6D1	440.0	90.2	35
McDonnell Douglas	DC-10-10	CF6-6D	440.0	90.2	35
Airbus	A-300B4-2C	CF6-50C	330.0	90.0	15
Airbus	A-300B4-2C	CF6-50C	336.6	90.0	15
Alfbus	A-30084-20	CF6-50C	346.5	90.0	15
McDoppell Develop	DC-9-30	KB211-220	396.0	90.0	50
Gates Leariet	1 FARIET 23	J10D-/A C1-610-1	94.0	89.9 80 7	50
McDonnell Douglas	DC - 10 - 10	CF6-6D1	430 0	89.6	35
McDonnell Douglas	DC-10-10	CF6-6D	430.0	89.6	35
Lockheed	L-188	5D1-D13	116.0	89.5	
Boeing	B-727-100	JT8D-7FCD	169.5	89.1	30
Boeing	B-727-100	JT8D-7FCD	160.5	89.1	30
Boeing	B-727-100	JT8D-1FCD	160.5	89.1	30
Boeing	B-727-100	JT8D-1FCD	169.5	89.1	30
McDonnell Douglas	DC-10-10	CF6-6D1	386.5	89.1	35
McDonnell Douglas	DC-10-10	ULO-01 1101-20	410.0	89.1	55 25
Aerospatiale	NORD 2620	BASTAN VITA	404.0	88 9	22
Boeing	B-727-200	JT8D-90N	172.5	88.9	40
Boeing	B-727-200	JT8D-150N	184.2	88.9	40
Boeing	B-727-200	JT8D-15QN	190.5	88.9	40
Boeing	B-727-200	JT8D-17QN	190.5	88.9	40
Boeing	B-727-200	JT8D-17QN	203.1	88.9	40
Boeing	B-727-200	JT8D-17RQN	208.0	88.9	40
Boeing	B-727-200	JT8D-9QN	184.8	88.9	40
Boeing	B-121-200 B-727 200	JT8D-17RON	197.0	88.9	40
Boeine	B-737-200	JIBD-/QN	109.0	88.8	40
Grumman American	GULESTREAM T	100-70N	700'2	00.0 90 4	40
McDonnell Douglas	DC-10-40	UARI FURJEY	1.55	00.0	75
Boeing	B-737-200	JT8D-170N	430.0	88 J	32
Boeing	B-737-200	JT8D-150N	115 5	88 1	30
Boeing	B-737-200	JT8D-150N	117.0	88.3	30
Gates Learjet	LEARJET 24E	CJ610-6	12.9	88.3	40
Gates Learjet	LEARJET 24F	CJ610-6	13.5	88.3	40
Lockheed	L329-25 JETSTAR II	TFE731-3-1E	43.8	88.3	50
Gates Learjet	LFARJET 25F	CJ610-6	15.0	88.2	40
vrw Fokker	F-27-200	MK532-7	43.5	88.1	

111-39

1.1

TABLE IX (Continued) ESTIMATED MAXIMUM A-WEIGHTED SOUND LEVELS FOR AIRPLANES AT PART 36, APPENDIX C LOCATIONS ***APPROACH***

Manufacturer	Airplane	Engine	Gr. Weight 1,000 Lbs.	Est. dBA	Flaps
Boeing	B-737-200	JT8D-9QN	109.0	87 .9	30
Boeing	B-737-200	JT8D-9QN	114.5	87.9	30
Boeing	B-737-200	JT8D-9QN	115.5	87.9	30
Boeing	B-737-200	JT8D-90N	117.0	87.9	30
Boeing	B-737-200	JT8D-70N	172.5	87.4	30
Boeing	B-727-200	JT8D-70N	169.5	87.4	30
VFW Fokker	F-27-400/600	MK532-7R	43.5	86.8	
General Dynamics	CV-580	ALLISON 501-D13D	54.6	86.3	
Dassault Breguet	FALCON 10	TFE731-2	18.7	86.2	52
Boeing	B-727-200	JT8D-150N	184.2	86.1	30
Boeing	B-727-200	JT8D-90N	184.8	86.1	30
Boeing	B-727-200	JT8D-17RON	197.0	86.1	30
Boeing	B-727-200	JT8D-150N	190.5	86.1	30
Boeing	B-727-200	JT8D-170N	203.1	86.1	30
Boeing	B-727-200	JT8D-170N	190.5	86.1	30
Boeing	B-727-200	JT8D-17RON	208.0	86.1	30
Mohawk	298	PT6A-45A	23.4	86.0	•••
Boeing	B-737-200	JT8D-7QN	100.5	85.8	30

Ι.

Charles.

estimated dBA levels. The aircraft listed in Table VI exceed the 85 dBA noise limit and would not normally be permitted to land at National Airport during nighttime hours.

Based on the above analysis, a noise limitation of 72 dBA on takeoff and 85 dBA on approach, as measured under 14 CFR 36 conditions, was chosen as the operational limits from 10:00 p.m. through 6:59 a.m., and was included as an assumption in the three new alternatives considered here.

AIR QUALITY

The August 1980 Environmental Impact Statement compared the air quality impacts associated with the five alternative policies, in terms of the projected emissions inventory at each of the three principal airports serving the Metropolitan Washington area. In addition, at the two Federal airports, ambient ground-level concentrations of carbon monoxide, total unburned hydrocarbons, nitrogen dioxide, and particulates were estimated for each of the five alternative policies, using an atmospheric dispersion model. Since the amount of emissions and the level of pollutant concentrations are related to three key factors (the number of passengers using each facility, the number of aircraft operations, and the type and number of engines on those aircraft), it is possible to infer the 1990 air quality impacts associated with the additional alternative policies addressed in this Final Supplement to the Environmental Impact Statement.

The conservative approach that was used in the August 1980 Environmental Impact Statement tends to overstate the aircraft contribution to an emissions inventory and to predicted ambient concentrations of pollutants. Since use of a conservative approach affects absolute values only, and does not effect a comparative analysis of alternative policy impacts, the same assumptions were used in considering the impacts of the additional alternative policies. The two principal contributions to the relatively high aircraft contributions are assumptions concerning emission factors and landing-takeoff (LTO) cycle. Subsequent to the preparation of the anlayses for the August 1980 Environmental Impact Statement, the Environmental Protection Agency (EPA) revised its aircraft emissions factors. The 1973 emission factors, used in the analyses, were higher than the emissions factors published by the EPA in 1980. For the computations of aircraft emissions used in the 1980 analyses, it was assumed that there will be no further reductions in these factors through 1990. In addition, the standard landing-takeoff cycle adopted by the Environmental Protection Agency was used for all scenarios at all three airports, in calculating aircraft emissions loading. The landing-takeoff cycle is different for each airport, depending primarily on the taxi-idle portion of the cycle where most of the aircraft contribution to carbon monoxide and hydrocarbon emissions occurs. For example, the taxi-idle portion of the EPA LTO cycle is 26 minutes. Typical times for taxi-idle are 16 minutes at Washington National Airport, 12 minutes at Baltimore-Washington International Airport, and 9 minutes at Dulles International Airport.

Daily Emissions Inventory

The daily emissions inventory in Table X is a convenient summary for comparing the pollution impact of alternative policies. The inventory is a sum of the aircraft emissions, airport-related emissions from automobile traffic and service-vehicles, and emissions from automobiles traveling to and from the three airports. The emissions inlcuded in the inventory are carbon monoxide, total unburned hydrocarbons, nitrogen oxides, total suspended particulates, and sulfur dioxide.

The total emissions inventories associated with the first five alternative policies in the table were compiled from information in the August 1980 Environmental Impact Statement. The emissions inventories associated with the three additional alternative policies were estimated from the projected passenger activity and the number and types of aircraft forecast to be operating at Washington National Airport under each policy alternative.

Washington National Airport and Dulles International Airport are both in the National Capital Interstate Air Quality Control Region (AQCR), and Baltimore-Washington International Airport is in the Metropolitan Baltimore Intrastate AQCR. Table X indicates that for Washington National Airport alone, the emissions loading is more sensitive to alternative policy considerations than the emissions inventories in the National Capital Interstate AQCR and in the biregional area (both AQCRs). The emissions loadings for these three additional alternatives at Washington National Airport are within the

TABLE X

TOTAL EMISSIONS INVENTORY (thousands of pounds per day)

	Washington National	Dulles International	Total in National Capital Interstate AQCR	Baltimore- Washington International	Total both AQCRs
Reduced Activity (14 million passengers annually at Washington National)	51.7	114.6	166.3	72.5	238.8
Controlled Growth (16 million)	55.5	105.6	161.1	68.8	229.9
Controlled Growth (18 million)	61.5	99.2	160.7	63.7	224.4
No Policy Change (19.2 million)	64.1	91.1	155.2	60.4	215.6
Expanded Growth (21.8 million)	74.4	92.8	167.2	56.0	223.2
Controlled Activity with Noise Limitations (16 million)	57.0 (63.0)*	106.0	163.0 (169.0)*	69.0	232.0 (238.0)*
Unconstrained Activity with Noise Limitations (22.8 million)	63.0 (71.)*	0.06	153.0 (161.0)*	54.0	207.0 (215.0)*
Controlled Activity with Noise Limitations as modified (16 million)	57.0 (63.0)*	106.0	163.0 (169.0)*	69.0	232.0 (238.0)*

*With widebody aircraft at Washington National Airport.

and the second se

1

111-44

range of the five alternative policies evaluated in the August 1980 Environmental Impact Statement. The Controlled Activity alternative and the Controlled Activity alternative as modified by the House of Representatives amendment, with 30% fewer passengers and 20% fewer operations in 1990, have lower emissions inventories at Washington National Airport than the Unconstrained Activity alternative, but the regional and bi-regional impacts of the two Controlled Activity alternatives are greater than the Unconstrained Activity alternative. If widebody aircraft models were accepted at Washington National Airport, the emissions inventories for the three new alternatives would increase about 10%, as shown in Table X.

The emissions inventories for the first two alternative policies are lower than the values which were shown in the Draft Supplement to the Environmental Impact Statement issued in July 1981. The calculations presented there were less precise than the revised values, inasmuch as the emissions factors used previously were all associated with older technology engines. The revised inventories, included here, use emissions factors associated with the new-technology engines which would be required for aircraft meeting the noise limitations after 1986.

Ambient Concentrations

In the August 1980 Environmental Impact Statement, an atmospheric dispersion model was used to estimate the ambient concentrations of

carbon monoxide, hydrocarbons, nitrogen dioxide and particulates from all sources at various locations in the vicinity of Washington National and Dulles International Airport.

The results of the dispersion analysis in the August 1980 Environmental Impact Statement were presented in a series of tables, in which the airport-related emissions were forecast for various locations in the airports' vicinity, and the airports' contributions were added to a non-airport wackground concentration. The background concentrations were based on measurements at other locations and on Metropolitan Washington Council of Governments regional projections, and may α may not be representative of the non-airport contributions at each of the locations analyzed. It is important to note that the estimated total ambient concentration at any location is sensitive to the assumed background levels.

The National Capital Interstate AQCR complies with the nitrogen dioxide standard. Application of the dispersion model indicated that the standards may be exceeded at several locations under any of the alternative policies considered. Application of that model to the three new policy alternatives would result in similar indications. It is recognized that application of any simple dispersion model to reactive gases, such as nitrogen oxides, is likely to indicate artifically high estimates since it assumes that all nitrogen oxides are converted to nitrogen dioxide and that no other chemical reactions occur during the dispersion processes.

Nitrogen dioxide is related to the ozone level, which is a regional problem, not a local problem. It should be noted that the airport is a minor source of nitrogen dioxide within the AQCR in comparison to major sources such as power plants and motor vehicles. In a recent FAA/EPA study³, the annual average nitrogen dioxide concentration at Washington National Airport was estimated to be 0.03 ppm with aircraft accounting for one-sixth of that estimated average. These levels are well below the standard, and the aircraft contribution is much smaller than indicated by the dispersion method.

The hydrocrabon standard was first set in 1971, but has been used as a guide in meeting EPA's national ambient standard for ozone. On May 15, 1981, the EPA proposed to recind this unused air quality standard because "review of the scientific data underlying this outdated standard confirms that it has no utility under the current Clean Air Act and should be dropped." The August 1980 Environmental Impact Statement discussed hydrocarbon emissions relative to the national ambient standards. This hydrocarbon "standard" would be exceeded for any of the policy alternatives, since the background (non-aviation) levels for hydrocarbon exceed the national ambient standard in either an urban (Washington National Airport) or rural (Dulles International Airport) setting.

^{3 &}quot;Impact of Aircraft Emissions on Air Quality in the Vicinity of Airports," FAA-EE-80-09A, July 1980.

The following discussion addresses the projected results of the alternative policies on ambient concentrations of carbon monoxide and particulates at Washington National Airport. There were no violations of the one-hour carbon monoxide or particulate standards in the analysis of the 1979 base case. The eight-hour carbon monoxide standard was estimated to be exceeded at half of the locations. The airport contribution, by itself, was below the standard, but the assumed background level was close to the standard without the airport contribution. A range of possible carbon monoxide background values for 1990 was included in the tables prepared for the five alternative policies analyzed. Based on the lower background value, all of the 1979 violations are eliminated under any of the policy alternatives analyzed earlier, and would be eliminated for either of the additional alternative policies presented here. Based on the higher background value, the ambient concentrations at one location (the vicinity of the terminal building at Washington National Airport) is projected to exceed the eight-hour carbon monoxide standard under the Expanded Growth Policy. This location is dominated by ground vehicle emissions. No other location was estimated to exceed the national ambient carbon monoxide standard for any of the five earlier policies. Comparing those results with the important parameters of the three additional policy alternatives presented here, it may be inferred that none of the three additional policy alternatives will result in a violation of the one-hour carbon monoxide standard, but the Unconstrained Activity

Policy alternative would contribute to a violation of the eight-hour carbon monoxide standard at the same location previously used. The two Controlled Activity alternatives would not contribute to a violation of that standard. These inferences assume that the higher value of background level and the same assumptions used in the earlier analyses are retained.

For 1990, a range of background particulate levels was used in estimating total suspended particulates. With the upper end of the range of the annual geometric mean of total suspended particulates estimated to equal the national ambient standard, any airport contribution results in a violation of that standard. Therefore, since background levels are high, any policy alternative causes a deleterious impact, despite a small airport contribution.

There are no present or future forecast violations of the carbon monoxide or particulates standards in the vicinity of Dulles International Airport as a consequence of any of the policy alternatives considered previously or in this supplement.

Mitigating Actions

It should be noted that these air quality analyses assumed "worst case" conditions, assumed that no changes would be made to the roadway system at the airport, and assumed that no other steps would be taken to mitigate emissions from surface vechicles. The adoption of an



operating policy would provide a basis for airport muser planning which could result in an improvement to the internal roadway system. Such an improvement would translate into reduced pollution concentrations at selected receptors (such as the one in front of the terminal building).

SURFACE ACCESS

The August 1980 Environmental Impact Statement analyzed surface access to the three Washington-area airports, for the five policy alternatives presented there. The major effects among the five alternatives appeared at Washington National Airport, where the annual passenger volumes varied from 14,000,000 (Reduced Activity Policy) to 21,750,000 (Expanded Growth Policy). The relative impacts of each policy varied in relation to the number of passengers associated with each policy alternative. With the exception of some momentary traffic stoppages on the southbound off-ramp from George Washington Parkway to Washington National Airport (Level of Service E) under the Expanded Growth Policy, no serious traffic impacts were expected from the five policy alternatives.

The impact of the Unconstrained Activity Policy alternative on surface access will be quite similar to those presented in the August 1980 Environmental Impact Statement for the Expanded Growth Policy alternative. The impacts on surface access for the three Washington-area airports, under the two Controlled Activity Policy alternatives would be similar to those presented in the August 1980 Environmental Impact Statement for the two Controlled Growth alternatives.

111 - 50

Using the FAA's aircraft fuel burn model, fuel consumption estimates were derived for typical short and long haul flights to and from Washington National Airport for each of the following aircraft types. Since data were available for only these types, it was assumed that they were representative of the aircraft types serving Washington National Airport under the noise restriction alternatives.

> 2-engine narrow body (2ENB): DC-9, 757 2-engine widebody (2EWB): A-300, 767 3-engine narrowbody (3ENB): 727-200 3-engine widebody (3EWB): L1011, DC-10

Note: This assumption does not imply any finding by the Administrator as to the approved use of any of these models at Washington National Airport, which are not now operating there. These models of aircraft are cited purely to illustrate the expected performance characteristics for analysis purposes.

Table XI lists for Washington National Airport the May 1981 air carrier operations and the forecast operations for October 1981 and 1990 under the three new policy alternatives. Based on the forecasts in Table XI, total air carrier daily fuel consumption at Washington

National Airport was calculated (see Table XII). The absolute numbers in Table XII are gross estimates based on assumption of representative flight profiles, trip lengths, aircraft types, etc. Although the numbers do not quantify accurately the total daily fuel burn, the percentage differences among the numbers provide a useful estimate of the fuel impacts of the policy alternatives. Therefore, the fuel consumption data are indexed (each number in Table XII is divided by the May 1981 base case figure); the results are displayed in Table XIII.

There are four aspects to the noise restriction alternatives which impact the air carrier fuel consumption at Washington National Airport—scheduling limitations, noise limitations, aircraft limitations, and nonstop perimeter limitations. The following discussion briefly identifies the direction of the impacts of these variables.

Scheduling Limitations

Air carriers are currently limited to 40 operations per nour at Washington National Airport. The introduction of a 37 operations per hour limitation would normally result in fewer permitted operations and fewer gallons burned as a result. The August 1980 Environmental Impact Statement indicated that sufficient capacity exists at Galtimore-Washington International and Dulles International Airports to Habdle the forecast demand there for the next 10-15 years. Washington

111-52

National Airport, however, has a capacity constraint. Therefore, imposing a 37 operations per hour limitation provides an additional benefit in terms of energy by limiting congestion and air carrier delay, thereby minimizing excess fuel use per operation at Washington National Airport. Alternatives which allow unconstrained activity will produce the opposite effect. Fuel use will increase due to a greater number of operations and greater fuel consumption per operation caused by aircraft delays.

The scheduling limitation has little or no effect in the short run. In May 1981 air carriers were only using an average of 560 of the 640 daily operations plus extra sections allowed under the current policy (40 per hour x 16 hours). A limitation of 37 operations per hour allows 555 (37 per hour x 15 hours) daily air carrier operations plus extra sections. There is no difference between the fuel impact of the controlled activity and unconstrained activity alternatives in October 1981 because the number of operations is not significantly, if at all, different in these two cases.

In 1990, however, the scheduling limitation restricts the increase in fuel use significantly. The controlled activity case results in a 22 percent increase (34 percent with widebody aircraft) over the May 1981 figure; fuel use rises 37 percent (59 percent with widebody aircraft) with unconstrained activity.

Noise Limitations

The noise limitations will not have any significant effect on energy consumption in 1981. However, in order to meet the noise limitations after 1986, only new technology aircraft can be used at Washington National Airport in 1990. Therefore, air carriers wishing to serve Washington National Airport will achieve improved fuel efficiency as well as quieter operation.

The new technology aircraft generally offer greater seating capacity than the existing narrow bodies which serve Washington National Airport. Therefore, assuming load factors remain constant, the same number of passengers can be served with fewer flights. Nevertheless, under both alternatives fuel consumption increases from October 1981 to 1990 despite the use of the more fuel-efficient aircraft. Assuming more passengers are being seved at Washington National Airport in 1990, fuel efficiency (in terms of passenger miles per gallon) may increase although total fuel consumption also increases. In the unconstrained activity alternative, fuel use rises due to a significant increase in the number of operations as well as the introduction of larger capacity aircraft.

Aircraft Limitations

Under current restrictions, widebody aircraft are prohibited at Washington National Airport. If carriers continue to provide the same number of flights substituting widebodies on certain flights, fuel consumption will go up. From Table XIII it is obvious that in each case fuel consumption is higher with widebody aircraft than without widebodies. The introduction of widebodies (which provide additional capacity and burn more fuel) at Washington National Airport is fuel-efficient only if the carriers reduce the number of flights to maintain load factors, or if passenger demand rises significantly to again maintain load factors. In these instances, overall fuel consumption may increase, but fuel efficiency in terms of passenger-miles per gallon will also increase.

Nonstop Limitation

Air carriers are currently limited to a 650 statute mile nonstop operating limitation, plus seven "grandfather" cities, at Washington National Airport. For the three additional alternative policies considered here, the nonstop perimeter is established at 1,000 statute miles. Air carriers would be expected to offer direct, nonstop service to several new major markets, e.g., New Orleans and Kansas City, which are within the new operating limitations. The average trip length for flights greater than 500 miles will increase somewhat, but not to a major extent. In those alternatives with controlled activity at Washington National Airport, the air carriers would be expected to drop some of the short-haul flights and substitute service to the newly available cities. Although total fuel consumption would rise to some extent, energy efficiency, in terms of passenger-miles per gallon, should increase since the longer stage lengths have a greater portion

III~55

of their flight time at cruise altitudes, where flight is more fuelefficient.

SUMMARY

Based on the forecast of operations in Table XI, air carrier fuel consumption at Washington National Airport increases 11 percent from May to October 1981. The proposed scheduling limitation and noise restriction have no effect in the short run. Fuel use rises due to an increase in the number of operations and, to a lesser extent, the slightly longer average trip length resulting from the proposed 1,000 mile nonstop perimeter. The introduction of widebodies would cause an additional 2 percent increase in fuel consumption in 1981.

In the longer run, 1990 fuel consumption rises anywhere from 22 to 59 percent over the base case (May 1981) depending on the policy alternative. In 1990, the scheduling limitation is effective in controlling the increase in fuel consumption. Fuel use rises significantly more for the unconstrained activity alternative than for the controlled activity cases. The noise restriction also impacts fuel use in 1990. New technology aircraft which meet the 80 dBA noise limit generally offer greater seating capacity than the existing narrowbodies which serve Washington National Airport. Although total fuel use may rise, fuel efficiency (in terms of passenger miles per gallon) may also increase if sufficient demand exists to maintain or increase load factors.

OTHER ENVIRONMENTAL IMPACTS

The impacts in the remaining environmental disciplines, including parklands and historical sites; social and economic conditions; and natural systems, are contained within the range of impacts assessed in the August 1980 Environmental Impact Statement. Moreover, the impacts at Dulles International and Baltimore-Washington International Airports for the proposed revised policy alternatives are also reflected within the range of impacts assessed in the August 1980 Environmental Impact Statement.

III-57

TABLE XI

FORECAST OF AIR CARRIER OPERATIONS AT WASHINGTON NATIONAL AIRPORT

	<u>1981</u>	1990
Existing Conditions (May 1981)	560	N.A.
Controlled Activity*		
No Widebody Aircraft	589	589
With Widebody Aircraft	572	558
Unconstrained Activity*		
No Widebody Aircraft	596	676
With Widebody Aircraft	572	676
Controlled Activity Modified*		
No Widebody Aircraft	625	589
With Widebody Aircraft	608	558

*With Noise Restrictions N.A. - Not Applicable

III-58

11

TABLE XII

AIR CARRIER FUEL CONSUMPTION AT WASHINGTON NATIONAL AIRPORT (gallons per day)

1981	1990
664,000	N.A.
739,000	812,000
747,000	892,000
740,000 747,000	912,000 1,055,000
776,000	812,000
794,000	892,000
	1981 664,000 739,000 747,000 740,000 747,000 747,000 747,000 794,000

*With Noise Restrictions N.A. - Not Applicable

2/

K

III-59

10 10 - 10 - 10 T
TABLE XIII

INDEX OF AIR CARRIER FUEL CONSUMPTION AT WASHINGTON NATIONAL AIRPORT

	<u>1981</u>	<u>1990</u>
Existing Conditions (May 1981)	1.00	N.A.
Controlled Activity*		
No Widebody Aircraft	1.11	1.22
With Widebody Aircraft	1.13	1.34
Unconstrained Activity*		
No Widebody Aircraft	1.11	1.37
With Widebody Aircraft	1.13	1,59
Controlled Activity, Modified*		
No Widebody Aircraft	1.17	1.22
With Widebody Aircraft	1.20	1.34

*With Noise Restrictions N.A. - Not Applicable

---- A

111-60

A STATE OF THE OWNER OF THE OWNER

SECTION IV: UNAVOIDABLE ADVERSE EFFECTS AND ACTIONS TAKEN TO MINIMIZE HARM

All of the alternative policies considered in the August 1980 Environmental Impact Statement and this Final Supplement involve some unavoidable adverse effects on the environment in the Washington area. For example, there will be some degree of continued airport noise, aircraft engine emissions, use of energy, and other effects resulting from the operation of the three airports. In the evaluation of each of the alternative policies, measures to minimize unavoidable adverse effects have been considered. Those measures are, in fact, the primary factors considered in assessing each of the alternative policies.

It is clear, however, from a review of Section II of this Final Supplement and the August 1980 Environmental Impact Statement that there is no alternative which, if adopted, would minimize all of the adverse consequences. In addition, alternatives which might provide a positive result at one airport may, in fact, have a negative result at another of the three Washington-area airports. Thus, the process of selecting an operating policy for the Metropolitan Washington Airports requires a balancing of the overall benefits and costs obtained from those airports.

TV-1

SECTION V: RELATIONSHIP BETWEEN SHORT-TERM USES OF MAN'S ENVIRONMENT AND THE MAINTENANCE AND ENHANCEMENT OF LONG-TERM PRODUCTIVITY

None of the alternative policies considered in the August 1980 Environmental Impact statement or this Final Supplement represents an irreversible action, nor would any foreclose permanently future new policies, if such were to become more advantageous. All alternatives considered seek to balance the productivity afforded by an efficient system of air transportation for the Washington area against the environmental impacts which that system imposes. A policy allowing the optimum use of each of the three airports is the intended goal of this decision process. That optimization is clearly seen to be different by each of the many factions affected by those airports. Unforeseen future constraints, for example, drastically curtailed petroleum supplies, could quickly shift the optimum balance of these factors.

V-1

SECTION VI: IRREVERSIBLE AND IRRETRIEVABLE COMMITMENTS OF RESOURCES

Each day's operation of the Washington-area airports represents an irretrievable commitment toward meeting the air transportation needs of the National Capital region. Each day's operation similarly represents an irretrievable use of fuel resources and the imposition of environmental impacts on the surrounding area. As noted before, a decision on the optimum operating policy for the Metropolitan Washington Airports seeks to provide a proper balancing of these uses of resources, to the overall benefit of the Nation and its society.

VI-1

SECTION VII: LIST OF PREPARERS

This Final Supplement Environmental Impact Statement was prepared by the U.S. Department of Transportation, Federal Aviation Administration.

Personnel	Title & Organization	Qualifications
John E. Wesler	Director of Environment and Energy, FAA	BS-Marine Engineering MS-Acoustical Engi- neering MS-Optical Engineering 28 years' experience in sound propagation; 11 years' experience in aviation noise abate- ment.
Robert F. Eisengrein	Attorney, Office of Chief Counsel, FAA	BBA-Business Adminis- tration (Finance) JD-Law 20 years' experience in government and corporate law; 8 years' experience in administration.
Edmund W. Sellman	Chief, Noise Technology Branch, Office of Environment and Energy, FAA	MS-Aeronautical Engi- neering (Propulsion) Over 20 years' experi- ence in aircraft power plants; 11 years' ex- perience in aircraft noise control.
Emanuel M. Ballenzweid	g Technical Advisor, Office of Environ- ment and Energy, FAA	BS-Meteorology MS-Meteorology MS-Engineering 27 years' experience in various aspects of environmental sciences and engineering.
Charles C. Erhard	Environmental Affairs Officer, Metropoli- tan Washington Airports, FAA	BA-Business Administra- tion MBA-Management Sciences Eight years' experience in airport planning and environmental sciences.
John W. Reynolds, Jr.	Environmental Specialist, Office Airports Planning and Programming, FAA	BS-Civil Engineering 14 years' experience in engineering and airport environmental planning.

VII-1

SECTION VIII - RESPONSE TO SUBSTANTIVE COMMENTS

This section addresses comments specifically on the Draft Supplement to the Environmental Impact Statement as well as comments to the docket of the Notice of Proposed Rulemaking 81-8 that relate to the EIS. The comments received have been carefully reviewed and, in accordance with CEQ Regulations, 40 CFR 1503.4, this Final Supplement to the Environmental Impact Statement has been modified and, in some instances, factual corrections have been made. Issues raised by one or more commentors have been summarized without intentional bias to the meaning. The summarized comments and the FAA's responses are set out below.

I. Overall Adequacy of the EIS.

Comment: The Supplemental Draft EIS is deficient since it did not address all other alternatives, including "innovative" flight tracks; nor were the precise environmental benefits of the proposed restrictions quantified.

Response: The Draft EIS addressed 32 alternatives which, in the August 1980 FEIS, were condensed to five alternative policies covering the range of options available from a significant reduction in activity at National to an expanded role for the airport. The Draft Supplement EIS addressed four additional alternatives involving noise constraints. "Innovative" flight paths, such as the "scatter plan" currently under consideration by the Washington Metropolitan Council of Governments and the FAA, will be assessed and tested prior to their adoption. The

relative benefits of the noise constraints considered in the Supplemental EIS will serve the noise impacted community, regardless of the flight tracks into and out of the airport. Further, the noise impacted areas and population due to near term (1981) and longer term (post 1986) noise restrictions are adequately quantified on page III-7.

Comment: The FAA has not completed a noise exposure map and noise compatibility program for Washington National and Dulles International Airports, as required by Section 105 of the Aviation Safety and Noise Abatement Act of 1979 (ASNA).

Response: ASNA does not prevent the FAA from establishing or changing operating procedures at either airport. However, such changes will be reflected in the noise exposure maps and the noise compatibility programs being developed for those airports.

II. Noise Levels and Nighttime Restrictions

Comment: It is apparent that there is some doubt concerning the actual noise levels produced by the planes under discussion, as noted on page III-25. The Final Supplement should clarify this issue, and should use noise levels that have been verified by past experience.

Response: FAR Part 36 requires the reporting of turbojet and large transport category aircraft certificated noise levels in units of Effective Perceived Noise Level in decibels (EPNdB). Many airport and other community noise anlayses utilize a noise rating scale that is

based upon A-weighted decibels. For this reason, the dBA noise levels for aircraft under FAR Part 36 conditions have been estimated to provide a reference source for aircraft noise levels that is consistent with the many noise rating scales having dBA as the basic weighted measure. These listings also provide public exposure to progress in the control and abatement of airplane noise, as well as offer a common noise level reference for potential future reductions.

Since the noise levels are estimated as they might occur during type certification tests conducted under Appendix C of Part 36, these values are intended to provide a consistent basis for comparison of noise levels of major aircraft models rather than of individual aircraft. The noise levels of individual aircraft may also differ due to variations in weight and operating procedures from those used during certification. For instance, takeoff noise levels are reduced substantially as aircraft takeoff weight is reduced. Takeoff weights during normal in-service operations are often less than the maximum certificated weighted. In general, for equal noise control technology, the lower the maximum weight of an airplane the lower in the tabulation it will appear on the attached listings. Conversely, those aircraft normally associated with high weight, long range operation and, therefore, greater productivity, have the higher noise levels and will appear predominately at the top of the list. This aspect of increasing noise levels with increasing weight is embodied in the noise certification requirements of Part 36. The takeoff noise levels are also dependent on operating procedures applied. The takeoff noise level estimates in the table represent full thrust conditions for some aircraft and a reduced thrust condition, as permitted by FAR Part 36,

for other aircraft. Neither of these conditions may be representative of the in-service operation of a particular aircraft at a particular airport. (See FAA Advisory Circular 91-53, Noise Abatement Departure Profile.) Variations from the values of the noise estimates presented in this circular for individual flights at actual airports under nominally the same conditions could range within plus or minus 3 dBA for airplanes certificated in accordance with Part 36 or more for those airplanes not noise certificated. Additional variations in absolute value occur when aircraft operating conditions do not conform with those corresponding to noise certification. However, the FAA believes that the ranking of aircraft noise levels that occur under uniform certification conditions provides the best information currently available on the relative noisiness of airplanes over a wide variety of conditions.

Nevertheless, the FAA is reexamining the data contained in Advisory Circular 36-3A (from which Tables VI-IX were taken) to ensure that the noise levels are correct. To this end, many of the aircraft manufacturers have been requested to verify the levels in AC-36-3A as well as to provide data on noise levels in dBA versus takeoff gross weight.

Comment: The noise analysis for the proposed nighttime flights includes two important assumptions about noise attenuation in residential structures and the interruption of sleep at certain noise levels. These assumptions are not well supported or documented in the Draft Supplement. For instance, the 15-20 decibel attenuation of sound for residential structures appears to be a liberal estimate, and it is

not clear why this range was used. It is also stated that most people's sleep will not be disturbed by a noise level of 50 dBA, but this important point is not documented.

Response: The 15-20 decibel attenuation of sound for residential structures along the Potomac River corridor is considered conservative in the analysis. Page C-17 of the EPA's "Levels Document" (Information on Levels of Environmental Noise Requisite to Protect Public Health and Welfare with an Adequate Margin of Safety dated March 1974) contains the following in relation to outdoor and indoor exposure: "a building reduces the level of most 'ntruding outdoor environmental noises by 15 dBA or more (windows partially open)."

The citation for the data in the supplemental EIS regarding sleep disturbance is: "Noise and Sleep: Information Needs for Noise Control" by Jeffrey Goldstein and Jerome Lukas; Proceedings of the Third International Congress on Noise as a Public Health Problem, Feiburg, West Germany, September 25-29, 1978; pp. 442-448.

Comment: Using May 1981 operations data for the base c se is inappropriate since May is not a month of peak activity.

Response: Average Day-Night Sound Level (Ldn) is the yearly average of the A-weighted sound level integrated over a 24-hour period. Therefore, it is not necessary to use operations from a month of peak activity for determining the base case noise exposure. May 1981 operations were used since that was the latest month from which data were obtainable in the preparation of the Supplement to the EIS.

Comment: Concern was expressed with regards to air quality impacts including the amount of additional burden to the emissions inventory and the fact that the "Unconstrained Activity" alternative would result in a violation of the eight-hour CO standard in the vicinity of the terminal building at Washington National Airport.

Response: A more precise analysis indicated that the emissions inventory at Washington National Airport as well as the airport and airport-related addition to the emissions inventory of the National Capital Air Quality Control Region and the bi-regional inventory, would be within the range of the previously analyzed alternatives. (The introduction of wide-body aircraft could increase these impacts by 10 percent.) The"Unconstrained Activity" alternative, which was projected to exceed the eight-hour CO standard if high background levels occur, can be mitigated by various means such as modifications to the internal roadway system.

Comment: Several commenters raised the issue of surface access to Washington National Airport. Some found the discussion of surface access in the Draft Supplement to be an inadequate, incomplete description of the impact and others referred to NPRM statements on access roads already at their capacity.

Response: The section on surface access in the supplement summarized the thorough analysis of surface access in the August 1980 Final Environmental Impact Statement. That analysis indicated that there would be no serious impacts for alternatives which maintain

passenger enplanements below 20 million per year. In those cases, momentary traffic stoppages on the southbound off-ramp from George Washington Parkway to Washington National Airport could be expected. References in the NPRM to capacity of roadways being exceeded today did not refer to the access roads, but to the internal airport roadways in the vicinity of the terminal. The need for improvements to the internal roadway system is addressed in a paragraph mitigating actions in the Air Quality section.

VIII-7

-t-

SECTION IX: COMMENTS RECEIVED ON DRAFT SUPPLEMENT TO THE AUGUST 1980 ENVIRONMENTAL IMPACT STATEMENT



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY REGION III 6TH AND WALNUT STREETS PHILADELPHIA, PENNSYLVANIA 19106

AUG 1 1 1981

Mr. James A. Wilding, Director Metropolitan Washington Airports Federal Aviation Administration Washington National Airport Hangar 9 Washington, DC 20001

Re: Metropolitan Washington Airports Policy

Dear Mr. Wilding:

We have reviewed the Draft Supplement to the EIS on the Metropolitan Washington Airports Policy, and have classified it in EPA's reference category ER-2. The attached copy of the Definition of Codes for the General Nature of EPA Comments provides an explanation of this rating. This classification will be published in the Federal Register in order to meet our public information obligations.

We are pleased to see that the goal of FAA's two new policy alternatives for Washington National Airport (WNA) is to create a reduction in the overall community noise impacts from aircraft. EPA is concerned, however, about the policy provision to allow nighttime operations, and we would like to see this issue reexamined in the Final Supplement.

The noise analysis for the proposed nighttime flights includes two important assumptions about noise attenuation in residential structures and the interruption of sleep at certain noise levels. These assumptions are not well supported or documented in the Draft Supplement. For instance, the 15-20 decibel attenuation of sound for residential structures appears to be a liberal estimate, and it is not clear why this range was used. It is also stated that most people's sleep will not be disturbed by a noise level of 50 dBA, but this important point is not documented. We do not believe that these aspects of the noise study lead to the kind of "worst case" analysis that should be included in an EIS.

It is also apparent that there is some doubt concerning the actual noise levels produced by the planes under discussion, as noted on page III-25. The Final Supplement should clarify this issue, and should use noise levels that have been verified by past experience.

The Draft Supplement also indicates that the "Unconstrained Activity" Alternative would result in a violation of the 8-hour CO standard at the WNA terminal. As you know, EPA is not in a position to comment favorably on any proposal that would result in a violation of the NAAQS. We encourage the FAA not to pursue an alternative that would result in such a violation.

Sincerely yours, 10 mille CeJohn R. Pomponio Chief

EIS & Wetlands Review Section

Enclosure

Definition of Codes for the General Nature of EPA Comments

Environmental Impact of the Action

LO--Lack of Objections

EPA has no objections to the proposed action as described in the draft impact statement or suggests only minor changes in the proposed action.

ER--Environmental Reservations

EPA has reservations concerning the environmental effects of certain aspects of the proposed action. EPA believes that further study of suggested alternatives or modifications is required and has asked the originating Federal agency to reassess these aspects.

EU-Environmentally Unsatisfactory

EPA believes that the proposed action is unsatisfactory because of its potentially harmful effect on the environment. Furthermore, the Agency believes that the potential safeguards which might be utilized may not adequately protect the environment from hazards arising from this action. The Agency recommends that alternatives to the action be analyzed further (including the possibility of no action at all).

Adequacy of the Impact Statement

Category 1---Adequate-

The draft impact statement adequately sets forth the environmental impact of the proposed project or action as well as alternatives reasonably available to the project or action.

Category 2--Insufficient information

EPA believes that the draft impact statement does not contain sufficient information to assess fully the environmental impact of the proposed project or action. However, from the information submitted, the Agency is able to make a preliminary determination of the impact on the environment. EPA has requested that the originator provide the information that was not included in the draft statement.

Category 3-Inadequate

EPA believes that the draft impact statement does not adequately assess the environmental impact of the proposed project or action, or that the statement inadequately analyzes reasonably available alternatives. The Agency has requested more information and analysis concerning the potential environmental hazards and has asked that substantial revision be made to the draft statement.

If a draft impact statement is assigned a Category 3, ordinarily no rating will be made of the project or action, since a basis does not generally exist on which to make such a determination.

BEFORE THE

FEDERAL AVIATION ADMINISTRATION

UNITED STATES DEPARTMENT OF TRANSPORTATION

WASHINGTON, D.C.

METROPOLITAN WASHINGTON AIRPORTS)

Docket 21955 Notice 81-8

COMMENTS OF NEW YORK AIRLINES, INC. RE: DRAFT SUPPLEMENT TO THE AUGUST, 1980 ENVIRONMENTAL IMPACT STATEMENT

> GERRY LEVENBERG, P.C. GARY L. FONTANA JEFFREY S. CHRISTIE Van Ness, Feldman, Sutcliffe, Curtis & Levenberg A Professional Corporation 1050 Thomas Jefferson Street, " Seventh Floor Washington, D.C. 20007 (202) 331-9400

Counsel for New York Airlines, Inc.

August 31, 1981

BEFORE THE

FEDERAL AVIATION ADMINISTRATION

UNITED STATES DEPARTMENT OF TRANSPORTATION

WASHINGTON, D.C.

METROPOLITAN WASHINGTON AIRPORTS

Docket 21955 Notice 81-8

COMMENTS OF NEW YORK AIRLINES, INC. RE: DRAFT SUPPLEMENT TO THE AUGUST, 1980 ENVIRONMENTAL IMPACT STATEMENT

New York Airlines, Inc. (New York Air") submitted the following comments on the "Draft Supplement to the August, 1980 Environmental Impact Statement" dated June, 1981.

<u>Comment #1</u>: It is inappropriate to use May, 1981, as the base period for calculating the impact of the proposed policy, since May is not a peak travel month. According to National Airport tower logs, the average number of air carrier flights on weekdays in July, 1981, was 628. In May, the average was only 588. These differences, amounting to 40 flights per day, will clearly have a substantial impact on any underlying analysis.

<u>Comment #2</u>: The draft fails to provide an adequate explanation for the 30 percent increase in the number of households within the 65 and 75 Ldn contours since the August, 1980, EIS. (See pages III-4 to III-8.)

<u>Comment #3</u>: It is a fallacy to assume that reducing the number of air carrier operations to 37 per hour will

IX-6

save fuel. (See page III-48.) If the aircraft are not used at National, they will certainly be put into service somewhere else and will burn the same number of gallons as before.

<u>Comment #4</u>: It is not necessarily true that a reduction in flights at National will save fuel by reducing airborne delays. (<u>See page III-48.</u>) This depends entirely on whether the aircraft denied access to National are put into service at an airport with average delays equal to or greater than those at National. In any event, the savings will be marginal at best.

<u>Comment #5</u>: The Draft fails to provide any explanation for the failure of the Department to chose the "Unconstrained Activity with Noise Restrictions" alternative. It appears to be superior to the chosen policy in every respect.

Respectfully submitted,

GERRY LEVENBERG, P.C. GARY L. FONTANA JEFFREY S. CHRISTIE Van Ness, Feldman, Sutcliffe, Curtis & Levenberg A Professional Corporation 1050 Thommas Jefferson Street, N.W. Seventh Floor Washington, D.C. 20007 (202) 331-9400

Counsel for New York Air

August 31, 1981

2



COMMONWEALTH of VIRGINIA

J.B. JACKSON, JR. ADMINISTRATOR Council on the Environment

903 NINTH STREET OFFICE BUILDIN RICHMOND 23219 804 786 4500

August 13, 1981

Mr. John E. Wesler Director of Environment and Energy 800 Independence Avenue, S.W. Washington, D.C. 20591

Dear Mr. Wesler:

The Commonwealth of Virginia has completed its review of the draft supplement to the Final Environmental Impact Statement on the Metropolitan Washington Airports Policy. The Council on the Environment is responsible for coordinating the State's review of federal environmental documents and for responding on behalf of the Commonwealth to appropriate federal officials. The following agencies have taken part in this review:

Department of Aviation Department of Highways and Transportation State Air Pollution Control Board Office of Emergency and Energy Services.

The Commonwealth of Virginia supports the proposed policy, since it will provide a distinct improvement over present conditions in regard to noise levels at National Airport and its environs. The Commonwealth hopes that a way will be found to ensure the provision of a sufficient number of commuter aircraft slots at National to serve adequately the growing needs of air travelers to and from Virginia cities.

The limitation of air carrier activities at National Airport is, of course, a desirable goal from the standpoint of air quality. This goal will be reached more readily when the Dulles Access Road is completed to Route 66 and further ground transportation improvements are made. Mr. John E. Wesler August 13, 1981 Page 2

Other comments of reviewing agencies are attached.

Thank you for the opportunity to review this document.

Sincerely,

ackson, Jr.

Attachments

cc: The Honorable Maurice B. Rowe, Secretary of Commerce and Resources Mr. Michael A. Waters, Department of Aviation Mr. R. L. Hundley, Department of Highways and Transportation Mr. K. Mercer Melvin, State Air Pollution Control Board Mr. A. E. Slayton, Jr., Office of Emergency and Energy Services

JBJ/CHE/all

E. FOLGED 3000 CH, OBAIRMAN STEULICIU

EVEN LIT IN HURADIZEDE, VICE CHARMAN MARGE LI VIELL

FOR LASS SONT LON-ECCOLD D

AXEN TUNAN (SOM) Normsfor - C

OADE GERMEN 1784 ALEXATIONA



COMMONWEALTH of VIRG

State Air Pallation Control Board

ROOM 1103, MM CLESTREET OFFICE READING RICHMOLID, VIHGINIA 21219 TELEPHONE, 1893) 735-2378 CONTRACTOR CONTRACTOR

11.2.2

August 7, 1981

Charles H. Ellis, III Environmental Impact Coordinator Council on the Environment Room 903, Kinth Street Office Building Richmond, Virginia 23219

Dear Mr. Ellis:

The staff of the State Air Pollution Control Board reviewed the Draft Supplement to the August 1980 EIS concerning Metropolitan Washington Airports Policy.

The two additional policies are primarily concerned with noise reductions. However, the new proposed Control Activity Policy would also reduce the annual passenger use by one-million persons per year from the level in the previously proposed policy that was to become effective October 25, 1981.

The most acceptable alternative from the standpoint of air quality is the Reduced Activity Policy at Washington National Airport. This would reduce vehicular traffic thus reducing hydrocarbon and carbon monoxide emissions and providing concomitant improvement in ozone and carbon monoxide air quality.

Sincerely,

antimuch.

J. C. Ruehrmund Director Division of Operations & Procedures

JCR/KMM/evb

cc: Michael A. Waters, Department of Aviation C #13



COMMONWEALTH of VIRGINIA

15.211.01.01 AD111.278.000

Council on the Environment

903 NINTH STREET OFFICE BUD DISG RICHNIOLD 23215 664 735 4500

August 12, 1981

MEITORANDUM

TO: File

FROM: C. Ellis

SUBJECT: Department of Aviation Comments - Metro Washington Airports Policy

Aviation per Mike Waters (today), applauds the policy in that it will reduce noise levels around National Airport. The Department is concerned about slot limitations on commuter aircraft since commuters are the main transportation link to Washington from major Virginia cities.

CHE/all

IX-11

Service Constraints
Service Constraints of the International State Constraints

1 4. CALLATER



THE MARKEN COMMONWEALTH of VIRGINIA

DEPARTMENT OF HIGHWAYS & TRANSPORTATION 1221 EAST BHOAD STREET RICHMOND, 23219 August 10, 1981

CEPTER BUSINESSE COPOLIC CONTROL OF SIGNAR ENGINE

J.T. Karner, DRUTIOS OF ADDITE HAMMER

J. M. WARKER (14) THEFUTUR CHICHISTERNUS

H. R. PERKING ST. P. Defect (DE DE RENGEZINTET ZHENGHAT

W. L. BARD REF, 24 DEFECTUAL GE ETAMA FRAM.

OSCAREM FITCHY DREETIGE OF REAMINELY

HE WERK RECALL. DIRECTION OF FILMOUND REPORTS

IN ROPEN PERCE PERCE

Metropolitan Washington Airports Policy - Draft Supplement to August 1980 EIS

Mr. Charles Ellis ElS Coordinator Council on the Environment Ninth Street Office Building Richmond, Virginia 23219

Dear Mr. Ellis:

Thank you for the opportunity to review this document. We have the following comments and questions.

There is no discussion in the document about the effects of improved surface access to Dulles. With the opening of I-66 and the Dulles Airport Access Road extension, Dulles should be more attractive to both the airlines and their passengers. How will this affect growth at National?

Provisions to limit activity at National should be contingent upon adequate access being provided to Dulles. Such access could be achieved by construction of the Dulles Access Road between Routes 123 and 66. Furthermore, express bus service between the West Falls Church Metro Station and Dulles would also enhance access. Ultimately, the most desirable means of access would be direct Metro rail service to Dulles.

Sincerely,

R.R. O. C. deller

R. L. Hundley (/ Environmental Engineer

cc: Mr. William G. Plent Department of Aviation

IX-12

TRANSPORTATION -- AMERICA'S LIFELINES

Lee H. Wigren, Chairman Furfax City Charles A. Funn, Vice-Chairman An ington County Joseph B. Wisniewski, Treasurer mattfax County John W. Eping Scoutty Director

COMMISSIONERS: Hon. Charles A. Bos

Northern Virginia

Planning District Commission

August 13, 1981

Mr. John E. Wesler Director of Environment and Energy Federal Aviation Administration 800 Independence Avenue, S.W. Washington, D.C. 20591

Dear Mr. Wesler:

The Northern Virginia Planning District Commission (NVPDC) has reviewed the Draft Supplement to the August 1980 Environmental Impact Statement and recommends favorable review with the following comments:

NVPDC supports the objectives of the proposed policy to achieve a more balanced utilization of the region's airports through a managed growth program for National Airport, consequently enhancing the role of Dulles Airport. In particular, the Commission concurs with the concept of an annual passenger ceiling at National Airport and the decision to enhance ground access to Dulles Airport by accelerating completion of the Dulles Access Road Extension to I-66 and the commitment to improve the quality of bus service to this facility.

However, NVPDC believes that this revised policy still does not go far enough in effecting a significant diversion of operations from National to Dulles, as recommended in the Commission's comments on the 1978 and 1979 Draft Environmental Impact Statements and the 1980 Final Environmental Impact Statement. While the revised policy's 16 million annual passenger ceiling is an improvement on the 1980 policy's 17 million ceiling, it would ensure that National will remain the region's primary airport for the foreseeable future, retaining nearly 45% of the region's projected air passenger traffic in 1990, and continuing the problems of aircraft noise, air pollution and the overburdening of ground access facilities. Therefore, NVFDC wishes to restate its previous recommendation that a 14 million annual passenger ceiling be established for National Airport, which represents a slight reduction in the present level of use.

Strengthening Local Government

Leesburg Hon. Ellen M. Bozman Arlington County Hon, William M. Calnan Fairfax City Carlos C. Campbell Fairfax County Hon. Thomas M. Davis III Fairfax County Hon. Thomas S. Dodson Loudoun County ilon. Sandra L. Duckworth cairfax County Hon. Nancy K. Falck Fairfax County Charles A. Funn Arlington County Hon. Maurice Gerson lanastes Hon Dorothy T Grotos Arlington Count Hon. Donald E. Kidwell Prince William County ion, Gary D. Knight rails Church Paul H. Krauss Alexandria John G. Magnutti, Jr. Arlington County Hon, G. Robert Maitland Manassas Park David B. Meterath William C. McLeod nnce William County ames J. Miller Alexandria Hon Audrey Moore airfax County 🗅 M. Moyer, Jr. lanassas James H. Pickford anter Count Intan Power oudoun County Hon. Cartyle C. Ring, Jr. exandica Charles F Robinson, Jr. Hon. Thomas D. Rust Herndon Hirst Sutton Falls Church Hon. Donald E. Upchurch Vienna Hon. Donald L. White Prince William County Lee H. Wigren Fairfax City Joseph B. Wisniewski Fairfax County V. Allen Young, Jr.

as of May 20, 1981

Manassas Park

Page Two Mr. John E. Wesler August 18, 1981

> The Commission concurs with the concept of daytime noise limitations at National Airport, and particularly with the need to make such noise limitations more stringent in the future when the new generation of quieter aircraft becomes generally available. However, NVPDC is greatly concerned about the policy formally establishing 24-hour operations at National Airport. The nighttime noise limitations appear to be stringent enough to exclude most commercial aircraft currently operating out of National. This could change when aircraft that can meet the standard come into general use resulting in far more nighttime operations out of National than at present. This will extend the noise burden for those who are impacted by commercial operations at National Airport to 24 hours a day. Meteorological conditions can cause a variance in sound pressure levels of as much as 20 dBA, which could mean a perceived noise level 4 times the limitation of 85 dBA as determined on approach and 72 dBA as determined on takeoff. Such meteorological conditions would in effect raise the nighttime noise limitations to 105 dBA on approach and 92 dBA on takeoff. Therefore, the absence of a mandatory curfew could mean that nighttime aircraft operations will result in severe noise impacts at certain times of the year. However, the draft EIS supplement does not consider the potential impacts of varying meteorological conditions. In light of the potential adverse impacts of nighttime operations, we wish to restate our previous position, as stated in the Commission's comments on the August, 1980 Final Environmental Impact Statement, supporting a mandatory nighttime curfew.

The decision to extend National Airport's non-stop service perimeter from 650 miles to 1,000 miles is likewise a step in the wrong direction. Such a change would further blur the distinction between the proper roles for National and Dulles Airports, discouraging shorthaul flights at National Airport and dealing a further blow to plans for the proper utilization of Dulles as a primary airport in the region. Recognizing that many sections of the country feel that the current perimeter restriction is not applied equitably due to the existence of seven "grandfathered" cities, NVPDC recommends that rather than increasing the perimeter to 1,000 miles in order to eliminate the need for grandfathering, nonstop service to these seven cities should be eliminated both for the sake of equity and to achieve the proper relationship between National and Dulles Airports.

Page Three Mr. John E. Wesler August 18, 1981

> The Commission is also concerned about the revised policy's proposal to allow extra sections of scheduled flights without regard to hourly slot allocations. Giving official sanction to this practice circumvents both the letter and intent of the policy's limitation on available slots and jeopardizes the equity of the slot allocation process.

NVPDC is pleased that in the revised policy the FAA has reconsidered its position on the use of widebody aircraft at National Airport, requiring further proof on a model by model basis that such aircraft can operate safely at National and that introduction of such aircraft would be compatible with the airport's gate, apron, baggage and passenger handling, and roadway facilities.

The Commission also recommends that further consideration be given to the possibility of future extension of METRO rapid rail to Dulles Airport, and to other alternative ground transportation modes should they appear feasible in the future.

Your cooperation in the intergovernmental review process is appreciated.

Sincerely yours, John W. Epling

7 Executive Director

SUBJECT: A-95 Review by Regional Clearinghouse Project Title: Draft Supplement to August 1980 EIS -Metro. Washington Airports Folicy Applicant: DOT-FAA SAI: VA820724-01500800001 NVPDC Staff Contact: Anita Capps

cc: Charles Ellis, Virginia Council on the Environment

