

AD-A106 621


BLACK AND VEATCH KANSAS CITY MO
NATIONAL DAM SAFETY PROGRAM, LIONS LAKE DAM (MO 20037); MISSOUR--ETC(U)
MAY 80 P R ZAMAN, E R BURTON, H L CALLAHAN DACW43-80-C-0074

F/G 13/13

UNCLASSIFIED

NL

1 of 1
AD-A
17442-



END
DATE
FILMED
DTIC

MISSOURI-KANSAS CITY BASIN

AD A106621

LIONS LAKE DAM

JOHNSON COUNTY, MISSOURI

MO 20037

**PHASE 1 INSPECTION REPORT
NATIONAL DAM SAFETY PROGRAM**



**United States Army
Corps of Engineers**
... Serving the Army
... Serving the Nation

St. Louis District

DTIC FILE COPY

DTIC
ELE
NOV 5 1981
S
A

PREPARED BY: U.S. ARMY ENGINEER DISTRICT. ST. LOUIS

FOR: STATE OF MISSOURI

Handwritten signature

MAY 1980

This document has been approved for public release and sale; its distribution is unlimited.

81 11 02 058

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)


REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO. AR-A106 621	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Phase I Dam Inspection Report National Dam Safety Program Lions Lake Dam (MO 20037) Johnson County, Missouri		5. TYPE OF REPORT & PERIOD COVERED Final Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Black & Veatch, Consulting Engineers		8. CONTRACT OR GRANT NUMBER(s) DACW43-80-C-0074 ✓
9. PERFORMING ORGANIZATION NAME AND ADDRESS U.S. Army Engineer District, St. Louis Dam Inventory and Inspection Section, LMSED-PD 210 Tucker Blvd., North, St. Louis, Mo. 63101		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS U.S. Army Engineer District, St. Louis Dam Inventory and Inspection Section, LMSED-PD 210 Tucker Blvd., North, St. Louis, Mo. 63101		12. REPORT DATE May 1980
		13. NUMBER OF PAGES Approximately 65
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Dam Safety, Lake, Dam Inspection, Private Dams		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report was prepared under the National Program of Inspection of Non-Federal Dams. This report assesses the general condition of the dam with respect to safety, based on available data and on visual inspection, to determine if the dam poses hazards to human life or property.		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)



SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

MISSOURI-KANSAS CITY BASIN

LIONS LAKE DAM

JOHNSON COUNTY, MISSOURI

MO 20037

PHASE 1 INSPECTION REPORT NATIONAL DAM SAFETY PROGRAM

Lions Lake Dam (MO 20037),
Missouri - Kansas City Basin, Johnson County,
Missouri. Phase I Inspection Report.



**United States Army
Corps of Engineers**

*... Serving the Army
... Serving the Nation*

St. Louis District

9 Final rept.,

DACW43-80-C-0074

10 Paul R. / Zaman Edwin R. / Burton
Harry L. / Callahan

PREPARED BY: U.S. ARMY ENGINEER DISTRICT. ST. LOUIS

FOR: STATE OF MISSOURI

11 **MAY 1980**



DEPARTMENT OF THE ARMY
ST. LOUIS DISTRICT, CORPS OF ENGINEERS
 210 TUCKER BOULEVARD, NORTH
 ST. LOUIS, MISSOURI 63101

REPLY TO
 ATTENTION OF

LMSD-PD

SUBJECT: Lions Lake Dam, MO. I.D. No. 20037
 Phase I Inspection Report

This report presents the results of field inspection and evaluation of the Lions Lake Dam.

It was prepared under the National Program of Inspection of Non-Federal Dams.

This dam has been classified as unsafe, non-emergency by the St. Louis District as a result of the application of the following criteria:

- a. Spillway will not pass 50 percent of the Probable Maximum Flood without overtopping the dam.
- b. Overtopping of the dam could result in failure of the dam.
- c. Dam failure significantly increases the hazard to loss of life downstream.

SUBMITTED BY: SIGNED 19 SEP 1980
 Chief, Engineering Division Date

APPROVED BY : SIGNED 22 SEP 1980
 Colonel, CE, District Engineer Date

Accession No.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
NTIC			
DTIC TAB			
Unannounced			
Justification			
By			
Distribution			
Availability Codes			
Dist			

LIONS LAKE DAM
JOHNSON COUNTY, MISSOURI
MISSOURI INVENTORY NO. 20037

PHASE I INSPECTION REPORT
NATIONAL DAM SAFETY PROGRAM

PREPARED BY:

BLACK & VEATCH
CONSULTING ENGINEERS
KANSAS CITY, MISSOURI

UNDER DIRECTION OF
ST. LOUIS DISTRICT CORPS OF ENGINEERS
FOR
GOVERNOR OF MISSOURI

MAY 1980

PHASE I REPORT
NATIONAL DAM SAFETY PROGRAM

Name of Dam	Lions Lake Dam
State Located	Missouri
County Located	Johnson County
Stream	Tributary to East Fork Post Oak Creek
Date of Inspection	15 May 1980

Lions Lake Dam was inspected by a team of engineers from Black & Veatch, Consulting Engineers for the St. Louis District, Corps of Engineers. The purpose of the inspection was to make an assessment of the general condition of the dam with respect to safety, based upon available data and visual inspection, in order to determine if the dam poses hazards to human life or property.


The guidelines used in the assessment were furnished by the Department of the Army, Office of the Chief of Engineers and developed with the help of several Federal and state agencies, professional engineering organizations, and private engineers. Based on these guidelines, this dam is classified as a small size dam with a high downstream hazard potential. According to the St. Louis District, Corps of Engineers, failure would threaten lives and property. The estimated damage zone extends approximately one mile downstream of the dam. Within the estimated damage zone are one home, one barn, and a trailer court. Contents of the estimated downstream damage zone were verified by the inspection team.


Our inspection and evaluation indicates the spillways do not meet the criteria set forth in the guidelines for a dam having the above size and hazard potential. The spillways will not pass the probable maximum flood without overtopping but will pass 13 percent of the probable maximum flood, and will pass the one percent chance flood (100-year flood). The spillway design flood recommended by the guidelines is 50 to 100 percent of the probable maximum flood. Considering the reservoirs in the upstream watershed and the hazard zone, the spillway design flood should be the probable maximum flood. The probable maximum flood is defined as the flood discharge which may be expected from the most severe combination of critical meteorologic and hydrologic conditions which are reasonably possible in the region.


Based on visual observations, this dam appears to be in good condition. Deficiencies visually observed by the inspection team were a quagmire and possible seepage area below the dam to the left of the

lower lagoon, erosion of the drainage ditches at the left abutment, erosion on the upstream slope, erosion of embankment material at the primary spillway pipe outlet, deterioration of a retaining wall at the downstream toe of dam, and a few animal burrows on the upstream side of the embankment. Seepage and stability analyses required by the guidelines were not available.

There were no observed deficiencies or conditions existing at the time of the inspection which indicated an immediate safety hazard. Future corrective action and regular maintenance will be required to correct or control the described deficiencies. In addition, detailed seepage and stability analyses of the existing dam, as required by the guidelines, should be performed. A detailed report discussing each of these deficiencies is attached.


Paul R. Zaman, PE
Illinois 6229261


Edwin R. Burton, PE
Missouri E-10137


Harry L. Callahan, Partner
Black & Veatch



OVERVIEW OF DAM

PHASE I INSPECTION REPORT
NATIONAL DAM SAFETY PROGRAM
LIONS LAKE DAM

TABLE OF CONTENTS

<u>Paragraph No.</u>	<u>Title</u>	<u>Page No.</u>
SECTION 1 - PROJECT INFORMATION		
1.1	General	1
1.2	Description of Project	1
1.3	Pertinent Data	2
SECTION 2 - ENGINEERING DATA		
2.1	Design	6
2.2	Construction	6
2.3	Operation	6
2.4	Geology	6
2.5	Evaluation	6
SECTION 3 - VISUAL INSPECTION		
3.1	Findings	7
3.2	Evaluation	8
SECTION 4 - OPERATIONAL PROCEDURES		
4.1	Procedures	10
4.2	Maintenance of Dam	10
4.3	Maintenance of Operating Facilities	10
4.4	Description of Any Warning System in Effect	10
4.5	Evaluation	10
SECTION 5 - HYDRAULIC/HYDROLOGIC		
5.1	Evaluation of Features	11
SECTION 6 - STRUCTURAL STABILITY		
6.1	Evaluation of Structural Stability	13
SECTION 7 - ASSESSMENT/REMEDIAL MEASURES		
7.1	Dam Assessment	14
7.2	Remedial Measures	14

TABLE OF CONTENTS (Cont'd)

LIST OF PLATES

<u>Plate No.</u>	<u>Title</u>
1	Location Map
2	Vicinity Topography
3	Plan
4	Dam Cross Section
5	Emergency Spillway Cross Sections
6	Emergency Spillway Profile
7	Photo Index

LIST OF PHOTOGRAPHS

<u>Photo No.</u>	<u>Title</u>
1	Upstream Face of Dam Looking North
2	Upstream Face of Dam Looking South
3	Crest of Dam
4	Downstream Slope of Dam Looking North
5	Downstream Slope of Dam Looking South
6	Primary Spillway Drop Inlet
7	Primary Spillway Outlet
8	Plunge Pool Below Primary Spillway
9	Emergency Spillway Channel

TABLE OF CONTENTS (Cont'd)

LIST OF PHOTOGRAPHS

<u>Photo No.</u>	<u>Title</u>
10	Concrete Retaining Wall at Toe of Dam
11	Quagmire at Toe of Dam
12	Drainage Ditch From Left Abutment Upstream Face
13	Drainage Ditch From Left Abutment Downstream Face
14	Sandstone Formation Left Abutment on Upstream Side of Dam
15	Animal Burrow on Upstream Face, Measured Approximately Five Feet Deep
16	Erosion Area on Upstream Face at Waterline

APPENDIX

Appendix A - Hydrologic and Hydraulic Analyses

SECTION 1 - PROJECT INFORMATION

1.1 GENERAL

a. Authority. The National Dam Inspection Act, Public Law 92-367, authorized the Secretary of the Army, through the Corps of Engineers, to initiate a program of safety inspection of dams throughout the United States. Pursuant to the above, the District Engineer of the St. Louis District, Corps of Engineers, directed that a safety inspection of the Lions Lake Dam be made.

b. Purpose of Inspection. The purpose of the inspection was to make an assessment of the general condition of the dam with respect to safety, based upon available data and visual inspection, in order to determine if the dam poses hazards to human life or property.

c. Evaluation Criteria. Criteria used to evaluate the dam were furnished by the Department of the Army, Office of the Chief of Engineers, in "Recommended Guidelines for Safety Inspection of Dams." These guidelines were developed with the help of several Federal agencies and many state agencies, professional engineering organizations, and private engineers.

1.2 DESCRIPTION OF PROJECT

a. Description of Dam and Appurtenances.

(1) The dam is an earth structure located in the valley of a tributary to East Fork Post Oak Creek at (Plate 1). The watershed area is hilly consisting of forested area, a residential area, and Pertle Springs dam Mo.I.D. No. 20044 and several small dams upstream. The dam is approximately 500 feet long along the crest and 22 feet high. The dam crest is 24 feet wide and has an asphalt road passing over the dam. Immediately below the embankment is a small lagoon formed by a dike around its perimeter.

(2) The primary spillway from the lake is an uncontrolled 36-inch steel pipe with a 48-inch diameter drop inlet installed in the embankment. The drop inlet has a 12-inch valved low level inlet. Flow through the pipe discharges into a plunge pool then through an open channel to the natural stream below. The emergency spillway consists of a concrete section of the road surface constructed in a low area of the embankment. Discharge through the emergency spillway overflows through a grass-lined channel between the road at the right abutment and the lagoon below the dam.

(3) Pertinent physical data are given in paragraph 1.3.

b. Location. The dam is located in South Central Johnson County, Missouri, as indicated on Plate 1. The lake formed by the dam is shown on the United States Geological Survey 7.5 minute series quadrangle map for Centerview, Missouri in Section 26 of T46N, R26W.

c. Size Classification. Criteria for determining the size classification of dams and impoundments are presented in the guidelines referenced in paragraph 1.1c above. Based on these criteria, the dam and impoundment are in the small size category.

d. Hazard Classification. The hazard classification assigned by the Corps of Engineers for this dam is as follows: The Lions Lake Dam has a high hazard potential, meaning that the dam is located where failure may cause loss of life, and serious damage to homes, agricultural, industrial and commercial facilities, and to important public utilities, main highways, or railroads. For the Lions Lake Dam the estimated flood damage zone extends approximately one mile downstream of the dam. Within the estimated damage zone are one residence, one barn, and a trailer court. Contents of the estimated downstream damage zone were verified by the inspection team.

e. Ownership. The dam is owned by the City of Warrensburg, 510 E. North St., Warrensburg, Missouri, Telephone 816-747-5291.

f. Purpose of Dam. The dam forms a 16-acre lake used for recreation in the city park.

g. Design and Construction History. Details of the design and construction of this dam are unknown. However, it was learned from the city that the dam was originally constructed by a water company to supply water to Warrensburg. The facilities were later purchased by the city. The water pumping station located near the dam is no longer in service.

h. Normal Operating Procedure. Normal rainfall, runoff, transpiration, evaporation, and overflow through the uncontrolled outlet pipe all combine to maintain a relatively stable water surface elevation.

1.3 PERTINENT DATA

a. Drainage Area - 426 acres

b. Discharge at Damsite.

(1) Normal discharge at the damsite is through an uncontrolled 36-inch outlet pipe and 48-inch drop inlet.

- (2) Estimated experienced maximum flood at damsite - Unknown.
- (3) Estimated ungated spillway capacity at maximum pool elevation 1,500 cfs (Probable Maximum Flood Pool El.763.1).

c. Elevation (Feet above m.s.l.).

- (1) Top of dam - 760.2 (see Plate 3)
- (2) Emergency spillway crest - 758.1_±
- (3) Primary spillway pipe invert - 746.0
- (4) Primary spillway drop inlet crest - 755.0
- (5) Streambed at toe of dam - 738.0 _±
- (6) Maximum tailwater - Unknown.

d. Reservoir.

- (1) Length of maximum pool - 1,300 feet _± (Probable maximum flood pool level)
- (2) Length of normal pool - 800 feet _± (Primary spillway drop inlet crest)

e. Storage (Acre-feet).

- (1) Top of dam - 160
- (2) Emergency spillway crest - 112
- (3) Primary spillway drop inlet crest - 54
- (4) Design surcharge - Not available.

f. Reservoir Surface (Acres).

- (1) Top of dam - 25.4
- (2) Emergency spillway crest - 21.3
- (3) Primary spillway drop inlet crest - 16.1

g. Dam.

- (1) Type - Earth embankment
- (2) Length - 465 feet \pm
- (3) Height - 22 feet \pm
- (4) Top width - 24 feet
- (5) Side slopes - upstream face 1.0 V on 2.4 H, downstream face between 1.0 V on 2.8 H and 1.0 V and 9.5 H (see Plate 4).
- (6) Zoning - Unknown.
- (7) Impervious core - Unknown.
- (8) Cutoff - Unknown.
- (9) Grout curtain - None.

h. Diversion and Regulating Tunnel - None.

i. Primary Spillway.

- (1) Type - 36-inch steel pipe with a 48-inch drop inlet.
- (2) Drop inlet crest elevation - 755.0 feet m.s.l.
- (3) Pipe invert elevation - 746.0
- (4) Outlet invert elevation 742.2 feet m.s.l.
- (5) Gates - None.
- (6) Upstream channel - Not applicable.
- (7) Downstream channel - Open channel to streambed.

j. Emergency Spillway.

- (1) Type - Concrete and asphalt open channel.
- (2) Width of channel - 103 feet.
- (3) Emergency spillway crest - 758.1.

(4) Gates - None.

(5) Upstream channel - Not applicable.

(6) Downstream channel - Grass lined open channel to the natural stream channel below.

k. Regulating Outlets - None.

SECTION 2 - ENGINEERING DATA

2.1 DESIGN

Design drawings were unavailable.

2.2 CONSTRUCTION

Construction records were unavailable.

2.3 OPERATION

No records of operation or of past floods were available.

2.4 GEOLOGY

The site of the dam and reservoir is located in a deeply dissected valley between two ridges. The dam impounds a small intermittent tributary of the East Fork of Post Oak Creek.

The soils of the dam and reservoir area consist of the Bolivar and Blackoar soil series. The Bolivar Series consists of moderately deep, well-drained soils formed in residuum from sandstone on uplands. The depth to rock is 20-40 inches. For engineering purposes the soils are classified as low plastic silt (ML), silty sand (SM) clayey sand (SC) or low plastic clays (CL). The Blackoar Series consists of deep, poorly drained soils on nearly level areas in the flood plain. The depth to bedrock is greater than 60 inches. For engineering purposes the soil is classified as a low plastic silt (ML) or a low plastic clay (CL).

The bedrock in the vicinity of the dam and reservoir consists of Warrensburg sandstone of the Pleasanton Group. The Warrensburg sandstone is a channel sandstone that is massive, medium grained, micaceous and crossbedded.

2.5 EVALUATION

a. Availability. No engineering data were available.

b. Adequacy. Seepage and stability analyses comparable to the requirements of the "Recommended Guidelines for Safety Inspection of Dams" were not available, which is considered a deficiency. These seepage and stability analyses should be performed for appropriate loading conditions (including earthquake loads) and made a matter of record.

c. Validity. The validity of the design, construction, and operation could not be determined due to the lack of engineering data.

SECTION 3 - VISUAL INSPECTION

3.1 FINDINGS

a. General. A visual inspection of Lions Lake Dam was made on 15 May, 1980. The inspection team included professional engineers with experience in dam design and construction, hydrology, hydraulic engineering, and geotechnical engineering. The inspection team consisted of Edwin R. Burton, team leader; Robert Pinker, geologist; Gary Van Riessen, geotechnical engineer; John Ruhl, hydrologist/hydraulic engineer; and Russell Burnham, structural engineer. Specific observations are discussed below. No observations were made of the condition of the upstream face of the dam below the pool elevation at the time of the inspection.

b. Dam. The inspection team observed the following conditions at the dam. There was no riprap on the upstream face of the dam. Some minor erosion had occurred at the waterline. A ditch excavated in the left abutment on the upstream side of the dam allowed runoff from the area south of the dam to drain into the lake. Another ditch excavated in the left abutment downstream at the dam allowed hillside runoff to divert around the dam. Both of these ditches show signs of erosion. Some erosion was also observed at the outlet end of the primary spillway pipe. Part of a retaining wall supporting a small portion of the right side of the embankment at the downstream toe had failed and the remaining part of the wall was leaning. The downstream face of the dam is grass-covered. A quagmire is located near the embankment toe to the left of the primary spillway discharge channel. Several small animal burrows exist in the upstream face of the dam. No cracking, sliding, sloughing, settlement, or sinkholes were observed. There are no toe drains or relief wells. No evidence was found to indicate the embankment had ever been overtopped.

c. Appurtenant Structures. The primary spillway consists of a 48-inch drop inlet to a 36-inch steel pipe running through the embankment. A 12-inch low level inlet was located at the bottom of the drop inlet. The inside of the drop inlet and several feet of the outlet end of the spillway pipe were observable. The drop inlet pipe appeared in good condition. There was no trash screen at the inlet; however, there was an antivortex plate across the center of the inlet. The outlet end of the primary spillway pipe has been distorted where the crown is bent. Otherwise, it appeared to be in good condition. A 4-inch riser pipe with a locked cap was attached to the drop inlet pipe. It is suspected that this pipe provides for operation of a valve to the low level inlet of the drop inlet. The emergency spillway is located near the right end of the embankment and consists of a concrete section of the roadway pavement across a low area of the embankment crest. A concrete paved strip of the spillway approach on the upstream face of the dam serves as a boat ramp. Overflow of the spillway crest flows through a grass lined open channel downstream of the crest.

The lagoon immediately below the dam is contained by a dike along the south and west sides. A concrete retaining wall along a part of the east end of the lagoon separates the lagoon and dam embankment. No inlet to or outlet from the lagoon was observed; however, the lagoon was full of water. The only surface drainage that can get into the lagoon would be runoff from the embankment from approximately the middle of the dam to the emergency spillway. A small area of nonflowing seepage was observed near the toe of the lagoon dike beside the channel downstream from the primary spillway. Standing water and uncut grass was observed at the toe of the left half of the dam. This is referred to as the quagmire area in the remainder of this text. This quagmire could have resulted from seepage or possibly from poor drainage of left abutment runoff or primary spillway channel overflows.

d. Geology. The soil in the area of the dam and reservoir is formed in alluvium and in residuum from sandstone bedrock. The soils formed in alluvium are classified by the USDA/SCS as the Blackoak Series and consists of sandy silt (ML). The soils formed in residuum from sandstone are classified by the USDA/SCS as the Bolivar Series and consist of silty or clayey soil sand (SM or SC).

Rock outcrops composed of sandstone were observed in the left abutment. The unit was massive and crossbedded and badly weathered. No outcrops were observed on the right abutment.

Samples of the embankment were taken near the upstream crest at the center of the dam using an Oakfield sampler. The material sampled consisted of sandy clay of low plasticity which was classified for engineering purposes as CL. The samples were classified in accordance with ASTM D 2488-69. Based on these samples, it is anticipated the embankment consists of sandy clay of low plasticity.

The left abutment of the dam is sandstone bedrock. The right abutment of the dam is anticipated to consist of sandy clay overlying sandstone bedrock. The foundation of the dam is anticipated to be sandy or clayey silt overlying sandstone bedrock.

e. Reservoir Area. No slides of the reservoir banks were observed. No appreciable reservoir sedimentation was observed.

f. Downstream Channel. The channel downstream of the spillway outlet pipe is an open channel to the original streambed.

3.2 EVALUATION

The various deficiencies observed at the time of the inspection are not believed to represent an immediate safety hazard. They do, however, warrant monitoring and control. The erosion in the left abutment may

cause local distress and weakening of the embankment. The absence of riprap slope protection on the upstream embankment face can make this area vulnerable to erosion due to wave action. Animal burrows in the upstream face allow water to enter the embankment material and may erode to cause serious deterioration of embankment material. The erosion at the outlet end of the primary spillway pipe may cause distress within the pipe, which could eventually lead to loss of the functional capability of the pipe. The retaining wall failure does not appear to be causing distress within the embankment. However, erosion or localized sloughing could occur in this area, which could directly affect the stability of the embankment. The quagmire area should be drained then monitored to determine if it was caused by seepage.

SECTION 4 - OPERATIONAL PROCEDURES

4.1 PROCEDURES

The pool is primarily controlled by rainfall, runoff, evaporation, transpiration, and the capacity of the uncontrolled primary spillway.

4.2 MAINTENANCE OF DAM

The existing maintenance program includes removal of woody vegetation as it appears on the slopes of the dam. The slopes of the dam are mowed periodically. The asphalt road on the crest appears to be well maintained.

4.3 MAINTENANCE OF OPERATING FACILITIES

The 12-inch valved pipe may serve to draw down the reservoir, however the valvestem was locked and the valve unobservable, thus no evaluation of their maintenance could be made.

4.4 DESCRIPTION OF ANY WARNING SYSTEM IN EFFECT

There is no existing warning system or preplanned scheme for alerting downstream residents for this dam.

4.5 EVALUATION

The area of possible seepage should be monitored periodically and, if flows increase significantly or if seepage flows become muddy, a qualified engineer should be consulted. The program of cutting and maintaining the grass cover on the embankment appears to be doing a good job of controlling erosion and should be continued. The valve on the low level inlet to the drop inlet should be operated and inspected periodically.

SECTION 5 - HYDRAULIC/HYDROLOGIC

5.1 EVALUATION OF FEATURES

a. Design Data. Design data pertaining to hydrology and hydraulics was unavailable.

b. Experience Data. The drainage area and lake surface area are developed from USGS Warrensburg West, Warrensburg East, Centerview, and Cornelia Quadrangle Maps. The dam layout is from a survey made during the inspection.

c. Visual Observations.

(1) The primary spillway appears to be in good condition. The lake level at the time of the inspection was slightly above the inlet level and there was flow through the pipe. Only the inlet and outlet ends were observable. The spillway pipe discharges with a free outfall into an open channel. Some erosion was observed at the outlet end of the spillway pipe. There were no obstructions to flow in the downstream channel.

(2) The emergency spillway channel is in good condition with no evidence of erosion at the time of the inspection. A boring taken downstream of the crest and road showed the discharge channel to consist of cinders and clay over sandy silty clay.

(3) Spillway discharges do not endanger the integrity of the dam.

d. Overtopping Potential. Hydraulic routing of storms included routing through significant upstream structures. The hydrologic and hydraulic analyses are outlined in Appendix A. The spillways will not pass the probable maximum flood without overtopping the dam. The probable maximum flood is defined as the flood discharge that may be expected from the most severe combination of critical meteorologic and hydrologic conditions that are reasonably possible in the region. The spillways will pass 13 percent of the probable maximum flood without overtopping the dam and will pass the one percent chance flood estimated to have a peak outflow of 760 cfs developed by a 48-hour rainfall. According to the recommended guidelines from the Department of the Army, Office of the Chief of Engineers, a high hazard dam of small size should pass 50 to 100 percent of the probable maximum flood. Considering the reservoirs in the upstream watershed, and the downstream hazard, the appropriate spillway design flood should be the probable maximum flood. The portion of the estimated peak discharge of the probable maximum flood overtopping the dam would be 5,900 cfs of the total discharge from the reservoir of 7,400 cfs. The estimated duration of overtopping is

8.7 hours with a maximum height of 2.9 feet. The embankment could be jeopardized by overtopping for this period of time. The portion of the estimated peak discharge of 50 percent of the probable maximum flood overtopping the dam would be 2,900 cfs of the total discharge from the reservoir of 4,000 cfs. The estimated duration of overtopping is 6.2 hours with a maximum height of 2.0 feet.

According to the St. Louis District, Corps of Engineers, the effect from rupture of the dam could extend approximately one mile downstream of the dam. One home, one barn, and a trailer court could be severely damaged and lives could be lost should failure of the dam occur. Contents of the estimated downstream damage zone were verified by the inspection team.

SECTION 6 - STRUCTURAL STABILITY

6.1 EVALUATION OF STRUCTURAL STABILITY

a. Visual Observations. Visual observations of conditions which affect the structural stability of this dam are discussed in Section 3, paragraph 3.1b.

b. Design and Construction Data. No design data relating to the structural stability of the dam were found. Seepage and stability analyses comparable to the requirements of the "Recommended Guidelines for Safety Inspection of Dams" were not available, which is considered a deficiency.

c. Operating Records. No operational records exist.

d. Postconstruction Changes. The dam was originally constructed to create a water supply lake. It was constructed with two sedimentation lagoons located below the dam and a pumping station located north of these lagoons. The two lagoons and pumping station are shown on Plate 2 which was taken from a USGS map dated 1954. According to Mr. David Curtis of the City of Warrensburg, the water supply facilities have been abandoned and are no longer in service. It was observed by the inspection team that the left sedimentation lagoon no longer existed and that no evidence of a dike around the lagoon was observed. The area where this lagoon appears on Plate 2 is now a quagmire. The outlet from Lions Lake is shown on the USGS map at the far left. The observed location of the Lions Lake primary spillway is at the center of the dam. The primary spillway discharge channel is located between the quagmire and right sedimentation lagoon. No connections between the quagmire, lagoon, Lions Lake, or pumping station were observed. It is unknown when these changes were made.

e. Seismic Stability. The dam is located in Seismic Zone 1 which is a zone of minor seismic risk. A properly designed and constructed earth dam using sound engineering principles and conservatism should pose no serious stability problems during earthquakes in this zone. The seismic stability of an earth dam is dependent upon a number of factors: embankment and foundation material classifications and shear strengths; abutment materials, conditions, and strengths; embankment zoning; and embankment geometry.

Adequate descriptions of embankment design parameters, foundation and abutment conditions, or static stability analyses to assess the seismic stability of this embankment were not available and therefore no inferences will be made regarding the seismic stability. An assessment of the seismic stability should be included as part of the stability analysis required by the guidelines.

SECTION 7 - ASSESSMENT/REMEDIAL MEASURES

7.1 DAM ASSESSMENT

a. Safety. Several conditions observed during the visual inspection by the inspection team should be monitored and/or controlled. These are erosion of the upstream face of the embankment at normal lake level, possible seepage into the quagmire and lagoon below the dam, erosion of the drainage ditches at the left abutment, erosion of embankment material at the primary spillway pipe outlet, and animal burrows in the embankment. Seepage and stability analyses comparable to the requirements of the "Recommended Guidelines for Safety Inspection of Dams" were not available, which is considered a deficiency.

b. Adequacy of Information. Due to the lack of engineering design data, the conclusions in this report were based only on performance history and visual conditions. The inspection team considers that these data are sufficient to support the conclusions herein. Seepage and stability analyses comparable to the requirements of the "Recommended Guidelines for Safety Inspection of Dams" were not available, which is considered a deficiency.

c. Urgency. A program should be developed as soon as possible to monitor at regular intervals the deficiencies described in this report. The remedial measures recommended in paragraph 7.2 should be accomplished in the near future. The item recommended in paragraph 7.2a should be pursued on a high priority basis.

d. Necessity for Phase II. The Phase I investigation does not raise any serious questions relating to the safety of the dam nor does it identify any serious dangers which would require a Phase II investigation. However, the additional analyses noted in paragraph 2.5b are necessary for compliance with the guidelines.

e. Seismic Stability. This dam is located in Seismic Zone 1. Adequate description of embankment design parameters, foundation and abutment conditions, or static stability analyses to assess the seismic stability of this embankment was not available and therefore no inferences will be made regarding the seismic stability. An assessment of the seismic stability should be included as part of the recommended stability analysis.

7.2 REMEDIAL MEASURES

a. Alternatives. The emergency spillway size and/or height of the dam would need to be increased or the lake level would need to be lowered to increase available flood storage in order to pass the spillway design flood. The emergency spillway should be protected to prevent erosion.

b. Operation and Maintenance Procedures. The following operation and maintenance procedures are recommended and should be implemented under the direction of a professional engineer experienced in the design, construction, and maintenance of earth dams.

(1) Riprap should be placed on the upstream face of the dam at the normal lake level and near the primary spillway pipe outlet to prevent erosion of the embankment material.

(2) The quagmire area noted during the visual inspection should be drained and closely monitored and documented to determine if seepage is occurring in this area. The water level in the lagoon should be monitored and any significant changes should be evaluated.

(3) The animal burrows in the embankment should be repaired since they can lead to piping. Control measures should be implemented to discourage increased animal activity in the area. The embankment slope should be monitored during this repair.

(4) The area of the retaining wall failure should be monitored. Should displacement worsen, corrective repairs should be made.

(5) Erosion of the drainage ditches at the left abutment should be controlled.

(6) Seepage and stability analysis should be performed.

(7) A detailed inspection of the dam should be made periodically. More frequent inspections may be required if additional deficiencies are observed or the severity of the reported deficiencies increase.






PLATE I



LIONS LAKE
VICINITY TOPOGRAPHY









PLATE 3



LIONS LAKE
DAM CROSS SECTION



LIONS LAKE DAM
EMERGENCY SPILLWAY CROSS SECTIONS



LIONS LAKE DAM
EMERGENCY SPILLWAY PROFILE




PLATE 7




PHOTO 1: UPSTREAM FACE OF DAM LOOKING NORTH




PHOTO 2: UPSTREAM FACE OF DAM LOOKING SOUTH



PHOTO 3: CREST OF DAM



PHOTO 4: DOWNSTREAM SLOPE OF DAM LOOKING NORTH




PHOTO 5: DOWNSTREAM SLOPE OF DAM LOOKING SOUTH




PHOTO 6: PRIMARY SPILLWAY DROP INLET



PHOTO 7: PRIMARY SPILLWAY OUTLET



PHOTO 8: PLUNGE POOL BELOW PRIMARY SPILLWAY



PHOTO 9: EMERGENCY SPILLWAY CHANNEL



PHOTO 10: CONCRETE RETAINING WALL AT TOE OF DAM



PHOTO 11: QUAGMIRE AT TOE OF DAM



PHOTO 12: DRAINAGE DITCH FROM LEFT ABUTMENT UPSTREAM FACE




PHOTO 13: DRAINAGE DITCH FROM LEFT ABUTMENT DOWNSTREAM FACE




PHOTO 14: SANDSTONE FORMATION LEFT ABUTMENT ON UPSTREAM SIDE
OF DAM



PHOTO 15: ANIMAL BURROW ON UPSTREAM FACE, MEASURED APPROXIMATELY FIVE FEET DEEP



PHOTO 16: EROSION AREA ON UPSTREAM FACE AT WATERLINE

APPENDIX A
HYDROLOGIC AND HYDRAULIC ANALYSES

HYDROLOGIC AND HYDRAULIC ANALYSES

To determine the overtopping potential of Lions Lake Dam , flood routings were performed by applying the Probable Maximum Precipitation (PMP) to synthetic unit hydrographs to develop inflow hydrographs for Lions Lake and its upstream reservoirs. The inflow hydrographs were then routed through the reservoirs and spillways. The overtopping analyses were determined using the computer program HEC-1 (Dam Safety Version) (1).

The PMP was determined from regional charts prepared by the National Weather Service in "Hydrometeorological Report No. 33" (HMR-33). Reduction factors were not applied. The rainfall distribution for the 48-hour PMP storm was determined according to the procedures outlined in HMR-33 and EM 1110-2-1411. The Kansas City, Missouri rainfall distribution (12 min. interval - 48 hours duration), as provided by the St. Louis District, Corp of Engineers, was used when the one percent chance probability flood was routed through the reservoirs and spillways.

The synthetic unit hydrographs for the watershed were developed by the computer program using the Soil Conervation Service (SCS) method. The parameters for the unit hydrographs are shown in Table 1.

The SCS curve number (CN) method was used in computing the infiltration losses for rainfall-runoff relationships. The CN values used, and the result from the computer output, are shown in Table 2.

Although many impoundments exist in the watershed for Lions Lake, it was determined from visual inspection that only two impoundments upstream of Lions Lake would be included in the hydrologic and hydraulic analyses. Storms were routed through Pertle Springs Lake (immediately upstream of Lions Lake) and the second lake upstream of Pertle Springs Lake (see Plate 2) which shall be referenced as "Upstream Lake" through the remainder of this appendix.

Routing through the reservoirs was performed using the Modified Puls Method. The initial reservoir pool elevations for the routing of each storm were determined to be equivalent to the primary spillway crest elevations in accordance with antecedent storm conditions preceding the one percent probability and probable maximum storms outlined by the U.S. Army Corps of Engineers, St. Louis District (5). The hydraulic capacity of the spillways and the storage capacity of the reservoirs were defined by the elevation, surface area, storage, and discharge relationships shown in Table 3.

The rating curves for the spillways are shown in Table 4. The flow over the crest of each of the dams the Lions Lake and emergency spillway was determined using the non-level dam crest option (\$L and \$V cards) of the HEC-1 program.

The program assumes critical flow over a broad-crested weir. The flow through the primary spillways was determined from the orifice flow equation and weir flow equation. The flow over the Pertle Springs Lake emergency spillway was determined from the weir equation.

Where routings through upstream reservoirs resulted in overtopping of those structures, breach analyses were performed using HEC-1. The breaching parameters are noted in Table 5.

The result of the routing and breach analyses indicates that 13 percent of the PMF will not overtop the Lions Lake dam.

A summary of the routing analysis for different ratios of the PMF is shown in Table 6.

The computer input data and a summary of the output data are presented at the back of this appendix.

TABLE 1
SYNTHETIC UNIT HYDROGRAPH

<u>Parameters:</u>	<u>Upstream Lake</u>	<u>Pertle Springs Lake</u>	<u>Lions Lake</u>
Drainage Area (A)	179 acres	275 acres	426 acres
Hydraulic Length of Watercourse (L)	3,900 feet	4,460 feet	4,550 feet
Hydrologic Soil Cover Complex Number (CN')	81 (AMC III) 64 (AMC II)	80 63	82 66
Average Watershed Land Slope (Y)	2.7%	2.6%	2.7%
Lag Time (L _g)	0.56 hours (AMC III) 0.90 hours (AMC II)	0.65 hours 1.04 hours	0.61 hours 0.96 hours
Time of concentration (T _c)	0.93 hours (AMC III) 1.50 hours (AMC II)	1.08 hours 1.73 hours	1.02 hours 1.60 hours
Duration (D)	7 minutes (AMC III) 12 minutes (AMC II) (use 10 minutes in all cases)	9 minutes 14 minutes	8 minutes 13 minutes

TABLE 1
(Continued)

Time (Min)*	Upstream Lake		Discharge (cfs)* Pertle Springs Lake		Lions Lake	
	AMC II	AMC III	AMC II	AMC III	AMC II	AMC III
0	0	0	0	0	0	0
10	11	32	12	35	22	63
20	33	106	35	112	66	204
30	67	190	71	224	135	392
40	108	210	120	280	223	463
50	132	182	160	274	286	432
60	137	129	182	229	307	343
70	129	80	184	162	302	222
80	112	53	173	107	270	148
90	89	35	154	75	229	102
100	64	23	129	52	174	68
110	48	15	98	36	129	47
120	37	10	75	25	99	31
130	28	6	58	17	78	21
140	21	4	47	12	60	14
150	16	3	37	8	46	10
160	12	2	29	6	36	7
170	9	1	23	4	28	5
180	7	1	18	3	21	3

*From HEC-1 computer output

FORMULAS USED:

$$L_g = \frac{1.486 \times (S + 1)^{0.7}}{1,900 \times Y^{0.5}} \quad (4)$$

$$S = \frac{1,000}{CN'} - 10$$

$$T_c = L_g / 0.6$$

$$D = 0.133 T_c$$

TABLE 2

RAINFALL-RUNOFF VALUES

<u>Selected Storm Event</u>	<u>Storm Duration (Hours)</u>	<u>Rainfall (Inches)</u>	<u>Runoff (Inches)</u>	<u>Loss (Inches)</u>
PMP				
Upstream Lake	48	34.58	31.92	2.66
Pertle Springs Lake	48	34.58	31.75	2.83
Lions Lake	48	34.58	32.08	2.50
1% Probability				
Upstream Lake	48	5.93	2.21	3.72
Pertle Springs Lake	48	5.93	2.13	3.80
Lions Lake	48	5.93	2.39	3.54

Additional Data:

- 1) The soil associations in this watershed are Bolivar, Barco, Deepwater, Macksburg, Sampsel, and Weller (3).
 92 percent of total drainage area in hydrologic soil group B.
 8 percent of total drainage area in hydrologic soil group C.
 40 percent of the land use was urban.
 40 percent of the land use was grassland.
 20 percent of the land use was timberland (2 and 4).
- 2) SCS Runoff Curve CN (AMC III) for ratios of the PMF:
 81 - Upstream Lake
 80 - Pertle Springs Lake
 82 - Lions Lake
- 3) SCS Runoff Curve CN (AMC II) for the one percent probability flood:
 64 - Upstream Lake
 63 - Pertle Springs Lake
 66 - Lions Lake

TABLE 3

ELEVATION, SURFACE AREA, STORAGE, AND DISCHARGE RELATIONSHIPS

<u>Elevation (feet-MSL)</u>	<u>Lake Surface Area (acres)</u>	<u>Lake Storage (acre-ft)</u>	<u>Spillway Discharge (cfs)</u>
Upstream Lake			
*785.0	1.0	2	0
***789.2	1.7	9	11
Pertle Springs Lake			
*774.0	16.1	75	0
**774.4	17.2	82	14
***777.6	25.8	149	924
Lions Lake			
*755.0	16.1	54	0
**758.1	21.3	112	113
***760.2	25.4	160	617

*Primary spillway crest elevation

**Emergency spillway crest elevation

***Top of dam elevation

The relationships in Table 3 were developed from the Centerview, Missouri and Cornelia, Missouri 7.5 minute quadrangle maps and the field measurements.

TABLE 4

SPILLWAY RATING CURVE

<u>Reservoir Elevation (ft-msl)</u>	<u>Primary Spillway Discharge (cfs)</u>	<u>Emergency Spillway Discharge (cfs)</u>	<u>Total Spillway Discharges (cfs)</u>
Upstream Lake			
785.0	0	-	0
786.0	10	-	10
787.0	10	-	10
788.0	10	-	10
789.0	11	-	11
**789.2	11	-	11
790.0	11	-	11
791.0	12	-	12
Pertle Springs Lake			
774.0	0	-	0
*774.4	14	0	14
775.0	340	19	53
776.0	97	94	191
777.0	142	206	348
**777.6	169	300	469
778.0	191	363	554
779.0	211	524	735
Lions Lake			
755.0	0	0	0
756.0	44	0	44
757.0	85	0	85
758.0	107	2	110
*758.1	109	4	113
759.0	124	99	223
760.0	140	377	518
**760.2	149	468	617
761.0	185	929	1114
762.0	192	1279	1461
763.0	196	1656	1852
764.0	200	2069	2269

*Emergency Spillway Crest Elevation

**Top of Dam Elevation

METHOD USED:

Upstream Lake

Primary spillway releases were determined by nomographs for corrugated metal pipe culverts with outlet control (7).

Pertle Springs Lake

Primary spillway release rates were based on the discharge calculated for flow through the pipe and drop inlet using the orifice equation:

$$Q = Ca[2gH]^{1/2}$$

where:

- C = 0.77 = coefficient of discharge for pipe or
- C = 0.57 = coefficient of discharge for drop inlet
- a = 7.07 sq. ft. = net area of orifice for pipe or
- a = 19.6 sq. ft. = net area of orifice for drop inlet
- g = 32.2 ft/sec² = gravitational acceleration
- H = difference between the energy gradient elevation upstream and the downstream tailwater elevation for pipe or
- H = height of water surface above the crest of the drop inlet (6).

Emergency spillway release rates were computed using the weir equation:

$$Q = CLH^{3/2}$$

L = 16 feet
H = head in feet
C = coefficient of discharge and varies between 2.61 and 3.32.

Lions Lake

Primary spillway release rates were based on the discharge calculated for flow through the drop inlet and pipe using the orifice equation and the weir equation for a sharp crest circular weir. The minimum discharge of the two equations at a given water surface elevation was used for the spillway rating curve.

Orifice equation:

$$Q = C_a [2gH]^{1/2}$$

where:

- C = 0.7 = coefficient of discharge
- a = 7.07 sq. ft. = net area of orifice
- g = 32.2 ft/sec² = gravitational acceleration
- H = difference between the energy gradient elevation upstream and the downstream tailwater elevation (6).

Circular weir equation:

$$Q = C_o (2\pi R_s) (H_o)^{3/2}$$

where:

- C_o = coefficient of discharge that varies between 1.0 and 3.5 with H_o.
- H_o = effective head
- R_s = radius of sharp crested weir = 2.0 feet

Emergency spillway releases were computed using the equations for flow over non-level crests:

$$d_c = 2/3 (H_m + 1/4 \Delta Y)$$

$$A = 1/2 T (2d_c - \Delta Y)$$

$$Q = (A^3 g/T)^{0.5}$$

where:

- d_c = critical depth (feet)
- H_m = available specific energy which is taken to be the height of the water surface in the reservoir above the bottom of the section (feet)
- ΔY = change in elevation across the section (feet)
- A = flow area (sq. ft.)
- T = top width (feet)
- Q = flow (cfs)
- g = 32.2 ft/sec² = acceleration due to gravity.

TABLE 5

BREACHING PARAMETERS

	<u>Upstream Lake</u>	<u>Pertle Springs Lake</u>
Bottom Width of Breach (BRWID)	10 feet	10 feet
Side Slope of Breach (z) (In feet horizontal to 1.0 feet vertical)	0.5	0.5
Elevation of Breach Bottom at Maximum Size of Breach (ELBM)	782.0 ft. m.s.l.	764.0 ft. m.s.l.
Time for Breach to Develop to Maximum Size (TFAIL)	1.0 hour	1.0 hour
Elevation of Water Surface Which Will Cause Dam to Fail (FAILEL)	789.2 ft. m.s.l.	777.6 ft. m.s.l.

TABLE 6

RESULTS OF FLOOD ROUTINGS

Ratio of PMF	Peak Inflow (CFS)	Peak Lake Elevation (ft.-MSL)	Total Storage (AC.-FT.)	Peak Outflow (CFS)	Depth (ft.) Over Top of Dam
-	0	*775.0	54	0	-
0.13	795	760.1	156	545	0
0.50	4,119	762.2	212	4,045	2.0
1.00	7,570	763.1	239	7,401	2.9

* Primary spillway drop inlet crest elevation.

BIBLIOGRAPHY

- (1) U.S. Army Corps of Engineers, Hydrologic Engineering Center, Flood Hydrograph Package (HEC-1), Dam Safety Version, July 1978, Davis, California.
- (2) U.S. Department of Agriculture, Soil Conservation Service, Technical Release No. 55, Urban Hydrology for Small Watersheds, January, 1975.
- (3) U.S. Department of Agriculture, Soil Conservation Service, Preliminary Soils Report for Johnson County, Missouri.
- (4) U.S. Department of Agriculture, Soil Conservation Service, National Engineering Handbook, Section 4, Hydrology, August 1972.
- (5) U.S. Army Corps of Engineers, St. Louis District, Hydrologic/Hydraulic Standards, Phase I Safety Inspection of Non-Federal Dams, 12 December 1979.
- (6) Horace W. King and Ernest F. Brater, Handbook of Hydraulics, Sixth Edition, McGraw Hill Book Company, 1976.
- (7) U.S. Department of Commerce, Bureau of Public Roads, Hydraulic Engineering Circular No. 5, Hydraulic Charts for the Selection of Highway Culverts, December, 1965.
- (8) U.S. Department of the Interior, Bureau of Reclamation, Design of Small Dams, 1974, Washington, D.C.
- (9) U.S. Department of Agriculture, Soil Conservation Service, Soil Survey Interpretations and Field Maps, 1980.
- (10) Mary H. McCracken, Missouri Division of Geological Survey, Geologic Map of Missouri, 1961.

48 5610. 05 764. 1. 774. 777.6 3
 49 K LIONS LAKE DAM (48 HR. PROBABLE MAXIMUM RUNOFF) 1
 50 1 2 .666 1

PROJECT 9166. DATE 27 AUG 80 PAGE 3
 FLOOD HYDROGRAPH PACKAGE - REC-1 PROGRAM M2702-OU TIME 18:16:26 CASE PAF

LINE NO	DESCRIPTION	100	120	130	140	150	160	
51	P	24.70	101	120	130	140		
52	T							
53	U2							
54	X	.61						
55	K		1					
56	K		7					
57	K1	COMBINE HYDROGRAPHS-TOTAL FLOW LIONS (48 HR. PAF)						
58	K	1	8					
59	K1	ROUTING THROUGH LIONS LAKE						
60	T		1					
61	V1							
62	V4	755.	756.	757.	758.	759.	760.	
63	V5	..	44.	85.3	107.7	123.7	140.5	
64	SAC.	16.13	24.69	43.74	65.51	95.75	131.02	
65	S1745.	755.	760.	770.	780.	790.	800.	
66	S1755.							
67	S0740.2							
68	S10.0	29.	44.	117.	225.	336.	469.	
69	S1757.9	756.1	759.1	760.4	760.6	760.8	761.2	
70	R							

LINE NO	DESCRIPTION	100	120	130	140	150	160
71	V1						
72	V4	755.	756.	757.	758.	759.	760.
73	V5	..	44.	85.3	107.7	123.7	140.5
74	SAC.	16.13	24.69	43.74	65.51	95.75	131.02
75	S1745.	755.	760.	770.	780.	790.	800.
76	S1755.						
77	S0740.2						
78	S10.0	29.	44.	117.	225.	336.	469.
79	S1757.9	756.1	759.1	760.4	760.6	760.8	761.2
80	R						

761. 762. 763. 764.
 191.7 193.8 199.8
 536. 572. 596.
 761.7 762.5 763.3

 FLOOD HYDROGRAPH PACKAGE (MFC-1)
 DAM SAFETY VERSION JULY 1978
 LAST MODIFICATION 06 FEB 80

MISSOURI DAM INSPECTION PROGRAM
 ST LOUIS DISTRICT US ARMY CORPS OF ENGINEERS
 EDWARDS/PERFILE SPRINGS LAKE-DAMS -- PMF

JOB SPECIFICATION
 NO NMR NREIN IDAY INK IMIN RETBC IPLT IPRT NSTAN
 288 0 10 0 0 0 0 0 0 0
 JOPER NWI LROPT TRACE
 5 0 0 0

MULTI-PLAN ANALYSES TO BE PERFORMED
 NPLAN= 1 NPJID= 7 LRJID= 1
 STICS= .10 .12 .13 .14 .15 .50 1.00

 SUB-AREA PUNOFF COMPUTATION

UPSTREAM DAM (42 HR. PROBABLE MAXIMUM RUNOFF)
 ISTAG ICOMP ISECON ITAFFE JPLT JPRT INAME ISTAGE IAUTO
 1 0 0 0 0 3 1 0 0

HYDROGRAPH DATA
 INYDC IUNG TAREA SHPP TRSBA TRSPC RATIO ISNOW ISAVE LOCAL
 1 2 .28 .00 .28 1.00 .000 0 0 0
 SPTT PMS RG R12 R44 R65 R72 R96
 .00 24.70 101.00 120.60 130.00 144.00 .00 .00

PRECIP DATA
 LOSS DATA
 LROPT STPAR QLTOL CRAIN SIKKS RTIOK STOTL CWSIL ALSMK RTIMP
 0 .00 .00 1.00 .00 .00 1.00 -1.00 -81.00 .00 .00

CURVE NO = 81.00 WETNESS = -1.60 EFFECT CN = 81.00

UNIT HYDROGRAPH DATA
 ICE .00 LAG .56
 RECUSSION DATA
 SRTOR= .00 GRCSM= .00 RTIOR= 1.00

UNIT HYDROGRAPH 19 END OF PERIOD ORIGINATES, TC= .00 HOURS, LAG= .56 VOL= 1.00 23.
 106. 196. 210. 182. 129. 80. 53. 33.
 15. 6. 4. 3. 2. 1. 1. 0.

END-OF-PERIOD FLOW

UNIL HYDROGRAPH 19 END OF PERIOD ORIGINATES, IC= .00 HOURS, LAG= .56 VOL= 1.00 23.
 32. 106. 190. 210. 182. 129. 80. 53. 35. 1.00
 15. 16. 6. 4. 3. 2. 1. 1. 0.

END-OF-PERIOD-FLOW

PLACK & VEATCH PROJECT 9166. DATE 27 AUG 80 PAGE 6
 FLOOD HYDROGRAPH PACKAGE - REC-1 PROGRAM M2102-00 TIME 1818126 CASE PM1

NO.	DA	HR.	HY	PERIOD	RAIN	EXCS	LOSS	COMP	NO.	DA	HR.	PERIOD	RAIN	EXCS	LOSS	COMP
1.01	1.01	1.01	1.01	1	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	3.
1.01	1.01	1.01	1.01	2	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	5.
1.01	1.01	1.01	1.01	3	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	8.
1.01	1.01	1.01	1.01	4	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	12.
1.01	1.01	1.01	1.01	5	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	15.
1.01	1.01	1.01	1.01	6	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	17.
1.01	1.01	1.01	1.01	7	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	19.
1.01	1.01	1.01	1.01	8	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	20.
1.01	1.01	1.01	1.01	9	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	20.
1.01	1.01	1.01	1.01	10	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	21.
1.01	1.01	1.01	1.01	11	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	21.
1.01	1.01	1.01	1.01	12	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	22.
1.01	1.01	1.01	1.01	13	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	22.
1.01	1.01	1.01	1.01	14	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	22.
1.01	1.01	1.01	1.01	15	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	22.
1.01	1.01	1.01	1.01	16	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	22.
1.01	1.01	1.01	1.01	17	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	22.
1.01	1.01	1.01	1.01	18	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	22.
1.01	1.01	1.01	1.01	19	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	22.
1.01	1.01	1.01	1.01	20	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	23.
1.01	1.01	1.01	1.01	21	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	23.
1.01	1.01	1.01	1.01	22	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	23.
1.01	1.01	1.01	1.01	23	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	23.
1.01	1.01	1.01	1.01	24	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	23.
1.01	1.01	1.01	1.01	25	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	23.
1.01	1.01	1.01	1.01	26	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	23.
1.01	1.01	1.01	1.01	27	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	23.
1.01	1.01	1.01	1.01	28	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	23.
1.01	1.01	1.01	1.01	29	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	23.
1.01	1.01	1.01	1.01	30	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	23.
1.01	1.01	1.01	1.01	31	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	23.
1.01	1.01	1.01	1.01	32	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	23.
1.01	1.01	1.01	1.01	33	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	24.
1.01	1.01	1.01	1.01	34	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	24.
1.01	1.01	1.01	1.01	35	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	24.
1.01	1.01	1.01	1.01	36	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	24.
1.01	1.01	1.01	1.01	37	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	24.
1.01	1.01	1.01	1.01	38	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	39	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	40	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	41	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	42	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	43	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	44	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	45	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	46	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	47	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	48	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	49	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	50	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	51	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	52	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	53	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.
1.01	1.01	1.01	1.01	54	.00	.00	.00	0	1.02	1.02	1.01	1.01	.03	.02	.01	26.

1.01	8.20	50	.01	.00	.01	0.	1.02	8.20	194	.13	.12	.01	123.
1.01	8.30	51	.01	.00	.01	0.	1.02	8.30	195	.13	.12	.01	123.
1.01	8.40	52	.01	.00	.01	0.	1.02	8.40	196	.13	.12	.01	124.
1.01	8.50	53	.01	.00	.01	0.	1.02	8.50	197	.13	.12	.01	124.
1.01	9.00	54	.01	.00	.01	0.	1.02	9.00	198	.13	.12	.01	126.
1.01	9.10	55	.01	.00	.01	0.	1.02	9.10	199	.13	.12	.01	129.
1.01	9.20	56	.01	.00	.01	0.	1.02	9.20	200	.13	.12	.01	129.
1.01	9.30	57	.01	.00	.01	0.	1.02	9.30	201	.13	.12	.01	127.
1.01	9.40	58	.01	.00	.01	0.	1.02	9.40	202	.13	.12	.01	128.
1.01	9.50	59	.01	.00	.01	0.	1.02	9.50	203	.13	.12	.01	128.
1.01	10.00	60	.01	.00	.01	0.	1.02	10.00	204	.13	.12	.01	129.
1.01	10.10	61	.01	.00	.01	0.	1.02	10.10	205	.13	.12	.01	129.
1.01	10.20	62	.01	.00	.01	0.	1.02	10.20	206	.13	.12	.01	129.
1.01	10.30	63	.01	.00	.01	0.	1.02	10.30	207	.13	.12	.01	130.
1.01	10.40	64	.01	.00	.01	0.	1.02	10.40	208	.13	.12	.01	130.
1.01	10.50	65	.01	.00	.01	0.	1.02	10.50	209	.13	.12	.01	131.
1.01	11.00	66	.01	.00	.01	0.	1.02	11.00	210	.13	.12	.01	131.
1.01	11.10	67	.01	.00	.01	0.	1.02	11.10	211	.13	.12	.01	131.
1.01	11.20	68	.01	.00	.01	0.	1.02	11.20	212	.13	.12	.01	131.
1.01	11.30	69	.01	.00	.01	0.	1.02	11.30	213	.13	.12	.01	132.
1.01	11.40	70	.01	.00	.01	0.	1.02	11.40	214	.13	.12	.01	132.
1.01	11.50	71	.01	.00	.01	0.	1.02	11.50	215	.13	.12	.01	132.
1.01	12.00	72	.01	.00	.01	0.	1.02	12.00	216	.13	.12	.01	133.
1.01	12.10	73	.01	.00	.01	0.	1.02	12.10	217	.62	.59	.02	161.
1.01	12.20	74	.03	.00	.03	0.	1.02	12.20	218	.42	.40	.02	170.
1.01	12.30	75	.03	.00	.03	0.	1.02	12.30	219	.42	.40	.02	222.
1.01	12.40	76	.03	.00	.03	0.	1.02	12.40	220	.42	.40	.02	280.
1.01	12.50	77	.03	.00	.03	0.	1.02	12.50	221	.42	.40	.02	330.
1.01	13.00	78	.03	.00	.03	1.	1.02	13.00	222	.40	.40	.02	366.
1.01	13.10	79	.04	.01	.03	1.	1.02	13.10	223	.50	.48	.02	391.
1.01	13.20	80	.04	.01	.03	3.	1.02	13.20	224	.50	.48	.02	416.
1.01	13.30	81	.04	.01	.03	5.	1.02	13.30	225	.50	.48	.01	442.
1.01	13.40	82	.04	.01	.03	5.	1.02	13.40	226	.50	.48	.01	466.
1.01	13.50	83	.04	.01	.03	6.	1.02	13.50	227	.50	.48	.01	486.
1.01	14.00	84	.04	.01	.03	7.	1.02	14.00	228	.50	.49	.01	500.
1.01	14.10	85	.05	.01	.03	8.	1.02	14.10	229	.50	.49	.01	513.
1.01	14.20	86	.05	.01	.03	9.	1.02	14.20	230	.62	.61	.01	533.
1.01	14.30	87	.05	.02	.03	11.	1.02	14.30	231	.62	.61	.01	563.
1.01	14.40	88	.05	.02	.03	12.	1.02	14.40	232	.62	.61	.01	590.
1.01	14.50	89	.05	.02	.03	14.	1.02	14.50	233	.62	.61	.01	614.
1.01	15.00	90	.05	.02	.03	15.	1.02	15.00	234	.62	.61	.01	632.
1.01	15.10	91	.04	.02	.03	16.	1.02	15.10	235	.57	.56	.01	651.
1.01	15.20	92	.02	.03	.04	18.	1.02	15.20	236	.95	.94	.01	658.
1.01	15.30	93	.13	.06	.07	21.	1.02	15.30	237	1.71	1.69	.02	714.
1.01	15.40	94	.33	.17	.15	31.	1.02	15.40	238	4.27	4.23	.04	939.
1.01	15.50	95	.09	.06	.04	48.	1.02	15.50	239	1.23	1.22	.01	1326.
1.01	16.00	96	.06	.04	.02	65.	1.02	16.00	240	.76	.75	.01	1696.
1.01	16.10	97	.04	.03	.02	71.	1.02	16.10	241	.58	.58	.00	1793.
1.01	16.20	98	.04	.03	.02	67.	1.02	16.20	242	.58	.58	.00	1631.
1.01	16.30	99	.04	.03	.02	57.	1.02	16.30	243	.58	.58	.00	1361.
1.01	16.40	100	.04	.03	.02	49.	1.02	16.40	244	.58	.58	.00	1108.
1.01	16.50	101	.04	.03	.02	42.	1.02	16.50	245	.56	.56	.00	944.
1.01	17.00	102	.04	.03	.02	38.	1.02	17.00	246	.56	.56	.00	835.
1.01	17.10	103	.04	.02	.01	36.	1.02	17.10	247	.46	.45	.00	739.
1.01	17.20	104	.04	.02	.01	34.	1.02	17.20	248	.46	.46	.00	689.
1.01	17.30	105	.04	.02	.01	32.	1.02	17.30	249	.46	.46	.00	645.
1.01	17.40	106	.04	.02	.01	30.	1.02	17.40	250	.46	.46	.00	589.
1.01	17.50	107	.04	.02	.01	28.	1.02	17.50	251	.46	.46	.00	563.
1.01	18.00	108	.04	.02	.01	28.	1.02	18.00	252	.46	.46	.00	539.
1.01	18.10	109	.00	.00	.00	25.	1.02	18.10	253	.04	.04	.00	510.
1.01	18.20	110	.00	.00	.00	24.	1.02	18.20	254	.04	.04	.00	436.

TIME	17:50	18:00	18:10	18:20	18:30	18:40	18:50	19:00	19:10	19:20	19:30	19:40	19:50	20:00	20:10	20:20	20:30	20:40	20:50	21:00	21:10	21:20	21:30	21:40	21:50	22:00	22:10	22:20	22:30	22:40	22:50	23:00	23:10	23:20	23:30	23:40	23:50	24:00
1.01	17:50	116	.54	.04	.01	.29	1.02	17:50	250	.46	.46	.00	.00	369.																								
1.01	18:00	117	.00	.00	.00	.19	1.02	18:00	255	.04	.04	.00	.00	277.																								
1.01	18:10	117	.00	.00	.00	.15	1.02	18:10	256	.04	.04	.00	.00	199.																								
1.01	18:20	113	.00	.00	.00	.10	1.02	18:20	257	.46	.46	.00	.00	510.																								
1.01	19:00	114	.00	.00	.00	.09	1.02	19:00	252	.46	.46	.00	.00	510.																								
1.01	19:10	115	.00	.00	.00	.06	1.02	19:10	259	.04	.04	.00	.00	110.																								
1.01	19:20	115	.00	.00	.00	.06	1.02	19:20	260	.04	.04	.00	.00	87.																								
1.01	19:30	117	.00	.00	.00	.04	1.02	19:30	261	.04	.04	.00	.00	72.																								
1.01	19:40	118	.00	.00	.00	.03	1.02	19:40	262	.04	.04	.00	.00	62.																								
1.01	19:50	119	.00	.00	.00	.03	1.02	19:50	263	.04	.04	.00	.00	56.																								
1.01	20:00	120	.00	.00	.00	.02	1.02	20:00	264	.04	.04	.00	.00	52.																								
1.01	20:10	121	.00	.00	.00	.02	1.02	20:10	265	.04	.04	.00	.00	49.																								
1.01	20:20	122	.00	.00	.00	.02	1.02	20:20	266	.04	.04	.00	.00	47.																								
1.01	20:30	123	.00	.00	.00	.02	1.02	20:30	267	.04	.04	.00	.00	46.																								
1.01	20:40	124	.00	.00	.00	.02	1.02	20:40	268	.04	.04	.00	.00	45.																								
1.01	20:50	125	.00	.00	.00	.02	1.02	20:50	269	.04	.04	.00	.00	45.																								
1.01	21:00	126	.00	.00	.00	.02	1.02	21:00	270	.04	.04	.00	.00	44.																								
1.01	21:10	127	.00	.00	.00	.02	1.02	21:10	271	.04	.04	.00	.00	44.																								
1.01	21:20	129	.00	.00	.00	.02	1.02	21:20	272	.04	.04	.00	.00	44.																								
1.01	21:30	129	.00	.00	.00	.02	1.02	21:30	273	.04	.04	.00	.00	44.																								
1.01	21:40	130	.00	.00	.00	.02	1.02	21:40	274	.04	.04	.00	.00	44.																								
1.01	21:50	131	.00	.00	.00	.02	1.02	21:50	275	.04	.04	.00	.00	44.																								
1.01	22:00	132	.00	.00	.00	.02	1.02	22:00	276	.04	.04	.00	.00	44.																								
1.01	22:10	133	.00	.00	.00	.02	1.02	22:10	277	.04	.04	.00	.00	44.																								
1.01	22:20	134	.00	.00	.00	.02	1.02	22:20	278	.04	.04	.00	.00	44.																								
1.01	22:30	135	.00	.00	.00	.02	1.02	22:30	279	.04	.04	.00	.00	44.																								
1.01	22:40	134	.00	.00	.00	.02	1.02	22:40	280	.04	.04	.00	.00	44.																								
1.01	22:50	137	.00	.00	.00	.02	1.02	22:50	281	.04	.04	.00	.00	44.																								
1.01	23:00	139	.00	.00	.00	.02	1.02	23:00	282	.04	.04	.00	.00	44.																								
1.01	23:10	139	.00	.00	.00	.02	1.02	23:10	283	.04	.04	.00	.00	44.																								
1.01	23:20	140	.00	.00	.00	.02	1.02	23:20	284	.04	.04	.00	.00	44.																								
1.01	23:30	141	.00	.00	.00	.02	1.02	23:30	285	.04	.04	.00	.00	44.																								
1.01	23:40	142	.00	.00	.00	.02	1.02	23:40	286	.04	.04	.00	.00	44.																								
1.01	23:50	143	.00	.00	.00	.02	1.02	23:50	287	.04	.04	.00	.00	44.																								
1.02	24:00	144	.00	.00	.00	.02	1.03	24:00	288	.04	.04	.00	.00	44.																								

SUM 34.58 31.92 2.66 36393.
 (772.)(611.)(65.)(973.90)

PEAK	6-HOUR	24-HOUR	72-HOUR	TOTAL VOLUME
178.3	719.	232.	119.	34325.
50.	20.	7.	3.	974.
25.89	30.82	31.73	31.73	31.73
606.89	722.85	805.89	805.89	605.99
357.	409.	474.	474.	474.
440.	567.	584.	584.	584.

HYDROGRAPH AT STA 1 FOR PLAN 1, RT10 1

PEAK	6-HOUR	24-HOUR	72-HOUR	TOTAL VOLUME
178.	72.	23.	17.	3432.
5.	2.	1.	0.	57.
2.35	3.00	3.17	3.17	3.17
606.89	722.85	805.89	805.89	605.99
357.	409.	474.	474.	474.
440.	567.	584.	584.	584.

HYDROGRAPH AT STA 1 FOR PLAN 1, RT10 6

PEAK 6-HOUR 24-HOUR 72-HOUR TOTAL VOLUME
891 360 116 60 17192

PROJECT 9166. DATE 27 AUG 80 PAGE 10
PROGRAM H21/02-00 TIME 18:10:26 CASE PMF

CM5 25. 10. 3. 2. 487.
INCHES 11.95 15.41 15.87 15.87
CM5 303.45 391.42 402.99 402.99
AC-FI 178. 250. 237. 237.
THOUS CU M 220. 264. 292. 292.

HYDROGRAPH AT STA 1 FOR PLAN 1, RT10 7

PEAK 6-HOUR 24-HOUR 72-HOUR TOTAL VOLUME
1753. 719. 232. 119. 34365.
CM5 50. 20. 7. 3. 974.
INCHES 25.59 30.82 31.73 31.73
CM5 626.85 792.85 805.99 805.99
AL-FI 357. 440. 476. 476.
THOUS CU M 440. 587. 588. 588.

HYDROGRAPH ROUTING

ROUTING THROUGH UPSTREAM DAM

ISTAG ICOMP ISECON ISTEP IJPLT JPRY IMAME ISTAGE IAUTO
2 1 C 0 0 0 1 0
ROUTING DATA
IRES ISAME IOPT IPMP LSTR
-6 .000 .00 1 1 0 0
NSTPS NSTBL LAG AMSKK R TSK STORA ISPRAT
1 0 0 .000 .000 .000 -785.
STAGE 785.00 797.00 788.00 789.00 790.00 791.00
FLOW .00 10.00 10.00 11.00 11.00 12.00
SURFACE AREA 0. 3. 11. 21. 44.
CAPACITY 0. 2. 11. 236. 557.

ELEVATION= 780. 785. 790. 800. 810. 820.
DAM DATA
LPII SP+JD CO+W ERPV FLEVI CO2L CAREA EXPL
139.2 .0 .0 1.5 .0 .0 .0 .0
TOPEL COGD ERPO DAMVID
789.2 2.6 1.5 264.
DAM BREACH DATA
BRVID 2 ELD TPRII USEL PAIREL

CMS 25. 10. 3. 487.
 INCHES 19.47 15.47 15.87 15.87
 PM 303.45 391.42 402.99 402.99
 AC-FT 178. 230. 237. 237.
 THOUS CU M 220. 264. 292. 292.

HYDROGRAPH AT STA 1 FOR PLAN 1, RT10 7

PEAK 6-HOUR 24-HOUR 72-HOUR TOTAL VOLUME
 CFS 1782. 719. 232. 119. 34365.
 CMS 50. 20. 7. 3. 974.
 INCHES 23.59 30.22 31.73 31.73
 PM 636.85 732.85 805.99 805.99
 AC-FT 357. 460. 474. 474.
 THOUS CU M 440. 507. 504. 504.

HYDROGRAPH ROUTING

ROUTING THROUGH UPSTREAM DAM

ISTAQ 1CONP IECON ISAPE JPLT JPRT INAME ISTAGE IAUFO
 2 1 0 0 0 0 1 0 0
 ROUTING DATA
 IRES ISAPE IOPT ISPR LSTR
 1 1 0 0 0

ASTPS NSTDL LAG AMRKE X ISK STORA ISPRAT
 1 0 0 0.000 .000 .000 -785. -1

STA 785.00 787.00 788.00 789.00 790.00 791.00

FLOW .03 10.00 10.00 10.00 11.00 11.00 12.00

SURFCE PRAEF 0. 1. 3. 11. 21. 44.

CAPACITY 0. 11. 77. 236. 557.

ELEVATION 780. 785. 790. 800. 810. 820.

CRLL SPVID COLU EXPM FLEVEL COOL CAREA EXPL
 739.2 .0 1.5 .0 .0 .0 .0

TOPEL COOD EXPD DAMVID
 789.2 2.0 1.5 264.

DAM BREAK DATA
 BRVFO ELBW TRAIL WSEL FRTEL

SUB-AREA RUNOFF COMPUTATION
 PERILE SPRINGS DAM (68 HR. PROBABLE MAXIMUM RUNOFF)

ISTAQ 3 ICOMP 0 IECON 0 ITAPE 0 JPLT 3 JPRY 3 IMARE 1 IMASTG 0 IAUTO 0

HYDROGRAPH DATA
 IHYD 1 IUNG 2 IAREA .43 SNAP TRSDA TRSPC RATIO ISNOW 0 ISAME 0 LOCAL 0

PRECIP DATA
 SPFE .00 PMS 24.70 R6 101.00 R12 120.00 R24 130.00 R48 140.00 R72 140.00 R96 .00

LOSS DATA
 LROPT 0 STRKR .00 DLTAR .00 RTIOL 1.00 ERAIN .00 STRES 1.00 RTIOK 1.00 STIRL -1.00 CASTL -80.00 ALSNR .00 RTIMP .00

CURVE NO = 60.00 WETNESS = -1.00 EFFECT CM = 80.00

UNIT HYDROGRAPH DATA
 TC = .00 LAG = .65

RECESION DATA
 STRTR = .00 RECSN = .00 RTIOR = 1.00

UNIT HYDROGRAPH 21 END OF PERIOD ORDINATES, TC = .00 HOURS, LAG = .65 VOL = 1.00
 35. 112. 224. 283. 27. 229. 162. 107. 75. 52.
 36. 25. 17. 12. 6. 4. 3. 2. 1.

MO.NA		MR.NM	PERIOD	RAIN	EXCS	LOSS	END-OF-PERIOD FLO4		NO.BA	MR.NM	PERIOD	RAIN	EXCS	LOSS	COMP 0
0							CUMP 0								
1.01	1.01	1.00	1	.00	.00	.00	0.	1.02	.10	145	.03	.02	.01	.01	4.
1.01	1.01	.20	2	.00	.00	.00	0.	1.02	.20	146	.03	.02	.01	.01	6.
1.01	1.01	.30	3	.00	.06	.00	0.	1.02	.30	147	.03	.02	.01	.01	10.
1.01	1.01	.40	4	.00	.00	.00	0.	1.02	.40	148	.03	.02	.01	.01	15.
1.01	1.01	.50	5	.00	.00	.00	0.	1.02	.50	149	.03	.02	.01	.01	19.
1.01	1.01	1.00	6	.00	.00	.00	0.	1.02	1.00	150	.03	.02	.01	.01	23.
1.01	1.01	1.10	7	.00	.03	.00	0.	1.02	1.10	151	.03	.02	.01	.01	26.
1.01	1.01	1.20	8	.00	.00	.00	0.	1.02	1.20	152	.03	.02	.01	.01	28.
1.01	1.01	1.30	9	.00	.00	.00	0.	1.02	1.30	153	.03	.02	.01	.01	29.
1.01	1.01	1.40	10	.00	.00	.00	0.	1.02	1.40	154	.03	.02	.01	.01	30.
1.01	1.01	1.50	11	.00	.00	.00	0.	1.02	1.50	155	.03	.02	.01	.01	31.
1.01	1.01	2.00	12	.00	.00	.00	0.	1.02	2.00	156	.03	.02	.01	.01	32.
1.01	1.01	2.10	13	.00	.00	.00	0.	1.02	2.10	157	.03	.02	.01	.01	32.
1.01	1.01	2.20	14	.00	.00	.00	0.	1.02	2.20	158	.03	.02	.01	.01	32.
1.01	1.01	2.30	15	.00	.00	.00	0.	1.02	2.30	159	.03	.02	.01	.01	33.

1.01	1.50	11	-00	-00	-00	0.	1.02	1.50	155	-03	-02	-01	31.
1.01	2.00	12	-00	-00	-00	0.	1.02	2.00	156	-03	-02	-01	32.
1.01	3.00	18	-00	-00	-00	0.	1.02	3.00	162	-03	-02	-01	33.
1.01	3.10	19	-00	-00	-00	0.	1.02	3.10	163	-03	-02	-01	33.
1.01	3.20	20	-00	-00	-00	0.	1.02	3.20	164	-03	-02	-01	34.
1.01	3.30	21	-00	-00	-00	0.	1.02	3.30	165	-03	-02	-01	34.
1.01	3.40	22	-00	-00	-00	0.	1.02	3.40	166	-03	-02	-01	34.
1.01	3.50	23	-00	-00	-00	0.	1.02	3.50	167	-03	-02	-01	34.
1.01	4.00	24	-00	-00	-00	0.	1.02	4.00	168	-03	-02	-01	34.
1.01	4.10	25	-00	-00	-00	0.	1.02	4.10	169	-03	-02	-01	34.
1.01	4.20	26	-00	-00	-00	0.	1.02	4.20	170	-03	-02	-01	34.
1.01	4.30	27	-00	-00	-00	0.	1.02	4.30	171	-03	-02	-01	35.
1.01	4.40	28	-00	-00	-00	0.	1.02	4.40	172	-03	-02	-01	35.
1.01	4.50	29	-00	-00	-00	0.	1.02	4.50	173	-03	-02	-01	35.
1.01	5.00	30	-00	-00	-00	0.	1.02	5.00	174	-03	-02	-01	35.
1.01	5.10	31	-00	-00	-00	0.	1.02	5.10	175	-03	-02	-01	35.
1.01	5.20	32	-00	-00	-00	0.	1.02	5.20	176	-03	-02	-01	35.
1.01	5.30	33	-00	-00	-00	0.	1.02	5.30	177	-03	-02	-01	35.
1.01	5.40	34	-00	-00	-00	0.	1.02	5.40	178	-03	-02	-01	35.
1.01	5.50	35	-00	-00	-00	0.	1.02	5.50	179	-03	-02	-01	35.
1.01	6.00	36	-00	-00	-00	0.	1.02	6.00	180	-03	-02	-01	36.
1.01	6.10	37	-00	-00	-00	0.	1.02	6.10	181	-13	-10	-03	39.
1.01	6.20	38	-00	-00	-00	0.	1.02	6.20	182	-13	-10	-03	48.
1.01	6.30	39	-00	-00	-00	0.	1.02	6.30	183	-13	-11	-02	67.
1.01	6.40	40	-00	-00	-00	0.	1.02	6.40	184	-13	-11	-02	90.
1.01	6.50	41	-00	-00	-00	0.	1.02	6.50	185	-13	-11	-02	113.
1.01	7.00	42	-00	-00	-00	0.	1.02	7.00	186	-13	-11	-02	133.
1.01	7.10	43	-00	-00	-00	0.	1.02	7.10	187	-13	-11	-02	148.
1.01	7.20	44	-00	-00	-00	0.	1.02	7.20	188	-13	-11	-02	158.
1.01	7.30	45	-00	-00	-00	0.	1.02	7.30	189	-13	-11	-02	163.
1.01	7.40	46	-00	-00	-00	0.	1.02	7.40	190	-13	-11	-02	171.
1.01	7.50	47	-00	-00	-00	0.	1.02	7.50	191	-13	-11	-02	175.
1.01	8.00	48	-00	-00	-00	0.	1.02	8.00	192	-13	-11	-02	179.
1.01	8.10	49	-00	-00	-00	0.	1.02	8.10	193	-13	-11	-02	181.
1.01	8.20	50	-00	-00	-00	0.	1.02	8.20	194	-13	-11	-02	184.
1.01	8.30	51	-00	-00	-00	0.	1.02	8.30	195	-13	-12	-02	185.
1.01	8.40	52	-00	-00	-00	0.	1.02	8.40	196	-13	-12	-01	187.
1.01	8.50	53	-00	-00	-00	0.	1.02	8.50	197	-13	-12	-01	188.
1.01	9.00	54	-00	-00	-00	0.	1.02	9.00	198	-13	-12	-01	190.
1.01	9.10	55	-00	-00	-00	0.	1.02	9.10	199	-13	-12	-01	191.
1.01	9.20	56	-00	-00	-00	0.	1.02	9.20	200	-13	-12	-01	192.
1.01	9.30	57	-00	-00	-00	0.	1.02	9.30	201	-13	-12	-01	193.
1.01	9.40	58	-00	-00	-00	0.	1.02	9.40	202	-13	-12	-01	194.
1.01	9.50	59	-00	-00	-00	0.	1.02	9.50	203	-13	-12	-01	194.
1.01	10.00	60	-00	-00	-00	0.	1.02	10.00	204	-13	-12	-01	195.
1.01	10.10	61	-00	-00	-00	0.	1.02	10.10	205	-13	-12	-01	196.
1.01	10.20	62	-00	-00	-00	0.	1.02	10.20	206	-13	-12	-01	196.
1.01	10.30	63	-00	-00	-00	0.	1.02	10.30	207	-13	-12	-01	197.
1.01	10.40	64	-00	-00	-00	0.	1.02	10.40	208	-13	-12	-01	198.
1.01	10.50	65	-00	-00	-00	0.	1.02	10.50	209	-13	-12	-01	198.
1.01	11.00	66	-00	-00	-00	0.	1.02	11.00	210	-13	-12	-01	199.
1.01	11.10	67	-00	-00	-00	0.	1.02	11.10	211	-13	-12	-01	199.
1.01	11.20	68	-00	-00	-00	0.	1.02	11.20	212	-13	-12	-01	200.
1.01	11.30	69	-00	-00	-00	0.	1.02	11.30	213	-13	-12	-01	200.
1.01	11.40	70	-00	-00	-00	0.	1.02	11.40	214	-13	-12	-01	201.
1.01	11.50	71	-00	-00	-00	0.	1.02	11.50	215	-13	-12	-01	201.

1.01	11:20	62	.01	.00	.01	1.02	11:10	211	.13	.12	.01	199.
1.01	11:20	72	.01	.00	.01	1.02	12:00	216	.13	.12	.01	202.
1.01	11:20	75	.03	.00	.03	1.02	12:10	217	.42	.39	.02	212.
1.01	11:20	74	.03	.00	.03	1.02	12:20	218	.42	.39	.02	242.
1.01	11:20	75	.03	.00	.03	1.02	12:30	219	.42	.40	.02	303.
1.01	11:20	76	.03	.00	.03	1.02	12:40	220	.42	.40	.02	379.
1.01	11:20	77	.03	.00	.03	1.02	12:50	221	.42	.40	.02	454.
1.01	11:20	78	.03	.00	.03	1.02	13:00	222	.42	.40	.02	518.
1.01	11:20	79	.04	.00	.03	1.02	13:10	223	.50	.48	.02	560.
1.01	11:20	80	.04	.01	.03	1.02	13:20	224	.50	.48	.02	606.
1.01	11:20	81	.04	.01	.03	1.02	13:30	225	.50	.48	.02	646.
1.01	11:20	82	.04	.01	.03	1.02	13:40	226	.50	.48	.02	684.
1.01	11:20	83	.04	.01	.03	1.02	13:50	227	.50	.48	.01	718.
1.01	11:20	84	.04	.01	.03	1.02	14:00	228	.50	.49	.01	745.
1.01	11:20	85	.05	.01	.04	1.02	14:10	229	.62	.61	.02	768.
1.01	11:20	86	.05	.01	.04	1.02	14:20	230	.62	.61	.01	796.
1.01	11:20	87	.05	.01	.04	1.02	14:30	231	.62	.61	.01	833.
1.01	11:20	88	.05	.02	.03	1.02	14:40	232	.62	.61	.01	874.
1.01	11:20	89	.05	.02	.03	1.02	14:50	233	.62	.61	.01	913.
1.01	11:20	90	.05	.02	.03	1.02	15:00	234	.62	.61	.01	946.
1.01	11:20	91	.04	.02	.03	1.02	15:10	235	.57	.56	.01	967.
1.01	11:20	92	.07	.03	.04	1.02	15:20	236	.95	.93	.01	990.
1.01	11:20	93	.13	.06	.07	1.02	15:30	237	1.71	1.68	.02	1057.
1.01	11:20	94	.33	.17	.16	1.02	15:40	238	4.27	4.22	.04	1308.
1.01	11:20	95	.09	.03	.04	1.02	15:50	239	1.23	1.22	.01	1731.
1.01	11:20	96	.06	.03	.02	1.02	16:00	240	.76	.75	.01	2269.
1.01	11:20	97	.04	.03	.02	1.02	16:10	241	.58	.58	.00	2536.
1.01	11:20	98	.04	.03	.02	1.02	16:20	242	.58	.58	.00	2493.
1.01	11:20	99	.04	.03	.02	1.02	16:30	243	.58	.58	.00	2740.
1.01	11:20	100	.04	.03	.02	1.02	16:40	244	.58	.58	.00	1892.
1.01	11:20	101	.04	.03	.02	1.02	16:50	245	.58	.58	.00	1399.
1.01	11:20	102	.04	.03	.02	1.02	17:00	246	.58	.58	.00	1402.
1.01	11:20	103	.04	.02	.01	1.02	17:10	247	.46	.45	.00	1265.
1.01	11:20	104	.04	.02	.01	1.02	17:20	248	.46	.45	.00	1154.
1.01	11:20	105	.04	.02	.01	1.02	17:30	249	.46	.45	.00	1063.
1.01	11:20	106	.04	.02	.01	1.02	17:40	250	.46	.45	.00	982.
1.01	11:20	107	.04	.02	.01	1.02	17:50	251	.46	.45	.00	917.
1.01	11:20	108	.04	.02	.01	1.02	18:00	252	.46	.46	.00	867.
1.01	11:20	109	.00	.00	.00	1.02	18:10	253	.04	.04	.00	818.
1.01	11:20	110	.00	.00	.00	1.02	18:20	254	.04	.04	.00	749.
1.01	11:20	111	.00	.00	.00	1.02	18:30	255	.04	.04	.00	640.
1.01	11:20	112	.00	.00	.00	1.02	18:40	256	.04	.04	.00	513.
1.01	11:20	113	.00	.00	.00	1.02	18:50	257	.04	.04	.00	391.
1.01	11:20	114	.00	.00	.00	1.02	19:00	258	.04	.04	.00	289.
1.01	11:20	115	.00	.00	.00	1.02	19:10	259	.04	.04	.00	217.
1.01	11:20	116	.00	.00	.00	1.02	19:20	260	.04	.04	.00	171.
1.01	11:20	117	.00	.00	.00	1.02	19:30	261	.04	.04	.00	139.
1.01	11:20	118	.00	.00	.00	1.02	19:40	262	.04	.04	.00	117.
1.01	11:20	119	.00	.00	.00	1.02	19:50	263	.04	.04	.00	101.
1.01	11:20	120	.00	.00	.00	1.02	20:00	264	.04	.04	.00	91.
1.01	11:20	121	.00	.00	.00	1.02	20:10	265	.04	.04	.00	83.
1.01	11:20	122	.00	.00	.00	1.02	20:20	266	.04	.04	.00	78.
1.01	11:20	123	.00	.00	.00	1.02	20:30	267	.04	.04	.00	75.
1.01	11:20	124	.00	.00	.00	1.02	20:40	268	.04	.04	.00	73.
1.01	11:20	125	.00	.00	.00	1.02	20:50	269	.04	.04	.00	71.
1.01	11:20	126	.00	.00	.00	1.02	21:00	270	.04	.04	.00	70.
1.01	11:20	127	.00	.00	.00	1.02	21:10	271	.04	.04	.00	69.

TIME	1.01	20.30	125	.00	.00	.00	4.	1.02	20.30	267	.04	.04	.00	.00	.00	.00
1.01 20.40	124	.00	.00	.00	.00	.00	4.	1.02 20.40	269	.04	.04	.00	.00	.00	.00	.00
1.01 20.50	125	.00	.00	.00	.00	.00	4.	1.02 20.50	269	.04	.04	.00	.00	.00	.00	.00
1.01 21.00	126	.00	.00	.00	.00	.00	4.	1.02 21.00	270	.04	.04	.00	.00	.00	.00	.00
1.01 21.10	127	.00	.00	.00	.00	.00	4.	1.02 21.10	271	.04	.04	.00	.00	.00	.00	.00
1.01 21.20	128	.00	.00	.00	.00	.00	4.	1.02 21.20	272	.04	.04	.00	.00	.00	.00	.00
1.01 21.30	129	.00	.00	.00	.00	.00	4.	1.02 21.30	273	.04	.04	.00	.00	.00	.00	.00
1.01 21.40	130	.00	.00	.00	.00	.00	4.	1.02 21.40	274	.04	.04	.00	.00	.00	.00	.00
1.01 21.50	131	.00	.00	.00	.00	.00	4.	1.02 21.50	275	.04	.04	.00	.00	.00	.00	.00
1.01 22.00	132	.00	.00	.00	.00	.00	4.	1.02 22.00	276	.04	.04	.00	.00	.00	.00	.00
1.01 22.10	133	.00	.00	.00	.00	.00	4.	1.02 22.10	277	.04	.04	.00	.00	.00	.00	.00
1.01 22.20	134	.00	.00	.00	.00	.00	4.	1.02 22.20	278	.04	.04	.00	.00	.00	.00	.00
1.01 22.30	135	.00	.00	.00	.00	.00	4.	1.02 22.30	279	.04	.04	.00	.00	.00	.00	.00
1.01 22.40	136	.00	.00	.00	.00	.00	4.	1.02 22.40	280	.04	.04	.00	.00	.00	.00	.00
1.01 22.50	137	.00	.00	.00	.00	.00	4.	1.02 22.50	281	.04	.04	.00	.00	.00	.00	.00
1.01 23.00	138	.00	.00	.00	.00	.00	4.	1.02 23.00	282	.04	.04	.00	.00	.00	.00	.00
1.01 23.10	139	.00	.00	.00	.00	.00	4.	1.02 23.10	283	.04	.04	.00	.00	.00	.00	.00
1.01 23.20	140	.00	.00	.00	.00	.00	4.	1.02 23.20	284	.04	.04	.00	.00	.00	.00	.00
1.01 23.30	141	.00	.00	.00	.00	.00	4.	1.02 23.30	285	.04	.04	.00	.00	.00	.00	.00
1.01 23.40	142	.00	.00	.00	.00	.00	4.	1.02 23.40	286	.04	.04	.00	.00	.00	.00	.00
1.01 23.50	143	.00	.00	.00	.00	.00	4.	1.02 23.50	287	.04	.04	.00	.00	.00	.00	.00
1.02 .00	144	.00	.00	.00	.00	.00	4.	1.03 .00	288	.04	.04	.00	.00	.00	.00	.00

SUM 34.58 31.75 2.83 52522.

PEAK	6-HOUR	24-HOUR	72-HOUR	TOTAL VOLUME
2536.	1097.	355.	182.	52483.
72.	31.	10.	5.	1480.
	23.74	30.68	31.54	31.54
	603.03	779.31	801.07	601.07
	544.	703.	723.	723.
	671.	967.	892.	892.

HYDROGRAPH-AT STA 3 FOR PLAN 1, RTIO-1

PEAK	6-HOUR	24-HOUR	72-HOUR	TOTAL VOLUME
254.	110.	35.	18.	5248.
7.	3.	1.	1.	149.
	2.37	3.07	3.15	3.15
	60.30	77.93	80.11	80.11
	54.	70.	72.	72.
	67.	87.	89.	89.

HYDROGRAPH-AT STA 3 FOR PLAN 1, RTIO 2

PEAK	6-HOUR	24-HOUR	72-HOUR	TOTAL VOLUME
304.	132.	43.	22.	6298.
9.	4.	1.	1.	176.
	2.85	3.68	3.78	3.78
	72.36	93.52	96.13	96.13
	65.	86.	87.	87.
	81.	104.	107.	107.

HYDROGRAPH-AT STA 3 FOR PLAN 1, RTIO-3

SUB-AREA RUMOFF COMPUTATION
 LIONS LAKE DAM (68 MP. PROBABLE MAXIMUM RUNOFF)

IJSTAD ICOMP IECOM ITRPF JPLT JPRT INAME IJSTAGE IAUTO
 6 0 0 0 0 3 1 0 0
 IHYDC IUNB IAREA SNAP TRSDA TRSPC RATIO ISNOA ISAPE LOCAL
 1 2 .67 .00 .67 1.00 .000 0 0 0
 PRECIP DATA
 SPE PMS R6 R12 R24 R48 R72 R96
 .00 24.70 101.00 120.65 130.00 140.00 .00 .00

LOSS DATA
 LROPT SIKR DLKX RIOL EMAN SIKS RTIOK STRTL CNSTL ALSX RTIMP
 0 .00 .00 1.00 .00 .00 1.00 -1.00 -82.00 .00 .00
 CURVE NO = -82.00 WETNESS = -1.00 EFFECT CN = 82.00

UNIT HYDROGRAPH DATA
 TC = .00 LAW = .61
 STRG = .00 GNCSM = .00 RTIOR = 1.00

UNIT HYDROGRAPH 20 END OF PERIOD ORIGINATES, TC = .00 HOURS, LAG = .61 VOL = 1.00
 63. 204. 392. 443. 432. 343. 222. 148. 102. 68.
 47. 31. 21. 14. 10. 7. 5. 3. 2. 1.

MO-CA	HR-MN	PERIOD	RAIN	EXCS	LOSS	COMP %	END-OF-PERIOD FLOW	NO-DA	HR-MN	PERIOD	RAIN	EXCS	LOSS	COPP %
1-01	10	1	.00	.00	.00	0	1.02	10	145	.03	.02	.01	7.	
1-01	20	2	.00	.00	.00	0	1.02	20	146	.03	.02	.01	11.	
1-01	30	3	.00	.00	.00	0	1.02	30	147	.03	.02	.01	18.	
1-01	40	4	.00	.00	.00	0	1.02	40	148	.03	.02	.01	26.	
1-01	50	5	.00	.00	.00	0	1.02	50	149	.03	.02	.01	34.	
1-01	1-00	6	.00	.00	.00	0	1.02	1-00	150	.03	.02	.01	40.	
1-01	1-10	7	.00	.00	.00	0	1.02	1-10	151	.03	.02	.01	44.	
1-01	1-20	8	.00	.00	.00	0	1.02	1-20	152	.03	.02	.01	47.	
1-01	1-30	9	.00	.00	.00	0	1.02	1-30	153	.03	.02	.01	49.	
1-01	1-40	10	.00	.00	.00	0	1.02	1-40	154	.03	.02	.01	50.	
1-01	1-50	11	.00	.00	.00	0	1.02	1-50	155	.03	.02	.01	51.	
1-01	2-00	12	.00	.00	.00	0	1.02	2-00	156	.03	.02	.01	52.	
1-01	2-10	13	.00	.00	.00	0	1.02	2-10	157	.03	.02	.01	53.	
1-01	2-20	14	.00	.00	.00	0	1.02	2-20	158	.03	.02	.01	53.	
1-01	2-30	15	.00	.00	.00	0	1.02	2-30	159	.03	.02	.01	54.	
1-01	2-40	16	.00	.00	.00	0	1.02	2-40	160	.03	.02	.01	54.	

1.01 2:00 12 0.00 0.00 0.00 1.02 2:00 156 .03 .02 .01 52.
 1.01 2:10 13 0.00 0.00 0.00 1.02 2:10 157 .03 .02 .01 53.
 1.01 2:20 14 0.00 0.00 0.00 1.02 2:20 158 .03 .02 .01 53.
 1.01 2:30 15 0.00 0.00 0.00 1.02 2:30 159 .03 .02 .01 54.
 1.01 2:40 16 0.00 0.00 0.00 1.02 2:40 160 .03 .02 .01 54.

PROJECT 9166. DATE 27 AUG 80 PAGE 96
 FLOOD-HYDROGRAPH PACKAGE --HEC-1 PROGRAM H21/02-0U TIME 18:16:26 CASE PPF

B L A C K S V E A T C M
 FLOOD-HYDROGRAPH PACKAGE --HEC-1

1.01	2:50	17	0.00	0.00	0.00	1.02	2:50	161	.03	.02	.01	54.
1.01	3:00	18	0.00	0.00	0.00	1.02	3:00	162	.03	.02	.01	54.
1.01	3:10	19	0.00	0.00	0.00	1.02	3:10	163	.03	.02	.01	55.
1.01	3:20	20	0.00	0.00	0.00	1.02	3:20	164	.03	.02	.01	55.
1.01	3:30	21	0.00	0.00	0.00	1.02	3:30	165	.03	.02	.01	55.
1.01	3:40	22	0.00	0.00	0.00	1.02	3:40	166	.03	.02	.01	55.
1.01	3:50	23	0.00	0.00	0.00	1.02	3:50	167	.03	.02	.01	55.
1.01	4:00	24	0.00	0.00	0.00	1.02	4:00	168	.03	.02	.01	56.
1.01	4:10	25	0.00	0.00	0.00	1.02	4:10	169	.03	.02	.01	56.
1.01	4:20	26	0.00	0.00	0.00	1.02	4:20	170	.03	.02	.01	56.
1.01	4:30	27	0.00	0.00	0.00	1.02	4:30	171	.03	.02	.01	56.
1.01	4:40	28	0.00	0.00	0.00	1.02	4:40	172	.03	.02	.01	56.
1.01	4:50	29	0.00	0.00	0.00	1.02	4:50	173	.03	.02	.01	56.
1.01	5:00	30	0.00	0.00	0.00	1.02	5:00	174	.03	.02	.01	57.
1.01	5:10	31	0.00	0.00	0.00	1.02	5:10	175	.03	.02	.01	57.
1.01	5:20	32	0.00	0.00	0.00	1.02	5:20	176	.03	.02	.01	57.
1.01	5:30	33	0.00	0.00	0.00	1.02	5:30	177	.03	.02	.01	57.
1.01	5:40	34	0.00	0.00	0.00	1.02	5:40	178	.03	.02	.00	57.
1.01	5:50	35	0.00	0.00	0.00	1.02	5:50	179	.03	.02	.00	57.
1.01	6:00	36	0.00	0.00	0.00	1.02	6:00	180	.03	.02	.00	58.
1.01	6:10	37	0.01	0.00	0.01	1.02	6:10	181	.13	.11	.02	65.
1.01	6:20	38	0.01	0.00	0.01	1.02	6:20	182	.13	.11	.02	81.
1.01	6:30	39	0.01	0.00	0.01	1.02	6:30	183	.13	.11	.02	114.
1.01	6:40	40	0.01	0.00	0.01	1.02	6:40	184	.13	.11	.02	155.
1.01	6:50	41	0.01	0.00	0.01	1.02	6:50	185	.13	.11	.02	153.
1.01	7:00	42	0.01	0.00	0.01	1.02	7:00	186	.13	.11	.02	223.
1.01	7:10	43	0.01	0.00	0.01	1.02	7:10	187	.13	.11	.02	244.
1.01	7:20	44	0.01	0.00	0.01	1.02	7:20	188	.13	.11	.02	259.
1.01	7:30	45	0.01	0.00	0.01	1.02	7:30	189	.13	.11	.02	269.
1.01	7:40	46	0.01	0.00	0.01	1.02	7:40	190	.13	.12	.02	272.
1.01	7:50	47	0.01	0.00	0.01	1.02	7:50	191	.13	.12	.01	283.
1.01	8:00	48	0.01	0.00	0.01	1.02	8:00	192	.13	.12	.01	287.
1.01	8:10	49	0.01	0.00	0.01	1.02	8:10	193	.13	.12	.01	291.
1.01	8:20	50	0.01	0.00	0.01	1.02	8:20	194	.13	.12	.01	294.
1.01	8:30	51	0.01	0.00	0.01	1.02	8:30	195	.13	.12	.01	296.
1.01	8:40	52	0.01	0.00	0.01	1.02	8:40	196	.13	.12	.01	298.
1.01	8:50	53	0.01	0.00	0.01	1.02	8:50	197	.13	.12	.01	300.
1.01	9:00	54	0.01	0.00	0.01	1.02	9:00	198	.13	.12	.01	302.
1.01	9:10	55	0.01	0.00	0.01	1.02	9:10	199	.13	.12	.01	303.
1.01	9:20	56	0.01	0.00	0.01	1.02	9:20	200	.13	.12	.01	304.
1.01	9:30	57	0.01	0.00	0.01	1.02	9:30	201	.13	.12	.01	305.
1.01	9:40	58	0.01	0.00	0.01	1.02	9:40	202	.13	.12	.01	307.
1.01	9:50	59	0.01	0.00	0.01	1.02	9:50	203	.13	.12	.01	308.
1.01	10:00	60	0.01	0.00	0.01	1.02	10:00	204	.13	.12	.01	309.
1.01	10:10	61	0.01	0.00	0.01	1.02	10:10	205	.13	.12	.01	310.
1.01	10:20	62	0.01	0.00	0.01	1.02	10:20	206	.13	.12	.01	311.
1.01	10:30	63	0.01	0.00	0.01	1.02	10:30	207	.13	.12	.01	312.
1.01	10:40	64	0.01	0.00	0.01	1.02	10:40	208	.13	.12	.01	313.
1.01	10:50	65	0.01	0.00	0.01	1.02	10:50	209	.13	.12	.01	313.
1.01	11:00	66	0.01	0.00	0.01	1.02	11:00	210	.13	.12	.01	313.
1.01	11:10	67	0.01	0.00	0.01	1.02	11:10	211	.13	.12	.01	316.
1.01	11:20	68	0.01	0.00	0.01	1.02	11:20	212	.13	.12	.01	315.
1.01	11:30	69	0.01	0.00	0.01	1.02	11:30	213	.13	.12	.01	315.
1.01	11:40	70	0.01	0.00	0.01	1.02	11:40	214	.13	.12	.01	316.
1.01	11:50	71	0.01	0.00	0.01	1.02	11:50	215	.13	.12	.01	317.
1.01	12:00	72	0.01	0.00	0.01	1.02	12:00	216	.13	.12	.01	317.

1.01 11-20 68 .01 .00 .01 .02 11-20 217 .42 .40 .02 .01 315.
1.01 11-30 69 .01 .00 .01 .02 11-30 218 .42 .40 .02 .01 315.
1.01 11-40 70 .01 .00 .01 .02 11-40 219 .42 .40 .02 .01 316.
1.01 11-50 71 .01 .00 .01 .02 11-50 220 .42 .40 .02 .01 317.
1.01 12-00 72 .01 .00 .01 .02 12-00 221 .42 .40 .02 .01 317.

B L A C K S V E A T C H
FLOOD HYDROGRAPH PACKAGE - HEC-1
PROJECT 9160- DATE 27 AUG 80 PAGE 97
PROGRAM W21702-0U TIME 18:16:26 CASE PWF

1.01 12-10 73 .03 .00 .05 .02 12-10 217 .42 .40 .02 .01 335.
1.01 12-20 74 .03 .00 .05 .02 12-20 218 .42 .40 .02 .01 391.
1.01 12-30 75 .03 .00 .05 .02 12-30 219 .42 .40 .02 .01 498.
1.01 12-40 76 .03 .00 .05 .02 12-40 220 .42 .40 .02 .01 626.
1.01 12-50 77 .03 .00 .05 .02 12-50 221 .42 .40 .02 .01 745.
1.01 13-00 78 .03 .00 .05 .02 13-00 222 .42 .40 .02 .01 841.
1.01 13-10 79 .03 .00 .05 .02 13-10 243 .50 .48 .02 .01 908.
1.01 13-20 80 .04 .01 .03 .01 13-20 224 .50 .49 .01 .01 968.
1.01 13-30 81 .04 .01 .03 .01 13-30 225 .50 .49 .01 .01 1030.
1.01 13-40 82 .04 .01 .03 .01 13-40 226 .50 .49 .01 .01 1088.
1.01 13-50 83 .04 .01 .03 .01 13-50 227 .50 .49 .01 .01 1138.
1.01 14-00 84 .04 .01 .03 .01 14-00 228 .50 .49 .01 .01 1177.
1.01 14-10 85 .05 .01 .03 .01 14-10 229 .62 .61 .01 .01 1211.
1.01 14-20 86 .05 .02 .03 .01 14-20 230 .62 .61 .01 .01 1234.
1.01 14-30 87 .05 .02 .03 .01 14-30 231 .62 .61 .01 .01 1315.
1.01 14-40 88 .05 .02 .03 .01 14-40 232 .62 .61 .01 .01 1381.
1.01 14-50 89 .05 .02 .03 .01 14-50 233 .62 .61 .01 .01 1441.
1.01 15-00 90 .05 .02 .03 .01 15-00 234 .62 .62 .01 .01 1468.
1.01 15-10 91 .05 .02 .03 .01 15-10 235 .62 .62 .01 .01 1518.
1.01 15-20 92 .07 .03 .04 .04 15-20 236 .94 .94 .01 .01 1550.
1.01 15-30 93 .13 .06 .07 .06 15-30 237 1.71 1.69 .02 .02 1608.
1.01 15-40 94 .33 .18 .14 .14 15-40 238 4.27 4.23 .03 .03 2115.
1.01 15-50 95 .69 .06 .06 .06 15-50 239 1.23 1.22 .01 .01 2855.
1.01 16-00 96 .05 .04 .02 .02 16-00 240 .76 .75 .00 .00 3744.
1.01 16-10 97 .04 .03 .02 .02 16-10 241 .58 .58 .00 .00 4020.
1.01 16-20 98 .04 .03 .02 .02 16-20 242 .58 .58 .00 .00 4500.
1.01 16-30 99 .04 .03 .02 .02 16-30 243 .58 .55 .00 .00 3406.
1.01 16-40 100 .04 .03 .02 .02 16-40 244 .58 .58 .00 .00 4802.
1.01 16-50 101 .04 .03 .02 .02 16-50 245 .58 .58 .00 .00 2375.
1.01 17-00 102 .04 .03 .02 .02 17-00 246 .58 .58 .00 .00 2094.
1.01 17-10 103 .04 .02 .01 .01 17-10 247 .46 .46 .00 .00 1889.
1.01 17-20 104 .04 .02 .01 .01 17-20 248 .46 .46 .00 .00 1735.
1.01 17-30 105 .04 .02 .01 .01 17-30 249 .46 .46 .00 .00 1597.
1.01 17-40 106 .04 .02 .01 .01 17-40 250 .46 .46 .00 .00 1479.
1.01 17-50 107 .04 .02 .01 .01 17-50 251 .46 .46 .00 .00 1385.
1.01 18-00 108 .03 .03 .01 .01 18-00 252 .46 .46 .00 .00 1315.
1.01 18-10 109 .03 .00 .00 .00 18-10 253 .04 .04 .00 .00 1243.
1.01 18-20 110 .03 .00 .00 .00 18-20 254 .04 .04 .00 .00 1179.
1.01 18-30 111 .00 .00 .00 .00 18-30 255 .04 .04 .00 .00 945.
1.01 18-40 112 .00 .00 .00 .00 18-40 256 .04 .04 .00 .00 737.
1.01 18-50 113 .00 .00 .00 .00 18-50 257 .04 .04 .00 .00 547.
1.01 19-00 114 .00 .00 .00 .00 19-00 258 .04 .04 .00 .00 397.
1.01 19-10 115 .00 .00 .00 .00 19-10 259 .04 .04 .00 .00 301.
1.01 19-20 116 .00 .00 .00 .00 19-20 260 .04 .04 .00 .00 238.
1.01 19-30 117 .00 .00 .00 .00 19-30 261 .04 .04 .00 .00 184.
1.01 19-40 118 .00 .00 .00 .00 19-40 262 .04 .04 .00 .00 163.
1.01 19-50 119 .00 .00 .00 .00 19-50 263 .04 .04 .00 .00 145.
1.01 20-00 120 .00 .00 .00 .00 20-00 264 .04 .04 .00 .00 132.
1.01 20-10 121 .00 .00 .00 .00 20-10 265 .04 .04 .00 .00 121.
1.01 20-20 122 .04 .03 .00 .00 20-20 266 .04 .04 .00 .00 117.
1.01 20-30 123 .00 .00 .00 .00 20-30 267 .04 .04 .00 .00 113.
1.01 20-40 124 .00 .00 .00 .00 20-40 268 .04 .04 .00 .00 110.
1.01 20-50 125 .00 .00 .00 .00 20-50 269 .04 .04 .00 .00 108.
1.01 21-00 126 .00 .00 .00 .00 21-00 270 .04 .04 .00 .00 107.
1.01 21-10 127 .00 .00 .00 .00 21-10 271 .04 .04 .00 .00 106.
1.01 21-20 128 .00 .00 .00 .00 21-20 272 .04 .04 .00 .00 106.

TIME	1-01	20-40	124	-00	-00	-00	1-02	21-30	273	-04	-04	-00	106
1-01	20-40	124	-00	-00	-00	1-02	21-30	273	-04	-04	-00	106	
1-01	20-50	125	-00	-00	-00	1-02	21-40	274	-04	-04	-00	106	
1-01	21-00	126	-00	-00	-00	1-02	21-50	275	-04	-04	-00	106	
1-01	21-10	127	-00	-00	-00	1-02	22-00	276	-04	-04	-00	106	
1-01	21-20	128	-00	-00	-00	1-02	22-10	277	-04	-04	-00	106	
1-01	22-00	134	-00	-00	-00	1-02	22-20	278	-04	-04	-00	106	
1-01	22-30	135	-00	-00	-00	1-02	22-30	279	-04	-04	-00	106	
1-01	22-40	136	-00	-00	-00	1-02	22-40	280	-04	-04	-00	106	
1-01	22-50	137	-00	-00	-00	1-02	22-50	281	-04	-04	-00	106	
1-01	23-00	138	-00	-00	-00	1-02	23-00	282	-04	-04	-00	106	
1-01	23-10	139	-00	-00	-00	1-02	23-10	283	-04	-04	-00	106	
1-01	23-20	140	-00	-00	-00	1-02	23-20	284	-04	-04	-00	106	
1-01	23-30	141	-00	-00	-00	1-02	23-30	285	-04	-04	-00	106	
1-01	23-40	142	-00	-00	-00	1-02	23-40	286	-04	-04	-00	106	
1-01	23-50	143	-00	-00	-00	1-02	23-50	287	-04	-04	-00	106	
1-02	-00	144	-00	-00	-00	1-03	-00	288	-04	-04	-00	106	

SUM 34.58 32.08 2.50 82219.
 (278.3) (835.3) (66.3) (2328.18)

PEAK	6-HOUR	24-HOUR	72-HOUR	TOTAL VOLUME
4080.	1709.	553.	285.	82164.
116.	48.	16.	8.	2377.
INCHES	23.87	30.91	31.88	31.88
MM	606.37	785.20	809.71	809.71
AC-FT	649.	1997.	1132.	1132.
THOUS CU M	1045.	1354.	1396.	1396.

HYDROGRAPH AT STA 6 FOR PLAN 1, RT10 1

PEAK	6-HOUR	24-HOUR	72-HOUR	TOTAL VOLUME
408.	171.	55.	29.	8216.
12.	5.	2.	1.	233.
INCHES	2.39	3.09	3.19	3.19
MM	60.64	78.52	80.97	80.97
AC-FT	85.	110.	113.	113.
THOUS CU M	105.	135.	140.	140.

HYDROGRAPH AT STA 6 FOR PLAN 1, RT10 2

PEAK	6-HOUR	24-HOUR	72-HOUR	TOTAL VOLUME
490.	205.	66.	34.	9860.
14.	6.	2.	1.	279.
INCHES	2.86	3.71	3.83	3.83
MM	72.76	96.24	97.17	97.17
AC-FT	102.	132.	136.	136.
THOUS CU M	125.	162.	168.	168.

HYDROGRAPH AT STA 6 FOR PLAN 1, RT10 3

SUB-AREA RUNOFF COMPUTATION

LIONS LAKE DAK (48 HR. PROBABLE PAKJFUM RUNOFF)

ISTAQ 6 ICOMP 0 TECM 0 ITAPE 0 JPLY 0 JPQT 3 IMARE 1 IASTAGE 0 IAUTO 0
 INYDG 1 IUNG 2 IAREA 67 ITRSDA 20 ITRSPC 67 ITRATIO 0 ITRSNOW 0 ITRSAPE 0 ITRLOCAL 0
 HYDROGRAPH DATA
 SPCF .00 PMS 24.70 R6 107.00 R12 120.00 R48 140.00 R72 146.00 R96 148.00
 LOSS DATA
 LROPT 0 STRR 0.00 DLTR 0.00 Q10L 1.00 E10L 1.00 STRKS 1.00 R10K 1.00 STREL 1.00 CUSIL 1.00 ALSKH 1.00 RTIMP 1.00
 CURVE NO = 82.00 WETNESS = -1.00 EFFECT CN = 82.00

UNIT HYDROGRAPH DATA

RECESSION DATA

UNIT HYDROGRAPH 20 END OF PERIOD ORDINATES, TCR 432. 343. 222. 148. 102. 68.
 47. 31. 21. 14. 7. 5. 3. 2. 1.

MO. IN	HR.-RN	PERIOD	RAIN	EXCS	LOSS	END-OF-PERIOD FLOW	COMP %	10.0A	HR.-RN	PERIOD	RAIN	EXCS	LOSS	COPP %
1.01	1.00	1	.06	.00	.00	0.	0.	1.02	1.0	145	.03	.02	.01	7.
1.01	2.00	2	.00	.00	.00	0.	0.	1.02	2.0	146	.05	.02	.01	11.
1.01	3.00	3	.00	.00	.00	0.	0.	1.02	3.0	147	.03	.02	.01	18.
1.01	4.00	4	.00	.00	.00	0.	0.	1.02	4.0	148	.03	.02	.01	26.
1.01	5.00	5	.00	.00	.00	0.	0.	1.02	5.0	149	.03	.02	.01	34.
1.01	6.00	6	.00	.00	.00	0.	0.	1.02	6.0	150	.03	.02	.01	40.
1.01	7.00	7	.00	.00	.00	0.	0.	1.02	7.0	151	.03	.02	.01	46.
1.01	8.00	8	.00	.00	.00	0.	0.	1.02	8.0	152	.03	.02	.01	47.
1.01	9.00	9	.00	.00	.00	0.	0.	1.02	9.0	153	.03	.02	.01	49.
1.01	10.00	10	.00	.00	.00	0.	0.	1.02	10.0	154	.03	.02	.01	50.
1.01	11.00	11	.00	.00	.00	0.	0.	1.02	11.0	155	.03	.02	.01	51.
1.01	12.00	12	.00	.00	.00	0.	0.	1.02	12.0	156	.03	.02	.01	52.
1.01	13.00	13	.00	.00	.00	0.	0.	1.02	13.0	157	.03	.02	.01	53.
1.01	14.00	14	.00	.00	.00	0.	0.	1.02	14.0	158	.03	.02	.01	53.
1.01	15.00	15	.00	.00	.00	0.	0.	1.02	15.0	159	.03	.02	.01	54.
1.01	16.00	16	.00	.00	.00	0.	0.	1.02	16.0	160	.03	.02	.01	54.

1-01	11:20	68	-01	-00	-01	0.	0.	1-02	11:20	212	-13	-12	-01	315.
1-01	11:30	69	-01	-00	-01	0.	0.	1-02	11:30	213	-13	-12	-01	315.
1-01	11:40	70	-01	-00	-01	0.	0.	1-02	11:40	214	-13	-12	-01	317.
1-01	11:50	71	-01	-00	-01	0.	0.	1-02	11:50	215	-13	-12	-01	317.
1-01	12:00	72	-01	-00	-01	0.	0.	1-02	12:00	216	-13	-12	-01	317.
1-01	12:10	73	-03	-00	-03	0.	0.	1-02	12:10	217	-42	-40	-02	335.
1-01	12:20	74	-03	-00	-03	0.	0.	1-02	12:20	218	-42	-40	-02	391.
1-01	12:30	75	-03	-00	-03	1.	1.	1-02	12:30	219	-42	-40	-02	498.
1-01	12:40	76	-03	-00	-03	1.	1.	1-02	12:40	220	-42	-40	-02	624.
1-01	12:50	77	-03	-00	-03	2.	2.	1-02	12:50	221	-42	-40	-01	745.
1-01	13:00	78	-03	-00	-03	4.	4.	1-02	13:00	222	-42	-40	-01	841.
1-01	13:10	79	-04	-01	-03	6.	6.	1-02	13:10	223	-50	-49	-01	908.
1-01	13:20	80	-04	-01	-03	8.	8.	1-02	13:20	224	-50	-49	-01	968.
1-01	13:30	81	-04	-01	-03	10.	10.	1-02	13:30	225	-50	-49	-01	1030.
1-01	13:40	82	-04	-01	-03	13.	13.	1-02	13:40	226	-50	-49	-01	1088.
1-01	13:50	83	-04	-01	-03	15.	15.	1-02	13:50	227	-50	-49	-01	1138.
1-01	14:00	84	-04	-01	-03	18.	18.	1-02	14:00	228	-50	-49	-01	1177.
1-01	14:10	85	-05	-01	-03	20.	20.	1-02	14:10	229	-61	-61	-01	1213.
1-01	14:20	86	-05	-02	-03	23.	23.	1-02	14:20	230	-62	-61	-01	1254.
1-01	14:30	87	-05	-02	-03	27.	27.	1-02	14:30	231	-62	-61	-01	1315.
1-01	14:40	88	-05	-02	-03	31.	31.	1-02	14:40	232	-62	-61	-01	1381.
1-01	14:50	89	-05	-02	-03	35.	35.	1-02	14:50	233	-62	-61	-01	1441.
1-01	15:00	90	-05	-02	-03	39.	39.	1-02	15:00	234	-62	-61	-01	1488.
1-01	15:10	91	-04	-02	-02	41.	41.	1-02	15:10	235	-57	-56	-01	1516.
1-01	15:20	92	-07	-03	-04	45.	45.	1-02	15:20	236	-95	-94	-01	1550.
1-01	15:30	93	-11	-06	-07	52.	52.	1-02	15:30	237	-171	-169	-02	1668.
1-01	15:40	94	-33	-18	-14	73.	73.	1-02	15:40	238	-427	-423	-03	2113.
1-01	15:50	95	-09	-06	-04	109.	109.	1-02	15:50	239	-123	-122	-01	2893.
1-01	16:00	96	-06	-04	-02	149.	149.	1-02	16:00	240	-76	-75	-03	3744.
1-01	16:10	97	-04	-03	-02	169.	169.	1-02	16:10	241	-58	-58	-00	4080.
1-01	16:20	98	-04	-03	-02	166.	166.	1-02	16:20	242	-58	-58	-00	3960.
1-01	16:30	99	-04	-03	-02	169.	169.	1-02	16:30	243	-58	-58	-00	3400.
1-01	16:40	100	-04	-03	-02	126.	126.	1-02	16:40	244	-58	-58	-00	2802.
1-01	16:50	101	-04	-03	-01	109.	109.	1-02	16:50	245	-58	-58	-00	2373.
1-01	17:00	102	-04	-03	-01	99.	99.	1-02	17:00	246	-58	-58	-00	2094.
1-01	17:10	103	-04	-02	-01	91.	91.	1-02	17:10	247	-46	-46	-00	1889.
1-01	17:20	104	-04	-02	-01	86.	86.	1-02	17:20	248	-46	-46	-00	1733.
1-01	17:30	105	-04	-02	-01	89.	89.	1-02	17:30	249	-46	-46	-00	1597.
1-01	17:40	106	-04	-02	-01	76.	76.	1-02	17:40	250	-46	-46	-00	1479.
1-01	17:50	107	-04	-02	-01	72.	72.	1-02	17:50	251	-46	-46	-00	1385.
1-01	18:00	108	-04	-03	-01	69.	69.	1-02	18:00	252	-46	-46	-00	1315.
1-01	18:10	109	-04	-00	-00	66.	66.	1-02	18:10	253	-04	-04	-00	1243.
1-01	18:20	110	-00	-00	-00	60.	60.	1-02	18:20	254	-04	-04	-00	1129.
1-01	18:30	111	-00	-00	-00	51.	51.	1-02	18:30	255	-04	-04	-00	943.
1-01	18:40	112	-00	-00	-00	40.	40.	1-02	18:40	256	-04	-04	-00	737.
1-01	18:50	113	-00	-00	-00	30.	30.	1-02	18:50	257	-04	-04	-00	542.
1-01	19:00	114	-00	-00	-00	22.	22.	1-02	19:00	258	-04	-04	-00	397.
1-01	19:10	115	-00	-00	-00	16.	16.	1-02	19:10	259	-04	-04	-00	301.
1-01	19:20	116	-00	-00	-00	13.	13.	1-02	19:20	260	-04	-04	-00	230.
1-01	19:30	117	-00	-00	-00	11.	11.	1-02	19:30	261	-04	-04	-00	194.
1-01	19:40	118	-00	-00	-00	9.	9.	1-02	19:40	262	-04	-04	-00	165.
1-01	19:50	119	-00	-00	-00	8.	8.	1-02	19:50	263	-04	-04	-00	143.
1-01	20:00	120	-00	-00	-00	7.	7.	1-02	20:00	264	-04	-04	-00	132.
1-01	20:10	121	-00	-00	-00	7.	7.	1-02	20:10	265	-04	-04	-00	123.
1-01	20:20	122	-00	-00	-00	6.	6.	1-02	20:20	266	-04	-04	-00	117.
1-01	20:30	123	-00	-00	-00	6.	6.	1-02	20:30	267	-04	-04	-00	113.
1-01	20:40	124	-00	-00	-00	6.	6.	1-02	20:40	268	-04	-04	-00	110.
1-01	20:50	125	-00	-00	-00	6.	6.	1-02	20:50	269	-04	-04	-00	108.
1-01	21:00	126	-04	-00	-00	6.	6.	1-02	21:00	270	-04	-04	-00	107.
1-01	21:10	127	-06	-00	-00	6.	6.	1-02	21:10	271	-04	-04	-00	104.
1-01	21:20	128	-00	-00	-00	6.	6.	1-02	21:20	272	-04	-04	-00	106.

1.01 20.40 124 .00 .00 1.02 20.40 268 .04 .00 110.
 1.01 20.50 125 .00 .00 1.02 20.50 269 .04 .00 108.
 1.01 21.00 126 .00 .00 1.02 21.00 270 .04 .00 107.
 1.01 21.10 127 .00 .00 1.02 21.10 271 .04 .00 106.
 1.01 21.20 128 .00 .00 1.02 21.20 272 .04 .00 106.

BLOCK & VEATCH PROJECT 9166. DATE 27 AUG 88 PAGE 98
 FLOOD-HYDROGRAPH PACKAGE - MEC-1 PROGRAM H21/02-00 TIME 18:16:26 CASE PRF

TIME	1.01	21.30	129	.00	.00	1.02	21.30	273	.04	.00	106.
1.01	21.40	130	.00	.00	.00	1.02	21.40	274	.04	.00	106.
1.01	21.50	131	.00	.00	.00	1.02	21.50	275	.04	.00	106.
1.01	22.00	132	.00	.00	.00	1.02	22.00	276	.04	.00	106.
1.01	22.10	133	.00	.00	.00	1.02	22.10	277	.04	.00	106.
1.01	22.20	134	.00	.00	.00	1.02	22.20	278	.04	.00	106.
1.01	22.30	135	.00	.00	.00	1.02	22.30	279	.04	.00	106.
1.01	22.40	136	.00	.00	.00	1.02	22.40	280	.04	.00	106.
1.01	22.50	137	.00	.00	.00	1.02	22.50	281	.04	.00	106.
1.01	23.00	138	.00	.00	.00	1.02	23.00	282	.04	.00	106.
1.01	23.10	139	.00	.00	.00	1.02	23.10	283	.04	.00	106.
1.01	23.20	140	.00	.00	.00	1.02	23.20	284	.04	.00	106.
1.01	23.30	141	.00	.00	.00	1.02	23.30	285	.04	.00	106.
1.01	23.40	142	.00	.00	.00	1.02	23.40	286	.04	.00	106.
1.01	23.50	143	.00	.00	.00	1.02	23.50	287	.04	.00	106.
1.02	.00	144	.00	.00	.00	1.03	.00	288	.04	.00	106.

SUM 34.50 32.00 2.50 82219.
 (878.91 815.)(64.)(2328.18)

	PEAK	6-HOUR	24-HOUR	72-HOUR	TOTAL VOLUME
CFS	4080.	1709.	553.	283.	82164.
CMS	116.	48.	16.	8.	2327.
INCHES	23.97	30.91	31.88	31.82	809.71
MM	606.37	755.20	809.71	809.71	809.71
AC-FT	845.	1097.	1132.	1132.	1132.
THOUS CU M	1045.	1354.	1396.	1396.	1396.

HYDROGRAPH AT STA 6 FOR PLAN 1, RTIO 1

	PEAK	6-HOUR	24-HOUR	72-HOUR	TOTAL VOLUME
CFS	408.	171.	55.	29.	8216.
CMS	12.	5.	2.	1.	233.
INCHES	2.39	3.09	3.19	3.19	3.19
MM	60.64	78.52	80.97	80.97	80.97
AC-FT	85.	110.	113.	113.	113.
THOUS CU M	105.	135.	140.	140.	140.

HYDROGRAPH AT STA 6 FOR PLAN 1, RTIO 2

	PEAK	6-HOUR	24-HOUR	72-HOUR	TOTAL VOLUME
CFS	490.	205.	66.	34.	9860.
CMS	14.	6.	2.	1.	279.
INCHES	2.86	3.71	3.53	3.53	3.83
MM	72.76	94.24	67.17	67.17	92.17
AC-FT	102.	132.	136.	136.	136.
THOUS CU M	125.	162.	168.	168.	168.

HYDROGRAPH AT STA 6 FOR PLAN 1, RTIO 3

530.
 622.
 1019.
 2941.
 6114.
 5583.
 1091.
 273.
 220.

537.
 617.
 411.
 2631.
 4902.
 5638.
 1296.
 294.
 221.

537.
 617.
 411.
 2631.
 4902.
 5638.
 1296.
 294.
 221.

6-HOUR PEAK
 7570.
 218.
 219.
 219.

24-HOUR
 1178.
 35.
 31.86
 809.19
 2117.
 2862.

72-HOUR
 505.
 17.
 32.70
 810.63
 2309.
 2959.

TOTAL VOLUME
 174341.
 4931.
 32.70
 630.62
 2169.
 2959.

ROUTING THROUGH LIONS LAKE

HYDROGRAPH ROUTING

STAGE	755.00	756.00	757.00	758.00	759.00	760.00	761.00	762.00	763.00	764.00
EL..	.00	44.00	85.50	107.70	123.70	140.50	156.70	173.00	189.50	199.80
SURFACE AREA	0.	16.	25.	44.	66.	96.	131.	171.	216.	268.
CAPACITY	0.	54.	155.	493.	1035.	1837.	2966.	4466.	6266.	8366.
ELEVATION	745.	755.	760.	770.	780.	790.	800.	810.	820.	830.

6-HOUR 24-HOUR 72-HOUR TOTAL VOLUME
 7570. 1178. 505. 174341.
 218. 35. 17. 4931.
 219. 31.86 32.70 32.70
 219. 809.19 810.63 630.62
 219. 2117. 2309. 2169.
 219. 2862. 2959. 2959.

PROJECT 9166. DATE 27 AUG 80 PAGE 100
 FLOOD HYDROGRAPH PACKAGE - HEC-1
 PROGRAM R21/02-00 - TIRE - 1810120 - CASE-PNF

LAST LENGTH 0. 29. 44. 117. 225. 336. 469. 536. 572. 594.
 AT OR BELOW 757.0 758.3 759.1 760.6 760.6 760.6 761.2 761.7 762.5 763.3
 ELEVATION STATION 0. PLAN 1. RATE 1

END-OF-PERIOD HYDROGRAPH ORDINATES

PEAK FLOW AND STORAGE (END OF PERIOD) SUMMARY FOR MULTIPLE PLAN-RATIO ECONOMIC COMPUTATIONS
 FLOWS IN CUBIC FEET PER SECOND (CUBIC METERS PER SECOND)
 AREA IN SQUARE MILES (SQUARE KILOMETERS)

OPERATION	STATION	AREA	PLAN	RATIOS APPLIED TO FLOWS						
				RATIO 1	RATIO 2	RATIO 3	RATIO 4	RATIO 5	RATIO 6	RATIO 7
				.10	.12	.13	.14	.15	.50	1.00
HYDROGRAPH AT	1	.28	1	176	214	252	250	267	291	1783
	(.73)	(5.053)	6.063)	6.563)	7.073)	7.573)	25.243)	50.463)
ROUTED TO	2	.28	1	255	262	285	264	267	659	1789
	(.73)	(7.233)	7.633)	7.503)	7.483)	7.573)	24.333)	50.673)
HYDROGRAPH AT	3	.43	1	254	304	330	355	383	1268	2536
	(1.11)	(7.163)	8.623)	9.333)	10.053)	10.773)	35.903)	71.803)
2 COMBINED	4	.71	1	422	507	549	591	633	2106	4325
	(1.64)	(11.953)	14.353)	15.553)	16.743)	17.933)	59.633)	122.463)
ROUTED TO	5	.71	1	255	314	350	386	426	2676	1831
	(1.84)	(7.223)	8.963)	9.713)	10.943)	12.113)	75.773)	108.463)
HYDROGRAPH AT	6	.57	1	468	476	530	571	612	2040	4080
	(1.72)	(11.553)	12.363)	13.023)	14.173)	15.333)	57.773)	115.533)
2 COMBINED	7	1.36	1	605	724	795	860	931	4119	7570
	(3.56)	(17.133)	20.663)	22.523)	24.343)	26.373)	116.633)	214.363)
ROUTED TO	8	1.55	1	342	472	545	622	702	4045	7401
	(3.55)	(9.623)	13.363)	15.433)	17.603)	19.873)	114.533)	209.573)

SUMMARY OF DAM SAFETY ANALYSIS

PLAN 1	ELEVATION STORAGE OUTFLOW	INITIAL VALUE	SPILLWAY CRIST	TOP OF DAM
		765.00	789.20	769.20
		2.	9.	9.
		0.	11.	11.

RATIO OF PHF	MAXIMUM RESERVOIR ELEVATION	MAXIMUM DEPTH OVER DAM	MAXIMUM STORAGE AC-FT	MAXIMUM OUTFLOW CFS	URATION OVER TOP HOURS	TIME OF PAK OUTFLOW HOURS	TIME OF FAILURE HOURS
.10	769.36	.16	9.	256.	.58	39.35	38.50
.12	769.35	.15	9.	264.	.60	38.87	38.00
.13	769.37	.17	9.	267.	.60	38.71	37.83
.14	769.35	.15	9.	266.	.60	38.37	37.50
.15	769.35	.16	9.	269.	.60	38.21	37.33
.20	769.38	.18	9.	289.	.62	40.33	32.33
1.00	790.33	1.11	12.	1789.	1.68	60.17	17.67

SUMMARY OF DAM SAFETY ANALYSIS

PLAN 1	ELEVATION STORAGE OUTFLOW	INITIAL VALUE	SPILLWAY CREST	TOP OF DAM
	75. 0.	774.00	774.00	777.60
			75. 0.	159. 924.

RATIO OF PHF	MAXIMUM RESERVOIR STORAGE	MAXIMUM DEPTH OVER DAP	MAXIMUM STORAGE AC-FT	MAXIMUM OUTFLOW CFS	DURATION OVER TOP HOURS	TIME OF MAX OUTFLOW HOURS	TIME OF FAILURE HOURS
.10	776.36	.00	120.	255.	.00	40.83	.00
.12	776.60	.00	125.	314.	.00	40.83	.00
.13	776.72	.00	128.	350.	.00	40.83	.00
.14	776.82	.00	130.	356.	.00	40.83	.00
.15	776.92	.00	132.	429.	.00	40.83	.00
.50	778.18	.58	164.	2374.	1.02	40.83	39.83
1.00	778.03	.43	160.	3031.	1.33	40.50	37.67

SUMMARY OF DAM SAFETY ANALYSIS

PLAN 1		ELEVATION	INITIAL VALUE	SPILLWAY CREST	TOP OF DAM		
		STORAGE	56.	755.00	760.20		
		OUTFLOW	0.	56.	100.		
					617.		
RATIO OF PHF	MAXIMUM RESERVOIR ELEV	MAXIMUM DEPTH OVER DAM	MAXIMUM STORAGE AC-FT	MAXIMUM OUTFLOW CFS	DURATION OVER TOP HOURS	TIME OF MAX OUTFLOW HOURS	TIME OF FAILURE HOURS
0.10	759.50	0.00	143.	342.	0.00	42.00	0.00
0.12	759.88	0.00	152.	472.	0.00	41.50	0.00
0.13	760.05	0.00	156.	545.	0.00	41.35	0.00
0.14	760.21	0.01	160.	622.	0.33	41.17	0.00
0.15	760.36	0.16	166.	702.	1.33	41.17	0.00
0.50	762.15	1.95	212.	4045.	6.17	40.50	0.00
1.00	763.07	2.87	239.	7401.	8.67	40.50	0.00