





Papers in this series have resulted from technical activities of The Hydrologic Engineering Center. Versions of some of these have been published in technical journals or in conference proceedings. The purpose of this series is to make the information available for use in the Center's training program and for distribution within the Corps of Engineers.

REFURI DULUARNIA I FUN FAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
. REPORT NUMBER 2. GOVY ACCESSION NO	S. RECIPIENT'S CATALOS NUMBER
Technical Paper No. 71 ADXA/09766	
TITLE (and Bubility)	S. TYPE OF REPORT & PERIOD COVERED
DETERMINATION OF LAND USE FROM SATELLITE	6. PERFORMING ORG. REPORT NUMBER
. AUTHOR(a)	8. CONTRACT OR GRANT NUMBERTA)
D. Date Make Dataset Council and Autor 5 1 to	
R. Pat, webb, Robert Lermak and Arien Feldman	1
PERFORMING ORGANIZATION NAME AND ADDRESS	10." PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
U.S. Army Corps of Engineers	1
ine hydrologic Engineering Center 609 Second Street, Davis - CA - 95616	
1. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE
	April 1980
	17
4. MONITORING AGENCY NAME & ADDRESS(II different from Controlling Office)	IL SECURITY CLASS. (of this report)
	164 DECLASSIFICATION DOWNGRADING
6. DISTRIBUTION STATEMENT (of this Report)	
Distuition of this work is to the t	
7. DISTRIBUTION STATEMENT (of the abetract entered in Block 20, if different i	inan Raport)
17. DISTRIBUTION STATEMENT (of the abetract entered in Block 20, if different i	inge Report)
17. DISTRIBUTION STATEMENT (of the shetrest entered in Block 29, if different i	irom Report)
17. DISTRIBUTION STATEMENT (of the abetract entered in Block 20, if different i	inen Reportj
7. DISTRIBUTION STATEMENT (of the shelfest entered in Block 20, if different i Pr 18. SUPPLEMENTARY NOTES Presented at The Environmental Personal Institute	nem Report)
Pr 17. DISTRIBUTION STATEMENT (of the obstract entered in Block 20, if different i Pr 18. SUPPLEMENTARY NOTES Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensi	of Michigan's
 DISTRIBUTION STATEMENT (of the observed on Block 20, if different in Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensing Environment, 23-30 April 1980, San Jose, Costa Rice 	of Hichigan's ng of the a
7. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different in Pr 10. SUPPLEMENTARY NOTES Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensin Environment, 23-30 April 1980, San Jose, Costa Rick	nam Report) of Hichigan's ng of the a
 DISTRIBUTION STATEMENT (of the obstract entered in Block 20, if different in Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensitienvironment, 23-30 April 1980, San Jose, Costa Rice KEY WORDS (Continue on reverse side if necessary and identify by Mack members) 	of Michigan's ng of the a
 DISTRIBUTION STATEMENT (of the observed entered in Block 20, if different in Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensing Environment, 23-30 April 1980, San Jose, Costa Rick Market Workes (Continue on reverse of a Hardward of Sensing Remote Sensing, LANDSAT, Land use, Hydrologic mode 	of Michigan's ng of the a w) ls, grid cell data base.
 DISTRIBUTION STATEMENT (of the shetrest entered in Block 20, If different in Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensing Environment, 23-30 April 1980, San Jose, Costa Rick KEY WORDS (Continue on reverse olde II necessary and identify by block number Remote sensing, LANDSAT, Land use, Hydrologic mode 	of Hichigan's ng of the a w) ls, grid cell data base.
 DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different in Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensing Environment, 23-30 April 1980, San Jose, Costa Rice KEY WORDS (Continue on review side if accessory and identify by Mach number Remote sensing, LANDSAT, Land use, Hydrologic mode 	of Michigan's ng of the a ** Is, grid cell data base.
7. DISTRIBUTION STATEMENT (of the observed entered in Block 20, if different in Pr 10. SUPPLEMENTARY NOTES Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensin Environment, 23-30 April 1980, San Jose, Costa Rick 10. KEY WORDS (Continue on reverse side if necessary and identify by Mech number Remote sensing, LANDSAT, Land use, Hydrologic mode Remote Sensing, LANDSAT, Land use, Hydrologic mode	of Hichigan's ng of the a ** Is, grid cell data base.
 DISTRIBUTION STATEMENT (of the shetrest entered in Block 20, If different in Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensing Environment, 23-30 April 1980, San Jose, Costa Rick KEY WORDS (Continue on reverse olde If necessary and identify by block number Remote sensing, LANDSAT, Land use, Hydrologic mode A land use/land cover identification methodole 	of Hichigan's ng of the a s, grid cell data base.
 DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different in Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensing Environment, 23-30 April 1980, San Jose, Costa Rick KEY WORDS (Continue on reverse elde II accossory and identify by block number A land use/land cover identification methodolic peen applied to six watersheds across the U.S. The terminational service and identify by block number A land use/land cover identification methodolic peen applied to six watersheds across the U.S. The terminational service and in the service of the service of the termination of the service of	of Michigan's ng of the a "" Is, grid cell data base. " ogy using LANDSAT imagery has e land use information is
 DISTRIBUTION STATEMENT (of the observed in Block 20, if different in Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensing Environment, 23-30 April 1980, San Jose, Costa Rick KEY WORDS (Continue on revuese side if necessary and identify by Mech number Remote sensing, LANDSAT, Land use, Hydrologic mode A land use/land cover identification methodolic been applied to six watersheds across the U.S. The stored in a grid cell data bank and is the basis for parameters for watershed models. Elood frequency of the store of the store of the sensing for the store of the sense of the s	of Hichigan's ng of the a "" Is, grid cell data base. " Ogy using LANDSAT imagery has e land use information is or calibration of hydrologic studies have been completed
 DISTRIBUTION STATEMENT (of the shetrest entered in Block 20, If different is Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensing Environment, 23-30 April 1980, San Jose, Costa Rick N. KEY WORDS (Centime on reverse olds If necessary and identify by block number A land use/land cover identification methodol is been applied to six watersheds across the U.S. The stored in a grid cell data bank and is the basis for parameters for watersheds with land use derived from the sensing with land use derived from the sension of the sensing with land use derived from the sensing with land use derived from the sensing with land use derived from the sension of the sensio	of Michigan's ng of the a "" Is, grid cell data base. " ogy using LANDSAT imagery has e land use information is or calibration of hydrologic studies have been completed om both satellite data and
Pr 18. SUPPLEMENTARY NOTES Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensition Environment, 23-30 April 1980, San Jose, Costa Rick 18. KEY WORDS (Continue on reverse elde II accosery and identify by Mech number A land use/land cover identification methodolic been applied to six watersheds across the U.S. The stored in a grid cell data bank and is the basis for arameters for watersheds with land use derived frecoment, San Jose, Costa Rick Content on the stores of the land use derived frecoment of the watersheds with land use derived frecoment, San	of Michigan's ng of the a "" Is, grid cell data base. " ogy using LANDSAT imagery has e land use information is or calibration of hydrologic studies have been completed om both satellite data and s paper discusses our experier
17. DISTRIBUTION STATEMENT (of the obstreet entered in Block 20, if different is Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensitienvironment, 23-30 April 1980, San Jose, Costa Rick Remote sensing, LANDSAT, Land use, Hydrologic mode A land use/land cover identification methodol been applied to six watersheds across the U.S. The stored in a grid cell data bank and is the basis for barameters for watersheds with land use derived from the watersheds with land use derived from the data bank and use derived from the watersheds with land use derived from the data bank and use derived from the data bank and use derived from the watersheds with land use derived from the data bank and bank and the data bank and the data bank and	of Michigan's ng of the a "" Is, grid cell data base. " ogy using LANDSAT imagery has e land use information is or calibration of hydrologic studies have been completed om both satellite data and s paper discusses our experier e and compares hydrologic resu
17. DISTRIBUTION STATEMENT (of the obstreet entered in Block 20, if different is Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensitienvironment, 23-30 April 1980, San Jose, Costa Rice Remote sensing, LANDSAT, Land use, Hydrologic mode A land use/land cover identification methodol been applied to six watersheds across the U.S. The stored in a grid cell data bank and is the basis for armeters for watersheds with land use derived from the alternative determinations of land use classification procedure obtained from the alternative determinations of land	of Michigan's ng of the a
TO DISTRIBUTION STATEMENT (of the observed in Block 20, If different is Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensit Environment, 23-30 April 1980, San Jose, Costa Rick M. KEY WORDS (Continue on reverse olds if necessary and identify by block member Remote sensing, LANDSAT, Land use, Hydrologic mode A land use/land cover identification methodol been applied to six watersheds across the U.S. The stored in a grid cell data bank and is the basis for parameters for watershed models. Flood frequency so on four of the watersheds with land use derived fro conventional low altitude aerial photography. This ising the LANDSAT land use classification procedure btained from the alternative determinations of lar D 1 JAN 75 1473 EDITION OF 1 NOV SB 15 OBOLETE	of Michigan's ng of the a w) ls, grid cell data base. o ogy using LANDSAT imagery has e land use information is or calibration of hydrologic studies have been completed om both satellite data and s paper discusses our experien- e and compares hydrologic resu of 19 82 00
Pr IS. SUPPLEMENTARY NOTES Presented at The Environmental Research Institute Fourteenth International Symposium on Remote Sensing Invironment, 23-30 April 1980, San Jose, Costa Rick IN. KEY WORDS (Continue on review olde H measurery and identify by Mech measurer Remote sensing, LANDSAT, Land use, Hydrologic mode A land use/land cover identification methodol ween applied to six watersheds across the U.S. The stored in a grid cell data bank and is the basis for arameters for watersheds with land use derived fre- conventional low altitude aerial photography. This ising the LANDSAT land use classification procedure btained from the alternative determinations of land D : JAM 72 1473 EDITION OF 1 NOV 45 16 OBDOLETE SECURITY C	of Michigan's ng of the a "" Is, grid cell data base. " ogy using LANDSAT imagery has e land use information is or calibration of hydrologic studies have been completed om both satellite data and s paper discusses our experier e and compares hydrologic result addition of this pace the back
TO DISTRIBUTION STATEMENT (of the abstract enfored in Block 20, If different is Presented at The Environmental Research Institute of Fourteenth International Symposium on Remote Sensing Environment, 23-30 April 1980, San Jose, Costa Rick Remote sensing, LANDSAT, Land use, Hydrologic mode A land use/land cover identification methodologic been applied to six watersheds across the U.S. The stored in a grid cell data bank and is the basis for barameters for watersheds with land use derived from the use flow of the watersheds with land use derived from conventional low altitude aerial photography. This using the LANDSAT land use classification procedure bataned from the alternative determinations of land D roma 1473 EDITION OF 1 NOV 85 15 OBOLETE SECURITY C	of Michigan's ng of the a w ls, grid cell data base. ogy using LANDSAT imagery has e land use information is or calibration of hydrologic studies have been completed om both satellite data and s paper discusses our experier e and compares hydrologic result of USA

DETERMINATION OF LAND USE FROM SATELLITE

IMAGERY FOR INPUT TO HYDROLOGIC MODELS*

R. Pat Webb, Robert Cermak and Arlen Feldman

The Hydrologic Engineering Center U.S. Army Corps of Engineers 609 Second Street Davis, California 95616

Acces	sion For							
NTIS	GRALI							
DTIC TAB								
Unann	Unannounced []							
Justi	Justification							
By Distr	vibution/							
	Avail and/or							
Dist	Special							
I H								

DISTRIBUTION STATEMENT A Approved for public release; Distribution Unlimited

*Presented at the Environmental Research Institute of Michigan's Fourteenth International Symposium on Remote Sensing of the Environment, 23-30 April 1980, San Jose, Costa Rica

....

DETERMINATION OF LAND USE FROM SATELLITE IMAGERY

FOR INPUT TO HYDROLOGIC MODELS

R. Pat Webb, Robert Cermak and Arlen Feldman

The Hydrologic Engineering Center U.S. Army Corps of Engineers 609 Second Street Davis, California 95616

ABSTRACT

A land use/land cover identification methodology using LANDSAT imagery has been applied to six watersheds across the U.S. The land use information is stored in a grid cell data bank and is the basis for calibration of hydrologic parameters for watershed models. Flood frequency studies have been completed on four of the watersheds with land use derived from both satellite data and conventional low altitude aerial photography. This paper discusses our experience using the LANDSAT land use classification procedure and compares hydrologic results obtained from the alternative determinations of land use.

Land use/land cover has been found to have a significant effect on the quantity, quality, and timing of storm runoff from urban (and urbanizing) drainage basins. In an attempt to quantify this important relationship, the Hydrologic Engineering Center (HEC) has interfaced state-of-the-art spatial data management techniques with hydrologic planning models, such as HEC-1 and STORM, to simulate storm runoff as a function of land use. The grid cell data banks also contain information on the watershed's environmental, economic, and social characteristics, thus permitting a comprehensive understanding of the interaction between the water resource system and possible future urban developments.

HEC has been involved in a NASA ASVT project which tests and evaluates a procedure developed at the University of California, Davis (UCD) for determining land use/land cover from LANDSAT imagery. The UCD procedure was designed with the objective of providing Corps of Engineers District offices with an operational cost-effective alternative to conventional methods of obtaining land use data. A constraint on the procedure was that it not require the use of special image processing or computing equipment beyond that which would normally be available to the field office; i.e., line printer, card reader, remote terminal, and access to a general purpose computer. The UCD procedure consists of an integrated set of computer programs centered around an unsupervised classification routine. Data quality check, geometric registration and correction, data classification, symbol map generation, resampling and masking are all accomplished without the use of an interactive color image display.

HEC has applied the UCD classification method to Crow Creek near Davemport, Iowa, and Walnut Creek near Austin, Texas. Available ground truth data permitted the identification of seven land cover categories from the LANDSAT imagery: agricultural, residential/highways, industrial/commercial, grassland, forest, undeveloped open space, and water. Hydrologic simulations of four additional watersheds, previously classified during the development of the procedure, were made, using both conventional and LANDSAT land use data. Resulting discharge frequency curves were compared to determine the effectiveness of LANDSAT land use in estimating "true" land use for hydrologic modeling purposes.

In addition, two commercial contractors provided a land use classification of the Walnut Creek watershed based on the same LANDSAT scene to help verify the accuracy of the UCD procedure with current state-of-the-art classification methodologies. Because the LANDSAT derived land use was placed in data banks which contained conventionally classified land use, detailed cell by cell comparisons were made between the conventional and all of the LANDSAT land use classifications to get an indication of spatial accuracies associated with LANDSAT data and the classification procedures.

Based on our experience in using the UCD procedure and commercially derived LANDSAT data, recommendations are presented regarding the role of remote sensing information in the Corps of Engineers hydrologic investigations program.

LANDSAT LAND USE FOR HYDROLOGIC MODELING

The hydrologic modeling of a watershed, particularly urban or urbanizing basins, requires that the distribution of land use be determined. The amount and timing of runoff is directly related to the infiltration capacity of a land area with the most important distinction being between pervious and impervious land surfaces. Water quality parameters have a similar dependence on land use data; rate of accumulation of a particular pollutant per unit area is normally expressed as a function of land use. Water resource planning studies are interested in not only an assessment of the present state of the water and related resource system, but also its possible future configuration. By expressing hydrologic parameters as a function of current land use it becomes possible to rationally predict the impact future land use changes will have on the quantity and quality of future runoff.

Manual methods for land use identification (e.g., interpretation of low altitude aerial photography and field surveys) are frequently used in watershed studies. With this approach, the resource requirements, both money and labor, for manual classification can be extensive. An attractive alternative is the utilization of available remote sensing systems and computer-assisted classification techniques.

The LANDSAT satellites have been shown to have the capability of providing land use data at acceptable levels of accuracy for hydrologic modeling purposes, (Jackson, 1977; Ragan, 1975). LANDSAT data is quicker and less costly to obtain and interpret than low altitude aerial photography, provides repetitive coverage of the same area at least every 18 days, and is available for all United States and many worldwide locations. Additionally, LANDSAT's digital format can be directly analyzed by several available classification computer programs, and can be resampled for automatic inclusion in a geographic data bank.

UCD PROCEDURES

An operational procedure for land use classification from LANDSAT data has been developed at the University of California, Davis (UCD) for use by the Corps of Engineers. Referred to as the UCD Procedure, it was designed to function under the following constraints:

(1) Only output equipment normally available in Corps' field offices (e.g., line printer) and batch-mode access to a general purpose computer could be expected. This would eliminate the need for highly expensive, dedicated, interactive image processing facilities.

(2) No additional software beyond that provided as part of the procedural package would be required.

(3) No specialized technical expertise in data analysis, computer programming, or remote sensing would be required.

(4) The final classification would be a usable product; i.e., one that can conveniently be entered into a grid cell data bank and that will adequately, from a hydrologic viewpoint, represent current land use conditions.

The UCD procedure consists of an organized set of computer programs and manual operations for the identification of land use from raw LANDSAT data. A detailed description of the procedure is given by Algazi (1979) and Meyer (1978). What follows is a brief outline of the primary tasks:

(1) Obtain LANDSAT Computer-Compatible Tapes (CCT), NASA high altitude aerial photography, and USGS topographic maps for the location and date of interest. Extract a rectangular area of data containing the watershed from the OCT. Check for radiometric errors in the LANDSAT digital data and, if necessary, correct.

(2) Determine the geometric registration of the LANDSAT image with the coordinate system of the topographic maps. LANDSAT control points are identified from the output of a UCD computer program which enhances roads and water bodies found in the LANDSAT image. A regression equation, estimated from the two sets of control points, provides a transformation mechanism for going between the image coordinate system and the map coordinate system, Universal Transverse Mercator (UTM).

(3) Use an unsupervised clustering algorithm to partition the LANDSAT four-dimensional data space. Groups or "clusters" are identified that contain points with spectral reflectance values that are similar to members of the same cluster, and dissimilar to the points of other clusters. The clustering program is allowed to generate a maximum of 30 clusters. Each pixel in the watershed data is assigned to a cluster.

(4) Select from a line printer map of the cluster assignments six sets of adjacent pixels (spatial groups), all belonging to the same cluster. Their corresponding location on the topographic maps is determined using the transformation equation of step (2). Visual translation, from the map to the aerial photographs, of the spatial group's location permits a land use to be assigned to each spatial group. For clusters having a consistent land use assigned to all six spatial groups, a final land use has been determined. But for those clusters where conflicts exist between the land use identified with each of the six spatial groups, further partitioning of the data space is required.

(5) Clusters with conflicting land use assignments and clusters whose associated land use could not be determined from the available maps and photos are reclustered by repeating step (3), and given final land use assignments by repeating step (4).

(6) At this point the watershed data file contains a land use classification (typically 5 to 7 categories) for all its pixels. The watershed file is then resampled at the grid cell centroids using a nearest-neighbor algorithm. The size of the grid cells is usually line printer compatible with the scale of USGS 7-1/2-min. topographic maps.

(7) The resampled file is entered directly into a grid cell data bank. Alternatively, a file containing the digitized (in UTM coordinates) watershed boundary can be used to mask the resampled file, leaving only the grid cells within the boundary. Total acreage of each land use class for the entire watershed is then computed.

HYDROLOGIC LAND USE COMPARISON

The primary reason for examining the land use classification ability of LANDSAT was for its potential application to hydrologic modeling. The computer program HEC-1 (U.S. Army Corps of Engineers, 1973) has the capability of explicitly relating land use to runoff using two procedures: Snyder's unit hydrograph with percent imperviousness, and the SCS curve number and unit hydrograph (U.S. Soil Conservation Service, 1972). The HYDPAR program (U.S. Army Corps of Engineers, 1978b) obtains the necessary information from a grid cell data bank and computes the specified hydrologic parameters, which are in turn input into an HEC-1 model of the basin. HYDPAR contains a regression equation formulation of Snyder's lag as a function of stream length, length to centroid of subbasin, stream slope, and percent imperviousness. A table associating a percent imperviousness with each land use category in the data bank enables HYDPAR to compute subbasin percent imperviousness from subbasin land use distribution.

In a similar manner HYDPAR can determine the SCS unit hydrograph parameter from stream length, basin average land slope, and subbasin average curve number. Curve numbers represent an empirical relationship between hydrologic soil type, land use, and their resultant runoff potential. From a table identifying a curve number with each combination of land use and hydrologic soil type, HYDPAR computes subbasin average curve number.

Both hydrologic modeling techniques, Snyder's unit hydrograph with percent imperviousness and the SCS curve number approach, were applied to the land use classifications of two watersheds: Rowlett Creek near Dallas, Texas, and Pennypack Creek in Philadelphia, Pennsylvania. For each watershed land use was determined from LANDSAT imagery using the UCD Procedure, and conventional interpretation of low-altitude aerial photography. The following contains summary results of the hydrologic land use comparison. Complete details of the study are reported in (U.S. Army Corps of Engineers, 1979).

ROWLETT CREEK

A calibrated HEC-1 model of a 24.6 square mile (63.7 Km^2) portion of the Rowlett Creek basin, referred to as Upper Spring Creek, was used to simulate runoff from selected recurrence interval rainfall. Initial assignments of percent imperviousness to Rowlett Creek's LANDSAT and conventional land use categories permitted HYDPAR to compute Snyder's lag for the twenty-three subbasins in Upper Spring Creek. Nearly identical values of lag were calculated from the LANDSAT and conventional land use data.

The calibrated HEC-1 model (using the two land use estimates of Snyder's lag) and synthetic rainfall produced the discharge values plotted in Figure 1 for selected stations in the Upper Spring Creek drainage. Differences between such discharge frequency curves can be interpreted as a measure of the hydrologic significance of LANDSAT's misclassification of land use. Considering the uncertainty involved in estimating a frequency curve (even from observed data), the difference between LANDSAT and conventional curves is insignificant.

PENNYPACK CREEK

The SCS curve number method was used to model the Pennypack Creek basin $(55.8.:^2, 144.5$ Km²). Curve numbers were assigned to the LANDSAT and conventional land use categories. For each of Pennypack Creek's sixty-five subbasins HYDPAR calculated subbasin average curve number and subbasin lag. Once again, nearly identical values of subbasin lag were computed from the LANDSAT and conventional land use data.

As an additional comparison, subbasin average curve number and lag were calculated for (1) all land use categories assigned the <u>industrial</u> category curve numbers, and (2) <u>all</u> land use categories assigned the <u>natural vegetation</u> curve numbers. Parameters estimated in these two cases, and the discharge frequency curves derived from them, demonstrate the possible extremes (in terms of runoff) that could have been generated from the martel.

The calibrated HEC-1 model of Pennypack Creek simulated the basin's discharge frequency behavior for conventional, LANDSAT, all industrial, and all natural vegetation conditions. The resulting discharge frequency curves for the entire drainage area are shown in Figure 2. It is clear from this figure, especially with reference to what could have been (i.e., all industrial and all natural vegetation conditions), that the difference between LANDSAT had conventionally derived frequency curves is not significant.

ACCURACY VS. SPATIAL INTEGRITY

As previously mentioned, in order to be able to conduct the hydrologic modeling assessment, the LANDSAT land use was processed into existing geographic information system data banks. These data banks already contained an exhaustive, spatially accurate representation of the land use which was derived by conventional means. The grid cell size of these existing data banks varied in size from 0.74 acres (Pennypack Creek) to 1.148 acres (Rowlett Creek and Walnut Creek) to 1.53 acres (Trail Creek and Castro Valley). The description of the ways in which the conventional land use classification and the LANDSAT classification were derived is presented in detail in HEC's Research Note No. 7 (U.S. Army Corps of Engineers, 1979). Table 1, UCD Classification vs. Conventional Land Use, shows a summary of the cell-by-cell comparison for the Walnut Creek watershed.

For a cell-by-cell comparison of the Walnut Creek watershed it was necessary to establish an explicit aggregation of the conventional land use categories into the fewer LANDSAT land use categories, Table 2. The RIA computer program (U.S. Army Corps of Engineers, 1978a) generated the coincident matrix, Table 1. The structure of this cross tabulation table is similar to others that will be presented later in this paper. Each element of the table (row and column combination) refers to all grid cells within the watershed data bank that have the concurrent LANDSAT and conventional land use specified by the row and column headings of that particular element. For example, the 2nd row, 1st column of Table 1 refers to all grid cells in the Walnut Creek data bank that are classified both commercial/industrial by LANDSAT and residential by the conventional classification. For each element of the table, four numbers



5

.

.

<u>```</u>

TABLE 1

Walnut Creek Land Use Comparison UCD LANDSAT vs. CONVENTIONAL

	Acres* Z Row	<u>CONVENTIONAL</u>						
	% Col % Total	RES	COM/IND	QUARRY	CROP/PASTURE /RANGE	FOREST	WATER	ROW TOTAL
	RES	3801 41.6 59.8 10.4	1098.8 12.0 31.6 3.0	225 2.5 22.0 0.6	3147 34.4 19.1 8.6	859 9.4 9.4 2.3	6 0.1 9.5 0.0	9136 100.0 25.0 25.0
	COM/IND	471 25.3 7.4 1.3	816 43.8 23.5 2.2	130 7.0 12.7 0.4	366 19.7 2.2 1.0	78 4.2 0.9 0.2	0 0.0 0.0 0.0	1861 100.0 5.1 5.1
UCD LAND SA T	QUARRY	13 5.8 0.2 0.0	61 27.4 1.8 0.2	111 49.8 10.9 0.3	17 7.6 0.1 0.0	21 9.4 0.2 0.1	0 0.0 0.0 0.0	223 100.0 0.6 0.6
	CRO P/ PAST URE	1581 10.3 24.9 4.3	1106 7.2 31.8 3.0	313 2.0 30.7 0.9	9324 60.9 56.4 25.5	2947 19.3 32.2 8.1	28 0.2 44.4 0.1	15229 100.0 41.8 .8
	FORE ST/ RANGE	493 4.9 7.8 1.3	361 3.6 10.4 1.0	234 2.3 22.9 0.6	3655 36.6 22.1 10.0	5233 52.4 57.2 14.3	13 0.1 20.6 0.0	9989 100.0 27.3 27.3
	WATER	0 0.0 0.0 0.0	31 44.3 0.9 0.1	8 11.4 0.8 0.8	9 12.9 0.1 0.0	6 8.6 0.1 0.0	16 22.9 25.4 0.0	70 100.0 0.2 0.2
	COLUMN TOT AL	6359 17.4 100.0 17.4	3473 9.5 100.0 9.5	1021 2.8 100.0 2.8	16518 45.2 100.0 45.2	9144 25.4 100.0 25.0	63 0.2 100.0 0.2	36578 100.0 100.0 100.0

*To obtain hectares, multiply acres by 2.471.

18.7

6

>

.

TABLE 2

,

7

. . .

WALNUT CREEK LAND USE CATEGORY MAPPING

Conventional Land Use	UCD LAND SAT	Battelle LANDSAT	GE LANDSAT	
Low density single family residential Medium density single family residential High density single family residential Multifamily residential Mobile home parks	residential residential		residential l residential 2	
Strip commercial Shopping centers Institutional Industrial Industrial and commercial complexes Public Use: cemetaries, public assembly areas, waste disposal areas Transportation, communication, utilities	commercial/ industrial	industrial/ commercial transportation	urban	
Barren land/quarry	barren land/	barren land	highly reflective	
Cropland Pasture/rangeland Developed open space Undeveloped urban land	cropland/ pasture	Cropland/ pasture rangeland	vegetation/ crops dark fields open area	
Forest	forest/ rangeland	forest riparian	woodland	
Water	water	water		

7

•

are given: (1) total acreage of all grid cells represented by the appropriate joint land use classification; (2) row percent, or the precent of all grid cells with the given LANDSAT classification that have also the given conventional classification; (3) column percent, or the percent of all grid cells with the given conventional land use that have also the given LANDSAT land use; and (4) total percent, or the percent of the entire watershed that has the given joint land use classification. Continuing our example above, 471 acres (1186 Hectares) were found to be classified both commercial/industrial by LANDSAT and residential by conventional means. This acreage represents 25.3% of all the area (1861 acres) that was classified by LANDSAT as commercial/industrial, 7.4% of all the area (6359 acres) that belonged to the conventional residential category, and 1.3% of the total watershed area (36,578 acres).

The far right column (row total) and the bottom row (column total) of Table 1 give the marginal distributions of LANDSAT and conventional land use, respectively. These represent the acres and percent in the different land use categories <u>without</u> the conditional requirement described above for the body of the table.

Figures 3 and 4 show the spatial location of both the conventional and the UCD classified land use which are part of the Walnut Creek grid cell data bank.

COMMERCIAL CAPABILITY

The UCD procedure provided completely acceptable land use percentages for the subbasins and total watershed areas (the marginal values in Table 1) which were input into the hydrologic models. Spurred on by this initial success, the HEC further participated in the Water Management and Control ASVT by comparing commercially prepared LANDSAT land use classifications. The objectives of HEC's participation were: (1) to compare the results of the UCD procedure to the results from commercial vendors, (2) to provide cost data to a cost-effectiveness study of LANDSAT determined land use which was part of the ASVT and, (3) to evaluate the ability of commercial vendors to create a computer file which could be directly inserted as a data variable into an existing grid cell data bank. In order to execute this porvion of the ASVT, the Walnut Creek data bank was selected as the test area because (1) the HEC was confident in the spatial integrity and accuracy of the conventional land use in the data bank, (2) the grid cell size was 1.148 acres which was comparable to a pixel size of 1.1 acres and, (3) the grid pattern for the study area was orientated to align with the UTM coordinate system. The commercial contractors which were selected to participate in this portion of the study were General Electric and Battelle's Pacific Northwest Labratories in Richland, Washington. Both commercial firms created resampled tapes which contained the land use value which corresponded to the centroid location of each of the Corps rectangular grid cells (200 feet x 250 feet). Table 2 contains the commercial LANDSAT land use classifications which correspond to the conventional classification. Tables 3 and 4 show the results of the cell-by-cell comparisons for the Battelle and General Electric classifications, respectively.

Using the diagonal percentages in Tables 1, 3 and 4, the overall cell by cell accuracies of the UCD procedure, Battelle and General Electric were 53, 44 and 44 percent, respectively. In evaluating the spatial integrity of the LANDSAT derived land use from the various classification procedures, there are three potential sources of error: (1) differences resulting from the land use, land cover conflict, (2) geometric correction and resampling error and (3) misclassification of the pixel spectral signatures.

When comparing LANDSAT and conventional land use classifications, it is important to recognize that the same land cover can be interpreted differently; i.e., <u>conventional land use</u> categories are <u>not always compatible</u> with <u>LANDSAT land cover</u> categories. For example, the conventional category "transportation/communication/utilities" includes major highways, right-of-way for railroads and power transmission lines, communication towers, airport facilities (including buildings, runways, and vacant land within the airport limits), and sewage treatment plants. In contrast, LANDSAT will recognize the treatment plant settling tanks as "water bodies", the open fields surrounding a runway as one of the vegetation categories, and right-of-ways as whatever land cover class is nearby. Even though this is a problem with any LANDSAT land use classification, in the Walnut Creek watershed only a very small portion of the watershed had the potential for this kind of error.



1

.....



TABLE 3

Walnut Creek Land Use Comparison Battelle LANDSAT vs. Conventional

	Acres*	CONVENTIONAL						
	% Row % Col % Total	RES	COM/IND	QUARRY	CROP/PASTURE /RANGE	FORE ST	WATER	ROW TOTAL
	RES	2723 41.8 45.6 7.8	976 15.0 31.6 2.8	70 1.1 7.2 0.2	1969 30.2 12.4 5.7	763 11.7 8.7 2.2	12 0.2 19.0 0.0	6513 100.0 18.8 18.8
	COM/IND	661 28.9 11.1 1.9	336 14.7 10.9 1.0	79 3.5 8.1 0.2	890 38.9 5.6 2.6	319 14.0 3.6 0.9	1 0.0 1.6 0.0	2286 100.0 6.6 6.6
BATTELLE LANDSAT CRO PAS RANG	QUARRY	212 15 3.5 0.6	160 11.3 5.2 0.5	111 7.8 11.3 0.3	614 43.4 3.9 1.8	319 22.5 3.6 0.9	0 0.0 0.0 0.0	1416 100.0 4.1 4.1
	CROP/ PASTURE RANGE	1720 9.5 28.8 5.0	1137 6.3 36.8 3.3	517 2.9 52.9 1.5	9803 54.1 61.8 28.3	4922 27.1 56.3 14.2	37 0.2 58.7 0.1	18136 100.0 52.3 52.3
	FOREST	636 10.1 10.6 1.8	464 7.4 15.0 1.3	201 3.2 20.6 0.6	2572 40.9 16.2 7.4	2410 38.3 27.6 6.9	12 0.2 19.0 0.0	6295 100.0 18.1 18.1
	WATER	23 42.6 0.4 0.1	13 24.1 0.4 0.0	0 0.0 0.0 0.0	8 14.8 0.1 0.0	9 16.7 0.1 0.0	1 1.9 1.6 0.0	54 100.0 0.2 0.2
	COL UMN TOTAL	5975 17.2 100.0 17.2	3086 8.9 100.0 8.9	978 2.8 100.0 2.8	15856 45.7 100.0 45.7	8742 25.2 100.0 25.2	63 0.2 100.0 0.2	34700 100.0 100.0 100.0

*To obtain hectares, multiply acres by 2.471.

11

\$

TABLE 4

Walnut Creek Land Use Comparison G. E. LANDSAT vs. Conventional

	Acres* Z Row Z Col Z Total	CONVENTIONAL						
		RES	COM/IND	QUARRY	CROP/PASTUR /RANGE	E FOREST	WATER	ROW TOTAL
	RES	3573.7 45.6 57.4 10.2	1060.8 13.5 31.6 3.0	205.5 2.6 20.8 0.6	2308.6 29.5 14.8 6.6	679.6 8.7 7.6 1.9	5.7 0.1 9.2 0.0	7833.9 100.0 22.3 22.3
	COM/IND	464.90 14.7 7.5 1.3	693.4 21.8 20.6 2.0	102.2 3.2 10.4 0.3	1678.3 52.8 10.8 4.8	231.9 7.3 2.6 0.7	3.4 0.1 5.5 0.0	3174.2 100.0 9.0 9.0
G.E. LAND SAT	QUARRY	358.2 18.9 5.8 1.0	690.1 36.4 20.5 2.0	289.3 15.3 29.3 0.8	433.9 22.9 2.8 1.2	106.8 5.6 1.2 0.3	16.1 0.9 26.0 0.1	1894.2 100.0 5.4 5.4
	AGRICUL- TURE/ OPEN SPACE	1587.6 9.9 25.5 4.5	677.4 4.2 20.2 1.9	261.8 1.6 26.6 0.8	8264.6 51.6 53.1 23.5	5208.5 32.5 58.3 14.8	13.7 0.1 22.1 0.0	16013.6 100.0 45.6 45.6
	WOODLAND	242.2 3.9 3.9 0.1	238.9 3.9 7.1 0.7	127.4 2.1 12.9 0.4	2871.1 46.3 18.5 8.2	2701.2 43.5 30.3 7.7	23.0 0.0 37.1 0.1	6203.8 100.0 17.7 17.7
	WATER	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 100.0 0 0
*********	COLUMN TOTAL	6226.8 17.4 100.0 17.7	3360.5 9.6 100.0 9.6	986.2 2.8 100.0 2.8	15556.6 44.3 100.0 44.3	8928.0 25.4 100.0 25.4	62.0 0.2 100.0 0.2	35119.6 100.0 100.0 100.0

*To obtain hectares, multiply acres by 2.471.

.....

•----

12

1,

A comparison at the grid cell level can be thought of as a comparison at the pixel level; both units of area are nearly the same size. At this scale errors introduced during the geometric correction and resampling steps will be erroneously interpreted as LANDSAT misclassification errors. This will be particularly true of land use categories defined by a small number of adjacent pixels. The border areas of the larger land use categories are also susceptible to geometric problems. In order to assess the magnitude of the registration/resampling error, the RIA program was used to calculate the linear distance each grid cell was from the nearest residential category. These distances were then overlaid on the actual residential locations from the three LANDSAT classifications. The reason for this overlay was that if the major problem in the cell-by-cell comparison was in the geometric correction/resampling procedures, all of the LANDSAT residential areas should be within one or two grid cells of an actual residential area. The LANDSAT residential areas which located beyond this distance could be assumed to be errors in misclassification.

Figure 5, LANDSAT RESIDENTIAL VS DISTANCE TO ACTUAL RESIDENTIAL, is a histogram of the spatial integrity of the three classifications for residential land use and is shown as a percentage of the residential area for each classification. The figure shows that at least 60 percent of all these classifications fell within 2 grid cells of the ground truth residential areas. The Battelle classification was more accurate for the residential areas, but when compared for all land use categories it was less accurate than the UCD procedure. There were at least two reasons for Battelle's higher residential accuracy when compared to UCD and G.E.; first, they had personnel from the Corps who were very familiar with the study area to help with the classification, which was not the case in the UCD and G.E. classifications and second, they had the capability to predefine urban areas and reclassify clusters which were given a residential value but were located outside "known" residential areas.

The third source of error, misclassification, was looked at for only the UCD classification. A RIA coincidence table was generated for the conventional land use and the cluster values to see if any of the clusters were misclassified. The HEC could not identify any obvious misclassifications, therefore, it was assumed that the remaining error (40-60 percent) in the cell-by-cell comparison was due to the limitations of either the clustering techniques or the satellite sensors themselves.



Figure 5

RESAMPLED TAPES

The resampled tapes supplied by UCD, Battelle, G.E. and Bendix (for the Castro Valley Watershed) were required to conform to the following specifications:

- (1) The first record on the tape would be a header record which would give the number of rows and the number of columns in the data matrix.
- (2) The data would be supplied a row (line) at a time, for however many number of rows there were in the study area.
- (3) The first land use value would correspond to the grid location 1, 1 on the Walnut Creek or Castro Valley Basemap.
- (4) If the contractor windowed out the watershed, cells outside the study area would be given a land use value of -1.

In addition, all contractors were warned that if they windowed the study area, to include at least some buffer area on the resampled tape to make sure that all grid cells in the existing data base would be given a value.

The HEC was able to process the UCD and Battelle tapes directly into the existing data base. The Battelle tape, however, had several problems. After the tape had been provided to HEC, it was discovered that the wrong corner grid cell was used in the resampling. All land use comparisons of the Battelle classification in this paper will be affected by this known resampling error. In addition, when the Battelle resampled file was entered into the Walnut Creek grid cell data bank only 34,697 acres (54.21 sq. mi.) were located within the geographically correct watershed boundary, the latter being defined in the data bank as containing 36,574 acres (57.15 sq. mi.). The total classified land area listed on Battelle's color-coded map was 35,869 acres (56.05 sq. mi.).

The G.E. tape was not produced to the original specifications, so that a new resampled tape had to be generated, and it also had resampling problems so that it only contained 35,120 acres (54.9 sq. mi.).

CONCLUSION

The LANDSAT derived land use classification percentages are well within an acceptable error to be used for hydrologic modeling. The LANDSAT derived land use classification may also be successfully placed into existing grid cell data banks to be used in other types of analysis, such as environmental assessments. Caution needs to be made though on the spatial integrity of the LANDSAT derived land use for grid cell data banks which have a grid cell size which is at about the same resolution as a pixel. The HEC is currently investigating the accuracies associated with a 4.6 and a 10.3 acre grid cell size with the same data.

The UCD procedure was successful in eliminating the need for expensive image processing equipment and its accuracy was as good or better than the commercial firms which supplied land use data for the same area. This paper presents problems encountered with the commercial products during the conduct of HEC's portion of the ASVT. The authors fully realize that because of continuous technology changes that these problems may have been eliminated.

REFERENCES

Algazi, V.R., G.E. Ford and D.I. Meyer, 1979, "A Non-Interactive Approach to Land Use Determination," 1979 Machine Processing of Remotely Sensed Data Symposium, Purdue University, June 27-29.

Cermak, R.J., A. Feldman and R.P. Webb, 1979, "Hydrologic Land Use Classification Using LANDSAT," Proceedings of the AWRA Satellite Hydrology Symposium, Sioux Falls, South Dakota, June 11-15 (in press).

Jackson, T.J., R.M. Ragan and W.N. Fitch, 1977, "Test of LANDSAT-Based Urban Hydrologic Modeling," <u>Journal of the Water Resources Planning and Management Division, ASCE</u>, 103 (WRI), pp. 141-158.

Meyer, D. and V.R. Algazi, 1978, "Land Use Classification of LANDSAT Data Using a Clustering Algorithm," Department of Electrical Engineering, University of California, Davis, California (draft).

Ragan, R.M. and T.J. Jackson, 1975, "Use of Satellite Data in Urban Hydrologic Models," Journal of the Hydraulics Division, ASCE, 101 (HY12), pp. 1469-1475.

U.S. Soil Conservation Service, 1972, "Hydrology," SCS National Engineering Handbook, Section 4, Washington, D.D.

U.S. Army Corps of Engineers, 1973, "HEC-1 Flood Hydrograph Package, Users Manual," The Hydrologic Engineering Center, Davis, California

U.S. Army Corps of Engineers, 1978a, "Resource Information and Analysis Using Grid Cell Data Banks: Users Manual," The Hydrologic Engineering Center, Davis, California.

U.S. Army Corps of Engineers, 1978b, "HYDPAR: Hydrologic Parameters, Users Manual," The Hydrologic Engineering Center, Davis, California.

U.S. Army Corps of Engineers, 1979, "Determination of Land Use from LANDSAT Imagery: Applications to Hydrologic Modeling, "Research Note No. 7, The Hydrologic Engineering Center, Davis, California.

s.

TECHNICAL PAPERS

Technical papers are written by the staff of the HEC, sometimes in collaboration with persons from other organizations, for presentation at various conferences, meetings, seminars and other professional frice gatherings.

- # 1 Use of Interrelated Records to Simulate Streamflow, Leo R. Beard, December 1964, 22 pages.
- # 2 Optimization Techniques for Hydrologic Engineering, Leo R. Beard, April 1966, 26 pages.
- # 3 Methods of Determination of Safe Yield and Compensation Water from Storage Reservoirs, Leo R. Beard, August 1965, 21 pages.
- 4 Functional Evaluation of a Mater Resources System, Leo R. Beard, Manuary 1967, 32 pages.
- # 5 Streamflow Synthesis for Ungaged Rivers, Leo R. Beard, October 1967, 27 mages.
- # 6 Simulation of Daily Streamflow, Leo R. Beard, April 1968, 19 pages.
- # 7 Pilot Study for Storage Requirements for Low Flow Augmentation, A. J. Fredrich, April 1963, 39 pages.
- # 8 Worth of Streamflow Data for Project Design A Pilot Study, D. R. Dawdv, H. E. Kubik, L. R. Beard, and E. R. Close, April 1968, 20 pages.
- # 9 Economic Evaluation of Reservoir System Accomplishments, Leo R. Beard, May 1968, 22 pages.
- #10 Hydrologic Simulation in Water-Yield Analysis, Leo R. Beard, 1964, 22 pages.
- #11 Survey of Programs for Water Surface Profiles, Bill S. Eichert, August 1968, 39 pages.
- #12 Hypothetical Flood Computation for a Stream System, Leo R. Beard, April 1968, 26 pages.

Price \$2.00 each

#13 Maximum Utilization of Scarce Data in Hydrologic Design, Leo R. Beard and A. J. Fredrich, March 1969, 20 pages. #14 Techniques for Evaluating Long-Term Reservoir Vields, A. J. Fredrich, February 1969, 36 pages. #15 Hydrostatistics - Principles of Application, Leo R. Beard, July 1969, 18 pages. #16 A Hydrologic Water Resource System Modeling Techniques, L. G. Hulman and D. K. Erickson, 1969, 42 pages. #17 Hydrologic Engineering Techniques for Regional Water Resources Planning, Augustine J. Fredrich and Edward F. Hawkins, October 1969, 30 pages. #18 Estimating Monthly Streamflows Within a Region, Leo R. Beard, Augustine J. Fredrich, Edward F. Hawkins, January 1970, 23 pages. #19 Suspended Sediment Discharge in Streams, Charles E. Abraham, April 1969, 24 pages. #20 Computer Determination of Flow Through Bridges, Bill S. Eichert and John Peters, July 1970, 32 pages. #21 An Approach to Reservoir Temperature Analysis, L. R. Beard and R. G. Willey, April 1970, 31 pages. #22 A Finite Difference Method for Analyzing Liquid Flow in Variably Saturated Porous Media, Richard L. Cooley, April 1970, 46 pages. #23 Uses of Simulation in River Basin Planning, William K. Johnson and E. T. McGee, August 1970, 30 pages. Hydroelectric Power Analysis in Reservoir Systems, Augustine #24 J. Fredrich, August 1970, 19 pages. #25 Status of Water Resource Systems Analysis, Leo R. Beard, January 1971, 14 pages. #26 System Relationships for Panama Canal Water Supply, Lewis G. Hulman. April 1971, 18 pages. This publication is not available to countries outside of the U.S.

#27

3

the U.S.

Systems Analysis of the Panama Canal Water Supply, David C. Lewis and Leo R. Beard, April 1971, 14 pages. This publication is not available to countries outside of

- #28 Digital Simulation of an Existing Water Resources System, Augustine J. Fredrich, October 1971, 32 pages.
- #29 Computer Applications in Continuing Education, Augustine J. Fredrich, Bill S. Eichert, and Darryl W. Davis, January 1972, 24 pages.
- #30 Drought Severity and Water Supply Dependability, Leo R. Beard and Harold E. Kubik, January 1972, 22 pages.
- #31 Development of System Operation Rules for an Existing System by Simulation, C. Pat Davis and Augustine J. Fredrich, August 1971, 21 pages.
- #32 Alternative Approaches to Water Resource System Simulation, Leo R. Beard, Arden Weiss, and T. Al Austin, May 1972, 13 pages.
- #33 System Simulation for Integrated Use of Hydroelectric and Thermal Power Generation, Augustine J. Fredrich and Leo R. Beard, October 1972, 23 pages.
- #34 Optimizing Flood Control Allocation for a Multipurpose Reservoir, Fred K. Duren and Leo R. Beard, August 1972, 17 pages.
- #35 Computer Models for Rainfall-Runoff and River Hydraulic Analysis, Darryl W. Davis, March 1973, 50 names.
- #36 Evaluation of Drought Effects at Lake Atitlan, Arlen D. Feldman, September 1972, 17 nages. This publication is not available to countries outside of the U.S.
- #37 Downstream Effects of the Levee Overtopping at Wilkes-Barre, PA, During Tropical Storm Agnes, Arlen D. Feldman, April 1973, 24 pages.
- #38 Water Quality Evaluation of Aquatic Systems, R. G. Willey, April 1975, 26 pages.
- #39 A Method for Analyzing Effects of Dam Failures in Design Studies, William A. Thomas, August 1972, 31 pages.

Price \$2.00 each

Price \$2.00 each

- #40 Storm Drainage and Urban Region Flood Control Planning, Darryl Davis, October 1974, 44 nages.
- #41 HEC-5C, A Simulation Model for System Formulation and Evaluation, Bill S. Eichert, March 1974, 31 pages.
- #42 Optimal Sizing of Urban Flood Control Systems, Darryl Davis, March 1974, 22 pages.
- #43 Hydrologic and Economic Simulation of Flood Control Aspects of Water Resources Systems, Bill S. Eichert, August 1975, 13 pages.
- #44 Sizing Flood Control Reservoir Systems by Systems Analysis, Bill S. Eichert and Darryl Davis, March 1976, 38 pages.
- #45 Techniques for Real-Time Operation of Flood Control Reservoirs in the Merrimack River Basin, Bill S. Eichert, John C. Peters and Arthur F. Pabst, November 1975, 48 pages.
- #46 Spatial Data Analysis of Nonstructural Measures, Robert ^P. Webb and Michael W. Burnham, August 1976, 24 pages.
- #47 Commrehensive Flood Plain Studies Using Spatial Data Management Techniques, Darryl N. Davis, October 1976, 23 pages.
- #48 Direct Runoff Hydrograph Parameters Versus Urbanization, David L. Gundlach, September 1976, 10 mages.
- #49 Experience of HEC in Disseminating Information on Hydrological Models, Bill S. Eichert, June 1977, 12 pages. (Superseded by TP#56)
- #50 Effects of Dam Removal: An Approach to Sedimentation, David T. Williams, October 1977, 39 pages.
- #51 Design of Flood Control Improvements by Systems Analysis: A Case Study, Howard O. Reese, Arnold V. Robbins, John R. Jordan, and Harold V. Doval, October 1971, 27 nages.
- #52 Potential Use of Digital Computer Ground Water Models, David L. Gundlach, April 1978, 40 pages.
- #53 Development of Generalized Free Surface Flow Models Using Finite Element Techniques, D. Michael Gee and Robert C. MacArthur, July 1978, 23 pages.
- #54 Adjustment of Peak Discharge Rates for Urbanization, David L. Gundlach, September 1978, 11 pages.

Price \$2.00 each

#55 The Development and Servicing of Spatial Data Management Techniques in the Corps of Engineers, R. Pat Webb and Darryl W. Davis, July 1978, 30 pages. Experiences of the Hydrologic Engineering Center in Main-#56 taining Widely Used Hydrologic and Water Resource Computer Models, Bill S. Eichert, November 1978, 19 pages. Flood Damage Assessments Using Spatial Data Management #57 Techniques, Darryl W. Davis and R. Pat Webb, May 1978. 30 pages. A Model for Evaluating Runoff-Duality in Metropolitan #58 Master Planning, L. A. Roesner, H. M. Nichandros, R. P. Shubinski, A. D. Feldman, J. W. Abbott, and A. O. Friedland, April 1972, 85 pages. Testing of Several Runoff Models on an Urban Watershed, #59 Jess Abbott, October 1978, 56 pages. #60 Operational Simulation of a Reservoir System with Pumped Storage, George F. McMahon, Vern Bonner and Bill S. Eichert, February 1979, 35 pages. Technical Factors in Small Hydropower Planning, Darryl W. #61 Davis, February 1979, 38 pages. #62 Flood Hydrograph and Peak Flow Frequency Analysis, Arlen D. Feldman, March 1979, 25 pages. #63 HEC Contribution to Reservoir System Operation, Bill S. Eichert and Vernon R. Bonner, August 1979, 32 pages. #64 Determining Peak-Discharge Frequencies in an Urbanizing Watershed: A Case Study, Steven F. Dalv and John Peters, July 1979, 19 pages. #65 Feasibility Analysis in Small Hydropower Planning, Darryl W. Davis and Brian W. Smith, August 1979, 24 pages. #66 Reservoir Storage Determination by Computer Simulation of Flood Control and Conservation Systems, Bill S. Eichert, October 1979, 14 pages. #67 Hydrologic Land Use Classification Using LANDSAT, Robert 3. Cermak, Arlen D. Feldman, and R. Pat Webb, October 1979, 30 pages.

Price \$2<u>.00 each</u>

- **#68** Interactive Nonstructural Flood-Control Planning, David T. Ford, June 1980, 18 pages.
- #69 Critical Water Surface by Minimum Specific Energy Using the Parabolic Method, Bill S. Eichert, 1969, 14 pages.
- #70 Corps of Engineers' Experience with Automatic Calibration of a Precipitation-Runoff Model, David T. Ford, Edward C. Morris, and Arlen D. Feldman, May 1980, 18 pages.
- #71 Determination of Land Use from Satellite Imagery for Input to Hydrologic Models, R. Pat Webb, Robert Cermak, and Arlen Feldman, April 1980, 24 pages.
- #72 Application of the Finite Element Method to Vertically Stratified Hydrodynamic Flow and Water Ouality, Robert C. MacArthur and William R. Norton, May 1980, 12 pages.
- #73 Flood Mitigation Planning Using HEC-SAM, Darryl W. Davis, June 1980, 23 pages.
- #74 Hydrographs by Single Linear Reservoir Model, John T. Pederson, John C. Peters, Otto J. Helweg, May 1980, 17 pages.
- #75 HEC Activities in Reservoir Analysis, Vern R. Bonner, June 1980, 16 pages.

....

- #76 Institutional Support of Water Resource Models, John C. Peters, May 1980, 23 pages.
- #77 Investigation of Soil Conservation Service Urban Hydrology Techniques, Duke G. Altman, William H. Espey, Jr. and Arlen D. Feldman, December 1980, 20 pages.

