


AD-A109 898

NEW YORK STATE DEPT OF ENVIRONMENTAL CONSERVATION ALBANY F/6 13/13  
NATIONAL DAM SAFETY PROGRAM. GLENMERE LAKE DAM; (INVENTORY NUMB—ETC(U)  
SEP 81 6 KOCH DACW51-79-C-0001  
NL

UNCLASSIFIED

1-2  
ALL  
OTHER



A  
989

REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS BEFORE COMPLETING FORM

AD A109 898

1. REPORT NUMBER		2. GOVT ACCESSION NO. <b>AD A109 898</b>		3. RECIPIENT'S CATALOG NUMBER	
4. TITLE (and Subtitle) Phase I Inspection Report Glenmere Lake Dam Lower Hudson River Basin, Orange County, N.Y. Inventory No. 224				5. TYPE OF REPORT & PERIOD COVERED Phase I Inspection Report National Dam Safety Program	
7. AUTHOR(s) GEORGE KOCH				9. CONTRACT OR GRANT NUMBER(s) DACW51-79-C-0001	
PERFORMING ORGANIZATION NAME AND ADDRESS New York State Department of Environmental Conservation 50 Wolf Road Albany, New York 12233				10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	
17. CONTROLLING OFFICE NAME AND ADDRESS Department of the Army 26 Federal Plaza New York District, CoFE New York, New York 10287				12. REPORT DATE 14 September 1981	
18. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Department of the Army 26 Federal Plaza New York District, CoFE New York, NY 10287				11. NUMBER OF PAGES	
15. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; Distribution unlimited.				13. SECURITY CLASS. (of this report) <b>UNCLASSIFIED</b>	
				15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	

8

LEVEL

DTIC  
SELECTE  
D  
JAN 22 1982  
H.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES  
"Original contains color plates: All DTIC reproductions will be in black and white"

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)  
Dam Safety  
National Dam Safety Program  
Visual Inspection  
Hydrology, Structural Stability  
Glenmere Lake Dam  
Orange County  
Lower Hudson River Basin

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  
This report provides information and analysis on the physical condition of the dam as of the report date. Information and analysis are based on visual inspection of the dam by the performing organization.

The examination of documents and the visual inspection of Glenmere Lake Dam did not reveal conditions which constitute an immediate hazard to human life or property. However, the dam has some deficiencies which require further investigation and remedial action.

DTIC FILE COPY

*cont* Using the Corps of Engineers' "screening criteria" for the initial review of spillway adequacy, it has been determined that the embankment would be overtopped for all storms in excess of 17% of the Probable Maximum Flood (PMF). The spillway is, therefore, adjudged as "seriously inadequate" and the dam is assessed as unsafe, non-emergency.

The classification of "unsafe" applied to a dam because of a "seriously inadequate" spillway is not meant to connote the same degree of emergency as would be associated with an "unsafe" classification applied for a structural deficiency. It does mean that there appears to be a serious deficiency in spillway capacity; and if a severe storm were to occur, overtopping and failure of the dam could take place significantly increasing the hazard to loss of life downstream of the dam.

It is, therefore, recommended that within 6 months of notification to the owner, detailed hydrological/hydraulic investigation of the structure should be undertaken to more accurately determine the site specific characteristics of the watershed. The results of this investigation will determine the appropriate remedial measures which will be required to achieve a spillway capacity adequate to discharge the outflow from at least the 1/2 PMF event. In the interim, a detailed emergency action plan must be developed and implemented during unusually heavy precipitation. Around-the-clock surveillance of the structure must be provided during these periods, also remove the stoplog.

Seepage and collapsing of the downstream retaining wall warrant further investigation of the embankment. This investigation will determine the type and extent of remedial measures required.

4 LOWER HUDSON RIVER BASIN  
2 GLENMERE LAKE DAM  
5 ORANGE COUNTY, NEW YORK  
3 INVENTORY NO. N.Y. 224  
1 PHASE I INSPECTION REPORT  
NATIONAL DAM SAFETY PROGRAM



APPROVED FOR PUBLIC RELEASE;  
DISTRIBUTION UNLIMITED

NEW YORK DISTRICT CORPS OF ENGINEERS

AUGUST, 1981

## **DISCLAIMER NOTICE**

**THIS DOCUMENT IS BEST QUALITY PRACTICABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.**

PREFACE

This report is prepared under guidance contained in the Recommended Guidelines for Safety Inspection of Dams, for Phase I Investigations. Copies of these guidelines may be obtained from the Office of Chief of Engineers, Washington, D.C. 20314. The purpose of a Phase I Investigation is to identify expeditiously those dams which may pose hazards to human life or property. The assessment of the general condition of the dam is based upon available data and visual inspections. Detailed investigation, and analyses involving topographic mapping, subsurface investigations, testing, and detailed computational evaluations are beyond the scope of a Phase I Investigation; however, the investigation is intended to identify any need for such studies.

In reviewing this report, it should be realized that the reported condition of the dam is based on observations of field conditions at the time of inspection along with data available to the inspection team. In cases where the reservoir was lowered or drained prior to inspection, such action, while improving the stability and safety of the dam, removes the normal load on the structure and may obscure certain conditions which might otherwise be detectable if inspected under the normal operating environment of the structure.

It is important to note that the condition of a dam depends on numerous and constantly changing internal and external conditions, and is evolutionary in nature. It would be incorrect to assume that the present condition of the dam will continue to represent the condition of the dam at some point in the future. Only through frequent inspections can unsafe conditions be detected and only through continued care and maintenance can these conditions be prevented or corrected.

Phase I inspections are not intended to provide detailed hydrologic and hydraulic analyses. In accordance with the established Guidelines, the Spillway Test flood is based on the estimated "Probable Maximum Flood" for the region (greatest reasonably possible storm runoff), or fractions thereof. Because of the magnitude and rarity of such a storm event, a finding that a spillway will not pass the test flood should not be interpreted as necessarily posing a highly inadequate condition. The test flood provides a measure of relative spillway capacity and serves as an aide in determining the need for more detailed hydrologic and hydraulic studies, considering the size of the dam, its general condition and the downstream damage potential.

DTIC  
COPY  
INSPECTED  
1

Accession For	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
DTIC			
Distribution			
Availability			
Dist			
Avail			
Spec			
			A 23

PHASE I INSPECTION REPORT  
NATIONAL DAM SAFETY PROGRAM  
GLENMERE LAKE DAM  
I.D. NO. NY 224  
DEC NO. 179D-460  
LOWER HUDSON RIVER BASIN  
ORANGE COUNTY, N.Y.

TABLE OF CONTENTS

		<u>PAGE NO.</u>
-	ASSESSMENT	-
-	OVERVIEW PHOTOGRAPH	-
1	PROJECT INFORMATION	1
1.1	GENERAL	1
1.2	DESCRIPTION OF PROJECT	1
1.3	PERTINENT DATA	2
2	ENGINEERING DATA	3
2.1	GEOTECHNICAL DATA	3
2.2	DESIGN RECORDS	3
2.3	CONSTRUCTION RECORDS	3
2.4	OPERATION RECORD	3
2.5	EVALUATION OF DATA	3
3	VISUAL INSPECTION	4
3.1	FINDINGS	4
3.2	EVALUATION OF OBSERVATIONS	5
4	OPERATION AND MAINTENANCE PROCEDURES	6
4.1	PROCEDURES	6
4.2	MAINTENANCE OF DAM	6
4.3	WARNING SYSTEM IN EFFECT	6
4.4	EVALUATION	6



		<u>PAGE NO.</u>
5	HYDROLOGIC/HYDRAULIC	7
5.1	DRAINAGE AREA CHARACTERISTICS	7
5.2	ANALYSIS CRITERIA	7
5.3	SPILLWAY CRITERIA	7
5.4	RESERVE CAPACITY	7
5.5	FLOODS OF RECORD	7
6.6	OVERTOPPING POTENTIAL	7
5.7	EVALUATION	7
6	STRUCTURAL STABILITY	8
6.1	EVALUATION OF STRUCTURAL STABILITY	8
7	ASSESSMENT/RECOMMENDATIONS	9
7.1	ASSESSMENT	9
7.2	RECOMMENDED MEASURES	10

#### APPENDICES

- A. PHOTOGRAPHS
- B. VISUAL INSPECTION
- C. HYDROLOGIC/HYDRAULIC
- D. REFERENCES
- E. DRAWINGS

Phase I Inspection Report  
National Dam Safety Program

Name of Dam: Glenmere Lake Dam  
I.D. No. NY - 224

State Located: New York

County Located: Orange

Watershed: Lower Hudson River Basin

Stream: Browns Creek

Date of Inspection: March 31, 1981

ASSESSMENT:

The examination of documents and the visual inspection of Glenmere Lake Dam did not reveal conditions which constitute an immediate hazard to human life or property. However, the dam has some deficiencies which require further investigation and remedial action.

Using the Corps of Engineers' "screening criteria" for the initial review of spillway adequacy, it has been determined that the embankment would be overtopped for all storms in excess of 17% of the Probable Maximum Flood (PMF). The spillway is, therefore, adjudged as "seriously inadequate" and the dam is assessed as unsafe, non-emergency.


The classification of "unsafe" applied to a dam because of a "seriously inadequate" spillway is not meant to connote the same degree of emergency as would be associated with an "unsafe" classification applied for a structural deficiency. It does mean that there appears to be a serious deficiency in spillway capacity; and if a severe storm were to occur, overtopping and failure of the dam could take place significantly increasing the hazard to loss of life downstream of the dam.

It is, therefore, recommended that within 6 months of notification to the owner, detailed hydrological/hydraulic investigation of the structure should be undertaken to more accurately determine the site specific characteristics of the watershed. The results of this investigation will determine the appropriate remedial measures which will be required to achieve a spillway capacity adequate to discharge the outflow from at least the 1/2 PMF event. In the interim, a detailed emergency action plan must be developed and implemented during unusually heavy precipitation. Around-the-clock surveillance of the structure must be provided during these periods, also remove the stoplog.

Seepage and collapsing of the downstream retaining wall warrant further investigation of the embankment. This investigation will determine the type and extent of remedial measures required.


In addition, the dam has a number of problem areas which if left uncorrected have the potential for the development of hazardous conditions and must be corrected within 1 year. These areas are:

1. Collapsing portions of the retaining wall on the downstream slope of the embankment.
2. Seepage at several points on the downstream toe of the embankment.
3. Deteriorated concrete elements and joints of the spillway structure, wingwalls should be repaired and backfilled.
4. Heavy vegetation and debris in and around the spillway channel.
5. Remove the stoplog in the spillway to reduce normal pool elevation. Rip rap the upstream slope.
6. Provide a program of periodic inspection and maintenance of the dam and appurtenance. Document this information for future reference.
7. Develop the above-mentioned emergency action plan.

  
G. Koch

Chief, Dam Safety Section  
New York State Department  
of Environmental Conservation  
NY License No. 45937

Approved by:

  
Col. W.M. Smith, Jr.  
New York District Engineer

Date:

14 Sep 81



Overview - Glenmere Lake Dam

Phase I Inspection Report  
National Dam Safety Program  
Glenmere Lake Dam I.D. No. NY 224  
DEC #179D-460 Lower Hudson River Basin  
Orange County

SECTION 1: PROJECT INFORMATION

1.1 GENERAL

a. Authority

The Phase I inspection reported herein was authorized by the Department of the Army, New York District, Corps of Engineers, to fulfill the requirements of the National Dam Inspection Act, Public Law 92-367.

b. Purpose of Inspection

This inspection was conducted to evaluate the existing conditions of the dam, to identify deficiencies and hazardous conditions, to determine if these deficiencies constitute hazards to life and property, and to recommend remedial measures where required.

1.2 DESCRIPTION OF PROJECT

a. Description of Dam and Appurtenances

The Glenmere Lake Dam is a 600 feet long earth embankment with a concrete drop inlet type spillway located at the right end of the embankment. It is 24 feet high at its maximum height. The upstream slope of the embankment is rip rapped below the present water surface at a 1½ horizontal to 1 vertical. The nearly vertical downstream slope is a 5 feet thick dry stone wall. This stone wall has been replaced in one 63 feet section by a concrete wall where it had previously collapsed. The embankment also serves a town road, maintained by the Town of Chester. The spillway has a weir length of 12.4 feet by which flow passes over and into a 6.5 by 6.0 feet rectangular culvert through the embankment. There is no operational reservoir drain. The downstream channel consists of an open section of channel leading to a horseshoe culvert under another downstream embankment believed to be associated with the previous mill operation.

b. Location

The dam is located on Browns Creek, a tributary of the Wallkill River and Hudson River, approximately one mile east of the Village of Florida, New York.

c. Size

The dam is 24 feet high and impounds 2830. acre feet at normal pool elevation with flashboards. The dam is classified as "intermediate" in size.

d. Hazard Classification

The dam is classified as high hazard due to its location above several low lying homes in the area between the dam and the Village of Florida, New York. The Village of Florida is within one mile of the Glenmere Lake Dam.

e. Ownership

The dam is owned by Florida Water Works Company, which is owned and operated by Mr. Raymond Green, Florida, New York (914)651-4164.

f. Purpose of Dam

Originally the dam was built to power a mill, however, since 1892 the storage provided has been used for water supply.

g. Design and Construction History

There is no information available with regard to design or construction. From information located in the NYSDEC files, it can be ascertained that the dam is about 100 years old.

h. Normal Operating Conditions

All flows in excess of the Florida Water Works requirements are passed over the uncontrolled spillway. A reservoir drain could not be located.

1.3 PERTINENT DATA

a. Drainage Area (sq. mi.)

2.40

b. Elevations (ft. USGS Datum)

Top of Dam	534.0
Top of Stop Logs	532.55
Spillway Crest	532.0
Original Stream Channel	510.0±

c. Reservoir

Surface Area @ Spillway Crest (acres)	328.0
Storage @ Top of Dam (acre feet)	3327.0
Storage @ Spillway Crest (acre feet)	2832.0

d. Dam

Type: Earth fill with rip rapped upstream slope and stone retaining wall downstream slope.

Length (ft.)	600.0
Height (max.; ft.)	24.0
Upstream Slope	1½H:1V
Downstream Slope	about 1H:5V
Crest Width (ft.)	23.0±

e. Spillway

Type: Drop inlet to 6.5 X 6.0 rectangular culvert through embankment.

Weir Length (ft.)	12.4
Spillway Capacity @ Top of Dam (cfs)	78.0
Reservoir Drain	None

## SECTION 2: ENGINEERING DATA

### 2.1 GEOTECHNICAL DATA

#### a. Geology

The Glenmere Lake Dam is located in the "Hudson Valley Lowlands" physiographic province of New York State. These lowland areas have gentle relief and are underlain by Ordovician shales that have been exposed by the erosion of overlying Silurian and Devonian limestones. Drainage is generally northeast towards the Hudson River.

#### b. Subsurface Investigation

The Troy-Cossayuna is the dominant association of the glacial till of the Hudson Valley (Ref. 8). No information could be found concerning site conditions during construction.

### 2.2 DESIGN RECORDS

The dam was constructed around one hundred years ago and consisted of an earth embankment protected with stone. The dam was originally used for power and intakes existed to the left of the present spillway. These intakes were blocked off at some time before 1926 when the Florida Water Works gained water rights to the lake. There are no plans or construction data available.

### 2.3 CONSTRUCTION RECORDS

There are no construction records available for Glenmere Lake Dam.

### 2.4 OPERATION RECORD

There are no operating records available.

### 2.5 EVALUATION OF DATA

The data presented in this report is compiled from information contained in the files of the Department of Environmental Conservation and from data gained from the visual inspection. This information appears to be adequate and reliable for Phase I inspection purposes.

## SECTION 3: VISUAL INSPECTION

### 3.1 FINDINGS

#### a. General

Visual inspection of the Glenmere Lake Dam and surrounding watershed was conducted on March 31, 1981. The weather was partially cloudy and the temperature ranged in the fifties. The reservoir water surface was at the top of the stoplogs. There was a higher draw of water than normal due to the emergency diversion of water to the Village of Goshen (Photo #2).

#### b. Dam

The earth embankment shows signs of distress which require further investigation to determine the severity of the problem areas. The upstream slope was found to be very irregular with some areas of movement as evidenced by the guard rails and shoreline (Photo #1). The dam has a town road running along its crest, and the shoulders of the road are showing signs of erosion and general wear from vehicular traffic (Photo #2). From the left abutment (Photo #7), there is local drainage running along the toe of the embankment; the pipeline to Goshen is leaking at the chlorination house. The downstream slope is caving in almost the entire length of the dam (Photos #9, 10, and 11). Seepage is emanating at several points along the downstream slope creating the sloughing and movement of the wall (Photo #8).

#### c. Seepage

Seepage was observed emanating from several points. The two major point seepages are located approximately 150 feet from the chlorination house and adjacent to the concrete retaining wall. The seepage totalled about 5 gallons per minute. This combined with the pipeline leakage to form the flow along the toe of the embankment. The flow did not appear to be carrying fines; however, the failure of the stone retaining walls warrants investigation into the seepage.

#### d. Spillway

The concrete drop inlet spillway is in fair condition. The concrete box culvert is in need of repair, joints should be cleaned and recaulked, cracks patched, and wingwalls repaired and back-filled. (Photos #4 and 5). The downstream channel is full of debris, which could block the horseshoe culvert diverting flow along the toe of the embankment (Photo #6).

#### e. Reservoir Drain

Besides the water supply draw off the only visible drain was an 8 inch pipe through the spillway wall, however, no control could be located.

#### f. Downstream Channel

The downstream channel is confined to a horseshoe culvert just downstream of the culvert through the embankment (Photo #6). There is heavy vegetation and debris in and around the channel. Upon exiting the horseshoe culvert, the channel takes a natural course which is well defined with steep side slopes.



g. Reservoir

There are no visible signs of instability around the reservoir. The lake formed by the dam is rather shallow as are the banks surrounding it.

3.2 EVALUATION

Significant conditions were observed which require investigation to determine what remedial action is required to insure the stability of the dam and appurtenances. The following is a summary of the problem areas encountered with appropriate recommended action:

1. The movement of guard rails and collapsing of portions of the wall indicate that movement of both upstream and downstream slopes has occurred. These areas should be monitored at bi-weekly intervals to ascertain if any ongoing movement is occurring. These areas must be repaired or replaced.
2. Seepage which was observed at several points along the toe of the embankment should be monitored at bi-weekly intervals with the aid of weirs. If the flow rate increases significantly or the migration of fines occurs, immediate remedial measures will be required to control this seepage.
3. The concrete elements of the spillway are cracked, and the joints are deteriorated. Repair all deteriorated areas during low flow periods and recaulk joints. The wingwalls should be repaired and backfilled.
4. Considerable vegetation was observed growing on the downstream slope around the spillway channel which is filled with vegetation and debris. Both vegetation and debris should be removed.

## SECTION 4: OPERATION AND MAINTENANCE PROCEDURE

### 4.1 PROCEDURES

The normal water surface elevation is approximated by the top of the slopes on the uncontrolled overflow spillway. The only other draw off from the reservoir is to the Florida Water Works Company.

### 4.2 MAINTENANCE OF THE DAM

The dam is maintained by the Florida Water Works Company; the roadway is maintained by the Town of Chester. Maintenance of the dam is not considered satisfactory as evidenced by the erosion of the upstream slope and crest, collapse of much of the retaining wall and overall deterioration of the spillway structures.

### 4.3 WARNING SYSTEM

There is no warning system in effect or in preparation.

### 4.4 EVALUATION

The dam and appurtenances have not been maintained in satisfactory condition as noted in "Section 3: Visual Inspection."

## SECTION 5: HYDROLOGIC/HYDRAULIC

### 5.1 DRAINAGE AREA CHARACTERISTICS

Glenmere Lake Dam is located on Browns Creek, about one mile east of the Village of Florida, Orange County, New York. The total drainage area is 2.40 square miles. The basin was broken into two sub-basins; one is 0.51 square miles, which is the surface area of the lake itself, and the other is 1.89 square miles which has rather mild slopes interspersed by scattered ponds.

### 5.2 ANALYSIS CRITERIA

The analysis of the spillway capacity of the dam and storage of the reservoir was performed using the Corps of Engineers HEC-1 computer program incorporating the "Snyder Synthetic Unit Hydrograph" method and the "Modified Puls" flood routing procedure. The floods selected for analysis were the PMF and 1/2 the PMF in accordance with the recommended guidelines of the Corps of Engineers.

### 5.3 SPILLWAY CAPACITY

The spillway has a capacity of 78 cfs. For 1/2 the PMF, the peak inflow will be 2406 cfs and the peak outflow will be 1182 cfs. During this event, the dam will be overtopped by 0.65 foot of water. For the PMF, the peak inflow will be 4812 cfs and the peak outflow will be 3029 cfs. During this event, the dam will be overtopped by 1.29 feet of water.

### 5.4 RESERVOIR CAPACITY

Capacity to normal water elevation is 2830 acre feet. Surge storage to top of dam is an additional 542 acre feet creating a total storage of 3372 acre feet. The surge storage between spillway and dam crests is equivalent to 4.23 inches of runoff.

### 5.5 FLOODS OF RECORD

No records of past floods for Browns Creek are available.

### 5.6 OVERTOPPING POTENTIAL

The analysis indicates the embankment will be overtopped during all storms in excess of 17% of the PMF. A storm equal to 1/2 the PMF will cause overtopping of the embankment by about 0.65 foot of water, whereas, the PMF is expected to cause overtopping by 1.29 feet.

### 5.7 EVALUATION

The spillway is inadequate to pass the floods exceeding 17% of the PMF. The spillway, therefore, is adjudged as "seriously inadequate", and the dam is assessed as unsafe, non-emergency.

## SECTION 6: STRUCTURAL STABILITY

### 6.1 EVALUATION OF STRUCTURAL STABILITY

#### a. Visual Observation

Signs of distress, significant enough to warrant further investigation, were found along the retaining wall, downstream slope of the embankment. Collapsing of the stone wall, movement of the guard rails, and seepage emanating from several points along the toe warrant this investigation.

#### b. Design and Construction Data

No information could be located regarding the structural stability of the structure.

#### c. Operation Records

No operating problems which would affect the stability of the dam were found. However, removal of the 0.55 foot stoplog would reduce the possibility of overtopping by wave run up somewhat.

#### d. Post Construction Changes

Since the original construction, which was for power to an adjacent mill, some changes have occurred. Information taken from the NYS Department of Environmental Conservation files shows that these changes were the present spillway and the blocking off of intakes to the mill.

#### e. Seismic Stability

Glenmere Lake Dam is located in Seismic Zone 1, therefore, no seismic analysis was performed.

## SECTION 7: ASSESSMENT/RECOMMENDATIONS

### 7.1 ASSESSMENT

#### a. Safety

The Phase I Inspection of Glenmere Lake Dam revealed that the spillway is "seriously inadequate," based upon the Corps of Engineers screening criteria; the outflows from any storm in excess of 17% of the PMF will overtop the dam. This overtopping could cause breaching of the dam, and the resulting flood wave would significantly increase the hazard to downstream residents. For these reasons, the dam has been assessed as unsafe, non-emergency.

In addition, the dam has a number of problem areas which if left uncorrected, have the potential for the development of hazardous conditions. These areas are:

1. Collapsing portions of the retaining wall on the downstream slope of the embankment.
2. Seepage at several points on the downstream toe of the embankment.
3. Deteriorated concrete elements and joints of the spillway structure. Wingwalls should be repaired and backfilled.
4. Vegetation and debris in and around the spillway channel.

#### b. Adequacy of Information

The information reviewed is considered adequate for Phase I Inspection purposes.

#### c. Need for Additional Investigations

Since the spillway is considered to be "seriously inadequate," additional hydrologic/hydraulic investigation is required to more accurately determine the site specific characteristics of the watershed. After the in-depth hydrologic/hydraulic investigation has been completed, remedial measures must be initiated to provide spillway capacity sufficient to discharge the outflow from the 1/2 PMF event. In addition, the seepage and deterioration of the embankment require further investigation of the embankment. This investigation will determine the type and extent of remedial measures required.

#### d. Urgency

The additional hydrologic/hydraulic investigation must be initiated within 6 months from the date of notification. Within 1 year of notification, remedial measures, as a result of these investigations, must be initiated with completion of the measures during the following year. In the interim, develop an emergency action plan for the notification of downstream residents and proper governmental authorities in the event of overtopping and provide round-the-clock surveillance of the dam during periods of extreme run off. The investigation of the embankment must be initiated within 6 months and remedial measures required, completed within 1 year. The other problem areas listed below must be corrected within 1 year from notification.

## 7.2 RECOMMENDED MEASURES

1. The results of the hydrologic/hydraulic investigation will determine the appropriate remedial actions for the spillway.
2. The results of the embankment investigation will determine the appropriate remedial work.
3. Monitor the downstream retaining wall at bi-weekly intervals to ascertain if a significant movement is occurring.
4. Monitor the seepage at the toe of the downstream slope at bi-weekly intervals with the aid of weirs. If flow rates increase significantly or migration of fines occurs, immediate remedial measures will be required to control this seepage.
5. Remove the stoplog in the spillway to reduce effect of wave action on the upstream slope. Rip rap the upstream slope for protection.
6. Repair all deteriorated concrete surfaces and clean and recaulk joints in spillway structure. Repair wingwalls and backfill.
7. Remove heavy vegetation and debris from downstream slope and spillway channel.
8. Provide a program of periodic inspection and maintenance of the dam and appurtenances. Document this information for future reference.
9. An emergency action plan must be developed and maintained during the life of the structure.

APPENDIX A

PHOTOGRAPHS



Photo #1 Upstream slope - Note irregularity and guard rail movement.



Photo #2 Crest of embankment. Pipeline to Goshen on right.






Photo #3 Deterioration of crest, right of spillway



Photo #4 Spillway crest. Note deterioration of concrete and construction joints.



Photo #5 Spillway culvert. Note deterioration of wingwalls and concrete.



Photo #6 Spillway channel. Note debris.



Photo #7 Embankment from left abutment




Photo #8 Seepage at toe of retaining wall.



Photo #9 Downstream slope. Note movement of guard rails and wall.



Photo #10. Collapse of retaining wall.




Photo #11. Collapse of wall and embankment.

APPENDIX B

VISUAL INSPECTION CHECKLIST

VISUAL INSPECTION CHECKLIST1) Basic Data

## a. General

Name of Dam GLENMERE LAKE DAM  
 Fed. I.D. # NY 224 DEC Dam No. 179D-460  
 River Basin LOWER HUDSON  
 Location: Town CHESTER County ORANGE  
 Stream Name BROWN'S CREEK  
 Tributary of WALKILL RIVER  
 Latitude (N) 41°20.4' Longitude (W) 74°21.9'  
 Type of Dam EARTH EMBANKMENT / MASONRY DOWNSTREAM SLOPE  
 Hazard Category high - "C"  
 Date(s) of Inspection MARCH 31, 1981  
 Weather Conditions cloudy - 50's.  
 Reservoir Level at Time of Inspection top of stop log

b. Inspection Personnel Robert Durrin, JAMIE VEITCH

c. Persons Contacted (Including Address & Phone No.) \_\_\_\_\_

John C. Harter, Mayor & Dan Kimiecik, Trustee

Village of Florida, Inc.

FLORIDA NY

(914) 651-7815

## d. History:

Date Constructed ~ 1880 Date(s) Reconstructed 1926

Designer UNKNOWN

Constructed By UNKNOWN

Owner FLORIDA WATER WORKS ; Mr. Ray Green

2) Embankment

a. Characteristics

- (1) Embankment Material earth, stone wall (downstream slope)
- (2) Cutoff Type UNKNOWN
- (3) Impervious Core UNKNOWN
- (4) Internal Drainage System ONLY IN CONCRETE SECTION OR RETAINING WALL
- (5) Miscellaneous \_\_\_\_\_

b. Crest

- (1) Vertical Alignment FAIR
- (2) Horizontal Alignment GOOD
- (3) Surface Cracks NONE
- (4) Miscellaneous CREST ROUNDED, WAVE EROSION ON UPSTREAM SLOPE, RUNOFF, vehicular wear crading downstream edge of crest.

c. Upstream Slope

- (1) Slope (Estimate) (V:H) 1: 1 1/2
- (2) Undesirable Growth or Debris, Animal Burrows None
- (3) Sloughing, Subsidence or Depressions EROSION CAUSED BY WAVE ACTION



(4) Slope Protection rip rap & some concrete - broken  
up

(5) Surface Cracks or Movement at Toe       

d. Downstream Slope

(1) Slope (Estimate - V:H) nearly vertical

(2) Undesirable Growth or Debris, Animal Burrows heavy brush  
and tree

(3) Sloughing, Subsidence or Depressions wall collapsing in  
several spots along dam

(4) Surface Cracks or Movement at Toe sloughing & collapsing  
along d/s toe

(5) Seepage several points of seepage

(6) External Drainage System (Ditches, Trenches; Blanket)         
trench along toe for local drainage - block  
w/ leaves, silt, debris

(7) Condition Around Outlet Structure filled with debris

(8) Seepage Beyond Toe NO

e. Abutments - Embankment Contact

seepage, debris, sloughing

93-15-3(9/80)

(1) Erosion at Contact No

(2) Seepage Along Contact YES

3) Drainage System

a. Description of System only from concrete portion of retaining wall

b. Condition of System -

c. Discharge from Drainage System dripping

4) Instrumentation (Monumentation/Surveys, Observation Wells, Weirs, Piezometers, Etc.)

None

5) Reservoir

- a. Slopes shallow
- b. Sedimentation NO APPARENT PROBLEM
- c. Unusual Conditions Which Affect Dam None

6) Area Downstream of Dam

- a. Downstream Hazard (No. of Homes, Highways, etc.) roadway ACROSS crest of DAM, several home d/s at another rd. crossing
- b. Seepage, Unusual Growth —
- c. Evidence of Movement Beyond Toe of Dam —
- d. Condition of Downstream Channel heavily treed, debris-

7) Spillway(s) (Including Discharge Conveyance Channel)

- a. General drop inlet, 1-6" stoplog
- b. Condition of Service Spillway concrete joints deteriorated, spalling

c. Condition of Auxiliary Spillway \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

d. Condition of Discharge Conveyance Channel *filled with debris -*  
*channel walls collapsing, downstream wingwall*  
*deteriorated, erosion along wing walls*  
 \_\_\_\_\_  
 \_\_\_\_\_

8) Reservoir Drain/Outlet *NA*

Type: Pipe \_\_\_\_\_ Conduit \_\_\_\_\_ Other \_\_\_\_\_

Material: Concrete \_\_\_\_\_ Metal \_\_\_\_\_ Other \_\_\_\_\_

Size: \_\_\_\_\_ Length \_\_\_\_\_

Invert Elevations: Entrance \_\_\_\_\_ Exit \_\_\_\_\_

Physical Condition (Describe): \_\_\_\_\_ Unobservable \_\_\_\_\_

Material: \_\_\_\_\_

Joints: \_\_\_\_\_ Alignment \_\_\_\_\_

Structural Integrity: \_\_\_\_\_

Hydraulic Capability: \_\_\_\_\_

Means of Control: Gate \_\_\_\_\_ Valve \_\_\_\_\_ Uncontrolled \_\_\_\_\_

Operation: Operable \_\_\_\_\_ Inoperable \_\_\_\_\_ Other \_\_\_\_\_

Present Condition (Describe): \_\_\_\_\_

\_\_\_\_\_

9) Structural

a. Concrete Surfaces                     

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

b. Structural Cracking                     

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

c. Movement - Horizontal & Vertical Alignment (Settlement)                     

*retaining wall collapsing entire length*

d. Junctions with Abutments or Embankments                     

*fair*

e. Drains - Foundation, Joint, Face                     

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

f. Water Passages, Conduits, Sluices                     

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

g. Seepage or Leakage                     

*seepage at several points at toe from retaining wall (causing sloughing)*

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

- h. Joints - Construction, etc. Joints in drop inlet and tunnel deteriorated
- i. Foundation APPARENTLY O.K.
- j. Abutments GOOD
- k. Control Gates NONE
- l. Approach & Outlet Channels APPROACH OKAY - OUTLET FULL OF DEBRIS
- m. Energy Dissipators (Plunge Pool, etc.) \_\_\_\_\_
- n. Intake Structures NONE
- o. Stability APPARENTLY GOOD, EXCEPT FOR RETAINING WALL WHICH
- p. Miscellaneous \_\_\_\_\_

10) Appurtenant Structures (Power House, Lock, Gatehouse, Other)

a. Description and Condition SMALL PUMP HOUSE AND  
chlorination building fair condition -  
at time of inspection there WAS A diversion  
pipeline to the village of GOSHEN

11) Operation Procedures (Lake Level Regulation):

one stoplog in place @ time of inspection -  
possible to add more.

APPENDIX C


HYDROLOGIC / HYDRAULIC

ENGINEERING DATA AND COMPUTATIONS



46 0782

K&E 10 X 10 TO THE INCH • 7 X 10 INCHES  
KEUFFEL & ESSER CO. MADE IN U.S.A.



GENETTE LAKE  
WARWICK NY USGS QUAD.  
1:25000

GLENMERE LAKE

DRAINAGE AREA :  $16.76 \frac{(24000)^2}{144(43560)} = 1539.0 \text{ ACRES}$   
 From USGS quad.  $= 2.40 \text{ mi.}^2$

POND AREA:  $3.57 (") = 327.8 \text{ ACRES @ } 532$   
 $= 0.51 \text{ mi.}^2$

$4.56 (") = 418.7 \text{ ACRES @ } 540$

$5.96 (") = 547.2 \text{ ACRES @ } 560$

EL.	AREA	AREA	Vol.	$\Sigma$ Vol
508	0	0	0	0
			$\frac{1}{3}Ah = \text{Vol}$	
532	328			2624
540	419	379	2992	5616
560	547	483	9660	15276

Height. approximately 24 feet high at its highest  
 full location.

Glenmere Lake

Spillway Capacity 539.0 ← TOP OF DAM →

ELEVATION 532.0

WEIR LENGTH = 12.4'

ASSUME FLASHBOARDS REMAINS INTACT

ASSUME C = 3.6 sharp crested

EL	H	C	Q
532.55	0	3.6	0.0
533.0	0.45	3.6	13.5
533.55	1.0	3.6	44.6
534.0	1.45	3.6	77.9
534.55	2.0	3.6	126.3
535.0	2.45	3.6	171.2

STEEP SLOPE  
( > CRITICAL )

PRECIPITATION

Σ PMP " = 21.5 "

DUR.	6	12	24	48
%	111	123	133	142

DRAINAGE AREA = 2.40 mi.<sup>2</sup>

$$L = 9.9 \left( \frac{21000}{12(5280)} \right) = 3.75 \text{ mi} \quad C_t = 2.0$$

$$L_{ca} = 5.9 (x) = 2.05 \text{ mi.} \quad C_p = .625$$

$$t_p = C_t (L \times L_{ca})^{0.3} = 2. (3.75 \times 2.05)^{0.3} = 3.69 \text{ hr.}$$

$$t_r = \frac{t_p}{5.5} = .67 \text{ hr} = 40 \text{ MIN.} \quad \text{USE } 30 \text{ MIN.}$$

$$T_p = t_p + 0.25(t_r - t_p) = 3.69 + .25(.9 - .67) = 3.65 \text{ HR.}$$

Glenmere LAKE

TRANSPOSITION FACTOR

$$TF = 1 - \frac{0.3008}{(DA)^{0.17718}} = 1 - \frac{0.3008}{(2.4)^{0.17718}} = 0.742$$

ANALYZE FOR TWO BASINS

POND AREA - DIRECT INPUT NO LOSS

UPPER AREA - LAGGED w/ LOSS of 1" INITIAL  
0.1" / hr

UPPER AREA

$$t_r = 30 \text{ MIN.}$$

$$\text{SNYDER U.H. } T_p = 3.65$$

$$C_p = 0.625$$

$$D.A. = 1.89 \text{ MI.}^2$$

POND AREA

$$t_r = 30 \text{ MIN.}$$

$$\text{INPUT U.H.} = \frac{A(1")}{30 \text{ MIN.}} = \frac{(51)(640)(43560)(1") \frac{1 \text{ hr}}{12}}{(30 \text{ MIN.}) 60 \frac{\text{s}}{\text{min.}}} = 658 \text{ cfs}$$

$$D.A. = 0.51 \text{ MI.}^2$$

CHECK LIST FOR DAMS  
HYDROLOGIC AND HYDRAULIC  
ENGINEERING DATA

1

AREA-CAPACITY DATA:

	<u>Elevation</u> (ft.)	<u>Surface Area</u> (acres)	<u>Storage Capacity</u> (acre-ft.)
1) Top of Dam	<u>534.0</u>	<u>351</u>	<u>3372</u>
2) Design High Water (Max. Design Pool)	<u>-</u>	<u>-</u>	<u>-</u>
3) Auxiliary Spillway Crest	<u>-</u>	<u>-</u>	<u>-</u>
4) Pool Level with Flashboards	<u>532.55</u>	<u>334</u>	<u>2830</u>
5) Service Spillway Crest	<u>532.55</u>	<u>334</u>	<u>2830</u>

DISCHARGES

	<u>Volume</u> (cfs)
1) Average Daily	<u>                    </u>
2) Spillway @ Maximum High Water	<u>78</u>
3) Spillway @ Design High Water	<u>NA</u>
4) Spillway @ Auxiliary Spillway Crest Elevation	<u>-</u>
5) Low Level Outlet	<u>-</u>
6) Total (of all facilities) @ Maximum High Water	<u>78</u>
7) Maximum Known Flood	<u>NA</u>
8) At Time of Inspection	<u>None</u>

CREST:

ELEVATION: \_\_\_\_\_

Type: Compacted earth. upstream face of dry stone wall

Width: 5' Length: 600'

Spillover \_\_\_\_\_

Location \_\_\_\_\_

SPILLWAY:

SERVICE

AUXILIARY

532.55' Elevation \_\_\_\_\_

Drop Inlet Type \_\_\_\_\_

12.4' Width \_\_\_\_\_

Type of Control

Uncontrolled \_\_\_\_\_

Controlled:

Flashboards Type \_\_\_\_\_  
(Flashboards; gate)

Number \_\_\_\_\_

0.55' high Size/Length \_\_\_\_\_

Invert Material \_\_\_\_\_

Anticipated Length  
of operating service \_\_\_\_\_

Chute Length \_\_\_\_\_

Height Between Spillway Crest  
& Approach Channel Invert  
(Weir Flow) \_\_\_\_\_

HYDROMETEROLOGICAL GAGES:

Type : None

Location: \_\_\_\_\_

Records:

Date - \_\_\_\_\_

Max. Reading - \_\_\_\_\_

FLOOD WATER CONTROL SYSTEM:

Warning System: None

Method of Controlled Releases (mechanisms):

None

DRAINAGE AREA: 2.40 mi.<sup>2</sup>

DRAINAGE BASIN RUNOFF CHARACTERISTICS:

Land Use - Type: Woods, open field, some residential development.

Terrain - Relief: Upper area - mild slope. Lower area - Pond

Surface - Soil: Silurian and Devonian limestones

Runoff Potential (existing or planned extensive alterations to existing (surface or subsurface conditions))

No alterations planned or anticipated

Potential Sedimentation problem areas (natural or man-made; present or future)

None evident

Potential Backwater problem areas for levels at maximum storage capacity including surcharge storage:

Several low lying homes downstream of the dam

Dikes - Floodwalls (overflow & non-overflow) - Low reaches along the Reservoir perimeter:

Location: None

Elevation: \_\_\_\_\_

Reservoir:

Length @ Maximum Pool \_\_\_\_\_ (Miles)

Length of Shoreline (@ Spillway Crest) \_\_\_\_\_ (Miles)



NEW YORK STATE  
 DEPT OF ENVIRONMENTAL CONSERVATION  
 FLOOD PROTECTION BUREAU

FLOOD HYDROGRAPH PACKAGE (HEC-1)  
 DAM SAFETY VERSION JULY 1978  
 LAST MODIFICATION 26 FEB 79  
 MODIFIED FOR HONEYWELL APR 79

A1 CLEWERE LAKE DPK  
 A2 PHASE I INSPECTION  
 A3 PAY 1981

1	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0
21	0	0	0	0	0	0	0
22	0	0	0	0	0	0	0
23	0	0	0	0	0	0	0
24	0	0	0	0	0	0	0
25	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0
27	0	0	0	0	0	0	0
28	0	0	0	0	0	0	0
29	0	0	0	0	0	0	0
30	0	0	0	0	0	0	0

11	25	2024	1610	10770
12	30	2024	1540	56.0
13	35	2024	1470	0.0
14	40	2024	1400	0.0
15	45	2024	1330	0.0
16	50	2024	1260	0.0
17	55	2024	1190	0.0
18	60	2024	1120	0.0
19	65	2024	1050	0.0
20	70	2024	980	0.0

1998

NO. 3014 (1) SURFACE OF STREAM NETWORK CALCULATIONS

INLET HYDROGRAPH AT 1  
INLET HYDROGRAPH AT 1  
CONCENTRATION HYDROGRAPHS AT 1  
ROUTE IN ORDER TO 1  
END OF RUN

.....  
 LA FUNK BIRTH  
 TYPE OF CERTIFICATE BEING FOR INFORMATION  
 FLOOD PROTECTION BOARD  
 .....

.....  
 LA FUNK BIRTH  
 TYPE OF CERTIFICATE BEING FOR INFORMATION  
 FLOOD PROTECTION BOARD  
 .....

.....  
 LA FUNK BIRTH  
 TYPE OF CERTIFICATE BEING FOR INFORMATION  
 FLOOD PROTECTION BOARD  
 .....

.....  
 LA FUNK BIRTH  
 TYPE OF CERTIFICATE BEING FOR INFORMATION  
 FLOOD PROTECTION BOARD  
 .....

.....  
 LA FUNK BIRTH  
 TYPE OF CERTIFICATE BEING FOR INFORMATION  
 FLOOD PROTECTION BOARD  
 .....

.....  
 LA FUNK BIRTH  
 TYPE OF CERTIFICATE BEING FOR INFORMATION  
 FLOOD PROTECTION BOARD  
 .....

.....  
 LA FUNK BIRTH  
 TYPE OF CERTIFICATE BEING FOR INFORMATION  
 FLOOD PROTECTION BOARD  
 .....

.....  
 LA FUNK BIRTH  
 TYPE OF CERTIFICATE BEING FOR INFORMATION  
 FLOOD PROTECTION BOARD  
 .....

.....  
 LA FUNK BIRTH  
 TYPE OF CERTIFICATE BEING FOR INFORMATION  
 FLOOD PROTECTION BOARD  
 .....

.....  
 LA FUNK BIRTH  
 TYPE OF CERTIFICATE BEING FOR INFORMATION  
 FLOOD PROTECTION BOARD  
 .....

.....  
 LA FUNK BIRTH  
 TYPE OF CERTIFICATE BEING FOR INFORMATION  
 FLOOD PROTECTION BOARD  
 .....











This image shows a page with a grid of small dots. The grid consists of 10 columns and 20 rows. The dots are arranged in a regular pattern, forming a grid that covers most of the page. The page is otherwise blank, with a thick black border around the edges.





AC-FT  
INCHES CU M

711. 1589. 1999. 1829.  
877. 1452. 2216. 2241.

HYDROGRAPH AT STA 1 FOR PLAN 1, RTIO 5

	3.	5.	3.	3.	3.	3.	3.	3.	3.	3.
3.	3.	3.	3.	3.	3.	3.	3.	3.	3.	3.
5.	5.	5.	5.	5.	5.	5.	5.	5.	5.	5.
3.	3.	3.	3.	3.	3.	3.	3.	3.	3.	3.
3.	3.	3.	3.	3.	3.	3.	3.	3.	3.	3.
3.	3.	3.	3.	3.	3.	3.	3.	3.	3.	3.
28.	21.	18.	16.	14.	12.	10.	8.	7.	6.	5.
7.	5.	4.	3.	2.	1.	1.	1.	1.	1.	1.
19.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
12.	10.	8.	6.	4.	3.	2.	1.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.

PEAK  
CFS 271.  
CMS 67.  
INCHES 9.91  
15.69  
M4 238.78 394.44 25.74  
AC-FT 9.08 1583. 603.10  
INCHES CU M 1167. 1490. 2397. 2311.

6-HOUR 1912.  
24-HOUR 797.  
72-HOUR 402.  
TOTAL VOLUME 34238.

AC-FT  
INCHES CU M

711. 1589. 1999. 1829.  
877. 1452. 2216. 2241.

HYDROGRAPH AT STA 1 FOR PLAN 2, RTIO 6

	3.	5.	3.	3.	3.	3.	3.	3.	3.	3.
3.	3.	3.	3.	3.	3.	3.	3.	3.	3.	3.
5.	5.	5.	5.	5.	5.	5.	5.	5.	5.	5.
3.	3.	3.	3.	3.	3.	3.	3.	3.	3.	3.
3.	3.	3.	3.	3.	3.	3.	3.	3.	3.	3.
3.	3.	3.	3.	3.	3.	3.	3.	3.	3.	3.
28.	21.	18.	16.	14.	12.	10.	8.	7.	6.	5.
7.	5.	4.	3.	2.	1.	1.	1.	1.	1.	1.
19.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
12.	10.	8.	6.	4.	3.	2.	1.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.
15.	12.	10.	8.	6.	4.	3.	2.	1.	1.	1.
17.	15.	12.	9.	7.	5.	4.	3.	2.	1.	1.

PEAK  
CFS 294.  
CMS 84.  
INCHES 11.76  
19.61  
M4 238.78 394.44 25.74  
AC-FT 9.08 1583. 603.10  
INCHES CU M 1167. 1490. 2397. 2311.

6-HOUR 2390.  
24-HOUR 995.  
72-HOUR 501.  
TOTAL VOLUME 72747.

THOUS CU M  
 AC-FT  
 PM  
 258.75 988.00 753.48 753.75  
 11.05 1975. 2930. 2014.  
 1462. 2437. 3683. 3719.

\*\*\*\*\*

SUB-AREA RUNOFF COMPUTATION

DIRECT INFLOW TO RESERVOIR FROM RAINFALL

ISTAT ICCP IICCN IIAPE JPLI JPRT IIRME ISTATE IAUIG  
 1 0 0 0 1 0 1 0 0 0

HYDROGRAPH DATA  
 IHYDG IUMG IAFSA SIAP IADGA IASPC RATIO ISEDM ISEME LOCAL  
 1 -1 0.51 0. 0.51 0. 0. 0. 0. 0. 0. 0.

PRECIP DATA  
 SPTS PFS PW R24 R72 R96  
 0. 21.50 111.00 123.00 133.00 142.00 0. 0.

PROPC COMPUTED BY THE PROGRAM IS 0.480

LOSS DATA  
 LROPI STRAN SLEAK PFIPL FRAIN STNKS RILCK CYRIL CYSIL ALSXK AYLDP  
 0 0. 0. 1.00 0. 0. 1.00 0. 0. 0. 0. 0. 0.

GIVEN UNIT GRAPH, NUMBER 1

CSH.

UNIT GRAPH TOTALS 658. CFS OR 1.00 INCHES OVER THE AREA

RECESSION DATA

PERIOD	HR-DA	EXCS	LOSS	END-JF-COMP 0	MC-DA	HR-DA	PERIOD	RAIN	EXCS	LOSS	COMP 0
1	0-00	0.00	0.00	0.	1-03	2-00	101	0.	0.	0.	0.
2	0-00	0.00	0.	0.	1-03	3-00	102	0.	0.	0.	0.
3	0-00	0.00	0.	0.	1-03	4-00	103	0.	0.	0.	0.
4	0-00	0.00	0.	0.	1-03	5-00	104	0.	0.	0.	0.
5	0-00	0.00	0.	0.	1-03	6-00	105	0.	0.	0.	0.
6	0-00	0.00	0.	0.	1-03	7-00	106	0.	0.	0.	0.
7	0-00	0.00	0.	0.	1-03	8-00	107	0.	0.	0.	0.
8	0-00	0.00	0.	0.	1-03	9-00	108	0.	0.	0.	0.
9	0-00	0.00	0.	0.	1-03	10-00	109	0.	0.	0.	0.
10	0-00	0.00	0.	0.	1-03	11-00	110	0.	0.	0.	0.
11	0-00	0.00	0.	0.	1-03	12-00	111	0.	0.	0.	0.
12	0-00	0.00	0.	0.	1-03	1-00	112	0.	0.	0.	0.
13	0-01	0.01	0.01	0.	1-03	2-00	113	0.	0.	0.	0.
14	0-01	0.01	0.01	0.	1-03	3-00	114	0.	0.	0.	0.
15	0-01	0.01	0.01	0.	1-03	4-00	115	0.	0.	0.	0.
16	0-01	0.01	0.01	0.	1-03	5-00	116	0.	0.	0.	0.
17	0-01	0.01	0.01	0.	1-03	6-00	117	0.	0.	0.	0.
18	0-01	0.01	0.01	0.	1-03	7-00	118	0.	0.	0.	0.
19	0-01	0.01	0.01	0.	1-03	8-00	119	0.	0.	0.	0.
20	0-01	0.01	0.01	0.	1-03	9-00	120	0.	0.	0.	0.
21	0-01	0.01	0.01	0.	1-03	10-00	121	0.	0.	0.	0.
22	0-01	0.01	0.01	0.	1-03	11-00	122	0.	0.	0.	0.
23	0-01	0.01	0.01	0.	1-03	12-00	123	0.	0.	0.	0.
24	0-01	0.01	0.01	0.	1-03	1-00	124	0.	0.	0.	0.

1.01	1.00	29	0.01	0.01	0.01	1.03	14.50	1.1	0.	0.	0.	363.
1.01	1.00	29	0.01	0.01	0.01	1.03	14.50	1.2	0.	0.	0.	363.
1.01	1.00	27	0.04	0.04	0.	1.03	15.50	1.27	0.	0.	0.	363.
1.01	1.00	24	0.08	0.08	0.	1.03	16.50	1.28	0.	0.	0.	363.
1.01	1.00	25	0.10	0.10	0.	1.03	17.50	1.25	0.	0.	0.	363.
1.01	1.00	30	0.10	0.10	0.	1.03	17.50	1.3	0.	0.	0.	363.
1.01	1.00	31	0.17	0.17	0.	1.03	17.50	1.31	0.	0.	0.	363.
1.01	1.00	32	0.27	0.27	0.	1.03	18.50	1.32	0.	0.	0.	363.
1.01	1.00	32	0.37	0.37	0.	1.03	19.50	1.33	0.	0.	0.	363.
1.01	1.00	34	0.53	0.53	0.	1.03	19.50	1.34	0.	0.	0.	363.
1.01	1.00	35	0.63	0.63	0.	1.03	19.50	1.35	0.	0.	0.	363.
1.01	1.00	30	0.17	0.17	0.	1.03	20.50	1.3	0.	0.	0.	363.
1.01	1.00	37	0.01	0.01	0.	1.04	20.50	1.37	0.	0.	0.	363.
1.01	1.00	38	0.01	0.01	0.	1.04	21.50	1.38	0.	0.	0.	363.
1.01	1.00	38	0.01	0.01	0.	1.04	21.50	1.39	0.	0.	0.	363.
1.01	1.00	39	0.01	0.01	0.	1.04	22.50	1.40	0.	0.	0.	363.
1.01	1.00	41	0.01	0.01	0.	1.04	22.50	1.41	0.	0.	0.	363.
1.01	1.00	42	0.01	0.01	0.	1.04	23.50	1.42	0.	0.	0.	363.
1.01	1.00	43	0.01	0.01	0.	1.04	23.50	1.43	0.	0.	0.	363.
1.01	1.00	44	0.01	0.01	0.	1.04	24.50	1.44	0.	0.	0.	363.
1.01	1.00	45	0.01	0.01	0.	1.04	24.50	1.45	0.	0.	0.	363.
1.01	1.00	46	0.01	0.01	0.	1.04	25.50	1.46	0.	0.	0.	363.
1.01	1.00	47	0.01	0.01	0.	1.04	25.50	1.47	0.	0.	0.	363.
1.01	1.00	48	0.01	0.01	0.	1.04	26.50	1.48	0.	0.	0.	363.
1.01	1.00	49	0.01	0.01	0.	1.04	26.50	1.49	0.	0.	0.	363.
1.01	1.00	50	0.01	0.01	0.	1.04	27.50	1.50	0.	0.	0.	363.
1.01	1.00	51	0.01	0.01	0.	1.04	27.50	1.51	0.	0.	0.	363.
1.01	1.00	52	0.01	0.01	0.	1.04	28.50	1.52	0.	0.	0.	363.
1.01	1.00	53	0.01	0.01	0.	1.04	28.50	1.53	0.	0.	0.	363.
1.01	1.00	54	0.01	0.01	0.	1.04	29.50	1.54	0.	0.	0.	363.
1.01	1.00	55	0.01	0.01	0.	1.04	29.50	1.55	0.	0.	0.	363.
1.01	1.00	56	0.01	0.01	0.	1.04	30.50	1.56	0.	0.	0.	363.
1.01	1.00	57	0.01	0.01	0.	1.04	30.50	1.57	0.	0.	0.	363.
1.01	1.00	58	0.01	0.01	0.	1.04	31.50	1.58	0.	0.	0.	363.
1.01	1.00	59	0.01	0.01	0.	1.04	31.50	1.59	0.	0.	0.	363.
1.01	1.00	60	0.01	0.01	0.	1.04	32.50	1.60	0.	0.	0.	363.
1.01	1.00	61	0.01	0.01	0.	1.04	32.50	1.61	0.	0.	0.	363.
1.01	1.00	62	0.01	0.01	0.	1.04	33.50	1.62	0.	0.	0.	363.
1.01	1.00	63	0.01	0.01	0.	1.04	33.50	1.63	0.	0.	0.	363.
1.01	1.00	64	0.01	0.01	0.	1.04	34.50	1.64	0.	0.	0.	363.
1.01	1.00	65	0.01	0.01	0.	1.04	34.50	1.65	0.	0.	0.	363.
1.01	1.00	66	0.01	0.01	0.	1.04	35.50	1.66	0.	0.	0.	363.
1.01	1.00	67	0.01	0.01	0.	1.04	35.50	1.67	0.	0.	0.	363.
1.01	1.00	68	0.01	0.01	0.	1.04	36.50	1.68	0.	0.	0.	363.
1.01	1.00	69	0.01	0.01	0.	1.04	36.50	1.69	0.	0.	0.	363.
1.01	1.00	70	0.01	0.01	0.	1.04	37.50	1.70	0.	0.	0.	363.
1.01	1.00	71	0.01	0.01	0.	1.04	37.50	1.71	0.	0.	0.	363.
1.01	1.00	72	0.01	0.01	0.	1.04	38.50	1.72	0.	0.	0.	363.
1.01	1.00	73	0.01	0.01	0.	1.04	38.50	1.73	0.	0.	0.	363.
1.01	1.00	74	0.01	0.01	0.	1.04	39.50	1.74	0.	0.	0.	363.
1.01	1.00	75	0.01	0.01	0.	1.04	39.50	1.75	0.	0.	0.	363.
1.01	1.00	76	0.01	0.01	0.	1.04	40.50	1.76	0.	0.	0.	363.
1.01	1.00	77	0.01	0.01	0.	1.04	40.50	1.77	0.	0.	0.	363.
1.01	1.00	78	0.01	0.01	0.	1.04	41.50	1.78	0.	0.	0.	363.
1.01	1.00	79	0.01	0.01	0.	1.04	41.50	1.79	0.	0.	0.	363.
1.01	1.00	80	0.01	0.01	0.	1.04	42.50	1.80	0.	0.	0.	363.
1.01	1.00	81	0.01	0.01	0.	1.04	42.50	1.81	0.	0.	0.	363.
1.01	1.00	82	0.01	0.01	0.	1.04	43.50	1.82	0.	0.	0.	363.
1.01	1.00	83	0.01	0.01	0.	1.04	43.50	1.83	0.	0.	0.	363.
1.01	1.00	84	0.01	0.01	0.	1.04	44.50	1.84	0.	0.	0.	363.
1.01	1.00	85	0.01	0.01	0.	1.04	44.50	1.85	0.	0.	0.	363.















527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.
527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.
527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.
527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.
527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.
527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.
527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.	527.

PLAN	6-HOUR	24-HOUR	72-HOUR	TOTAL VOLUME
2149.	2477.	1230.	713.	10491.
CFS		35.	20.	2033.
105.				
INCHES	9.33	18.62	52.14	53.74
MM	243.74	487.55	842.72	457.01
AC-FT	1214.	2429.	5247.	4317.
THOUS CU M	1514.	2986.	5236.	5324.

SUM OF 2 HYDROGRAPHS AT PLAY 1 HIG 5

I.	SUM OF 2 HYDROGRAPHS AT				PLAY 1 HIG 5				I.
	7.	12.	18.	7.	7.	12.	18.	7.	
7.	12.	12.	12.	12.	7.	12.	12.	12.	7.
12.	12.	12.	12.	12.	12.	12.	12.	12.	12.
18.	67.	70.	62.	68.	68.	61.	57.	59.	61.
7.	57.	54.	51.	45.	45.	43.	41.	43.	41.
51.	45.	47.	47.	49.	49.	47.	47.	50.	47.
12.	138.	140.	157.	187.	187.	181.	187.	233.	181.
207.	835.	871.	1021.	1158.	1481.	1533.	2062.	4812.	2712.
2100.	2935.	3282.	3132.	3317.	3327.	3201.	2974.	2712.	2712.
2462.	1927.	1728.	1548.	1375.	1259.	1143.	1042.	954.	954.
370.	777.	691.	559.	459.	459.	433.	457.	421.	421.
659.	659.	659.	659.	659.	659.	659.	659.	659.	659.
659.	659.	659.	659.	659.	659.	659.	659.	659.	659.
659.	659.	659.	659.	659.	659.	659.	659.	659.	659.
659.	659.	659.	659.	659.	659.	659.	659.	659.	659.
659.	659.	659.	659.	659.	659.	659.	659.	659.	659.
659.	659.	659.	659.	659.	659.	659.	659.	659.	659.
659.	659.	659.	659.	659.	659.	659.	659.	659.	659.
659.	659.	659.	659.	659.	659.	659.	659.	659.	659.
659.	659.	659.	659.	659.	659.	659.	659.	659.	659.
659.	659.	659.	659.	659.	659.	659.	659.	659.	659.
659.	659.	659.	659.	659.	659.	659.	659.	659.	659.

PLAN	6-HOUR	24-HOUR	72-HOUR	TOTAL VOLUME
4212.	3070.	1429.	693.	13014.
CFS		47.	28.	594.
136.				
INCHES	12.00	23.65	41.97	42.14
MM	304.68	600.55	1053.40	1071.27
AC-FT	1527.	3023.	5306.	5355.
THOUS CU M	1803.	3732.	5545.	6550.

HYDROGRAPH ROUTING

ROUTE THROUGH RECEIVING	ISTAQ	ICOMP	IECON	ITAPE	JPLT	JPRI	ITAME	ISTAGE	IAUTO
	1	1	0	0	2	2	1	0	0
				ROUTING DATA					
CLASS	CLASS	ASC	DESC	ISAME	ICPT	IPMP			LCYR



3401. 3402. 3403. 3404. 3405. 3406. 3407. 3408. 3409. 3410. 3411. 3412. 3413. 3414. 3415. 3416. 3417. 3418. 3419. 3420. 3421. 3422. 3423. 3424. 3425. 3426. 3427. 3428. 3429. 3430. 3431. 3432. 3433. 3434. 3435. 3436. 3437. 3438. 3439. 3440. 3441. 3442. 3443. 3444. 3445. 3446. 3447. 3448. 3449. 3450. 3451. 3452. 3453. 3454. 3455. 3456. 3457. 3458. 3459. 3460. 3461. 3462. 3463. 3464. 3465. 3466. 3467. 3468. 3469. 3470. 3471. 3472. 3473. 3474. 3475. 3476. 3477. 3478. 3479. 3480. 3481. 3482. 3483. 3484. 3485. 3486. 3487. 3488. 3489. 3490. 3491. 3492. 3493. 3494. 3495. 3496. 3497. 3498. 3499. 3500.


| STAGE | 3-HOUR | 24-HOUR | 72-HOUR | TOTAL VOLUME |
|-------|--------|---------|---------|--------------|
| 512.0 | 532.6  | 532.6   | 532.6   | 512.6        |
| 512.1 | 532.6  | 532.6   | 532.6   | 512.6        |
| 512.2 | 532.6  | 532.6   | 532.6   | 512.6        |
| 512.3 | 532.6  | 532.6   | 532.6   | 512.6        |
| 512.4 | 532.6  | 532.6   | 532.6   | 512.6        |
| 512.5 | 532.6  | 532.6   | 532.6   | 512.6        |
| 512.6 | 532.6  | 532.6   | 532.6   | 512.6        |
| 512.7 | 532.6  | 532.6   | 532.6   | 512.6        |
| 512.8 | 532.6  | 532.6   | 532.6   | 512.6        |
| 512.9 | 532.6  | 532.6   | 532.6   | 512.6        |
| 513.0 | 532.6  | 532.6   | 532.6   | 512.6        |
| 513.1 | 532.6  | 532.6   | 532.6   | 512.6        |
| 513.2 | 532.6  | 532.6   | 532.6   | 512.6        |
| 513.3 | 532.6  | 532.6   | 532.6   | 512.6        |
| 513.4 | 532.6  | 532.6   | 532.6   | 512.6        |
| 513.5 | 532.6  | 532.6   | 532.6   | 512.6        |
| 513.6 | 532.6  | 532.6   | 532.6   | 512.6        |
| 513.7 | 532.6  | 532.6   | 532.6   | 512.6        |
| 513.8 | 532.6  | 532.6   | 532.6   | 512.6        |
| 513.9 | 532.6  | 532.6   | 532.6   | 512.6        |
| 514.0 | 532.6  | 532.6   | 532.6   | 512.6        |
| 514.1 | 532.6  | 532.6   | 532.6   | 512.6        |
| 514.2 | 532.6  | 532.6   | 532.6   | 512.6        |
| 514.3 | 532.6  | 532.6   | 532.6   | 512.6        |
| 514.4 | 532.6  | 532.6   | 532.6   | 512.6        |
| 514.5 | 532.6  | 532.6   | 532.6   | 512.6        |
| 514.6 | 532.6  | 532.6   | 532.6   | 512.6        |
| 514.7 | 532.6  | 532.6   | 532.6   | 512.6        |
| 514.8 | 532.6  | 532.6   | 532.6   | 512.6        |
| 514.9 | 532.6  | 532.6   | 532.6   | 512.6        |
| 515.0 | 532.6  | 532.6   | 532.6   | 512.6        |

PEAK OUTFLOW IS 132. AT TIME 97.56 HOURS

| PEAK  | 3-HOUR | 24-HOUR | 72-HOUR | TOTAL VOLUME |
|-------|--------|---------|---------|--------------|
| 132.  | 132.   | 132.    | 132.    | 12210.       |
| 4.    | 4.     | 4.      | 4.      | 340.         |
| 0.51  | 0.51   | 0.51    | 0.51    | 3.74         |
| 12.08 | 12.08  | 12.08   | 12.08   | 103.17       |
| 63.   | 63.    | 63.     | 63.     | 503.         |
| 321.  | 321.   | 321.    | 321.    | 522.         |

STATION 1

INFLOW (I), OUTFLOW (O) AND OBSERVED FLOW (A)  
400. 300. 200. 100. 0.





1000  
2000  
3000  
4000  
5000  
6000  
7000  
8000  
9000  
10000  
11000  
12000  
13000  
14000  
15000  
16000  
17000  
18000  
19000  
20000  
21000  
22000  
23000  
24000  
25000  
26000  
27000  
28000  
29000  
30000  
31000  
32000  
33000  
34000  
35000  
36000  
37000  
38000  
39000  
40000  
41000  
42000  
43000  
44000  
45000  
46000  
47000  
48000  
49000  
50000  
51000  
52000  
53000  
54000  
55000  
56000  
57000  
58000  
59000  
60000  
61000  
62000  
63000  
64000  
65000  
66000  
67000  
68000  
69000  
70000  
71000  
72000  
73000  
74000  
75000  
76000  
77000  
78000  
79000  
80000  
81000  
82000  
83000  
84000  
85000  
86000  
87000  
88000  
89000  
90000  
91000  
92000  
93000  
94000  
95000  
96000  
97000  
98000  
99000  
100000



19-00163  
19-00164  
19-00165  
19-00166  
19-00167  
19-00168  
19-00169  
19-00170  
19-00171  
19-00172  
19-00173  
19-00174  
19-00175  
19-00176  
19-00177  
19-00178  
19-00179  
19-00180  
19-00181  
19-00182  
19-00183  
19-00184  
19-00185  
19-00186  
19-00187  
19-00188  
19-00189  
19-00190  
19-00191  
19-00192  
19-00193  
19-00194  
19-00195  
19-00196  
19-00197  
19-00198  
19-00199  
19-00200

STATION 1, PLAN 1, RATIO 2

FIND-OF-PERIOD HYDROGRAPH ORDINATES

| CUIFLOW |      | STORAGE |    |
|---------|------|---------|----|
| 0.      | 1.   | 0.      | 1. |
| 0.      | 0.   | 0.      | 0. |
| 0.      | 0.   | 0.      | 0. |
| 1.      | 1.   | 0.      | 0. |
| 2.      | 2.   | 0.      | 0. |
| 3.      | 3.   | 0.      | 0. |
| 4.      | 4.   | 0.      | 0. |
| 5.      | 5.   | 0.      | 0. |
| 6.      | 6.   | 0.      | 0. |
| 7.      | 7.   | 0.      | 0. |
| 8.      | 8.   | 0.      | 0. |
| 9.      | 9.   | 0.      | 0. |
| 10.     | 10.  | 0.      | 0. |
| 11.     | 11.  | 0.      | 0. |
| 12.     | 12.  | 0.      | 0. |
| 13.     | 13.  | 0.      | 0. |
| 14.     | 14.  | 0.      | 0. |
| 15.     | 15.  | 0.      | 0. |
| 16.     | 16.  | 0.      | 0. |
| 17.     | 17.  | 0.      | 0. |
| 18.     | 18.  | 0.      | 0. |
| 19.     | 19.  | 0.      | 0. |
| 20.     | 20.  | 0.      | 0. |
| 21.     | 21.  | 0.      | 0. |
| 22.     | 22.  | 0.      | 0. |
| 23.     | 23.  | 0.      | 0. |
| 24.     | 24.  | 0.      | 0. |
| 25.     | 25.  | 0.      | 0. |
| 26.     | 26.  | 0.      | 0. |
| 27.     | 27.  | 0.      | 0. |
| 28.     | 28.  | 0.      | 0. |
| 29.     | 29.  | 0.      | 0. |
| 30.     | 30.  | 0.      | 0. |
| 31.     | 31.  | 0.      | 0. |
| 32.     | 32.  | 0.      | 0. |
| 33.     | 33.  | 0.      | 0. |
| 34.     | 34.  | 0.      | 0. |
| 35.     | 35.  | 0.      | 0. |
| 36.     | 36.  | 0.      | 0. |
| 37.     | 37.  | 0.      | 0. |
| 38.     | 38.  | 0.      | 0. |
| 39.     | 39.  | 0.      | 0. |
| 40.     | 40.  | 0.      | 0. |
| 41.     | 41.  | 0.      | 0. |
| 42.     | 42.  | 0.      | 0. |
| 43.     | 43.  | 0.      | 0. |
| 44.     | 44.  | 0.      | 0. |
| 45.     | 45.  | 0.      | 0. |
| 46.     | 46.  | 0.      | 0. |
| 47.     | 47.  | 0.      | 0. |
| 48.     | 48.  | 0.      | 0. |
| 49.     | 49.  | 0.      | 0. |
| 50.     | 50.  | 0.      | 0. |
| 51.     | 51.  | 0.      | 0. |
| 52.     | 52.  | 0.      | 0. |
| 53.     | 53.  | 0.      | 0. |
| 54.     | 54.  | 0.      | 0. |
| 55.     | 55.  | 0.      | 0. |
| 56.     | 56.  | 0.      | 0. |
| 57.     | 57.  | 0.      | 0. |
| 58.     | 58.  | 0.      | 0. |
| 59.     | 59.  | 0.      | 0. |
| 60.     | 60.  | 0.      | 0. |
| 61.     | 61.  | 0.      | 0. |
| 62.     | 62.  | 0.      | 0. |
| 63.     | 63.  | 0.      | 0. |
| 64.     | 64.  | 0.      | 0. |
| 65.     | 65.  | 0.      | 0. |
| 66.     | 66.  | 0.      | 0. |
| 67.     | 67.  | 0.      | 0. |
| 68.     | 68.  | 0.      | 0. |
| 69.     | 69.  | 0.      | 0. |
| 70.     | 70.  | 0.      | 0. |
| 71.     | 71.  | 0.      | 0. |
| 72.     | 72.  | 0.      | 0. |
| 73.     | 73.  | 0.      | 0. |
| 74.     | 74.  | 0.      | 0. |
| 75.     | 75.  | 0.      | 0. |
| 76.     | 76.  | 0.      | 0. |
| 77.     | 77.  | 0.      | 0. |
| 78.     | 78.  | 0.      | 0. |
| 79.     | 79.  | 0.      | 0. |
| 80.     | 80.  | 0.      | 0. |
| 81.     | 81.  | 0.      | 0. |
| 82.     | 82.  | 0.      | 0. |
| 83.     | 83.  | 0.      | 0. |
| 84.     | 84.  | 0.      | 0. |
| 85.     | 85.  | 0.      | 0. |
| 86.     | 86.  | 0.      | 0. |
| 87.     | 87.  | 0.      | 0. |
| 88.     | 88.  | 0.      | 0. |
| 89.     | 89.  | 0.      | 0. |
| 90.     | 90.  | 0.      | 0. |
| 91.     | 91.  | 0.      | 0. |
| 92.     | 92.  | 0.      | 0. |
| 93.     | 93.  | 0.      | 0. |
| 94.     | 94.  | 0.      | 0. |
| 95.     | 95.  | 0.      | 0. |
| 96.     | 96.  | 0.      | 0. |
| 97.     | 97.  | 0.      | 0. |
| 98.     | 98.  | 0.      | 0. |
| 99.     | 99.  | 0.      | 0. |
| 100.    | 100. | 0.      | 0. |

| CUIFLOW |      | STORAGE |    |
|---------|------|---------|----|
| 0.      | 1.   | 0.      | 1. |
| 0.      | 0.   | 0.      | 0. |
| 0.      | 0.   | 0.      | 0. |
| 1.      | 1.   | 0.      | 0. |
| 2.      | 2.   | 0.      | 0. |
| 3.      | 3.   | 0.      | 0. |
| 4.      | 4.   | 0.      | 0. |
| 5.      | 5.   | 0.      | 0. |
| 6.      | 6.   | 0.      | 0. |
| 7.      | 7.   | 0.      | 0. |
| 8.      | 8.   | 0.      | 0. |
| 9.      | 9.   | 0.      | 0. |
| 10.     | 10.  | 0.      | 0. |
| 11.     | 11.  | 0.      | 0. |
| 12.     | 12.  | 0.      | 0. |
| 13.     | 13.  | 0.      | 0. |
| 14.     | 14.  | 0.      | 0. |
| 15.     | 15.  | 0.      | 0. |
| 16.     | 16.  | 0.      | 0. |
| 17.     | 17.  | 0.      | 0. |
| 18.     | 18.  | 0.      | 0. |
| 19.     | 19.  | 0.      | 0. |
| 20.     | 20.  | 0.      | 0. |
| 21.     | 21.  | 0.      | 0. |
| 22.     | 22.  | 0.      | 0. |
| 23.     | 23.  | 0.      | 0. |
| 24.     | 24.  | 0.      | 0. |
| 25.     | 25.  | 0.      | 0. |
| 26.     | 26.  | 0.      | 0. |
| 27.     | 27.  | 0.      | 0. |
| 28.     | 28.  | 0.      | 0. |
| 29.     | 29.  | 0.      | 0. |
| 30.     | 30.  | 0.      | 0. |
| 31.     | 31.  | 0.      | 0. |
| 32.     | 32.  | 0.      | 0. |
| 33.     | 33.  | 0.      | 0. |
| 34.     | 34.  | 0.      | 0. |
| 35.     | 35.  | 0.      | 0. |
| 36.     | 36.  | 0.      | 0. |
| 37.     | 37.  | 0.      | 0. |
| 38.     | 38.  | 0.      | 0. |
| 39.     | 39.  | 0.      | 0. |
| 40.     | 40.  | 0.      | 0. |
| 41.     | 41.  | 0.      | 0. |
| 42.     | 42.  | 0.      | 0. |
| 43.     | 43.  | 0.      | 0. |
| 44.     | 44.  | 0.      | 0. |
| 45.     | 45.  | 0.      | 0. |
| 46.     | 46.  | 0.      | 0. |
| 47.     | 47.  | 0.      | 0. |
| 48.     | 48.  | 0.      | 0. |
| 49.     | 49.  | 0.      | 0. |
| 50.     | 50.  | 0.      | 0. |
| 51.     | 51.  | 0.      | 0. |
| 52.     | 52.  | 0.      | 0. |
| 53.     | 53.  | 0.      | 0. |
| 54.     | 54.  | 0.      | 0. |
| 55.     | 55.  | 0.      | 0. |
| 56.     | 56.  | 0.      | 0. |
| 57.     | 57.  | 0.      | 0. |
| 58.     | 58.  | 0.      | 0. |
| 59.     | 59.  | 0.      | 0. |
| 60.     | 60.  | 0.      | 0. |
| 61.     | 61.  | 0.      | 0. |
| 62.     | 62.  | 0.      | 0. |
| 63.     | 63.  | 0.      | 0. |
| 64.     | 64.  | 0.      | 0. |
| 65.     | 65.  | 0.      | 0. |
| 66.     | 66.  | 0.      | 0. |
| 67.     | 67.  | 0.      | 0. |
| 68.     | 68.  | 0.      | 0. |
| 69.     | 69.  | 0.      | 0. |
| 70.     | 70.  | 0.      | 0. |
| 71.     | 71.  | 0.      | 0. |
| 72.     | 72.  | 0.      | 0. |
| 73.     | 73.  | 0.      | 0. |
| 74.     | 74.  | 0.      | 0. |
| 75.     | 75.  | 0.      | 0. |
| 76.     | 76.  | 0.      | 0. |
| 77.     | 77.  | 0.      | 0. |
| 78.     | 78.  | 0.      | 0. |
| 79.     | 79.  | 0.      | 0. |
| 80.     | 80.  | 0.      | 0. |
| 81.     | 81.  | 0.      | 0. |
| 82.     | 82.  | 0.      | 0. |
| 83.     | 83.  | 0.      | 0. |
| 84.     | 84.  | 0.      | 0. |
| 85.     | 85.  | 0.      | 0. |
| 86.     | 86.  | 0.      | 0. |
| 87.     | 87.  | 0.      | 0. |
| 88.     | 88.  | 0.      | 0. |
| 89.     | 89.  | 0.      | 0. |
| 90.     | 90.  | 0.      | 0. |
| 91.     | 91.  | 0.      | 0. |
| 92.     | 92.  | 0.      | 0. |
| 93.     | 93.  | 0.      | 0. |
| 94.     | 94.  | 0.      | 0. |
| 95.     | 95.  | 0.      | 0. |
| 96.     | 96.  | 0.      | 0. |
| 97.     | 97.  | 0.      | 0. |
| 98.     | 98.  | 0.      | 0. |
| 99.     | 99.  | 0.      | 0. |
| 100.    | 100. | 0.      | 0. |

534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2  
 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2  
 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2  
 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2  
 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2  
 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2  
 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2  
 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2  
 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2 534.2

77% AT TIME 46.00 HOURS

|               | 11.26 | 6-HOUR | 2-HOUR | 75-HOUR | TOTAL  |
|---------------|-------|--------|--------|---------|--------|
| CPS           | 71.6  | 677.   | 463.   | 251.    | 1431.  |
| CPS           | 22.   | 19.    | 11.    | 7.      | 59.    |
| INCHES        |       | 2.62   | 6.29   | 13.64   | 22.55  |
| AC-FI         |       | 58.62  | 159.71 | 309.71  | 528.04 |
| THOUS. CU. M. |       | 356.   | 309.   | 1540.   | 1925.  |
|               |       | 414.   | 992.   | 1897.   | 3303.  |



|      |   |
|------|---|
| 2850 | 1 |
| 2851 | 1 |
| 2852 | 1 |
| 2853 | 1 |
| 2854 | 1 |
| 2855 | 1 |
| 2856 | 1 |
| 2857 | 1 |
| 2858 | 1 |
| 2859 | 1 |
| 2860 | 1 |
| 2861 | 1 |
| 2862 | 1 |
| 2863 | 1 |
| 2864 | 1 |
| 2865 | 1 |
| 2866 | 1 |
| 2867 | 1 |
| 2868 | 1 |
| 2869 | 1 |
| 2870 | 1 |
| 2871 | 1 |
| 2872 | 1 |
| 2873 | 1 |
| 2874 | 1 |
| 2875 | 1 |
| 2876 | 1 |
| 2877 | 1 |
| 2878 | 1 |
| 2879 | 1 |
| 2880 | 1 |
| 2881 | 1 |
| 2882 | 1 |
| 2883 | 1 |
| 2884 | 1 |
| 2885 | 1 |
| 2886 | 1 |
| 2887 | 1 |
| 2888 | 1 |
| 2889 | 1 |
| 2890 | 1 |
| 2891 | 1 |
| 2892 | 1 |
| 2893 | 1 |
| 2894 | 1 |
| 2895 | 1 |
| 2896 | 1 |
| 2897 | 1 |
| 2898 | 1 |
| 2899 | 1 |
| 2900 | 1 |
| 2901 | 1 |
| 2902 | 1 |
| 2903 | 1 |
| 2904 | 1 |
| 2905 | 1 |
| 2906 | 1 |
| 2907 | 1 |
| 2908 | 1 |
| 2909 | 1 |
| 2910 | 1 |
| 2911 | 1 |
| 2912 | 1 |
| 2913 | 1 |
| 2914 | 1 |
| 2915 | 1 |
| 2916 | 1 |
| 2917 | 1 |
| 2918 | 1 |
| 2919 | 1 |
| 2920 | 1 |
| 2921 | 1 |
| 2922 | 1 |
| 2923 | 1 |
| 2924 | 1 |
| 2925 | 1 |
| 2926 | 1 |
| 2927 | 1 |
| 2928 | 1 |
| 2929 | 1 |
| 2930 | 1 |
| 2931 | 1 |
| 2932 | 1 |
| 2933 | 1 |
| 2934 | 1 |
| 2935 | 1 |
| 2936 | 1 |
| 2937 | 1 |
| 2938 | 1 |
| 2939 | 1 |
| 2940 | 1 |
| 2941 | 1 |
| 2942 | 1 |
| 2943 | 1 |
| 2944 | 1 |
| 2945 | 1 |
| 2946 | 1 |
| 2947 | 1 |
| 2948 | 1 |
| 2949 | 1 |
| 2950 | 1 |
| 2951 | 1 |
| 2952 | 1 |
| 2953 | 1 |
| 2954 | 1 |
| 2955 | 1 |
| 2956 | 1 |
| 2957 | 1 |
| 2958 | 1 |
| 2959 | 1 |
| 2960 | 1 |
| 2961 | 1 |
| 2962 | 1 |
| 2963 | 1 |
| 2964 | 1 |
| 2965 | 1 |
| 2966 | 1 |
| 2967 | 1 |
| 2968 | 1 |
| 2969 | 1 |
| 2970 | 1 |
| 2971 | 1 |
| 2972 | 1 |
| 2973 | 1 |
| 2974 | 1 |
| 2975 | 1 |
| 2976 | 1 |
| 2977 | 1 |
| 2978 | 1 |
| 2979 | 1 |
| 2980 | 1 |
| 2981 | 1 |
| 2982 | 1 |
| 2983 | 1 |
| 2984 | 1 |
| 2985 | 1 |
| 2986 | 1 |
| 2987 | 1 |
| 2988 | 1 |
| 2989 | 1 |
| 2990 | 1 |
| 2991 | 1 |
| 2992 | 1 |
| 2993 | 1 |
| 2994 | 1 |
| 2995 | 1 |
| 2996 | 1 |
| 2997 | 1 |
| 2998 | 1 |
| 2999 | 1 |
| 3000 | 1 |

This image shows a large grid of dotted lines on a white background. The grid consists of 10 columns and 15 rows. The lines are evenly spaced and form a rectangular pattern. The grid is used for data entry or record-keeping.

|    |    |    |    |    |    |    |    |    |     |
|----|----|----|----|----|----|----|----|----|-----|
| 1  | 2  | 3  | 4  | 5  | 6  | 7  | 8  | 9  | 10  |
| 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20  |
| 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30  |
| 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 | 39 | 40  |
| 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 | 50  |
| 51 | 52 | 53 | 54 | 55 | 56 | 57 | 58 | 59 | 60  |
| 61 | 62 | 63 | 64 | 65 | 66 | 67 | 68 | 69 | 70  |
| 71 | 72 | 73 | 74 | 75 | 76 | 77 | 78 | 79 | 80  |
| 81 | 82 | 83 | 84 | 85 | 86 | 87 | 88 | 89 | 90  |
| 91 | 92 | 93 | 94 | 95 | 96 | 97 | 98 | 99 | 100 |





|       |       |       |       |       |       |       |       |       |       |       |       |       |       |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 536.4 | 536.4 | 536.4 | 536.4 | 536.4 | 536.4 | 536.4 | 536.4 | 536.4 | 536.4 | 536.4 | 536.4 | 536.4 | 536.4 |
| 536.3 | 536.3 | 536.3 | 536.3 | 536.3 | 536.3 | 536.3 | 536.3 | 536.3 | 536.3 | 536.3 | 536.3 | 536.3 | 536.3 |
| 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 |
| 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 |
| 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 |
| 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 |
| 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 |
| 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 |
| 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 | 536.2 |

PEARL DIFFERENTIALS AT TIME 45450 HOURS

|             |        |         |         |         |       |
|-------------|--------|---------|---------|---------|-------|
| PEARL       | 6-4100 | 24-HOUR | 72-HOUR | TOTAL   | 45450 |
| 1182.       | 1017.  | 567.    | 397.    | 4970.   |       |
| CFS         | 34.    | 15.     | 10.     | 145.    |       |
| CMS         | 3.94   | 8.76    | 10.12   | 15.14   |       |
| INCHES      | 100.08 | 222.51  | 509.57  | 1079.26 |       |
| AC-FY       | 504.   | 1121.   | 2063.   | 2063.   |       |
| DRUG CO. S. | 527.   | 1333.   | 2381.   | 2381.   |       |

STATION 1

INFLOW (I), OUTFLOW (O) AND OBSERVED FLOW (A)

400. 1200. 1600. 2000. 2400. 2800. 3200. 3600. 4000. 4400. 4800. 5200. 5600. 6000. 6400. 6800. 7200. 7600. 8000. 8400. 8800. 9200. 9600. 10000.

| Time | Inflow (I) | Outflow (O) | Observed Flow (A) |
|------|------------|-------------|-------------------|
| 1    |            |             |                   |
| 2    |            |             |                   |
| 3    |            |             |                   |
| 4    |            |             |                   |
| 5    |            |             |                   |
| 6    |            |             |                   |
| 7    |            |             |                   |
| 8    |            |             |                   |
| 9    |            |             |                   |
| 10   |            |             |                   |
| 11   |            |             |                   |
| 12   |            |             |                   |
| 13   |            |             |                   |
| 14   |            |             |                   |
| 15   |            |             |                   |
| 16   |            |             |                   |
| 17   |            |             |                   |
| 18   |            |             |                   |
| 19   |            |             |                   |
| 20   |            |             |                   |
| 21   |            |             |                   |
| 22   |            |             |                   |
| 23   |            |             |                   |
| 24   |            |             |                   |
| 25   |            |             |                   |
| 26   |            |             |                   |
| 27   |            |             |                   |
| 28   |            |             |                   |
| 29   |            |             |                   |
| 30   |            |             |                   |
| 31   |            |             |                   |
| 32   |            |             |                   |
| 33   |            |             |                   |
| 34   |            |             |                   |
| 35   |            |             |                   |
| 36   |            |             |                   |
| 37   |            |             |                   |
| 38   |            |             |                   |
| 39   |            |             |                   |
| 40   |            |             |                   |
| 41   |            |             |                   |
| 42   |            |             |                   |
| 43   |            |             |                   |
| 44   |            |             |                   |
| 45   |            |             |                   |
| 46   |            |             |                   |
| 47   |            |             |                   |
| 48   |            |             |                   |
| 49   |            |             |                   |
| 50   |            |             |                   |
| 51   |            |             |                   |
| 52   |            |             |                   |
| 53   |            |             |                   |
| 54   |            |             |                   |
| 55   |            |             |                   |
| 56   |            |             |                   |
| 57   |            |             |                   |
| 58   |            |             |                   |
| 59   |            |             |                   |
| 60   |            |             |                   |
| 61   |            |             |                   |
| 62   |            |             |                   |
| 63   |            |             |                   |
| 64   |            |             |                   |
| 65   |            |             |                   |
| 66   |            |             |                   |
| 67   |            |             |                   |
| 68   |            |             |                   |
| 69   |            |             |                   |
| 70   |            |             |                   |
| 71   |            |             |                   |
| 72   |            |             |                   |
| 73   |            |             |                   |
| 74   |            |             |                   |
| 75   |            |             |                   |
| 76   |            |             |                   |
| 77   |            |             |                   |
| 78   |            |             |                   |
| 79   |            |             |                   |
| 80   |            |             |                   |
| 81   |            |             |                   |
| 82   |            |             |                   |
| 83   |            |             |                   |
| 84   |            |             |                   |
| 85   |            |             |                   |
| 86   |            |             |                   |
| 87   |            |             |                   |
| 88   |            |             |                   |
| 89   |            |             |                   |
| 90   |            |             |                   |
| 91   |            |             |                   |
| 92   |            |             |                   |
| 93   |            |             |                   |
| 94   |            |             |                   |
| 95   |            |             |                   |
| 96   |            |             |                   |
| 97   |            |             |                   |
| 98   |            |             |                   |
| 99   |            |             |                   |
| 100  |            |             |                   |

Table with multiple columns and rows, containing numerical data and some text. The table is oriented vertically on the page.

8.30 1

7.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

1.00 1

A large grid of 10 columns and 20 rows of dotted lines, intended for handwriting practice. The grid is composed of small, evenly spaced dots forming a rectangular pattern.

Handwriting practice lines at the bottom of the page, consisting of a grid of dotted lines.

|  |  |
|--|--|
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |

A series of approximately 18 vertical lines spaced evenly across the right half of the page, providing a guide for writing columns of text.

STATION 1, PLAN 1, RATIO 4

END-OF-PERIOD HYDROGRAPH ORDINATES

| INFLOW |     | STORAGE |     | STAGE |     |
|--------|-----|---------|-----|-------|-----|
| 0.     | 1.  | 0.      | 1.  | 0.    | 1.  |
| 6.     | 0.  | 0.      | 0.  | 0.    | 0.  |
| 9.     | 0.  | 0.      | 0.  | 0.    | 0.  |
| 1.     | 0.  | 1.      | 1.  | 1.    | 1.  |
| 3.     | 0.  | 2.      | 2.  | 2.    | 2.  |
| 5.     | 0.  | 3.      | 3.  | 3.    | 3.  |
| 8.     | 0.  | 4.      | 4.  | 4.    | 4.  |
| 11.    | 0.  | 5.      | 5.  | 5.    | 5.  |
| 14.    | 0.  | 6.      | 6.  | 6.    | 6.  |
| 17.    | 1.  | 7.      | 7.  | 7.    | 7.  |
| 20.    | 1.  | 8.      | 8.  | 8.    | 8.  |
| 23.    | 1.  | 9.      | 9.  | 9.    | 9.  |
| 26.    | 2.  | 10.     | 10. | 10.   | 10. |
| 29.    | 2.  | 11.     | 11. | 11.   | 11. |
| 32.    | 2.  | 12.     | 12. | 12.   | 12. |
| 35.    | 3.  | 13.     | 13. | 13.   | 13. |
| 38.    | 3.  | 14.     | 14. | 14.   | 14. |
| 41.    | 3.  | 15.     | 15. | 15.   | 15. |
| 44.    | 4.  | 16.     | 16. | 16.   | 16. |
| 47.    | 4.  | 17.     | 17. | 17.   | 17. |
| 50.    | 4.  | 18.     | 18. | 18.   | 18. |
| 53.    | 5.  | 19.     | 19. | 19.   | 19. |
| 56.    | 5.  | 20.     | 20. | 20.   | 20. |
| 59.    | 5.  | 21.     | 21. | 21.   | 21. |
| 62.    | 6.  | 22.     | 22. | 22.   | 22. |
| 65.    | 6.  | 23.     | 23. | 23.   | 23. |
| 68.    | 6.  | 24.     | 24. | 24.   | 24. |
| 71.    | 7.  | 25.     | 25. | 25.   | 25. |
| 74.    | 7.  | 26.     | 26. | 26.   | 26. |
| 77.    | 7.  | 27.     | 27. | 27.   | 27. |
| 80.    | 7.  | 28.     | 28. | 28.   | 28. |
| 83.    | 8.  | 29.     | 29. | 29.   | 29. |
| 86.    | 8.  | 30.     | 30. | 30.   | 30. |
| 89.    | 8.  | 31.     | 31. | 31.   | 31. |
| 92.    | 8.  | 32.     | 32. | 32.   | 32. |
| 95.    | 9.  | 33.     | 33. | 33.   | 33. |
| 98.    | 9.  | 34.     | 34. | 34.   | 34. |
| 101.   | 9.  | 35.     | 35. | 35.   | 35. |
| 104.   | 9.  | 36.     | 36. | 36.   | 36. |
| 107.   | 10. | 37.     | 37. | 37.   | 37. |
| 110.   | 10. | 38.     | 38. | 38.   | 38. |
| 113.   | 10. | 39.     | 39. | 39.   | 39. |
| 116.   | 10. | 40.     | 40. | 40.   | 40. |
| 119.   | 11. | 41.     | 41. | 41.   | 41. |
| 122.   | 11. | 42.     | 42. | 42.   | 42. |
| 125.   | 11. | 43.     | 43. | 43.   | 43. |
| 128.   | 11. | 44.     | 44. | 44.   | 44. |
| 131.   | 12. | 45.     | 45. | 45.   | 45. |
| 134.   | 12. | 46.     | 46. | 46.   | 46. |
| 137.   | 12. | 47.     | 47. | 47.   | 47. |
| 140.   | 12. | 48.     | 48. | 48.   | 48. |
| 143.   | 12. | 49.     | 49. | 49.   | 49. |
| 146.   | 13. | 50.     | 50. | 50.   | 50. |
| 149.   | 13. | 51.     | 51. | 51.   | 51. |
| 152.   | 13. | 52.     | 52. | 52.   | 52. |
| 155.   | 13. | 53.     | 53. | 53.   | 53. |
| 158.   | 13. | 54.     | 54. | 54.   | 54. |
| 161.   | 14. | 55.     | 55. | 55.   | 55. |
| 164.   | 14. | 56.     | 56. | 56.   | 56. |
| 167.   | 14. | 57.     | 57. | 57.   | 57. |
| 170.   | 14. | 58.     | 58. | 58.   | 58. |
| 173.   | 14. | 59.     | 59. | 59.   | 59. |
| 176.   | 15. | 60.     | 60. | 60.   | 60. |
| 179.   | 15. | 61.     | 61. | 61.   | 61. |
| 182.   | 15. | 62.     | 62. | 62.   | 62. |
| 185.   | 15. | 63.     | 63. | 63.   | 63. |
| 188.   | 15. | 64.     | 64. | 64.   | 64. |
| 191.   | 15. | 65.     | 65. | 65.   | 65. |
| 194.   | 15. | 66.     | 66. | 66.   | 66. |
| 197.   | 15. | 67.     | 67. | 67.   | 67. |
| 200.   | 15. | 68.     | 68. | 68.   | 68. |
| 203.   | 15. | 69.     | 69. | 69.   | 69. |
| 206.   | 15. | 70.     | 70. | 70.   | 70. |

| INFLOW |     | STORAGE |      | STAGE |      |
|--------|-----|---------|------|-------|------|
| 0.     | 1.  | 0.      | 1.   | 0.    | 1.   |
| 210.   | 15. | 71.     | 71.  | 71.   | 71.  |
| 213.   | 15. | 72.     | 72.  | 72.   | 72.  |
| 216.   | 15. | 73.     | 73.  | 73.   | 73.  |
| 219.   | 15. | 74.     | 74.  | 74.   | 74.  |
| 222.   | 15. | 75.     | 75.  | 75.   | 75.  |
| 225.   | 15. | 76.     | 76.  | 76.   | 76.  |
| 228.   | 15. | 77.     | 77.  | 77.   | 77.  |
| 231.   | 15. | 78.     | 78.  | 78.   | 78.  |
| 234.   | 15. | 79.     | 79.  | 79.   | 79.  |
| 237.   | 15. | 80.     | 80.  | 80.   | 80.  |
| 240.   | 15. | 81.     | 81.  | 81.   | 81.  |
| 243.   | 15. | 82.     | 82.  | 82.   | 82.  |
| 246.   | 15. | 83.     | 83.  | 83.   | 83.  |
| 249.   | 15. | 84.     | 84.  | 84.   | 84.  |
| 252.   | 15. | 85.     | 85.  | 85.   | 85.  |
| 255.   | 15. | 86.     | 86.  | 86.   | 86.  |
| 258.   | 15. | 87.     | 87.  | 87.   | 87.  |
| 261.   | 15. | 88.     | 88.  | 88.   | 88.  |
| 264.   | 15. | 89.     | 89.  | 89.   | 89.  |
| 267.   | 15. | 90.     | 90.  | 90.   | 90.  |
| 270.   | 15. | 91.     | 91.  | 91.   | 91.  |
| 273.   | 15. | 92.     | 92.  | 92.   | 92.  |
| 276.   | 15. | 93.     | 93.  | 93.   | 93.  |
| 279.   | 15. | 94.     | 94.  | 94.   | 94.  |
| 282.   | 15. | 95.     | 95.  | 95.   | 95.  |
| 285.   | 15. | 96.     | 96.  | 96.   | 96.  |
| 288.   | 15. | 97.     | 97.  | 97.   | 97.  |
| 291.   | 15. | 98.     | 98.  | 98.   | 98.  |
| 294.   | 15. | 99.     | 99.  | 99.   | 99.  |
| 297.   | 15. | 100.    | 100. | 100.  | 100. |
| 300.   | 15. | 101.    | 101. | 101.  | 101. |
| 303.   | 15. | 102.    | 102. | 102.  | 102. |
| 306.   | 15. | 103.    | 103. | 103.  | 103. |
| 309.   | 15. | 104.    | 104. | 104.  | 104. |
| 312.   | 15. | 105.    | 105. | 105.  | 105. |
| 315.   | 15. | 106.    | 106. | 106.  | 106. |
| 318.   | 15. | 107.    | 107. | 107.  | 107. |
| 321.   | 15. | 108.    | 108. | 108.  | 108. |
| 324.   | 15. | 109.    | 109. | 109.  | 109. |
| 327.   | 15. | 110.    | 110. | 110.  | 110. |
| 330.   | 15. | 111.    | 111. | 111.  | 111. |
| 333.   | 15. | 112.    | 112. | 112.  | 112. |
| 336.   | 15. | 113.    | 113. | 113.  | 113. |
| 339.   | 15. | 114.    | 114. | 114.  | 114. |
| 342.   | 15. | 115.    | 115. | 115.  | 115. |
| 345.   | 15. | 116.    | 116. | 116.  | 116. |
| 348.   | 15. | 117.    | 117. | 117.  | 117. |
| 351.   | 15. | 118.    | 118. | 118.  | 118. |
| 354.   | 15. | 119.    | 119. | 119.  | 119. |
| 357.   | 15. | 120.    | 120. | 120.  | 120. |

| INFLOW |     | STORAGE |      | STAGE |      |
|--------|-----|---------|------|-------|------|
| 0.     | 1.  | 0.      | 1.   | 0.    | 1.   |
| 360.   | 15. | 121.    | 121. | 121.  | 121. |
| 363.   | 15. | 122.    | 122. | 122.  | 122. |
| 366.   | 15. | 123.    | 123. | 123.  | 123. |
| 369.   | 15. | 124.    | 124. | 124.  | 124. |
| 372.   | 15. | 125.    | 125. | 125.  | 125. |
| 375.   | 15. | 126.    | 126. | 126.  | 126. |
| 378.   | 15. | 127.    | 127. | 127.  | 127. |
| 381.   | 15. | 128.    | 128. | 128.  | 128. |
| 384.   | 15. | 129.    | 129. | 129.  | 129. |
| 387.   | 15. | 130.    | 130. | 130.  | 130. |
| 390.   | 15. | 131.    | 131. | 131.  | 131. |
| 393.   | 15. | 132.    | 132. | 132.  | 132. |
| 396.   | 15. | 133.    | 133. | 133.  | 133. |
| 399.   | 15. | 134.    | 134. | 134.  | 134. |
| 402.   | 15. | 135.    | 135. | 135.  | 135. |
| 405.   | 15. | 136.    | 136. | 136.  | 136. |
| 408.   | 15. | 137.    | 137. | 137.  | 137. |
| 411.   | 15. | 138.    | 138. | 138.  | 138. |
| 414.   | 15. | 139.    | 139. | 139.  | 139. |
| 417.   | 15. | 140.    | 140. | 140.  | 140. |
| 420.   | 15. | 141.    | 141. | 141.  | 141. |
| 423.   | 15. | 142.    | 142. | 142.  | 142. |
| 426.   | 15. | 143.    | 143. | 143.  | 143. |
| 429.   | 15. | 144.    | 144. | 144.  | 144. |
| 432.   | 15. | 145.    | 145. | 145.  | 145. |
| 435.   | 15. | 146.    | 146. | 146.  | 146. |
| 438.   | 15. | 147.    | 147. | 147.  | 147. |
| 441.   | 15. | 148.    | 148. | 148.  | 148. |
| 444.   | 15. | 149.    | 149. | 149.  | 149. |
| 447.   | 15. | 150.    | 150. | 150.  | 150. |
| 450.   | 15. | 151.    | 151. | 151.  | 151. |
| 453.   | 15. | 152.    | 152. | 152.  | 152. |
| 456.   | 15. | 153.    | 153. | 153.  | 153. |
| 459.   | 15. | 154.    | 154. | 154.  | 154. |
| 462.   | 15. | 155.    | 155. | 155.  | 155. |
| 465.   | 15. | 156.    | 156. | 156.  | 156. |
| 468.   | 15. | 157.    | 157. | 157.  | 157. |
| 471.   | 15. | 158.    | 158. | 158.  | 158. |
| 474.   | 15. | 159.    | 159. | 159.  | 159. |
| 477.   | 15. | 160.    | 160. | 160.  | 160. |
| 480.   | 15. | 161.    | 161. | 161.  | 161. |
| 483.   | 15. | 162.    | 162. | 162.  | 162. |
| 486.   | 15. | 163.    | 163. | 163.  | 163. |
| 489.   | 15. | 164.    | 164. | 164.  | 164. |
| 492.   | 15. | 165.    | 165. | 165.  | 165. |

|       |       |       |       |       |       |       |       |       |       |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 |
| 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 |
| 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 |
| 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 |
| 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 |
| 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 |
| 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 |
| 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 |
| 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 |
| 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 | 534.3 |


PEAK FLOW IS 1576. AT 11:57 45.01 HOURS

| CF   | PEAK | 6-HOUR | 24-HOUR | 72-HOUR | TOTAL VOLUME |
|------|------|--------|---------|---------|--------------|
| 1576 | 1576 | 137.95 | 249.20  | 515.24  | 515.24       |
| 45   | 45   | 678    | 1437    | 2589    | 2589         |
|      |      | 826    | 1772    | 3189    | 3189         |



STATION 1

INFLOW (1), OUTFLOW (2) AND OBSERVED FLOW (3)  
800. 1200. 1600. 2000. 2400. 3200.



2000 00  
 2000 01  
 2000 02  
 2000 03  
 2000 04  
 2000 05  
 2000 06  
 2000 07  
 2000 08  
 2000 09  
 2000 10  
 2000 11  
 2000 12  
 2000 13  
 2000 14  
 2000 15  
 2000 16  
 2000 17  
 2000 18  
 2000 19  
 2000 20  
 2000 21  
 2000 22  
 2000 23  
 2000 24  
 2000 25  
 2000 26  
 2000 27  
 2000 28  
 2000 29  
 2000 30  
 2000 31  
 2000 32  
 2000 33  
 2000 34  
 2000 35  
 2000 36  
 2000 37  
 2000 38  
 2000 39  
 2000 40  
 2000 41  
 2000 42  
 2000 43  
 2000 44  
 2000 45  
 2000 46  
 2000 47  
 2000 48  
 2000 49  
 2000 50  
 2000 51  
 2000 52  
 2000 53  
 2000 54  
 2000 55  
 2000 56  
 2000 57  
 2000 58  
 2000 59  
 2000 60  
 2000 61  
 2000 62  
 2000 63  
 2000 64  
 2000 65  
 2000 66  
 2000 67  
 2000 68  
 2000 69  
 2000 70  
 2000 71  
 2000 72  
 2000 73  
 2000 74  
 2000 75  
 2000 76  
 2000 77  
 2000 78  
 2000 79  
 2000 80  
 2000 81  
 2000 82  
 2000 83  
 2000 84  
 2000 85  
 2000 86  
 2000 87  
 2000 88  
 2000 89  
 2000 90  
 2000 91  
 2000 92  
 2000 93  
 2000 94  
 2000 95  
 2000 96  
 2000 97  
 2000 98  
 2000 99

11.5010  
11.5011  
12.5012  
13.5013  
14.5014  
15.5015  
16.5016  
17.5017  
18.5018  
19.5019  
20.5020  
21.5021  
22.5022  
23.5023  
24.5024  
25.5025  
26.5026  
27.5027  
28.5028  
29.5029  
30.5030  
31.5031  
32.5032  
33.5033  
34.5034  
35.5035  
36.5036  
37.5037  
38.5038  
39.5039  
40.5040  
41.5041  
42.5042  
43.5043  
44.5044  
45.5045  
46.5046  
47.5047  
48.5048  
49.5049  
50.5050

00000  
10000  
20000  
30000  
40000  
50000  
60000  
70000  
80000  
90000  
00000  
10000  
20000  
30000  
40000  
50000  
60000  
70000  
80000  
90000

4



|       |       |       |       |       |       |       |       |       |       |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 536.0 | 536.0 | 536.0 | 536.0 | 536.0 | 536.0 | 536.0 | 536.0 | 536.0 | 536.0 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |

PEAK GULF LGN IS 531.7 AT TIME 14:50 HOURS

|            | FCAR   | 6-HOUR | 24-HOUR | 72-HOUR | ICAL | VOLUME |
|------------|--------|--------|---------|---------|------|--------|
| CFS        | 231.0  | 191.0  | 1041.0  | 611.0   |      | 3827.0 |
| CWC        | 56.0   | 56.0   | 29.0    | 17.0    |      | 24.0   |
| INCMS      | 7.72   | 16.14  | 28.91   | 28.91   |      | 28.91  |
| MM         | 196.12 | 409.95 | 721.63  | 721.63  |      | 721.63 |
| AC-FT      | 988.0  | 2065.0 | 3635.0  | 3635.0  |      | 3635.0 |
| THOUS CU M | 1218.0 | 2547.0 | 4483.0  | 4483.0  |      | 4483.0 |



Table with columns for numbers and binary digits (0, 1). The numbers are listed in the left column, and the corresponding binary digits are listed in the right column.

530 5

530 1

530 1

720 1

600 1

515 1

350 1

350 1

110 1

110 1

120 1

50 1

350 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1

120 1



12.5011  
13.5012  
14.5013  
15.5014  
16.5015  
17.5016  
18.5017  
19.5018  
20.5019  
21.5020  
22.5021  
23.5022  
24.5023  
25.5024  
26.5025  
27.5026  
28.5027  
29.5028  
30.5029  
31.5030  
32.5031  
33.5032  
34.5033  
35.5034  
36.5035  
37.5036  
38.5037  
39.5038  
40.5039  
41.5040  
42.5041  
43.5042  
44.5043  
45.5044  
46.5045  
47.5046  
48.5047  
49.5048  
50.5049  
51.5050  
52.5051  
53.5052  
54.5053  
55.5054  
56.5055  
57.5056  
58.5057  
59.5058  
60.5059  
61.5060  
62.5061  
63.5062  
64.5063  
65.5064  
66.5065  
67.5066  
68.5067  
69.5068  
70.5069  
71.5070  
72.5071  
73.5072  
74.5073  
75.5074  
76.5075  
77.5076  
78.5077  
79.5078  
80.5079  
81.5080  
82.5081  
83.5082  
84.5083  
85.5084  
86.5085  
87.5086  
88.5087  
89.5088  
90.5089  
91.5090  
92.5091  
93.5092  
94.5093  
95.5094  
96.5095  
97.5096  
98.5097  
99.5098  
100.5099

14.5015  
14.5016  
14.5017  
14.5018  
14.5019  
14.5020  
14.5021  
14.5022  
14.5023  
14.5024  
14.5025  
14.5026  
14.5027  
14.5028  
14.5029  
14.5030  
14.5031  
14.5032  
14.5033  
14.5034  
14.5035  
14.5036  
14.5037  
14.5038  
14.5039  
14.5040  
14.5041  
14.5042  
14.5043  
14.5044  
14.5045  
14.5046  
14.5047  
14.5048  
14.5049  
14.5050

AD-A109 898

NEW YORK STATE DEPT OF ENVIRONMENTAL CONSERVATION ALBANY F/6 13/13  
NATIONAL DAM SAFETY PROGRAM. GLENMERE LAKE DAM; (INVENTORY NUMB--ETC(U)  
SEP 81 6 KOCH DACW51-79-C-0001  
NL

UNCLASSIFIED

2.2

2.2




END

DATE

FILED

7-82

DTIC



MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A



|       |       |       |       |       |       |       |       |       |       |       |       |       |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |
| 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 | 534.4 |

PEAK CURVES IS 302% AT TIME 44.51 HOURS

|            | PEAK  | 8-HOUR | 24-HOUR | 72-HOUR | TOTAL  |
|------------|-------|--------|---------|---------|--------|
| UFS        | 2029. | 2029.  | 1360.   | 783.    | 11332. |
| CMS        | 86.   | 74.    | 39.     | 27.     | 3215.  |
| INCHES     |       | 10.17  | 21.09   | 36.63   | 36.68  |
| MM         |       | 258.44 | 535.79  | 930.10  | 931.34 |
| AC-FT      |       | 1312.  | 2694.   | 4587.   | 4533.  |
| TOTALS CUR |       | 3505.  | 3328.   | 5781.   | 5738.  |

174



6230 871  
6235 541  
6240 591  
6245 601  
6250 701  
6255 711  
6260 721  
6265 731  
6270 741  
6275 751  
6280 761  
6285 771  
6290 781  
6295 791  
6300 801  
6305 811  
6310 821  
6315 831  
6320 841  
6325 851  
6330 861  
6335 871  
6340 881  
6345 891  
6350 901  
6355 911  
6360 921  
6365 931  
6370 941  
6375 951  
6380 961  
6385 971  
6390 981  
6395 991  
6400 001  
6405 011  
6410 021  
6415 031  
6420 041  
6425 051  
6430 061  
6435 071  
6440 081  
6445 091  
6450 101  
6455 111  
6460 121  
6465 131  
6470 141  
6475 151  
6480 161  
6485 171  
6490 181  
6495 191  
6500 201  
6505 211  
6510 221  
6515 231  
6520 241  
6525 251  
6530 261  
6535 271  
6540 281  
6545 291  
6550 301  
6555 311  
6560 321  
6565 331  
6570 341  
6575 351  
6580 361  
6585 371  
6590 381  
6595 391  
6600 401  
6605 411  
6610 421  
6615 431  
6620 441  
6625 451  
6630 461  
6635 471  
6640 481  
6645 491  
6650 501  
6655 511  
6660 521  
6665 531  
6670 541  
6675 551  
6680 561  
6685 571  
6690 581  
6695 591  
6700 601  
6705 611  
6710 621  
6715 631  
6720 641  
6725 651  
6730 661  
6735 671  
6740 681  
6745 691  
6750 701  
6755 711  
6760 721  
6765 731  
6770 741  
6775 751  
6780 761  
6785 771  
6790 781  
6795 791  
6800 801  
6805 811  
6810 821  
6815 831  
6820 841  
6825 851  
6830 861  
6835 871  
6840 881  
6845 891  
6850 901  
6855 911  
6860 921  
6865 931  
6870 941  
6875 951  
6880 961  
6885 971  
6890 981  
6895 991  
6900 001  
6905 011  
6910 021  
6915 031  
6920 041  
6925 051  
6930 061  
6935 071  
6940 081  
6945 091  
6950 101  
6955 111  
6960 121  
6965 131  
6970 141  
6975 151  
6980 161  
6985 171  
6990 181  
6995 191  
7000 201  
7005 211  
7010 221  
7015 231  
7020 241  
7025 251  
7030 261  
7035 271  
7040 281  
7045 291  
7050 301  
7055 311  
7060 321  
7065 331  
7070 341  
7075 351  
7080 361  
7085 371  
7090 381  
7095 391  
7100 401  
7105 411  
7110 421  
7115 431  
7120 441  
7125 451  
7130 461  
7135 471  
7140 481  
7145 491  
7150 501  
7155 511  
7160 521  
7165 531  
7170 541  
7175 551  
7180 561  
7185 571  
7190 581  
7195 591  
7200 601  
7205 611  
7210 621  
7215 631  
7220 641  
7225 651  
7230 661  
7235 671  
7240 681  
7245 691  
7250 701  
7255 711  
7260 721  
7265 731  
7270 741  
7275 751  
7280 761  
7285 771  
7290 781  
7295 791  
7300 801  
7305 811  
7310 821  
7315 831  
7320 841  
7325 851  
7330 861  
7335 871  
7340 881  
7345 891  
7350 901  
7355 911  
7360 921  
7365 931  
7370 941  
7375 951  
7380 961  
7385 971  
7390 981  
7395 991  
7400 001  
7405 011  
7410 021  
7415 031  
7420 041  
7425 051  
7430 061  
7435 071  
7440 081  
7445 091  
7450 101  
7455 111  
7460 121  
7465 131  
7470 141  
7475 151  
7480 161  
7485 171  
7490 181  
7495 191  
7500 201  
7505 211  
7510 221  
7515 231  
7520 241  
7525 251  
7530 261  
7535 271  
7540 281  
7545 291  
7550 301  
7555 311  
7560 321  
7565 331  
7570 341  
7575 351  
7580 361  
7585 371  
7590 381  
7595 391  
7600 401  
7605 411  
7610 421  
7615 431  
7620 441  
7625 451  
7630 461  
7635 471  
7640 481  
7645 491  
7650 501  
7655 511  
7660 521  
7665 531  
7670 541  
7675 551  
7680 561  
7685 571  
7690 581  
7695 591  
7700 601  
7705 611  
7710 621  
7715 631  
7720 641  
7725 651  
7730 661  
7735 671  
7740 681  
7745 691  
7750 701  
7755 711  
7760 721  
7765 731  
7770 741  
7775 751  
7780 761  
7785 771  
7790 781  
7795 791  
7800 801  
7805 811  
7810 821  
7815 831  
7820 841  
7825 851  
7830 861  
7835 871  
7840 881  
7845 891  
7850 901  
7855 911  
7860 921  
7865 931  
7870 941  
7875 951  
7880 961  
7885 971  
7890 981  
7895 991  
7900 001  
7905 011  
7910 021  
7915 031  
7920 041  
7925 051  
7930 061  
7935 071  
7940 081  
7945 091  
7950 101  
7955 111  
7960 121  
7965 131  
7970 141  
7975 151  
7980 161  
7985 171  
7990 181  
7995 191  
8000 201  
8005 211  
8010 221  
8015 231  
8020 241  
8025 251  
8030 261  
8035 271  
8040 281  
8045 291  
8050 301  
8055 311  
8060 321  
8065 331  
8070 341  
8075 351  
8080 361  
8085 371  
8090 381  
8095 391  
8100 401  
8105 411  
8110 421  
8115 431  
8120 441  
8125 451  
8130 461  
8135 471  
8140 481  
8145 491  
8150 501  
8155 511  
8160 521  
8165 531  
8170 541  
8175 551  
8180 561  
8185 571  
8190 581  
8195 591  
8200 601  
8205 611  
8210 621  
8215 631  
8220 641  
8225 651  
8230 661  
8235 671  
8240 681  
8245 691  
8250 701  
8255 711  
8260 721  
8265 731  
8270 741  
8275 751  
8280 761  
8285 771  
8290 781  
8295 791  
8300 801  
8305 811  
8310 821  
8315 831  
8320 841  
8325 851  
8330 861  
8335 871  
8340 881  
8345 891  
8350 901  
8355 911  
8360 921  
8365 931  
8370 941  
8375 951  
8380 961  
8385 971  
8390 981  
8395 991  
8400 001  
8405 011  
8410 021  
8415 031  
8420 041  
8425 051  
8430 061  
8435 071  
8440 081  
8445 091  
8450 101  
8455 111  
8460 121  
8465 131  
8470 141  
8475 151  
8480 161  
8485 171  
8490 181  
8495 191  
8500 201  
8505 211  
8510 221  
8515 231  
8520 241  
8525 251  
8530 261  
8535 271  
8540 281  
8545 291  
8550 301  
8555 311  
8560 321  
8565 331  
8570 341  
8575 351  
8580 361  
8585 371  
8590 381  
8595 391  
8600 401  
8605 411  
8610 421  
8615 431  
8620 441  
8625 451  
8630 461  
8635 471  
8640 481  
8645 491  
8650 501  
8655 511  
8660 521  
8665 531  
8670 541  
8675 551  
8680 561  
8685 571  
8690 581  
8695 591  
8700 601  
8705 611  
8710 621  
8715 631  
8720 641  
8725 651  
8730 661  
8735 671  
8740 681  
8745 691  
8750 701  
8755 711  
8760 721  
8765 731  
8770 741  
8775 751  
8780 761  
8785 771  
8790 781  
8795 791  
8800 801  
8805 811  
8810 821  
8815 831  
8820 841  
8825 851  
8830 861  
8835 871  
8840 881  
8845 891  
8850 901  
8855 911  
8860 921  
8865 931  
8870 941  
8875 951  
8880 961  
8885 971  
8890 981  
8895 991  
8900 001  
8905 011  
8910 021  
8915 031  
8920 041  
8925 051  
8930 061  
8935 071  
8940 081  
8945 091  
8950 101  
8955 111  
8960 121  
8965 131  
8970 141  
8975 151  
8980 161  
8985 171  
8990 181  
8995 191  
9000 201  
9005 211  
9010 221  
9015 231  
9020 241  
9025 251  
9030 261  
9035 271  
9040 281  
9045 291  
9050 301  
9055 311  
9060 321  
9065 331  
9070 341  
9075 351  
9080 361  
9085 371  
9090 381  
9095 391  
9100 401  
9105 411  
9110 421  
9115 431  
9120 441  
9125 451  
9130 461  
9135 471  
9140 481  
9145 491  
9150 501  
9155 511  
9160 521  
9165 531  
9170 541  
9175 551  
9180 561  
9185 571  
9190 581  
9195 591  
9200 601  
9205 611  
9210 621  
9215 631  
9220 641  
9225 651  
9230 661  
9235 671  
9240 681  
9245 691  
9250 701  
9255 711  
9260 721  
9265 731  
9270 741  
9275 751  
9280 761  
9285 771  
9290 781  
9295 791  
9300 801  
9305 811  
9310 821  
9315 831  
9320 841  
9325 851  
9330 861  
9335 871  
9340 881  
9345 891  
9350 901  
9355 911  
9360 921  
9365 931  
9370 941  
9375 951  
9380 961  
9385 971  
9390 981  
9395 991  
9400 001  
9405 011  
9410 021  
9415 031  
9420 041  
9425 051  
9430 061  
9435 071  
9440 081  
9445 091  
9450 101  
9455 111  
9460 121  
9465 131  
9470 141  
9475 151  
9480 161  
9485 171  
9490 181  
9495 191  
9500 201  
9505 211  
9510 221  
9515 231  
9520 241  
9525 251  
9530 261  
9535 271  
9540 281  
9545 291  
9550 301  
9555 311  
9560 321  
9565 331  
9570 341  
9575 351  
9580 361  
9585 371  
9590 381  
9595 391  
9600 401  
9605 411  
9610 421  
9615 431  
9620 441  
9625 451  
9630 461  
9635 471  
9640 481  
9645 491  
9650 501  
9655 511  
9660 521  
9665 531  
9670 541  
9675 551  
9680 561  
9685 571  
9690 581  
9695 591  
9700 601  
9705 611  
9710 621  
9715 631  
9720 641  
9725 651  
9730 661  
9735 671  
9740 681  
9745 691  
9750 701  
9755 711  
9760 721  
9765 731  
9770 741  
9775 751  
9780 761  
9785 771  
9790 781  
9795 791  
9800 801  
9805 811  
9810 821  
9815 831  
9820 841  
9825 851  
9830 861  
9835 871  
9840 881  
9845 891  
9850 901  
9855 911  
9860 921  
9865 931  
9870 941  
9875 951  
9880 961  
9885 971  
9890 981  
9895 991  
9900 001  
9905 011  
9910 021  
9915 031  
9920 041  
9925 051  
9930 061  
9935 071  
9940 081  
9945 091  
9950 101  
9955 111  
9960 121  
9965 131  
9970 141  
9975 151  
9980 161  
9985 171  
9990 181  
9995 191  
10000 201



11.0011  
12.0022  
13.0033  
14.0044  
15.0055  
16.0066  
17.0077  
18.0088  
19.0099  
20.0100  
21.0111  
22.0122  
23.0133  
24.0144  
25.0155  
26.0166  
27.0177  
28.0188  
29.0199  
30.0200  
31.0211  
32.0222  
33.0233  
34.0244  
35.0255  
36.0266  
37.0277  
38.0288  
39.0299  
40.0300  
41.0311  
42.0322  
43.0333  
44.0344  
45.0355  
46.0366  
47.0377  
48.0388  
49.0399  
50.0400  
51.0411  
52.0422  
53.0433  
54.0444  
55.0455  
56.0466  
57.0477  
58.0488  
59.0499  
60.0500  
61.0511  
62.0522  
63.0533  
64.0544  
65.0555  
66.0566  
67.0577  
68.0588  
69.0599  
70.0600  
71.0611  
72.0622  
73.0633  
74.0644  
75.0655  
76.0666  
77.0677  
78.0688  
79.0699  
80.0700  
81.0711  
82.0722  
83.0733  
84.0744  
85.0755  
86.0766  
87.0777  
88.0788  
89.0799  
90.0800  
91.0811  
92.0822  
93.0833  
94.0844  
95.0855  
96.0866  
97.0877  
98.0888  
99.0899  
100.0900

PEAK FLOW AND STORAGE (EAD OF PERIOD) SUMMARY FOR MULTIPLE PLAN-RATIO ECONOMIC COMPUTATIONS  
 FLOWS IN CUBIC FEET PER SECOND (CUBIC METERS PER SECOND)  
 AREA IN SQUARE FEET (SQUARE KILOMETERS)

| OPERATION     | STATION | AREA                | PLAN RATIO | RATIOS APPLIED TO FLOOD |         |         |         |         |         |
|---------------|---------|---------------------|------------|-------------------------|---------|---------|---------|---------|---------|
|               |         |                     |            | RATIO 1                 | RATIO 2 | RATIO 3 | RATIO 4 | RATIO 5 | RATIO 6 |
| HYDROGRAPH A1 | 1       | 1,833<br>(7,955.72) | 1          | 0.50                    | 3.40    | 0.50    | 3.60    | 3.90    | 1.00    |
|               |         |                     |            | 155.                    | 1,145.  | 1,482.  | 1,779.  | 2,001.  | 2,354.  |
| HYDROGRAPH A1 | 1       | 8,511<br>(7,955.72) | 1          | 0.50                    | 3.40    | 0.50    | 3.60    | 3.90    | 1.00    |
|               |         |                     |            | 1,273.                  | 31,033. | 41,973. | 50,363. | 57,111. | 63,543. |
| HYDROGRAPH A1 | 1       | 2,910<br>(7,955.72) | 1          | 0.50                    | 3.40    | 0.50    | 3.60    | 3.90    | 1.00    |
|               |         |                     |            | 786.                    | 1,572.  | 1,815.  | 2,177.  | 2,301.  | 3,529.  |
| HYDROGRAPH A1 | 1       | 2,910<br>(7,955.72) | 1          | 0.50                    | 3.40    | 0.50    | 3.60    | 3.90    | 1.00    |
|               |         |                     |            | 967.                    | 1,425.  | 1,406.  | 2,447.  | 3,833.  | 4,812.  |
| HYDROGRAPH A1 | 1       | 2,910<br>(7,955.72) | 1          | 0.50                    | 3.40    | 0.50    | 3.60    | 3.90    | 1.00    |
|               |         |                     |            | 137.                    | 775.    | 1,142.  | 1,576.  | 2,319.  | 3,029.  |

ELEVATION 531.55 TOP OF DAM 534.00  
 STORAGE 2830. 532.55  
 CUTELO 0. 2810. 5372.  
 0. 78.

| STATION | ELEVATION | MAXIMUM DEPTH OVER DAM | MAXIMUM STORAGE ACFT | MAXIMUM CUTELO CFS | DURATION OVER TOP HOURS | TIME OF MAX OUTFLOW HOURS | TIME OF FAILURE HOURS |
|---------|-----------|------------------------|----------------------|--------------------|-------------------------|---------------------------|-----------------------|
| 0+0     | 534.08    | 0.78                   | 3403.                | 832.               | 45.23                   | 22.50                     | 0.                    |
| 0+4     | 534.15    | 0.79                   | 3374.                | 775.               | 57.23                   | 41.50                     | 0.                    |
| 0+8     | 534.27    | 0.77                   | 3271.                | 1182.              | 53.23                   | 43.50                     | 0.                    |
| 0+12    | 534.32    | 0.82                   | 3275.                | 1576.              | 53.00                   | 45.00                     | 0.                    |
| 0+16    | 535.38    | 1.08                   | 3774.                | 2319.              | 63.00                   | 44.50                     | 0.                    |
| 1+00    | 555.29    | 1.29                   | 3856.                | 3039.              | 61.50                   | 44.50                     | 0.                    |

APPENDIX D

REFERENCES


APPENDIX D

REFERENCES


- 1) U.S. Department of Commerce, Technical Paper No. 40, Rainfall Frequency Atlas of the United States, May 1961.
- 2) U.S. Department of Commerce, Hydrometeorological Report No. 33, Seasonal Variation of the Probable Maximum Precipitation East of the 105th Meridian for Areas from 10 to 1,000 Square Miles and Durations of 6, 12, 24, and 48 Hours; April 1956.
- 3) Soil Conservation Service, National Engineering Handbook, Section 4, Hydrology, August 1972 (U.S. Department of Agriculture).
- 4) H.W. King and E.F. Brater, Handbook of Hydraulics, 5th edition, McGraw-Hill, 1963.
- 5) T.W. Lambe and R.V. Whitman, Soil Mechanics, John Wiley and Sons, 1965.
- 6) W.D. Thornbury, Principles of Geomorphology, John Wiley and Sons, 1969.
- 7) University of the State of New York, Geology of New York, Education Leaflet 20, Reprinted 1973.
- 8) Cornell University Agriculture Experiment Station (compiled by M.G. Cline and R.L. Marshall), General Soil Map of New York State and Soils of New York Landscapes, Information Bulletin 119, 1977.

**APPENDIX E**

**DRAWINGS**



VICINITY MAP



TOPOGRAPHIC MAP