AD-AI10 551 UNCLASSIFIED	SEORGE SENSIT AUG 81 SERIAL	WASHIN IVITY A A V F -T-437	NO PAR/	NIV WAS Ametric A Shaei	SHINGTO BOUND 41	N DC PR ANALYSI	DGRAM I 5 OF AN	N LOGIS ELECTR NODO14	TICS I IC POW -75-C-(76 10/2 RET 1729 NL	2 C(U)	ĺ
$\int_{\frac{M}{M}} \int_{\frac{M}{M}} \int_{\frac$	9 7											
END DATT PROFE DEC												
			_									





2

SENSITIVITY AND PARAMETRIC BOUND ANALYSIS OF AN ELECTRIC POWER GENERATION GP MODEL: OPTIMAL STEAM TURBINE EXHAUST ANNULUS AND CONDENSER SIZES

by

A. V. Fiacco A. Ghaemi

Serial-T-437 ⁴ 1 August 1981

1 日本 一

ş



The George Washington University School of Engineering and Applied Science Institute for Management Science and Engineering

Program in Logistics

Contract N00014-75-C-0729 Project NR 347 020 Office of Naval Research

This document has been approved for public sale and release; its distribution is unlimited.

N	EPUKI DUCUMEN	ITATION PAGE	BEFORE COMPLETING FORM
REPORT NUMBE	R	2. GOVT ACCESSION NO	3. RECIPIENT'S CATALOG NUMBER
	T-43 7	AD-A1105	51
. TITLE (and Subt)	(I.) SENSITIVITY		S. TYPE OF REPORT & PERIOD COVERED
BOUND ANA	LYSIS OF AN ELI	ECTRIC POWER GENERATION	COLEMPTETC
GP MODEL:	OPTIMAL STEAM ?	TURBINE EXHAUST ANNULUS	A DERECOMING ODG DEPODE NUMBER
	AND CONDENSI	ER SIZES	T-437
AUTHOR(+)		-	S. CONTRACT OR GRANT NUMBER(+)
	A. V. FIACCO	0	N0001/ 75 0 0700
	A. GHANMI		NUUU14-/5-C-0/29
PERFORMING OF	GANIZATION NAME AN	D ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
PROGRAM IN	LOGISTICS		{
WASHINGTON.	DC 20052		
APRINE AP N	AVAT BOODANON	VNE 33	
CODE 434	AVAL REJEAKUI		13. NUMBER OF PAGES
ARLINCTON	VA 22217		36
4. MONITORING A	GENCY NAME & ADDRES	S(il dillerent from Controlling Office)	18. SECURITY CLASS. (of this report)
			UNCLASSIFIED
			18. DECLASSIFICATION DOWNGRADING
APPROV	ED FOR PUBLIC S	ALE AND RELEASE; DISTRI	BUTION UNLIMITED.
APPROV	ED FOR PUBLIC S	ALE AND RELEASE; DISTRI	BUTION UNLIMITED.
APPROV	ED FOR PUBLIC S	SALE AND RELEASE; DISTRI	BUTION UNLIMITED.
APPROV DISTRIBUTION S SUPPLEMENTAP	ED FOR PUBLIC S	ALE AND RELEASE; DISTRI	BUTION UNLIMITED.
APPROV DISTRIBUTION S SUPPLEMENTAP NONLINEAR P CONVEX PARAM SENSITIVITY PADAMETER	ED FOR PUBLIC S	ALE AND RELEASE; DISTRI	BUTION UNLIMITED.
APPROV DISTRIBUTION S UPPLEMENTAR SUPPLEMENTAR NONLINEAR P CONVEX PARAI SENSITIVITY PARAMETRIC	ED FOR PUBLIC S	SALE AND RELEASE; DISTRI	BUTION UNLIMITED.
APPROV DISTRIBUTION S UPPLEMENTAR SUPPLEMENTAR NONLINEAR P CONVEX PARAI SENSITIVITY PARAMETRIC ABSTRACT (Cont As a fur programming	ED FOR PUBLIC S TATEMENT (of the ebets NY NOTES ROGRAMMING METRIC PROGRAM ANALYSIS ANALYSIS Inue on reverse side if me ther demonstrat g model for the	ALE AND RELEASE; DISTRI	BUTION UNLIMITED. Report) ?LECTRIC POWER GENERATION 'ONDENSER SIZE ANNULUS SIZE ability, a posynomial team turbine exhaust
APPROV DISTRIBUTION S SUPPLEMENTAR SUPPLEMENTAR NONLINEAR P CONVEX PARA SENSITIVITY PARAMETRIC ASSYRACT (Cont As a fur programming annulus and analyzed fo value bound	ED FOR PUBLIC S TATEMENT (of the ebets AV NOTES NOTES NOTES METRIC PROGRAM ANALYSIS ANALYSIS Thus on reverse side if me ther demonstrat g model for the d condenser siz or optimal valu ds. This provi	ALE AND RELEASE; DISTRI	BUTION UNLIMITED. Report) ?LECTRIC POWER GENERATION 'ONDENSER SIZE ANNULUS SIZE ability, a posynomial team turbine exhaust nd Wiebking is solved and s and parametric optimal mation for conduction a
APPROV DISTRIBUTION S SUPPLEMENTAR NONLINEAR P CONVEX PARAI SENSITIVITY PARAMETRIC ASSYMACT (Comm TAS a furth programming annulus and analyzed for value bound thorough co for this es	ED FOR PUBLIC S TATEMENT (of the ebets without on reverse side if a ROGRAMMING METRIC PROGRAM ANALYSIS ANALYSIS Inse on reverse side if ac ther demonstrat g model for the d condenser siz or optimal valu ds. This provi ost benefit ana ktremely import.	ALE AND RELEASE; DISTRI	BUTION UNLIMITED. Report) Report Report) Report Report) Report Rep
APPROV DISTRIBUTION S SUPPLEMENTAR SUPPLEMENTAR NONLINEAR P CONVEX PARA SENSITIVITY PARAMETRIC ABSTRACT (Cont As a fur programming annulus and analyzed for value bound thorough co for this ex	ED FOR PUBLIC S TATEMENT (of the ebets AV NOTES MUNICIPAL ROGRAMMING METRIC PROGRAM ANALYSIS ANALYSIS ANALYSIS Invo en reverce side if me ther demonstrat g model for the d condenser siz or optimal valu ds. This provi ost benefit ana xtremely import.	ALE AND RELEASE; DISTRI	BUTION UNLIMITED. Report) PLECTRIC POWER GENERATION 'ONDENSER SIZE ANNULUS SIZE ability, a posynomial team turbine exhaust nd Wiebking is solved and s and parametric optimal mation for conducting a rameter changes considered, lications.

THE GEORGE WASHINGTON UNIVERSITY School of Engineering and Applied Science Institute for Management Science and Engineering

Program in Logistics

Abstract of Serial T-437 1 August 1981

SENSITIVITY AND PARAMETRIC BOUND ANALYSIS OF AN ELECTRIC POWER GENERATION GP MODEL: OPTIMAL STEAM TURBINE EXHAUST ANNULUS AND CONDENSER SIZES

by

A. V. Fíacco A. Ghaemi

ß

As a further demonstration of practical applicability, a posynomial programming model for the optimal selection of steam turbine exhaust annulus and condenser sizes developed by Ecker and Wiebking is solved and analyzed for optimal value function sensitivities and parametric optimal value bounds. This provides the essential information for conducting a thorough cost benefit analysis over the large parameter changes considered, for this extremely important class of energy applications.

	Accession Tor
Research Supported by	NTIS CAR
Contract N00014-75-C-0729 Project NR 347 020 Office of Naval Research	bine by cont

TABLE OF CONTENTS

24

Abstract

Sec. Harris

ورجيا

Ľ,

Sec. 1

ž

C.

	List of Figures and Tables	
1.	Introduction	1
2.	Parametric Optimal Value Bounds	3
3.	The Model	8
4.	Model Solution	16
5.	Optimal Value Function Sensitivities and Bounds	18
	References	30

أسو

LIST OF FIGURES AND TABLES

j,

et an in

FIGURES

į

1.	A Simplified Layout of a Steam Turbine Power Plant	2
2.	Parametric Bounds on f*(a ₃)	26
3.	Parametric Bounds on f*(c _t)	28
TABLES		
1.	Problem Data	19
2.	Optimal Value Function Sensitivity Results	21
3.	Parameters Selected for Bound	5 1

THE GEORGE WASHINGTON UNIVERSITY School of Engineering and Applied Science Institute for Management Science and Engineering

SENSITIVITY AND PARAMETRIC BOUND ANALYSIS OF AN ELECTRIC POWER GENERATION GP MODEL: OPTIMAL STEAM TURBINE EXHAUST ANNULUS AND CONDENSER SIZES

by

A. V. Fiacco A. Ghaemi

1. Introduction

Currently, about 25 percent of the energy consumed in the United States is in the form of electric energy generated by power plants. More than 80 percent of this electricity production is due to steam power plants [15]. This reveals the important role of steam turbine power plants as a major contributor to energy production and suggests the efficient design and operations of these plants as a vitally important objective in this era of energy shortage.

The efficient design of steam power plants has been a source of contention since the late 19th century. During the past 80 years, the efficiency of the steam power plants has been increased from about 4 percent to about 33 percent. That is, only about one-eight as much fossil fuel is now required per unit of electric energy production, compared to that of 1900 [12]. This advance has been due to a variety of reasons, such as mechanical design improvements, advances of thermodynamics, and metallurgical developments that have made high temperature boilers and turbines possible. There have been numerous studies addressed to the optimal design and economic operation of the various components of steam turbine power plants. A good survey of these studies is given by Wiebking [15]. The major components consist of the boiler, steam turbine, condenser, pump and generator. Figure 1 depicts a simplified layout of these components in a steam turbine power plant.



Figure 1. A simplified layout of a steam turbine power plant

It is well known that the optimal design of the subsystems and individual components of a given system do not necessarily lead to an overall optimal design of the given system. In power plants, however, Wilson and Malouf [17] and Wilson [16] have shown that the overall optimal sizing of the condensing system and turbine exhaust annulus can be closely approximated by optimizing these systems independently of the remaining components. Based on this finding Wiebking [15] has formulated and solved numerous geometric programming models with different design configurations, for optimal sizing of the turbine exhaust and condensing systems of steam turbine power plants.

In the present paper, we analyze one of these GP models, studied by Ecker and Wiebking [3], [4], for optimal value function sensitivity and parametric bounds, with respect to many of the model parameters. The sensitivity analysis methodology used here is based on the work of Fiacco [6], and the optimal value bound approach was proposed by Fiacco

T-437

- 2 -

and implemented by Fiacco and Ghaemi [10]. Ghaemi has successfully demonstrated the applicability of this bound calculation procedure to several nontrivial problems [11].

It is not the purpose of this study to elaborate on and justify the choice of constraints or objective function, or their derivation, involved in the model under consideration. Readers interested in these aspects may refer to [15]. Here, after presenting the mathematical formulation of the model and identifying the variables and parameters, we report on the solution of a convex equivalent of the model and analyze it for sensitivities and optimal value bounds, using the latest version of our penalty function-sensitivity analysis computer program SENSUMT [10].

The paper is organized as follows. Section 2 briefly reviews the basic idea of the optimal value bound calculation, its implementation on the computer, and its application to GP models. Section 3 lists the model parameters and variables and problem formulation. The usual exponential transformation is applied to convert the GP to a standard convex nonlinear programming (NLP) problem. Sections 4 and 5 present the solution, sensitivity, and bound analysis results.

2. Parametric Optimal Value Bounds

In this section we briefly outline the procedure for calculating piecewise linear parametric upper and lower bounds on the optimal value function of the convex right-hand side perturbation problem, which is known to have a convex optimal value function. Making additional use of some recent developments by Dembo [2], we will demonstrate the applicability of this technique to geometric programs.

Parametric Bounds on the Optimal Value Function of Convex Right-Hand Side Problems $CR(\varepsilon)$

Consider the following parametric programming problem $R(\varepsilon)$:

Minimize
$$f(x)$$

subject to $g_i(x) \ge \varepsilon_i$, $i=1,m$ $R(\varepsilon)$
 $h_j(x) = \varepsilon_j$, $j=m+1,p$,

T-437

- 3 -

where the decision variable $x \in E^n$, i, g_i , and h_j : $E^n + E^1$ are C^2 and the parameter vector $\varepsilon = (\varepsilon_1, \ldots, \varepsilon_p)$ is in E^p . If f(x) and $-g_i(x)$, i=1,m, are convex and $h_j(x)$, j=m+1,p are affine, then the problem $R(\varepsilon)$ is convex and will be designated as $CR(\varepsilon)$. It is well known that $f^*(\varepsilon)$, the optimal value function of the problem $CR(\varepsilon)$ is convex over any convex subset of the parameter space on which a solution is defined.

The convexity of the optimal value function $f^*(\varepsilon)$ of the problem CR(ε) allows for a simple calculation of parametric linear upper and lower bounds of this function when any of the problem parameters is perturbed. In our application, this will require the solution and corresponding optimal value function sensitivity information for both perturbed and unperturbed problems. The idea follows immediately from two well known properties of convex functions:

- (i) Any line connecting two points on the graph of a convex function does not underestimate that function between the points.
- (ii) Any tangent line to the graph of a convex function does not overestimate that function.

These two properties lend themselves in a natural way to the calculation of parametric bounds on the optimal value function of the problem $CR(\varepsilon)$ under large perturbations of any of the problem parameters, say ε_i .

The idea of using properties (i) and (ii) for calculating bounds on the optimal value function of the problem with a convex or concave optimal value function and for estimating bounds on nonconvex problems by way of estimating problems with convex or concave optimal value function is due to Fiacco [7]. Fiacco also notes that techniques for generating

1-437

- 4 -

underestimating problems that are jointly convex in the decision variable and the parameter (hence, that have a convex optimal value function [13]) are already available for problems that are jointly separable [5] or jointly factorable [14], thus making it possible to calculate lower bounds using known procedures. The first computational implementation of this approach was developed and reported by Ghaemi [11], who also derived the formulas for calculating a jointly convex overestimating problem of a factorable program, thus making it possible to numerically implement the proposed scheme for calculating upper bounds when the problem functions are factorable (as they inevitably are, in practice).

Suppose $f^{*}(\varepsilon)$ is differentiable. (Well-known conditions guaraneeing this were given by Fiacco [6].)

Basis for Calculation of Bounds on $f^*(\varepsilon)$ of the Problem $CR(\varepsilon)$

For simplicity, suppose that some ϵ_i is perturbed from $\overline{\epsilon}_{i1}$ to $\overline{\epsilon}_{i2}$, while the remaining parameters are fixed at their base values.

Step 1. Solve the unperturbed problem and obtain $f^*(\epsilon_i)$

and $df^{*}(\varepsilon_{i})/d\varepsilon_{i}$ at $\varepsilon_{i} = \overline{\varepsilon}_{11}$. Under general conditions (e.g., see Armacost and Fiacco [1]),

$$\frac{df^{\star}(\varepsilon_{i})}{d\varepsilon_{i}} = \begin{cases} u_{i}(\varepsilon_{i}) , & i=1,\ldots,m \\ -w_{i}(\varepsilon_{i}) , & i=m+1,p \end{cases}$$

- 5 -

where u and w are optimal Lagrange multipliers associated with inequality and equality constraints of $CR(\varepsilon)$, respectively.

Step 2. Resolve the problem and obtain $f^*(\varepsilon_i)$ and $df^*(\varepsilon_i)/d\varepsilon_i$ at $\varepsilon_i = \overline{\varepsilon}_{12}$.

Step 3. Derive the equation of the line passing through the points $(\overline{\epsilon}_{i1}, f^*(\overline{\epsilon}_{i1}))$ and $(\overline{\epsilon}_{i2}, f^*(\overline{\epsilon}_{i2}))$. This line provides a parametric upper bound $\overline{f}^*(\epsilon_i)$ for $f^*(\epsilon_i)$ as a function of $\epsilon_i \in [\overline{\epsilon}_{i1}, \overline{\epsilon}_{i2}]$.

Step 4. Derive the equation of the tangent lines to $f^*(\varepsilon_i)$ at the above two points with the slopes

$$\frac{df^{*}(\varepsilon_{i})}{d\varepsilon_{i}} | \begin{array}{c} \text{and} & \frac{df^{*}(\varepsilon_{i})}{d\varepsilon_{i}} \\ \varepsilon_{i} = \overline{\varepsilon}_{11} & \frac{df^{*}(\varepsilon_{i})}{d\varepsilon_{i}} \\ \varepsilon_{i} = \overline{\varepsilon}_{12} \end{array} |$$

calculated in Steps 1 and 2, respectively. The maximum of these two lines provides a piecewiselinear parametric lower bound $f^*(\varepsilon_i)$ for $f^*(\varepsilon_i)$ as a function of ε_i in $[\overline{\varepsilon}_{i1}, \overline{\varepsilon}_{i2}]$.

The lines obtained in Steps 3 and 4 provide the desired bounds, forming a triangle which encloses the optimal value function $f^*(\varepsilon_i)$ over the given range of ε_i . Further, a smooth estimate of $f^*(\varepsilon_i)$ over the given interval can also be made by fitting any differentiable convex function that passes through the points given in Step 3, having the corresponding slopes at these points obtained in Steps 1 and 2. In our implementations, we calculate the highest quadratic function passing through the given end points and having the required slope at one of the end points. It can be shown that this function is entirely contained in the indicated triangle and is convex.

It is clear that the fundamental property exploited in calculating the above bounds is the convexity of the optimal value function. Thus, the use of this procedure is not limited to problems of the form $CR(\varepsilon)$, but can be applied to any parametric problem that has a convex optimal value. In fact, it is obvious that this technique is also applicable to parametric programs with concave optimal value functions. The only minor alteration is that Step 3 of the algorithm will provide the lower bound, while Step 4 will yield the upper bound.

The relevance of the application of the above technique to the problem under consideration in the present study is that the posynomial programs, under the usual exponential transformation, becomes a convex problem. Since the transformation does not affect the value of the problem functions, the above technique may obviously be applied to calculate parametric bounds on the optimal value function of GP problems with respect to right-hand side perturbations. The convexity of the optimal value of the posynomial GP as a function of the right-hand side perturbations follows immediately from the exponential transformation and a well-known result. Furthermore, it follows that the optimal value function of the primal GP (posynomial) problem (formulated as a minimization problem) is a monotone nondecreasing concave function of the coefficients appearing in the GP primal objective function. This follows from the linearity of the objective function as a function of these coefficients and the fact that $f^*(\varepsilon) = \min_p f(x, \varepsilon)$ is concave if $f(x,\varepsilon)$ is concave in ε and R does not depend on ε . Concavity with respect to each ε_1 was noted by Dembo [2], who did not make use of the general result indicated but calculated the second derivatives of the optimal value function. In Section 4, using these results, we are

- 7 -

able to apply the given technique to derive piecewise linear parametric bounds on the optimal value function of the model under consideration as a function of the model parameters.

3. The Model

As mentioned earlier, it is not the purpose of this study to justify the underlying theory and formulation of the resulting GP problem. We list the problem variables and parameters, followed by a concise statement of the model objective function and constraints. Readers interested in details regarding the derivation of the model may refer to [3], [4] and [15].

The model under consideration requires the minimization of the total cost involved in the steam turbine power plantas a function of the turbine exhaust annulus and the condenser system design, subject to a multitude of engineering and thermodynamic constraints.

Model variables

The variables involved in the model and their description, extracted from [3], are as follows:

A_{an} : total turbine exhaust annulus area, sq ft
T_s : saturation temperature of steam,^oF
N : number of tubes in condenser
D_o : outside tube diameter, ft
D_i : inside tube diameter, ft
L : condenser tube length, ft
q : rate of heat transfer, Btu/hr
Q_a : condenser flow, lb/hr
f_M : moisture correction factor at expansion line
end point

- 8 -

- Δh : exhaust loss, Btu/lb
- T_h : hot water temperature, ^oF
- Model parameters

and the second second

There are numerous parameters involved in the derivations of the models developed in [15] by Wiebking. Here we will only state those parameters which are explicitly involved in the formulation of the model considered here:

a _i (i=1,6)	:	regression coefficient involved in derivation of emperical formulas for the model
8	:	pressure drop factor
b _i (i=1,5 and i=61, 62)	:	regression coefficients involved in derivation of emperical formulas for the model
b an	:	exponent in annulus area cost relation
c _{an}	:	coefficient in annulus area cost relation
с _Е	:	cost of electricity, \$/(kW-hr)
с р	:	<pre>specific heat,Btu/(lb-^OF)</pre>
°t	:	unit cost of condenser surface, \$/sq ft
D _{o,ain}	:	minimum allowable outside tube diameter, ft
ſ _{M,R}	:	moisture correction factor at rated average conditions
g	:	gravitational constant, ft/sec ²
^h 2,R	:	expansion line, end point, at rated average conditions, Btu/lb
k	:	thermal conductivity, Btu/ft-hr- ^O F)
l	:	tube wall thickness, ft
Pr	:	Prandtl number

T-437

- 9 -

P : rate of depreciation per year $Q_{a,R}$: condenser flow at rated average conditions, lb/hr T_{c} : cold water temperature, ${}^{o}F$ t : load factor - effective operating time, hours/year u : minimum tube velocity, ft/sec : lower bound on annulus velocity of steam, ft/sec V_L ٧,, : upper bound on annulus velocity of steam, ft/sec : water flow rate, lb/hr ы : generator efficiency η_c : pump efficiency η_p : latent heat of evaporation, Btu/1b λ : viscosity, lb/(ft-hr) μ : density, lb/cu ft τ_{max} : allowable last stage bucket loading, 1b/(hr-sq ft) $\begin{array}{c} \Delta T & \text{maximum allowable temperature increase of cooling} \\ & \text{water, } {}^{O}F \end{array}$ f : outside film, a subscript

The objective function g_{Ω}

The model minimizes g_0 , the total annual cost involved in the steam turbine power plant as a function of the exhaust annulus and the condenser system design, and consists of two parts: fixed costs and operating costs. Denoting the fixed and operating costs of the turbine by $C_{F,T}$ and $C_{0,T}$ and those of the condenser by $C_{F,C}$ and $C_{0,C}$, respectively, the total annual cost to be minimized is

 $g_0 = (C_{F,T} + C_{0,T}) + (C_{F,C} + C_{0,C})$.

-10 -

The formulas derived in [3] and [4] for the above cost components, as a function of the design variables and parameters, are as follows:

 $C_{F,T} = c_1 \Lambda_{an}^{b} an \qquad $/year$ $C_{O,T} = c_2 (q-q_R) + fuel cost \qquad $/year$

$$C_{0,C} = c_4 L/(D_1^{4.8} * N^{1.8})$$
 \$/year

where

$$c_{1} = c_{an} P_{c}$$

$$c_{2} = c_{E} t \eta_{G} / 3412.75$$

$$c_{3} = \pi c_{t} P_{c}$$

$$c_{4} = (32)(.046) C_{E} Bt W^{2.8} (\mu/4)^{2} / (g\eta_{p} \rho^{2} \pi^{1.8})$$

and q_R is the rate of heat transfer at the rated average conditions in Btu/hr.

Notice that the operation cost of the turbine $C_{0,T}$ consists of the replacement energy cost and the fuel cost. In the formulation of the model, it is assumed that the turbine generator runs at full load, implying that the cost of fuel is constant. Also, in replacement cost terms, the quantity c_2q_R is constant. Thus, the fuel cost and c_2q_R are deleted from consideration in the optimation model.

The Constraints

(i) constraint on condenser rejected heat

$$g_1: c_5 \frac{Q_a}{q} + c_6 \frac{Q_a T_s}{q} + c_7 \frac{Q_a f_M \Delta h'}{q} \leq 1$$

- 11 -

where

S. Beerton

$$c_{5} = h_{2,R} + a_{1}f_{M,R} + .87 a_{4}a_{6} - a_{2}$$

$$c_{6} = b_{1}f_{M,R} + .87 b_{4}a_{6} - b_{2}$$

$$c_{7} = 1$$

$$\Delta h' = \Delta h - a_{6}$$

(ii) Moisture correction factor constraint

$$g_2: c_8 \frac{1}{f_M} + c_9 \frac{T_s}{f_M} \leq 1$$

where

 $c_8 = .87 a_4$ $c_9 = .87 b_4$

(iii) Exhaust loss constraint

$$g_3: c_{10} \frac{T_s^{2b_5}}{A_{an}^2 \Delta h'} + c_{11} \frac{A_{an}}{T_s^{5} \Delta h'} \leq 1$$

where

in the second

- - - -

$$c_{10} = b_{61}$$

 $c_{11} = \frac{b_{62}}{a_5 Q_{a,R}}$

(iv) Heat exchanger mean temperature drop constraint

$$g_4: c_{12} \frac{1}{T_s} + c_{13} \frac{q}{T_s} + c_{14} \frac{q^{4/3}}{T_s N^{7/6} D_0 L^{4/3}} + c_{15} \frac{g D_1}{T_s L N^{2}} \leq 1$$

- 12 -

T-437

where

$$c_{12} = T_{c}$$

$$c_{13} = 1/(2 c_{p} W)$$

$$c_{14} = (.725 \pi)^{-4/3} \left[\frac{\mu_{f}}{(2)(3600)^{2} k_{f}^{3} \rho f^{2} g \lambda} \right]^{1/3}$$

$$c_{15} = (.023 \pi k Pr^{4})^{-1} * (\frac{\pi \mu}{4W})^{.8}$$

$$g_5: c_{16} = \frac{1}{Q_a} + c_{17} = T_s \le 1$$

where

$$c_{16} = \frac{Q_{a,R}}{a_3}$$
 and
 $c_{17} = -\frac{b_3}{a_3}$

(vi) Heat exchanger tube diameter constraints

$$g_6: c_{18} \quad \frac{1}{D_0} + c_{19} \quad \frac{D_i}{D_0} \leq 1$$
 and
 $g_7: c_{20} \quad \frac{1}{D_0} \leq 1$

where

- 13 -

(vii) Annulus fluid velocity constraints

A DESCRIPTION OF THE ADDRESS OF THE OWNER OF THE DESCRIPTION

$$g_8: c_{21} \xrightarrow{T_8} f_{an} \leq 1$$

$$g_{g}: c_{22} \xrightarrow{an} 5_{5} \leq 1$$

where

$$c_{21} = \frac{a_5 Q_{a,R}}{V_U}$$

$$c_{22} = \frac{V_L}{a_5 Q_{a,R}}$$

(viii) Last stage bucket loading constraint

$$g_{10}: c_{23} \xrightarrow{Q_a} \leq 1$$

where

$$c_{23} = \frac{1}{\tau_{max}}$$

(1x) Heat exchanger tube water velocity constraint

$$B_{11} : C_{24} N D_{i}^{2} \le 1$$

where

$$c_{24} = \frac{3600 \text{ u}_{\min} \pi \rho}{4W}$$

- 14 -

1-4.37

(x) Thermal pollution constraint

$$g_{12}: c_{25} T_h \leq 1$$

 $c_{25} = \frac{1}{T_c + \Delta T_{max}}$

Denoting the model variables A_{an} , T_s , N, D_o , D_i , L, q, Q_a , f_M , (Ab.) and T_h by x_1 through x_{11} , respectively, the model is secondated as follows.

The GP problem

~ 15 -

$$g_{10} = c_{23} x_8 x_1^{-1} \ge 1$$

$$g_{11} = c_{24} x_3 x_5^2 \le 1$$

$$g_{12} = c_{25} x_{11} \le 1$$

4. Model Solution

and the second second

Ecker and Wiebking [3], using a data base drawn from [15], have solved this model. In [3], they conclude from a preliminary analysis that constraints $g_8 - g_{12}$, with the given data base, are not binding and thus ignore these constraints in determining a solution to the CP problem. Henceforward, the problem with $g_8 - g_{12}$ deleted will be the focus of our attention, and will be called the "reduced problem."

The values of coefficients c_1 through c_{20} in [3] are given as follows:

 $c_{1} = 2541.0 \quad c_{6} = .23972 \quad c_{11} = 6.2139 * 10^{-8} \quad c_{16} = 2.447 * 10^{6}$ $c_{2} = .012293 \quad c_{7} = 1.0 \quad c_{12} = 50.0 \quad c_{17} = 1.0289 * 10^{-3}$ $c_{3} = 2.4190 \quad c_{8} = .62004 \quad c_{13} = 4.7394 * 10^{-9} \quad c_{18} = 8.1667 * 10^{-3}$ $c_{4} = 77171.0 \quad c_{9} = 1.1072 * 10^{-3} \quad c_{14} = 7.3124 * 10^{-1} \quad c_{19} = 1.0$ $c_{5} = 888.76 \quad c_{10} = 2.1872 * 10^{16} \quad c_{15} = 1.2577 * 10^{-5} \quad c_{20} = .083333$

Using the above coefficients, they obtain the solution of the reduced model by means of a modified concave simplex algorithm that solves the dual geometric program. The solution, obtained after 300 seconds of CPU time on an IBM system 360/50 computer, is listed below.

Dual objective function: 32.3728 · 10⁶

- 16 -

Primal objective function: $32.0356 + 10^6$ Primal variables: $q = 2.5503 + 10^9$ $T_g = 85.455$ $A_{an} = 409.16$ N = 13,662 $f_M = 0.71520$ $D_i = 0.082461$ $Q_a = 2.7010 + 10^6$ $D_o = 0.091950$ $\Delta h^* = 46.882$ L = 70.606

To solve the reduced GP problem in this study, the convex equivalent of the (reduced) model was formulated via the usual exponential transformation, $x_i = e^{-t_i}$, i=1, 10, and the same coefficients c_i used by Ecker and Wiebking and reported in [3] were utilized. To prevent over-and under-flow in the process of obtaining the numerical solution, the following constraints (which proved to be nonbinding at the optimal solution) were added to the model:

$$-170 \le t_6^{-4.8} t_5 - 1.8 t_3 \le 170$$

 $-30 \le t_4 \le 30 i=1,10$

The resulting problem was solved by SENSUMT, on The George Washington University IBM 3031. The solution, obtained in 57 seconds of CPU time, is listed below.

Dual objective function 32.37324 ± 10^6 Primal objective function 32.37325 ± 10^6 $x_1 = A_{an} = 408.88$ $x_6 = L = 58.46230$ $x_2 = T_g = 85.452$ $x_7 = q = 2.52929 \pm 10^9$ $x_3 = N = 18979.5$ $x_8 = Q_a = 2.68298 \pm 10^6$ $x_4 = D_o = .07902$ $x_9 = f_M = .71455$ $x_5 = D_i = .07085$ $x_{10} = \Delta h' = 46.88288$

- 17 -

The significantly greater accuracy of this solution, based on the gap between the values of the dual and primal objective functions, compared to that obtained in [3], is apparent from the given data. The two solution vectors, although considerably different in some components, are of the same order of magnitude. As noted, the CPU time required by SENSUMT to obtain a relatively very accurate solution of the given model was about 1/5 of the CPU time spent by the algorithm in [3] to obtain a rather crude estimate of a solution. Of course, since the IBM 3031, is faster than the IBM 360/50 and since we do not know the initial point used in [3] to solve the problem, it is not possible to make a definitive comparison of the relative efficiency of the subject codes.

In the next section, we analyze the reduced model for sensitivity information and optimal value parametric bounds.

5. Optimal Value Function Sensitivities and Bounds

5.1 Optimal value function sensitivities

To conduct sensitivity and bound calculations with respect to the various parameters involved in the model, the coefficient c_1 (1=1, 20) must be expressed as a function of the model parameters, rather than being considered independent and assigned fixed values (as was done in defining the data of the problem solved in Section 4). To accomplish this, the formulas taken from [4] and given in Section 3 for c_1 (1=1, 20) were coded. Using the values for the various problem parameters, given in [3] and [15] and shown in Table 1, the following values were calculated for the components of the parameter - dependent coefficient vector $c=(c_1, \ldots, c_{20})$. $c_1 = 1270.5$ $c_6 = .2397342$ $c_{11} = 6.213914 * 10^{-8}$ $c_{16} = 2.477010 * 10^{6}$ $c_2 = .01229334$ $c_7 = 1.0$ $c_{12} = 50.0$ $c_{17} = 1.028863 * 10^{-3}$ $c_3 = 2.419023$ $c_8 = .6200489$ $c_{13} = 4.739336 * 10^{-9}$ $c_{18} = 8.166663 * 10^{-3}$

 $c_4 = 77169.87$ $c_9 = 1.107162 * 10^{-3}$ $c_{14} = 7.312399 * 10^{-6}$ $c_{19} = 1.0$ $c_5 = 888.7634$ $c_{10} = 2.18723 * 10^{18}$ $c_{15} = 1.2577 * 10^{-5}$ $c_{20} = .08333296$

A 75 14

.

Table 1

Problem Data

Symbol	Level	Symbol	Level
^a 1	-159.9	к _f	. 3630
a ₂	-32.08	L	.06 408
a ₃	1.1087	Pr	8.277
a4	0.7127	P c	.154
^a 5	92340.	Q _{a,R}	2.713×10^{6}
^a 6	-27.444	Tc	50.0
в	1.2	t	6337.86
b ₁	1.7599	umin	5.0
ь ₂	1.0	V _L	250
^b 3	-1.1407×10^{-3}	v _U	1400
b ₄	1.2726×10^{-3}	W	1.055×10^8
b ₅	-3.0122	n _G	. 988
^b 61	3.4851×10^{-5}	η _P	.8
^b 62	1.5567×10^4	λ	1037.2
b an	1.		
c _{an}	8250.	μ	2.808
с _Е	.00067	μ _f	1.6402
с р	1.0	r	61.63
° _t	5.0	ρ _f	61.38
D o.min	.083333	Tmax	15000
f _{M.R}	.7217	ΔT _{max}	30.0
g	32.174		
h _{2.R}	989.1		
k	. 3393		

Except for c_1 , the components of c_1 are in close agreement with those used in [3] and given in Section 4. (We note that in [15], the value of c_1 conforms exactly to the above value, which is 1/2 of the value reported in [3]. This suggests that the value of c_1 derived here is correct.) The results reported in the remainder of the paper are consequently based on these components of c_1 .

Table 2 depicts the sensitivity of the optimal total cost with respect to numerous parameters of the model. As shown in this table, we do not conduct sensitivity analysis with respect to all of the model data (parameters) listed in Table 1. This is because some data cannot be meaningfully altered. For example, the gravitational constant g is assumed known and fixed. The specific heat c_p , the viscosity μ , etc., are internal properties of the fluid and cannot freely be altered.

As elaborated in our earlier papers, [8], [9], the sensitivity measure $\partial f^*(\varepsilon) / \partial \varepsilon_*$ corresponds to the rate of change of the optimal value function $f^*(\epsilon)$ with respect to ϵ_i , at a given value of ϵ . It would seem that the larger the absolute value of $-\partial f^*(\varepsilon)/\partial \varepsilon_+$ the greater the sensitivity of $f^*(\varepsilon)$ with respect to ε_{i} . However, it would be erroneous to conclude this and misleading to use the information without further analysis, as a guideline for making and implementing appropriate decisions. This is, in part, because this rate of change is local and does not necessarily reflect the change that can result from finite data changes. Nor does this measure reflect the likelihood of a given finite change. For such reasons, it is imperative to calculate some measures of stability in the large, to estimate or at least contain the cifects of finite data changes on the optimal solution. Moreover, sensitivities are often interpreted as the "change in $f^*(\varepsilon)$ per unit change in $|\varepsilon_{+}|^{\prime\prime}$. Such interpretations may also prove to be misleading because they tacitly suggest that a unit change is meaningful and that it might be realized in a given parameter ε_i . However, a one unit change for one parameter may be too large to be practically feasible, while for

T-437

- 20 -

T-437

(1)	(2)	(3) Parameter	(4)	(5) Scaled	(6)
Parameter No.	Parameter	Value	Sensitivity	Sensitivity	Rank
i	٤i	ēi	ðf*(ε)/ðε _i	$.01\overline{\epsilon}_{i} $ ($\partial f \star (\overline{\epsilon}) / \partial \epsilon_{i}$)	
1	a ₁	-159.9	22.577.27	36,101.05	8
2	a ₂	- 32.08	-31,283.56	-10,035.77	15
3	+ a ₃	1.1087	3294094 * 10 ⁸	-365,216.2	3
4	^a 4	.7127	341,840.9	2,436.30	24
5	^a 5	92340	8.288348	7,653.46	17
6	^a 6	-27.444	22,112.94	6,068.67	19
7	В	1.2	33,954.16	407.45	26
8	^b 1	1.7599	1,770.420	31,157.62	9
9	^b 2	1.0	-2,453,125.	-24,531.25	11
· 10	^b 3	-1.1407×10^{-3}	2583156×10^{10}	-29,466.06	11
11	^ь 4	1.2716×10^{-3}	.2680632 * 10 ⁸	341.14	27
12	^ь 5	-3.0122	3,316,445.	99,897.95	6
13	^b 61	3.4851×10^{-5}	$.1728371 \pm 10^{11}$	6,023.55	20
14	^b 62	1.5567×10^4	28.58427	4,449.71	22
15	b an	1.	4,710,256.	47,102.56	7
16	t c _{an}	8250.	80.40698	7,376.07	18
17	с _Е	.00067	.4588196 * 10 ¹⁰	30,740.91	10
18	† c _t	5.0	55,620.45	2,781.02	23
19	R	.06408	3,797,937.	154.96	28
	ł	1			

•

Table 2Optimal Value Function Sensitivity Results

continued

- 21 -

Table 2 (continued)Optimal Value Function Sensitivity Results

(1) Parameter No.	(2) Parameter	(3) Parameter Value	(4) Sensitivity	(5) Scaled Sensitivity	(6) Rank
i	^F i	Ēi		$.01\overline{\varepsilon}_{i} (\partial f \star (\overline{\varepsilon})/\partial \varepsilon_{i})$	
20	Р с	.154	6,609,746.	10,179.01	14
21	т _с	50.0	17,350.95	8,675.47	16
22	† t	6337.86	4,850.329	307,407.06	4
23	W	1.055 * 10 ⁸	0175986	18,566.52	13
24	† դ ₆	.988	$.3107304 + 10^8$	307,001.64	5
25	P mi	$1.25(=\frac{1}{.8})$	32,596.29	407.453	25
	$+(=\frac{1}{\eta_{p}})$				
⁻ 26	Q _{a,R}	2.713×10^{6}	12.97611	352,041.86	1
27	^h 2,R	989.1	31,283.35	309,423.61	2
28	f _{M,R}	.7217	-684,874.7	- 4,942.74	21

† Candidate for parametric bound calculation on $f^*(\varepsilon)$.

The same read and the second second second second second second second

والأفاق والافان والمعادلة والمساورة والمعارفة والمعارية والمراجع ومعارضها أنحو أرباع الأفلال كالعار والمتعالية

- 22 -

another it may be too small to be numerically significant. Parameters $n_{\rm C}$, the turbine efficiency, and W, the water flow rate, in Table 2 provide good examples of both instances.

With these points in mind, and assuming that the sensitivities are acceptable in a small (finite) neighborhood of the problem data, we prefer to base our judgments on "scaled" sensitivities such as those given in Column (5) of Table 2, which correspond to the estimated changes resulting from a one percent change in a given parameter value. Column 6 of this table ranks the above scaled sensitivity measures, in decreasing order of their absolute values. The importance of providing the kind of information depicted in Table 2 for real world systems seems obvious and cannot be overstated. For example, it provides guidelines for setting priorities on the relative importance of the parameters, and suggests actions that can be taken to obtain optimum marginal improvements in the optimum performance.

5.2 Optimal value function bounds

here, we apply the bound calculation technique discussed in Section 2, to derive piecewise linear parametric upper and lower bounds on the optimal total cost of the steam turbine power plant under study.

The parameters marked by (†) in Table 2 are retabulated in Table 3 and are selected for bound calculation. Notice that parameter a_3 is, in fact, a right-hand side parameter of constraint g_5 . Recall that

$$g_5 = c_{16} x_8^{-1} + c_{17} x_2 \le 1$$

where

$$c_{16} = \frac{Q_{a,R}}{a_3}$$
 and $c_{17} = -\frac{b_3}{a_3}$

Thus g₅ can be written as

$$Q_{a,R} x_8^{-1} - b_3 x_2 \le a_3$$
.

Thus, optimal value function of the model under study is a convex non-increasing function of a_3 .

- 23 -

Parameter No.	Parameter Name	Parameter Value	Perturbation
3	a ₃	1.1087	.2527
16	c an	8250.	-2062.5
18	°t	5.0	-1.25
22	t	6337.86	-1584.465
24	۹ _C	.988	247
25	$P_{mi}(=\frac{1}{\eta_p})$	1.25 $(=\frac{1}{.8})$	125

Table 3Parameters Selected For Bound Calculation

Also, parameters c_{an} , c_{L} , t and η_{G} taken one at a time, appear in the objective function coefficients linearly and do not appear in the constraints. Thus, the optimal annual cost of the plant under consideration is a concave nondecreasing function of each of these parameters. This means that our bound calculation procedure can readily be applied to these parameters. Notice that parameter η_{p} (pump efficiency) does not appear linearly in the objective function coefficients. For this reason, we replace $\frac{1}{\eta_{p}}$ by P_{mi} . This enables us to calculate optimal value bounds relative to changes in P_{mi} and, hence, relative to changes in η_{p} .

The last column in Table 3 shows the magnitude of the perturbations allowed in the respective parameter value, each taken in the direction that decreases the optimal value function, as determined by the sensitivity information in Table 2. In the following, we list the resulting parametric bounds on the optimal value over the given range of the parameter, obtained by our latest version of the computer programming code SENSUMT [10].

• Bounds w.r.t.
$$a_3$$
, 1.1087 $\leq a_3 \leq 1.3614$
Upper bound $\overline{F} = -.1792469 * 10^8 a_3 + .5163132 * 10^8$
Lower bound $\underline{F} = Max \{-.3294094 * 10^8 a_3 + .6827984 * 10^8, -.6760806 * 10^7 a_3 + .3643282 * 10^8\}$

Figure 2 depicts the resulting computer output for this and supplemental bound calculation for a_3 .

• Sounds w.r.t. e_{an} , 6187.5 $\leq e_{an} \leq 8250$.

- 25 -

Optimal Value Function Bounds When Par(3) is Perturbed

Point 1 (Unperturbed Solution) : Par(3) = 0.1108700D 01

F(Par(3)) = 0.3175823D 08

Point 2 (Perturbed Solution) : Par(3)) = 0.1361400D 01

F(Par(3)) = 0.2722866D 08

Line passing through Points 1 and 2 and overestimating f*

F = -0.1792469D 08 * Par(3) + 0.5163132D 08

Line underestimating f* at Point 1

 $F = -0.3294094D \ 08 \ * Par(3) \ + \ 0.6827984D \ 08$

Line underestimating f* at Point 2

F = -0.6760806D 07 * Par(3) + 0.3643282D 08

Quadratic Estimation of f* through Points 1 and 2

 $F = 0.4417841D \ 08 \ * Par(3) \ * 2 \ - \ 0.1270497D \ 09 \ * Par(3) \ + \ 0.1183135D \ 09$

f* bound evaluation at ten equidistant points between Points 1 and 2

<u>Par(3)</u>	Lower Bound	Upper Bound	Quad Estimate
1.109	0.3175823D 08	0.3175823D 08	0.3175823D 08
1.134	0.3092581D 08	0.3130527D 08	0.3105137D 08
1.159	0.3009339D 08	0.3085231D 08	0.3040093D 08
1.185	0.2926097D 08	0.3039935D 08	0.2980692D 08
1.210	0.2842856D 08	0.2994640D 08	0.2926933D 08
1.235	0.2808288D 08	0.2949344D 08	0.2878816D 08
1.260	0.2791204D 08	0.2904048D 08	0.2836342D 08
1.286	0.2774119D 08	0.2858753D 08	0.2799509D 08
1.311	0.2757035D 08	0.2813457D 08	0.2768319D 08
1.336	0.2739950D 08	0.2768161D 08	0.2742771D 08
1.361	0.2722866D 08	0.2722866D 08	0.2722866D 08

Figure 2.	Parametric	bounds	on	f*(a_)
-----------	------------	--------	----	--------

- 26 -

T-437

Upper bound
$$\tilde{F} = min \{89.40698 \ c_{an} + .3102062 * 10^8, 100.5829 \ c_{an} + .3094000 * 10^8\}$$

Lower bound $\underline{F} = 94.96585 \ c_{an} + .3097476 * 10^8$

. Bounds w.r.t.
$$c_t$$
, $3.75 \le c_t \le 5.0$
Upper bound $\overline{F} = \min \{55620.45 \ c_t + .3148012 * 10^8, 60878.7 \ c_t + .3145717 * 10^8\}$
Lower bound $\underline{F} = 58209.10 \ c_t + .3146718 * 10^8$

Figure 3 depicts the resulting computer output for bound calculation with respect to c_r .

Bounds w.r.t. t, 4753.395
$$\leq$$
 t \leq 6337.86
Upper bound \overline{F} = min {4850.329 t + .1017524 * 10⁷,
4860.131 t + .8543850 * 10⁶}
Lower bound \overline{F} = 4863.883 t + .9316157 * 10⁶

. Bounds w.r.t η_G , .741 $\leq \eta_G \leq$.988 Upper bound $\overline{F} = \min \{.3107304 * 10^8 \eta_G + .1058064 * 10^7, .3126812 * 10^8 \eta_G + .8912627 * 10^7\}$

Lower bound $\underline{F} = .3116310 \times 10^8 \eta_G + .9690873 \times 10^6$

- 27 -

Optimal Value Function Bounds When Par(18) is Perturbed

Point I (Unperturbed Solution) : Par(18) = 0.50000000 01	F(Par(18)) = 0.3175823D 08
Point 2 (Perturbed Solution) : Par(18)) = 0.3750000D 01	F(Par(18)) = 0.3168546D 08

Line passing through Points 1 and 2 and underestimating f*

F = 0.5820910D 05 * Par(18) + 0.3146718D 08

Line overestimating f* at Point 1

F = 0.5562045D 05 * Par(18) + 0.3148012D 08

Line overestimating f* at Point 2

*

F = 0.6087870D 05 * Par(18) + 0.3145717D 08

Quadratic estimation of f* through Points 1 and 2

F = -0.2070913D 04 * Par(18) **2 + 0.7632959D 05 * Par(18) + 0.3142835D 08

f* bound evaluation at ten equidistant points between Points 1 and 2

Par (18)	Lower Bound	Upper Bound	Quad Estimate
5.000	0.3175823D 08	0.3175823D 08	0.3175823D 08
4.875	0.31750950 08	0.3175127D 08	0.3175124D 08
4.750	0.3174367D 08	0.3174432D 08	0.3174419D 08
4.625	0.3173640D 08	0.3173737D 08	0,3173708D 08
4.500	0.3172912D 08	0.3173042D 08	0.3172990D 08
4.375	0.3172184D 08	0.3172346D 08	0.3172265D 08
4.250	0.3171457D 08	0.3171590D 08	0.3171535D 08
4.125	0.3170729D 08	0.3170829D 08	0.3170797D 08
4.000	0.3170002D 08	0,3170068D 08	0.3170053D 08
3.875	0.3169274D 08	0.3169307D 08	0.3169303D 08
3.750	0.3168546D 08	0.3168546D 08	0.3168546D 08

Figure 3. Parametric bounds on $f^{(c)}$

- 28 -

Bounds on
$$P_{mi} = \frac{1}{r_p}$$
, $1.125 \le \frac{1}{n_p} \le 1.25$ ($.8 \le n_p \le .889$)
Upper bound $\overline{F} = min \{.3259629 \pm 10^{5} - \frac{1}{n_p} \pm .3171748 \pm 10^{8}, .3536232 \pm 10^{5} - \frac{1}{n_p} \pm .3171425 \pm 10^{3}\}$
Lower bound $\underline{F} = .3355953 \pm 10^{5} - \frac{1}{n_p} \pm .3171628 \pm 10^{8}$

t

These bounds are piecewise linear as a function of P_{mi} , hence they are nonlinear as a function of η_p .

- 29 -

REFERENCES

- [1] ARMACOST, R. L., and A. V. FIACCO (1976). NLP sensitivity analysis for RHS perturbation: A brief survey and recent second-order extensions. Technical Paper Serial T-334. Institute for Management Science and Engineering, The George Washington University.
- [2] DEMBO, R. S. (1978). Sensitivity analysis in geometric programming.
 Working Paper No. 35. School of Organization and Management,
 Yale University.
- [3] ECKER, J. G. and R. D. WIEBKING (]976). Application of geometric programming to energy related design problems. In <u>ENERGY</u>: <u>MATHEMATICS AND MODELS</u>, 153-175. Edited by Fred S. Roberts. Society for Industrial and Applied Mathematics.
- [4] ECKER, J. G. and R. D. WIEBKING (1976). Optimal selection of steam turbine exhaust annulus and condenser sizes by geometric programming. <u>Engineering Optimization</u> 2, 173-181.
- [5] FALK, J. E. and R. M. SOLAND (1969). An algorithm for separable nonconvex programming problems. <u>Management Sci.</u> 15(9), 550-569.
- [6] FIACCO, A. V. (1976). Sensitivity analysis for nonlinear programming using penalty methods. Mathematical Programming 10(3), 287-311.

- 30 -

- [7] FIACCO, A. V. (1981). Computable optimal value bounds and solution vector estimates for general parametric NLP programs. Technical Paper T-451. Institute for Management Science and Engineering, The George Washington University.
- [8] FIACCO, A. V. and A. GHAEMI (1979). Optimal treatment levels of a stream abatement system under three environmental control policies, Part II: Preliminary sensitivity analysis of a convex equivalent of the fixed dissolved oxygen requirement policy GP model using SENSUMT. Technical Paper Serial T-405. Program in Logistics, The George Washington University.
- [9] FIACCO, A. V. and A. GHAEMI (1979). Sensitivity analysis of a nonlinear structural design problem. Technical Paper Serial T-413. Program in Logistics, The George Washington University.
- [10] FIACCO, A. V. and A. GHAEMI (1980). A USER'S MANUAL FOR SENSUMT: A computer programming model for solution, sensitivity analysis and bound calculation in parametric nonlinear programs. Technical Paper Serial T-434. Institute for Management Science and Engineering, The George Washington University.

[11] GHAEMI, A. (1980). Computable stability analysis techniques for nonlinear programming: Sensitivities, optimal value bounds, and applications. D.SC. Dissertation, Department of Operations Research, The George Washington University.

- 31 -

- [12] KRENZ, JERROLD H. (1976). <u>Energy Conversion and Utilization</u>. Allyn and Bacon, Inc.
- [13] MANGASARIAN, O. L. and J. B. ROSEN (1964). Inequalities for stochastic nonlinear programming problems. <u>Operations Res</u>. 12(1), 143-154.
- [14] MCCORMICK, G. P. (1976). Computability of global solutions to factorable nonconvex programs Part I: Convex underestimating problems. <u>Mathematical Programming</u> 10(2), 147-175.
- [15] WIEBKING, R. D. (1973). Deterministic and stochastic geometric programming models for optimal engineering design problems in electric power generation and computer solutions. D.Sc. Dissertation, Rensselear Polytechnic Institute.
- [16] WILSON, W. A. (1957). An analytic procedure for optimizing the selection of power plant components. <u>ASME Transactions</u> 79.

[17] WILSON, W. A. and L. G. MALOUF (1956). An approach to the economic problem of matching condenser surface with exhaust annulus area. <u>ASME Transactions</u> 78.

- 32 -

THE GEORGE WASHINGTON UNIVERSITY

Program in Logistics

Distribution List for Technical Papers

The George Washington University Office of Sponsored Research Gelman Library Vice President H. F. Bright Dean Harold Liebowitz Dean Henry Solomon

ONR Chief of Naval Research (Codes 200, 434) Resident Representative

OPNAV OP-40 DCNO, Logistics Navy Dept Library NAVDATA Automation Cmd

Naval Aviation Integrated Log Support

NARDAC Tech Library

Naval Electronics Lab Library

Naval Facilities Eng Cmd Tech Library

Naval Ordnance Station Louisville, Ky. Indian Head, Md.

Naval Ordnance Sys Cmd Library

Naval Research Branch Office Boston Chicago New York Pasadena San Francisco

Naval Ship Eng Center Philadelphia, Pa.

Naval Ship Res & Dev Center

Naval Sea Systems Command PMS 30611 Tech Library Code 073

Naval Supply Systems Command Library Operations and Inventory Analysis

Naval War College Library Newport

Newport BUPERS Tech Library

FMSO

USN Ammo Depot Earle

USN Postgrad School Monterey Library Dr Jack R. Borsting Prof C. R. Jones

US Coast Guard Academy Capt Jimmie D. Woods

US Marine Corps Commandant Deputy Chief of Staff, R&D

Marine Corps School Quantico Landing Force Dev Ctr Logistics Officer Armed Forces Industrial College

Army War College Library Carlisle Barracks

Army Cmd & Gen Staff College

Army Logistics Mgt Center Fort Lee

Commanding Officer, USALDSRA New Cumberland Army Depot

Army Inventory Res Ofc Philadelphia

Army Trans Material Cmd TCMAC-ASDT

Air Force Headquarters AFADS-3 LEXY SAF/ALG

Griffiss Air Force Base Reliability Analysis Center

Gunter Air Force Base AFLMC/XR

Maxwell Air Force Base Library

Wright-Patterson Air Force Base AFLC/OA Research Sch Log AFALD/XR

Defense Technical Info Center

National Academy of Sciences Maritime Transportation Res Bd Lib

National Bureau of Standards Dr B. H. Colvin Dr Joan Rosenblatt

National Science Foundation

National Security Agency

Weapons Systems Evaluation Group

British Navy Staff

National Defense Hdqtrs, Ottawa Logistics, OR Analysis Estab

American Power Jet Co George Chernowitz

General Dynamics, Pomona

General Research Corp Library

Logistics Management Institute Dr Nurray A. Geisler

Rand Corporation Library Mr William P. Hutzler

Carnegie-Mellon University Dean H. A. Simon Prof G. Thompson Case Western Reserve University Prof B. V. Dean Pref M. Mesarovic

Cornell University Prof R. F. Bochhofer Prof R. W. Conway Prof Andrew Schultz, Jr.

Cowles Foundation for Research in Ecomonics Prof Martin Shubik

Florida State University Prof R. A. Bradley

Harvard University Prof W. G. Cochran Prof Arthur Schleifer, Jr.

Princeton University Prof A. W. Tucker Prof J. W. Tukey Prof Geoffrey S. Watson

Purdue University Prof S. S. Gupta Prof H. Rubin Prof Andrew Whinston

Stanford University Prof T. W. Anderson Prof Kenneth Arrow Prof G. B. Dantzig Prof F. S. Hillier Prof D. L. Iglehart Prof Samuel Karlin Prof G. J. Lieberman Prof Herbert Solomon Prof A. F. Veinott, Jr.

University of California, Berkeley Prof R. E. Barlow Prof D. Gale Prof Jack Kiefer

University of California, Los Angeles Prof R. R. O'Neill

University of North Carolina Prof W. L. Smith Prof M. R. Leadbetter

University of Pennsylvania Prof Russell Ackotf

University of Texas Institute for Computing Science and Computer Applications

Yale University Prof F. J. Anscombe Prof H. Scarf

Prof Z. W. Birnbaum University of Washington

Prof B. H. Bissinger The Pennsylvania State University

Prof Seth Bonder University of Michigan

Prof G. E. Box University of Wisconsin

Dr Jerome Bracken Institute for Defense Analyses

Continued

Prof A. Charnes University of Texas

Prof H. Chernoff Mass Institute of Technology

Prof Arthur Cohen Rutgers - The State University

Mr Wallace M. Cohen US General Accounting Office

Prof C. Derman Columbia University

Prof Masao Fukushima Kyoto University

Prof Saul I. Gass University of Maryland

Dr Donald P. Gaver Carmel, California

Prof Amrit L. Goel Syracuse University

Prof J. F. Hannan Michigan State University

Prof H. O. Hartley Texas A & M Foundation

Prof W. M. Hirsch Courant Institute

Dr Alan J. Hoffman IBM, Yorktown Heights

Prof John R. Isbell SUNY, Amherst

Dr J. L. Jain University of Delhi

Prof J. H. K. Kao Polytech Institute of New York Prof W. Kruskal University of Chicago

Mr S. Kuman University of Madras

Prof C. E. Lemke Rensselaer Polytech Institute

Prof Loynes University of Sheffieid, England

Prof Tom Maul Kowloon, Hong Kong

Prof Steven Nahmias University of Santa Clara

Prof D. B. Owen Southern Methodist University

Prof P. R. Parathasarathy Indian Institute of Technology

Prof E. Parzen Texas A & M University

Prof H. O. Posten University of Connecticut

Prof R. Remage, Jr. University of Delaware

Prof Hans Riedwyl University of Berne

Mr David Rosenblatt Washington, D. C.

Prof M. Rosenblatt University of California, San Diego

Prof Alan J. Rowe University of Southern California Prof A. H. Rubenstein Northwestern University

Prof Thomas L. Saaty University of Pittsburgh

Dr M. E. Salveson West Los Angeles

Prof Gary Scudder University of Minnesota

Prof Edward A. Silver University of Waterloo, Canada

Prof Rosedith Sitgreaves Washington, DC

LTC G. L. Slyman, MSC Department of the Army

Prof M. J. Sobel Georgia Inst of Technology

Prof R. M. Thrall Rice University

Dr S. Vajda University of Sussex, England

Prof T. M. Whitin Wesleyan University

Prof Jacob Wolfowitz University of South Florida

Prof Max A. Woodbury Duke University

Prof S. Zacks SUNY, Binghamton

Dr Israel Zang Tel-Aviv University

February 1981

