

AD-A110 592

NAVAL SURFACE WEAPONS CENTER DAHLGREN VA
USE OF AQUEOUS FOAM TO REDUCE SHOULDER-LAUNCHED ROCKET NOISE LE--ETC(U)

F/G 19/7

JUL 81 L L PATER

NSWC/TR-81-268


NL

UNCLASSIFIED

1-1
AD-A110 592



END
DATE
FILMED
3-82
DTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS (1963-A)

AD A110592

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER TR 81-268	2. GOVT ACCESSION NO. AD-A11C 597	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) USE OF AQUEOUS FOAM TO REDUCE SHOULDER-LAUNCHED ROCKET NOISE LEVEL: FEASIBILITY INVESTIGATION	5. TYPE OF REPORT & PERIOD COVERED Final	
	6. PERFORMING ORG. REPORT NUMBER	
7. AUTHOR(s) L. L. Pater	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Surface Weapons Center (N43) Dahlgren, VA 22448	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62332N ZF-32-300-082	
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Material Command Washington, DC 20360	12. REPORT DATE July 1981	
	13. NUMBER OF PAGES 44	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) UNCLASSIFIED	
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Military Operations in Urban Terrain (MOUT) Program noise signature reduction aqueous foam		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The efficacy of aqueous foam for reducing the noise level due to the breech blast of a shoulder-launched rocket weapon was investigated experimentally. Results indicated that, for canisters of practical size, modest reductions in peak sound pressure level (SPL) could be achieved, at the expense of significantly increased recoil impulse.		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-LF-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

ijii

411 567

50

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

FOREWORD

This report was prepared as part of the Military Operations in Urban Terrain (MOUT) Program, a U.S. Marine Corps exploratory development effort under Naval Materiel Command Program Element 62332N ZF-32-300-082.

This report has been reviewed and approved by F. H. Maillie and J. F. Horton of the Systems Safety Division, Combat Systems Department.

Released by:



THOMAS A. CLARE, Head
Combat Systems Department

Approved For	
Reviewed	✓
Checked	
Mailbox	
Dist	Special
A	



ACKNOWLEDGEMENTS

The work described herein was greatly facilitated by the assistance and cooperation of Mr. Jerry Arszman of U.S. Army MIRADCOM (Missile Research and Development Command) and Mr. Charles Carter and Mr. George Pinson of Boeing Army Systems Division, Huntsville, Alabama. Contributions included the sharing of previous data and experience and the loan of the canister hardware.

CONTENTS

	<u>Page</u>
INTRODUCTION	1
OBJECTIVE	1
APPARATUS	1
RESULTS	2
CONCLUSIONS	6
REFERENCES	6
APPENDIXES	
A--BALLISTIC PENDULUM	9
B--EXPERIMENTAL DATA	15
C--TYPICAL RAW NOISE DATA TRACES	25
DISTRIBUTION	

LIST OF ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
1	Ballistic Pendulum With LAW Installed in Cradle	3
2	Breech View of Pendulum and Near-Field Pressure Transducers (LAW Installed in Cradle)	4
3	Ballistic Pendulum Showing LAW Installed in Cradle and a Typical Canister Attached to LAW Breech	5
A-1	Ballistic Pendulum	9
A-2	Free Body Diagram of a Typical Rod	10
A-3	Free Body Diagram of Pendulum Mass (showing two typical suspension points)	10
A-4	Ballistic Pendulum Parameters	12
C-1	Typical Sound Pressure Data for Gunner's Head Location	25
C-2	Typical Sound Pressure Data at 90°, ≈ 1 Meter from Breech . .	28
C-3	Typical Peak-and-Hold Sound Pressure Level Data in the Far Field	31

List of Tables

<u>Table</u>		<u>Page</u>
B-1	Transducer Types and Locations	16
B-2	Near Field Peak Overpressure Data	17
B-3	Bare Breech Overpressure Data	18
B-4	Ballistic Pendulum Recoil Impulse Data	19
B-5	Effect of Empty Canisters Relative to Bare Breech	20
B-6	Effect of Foam Relative to Empty Canisters	21

INTRODUCTION

Considerable effort has been devoted recently toward reducing the noise signature of weapons, primarily to avoid hearing damage to nearby personnel. One type of weapon that has received a great deal of attention is the shoulder-launched in-tube-burning rocket. The need for reduced noise level becomes more acute when the weapon is to be fired from an enclosed space such as might occur in urban warfare.

Recent investigations^{1,2,3} have shown that aqueous foam can greatly reduce the blast pressure resulting from explosive charge detonations and gun muzzle blast. The aqueous foam that has been used for this purpose is basically foam of the type commonly used in firefighting. In the case of guns, the foam was contained in a metal canister mounted on the gun muzzle, and resulted in peak sound pressure level (SPL) reductions in excess of 20 dB.³ Since the propellant gas flow from the muzzle of a gun bears some resemblance to that from the breech of a shoulder-fired rocket launcher, it seemed plausible that a foam-filled canister mounted on the breech of such a launcher tube might yield significant noise level reductions.

OBJECTIVE

The objective of the investigation reported herein was to determine the feasibility and efficacy of aqueous foam for reduction of noise due to the firing of a shoulder-launched rocket weapon.

APPARATUS

The rocket launcher used for the experiments was the 66-mm M72A2 Light Antitank Weapon (LAW), chosen as being representative of the weapon type and because of availability. The LAW round was mounted in the cradle of a ballistic pendulum as shown in Figure 1 and was fired by means of a yoke linkage actuated by an automotive solenoid. The warhead was detonated against a large steel plate located approximately 100 meters downrange. The ballistic pendulum enabled measurement of recoil impulse* as described in detail in Appendix A. Each component used for each test round was carefully weighed; extra weight was added for some rounds, for which large recoil impulse was expected, to maintain the motion of the pendulum within safe limits. The motion of the pendulum was measured by means of a pen attached to one of the suspension rods in such a fashion that it traced an arc on an indicator card, enabling measurement of the maximum angular motion of the pendulum.

*Here "impulse" has the strict meaning "time integral of force."

Instrumentation consisted of four blast gages and a wall pressure gage, as described in detail in Table B-1 of Appendix B. The gages are shown in the photographs of Figures 1, 2, and 3. A General Radio Model 1982 sound level meter, located at 200 ft (61 meters) from the breech along an azimuth 130° from the line of fire, was used to document the far-field SPL. All data was recorded on magnetic tape using an FM recorder with 40 kHz frequency response.

The aqueous foam used was firefighting foam produced at an expansion ratio of 27. Each test round that utilized foam was fired within 3 minutes after the foam was produced, to minimize changes in foam characteristics due to foam structure deterioration. The foam was contained in aluminum canisters described in detail in Reference 4; a typical canister is shown in Figure 3. Shapes and sizes of the canisters tested are described in detail in Appendix B.

RESULTS

Typical raw data plots are shown in Appendix C. Tabulated numerical data and calculated performance parameters are shown in Appendix B. Table B-3, a compilation of data from bare breech rounds only, illustrates clearly that considerable round-to-round variation in noise level (standard deviation of about one to two decibels) occurred. This variability must be kept in mind during interpretation of the data.

The effects of the empty canisters, relative to bare breech, are summarized in Table B-5. It can be seen that the empty canister configurations tested offer a generally modest (~5 dB) reduction in peak noise level at the gunner's head location, at the expense of a significant (~3 lbf-sec) increase in recoil impulse.*

The data showing the effect of the foam, relative to the empty canisters, are summarized in Table B-6. These data indicate that the peak noise level reduction due to foam is apparently not large, perhaps on the order of two decibels. The data, unfortunately, demonstrates considerable variability. Also, the LAW uses "det cord" as the ignition link between a percussion cap and the rocket motor, which results in a shock wave prior to rocket motor ignition. Evidence of the det cord noise may be seen in the far-field noise data of Figure C-3, which is peak flat (unweighted) sound pressure level "peak-and-hold" data. In Figure C-3(a) the initial level is the maximum ambient level (about 97 dB) prior to the test round. The first level change is due to the det cord, followed several milliseconds later by a larger level change due to the breech blast. This same sequence is present in Figure C-3(b), with the

*A recoil impulse of 3 lbf-sec is roughly characteristic of typical shotguns and high-powered sporting rifles.




Figure 1. Ballistic Pendulum With LAW Installed in Cradle




Figure 2. Breech View of Pendulum and Near-Field Pressure Transducers
(LAW Installed in Cradle)



det cord noise level evidently somewhat reduced by the empty canister. Figure C-3(c) shows that the foam reduced the det cord noise to a level lower than the initial maximum ambient level. The above description applies to all of the data rounds. It is possible that the shock wave due to the det cord may have dispersed or otherwise affected the foam such that only a small reduction in breech blast noise level was obtained. Thus, the effect on shoulder-launched rocket noise level due to a foam-filled canister was not conclusively demonstrated in the present experiment. It is clear from the data presented in Table B-6 that filling the canisters with foam resulted in greatly increased recoil impulse.

CONCLUSIONS

Aqueous foam contained in breech-mounted metal canisters yielded rather small peak noise level reductions, at the expense of greatly increased recoil impulse. Size, weight, and remaining engineering development of suitable canisters and foam generators are other important considerations. Thus, it appears doubtful that aqueous foam will be of general utility for reducing noise levels due to shoulder-launched rocket weapons.

REFERENCES

1. A. Clark, et al., *The Reduction of Noise Levels from Explosive Test Facilities Using Aqueous Foam*, Royal Armament Research and Development Establishment, Ft. Halstead, Sevenoaks, Kent, U.K., 1976.
2. D. Dadley, E. Robinson, and V. Pickett, *The Use of Foam to Muffle Blasts from Explosions*, paper presented at IEP-ABCA-5 conference at Indian Head, MD, June 1976.
3. Pater, L. L. and J. W. Shea, *Use of Foam to Reduce Gun Blast Noise Levels*, NSWC TR 81-94, Naval Surface Weapons Center, Dahlgren, VA, March 1981.
4. Carter, Charles R., *Rocket Motors Peak Noise Reduction Program*, Report T-CR-78-27, Boeing Aerospace Company, Army Systems Division, Huntsville, AL, 30 September 1978.

APPENDIX A
BALLISTIC PENDULUM

7/8

BALLISTIC PENDULUM

Consider a ballistic pendulum as shown in Figure A-1, consisting of a mass m_p suspended by N rods each of mass m_i ($i = 1, 2, \dots, N$) and uniform length ℓ . The mass m_p is acted upon by an impulsive horizontal force $F_R(t)$, which is of such short duration Δt that very little motion occurs* ($\theta \approx 0$).




Figure A-1. Ballistic Pendulum

Consider a typical rod, as shown in Figure A-2. Making use of the principle that angular impulse is equal to the change in angular momentum, with rotation about the fixed point O_i , leads to the expression

$$\ell \int_{\Delta t} F_{i_x} dt = I_{O_i} \omega = \frac{m_i \ell^2}{3} \frac{V_p}{\ell} \quad (\text{A-1})$$

or

$$\int_{\Delta t} F_{i_x} dt = \frac{m_i V_p}{3}$$

where V_p is the magnitude of the (essentially horizontal) velocity of the pendulum mass after the short time Δt .

*The period of oscillation of the experimental apparatus was approximately two seconds, whereas the duration of the recoil force due to the rocket motor was about two milliseconds. Thus, the impulsive-force model is appropriate.




Figure A-2. Free Body Diagram of a Typical Rod




Figure A-3. Free Body Diagram of Pendulum Mass (showing two typical suspension points)

Now consider the pendulum mass. Making use of the fact that linear impulse is equal to the change in linear momentum yields

$$\int_{\Delta t} F_R dt - \sum_{i=1}^N \int_{\Delta t} F_{i_x} dt = m_p V_p \quad (A-2)$$

Using equation A-1 to eliminate the terms involving the internal components, F_{i_x} yields

$$I_R = \int_{\Delta t} F_R(t) dt = m_p V_p + \sum_{i=1}^N \frac{m_i V_p}{3}$$

or

$$I_R = V_p \left(m_p + \frac{1}{3} \sum_{i=1}^N m_i \right) \quad (A-3)$$

Energy methods can be used to determine how high the pendulum swings. Note that the center of mass of the uniform suspension rods rises half as much as the pendulum mass.

$$\sum_{i=1}^N \frac{1}{2} I_{o_i} w^2 + \frac{1}{2} m_p V_p^2 = m_p gh + \sum_{i=1}^N m_i g \frac{h}{2}$$

But

$$I_{o_i} = \frac{m_i \ell^2}{3} \quad (\text{for a uniform slender rod})$$

$$w = V_p / \ell$$

so

$$\frac{V_p^2}{2} \left(m_p + \frac{1}{3} \sum_{i=1}^N m_i \right) = gh \left(m_p + \frac{1}{2} \sum_{i=1}^N m_i \right) \quad (A-4)$$

where

$$h = \ell(1 - \cos \theta) \quad (A-5)$$

Combining equations A-3 and A-4 to eliminate V_p yields*

$$I_R^2 = 2gh \left(m_p + \frac{1}{3} \sum_{i=1}^N m_i \right) \left(m_p + \frac{1}{2} \sum_{i=1}^N m_i \right) \quad (A-6)$$

A graphical representation of equation A-6 is shown in Figure A-4. These curves were used during the experiment to select appropriate values of pendulum mass m_p to maintain pendulum rise h within safe limits.




Figure A-4. Ballistic Pendulum Parameters

*Note that if the mass of the rods is neglected, the result becomes

$$I_R^2 = 2gh m_p^2$$


which is the result for a simple pendulum.

APPENDIX B
EXPERIMENTAL DATA

13/14

CANISTER CONFIGURATION NOMENCLATURE

Test rounds that did not employ any canister, fired to provide baseline information, are denoted by "BB" (Bare Breech). The various canister configurations tested are denoted by a shorthand notation as follows:



For example, F-8-9-3,6 would signify a foam-filled canister of 8" I.D., 9" in length, with interior baffles at 3" and at 6" behind the launch tube exit plane. The configuration C-10 consisted of simply a 10 inch (25.4 cm) diameter disk attached to the breech of the launcher. All baffles and endcaps utilized a 2.6 inch (66 mm) diameter center hole, which is the same as the inside diameter of the launch tube.

Table B-1. Transducer Types and Locations

Symbol	Transducer	Location
P1	PCB 113A51 "Lollipop"	P1 and P2 were located approximately 90 cm (35.5 in.) from the breech exit plane centroid (for bare breech rounds) or the canister exit plane centroid, along an azimuth of 90° from the direction of fire.
P2	Susquehanna ST-2	
P3	Susquehanna ST-2	12.3 cm (4.8 in.) left of tube centerline, 21.5 cm (8.5 in.) forward of launch tube exit plane (represents canister head location), transducer oriented with plane of sensing surface through launch tube centerline (see Figure 2).
P4	Susquehanna ST-2	12.3 cm (4.8 in.) right of tube centerline, 21.5 cm (8.5 in.) forward of launch tube exit plane (reflection of P3 location), transducer oriented with plane of sensing surface vertical and parallel to launch tube centerline (see Figure 2).
P5	PCB 111A22	Located in the breech support ring of the ballistic pendulum apparatus, used to provide zero reference for elapsed time for the other pressure gages.

Table B-2. Near Field Peak Overpressure Data

Round No.	Configuration	Peak Overpressure (psi) @			
		P1	P2	P3	P4
1	BB	1.70	1.90	2.23	--
2	BB	2.50	2.40	2.52	--
3	BB	2.55	2.50	2.26	1.60
4	C-8-3	2.60	2.25	1.20	0.82
5	F-8-3	2.05	1.25	1.10	1.08
6	C-10-3	3.00	2.35	0.92	1.18
7	F-10-3	1.50	1.40	0.98	1.24
8	F-10-3	1.60	1.35	1.74	2.00
9	C-8-9	1.70	1.58	0.80	0.90
10	BB	2.21	2.05	1.58	2.18
11	BB	2.72	--	2.40	2.70
12*	F-8-9	*	*	*	*
13	C-8-9-Open	2.82	2.32	2.43	2.04
14**	F-8-9-Open	1.90	1.93	2.08	1.52
15	BB	2.52	2.20	2.16	2.68
16	C-8-6	2.37	1.78	1.18	1.34
17	F-8-6	1.62	1.33	1.10	0.52
18*	C-10-6	*	*	*	*
19	BB	2.65	--	2.41	2.32
20	C-8-6-3	2.63	1.92	1.08	1.12
21	F-8-6-3	1.25	1.10	0.9	0.79
22	C-8-9-3,6	1.85	1.40	1.01	0.89
23	F-8-9-3,6	1.40	--	0.82	0.83
24	C-10	2.08	2.10	1.28	1.39
25	BB	2.31	--	1.70	1.78
26	C-8-9-3,6	2.00	1.90	0.80	0.98
27	C-10-6-3	2.31	--	1.18	1.57

* Data invalid due to hardware malfunction.

** Most of the foam ran out of the open aft end of the canister before the round could be fired.

Table B-3. Bare Breech Overpressure Data

Round No.	P1 (psi)	P2 (psi)	P3 (psi)	P4 (psi)
1	1.70	1.90	2.23	--
2	2.50	2.40	2.52	--
3	2.55	2.50	2.26	1.60
10	2.21	2.05	1.58	2.18
11	2.72	--	2.40	2.70
15	2.52	2.20	2.16	2.68
19	2.65	--	2.41	2.32
25	2.31	--	1.70	1.78
Mean	2.40 (178.4 dB)	2.21 (177.6 dB)	2.16 (177.4 dB)	2.21 (177.6 dB)
σ	0.33	0.24	0.34	0.45
	P1 (dB)	P2 (dB)	P3 (dB)	P4 (dB)
1	175.4	176.3	177.7	--
2	178.7	178.4	178.8	--
3	178.9	178.7	177.8	174.8
10	177.6	177.0	174.7	177.5
11	179.4	--	178.4	179.4
15	178.8	177.6	177.4	179.3
19	179.2	--	178.4	178.1
25	178.0	--	175.4	175.8
Mean	178.2	177.6	177.3	177.5
σ	1.3	1.0	1.5	1.9

Table B-4. Ballistic Pendulum Recoil Impulse Data

Round No.	Configuration	m_p (lbm)	θ (deg)	h (in.)	I_R (lbf-sec)
1	BB	15.86	5.5	0.04	0.25
2	BB	15.84	4.5	0.03	0.21
3	BB	15.80	3.5	0.02	0.17
4	C-8-3	24.98	23.4	0.74	1.63
5	F-8-3	25.18	59.3	4.68	4.12
6	C-10-3	28.74	20.6	0.58	1.65
7	F-10-3	29.09	72.0	6.82	5.71
8	F-10-3	29.42	84.0	9.17	6.70
9	C-8-9	30.46	62.5	5.18	5.20
10	BB	16.16	--	--	--
11	BB	16.41	8.0	0.09	0.38
12*	F-8-9	54.25	*	*	*
13	C-8-9-Open	26.64	26.5	0.95	1.96
14	F-8-9-Open	26.71	21.0	0.60	1.56
15	BB	16.51	7.0	0.07	0.34
16	C-8-6	51.00	29.5	1.18	4.09
17	F-8-6	51.40	61.5	5.02	8.50
18*	C-10-6	55.48	*	*	*
19	BB	16.43	7.5	0.08	0.36
20	C-8-6-3	29.84	39.0	2.05	3.21
21	F-8-6-3	43.13	65.0	5.59	7.56
22	C-8-9-3,6	46.99	30.5	1.27	3.92
23	F-8-9-3,6	47.63	83.0	8.97	10.55
24	C-10	20.01	12.5	0.21	0.70
25	BB	29.35	--	--	--
26	C-8-9-3,6	47.00	32.0	1.38	4.08
27	C-10-6-3	48.02	22.0	0.66	2.88
1,2,3,11,15,19	BB (Mean)	--	--	--	0.28

* Data invalid due to hardware malfunction.

NOTE: $l = 35.72$ inches (90.7 cm) and $\Sigma m_i = 3.12$ lbm (1.4 kg) for all rounds. Weight was added to m_p for some rounds to maintain θ within safe limits.

Table B-5. Effect of Empty Canisters Relative to Bare Breech

Configuration	Round No.	I_R (lbf-sec)	ΔI_R (lbf-sec)	P1 (dB)	$\Delta P1$ (dB)	P2 (dB)	$\Delta P2$ (dB)	P3 (dB)	$\Delta P3$ (dB)	P4 (dB)	$\Delta P4$ (dB)
BB (Mean) "Baseline"	1,2,3, 11,15,19	0.28	--	178.2	--	177.6	--	177.3	--	177.5	--
C-8-3	4	1.63	+1.35	179.0	+0.8	177.8	+0.2	172.3	-5.0	169.0	-8.5
C-8-6	16	4.09	+3.81	178.2	+0.0	175.8	-1.8	172.2	-5.1	173.3	-4.2
C-8-6-3	20	3.21	+2.93	179.2	+1.0	176.4	-1.2	171.4	-5.9	171.7	-5.8
C-8-9	9	5.20	+4.92	175.4	-2.8	174.7	-2.9	168.8	-8.5	169.8	-7.7
C-8-9-Open	13	1.96	+1.68	179.8	+1.6	178.1	+0.5	178.5	+1.2	176.9	-0.6
C-8-9-3,6	22	3.92	+3.64	176.1	-2.1	173.7	-3.9	170.8	-6.5	169.7	-7.8
C-8-9-3,6	26	4.08	+3.80	176.8	-1.4	176.3	-1.3	168.8	-8.5	170.6	-6.9
C-10 (Disk)	24	0.70	+0.42	177.1	-1.1	177.2	-0.4	172.9	-4.4	173.6	-3.9
C-10-3	6	1.65	+1.37	180.3	+2.1	178.2	+0.6	170.0	-7.3	172.2	-5.3
C-10-6-3	27	2.88	+2.60	178.0	-0.2	--	--	172.2	-5.1	174.7	-2.8


Table B-6. Effect of Foam Relative to Empty Canisters

Configuration	Round No.	I _R (lbf-sec)	ΔI _R (lbf-sec)	P1 (dB)	ΔP1 (dB)	P2 (dB)	ΔP2 (dB)	P3 (dB)	ΔP3 (dB)	P4 (dB)	ΔP4 (dB)
F-8-3	5	4.12	+2.49	177.0	-2.0	172.7	-5.1	171.6	-0.7	171.4	+2.4
F-8-6	17	8.50	+4.41	174.9	-3.3	173.2	-2.6	171.6	-0.6	165.1	-8.2
F-8-6-3	21	7.56	+4.35	172.7	-6.5	171.6	-4.8	169.8	-1.6	168.7	-3.0
F-8-9-3,6	23	10.55	+6.63	173.7	-2.4	--	--	169.0	-1.8	169.1	-0.6
F-10-3	7	5.71	+4.06	174.3	-6.0	173.7	-4.5	170.6	+0.6	172.6	+0.4
F-10-3	8	6.70	+5.05	174.8	-5.5	173.3	-4.9	175.6	+5.6	176.8	+4.6

APPENDIX C


TYPICAL RAW NOISE DATA TRACES

23/24




C-1(a). Bare Breech

Figure C-1. Typical Sound Pressure Data for Gunner's Head Location




C-1(b). Canister, Empty

Figure C-1. Typical Sound Pressure Data for Gunner's Head Location (Continued)




C-1(c). Canister, Foam-Filled

Figure C-1. Typical Sound Pressure Data for Gunner's Head Location (Continued)




C-2(a). Bare Breech

Figure C-2. Typical Sound Pressure Data at 90°, ≈ 1 Meter from Breech




C-2(b). Canister, Empty

Figure C-2. Typical Sound Pressure Data at 90°, ≈ 1 Meter from Breech (Continued)




C-2(c). Canister, Foam-Filled

Figure C-2. Typical Sound Pressure Data at 90°, ≈ 1 Meter from Breech (Continued)




C-3(a). Bare Breech

Figure C-3. Typical Peak-and-Hold Sound Pressure Level Data in the Far Field



C-3(b). Canister, Empty

Figure C-3. Typical Peak-and Hold Sound Pressure Level Data in the Far Field (Continued)



C-3(c). Canister, Foam-Filled

Figure C-3. Typical Peak-and-Hold Sound Pressure Level Data in the Far Field (Continued)

DISTRIBUTION

Director
Defense Advanced Research Projects Agency
1400 Wilson Boulevard
Arlington, VA 22209

Department of Defense Explosive Safety Board
Hoffman Building
2461 Eisenhower Avenue
Alexandria, VA 22331
ATTN: T. Zaker

Commander
Naval Amphibious School
Little Creek, VA 23461

Commandant
Headquarters, U.S. Marine Corps
Washington, DC 20380
ATTN: MCOTI
MCOTO

(2)

Director
Development Center
Marine Corps Development and Education Command
Quantico, VA 22134

U.S. Army Engineer Research and Development Laboratories
Ft. Belvoir, VA 22060

Commanding General
White Sands Proving Ground
White Sands, NM 88002

Southwest Research Institute
San Antonio, TX 78291
ATTN: P. S. Westine

National Technical Information Service
Springfield, VA 22161

Commander
Naval Weapons Center
China Lake, CA 93555
ATTN: Code 6223 (Pullen)
Code 0632 (Finder)
Code 6224 (Young)

(3)

DISTRIBUTION (Continued)

Commander

Naval Sea Systems Command
Washington, DC 20362

ATTN: 62Y11 (W. Greenlees)
62Y1B (T. Lee)
62R (Edwards)
04H (Daugherty)

(4)

Commander

Naval Facilities Engineering Command
200 Stovall Street
Alexandria, VA 22332

ATTN: 2013C (D. Kurtz)
0451D (Buynak)
032B (S. Hurley)

(3)

Commander

Naval Undersea Center
San Diego, CA 92132

ATTN: 401 (R. Young)
401 (R. Gales)

(2)

Commander

Naval Air Station
North Island, CA 92135

ATTN: 661 (R. Glass)

Chief of Naval Operations

The Pentagon
Washington, DC 20350

ATTN: OP04E (CDR Greenwald)
OP45 (C. Zillig)
OP098
OP099
OP991B (Malehorn)
OP64

(6)

Commander

Naval Environmental Support Office
Naval Construction Bn. Center

Port Hueneme, CA 93043
ATTN: 2522 (D. Owen)

Commander

Atlantic Fleet Weapons Training Facility
Roosevelt Roads, Puerto Rico

DISTRIBUTION (Continued)

Commander
Ballistic Research Laboratory
Aberdeen Proving Ground, MD 21005
ATTN: Dr. Ed Schmidt

Commander
Material Test Directorate
Aberdeen Proving Ground, MD 21005
ATTN: R. Ainsley

Darby-Ebisu and Associates, Inc.
354 Uluniu Street
Kailua, HI 96734

Commander
AMSSA
Aberdeen Proving Ground, MD 21005
ATTN: W. Hughes

Commander
U.S. Army Environmental Hygiene Agency
Aberdeen Proving Ground, MD 21005
ATTN: Bioacoustic Div. (G. Luz)

Commander
U.S. Army Human Engineering Lab.
Aberdeen Proving Ground, MD 21005
ATTN: Garinther

Director
6570 AMRL/BBE
Wright-Patterson AFB, OH 45433
ATTN: Dr. H. Von Gierke

Bolt Baranek and Newman, Inc.
50 Moulton Street
Cambridge, MA 02138
ATTN: K. Eldred

Wave Propagation Laboratory
Boulder, CO 80302
ATTN: Dr. Freeman Hall

Office of Naval Research
800 No. Quincy Street
Arlington, VA 22217
ATTN: 441 (Libber)

DISTRIBUTION (Continued)

Commander
Navy Personnel R&D Center
San Diego, CA 92132
ATTN: 311 (Newman)

Commander
Naval Material Command
2211 Jefferson Davis Highway
Arlington, VA 20360
ATTN: 036 (J. Sivy) (2)
0324 (CDR Tadlock)

Commander
Vandenburg AFB, CA 93437
ATTN: SAMTEC/SE (C. Gardner) (2)
SAMTEC/WE (Maj. Burnett)

Commander
6585 TESTG/WE
Holloman AFB, NM 88330

Commander
Army Combat Surveillance and Target Acquisition Laboratory
Ft. Monmouth, NJ 07703
ATTN: DELCS-S (J. Silverstein)

Commander
Naval Surface Forces
U.S. Atlantic Fleet
Norfolk, VA 23511
ATTN: N625 (Capt. Lindsey)

Commander
U.S. Army Engineer Center
ATZA - PTST
Ft. Belvoir, VA 22060

Commander in Chief
U.S. Atlantic Fleet
Norfolk, VA 23511
ATTN: NRT2 (CDR Eckhoff)

Navy Environmental Health Center
Cincinnati, OH 45220
ATTN: A. Johnson

DISTRIBUTION (Continued)

Naval Ocean Systems Center
San Diego, CA 92132
ATTN: Acoustics, Behavior, and Communication
Group (R. S. Gales)

Naval Pacific Missile Test Center
Point Mugu, CA 93942
ATTN: D. Robertson

Naval Weapons Center
China Lake, CA 93551
ATTN: T. Dodson

Bureau of Mines
Noise Research Laboratory
4800 Forbes Avenue
Pittsburgh, PA 15213
ATTN: A. Burkes

Bureau of Mines
Rolla Metallurgy Research Center
P.O. Box 280
Rolla, MO 65401
ATTN: A. Visnapoo

Commander Third Fleet
Ford Island, HI 96818
ATTN: N33

Bolt Baranek and Newman, Inc.
21120 Vanowen Street
P.O. Box 633
Canoga Park, CA 91305
ATTN: Dr. B. Galloway

Sandia Corporation
P.O. Box 5800
Albuquerque, NM 87115
ATTN: Jack Reed

Commanding Officer
U.S. Army Fort A.P. Hill
Bowling Green, VA

Office of Noise Abatement and Control
Environmental Protection Agency
Washington, DC 20460

DISTRIBUTION (Continued)

Air Force Aerospace Medical Research Laboratory
Wright-Patterson Air Force Base
Fairborn, OH 45433
ATTN: Biodynamic Branch (J. Cole)

Army Ballistics Research Laboratory
Aberdeen Proving Ground
Aberdeen, MD 21005
ATTN: A. LaGrange

Army Construction Engineering Research Laboratory
Champaign, IL 61820
ATTN: P. Schomer

Army Environmental Hygiene Agency
Bioacoustics Division
USAEHA, Building E-2100
Aberdeen Proving Ground
Aberdeen, MD 21005
ATTN: D. Ohlin

Army Materials Systems Analysis
Aberdeen Proving Ground
Aberdeen, MD 21005
ATTN: B. Cummings

Army Mobility Equipment Research and Development Center
Ft. Belvoir, VA 22060
ATTN: J. Hoeschen

Army Tank - Automotive Command
Warren, MI 48090
ATTN: D. Reese

Naval Aircraft Environmental Support Office
NAVAIRE WORKFAC North Island
San Diego, CA 92135
ATTN: R. Glass

Naval Air Development Center
Warminster, PA 18974
ATTN: Air Vehicle Technology Department (W.C. Hallow)
Crew Systems Department (D. DiSimone)

(2)

Wythe Laboratories
128 Maryland Street
El Segundo, CA 90245
ATTN: L. Sutherland

DISTRIBUTION (Continued)

Director
U.S. Army Construction Engineering Research Laboratory
P.O. Box 4005
Champaign, IL 61820
ATTN: Dr. P. Schomer

Defense Nuclear Agency
Hybla Valley Federal Building
6801 Telegraph Road
Alexandria, VA 20305
ATTN: J. Moulton

Commanding Officer
Picatinny Arsenal
Dover, NJ 07801
ATTN: M. Salsbury

Defense Technical Information Center (12)
Cameron Station
Alexandria, VA 22314

Library of Congress (4)
Washington, DC 20540
ATTN: Gift and Exchange Division

Local:

C
C07
CD-03 (Pifer)
D
G14 (Jones)
GIDEP Operations Office
Corona, CA 91720 (20)
N43
N01
R15 (Swisdak)
R15 (Berry)
R15 (Proctor)
R15 (Lorenz)
R14 (Young)
E41 (6)
X210 (10)
G31

DA
FILM
S