

AD-A113 769

NAVAL RESEARCH LAB WASHINGTON DC

F/G 12/1

ANOTHER STRATEGY FOR FAST 'POISSON' SOLVING WITH NON-CONSTANT C--ETC(U)

APR 82 J P BORIS

UNCLASSIFIED

NRL-MR-4715

NL

| or |  
40 4  
13700



END  
DATE  
FILMED  
05-82  
DTIC

AD A113769

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NRL Memorandum Report 4715	2. GOVT ACCESSION NO. AD-A113 729	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) ANOTHER STRATEGY FOR FAST "POISSON" SOLVING WITH NON-CONSTANT COEFFICIENTS	5. TYPE OF REPORT & PERIOD COVERED Interim report on a continuing NRL problem.	
	6. PERFORMING ORG. REPORT NUMBER	
7. AUTHOR(s) J. P. Boris	8. CONTRACT OR GRANT NUMBER(s) N0001482AE00001	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Research Laboratory Washington, DC 20375	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 44-1529-0-2 61153N/RR011-09-43	
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Research Laboratory Washington, DC 20375	12. REPORT DATE April 9, 1982	
	13. NUMBER OF PAGES 7	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) UNCLASSIFIED	
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Poisson solving Elliptic equations Poisson equations		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The key to fast Poisson solving in an extended domain is nonlocal residual error dispersal. The fastest, most stable iterations are obtained when "most" of the nonconstant-coefficient elliptic operator can be inverted implicitly. Although local inversion approaches (ICCG, SOR, etc.) are workable, there are good incentives to seek computationally inexpensive nonlocal techniques whose worst case convergence is expected to be far better than for local inverse techniques. This note presents one such approach for a useful class of variable coefficient problems.		

DD FORM 1473  
1 JAN 73EDITION OF 1 NOV 65 IS OBSOLETE  
S/N 0102-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

## ANOTHER STRATEGY FOR FAST "POISSON" SOLVING WITH NON-CONSTANT COEFFICIENTS

### I. The Introduction

The key to fast Poisson solving in an extended domain is nonlocal residual error dispersal. On a two-dimensional domain characterized by  $N$  grid points in one direction (taken as  $x$  below) and  $M$  grid points in another (taken as  $y$ ), the general finite difference equation could be solved in  $\sim (NM)^3$  operations by matrix inversion. Because the matrix is so sparse, however, faster algorithms are sought. For a number of useful cases, usually characterized by cyclic reduction, Fourier transforms, or similar folding techniques, fast  $NM \log_2 NM$  algorithms exist and have been in use for some time. These direct solution methods are non-iterative and disperse the errors globally and correctly in one application because the complete elliptic operator can be inverted.

When complex stretched grids are used or diffusion/dielectric coefficients vary generally in space, the nature of the physical solutions does not change but the variable nature of the finite-difference coefficients in the resulting elliptic equations obviates the use of direct methods. Although local inversion approaches such as ICCG, SOR, etc. are often useful, there are still good reasons to seek computationally inexpensive nonlocal techniques whose worst case convergence is expected to be far better than for local inverse techniques.

A nonlocal technique spreads residual error at each point all over the mesh in a single iteration cycle. The analytic formulation for this involves

Manuscript submitted November 2, 1981.

the manipulation of the Green's function. Numerically, the use of Green's function in a general case can be prohibitively expensive, so cheaply manipulated approximate Green's functions are sought. It is not necessary for an algorithm to be local, to be fast.

## II. The Idea

This short note contains an idea for fast cheap "Poisson" solving on a rectangular domain. Consider a finite-difference formulation of the equation

$$\nabla^2 \tilde{v}(x,y) - \tilde{w}(x,y) \tilde{P}(x,y) = \tilde{S}(x,y) \quad (1)$$

where  $\tilde{v}(x,y) > 0$ ,  $\tilde{w}(x,y) \geq 0$  and  $(x,y)$  in the domain  $(0 \leq x \leq x_{\max}, 0 \leq y \leq y_{\max})$ .

Heat transport, special treatments of fluid dynamics, and electromagnetic propagation in varying media all satisfy similar equations. For the scalar field  $\{P_{ij}\}$  ( $1 \leq i \leq N$ ,  $1 \leq j \leq M$ ), the following finite difference equation plus well posed boundary conditions approximates (1),

$$\begin{aligned} v_{i+1/2j}^x (P_{i+1j} - P_{ij}) - v_{i-1/2j}^x (P_{ij} - P_{i-1j}) - \omega_{ij} P_{ij} + \\ v_{ij+1/2}^y (P_{ij+1} - P_{ij}) - v_{ij-1/2}^y (P_{ij} - P_{ij-1}) = S_{ij} \end{aligned} \quad (2)$$

Suppose  $\{P_{ij}\}$  is unknown with  $\{\omega_{ij}\}$ ,  $\{S_{ij}\}$ ,  $\{v_{i+1/2j}^x\}$ , and  $\{v_{ij+1/2}^y\}$  given.

A new set of unknowns  $\{\phi_{ij}\}$  can be defined by the substitution in Eq. (2),

$$P_{ij} = v_{ij} \phi_{ij}, \quad (i = 1, \dots, N; j = 1, \dots, M). \quad (3)$$

The purpose of the transformation is to provide a set of adjustable coefficients  $\{\phi_{ij}\}$  which will be optimized with reference to the coefficients  $\{v_{i+1/2j}^x\}$ ,  $\{v_{ij+1/2}^y\}$ ,  $\{\omega_{ij}\}$  but not with respect to  $\{S_{ij}\}$  which may change from one timestep to the next.

By appropriate choice of  $\{\psi_{ij}\}$ , the coefficients in the derived Poisson-like elliptic equation for  $\{\phi_{ij}\}$  can be made as nearly constant as possible. Since constant coefficient problems can be solved using fast algorithms, the non-constant portion of the coefficients are minimized row by row and added as a residual to the source term on the right hand side. The object equation derived from (2) by substituting (3) is

$$\begin{aligned}
 &v_{i+1/2j}^x \psi_{i+1j} \phi_{i+1j} + v_{i-1/2j}^x \psi_{i-1j} \phi_{i-1j} + v_{ij+1/2}^y \psi_{ij+1} \phi_{ij+1} + \\
 &v_{ij-1/2}^y \psi_{ij-1} \phi_{ij-1} - \psi_{ij} (v_{i+1/2j}^x + v_{i-1/2j}^x + v_{ij+1/2}^y + v_{ij-1/2}^y + \\
 &\omega_{ij}) \phi_{ij} = S_{ij}.
 \end{aligned} \tag{4}$$

For each row  $j$  five constants ( $a_j, b_j, c_j, d_j, e_j$ ) are to be chosen in conjunction with the as yet undetermined  $\{\psi_{ij}\}$  to minimize the following error measure:

$$\begin{aligned}
 E = \sum_{j=1}^M E_j = &\alpha \sum_{j=1}^M \sum_{i=1}^N [a_j - v_{i+1/2j}^x \psi_{i+1j}]^2 + \gamma \sum_{j=1}^M \sum_{i=1}^N [c_j - v_{i-1/2j}^x \psi_{i-1j}]^2 + \\
 &\delta \sum_{j=1}^M \sum_{i=1}^N [d_{j+1} - v_{ij+1/2}^y \psi_{ij+1}]^2 + \epsilon \sum_{j=1}^M \sum_{i=1}^N [e_{j-1} - v_{ij-1/2}^y \psi_{ij-1}]^2 \\
 &+ \sum_{j=1}^M \sum_{i=1}^N [b_j - (\text{---})_{ij} \psi_{ij}]^2
 \end{aligned} \tag{5}$$

where I have designated  $(\text{---})_{ij} = (v_{i+1/2j}^x + v_{i-1/2j}^x + v_{ij+1/2}^y + v_{ij-1/2}^y + \omega_{ij})$ .

$$\tag{6}$$

The undetermined row constants  $\{a_j\}$ ,  $\{c_j\}$ ,  $\{d_j\}$ , and  $\{e_j\}$ , along with the undetermined potential multipliers  $\{\psi_{ij}\}$  satisfy a set of equations derived by setting the derivatives of  $E$  to zero in the usual least squares manner.

From

$$\frac{\partial E}{\partial \psi_{ij}} = 0$$



3

Accession For	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
DTIC GRA&I			
DTIC TAB			
Unannounced			
Justification			
By			
Distribution			
Special			

(7)

A

one finds

$$\psi_{ij} = F_{ij} [\alpha v_{i-1/2j}^x a_j + \gamma v_{i+1/2j}^x c_j + \delta v_{ij-1/2}^y d_j + \epsilon v_{ij+1/2}^y e_j + (\text{---})_{ij}], \quad (8)$$

where the freedom to choose the multiplicative scale of  $\psi_{ij}$  in Eq. (3) permits us to set  $\{b_j\} = 1$  without loss of generality. Here I have defined

$$F_{ij} = 1/[\alpha(v_{i-1/2j}^x)^2 + \gamma(v_{i+1/2j}^x)^2 + \delta(v_{ij-1/2}^y)^2 + \epsilon(v_{ij+1/2}^y)^2 + (\text{---})_{ij}^2]. \quad (9)$$

The row constants are also found by minimizing  $E$ . Setting  $\partial E/\partial a_j = 0$ ,  $\partial E/\partial b_j = 0$ , etc. gives the additional four equations for  $\{a_j\}$ ,  $\{c_j\}$ ,  $\{d_j\}$  and  $\{e_j\}$ .

$$Na_j = \sum_{i=1}^N v_{i+1/2j}^x F_{i+1j} [\alpha v_{i+1/2j}^x a_j + \gamma v_{i+3/2j}^x c_j + \delta v_{i+1j-1/2}^y d_j + \epsilon v_{i+1j+1/2}^y e_j + (\text{---})_{i+1j}], \quad (10a)$$

$$Nc_j = \sum_{i=1}^N v_{i-1/2j}^x F_{i-1j} [\alpha v_{i-3/2j}^x a_j + \gamma v_{i-1/2j}^x c_j + \delta v_{i-1j-1/2}^y d_j + \epsilon v_{i-1j+1/2}^y e_j + (\text{---})_{i-1j}], \quad (10c)$$

$$Nd_j = \sum_{i=1}^N v_{ij-1/2}^y F_{ij} [\alpha v_{i-1/2j}^x a_j + \gamma v_{i+1/2j}^x c_j + \delta v_{i-1/2}^y d_j + \epsilon v_{ij+1/2}^y e_j + (\text{---})_{ij}], \quad \text{and} \quad (10d)$$

$$Ne_j = \sum_{i=1}^N v_{ij+1/2}^y F_{ij} [\alpha v_{i-1/2j}^x a_j + \gamma v_{i+1/2j}^x c_j + \delta v_{ij-1/2}^y d_j + \epsilon v_{ij+1/2}^y e_j + (\text{---})_{ij}]. \quad (10e)$$

These four linear inhomogeneous equations for  $a_j$ ,  $c_j$ ,  $d_j$  and  $e_j$  can be solved without reference to the results derived from any other row. A block tridiagonal system does not result.

Given these row coefficients, which can be seen not to depend on the source term  $\{S_{ij}\}$ , Eq. (8) yields the multiplicative coefficients  $\{\psi_{ij}\}$  for each of the unknown potential values  $\{\phi_{ij}\}$ . The finite-difference equation which results to describe  $\{\phi_{ij}\}$  has nearly constant coefficients, row by row, the complicating spatial variation being largely cancelled out by the derived variations of  $\{\psi_{ij}\}$ .

### III. The Implementation

This algorithm has not yet been implemented numerically. Using the row constants derived from Eqs. (10) and the multiplication coefficients  $\{\psi_{ij}\}$ , the left hand side of Eq. (1) can be expanded as follows:

$$\begin{aligned} \nabla \cdot \tilde{v}(x,y) \nabla \tilde{F}(x,y) - \tilde{w}(x,y) \tilde{F}(x,y) = D^2 \phi(x,y) + [\nabla \cdot \tilde{v} \nabla \tilde{F} \phi(x,y) \\ - \tilde{w} \tilde{F} \phi(x,y) - D^2 \phi(x,y)]. \end{aligned} \quad (11)$$

The operator  $D^2$ , by construction, is Fourier-transformable in the  $x$  direction and results in decoupled tridiagonal equations in the  $y$  direction. The second term on the right in (11), which I shall call  $R^2$ , has been minimized in a simple least squares sense. Rewriting Eq. (1) gives

$$D^2(x,y) \phi^{m+1}(x,y) = \tilde{S}(x,y) - R^2(x,y) \phi^m(x,y) \quad (12)$$

as an iterative form for solving (1) which should converge rapidly. The superscript  $m$  indicates which level of iteration has been passed. The right hand side of (12) is initialized using  $\phi^0(x,y)$ , a guess at the expected potential.



IV. Acknowledgement

This work was supported by the Office of Naval Research and  
Naval Research Laboratory.

FILMED  
5-8