

AD-A123 275

VIBRATIONAL ENERGY TRANSFER AT A GOLD SURFACE IN  
REACTING SYSTEMS CYCLOBU. (U) WASHINGTON UNIV SEATTLE  
DEPT OF CHEMISTRY W YUAN ET AL. 01 DEC 82


1/1


UNCLASSIFIED

NR092-549-TR26 N00014-75-C-0690

F/G 7/4

NL





MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

1.2

Vibrational Energy Transfer at a Gold Surface in Reacting  
Systems. Cyclobutene and Nitromethane

Wei Yuan and B. S. Rabinovitch

Department of Chemistry BG-10, University of Washington  
Seattle, Washington 98195

AD A 1 23 27 5

Technical Report No. NR092-549-TR26 ✓

Contract N00014-75-C-0690, NR-092-549

December 1, 1982

Prepared for Publication in  
Journal of Physical Chemistry  
(Flygare Memorial Issue)

OFFICE OF NAVAL RESEARCH  
Department of the Navy Code 473,  
800 N. Quincy  
Arlington, VA 22217

DTIC  
SELECTED  
JAN 10 1983  
A

Reproduction in whole or in part is permitted for any purpose  
of the United States Government. This document has been approved  
for public release; its distribution is unlimited.

83 01 10 008

DTIC FILE COPY

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NR092-549-TR2	2. GOVT ACCESSION NO. AD-A123275	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Vibrational Energy Transfer at a Gold Surface in Reacting Systems. Cyclobutene and Nitromethane.		5. TYPE OF REPORT & PERIOD COVERED Technical
7. AUTHOR(s) W. Yuan and B. S. Rabinovitch		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Professor B. S. Rabinovitch Department of Chemistry BG-10 University of Washington, Seattle, WA 98195		8. CONTRACT OR GRANT NUMBER(s) N00014-75-C-0690 NR092-549
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research, Code 743 Department of the Navy 800 N. Quincy, Arlington, VA 22217		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE Dec. 1, 1982
		13. NUMBER OF PAGES 20
		15. SECURITY CLASS. (of this report) Unclassified
		18a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  This document has been approved for public release; its distribution is unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)  Prepared for publication in J. Phys. Chem.		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Accommodation coefficient      Nitromethane Cyclobutene                              Surfaces Energy Transfer                      Unimolecular Reaction Gold    Vibrational Relaxation High Temperature		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Single collision vibrational excitation probabilities were measured on treated polycrystalline gold plane and wire surfaces. For cyclobutene, strong collider behavior obtains below 600 K. The energy transfer efficiency is greater than that on a seasoned silica surface. The energy transfer efficiency declined above 600 K to a quasi-constant value in the range 900 K - 1150 K. This may be evidence for surface mobility. Unlike cyclobutene, and earlier studies of nitromethane on silica surfaces where reproducible non-catalytic behavior could be attained, nitromethane on gold showed apparent surface sensitivity which the various conditioning treatments failed to repress.		

DD 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE  
S/N 0102 LF 014-6601

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

Vibrational Energy Transfer at a Gold Surface in Reacting Systems.  
Cyclobutene and Nitromethane<sup>†</sup>

Wei Yuan<sup>‡</sup> and B. S. Rabinovitch<sup>\*</sup>

Department of Chemistry BG-10, University of Washington  
Seattle, Washington 98195

Abstract

Single collision excitation probabilities were measured for cyclobutene and nitromethane on polycrystalline gold plane and wire surfaces. Transport above the reaction thresholds for isomerization and decomposition, respectively, for the two substrates was used as the criterion of vibrational energy transfer. Several different seasoning and processing procedures of the surfaces were tested. For cyclobutene, a defect from strong collider transition probabilities appeared only above 550 K - 600 K, which signifies that the energy transfer efficiency at a treated gold surface is greater than that at a seasoned silica surface. The vibrational energy transfer efficiency declined above 600 K and fell abruptly to a quasi-constant value in the range 900 K - 1100 K. Above 1100 K the differences between various conditioned surfaces diminished progressively. Unlike cyclobutene, and earlier studies of nitromethane on silica surfaces where reproducible non-catalytic behavior could be attained, nitromethane on gold showed apparent catalytic phenomena which the various conditioning treatments failed to repress.



Session For	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
GRANT			
TAB			
Revised			
Publication			
Distribution/ Availability Codes			
Avail and/or Special			
A			

## Introduction

The study of vibrational energy transfer between molecules and metal surfaces is of continuing interest both for theoreticians and experimentalists.<sup>1-3</sup> Rosenblatt<sup>4</sup> has studied energy transfer efficiencies at room temperature on different "dirty" metal surfaces, particularly iron, by an ingenious vibrating surface method and obtained relative values for energy transfer involving internal and translational degrees of freedom. He and his co-workers found that hydrocarbons exhibited larger energy transfer facility than did diatomic molecules; for heavier paraffin hydrocarbons ( $C_4-C_8$ ) the vibrational energy accommodation coefficients approached 0.9, presumably due to longer residence times. Related results at higher temperature have also been reported by Foner and Hudson.<sup>5</sup> They measured the vibrational accommodation coefficient of n-butane on a "dirty" polycrystalline platinum ribbon at  $1000^{\circ}C$  and reported a value of 0.05.

Our recent series of studies by the Variable Encounter Method<sup>6</sup> has been devoted to the phenomenon of gas-surface vibrational energy transfer on seasoned silica surfaces at a level of vibrational excitation above reaction threshold. Single collision systems have been examined as a special case of the VEM method.<sup>7,8</sup> The energy transport of reactant molecules to levels above the reaction threshold can be observed most simply under single collision conditions. For multi-collision conditions, the energetic distribution of excited molecules is an average effect of a sequence of collisions. Both conditions have their own uses.<sup>8</sup>

Several of our studies dealt with energy relaxation by cyclobutene<sup>7-10</sup> and nitromethane.<sup>11</sup> Energy transfer efficiencies at seasoned pyrex and fused silica surfaces were examined. Because of its polarity, a larger energy transfer efficiency for nitromethane was expected and found. Amorebleta and Colussi<sup>12</sup> have recently reported a study of vibrational energy transfer in an

n-octane-seasoned silica system using a variant of the VEM method and a diagnostic energy technique similar to that of ref. 5. Their evaluated accommodation coefficient had a value of 0.66 at 350 K and decreased approximately linearly with temperature. Their result is quite different from the approximate strong collider character obtained for cyclobutene below 450 K<sup>7</sup> by Arakawa et al.<sup>8,10</sup> It is of interest to note that if one plots the accommodation coefficients against temperature for cyclobutene on a seasoned silica surface, calculated on the basis of the Boltzmann-Exponential energy transfer model,<sup>8,9</sup> then the result of Foner and Hudson fits on the same curve. The comparison is shown in Fig. 1.

One might expect that a metal surface would be a stronger collider because of the variety of possible energy relaxation mechanisms, including phonon, hole pair and plasmon excitation, that are postulated to function for molecules on metals.<sup>13-15</sup> However, it is possible that the relaxation process on a seasoned or "dirty" metal surface might simply resemble the better known<sup>16</sup> gas phase, molecule-molecule energy exchange behavior. One molecule of the pair would be represented by the graphitic/polymeric covering on the seasoned surface. Of course, gas/solid interaction is presumably not subject to the angular momentum conservation restrictions found for two-body gas phase transfers.

In the present paper we have extended the study of surface variation to a single collision study of cyclobutene isomerization to 1,3-butadiene on a polycrystalline gold surface. We have chosen to use gold because it is one of the most amenable of the metallic elements. In the form of finely divided particles supported on oxide substrate, gold can catalyze some hydrogenation, isotope exchange and isomerization reactions of hydrocarbons; however, the massive form of the element is usually catalytically inert.<sup>17</sup> The behavior of nitromethane, which in the earlier work was found to exhibit greater sensitivity to surface conditions, has been studied as well. We find that the gold surface is relatively inert in the isomerization of cyclobutene to 1,3-butadiene but not in nitromethane decomposition.

## Experimental

Cyclobutene was obtained from Columbia Chemicals (99.9% pure) and was used without further purification. Nitromethane (Aldrich Chemical Co. 99%, spectrophotometric grade) was used without purification. Gas chromatographic analysis showed that it contained less than 0.5% nitroethane.

Two types of polycrystalline gold surfaces and experimental arrangements were used.

### A. Gold plated finger reactor

The basic design of this reactor was similar to that of previous work.<sup>7</sup> A stainless steel, hollow finger, 3.8 cm o.d., was located at the center of a 5-liter flask which was immersed in an ice bath. The outer surface of the finger was electroplated (over nickel) with a layer of gold (> 99.8% pure),  $= 2.5 \times 10^{-3}$  cm in thickness. The length of the active section was 5.9 cm, and the area of the gold surface including the flat bottom was  $= 80 \text{ cm}^2$ . Above the active region was a 1 cm length of plated thin-wall (to reduce thermal conduction from the bottom heated part) section which led to a 3 cm water-cooled length of the stainless steel finger. The inner region of the 5.9 cm length of the finger was filled with a Pb-Sn-Bi eutectic alloy and was used as an internal heating bath. A blade stirrer produced a uniform bath temperature. The temperature profile of the bath was measured by a chromel-alumel thermocouple which moved inside a thin wall stainless steel tube. This design gave fairly uniform temperature distribution over the finger surface. Except for the uppermost part of the gold surface adjacent to the thin-walled section, the variation of temperature over the surface was  $\pm 4^\circ$ . The average distance between the hot surface of the finger and the wall of the 5-l flask was about 7 cm.

The surface of the finger reactor was processed by three methods:

a) oxidation with 1 torr oxygen; b) oxidation followed by reduction with



1 torr hydrogen; c) seasoning with  $10^{-2}$  torr reactant. All the processing procedures were conducted at 600 K to 700 K and repeated anew each day.

#### B. Gold wire reactor

A length of 26 gauge fine gold wire was drawn by Speyer Metallurgy Co., Seattle. A U-shaped double length of gold wire was hung longitudinally on small glass hooks in a glass cylinder of diameter 9 cm. The wire diameter was 0.1 mm and its total length was 69.5 cm. The geometric surface area of this wire was  $2 \text{ cm}^2$ . The ends of the gold wire were spot-welded to a nickel-coated tungsten rod. The wire was heated to a maximum temperature of 1200 K by resistive heating. The electric resistance was found by measuring the voltage and current with Keithley voltammeters. Adjustment of the temperature of the wire was fast and easy. The temperature of the glass cylinder wall was maintained at room temperature. The average distance between the wire and the glass cylinder was 4 cm.

Due to end losses there were two cooler regions on the uppermost parts of the gold wire; the length of each region was approximately 4 cm. In order to estimate the temperature distribution over this length, we resorted to the treatment of a similar circumstance reported for tungsten wire.<sup>18,19</sup> After correction for the end effect, the average temperature of the wire was calculated from a chart of the specific electric resistance vs. temperature drawn from data in the literature.<sup>20</sup> To check the value and uniformity of the temperature along the main part of the gold wire, temperature measurements were also made with an optical pyrometer. The temperature variation over the length of the wire was  $\pm 25^\circ$ , while the average temperature given by the pyrometer agreed with the resistance measurements within  $10^\circ$ . The latter measurement was adopted for the temperature of the wire.

Similar processing procedures as for the finger were used except that they were carried out at 100-fold lower pressures. It was found that a half-hour

seasoning gave reproducible results. The procedure was carried out at 1100 K.

### Procedure

Before a cyclobutene run, the reactor was evacuated to  $\approx 3 \times 10^{-6}$  torr for the finger reactor and  $1-2 \times 10^{-6}$  torr for the wire reactor. The substrate reaction pressure was  $\approx 1-2 \times 10^{-4}$  torr. The reaction fraction was 0.5% to 80% (finger) and 0.5% to 50% (wire). The average temperature change during a run was  $\pm 0.5^\circ$  for the shortest run and  $\pm 4^\circ$  for the longest one. The reaction temperatures were varied over the range of 425 - 668 K, for the finger reactor, and 525 - 1150 K, for the wire reactor, so that there was an overlap region in which the results obtained from the two reactors could be compared. The reaction mixture was collected in a liquid nitrogen trap. Analysis was made with a squalane SCOT column and FID. No side reaction was found. In all details, the procedure was similar to that described earlier.<sup>7,10</sup>

Nitromethane was studied only in the wire reactor. As before,<sup>11</sup> acetonitrile was used as an internal standard against which the disappearance of substrate could be accurately measured. No attempt was made to monitor all of the product species which, for this system, are very numerous. Separation of the reaction products was made on a 1-m column of 3mm copper tubing packed with Porapak Q and maintained at 150°C. The detector was FID.

## Results and Discussion

### Cyclobutene

The molecules of cyclobutene energized above the threshold have a greater than 99% probability of reaction during their flight time from the surface, according to RRKM calculations.<sup>8-10</sup> Collision of the activated molecule with the bath gas during the flight time can be neglected and the unimolecular isomerization reaction is close to the second order region under present conditions.

The isomerization of cyclobutene on the gold finger obeyed the first order rate law; sample curves are shown in Fig. 2. Within the experimental error, no difference in the results was noticed between the different processing procedures for the surface. The apparent rate constant  $k$  is plotted against temperature in Fig. 3. Some points, especially at higher temperatures, are the average of three to four measurements. The experimental reaction probability  $P_c$  was obtained by use of the equation,  $P_c = 4Vk/S\bar{c}$ , where  $V$  is the volume of the reactor,  $S$  is the area of the hot gold surface, and  $\bar{c}$  is the average translational velocity of the reactant molecules at the temperature of the cold wall. A plot of  $P_c$  vs. temperature is given in Fig. 4; two theoretical strong collider  $P_c$  curves are also shown, which were calculated for two values of the reaction threshold energy,<sup>21</sup> 32.0 and 32.4 kcal mol<sup>-1</sup>. The two values correspond to two different activated complexes; Elliott and Frey prefer the latter value although there is little to choose between them.

The earlier studies in this laboratory<sup>7,9,10</sup> showed that seasoned pyrex and silica surfaces exhibit strong collider character near and below 400 K. From Fig. 4, one can conclude that the gold surface behaves as an even stronger collider than those. The defect from strong collider behavior is only evident at temperatures above 600 K.

The isomerization of cyclobutene in the wire reactor also obeyed the first order rate law (Fig. 5). The measured  $P_c$  values are shown in Fig. 5 or 6. When

compared with the data for the finger reactor, it is apparent that the two sets of values in the lower, overlap temperature region concord quite well. Some differences arise however in the effect of the processing procedure on the gold wire at intermediate temperatures. As was the case in earlier work with hydrocarbons, the cyclobutene seasoned surface again gave the lowest rate. The oxidized surface seemed to behave as a stronger collider than the seasoned (reduced) surface. It is noteworthy, however, that all seasoning procedures converge on the same energy transfer efficiency at the highest temperatures (1100 K - 1150 K); this leads us to believe that surface catalytic reaction effects are not important in the wire activation experiments.

Some analogy may be drawn with work of Somorjai and co-workers.<sup>22,23</sup> His group has tested the adsorption of butane and pentane on the Pt(111) crystal surface at 110 K. They have found that preadsorbed oxygen promoted the adsorption of the hydrocarbons and that preadsorbed hydrogen hindered it. Although our experimental temperature was much higher than theirs, for what it is worth, we do have a related tendency, i.e., the oxygen-processed gold surface gave a higher energy transfer efficiency than did the hydrogen-processed surface. Furthermore, they found that the carbonaceous overlayer formed on the metal surface by the pyrolysis of organic materials decreased the reaction rate. This conclusion is parallel with our observations.

Another factor which is worthy of mention is sintering or reorganization of the crystal lattice. The  $P_c$  curves in Fig. 6 bend over rather quickly as the temperature was increased, and all three curves approach each other. From estimates of the Tammann temperature<sup>24</sup> and the melting point (1336 K) of gold, then in the range 400 - 600 K the crystal lattice of gold may start to become mobile, the surface atoms may exchange with the bulk atoms and at even higher temperature the influence of different processing procedures is more likely to be lost.

It may be useful to point out that the strong collider characteristic of the gold surface at low temperature could in some circumstances be useful for

the estimation of the threshold energy  $E_0$  of some chemical reactions. As a routine method,  $E_0$  is usually derived from the high pressure Arrhenius parameters. Sometimes high pressure experiments give troubles. In that case, it might be a better choice to take advantage of lower pressure and the strong collider character of gold or other surfaces.

#### Nitromethane

Energy transfer by nitromethane at a silica surface has been studied before by the VEM method.<sup>11</sup> Although the products of the reaction were not identified thoroughly, the species were similar to the products reported in the literature<sup>25-27</sup> for which a C-N bond rupture mechanism has been concluded. When the silica surface was simply seasoned with the reactant itself, as was customary in earlier experiments with hydrocarbons in order to eliminate surface reaction,<sup>6-10</sup> some evidence of surface catalysis and irreproducibility was exhibited. Processing of the silica by oxygen in fact gave the lowest decomposition rate as well as reproducible data. A higher energy transfer efficiency for nitromethane relative to cyclobutene was found, presumably due to the higher polarity of the former. A threshold energy,  $E_0 = 54.4 \text{ kcal mol}^{-1}$ , used to fit these experimental results was calculated from Arrhenius parameters in the literature.<sup>27</sup>

In the gold wire reactor, a pressure of  $\sim 1 \times 10^{-4}$  torr nitromethane on variously processed/seasoned surfaces was employed. To process the gold surface, a variety of additional procedures was used: oxidation by oxygen; oxidation followed by exposure to hydrogen, or nitrogen, or argon or xenon; reduction by carbon monoxide, or by nitromethane itself, or by cyclopropane. The processing temperature was 1000-1100 K. Under all of these conditions the gold-nitromethane system exhibited strong catalytic and, more or less ( $\pm 50\%$ ), reproducible characteristics, i.e., the different processing procedures gave no large differences in reactivity in the experimental temperature range. However, the

experimental  $P_c$  values were one to two magnitudes higher than the values calculated for a strong collider, based on the threshold of  $54.4 \text{ kcal mol}^{-1}$ . From 500 K to 900 K, the  $P_c$  value increased with temperature. From 900 K to 1100 K, (the highest temperature examined), the  $P_c$  curve became flat. This phenomenon is quite different from the behavior of nitromethane at the silica surface.<sup>11</sup> In Fig. 7 a graph of results on the cyclopropane-seasoned (at 1000 K) gold wire surface is shown. The experimental points roughly follow a strong collider curve having a threshold energy of  $31\text{-}32 \text{ kcal mol}^{-1}$ . It is quite evident that the seasoning, resulting in deposition of a graphitic polycyclopropane layer in this case, does not necessarily mask the effect and behavior of the underlying substrate.

## Appendix

Vibrational frequencies ( $\text{cm}^{-1}$ ) and parameters used in calculation:

(1) Cyclobutene:<sup>21</sup>

Molecule: 3126, 3058, 2955(2), 2933, 2916, 1566, 1444, 1426, 1288, 1276,  
1210, 1186, 1113, 1100, 1074, 986, 875, 850, 846, 800, 640, 635,  
325.

Activated complex A: 3015(6), 1340(7), 1005(6), 670(3), 335.  $E_0=32.0$  kcal/mol

Activated complex C: 3300(6), 1320(12), 660(5).  $E_0=32.4$  kcal/mol;  $F=1.3$

(2) Nitromethane:<sup>11,28</sup>

Molecule: 3048(2), 2965, 1582, 1488, 1449, 1413, 1384, 1153, 1097, 921, 647,  
599, 476, internal rotation ( $\sigma = 6$ )

## References

- † This work was supported by the Office of Naval Research.
- ‡ Visiting Scholar from Qinghua University, Beijing, P.R.C.
1. Ceyer, S. T.; Somorjai, G. A. Ann. Rev. Phys. Chem. **28** (1977) 477.
  2. Goodman, F. O. J. Phys. Chem. **84** (1980) 1431.
  3. Cardillo, M. J. Ann. Rev. Phys. Chem. **32** (1981) 331.
  4. Rosenblatt, G. M. Acc. Chem. Res. **14** (1981) 42.
  5. Foner, S. N.; Hudson, R. L. J. Chem. Phys. **75** (1981) 4727.
  6. Kelley, D. F.; Zalotai, L.; Rabinovitch, B. S. Chem. Phys. **46** (1980) 379.
  7. Kelley, D. F.; Kasai, T.; Rabinovitch, B. S. J. Phys. Chem. **85** (1980) 1100.
  8. Arakawa, R.; Kelley, D. F.; Rabinovitch, B. S. J. Chem. Phys. **76** (1982) 2384.
  9. Flowers, M. C.; Wolters, F. C.; Kelley, D. F.; Rabinovitch, B. S. Chem. Phys. Lett. **69** (1980) 543.
  10. Wolters, F. C.; Flowers, M. C.; Rabinovitch, B. S. J. Phys. Chem. **85** (1981) 589.
  11. Yuan, W.; Rabinovitch, B. S.; Tosa, R. J. Phys. Chem. **86** (1982) 2796.
  12. Amorebleta, V. T.; Colussi, A. J. J. Phys. Chem. **86** (1982) 3058.
  13. Kuzhushner, M. A.; Kustarev, V. G.; Shub, B. R. Dokl. Phys. Chem. (USSR) **237** (1977) 1148.
  14. Rossetti, R.; Brus, L. E. J. Chem. Phys. **76** (1982) 1146.
  15. Ueba, H. J. Chem. Phys. **77** (1982) 3759.
  16. Tardy, D. C.; Rabinovitch, B. S. Chem. Rev. **77** (1977) 369.
  17. Puddephatt, R. J. "The Chemistry of Gold" Elsevier Scientific Publishing Company, 1978, p. 253.
  18. Worthing, A. G.; Halliday, D. "Heat" (second printing) John Wiley & Sons, Inc. (1948) p. 172.
  19. Herzfeld, C. M. "Temperature; Its Measurement and Control in Science and Industry" Vol. 3, Part 2. Reinhold Publishing Corp. (1962) p. 530.



20. Forsythe, W. E. "Smithsonian Physical Tables" (Ninth Revised Edition) City of Washington, published by the Smithsonian Institution (1954).
21. Elliott, C. S.; Frey, H. M. Trans. Faraday Soc. 62 (1966) 895.
22. Salmeron, M.; Somorjai, G. A. J. Phys. Chem. 85 (1981) 3835.
23. Somorjai, G. A.; Zaera, F. J. Phys. Chem. 86 (1982) 3070.
24. Drauglis, E.; Gretz, R. D.; Jaffee, R. I. "Molecular Processes on Solid Surfaces" McGraw-Hill Book Company (1969) p. 14.
25. Dubikhin, V. V.; Nazin, G. M.; Manelis, G. B. Akad. Nauk. SSSR, Chem. Sci. Div. Bull. (1971) 1247.
26. Perche, A.; Tricot, J. C.; Lucquin, M. J. Chem. Res. (S) (1979) 116, (1979) 304, (1979) 306.
27. Glanzer, K.; Troe, J. Helv. Chim. Acta 55 (1972) 2884; Troe, J. J. Chem. Phys. 66 (1977) 4758.
28. Wells, A. J.; Wilson, E. B. Jr. J. Chem. Phys. 9 (1941) 314.

Figure Captions:

Fig. 1. Comparison of accommodation coefficients.

○, *n*-octane—silica system<sup>12</sup>; ▲, *n*-butane—platinum system<sup>5</sup>;  
 □, cyclobutene—silica system, this laboratory.<sup>7,8,10</sup>

Fig. 2. First order plots, gold finger reactor.

□, oxidized surface; ■, seasoned surface; ○, oxidized-reduced surface.

Fig. 3. The apparent rate constant  $k$  vs. the temperature  $T$  K for the finger reactor;

□, oxidized surface; ■, seasoned surface; ○, oxidized-reduced surface.

Fig. 4. The single-collision reaction probability  $P_c$  for cyclobutene vs.  $T$  K for

the finger reactor; - - - strong collider curve ( $E_0 = 32.0 \text{ kcal mol}^{-1}$ );  
 — strong collider curve ( $E_0 = 32.4 \text{ kcal mol}^{-1}$ ); □, oxidized surface;  
 ■, seasoned surface; ○, oxidized-reduced surface.

Fig. 5. First order plots, gold wire reaction; ○,  $C = 10^{-2}$ ,  $T = 1015 \text{ K}$ , oxidized-reduced surface; ●,  $C = 10^{-3}$ ,  $T = 844 \text{ K}$ , seasoned surface.

Fig. 6. The single-collision reaction probability  $P_c$  for cyclobutene vs. temperature  $T$  in the gold wire reactor;

- - - strong collider curve ( $E_0 = 32.0 \text{ kcal mol}^{-1}$ ); — strong collider curve ( $E_0 = 32.4 \text{ kcal mol}^{-1}$ ); □, oxidized surface; ■, seasoned surface; ○, oxidized-reduced surface.

Fig. 7. The experimental, ○, single-collision reaction probability  $P_c$  for nitromethane vs. temperature  $T$  in the gold wire reactor. The number on every solid curve is the assumed  $E_0$  value ( $\text{kcal mol}^{-1}$ ) used for calculating strong collider curves.




Fig. 1




Fig. 2




Fig 3





Fig. 4







Fig. 6





INIT

DISTRIBUTION LIST

November 30, 1982

	<u>No. Copies</u>		<u>No. Copies</u>
Dr. L.V. Schmidt Assistant Secretary of the Navy (R,E, and S) Room 5E 731 Pentagon Washington, D.C. 20350	1	Dr. F. Roberto Code AFRPL MKPA Edwards AFB, CA 93523	1
Dr. A.L. Slafkosky Scientific Advisor Commandant of the Marine Corps Code RD-1 Washington, D.C. 20380		Dr. L.H. Caveny Air Force Office of Scientific Research Directorate of Aerospace Sciences Bolling Air Force Base Washington, D.C. 20332	1
Dr. Richard S. Miller Office of Naval Research Code 473 Arlington, VA 22217	10	Mr. Donald L. Ball Air Force Office of Scientific Research Directorate of Chemical Sciences Bolling Air Force Base Washington, D.C. 20332	1
Mr. David Siegel Office of Naval Research Code 260 Arlington, VA 22217	1	Dr. John S. Wilkes, Jr. FJSRL/NC USAF Academy, CO 80840	1
Dr. R.J. Marcus Office of Naval Research Western Office 1030 East Green Street Pasadena, CA 91106	1	Dr. R.L. Lou Aerojet Strategic Propulsion Co. P.O. Box 15699C Sacramento, CA 95813	1
Dr. Larry Peebles Office of Naval Research East Central Regional Office 666 Summer Street, Bldg. 114-D Boston, MA 02210	1	Dr. V.J. Keenan Anal-Syn Lab Inc. P.O. Box 547 Paoli, PA 19301	1
Dr. Phillip A. Miller Office of Naval Research San Francisco Area Office One Hallidie Plaza, Suite 601 San Francisco, CA 94102	1	Dr. Philip Howe Army Ballistic Research Labs ARRADCOM Code DRDAR-BLT Aberdeen Proving Ground, MD 21005	1
Mr. Otto K. Heiney AFATL - DLDL Eglin AFB, FL 32542	1	Mr. L.A. Watermeier Army Ballistic Research Labs ARRADCOM Code DRDAR-BLI Aberdeen Proving Ground, MD 21005	1
Mr. R. Geisler ATTN: MKP/MS24 AFRPL Edwards AFB, CA 93523	1	Dr. W.W. Wharton Attn: DRSMI-RKL Commander U.S. Army Missile Command Redstone Arsenal, AL 35898	1

INIT

DISTRIBUTION LIST

	<u>No. Copies</u>		<u>No. Copies</u>
Mr. J. Murrin Naval Sea Systems Command Code 62R2 Washington, D.C. 20362	1	Dr. A. Nielsen Naval Weapons Center Code 385 China Lake, CA 93555	1
Dr. P.J. Pastine Naval Surface Weapons Center Code R04 White Oak Silver Spring, MD 20910	1	Dr. R. Reed, Jr. Naval Weapons Center Code 388 China Lake, CA 93555	1
Mr. L. Roslund Naval Surface Weapons Center Code R122 White Oak Silver Spring, MD 20910	1	Dr. L. Smith Naval Weapons Center Code 3205 China Lake, CA 93555	1
Mr. M. Stosz Naval Surface Weapons Center Code R121 White Oak Silver Spring, MD 20910	1	Dr. B. Douda Naval Weapons Support Center Code 5042 Crane, IN 47522	1
Dr. E. Zimmet Naval Surface Weapons Center Code R13 White Oak Silver Spring, MD 20910	1	Dr. A. Faulstich Chief of Naval Technology MAT Code 0716 Washington, D.C. 20360	1
Dr. D.R. Derr Naval Weapons Center Code 388 China Lake, CA 93555	1	LCDR J. Walker Chief of Naval Material Office of Naval Technology MAT, Code 0712 Washington, D.C. 20360	1
Mr. Lee N. Gilbert Naval Weapons Center Code 3205 China Lake, CA 93555	1	Mr. Joe McCartney Naval Ocean Systems Center San Diego, CA 92152	1
Dr. E. Martin Naval Weapons Center Code 3858 China Lake, CA 93555	1	Dr. S. Yamamoto Marine Sciences Division Naval Ocean Systems Center San Diego, CA 91232	1
Mr. R. McCarten Naval Weapons Center Code 3272 China Lake, CA 93555	1	Dr. G. Bosmajian Applied Chemistry Division Naval Ship Research & Development Center Annapolis, MD 21401	1
		Dr. H. Shuey Rohr and Haas Company Huntsville, AL 35801	1

INIT

DISTRIBUTION LIST

	<u>No. Copies</u>		<u>No. Copies</u>
Mr. R. Brown Naval Air Systems Command Code 330 Washington, D.C. 20361	1	Dr. J. Schnur Naval Research Lab. Code 6510 Washington, D.C. 20375	1
Dr. H. Rosenwasser Naval Air Systems Command AIR-310C Washington, D.C. 20360	1	Mr. R. Beauregard Naval Sea Systems Command SEA 64E Washington, D.C. 20362	1
Mr. B. Sobers Naval Air Systems Command Code 03P25 Washington, D.C. 20360	1	Mr. G. Edwards Naval Sea Systems Command Code 62R3 Washington, D.C. 20362	1
Dr. L.R. Rothstein Assistant Director Naval Explosives Dev. Engineering Dept. Naval Weapons Station Yorktown, VA 23691	1	Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, PA 19112	1
Dr. Lionel Dickinson Naval Explosive Ordnance Disposal Tech. Center Code D Indian Head, MD 20640	1	Dr. H.G. Adolph Naval Surface Weapons Center Code R11 White Oak Silver Spring, MD 20910	1
Mr. C.L. Adams Naval Ordnance Station Code PM4 Indian Head, MD 20640	1	Dr. T.D. Austin Naval Surface Weapons Center Code R16 Indian Head, MD 20640	1
Mr. S. Mitchell Naval Ordnance Station Code 5253 Indian Head, MD 20640	1	Dr. T. Hall Code R-11 Naval Surface Weapons Center White Oak Laboratory Silver Spring, MD 20910	1
Dr. William Tolles Dean of Research Naval Postgraduate School Monterey, CA 93940	1	Mr. G.L. Mackenzie Naval Surface Weapons Center Code R101 Indian Head, MD 20640	1
Naval Research Lab. Code 6100 Washington, D.C. 20375	1	Dr. K.F. Mueller Naval Surface Weapons Center Code R11 White Oak Silver Spring, MD 20910	1

DISTRIBUTION LIST

	<u>No. Copies</u>		<u>No. Copies</u>
Dr. R.G. Rhoades Commander Army Missile Command DRSMI-R Redstone Arsenal, AL 35898	1	Dr. E.H. Debutts Hercules Inc. Baccus Works P.O. Box 98 Magna, UT 84044	1
Dr. W.D. Stephens Atlantic Research Corp. Pine Ridge Plant 7511 Wellington Rd. Gainesville, VA 22065	1	Dr. James H. Thacher Hercules Inc. Magna Baccus Works P.O. Box 98 Magna, UT 84044	1
Dr. A.W. Barrows Ballistic Research Laboratory USA ARRADCOM DRDAR-BLP Aberdeen Proving Ground, MD 21005	1	Mr. Theodore M. Gilliland Johns Hopkins University APL Chemical Propulsion Info. Agency Johns Hopkins Road Laurel, MD 20810	1
Dr. C.M. Frey Chemical Systems Division P.O. Box 358 Sunnyvale, CA 94086	1	Dr. R. McGuire Lawrence Livermore Laboratory University of California Code L-324 Livermore, CA 94550	1
Professor F. Rodriguez Cornell University School of Chemical Engineering Olin Hall Ithaca, NY 14853	1	Dr. Jack Linsk Lockheed Missiles & Space Co. P.O. Box 504 Code Org. 83-10, Bldg. 154 Sunnyvale, CA 94088	1
Defense Technical Information Center DTIC-DDA-2 Cameron Station Alexandria, VA 22314	12	Dr. B.G. Craig Los Alamos National Lab P.O. Box 1663 NSP/DOD, MS-245 Los Alamos, NM 87545	1
		Dr. R.L. Rabie WX-2, MS-952 Los Alamos National Lab. P.O. Box 1663 Los Alamos, NM 37545	1
Dr. Ronald L. Simmons Hercules Inc. Eglin AFATL/DL DL Eglin AFB, FL 32542	1	Dr. R. Rogers Los Alamos Scientific Lab. WX-2 P.O. Box 1663 Los Alamos, NM 87545	1

6/81

## DISTRIBUTION LIST

<u>No. Copies</u>	<u>No. Copies</u>
Dr. J.F. Kincaid Strategic Systems Project Office Department of the Navy Room 901 Washington, D.C. 20376	1
Strategic Systems Project Office Propulsion Unit Code SP2731 Department of the Navy Washington, D.C. 20376	1
Mr. E.L. Throckmorton Strategic Systems Project Office Department of the Navy Room 1048 Washington, D.C. 20376	1
Dr. D.A. Flanigan Thiokol Huntsville Division Huntsville, AL 35807	1
Mr. G.F. Mangum Thiokol Corporation Huntsville Division Huntsville, AL 35807	1
Mr. E.S. Sutton Thiokol Corporation Elkton Division P.O. Box 241 Elkton, MD 21921	1
Dr. G. Thompson Thiokol Wasatch Division MS 240 P.O. Box 524 Brigham City, UT 84302	1
Dr. T.F. Davidson Technical Director Thiokol Corporation Government Systems Group P.O. Box 9258 Ogden, UT 84409	1
Dr. C.W. Vriesen Thiokol Elkton Division P.O. Box 241 Elkton, MD 21921	1
Dr. J.C. Hinshaw Thiokol Wasatch Division P.O. Box 524 Brigham City, UT 83402	1
U.S. Army Research Office Chemical & Biological Sciences Division P.O. Box 12211 Research Triangle Park, NC 27709	1
Dr. R.F. Walker USA ARRADCOM DRDAR-LCE Dover, NJ 07801	1
Dr. T. Sinden Munitions Directorate Propellants and Explosives Defense Equipment Staff British Embassy 3100 Massachusetts Ave. Washington, D.C. 20008	1
Mr. J.M. Frankle Army Ballistic Research Labs ARRADCOM Code DRDAR-BLI Aberdeen Proving Ground, MD 21005	1
Dr. Ingo W. May Army Ballistic Research Lab ARRADCOM Code DRDAR-BLI Aberdeen Proving Ground, MD 21005	1

INIT

6/81

DISTRIBUTION LIST

	<u>No. Copies</u>		
E. J. Palm Commander Army Missile Command DRSMI-RK Redstone Arsenal, AL 35898	1	Dr. Kenneth O. Hartman Hercules Aerospace Division Hercules Incorporated Allegany Ballistics Lab P.O. Box 210 Cumberland, MD 21502	1
Dr. Merrill K. King Atlantic Research Corp. 5390 Cherokee Avenue Alexandria, VA 22314	1	Dr. Joyce J. Kaufman The Johns Hopkins University Department of Chemistry Baltimore, MD 21218	1
Dr. R.J. Bartlett Batelle Columbus Laboratories 505 King Avenue Columbus, OH 43201	1	Dr. John K. Dienes T-3, MS-216 Los Alamos National Lab P.O. Box 1663 Los Alamos, NM 87544	1
Dr. P. Rentzepis Bell Laboratories Murray Hill, NJ 07971	1	Dr. H.P. Marshall Dept. 52-35, Bldg. 204.2 Lockheed Missile & Space Co. 3251 Hanover Street Palo Alto, CA 94304	1
Professor Y.T. Lee Department of Chemistry University of California Berkeley, CA 94720	1	Professor John Deutsch MIT Department of Chemistry Cambridge, MA 02139	1
Professor M. Nicol Department of Chemistry 405 Hilgard Avenue University of California Los Angeles, CA 90024	1	Professor Barry Kunz College of Sciences & Arts Department of PHysics Michigan Technological Univ. Houghton, MI 49931	1
Professor S.S. Penner University of California Energy Center Mail Code B-010 La Jolla, CA 92093	1	Dr. R. Bernecker Code R13 Naval Surface Weapons Center White Oak Silver Spring, MD 20910	1
Professor Curt Wittig University of Southern CA Dept. of Electrical Engineering University Park Los Angeles, CA 90007	1	Dr. C.S. Coffey Naval Surface Weapons Center Code R13 White Oak Silver Spring, MD 20910	1

DISTRIBUTION LIST

	<u>No. Copies</u>
Dr. W. L. Elban Code R13 Naval Surface Weapons Center White Oak Silver Spring, MD 20910	1
Mr. K.J. Graham Naval Weapons Center Code 3835 China Lake, CA 93555	1
Dr. B. Junker Office of Naval Research Code 421 Arlington, VA 22217	1
Prof. H.A. Rabitz Department of Chemistry Princeton University Princeton, NH 08540	1
Dr. M. Farber Space Sciences, Inc. 135 West Maple Avenue Monrovia, CA 91016	1
Mr. M. Hill SRI International 333 Ravenswood Avenue Menlo Park, CA 94025	1
U.S. Army Research Office Engineering Division Box 12211 Research Triangle Park, NC 27709	1
U.S. Army Research Office Metallurgy & Materials Sci. Div. Box 12211 Research Triangle Park, NC 27709	1
Professor G.D. Duvall Washington State University Department of Physics Pullman, WA 99163	1



300 500 700 900 1100 1300  
T/K

*Fig. 1*

**END**

**FILMED**

**2-83**

**DTIC**

Dr. Ronald L. Simmons  
Hercules Inc. Eglin  
AFATL/DLDL  
Eglin AFB, FL 32542

1

Los Alamos Scientific Lab.  
P.O. Box 1663  
Los Alamos, NM 87545

Dr. R. Rogers  
Los Alamos Scientific Lab.  
WX-2  
P.O. Box 1663  
Los Alamos, NM 87545

1

1  
Dr. T.F. Davidson  
Technical Director  
Thiokol Corporation  
Government Systems Group  
P.O. Box 9258  
Ogden, UT 84409

1  
Dr. Ingo W. May  
Army Ballistic Research Lab  
ARRADCOM  
Code DRDAR-BLI  
Aberdeen Proving Ground, MD 21005

Naval Surface Weapons Center  
Code R13  
White Oak  
Silver Spring, MD 20910

Washington State University  
Department of Physics  
Pullman, WA 99163

DTIC