

AD A 123797



INSTALLATION
RESTORATION PROGRAM

PHASE I - RECORDS SEARCH

ROBINS AFB, GEORGIA

PREPARED FOR

UNITED STATES AIR FORCE
AFESC/DEV

Tyndall AFB, Florida

DTIC FILE COPY

DTIC
ELECTE
JAN 26 1983
S D D

ES ENGINEERING-SCIENCE

APRIL, 1982

DISTRIBUTION STATEMENT A
Approved for public release
Distribution Unlimited

88 01 12 03 7

PII Redacted

This report has been prepared for the U.S. Air Force by Engineering-Science for the purpose of aiding in the implementation of the Air Force Installation Restoration Program. It is not an endorsement of any product. The views expressed herein are those of the contractor and do not necessarily reflect the official views of the publishing agency, the United States Air Force or the Department of Defense.

INSTALLATION RESTORATION PROGRAM
PHASE I: RECORDS SEARCH
ROBINS AFB, GEORGIA

Prepared For
United States Air Force
AFESC/DEV
Tyndall AFB, Florida

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By <u>Per Ltr. on file</u>	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	



April, 1982

By

ENGINEERING-SCIENCE, INC.
57 Executive Park South, N.E.
Suite 590
Atlanta, Georgia 30329

DISTRIBUTION STATEMENT A
Approved for public release
Distribution Unlimited

This report has been prepared for the U.S. Air Force by Engineering-Science for the purpose of aiding in the implementation of the Air Force Installation Restoration Program. It is not an endorsement of any product. The views expressed herein are those of the contractor and do not necessarily reflect the official views of the publishing agency, the United States Air Force or the Department of Defense.

ES ENGINEERING-SCIENCE

57 EXECUTIVE PARK SOUTH, N.E., SUITE 590 • ATLANTA, GEORGIA 30329 • 404/325-0770

CABLE ADDRESS: ENGINSCI
TELEX: 54-2882

9654

April 13, 1982

Mr. Bernard Lindenberg
AFESC/DEVP
Tyndall AFB, Florida 32403

Dear Mr. Lindenberg:

Enclosed is the Engineering-Science, Inc. (ES) final report entitled "Installation Restoration Program, Phase I - ~~Records Search~~, Robins AFB, Georgia." This report has been prepared in accordance with the ES proposal dated July 15, 1981 and Air Force Contract Number F08637-80-0009 Call #0009.

Presented in this report are introductory background information on the Installation Restoration Program, a description of the Robins AFB installation including past activities, mission and environmental setting, a review of industrial activities at Robins AFB, an inventory of major solid and hazardous waste from past activities, a review of past and present waste handling, treatment and disposal facilities, an evaluation of the pollution potential of waste disposal sites, and recommendations for the Installation Restoration Program, Phase II, Problem Confirmation and Quantification.

Any questions concerning this report should be directed to the Office of Public Affairs, Robins Air Force Base, 912/926-5202.

We appreciate the opportunity to work with you and the other Air Force personnel who contributed information to us for the completion of this assessment.

Very truly yours,

ENGINEERING-SCIENCE, INC.

E. J. Schroeder

E. J. Schroeder, P.E.
Manager, Solid & Hazardous Waste

EJS/lmr

Enclosure

TABLE OF CONTENTS

		<u>Page</u>
	LIST OF FIGURES	iv
	LIST OF TABLES	v
	EXECUTIVE SUMMARY	1
CHAPTER 1	INTRODUCTION	1-1
	Background	1-1
	Purpose and Scope	1-1
	Methodology	1-2
CHAPTER 2	INSTALLATION DESCRIPTION	2-1
	Location, Size and Boundaries	2-1
	Base History	2-1
	Organization and Mission	2-5
CHAPTER 3	ENVIRONMENTAL SETTING	3-1
	Meteorology	3-1
	Geography	3-1
	Topography	3-4
	Drainage	3-4
	Surface Soils	3-4
	Geology	3-9
	Stratigraphy	3-9
	Distribution	3-10
	Hydrogeology	3-10
	Ground-Water Quality	3-16
	Surface Water Quality	3-22
	Wetland Areas	3-23
	Summary of Environmental Settings	3-25
CHAPTER 4	FINDINGS	4-1
	Past Shops and Base Activity Review	4-1
	Industrial Shops	4-2
	Fire Protection Training	4-9
	Pesticide Utilization	4-14
	Fuel Management	4-15
	Description of Past On-Base Disposal Methods	4-18
	Landfills	4-19
	Waste Dumps	4-24

	Sludge Lagoon	4-28
	Hazardous Waste Burial Site	4-28
	Low-Level Radioactive Waste Sites	4-30
	Industrial Wastewater Treatment Plants	4-33
	Sanitary Wastewater Treatment Facilities	4-34
	Storm Sewer System	4-36
	Refuse Incineration	4-36
	Evaluation of Past Disposal Activities and Facilities	4-36
CHAPTER 5	CONCLUSIONS	5-1
CHAPTER 6	RECOMMENDATIONS	6-1
APPENDIX A	BIOGRAPHICAL DATA	
APPENDIX B	INSTALLATION HISTORY, ORGANIZATION AND MISSION	
APPENDIX C	SUPPLEMENTAL ENVIRONMENTAL SETTING INFORMATION	
APPENDIX D	MASTER LIST OF INDUSTRIAL SHOPS	
APPENDIX E	PHOTOGRAPHS	
APPENDIX F	WATER SUPPLY WELL LOGS	
APPENDIX G	HAZARD EVALUATION METHODOLOGY	
APPENDIX H	SITE RATING FORMS	
APPENDIX I	REFERENCES	
APPENDIX J	GLOSSARY	

LIST OF FIGURES

<u>Number</u>	<u>Title</u>	<u>Page</u>
1	Contaminated Site Locations	4
1.1	Decision Tree	1-5
2.1	Regional Location	2-2
2.2	Area Location	2-3
2.3	Site Plan	2-4
3.1	Physiographic Provinces of Georgia	3-3
3.2	Major Drainage Basins of Georgia	3-5
3.3	Surface Drainage	3-6
3.4	Soil Associations	3-7
3.5	Surficial Geology	3-12
3.6	Generalized Cross Section of Major Geologic Units	3-13
3.7	Principal Aquifers of The Coastal Plain of Georgia	3-15
3.8	Well Locations, City of Warner Robins	3-17
3.9	Base Water-Supply Well Locations	3-19
3.10	Boring and Monitoring Well Locations	3-21
3.11	Surface Water Quality Monitoring Station Locations	3-24
4.1	Fire Protection Training Areas	4-10
4.2	Fire Protection Training Area No. 2	4-12
4.3	Fire Protection Training Area No. 3 & No. 4	4-13
4.4	Pesticide Storage Area	4-16
4.5	Landfill Locations	4-20
4.6	Landfills No. 1 & No. 2	4-22
4.7	Landfill No. 3	4-25
4.8	Landfill No. 4 and Sludge lagoon	4-26
4.9	Waste Dump Locations	4-27
4.10	Hazardous Waste Burial Site	4-29
4.11	Radioactive Waste Burial Site and Aircraft Wash Areas	4-31
4.12	Radioactive Waste Burial Site	4-32
4.13	Wastewater Treatment Facilities	4-35

LIST OF TABLES

<u>Number</u>	<u>Title</u>	<u>Page</u>
1	Priority Ranking of Potential Contamination Sources	5
2	Recommended Monitoring Program for Phase II	7
3.1	Robins AFB Climatic Data	3-2
3.2	Robins AFB Base Soils	3-8
3.3	Geologic Formations	3-11
3.4	City of Warner Robins Municipal Wells	3-18
3.5	Summary of Robins AFB Wells	3-20
4.1	Industrial Operations (Shops)	4-3
4.2	Summary of Major Fuel Oil and Chemical Storage Capacities	4-17
4.3	Summary of Landfill Disposal Sites	4-21
4.4	Summary of On-Base Oil/Water Separators	4-37
4.5	Summary of HARM Scores for Potential Contamination Sources	4-38
5.1	Priority Ranking of Potential Contamination Sources	5-2
6.1	Recommended Monitoring Program for Phase II	6-5
6.2	List of Analytical Parameters	6-8

EXECUTIVE SUMMARY

EXECUTIVE SUMMARY

The Department of Defense (DOD) has developed a program to identify and evaluate past hazardous material disposal sites on DOD property, to control the migration of hazardous contaminants, and to control hazards to health or welfare that may result from these past disposal operations. This program is called the Installation Restoration Program (IRP). The IRP has four phases consisting of Phase I, Initial Assessment/Records Search, Phase II, Problem Confirmation, Phase III, Technology Base Development, and Phase IV, Operations. Engineering-Science (ES) was retained by the Air Force Engineering and Services Center to conduct the Phase I, Initial Assessment/Records Search at Robins AFB under Contract No. F08637-80-G009, Call No. 0009, using funding provided by the Air Force Logistics Command.

INSTALLATION DESCRIPTION

Robins AFB is located in middle Georgia approximately 90 miles southeast of Atlanta and 18 miles south of Macon. The base was activated in 1942 and presently comprises 8,855 acres. The primary mission of the base is serving as the parts and equipment logistics manager for a variety of aircraft. This mission has not changed significantly since the mid 1940's.

ENVIRONMENTAL SETTING

The environmental setting data reviewed for this study indicate the following key items concerning the impact of past waste disposal practices on the base:

- o Alluvial deposits cover the upper 20 to 40 feet of the base. The eastern part of the base is swampy with peat deposits covering the upper 10 to 15 feet and underlain by a thin layer of clay. The western part of the site consists of more sandy alluvial deposits which extend eastward below the swamp deposits.

- o The water table beneath the site is shallow, particularly to the east where a surface discharge contributes toward the creation of a swampy area. In the western part of the base, the surface soils are sandy and infiltration of precipitation is expected to be high. This infiltration would directly recharge the shallow aquifer.
- o The primary regional aquifer, the Cretaceous aquifer, underlies Robins AFB at a depth of about 40 to 50 feet and extends to a depth of approximately 650 feet below the surface. It consists of sand with a few clay lenses interspersed throughout its thickness.
- o Robins AFB obtains its water supply from twelve wells distributed over the installation. The City of Warner Robins has a separate system consisting of 11 wells, located throughout the city. All wells are drilled into the Tuscaloosa Formation of the Cretaceous aquifer.
- o Recharge for the Cretaceous aquifer occurs west of Robins AFB where the Providence sand outcrops at the surface. Some recharge may also occur beneath the base as some interconnection between alluvial and underlying deposits may occur.
- o Area precipitation rates (44.1 inches per year) are higher than potential evapotranspiration rates (42 inches per year).
- o Approximately 1200 acres of wetlands in the form of an unimproved river swamp system are located on the east side of the base. The wetlands are known to harbor two species of animals listed by the Federal government as threatened or endangered; American alligator and the red-cockaded woodpecker.

METHODOLOGY

During the course of this project, interviews were conducted with base personnel (past and present) familiar with past waste disposal practices, file searches were performed for facilities which have generated, handled, transported, and disposed of waste materials, interviews were held with local, state and federal agencies, and site inspections were conducted at facilities that have generated, treated,

stored, and disposed of hazardous waste. Thirteen disposal sites located on the Robins AFB property were identified as containing hazardous waste resulting from past waste disposal activities, (Figure 1). These sites have been assessed using a hazardous assessment rating methodology (HARM) which takes into account factors such as site characteristics, waste characteristics, potential for contaminant migration and waste management practices. The details of the rating procedure are presented in Appendix B and the results of the assessment are given in Table 1. The rating system is designed to indicate the relative need for follow-on action. Recent data for further assessment of potential contaminant migration are included.

FINDINGS AND CONCLUSIONS

The following conclusions have been developed based on the results of the project team's field inspection, review of base records and files and interviews with base personnel.

The areas determined to have a high potential for contaminant migration are as follows:

- o Sludge Lagoon
- o Landfill No. 4
- o DDT Spill (1979)


The areas determined to have a moderate potential for contaminant migration are as follows:

- o Fire Protection Training Area No. 2
- o Landfill No. 1
- o Landfill No. 2
- o JP-4 Spill (1965)
- o Hazardous Waste Burial Site
- o Fire Protection Training Area No. 1
- o Laboratory Chemical Disposal Site

The areas determined to have a low potential for contaminant migration are as follows:

- o Landfill No. 3
- o Fire Protection Training Area No. 3
- o Low Level Radioactive Waste (Solid) Burial Site

ROBINS AFB SITES WITH POTENTIAL FOR CONTAMINANT MIGRATION



NOTE:
Fire Protection Training Area No. 1 is situated in the area between Second Street and the southern end of the main runway.

SCALE 0 500 1000 2000 FEET

N

SOURCE: ROBINS AFB INSTALLATION DOCUMENTS

TABLE 1
PRIORITY RANKING OF POTENTIAL CONTAMINATION SOURCES
ROBINS AFB

Rank	Site Name	Date of Operation or Occurrence	Overall Total Score
1	Sludge Lagoon	1963-1978	77
2	Landfill No. 4	1965-1978	73
3	DDT Spill (1979)	1979	70
4	Fire Protection Training Area No. 2	mid 1950's to mid 1960's	64
5	Landfill No. 1	1943-1951	59
6	Landfill No. 2	1951-1953	58
7	JP-4 Spill (1965)	1965	57
8	Hazardous Waste Burial Site	1976, 1977	54
9	Fire Protection Training Area No. 1	1943-mid 1950's	52
10	Laboratory Chemical Disposal Site	early 1960's	51
11	Landfill No. 3	1964	47
12	Fire Protection Training Area No. 3	mid 1960's to 1969	45
13	Low Level Radioactive Waste (Solid) Burial Site	1940's to 1950's	31

Note: This ranking was performed according to the Hazardous Assessment Rating Methodology (HARM) described in Appendix G. Individual site rating forms are in Appendix H.

RECOMMENDATIONS

The detailed recommendations developed for further assessment of potential contaminant migration are presented in Chapter 6. These recommendations are summarized as follows:

- o Sludge Lagoon and Landfill No. 4 - Conduct geophysical surveys and additional ground-water monitoring.
- o DDT Spill Site - Remove contaminated soils and sample soils to verify clean up.
- o Fire Protection Training Area No. 2 - Collect and analyze soil borings in and around the site.
- o Landfill No. 1 and JP-4 Spill Site - Conduct geophysical surveys or sample the top of the water table. Also sample landfill leachate stream.
- o Landfill No. 2 and Fire Protection Training Area No. 1 - Conduct ground-water monitoring program.
- o Hazardous Waste Burial Site - Conduct ground-water monitoring program.
- o Laboratory Chemical Disposal Site - Conduct geophysical survey and collect and analyze soil borings.
- o Water Supply Wells - Sample and analyze well water.
- o Surface Water - Conduct additional surface water monitoring on the base.

CHAPTER 1
INTRODUCTION

CHAPTER 1
INTRODUCTION

BACKGROUND

The United States Air Force, due to its primary mission, has long been engaged in a wide variety of operations dealing with toxic and hazardous materials. Federal, state and local governments have developed strict regulations to require that disposers identify the locations and contents of disposal sites and take action to eliminate the hazards in an environmentally responsible manner. The Department of Defense (DOD) has issued Defense Environmental Quality Program Policy Memorandums 80-6 and 81-5 which require the identification and evaluation of past hazardous material disposal sites on DOD property, the control of migration of hazardous contaminants, and the control of hazards to health or welfare that resulted from these past operations. This program is called the Installation Restoration Program (IRP). The IRP will be a basis for response actions on Air Force Installations under the provisions of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) of 1980.

PURPOSE AND SCOPE OF THE ASSESSMENT

The Installation Restoration Program has been developed as a four-phased program as follows:

- Phase I - Initial Assessment/Records Search
- Phase II - Problem Confirmation
- Phase III - Technology Base Development
- Phase IV - Operations (Control Measures)

Engineering-Science (ES) was retained by the Air Force Engineering and Services Center to conduct the Phase I Records Search at Robins AF Base under Contract No. F08637-80-G0009, Call No. 0009, using funding provided by the Air Force Logistics Command. This report contains a

summary and an evaluation of the information collected during Phase I of the IRP.

The goal of the first phase of the program was to identify the potential for environmental contamination from past waste disposal practices at Robins AFB, and to assess the potential for contaminant migration. The activities undertaken in Phase I included the following:

- Review site records
- Interview personnel familiar with past generation and disposal activities
- Inventory wastes
- Determine quantities and locations of current and past hazardous waste storage, treatment and disposal
- Define the environmental setting at the base
- Review past disposal practices and methods
- Conduct field inspection
- Gather pertinent information from federal, state and local agencies
- Assess potential for contaminant migration

To perform the on-site portion of the records search phase, ES assembled the following core team of professionals:

- E. J. Schroeder, Environmental Engineer and Project Manager, MSCE, 14 years of professional experience
- R. E. Zimmermann, Hydrogeologist, BS Geology, 4 years of professional experience
- G. M. Gibbons, Environmental Engineer, MSCE, 3 years of professional experience
- M. I. Spiegel, Environmental Scientist, BS Environmental Science, 5 years of professional experience
- R. M. Reynolds, Chemical Engineer, BSChE, 8 years of professional experience

More detailed information on these individuals is presented in Appendix A.

METHODOLOGY

The methodology utilized in the Robins AFB Records Search began with a review of past and present industrial operations conducted at the

base. Information was obtained from available records such as shop files and real property files, as well as interviews with past and present base employees from the various operating areas of the base. Those interviewed included current and past environmental personnel associated with the Civil Engineering Squadron, the Bioenvironmental Engineering Services Division Office, and the Directorate of Maintenance. Several current or past personnel associated with the fire protection, wastewater treatment plant, pesticide program, fuels management and solid waste collection and disposal were interviewed extensively. Experienced personnel from the tenant organizations were also interviewed. Formal interviews were conducted with 62 personnel to obtain the needed past activity information.

Concurrent with the base interviews the applicable federal, state and local agencies were contacted for pertinent base related environmental data. The agencies contacted and interviewed are listed as follows:

- o U.S. Environmental Protection Agency, Region IV, Atlanta, Georgia
- o U.S. Soil Conservation Service, Atlanta, Georgia
- o U.S. Geological Survey, Atlanta, Georgia
- o Georgia Geological Survey, Atlanta, Georgia
- o Georgia Environmental Protection Division, Atlanta, Georgia
- o City of Warner Robins Water Department, Warner Robins, Georgia
- o Georgia Game and Fish Division of the Department of Natural Resources, Fort Valley, Georgia.

The next step in the activity review was to determine the past management practices regarding the use, storage, treatment, and disposal of hazardous materials from the various operations on the base. Included in this part of the activities review was the identification of all known past disposal sites and other possible sources of contamination such as fuel-saturated areas resulting from spills.

An aerial overflight and a general ground tour of identified sites were then made by the ES Project Team to gather site specific information including (1) visual evidence of environmental stress, (2) the presence of nearby drainage ditches or surface-water bodies, and (3)


visual inspection of these water bodies for any obvious signs of contamination or leachate migration.

A decision was then made, based on all of the above information, whether a potential exists for hazardous material contamination at any of the identified sites using the decision tree shown in Figure 1.1. If no potential exists, the site was deleted from further consideration. For those sites where a potential for contamination was identified, a determination of the potential for migration of the contamination was made by considering site-specific conditions. If the potential for contaminant migration was considered significant, then the site was evaluated and prioritized using the hazardous assessment rating methodology (HARM).

The HARM score indicates the relative potential for contaminant migration at each site. For those sites showing a high potential, recommendations are made to quantify the potential contaminant migration problem under Phase II of the Installation Restoration Program. For those sites showing a moderate potential, a limited Phase II program may be recommended to confirm that a contaminant migration problem does or does not exist. For those sites showing a low potential, no further follow-up Phase II work would be recommended.

PHASE I INSTALLATION RESTORATION PROGRAM

DECISION TREE



CHAPTER 2
INSTALLATION DESCRIPTION

CHAPTER 2 INSTALLATION DESCRIPTION

LOCATION, SIZE AND BOUNDARIES

Robins AFB is located in middle Georgia approximately 90 miles southeast of Atlanta and 18 miles south of Macon as shown in Figures 2.1, 2.2 and 2.3. The base lies within the lower Ocmulgee River Basin and drains primarily to Horse Creek. The boundaries of the base cover 8,855 acres with facilities for operation, industrial, administrative and supply functions. Present land areas adjacent to the base are primarily as follows:

- North - commercial, residential
- East - dense forest, swamp
- South - commercial, residential
- West - commercial, residential

The most prominent physiographic features of the area are the Ocmulgee River and the swamp surrounding the east portion of the base.

BASE HISTORY

The initial construction of Robins AFB began in 1941 on a 3,000 acre tract of land donated by the City of Macon and Bibb County. The base was officially activated in March 1942. Subsequent acquisitions by the Federal government increased the size of the installation to its present 8,855 acres. The original intent was to establish Robins AFB as a maintenance and supply depot, but the installation also was used as a training center. Original facilities included both temporary and permanent structures. After World War II, the base ceased its training functions while continuing its supply and maintenance role.

A second growth surge began in 1949 when the Fourteenth Air Force Headquarters moved to Robins AFB, where it remained until deactivated in 1960. The largest construction program commenced in 1958 to prepare facilities for the 19th Bombardment wing as a tenant organization. Runway enlargement and family housing areas were included in this

FIGURE 2.1






FIGURE 2.2



ROBINS AFB SITE PLAN



SOURCE: ROBINS AFB INSTALLATION DOCUMENTS

program. In 1962, the runways were further rehabilitated to better accommodate the B-52 and KC-135 aircraft. In 1974, the Technology Repair Center (TRC) was created as a function of the Warner Robins Air Logistics Center (WR-ALC). In addition to depot maintenance responsibility for assigned aircraft, the WR-ALC, TRC, performed repair services on aircraft component systems.

A complete description of Robins Air Force Base history is presented in Appendix B.

ORGANIZATION AND MISSION

The primary mission of Robins AFB are the responsibilities assigned to the Warner Robins Air Logistics Center (WR-ALC). The WR-ALC has a threefold mission as follows:

- a. It is the worldwide logistics manager for assigned aircraft and commodities;
- b. It is the repair center for aircraft and five distinct technologies;
- c. It serves as a storage center at wholesale and retail levels for Air Force spare parts and systems.

The WR-ALC is logistics manager for five Air Force transport aircraft (C-141, C-130, C-7, C-140, C-123), the F-15 fighter, a bomber used in reconnaissance (B-57), eight missiles, five helicopters, seven utility aircraft and seven drones and remotely piloted vehicles. In addition, electronics equipment managed at WR-ALC ties its support to every element of the aerospace combat forces.

WR-ALC is the exclusive technology repair center for airborne electronics for the Air Force. In addition, aircraft repair and maintenance responsibilities for the F-15, C-141 and C-130 are assigned to the WR-ALC. The WR-ALC has various shops (plating, machining, metal bonding, etc.) which support the major workload activities.

The third major mission involves receiving, storing, issuing and transporting material. These functions are carried out in automated warehouses on base. In conjunction with its worldwide missions, WR-ALC has a geographical area of responsibility for logistics support of Air Force installations which include Eastern United States, Newfoundland,

Greenland, Iceland, Bermuda, The Azores and activities in Europe, Africa and the Mid-East.

The 2853rd Air Base Group provides the services and support to carry out the mission of the WR-ALC and other tenant organizations on Robins AFB. Descriptions of the tenant organizations and their missions are presented in Appendix B.

CHAPTER 3
ENVIRONMENTAL SETTING

CHAPTER 3

ENVIRONMENTAL SETTING

The environmental setting of Robins AFB is described in this chapter with the primary emphasis directed toward identifying features which may affect the movement of hazardous waste contaminants. A summary of the environmental setting pertinent to the study are highlighted at the end of the section.

METEOROLOGY

Temperature and precipitation data furnished by the Global Climatology Branch, Robins AFB, are presented in Table 3.1. The period of record is 33 years. The summarized data indicate that the mean annual precipitation is 44.1 inches. Using Thornthwaites Equation (Chow, 1964, p.11.27-28) potential evapotranspiration for the Warner Robins Area is 42.0 inches.

GEOGRAPHY

Robins Air Force Base lies along the upper margin of the Coastal Plain province. The Coastal Plain is part of a large coastal province extending from Long Island, N.Y., to the Mexican border (LeGrand, 1962). Just north of the study area, lies the Piedmont Province (Figure 3.1). The line separating the Piedmont from the Coastal Plain is generally known as the Fall Line. This line separates the more resistant crystalline rocks of the Piedmont from the less resistant deposits of the Coastal Plain.

Locally, Robins AFB lies within the Coastal Plain province but is situated on alluvial deposits along the Ocmulgee River. These deposits form a low terrace about 3 miles wide extending westward from the river to the City of Warner Robins.

TABLE 3.1


ROBINS AFB CLIMATIC DATA

Month	Precipitation		Mean max (°F)	Temperature	
	Mean (in.)	Max (in.)		Mean (°F)	Mean min (°F)
January	4.0	8.4	57.5	47.5	37.2
February	4.5	9.0	60.7	50.2	39.2
March	4.8	10.6	67.7	56.9	45.7
April	3.2	8.4	76.9	65.4	53.6
May	3.5	7.2	84.0	73.1	61.7
June	3.7	7.0	88.9	78.9	68.5
July	5.1	9.3	90.3	81.1	71.6
August	3.8	6.7	90.2	80.7	70.9
September	2.9	7.9	85.3	75.8	65.9
October	2.2	7.4	77.1	65.8	54.0
November	2.2	5.4	67.3	55.6	43.5
December	4.4	11.5	59.5	49.2	38.5
Annual	44.3	--	75.5	65.0	54.2

Source: Global Climatology Branch, Robins AFB

FIGURE 3.1

PHYSIOGRAPHIC PROVINCES OF GEORGIA



Topography

The Coastal Plain is basically level with an eastward slope of approximately 2-3 feet per mile from the Fall Line to the Georgia coast (Thomson et al, 1956). Robins AFB is located on a low alluvial terrace of the Ocmulgee River. The slope of the base east of Highway 247 is towards the east with elevations of 300 feet MSL on the western edge of the site and 240 feet MSL on the east along the Ocmulgee River. Much of the area bordering the base is low lying swamp land and parts of the base have been constructed over reclaimed swamp land.

Drainage

Robins AFB lies within the drainage basin of the Ocmulgee River, known as the Altamaha basin (Figure 3.2). The installation is drained by several unnamed intermittent streams as well as overland flow. Direction of surface flow is to the east, through the swamp (Figure 3.3).


A large portion of precipitation on the site may not become surface flow but rather infiltrate through the sandy soil. Based on the intensity of precipitation and on the amount of moisture in the soil, this water most likely will recharge the shallow aquifer. Approximately 4.2 inches of total annual precipitation will become recharge to the shallow aquifer. Flooding is a problem on the eastern boundary of the base where the water table intersects the surface and results in swamp development. During flooding periods, Hannah Road would become inundated, as would several other areas at the base including parts of some past waste disposal sites.

Surface Soils

Surface soils of the Robins Air Force Base area have been reported by the USDA, Soil Conservation Service (1967). Twenty soil types have been mapped within installation boundaries and are depicted on Figure 3.4. The individual soil types are discussed on Table 3.2. Base soils fall within two distinct groups: sandy upland soils, and wet, organic lowland types. All the soil types present on the installation exhibit moderate to severe constraints on the development of waste disposal facilities, due either to permeability or flooding potential.

FIGURE 3.2

MAJOR DRAINAGE BASINS OF GEORGIA



LEGEND

— MAJOR DRAINAGE BASIN BOUNDARY

SOURCE: THOMSON, HERRICK, BROWN ET AL. (1956)

0 50
SCALE MILES






FIGURE 3.3

ROBINS AFB SURFACE DRAINAGE



SOURCE: ROBINS AFB INSTALLATION DOCUMENTS

FIGURE 3.4



ROBINS AFB SOIL ASSOCIATIONS

SOURCE: USDA-SOIL CONSERVATION SURVEY (1967)

TABLE 3.2

ROBINS AIR FORCE BASE SOILS

Symbol	Description	USDA Texture	Thickness (in.)	Unified Classification	Permeability (in/hr)	RWD Facility Use Constraints
Avp	Alluvial land, wet, 0-2 percent slopes	Organic clay loam, clay	36+	SC,CL,CH,OH	Not estimated	Severe - floods
Cls	Chastain leaf soils, 0-2 percent slopes	Silt loam, silty clay loam, silty clay; clay	50	M1,CL	<0.2 - 0.63	Severe - floods
LcB	Lucy sand, 0-5 percent slopes	Sand, loamy sand, sandy	60	SP,SM,SC,CL	0.63 - >6.3	Severe - High permeability
LcC	Lucy sand, 5-8 percent slopes	Sand, loamy sand, sandy	60	SP,SM,SC,CL	0.63 - >6.3	Severe - High permeability
LcD	Lucy sand, 8-12 percent slopes	Sand, loamy sand, sandy	60	SP,SM,SC,CL	0.63 - >6.3	Severe - High permeability
LcM	Local alluvial land, 0-2 percent slopes	This unit is highly variable.	24-36	Properties not estimated		Severe - floods
LqB	Lakeland fine sand, 0-5 percent slopes	Fine sand, sand	60	SP,SM	>6.3	Severe - High permeability
LqD	Lakeland fine sand, 5-12 percent slopes	Fine sand, sand	60	SP,SM	>6.3	Severe - High permeability
NgA	Norfolk loamy fine sand, 0-2 percent slopes	Loamy fine sand, sandy clay loam	58	SM,SC,CL	0.63 - >6.3	Moderate permeability
NgB	Norfolk loamy fine sand, 2-5 percent slopes	Loamy fine sand, sandy clay loam	58	SM,SC,CL	0.63 - >6.3	Moderate permeability
NgB ₂	Norfolk loamy fine sand, 2-5 percent slopes, eroded	Loamy fine sand, sandy clay loam	58	SM,SC,CL	0.63 - >6.3	Moderate permeability
NgC ₂	Norfolk loamy fine sand, 5-8 percent slopes, eroded	Loamy fine sand, sandy clay loam	58	SM,SC,CL	0.63 - >6.3	Moderate permeability
OgA	Orangeburg loamy fine sand, 0-2 percent slopes	Loamy fine sand, sandy clay loam	64	SM,SC	0.63 - >6.3	Moderate permeability
OgB	Orangeburg loamy fine sand, 2-5 percent slopes	Loamy fine sand, sandy clay loam	64	SM,SC	0.63 - >6.3	Moderate permeability
OgB ₂	Orangeburg loamy fine sand, 2-5 percent slopes, eroded	Loamy fine sand, sandy clay loam	64	SM,SC	0.63 - >6.3	Moderate permeability
OgC ₂	Orangeburg loamy fine sand, 5-8 percent slopes, eroded	Loamy fine sand, sandy clay loam	64	SM,SC	0.63 - >6.3	Moderate permeability
OgD ₂	Orangeburg loamy fine sand, 8-12 percent slopes, eroded	Loamy fine sand, sandy clay loam	64	SM,SC	0.63 - >6.3	Moderate permeability
RhA	Red Bay fine sandy loam, 0-2 percent slopes	Fine sandy loam, sandy clay loam	70	SM,SC,CL	0.63 - 6.3	Moderate permeability
Swa	Swamp	Perennial wetland		Properties not estimated		Severe - floods
VOD ₂	Vaucluse-Hoffman complex, 8-12 percent slopes, eroded	Loamy sand, sandy clay loam	60	SM,SC,CL	0.63 - >6.3	Moderate permeability

Source: USDA, Soil Conservation Service, 1967

GEOLOGY

The geology of the Warner Robins AFB has been reported by LeGrand (1962), Herrick (1961, 1963, and 1965), Thomson et al. (1956), Herrick and Vorhis (1963), Sonderegger (1978), Pollard (1980), and Mitchell (1979) among others. A brief review of their work has been summarized in support of this investigation.

Stratigraphy

Stratigraphy of the area was studied in order to understand the occurrence and movement of ground water beneath the site. Geologic units ranging from Cretaceous to Quaternary have been described in the Warner Robins area and are presented in Table 3.3. The lithologies of these units are typically unconsolidated material. Older Cretaceous units are encountered at depths of approximately 1700 feet. Crystalline basement rocks are typically encountered at depths greater than 1750 feet below ground surface (LeGrand, 1962).

Regionally, the site is located within the upper Coastal Plain province, but locally, lies on an alluvial terrace of the Ocmulgee River. Sections of the base constructed in swamps have been built up over fill material and do not represent original stratigraphic sequences. The uppermost native unit consists of alluvial deposits of two types depending upon exact location on the base (refer to Geologic Map and legend, Figure 3.5). In the lowland or swampy areas typical of the eastern portion of the base, as well as beneath many of the artificially filled areas, a 5 to 15 foot thick layer of peat and fine silts are encountered, generally underlain by a thin (3 to 5 feet) layer of clay. In upland areas typical of the western half of the base, however, fine alluvial sands and silts are present at the surface and grade into sands and fine gravels with increasing depth. A clay layer not known to exist below these deposits. These sand and fine gravel alluvial deposits also underlie the organic deposits in the lowlands. These are recent deposits and may be 20 to 25 feet thick.

Directly below the surficial alluvial deposits are the most significant geologic units, comprised primarily of several hundred feet of permeable sands. The uppermost major unit is the Providence Sand. It is the youngest and uppermost Cretaceous formation in Georgia.

It consists of light colored sands, interbedded with numerous layers of clay. Thickness of the Providence Sand ranges from 60 to 120 feet and is approximately 60 feet at Robins AFB (LeGrand, 1962).

Immediately underlying the Providence Sand is the Tuscaloosa Formation. Although it does not crop out at the base, it is the oldest outcropping formation of Georgia's Coastal Plain Region (LeGrand 1962). Lithologically, the Tuscaloosa is almost identical to the Providence Sand. It also consists of a light-colored sand with numerous lenticular masses of clay interbedded throughout the formation. These clay beds are generally lenses which can not be traced far. Thickness of this formation ranges from 500 to 600 feet. A generalized geologic section depicting the relationships of major geologic units is presented as Figure 3.6. The Tuscaloosa Formation is a superb aquifer capable of producing tremendous quantities of excellent quality water. Both Robins AFB and the City of Warner Robins use this formation as a source of their water supplies.

Immediately below the Tuscaloosa formation are crystalline rocks of Paleozoic, or possibly older, age. No records were found of wells reaching bedrock, therefore, the exact depth to these units is uncertain. Due to the depth and nature of these formations, they would not be a significant source of water in this area.

Distribution

The areal distribution of geologic units significant to this study is mapped on Figure 3.5, which is modified from the work published by H. E. LeGrand (1962). Most of the site is immediately underlain by alluvial deposits of the Ocmulgee River. The depth to consolidated deposits is not confirmed, but presumed to be at least 1700 feet below the surface, based upon regional geologic data. The western half of the base is dominated by sandy alluvial deposits while the eastern part of the base is underlain by peat and fine grained organic silt deposits.

HYDROGEOLOGY

Ground-water hydrology of the Warner Robins Area has been reported by LeGrand (1962), Mitchell (1979), Pollard and Vorhis (1980), Thomson (1956), Herrick (1961) and Sonderegger (1978). Supporting information


TABLE 3.3
GEOLOGIC FORMATIONS IN ROBINS AFB AREA

System	Series	Formation	Thickness (feet)
Quaternary	Pliocene to Recent	Swamp Deposits: Peat, organic silty clays deposited in Ocmulgee River generally over alluvian.	5-20
		Alluvial Deposits: Silts, sands and gravels deposited along major stream borders and in interstream areas.	
Tertiary	NONE PRESENT	UNDERLYING ROBINS AFB	
Cretaceous	Upper	Providence Sand: Light colored sand interbedded with lenticular layers of clay.	60-120
		Tuscaloosa Formation: Light colored sand interbedded with several lenticular layers of clay.	500-600

Source: LeGrand, 1962

FIGURE 3.5

ROBINS AFB SURFICIAL GEOLOGY




LEGEND

- Quaternary: Alluvium
- Tertiary : Ocala Limestone and Barnwell Formation
- Tertiary : Gosport Sand
- Cretaceous: Providence Sand
- Cretaceous: Rocks of Late Cretaceous Age, Undifferentiated

SOURCE: LEGRAND (1962)

FIGURE 3.6

GENERALIZED CROSS SECTION OF MAJOR GEOLOGIC UNITS



has been obtained from Robins AFB water department files and files from the City of Warner Robins water plant. Additional information on permeabilities and shallow ground-water quality were obtained from a report by Law Engineering Testing Company (LETCO, 1980).


The Coastal Plain province in Georgia extends from the Fall Line on the north to Florida in the south and from the Savannah River and the Atlantic Ocean on the east to the Chattahoochee River on the west.

The Coastal Plain may be divided into three areas (Figure 3.7) according to aquifer availability and utilization (Thomson, Herrick, Brown et al, 1956). Along the Fall Line, and for a distance of 30 to 60 miles south of it, sand and gravel of Cretaceous age constitute the principle aquifer. Sands and gravels of both the Providence Sand and Tuscaloosa Formation comprise the Cretaceous aquifer which extend to a depth of 600 to 700 feet below the surface at Robins AFB.

An important consideration in assessing ground-water contamination is the water present in the upper alluvial deposits. These deposits are not used locally as a source of water supply, although some degree of interconnection may occur between this and the underlying formations.

Ground water exists beneath Robins AFB under both water table and artesian conditions. The water table is present throughout the base in the upper sandy alluvial deposits. The water table discharges to the east and contributes to the development of a swampy area extending to the Ocmulgee River, LeGrand, (1962). There appears to be a confining bed just below the swamp deposits which would create weak artesian conditions immediately below this upper layer. Both the land surface and the beds are inclined towards the southeast, but the inclination of the beds is steeper. The numerous interbedded clay layers in both the Providence Sand and the Tuscaloosa Formation create artesian conditions within them. Surface water recharge, particularly precipitation, enters the ground, percolates to the water table and flows downgradient to a point where the zone of saturation is interrupted by an impermeable bed. Part of the water may pass above the bed and continue to flow under water table conditions and the other part of it flows beneath the confining bed. This is confined or artesian water; it will rise in a tightly cased well to a height above the bottom of the confining bed. The interlayering of clay and sand results in a composite artesian


PRINCIPAL AQUIFERS OF THE COASTAL PLAIN OF GEORGIA



LEGEND

— AQUIFER BOUNDARY

SCALE 0 50 MILES



SOURCE: THOMSON, HERRICK, BROWN ET AL. (1956)

system consisting of several artesian sand aquifers, and intervening clay confining beds.


In the study area, deposits of Cretaceous age furnish adequate water supplies to present users and are capable of yielding large supplies to future developers. The City of Warner Robins obtains its water from wells screened in various sand layers of the Tuscaloosa Formation (See Well Logs - Appendix F). Figure 3.8 shows the location of these wells and Table 3.4 gives a brief summary of the wells. The city wells have capacities which range from 1000 to 1600 gpm indicating the large quantity of water available from this aquifer. Robins AFB has 12 wells. The logs of these wells are shown also in Appendix F. Of these 12 wells, numbers 1 through 8 are used as a drinking water source. Locations and a summary of these wells are given in Figure 3.9 and Table 3.5. Well No. 9 furnishes water supplies to the Federal Aviation Administration (FAA) building. Well No. 10 is not connected to the public system but is an independent two-inch diameter well used for drinking water supply at the skeet range. Wells No. 11 and No. 12 are used for water level maintenance at Luna and Scout Lakes.

Ground-Water Quality

Ground-water flow direction in the Cretaceous aquifer is in an easterly-southeasterly direction (LeGrand, 1962), discharging to the Ocmulgee River locally. Natural ground-water quality in the Cretaceous aquifer has been reported to be excellent (LeGrand, 1962). Results from samples collected from these wells in January of 1978 indicated the quality to be excellent with very little mineral content present. Results did not indicate any contamination of these wells for the parameters tested; an organic scan was not run.

Shallow ground water in the vicinity of Landfill No. 4 was reported by Law Engineering Testing Company (LETCO, 1980) to be contaminated. Several shallow monitoring wells installed by LETCO (Figure 3.10) indicate the presence of various concentrations of chloride, dissolved solids, nitrate, cyanide, arsenic, calcium, chromium, lead, manganese and zinc. An organic scan was run on monitoring wells nos. 4, 5, 15, and 18. The results of this analyses indicated the presence of methylene chloride, phenol, diethylphthalate, bis(2-ethylhexyl)phthalate, benzene, chlorobenzene, trans-1,2-dichloroethylene,

City of Warner Robins WELL LOCATIONS




SOURCE: CITY OF WARNER ROBINS, WATER DEPARTMENT DOCUMENTS (1981)

TABLE 3.4
CITY OF WARNER ROBINS MUNICIPAL WELLS

Well No.	Casing Diam. (in.)	Total Depth (feet)	Capacity (GPM)	Static Depth Below Ground Surface (Feet)	Motor H.P.	Date Drilled	Remarks
1A	12	540	1557	129	150	1981	10' screens at 340', 370' and 420' 20' screens at 440', 470' & 510'
2A	25	580	1613	132	150	1979	10' screens at 174', 300', 478' and 495' 40' screen at 400'
3	10	415	1000	105	75	1961	10' screen at 360' 20' screen at 275' 15' screen at 390'
4	12	390	1559	122	100	1960	10' screen at 240' and 320' 20' screen at 360'
5	12	422	1100	132	75	1962	10' screens at 235' & 270' 20' screen at 392' 5' screen at 349'
6	12	435	1050	116	100	1968	10' screens at 250', 390' and 415' 20' screen at 290'
7	12	440	1641	105	150	1972	10' screen at 240', 20' screen at 345', 30' screen at 400'
8	12	430	1641	101	150	1970	20' screens at 240', 360' and 400' 15' screen at 305'
9	12	490	1613	101	150	1971	10' screens at 330' and 405' 20' screens at 360' and 460'
10	12	480	1613	56		1976	
11	12	440	1600	47	100	1976	

Source: City of Warner Robins Water Plant Files

ROBINS AFB WATER SUPPLY WELL LOCATIONS



SOURCE: ROBINS AFB INSTALLATION DOCUMENTS


TABLE 3.5
SUMMARY OF ROBINS AFB WELLS

Bldg No.	Well No.	Casing Diam.	Feet Depth	Capacity (GPM)	Orig. Static Level	Motor H.P.	Pump Type	Date Drilled	Remarks
186	1	12"	362	835		100	Vertical turbine	1941	Redrilled
	1A	12"	389	950				1975	
164	2	12"	255	900		100		1941	Redrilled
	2A	12"	386	900				1974	
	3	12"	298	1300			Vertical turbine	1942	
648	4	12"	430	775		60		1943	
	4A	12"	385	992		60		1956	
511	5	12"	355	700				1942	Redrilled
	5A	12"	430	1230	45'	100		1963	
	6	12"	367	1500	45'	150		1943	
	6A	12"	495	1500	63'			1976	Redrilled
	7							1944	Redrilled
	7A	12"	490	992	38'	100		1958	
61	8	8"	522	900	9'	75		1958	
	9	6"	140	30	60'	3	Submersible	1958	
	9A	-	135	300		7 1/2	Submersible	1970	6"Outlet
	10	(Small well - data unavailable)							
	11		180	10	45'	1	Jet pump	1968	2"Outlet
	12			20		1	Submersible	1966	4"Outlet

Source: Robins AFB Files

Note: The A notation after the Well No. indicates that the well was redrilled.

FIGURE 3.10



trichloroethylene, and 1,1,2,2 tetrachloroethylene in the shallow ground water downgradient of Landfill No. 4 and the sludge lagoon. A summary of the LETCO ground-water quality data is included in the appendix. This study was conducted at Landfill No. 4 and shallow ground-water quality elsewhere on the base has not been investigated.

In the area of Landfill No. 4, weak artesian conditions may exist below the thin clay layer which underlies the swamp deposits (LeGrand, 1962, Figures 6). Both of these factors (clay layer and artesian conditions) may affect the concentrations of contaminants entering the lower aquifer. The upper clay layer, which is probably restricted to the zone underlying the swamp deposits, may act as a confining bed preventing any further infiltration. It is important to note however, that organic compounds such as methylene chloride and other chlorinated hydrocarbons have the ability to move through clay more rapidly than water would move through clay (Roberts et al, 1980, and Giger and Molnar-Kubica, 1978). The mechanisms through which this occurs are extremely complex but have been shown through experimentation. Under normal circumstances, weak artesian conditions appear to exist in the deposits immediately below the clay. This may cause the "upwelling" of water from below the fill rather than infiltration from the fill into the aquifer. The fate of organics in the subsurface is extremely difficult to predict because of the uncertainty involved in describing precise attenuation mechanisms occurring under unsaturated and saturated conditions.

SURFACE WATER QUALITY

Robins AFB has several streams and surface drainage systems which originate on or flow through the base property. All of these streams drain in a general west-to-east course and ultimately flow to the Ocmulgee River either via defined creek beds such as Horse Creek or by dissipated overland drainage through the adjacent swamp areas. The streams have been monitored routinely at several locations by the base Bioenvironmental Engineering Services Division (BESD) in compliance with State permit requirements. In addition to the required monthly sampling program, the BESD conducted a baseline chemical characterization survey of the non-potable surface waters within the base between 1978 and 1979

(Talley, et al., 1979). Figure 3.11 depicts the surface water monitoring stations presently sampled for NPDES permit compliance as well as the additional stations sampled during the 1978-1979 baseline survey. Summaries of the data compiled during the 1978-1979 study and the 1981 NPDES data are included in Appendix C.


The 1978-1979 water quality survey detected levels of phenol from 0.05 to 1.5 mg/l in the Hannah Road runoff ditch, Station 004. Ammonia-nitrogen concentrations at Station 004 ranged between 4.0 and 8.6 mg/l and manganese concentrations ranged from 0.057 to 0.18 mg/l. The phenol and ammonia values may be attributable to the sanitary sewage treatment plant No. 1 discharge or to seepage from past landfills adjacent to the creek. The 1981 NPDES data revealed only one sample which exceeded the 2.0 mg/l ammonia nitrogen limitation at a concentration of 2.4 mg/l. Phenols were not sampled at this location; however, the phenol data collected directly from the sanitary treatment plant No. 1 effluent (Station 009) were at or below the NPDES limits. Oil and grease concentrations ranged from 0.3 to 6.2 mg/l at Station 004 and from 0.2 to 4.7 mg/l at Station 009. The oil and grease concentrations at Station 004 was frequently higher than those detected upstream at Station 009, signifying that oil and grease may be entering the ditch at some point downstream of the industrial wastewater treatment plant.

All remaining monitoring stations were found to have good water quality values. The only noticeably high constituent detected was total iron in samples collected from Stations 001 and 005 during the 1978-1979 survey. These concentrations ranged from 0.28 to 3.4 mg/l for Station 001 and 0.57 to 1.8 mg/l for Station 005.

WETLAND AREAS

Robins AFB has 1,178 acres of wetlands in the form of an unimproved river swamp system. The swamp area provides important functions for the sustenance of aquatic life and water quality in the river and streams receiving its drainage. These functions include providing breeding

ROBINS AFB SURFACE WATER QUALITY MONITORING STATION LOCATIONS



SOURCE: ROBINS AFB INSTALLATION DOCUMENTS

grounds for various aquatic organisms as well as providing the streams with vital organic matter which serves as a food source for the many organisms inhabiting these areas. In addition, the swamp is known to harbor two species of animals listed by the Federal government as threatened or endangered. These species are the American alligator and the red-cockaded woodpecker. Ten alligators have been sighted on Robins AFB and it is estimated that approximately 15-20 alligators actually exist on base. Approximately ten red-cockaded woodpeckers have been sighted on the base. A list of the threatened or endangered vertebrate species potentially present is included in Appendix C. There are also several species of threatened or endangered plants which potentially occur within the swamp area.

Summary of Environmental Settings

The environmental setting data reviewed for this study indicate the following key items concerning the impact of past waste disposal practices on the base:

- o Alluvial deposits cover the upper 20 to 40 feet of the base. The eastern part of the base is swampy with peat deposits covering the upper 10 to 15 feet and underlain by a thin layer of clay. The western part of the site consists of more sandy alluvial deposits which extend eastward below the swamp deposits.
- o The water table beneath the base is shallow, particularly to the east where a surface discharge contributes toward the creation of a swampy area. In the western part of the base, the surface soils are sandy and infiltration of precipitation is expected to be high. This infiltration may directly recharge the shallow aquifer.
- o The primary regional aquifer, the Cretaceous aquifer, underlies Robins AFB at a depth of about 40 to 50 feet and extends to a depth of approximately 650 feet below the surface. It consists of sand with a few clay lenses interspersed throughout its thickness.
- o Robins AFB obtains its water supply from twelve wells distributed over the installation. The City of Warner Robins has a separate system consisting of 11 wells, located throughout the

city. All wells are drilled into the Tuscaloosa Formation of the Cretaceous aquifer.

- o Recharge for the Cretaceous aquifer occurs west of Robins AFB where the Providence sand outcrops at the surface. Some recharge may also occur beneath the base as some interconnection between alluvial and underlying deposits may occur.
- o Area precipitation rates (44.1 inches per year) are higher than potential evapotranspiration rates (42 inches per year).
- o Approximately 1200 acres of wetlands in the form of an unimproved river swamp system are located on the east side of the base. The wetlands are known to harbor two species of animals listed by the Federal government as threatened or endangered; American alligator and the red-cockaded woodpecker.

From these major points, it may be seen that the potential for the generation and migration of contamination caused by past waste disposal practices is high. The presence of shallow ground-water contaminants has been documented near landfill No. 4 (LETCO, 1980). Although the production wells located on the base are several hundred feet deep, some degree of interconnection between upper and lower aquifers potentially could occur. Information obtained from base production wells and from ground-water monitoring data (LETCO, 1980) indicate that the base is located in a ground-water discharge area; i.e. the hydraulic gradient is upward. However, the production wells will alter this gradient within their particular zone of influence and may induce the downward movement of leachate. On the eastern edge of the base, some migrating contaminants may be transported in shallow ground-water flow and discharged at the surface into the swamp.

CHAPTER 4

FINDINGS

CHAPTER 4

FINDINGS

To assess hazardous waste management at Robins Air Force Base, waste generation and disposal methods were reviewed. This chapter summarizes the hazardous waste generated by activity, describes waste disposal methods, identifies the disposal sites located on the base, and evaluates the potential for contaminant migration.

PAST SHOP AND BASE ACTIVITY REVIEW

To identify past base activities that resulted in generation and disposal of hazardous waste, a review was conducted of current and past waste generation and disposal methods. This review consisted of interviews with base employees, a search of files and records, and site inspections.

The source of most hazardous wastes on Robins AFB can be associated with one of the following activities:

- o Industrial shops
- o Fire protection training
- o Pesticide utilization
- o Fuels management

The following discussion addresses only those wastes generated on base which are either hazardous or potentially hazardous. In this discussion a hazardous waste is defined as hazardous by the Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA). A potentially hazardous waste is one which is suspected of being hazardous although insufficient data are available to fully characterize the waste material.

Industrial Shops

The industrial operations at Robins AFB can be divided into two major groups as follows: The Directorate of Maintenance and other base facilities or tenant organizations. Five major divisions embody the majority of the shop activities for the Directorate of Maintenance. The divisions include the Aircraft Division, Plant Management Division, Airborne Electronics Division, Quality Division and Industrial Products Division. A principal source of waste materials generated at Robins AFB has been the Directorate of Maintenance areas.

Other base maintenance support activities include the industrial shops from the Directorate of Distribution, the 2853rd Air Base Group, the 2853rd Civil Engineering Squadron, the 5th Combat Communications Group, the 19th Bombardment Wing, and the 1926th Communication Installation Group. These industrial operations include primarily vehicle, electrical and aircraft maintenance and repair.

In order to identify those shops which handle hazardous materials and/or generate hazardous waste, a review was made of the Bioenvironmental Engineering Services Division shop files. The results of this file review are shown in Appendix D, Master List of Industrial Shops.

For those shops identified that handled hazardous materials or generated hazardous waste, key personnel within the Directorate of Maintenance and other base maintenance support functions were interviewed. A timeline of disposal methods was established for major wastes generated. The information from the interviews with base personnel and base records is summarized in Table 4.1. This table shows the building locations as well as the waste material names, waste quantities, and disposal method timeline.

TABLE 4.1 INDUSTRIAL OPERATIONS (Shops)

HAZARDOUS WASTE MANAGEMENT

1 of 6

SHOP NAME	LOCATION (BLDG. NO.)	WASTE MATERIAL	WASTE QUANTITY ⁽¹⁾	METHOD(S) OF TREATMENT, STORAGE & DISPOSAL 1950 1960 1970 1980
DIRECTORATE of DISTRIBUTION HAZARDOUS CHEMICAL STORAGE	327	NON-SALABLE PAINT STRIPPERS NON-SALABLE, EXPIRED SHELF-LIFE CHEMICALS	10 to 15 GALS. /YR. 15 to 30 LBS. /YR.	SANITARY SEWER DPDO (4) ON-BASE LANDFILLS DPDO OFF-BASE CONTRACTORS DPDO ON-BASE LANDFILLS DPDO OFF-BASE CONTRACTORS DRUMMED TO BASE LANDFILLS DPDO DPDO DPDO DPDO 1950 1980
PAINT SHOP	358	PAINT SHOP WASTES, MISCELLANEOUS	25 GALS. /MO.	
GUN ROOM (Cleaning)	368	SOLVENTS	25 GALS. /18 MOS.	
DIRECTORATE of MAINTENANCE <u>AIRCRAFT DIVISION</u> CORROSION CONTROL	58 (1979 to Present) 110 (to 1979)	PHENOLIC/NON-PHENOLIC PAINT STRIPPERS PHOSPHORIC ACID CLEANER CHROMIC ACID CLEANER	1,500 to 2,000 GALS. /WK. 800 GALS. /MO. 800 GALS. /MO. 55 GALS. /WK.	NEGLECTIBLE STRIPPING 1957 STORM SEWER IWTP NEUTRALIZED TO SANITARY SEWER IWTP CHEMICAL REDUCTION TO STORM SEWER IWTP BURNED IN FPT (3) AREAS DPDO STORM SEWER OR BURNED IN FPT AREAS SLUDGE LAGOON OR ON-BASE LANDFILL DPDO BURNED IN FPT AREAS DPDO BURNED IN FPT AREAS DPDO BURNED IN FPT AREAS DPDO
PAINT SHOP	77 89 (Bldg. 89 - 1964 to Present)	PAINT RESIDUE, THINNERS & SOLVENTS	800 GALS. /MO.	
NOSE DOCKS	44, 47, 48 & 49	PD-680 HYDRAULIC FLUID }	100 GALS. /MO.	
ENGINE REPAIR SHOP	125	PD-680 WASTE OILS }	50 GALS. /MO.	
LANDING GEAR SHOP	125	PD-680	50 GALS. /2 MOS.	

KEY

?/ ACTIVITY ASSUMED TO OCCUR IN A SHOP LOCATED ELSEWHERE

— CONFIRMED TIME-FRAME DATA BY SHOP PERSONNEL

--- ESTIMATED TIME-FRAME DATA BY SHOP PERSONNEL

(1) BASED ON CURRENT RATES AND BEST ESTIMATES OF PAST RATES

(2) IWTP = INDUSTRIAL WASTE TREATMENT PLANT

(3) FPT = FIRE PROTECTION TRAINING

(4) DPDO = DEFENSE PROPERTY DISPOSAL OFFICE

TABLE 4.1 (continued)
INDUSTRIAL OPERATIONS (Shops)

HAZARDOUS WASTE MANAGEMENT

2 of 6

SHOP NAME	LOCATION (BLDG. NO.)	WASTE MATERIAL	WASTE QUANTITY	METHOD(S) OF TREATMENT, STORAGE & DISPOSAL			
				1950	1960	1970	1980
AIRBORNE ELECTRONICS DIVISION COMPOSITE - ALL SHOPS	640 & 685	ACETONE PD-680 METHYLENE CHLORIDE METHYL ETHYL KETONE PAINT THINNERS POLYSULFIDE SEALANT TRICHLOROETHYLENE (to '79) TRICHLOROETHANE (from '79) PAINT WASTE	600 to 800 GALS./MO. (1950s to 1972) 100 GALS./WK. (1972 to Present) 100 GALS./WK.	BURNED IN FPT AREAS → SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO			
				STORM SEWER OR BURNED IN FPT AREAS → SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO			
				STORM SEWER OR BURNED IN FPT AREAS → SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO			
				BURNED IN FPT AREAS → DPDO			
				BURNED IN FPT AREAS → DPDO			
				BURNED IN FPT AREAS → SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO			
				BURNED IN FPT AREAS → DPDO			
				BURNED IN FPT AREAS → DPDO			
				BURNED IN FPT AREAS → SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO			
				BURNED IN FPT AREAS → DPDO			
INDUSTRIAL PRODUCTS DIVISION PAINT SHOP	125	PAINT RESIDUE, THINNERS & SOLVENTS	50 to 100 GALS./2 WKS.	STORM SEWER OR BURNED IN FPT AREAS → SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO			
				BURNED IN FPT AREAS → DPDO			
				BURNED IN FPT AREAS → DPDO			
				BURNED IN FPT AREAS → SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO			
TURRET SHOP	7/180 (Bldg. 140 - 1971 to Present)	TRICHLOROETHYLENE	50 GALS./WK.	BURNED IN FPT AREAS → DPDO			
				BURNED IN FPT AREAS → DPDO			
PROPELLER & PROP CLEANING	7/180 (Bldg. 140 - 1971 to Present)	WASTE OILS METHYL ETHYL KETONE HYDRAULIC FLUID TRICHLOROETHYLENE	100 GALS./MO. 50 GALS./MO. 50 GALS./MO.	BURNED IN FPT AREAS → DPDO			
				BURNED IN FPT AREAS → DPDO			
				BURNED IN FPT AREAS → DPDO			
				BURNED IN FPT AREAS → DPDO			
ELECTROPLATING SHOP	182 (1969 to Present) 128 (1993 to 1993) 125 (1996 to 1993)	CARBON REMOVER, PHENOLIC CHROME BATHS WASTE ACID CLEANERS SLUDGE CYANIDE BATHS	200 to 400 GALS./YR. 200 LBS./YR. 500 GALS./YR.	BURNED IN FPT AREAS → SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO			
				CHEMICAL REDUCTION TO STORM SEWER → IWTW			
				STORM SEWER → IWTW			
				SANITARY SEWER → IWTW			

TABLE 4.1 (continued)
INDUSTRIAL OPERATIONS (Shops)

HAZARDOUS WASTE MANAGEMENT

SHOP NAME	LOCATION (BLDG. NO.)	WASTE MATERIAL	WASTE QUANTITY	METHOD(S) OF TREATMENT, STORAGE & DISPOSAL					
				1950	1960	1970	1980		
INDUSTRIAL PRODUCTS DIVISION (continued) ELECTROPLATING SHOP (continued)	127 (1989 to Present) 139 (1993 to 1997) 125 (1990s to 1995)	WASTE ALKALINE CLEANERS	400 GALS. /3 MOS.	STORM SEWER				IWTP	
		TRICHLOROETHYLENE	150 GALS. /WK.	BURNED IN PPT AREAS				DPDO	
		TRICHLOROETHANE	150 GALS. /WK.	BURNED IN PPT AREAS				DPDO	
		PERCHLOROETHYLENE	150 GALS. /WK.	BURNED IN PPT AREAS				DPDO	
	HYDROSTATIC TESTING	150	PAINT WASTES & RESIDUE	30 GALS. /MO.	STORM SEWER OR BURNED IN PPT AREAS			SLUDGE LAGOON OR ON-BASE LANDFILLS	DPDO
		150	WASTE ACIDS	25 GALS. /MO.	STORM SEWER			IWTP	
	PARTS CLEANING & METAL BOND	169	PAINT STRIPPER, PHENOLIC	110 GALS. /DAY	SANITARY SEWER			IWTP	
		670 & 680	TRICHLOROETHANE	55 GALS. /WK.	BURNED IN PPT AREAS			DPDO	
	PLASTICS SHOP & RADOME SHOP	670 & 680	METHYL ETHYL KETONE } TOLUENE }	150 GALS. /MO.	BURNED IN PPT AREAS			SLUDGE LAGOON OR ON-BASE LANDFILLS	DPDO
			PAINT RESIDUE	50 GALS. /3 WKS.	STORM SEWER OR BURNED IN PPT AREAS			SLUDGE LAGOON OR ON-BASE LANDFILLS	DPDO
5 COMBAT COMMUNICATIONS GROUP (CCG)	614	WASTE GENERATOR OIL	110 GALS. /MO.					1967 DPDO	
	655	SKIMMED OIL SLUDGE	100 GALS. /4 MOS.					SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO 1974	
19 BOMBARDMENT WING (BW)	52	SKIMMED OIL/FUEL SLUDGE	200 GALS. /4 MOS.					SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO 1965	

TABLE 4.1 (continued)
INDUSTRIAL OPERATIONS (Shops)

HAZARDOUS WASTE MANAGEMENT

SHOP NAME	LOCATION (BLDG. NO.)	WASTE MATERIAL	WASTE QUANTITY	METHOD(S) OF TREATMENT, STORAGE & DISPOSAL			
				1950	1960	1970	1980
19 BOMBARDMENT WING (BW) (continued)							
<u>FIELD MAINTENANCE SQUADRON (FMS) (continued)</u>							
PNEUDRAULICS SHOP	79	PD-680 HYDRAULIC FLUID	160 GALS. /6 MOS.			1965 DPDO DISPOSED OF AT BLDG. 79	
ELECTRIC SYSTEMS SHOP	79	WASTE BATTERY ACID	1 QT. /MO.			1965 IWTB VIA BLDG. 154	
CORROSION CONTROL	80	PAINT RESIDUE THINNERS PAINT STRIPPERS ACID CLEANERS METAL BRIGHTENERS	10 GALS. /6 MOS.			1965 SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO	
AEROSPACE GROUND EQUIPMENT (AGE) REPAIR SHOP & AGE SERVICEING SHOP	82 & 85	JP-4 MOCAS HYDRAULIC FLUID PAINT THINNER PAINT STRIPPER LUBRICATION OIL	55 GALS. /MO. 100 GALS. /MO. 100 GALS. /MO.			1965 DPDO 1965 DPDO 1965 SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO	
PROPULSION BRANCH	76	JP-4 ENGINE OIL	200 GALS. /MO. 100 GALS. /MO. 10 GALS. /MO.			1965 DPDO 1965 DPDO 1965 SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO	
<u>MUNITION MAINTENANCE SQUADRON</u> EQUIPMENT MAINTENANCE BRANCH	86	HYDRAULIC FLUID PD-680	Also included in AGE Shop waste total 36 GALS. /MO.			1965 DPDO 1965 DPDO 1965 SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO	

TABLE 4.1 (continued)
INDUSTRIAL OPERATIONS (Shops)

HAZARDOUS WASTE MANAGEMENT

SHOP NAME	LOCATION (BLDG. NO.)	WASTE MATERIAL	WASTE QUANTITY	METHOD(S) OF TREATMENT, STORAGE & DISPOSAL
19 BOMBARDMENT WING (BW) (continued)				
<u>ORGANIZATION MAINT. SQUADRON</u>				
BOMBER-PHASE MAINTENANCE	67	ENGINE OIL	100 GALS./MO.	1965 DPDO
TANKER-PHASE MAINTENANCE	81	HYDRAULIC FLUID	100 GALS./MO.	1965 DPDO
1926 COMMUNICATIONS & INSTALLATION GROUP				
MINOR VEHICLE MAINTENANCE	978	SKIMMED OIL SLUDGE	20 to 30 GALS./YR.	1965 DPDO
WEATHER EQUIPMENT REPAIR	1684	WASTE OILS, FLUIDS	5 GALS./YR.	1965 DPDO
2853 AIR BASE GROUP (ABG)				
<u>VEHICLE TRANSPORTATION DIVISION</u>				
FUEL VEHICLE REPAIR	190	MOTOR OIL	800 GALS./MO.	DPDO
VEHICLE MAINTENANCE SHOP	302	AUTOMATIC TRANS. FLUID		DPDO
AUTO MAINTENANCE SHOP	307	HYDRAULIC FLUID		DPDO
PAIN & BODY SHOP	304	THINNERS & PAINT REMOVER PAINT BOOTH SLUDGE PAINT RESIDUE	55 GALS./YR. 55 GALS./3 YRS. 55 GALS./2 YRS.	SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO SLUDGE LAGOON OR ON-BASE LANDFILLS DPDO
2853 CIVIL ENGINEERING SQUADRON (CES)				
INDUSTRIAL WASTE TREATMENT PLTS.	141, 147 & 314	IWTP SLUDGES	900 CU. YDS./YR.	SANITARY SEWER, STORM SEWER OR ON-BASE LANDFILLS
TRANSFORMER STORAGE	1190	PCB TRANSFORMERS	1 to 2 EA./2 to 5 YRS.	ELECTRIC REHABILITATION CONTRACTORS (CES) SLUDGE LAGOON SLUDGE DEWATERING FACILITY

TABLE 4.1 (continued)
INDUSTRIAL OPERATIONS (Shops)

HAZARDOUS WASTE MANAGEMENT

SHOP NAME	LOCATION (BLDG. NO.)	WASTE MATERIAL	WASTE QUANTITY	METHOD(S) OF TREATMENT, STORAGE & DISPOSAL				
				1950	1960	1970	1980	1980
2853 CIVIL ENGINEERING SQUADRON (CES) PAINT SHOP	275	PAINT RESIDUE THINNERS	100 GALS. /3 MOS. 50 GALS. /3 MOS.	STORM SEWER OR BURNED IN FPT AREAS	STORM SEWER OR BURNED IN FPT AREAS	SLUDGE LAGOON OR ON-BASE LANDFILLS	DPDO	DPDO
	295 & 296	RINSED CONTAINERS	10 to 20 EA. /YR.	ON-BASE LANDFILLS	ON-BASE LANDFILLS	ON-BASE LANDFILLS	COUNTY LANDFILL	COUNTY LANDFILL
ENTOMOLOGY UNIT		OFF-SPEC GRANULAR MALATHION	40 TONS (One-Time Occurrence)	ON-BASE LANDFILL	ON-BASE LANDFILL	HAZARDOUS WASTE BURIAL SITE	1976	
		AEROSOL CANS OF DDT	240 CANS (One-Time Occurrence)					
GROUNDS SHOP	591 & 593	RINSED CONTAINERS	10 to 12 EA. /YR.	ON-BASE LANDFILLS	ON-BASE LANDFILLS		1967	

6 of 6

From the early 1940's to approximately 1965, many ignitable waste chemicals and petroleum compounds were burned in fire protection training pits during training exercises. Waste solvents were burned in the fire protection training pits through approximately 1955, then the base began disposal of the material through resale or reuse. Rinse water from the plating and painting operations were previously discharged to the storm sewer. Cyanide solutions from the plating facility were discharged to the sanitary sewer system.

Burning of ignitable and other chemical waste in the fire protection training pits was decreased about 1965 due to air quality considerations. An industrial waste treatment system became operational in 1964 and expanded in 1969. Treatment began of waste streams from facilities such as the Electroplating Shop and the Corrosion Control Shop which had previously discharged to the storm sewer or sanitary sewer. A sludge lagoon was also constructed in the mid-1960's to dispose of industrial waste treatment plant sludge. Many types of waste chemicals and chemical sludges were also disposed of in the sludge lagoon. Paint residue, thinners and paint skimmings were typically disposed of in the on-base landfills. Petroleum products were sold by DPDO beginning in approximately 1965.


In 1978, the on-base disposal of all hazardous solid wastes and most non-hazardous solid waste was discontinued. Solid wastes were disposed of off-base by contract disposal. New industrial waste treatment plant sludge disposal facilities were also completed and started up about this time.

Fire Protection Training

The Fire Department has operated four fire protection training areas since 1943. These areas were used for practice exercises where petroleum based fires are set and then extinguished. The following list gives specific designation for the areas and their approximate period of use (See Figure 4.1).

<u>Fire Protection Training Area</u>	<u>Period of Operation</u>
No. 1	1943-mid 1950's
No. 2	Mid 1950's-mid 1960's
No. 3	Mid 1960's-1969
No. 4	1969-present

ROBINS AFB FIRE PROTECTION TRAINING AREAS



Fire Protection Training Area No. 4 (1969-present)

Fire Protection Training Area No. 3 (mid 1960s-1969)

Fire Protection Training Area No. 2 (mid 1950s-mid 1960s)

NOTE: FIRE PROTECTION TRAINING AREA No. 1 IS SITUATED IN THE AREA BETWEEN SECOND STREET AND THE SOUTHERN END OF THE MAIN RUNWAY

SOURCE: ROBINS AFB INSTALLATION DOCUMENTS

In the past, the common mode of operation was for the Fire Department to dump drums of contaminated fuel, oil, solvents, and ignitable chemicals on previously water saturated ground. The area was repeatedly ignited and extinguished during each exercise until it would no longer burn. This was the standard procedure until air pollution control regulations became more stringent in the mid 60's. These regulations curtailed the number of exercises and required the use of only uncontaminated JP-4 (less than 10 percent contaminants).

High pressure water was used to extinguish fires at Robins AFB until the introduction of protein foam in 1950. The protein foam was replaced in 1972 by the AFFF as an extinguishing agent for fire fighting training exercises.

Fire Protection Training Area No. 1

Fire protection training area No. 1 was located in the general vicinity of landfills No. 1 & No. 2, near the POL bulk storage area, however, the exact location of fire protection training area No. 1 could not be determined. This area was an unlined pit surrounded with earthen dikes and was used twice a week from 1943 until the mid 1950's.

Fire Protection Training Area No. 2

Fire protection training area No. 2 was actually a number of sites in the general area of Lake Luna as shown in Figure 4.2. These sites were used from the mid 1950's until the early to mid 1960's. During this period the Fire Department did not use a pit but conducted training exercises on open sites. Operating procedures included saturating the ground with water and then burning various flammable materials or chemical wastes.

Fire Protection Training Area No. 3

Fire protection training area No. 3, was another diked, unlined pit. This area was located close to the present site (No. 4), as shown in Figure 4.3. The site was operated from the early 1960's until the construction of the present training area in 1969. As previously mentioned, air pollution regulations curtailing the number of exercises and requiring the use of only uncontaminated fuel became effective during this period.

FIGURE 4.2





FIGURE 4.3



Fire Protection Training Area No. 4

The current site, fire protection training area No. 4, is a concrete lined, diked pit located in the SAC area as shown in Figure 4.3. Permanent fuel tanks with gravity feed were also installed during construction. Training exercises are limited to twice per quarter using uncontaminated JP-4.

Pesticide Utilization

Pest control has been an on-going program since the inception of Robins AFB. The Entomology Shop initially administered the pest control program while the grounds and pavements shop was responsible for weed control. In 1967, the two programs were combined and the Entomology Shop became responsible for both programs. The Entomology Shop has always been located in building 295 and the chemical storage areas have been situated in the facilities neighboring the shop. Grounds and pavements has been located in the same compound as Entomology occupying facilities 294 and 286.

The pesticide program entails routine and specific job order spraying. Both truck-mounted and hand-held sprayers are utilized. A listing of the pest and weed control chemicals presently on hand is included in Appendix C. Standard procedures include mixing and using all pesticides immediately or storing any residual mixtures for use within 15 to 30 days. In 1966, a wash rack was constructed in an area adjacent to the Entomology Shop to rinse empty containers and spray equipment. Water collected in the wash rack is stored in an underground tank. The water is routinely pumped and used as make-up water for chemical mixing. Prior to the wash rack installation, Entomology Shop personnel interviewed stated that excess herbicides were usually sprayed on the adjacent lot. Empty pesticide containers are presently triple rinsed, punctured or crushed and disposed along with the base refuse.

It was indicated by several base personnel that a one time quantity of pesticide, approximately 40 tons, had been disposed in Landfill No. 2. It is suspected that the material was a mixture of clay or aggregate with 1.5 to 10 percent granular malathion used for aerial spraying to control mosquitoes and gnats. Further investigation revealed that the disposal operation would likely have occurred prior to 1964.

In October 1979, 55 gallons of DDT solution leaked from a drum stored in a gravel section of the chemical storage area adjacent to building 295, (Figure 4.4). The Bioenvironmental Engineering Services Division collected soil samples from the site and the drainage paths from the storage area to determine the extent and degree of migration of the DDT (SGB, 1980). Soil under the gravel was found to be primarily a sandy loam. The chemical analyses were conducted by USAF OEHL, Brooks AFB, TX and are summarized below:

<u>Location</u>	<u>Concentration DDT in ppm</u>
Surface of soil under pallet	2144
Crystalline material from pallet	55
Soil sample 6"-10" under surface	7600
Soil sample 18" under surface	6760
10' west of pallet	1124
Surface - east runoff ditch	135
Drainage ditch at entrance to storm sewer	3


The area at the leak site has since been covered with an asphalt pad incorporating a four inch high curb along the perimeter. This area continues to serve as the drummed chemical storage area for the entomology shop.

Fuel Management

The Robins AFB Fuels Management storage system consists of numerous under-ground and above-ground storage tanks in various locations throughout the base. A description of major fuel, oil and chemical bulk storage capacities is summarized in Table 4.2. These include JP-4, DF-2 (distillate fuel), MOGAS, AVGAS, solvents, oil and other chemicals. Bulk storage of fuels is located in the fenced POL tank area. The JP-4 tanks in the bulk storage area are supplied by a four inch diameter steel pipe running from the Standard Transmission Corporation tank farm located north of the base on Georgia Highway 247. An eight inch diameter steel line supplies JP-4 to the SAC area from the POL storage area. The POL storage area was paved with concrete some time between 1978 and 1979. Prior to this time the containment dikes were tarred and the rest of the ground surface was covered with gravel.

Fuel storage tanks have been cleaned every three years and 1 to 50 gallons of sludge per tank was removed during cleaning. Until 1975, the

FIGURE 4.4



SOURCE: ROBINS AFB INSTALLATION DOCUMENTS

TABLE 4.2

SUMMARY OF MAJOR FUEL, OIL AND CHEMICAL STORAGE CAPACITIES

Robins Air Force Base

Item	No. of Tanks	Maximum Tank Volume (gals.)	Minimum Tank Volume (gals.)	Total Storage Volume (gals.)
JP-4	20	788,739	48,770	2,909,369
MOGAS	4	17,387	9,988	58,771
Fuel Oil	4	1,063,223	2,018	1,115,189
AVGAS	1	24,403	24,493	24,493
JPTS	1	24,963	24,963	24,963
Aluminum Sulfate	1	5,250	5,250	5,250
Sodium Hydroxide	1	16,000	16,000	16,000
Sulfuric Acid	1	16,000	16,000	16,000
Oil, Phillips 220	1	30,000	30,000	30,000
Solvents	1	1,400	1,400	1,400
Calibration Fluid	1	5,000	5,000	5,000

Note: Information obtained from Robins AFB Oil and Hazardous Substances - Pollution Contingency Plan, 30 September 1981.

sludge was dumped next to the cleaned tank, the area was roped off and the sludge allowed to weather. Sludges removed from the tanks are now disposed of off-base by contractor service through DPDO.

Spent fuel filters were placed in buckets to allow the fuel to evaporate. After the fuel filter has sufficiently weathered it was discarded into a dumpster to be disposed of with the general refuse.

Interviews with base personnel indicated there have been three major fuel spills on the base. A leak of an undetermined amount of JP-4 occurred from the four inch diameter supply line about the mid 1960's. The leak was located north of the POL bulk storage area by landfill No. 1. After the pipeline was repaired the pipe trench was closed and no attempt was made to recover the JP-4 that was spilled. JP-4 has been found in pipe trenches and other excavations in this general area on a regular basis since the leak occurred.

A second major spill of JP-4 occurred in the early 1970's. An estimated 60,000 gallon of fuel overflowed a tank in the POL storage area. The containment dike valve was left open and the fuel flowed into the drainage ditches leading to Horse Creek. Only a small portion of the spilled JP-4 was recovered. Contaminated soil in the affected area of the sump was excavated and removed.

A third JP-4 spill occurred in May of 1978 when approximately 1,000 gallons of fuel overflowed a tank in the storage area. This spill was contained and recovered.

Numerous small leaks were mentioned in the interviews along the four inch diameter JP-4 supply line and the eight inch diameter SAC JP-4 supply line. These pipelines were originally installed without cathodic protection and were susceptible to corrosion. Most of the pipe has been replaced and protection has been installed during the replacement effort.

DESCRIPTION OF PAST ON-BASE DISPOSAL METHODS

Prior to 1977, many waste materials generated at Robins AFB were disposed of or treated on the base by landfilling, burning in the fire protection training pits, or discharged to the sludge lagoon or industrial wastewater treatment plant. The collection and on-base transportation of liquid waste solvents from a portion of the various base

organizations has been a contract service from 1974 to 1982. The contractor has been responsible for emptying and cleaning various degreasing vats, solution tanks and paint booths and containerizing the waste material. He was also responsible for transporting the waste from the on-base industrial facility to the on-base waste holding area. The waste holding area was located in the vicinity of industrial waste treatment plant No. 1 and Landfill No. 4 from approximately 1965 through 1979. From 1965 to 1974, base employees performed these services.

Since 1980, the Defense Property Disposal Office (DPDO) has been responsible for disposal of hazardous wastes. DPDO has awarded one year contracts that require the contractor to load and transport the materials for off-base reprocessing or disposal.

The on-site facilities which have been used for management and disposal of waste can be categorized as follows:

- o Landfills
- o Waste Dumps
- o Sludge Lagoon
- o Hazardous Waste Burial Sites
- o Low Level Radioactive Waste Sites
- o Industrial Wastewater Treatment Plant
- o Sanitary Wastewater Treatment Plant
- o Storm Sewers (Oil/Water Separators)
- o Refuse Incineration

The types of waste management facilities are discussed individually in the following subsections.


Landfills

On-base landfills have been used for disposal of non-hazardous and hazardous solid wastes at Robins Air Force Base. Landfills were operated at four locations on the base as shown in Figure 4.5. Table 4.3 contains a summary of pertinent information concerning each landfill disposal site. Since 1978, solid wastes have been hauled off-base and no landfills were operated on the base.

Landfill No. 1

Landfill No. 1 is located, as shown in Figure 4.6, near the south end of the runway, between the fuels management (POL) tank farm and Second Street. The site was operated from 1946 to 1951, encompassing an

FIGURE 4.5



ROBINS AFB LANDFILL LOCATIONS

SOURCE: ROBINS AFB INSTALLATION DOCUMENTS


TABLE 4.3

SUMMARY OF LANDFILL DISPOSAL SITES


Landfill	Operation Period	Approximate Size (Acres)	Types of Wastes	Estimated Waste Quantity (cu.yd.)	Method of Operation	Closure Status	Surface Drainage	Comments
Number 1	1946-1951	2	<ul style="list-style-type: none"> •General Refuse •Probably some industrial wastes •Boiler bottom ash (daily cover) •Ash from refuse incinerator 	65,500	Trench and daily bottom ash cover Filled in water table	Closed: cover of sandy-loam and local grasses. Impact sited located in area.	To Horse Creek and swamp	<ul style="list-style-type: none"> •Surface erosion on slope -landfilled material exposed •Leachate entering ditch -bright green color
Number 2	1951-1963	22	<ul style="list-style-type: none"> •General Refuse •Probably some industrial wastes •Boiler bottom ash cover •Approx. 40 tons of granular malathion and aggregate 	580,000	Trench and daily bottom ash cover Filled in water table. A wood burning face located on west	Closed: cover of sandy loam and local grasses, runway buffer area. Ponding on the surface.	To Horse Creek and swamp	<ul style="list-style-type: none"> •Water on surface of trench areas •Drainage stream traverses the site
Number 3	1964	2	<ul style="list-style-type: none"> •General Refuse 	65,500	Surface dump in water table	Closed: cover of sandy loam. Used for a baseball field.	To Horse Creek and swamp	<ul style="list-style-type: none"> •Permeable soil •Close Proximity to Lake Luna
Number 4	1965-1978	45	<ul style="list-style-type: none"> •General Refuse •Probably some industrial wastes 	484,000	Surface dump and daily cover with west end-trench and daily cover. Filled in water table of swamp	Closed: cover of sandy loam.	To Horse Creek and surrounding swamp	<ul style="list-style-type: none"> •Reported G.W. contamination (from monitoring wells installed 1980) •Permeable soil cover •Erosion on edges of fill •Waste chemical drums once stored on top of fill

FIGURE 4.6

ROBINS AFB LANDFILLS NO. 1 & NO. 2



SOURCE: ROBINS AFB
INSTALLATION DOCUMENTS



area of approximately two acres. The landfill was a trench and fill operation with daily cover of bottom ash from the boiler. The area had been previously filled with a sandy loam. Trench depths of 20 feet penetrated the fill material and sometimes extended below the water table requiring pumping when equipment had to operate near the trench bottom. General refuse from the base and housing areas was the primary material landfilled. Disposal of chemicals in the landfill was not standard procedure, however, some industrial wastes may have been placed in this landfill. An impact test facility sled was constructed on the site after landfill was closed. During construction of the sled, JP-4 seeped into the excavation that had been dug in the landfill. The source of the fuel may have resulted from a previous leak in the 4-inch diameter fuel supply line. Apparently, portions of the landfill contained JP-4 from the leaking supply line. The landfill is closed and the area is covered with soil and has established grass. During visual inspection of the site a green colored leachate was noted flowing from an eroded section on the northwest slope of the landfill. The site is 800 feet from a drinking water well and 4500 feet from the base boundary.

Landfill No. 2

Landfill No. 2 is located, as shown in Figure 4.6, east of the first site, across Second Street. This fill encompasses approximately 22 acres and was in operation from 1951 to 1963. Operation of landfill No. 2 was similar to No. 1, and included trenching into a previously filled area with daily cover of boiler bottom ash. The trench depths of 20 feet also penetrated the water table. Landfill No. 2 had a burning face on the west side of the site for disposing of scrap lumber from the base. Disposal material in landfill No. 2 included general refuse and moderate quantities of industrial wastes. Information obtained from interviews with base personnel revealed that in the early 1960's, forty tons of off-specification pesticide was buried at this site (1/2 ton or aggregate and 1.5 tons 0 percent granular malathion). The site is closed and is covered with soil and vegetation has been established. An inspection of landfill No. 2 revealed some ponding of rain water on the top of the site. A drainage stream is located in the southwest corner

of the site. Landfilling occurred on both sides of the drainage stream. This site is approximately 2200 feet from a drinking water well.

Landfill No. 3

Landfill No. 3 is located, as shown in Figure 4.7, in the southeastern part of the Robins AFB property near Lake Luna. The site was operated in 1964, primarily to fill a swampy area. Total area of the fill is approximately 2 acres. General refuse was deposited followed by a daily cover of sandy loam. Fire protection training exercises were conducted around the landfill site. The landfill is closed and the area has an established vegetation cover and a baseball field is built over it.


Landfill No. 4

Landfill No. 4 is located, as shown in Figure 4.8, near landfill No. 2, southeast of the industrial waste treatment plant addition. The fill was operated from 1965 to 1978, encompassing approximately 45 acres. Landfill No. 4 was the last on-base disposal site for solid waste. General refuse was deposited into the swamp and covered daily with a sandy soil. Little or no boiler bottom ash was used as cover due to the conversion of the boiler system to natural gas in 1966. There was occasional dumping of industrial wastes in this landfill throughout its life. The site is now covered with a sandy soil loam and partially established vegetation. This site is approximately 2200 feet from a drinking water well and is located adjacent to drainage ditches which flow to Horse Creek. From 1976 to 1979, approximately 1500 drums of waste material were stored at the west end of the landfill. A groundwater monitoring study was conducted around Landfill No. 4 and the sludge lagoon (LETCO, 1980). The results of this monitoring program indicate the presence of contaminants in the shallow aquifer has occurred downgradient of the site.

Waste Dumps

Four sites on-base were used for general refuse and landscape trash. The general locations of the waste dumps are indicated on Figure 4.9. Waste dump No. 1 and 2 were operated from early 1942 through 1946. The exact method of operation of the waste dumps was not determined. It is speculated that refuse was surface dumped at these sites and burned when it began to accumulate. No daily cover was probably applied,

FIGURE 4.7



**ROBINS AFB
LANDFILL No. 3**

LUNA LAKE


**LANDFILL
No. 3
(1964)**

Rd.

Perimeter Rd.


SCOUT LAKE

Perimeter



SOURCE: ROBINS AFB INSTALLATION DOCUMENTS

FIGURE 4.8



ROBINS AFB LANDFILL NO. 4 & SLUDGE LAGOON

Treatment
Plant Outfall

SLUDGE
LAGOON
(1963-1978)

LANDFILL NO. 4
(1965-1978)

SWAMP

Hannah Road

To Horse Creek

LEGEND

- ▶ PERENNIAL STREAM
- - -▶ INTERMITTENT STREAM

SOURCE: LETCO (1980)

SCALE
0 600 1200
FEET





FIGURE 4.9

ROBINS AFB WASTE DUMP LOCATIONS



SOURCE: ROBINS AFB INSTALLATION DOCUMENTS

however, both waste dump No. 1 and No. 2 have been given a final cover.

Waste dump No. 3 and No. 4 are currently active sites where primarily landscape refuse has been disposed. Portions of these areas are covered with soil. Small quantities of paint cans, construction material wastes, automotive filters and oil cans, tires, and empty fire extinguisher agent containers were observed during a visual inspection. No hazardous wastes were found at these sites.

Sludge Lagoon

A sludge lagoon was used for disposal of industrial wastewater treatment plant sludges from approximately 1962 until its closure in 1978. The lagoon encompassed approximately 1.5 acres located on the north end of Landfill No. 4 (Figure 4.8). The lagoon was an unlined, diked pit with the bottom excavated below the water table level.


Sludges (2-5 percent solids) from both industrial waste treatment plants were dumped into the lagoon. Sludge from industrial waste treatment plant No. 1 contained some phenols and oils. Industrial waste treatment plant No. 2 treated waste water from metal plating operations and the sludges contained cyanide, chrome, and other heavy metals. Other industrial wastes such as paint removers, solvents, hydraulic fluids, and oils were occasionally disposed of in the sludge lagoon.

The sludge lagoon was closed in 1978 when the sludge dewatering and disposal building was started up. The lagoon is now covered with sandy loam soil which also covers Landfill No. 4. The lagoon is approximately 2200 feet from a drinking water well and 5200 feet from the nearest base boundary. The ground-water monitoring program recently conducted indicated the presence of contaminants in the shallow aquifer downgradient of the sludge lagoon.

Hazardous Waste Burial Sites

In January 1976, approximately 240 aerosol cans of DDT with pyrethrin were disposed by burial on the south portion of the base (Figure 4.10). Several sections of 30 inch diameter reinforced concrete pipe 48 inch in length were used as containers. These sections were placed vertically in a trench then capped at the bottom end with concrete. The aerosol cans were placed in the pipe sections. Each pipe section was capped at the top end with concrete for a secure closure. The trench was filled and 24 inches of natural earth cover was placed over the pipe

FIGURE 4.10



SOURCE: ROBINS AFB
INSTALLATION DOCUMENTS

sections. Similar procedures were used at this same location for disposal of two containers of mercury contaminated material and one container of a small amount of PCB material in April 1976. Approximately 15 gallons of wastes contaminated with mercury were disposed at this location in April 1977. The waste material was placed in plastic bags, then placed in metal containers. The containers were placed in additional plastic bags, then were encapsulated with six inches of concrete prior to final burial. No indication of further waste disposal at this site was determined from the base records and personnel interviews.

Laboratory chemicals which had exceeded their recommended shelf life were buried in two unlined pits in the southeastern end of the base sometime between 1962 and 1964. This was a one time disposal of old bottles, canisters and jars of a variety of laboratory chemicals from the base storage. The disposal site is believed to be in the vicinity of Luna Lake by the dog kennel, however, an exact location could not be determined.


Low Level Radioactive Waste Sites

Low level radioactive wastes have been generated on-base from instrument repair work and washdown of radioactive aircraft. The disposal sites for these wastes occurred in the locations shown in Figure 4.11 and are described below.


The radioactive waste (solid) disposal site, facility number 8315, is located, as shown in Figure 4.12, on the southeast corner of the base along Perimeter Road south of the firing range. It is comprised of a concrete vault buried approximately six feet below the ground surface. A locked chain-linked fence with two barbed wire strands surrounds the disposal area. Two signs are posted on the fence designating the area as a "Radiation Hazard Area". The site was used in the early 1950's for disposal of low-level solid radioactive wastes such as old radium dials, contaminated radioactive brushes, election tubes and spark gaps. Soil samples collected within and adjacent to the burial area have been analyzed annually. The 1980 soil analyses are presented in Table C.13 (Appendix C). The area was last surveyed with a beta/gamma radioactivity detector in September of 1981. Radiation levels did not exceed 0.03 mr/hr above a background of 0.01 mr/hr; indicating radioactive

RADIOACTIVE WASTE BURIAL SITE & AIRCRAFT WASH AREAS

ROBINS AFB



SOURCE: ROBINS AFB INSTALLATION DOCUMENTS



SOURCE: ROBINS AFB
INSTALLATION DOCUMENTS

materials are present, but do not result in radioactivity levels hazardous to human health.

Two open radioactive aircraft wash areas were utilized at Robins AFB for decontamination caused by airborne fission products. Wash area No. 1 was located east of the SAC ordinance area. This area was used in 1956 to decontaminate one aircraft. The aircraft was positioned off of the taxiway onto a grass area for washdown. The area was restricted after washing until monitoring for levels of radioactivity indicated only background amounts.

Similar washdown operations occurred in area No. 2. Approximately four aircraft were decontaminated at this location during 1957. Similar area restrictions and monitoring were initiated until only background levels of radioactivity were detectable.

Two underground storage tanks (wash area No. 3) located adjacent to the east side of building 58, were designed to collect washdown from aircraft that also may have been contaminated by airborne fission products. The contents of these tanks were sampled in 1978 and found to contain water contaminated with zinc, iron, low level radiation and a surfactant. The east tank also contained a stratified upper layer mixture of a petroleum base solvent and a compound similar to methyl ethyl ketone. The solutions were probably generated around 1963 during a washdown operation. During interviews with the Bioenvironmental Engineering Services Division personnel, it was learned that these tanks were pumped out in 1978 and the water was discharged to the wastewater treatment plant at a predetermined, dilution ratio.

Industrial Waste Treatment Plants

The first industrial waste treatment at Robins AFB began in 1960 with batch treatment of cyanide wastes. The treated wastes were combined with treated sanitary sewer wastes and discharge to Horse Creek. Prior to this many aqueous industrial wastes may have been neutralized, diluted and discharged to the storm sewer system.

The first industrial waste treatment plant was built in 1964 primarily as an air flotation system for removal of oils and phenols. In 1971, the plant was upgraded to provide treatment for reduction of hexavalent chromium, neutralization, and coagulation/precipitation of heavy

metals. Industrial waste treatment plant No. 1 treats all the industrial waste from the base except the plating shops, and includes wastes from aircraft stripping operations and washdown. The wastewater contains oils, phenols, chrome, paint residues, solvents and alkaline based stripping materials. Sludge from the treatment plant was discharged into the sludge lagoon until its closure in 1978. Sludge has been dewatered and placed in the sludge disposal building since 1978. Effluent from industrial waste treatment plant No. 1 flows through a sanitary waste treatment facility for biological oxidation of residual phenols.


Industrial waste treatment plant No. 2 was built in 1969 to treat the base plating shops wastes. Influent is typical plating waste and includes high levels of chrome, cyanide and heavy metals. Sludge from the clarifier underflow of this facility was also disposed in the sludge lagoon until its closure in 1978. Since then the sludge has been dewatered and placed in the sludge disposal building.

The sludge dewatering and disposal facility was built in 1978 as part of the closure of the sludge lagoon. The disposal building is completely enclosed with a concrete floor. Decant from sludge dewatering (plate and frame pressure filter) is returned to industrial waste treatment plant No. 1. The sludge disposal building was designed for a total dry sludge storage volume of 9,323 cubic yards and an estimated life of 10 years at current sludge generation rates. The locations of the waste treatment facilities are shown in Figure 4.13.

Sanitary Wastewater Treatment Facilities

Domestic sewage has been treated on-base since 1942 by a single stage trickling filter system located in the area of industrial waste treatment plant No. 1. This sanitary treatment facility discharges treated effluent to a tributary of Horse Creek. The sludge generated from this treatment facility was applied to various land areas on-base. This system may have received wastewater streams containing phenolic and non-phenolic paint strippers from the mid 1940's to 1965. Also this system may have received batches of partially or completely treated cyanide baths from the electroplating operations on-base during the same period.

ROBINS AFB WASTEWATER TREATMENT FACILITIES



SOURCE: ROBINS AFB INSTALLATION DOCUMENTS

An additional sanitary wastewater treatment plant was operational from 1943 through approximately 1979. In 1973 this facility was upgraded from a primary to a secondary treatment facility. This facility is located off Hannah Road near Seventh Street. It is believed that this plant received little or no industrial waste streams. This facility is now used only as a pumping station. The locations of the waste treatment facilities are shown in Figure 4.13.

Storm Sewer Systems

The storm sewer systems on-base consist primarily of concrete conduits or open-channels which direct drainage towards tributaries of Horse Creek. The systems in the areas of aircraft maintenance functions received some discharges of wastes from maintenance activities from the mid 1940's through the early 1970's. In the mid 1970's, oil/water separators were installed in many of the systems. A list of these units is shown in Table 4.4.

Refuse Incineration

General refuse from the base was disposed of by incineration in the late 1940's. The incinerator was located west of landfill No. 4. Ash from the incinerator was buried in landfill No. 1. The operation was discontinued in the early 1950's and the refuse went directly to the landfill for disposal.

EVALUATION OF PAST DISPOSAL ACTIVITIES AND FACILITIES

The review of past operation and maintenance functions and past waste management practices at Robins AFB has resulted in the identification of 13 sites containing hazardous waste materials and having the potential for migration of contaminants. Other sites were reviewed and eliminated from further evaluation based on the logic presented in the decision tree shown in Figure 1.1.

The 13 sites have been assessed using a hazardous assessment rating methodology (HARM) which takes into account characteristics of potential receptors, waste characteristics, pathways for migration and specific characteristics of the site related to waste management practices. The details of the HARM procedures are presented in Appendix G and the results of the assessment are summarized in Table 4.5. The rating system is designed to indicate the relative need for follow-on action. The

TABLE 4.4

SUMMARY OF ON-BASE OIL/WATER SEPARATORS

Separator Number	Date Installed	Building Location	Description
0-01	1972	23	North Side
0-02	1978	30	Noise Suppressor N.E. Corner
0-03	1969	33	East of Pad
0-04	1970	47	West Side
0-05	1967	48	East Side
0-06	1967	49	East Entrance
0-07	1954	628	West Side ALC
0-08	1976	656	N.W. Side
0-09	1975	959	(Gray Eagle Unit)
0-10	1979	979	S.W. Side
0-11	1977	377	East Side (Fire Dept.)
0-12	1952	318	East Side (Land Fill)
0-13	1956	194	S.E. of Bldg. 153 on Parking Ramp
0-14	1964	302	East End of Washrack
0-15	1960	67	N.W. Side
0-16	1960	67	North Side
0-17	1975	85	North Side
0-18	1960	76	N.E. Corner
0-19	1960	82	North Side
0-20	1962	52	South Side
0-21	1962	52	North Side
0-22	1963	190	North Side
0-23	1963	190	N.E. Holding Tank
0-24	1963	196	North of Bldg. 192 (POL)
0-25	1963	196	Area near Bldg. 73 (POL)
0-26	1960	79	Adjacent to Washrack
0-27	1979	PB64	Outside Flight Line Area along 1st St.
0-28	1974	922	BX Service Station
0-29	1979	979	Washrack
0-30	1980	184	Aero Club/Aircraft Parking Lot
0-31	1967	985	Base Hobby Shop
0-32	1963	109	Fire Department
0-33	1951	93	Paint Storage (inactive)

SOURCE: Bioenvironmental Engineering Services Division Files, verified and updated by CES

TABLE 4.5
SUMMARY OF HARM SCORES FOR POTENTIAL CONTAMINATION SOURCES

Rank	Site Name	Receptor Subscore	Pathways Subscore	Waste Characteristics Subscore	Waste Management Factor	Overall Total Score
1	Sludge Lagoon	57	100	75	1.0	77
2	Landfill No. 4	59	100	60	1.0	73
3	DWT Spill (1979)	51	100	60	1.0	70
4	Fire Protection Training Area No. 2	46	55	90	1.0	64
5	Landfill No. 1	46	80	50	1.0	59
6	Landfill No. 2	42	80	53	1.0	58
7	JP-4 Spill (1965)	44	80	45	1.0	57
8	Hazardous Waste Burial Site	44	48	80	0.95	54
9	Fire Protection Training Area No. 1	44	62	50	1.0	52
10	Laboratory Chemical Burial Site	42	80	30	1.0	51
11	Landfill No. 3	46	56	40	1.0	47
12	Fire Protection Training Area No. 3	40	56	40	1.0	45
13	Radioactive Waste (Solid) Disposal Site	44	41	14	0.95	31

information presented in Table 4.5 is intended as a guide for assigning priorities for further evaluation of the Robins AFB disposal areas (Chapter 5, Conclusions and Chapter 6, Recommendations). The rating forms for the individual waste disposal sites on Robins AFB are presented in Appendix H. Photographs of some of the key disposal sites are contained in Appendix E.

CHAPTER 5
CONCLUSIONS

CHAPTER 5

CONCLUSIONS

The goal of Phase I of the IRP is to identify the potential for environmental contamination from past waste disposal practices at Robins AFB and to assess the probability of contaminant migration. The conclusions given below are based on the assessment of the information collected from the project team's field inspection, review of records and files, interviews with base personnel, past employees and state and local government employees and review of the environmental setting. Table 5.1 contains a summary of HARM scores for sites at Robins AFB.

- 1) The sludge lagoon has a high potential for migration of contaminants. This lagoon was used from approximately 1962 through 1978 to dispose of sludges from the industrial waste treatment plants. Sludges and industrial wastes from other industrial operations on-base were also disposed of in this lagoon. The results of a recently conducted ground-water monitoring program (LETGO, 1980), indicated contamination of the shallow aquifer down-gradient of the site. The lagoon is approximately 2,200 feet from a drinking water well and 5,200 feet from the base boundary. The lagoon was constructed in a former swamp area and the bottom extends below the water table. A stream flows adjacent to the lagoon site and standing water conditions commonly occur near the lagoon site. This site received a rating score of 77.
- 2) Landfill No. 4 has a high potential for migration of contaminants. This landfill was utilized from 1965 through 1978 for disposal of general refuse and significant quantities of industrial wastes. The results of a ground-water monitoring study (LETGO, 1980) indicate contamination of the shallow aquifer downgradient of the site. Landfill No. 4 is located approximately 2,000 feet from a drinking water well and 4,800 feet from the nearest base boundary. The bottom of the landfill is in the ground-water

TABLE 5.1

PRIORITY RANKING OF POTENTIAL CONTAMINATION SOURCES
ROBINS AFB

Rank	Site Name	Date of Operation or Occurrence	Overall Total Score
1	Sludge Lagoon	1963-1978	77
2	Landfill No. 4	1965-1978	73
3	DDT Spill (1979)	1979	70
4	Fire Protection Training Area No. 2	mid 1950's to mid 1960's	64
5	Landfill No. 1	1943-1951	59
6	Landfill No. 2	1951-1953	58
7	JP-4 Spill (1965)	1965	57
8	Hazardous Waste Burial Site	1976, 1977	54
9	Fire Protection Training Area No. 1	1943-mid 1950's	52
10	Laboratory Chemical Disposal Site	early 1960's	51
11	Landfill No. 3	1964	47
12	Fire Protection Training Area No. 3	mid 1960's to 1969	45
13	Low Level Radioactive Waste (Solid) Burial Site	1940's to 1950's	31

table. This site is presently closed and covered with sandy loam and has some vegetation established. Landfill No. 4 was given a HARM score of 73.

3) The DDT spill (1979) poses a high potential for contaminant migration. The spill involved a 55-gallon drum which leaked concentrated pesticide prior to discovery by base personnel. The immediate area around the spill received significant quantities of DDT as determined by soil samples taken by the Bioenvironmental Engineering Services Division office. The surface drainage pathway of the spilled material leading to Horse Creek was also sampled and contained lower levels of DDT. The remedial action taken consisted of covering the contaminated spill site with asphalt material. No removal of contaminated soil from the spill area or drainage pathway was reported. This site received a HARM score 70.

4) Fire Protection Training Area No. 2 poses a moderate potential for migration of contaminants. This area actually consists of several grade level open burning sites used from the mid 1950's through the mid 1960's. Significant amounts of chemical wastes, solvents, and paint wastes may have been routinely burned at this site in addition to the petroleum based materials used in each exercise. The estimated locations of the burn areas are within 1,200 feet to 600 feet of a drinking water well and are within 1,200 feet to 2,000 feet from the base boundary. The depth to ground water is estimated to be between 20 feet and 25 feet. This area received a HARM score of 64.

5) Landfill No. 1 poses a moderate potential for contaminant migration. Landfill No. 1 was operated from 1946 to 1957 and may have received small quantities of industrial wastes as well as general refuse. During a visual inspection of the site, a green colored leachate was noted flowing from an eroded section on the northwest slope of the landfill. The landfill may contain JP-4 as a result of a pipeline leak that occurred in the 1960's. This site is 800 feet from a drinking water well and 4,500 feet from the base boundary. Landfill No. 1 is now covered with soil and established vegetation. This landfill received a HARM score of 59.

- 6) Landfill No. 2 poses a moderate potential for migration of contaminants. Landfill No. 2 was used for disposal of general refuse and may have received moderate quantities of industrial wastes from 1951 to 1963. This site is approximately 2200 feet from a drinking water well and is located adjacent to drainage ditches which lead to Horse Creek. The distance from the bottom of the landfill to ground water is estimated to be 5 feet or less. This site is closed and covered with soil and vegetation is established. This landfill received a HARM score of 58.
- 7) The JP-4 leak (1965) poses a moderate potential for migration of contaminants. Several incidents of finding JP-4 seepage during excavations have been reported in the area of the old pipeline leak specifically around Landfill No. 1. It is believed that a moderate to large quantity of JP-4 may be floating on the ground water table down-gradient of the leak site. The quantity of fuel spilled and the quantity remaining on the ground-water table has not been determined. The JP-4 spill received a HARM score of 57.
- 8) The hazardous waste burial site poses a moderate potential for migration of contaminants. This site contains moderate amounts of hazardous wastes. Encapsulation of the wastes in concrete pipes was completed at the hazardous waste disposal site prior to burial of the material. The hazardous waste disposal site received a HARM score of 54.
- 9) Fire Protection Training Area No. 1 poses a moderate potential for contaminant migration. Hazardous materials have been burned in this area along with petroleum materials. The area was operated from 1943 through 1950. The precise location of Fire Protection Training Area No. 1 could not be determined, but it is believed to be located in or by Landfill No. 2. This site received a HARM score of 52.
- 10) The laboratory chemical disposal site is believed to pose a moderate potential for migration of contaminants. This site is located somewhere in the vicinity of Luna Lake and the dog kennel but the exact location could not be determined. Bottles, canisters and jars of outdated laboratory chemicals from the base storage

facility were buried at this site. The disposal site received a HARM score of 51.

11) Landfill No. 3 poses low potential for migration of contaminants. This site was operated in 1964 and is believed to have received primarily general refuse and little or no waste chemicals for disposal. The site is covered with vegetation and soil. Landfill No. 3 received a HARM score of 47.

12) Fire Protection Training Area No. 3 poses a low potential for contaminant migration. Fire training was conducted in this area from 1960 through 1969, only petroleum substances were known to be used in the training exercises. The site received a HARM score of 45.

13) The low level radioactive waste (solid) burial site poses a low potential for migration of contaminants. A concrete vault was used to dispose small quantities of low-level radiation materials in the late 1940's and early 1950's. The site is fenced securely and marked with warning signs. This site received the lowest HARM score, 31.

CHAPTER 6
RECOMMENDATIONS

CHAPTER 6
RECOMMENDATIONS

To aid in the comparison of the 13 sites on Robins AFB with those sites identified in the IRP at other Air Force Bases, a hazardous assessment rating methodology (HARM) was developed. Of primary concern at Robins AFB are those sites with a high potential for contaminant migration and with HARM scores greater than 65. These sites require further investigation in Phase II. Sites of secondary concern are those with moderate potential for contaminant migration and have HARM scores from 50 to 64. Further investigation at these sites is recommended. No further monitoring is recommended for those sites with low potential for migration of contaminants (scores from 0 to 49) unless data collected from other locations indicate a potential problem could exist at one of these sites.

The following recommendations are made to further assess the potential for contaminant migration from waste disposal areas at Robins AFB. The recommended monitoring program for Phase II is summarized in Table 6.1.

1) Landfill No. 4 is considered to have a high potential for migration of contaminants as demonstrated by the contamination of the shallow ground water down-gradient of the site. The recommended monitoring at this site is intended to define the extent of contamination and help determine remedial measures.

Geophysical survey techniques are recommended to help map the contaminant plume and further define site geology. The swamp area may restrict the performance of geophysical survey techniques.

A revised ground water monitoring program is recommended to determine plume configuration, depth of contamination, and concentration of contaminants. The monitoring program should consist of the following:

- o Evaluate the existing down-gradient monitoring wells along Hannah Road to determine their condition. The wells are

constructed of polyvinyl chloride (PVC) pipe and some of the organic contaminants such as methylene chloride will react with the PVC. Use these wells if no distortion or softening of the PVC is noted. If PVC deterioration is observed, then construct new monitoring wells with Teflon®, stainless steel, or other inert material.

- o Establish three wells in deeper zones above Hannah Road, to depths of 50, 75 and 100 feet, respectively. These wells can be used to evaluate vertical migration of contaminants. Monitor for the parameters in List A, Table 6.2. If contamination is found at 100 feet, then deeper wells should be constructed to define the depth of the plume. The material for well construction should be determined from the previous evaluation.
 - o Establish an up-gradient well nest west of Landfill No. 4 and other sources of contamination. The ground-water should be sampled at 25, 50, 75 and 100 feet. Monitor for the parameters in List A, Table 6.2. The existing up-gradient well is in an area down-gradient of another potential source of contamination (Landfill No. 2). Therefore this well is not representative of background conditions.
 - o Establish eight monitoring wells down-gradient at the landfill perimeter, capable of sampling to depths of 25, 50, 75 and 100 feet. These wells should be constructed of stainless steel or Teflon® since deterioration of the existing perimeter wells constructed of PVC has already been observed. Monitor for the parameters in List A, Table 6.2.
 - o Abandon and seal the existing up-gradient and perimeter monitoring wells in accordance with Section 391-3-2.13 of the Georgia Ground Water Use Act of 1974.
 - o Monitoring wells should be established to determine the furthest edge of the ground-water contaminant plume. This may be difficult to achieve in the swamp area. Samples should be analyzed for the parameters in List A, Table 6.2.
- 2) The sludge lagoon is also considered to have a high potential for migration of contaminants as demonstrated by the contamination of the shallow ground water down-gradient of the site. Landfill No. 4 and the

sludge lagoon are too close to each other to monitor separately, therefore, the program described for monitoring Landfill No. 4 will include the sludge lagoon.

3) The DDT spill (1979) site has a high potential for contaminant migration. Sampling has shown that the soil around the site is contaminated with DDT. The contaminated soil should be removed and replaced with fill material then the area paved to prevent infiltration. Sampling and analyses for DDT should be performed to verify clean up of the site.

4) The Fire Protection Training Area No. 2 is considered to have a moderate potential for migration of contaminants. The exact location of this site was not clearly defined by the records search project therefore part of the monitoring will be aimed at identifying the pit location. Collect soil borings in and around the suspected area of the old pits (100 ft. by 200 ft., 15 in the general pit area and 1 outside the area). The borings should be on a 50 foot grid, ten feet deep with soil samples taken at regular intervals and at any interface. Analyses should be performed on water extractions and then analyzed for the parameters in List B (Table 6.2).

5) Landfill No. 1 is considered to have a moderate potential for contaminant migration and monitoring is recommended. Geophysical survey techniques are recommended to identify any JP-4 in or around the site. If the geophysical survey is not affective, then install six monitoring wells (PVC) into the top of the water table down-gradient of the landfill and sample for floating oil. Samples of any leachate stream(s) should be collected and analyzed for the parameters in List A, Table 6.2.

6) Landfill No. 2 is considered to have a moderate potential for migration of contaminants and monitoring of this site is recommended. One upgradient and three downgradient monitoring wells (Schedule 40 PVC) should be constructed in the uppermost aquifer and the shallow ground water should be monitored for the parameters in List A, Table 6.2.

7) The area around the JP-4 leak (1965) is considered to have a moderate potential for migration of JP-4 and monitoring down-gradient of the site is recommended. Geophysical survey techniques may be effective

for defining JP-4 floating on top of the water table. If the geophysical survey is not effective then install six monitoring wells (PVC) into the top of the water table down-gradient of the leak and sample for floating material. This monitoring should be done jointly with monitoring for Landfill No. 1.

8) The hazardous waste burial site has a moderate potential for contaminant migration. One up-gradient and two down-gradient monitoring wells are recommended at this site. The wells should be constructed of Schedule 40 PVC and the ground water should be sampled and analyzed for the parameters in List B, Table 6.2.

9) The Fire Protection Training Area No. 1 has a moderate potential for contaminant migration. Since this site is believed to be located in or around Landfill No. 2, it will be included as part of the monitoring of Landfill No. 2.

10) The laboratory chemical disposal site is considered to have a moderate potential for contaminant migration. The exact location of this site could not be determined by the records search project. Since some of the materials were disposed of in metal containers, geophysical surveys techniques may be effective in identifying the location. The waste were reported buried on the south side of Luna Lake near the dog kennels. If the site is identified, collect soil borings as described for fire protection area No. 2.

11) Conduct a one-time water sampling program for water supply wells Nos. 3, 6, 8 and 12. Analyze each sample for the parameters shown in List A of Table 6.2.

12) Sample water and sediments of the drainage courses around landfill No. 4 to determine if leachate from the landfill and sludge lagoon are entering the drainage ditch. Set up eight sample stations and analyze for the parameters in List B, Table 6.2.

TABLE 6.1

RECOMMENDED MONITORING PROGRAM FOR PHASE II - ROBINS AIR FORCE BASE

Site	HARM Score	Recommended Monitoring	Comments
Landfill No. 4	73	<p>a. Utilize geophysical survey techniques to map contaminant plume, if site geology permits.</p> <p>b. Establish a revised ground-water monitoring program to determine configuration, depth of contamination, and concentrations of contaminants. Monitoring program should consist of:</p> <ul style="list-style-type: none"> - Evaluate existing down-gradient monitoring wells along Hannah Road to determine condition. Continue use if well condition is adequate. - Abandon and seal (per Section 391-3-2.13 of the Ground Water Use Act of 1974) up-gradient well and landfill perimeter wells. - Establish new upgradient well, west of Landfill No. 4, at depths of 25, 50, 75 and 100 feet. Monitor for parameters in List A, Table 6.2. - Establish eight monitoring wells down-gradient at landfill perimeter capable of sampling to depths of 25, 50, 75 and 100 feet. Construct wells of stainless steel or Teflon®. Monitor for parameters in List A (Table 6.2). - If condition permits, use LETCO Hannah Road wells to monitor shallow ground-water quality. If well condition is poor, replace wells with stainless steel or Teflon®. Monitor for parameters in List A, Table 6.2. - Establish wells in deeper zones along Hannah Road, to depths of 50, 75 and 100 feet. Analyze for parameters in List A, Table 6.2. - If possible, establish a line of monitoring wells along edge of farthest plume extent. Construct and monitor for parameters in List A, Table 6.2. - If contamination is determined to exist at depths of 100 feet, increase monitoring depth in order to determine maximum depth of contamination. Monitor for parameters specified in List A, Table 6.2. 	<p>Geophysical survey performance may be degraded by site geology and wetland environment.</p> <p>Contamination of the shallow aquifer downgradient of this site has been documented by previous ground-water monitoring (LETCO, 1980).</p> <p>This recommended monitoring program is more extensive than confirming if contamination exists. It is intended to define the extent of contamination and help determine remedial action.</p>
Sludge Lagoon	77	<p>Monitoring program described under Landfill No. 4 will include the sludge lagoon.</p>	<p>Landfill No. 4 and the sludge lagoon are too close to monitor separately.</p>

TABLE 6.1 (Continued)

Site	HARM Score	Recommended Monitoring	Comments
DDT Spill (1979)	70	Monitor soil samples for DDT to verify clean up of the site.	Preliminary monitoring has indicated DDT contamination. The soil in the spill area should be removed and replaced with fill material then pave over the site.
Fire Protection Area No. 2	64	Collect soil borings in and around the suspected area of the old pits (100 ft. by 200 ft., 15 in the pit area and 1 outside the area). The borings should be on 50 foot grid, ten feet deep and soil samples taken at regular intervals and at any interface. Analyses should be performed on water extractions and then analyzed for the parameters in List B (Table 6.2).	
Landfill No. 1	59	<p>a. Conduct geophysical survey in the area in and around the landfill (approximately 15 to 20 acres). If geophysical survey techniques do not work then install six monitoring wells into the top of the water table down-gradient of the site (about 10 to 20 feet deep). Sample for floating material.</p> <p>b. Collect surface water samples of leachate stream(s). Analyze for parameters in List A (Table 6.2).</p>	JP-4 spill (1965) occurred around Landfill No. 1. Therefore monitoring of these sites should be performed jointly.
Landfill No. 2	58	Establish shallow ground-water quality monitoring system in uppermost aquifer, consisting of one upgradient and three downgradient wells. Construct wells of PVC (Schedule 40) and monitor for parameters in List A (Table 6.2).	
JP-4 Spill (1965)	57	Conduct monitoring as described under Landfill No. 1.	Should monitor with Landfill No. 1 since they are in the same area.
Hazardous Waste Burial Site	54	Establish shallow ground-water quality monitoring system in uppermost aquifer consisting of one upgradient and two down-gradient wells. Construct wells of PVC (Schedule 40) pipe and monitor for parameters in List B (Table 6.2).	
Fire Protection Training Area No. 1	52	Monitoring will be included as part of monitoring program at Landfill No. 2.	
Laboratory Chemical Disposal Site	51	Utilize geophysical survey techniques to locate site. If site is identified, collect soil boring as described for Fire Protection Area No. 2.	Unable to determine location of this site. Geophysical survey may be able to detect metal containers.

TABLE 6.1 (Continued)

Site	HARM Score	Recommended Monitoring	Comments
Water Supply Wells	-	Conduct a water sample collection and analyses program for water supply wells Nos. 3, 6, 8 and 12. The parameters shown in List A of Table 6.2 should be used for analyses of each sample.	
Surface Water Monitoring	-	Sample water and sediments of the drainage courses from Landfill No. 4 to the base boundary. Set up approximately 8 sampling stations and analyze for the parameters in List A (Table 6.2).	

TABLE 6.2

RECOMMENDED LIST OF ANALYTICAL PARAMETERS

List A

Samples from:

Ground-water monitoring wells
 Leachate
 Base water supply wells
 Stream sediment samples
 Stream water samples

Analyses to include:

GC/MS scan
 Total organic carbon
 pH
 Nickel
 Phenol
 Cyanide
 Copper
 Zinc
 Manganese
 Total dissolved solids
 Interim Primary Drinking Water Standards (selected list)

Arsenic	Lead	Endrin	2,4,5-TP Silvex
Barium	Mercury	Lindane	Radium
Cadmium	Nitrate	Methoxychlor	Gross alpha
Chromium	Selenium	Toxaphene	Gross Beta
Fluoride	Silver	2,4-D	

List B

Samples from:

Ground-water monitoring wells
 Water extract of soil borings

Analyses to include:

Interim Primary Drinking Water Standards (see above list)
 pH
 Total organic carbon
 Nickel
 Phenol
 Cyanide
 Copper
 Zinc
 Manganese
 Total Dissolved Solids

APPENDICES

APPENDIX A

BIOGRAPHICAL DATA

G. M. Gibbons

R. M. Reynolds, P.E.


E. J. Schroeder, P.E.

M. I. Spiegel

R. E. Zimmermann, C.P.G.

Biographical Data
GREGORY M. GIBBONS
Sanitary Engineer

PII Redacted



Education

B.S. in Civil Engineering, 1978, University of Notre Dame
M.S. in Sanitary Engineering, 1980, University of Michigan,
Ann Arbor.

Professional Affiliations

Engineering-in-Training (Indiana)
American Society of Civil Engineers
Water Pollution Control Federation

Experience Record

1977-Date Engineering-Science. Technical Specialist (1977).
Responsible for reviewing shop drawings and performing
general office duties.

Assistant Engineer (1978). Prepared designs, wrote
specifications, and reviewed shop drawings.

Engineer (1979). Responsible for design preparation,
pilot plant operation, and data analysis. Also in-
volved in contract administration.

Sanitary Engineer (1980-Date). Responsible for indus-
trial waste survey, characterization and treatability
studies, including field surveys, analyses, interviewing
and report preparation. Responsible for field inves-
tigation and report preparation for sludge land
application EIS at Des Moines, Iowa. Assisted in air
pollution source tests and compliance determinations
at various industrial facilities. Assisted in EIS
preparation for wastewater treatment plant in Hanover
County, Virginia. Responsible for design of components
of 100-mgd Division Avenue Water Treatment Plant (Cleveland,
Ohio). Lead responsibility in process design for elec-
troplating waste treatment system. Project Manager for
resource recovery assessment of newsprint for the
Commonwealth of Virginia.


1978-1979 University of Michigan, Ann Arbor, Michigan. Laboratory
Aide (1978). Teaching Assistant (1979). Responsible
for instructing laboratory classes in water quality
analysis.

Biographical Data

Randal M. Reynolds

Senior Engineer

PII Redacted



Education

BChE (Chemical Engineering), 1973, Georgia Institute of Technology,
Atlanta, Georgia

Professional Affiliations

Registered Professional Engineer, Georgia #13023
Air Pollution Control Association
American Institute of Chemical Engineers (Chapter Secretary)

Experience Record

- 1973-1975 U.S. Environmental Protection Agency, Water Enforcement Branch, Atlanta, Georgia. Chemical Engineer. Responsible for developing draft NPDES limitations for industrial discharges, issuing public notices and final NPDES permits and participating in public hearings concerning NPDES permits.
- 1975-1981 Gold Kist Inc., Corporate Engineering, Atlanta, Georgia. Environmental Process Engineer. Responsible for reviewing and implementing new air quality, NPDES, RCRA and TSCA regulations. Supervised preparation and submittal of air quality, water quality and hazardous waste permit applications. Kept management informed of impact of regulations on existing and future projects.
- Served as staff engineer responsible for preparing preliminary designs for air pollution control systems and detailed cost estimates for air system capital projects. Major projects included the preliminary selection of alternatives for a particulate emission control system for a 60,000 lbs/hr industrial steam boiler (peanut hull/wood fired).
- 1981-Date Engineering-Science, Inc., Atlanta, Georgia. Senior Engineer. Responsibility for developing environmental studies and alternative evaluations for clients.

Randal M. Reynolds, Continued

Project Engineer for Phase I Installation Restoration Program projects for the Department of Defense. Developed hazardous chemical usage, waste generation and waste disposal practice timelines for industrial operations at several Air Force bases. Identified industrial operation disposal practices which could result in migration of contaminants and recommended priority disposal practices requiring further investigation.

Project Engineer assisting in a comprehensive study of the solid waste management program for the City of Roswell, Georgia. Developed conceptual cost estimates for a city operated sanitary landfill and incinerator disposal alternatives.

Project Manager for development of a Spill Prevention Control and Countermeasures (SPCC) Plan for an industrial facility. Coordinated the design of spill containment structures and recommended structure modifications. Recommended essential spill control and clean-up equipment.

Publications and Presentations

R. M. Reynolds, "Practical Tips - Bagging Sludge?", Pollution Engineering, Vol. 12, No. 7, July 1980, pg. 28.

R. M. Reynolds, "Pulse-Type Fabric Filters in a Soybean Processing Facility," Operation and Maintenance of Air Particulate Control Equipment, R. A. Young, F. L. Cross, Jr., editors, Ann Arbor Science Publishers, Inc., Ann Arbor, Michigan, July 1980, pp. 121-123.

"Operation, Maintenance and Design of Fabric Filters for a Soybean Processing Facility," a slide presentation for the EPA technology transfer seminar, "Operation and Maintenance of Air Pollution Equipment for Particulate Control," April 12, 1979, Atlanta, Georgia.

Biographical Data

ERNEST J. SCHROEDER

Environmental Engineer
Manager, Solid and Hazardous Waste

Education

B.S. in Civil Engineering, 1966, University of Arkansas,
Fayetteville, Arkansas
M.S. in Sanitary Engineering, 1967, University of Arkansas,
Fayetteville, Arkansas

Professional Affiliations

Registered Professional Engineer (Arkansas No. 3259, Georgia
No. 10618, Texas No. 33556 and Florida No. 0029175)
Water Pollution Control Federation

Honorary Affiliations

Chi Epsilon

Experience Record

1967-1976 Union Carbide Technical Center, Engineering Department,
South Charleston, West Virginia (1967-1968). Project
Engineer. Responsible for environmental protection
engineering projects for various organic chemicals and
plastics plants. Conducted industrial waste surveys,
landfill design, and planning for plant environmental
protection programs; evaluated air pollution discharges
from new sources; reviewed a wastewater treatment plant
design; and participated on a project team to design a
new chemical unit.

Union Carbide Corporation, Environmental Protection
Department, Texas City, Texas (1969-1975). Project
Engineer and Engineering Supervisor. Responsible for
various aspects of plant pollution abatement programs,
including preparation of state and federal permits for
wastewater treatment activities.

Operations Representative on \$8 million regional waste-
water treatment project and member of design team which
made the initial site selection and process evaluation

ERNEST J. SCHROEDER (Continued)

and recommendation. Participated in contract negotiations, process and detailed engineering design, construction of the facilities, preparation of start-up manuals, operator training, and the start-up activities. Designated as Project Engineer after start-up on expansion to original waste treatment unit.

Engineering Supervisor responsible for operation of wastewater treatment facilities including collection system, sampling and monitoring programs, spill control and clean-up, primary waste treatment, wastewater transfer system, biological waste treatment, and waste treatment pilot plants. Developed odor control program which successfully reduced odor emissions and represented Union Carbide at a public hearing on community odor problems.

Led special projects such as an excess loss control program to reduce water pollution losses; sewer segregation program involving coordination and reporting of 38 projects for the separation of contaminated and non-contaminated water; and sludge disposal program to develop long-term sludge disposal alternatives and recover land in present sludge landfill area. Developed improved methods of sampling and continuous monitoring of wastewater.

Union Carbide Corporation, Environmental Protection Project Engineer, Toronto, Ontario, Canada (1975-1976). Responsible for the overall environmental permitting, engineering design, construction and start-up of waste treatment systems associated with a new refinery.

1976-Date Engineering-Science, Inc., Project Manager (1976-1978). Responsible for several industrial wastewater projects including the following: wastewater investigation to characterize sources of waste streams in a chemical plant and to develop methods to reduce the wastes, sludge settling studies to evaluate settling characteristics of activated sludge at a chemical plant, development of a process document for the design and operation of a wastewater treatment facility at a petrochemical complex, wastewater treatment evaluation which included characterization of wastewater, unit process evaluation, inhibition studies, design review, operations review, preparation of operations manual, operator training and providing operating assistance for waste treatment facilities, various biological treatability studies and bench-scale and pilot-scale evaluation of advanced waste treatment technologies such as granular carbon adsorption, multimedia filtration, powdered activated carbon treatment, ion exchange and ozonation.

ERNEST J. SCHROEDER (Continued)

Project Manager for hazardous waste disposal projects involving waste characterization, development of criteria for disposal of hazardous waste, site investigation, preparation of permits, detailed design, construction of facilities and spill clean-up activities.

Deputy Project Manager for industry-wide pilot plant study of advanced waste treatment in the textile industry. Technologies evaluated included coagulation/clarification, multi-media filtration, granular carbon adsorption, powdered activated carbon treatment, ozonation and dissolved air flotation.

Engineering-Science, Inc., Manager of the Industrial Waste Group in the Atlanta, Georgia office (1978-1980). Responsible for the supervision of industrial waste project managers and project engineers and the management of industrial waste studies conducted in the office. Also directly involved in project management consulting with clients on environmental studies and environment assessment projects, e.g., project manager for several spill control and wastewater treatability projects and for a third-party EIS for a new phosphate mine in Florida.

Engineering-Science, Inc., Manager of Solid and Hazardous Waste Group in the Atlanta, Georgia office (1980-date). Responsible for the supervision of solid and hazardous waste project managers and project engineers and the management of solid and hazardous waste projects in the office. Project activities have included permit and regulatory assistance, environmental audits, waste management program development, ground water monitoring, landfill evaluations, landfill closure design, hazardous waste management, waste inventory, waste recovery/recycle evaluation, waste disposal alternative evaluation, transportation evaluation, and spill control and counter-measure planning.

Project Manager for several Phase I Installation Restoration Program projects for the U.S. Air Force. The objective of this program is to audit past hazardous waste disposal practices that could result in migration of contaminants and recommend priority sites requiring further investigation. Also conducted environmental audits (air, water and solid waste) at several Gulf Oil Company facilities.

ERNEST J. SCHROEDER (Continued)

Publications and Presentations

Schroeder, E. J., "Filamentous Activated Sludge Treatment of Nitrogen Deficient Waste," research paper submitted in partial fulfillment of the requirements for MSCE degree, 1967.

Schroeder, E. J., and Loven, A.W., "Activated Carbon Adsorption for Textile Wastewater Pollution Control," Symposium Proceedings: Textile Industry Technology, December 1978, Williamsburg, VA.

Schroeder, E. J., "Summary Report of the BATEA Guidelines (1974) Study for the Textile Industry," North Carolina Section of AWWA/WPCA, Pinehurst, North Carolina, November 1979.

Mayfield, R. E., Sargent, T. N. and Schroeder, E. J., "Evaluation of BATEA Guidelines (1974) Textiles," U.S. EPA Report, Grant No. R-804329, February 1980.

Storey, W. A., and Schroeder, E. J., "Pilot Plant Evaluation of the 1974 BATEA Guidelines for the Textile Industry," Proceedings of the 35th Industrial Waste Conference, Purdue University, May 1980.

Pope, R. L., and Schroeder, E. J., "Treatment of Textile Wastewaters Using Activated Sludge With Powdered Activated Carbon," U.S. EPA Report, Grant No. R-804329, December 1980.

Schroeder, E. J., "Industrial Solid Waste Management Program to Comply with RCRA," Engineering Short Course Instructor, Auburn University, October 1980.

Schroeder, E. J., "Technical and Economic Impact of RCRA on Industrial Solid Waste Management, Florida Section, American Chemical Society, May 1981.

Biographical Data

MARK I. SPIEGEL

Environmental Scientist

PII Redacted

Education

B.S. in Environmental Health Science (Magna cum laude), 1976,
University of Georgia, Athens, Georgia
Limnology and Environmental Biology, University of Florida,
Gainesville, Florida
Business Administration, Georgia State University

Professional Affiliations

American Water Resources Association
Technical Association of the Pulp and Paper Industry

Experience Record

1974-1976 U.S. Environmental Protection Agency, Surveillance and Analysis Division. Cooperative Student. On assignment to Air Surveillance Branch, participated in ambient air study in Natchez, Mississippi, and operated unleaded fuel sampling program for Southeast National Air Surveillance Network. For Engineering Branch, participated in NPDES compliance monitoring of industrial facilities throughout the southeast; operation and maintenance studies of municipal waste treatment facilities; and post-impoundment study of West Point Reservoir, West Point, Georgia. Participated in industrial bioassay studies for the Ecological Branch.

1977-Date Engineering-Science. Environmental Scientist. Responsible for the conduct of water and wastewater sampling programs and analyses, quality control, laboratory process evaluations, and evaluation of other environmental assessment data. Conducted leachate extraction studies of sludges produced at a large organic chemicals plant to define nature of sludges according to the Resource Recovery and Conservation Act guidelines. Involved in laboratory quality assurance program for the analysis of water samples used in a stream modeling project. Conducted water quality modeling study for Amerada Hess Corporation to determine the assimilative capacity of a stream receiving effluent from a southern Mississippi refinery.

Mark I. Spiegel (Continued)

Participated in bench-scale industrial treatability studies conducted for the American Textile Manufacturers Institute and Eli Lilly Pharmaceuticals in Mayaguez, Puerto Rico, and in carbon adsorption studies for an American Cyanamid chemical plant and Union Carbide Agricultural Products Division.

Involved in various aspects of several industrial environmental impact assessments including preliminary planning for a comprehensive study for St. Regis Paper Company on a major pulp and paper mill expansion project. Assisted in preparation of third-party EIS for EPA and Mobil Chemical Company concerning a proposed 16,000-acre phosphate mining and beneficiation facility. Developed an EIA prior to construction of a pulp and paper complex by the Weyerhaeuser Company in Columbus, Mississippi, which included preparation of a separate document for the Interstate Commerce Commission concerning the construction of a railroad spur to serve the complex. Also involved in formulating the water quality, water resource and socio-economic aspects of an environmental impact assessment for International Paper Company. Participated in large scale site evaluation to determine the suitability and environmental permitting requirements of a site for an east coast brewery for the Adolph Coors Company. Assisted in development of a peat mining and restoration plan for a private concern in coastal North Carolina.

Project Manager. Conducted comprehensive process evaluation of an 80 mgd wastewater treatment system for Weyerhaeuser Company. Responsible for a study to determine the leaching characteristics of sludges for a paint manufacturing facility for RCRA compliance. Also managed study for development of a solid waste management plan for a ceramic pottery manufacturer in northern Alabama which included evaluating surface and groundwater contamination potential from the existing disposal site and assisting manufacturer in developing a disposal program acceptable to state agencies.

Participated as project team member for Phase I Installation Restoration Program projects for the Department of Defense. Studies were conducted at five Air Force bases to identify past hazardous waste disposal practices that could result in migration of contaminants and recommend priority sites requiring further investigation.

Biographical Data

ROBERT E. ZIMMERMANN

Geologist

PII Redacted



Education

B.S. in Geology, 1978, University of Akron, Akron, Ohio
Post baccalaureate Studies - University of Akron - Geology, 1979
M.S. - Environmental Geology, University of Akron - Presently
working towards degree
Cartographic Certification - 1981 - University of Akron

Professional Affiliations

American Institute of Professional Geologists
National Water Well Association
Geological Society of America
American Society of Photogrammetry

Experience Record

1978 - 1981 Ohio Environmental Protection Agency, Twinsburg, Ohio
Geologist

- ...Performed RCRA Site inspections of Hazardous Waste Facilities as part of permit process
- ...Performed site investigations and evaluations for the disposal of hazardous and solid waste materials.
- ...Hydrogeologic studies of ambient groundwater quality in various aquifers in Northeast Ohio.
- ...Performed groundwater contamination studies due to various pollution sources (landfills, chemical disposal sites, salt storage, road salting, brine disposal, etc.)
- ...Hydrogeologic evaluation for injection well sites.
- ...Conducted Surface Impoundment Assessment in Northeast Ohio as required by the Safe Drinking Water Act and completed groundwater pollution potential reports on selected impoundments.
- ...Responsible for the compiling and drafting of final copies of groundwater aquifer maps for State of Ohio.
- ...Worked with general public on water quality and well problems.

Robert E. Zimmermann (Continued)

Additional Responsibilities

- ...Worked very closely with various consultants on groundwater contamination problems and approval of new or expanding land-fill sites;
- ...Compiled and drafted soil capability maps, groundwater quality maps, aquifer maps, etc.;
- ...Collected and interpreted geochemical analyses of groundwater samples;
- ...Provided input for Ohio's proposed Groundwater Protection Strategy;
- ...Provided geologic information as needed by Ohio EPA staff and general public

1981 - Date

Engineering-Science, Inc., Cleveland, Ohio.
Geologist. Responsible for setting up groundwater monitoring programs for industry; supervising drilling and well construction of monitoring wells; assessing impact of contaminants on groundwater quality; determining flow rates, directions, etc., of groundwater at industrial disposal sites; locate and determine new sites suitable for solid and hazardous waste disposal, monitoring groundwater at solid waste facilities; determination of subsurface geology at various locations; hydrogeologic studies at various solid and hazardous waste disposal facilities.

Special Skills

Certified Cartographer, drafting abilities, calligrapher

APPENDIX B

INSTALLATION HISTORY, ORGANIZATION AND MISSIONS

APPENDIX B
INSTALLATION HISTORY, ORGANIZATION AND MISSIONS

HISTORY

This information was obtained from Robins AFB records.

Robins Air Force Base began in 1941 with the announcement by Congressman Carl Vinson of plans to establish a maintenance and supply depot in the southeast. The original tract of 3,000 acres of land was donated by the City of Macon and Bibb County. Subsequent acquisitions by the Federal Government increased the size of the installation to its present 8,855 acres.

The names "Robins" for the Base and "Warner Robins" for the ALC and the City honor the memory of Brigadier General Augustine Warner Robins, Chief of the Air Corps, Material Division, Army Air Corps, 1935-1939, and Commandant of Randolph Field at the time of his death in 1940.

Officially activated on 1 March 1942 and declared a permanent military installation in 1952, the base today is a multi-mission facility. The original intent was to establish a maintenance and supply depot but the installation also became a training center. Original facilities were both temporary and permanent. After World War II, Robins ceased to be a training center but continued as an Air Material Area of AMC (now AFLC).

A second growth spurt began in 1949 when the Fourteenth Air Force Headquarters moved to Robins where it remained until deactivated in 1960. Headquarters Continental Air Command moved to Robins in 1961. Other factors contributing to the expansion were the Korean Conflict in 1950 and the decentralization of prime responsibility by the Air Material Command to its Air Material Areas.

The largest construction program commenced in 1958 with contracts exceeding 26 million dollars to prepare facilities for the 19th Bombardment Wing as a tenant organization. Runway enlargement and Capehart Family Housing were two of the numerous items of this program. In 1962,

the runways were further rehabilitated to better accommodate the heavy B-52 and KC-135 aircraft.

Today, Robins AFB, an Air Force Logistics Command installation, is a huge, sprawling military complex of closely related units with diversified missions. The Warner Robins Air Logistic Center is one of five similar organizations in the Air Force. These Centers provide logistics support to the entire Air Force, and it is their mission to keep the United States Air Force Weapons Systems at constant state of readiness.

The Warner Robins ALC determines the parts, supplies, and equipment needed to support the weapon systems for which it is responsible.

The ALC budgets for these items, buys them, stores them, distributes them, repairs and maintains them, and finally disposes of them when they have outlived their usefulness.

In short, the Warner Robins ALC is system manager for 41 aircraft, missile and support systems. In addition, the ALC has 10 program management assignments. The ALC's support mission includes management of 167,000 items in virtually all commodity areas.

The commodity range is from simple hardware items to the free world's most sophisticated aerospace communications and electronic equipment.

The entire Air Force fleet of bombers, fighter-interceptors, reconnaissance, cargo aircraft, and helicopters depends on Warner Robins logistics expertise to fulfill vital logistical needs.

In 1973, the ALC was designed as the Technology Repair Center for airborne electronics, gyros and life support systems. Airborne electronics is one of the largest and most sophisticated repair loads of the new assignments.

The Warner Robins Air Logistics Center has command jurisdiction over the installation with the 2853rd Air Base Group providing the housekeeping functions vital to operation of the installation.

Throughout its 41 years, the relationship of Robins AFB with its neighboring communities has been outstanding. The Base depends upon the local area for many community services and its most important resource people. In turn, Robins AFB is an integral part of the Middle Georgia economy. There is recognition of this dependence as the base and the

communities work together for a solution of mutual problems and the further strengthening of the ties that bind the two.

ORGANIZATIONS AND MISSIONS

This information was obtained from the Robins Air Force Base Tab A-1 Environmental Narrative and the Warner Robins-Air Logistics Center Information Handbook, Fiscal Year 1981, prepared by Management and Cost Analysis, Comptroller.

Warner Robins-Air Logistics Center

The Warner Robins Air Logistics Center (WR-ALC) is one of five organizations that provide logistics support to the entire U. S. Air Force. As a worldwide logistics manager, it is one of the vital parts of the Air Force Logistics Command (AFLC) which supports the aerospace forces.

The Center determines the spare parts, supplies and equipment needed to support the weapon systems for which it is responsible. It budgets for these, buys them, stores them, distributes them, and finally disposes of them when they have outlived their usefulness.

Warner Robins ALC currently serves as System Manager - that is, the overall Air Force focal point - for five transport aircraft, seven utility aircraft, five helicopters, eight air-to-air and air-to-ground missiles, seven drones, the F-15 Fighter and B-57 reconnaissance bomber. The latest system management responsibility assignment is the H-60 Helicopter.

Warner Robins ALC's support mission includes management of nearly 200,000 items ranging from single hardware items to the most sophisticated communications and electronic equipment. The entire fleets of Air Force bombers, fighter-interceptors, reconnaissance, cargo aircraft, and helicopters depend on the Warner Robins ALC to fulfill their logistics needs. Other item management responsibilities include bombing-navigation systems, fire control systems, target acquisition systems, airborne radar, airborne electronic warfare systems, propellers, bearings, general purpose automatic data processing equipment, satellite communication equipment, guns and vehicles.

The largest group of people in the ALC are engaged in repairing, modifying, and overhauling aircraft and equipment. In the aircraft area, this involves depot level repair of the C-141, C-130 and the F-15.

The WR-ALC is also the technology repair center for aircraft propellers, life support equipment, instruments, gyros, and airborne electronics. As Avionics Center of the Air Force, we use some of the most sophisticated equipment and skills anywhere in the world.

The Center has the geographic area logistics support responsibility for most Air Force bases along the eastern coast as well as the Atlantic Missile Test Range, Newfoundland, Labrador, Greenland, Iceland, Bermuda and the Azores.

Tenant Organizations

Robins AFB is the host to many tenants and provides services, facilities, and other support to these organizations. The following list shows the tenant units located on Robins Air Force Base. In addition, Robins AFB supports some 63 off base organizations ranging from high school ROTC detachments to American units in 11 foreign countries.

Robins Air Force Base Exchange (AAFES)

The mission of the Army & Air Force Exchange Service is to:
(1) provide merchandise and services of necessity and convenience which are not furnished from appropriated funds to authorized patrons at uniformly low prices.

Robins Air Force Base Commissary (AFCOMS)

The Air Force Commissary Service (AFCOMS) is a centralized commissary system which manages and operates the worldwide Air Force Commissary function.

1926th Communications Squadron (AFCC)

The mission of the 1926 Communications Squadron is to manage, operate, and maintain communications-electronics-meteorological (C-E-M) services and the air traffic control (ATC) services/facilities in support of Robins AFB.

Detachment 5, Air Force Communications Command (AFCC)

The mission of DET 5, AFCC, is to provide communications-electronics (C-E) and air traffic control (ATC) staff support to Headquarters Air Force Reserve (AFRES).

5th Combat Communications Group (AFCC)

The mission of 5th Combat Communications Group is to provide mobile and transportable communications, aids to navigation, and air traffic control services for use in any area of the world, but primarily in support of the Tactical Air Command.

1839th Engineering Installation Group, Operating Location C (AFCC)

The mission of the 1839th Engineering Installation Group, Operating Location C, Robins Air Force Base, Georgia, is to fabricate AN/TSC-107 (Quick Reaction Package), test, furnish emergency and depot level maintenance of these systems in the field.

Headquarters Air Force Reserve (AFRES)

The United States Air Force Reserve develops, maintains, and provides operationally ready units and trained individuals needed to augment the Air Force in time of war, national emergency or when required to maintain national security.

94th Aerial Port Squadron (AFRES)

The primary peacetime mission of the 94th Aerial Port Squadron is to attain and maintain through training a state of operational readiness that will permit the 94th Aerial Port Squadron to fulfill its mobilization and/or contingency responsibilities.

402d Combat Logistics Support Squadron (AFRES)

The primary mission of the 402d Combat Logistics Support Squadron is to provide highly trained worldwide deployable military teams to accomplish rapid aircraft battle damaged repair and combat packaging and supply operations.

Detachment 6, 3025th Management Engineering Team (AFLC)

The Management Engineering Team (MET) provides manpower, organization, management engineering and management advisory services to all ALC activities.

Detachment 8, 2762d Logistics Squadron (Special) (AFLC)

Det 8 insures equipment, skills, and techniques capable of performing and supporting the system's operational role are compositely

programmed, managed, and furnished in keeping with overall program objectives.

NCO Academy/Leadership School (AFLC)

The mission of the NCO Academy and NCO Leadership School is to insure that selected NCOs are prepared to assume supervisory positions, more advanced leadership and management responsibilities, and are able to fulfill their role in the Air Force.

321st Field Training Detachment (ATC)

FTD 321 is an off-campus unit of the U.S. Air Force School of Applied Aerospace Sciences, Sheppard AFB, Texas.

3503d USAF Recruiting Group (ATC)

The Group is responsible for all active duty Air Force recruiting programs in 12 states and Puerto Rico.

14th Flying Training Wing (ATC)

The detachment trains the co-pilots of the 19th Bomb wing.

Office of the Placement Coordinator Zone 2
and Atlantic Theatre (DOD)

The DOD Placement Coordinator, Zone 2/Atlantic Theatre, acts for the Assistance Secretary of Defense (Manpower, Reserve Affairs and Logistics) in implementing and administering various DOD-wide personnel programs in the geographic area of the Southeast and Southwest Civil Service Regions and the Atlantic Theatre.

DCAS Quality Assurance Section (DLA)

DCAS Quality Assurance Section is a management area of Defense Contracts Administration Region Atlanta located in Marietta, Georgia.

Defense Property Disposal Office (DLA)

The Defense Property Disposal Office mission is to receive, segregate, inspect, classify, and store excess surplus and scrap property turned in by all host installation organizations and other generators in the geographical area. Dispose of property through reutilization, transfer, donation, sale and destruction.

Federal Aviation Administration

Radar Approach Control (FAA)

The mission of the FAA Radar Approach Control is to provide for the

management of civil and military air traffic operating within the geographical boundaries of the facility's allocated navigable airspace.

Air Force Audit Agency Area Office

Detachment 960 (AFAA)

The mission of Det 960, Air Force Audit Agency (AFAA) Area Audit Office is to provide all levels of Air Force management with independent, objective, and constructive evaluations of the economy, effectiveness, and efficiency with which managerial responsibilities (including financial, operational, and support activities) are carried out.

Detachment 712, Air Force Office of

Special Investigations (AFOSI)

AFOSI Detachment 712 is a field extension of AFOSI District 7, Patrick AFB, FL. AFOSI investigates fraudulent activities, major administrative irregularities and violations of public trust involving Air Force procurement, disposal, pay and allowance matters, and nonappropriated fund activities.

Area Defense Counsel (USAF)

The Area Defense Counsel's mission is to perform legal defense functions.

Detachment 13, 15th Weather Squadron (MAC)

The mission of Det 13, 15 Weather Squadron is to provide or arrange for the environmental services needed to support the exercise, contingency, and wartime requirements of the Warner Robins Logistics Center and the 19th Bombardment Wing.

Headquarters 19th Bombardment Wing (SAC)

The mission of the 19th Bombardment Wing, Heavy, (BMW) is to develop and maintain operational capability to permit the conduct of strategic warfare according to the emergency war order (EWO) plans as directed by proper command authority.

Procurement Center Representative (SBA)

The Procurement Center Representatives (PCRs) represent the Small Business Administration to the commanding officer of the installation on any procurement or technical matter pertaining to policy or operation SBAs programs or the small business community.

4400th Mobility Support Flight (TAC)

The mission is to acquire, store, and maintain the Harvest Eagle Air Transportable Housekeeping Package in a serviceable condition for deployments in support of wartime commitments, contingencies, and exercises.

Detachment 3, 2d Aircraft Delivery Group (TAC)

Responsible for the movement of aircraft from the Southern United States and Central and South America.

RAF - Royal Air Force C-130 Liaison Team

This team serves as liaison for the C-130 program between the Royal Air Force and Robins AFB.

RCAF - Canadian Forces Logistics Unit

The first Canadian Forces Logistics Liaison Detachment is to serve as liaison agency between logistics functions at Robins AFB and the Royal Canadian Air Force.

RAAF - Royal Australian AF Liaison Office

The Royal Australian AF Liaison Office is to serve as liaison agency between logistics functions at Robins AFB and the Royal Australian Air Force.

U. S. Army Corps of Engineers

This U. S. Army unit is known as the U. S. Army Corps of Engineers, Savannah District. It administers and supervises Air Force and Army construction contracts at Robins and the surrounding areas. It coordinates contract sales of government real estate properties and facilities.

General Accounting Office (USGAO)

The U. S. General Accounting Office is an independent, nonpolitical agency in the legislative branch of the government. It provides the Congress, its committees and members with information, analyses and recommendations concerning operations of the government, primarily the executive branch.

GAO is concerned that the federal departments and agencies through their programs and activities, carry out the mandate or intent of legislation enacted by the Congress.

APPENDIX C

SUPPLEMENTAL ENVIRONMENTAL SETTING INFORMATION

APPENDIX C

SUPPLEMENTAL ENVIRONMENTAL SETTING INFORMATION

BIOLOGICAL RESOURCES

The following information regarding the Robins AFB biological resources was obtained from the Tab A-1, Environmental Narrative, 1976. The information pertaining to threatened and endangered vertebrate species was verified and updated by the Georgia Game and Fish Division (GA Game and Fish Div., 1982).

Robins AFB encompasses natural forests totaling 1,964 acres (60% wetlands) and grasslands with low bush totaling 4,197 acres. The wet ecosystem of the wetlands promotes the growth of hardwoods such as oak and hinders the growth of softwoods such as pine. Floating, submerged and emergent types of aquatic plants are present in the wetlands.

The natural forests and grasslands on-base provide habitat areas for a wide variety of animal life. Large and small game animals and a variety of predatory bird exist on-base. Numerous species of fish and waterfowl inhabit the lakes and wetlands on-base. Several of the animal species are included as threatened or endangered as shown in Table C.1.

SUMMARY OF SURFACE WATER QUALITY DATA

A summary of NPDES water quality sampling data is shown in Table C.2. A summary surface water quality sampling data conducted by the Base Bioenvironmental Engineering Office is shown in Tables C.3 through C.10. The EPA interim primary and proposed secondary drinking water standards are shown in Table C.11.

INVENTORY OF PESTICIDES

A summary of the current inventory of pesticides on-base is shown in Table C.12.

GROUND-WATER MONITORING - LANDFILL NO. 4

In October 1979 Law Engineering Testing Company (LETCO) was sub-contracted to perform a hydrogeologic and ground-water quality study at Landfill No. 4. The objectives of the study were to determine if any ground or surface water contamination was occurring from Landfill No. 4 or the sludge lagoon, determine the magnitude of contamination if demonstrated to exist, and provide other relevant landfill closure information.

The study consisted of an exploratory drilling program, the installation of a monitoring well system and ground and surface water sampling, summarized in a formal report. The study confirmed the presence of several metals and numerous priority pollutants hydraulically down stream and down-gradient of Landfill No. 4 (LETCO, 1980). Recommendations for further studies were included in the formal report. The Phase I IRP report is a follow-on project to the earlier study and supplements the information collected in the previous work.

TABLE C.1
 THREATENED OR ENDANGERED VERTEBRATE SPECIES
 POTENTIALLY FOUND WITHIN
 ROBINS AIR FORCE BASE

Common Name	Status	Habitat
<u>Fish</u>		
Suwannee Bass	Threatened	Unpolluted springs & rivers
Trispot Darter	Threatened	Unpolluted streams
<u>Reptiles and Amphibians</u>		
American Alligator	Endangered	Coastal plain swamps & bayous
Pine Barrens Tree Frog	Threatened	Pine barren swamps
<u>Birds</u>		
Southern Bald Eagle	Endangered	Estuarine shores, rivers
Florida Sandhill Crane	Threatened	Wet prairies and fields
Ivory-Billed Woodpecker	Endangered	Bottom land hardwood stands
Red-Cockaded Woodpecker	Endangered	Old-age pine woodlands
Bachman's Warbler	Endangered	River swamp forest
<u>Mammals</u>		
Florida Panther	Endangered	Large, unmolested swamp, deer available

Source: Robins AFB TAB A-2, Updated 1976
 Verified and updated by Georgia Game and Fish Division, 1982

TABLE C.2
1981 NPDES DATA SUMMARY

Station/Parameter	Unit	Permit Requirement	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV
<u>Station 001 (Runoff Ditch by Missile Storage)</u>													
BOD	mg/l	10.0	5.8	4.7	2.5	2.4	1.6	1.5	2.6	5.1	4.3	2.3	2.5
Oil/Grease	mg/l	15.0	3.1	0.6	1.5	1.0	1.3	5.4	2.3	10.3	3.1	2.7	4.8
Suspended Solids	mg/l	50.0	--	6.0	4.5	1.3	1.2	--	1.6	3.2	2.4	1.0	2.7
pH	unit	6.0-8.5	6.7	6.9	6.2	6.8	7.3	7.7	7.1	6.9	7.2	6.7	6.7
<u>Station 002 (Runoff Ditch by Ammo Storage Area)</u>													
BOD	mg/l	15.0	8.0	6.3	6.9	3.8	3.0	1.9	1.4	4.1	3.5	2.7	2.2
Oil/Grease	mg/l	15.0	4.6	0.6	1.2	1.9	2.9	3.9	4.1	9.1	5.4	3.8	4.2
pH	unit	6.0-8.5	6.6	6.9	8.5	7.3	7.2	7.4	7.4	7.0	6.8	7.4	6.6
<u>Station 003 (Runoff Ditch North SAC Alert)</u>													
BOD	mg/l	15.0	7.0	4.3	3.2	2.5	3.0	1.3	2.0	4.1	2.5	2.6	1.8
Oil/Grease	mg/l	15.0	3.0	0.8	2.1	1.3	1.7	2.1	1.7	11.0	2.6	3.1	8.4
pH	unit	6.0-8.5	6.7	10.3	7.2	6.5	7.3	7.2	7.6	7.3	8.0	6.9	6.7
<u>Station 004 (Hannah Rand Runoff Ditch)</u>													
BOD	mg/l	15.0	5.1	2.4	3.7	2.3	1.8	2.0	1.6	1.6	2.5	1.3	2.0
Oil/Grease	mg/l	15.0	1.8	0.3	1.3	1.5	3.4	1.2	2.9	2.9	6.2	4.7	4.6
pH	unit	6.0-8.5	6.5	7.1	7.1	6.9	7.1	7.1	7.1	6.9	6.7	6.9	6.5
NH ₃ -N	mg/l	2.0	0.56	0.28	0.8	0.3	0.5	1.4	0.56	1.8	0.001	2.4	0.3

TABLE C.2
(Continued)
1981 NPDES DATA SUMMARY

Station/Parameter	Unit	Permit Requirement	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV
<u>Station 005 (Ditch at End of San. Treat. Plant No. 2 Pipe)</u>													
BOD	mg/l	15.0	3.5	3.5	3.7	3.4	2.7	2.4	2.4	4.9	3.0	2.9	2.5
Oil/Grease	mg/l	15.0	1.8	0.1	1.6	2.5	2.1	1.6	4.8	3.7	4.1	4.4	3.2
pH	unit	6.0-8.5	6.9	6.7	6.7	6.7	7.1	7.2	7.2	6.9	7.0	7.1	6.6
NH ₃ -N	mg/l	2.0	0.42	1.12	0.56	0.2	0.92	0.56	0.56	0.84	0.001	0.28	0.2
<u>Station 006 (Ditch by Dependent Pool)</u>													
BOD	mg/l	15.0	4.7	3.9	3.6	2.9	2.4	1.8	1.4	4.6	1.4	2.8	1.7
Oil/Grease	mg/l	15.0	2.3	0.4	1.4	1.0	4.3	1.5	1.3	2.7	5.2	6.8	3.1
pH	unit	6.0-8.5	7.3	6.4	6.8	6.9	7.4	7.2	7.9	7.4	7.3	6.9	7.0
<u>Station 008 (Industrial Waste Treatment Plant #2)</u>													
BOD	mg/l	30.0	2.1	2.3	3.2	1.3	3.3	1.7	6.8	3.7	3.1	3.1	2.9
Suspended Solids	mg/l	30.0	13.0	18.0	7.9	6.0	5.8	9.9	5.8	8.4	10.0	7.6	6.8
COD	mg/l	150.0	40.0	50.0	38.0	20.0	48.0	60.0	61.0	60.2	55.0	60.0	40.0
Oil/Grease	mg/l	15.0	1.1	1.8	9.4	4.1	6.3	9.0	4.4	6.4	3.1	8.0	6.1
Phenol	mg/l	0.2	0.02	0.2	0.19	0.2	0.1	0.2	0.1	0.1	0.001	0.01	0.01
Cyanide	mg/l	0.35	0.04	0.04	0.05	0.06	0.05	0.1	0.04	0.05	0.03	0.04	0.05
Cadmium	mg/l	0.15	0.02	0.02	0.03	0.02	0.08	0.05	0.02	0.13	0.02	0.02	0.01
Chromium (total)	mg/l	0.45	0.08	0.01	0.01	0.01	0.13	0.07	0.13	0.20	0.10	0.01	0.08
Zinc	mg/l	0.45	0.08	0.05	0.06	0.01	0.10	0.11	0.07	0.10	0.18	0.12	0.1
Nickel	mg/l	0.75	0.01	0.01	0.01	0.12	0.12	0.07	0.1	0.17	0.34	0.06	0.04
Lead	mg/l	0.15	0.01	0.01	0.01	0.01	0.02	0.05	0.01	0.01	0.10	0.08	0.1
Copper	mg/l	0.30	0.02	0.04	0.2	0.02	0.18	0.10	0.07	0.3	0.04	0.07	0.08
pH	unit	6.0-9.0	8.8	8.8	8.3	8.9	8.6	8.8	9.0	9.0	9.0	9.0	8.1

TABLE C.2

(Continued)

1981 NPDES DATA SUMMARY

Station/Parameter	Unit	Permit Requirement	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV
Station 009 (Industrial Waste Treatment Plant #1)													
BOD	mg/l	Not Listed	16.0	20.0	23.0	27.0	21.0	25.0	19.0	18.0	15.0	8.0	8.0
COD	mg/l	"	39.0	50.0	44.0	10.0	32.0	20.0	50.0	31.0	31.4	20.0	20.0
Suspended Solids	mg/l	"	15.0	13.0	25.0	11.0	17.0	18.0	14.0	13.0	15.0	4.0	4.0
Phenol	mg/l	0.20	0.10	0.02	0.02	0.2	0.2	0.2	0.2	0.1	0.1	0.02	0.01
Oil/Grease	mg/l	15.0	0.90	0.2	1.1	2.0	1.6	1.5	4.7	2.3	2.1	2.1	3.0
NH ₃ -N	mg/l	2.0	0.28	0.56	0.77	1.1	0.6	1.6	0.28	1.8	0.001	0.56	0.2
Fecal Coliform	N/100 ml	400.0	1.0	200.0	131.00	1000	TNTC	219.0	1000	3500	5000	4.0	1.0
pH	Unit	6.0-9.0	7.5	7.9	7.3	7.3	7.0	7.4	7.4	7.3	7.2	7.3	7.2

TNTC = too numerous to count

TABLE C.3
 SUMMARY OF WATER SAMPLE RESULTS
 FROM MONITORING STATION NO. 001
 (Missile Storage Area)
 March 1979

Day	COD (mg/l)	TOC (mg/l)	Oil & Grease (mg/l)	Fe (μ g/l)	K (mg/l)	Na (mg/l)	CN (mg/l)
13	20	7	0.6	2,300	1.3	5.9	0.2
14	20	8	0.3	1,600	1.1	4.5	0.1
15	20	5	(a)	1,000	1.1	4.5	(b)
16	15	7	(a)	280	1.1	4.5	(b)
17	15	9	(a)	2,900	1.0	6.0	(b)
18	14	7	(a)	3,400	0.7	6.0	2.1

(a) Less than detectable limits of 0.3 mg/l.

(b) Less than detectable limits of 0.1 mg/l.

(c) Results for the following parameters were less than the detectable limits shown:

NH_3 (0.2 mg/l), PO_4 (0.2 mg/l), Cd (10 μ g/l), Cr^{+3} (50 μ g/l),

Cr^{+6} (50 μ g/l), Cu (20 μ g/l), Pb (50 μ g/l), Hg (5 μ g/l), Ni (50 μ g/l)
 and Zn (50 g/l).

TABLE C-4

SUMMARY OF WATER SAMPLE RESULTS FROM
MONITORING STATION NO. 002 (SAC DITCH), NOVEMBER 1978

Day	COD mg/l	TOC mg/l	Oil & Grease mg/l	Cd µg/l	Cr ⁺³ µg/l	Cu µg/l	Ag mg/l	Na mg/l	K mg/l	Zn µg/l	Temp. °F	pH S.U.	D.O. mg/l	NH ₃ mg/l	Cl ⁻ mg/l
15	11	1	(b)	31	100	38	28	28	1.6	100	68.9	7.2	8.0	0	0
16	6	(a)	(b)	15	(c)	30	(d)	54.3	1.3	140	68.9	6.8	7.0	0	0
17	5	(a)	(b)	19	58	27	(d)	16	0.4	84	68.9	7.2	6.5	0	0
18	11	(a)	(b)	25	(c)	29	(d)	.31	2.0	100	68	7.2	7.5	0	0
19	6	(a)	0.4	11	(c)	29	(d)	14.1	0.8	70	59	7.2	7.0	0	0
20	6	(a)	0.4	<10	(c)	40	(d)	2.2	0.5	70	62.6	7.0	7.5	0	0
21	6	1	(b)	41	(c)	35	(a)	65.5	1.3	95	66.2	7.0	7.0	0	0

C-8

- (a) Less than detectable limits of 1.0 mg/l
- (b) Less than detectable limits of 0.3 mg/l
- (c) Less than detectable limits of 50 g/l
- (d) Less than detectable limits of 10 g/l
- (e) Results for the following parameters were less than the detectable limits shown:
CN (0.1 mg/l), Phenol (0.1 mg/l), Cr⁺⁶ (50 µg/l), Pb (50 µg/l), Ni (50 µg/l),
Surfactants (0.1 mg/l).

TABLE C.5

SUMMARY OF WATER SAMPLE RESULTS FROM
MONITORING STATION NO. 004
(Hannah Rd.,) February 1979

Day	Lead (µg/l)	Tox (mg/l)	Oil & Grease (mg/l)	NH ₃ (mg/l)	NO ₂ (mg/l)	PO ₄ (mg/l)	Cd (µg/l)	Cr ⁺³ (µg/l)	Cr ⁺⁶ (µg/l)	Cu (µg/l)	Fe ⁺³ (µg/l)	Mn (µg/l)	Hg (µg/l)	Ni (µg/l)	Ag (µg/l)	Zn (µg/l)	Cu (mg/l)	Mg (mg/l)	K (mg/l)	Na (mg/l)	Cl ⁻ (mg/l)	SO ₄ ⁻² (mg/l)	Sulf-act-ante (mg/l)	Phenol (mg/l)	CM (mg/l)
7	110	35	(a)	6.0(b)	0.5	0.5	(d)	(e)	(e)	81	2.3	170	(e)	(e)	(d)	91	21	3	4	36	16	100	0.3	0.55 ^(c)	0
8	95	23	(a)	8.6(b)	0.5	0.5	(d)	5.2	(e)	36	2.0	150	(e)	(e)	(d)	69	22.5	3	5	37	20	95	0.4	1.1 ^(c)	0
9	20	5	0.4	4.7(b)	0.5	0.4	(d)	(e)	(e)	30	2.2	140	(e)	(e)	(d)	140	17	2	3	19	16	46	0.1	0.45 ^(c)	0
10	35	11	0.8	7.5(b)	0.4	0.4	(d)	(e)	(e)	32	2.2	150	(e)	50	(d)	89	20	2	4	32	24	63	0.2	0.05	0
11	11	5	(a)	4.0(b)	0.6	0.4	(d)	(e)	(e)	32	1.6	130	(e)	(e)	(d)	44	14	2	2	15	28	33	0.1	0.02	0
12	35	10	1.4	7.5(b)	0.5	0.5	13	(e)	57	39	1.0	57	(e)	(e)	(d)	44	10	<1	4	32	16	78	0.2	0.17	0
13	50	12	1.0	8.0(b)	0.4	0.5	(d)	57	57	110	2.4	100	(e)	(e)	(d)	130	17	2	4	37	16	85	0.4	1.5 ^(c)	0

(a) Less than detectable limits of 0.3 mg/l

(b) Exceeds MDEQS permit limits of 2.0 mg/l

(c) Exceeds MDEQS permit limits of 0.2 mg/l

(d) Less than detectable limits of 10 µg/l

(e) Less than detectable limits of 50 µg/l

TABLE C.6

SUMMARY OF WATER SAMPLE RESULTS FROM MONITORING STATION NO. 005
(Golf Course Lake), March 1979

Day	COD mg/l	TOC mg/l	Oil & Grease mg/l	PO ₄ mg/l	Cu µg/l	Fe µg/l	Hg µg/l	Zn µg/l	K mg/l	Na mg/l	Ca mg/l	CN mg/l
20	10	(a)	(b)	0.3	-	1,400	20	-	0.5	1.4	12.2	-
21	10	(a)	(b)	0.2	36	1,800	(d)	(e)	0.5	2.7	-	2.3
22	6	1	(b)	0.4	65	1,600	(d)	50	0.5	2.3	-	-
23	6	(a)	(b)	(c)	40	1,400	(d)	(e)	0.5	2.3	-	-
24	6	(a)	(b)	(c)	35	570	(d)	(e)	1.5	0.8	-	-
25	6	1	(b)	(c)	30	800	(d)	(e)	1.2	1.1	-	-
26	<5	(a)	5	(c)	<20	1,200	(d)	170	1.5	1.9	-	-

- (a) Less than detectable limits of 1.0 mg/l
- (b) Less than detectable limits of 0.3 mg/l
- (c) Less than detectable limits of 0.2 mg/l
- (d) Less than detectable limits of 5 µg/l
- (e) Less than detectable limits of 50 µg/l

(f) Results for the following parameters were less than the detectable limits shown:
NH₃ (0.2 mg/l), Cd (10 µg/l), Cr⁺³ (50 µg/l), Cr⁺⁶ (50 µg/l), Pb (50 µg/l),
and Ni (50 µg/l).

TABLE C.7
 SUMMARY OF WATER SAMPLE RESULTS FROM
 HORSE CREEK (HC) AND THE STABLE AREA (006)
 APRIL 1979

Day	COD (mg/l)	TOC (mg/l)	Oil & Grease (mg/l)
<u>Stable Area</u>			
2	15	5	(a)
3	(a)	4	(a)
4	(a)	4	(a)
5	10	4	(a)
6	6	3	(a)
7	6	(a)	(a)
8	6	3	(a)
<u>Horse Creek</u>			
9	15	0.7	(a)
10	10	3	(a)
11	15	4	(a)
12	5	4	(a)
13	5	5	(a)
14	10	5	(a)
15	5	3	(a)

(a) Less than detectable limits of 0.3 mg/l.

(b) Results for the following parameters were less than the detectable limits shown:

NH₃ (0.2 mg/l), PO₄ (0.2 mg/l) and surfactants (0.1 mg/l).

TABLE C.8
SUMMARY OF WATER SAMPLE RESULTS FROM
INDUSTRIAL WASTE TREATMENT PLANT ADDITION

Day	COD (mg/l)	TOC (mg/l)	NH ₃ (mg/l)	NO ₃ (mg/l)	PO ₄ (mg/l)	Surfac- tants (mg/l)	Phenol (mg/l)	CN (mg/l)	pH
1	30	13	7.2	0.5	3.1	0.2	0	0	7.2
2	10	2	3.2	1.9	3.5	0.1	0	0	7.4
3	30	13	8.0	0.3	4.1	0.1	0	0	7.2
4	28	13	4.0	0.8	3.5	0.1	0	0	7.4
5	28	11	3.5	1.0	2.8	0.2	0	0	7.2
6	15	10	2.5	1.2	2.5	0.1	0	0	7.4
7	30	13	4.0	0.9	2.0	0.2	0	0	7.2

- (a) Results for oil and grease were less than the detectable limit of 0.3 mg/l.
- (b) No sample results were given for the following parameters: Cd, Cr⁺³, Cr⁺⁶, Cu, Fe, Mn, Hg, Ni, Ag, Zn, Ca, Mg, K, Na, Cl⁻, SO₄

TABLE C.9

SUMMARY OF WATER SAMPLE RESULTS FROM MAJOR BASE LAKES,
August 8 to October 13, 1978

	DUCK LAKE			LUNA LAKE			SCOUT LAKE					
	No. of Samples	Min.	Max.	Mean	No. of Samples	Min.	Max.	Mean	No. of Samples	Min.	Max.	Mean
Cu, µg/l	11	0	0	-	4	0	0	-	4	0	0	-
Cr ⁺⁶ , µg/l	11	0	0	-	4	0	0	-	4	0	0	-
Cr ⁺³ , µg/l	11	0	0	-	4	0	0	-	4	0	0	-
NH ₃ , mg/l	11	0	0	-	4	0	0	-	4	0	0	-
NO ₃ , mg/l	11	0	0	-	4	0	0	-	4	0	0	-
NO ₂ , mg/l	11	0	0	-	4	0	0	-	4	0	0	-
PO ₄ , mg/l	11	0	0.4	0.12	4	0	0.18	0.05	4	0	0	-
Fe, µg/l	10	100	300	160	4	0	100	40	4	0	100	30
SO ₄ , mg/l	10	0	0	-	4	0	0	-	4	0	0	-
Ca, mg/l	1	10	10	10	1	5	5	5	1	5	5	5
Cl ⁻ , mg/l	1	2.5	2.5	2.5	1	2.5	2.5	2.5	1	2.5	-	-
Pb, µg/l	10	6.8	8.0	7.1	1	5.5	5.5	5.5	1	-	-	-

TABLE C.10

SUMMARY OF WATER SAMPLE RESULTS FROM THE WASTE TREATMENT PLANTS

August 8 - December 13, 1978

	Station 009 (Ind. Waste Treat. Pit #1)				Station 005 (End of San. Treat. Pit. No. 2 Pipe)				Station 004 (Hannah Road Ditch)			
	No. of Samples	Min.	Max.	Mean	No. of Samples	Min.	Max.	Mean	No. of Samples	Min.	Max.	Mean
Cu, µg/l	13	0	0	-	13	0	0	-	13	0	0	-
Cr ⁺⁶ , µg/l	13	0	0	-	13	0	0	-	13	0	0	-
Cr ⁺³ , µg/l	13	0	0	-	13	0	0	-	13	0	0	-
NH ₃ , mg/l	13	3	12.7	7.4	13	1.2	10.5	5.2	14	1.6	8.3	4.2
NO ₃ , mg/l	9	0.1	5.1	2.5	6	1	3	1.9	6	0.1	1.0	0.96
NO ₂ , mg/l	9	0.01	1.0	0.5	7	0.03	2.4	0.12	6	0	0.9	0.4
PO ₄ , mg/l	10	1.8	4.0	2.8	10	5	18	10.3	9	0.7	5.1	1.7
Fe, µg/l	12	200	500	370	13	50	210	130	9	0.6	1.2	1.0
SO ₄ , mg/l	6	40	80	65	7	15	18	15.4	6	20	50	37
Ca, mg/l	6	50	60	52.5	7	40	50	47.8	5	30	35	34
Cl, mg/l	7	18	30	22.3	7	20	25	22.8	5	25	30	28
PS, µg/l	7	6.8	7.4	7.2	7	7.2	7.4	7.3	6	5.5	6.8	6.4

TABLE C.11
EPA INTERIM PRIMARY AND PROPOSED SECONDARY
DRINKING WATER STANDARDS

PARAMETER	MAXIMUM LEVEL	
<u>A. Interim Primary</u>		
Arsenic	0.05	mg/l
Barium	1.0	mg/l
Cadmium	0.01	mg/l
Chromium (VI)	0.05	mg/l
Fluoride	1.4 to 2.4	mg/l
Lead	0.05	mg/l
Mercury	0.002	mg/l
Nitrate (as N)	10	mg/l
Selenium	0.01	mg/l
Silver	0.05	mg/l
Endrin	0.002	mg/l
Lindane	0.004	mg/l
Methoxychlor	0.1	mg/l
Toxyphene	0.005	mg/l
2,4-D	0.01	mg/l
2,4,5-TP Silvex	0.01	mg/l
Radium	5 pCi/l	
Gross Alpha	15 pCi/l	
Gross Beta	4 millirem/yr	
Turbidity	1 TU	
Coliform Bacteria	1/100 ml	
<u>B. Secondary</u>		
Chloride	250	mg/l
Copper	1	mg/l
Foaming Agents	0.5	mg/l
Hydrogen Sulfide	0.05	mg/l
Iron	0.3	mg/l
Manganese	0.05	mg/l
Sulfate	250	mg/l
Total Dissolved Solids	500	mg/l
Zinc	5	mg/l
Color	15 Color Units	
Corrosivity	Non-corrosive	
Odor	3 threshold Odor Number	
pH	6.5 to 8.5	

TABLE C.12
 ROBINS AIR FORCE BASE
 CURRENT PESTICIDES USED

Insecticides	Herbicides	Rodenticides
Avitral	Ansar	Zinc Phosphide Bait
Amdro	Borocil	Pinalyl Bait
Baygon	Diquat	Diphacinone Bait
Chlordane	Maintain	Strychnine Bait
Cyanogas	Retard	
Cygon	Round-Up	
Dursban	Spike	
Dibrom (Naled)	Velpar	
Diazinon	2,4-D	
Ficam		
Lindane		
Malathion		
Naptha		
DDVP		
Sevin		
D-Phenothrin		

Source: Robins AFB Bioenvironmental Engineering Files

TABLE C. 13

ANALYSIS OF SOIL SAMPLES COLLECTED FROM THE RADIOACTIVE
WASTE DISPOSAL AREA

Parameters	Units	Approximate Sample Location			
		100' from Site (Bottom of Hill)	Center of Site	20' from Site (Up Hill)	50' from Site (Down Grade)
Gross Alpha	pCi/g	20	26	20	20
Gross Beta	pCi/g	17	27	20	24
Potassium 40	pCi/g	.17	1.82	.97	1.24
Cesium 137	pCi/g	.084	1.59	.77	.30
Uranium 238	pCi/g	1.07	1.03	1.88	1.87
Radium 226	pCi/g	.91	1.26	1.35	1.66
Thorium 232	pCi/g	1.45	1.34	2.00	2.40
Cobalt 60	pCi/g		.070		

SOURCE: Base reports

APPENDIX D
MASTER LIST
INDUSTRIAL SHOPS

APPENDIX D
 MASTER LIST
 INDUSTRIAL SHOPS

Name	Present Location (Bldg. No.)	Handles Hazardous Materials	Generates Hazardous Wastes
<hr/>			
DIRECTORATE OF DISTRIBUTION (DS*)			
<hr/>			
Supply & Equip. Shed	28		
Supply & Equip. Shed	29		
LOX Storage	32		
Hydrogen Fluoride Bldg.	38		
Liq. Fluoride Pump Station	39		
LOX Storage	50		
Supply & Equipment Warehouse	59		
Liq. Fuel Pump Station	70		
Liq. Fuel Pump Station	72		
Liq. Fuel Pump Station	73		
Terminal Air Freight	127		
Supply & Issue Shipping	153		
(Name not listed)**	193		
POL Operations/Qual. Control	194	X	
Liq. Fuel Pump Station	195		
POL Operations/Qual. Control	196	X	
(Name not listed)	209		

* Office symbols used by the Air Force.
 ** Indicates no name for the facility was listed in the BEE records.
 X Indicates presence of hazardous materials or generation of hazardous waste.

APPENDIX D (CONTINUED)

Name	Present Location (Bldg. No.)	Handles Hazardous Materials	Generates Hazardous Wastes
Directorate of Distribution (Continued)			
(Name not listed)	211		
Supply & Equipment Warehouse	232		
Shop Shelter	(241-closed)		
Depot MAT Process	247		
Shop Shelter	248		
Logistics Facility Depot	300		
Warehouse Supply & Equip. Depot	301		
Vehicle Fueling Station	303		
Mag Storage	306		
Supply & Equipment Warehouse	309		
Supply & Equipment Warehouse	310		
Storage Igloo	311		
Storage Igloo	312		
Segregated Mag Storage	313		
Supply & Equip. Shed	320		
Supply & Equip. Shed	322		
Chemical Storage	327	X	X
Chemical Storage	328	X	
Bottled Gas Storage	329		
Bottled Gas Storage	330		
Bottled Gas Storage	331		
Supply & Equip Shed	334		

APPENDIX D (CONTINUED)

Name	Present Location (Bldg. No.)	Handles Hazardous Materials	Generates Hazardous Wastes
Directorate of Distribution (Continued)			
Supply & Equip Shed	334		
Supply & Equip Shed	335		
Supply & Equip. Shed	336		
Supply & Equip. Shed	337		
Supply & Equip. Shed	338		
Supply & Equip. Shed	339		
Supply & Equip. Shed	350		
Material Process. Depot	351		
Material Process. Depot	354	X	X
(Name not listed)	357		
Material Process Depot	364		
Material Process Depot	365		
Supply & Equipment Warehouse	366		
Supply & Equipment Warehouse	367		
Lumber Shed	372		
Material Process Depot	376		
Supply & Equipment Warehouse	380		
Supply & Equipment Warehouse	385		
Supply & Equipment Warehouse	602		
Material Process Depot	606		
Supply & Equipment Warehouse	641		

APPENDIX D (CONTINUED)

Name	Present Location (Bldg. No.)	Handles Hazardous Materials	Generates Hazardous Wastes
Directorate of Distribution (Continued)			
Supply & Equipment Warehouse	660		
(Name not listed)	10091		
(Name not listed)	10094		
(Name not listed)	10187		
(Name not listed)	10188		
DIRECTORATE OF MAINTENANCE (MA)			
Aircraft Division (MAB)			
Hydrogen Fluoride Bldg.	23	X	
Functional Testing	40	X	X
Nose Dock	44	X	X
Nose Dock	47	X	
Nose Dock	48	X	
Nose Dock	49	X	
Compress Air Bldg.	53		
Corrosion Control	54	X	X
Nose Dock	55	X	X
Paint Shop	89	X	X
Hazardous Storage	93	X	
(Old Corrosion Control)	(110)	(X)	(X)
Hazardous Storage	112	X	

APPENDIX D (CONTINUED)

Name	Present Location (Bldg. No.)	Handles Hazardous Materials	Generates Hazardous Wastes
------	------------------------------	-----------------------------	----------------------------

Aircraft Division (Continued)

(Name not listed)	115		
Aircraft Training Facility	120		
Non-Destructive Inspect.	125	X	
Welding	125		
C-141	125		
C-130	125		
F-15	125		
Radio Repair	125		
Engine Repair	125	X	X
Landing Gear	125	X	X
Tire Shop	125		
Sealant Shop	125	X	
(Name not listed)	145		
F-15 Maintenance	149	X	X
Hazardous Storage	151		

AIRBORNE ELECTRONICS DIVISION (MAI)

Surveillance & Inst. Shop	635		
Bomb Navigation	640	X	X
Radar Navigation	640	X	X
Weapons	640	X	X
Communications Shop	645	X	X
Fire Control Shop	645	X	X

APPENDIX D (CONTINUED)

Name	Present Location (Bldg. No.)	Handles Hazardous Materials	Generates Hazardous Wastes
<hr/>			
Airborne Electronics Division (Continued)			
<hr/>			
Electronic Warfare	645	X	
Air Cond. & Engr. Shop	647		
Boresight Shop	675		
<hr/>			
INDUSTRIAL PRODUCTS DIVISION (MAN)			
<hr/>			
Paint Shop	125	X	X
Life Support	128		
Hazardous Storage	132	X	
Pylon Shop	140		
Tubing & Cable	140		
F-15 Shop	140		
Parachute Shop	140		
Turret Shop	140	X	X
Electric Shop	140		
F-15 Pylon	140		
Pneudraulics	140	X	
Propeller Cleaning	140	X	X
Propeller Shop	140	X	X
Machine Shop	140		
Heat Treat Shop	140		
Electroplating Shop	142		X
<hr/>			

APPENDIX D (CONTINUED)

Name	Present Location (Bldg. No.)	Handles Hazardous Materials	Generates Hazardous Wastes
------	------------------------------	-----------------------------	----------------------------

Industrial Products Division (Continued)

Hydrostatic Testing	150	X	X
Battery Shop	150	X	X
(Name not listed)	154		
Physical Lab	165	X	
Chemical Lab	165	X	
Tubing & Cable	169		
Small Motor Repair	169		
Cleaning Shop	169	X	X
Metal Bond	169	X	
Forms and Patterns	169		
Small Motor Mfg.	169		
Plant Services	173	X	
Industrial X-ray	181	X	X
Fabric Shop	181		
Parachute Shop	181		
Paint Shop	605	X	X
Plastics Shop	670	X	X
Radome Strip	680	X	X

DIRECTORATE OF CONTRACTING AND MANUFACTURING (PM)

Maintenance Dock	67		
Aircraft Engine Shipping	148	X	
Precision Measurement Equip. Lab	162	X	X

APPENDIX D (CONTINUED)

Name	Present Location (Bldg. No.)	Handles Hazardous Materials	Generates Hazardous Wastes
<hr/> USAF HOSPITAL <hr/>			
X-ray Lab	700	X	
Dental Lab	700	X	
<hr/> 5 COMBAT COMMUNICATIONS GROUP (CCG) <hr/>			
(Name not listed)	600		
(Name not listed)	611		
Generator Shop	615		
Supply & Equipment Warehouse	651		
Vehicle Maintenance	655		
Chemical Storage	656		
Supply & Equipment Warehouse	658		
Supply & Equipment Warehouse	659		
Maintenance Facility	925		
(Name not listed)	948		
(Name not listed)	949		
(Name not listed)	950		
(Name not listed)	951		
Communications Shipping	962		
(Name not listed)	10000		
(Name not listed)	10023		
(Name not listed)	10070		

APPENDIX D (CONTINUED)

Name	Present Location (Bldg. No.)	Handles Hazardous Materials	Generates Hazardous Wastes
------	------------------------------	-----------------------------	----------------------------

5 Combat Communications Group (Continued)

(Name not listed)	10085		
(Name not listed)	10098		
(Name not listed)	10205		
(Name not listed)	10207		
(Name not listed)	10212-10218		

19 BOMBARDMENT WING (BW)

(Name not listed)	1		
Traffic Check House	6		
Ordinance Control Point	8		
(Name not listed)	9		
(Name not listed)	10		
Readiness Crew	12		
Traffic Check House	16		
Aircraft Maintenance Shipping	22		
Engine Test Cell	31	X	X
Fuel Cell Repair	59	X	X
Nose Dock	66		
Nose Dock	67		
(Name not listed)	69		
(Name not listed)	74		

APPENDIX D (CONTINUED)

Name	Present Location (Bldg. No.)	Handles Hazardous Materials	Generates Hazardous Wastes
<hr/> 19 Bombardment Wing (Continued) <hr/>			
Weapons Shop	75	X	
Propulsion Shop	76	X	
Environmental Systems	76		
Munitions Shop	76		
Multi-Maintenance Shops	79	X	
Corrosion Control	80	X	X
Tire Shop	81	X	
Aerospace Ground Equipment (AGE)	82	X	X
(Name not listed)	85	X	
Equipment Maintenance	86	X	
Munitions Shop	94		
SRAM Missile Shop	100		
(Name not listed)	10001		
(Name not listed)	10004		
(Name not listed)	10006		
(Name not listed)	10007		
(Name not listed)	10079		
(Name not listed)	10080		
(Name not listed)	10082		
(Name not listed)	10102		
(Name not listed)	10120		

APPENDIX D (CONTINUED)

Name	Present Location (Bldg. No.)	Handles Hazardous Materials	Generates Hazardous Wastes
------	------------------------------	-----------------------------	----------------------------

1926 COMMUNICATIONS INSTALLATION GROUP (CIG)

(Name not listed)	10148-10154		
(Name not listed)	3		
(Name not listed)	19		
(Name not listed)	26	X	
Aircraft Maintenance	46		
Facility Depot	56		
Communications Center	161		
Base Communications	225		
(Name not Listed)	608		
Vehicle Maintenance	978		
Instrument Repair	1684	X	

2853 AIR BASE GROUP (ABG)

Graphics Services	321	X	
Photo Lab	321	X	X
BX Gas Station	922	X	X
Auto Hobby Shop	985	X	X
Fuel Vehicle Repair	190	X	X
Vehicle Maintenance	302	X	X
Paint & Body Shop	304	X	X
Auto Maintenance Shop	307	X	X

APPENDIX D (CONTINUED)

Name	Present Location (Bldg. No.)	Handles Hazardous Materials	Generates Hazardous Wastes
<hr/>			
2853 CIVIL ENGINEERING SQUADRON (CES)			
<hr/>			
Tire Shop	308	X	
Fire Training	5	X	
Fire Training	7	X	
Fuel Tank Repair	63	X	
Steam Facility	83		
Fire Station	109	X	
Indus. Waste Treat. Plant (IWTP)	141	X	X
IWTP	147		
Steam Plant	177		
Metal Maintenance Shop	270		
Paint Shop	272	X	X
Plumbing Shop	272		
Refrig. Shop	272		
Structural Shop	272		
Electric Shop	273		
Paint Shop	275	X	X
Generator Shop	286		
Entomology Unit	295, 296	X	
Sludge Dewatering	352	X	X
Grounds Shop	591, 593	X	X
<hr/>			

APPENDIX E

PHOTOGRAPHS

**Impact
Sled
Testing
Facility**

**Bulk
Fuel
Storage
Tanks**

**Landfill
No. 1**



LANDFILL No. 1

**Landfill
No. 2**

**Sludge
Lagoon**

**Landfill
No. 4**



**LANDFILLS No. 2 & No. 4
and SLUDGE LAGOON**

**Sludge
Lagoon**



**Landfill
No. 4**

SLUDGE LAGOON

**Location
of
Disposal
Trench**




HAZARDOUS WASTE BURIAL SITE



Location
of
Disposal
Trench

HAZARDOUS WASTE BURIAL SITE




Fire
Protection
Training
Area
No. 4

FIRE PROTECTION TRAINING AREA NO. 4

**Estimated Location of
Fire Protection Training Area No. 2**


**Dog
Kennels**



**FIRE PROTECTION
TRAINING AREA No. 2**

**Landfill
No. 3**

**Luna
Lake**



LANDFILL No. 3

APPENDIX F
WATER SUPPLY WELL LOGS

- City of Warner Robins
- Robins AFB

ENVIRONMENTAL PROTECTION DIVISION
WATER SUPPLY SECTION
270 WASHINGTON STREET, S.W.
ATLANTA, GEORGIA 30334

WELL DATA SHEET FOR PUBLIC WATER SYSTEM
(TO BE COMPLETED BY WATER WELL CONTRACTOR)

OF WATER SYSTEM: Warner Robins, Ga - Well No. 1-A COUNTY: Houston
LOCATED AT No. 1 Water plant TYPE WATER SYSTEM: COMMUNITY NON-COMMUNITY
OWNER City of Warner Robins, GA DRILLER Rowe Drilling Co., Inc.
ADDRESS P.O. Box 1468, Warner Robins, Ga 31093 ADDRESS P.O. Box 1363, Tallahassee, FL 32302
PHONE _____ PHONE (904) 576-1271 LIC. NO.: 72

WELL DESCRIPTION

DATE DRILLED: 6/8/81
TOTAL DEPTH: 540 FT. **A**
TYPE DRILLING (INDICATE):
ROTARY PERCUSSION OTHER
HOLE DIAMETER
SIZE 22 IN. FROM 0 FT. TO 120 FT.
SIZE 25 IN. FROM 120 FT. TO 540 FT.
SIZE _____ IN. FROM _____ FT. TO _____ FT.
(USE ADDITIONAL SHEETS IF NECESSARY)

CASING RECORD
TYPE MATERIAL Black Steel
WALL THICKNESS .375
WEIGHT/FOOT _____
SIZE 26 IN. FROM 0 FT. TO 120 FT.
SIZE 16 IN. FROM 0 FT. TO 255 FT.
SIZE 12 IN. FROM 255 FT. TO 540 FT.
(USE ADDITIONAL SHEETS IF NECESSARY)

WELL SCREEN
TYPE MATERIAL 304 Stainless Steel
SIZE 12 IN. FROM 340 FT. TO 350 FT.
SIZE 12 IN. FROM 320 FT. TO 380 FT.
SIZE 12 IN. FROM 420 FT. TO 430 FT.
SIZE 12 IN. FROM 440 FT. TO 460 FT.
SIZE 12 IN. FROM 470 FT. TO 490 FT.
SIZE 12 IN. FROM 510 FT. TO 530 FT.
WAS SLOT SIZE DETERMINED BY SIEVE ANALYSIS:
YES NO

GROUTING
TYPE GROUT Neat Portland
APPLIED BY PRESSURE: YES NO
FROM 120 FT TO 0 FT
FROM _____ FT. TO _____ FT.

STATIC WATER LEVEL 129 FT.
PUMPING WATER LEVEL: 149 FT. AT 1557 GPM

TEST PUMP DATA

DATE TESTED: June 8 & 9, 1981
PUMPED BAILED ESTIMATED
PUMP RATED: 4000 GPM 217 HP
TOTAL CONTINUOUS HRS. TESTED: 24
DID WATER LEVEL STABILIZE: YES NO
HRS. RUN BEFORE STABILIZATION 1
YIELD 1557 GPM AFTER 24 HRS. OF CONTINUOUS PUMPING
DISCHARGE PRESSURE: 0 PSI
WATER LEVEL BEFORE TEST: 129 FT.
TOTAL DRAWDOWN: 16 FT.
(ATTACH COPY OF DRAWDOWN MEASUREMENTS)
SPECIFIC CAPACITY: 62.5 GPM/FT.
NO. MINUTES FOR WELL TO RECOVER: _____
WAS WELL DEVELOPED AND DISINFECTED: YES NO
WERE UNTREATED WATER SAMPLES COLLECTED
FOR BACTI: YES NO
FOR CHEMICAL: YES NO

PERMANENT PUMP DATA (BY CONTRACTOR OR OWNER)

PUMP TYPE Perless OUTLET SIZE 10 IN.
POWERED BY: 150 HP
RATE: 1500 GPM
TOTAL DYNAMIC HEAD: 216 FT.
PUMP SET AT: 200 FT. w/30 Ft. Tail Pipe
PUMP DISINFECTED: YES NO
DEEP WELL AIR LINE, TYPE MATERIAL: Galv
LENGTH 200 FT.
ACCESS PORT, DIA.: 2 IN.

WELL LOG

1-A

FROM FEET	TO FEET	TYPE MATERIAL ENCOUNTERED	REMARKS	INDICATE WATER BEARING ZONES
0	20	red clay		
20	33	coarse sand, red		
33	45	brown coarse sand		
45	82	clay		
82	86	coarse sand		
89	110	fine & coarse sand		
110	122	clay		
122	164	coarse sand		
164	190	red coarse sand		
190	205	brown coarse sand & clay		
205	208	clay		
208	286	coarse sand		
286	294	clay		
294	307	coarse sand, little red clay		
307	317	clay		
317	372	coarse sand		
372	437	sand		
437	470	coarse sand		
470	480	coarse sand, little clay		
480	523	sand		
523	538	coarse sand, little clay		
538	540	clay		
540	566	coarse sand, little clay		
566	588	coarse sand, very little clay		
588	605	coarse sand, very little clay		

(If More Space is Required, Use Additional Sheet)

THIS WELL WAS DRILLED ACCORDING TO THE RULES FOR SAFE DRINKING WATER (CHAPTER 391-3-5) OF THE GEORGIA DEPARTMENT OF NATURAL RESOURCES AND THE INFORMATION ON THIS FORM IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE

SIGNED
WATER WELL CONTRACTOR'S SIGNATURE

LIC. NO.: 72

DATE 6/9/81

WELL COMPLETED
FORM TO:

2A

GEORGIA DEPARTMENT OF NATURAL RESOURCES
ENVIRONMENTAL PROTECTION DIVISION
WATER SUPPLY SECTION
270 WASHINGTON STREET, S.W.
ATLANTA, GEORGIA 30334

WELL DATA SHEET FOR PUBLIC WATER SYSTEM
(TO BE COMPLETED BY WATER WELL CONTRACTOR)

EPD Project No.
79-E-WS-14

NAME OF WATER SYSTEM: City of Warner Robins, Georgia COUNTY: Houston
LOCATED AT: Warner Robins TYPE WATER SYSTEM: COMMUNITY NON-COMMUNITY
OWNER: City of Warner Robins DRILLER: Layne Atlantic Company
ADDRESS: _____ ADDRESS: Post Office Box 669, Albany, Georgia
PHONE: _____ PHONE: 912/435-8338 LIC. NO.: 14

"City Well No. 2-A - South Pleasant at City Maintenance Yard"

WELL DESCRIPTION

DATE DRILLED: May 7, 1979
TOTAL DEPTH: 580 FT.
TYPE DRILLING (INDICATE):
ROTARY PERCUSSION _____ OTHER _____

PIPE DIAMETER

SIZE: 32 IN., FROM 0 FT. TO 125 FT.
SIZE: 25 IN., FROM 125 FT. TO 510 FT.
SIZE: _____ IN., FROM _____ FT. TO _____ FT.
(USE ADDITIONAL SHEETS IF NECESSARY)

CASING RECORD

PIPE MATERIAL: Black Steel pipe
WALL THICKNESS: 0.375 Sch. 40
WEIGHT/FOOT: Schedule 40 P.E.
SIZE: 26 IN., FROM 0 FT. TO 125 FT.
SIZE: 16 IN., FROM 0 FT. TO 250 FT.
SIZE: 12 IN., FROM 250 FT. TO 510 FT.
(USE ADDITIONAL SHEETS IF NECESSARY)

WELL SCREEN

PIPE MATERIAL: Stainless Steel Type 304
SIZE: 12 IN., FROM 274 FT. TO 284 FT.
SIZE: 12 IN., FROM 300 FT. TO 310 FT.
SIZE: 12 IN., FROM 400 FT. TO 440 FT.
SIZE: 12 IN., FROM 478 FT. TO 488 FT.
SIZE: 12 IN., FROM 495 FT. TO 500 FT.
WAS SLOT SIZE DETERMINED BY SIEVE ANALYSIS:
YES NO _____

ROUTING

TYPE GROUT: Cement
APPLIED BY PRESSURE YES NO _____
FROM 0 FT TO 125 FT.
THICKNESS: _____ FT TO _____ FT.

STATIC WATER LEVEL: 132 FT.
PUMPING WATER LEVEL: 235 FT. AT 1,613 GPM

TEST PUMP DATA

DATE TESTED: June 13, 1979
PUMPED BAILED _____ ESTIMATED _____
PUMP RATED: 1613 GPM 150 HP
TOTAL CONTINUOUS HRS. TESTED: 24
DID WATER LEVEL STABILIZE: YES NO _____
HRS. RUN BEFORE STABILIZATION: 10
YIELD: 1,613 GPM AFTER 24 HRS. OF CONTINUOUS PUMPING
DISCHARGE PRESSURE: 0 PSI
WATER LEVEL BEFORE TEST: 132 FT.
TOTAL DRAWDOWN: 103 FT.
(ATTACH COPY OF DRAWDOWN MEASUREMENTS)
SPECIFIC CAPACITY: 15.66 GPM/FT.
NO. MINUTES FOR WELL TO RECOVER: 2-hrs
WAS WELL DEVELOPED AND DISINFECTED: YES NO _____
WERE UNTREATED WATER SAMPLES COLLECTED
FOR BACTI: YES NO _____
FOR CHEMICAL: YES NO _____

PERMANENT PUMP DATA (BY CONTRACTOR OR OWNER)

PUMP TYPE: Layne OUTLET SIZE: 8 IN.
POWERED BY: 40 HP
RATE: 600+ GPM
TOTAL DYNAMIC HEAD: 202 FT.
PUMP SET AT: 160 FT.
PUMP DISINFECTED: YES NO _____
DEEP WELL AIR LINE, TYPE MATERIAL: 1/2" Galv.
LENGTH: 160 FT.
ACCESS PORT, DIA.: 1 IN.

4831

COMPLETE WELL LOG ON REVERSE SIDE

WELL LOG

2A

FROM FEET	TO FEET	TYPE MATERIAL ENCOUNTERED	REMARKS	INDICATE WATER BEARING ZONES
0	15	Red Clay		
15	45	Red Clay & White Clay		
45	60	White Clay & fine sand		
60	75	Coarse white sand & clay		
75	94	Coarse white sand & little clay		
94	109	Coarse sand		
109	123	White & red clay - slow		
123	168	Coarse white sand		
168	228	White coarse sand		
228	241	Coarse sand with little clay streaks		
241	256	Coarse sand and little white clay		
256	270	Fine pepper sand - slow		
270	285	Fine sand and red clay		
285	300	Fine sand & little clay streaks		
300	315	Coarse sand with little clay streaks		
315	328	Sand with little clay streaks		
328	343	Coarse sand & clay streaks		
343	359	Sand - little clay streaks - slow		
359	372	Sand with little clay streaks		
372	386	Coarse sand with little clay streaks		
386	400	White sand little clay streaks		
400	415	Sand little white clay		

(If More Space is Required, Use Additional Sheet)

THIS WELL WAS DRILLED ACCORDING TO THE RULES FOR SAFE DRINKING WATER (CHAPTER 391-3-5) OF THE GEORGIA DEPARTMENT OF NATURAL RESOURCES AND THE INFORMATION ON THIS FORM IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE

SIGNED
WATER WELL CONTRACTOR'S SIGNATURE

DATE

John S. Cobb Dist. Major LIC. NO. 14
5/20/60

LAYNE ATLANTIC COMPANY
 P. O. BOX 669
 ALBANY, GEORGIA 31702

WELL LOG

2A

FROM FEET	TO FEET	TYPE MATERIAL ENCOUNTERED	REMARKS	INDICATE WATER BEARING ZONES
415	430	Coarse sand and little white clay - med.		
430	444	White sand with little clay streaks		
444	460	Coarse white sand		
460	473	Yellow fine sand and clay		
473	488	Sand & red clay - slow		
488	502	Coarse sand little clay - med.		
502	532	Fine white sand - tight		
532	548	Fine white sand & clay streaks		
548	561	Fine white sand & clay - med.		
561	580	Fine sand & clay - slow		

(If More Space is Required, Use Additional Sheet)

THIS WELL WAS DRILLED ACCORDING TO THE RULES FOR SAFE DRINKING WATER (CHAPTER 391-3-5) OF THE GEORGIA DEPARTMENT OF NATURAL RESOURCES AND THE INFORMATION ON THIS FORM IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE.

SIGNED: [Signature] LIC NO.: 14
 WATER WELL CONTRACTOR'S SIGNATURE

DATE: 3/2/89

LAYNE ATLANTIC COMPANY
 P. O. BOX 649
 ALBANY, GEORGIA 31702

DEPARTMENT OF NATURAL RESOURCES
STATE OF GEORGIA
APPLICATION FOR A PERMIT TO USE GROUNDWATER
PART B - WELL DATA

Submit one (1) Form for Each Well

(Print or Type all Information)

APPLICANT CITY OF WARNER ROBINS

WELL NO. 3 (Key to Attached Location Map) Ground Elevation _____ ft.
Latitude 32°36'43" N Longitude 83°36'46" W (if available)

WELL CONSTRUCTION DESCRIPTION EXISTING PROPOSED

Name of Aquifer(s) being or to be Utilized Tuscaloosa Group

TYPE DRILLING (Indicate)

Rotary
 Percussion Total Depth 415 ft.
 Bored Static Water Level 105 Ft.

DRILL HOLE DIAMETER

From 0 ft., to 97 ft., 26 in.
From 0 ft., to 415 ft., 25 in.
From _____ ft., to _____ ft., _____ in.
From _____ ft., to _____ ft., _____ in.
From _____ ft., to _____ ft., _____ in.

CASING RECORD

Type Material Steel
Wall Thickness 0.312, 0.375, 0.365 in.
Weight/Foot 65.71, 49.56, 40.48 Lb.
Size 20 in. from 0 ft., to 97 ft.
Size 12 in. from 0 ft., to 200 ft.
Size 10 in. from 200 ft., to 415 ft.
Size _____ in. from _____ ft., to _____ ft.
Size _____ in. from _____ ft., to _____ ft.

WELL SCREEN

Type Material Stainless Steel
Size 10 in. from 275 ft., to 295 ft.
Size 10 in. from 360 ft., to 370 ft.
Size 10 in. from 390 ft., to 405 ft.
Size _____ in. from _____ ft., to _____ ft.
Size _____ in. from _____ ft., to _____ ft.

Date Drilled March 1961
Date to be Drilled _____
Driller Layne-Atlantic Co.

GROUTING: Yes No

Type Pressure (cement) _____
From 97 ft., to 0 ft.
From _____ ft., to _____ ft.
From _____ ft., to _____ ft.

TEST PUMP DATA

Pumped Test _____ Bailed _____
Estimated _____ Actual Test _____
Date Tested Feb. 24, 1961
Pump Rated 1000/1500 GPM 75 HP
Test Yield _____ GPM After 5 & 5 hrs. of pumping
Water Level before Test 105 ft.
Drawdown 33/53 ft.
Specific Capacity 30.3 / 28.3 GPM/ft.

PERMANENT PUMP DATA (if available)

Pump Type Deep Well Turbine
Outlet Size 8"
Powered by Electric Motor
Horsepower 75
Rate 1000 GPM
Pumping Level 138/158 Ft.
Average Hours Pumped Per Day _____

NOTE: Detailed well construction specifications of a proposed well may be required by the Division upon review of the submitted application.

Complete WELL LOG on reverse side, if available.

WELL LOG

3

TO FEET	TYPE MATERIAL ENCOUNTERED	REMARKS	INDICATE WATER BEARING ZONES
1	Top Soil		
5	Yellow Sandy Clay		
14	Red Clay		
22	Med. Coarse Sand		
32	White Clay W/Sand - Slow		
49	White Clay - Slow		
58	Coarse Sand - Thin Stks White Clay		
72	Coarse Sand		
96	Clay W/Stks Sand		
102	Clay - Slow		
108	Clay W/ Stks Sand		
114	Clay - Slow		
146	Coarse White Sand - Soft		
149	Clay		
158	Coarse White Sand - Soft		
161	Yellow Clay		
194	Coarse Sand W/Thin Stks of Clay		
198	Yellow Clay - Slow Drilling		
218	Med. Coarse Sand - Soft		
220	Streaks of Clay		
238	Med. Coarse Sand - Soft		
240	Streaks of Clay		

(If More Space is Required, Use Additional Sheet)

The above information is true and correct to the best of my knowledge.

Signed _____ Title _____

Date _____

No. 3

TO FEET	TYPE MATERIAL ENCOUNTERED	REMARKS	INDICATE WATER BEARING ZONES
257	Med. Coarse Sand - Soft		
265	Lavender Clay - Slow		
337	Med. Coarse Sand - Soft		
399	Med. Coarse Sand W/ Thin Stks of Clay		
400	Streaks of Clay		
412	Med. Coarse Sand - Soft		
425	White Clay - Slow Drilling		
433	Med. Coarse Sand - Soft		
440	White Clay - Slow Drilling		
465	Med. Coarse Sand W/ Stks of Clay		
478	White Clay - Slow Drilling		

(If More Space is Required, Use Additional Sheet)

The above information is true and correct to the best of my knowledge.

Signed _____ Title _____

Date _____

DEPARTMENT OF NATURAL RESOURCES
STATE OF GEORGIA
APPLICATION FOR A PERMIT TO USE GROUNDWATER
PART B - WELL DATA

Submit one (1) Form for Each Well

(Print or Type all Information)

APPLICANT CITY OF WARNER ROBINS

WELL NO. 4 (Key to Attached Location Map) Ground Elevation _____ ft.
Latitude 32°36'29"N Longitude 83°36'55"W (if available)

WELL CONSTRUCTION DESCRIPTION EXISTING PROPOSED

Name of Aquifer(s) being or to be Utilized Tuscaloosa Group

TYPE DRILLING (Indicate)

Rotary
Percussion Total Depth 390 ft.
Bored Static Water
Level 122 Ft.

DRILL HOLE DIAMETER

From 0 ft., to 60 ft., 26 in.
From 0 ft., to 390 ft., 25 in.
From _____ ft., to _____ ft., _____ in.
From _____ ft., to _____ ft., _____ in.
From _____ ft., to _____ ft., _____ in.

CASING RECORD

Type Material Steel
Wall Thickness 0.312, 0.375 in.
Weight/Foot 65.71, 49.56 Lb.
Size 20 in. from 0 ft., to 60 ft.
Size 12 in. from 0 ft., to 390 ft.
Size _____ in. from _____ ft., to _____ ft.
Size _____ in. from _____ ft., to _____ ft.
Size _____ in. from _____ ft., to _____ ft.

WELL SCREEN

Type Material Stainless Steel
Size 12 in. from 240 ft., to 250 ft.
Size 12 in. from 320 ft., to 330 ft.
Size 12 in. from 360 ft., to 380 ft.
Size _____ in. from _____ ft., to _____ ft.
Size _____ in. from _____ ft., to _____ ft.

Date Drilled February 1960
Date to be Drilled _____
Driller Layne-Atlantic Co.

GROUTING: Yes No

Type Pressure (Cement)
From 60 ft., to 0 ft.
From _____ ft., to _____ ft.
From _____ ft., to _____ ft.

TEST PUMP DATA

Pumped Test _____ Bailed _____
Estimated _____ Actual Test _____
Date Tested Feb. 20, 1960
Pump Rated 1500 GPM 100 HP
Test Yield 1559 GPM After 12 hrs. of pumping
Water Level before Test 122 ft.
Draudown 60 ft.
Specific Capacity 25 GPM/ft.

PERMANENT PUMP DATA (if available)

Pump Type Deep Well Turbine
Outlet Size 10 in.
Powered by Electric Motor
Horsepower 100
Rate 1500 GPM
Pumping Level 182 Ft.
Averag. Hours Pumped Per Day _____

NOTE: Detailed well construction specifications of a proposed well may be required by the Division upon review of the submitted application.

Complete WELL LOG on reverse side, if available.

WELL LOG

4

DOWN FEET	TO FEET	TYPE MATERIAL ENCOUNTERED	REMARKS	INDICATE WATER BEARING ZONES
0	3	Fill Dirt		
3	23	Sandy Red Clay		
23	42	Sand w/stks of Clay		
42	47	Clay - Slow		
47	56	Sand - Soft		
56	73	Clay - Slow		
73	97	Coarse Sand - Soft		
97	106	Clay - Medium		
106	124	Clay w/stks of Sand - Soft		
124	154	Coarse White Sand - Soft		
154	178	Coarse White Sand w/thin stks of Clay - Soft		
178	201	Coarse Reddish Sand - Soft		
201	211	Clay - Medium Drilling		
211	232	Coarse Reddish Sand - Soft		
232	236	Clay - Soft		
236	261	Medium Coarse Reddish Sand - Soft		
261	264	Clay - Medium		
264	275	Med. Coarse Sand - Soft - Cut Rough		
275	292	Med. Coarse Sand - Soft		
292	301	Clay - Slow Drilling		
301	316	Med. Coarse Sand - Soft		
316	318	Clay - Med. Drilling		

(If More Space is Required, Use Additional Sheet)

The above information is true and correct to the best of my knowledge.

Signed _____ Title _____
 Date _____

No. 4.

TO FEET	TYPE MATERIAL ENCOUNTERED	REMARKS	INDICATE WATER BEARING ZONES
343	Coarse Sand - Soft- Cut Rough		
346	Clay - Med. Drilling		
360	Coarse Sand W/Stks of Clay- Soft		
380	Coarse White Sand - Soft		
384	Sandy Clay - Soft		
403	Coarse White Sand - Soft		
405	Clay - Med. Drilling		
432	Coarse White Sand - Soft - Cut Rough		
438	Clay Med. Drilling		
485	Med. Coarse White Sand w/stks of Clay - Soft		
491	White Clay - Med. Drilling		

(If More Space is Required, Use Additional Sheet)

The above information is true and correct to the best of my knowledge.

 Title

Date _____

116

ENVIRONMENTAL PROTECTION DIVISION
 DEPARTMENT OF NATURAL RESOURCES
 STATE OF GEORGIA
 APPLICATION FOR A PERMIT TO USE GROUNDWATER
 PART 8 - WELL DATA

Submit one (1) Form for Each Well

(Print or Type all Information)

APPLICANT CITY OF WARNER ROBINS

WELL NO. 5 (Key to Attached Location Map) Ground Elevation 431.1 ft.
 Latitude 32°35'44"N Longitude 83°38'42"W (if available)

WELL CONSTRUCTION DESCRIPTION EXISTING PROPOSED

Name of Aquifer(s) being or to be Utilized Tuscaloosa Group

TYPE DRILLING (Indicate)

Rotary
 Percussion Total Depth 422 ft.
 Bored Static Water Level 132 Ft.

DRILL HOLE DIAMETER

From 0 ft., to 94 ft., 26 in.
 From 0 ft., to 422 ft., 25 in.
 From ft., to ft., in.
 From ft., to ft., in.
 From ft., to ft., in.

CASING RECORD

Type Material Steel
 Wall Thickness 0.312, 0.375 In.
 Weight/Foot 65.71, 49.56 Lb.
 Size 20 in. from 0 ft., to 94 ft.
 Size 12 in. from 0 ft., to 422 ft.
 Size in. from ft., to ft.
 Size in. from ft., to ft.
 Size in. from ft., to ft.

WELL SCREEN

Type Material Stainless Steel
 Size 12 in. from 235 ft., to 245 ft.
 Size 12 in. from 270 ft., to 280 ft.
 Size 12 in. from 349 ft., to 354 ft.
 Size 12 in. from 366 ft., to 371 ft.
 Size 12 in. from 392 ft., to 412 ft.

Date Drilled November 1962
 Date to be Drilled
 Driller Layne-Atlantic Co.

GROUTING: Yes No

Type Pressure (Cement)
 From 94 ft., to 0 ft.
 From ft., to ft.
 From ft., to ft.

TEST PUMP DATA

Pumped Test Bailed
 Estimated Actual Test
 Date Tested November 27, 1962
 Pump Rated 1100 GPM 75 HP
 Test Yield GPM After 24 hrs. of pumping
 Water Level before Test 132 ft.
 Drawdown 24 ft.
 Specific Capacity 45.8 GPM/ft.

PERMANENT PUMP DATA (if available)

Pump Type Deep Well Turbine
 Outlet Size 8"
 Powered by Electric Motor
 Horsepower 75
 Rate 1000 GPM
 Pumping Level 156 Ft.
 Average Hours Pumped Per Day

NOTE: Detailed well construction specifications of a proposed well may be required by the Division upon review of the submitted application.

Complete WELL LOG on reverse side, if available.

WELL LOG
5

FROM FEET	TO FEET	TYPE MATERIAL ENCOUNTERED	REMARKS	INDICATE WATER BEARING ZONES
0	1	Top Soil		
1	10	Red Clay		
10	20	Red Sandy Clay		
20	30	Dark Red Clay		
30	35	Coarse Red Sandy Clay		
35	44	Red Clay		
44	51	Fine Red Sandy Clay		
51	59	Fine Sand w/Stks of White Clay		
59	74	Fine Sand w/Heavy Stks of Clay		
74	84	Med Coarse Sand		
84	94	Pink & White Clay (Med. - Slow)		
94	105	Red Clay (Med.-Slow)		
105	139	White Clay		
139	148	Sand		
148	155	Coarse Sand w/White Clay		
155	185	Coarse Sand w/Stks of Clay		
185	216	Coarse Sand w/Stks of White Clay		
216	258	Med. Coarse Sand w/Very Little Clay		
258	298	Coarse Sand w/Iron Granules		
298	308	White Clay - Slow		
308	321	Red & White Clay - Slow		
321	332	White Clay - Slow		

(If More Space is Required, Use Additional Sheet)

The above information is true and correct to the best of my knowledge.

Signed _____ Title _____

Date _____

obtained

WELL LOG

5

DEPTH FEET	TO FEET	TYPE MATERIAL ENCOUNTERED	REMARKS	INDICATE WATER BEARING ZONES
32	339	Pink & White Clay w/Stks of Silt Sand		
39	370	Coarse White Sand w/Stks of Clay		
70	390	Coarse White Sand w/Possible Clay Stks		
90	400	Med. Coarse White Sand w/Stks of White Clay		
00	430	Coarse Sand w/ Stks of Clay		
30	460	Clay w/Stks of Coarse Sand		

(If More Space is Required, Use Additional Sheet)

The above information is true and correct to the best of my knowledge.

Signed _____ Title _____
Date _____

ENVIRONMENTAL PROTECTION DIVISION
DEPARTMENT OF NATURAL RESOURCES
STATE OF GEORGIA
APPLICATION FOR A PERMIT TO USE GROUNDWATER
PART B - WELL DATA

No. 6

Submit one (1) Form for Each Well

(Print or Type all Information)

APPLICANT CITY OF WARNER ROBINS

WELL NO. 6 (Key to Attached Location Map) Ground Elevation 393 + ft.
Latitude 32°37'58"N Longitude 83°37'42"W (if available)

WELL CONSTRUCTION DESCRIPTION EXISTING PROPOSED

Name of Aquifer(s) being or to be Utilized Tuscaloosa Group

TYPE DRILLING (Indicate)

Rotary
 Percussion Total Depth 435 ft.
 Bored Static Water Level 116 Ft.

DRILL HOLE DIAMETER

From 0 ft., to 70 ft., 32 in.
From 0 ft., to 435 ft., 25 in.
From ft., to ft., in.
From ft., to ft., in.
From ft., to ft., in.

CASING RECORD

Type Material Steel
Wall Thickness 0.312, 0.375, 0.375 in.
Weight/Foot 85.73, 62.58, 49.56 Lb.
Size 26 in. from 0 ft., to 70 ft.
Size 16 in. from 0 ft., to 230 ft.
Size 12 in. from 230 ft., to 435 ft.
Size in. from ft., to ft.
Size in. from ft., to ft.

WELL SCREEN

Type Material Stainless Steel
Size 12 in. from 250 ft., to 260 ft.
Size 12 in. from 290 ft., to 310 ft.
Size 12 in. from 390 ft., to 400 ft.
Size 12 in. from 415 ft., to 425 ft.
Size in. from ft., to ft.

Date Drilled July 1968
Date to be Drilled
Driller Layne-Atlantic

GROUTING: Yes No

Type Pressure (Cement)
From 70 ft., to 0 ft.
From ft., to ft.
From ft., to ft.

TEST PUMP DATA

Pumped Test Bailed
Estimated 1050 GPM
Date Tested July 16, 1968
Pump Rated 1040 GPM 100 HP
Test Yield GPM After 24 hrs. of pumping
Water Level before Test 116 ft.
Drawdown 15 ft.
Specific Capacity 69.3 GPM/ft.

PERMANENT PUMP DATA (if available)

Pump Type Deep Well Turbine
Outlet Size 8"
Powered by Electric Motor
Horsepower 100
Rate 1100 GPM
Pumping Level 131 Ft.
Average Hours Pumped Per Day

NOTE: Detailed well construction specifications of a proposed well may be required by the Division upon review of the submitted application.

Complete WELL LOG on reverse side, if available.

WELL LOG

6

FROM FEET	TO FEET	TYPE MATERIAL ENCOUNTERED	REMARKS	INDICATE WATER BEARING ZONES
0	1	Top Soil		
1	18	Sand Clay		
18	32	White Clay		
32	47	White Clay & Sand		
47	64	Red Clay W/Little Sand		
64	74	Clay		
74	122	Coarse Sand		
122	130	Clay - White		
130	155	Coarse Sand W/ Stks Clay		
155	180	Med. Coarse Sand		
180	185	White Clay		
185	215	Med. Coarse Sand		
215	224	Clay		
224	281	Med. Coarse Sand		
281	296	Sand & Clay		
296	341	Med. Coarse Sand W/Little Stks of White Clay		
341	357	Med. Coarse Sand W/Some White Clay		
357	369	Coarse Sand		
369	385	Med. Coarse Sand		
385	393	Sand W/Lots of Clay - Clay Washes Out		
393	435	Coarse Sand - Little Clay		
435	464	Coarse Sand W/ Stks of White Clay		

(If More Space is Required, Use Additional Sheet)

The above information is true and correct to the best of my knowledge.

Signed _____ Title _____

Date _____

No 7
10-11

Georgia Department of Public Health
Water Supply Service
47 Trinity Avenue, S. W.
Atlanta, Georgia 30334

DO NOT WRITE	
CLASS II	
CLASS III	
INDIVIDUAL	

WELL DATA SHEET
For
PUBLIC OR COMMUNITY WATER SUPPLY SYSTEMS OR INDIVIDUAL WATER SUPPLY

Well No. 7 (Water Plant No. 3):

INSTRUCTIONS:

Name of Water System: Warner Robins, Georgia Location Arizona Street County Houston

Type: Municipal I ; Subdivision _____ No of Lots _____ ; Mobile Homes _____ or Trailer Parks _____
No of Lots _____ ; Industrial _____ ; Commercial _____ ; Individual _____ ; Other _____

Owner City of Warner Robins Driller Singer-Layne Atlantic Company

Address _____ Address Albany, Georgia

Date Drilling Started JANUARY 1972 Date Completed February 1972

WELL DESCRIPTION

TYPE DRILLING (Check)

Rotary X

Perforation _____

Brand _____

Total depth of Well 110 Ft.

Depth to water (SWL) 109 Ft.

GROUTING

Type Grout Cement

Applied by pressure X Other _____

From 0 Ft. To 140 Ft.

From _____ Ft. To _____ Ft.

From _____ Ft. To _____ Ft.

MOLE DIAMETER:

From 0 Ft. To 140 Ft. 32 in.

From 0 Ft. To 110 Ft. 25 in.

From _____ Ft. To _____ Ft. _____ in.

From _____ Ft. To _____ Ft. _____ in.

From _____ Ft. To _____ Ft. _____ in.

TEST PUMP DATA:

Pumped Test Soiled _____

Estimated Actual Test

Date Tested February 8, 1972

Pump rated 1643 GPM HP Test Engine

Yield 1643 GPM other 26 in.

of stabilization

Water Level before Test 105 Ft.

Drawdown 42 Ft.

Specify Capacity 39.0 GPM per ft.

CASING RECORD:

Type Material Steel

Size 6 in. From 0 Ft. To 140 Ft.

Size 16 in. From 0 Ft. To 200 Ft.

Size 12 in. From 200 Ft. To 110 Ft.

Size _____ in. From _____ Ft. To _____ Ft.

Size _____ in. From _____ Ft. To _____ Ft.

12" x 16" steel surge

Well developed and Disinfected:

X Yes _____ No

WELL SCREEN:

Type Material Layne Stainless Steel Chatter

Size 12 in. From 240 Ft. To 290 Ft.

Size 12 in. From 343 Ft. To 365 Ft.

Size 12 in. From 400 Ft. To 430 Ft.

Size _____ in. From _____ Ft. To _____ Ft.

Size _____ in. From _____ Ft. To _____ Ft.

PERMANENT PUMP DATA (If Available)

Pump Type Singer-Layne & Bouler

Outlet Size 2"

Powered by 150 ELECTRIC MOTOR

Horse power 150

Rate 1500 GPM

Pumping Level 146

Pump Disinfected X Yes _____ No

FOR WELL LOG, USE REVERSE SIDE

WELL LOG

7

From FEET	Thickness each stratum TO FEET	TYPE MATERIAL ENCOUNTERED	REMARKS	INDICATE WATER BEARING ZONES
1	1	Top Soil		
18	17	Sand Clay		
32	14	White Clay		
47	15	White Clay & Sand		
64	17	Red Clay w/Little Sand		
74	10	Clay		
122	48	Coarse Sand		
130	8	Clay-white		
135	25	Coarse Sand w/Some Clay		
180	30	Med. Coarse Sand		
184	5	White Clay		
219	30	Med. Coarse Sand		
224	9	Clay		
281	57	Med. Coarse Sand		
296	15	Sand & Clay		
341	45	Med. Coarse Sand w/Little stks. of white clay		
357	16	Med. Coarse Sand w/Some White Clay		
360	39	Coarse Sand		
385	16	Med. Coarse Sand		
393	8	Sand w/lots of Clay. Clay washes out.		
439	42	Coarse Sand Little Clay		
464	29	Coarse Sand w/Some of White Clay		
488	24	Med. Sand w/Little Clay		
495	7	Med. Med Sand w/Little Clay		
503	8	Red Clay w/Little Sand		

(If More Space is Required, Use Additional Sheet)

This well was drilled according to the Rules and Regulations of the Georgia Department of Public Health and the above information is true and correct to the best of my knowledge.

Signed John W. Platt Title District Manager
 Date June 15, 1972

NO 8

ENVIRONMENTAL PROTECTION DIVISION
DEPARTMENT OF NATURAL RESOURCES
STATE OF GEORGIA
APPLICATION FOR A PERMIT TO USE GROUNDWATER
PART B - WELL DATA

Submit one (1) Form for Each Well

(Print or Type all Information)

APPLICANT CITY OF WARNER ROBINS

WELL NO. 8 (Key to Attached Location Map) Ground Elevation 396 + ft.
Latitude 32°35'44" N Longitude 83°38'57" W (if available)

WELL CONSTRUCTION DESCRIPTION EXISTING PROPOSED

Name of Aquifer(s) being or to be Utilized Tuscaloosa Group

TYPE DRILLING (Indicate)

Rotary
 Percussion Total Depth 430 ft.
 Bored Static Water Level 101 Ft.

DRILL HOLE DIAMETER

From 0 ft., to 100 ft., 32 in.
From 0 ft., to 430 ft., 25 in.
From ft., to ft., in.
From ft., to ft., in.
From ft., to ft., in.

CASING RECORD

Type Material Steel
Wall Thickness 0.312, 0.375, 0.375 in.
Weight/Foot 85.73, 62.58, 49.56 lb.
Size 26 in. from 0 ft., to 100 ft.
Size 16 in. from 0 ft., to 225 ft.
Size 12 in. from 225 ft., to 430 ft.
Size in. from ft., to ft.
Size in. from ft., to ft.

WELL SCREEN

Type Material Stainless Steel
Size 12 in. from 240 ft., to 260 ft.
Size 12 in. from 305 ft., to 320 ft.
Size 14 in. from 360 ft., to 380 ft.
Size 12 in. from 400 ft., to 420 ft.
Size in. from ft., to ft.

Date Drilled August 1970
Date to be Drilled
Driller Singer-Layne-Atlantic Co.

GROUTING: Yes No
Type Pressure (Cement)

From 100 ft., to 0 ft.
From ft., to ft.
From ft., to ft.

TEST PUMP DATA

Pumped Test Bailed
Estimated 1500 GPM
Date Tested August 13, 1970
Pump Rated 1641 GPM 150 HP
Test Yield 1641 GPM After 24 hrs. of pumping
Water Level before Test 101 ft.
Drawdown 27 ft.
Specific Capacity 60.8 GPM/ft.

PERMANENT PUMP DATA (if available)

Pump Type Deep Well Turbine
Outlet Size 8 in.
Powered by Electric Motor
Horsepower 150
Rate 1500 GPM
Pumping Level 128 Ft.
Average Hours Pumped Per Day

NOTE: Detailed well construction specifications of a proposed well may be required by the Division upon review of the submitted application.

Complete WELL LOG on reverse side, if available.

WELL LOG

8

FROM FEET	TO FEET	TYPE MATERIAL ENCOUNTERED	REMARKS	INDICATE WATER BEARING ZONES
0	15	Red Sandy Clay w/Hard Stks of Rock		
5	35	Yellow Sandy Clay		
35	42	Sandy Clay		
42	50	Red Clay - Slow		
50	65	Red Clay - Very Slow		
65	80	Red Sandy Clay - Slow		
80	87	Med. Coarse Sand & Little Clay - Soft		
87	100	Clay		
100	126	Coarse Sand w/Small Stks of Clay		
126	187	Coarse Sand		
187	274	Med. Coarse Sand		
274	294	Med. Coarse Sand w/Stks of Clay		
294	443	Med. Coarse Sand - Soft		
443	463	Med. Coarse Sand - W/Stks of Clay		
463	480	Med. Coarse Sand - Soft		
480	494	Red Sandy Clay - Very Slow		

(If More Space is Required, Use Additional Sheet)

The above information is true and correct to the best of my knowledge.

Signed _____ Title _____

Date _____

Georgia Department of Public Health
 Water Supply Service
 47 Trinity Avenue, S. W.
 Atlanta, Georgia 30334

DO NOT WRITE
CLASS II
CLASS III
INDIVIDUAL

WELL DATA SHEET
 For
 PUBLIC OR COMMUNITY WATER SUPPLY SYSTEMS OR INDIVIDUAL WATER SUPPLY
 Well No. 9 (Water Plant No. 2)

INSTRUCTIONS:

Name of Water System: Warner Robins Location Arrowhead Trail County Houston
 Type: Municipal ; Subdivision _____ No of Lots _____ ; Mobile Homes _____ or Trailer Parks _____
 No of Lots _____ ; Industrial _____ ; Commercial _____ ; Individual _____ ; Other _____
 Owner City of Warner Robins Driller Singer-Layne Atlantic Company
 Address _____ Address Albany, Georgia
 Date Drilling Started September 1971 Date Completed October 1971

WELL DESCRIPTION

TYPE DRILLING

(Check)

Rosary
 Percussion _____
 Bored _____
 Total depth of Well 490 Ft.
 Depth to water (SWL) 101 Ft.

GROUTING

Type Grout Cement
 Applied by pressure Other _____
 From 0 Ft. To 110 Ft.
 From _____ Ft. To _____ Ft.
 From _____ Ft. To _____ Ft.

HOLE DIAMETER:

From 0 Ft. To 110 Ft. 32 in.
 From 0 Ft. To 190 Ft. 25 in.
 From _____ Ft. To _____ Ft. _____ in.
 From _____ Ft. To _____ Ft. _____ in.
 From _____ Ft. To _____ Ft. _____ in.

TEST PUMP DATA:

Pumped Test Bailed _____
 Estimated Actual Test
 Date Tested October 5, 1971
 Pump rated 1613 GPM HP Test Engine
 Yield 1613 GPM other _____ hr.
 of stabilization
 Water Level before Test 101 Ft.
 Drawdown 22 3/4 Ft.
 Specific Capacity 52 GPM per ft.

CASING RECORD:

Type Material Steel
 Size 26 in., From 0 Ft. To 110 Ft.
 Size 16 in., From 0 Ft. To 250 Ft.
 * Size 12 in., From 250 Ft. To 490 Ft.
 Size _____ in., From _____ Ft. To _____ Ft.
 Size _____ in., From _____ Ft. To _____ Ft.

*Steel Sauge 12"x16"

WELL SCREEN:

Type Material Layne Stainless Steel Shutter
 Size 12 in., From 330 Ft. To 340 Ft.
 Size 12 in., From 360 Ft. To 380 Ft.
 Size 12 in., From 405 Ft. To 415 Ft.
 Size 12 in., From 460 Ft. To 480 Ft.
 Size _____ in., From _____ Ft. To _____ Ft.

Well developed and Disinfected:

Yes _____ No

PERMANENT PUMP DATA (If Available)

Pump Type Singer-Layne & Bowler
 Outlet Size 8"
 Powered by Electric Motor
 Horse power 150
 Rate 1500 GPM
 Pumping Level 130'
 Pump Disinfected Yes _____ No

FOR WELL LOG, USE REVERSE SIDE

SH 430

WELL LOG
9

Total Depth	Thickness each Stratum	TYPE MATERIAL ENCOUNTERED	REMARKS	INDICATE WATER BEARING ZONES
7	7	Sand		
20	13	Sand & White Clay		
36	16	Sand W/Little Stks. of White Clay		
50	14	Coarse Sand & White Clay-Slow		
80	30	Coarse Sand		
127	47	Coarse Sand W/Stks. of White Clay		
189	62	Med. Coarse Sand		
221	32	Med. Coarse Sand W/Stks of Clay		
231	10	Med. Coarse Sand-Soft		
253	22	Med. Coarse Sand & Stks. of Clay-Soft		
270	23	Med. Sand & Red Clay-Slow		
295	25	Sand & Red Clay-Very Slow		
314	19	Coarse Sand-Very Slow		
311	30	Med. Coarse Sand-Soft		
366	42	Med. Coarse Sand W/Little Clay-Soft		
396	10	Red Sand Clay-Slow		
427	21	Med. Coarse Sand-Soft		
437	20	Coarse Sand Home Clay-Slow		
450	13	Sand Clay-Slow		
467	17	Med. Coarse Sand-Soft		
497	30	Med. Coarse Sand W/Little Clay-Soft		
528	31	Sand W/Little Clay-Soft.		


(If More Space is Required, Use Additional Sheet)

This well was drilled according to the Rules and Regulations of the Georgia Department of Public Health and the above information is true and correct to the best of my knowledge.

Signed John W. Flatt Title District Manager
Date June 15, 1972

No. 10

ALL MEASUREMENTS TAKEN FROM (GROUND) (TOP OF FOUNDATION) (TOP OF CASING) (TOP BASE PLATE)



STARTED WELL _____ IN _____ AND COMPLETED _____ IN _____
 TOTAL DEPTH 180 ELEVATION _____ STATIC WATER LEVEL _____
 LENGTH SURFACE CASING _____ SIZE _____ THICKNESS _____
 CEMENTED WITH _____ BAGS CEMENT TYPE PACKER _____
 LENGTH WELL CASING 121 SIZE 26 WEIGHT SCH 40
 CEMENTED WITH _____
 INNER CASING 16x12 WEIGHT STD SCH 40
 WITH AS SHOWN _____ TYPE BACKOFF _____
 END SEAL _____ GUIDE _____
 WELL STRAINER MAKE Layne SIZE 12 LENGTH 75 OPENING 7/8"
 TYPE MATERIAL S.S. _____ WELDED _____ CONNECTIONS _____
 SIZE HOLE DRILLED FOR SURFACE CASING 32 WITH Tri-Cone
 SIZE HOLE DRILLED FOR WELL CASING 26 WITH Tri-Cone
 SIZE HOLE DRILLED FOR WELL CASING 26 WITH Tri-Cone
 YARDS OF GRAVEL USED _____ PLACED _____
 HOW WAS WELL TESTED _____
 NOTES _____

RIG USED Gardner Denver DRILLER Sylvester Yarn
 SERIAL NUMBER _____ MAKE _____ FOUNDATION _____
 LENGTH COLUMN _____ SIZE _____ TYPE _____ # 10 LENGTHS
 BOWL SIZE _____ TYPE _____ STAGES _____ MATERIAL IMPELLER _____
 MATERIAL BOWL _____ WITH _____ PORTS AND _____ SHAFT _____
 SUCTION SIZE _____ LENGTH _____ SUCTION STRAINER _____
 IS PUMP SEALED HOW _____ WHERE _____ WITH WHAT _____
 LUBRICATOR TYPE _____ SIZE _____ VOLTAGE _____
 LENGTH OF AIRLINE _____ SIZE _____ TYPE MATERIAL _____
 AIR RELEASE VALVE TYPE _____ SIZE _____
 SIZE SURFACE DISCHARGE _____ TYPE _____ DAYTON COUPLING _____
 PRESSURE GAUGE _____ SPEED _____
 NOTES _____

RIG USED TO SET PUMP _____ INSTALLER _____
 DATE PUMP INSTALLED _____ IN _____ DATE IN OPERATION _____ IN _____
 MAKE _____ HP _____ PHASE _____ CYCLE _____ VOLT. 220/440
 SPEED _____ MODEL _____ SERIAL NUMBER _____
 TOP BEARING _____ BOTTOM BEARING _____ RATCHET _____
 STARTER _____ PRESSURE SWITCH _____ FLOAT _____

MAKE _____ MODEL _____ SIZE _____ RATIO _____ NO _____
 SIZE PULLEY _____ TYPE MOTOR FRAME _____
 MAKE _____ MODEL _____ HP _____ SERIAL NUMBER _____
 SPEED _____ SIZE PULLEY _____ FOUNDATION _____
 TYPE FUEL TANK _____ MAKE MAG _____ NO _____
 MAKE STARTER _____ HP _____ TYPE FUEL _____
 MAKE FLEXIBLE SHAFT _____ SIZE _____ LENGTH _____ BELT LENGTH _____

PURPOSE FOR WHICH THIS WATER IS USED _____
 TEMPERATURE _____ IS WATER CLEAR _____ CAPACITY _____
 SAND _____ HARDNESS _____ PH _____ IRON _____ NaCl _____
 TYPE TREATMENT USED _____
 IS THERE A DERRICK OVER THE WELL _____ HEIGHT _____ TYPE _____
 CAN TRUCK OR TRUCK BODY GO TO WELL _____
 PUMP HOLES _____ SIZE MATCH _____

COMPANY RESIST NO. AL-0158

OUR WELL NO. 10 IN WELL NO. 10 IN TEST HOLE NO. _____
 LOCATION OF THE WELL Taber Drive
 INSTALLED FOR City of Warner Robins
 ADDRESS City Warner Robins COUNTY Houston STATE Georgia

Contractor: Arthur Lew Construction Co. YEAR 1916
 Engineer: Flood & Associates

ENGINEER PROJECT NO. 71064
 DATE _____
 [Signature Box]

WELL NO. 10
 CITY OF WARNER ROBINS
 CONTRACT NO. AL-0150
FORMATION LOG OF THE WELL OR TEST HOLE


STARTED TEST HOLE Dec. 13 1976 FINISHED Dec. 17 1976 TEST HOLE NUMBER _____
 LOCATION City of Warner Robins SEC _____ TS _____ RANGE _____ ELEVATION _____
 Taber Drive

TOTAL DEPTH	THICKNESS EACH STRATUM	FORMATION	TOTAL DEPTH	THICKNESS EACH STRATUM	FORMATION
36	36	Red Sandy Clay- Slow.			
66	30	Red & White Sandy Clay			
96	30	Coarse Sand & Clay			
116	20	Med. Coarse Sand & Clay. Soft			
125	9	White Sandy Clay. Very Slow.			
135	10	White Clay & Sand. Slow.			
155	20	Sand & Stks. of White Clay. Soft.			
181	28	Coarse Sand & Little White Clay. Soft.			
213	30	Coarse Sand. Soft.			
240	57	Coarse Sand & Little White Clay. Soft.			
295	35	Med. Coarse Sand. Soft.			
325	20	Sand & Red Clay. Very Slow.			
500	175	Coarse Sand & Little Stks. of White Clay. Soft & Slow.			
561	61	Coarse Sand & Stks. of Red Clay			
MUD PIT SIZE _____ FT. X _____ FT. X _____ FT. DEEP TYPE BIT USED TO CUT SAND _____ SIZE OF TEST HOLE THROUGH SAND _____ TYPE OF BIT USED TO CUT UPPER FORMATIONS _____ SIZE _____ TYPE MUD PUMP USED _____ DRILLING PRESSURE IN SAND _____ TYPE OF MUD USED _____ NOTES: _____					
TEST DATA					
			PRELIMINARY TEST		FINAL TEST
			STATIC WATER LEVEL 56'		
			PUMPED G. P. M. 141.7		
			PRESSURE, POUNDS		
			DRAWDOWN 48'		
			G. P. F. D.		
			GUARANTEED G. P. M. 1500		
			GUARANTEED PRESSURE		
			DATE OF TEST MAR 8, 1977		
REMARKS					
			DRILLER Sylvester Yano		
			FIELD SUPT. Jess Fendenhall		

No. 11

ALL MEASUREMENTS TAKEN FROM (GROUND) (TOP OF FOUNDATION) (TOP OF CASING) (TOP BASE PLATE)

DRAWING OF THE WELL



WELL DATA

STARTED WELL Oct. 25 1976 AND COMPLETED Dec. 7 1976
 TOTAL DEPTH 440 ELEVATION _____ STATIC WATER LEVEL _____
 LENGTH SURFACE CASING _____ SIZE _____ THICKNESS _____
 CEMENTED WITH _____ SACKS CEMENT TYPE PACKER _____
 LENGTH WELL CASING 180' SIZE 26 WEIGHT SCU 70
 CEMENTED WITH _____ SACKS CEMENT TYPE PACKER _____
 INNER CASING LENGTH 16x12 SIZE 18"x260" WEIGHT SCU 70
 WITH _____ X _____ GUIDES LOCATED Shown TYPE BACKOFF _____
 LEAD SEAL _____ BACKPRESSURE VALVE _____ GUIDE _____
 WELL STRAINER MAKE Layne SIZE 12 LENGTH 25 OPENING 2"
 TYPE MATERIAL S.S. WITH Welded CONNECTIONS _____
 SIZE HOLE DRILLED FOR SURFACE CASING 22 WITH Tri-Cone
 SIZE HOLE DRILLED FOR WELL CASING 26 WITH Tri-Cone
 SIZE HOLE DRILLED FOR STRAINER 26 WITH Tri-Cone
 YARDS OF GRAVEL USED _____ HOW PLACED _____
 HOW WAS WELL DEVELOPED _____
 NOTES: _____

RIG USED Gardner Denver DRILLER Sylvester Yarn

PUMP RECORD

SERIAL NUMBER 82863 MAKE Layne FOUNDATION Concrete
 LENGTH COLUMN 100 SIZE 10x12x24 TYPE Oil @ 20 LENGTHS
 BOWL SIZE 12 TYPE TLC STAGES 6 MATERIAL IMPELLER _____
 MATERIAL BOWL C.I. WITH Open PORTS AND S.S. SHAFT _____
 SUCTION SIZE 10 LENGTH 30 SUCTION STRAINER Galy Cone
 IS PUMP SEALED HOW Yes WHERE Foundation WITH WHAT Concrete
 LUBRICATOR TYPE Oil SIZE 4 Qts. VOLTAGE 460
 LENGTH OF AIRLINE 100 SIZE 1/4 TYPE MATERIAL Galy
 AIR RELEASE VALVE TYPE Crispen SIZE 2"
 SIZE SURFACE DISCHARGE 10 TYPE _____ DAYTON COUPLING _____
 PRESSURE GAUGE 0-100 SPEED 1800
 NOTES: _____

RIG USED TO SET PUMP Crane INSTALLER R. Castleberry
 DATE PUMP INSTALLED 3-2 1977 DATE IN OPERATION 11-1 1977

MOTOR

MAKE GE HP 100 FRAME B444TP PHASE 3 CYCLE 60 VCLT. 440
 SPEED 1800 MODEL 5K6277 X H2A SERIAL NUMBER MD1013153
 TOP BEARING _____ BOTTOM BEARING _____ RATCHET RRR
 STARTER _____ PRESSURE SWITCH _____ FLOAT _____

GEAR

MAKE Johnson MODEL CH200 SIZE 200 HP RATIO 1:1 NO _____
 SIZE PULLEY _____ TYPE MOTOR FRAME Combination

ENGINE

MAKE Waukesha MODEL F-1197GU HP 253 SERIAL NUMBER 365649
 SPEED 1800 SIZE PULLEY _____ FOUNDATION Concrete
 TYPE FUEL TANK _____ MAKE MAG _____ NO _____
 MAKE STARTER _____ NO _____ TYPE FUEL Natural Gas
 MAKE FLEXIBLE SHAFT _____ SIZE _____ LENGTH _____ BELT LENGTH _____
Hillard Twiflex 1226-1-1/2x100

GENERAL

PURPOSE FOR WHICH THIS WATER IS USED Municipal
 TEMPERATURE _____ IS WATER CLEAR Yes CAPACITY 1500
 SAND No HARDNESS 4 PH 5.6 IRON 8.01 N-CL _____
 TYPE TREATMENT USED _____
 IS THERE A DERRICK OVER THE WELL No HEIGHT _____ TYPE _____
 CAN TRUCK OR RIG EASILY GET TO WELL No In House _____
 PUMP HOUSE Yes SIZE HATCH 4'x6'

CONTRACT NO. AI-0150

OUR WELL NO. 11 THEIR WELL NO. 11 IN TEST HOLE NO. _____

LOCATION OF THE WELL Labor Street

INSTALLED FOR City of Warner Robins

ADDRESS CITY Warner Robins COUNTY Houston STATE Georgia

Prime Contractor: Arthur Fox Construction Co.
 Engineer: Flood & Associates

YEAR 1976

No. 11

WELL NO. 11
CORRECTION NO. AL-0150
FORMATION LOG OF THE WELL OR TEST HOLE

STARTED TEST HOLE _____ 19 76 FINISHED November 3 19 76 TEST HOLE NUMBER _____
LOCATION: 1st St. & 1st Ave. Sec _____ TS _____ RANGE _____ ELEVATION _____

TOTAL DEPTH	THICKNESS EACH STRATUM	FORMATION	TOTAL DEPTH	THICKNESS EACH STRATUM	FORMATION
2	2	Red Sand Clay	559	50	Red Sand & Clay. Very Clay.
22	20	Red Clay			
42	20	Red Sand Clay			
62	20	Red & White Sandy Clay			
82	20	Yellow Sand & Clay			
102	20	Coarse Gravel. Circulation Problems.			
122	20	Coarse Sand & Little White Clay			
142	20	Coarse Sand & Stks of White Clay. Soft.			
162	20	Sand & White Clay. Soft.			
182	20	Med. Coarse Sand & White Clay Soft.			
202	20	Coarse Sand with Stks. of White Clay. Soft.			
222	20	Med. Coarse Sand with Little White Clay. Soft.			
242	20	Coarse Sand with Stks. of White Clay. Soft.			
262	20	White Clay (No Sample) Slow.			
282	20	Coarse Sand & Little White Clay. Soft.			
302	20	Med. Coarse Sand, Little Clay Medium Drilling.			
322	20	Red & White Clay. Very Slow.			
342	20	Coarse Sand & Little Clay. Soft.			
362	20	Coarse Sand with Stks. of White Clay. Soft.			
382	20	Coarse Sand & Little Clay. Soft.			
402	20	Sand & Little Stks. of Red Clay			
422	20	Sand & Red Clay. Slow.			
442	20	Brown Sand with little Clay. Slow.			
462	20	Sand & Stks of Red Clay			

MUD PIT SIZE _____ FT. X _____ FT. X _____ FT. DEEP
TYPE BIT USED TO CUT SAND _____
SIZE OF TEST HOLE THROUGH SAND _____
TYPE OF BIT USED TO CUT UPPER FORMATIONS _____ SIZE _____
TYPE MUD PUMP USED _____
DRILLING PRESSURE IN SAND _____
TYPE OF MUD USED _____
NOTES: _____

TEST DATA	
PRELIMINARY TEST	FINAL TEST
STATIC WATER LEVEL 47'	
PUMPED G P. M. 1613	
PRESSURE POUNDS _____	
DRAWDOWN 25	
G P. F. D. 64.52	
GUARANTEED G P. M. 1600	
GUARANTEED PRESSURE _____	
DATE OF TEST December 2, 1976	

REMARKS _____
DRILLER Sylvester Yawn
FIELD Supt. Jess Hendenhall

No. 1

LAYNE ATLANTIC COMPANY

NORFOLK, VA.

E. H. Smith

LOG OF WELL For Robins Field (Georgia Air Depot)

Located at Wellston in Georgia (near Macon, Ga.) County, State

Date Drilling Started September 2, 1941 Date Started August 21, 1941

Finished Drilling September 16, 1941 Finished October 25, 1941

FORMATIONS AND DEPTH OF WELL

DIMENSIONS OF CASING AND SCREEN

TOTAL DEPTH OF ALL STRATA		DEPTH OF EACH STRATUM		FORMATION FOUND AT EACH STRATUM
FT.	IN.	FT.	IN.	
				Well #1
20	20			Brown sand
40	20			Yellow sand
48	8			Yellowish white sand
70	22			Coarse white sand
76	6			Very coarse sand
86	10			Coarse white sand
96	9			Coarse sand, some chalk
122	27			Coarse white sand and fine gravel Signs of chalk 95 to 100 1 ft. very hard streak at 109
132	10			Soft coarse white sand
136	4			Hard chalk and gravel
152	16			Chalk and gravel
157	5			Soft coarse white sand
162	5			Soft chalk and coarse gravel
167	5			Medium hard coarse gravel - used 1/2 pit of water
172	5			Coarse white sand
177	5			Chalk and gravel
182	5			Soft coarse sand
207	25			Hard clay and gravel
234	27			Coarse white sand
239	5			Hard streak (?). No sample
283	44			Fine white sand
270	17			Coarse sand - used water
274	4			Very hard gravel
290	16			Very hard chalk
316	26			Coarse sand
318	2			Coarse sand and little clay
328	10			Coarse sand
332	4			Coarse and fine white sand with white clay
337	5			Fine sand
344	7			Coarse sand, soft
357	13			Coarse and fine sand - little chalk
362	5			Very coarse sand - soft ? - used pit of water 301 to 308

TOTAL LENGTH OF ALL SCREENS AND CASINGS		LENGTH OF EACH SEC. OF SCREENS OR CASING		SPECIES OF SCREEN OR CASING	SIZE OF SCREEN OR CASING	GAUGE OF SCREEN
FT.	IN.	FT.	IN.			
76	76			Casing	20	5/16
				12" casing commences at 60'		
80	80	50	50	Casing	12	60%
70	70	20	20	Screen	12	6
190	190	120	120	Casing	12	60%
210	210	20	20	Screen	12	6

WELL DATA:

Preliminary Test

Date Tested 9-20 1941 Static Level
Production 1400 GPM Pumping Level
73' drawdown Permanent Test

Date Tested 9-22 1941 Static Level 40'
Production 835 GPM Active St. Level
Drawdown 35' Pumping Level

Remarks: 36 hour test

PUMP DATA:

Shop No. Type Lubr.
Type Head Size Suction
Depth Setting (BP to MB)
Size Column Length Suction
Type Bowl Length Air Line
No. Stages Discharge-
Cap'y and Head Pressure

MOTOR DATA:

Horsepower Voltage
RPM Phase
Type Cycles
Make Frame No.

No. 1

WELL DATA			INSTALLATION Robins AFB, Georgia			WELL NO. #1			
ELEVATION (FT)		LOCATION Bldg # 186			DATE CONSTRUCTION 28 October 1941				
WELL	TYPE Drilled Well (Underreamed Gravel - Packed Well)								
	DEPTH 265 ft.		DIAMETER 8 in.		PUMP SETTING DEPTH 100 ft.				
	ORIG STATIC WATER LEVEL No Record		DRAWDOWN 35'		RECOVERY TIME				
TEST DATA			AIR LINES AND GAGES			SPECIFIC CAPACITY (Gal per ft)			
Well capacity 850 GPM	Pumping level	X	Yes	No	Length	GPM = DRAWDOWN			
WELL PUMPING EQUIPMENT									
PUMP	TYPE AND MAKE Vertical Turbine Layne Pump No. 17097						CAPACITY 850 GPM		
	SUCTION (FT) 20 Ft. 6 in.		SIZE AND LENGTH			COLUMN 8 in.			
	HEAD			NUMBER BOWLS		SIZE AND TYPE		NO. STAGES	
Above grad	Below grad	Total	4 Stage		12" BKMC		4		
MOTOR	SERIAL NO. 286857	TYPE CFU	MAKE U. S. Motor	RPM 75	FRAME 1800	PHASE 952	CYCLES 3	VOLTAGE 60 220/440	
	STANDBY POWER Yes		MAKE General Motors diesel				SIZE		
	HP 90	RPM 1800	DESCRIPTION Ser. No. 4A-90389; Model 4030C						
CASING AND WELL SCREENING MATERIAL USED						SETTING DEPTH	LENGTH EACH		
75 ft. of 20" pit casing cemented in place.									
Top of original 12" screen line at 60'									
Top of 8" screen line at 108'									
8" stainless steel screen at 110' - 130' and 245' - 265'									
NOTE: Above well was relined in March 1953 to data shown above.									
PUMP: Layne No. 17097									
100' of 8" X 2 1/2" X 1 1/2" Column									
4 Stage 12" BKMC Bowls									
20' of 6" Suction									
Gear Drive: Johnson 1 1/3 - 1									

1A

MEASUREMENTS TAKEN FROM (GROUND) (TOP OF FOUNDATION) (TOP OF CASING) (TOP BASE PLATE)

DRAWING OF THE WELL

STARTED WELL August 13 1975 AND COMPLETED Sept. 17 1975
 TOTAL DEPTH 360 ELEVATION _____ STATIC WATER LEVEL 37'
 LENGTH SURFACE CASING 154 SIZE 26 THICKNESS 0.375
 CEMENTED WITH 400 BAGS CEMENT TYPE PACKER _____
 LENGTH WELL CASING _____ SIZE _____ WEIGHT _____
 CEMENTED WITH _____ BAGS CEMENT TYPE PACKER _____
 INNER CASING LENGTH 360 SIZE 12" WEIGHT 0.375 wall
 WITH ns shown GUIDES LOCATED _____ TYPE BACKOFF _____
 LEAD SEAL _____ BACKPRESSURE VALVE _____ GUIDE _____
 WELL STRAINER MAKE Cook SIZE 12 LENGTH 50 OPENING 0.55
 TYPE MATERIAL SS (304) WITH _____ CONNECTIONS _____
 SIZE HOLE DRILLED FOR SURFACE CASING 32 WITH Tri Cone
 SIZE HOLE DRILLED FOR WELL CASING 26 WITH " "
 SIZE HOLE DRILLED FOR STRAINER 26 WITH " "
 YARDS OF GRAVEL USED 70 HOW PLACED Gravity & Back Flow
 HOW WAS WELL DEVELOPED Test Pump & Air
 NOTES: _____
 RIG USED Gardner-Denver DRILLER S. Yawn

SERIAL NUMBER 17097 MAKE Lyvne FOUNDATION _____
 LENGTH COLUMN 100 SIZE 8 x 1 1/2 x 2 1/2 TYPE Oil # 10 LENGTHS
 BOWL SIZE 12 TYPE BKAM STAGES 4 MATERIAL IMPELLER bronze
 MATERIAL BOWL C.I. WITH ORDN PORTS AND _____ SHAFT
 SUCTION SIZE 8" LENGTH 10' SUCTION STRAINER CORR
 IS PUMP SEALED NOW _____ WHERE _____ WITH WHAT _____
 LUBRICATOR TYPE _____ SIZE _____ VOLTAGE _____
 LENGTH OF AIRLINE 100' SIZE 1" TYPE MATERIAL galvanized
 AIR RELEASE VALVE TYPE _____ SIZE _____
 SIZE SURFACE DISCHARGE _____ TYPE _____ DAYTON COUPLING _____
 PRESSURE GAUGE _____ SPEED _____
 NOTES: _____
 RIG USED TO SET PUMP _____ INSTALLER _____
 DATE PUMP INSTALLED 19 _____ DATE IN OPERATION 19 _____

MAKE U.S. HP 100 FRAME 404TP PHASE 3 CYCLE 50 VOLT 440/420
 SPEED 1800 MODEL _____ SERIAL NUMBER _____
 TOP BEARING _____ BOTTOM BEARING _____ RATCHET _____
 STARTER _____ PRESSURE SWITCH _____ FLOAT _____

MAKE _____ MODEL _____ SIZE _____ RATIO _____ NO _____
 SIZE PULLEY _____ TYPE MOTOR FRAME _____

MAKE _____ MODEL _____ HP _____ SERIAL NUMBER _____
 SPEED _____ SIZE PULLEY _____ FOUNDATION _____
 TYPE FUEL TANK _____ MAKE MAG _____ NO _____
 MAKE STARTER _____ NO _____ TYPE FUEL _____
 MAKE FLEXIBLE SHAFT _____ SIZE _____ LENGTH _____ BELT LENGTH _____

PURPOSE FOR WHICH THIS WATER IS USED _____
 TEMPERATURE _____ IS WATER CLEAR _____ CAPACITY _____
 SAND _____ HARDNESS _____ PH _____ IRON _____ NACl _____
 TYPE TREATMENT USED _____
 IS THERE A DERRICK OVER THE WELL _____ HEIGHT _____ TYPE _____
 CAN TRUCK OR RIG EASILY GET TO WELL _____
 PUMP HOUSE _____ SIZE MATCH _____

CONTRACT NO. 13254 - 171

OUR WELL NO. 1(a) THEIR WELL NO. 1(a) IN TEST HOLE NO. _____
 LOCATION OF THE WELL Robins Air Force Base
 INSTALLED FOR Mid-South Construction Company
 ADDRESS CITY Warner Robins COUNTY Houston STATE Georgia

IAFP Contract No. F09650-75-C-0083
 Redrill Well No. 1
 Project No. WR 134-5

YEAR 1975

No. 1A

Contract No. 13264

FORMATION LOG OF THE WELL OR TEST HOLE

STARTED TEST HOLE Aug. 20 1975 FINISHED Aug. 26 1975 TEST HOLE NUMBER 1
LOCATION Well No. 1 (a) SEC TS RANGE ELEVATION
North of old Well No. 1, Bldg. No. 186 approximately 300'

TOTAL DEPTH	THICKNESS EACH STRATUM	FORMATION	TOTAL DEPTH	THICKNESS EACH STRATUM	FORMATION
10	10	Filled Sand & Clay			
20	10	Sandy Clay - Slow			
37	17	Sand & Little Clay-Soft			
70	33	Sandy Clay - 50'			
126	56	Sand & Stks. of White Clay-Soft			
155	29	Sandy W/Hard Stks. of Clay			
177	22	Sand & Little Clay - Soft.			
192	15	White Clay & Sand - Slow			
216	24	Sand - Little White Clay-Soft			
244	28	Coarse Sand - Soft			
260	16	Coarse Sand Little Clay - Soft			
277	17	Red Sand Clay - Slow			
364	87	Coarse Sand & Little Clay Soft.			
389	25	Coarse Sand & Stks. of Clay-Soft			

MUD PIT SIZE _____ FT. X _____ FT. X _____ FT. DEEP
TYPE BIT USED TO CUT SAND _____
SIZE OF TEST HOLE THROUGH SAND _____
TYPE OF BIT USED TO CUT UPPER FORMATIONS _____ SIZE _____
TYPE MUD PUMP USED _____
DRILLING PRESSURE IN SAND _____
TYPE OF MUD USED _____
NOTES: Set 154' of 26" casing and grouted in place. Before completing test hole. This well was located on side of hill in back fill soil conditions on surface.

TEST DATA	
PRELIMINARY TEST	FINAL TEST
STATIC WATER LEVEL	37'
PUMPED G. P. M.	1613
PRESSURE, POUNDS	
DRAWDOWN	23'
G. P. D.	37.51
GUARANTEED G. P. M.	950
GUARANTEED PRESSURE	
DATE OF TEST	9-11-75

REMARKS

DRILLER S. Yawn
FIELD SUPT. J. Flatt

LAYNE ATLANTIC COMPANY E. H. ...
NORFOLK, VA.

LOC. OF WELL For Robins Field (Georgia Air Impor)
 Located at Wellston in (Near Macon, Ga.) County, State Georgia 122
 Date Drilling Started September 19, 1941 Date Started August 21, 1941
 Finished Drilling September 27, 1941 Finished October 28, 1941

FORMATIONS AND DEPTH OF WELL

DIMENSIONS OF CASING AND SCREEN

TOTAL DEPTH OF ALL STRATA		DEPTH OF EACH STRATUM		FORMATION FOUND AT EACH STRATUM
FT.	IN.	FT.	IN.	
				Well #2
45		45		Fine brown sand
67		22		Medium white and yellow sand
72		5		Fine white sand
78		6		Coarse sand and gravel - very hard
80		2		Clay
95		15		Coarse dark sand
108		13		Medium white sand - soft
122		14		Clay and chalk - soft
140		18		Coarse sand and gravel - soft, used 2 pits of water
173		33		Very soft white sand - used water
196		22		Coarse white sand - out medium
199		4		Clay
205		6		Fine sand and chalk
210		5		Fine white sand
216		6		Fine white sand and chalk
220		5		Clay and gravel
225		5		Coarse gravel - hard
230		5		Coarse white sand, cut medium, used 1/4 pit of water
240		9		Coarse white sand - hard
250		10		Fine white sand - medium
260		10		" " " - soft
266		6		Coarse " " - hard
270		5		Coarse gravel - hard
290		20		Chalk and gravel

bottom of well 255'

Under-reamed from 125 to 170
and from 225 to 255

TOTAL LENGTH OF ALL SCREENS and CASINGS		LENGTH OF EACH SEC. OF SCREENS or CASING		SPECIFY SCREEN or CASING	SIZE OF SCREEN or CASING	GAUGE OF SCREEN
FT.	IN.	FT.	IN.			
75		75		Casing	20	5/16
12"		casing commences 56'-6".				

Cased 20"

Carried 1000'

WELL DATA:

Preliminary Test

Date Tested 10-3 19 41 Static Level 32'
 Production 900 to 925 GPM Pumping Level
 GPM Permanent Test

Date Tested 19 Static Level
 Production GPM Active St. Level
 Drawdown Pumping Level

Remarks:

PUMP DATA:

Shop No. Type Lubr.
 Type Head Size Section
 Depth Setting (BP to MB)
 Size Column Length Suction
 Type Bowl Length Air Line
 No. Stages Discharge-
 Cap'y and Head Pressure

MOTOR DATA:

Horsepower Voltage
 RPM Phase
 Type Cycles
 Make Frame No.

ESZ

SECTION 111

No. 2

Well Contract No. 100-14-0000
 USA Contract No. 13129

FORMATION LOG OF THE WELL OR TEST HOLE

STARTED TEST HOLE _____ FINISHED _____ 19__ TEST HOLE NUMBER _____
 LOCATION _____ SEC. _____ T5 _____ RANGE _____ ELEVATION _____

TOTAL DEPTH	THICKNESS EACH STRATUM	FORMATION	TOTAL DEPTH	THICKNESS EACH STRATUM	FORMATION
0	8	Red sand clay			
8	11	Coarse sand w/little clay			
19	11	White clay, 1st clay washed out no sample			
30	48	White sand- soft			
78	11	White sand w/little clay of clay			
89	12	Coarse sand w/little silica medium clay			
101	22	Sand w/little clay- soft			
123	5	White clay w/little sand- last of clay washed out flow			
128	11	White sand-soft			
139	11	Sand- med. flow			
150	10	Sand w/little clay of white clay- soft			
160	14	sand- med. flow			
174	9	White clay w/little sand- med. flow			
183	44	Red. coarse sand w/little clay. of white clay- med. soft			
227	11	Coarse sand w/little white clay med. flow			
238	11	med. coarse sand			

MUD PIT SIZE _____ FT. X _____ FT. X _____ FT. DEEP
 TYPE BIT USED TO CUT SAND _____
 SIZE OF TEST HOLE THROUGH SAND _____
 TYPE OF BIT USED TO CUT UPPER FORMATIONS _____
 TYPE MUD PUMP USED _____
 DRILLING PRESSURE IN SAND _____
 TYPE OF MUD USED _____
 NOTES: _____

TEST DATA	
PRELIMINARY TEST	FINAL TEST
STATIC WATER LEVEL _____	
PUMPED G P M _____	
PRESSURE POUNDS _____	
DRAWDOWN _____	
G P F D _____	
GUARANTEED G P M _____	
GUARANTEED PRESSURE _____	
DATE OF TEST July 31, 1957	


REMARKS _____

 DRILLER _____
 FIELD SPT _____

No. 2

ALL MEASUREMENTS TAKEN FROM (GROUND) (TOP OF FOUNDATION) (TOP OF CASING) (TOP BASE PLATE)

DRAWING OF THE WELL



5" GUIDES @ 145'
 5" " " 200'
 5" " " 255'
 5" " " 300'
 5" " " 365'

WELL DATA

STARTED WELL July 7 1974 AND COMPLETED August 2 1974
 TOTAL DEPTH 370 ELEVATION _____ STATIC WATER LEVEL 50'
 LENGTH SURFACE CASING 150' SIZE 26" THICKNESS 0.375
 CEMENTED WITH 250 SACKS CEMENT TYPE PACKER _____
 LENGTH WELL CASING _____ SIZE _____ WEIGHT _____
 CEMENTED WITH _____ SACKS CEMENT TYPE PACKER _____
 INNER CASING LENGTH 370' SIZE 12" I.D. WEIGHT 0.375
 WITH 5 X 5 GUIDES LOCATED SHOWN TYPE BACKOFF Orange Peel
 LEAD SEAL _____ BACKPRESSURE VALVE _____ GUIDE _____
 WELL STRAINER MAKE COOK SIZE 12" LENGTH 50' OPENING .55
 TYPE MATERIAL S.S. Type 30 WITH Welded CONNECTIONS _____
 SIZE HOLE DRILLED FOR SURFACE CASING 32 WITH Tri-Cone
 SIZE HOLE DRILLED FOR WELL CASING 26 WITH " "
 SIZE HOLE DRILLED FOR STRAINER 25 WITH " "
 YARDS OF GRAVEL USED 60 Tons HOW PLACED Pumped Low Pressure
 HOW WAS WELL DEVELOPED Test Pump & Surging
 NOTES: _____
 RIG USED Cardwell 1946 DRILLER Sylvester Yaw

PUMP RECORD

SERIAL NUMBER _____ MAKE _____ FOUNDATION _____
 LENGTH COLUMN _____ SIZE _____ TYPE _____ ϕ 10 LENGTH _____
 BOWL SIZE _____ TYPE _____ STAGES _____ MATERIAL IMPELLER _____
 MATERIAL BOWL _____ WITH _____ PORTS AND _____ SHA _____
 SUCTION SIZE _____ LENGTH _____ SUCTION STRAINER _____
 IS PUMP SEALED HOW _____ WHERE _____ WITH WHAT _____
 LUBRICATOR TYPE _____ SIZE _____ VOLTAGE _____
 LENGTH OF AIRLINE _____ SIZE _____ TYPE MATERIAL _____
 AIR RELEASE VALVE TYPE _____ SIZE _____
 SIZE SURFACE DISCHARGE _____ TYPE _____ DAYTON COUPLING _____
 PRESSURE GAUGE _____ SPEED _____
 NOTES: _____
 RIG USED TO SET PUMP _____ INSTALLER _____
 DATE PUMP INSTALLED _____ IS _____ DATE IN OPERATION _____ IS _____

MOTOR

MAKE _____ HP _____ FRAME _____ PHASE _____ CYCLE _____ VOLT. 220/440
 SPEED _____ MODEL _____ SERIAL NUMBER _____
 TOP BEARING _____ BOTTOM BEARING _____ RATCHET _____
 STARTER _____ PRESSURE SWITCH _____ FLOAT _____

GEAR

MAKE _____ MODEL _____ SIZE _____ RATIO _____ NO. _____
 SIZE PULLEY _____ TYPE MOTOR FRAME _____

ENGINE

MAKE _____ MODEL _____ HP _____ SERIAL NUMBER _____
 SPEED _____ SIZE PULLEY _____ FOUNDATION _____
 TYPE FUEL TANK _____ MAKE MAG _____ NO. _____
 MAKE STARTER _____ NO. _____ TYPE FUEL _____
 MAKE FLEXIBLE SHAFT _____ SIZE _____ LENGTH _____ BELT LENGTH _____

GENERAL

PURPOSE FOR WHICH THIS WATER IS USED Municipal for Base
 TEMPERATURE _____ IS WATER CLEAR YES CAPACITY 900
 SAND NONE HARDNESS 5 PH 5.6 IRON .05 NaCl _____
 TYPE TREATMENT USED C/2
 IS THERE A DERRICK OVER THE WELL NO HEIGHT _____ TYPE _____
 CAN TRUCK OR RIG EASILY GET TO WELL YES
 PUMP HOUSE _____ SIZE MATCH _____

CONTRACT NO. 13172 - 100

OUR WELL NO. 2(a) THEIR WELL NO. 2(a) IN TEST HOLE NO. 1

LOCATION OF THE WELL Rolling Air Force Base

INSTALLED FOR Rolling Air Force Base

ADDRESS CITY Warner Rolling COUNTY Houston STATE Georgia

Contract No. 109650-74-0326
 Mid-Loath Construction Co.
 Warner Rolling, Georgia Prime Contractor

YEAR 1974

WELL DATA		INSTALLATION		WELL NO.	
		Robins AFB, Georgia		#2	
ELEVATION (Ft)		LOCATION		DATE CONSUMED	
		Bldg # 164		28 October 1941	
TYPE Drilled Well (Underreamed Gravel - Packed Well)					
DEPTH		DIAMETER		PUMP SETTING DEPTH	
247 ft.		8 in.		120 ft.	
ORIG STATIC WATER LEVEL		DRAWDOWN		RECOVERY TIME	
32 ft.					
TEST DATA		AIR LINES AND GAGES		SPECIFIC CAPACITY (Gal per	
Well capacity	Pumping level	X	Yes	No	Length
950 GPM					
SPECIFIC CAPACITY (Gal per DRAWDOWN =					
WELL PUMPING EQUIPMENT					
TYPE AND MAKE					CAPACITY
Vertical Turbine Layne Pump No. 14428					950 GPM
SUCTION (Ft)		SIZE AND LENGTH		COLUMN	
30 1/2"				8 in.	
HEAD			NUMBER BOWLS	SIZE AND TYPE	NO STAGES
Above grad	Below grad	Total	4 Stage	12" RKHC	4
SERIAL NO.		TYPE	MAKE	HP	RPM
6276089		KF	G. E.	100	1765
STANDBY POWER		MAKE		FRAME	PHASE
YES		Sterling - Model Nr. LC-6		N-6508	3
CYCLES		VOLTAGE		SIZE	
60		220/440			
HP		RPM	DESCRIPTION		
135		1350	Gasoline Engine 135 HP		
CASING AND WELL SCREENING MATERIAL USED				SETTING DEPTH	LENGTH EACH
75' of 20" pit casing cemented in place.					
Top of original 12" screen line 56' - 6"					
Top of 8" screen line at 128' - 6"					
8" stainless steel screen at 130 - 150' and 227 - 247'					
<u>NOTE:</u> Above well was relined in May 1954 to data as shown					
above.					
<u>PUMP:</u> Layne No. 14428					
120' of 8" X 2 1/2" X 1 1/2" Column					
4 Stage 12" RKHC. Bowls					
30' of 6" Suction					
Gear Drive: Johnson 1 1/3 - 1					

No. 3

LAYNE ATLANTIC COMPANY
NORFOLK, VA.

7.3

LOG OF WELL For William Field (Well 2)
 Located at Waller in Waller County, State Georgia
 Date Drilling Started 19 Date Started 19
 Finished Drilling 19 Finished Oct. 10 1920

FORMATIONS AND DEPTH OF WELL

INMENSIONS OF CASING AND SCREEN

TOTAL DEPTH OF ALL STRATA		DEPTH OF EACH STRATUM		FORMATION FOUND AT EACH STRATUM	TOTAL LENGTH OF ALL SCREENS and CASINGS		LENGTH OF EACH SEC. OF SCREEN OR CASING		SPECIFY SCREEN OR CASING	SIZE OF SCREEN OR CASING	GAGE OF SCREEN
FT.	IN.	FT.	IN.		FT.	IN.	FT.	IN.			
25		10		Coarse gravel & sand	75		75		Casing	10	
100		10		Coarse sand	(85 to 100)		130		Casing	10	
110		20		Coarse sand	210		30		Screen	12	
120		0		Coarse sand, chalk, gravel	225		25		Casing	12	
130		0		Hard	205		20		Screen	12	
135		5		Med. chalk							
140		5		Clay & chalk, hard							
150		10		Coarse sand, med. wh. & gray							
160		10		Med. white sand, soft							
170		10		Coarse white sand, very soft							
180		5		Med. brown white sand, soft							
190		10		Coarse yellow sand							
200		10		Coarse fine white sand, soft							
210		5		Soft coarse white sand							
220		5		Hard							
235		15		Chalk & gravel							
240		5		Soft coarse white sand							
245		5		Med. coarse white sand							
247		10		Med. & hard white sand							
247		6		Chalk & coarse sand							
249		15		Chalk & sand							
249		5		Med. fine sand & chalk							
250		15		Med. coarse sand							
255		11		Coarse white sand							
260		10		Med. coarse white sand							
260		15		Coarse sand & chalk							
268		10		Coarse white sand, soft							
278		5		Coarse sand & gravel							
283		10		Fine sand							
294		6		Clay & chalk							
300		0		Coarse sand & gravel							
350		7		Chalk							
365		7		Chalk, clay & coarse sand							
375		10		Hard clay - bottom of hole							

WELL DATA:

Preliminary Test

Date Tested 19 Static Level 3.0
 Production GPM Pumping Level

Permanent Test

Date Tested 19 Static Level
 Production GPM Active St. Level
 Drawdown Pumping Level
 Remarks:

PUMP DATA:

Shop No. 11109 Type Lubr.
 Type Head Size Section
 Depth Setting (BP to MB)
 Size Column Length Section
 Type Bowl Length Air Line
 No. Stages Discharge-
 Cap'y and Head Pressure

MOTOR DATA:

Horsepower Voltage
 RPM Phase
 Type Cycles
 Make Frame No.

WELL DATA		INSTALLATION Robins AFB, Georgia		WELL NO. #3					
ELEVATION (Ft)		LOCATION Bldg # 191		DATE CONSTR ENDED 10 October 1942					
WELL	TYPE Drilled Well (Underreamed Gravel - Packed 1)								
	DEPTH 298 ft.	DIAMETER 8 in.		PUMPSETTING DEPTH 80 ft.					
	ORIG STATIC WATER LEVEL 30 ft.	DRAWDOWN		RECOVERY TIME					
TEST DATA		AIR LINES AND GAGES		SPECIFIC CAPACITY (Gal per ft) GPM _____ = DRAWDOWN					
Well capacity 1300 GPM	Pumping level	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Length					
WELL PUMPING EQUIPMENT									
PUMP	TYPE AND MAKE Vertical Turbine Layne Pump No. 38749				CAPACITY 1300 GPM				
	SUCTION (Ft) 10 ft. 8 in.	SIZE AND LENGTH		COLUMN 8 in.					
	HEAD Above grad Below grad Total			NUMBER BOWLS 5 Stage	SIZE AND TYPE 12" RKHC	NO. STAGES 5			
MOTOR	SERIAL NO. 95128	TYPE	MAKE U. S. Motors	HP 100	RPM 1800	FRAME 7128	PHASE 3	CYCLES 60	VOLTAGE 220/440
	STANDBY POWER NO		MAKE						SIZE
	HP	RPM	DESCRIPTION						
CASING AND WELL SCREENING MATERIAL USED							SETTING DEPTH	LENGTH EACH	
75' of 18" pit casing cemented in place.									
Top of original 12" screen line at 60'									
Top of 8" screen line at 101'									
8" stainless steel screen set at 190' - 210' and 276' - 296'									
80' of 8" X 1 11/16" X 2 1/4" column									
5 Stage 12" RKHC Bowls									
10' of 8" Suction									

#4

NORFOLK, VA.

LOG OF WELL For Johns Hill (Well #4)
 Located at Johns Hill in (near Block 3) County, State Virginia
 Date Drilling Started 19 Date Started 19
 Finished Drilling 19 Finished Nov 19 19

FORMATIONS AND DEPTH OF WELL

DIMENSIONS OF CASING AND SCREEN

TOTAL DEPTH OF ALL STRATA		DEPTH OF EACH STRATUM		FORMATION FOUND AT EACH STRATUM	TOTAL LENGTH OF ALL SCREENS AND CASINGS		LENGTH OF EACH SEC. OF SCREEN OR CASING		SPECIFY SCREEN OR CASING	SIZE OF SCREEN OR CASING	GAUGE OF SCREEN
FT.	IN.	FT.	IN.		FT.	IN.	FT.	IN.			
10		10		Top soil							
20		10		Red clay gravel							
25		5		Red clay coarse sand, hard, little white chalk							
30		5		White chalk, clay, slow drilling							
40		10		Sand & clay slow drilling							
50		10		Coarse sand, fast drilling							
60		10		Coarse sand & clay, med. drilling							
70		10		Coarse sand, soft drilling							
80		10		Blue clay, slow drilling							
100		20		Blue & white chalk, clay, medium drilling							
120		20		Sand, fast drilling							
130		10		White clay, cut hard							
140		10		Fine white sand, cut fast & rough, used water							
150		10		Coarse sand, soft drilling							
160		10		Coarse white sand, soft drilling							

WELL DATA:

Preliminary Test
 Date Tested 19 Static Level
 Production GPM Pumping Level
 Permanent Test
 Date Tested 19 Static Level
 Production GPM Active St. Level
 Drawdown Pumping Level
 Remarks:

PUMP DATA:

Shop No.
 Type Head
 Depth Setting
 Size Column
 Type Bowl
 No. Stages
 Cap'y and Head
 Type Lubr.
 Size Suction (BP to MB)
 Length Suction
 Length Air Line
 Discharge-Pressure

MOTOR DATA:

Horsepower
 RPM
 Type
 Make
 Voltage
 Phase
 Cycles
 Frame No.

NAME OF WELL: **Field**
 Located at **Robline Field** in **Houston** County, State **Georgia**
 Date Drilling Started **April 25** 19 **56** Date Started **April 19** 19 **56**
 Finished Drilling **May 9** 19 **56** Finished **May 24** 19 **56**

Georgia **54**
 19 **56**
 19 **56**

FORMATIONS AND DEPTHS OF WELL

DIMENSIONS OF CASING AND SCREEN

TOTAL DEPTHS OF ALL STRATA		DEPTH OF EACH STRATUM	FORMATION FOUND AT EACH STRATUM	TOTAL LENGTHS OF ALL SCREENS AND CASINGS		LENGTHS OF EACH SEC. OF SCREEN OR CASING	SPECIFY SCREEN OR CASING	SIZE OF SCREEN OR CASING	GUAGE OF SCREEN
FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	IN.	
1		1		32		32		Casing	20 Cemented in place
19		18		Top of screen line is at surface					
33		14		175		175		Casing	12
45		12		220		25		Casing	10
56		11		230		10		Screen	10
65		9		300		70		Casing	10
105		40		310		10		Screen	10
111		6		330		20		Casing	10
121		20		350		20		Screen	10
140		9		360		10		Casing	10
152		12		370		10		Screen	10
165		13		385		10		Casing	10
185		21		Bottom of finished well is at 385' with steel plate welded across screen line.					
204		18							
231		27							
236		5							
248		12							
260		12							
340		80							
360		20							
375		6							
388		17							
402		10							
440		38							

WELL DATA:

Preliminary Test

Date Tested 19 Static Level
 Production GPM Pumping Level

Permanent Test

Date Tested 19 Static Level
 Production 982 GPM Active St. Level 39'
 Drawdown 48' Pumping Level 87'

Remarks: Ran pumping test 12 hours, installed pump from old well #4.

PUMP DATA:

Shop No. 11860 Type Lubr. Oil
 Type Head TF 825 Size Section 8"
 Depth Setting 100' (BP to MB)
 Size Column 4" x 1 1/2" Length Suction 38"
 Type Bowl 12" BRIC Length Air Line 100"
 No. Stages 5 Discharge-
 Cap'y and Head Pressure

MOTOR DATA:

Horsepower 60 Voltage 220/440
 RPM 1800 Phase 3
 Type Cycles 60
 Make, S. Electrical Frame No. 950

No. 4

LAYNE ATLANTIC COMPANY
NORFOLK, VA.

LOG OF WELL For Robin Field (well #4)
 Located at Ballston (New Market, Virginia) County, State Virginia
 Date Drilling Started May 25 1953 Date Started May 19 1953
 Finished Drilling June 15 1953 Finished July 2 1953

FORMATIONS AND DEPTH OF WELL				DIMENSIONS OF CASING AND SCREEN					
TOTAL DEPTH OF ALL STRATA		DEPTH OF EACH STRATUM	FORMATION FOUND AT EACH STRATUM	TOTAL LENGTH OF ALL SCREENS AND CASINGS		LENGTH OF EACH SEC. OF SCREEN OR CASING	SPECIFY SCREEN OR CASING	SIZE OF SCREEN OR CASING	GAUGE OF SCREEN
FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	IN.	
10	20			20	20			Casing 12	Completed in Place
20	10								
25	5								
30	5			200	200			Casing 12	
40	10			210	10			Screen 12	
70	30			240	30			Casing 12	
90	20			270	30			Screen 12	
115	25			290	20			Casing 12	
125	10			300	10			Screen 12	
175	50			360	60			Casing 12	
225	50			370	10			Screen 12	
235	10								
265	30								
272	10								Bottom of Completed well at 280'
285	13								
295	10								
305	10								
380	75								
430	50								

Old well #4, has been discontinued, done away with. and new well drilled

WELL DATA:

Preliminary Test
 Date Tested 19 Static Level
 Production GPM Pumping Level
 Permanent Test
 Date Tested 7/23 1953 Static Level 32' (?)
 Production 775 GPM Active St. Level 32' (?)
 Drawdown 47 Pumping Level 79'
 Remarks: Run test 13 hours. Installed new pump head assembly June 6, 1953.

PUMP DATA:

Shop No. 11860 Type Lubr. Oil
 Type Head 17025 Size Suction 8"
 Depth Setting 140 (BP to MB)
 Size Column 8-1/2" Length Suction 10'
 Type Bowl 12" RRLC Length Air Line
 No. Stages 5 Discharge-
 Cap'y and Head Pressure

MOTOR DATA:

Horsepower 6 Voltage 220/440
 RPM 1750 Phase 3
 Type (S) Cycles 60
 Frame No. 60

WELL DATA		INSTALLATION		WELL NO					
ELEVATION (FT)		LOCATION		DATE INSERTEDED					
		Bldg # 648		24 May 1956					
WELL	TYPE Drilled Well (Underreamed Gravel - Packed well)								
	DEPTH 385 ft.		DIAMETER 8 in.		PUMP SETTING DEPTH 100ft.				
	ORIG STATIC WATER LEVEL 39 ft.		DRAWDOWN		RECOVERY TIME				
TEST DATA		AIR LINES AND LAGES		SPECIFIC CAPACITY (Gal per					
Well capacity 900 GPM	Pumping level	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Length	(1) $\frac{\text{GPM}}{\text{DRAWDOWN}} =$				
WELL PUMPING EQUIPMENT									
PUMP	TYPE AND MAKE Vertical Turbine Layne Pump No. 11860				CAPACITY 900 GPM				
	SUCTION (FT) 28 ft. 8 in.		SIZE AND LENGTH		COLUMN 8 in.				
	HEAD			NUMBER BOWLS	SIZE AND TYPE	NO STAGES			
Above grad			Below grad	Total	5 Stage	12" RKLC	5		
MOTOR	SERIAL NO.	TYPE	MAKE	HP	RPM	FRAME	PHASE	CYCLES	VOLTAGE
	STANDBY POWER NO		MAKE					SIZE	
	HP	RPM	DESCRIPTION						
CASING AND WELL SCREENING MATERIAL USED							SETTING DEPTH	LENGTH EACH	
52' of 20" pit casing cemented in place.									
Top of 12 X 10" screen line at ground surface.									
12" pipe to 195'									
10" pipe from 195' to 220'									
10" stainless steel screen line - 220' to 230'									
300' to 310'									
330' to 350'									
360' to 370'									
NOTE: Attempted to reline old well #4 in February 1956, but was unable to do so.									
PUMP: Layne No. 11860									
100' of 8" X 1 1/2" X 2 1/2" Column									
5 Stage 12" RKLC Bowls									
28' of 8" Suction									

LAYNE ATLANTIC COMPANY
Albany, Georgia

LOG OF WELL For **Mobins Air Force Base** - Well No. 5 (Relocated 1963)
Located **Mobins AFB** in **Houston** County, State **Georgia**
Date Drilling Started **July 25** 19 **63** Date Started 19
Finished Drilling **Oct. 25** 19 **63** Finished 19

FORMATIONS AND DEPTH OF WELL				DIMENSIONS OF CASING AND SCREEN						
TOTAL DEPTH OF ALL STRATA		DEPTH OF EACH STRATUM		FORMATION FOUND AT EACH STRATUM	TOTAL LENGTH OF ALL SCREENS AND CASINGS		LENGTH OF EACH SEC. OF SCREEN OR CASING	SPECIFY SCREEN OR CASING	SIZE OF SCREEN OR CASING	GAUGE OF SCREEN
FT.	IN.	FT.	IN.		FT.	IN.	FT.	IN.	IN.	
1		1		Top Soil	40		90		casing 20	Pit Casing
12		11		Sand Clay					Connected in 26" Hole	
25		14		Coarse Sand					Screen line starts at ground	
38		130		Clay - one band					surface.	
50		12		Sandy Clay	253		253		casing 12	
78		28		Coarse white sand	263		10		screen 12	#7 gauge 33
52		15		Clay, little sand	310		47		Casing 12	
123		30		Coarse sand	328		8		Screen 12	#7 gauge 36
126		6		Clay	350		25		casing 12	
140		31		Coarse sand	365		15		screen 12	#7 gauge 33
185		28		Coarse sand with strk. of yellow clay	370		5		Casing 12	
216		31		Coarse sand	360		10		screen 12	#7 gauge 33
226		10		Coarse sand, strk. of white clay	350		10		casing 12	
236		10		Clay					Bottom of screen line orange potted weld.	
238		102		Coarse sand and little white clay.					Total 40' Layne Stainless Steel Shutter Screen #7 gauge.	
330		52		Coarse sand and some white clay						

WELL DATA:

Preliminary Test

Date Tested 19 63 Static Level 45'
Production 1220 GPM Pumping Level 45'
Permanent Test

Date Tested 8/25 19 63 Static Level 45'
Production 1220 GPM Active St. Level 45'
Drawdown 20' Pumping Level 65'

Remarks: Test pumped well 12 hrs. Installed existing pump and electric motor with new auxiliary engine.

PUMP DATA:

Shop No. 12868A Type Lubr. Oil
Type Head IF629 Size Suction 10"
Depth Setting 130 (BP to MD)
Size Column 10 1/2" x 21" Length Suction 30'
Type Bowl 12" BKMC Length Air Line 121'
No. Stages 5 Discharge
Cup's and Head Pressure

MOTOR DATA:

Horsepower 100 Voltage 440
RPM 1800 Phase 3
Type CFJ Cycles 60
Make US Frame No. 952

Changed existing Johnson Gear Drive model S9100 Serial No. 7723 from 1171 to 1171
New Continental Engine Speed 1800 RPM, Type R2572.

LAYNE ATLANTIC COMPANY
Albany, Georgia

LOG OF WELL For **Robins Air Force Base**
Located **Robins AFB** in **Houston**
Date Drilling Started **July 25** 19 **63** Date Started
Finished Drilling **Oct. 25** 19 **63** Finished

Well No. 5 (Relocated 1963)
County, State **Georgia**

FORMATIONS AND DEPTH OF WELL				DIMENSIONS OF CASING AND SCREEN						
TOTAL DEPTH OF ALL STRATA		DEPTH OF EACH STRATUM		FORMATION FOUND AT EACH STRATUM	TOTAL LENGTH OF ALL SCREENS AND CASINGS		LENGTH OF EACH SEC. OF SCREEN OR CASING	SPECIFY SCREEN OR CASING	SIZE OF SCREEN OR CASING	GAUGE OF SCREEN
FT.	IN.	FT.	IN.		FT.	IN.				
1		1		Top soil	90		90		casing 20	Pit Casing
12		11		Sand Clay					Cemented in 26" Hole	
25		14		Coarse sand					Screen line starts at ground surface.	
38		13		Clay and sand						
50		12		Sandy Clay	253		253		casing 12	
76		28		Coarse white sand	265		10		screen 12	#7 gauge SS
92		15		Clay, little sand	310		47		casing 12	
123		30		Coarse sand	325		5		screen 12	#7 gauge SS
126		6		Clay	380		25		casing 12	
140		31		Coarse sand	365		15		screen 12	#7 gauge SS
188		25		Coarse sand with str. of yellow clay	370		5		Casing 12	
214		31		Coarse sand	380		10		screen 12	#7 gauge SS
226		10		Coarse sand, other of white clay	390		10		casing 12	
236		10		Clay					Bottom of screen line orange pebbled wold.	
238		102		Coarse sand and little white clay					Total 40' Layne Stainless Steel Shutter Screen #7 gauge.	
330		92		Coarse sand and some white clay						

WELL DATA:

Preliminary Test

Date Tested 10/25/63 Static Level 78.2'
Production 1200 GPM Pumping Level 78.2'
Permanent Test 80.0'

Date Tested 8/28/63 Static Level 45.0'
Production 1230 GPM Active St. Level 45.0'
Drawdown 20.0' Pumping Level 45.0'

Remarks: Test Pumped well 12 hrs. Installed existing pump and electric motor with new auxiliary engine.

PUMP DATA:

Shop No. 12868A Type Lubr. Oil
Type Head 1F025 Size Suction 10"
Depth Setting 130 (BP to MD)
Size Column 10 1/2" Length Suction 30"
Type Bowl 12" RMC Length Air Line 121"
No. Stages 5 Discharge Pressure
Cup'y and Head

MOTOR DATA:

Horsepower 100 Voltage 440
RPM 1800 Phase 3
Type CFU Cycles 60
Make US Frame No. 252

Changed existing Johnson Gear Drive Model 39100 Serial No. 7723 from 1F1 to 1F1
New Continental Engine Speed 1800 RPM, Type ND572.

LAYNE ATLANTIC COMPANY

NORFOLK, VA.

25

LOG OF WELL For Widdow Field (Well 25)
 Located at Willsboro in (near Lynch, Va.) County, State Georgia
 Date Drilling Started 19 Date Started 19
 Finished Drilling 19 Finished June 19

FORMATIONS AND DEPTH OF WELL				DIMENSIONS OF CASING AND SCREEN								
TOTAL DEPTH OF ALL STRATA		DEPTH OF EACH STRATUM		FORMATION FOUND AT EACH STRATUM		TOTAL LENGTH OF ALL SCREENS and CASINGS		LENGTH OF EACH SEC. OF SCREEN OR CASING		SPECIFY SCREEN OR CASING	SIZE OF SCREEN OR CASING	GAUGE OF SCREEN
FT.	IN.	FT.	IN.			FT.	IN.	FT.	IN.		IN.	
25		25		red sandy clay		80		80		Casing	18	
35		5		white clay		200		140		Casing	12	
						210		10		Screen	12	7
45		10		rough sandy clay		260		50		Casing	12	
						270		10		Screen	12	
70		30		Coarse sand		290		20		Casing	12	
						300		10		Screen	12	
90		20		Coarse sandy clay		360		60		Casing	12	
						370		10		Screen	12	
115		25		Coarse sand, soft								
130		60		Blue & white clay								
134		40		Soft sand								
135		10		Hard white clay								
145		28		Fine white sand								
155		93		Coarse white sand								

Handwritten note: 25' Max. 6" (with 25' pump) temperature for 10' depth by Layne et al.

WELL DATA:

Preliminary Test

Date Tested 6/10/19 Static Level 33

Production 700 GPM Pumping Level

Permanent Test

Date Tested 19 Static Level

Production GPM Active St. Level

Drawdown Pumping Level

Remarks:

PUMP DATA:

Shop No. 1

Type Lubr.

Type Head

Size Suction

Depth Setting

(IP to MB)

Size Column

Length Suction

Type Bowl

Length Air Line

No. Stages

Discharge

Cap'y and Head

Pressure

WELL DATA			INSTALLATION Robins AFB, Georgia			WELL NO. #5			
ELEVATION (Ft)		LOCATION Bldg # 511			DATE CONSTR ENDED 25 October 1963				
WELL	TYPE Drilled Well (Underreamed Gravel - Packed Well)								
	DEPTH 390 ft.		DIAMETER 10 in.		PUMP SETTING DEPTH 130 ft.				
	ORIG STATIC WATER LEVEL 45 ft.		DRAWDOWN 20 ft.		RECOVERY TIME				
TEST DATA			AIR LINES AND GAGES			SPECIFIC CAPACITY (Gal per ft)			
Well capacity 1050	Pumping level 65 ft.	X	Yes	No	Length 121 ft.	GPM = DRAWDOWN			
WELL PUMPING EQUIPMENT									
PUMP	TYPE AND MAKE Vertical Turbine Layne Pump No. 12868A						CAPACITY 1050		
	SUCTION (Ft) 30 ft.		SIZE AND LENGTH			COLUMN 10 in.			
	HEAD			NUMBER BOWLS		SIZE AND TYPE		NO. STAGES	
Above grad	Below grad	Total	5 Stage		12" HKMC		5		
MOTOR	SERIAL NO. 328387	TYPE CPU	MAKE U.S. Motors	HP 100	RPM 1800	FRAME 982-A	PHASE 3	CYCLES 60	VOLTAGE 220/440
	STANDBY POWER Yes		MAKE Continental Red Seal					SIZE	
	HP 154	RPM 1800	DESCRIPTION Model - 39100						
CASING AND WELL SCREENING MATERIAL USED						SETTING DEPTH	LENGTH EACH		
90' of 20" pit casing cemented in place.									
Screen line starts at ground surface.									
Total 40' Layne stainless steel shutter.									
Screen #7 gauge									
<u>NOTE:</u> This well was drilled to replace the old #5 well.									
<u>PUMP:</u> 130' of 10 X 1 1/2" X 2 1/2" Column									
5 Stage 12" HKMC Bowls									
30' of 10" Suction									
<u>NOTE:</u> Changed existing Johnson Gear Drive									
Model 39100 Serial No. 7723 from 1 1/2:1 to 1:1									
New Continental Engine installed.									

WELL DATA			INSTALLATION Robins AFB, Georgia			WELL NO. #6			
ELEVATION (Ft)		LOCATION Bldg # 1688			DATE CONSTRUCTION 29 July 1943				
W E L L	TYPE Drilled Well (Underreamed Gravel - Packed Well)								
	DEPTH 311 ft.		DIAMETER 8 in.		PUMP SETTING DEPTH 100 ft.				
	ORIG STATIC WATER LEVEL 45 ft.		DRAWDOWN		RECOVERY TIME				
TEST DATA			AIR LINES AND GAGES			SPECIFIC CAPACITY (Gal per ft)			
Well capacity 1500 GPM		Pumping level		Yes	<input checked="" type="checkbox"/>	No	Length	GPM DRAWDOWN	
WELL PUMPING EQUIPMENT									
P U M P	TYPE AND MAKE Vertical Turbine Layne Pump No. 49616							CAPACITY 1500 GPM	
	SUCTION (Ft) 30 ft.		SIZE AND LENGTH 8 in.		COLUMN 8 in.				
	HEAD			NUMBER BOWLS	SIZE AND TYPE	NO. STAGES			
Above grad	Below grad	Total							
M O T O R	SERIAL NO. RJJ221005	TYPE K	MAKE G. E.	HP 150	RPM 1775	FRAME 6542	PHASE 3	CYCLES 60	VOLTAGE 220/440
	STANDBY POWER Yes		MAKE Waukesha						SIZE
	HP 145	RPM 1750	DESCRIPTION Model No. 145-GK						
CASING AND WELL SCREENING MATERIAL USED							SETTING DEPTH	LENGTH EACH	
80' of 18" pit casing submitted in place.									
Top of 12" screen line at 53'									
12" screen set as follows: 151' - 161'									
221' - 231'									
251' - 261'									
301' - 311'									
PUMP:									
100' of 8" Column									
100' of 2 1/2" tubing									
100' stainless steel shaft									
30' of 8" Suction									
A new concrete foundation for pump under work completed									
8 June 1944.									

LAYNE ATLANTIC COMPANY
NORFOLK, VA.

#6

LOG OF WELL For Robbins Field (Well # 6)

Located at Wellston in (near Macon, Ga.) County, State Georgia

Date Drilling Started June 21, 1943 Date Started 19

Finished Drilling 19 Finished July 29, 1943

FORMATIONS AND DEPTH OF WELL				DIMENSIONS OF CASING AND SCREEN			
TOTAL DEPTH OF ALL STRATA	DEPTH OF EACH STRATUM	FORMATION FOUND AT EACH STRATUM	TOTAL LENGTH OF ALL SCREENS AND CASINGS	LENGTH OF EACH SEC. OF SCREEN OR CASING	SPECKS OF SCREEN OR CASING	SIZE OF SCREEN OR CASING	GAUGE OF SCREEN
FT.	IN.	FT. IN.	FT.	IN.	FT.	IN.	IN.
8	8	Red clay, cut slow	80	80	Casing	18	
36	28	Brown sand, fast drilling	151	98	Casing	12	
40	4	White chalk clay	161	10	Screen	12	#7
60	20	Fine white sand, med. drilling	221	60	Casing	12	
			231	10	Screen	12	#7
100	40	Coarse white sand, medium drilling	251	20	Casing	12	
			261	10	Screen	12	#7
157	57	Coarse white sand, medium drilling (lumps of white clay)	301	40	Casing	12	
199	42	Coarse white sand, medium drilling	311	10	Screen	12	#7
230	31	Fine white sand, cut soft					
240	10	Sand & chalk clay, medium drilling					
300	60	Coarse white sand, medium drilling					
315	15	Fine white sand, medium drilling					
367	52	Sandy clay, slow drilling					

Preliminary Test

Date Tested 8/21 1943 Static Level 45
 Production ~~250~~ 1500 GPM Pumping Level 58.5
 Permanent Test Drawdown 12.5

Date Tested 19 Static Level
 Production GPM Active St. Level
 Drawdown Pumping Level
 Remarks:

PUMP DATA:

Shop No. 12969 Type Lubr.
 Type Head Size Suction
 Depth Setting 115.5 (BP to MB)
 Size Column Length Suction
 Type Bowl Length Air Line
 No. Stages Discharge-
 Cap'y and Head Pressure

MOTOR DATA:

Horsepower Voltage
 RPM Phase
 Type Cycles
 Make Frame No.

LAYNE ATLANTIC COMPANY

NORFOLK, VA.

#7

LOG OF WELL For Robins Air Force Base - Capehart Offsets Utilities
 Located at Robins Field in Houston County, State Georgia
 Date Drilling Started Sept. 17 19 58 Date Started Sept. 8 19 58
 Finished Drilling Oct. 9 19 58 Finished Dec. 18 19 58

FORMATIONS AND DEPTH OF WELL

DIMENSIONS OF CASING AND SCREEN

TOTAL DEPTH OF ALL STRATA		DEPTH OF EACH STRATUM		FORMATION FOUND AT EACH STRATUM	TOTAL LENGTH OF ALL SCREENS and CASINGS		LENGTH OF EACH SEC. OF SCREEN OR CASING		SPECIFY SCREENS OR CASING	SIZE OF SCREENS OR CASING	GAUGE OF SCREEN
FT.	IN.	FT.	IN.		FT.	IN.	FT.	IN.			
3		3		Top Soil	165		165		Casing	20	Pit casing cemented in place.
15		12		Red Sand							
65		50		Sand with thin streaks clay							Top of screen line is at 140'.
83		18		Coarse sand							
105		20		Coarse sand with clay particles	200		60		casing	12	
125		20		Coarse sand	266		66		Casing	10	
161		36		Yellowish coarse sand.	286		20		Screen	10	#7 S. S.
168		7		Grey clay & some shell rock	315		29		Casing	10	
198		26		White Coarse sand	325		10		Screen	10	#7 S. S.
195		1		Streak of Clay	340		15		Casing	10	#
203		6		Grey Coarse Sand	350		10		Screen	10	#7 S. S.
220		17		Mixture of Clays. Grey & White	420		70		Casing	10	
230		10		White Coarse Sand	430		10		Screen	10	#7 S. S.
241		12		Clay with streaks of coarse sand	448		18		Casing	10	
251		13		White Coarse sand							Bottom of screen line "Orange Pealed".
256		3		Kaolin							Bottom of completed well is 440'.
264		6		Soft sand.							
266		2		Kaolin							
325		30		Coarse white sand							
339		4		Coarse sand with thin streaks of clay							
355		15		Kaolin							
389		30		Coarse sand. Soft							
400		15		Coarse sand with thin streaks of clay							
414		14		Sand with more clay than above.							
430		16		Pink clay. Slow Drilling							
490		60		Coarse white sand							
				Coarse white sand with very thin streaks of kaolin. Soft.							

WELL DATA:

Preliminary Test

Date Tested 19 Static Level

Production GPM Pumping Level

Permanent Test

Date Tested Oct. 17 1958 Static Level 38

Production 992 GPM Active St. Level 33

Drawdown 24' Pumping Level 62'

Remarks: Ran pumping test 12 hours.

PUMP DATA:

Shop No. 39690 Type Lubr. Oil

Type Head TFG18 Size Suction 8"

Depth Suction 6'

WELL DATA				INSTALLATION Robins AFB, Georgia				WELL NO #7				
ELEVATION (Ft)			LOCATION Bldg # 1004				DATE CONSTRUCTION 18 December 1958					
W F I L	TYPE Drilled Well (Underreamed Gravel - Packed Well)											
	DEPTH 440 ft.			DIAMETER 8 in.			PUMP SETTING DEPTH 100 ft.					
	ORIG STATIC WATER LEVEL 38 ft.			DRAWDOWN 24 ft.			RECOVERY TIME					
TEST DATA			AIR LINES AND GAGES				SPECIFIC CAPACITY (Gal per (1) GPM = DRAWDOWN					
Well capacity 1100 GPM		Pumping level		<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		Length						
WELL PUMPING EQUIPMENT												
P U M P	TYPE AND MAKE Vertical Turbine Layne Pump No. 39690								CAPACITY 1100 GPM			
	SUCTION (Ft) 10 ft. 8 in.		SIZE AND LENGTH				COLUMN 8 in.					
	HEAD			NUMBER BOWLS		SIZE AND TYPE		NO STAGES				
Above grad		Below grad		Total		5 Stage		12 in. RMC		5		
M O T O R	SERIAL NO. 1158727		TYPE CFU		MAKE U.S. Motors		HP 100	RPM 1800	FRAME 504-P4	PHASE 3	CYCLES 60	VOLTAGE 220/440
	STANDBY POWER No			MAKE								
	HP		RPM		DESCRIPTION							
CASING AND WELL SCREENING MATERIAL USED								SETTING DEPTH		LENGTH EACH		
165' of 20" pit casing cemented in place.												
Top of 12" X 10" screen line 140'												
12" pipe 140' to 200'												
10" pipe and screen line below.												
10" stainless steel screen set at: 266' - 286'												
315' - 325'												
340' - 350'												
420' - 430'												
PUMP: Layne No. 39690												
100' of 8" X 1 11/16" X 2 1/2" Column												
5 Stage 12" RMC Bowls												
10' of 8" Suction												

LAYNE ATLANTIC COMPANY

NORFOLK, VA.

#8

LOG OF WELL For GAC Paving Y-08
 Located at Babias Flank in Newton County, State Georgia
 Date Drilling Started October 26 1956 Date Started Oct. 23 1956
 Finished Drilling November 14 1956 Finished Nov 18 1956

FORMATIONS AND DEPTH OF WELL				DIMENSIONS OF CASING AND SCREEN						
TOTAL DEPTH OF ALL STRATA		DEPTH OF EACH STRATUM		FORMATION FOUND AT EACH STRATUM		TOTAL LENGTH OF ALL SCREENS and CASINGS	LENGTH OF EACH SEC. OF SCREEN OR CASING	SPECIFY SCREEN OR CASING	SIZE OF SCREEN OR CASING	GAGE OF SCREEN
FT.	IN.	FT.	IN.			FT.	IN.		IN.	
7		7		Clay		82	82	Casing	20	Pit Casing cemented in place.
20		21		Soft sand						
36		12		Coarse sand & clay						12" screen line is at ground surface.
76		40		Med. soft		170	170	Casing	12	
81		5		Clay. Slow		180	10	Screen	12	#7
104		23		Coarse sand with thin streaks of Kaolin		278	98	Casing	12	
115		11		Clay with sand. Slow		289	10	Screen	12	#7
170		63		Coarse sand with very thin streaks of clay. Drilled fast.		315	20	Screen	12	#7
						375	60	Casing	12	
186		8		Coarse sand with clay. Soft		383	18	Screen	12	#7
207		19		Coarse sand with a little clay.		402	15	Casing	12	
217		10		Coarse sand & clay. Medium						Bottom of screen line storage pooled.
241		24		Coarse sand. Soft.						Completed well depth 400'.
252		11		Kaolin. Slow drilling.						
266		14		Kaolin with thin streaks sand.						
280		14		Kaolin with heavy sand.						

288		8		Coarse speckled sand with streaks of clay. Medium soft.
299		4		Kaolin. Slow drilling.
303		12		Kaolin with coarse sand. Soft.
315		9		Yellow sandy clay. Slow.
326		2		Coarse sand. Soft.
328		2		Clay. Slow drilling.
377		10		Coarse sand soft.
387		21		Clay. slow drilling.
407		9		Coarse sand with streaks of clay.
411		4		Pink clay. Slow
421		10		Mixture of clays with thin streaks of sand. Medium.
431		10		Red clay. Slow drilling.
441		10		Red and white clay. Some sand.
474		33		Sandy red and yellow clay.
492		18		Coarse yellow sand. Soft.
496		3		Yellow and white clay.
508		13		Coarse white sand.
511		3		Kaolin - Slow drilling.
522		11		Coarse white sand.

WELL DATA:
 Preliminary Test
 Date Tested 19 Static Level
 Production GPM Pumping Level
 Permanent Test
 Date Tested Nov. 2 1956 Static Level 9'
 Production 1816 GPM Active St. Level 9'
 Drawdown 20'-40' Pumping Level 39' - 39'
 Remarks: Ran test 17 hours. Pumped 1500 gpm last 4 hours. Installed Johnson Combination Gear Drive and Fairbanks Morse Diesel 400-7 Engine as Standby.

PUMP DATA:
 Shop No. 39623 Type Lubr. Oil
 Type Head 1781M Size Suction 8"
 Depth Setting 80' (BP to MB)
 Size Column 8" x 12" x 24" Length Suction 10'
 Type Bowl 12" B&M Length Air Line 80'
 No. Stages 3 Discharge-
 Cap'y and Head 3700 Pressure

MOTOR DATA:
 Horsepower 7.5 Voltage 440
 RPM 1800 Phase 3
 Type CPU Cycles 60
 Make U. S. Electrical Frame No. 4457

WELL DATA		INSTALL YR/MK		DATE		#8			
ELEVATION (FT)		LOCATION		DATE COMPLETED					
		Bldg # 01							
WELL	TYPE Drilled Well (Underreamed Gravel - Packed Well)								
	DEPTH 400 ft.		DIAMETER 8 in.		PUMP SETTING DEPTH 80 ft.				
	ORIG STATIC WATER LEVEL 9 ft.		DRAWDOWN		RECOVERY TIME				
TEST DATA		AIR LINES AND GAGES			SPECIFIC CAPACITY (GPM/FT)				
Well capacity 900 GPM	Pumping level	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Length	GPM / DRAWDOWN =				
WELL PUMPING EQUIPMENT									
PUMP	TYPE AND MAKE Vertical Turbine Layne Pump No. 39623						CAPACITY 900 GPM		
	SUCTION (FT) 10 ft. 8"		SIZE AND LENGTH		COLUMN 8 in.				
	HEAD			NUMBER BOWLS		SIZE AND TYPE	NO STAGES		
Above grad	Below grad	Total	5 Stage		12" RIMC	5			
MOTOR	SERIAL NO. 1089523	TYPE CFU	MAKE U.S. Motors	HIP 75	RPM 1800	FRAME 445P	PHASE 3	CYCLES 60	VOLTAGE 220/440
	STANDBY POWER Yes		MAKE Fairbanks - Morse, Diesel				SIZE		
	HIP 90	RPM 1800	DESCRIPTION Model Nr. 49B-4½=18S						
CASING AND WELL SCREENING MATERIAL USED						SETTING DEPTH	LENGTH EACH		
82' of 20" pit casing cemented in place.									
Top of 12" screen line at ground surface.									
12" stainless steel screen set at: 170' - 180'									
278' - 288'									
295' - 315'									
375' - 385'									
PUMP: Layne No. 39623									
80' of 8" X 1½" X 2½" Column									
5 Stage 12" RIMC Bowls									
10' of 8" Suction									

APPENDIX G
HAZARD EVALUATION METHODOLOGY

APPENDIX G

USAF INSTALLATION RESTORATION PROGRAM HAZARD ASSESSMENT RATING METHODOLOGY

BACKGROUND

The Department of Defense (DOD) has established a comprehensive program to identify, evaluate, and control problems associated with past disposal practices at DOD facilities. One of the actions required under this program is to:

"develop and maintain a priority listing of contaminated installations and facilities for remedial action based on potential hazard to public health, welfare, and environmental impacts." (Reference: DEQPPM 81-5, 11 December 1981).

Accordingly, the United States Air Force (USAF) has sought to establish a system to set priorities for taking further actions at sites based upon information gathered during the Records Search phase of its Installation Restoration Program (IRP).

The first site rating model was developed in June 1981 at a meeting with representatives from USAF Occupational Environmental Health Laboratory (OEHL), Air Force Engineering Services Center (AFESC), Engineering-Science (ES) and CH₂M Hill. The basis for this model was a system developed for EPA by JRB Associates of McLean, Virginia. The JRB model was modified to meet Air Force needs.

After using this model for 6 months at over 20 Air Force installations, certain inadequacies became apparent. Therefore, on January 26 and 27, 1982, representatives of USAF OEHL, AFESC, various major commands, Engineering Science, and CH₂M Hill met to address the inadequacies. The result of the meeting was a new site rating model designed to present a better picture of the hazards posed by sites at Air Force installations. The new rating model described in this presentation is referred to as the Hazard Assessment Rating Methodology.

PURPOSE

The purpose of the site rating model is to provide a relative ranking of sites of suspected contamination from hazardous substances. This model will assist the Air Force in setting priorities for follow-on site investigations and confirmation work under Phase II of IRP.

This rating system is used only after it has been determined that (1) potential for contamination exists (hazardous wastes present in sufficient quantity), and (2) potential for migration exists. A site can be deleted from consideration for rating on either basis.

DESCRIPTION OF MODEL

Like the other hazardous waste site ranking models, the U.S. Air Force's site rating model uses a scoring system to rank sites for priority attention. However, in developing this model, the designers incorporated some special features to meet specific DOD program needs.

The model uses data readily obtained during the Record Search portion (Phase I) of the IRP. Scoring judgments and computations are easily made. In assessing the hazards at a given site, the model develops a score based on the most likely routes of contamination and the worst hazards at the site. Sites are given low scores only if there are clearly no hazards at the site. This approach meshes well with the policy for evaluating and setting restrictions on excess DOD properties.

As with the previous model, this model considers four aspects of the hazard posed by a specific site: the possible receptors of the contamination, the waste and its characteristics, potential pathways for waste contaminant migration, and any efforts to contain the contaminants. Each of these categories contains a number of rating factors that are used in the overall hazard rating.


The receptors category rating is calculated by scoring each factor, multiplying by a factor weighting constant and adding the weighted scores to obtain a total category score.

The pathways category rating is based on evidence of contaminant migration or an evaluation of the highest potential (worst case) for contaminant migration along one of three pathways. If evidence of contaminant migration exists, the category is given a subscore of 80 to 100 points. For indirect evidence, 80 points are assigned and for direct evidence 100 points are assigned. If no evidence is found, the highest score among three possible routes is used. These routes are surface water migration, flooding, and ground-water migration. Evaluation of each route involves factors associated with the particular migration route. The three pathways are evaluated and the highest score among all four of the potential scores is used.

The waste characteristics category is scored in three steps. First, a point rating is assigned based on an assessment of the waste quantity and the hazard (worst case) associated with the site. The level of confidence in the information is also factored into the assessment. Next, the score is multiplied by a waste persistence factor, which acts to reduce the score if the waste is not very persistent. Finally, the score is further modified by the physical state of the waste. Liquid wastes receive the maximum score, while scores for sludges and solids are reduced.

The scores for each of the three categories are then added together and normalized to a maximum possible score of 100. Then the waste management practice category is scored. Sites at which there is no containment are not reduced in score. Scores for sites with limited containment can be reduced by 5 percent. If a site is contained and well managed, its score can be reduced by 90 percent. The final site score is calculated by applying the waste management practices category factor to the sum of the scores for the other three categories.

HAZARDOUS ASSESSMENT RATING METHODOLOGY FLOW CHART



**FIGURE 2
HAZARDOUS ASSESSMENT RATING FORM**

NAME OF SITE _____
 LOCATION _____
 DATE OF OPERATION OR OCCURRENCE _____
 OWNER/OPERATOR _____
 COMMENTS/DESCRIPTION _____
 SITE RATED BY _____

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site		4		
B. Distance to nearest well		10		
C. Land use/zoning within 1 mile radius		3		
D. Distance to reservation boundary		6		
E. Critical environments within 1 mile radius of site		10		
F. Water quality of nearest surface water body		6		
G. Ground water use of uppermost aquifer		9		
H. Population served by surface water supply within 3 miles downstream of site		6		
I. Population served by ground-water supply within 3 miles of site		6		

Subtotals _____

Receptors subscore (100 X factor score subtotal/maximum score subtotal)

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

1. Waste quantity (S = small, M = medium, L = large) _____

2. Confidence level (C = confirmed, S = suspected) _____

3. Hazard rating (H = high, M = medium, L = low) _____

Factor Subscore A (from 20 to 100 based on factor score matrix)

B. Apply persistence factor

Factor Subscore A X Persistence Factor = Subscore B

_____ X _____ = _____

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

_____ X _____ = _____

III. PATHWAYS

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore _____

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
Distance to nearest surface water		8		
Net precipitation		6		
Surface erosion		8		
Surface permeability		6		
Rainfall intensity		8		

Subtotals _____

Subscore (100 X factor score subtotal/maximum score subtotal) _____

2. Flooding

Subscore (100 x factor score/3) _____

3. Ground-water migration

Depth to ground water		8		
Net precipitation		6		
Soil permeability		8		
Subsurface flows		8		
Direct access to ground water		8		

Subtotals _____

Subscore (100 x factor score subtotal/maximum score subtotal) _____

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore _____

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors _____
 Waste Characteristics _____
 Pathways _____

Total _____ divided by 3 = _____
 Gross Total Score

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

G-6 _____ X _____ =

TABLE 1

HAZARDOUS ASSESSMENT RATING METHODOLOGY GUIDELINES

I. RECEPTORS CATEGORY

Rating Factors	Rating Scale Levels			Multiplier	
	0	1	2		
A. Population within 1,000 feet (includes on-base facilities)	0	1 - 25	26 - 100	Greater than 100	4
B. Distance to nearest water well	Greater than 3 miles	1 to 3 miles	3,001 feet to 1 mile	0 to 3,000 feet	10
C. Land Use/zoning (within 1 mile radius)	Completely remote (zoning not applicable)	Agricultural	Commercial or Industrial	Residential	6
D. Distance to installation boundary	Greater than 2 miles	1 to 2 miles	1,001 feet to 1 mile	0 to 1,000 feet	3
E. Critical environments (within 1 mile radius)	Not a critical environment	Natural areas	Pristine natural areas; minor wetlands; preserved areas; presence of economically important natural resources susceptible to contamination.	Major habitat of an endangered or threatened species; presence of recharge area; major wetlands.	10
F. Water quality/use designation of nearest surface water body	Agricultural or industrial use.	Recreation, propagation and management of fish and wildlife.	Shellfish propagation and harvesting.	Potable water supplies	6
G. Ground-Water use of uppermost aquifer	Not used, other sources readily available.	Commercial, industrial, or irrigation, very limited other water sources.	Drinking water, municipal water available.	Drinking water, no municipal water available; commercial, industrial, or irrigation, no other water source available.	9
H. Population served by surface water supplies within 3 miles downstream of site	0	1 - 50	51 - 1,000	Greater than 1,000	6
I. Population served by aquifer supplies within 3 miles of site	0	1 - 50	51 - 1,000	Greater than 1,000	6

TABLE 1 (Continued)
 HAZARDOUS ASSESSMENT RATING METHODOLOGY GUIDELINES (Cont'd)

II. WASTE CHARACTERISTICS

- A-1 Hazardous Waste Quantity
- S = Small quantity (<5 tons or 20 drums of liquid)
 - M = Moderate quantity (5 to 20 tons or 21 to 85 drums of liquid)
 - L = Large quantity (>20 tons or 85 drums of liquid)
- A-2 Confidence Level of Information
- C = Confirmed confidence level (minimum criteria below)
 - o Verbal reports from interviewer (at least 2) or written information from the records.
 - o Knowledge of types and quantities of wastes generated by shops and other areas on base.
 - o Based on the above, a determination of the types and quantities of waste disposed of at the site.
 - S = Suspected confidence level
 - o No verbal reports or conflicting verbal reports and no written information from the records.
 - o Logic based on a knowledge of the types and quantities of hazardous wastes generated at the base, and a history of past waste disposal practices indicate that these wastes were disposed of at a site.

A-3 Hazard Rating

Hazard Category	Rating Scale Levels		
	0	1	2
Toxicity	Sax's Level 0 Flash point greater than 200°F	Sax's Level 1 Flash point at 140°F to 200°F	Sax's Level 2 Flash point at 80°F to 140°F
Ignitability	At or below background levels	1 to 3 times back-ground levels	3 to 5 times back-ground levels
Radioactivity			Over 5 times back-ground levels

Use the highest individual rating based on toxicity, ignitability and radioactivity and determine the hazard rating.

Hazard Rating	Points
High (H)	3
Medium (M)	2
Low (L)	1

TABLE 1 (Continued)

HAZARDOUS ASSESSMENT RATING METHODOLOGY GUIDELINES (Cont'd)

II. WASTE CHARACTERISTICS (Continued)

Waste Characteristics Matrix

Point Rating	Hazardous Waste Quantity	Confidence Level of Information	Hazard Rating
100	L	C	H
80	L	C	M
	M	C	H
70	L	S	H
60	S	C	H
	M	C	M
50	L	S	M
	L	C	L
	M	S	H
40	S	C	M
	S	S	H
	M	S	M
30	M	C	L
	M	S	L
	S	S	M
20	S	S	L

Notes:
 For a site with more than one hazardous waste, the waste quantities may be added using the following rules:
 Confidence Level
 o Confirmed confidence levels (C) can be added
 o Suspected confidence levels (S) can be added
 o Confirmed confidence levels cannot be added with suspected confidence levels
 Waste Hazard Rating
 o Wastes with the same hazard rating can be added
 o Wastes with different hazard ratings can only be added in a downgrade mode, e.g., MCM + SCH = LCM if the total quantity is greater than 20 tons.
 Example: Several wastes may be present at a site, each having an MCM designation (60 points). By adding the quantities of each waste, the designation may change to LCM (80 points). In this case, the correct point rating for the waste is 80.

B. Persistence Multiplier for Point Rating

Persistence Criteria	Multiply Point Rating From Part A by the Following
Metals, polycyclic compounds, and halogenated hydrocarbons	1.0
Substituted and other ring compounds	0.9
Straight chain hydrocarbons	0.8
Easily biodegradable compounds	0.4

C. Physical State Multiplier

Physical State	Multiply Point Total From Parts A and B by the Following
Liquid	1.0
Sludge	0.75
Solid	0.50

TABLE 1 (Continued)

HAZARDOUS ASSESSMENT RATING METHODOLOGY GUIDELINES (Cont'd)

III. PATHWAYS CATEGORY

A. Evidence of Contamination

Direct evidence is obtained from laboratory analyses of hazardous contaminants present above natural background levels in surface water, ground water, or air. Evidence should confirm that the source of contamination is the site being evaluated.

Indirect evidence might be from visual observation (i.e., leachate), vegetation stress, sludge deposits, presence of taste and odors in drinking water, or reported discharges that cannot be directly confirmed as resulting from the site, but the site is greatly suspected of being a source of contamination.

B-1 POTENTIAL FOR SURFACE WATER CONTAMINATION

Rating Factor	Rating Scale Levels			Multiplier
	0	1	2	
Distance to nearest surface water (includes drainage ditches and storm sewers)	Greater than 1 mile	2,000 feet to 1 mile	501 feet to 2,000 feet	8
Net precipitation	Less than -10 in.	-10 to + 5 in.	+5 to +20 in.	6
Surface erosion	None	Slight	Moderate	8
Surface permeability	0% to 15% clay (>10 ⁻² cm/sec)	15% to 30% clay (10 ⁻² to 10 ⁻⁶ cm/sec)	30% to 50% clay (>10 ⁻⁶ to 10 ⁻⁸ cm/sec)	6
Rainfall intensity based on 1 year 24-hr rainfall	<1.0 inch	1.0-2.0 inches	2.1-3.0 inches	8

B-2 POTENTIAL FOR FLOODING

Floodplain	Beyond 100-year floodplain	In 25-year floodplain	In 10-year floodplain	Floods annually	1
------------	----------------------------	-----------------------	-----------------------	-----------------	---

B-3 POTENTIAL FOR GROUND-WATER CONTAMINATION

Depth to ground water	Greater than 500 ft	50 to 500 feet	11 to 50 feet	0 to 10 feet	8
Net precipitation	Less than -10 in.	-10 to +5 in.	+5 to +20 in.	Greater than +20 in.	6
Soil permeability	Greater than 50% clay (>10 ⁻⁶ cm/sec)	30% to 50% clay (10 ⁻⁶ to 10 ⁻⁸ cm/sec)	15% to 30% clay (10 ⁻² to 10 ⁻⁶ cm/sec)	0% to 15% clay (<10 ⁻² cm/sec)	8
Subsurface flows	Bottom of site greater than 5 feet above high ground-water level	Bottom of site occasionally submerged	Bottom of site frequently submerged	Bottom of site located below mean ground-water level	8
Direct access to ground water (through faults, fractures, faulty well casings, subsidence fissures, etc.)	No evidence of risk	Low risk	Moderate risk	High risk	8

TABLE 1 (Continued)
HAZARDOUS ASSESSMENT RATING METHODOLOGY GUIDELINES (Cont'd)

IV. WASTE MANAGEMENT PRACTICES CATEGORY

A. This category adjusts the total risk as determined from the receptors, pathways, and waste characteristics categories for waste management practices and engineering controls designed to reduce this risk. The total risk is determined by first averaging the receptors, pathways, and waste characteristics subscores.

B. WASTE MANAGEMENT PRACTICES FACTOR

The following multipliers are then applied to the total risk points (from A):

<u>Waste Management Practice</u>	<u>Multiplier</u>
No containment	1.0
Limited containment	0.95
Fully contained and in full compliance	0.10

Guidelines for fully contained:

Landfills:

- o Clay cap or other impermeable cover
- o Leachate collection system
- o Liners in good condition
- o Adequate monitoring wells

Surface Impoundments:

- o Liners in good condition
- o Sound dikes and adequate freeboard
- o Adequate monitoring wells

Spills:

- o Quick spill cleanup action taken
- o Contaminated soil removed
- o Soil and/or water samples confirm total cleanup of the spill

Fire Protection Training Areas:

- o Concrete surface and berms
- o Oil/water separator for pretreatment of runoff
- o Effluent from oil/water separator to treatment plant

General Note: If data are not available or known to be complete the factor ratings under items I-A through I, III-B-1 or III-B-3, then leave blank for calculation of factor score and maximum possible score.

APPENDIX H
SITE RATING FORMS

SITE RATING FORMS

TABLE OF CONTENTS

<u>Site</u>	<u>Page</u>
Sludge Lagoon	H-1
Landfill No. 4	H-3
DDT Spill at Pesticide Storage Area	H-5
Fire Protection Training Area No. 2	H-7
Landfill No. 1	H-9
Landfill No. 2	H-11
JP-4 Spill (1965)	H-13
Hazardous Waste Burial Site	H-15
Fire Protection Training Area No. 1	H-17
Laboratory Chemical Disposal Site	H-19
Landfill No. 3	H-21
Fire Training Pit No. 3	H-23
Radioactive (Solid) Waste Burial Site	H-25

HAZARDOUS ASSESSMENT RATING FORM

Page 1 of 2

NAME OF SITE Sludge Lagoon
 LOCATION North of and Adjacent to Landfill No. 4
 DATE OF OPERATION OR OCCURRENCE 1962 to 1978
 OWNER/OPERATOR Robins AFB
 COMMENTS/DESCRIPTION _____
 SITE RATED BY S. J. Schneider

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site	2	4	8	12
B. Distance to nearest well	3	10	30	30
C. Land use/zoning within 1 mile radius	2	3	6	9
D. Distance to reservation boundary	2	6	12	18
E. Critical environments within 1 mile radius of site	2	10	20	30
F. Water quality of nearest surface water body	0	6	0	18
G. Ground water use of uppermost aquifer	1	9	9	27
H. Population served by surface water supply within 3 miles downstream of site	0	6	0	18
I. Population served by ground-water supply within 3 miles of site	3	6	18	18
Subtotals			<u>103</u>	<u>180</u>
Receptors subscore (100 X factor score subtotal/maximum score subtotal)				<u>57</u>

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

1. Waste quantity (S = small, M = medium, L = large)
2. Confidence level (C = confirmed, S = suspected)
3. Hazard rating (H = high, M = medium, L = low)

L
 C
 H

Factor Subscore A (from 20 to 100 based on factor score matrix)

100

B. Apply persistence factor

Factor Subscore A X Persistence Factor = Subscore B

$$\frac{100}{\quad} \times \frac{1.0}{\quad} = \frac{100}{\quad}$$

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

$$\frac{100}{\quad} \times \frac{0.75}{\quad} = \frac{75}{\quad}$$

III. PATHWAYS

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore 100

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Distance to nearest surface water		8		
Net precipitation		6		
Surface erosion		8		
Surface permeability		6		
Rainfall intensity		8		

Subtotals _____

Subscore (100 X factor score subtotal/maximum score subtotal) N/A

2. Flooding

		1		
--	--	---	--	--

Subscore (100 x factor score/3) N/A

3. Ground-water migration

Depth to ground water		8		
Net precipitation		6		
Soil permeability		8		
Subsurface flows		8		
Direct access to ground water		8		

Subtotals _____ N/A

Subscore (100 x factor score subtotal/maximum score subtotal) _____

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore 100

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors		<u>57</u>
Waste Characteristics		<u>75</u>
Pathways		<u>100</u>
Total	232	divided by 3 = <u>77</u>
		Gross Total Score

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

77 x 1.0 = 77

HAZARDOUS ASSESSMENT RATING FORM

NAME OF SITE Landfill No. 4
 LOCATION Southeast of Industrial Waste Treatment Plant No. 1
 DATE OF OPERATION OR OCCURRENCE 1965 to 1978
 OWNER/OPERATOR Robins AFB
 COMMENTS/DESCRIPTION _____
 SITE RATED BY S / [Signature]

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site	3	4	12	12
B. Distance to nearest well	3	10	30	30
C. Land use/zoning within 1 mile radius	2	3	6	9
D. Distance to reservation boundary	2	6	12	18
E. Critical environments within 1 mile radius of site	2	10	20	30
F. Water quality of nearest surface water body	0	6	0	18
G. Ground water use of uppermost aquifer	1	9	9	27
H. Population served by surface water supply within 3 miles downstream of site	0	6	0	18
I. Population served by ground-water supply within 3 miles of site	3	6	18	18
Subtotals			<u>107</u>	<u>180</u>
Receptors subscore (100 X factor score subtotal/maximum score subtotal)				<u>59</u>

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

- | | |
|--|---|
| 1. Waste quantity (S = small, M = medium, L = large) | M |
| 2. Confidence level (C = confirmed, S = suspected) | C |
| 3. Hazard rating (H = high, M = medium, L = low) | H |

Factor Subscore A (from 20 to 100 based on factor score matrix) 80

B. Apply persistence factor

Factor Subscore A X Persistence Factor = Subscore B

$$\underline{80} \quad \times \quad \underline{1} \quad = \quad \underline{80}$$

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

$$\underline{80} \quad \times \quad \underline{0.75} \quad = \quad \underline{60}$$

III. PATHWAYS

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore 100

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
Distance to nearest surface water		8		
Net precipitation		6		
Surface erosion		8		
Surface permeability		6		
Rainfall intensity		8		

Subtotals _____ N/A

Subscore (100 X factor score subtotal/maximum score subtotal) _____

2. Flooding

		1		
--	--	---	--	--

Subscore (100 x factor score/3) N/A

3. Ground-water migration

Depth to ground water		8		
Net precipitation		6		
Soil permeability		8		
Subsurface flows		8		
Direct access to ground water		8		

Subtotals _____

Subscore (100 x factor score subtotal/maximum score subtotal) N/A

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore 100

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors	<u>59</u>
Waste Characteristics	<u>60</u>
Pathways	<u>100</u>

Total 219 divided by 3 = 73
Gross Total Score

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

73 x 1.0 = 73

HAZARDOUS ASSESSMENT RATING FORM

Page 1 of 2

NAME OF SITE DDT Spill at Pesticide Storage Area
 LOCATION Asphalt Pad Adjacent to Building 295
 DATE OF OPERATION OR OCCURRENCE 1979
 OWNER/OPERATOR Robins AFB
 COMMENTS/DESCRIPTION DDT solution spilled over a gravel lot
 SITE RATED BY E. J. Schneider

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site	3	4	12	12
B. Distance to nearest well	3	10	30	30
C. Land use/zoning within 1 mile radius	2	3	6	9
D. Distance to reservation boundary	3	6	18	18
E. Critical environments within 1 mile radius of site	0	10	0	30
F. Water quality of nearest surface water body	0	6	0	18
G. Ground water use of uppermost aquifer	1	9	9	27
H. Population served by surface water supply within 3 miles downstream of site	0	6	0	18
I. Population served by ground-water supply within 3 miles of site	3	6	18	18
Subtotals			<u>93</u>	<u>180</u>
Receptors subcore (100 X factor score subtotal/maximum score subtotal)				<u><u>51</u></u>

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

- | | |
|---|-----------|
| 1. Waste quantity (S = small, M = medium, L = large) | <u>S</u> |
| 2. Confidence level (C = confirmed, S = suspected) | <u>C</u> |
| 3. Hazard rating (H = high, M = medium, L = low) | <u>H</u> |
| Factor Subscore A (from 20 to 100 based on factor score matrix) | <u>60</u> |

B. Apply persistence factor

Factor Subscore A X Persistence Factor = Subscore B

$$\underline{60} \times \underline{1.0} = \underline{60}$$

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

$$\underline{60} \times \underline{1.0} = \underline{\underline{60}}$$

III. PATHWAYS

Rating Factor **Factor Rating (0-3)** **Multiplier** **Factor Score** **Maximum Possible Score**

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore 100

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Distance to nearest surface water		8		
Net precipitation		6		
Surface erosion		8		
Surface permeability		6		
Rainfall intensity		8		

Subtotals _____

Subscore (100 X factor score subtotal/maximum score subtotal) _____

2. Flooding

		1		
--	--	---	--	--

Subscore (100 x factor score/3) _____

3. Ground-water migration

Depth to ground water		8		
Net precipitation		6		
Soil permeability		8		
Subsurface flows		8		
Direct access to ground water		8		

Subtotals _____

Subscore (100 x factor score subtotal/maximum score subtotal) _____

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore 100

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors			51	
Waste Characteristics			<u>60</u>	
Pathways			<u>100</u>	
Total	211	divided by 3	70	
			<u>70</u>	Gross Total Score

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

70 x 1.0 = 70

HAZARDOUS ASSESSMENT RATING FORM

NAME OF SITE Fire Protection Training Area No. 2
 LOCATION Near Northwest Corner of Luna Lake
 DATE OF OPERATION OR OCCURRENCE Mid-1950's to mid-1960's
 OWNER/OPERATOR Robins AFB
 COMMENTS/DESCRIPTION May have been several pit areas between Luna & Scout Lakes
 SITE RATED BY E. J. Schneider

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site	1	4	4	12
B. Distance to nearest well	3	10	30	30
C. Land use/zoning within 1 mile radius	1	3	3	9
D. Distance to reservation boundary	2	6	12	18
E. Critical environments within 1 mile radius of site	0	10	0	30
F. Water quality of nearest surface water body	1	6	6	18
G. Ground water use of uppermost aquifer	1	9	9	27
H. Population served by surface water supply within 3 miles downstream of site	0	6	0	18
I. Population served by ground-water supply within 3 miles of site	3	6	18	18
Subtotals			<u>82</u>	<u>180</u>
Receptors subscore (100 X factor score subtotal/maximum score subtotal)				<u><u>46</u></u>

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

- | | |
|--|----------|
| 1. Waste quantity (S = small, M = medium, L = large) | <u>L</u> |
| 2. Confidence level (C = confirmed, S = suspected) | <u>C</u> |
| 3. Hazard rating (H = high, M = medium, L = low) | <u>H</u> |

Factor Subscore A (from 20 to 100 based on factor score matrix) 100

B. Apply persistence factor

Factor Subscore A X Persistence Factor = Subscore B

$$\underline{100} \times \underline{0.9} = \underline{90}$$

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

$$\underline{90} \times \underline{1.0} = \underline{\underline{90}}$$

III. PATHWAYS

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore N/A

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
Distance to nearest surface water	3	8	24	24
Net precipitation	1	6	6	18
Surface erosion	0	8	0	24
Surface permeability	1	6	6	18
Rainfall intensity	3	8	24	24

Subtotals 60 108

Subscore (100 X factor score subtotal/maximum score subtotal) 55

2. Flooding	0	1	0	3
-------------	---	---	---	---

Subscore (100 x factor score/3) 0

3. Ground-water migration

Depth to ground water	2	8	16	24
Net precipitation	1	6	6	18
Soil permeability	2	8	16	24
Subsurface flows	1	8	8	24
Direct access to ground water	0	8	0	24

Subtotals 46 114

Subscore (100 x factor score subtotal/maximum score subtotal) 40

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore 55

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors	<u>46</u>
Waste Characteristics	<u>90</u>
Pathways	<u>55</u>
Total <u>191</u> divided by 3 =	<u>64</u>
	Gross Total Score

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

64 x 1.0 = 64

HAZARDOUS ASSESSMENT RATING FORM

Page 1 of 2

NAME OF SITE Landfill No. 1
 LOCATION East of Second Street near Fuel Storage Tanks
 DATE OF OPERATION OR OCCURRENCE 1946-1951
 OWNER/OPERATOR Robins AFB
 COMMENTS/DESCRIPTION Site was previously filled with sandy loam
 SITE RATED BY E. J. Schneider

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site	2	4	8	12
B. Distance to nearest well	3	10	30	30
C. Land use/zoning within 1 mile radius	2	3	6	9
D. Distance to reservation boundary	2	6	12	18
E. Critical environments within 1 mile radius of site	0	10	0	30
F. Water quality of nearest surface water body	0	6	0	18
G. Ground water use of uppermost aquifer	1	9	9	27
H. Population served by surface water supply within 3 miles downstream of site	0	6	0	18
I. Population served by ground-water supply within 3 miles of site	3	6	18	18
Subtotals			<u>83</u>	<u>180</u>
Receptors subscore (100 X factor score subtotal/maximum score subtotal)				<u>46</u>

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

- | | |
|--|---|
| 1. Waste quantity (S = small, M = medium, L = large) | M |
| 2. Confidence level (C = confirmed, S = suspected) | S |
| 3. Hazard rating (H = high, M = medium, L = low) | H |

Factor Subscore A (from 20 to 100 based on factor score matrix) 50

B. Apply persistence factor

Factor Subscore A X Persistence Factor = Subscore B

$$\underline{50} \times \underline{1.0} = \underline{50}$$

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

$$\underline{50} \times \underline{1.0} = \underline{50}$$

III. PATHWAYS

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore 80

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
Distance to nearest surface water	1	8	8	24
Net precipitation	1	6	6	18
Surface erosion	1	8	8	24
Surface permeability	1	6	6	18
Rainfall intensity	3	8	24	24
Subtotals			<u>52</u>	<u>108</u>

Subscore (100 X factor score subtotal/maximum score subtotal) 48

2. Flooding

	0	1	0	3
--	---	---	---	---

Subscore (100 x factor score/3) 0

3. Ground-water migration

Depth to ground water	2	8	16	24
Net precipitation	1	6	6	18
Soil permeability	2	8	16	24
Subsurface flows	1	8	8	24
Direct access to ground water	0	8	0	24
Subtotals			<u>46</u>	<u>114</u>

Subscore (100 x factor score subtotal/maximum score subtotal) 40

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore 80

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors	<u>46</u>
Waste Characteristics	<u>50</u>
Pathways	<u>80</u>
Total <u>176</u> divided by 3 =	<u>59</u>
	Gross Total Score

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

59 x 1.0 = 59

HAZARDOUS ASSESSMENT RATING FORM

Page 1 of 2

NAME OF SITE Landfill No. 2
 LOCATION North of Second Street near Main Runway
 DATE OF OPERATION OR OCCURRENCE 1951 to 1963
 OWNER/OPERATOR Robins AFB
 COMMENTS/DESCRIPTION Site was previously filled with sandy loam.
 SITE RATED BY E. J. Schneider

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site	0	4	0	12
B. Distance to nearest well	3	10	30	30
C. Land use/zoning within 1 mile radius	2	3	6	9
D. Distance to reservation boundary	2	6	12	18
E. Critical environments within 1 mile radius of site	0	10	0	30
F. Water quality of nearest surface water body	0	6	0	18
G. Ground water use of uppermost aquifer	1	9	9	27
H. Population served by surface water supply within 3 miles downstream of site	0	6	0	18
I. Population served by ground-water supply within 3 miles of site	3	6	18	18
Subtotals			<u>75</u>	<u>180</u>
Receptors subscore (100 X factor score subtotal/maximum score subtotal)				<u><u>42</u></u>

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

- | | |
|---|-----------|
| 1. Waste quantity (S = small, M = medium, L = large) | <u>L</u> |
| 2. Confidence level (C = confirmed, S = suspected) | <u>S</u> |
| 3. Hazard rating (H = high, M = medium, L = low) | <u>H</u> |
| Factor Subscore A (from 20 to 100 based on factor score matrix) | <u>70</u> |

B. Apply persistence factor
 Factor Subscore A X Persistence Factor = Subscore B

$$\underline{70} \times \underline{1.0} = \underline{70}$$

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

$$\underline{70} \times \underline{0.75} = \underline{52.5}$$

III. PATHWAYS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
---------------	---------------------	------------	--------------	------------------------

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore 80

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Distance to nearest surface water	3	8	24	24
Net precipitation	1	6	6	18
Surface erosion	1	8	8	24
Surface permeability	1	6	6	18
Rainfall intensity	3	8	24	24
Subtotals			<u>68</u>	<u>108</u>

Subscore (100 X factor score subtotal/maximum score subtotal) 63

2. Flooding	0	1	0	3
-------------	---	---	---	---

Subscore (100 x factor score/3) 0

3. Ground-water migration

Depth to ground water	2	8	16	24
Net precipitation	1	6	6	18
Soil permeability	2	8	16	24
Subsurface flows	2	8	16	24
Direct access to ground water	0	8	0	24
Subtotals			<u>54</u>	<u>114</u>

Subscore (100 x factor score subtotal/maximum score subtotal) 47

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore 80

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors	42
Waste Characteristics	<u>52.5</u>
Pathways	<u>80</u>
Total <u>174.5</u> divided by 3 =	<u>58</u>
	Gross Total Score

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

58 x 1.0 = 58

HAZARDOUS ASSESSMENT RATING FORM

Page 1 of 2

NAME OF SITE JP-4 Spill
 LOCATION POL Bulk Storage Area
 DATE OF OPERATION OR OCCURRENCE 1965
 OWNER/OPERATOR Robins AFB
 COMMENTS/DESCRIPTION Leak in four-inch diameter JP-4 supply line
 SITE RATED BY E. J. Adreeda

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site	2	4	8	12
B. Distance to nearest well	3	10	30	30
C. Land use/zoning within 1 mile radius	2	3	6	9
D. Distance to reservation boundary	2	6	12	18
E. Critical environments within 1 mile radius of site	0	10	0	30
F. Water quality of nearest surface water body	0	6	0	18
G. Ground water use of uppermost aquifer	1	9	9	27
H. Population served by surface water supply within 3 miles downstream of site	0	6	0	18
I. Population served by ground-water supply within 3 miles of site	3	6	18	18
Subtotals			<u>83</u>	<u>180</u>
Receptors subscore (100 X factor score subtotal/maximum score subtotal)				<u>46</u>

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

- | | |
|--|----------|
| 1. Waste quantity (S = small, M = medium, L = large) | <u>L</u> |
| 2. Confidence level (C = confirmed, S = suspected) | <u>S</u> |
| 3. Hazard rating (H = high, M = medium, L = low) | <u>M</u> |

Factor Subscore A (from 20 to 100 based on factor score matrix) 50

B. Apply persistence factor
 Factor Subscore A X Persistence Factor = Subscore B

$$\underline{50} \times \underline{0.9} = \underline{45}$$

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

$$\underline{45} \times \underline{1.0} = \underline{45}$$

III. PATHWAYS

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore 80

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
Distance to nearest surface water	2	8	16	24
Net precipitation	1	6	6	18
Surface erosion	N/A	8	-	-
Surface permeability	1	6	6	18
Rainfall intensity	3	8	24	24
Subtotals			<u>52</u>	<u>84</u>

Subscore (100 X factor score subtotal/maximum score subtotal) 62

2. Flooding	0	1	0	3
Subscore (100 x factor score/3)			<u>0</u>	

3. Ground-water migration

Depth to ground water	2	8	16	24
Net precipitation	1	6	6	18
Soil permeability	2	8	16	24
Subsurface flows	1	8	8	24
Direct access to ground water	0	8	0	24
Subtotals			<u>46</u>	<u>114</u>

Subscore (100 x factor score subtotal/maximum score subtotal) 40

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore 80

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors	<u>46</u>
Waste Characteristics	<u>45</u>
Pathways	<u>80</u>
Total <u>171</u> divided by 3 =	<u>57</u>
	Gross Total Score

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

57 x 1.0 = 57

HAZARDOUS ASSESSMENT RATING FORM

Page 1 of 2

NAME OF SITE Hazardous Waste Burial Site
 LOCATION Near Radioactive (Solid) waste Disposal Site
 DATE OF OPERATION OR OCCURRENCE 1976, 1977
 OWNER/OPERATOR Robins AFB
 COMMENTS/DESCRIPTION _____
 SITE RATED BY E. J. Schreiner

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site	1	4	4	12
B. Distance to nearest well	3	10	30	30
C. Land use/zoning within 1 mile radius	0	3	0	9
D. Distance to reservation boundary	3	6	18	18
E. Critical environments within 1 mile radius of site	0	10	0	30
F. Water quality of nearest surface water body	0	6	0	18
G. Ground water use of uppermost aquifer	1	9	9	27
H. Population served by surface water supply within 3 miles downstream of site	0	6	0	18
I. Population served by ground-water supply within 3 miles of site	3	6	18	18

Subtotals 79 180

Receptors subscore (100 X factor score subtotal/maximum score subtotal) 44

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

- | | |
|--|----------|
| 1. Waste quantity (S = small, M = medium, L = large) | <u>M</u> |
| 2. Confidence level (C = confirmed, S = suspected) | <u>C</u> |
| 3. Hazard rating (H = high, M = medium, L = low) | <u>H</u> |

80

Factor Subscore A (from 20 to 100 based on factor score matrix)

B. Apply persistence factor
 Factor Subscore A X Persistence Factor = Subscore B

$$\underline{80} \times \underline{1.0} = \underline{80}$$

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

$$\underline{80} \times \underline{1.0} = \underline{80}$$

III. PATHWAYS

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore N/A

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
Distance to nearest surface water	1	8	8	24
Net precipitation	1	6	6	18
Surface erosion	1	8	8	24
Surface permeability	1	6	6	18
Rainfall intensity	3	8	24	24
Subtotals			<u>52</u>	<u>108</u>

Subscore (100 X factor score subtotal/maximum score subtotal) 48

2. Flooding	0	1	0	3
-------------	---	---	---	---

Subscore (100 x factor score/3) 0

3. Ground-water migration

Depth to ground water	2	8	16	24
Net precipitation	1	6	6	18
Soil permeability	2	8	16	24
Subsurface flows	1	8	8	24
Direct access to ground water	0	8	0	24
Subtotals			<u>46</u>	<u>114</u>

Subscore (100 x factor score subtotal/maximum score subtotal) 40

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore 48

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors	<u>44</u>
Waste Characteristics	<u>80</u>
Pathways	<u>48</u>

Total 172 divided by 3 = 57

Gross Total Score

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

57 x 0.95 = 54

HAZARDOUS ASSESSMENT RATING FORM

Page 1 of 2

NAME OF SITE Fire Protection Training Area No. 1
 LOCATION Second Street near Bulk Fuel Storage Tank
 DATE OF OPERATION OR OCCURRENCE 1943 to mid-1950's
 OWNER/OPERATOR Robins AFB
 COMMENTS/DESCRIPTION Exact location not determined
 SITE RATED BY E. J. Schneider

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site	1	4	4	12
B. Distance to nearest well	3	10	30	30
C. Land use/zoning within 1 mile radius	2	3	6	9
D. Distance to reservation boundary	2	6	12	18
E. Critical environments within 1 mile radius of site	0	10	0	30
F. Water quality of nearest surface water body	0	6	0	18
G. Ground water use of uppermost aquifer	1	9	9	27
H. Population served by surface water supply within 3 miles downstream of site	0	6	0	18
I. Population served by ground-water supply within 3 miles of site	3	6	18	18

Subtotals 79 180

Receptors subscore (100 X factor score subtotal/maximum score subtotal) 44

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

- | | |
|--|----------|
| 1. Waste quantity (S = small, M = medium, L = large) | <u>M</u> |
| 2. Confidence level (C = confirmed, S = suspected) | <u>S</u> |
| 3. Hazard rating (H = high, M = medium, L = low) | <u>H</u> |

Factor Subscore A (from 20 to 100 based on factor score matrix) 50

B. Apply persistence factor

Factor Subscore A X Persistence Factor = Subscore B

$$\underline{50} \times \underline{1.0} = \underline{50}$$

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

$$\underline{50} \times \underline{1.0} = \underline{\underline{50}}$$

III. PATHWAYS

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore N/A

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
Distance to nearest surface water	2	8	16	24
Net precipitation	1	6	6	18
Surface erosion	N/A	8	-	-
Surface permeability	1	6	6	18
Rainfall intensity	3	8	24	24
Subtotals			<u>52</u>	<u>84</u>

Subscore (100 X factor score subtotal/maximum score subtotal) 62

2. Flooding	0	1	0	3
-------------	---	---	---	---

Subscore (100 x factor score/3) 0

3. Ground-water migration

Depth to ground water	2	8	16	24
Net precipitation	1	6	6	18
Soil permeability	2	8	16	24
Subsurface flows	1	8	8	24
Direct access to ground water	0	8	0	24
Subtotals			<u>46</u>	<u>114</u>

Subscore (100 x factor score subtotal/maximum score subtotal) 40

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore 62

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors	<u>44</u>
Waste Characteristics	<u>50</u>
Pathways	<u>62</u>

Total 156 divided by 3 =

52
Gross Total Score

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

52 x 1.0 = 52

HAZARDOUS ASSESSMENT RATING FORM

Page 1 of 2

NAME OF SITE Laboratory Chemical Disposal Site
 LOCATION Near Luna Lake
 DATE OF OPERATION OR OCCURRENCE 1962 to 1964
 OWNER/OPERATOR Robins AFB
 COMMENTS/DESCRIPTION One time disposal of expired shelf life chemicals
 SITE RATED BY E. J. Schneider

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site	1	4	4	12
B. Distance to nearest well	3	10	30	30
C. Land use/zoning within 1 mile radius	1	3	3	9
D. Distance to reservation boundary	2	6	12	18
E. Critical environments within 1 mile radius of site	0	10	0	30
F. Water quality of nearest surface water body	0	6	0	18
G. Ground water use of uppermost aquifer	1	9	9	27
H. Population served by surface water supply within 3 miles downstream of site	0	6	0	18
I. Population served by ground-water supply within 3 miles of site	3	6	18	18
Subtotals			<u>76</u>	<u>180</u>
Receptors subscore (100 X factor score subtotal/maximum score subtotal)				<u>42</u>

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

- | | |
|--|---|
| 1. Waste quantity (S = small, M = medium, L = large) | M |
| 2. Confidence level (C = confirmed, S = suspected) | C |
| 3. Hazard rating (H = high, M = medium, L = low) | M |

Factor Subscore A (from 20 to 100 based on factor score matrix) 60

B. Apply persistence factor
 Factor Subscore A X Persistence Factor = Subscore B

$$\underline{\quad 60 \quad} \times \underline{\quad 1.0 \quad} = \underline{\quad 60 \quad}$$

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

$$\underline{\quad 60 \quad} \times \underline{\quad 0.5 \quad} = \underline{\quad 30 \quad}$$

III. PATHWAYS

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore 80

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
Distance to nearest surface water	2	8	16	24
Net precipitation	1	6	6	18
Surface erosion	0	8	0	24
Surface permeability	1	6	6	18
Rainfall intensity	3	8	24	24
Subtotals			<u>52</u>	<u>108</u>
Subscore (100 X factor score subtotal/maximum score subtotal)				<u>48</u>

2. Flooding

	0	1	0	3
Subscore (100 x factor score/3)				<u>0</u>

3. Ground-water migration

Depth to ground water	2	8	16	24
Net precipitation	1	6	6	18
Soil permeability	2	8	16	24
Subsurface flows	1	8	8	24
Direct access to ground water	3	8	24	24
Subtotals			<u>70</u>	<u>114</u>
Subscore (100 x factor score subtotal/maximum score subtotal)				<u>61</u>

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore 80

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors	<u>42</u>
Waste Characteristics	<u>30</u>
Pathways	<u>80</u>
Total <u>152</u> divided by 3 =	<u>51</u>
	Gross Total Score

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

51 x 1.0 = 51

HAZARDOUS ASSESSMENT RATING FORM

Page 1 of 2

NAME OF SITE Landfill No. 3
 LOCATION West Side of Luna Lake
 DATE OF OPERATION OR OCCURRENCE 1964
 OWNER/OPERATOR Robins AFB
 COMMENTS/DESCRIPTION _____
 SITE RATED BY S. J. Schneider

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site	1	4	4	12
B. Distance to nearest well	3	10	30	30
C. Land use/zoning within 1 mile radius	1	3	3	9
D. Distance to reservation boundary	2	6	12	18
E. Critical environments within 1 mile radius of site	0	10	0	30
F. Water quality of nearest surface water body	1	6	6	18
G. Ground water use of uppermost aquifer	1	9	9	27
H. Population served by surface water supply within 3 miles downstream of site	0	6	0	18
I. Population served by ground-water supply within 3 miles of site	3	6	18	18

Subtotals 82 180

Receptors subscore (100 X factor score subtotal/maximum score subtotal) 46

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

- | | |
|--|----------|
| 1. Waste quantity (S = small, M = medium, L = large) | <u>S</u> |
| 2. Confidence level (C = confirmed, S = suspected) | <u>S</u> |
| 3. Hazard rating (H = high, M = medium, L = low) | <u>H</u> |

Factor Subscore A (from 20 to 100 based on factor score matrix) 40

B. Apply persistence factor
 Factor Subscore A X Persistence Factor = Subscore B

$$\underline{40} \times \underline{1.0} = \underline{40}$$

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

$$\underline{40} \times \underline{1.0} = \underline{40}$$

III. PATHWAYS

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore 0

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
Distance to nearest surface water	3	8	24	24
Net precipitation	1	6	6	18
Surface erosion	0	8	0	24
Surface permeability	1	6	6	18
Rainfall intensity	3	8	24	24
Subtotals			<u>60</u>	<u>108</u>
Subscore (100 X factor score subtotal/maximum score subtotal)				<u>56</u>

2. Flooding

	0	1	0	3
Subscore (100 x factor score/3)				<u>0</u>

3. Ground-water migration

Depth to ground water	2	8	16	24
Net precipitation	1	6	6	18
Soil permeability	2	8	16	24
Subsurface flows	2	8	16	24
Direct access to ground water	0	8	0	24
Subtotals			<u>54</u>	<u>114</u>
Subscore (100 x factor score subtotal/maximum score subtotal)				<u>47</u>

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore 56

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors	<u>46</u>
Waste Characteristics	<u>40</u>
Pathways	<u>56</u>
Total <u>142</u> divided by 3 =	<u>47</u>
Gross Total Score	

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

47 x 1.0 = 47

HAZARDOUS ASSESSMENT RATING FORM

Page 1 of 2

NAME OF SITE Fire Training Pit No. 3
 LOCATION North of Existing Site in SAC area
 DATE OF OPERATION OR OCCURRENCE Mid-1960's to 1969
 OWNER/OPERATOR Robins AFB
 COMMENTS/DESCRIPTION _____
 SITE RATED BY E. J. Schneider

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site	0	4	0	12
B. Distance to nearest well	3	10	30	30
C. Land use/zoning within 1 mile radius	1	3	3	9
D. Distance to reservation boundary	2	6	12	18
E. Critical environments within 1 mile radius of site	0	10	0	30
F. Water quality of nearest surface water body	0	6	0	18
G. Ground water use of uppermost aquifer	1	9	9	27
H. Population served by surface water supply within 3 miles downstream of site	0	6	0	18
I. Population served by ground-water supply within 3 miles of site	3	6	18	18

Subtotals 72 180

Receptors subscore (100 X factor score subtotal/maximum score subtotal) 40

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

- | | |
|--|----------|
| 1. Waste quantity (S = small, M = medium, L = large) | <u>M</u> |
| 2. Confidence level (C = confirmed, S = suspected) | <u>S</u> |
| 3. Hazard rating (H = high, M = medium, L = low) | <u>M</u> |

Factor Subscore A (from 20 to 100 based on factor score matrix) 40

B. Apply persistence factor
 Factor Subscore A X Persistence Factor = Subscore B

$$\underline{40} \times \underline{1.0} = \underline{40}$$

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

$$\underline{40} \times \underline{1.0} = \underline{40}$$

III. PATHWAYS

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore N/A

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
Distance to nearest surface water	3	8	24	24
Net precipitation	1	6	6	18
Surface erosion	0	8	0	24
Surface permeability	1	6	6	18
Rainfall intensity	3	8	24	24
Subtotals			<u>60</u>	<u>108</u>
Subscore (100 X factor score subtotal/maximum score subtotal)				<u>56</u>

2. Flooding

	0	1	0	3
Subscore (100 x factor score/3)				<u>0</u>

3. Ground-water migration

Depth to ground water	2	8	16	24
Net precipitation	1	6	6	18
Soil permeability	2	8	16	24
Subsurface flows	1	8	8	24
Direct access to ground water	0	8	0	24
Subtotals			<u>46</u>	<u>114</u>
Subscore (100 x factor score subtotal/maximum score subtotal)				<u>40</u>

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore 56

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors	<u>40</u>
Waste Characteristics	<u>40</u>
Pathways	<u>56</u>
Total <u>136</u> divided by 3 =	<u>45</u>
	Gross Total Score

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

45 x 1.0 = 45

HAZARDOUS ASSESSMENT RATING FORM

Page 1 of 2

NAME OF SITE Radioactive (Solid) Waste Burial Site
 LOCATION Facility No. 8315 near Pistol Range
 DATE OF OPERATION OR OCCURRENCE 1940's to 1950's
 OWNER/OPERATOR Robins AFB
 COMMENTS/DESCRIPTION _____
 SITE RATED BY E. J. Schneider

I. RECEPTORS

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
A. Population within 1,000 feet of site	1	4	4	12
B. Distance to nearest well	3	10	30	30
C. Land use/zoning within 1 mile radius	0	3	0	9
D. Distance to reservation boundary	3	6	18	18
E. Critical environments within 1 mile radius of site	0	10	0	30
F. Water quality of nearest surface water body	0	6	0	18
G. Ground water use of uppermost aquifer	1	9	9	27
H. Population served by surface water supply within 3 miles downstream of site	0	6	0	18
I. Population served by ground-water supply within 3 miles of site	3	6	18	18
Subtotals			<u>79</u>	<u>180</u>
Receptors subscore (100 X factor score subtotal/maximum score subtotal)				<u>44</u>

II. WASTE CHARACTERISTICS

A. Select the factor score based on the estimated quantity, the degree of hazard, and the confidence level of the information.

1. Waste quantity (S = small, M = medium, L = large)
2. Confidence level (C = confirmed, S = suspected)
3. Hazard rating (H = high, M = medium, L = low)

S

C

L

30

Factor Subscore A (from 20 to 100 based on factor score matrix)

B. Apply persistence factor
 Factor Subscore A X Persistence Factor = Subscore B

$$\underline{30} \times \underline{0.9} = \underline{27}$$

C. Apply physical state multiplier

Subscore B X Physical State Multiplier = Waste Characteristics Subscore

$$\underline{27} \times \underline{0.5} = \underline{13.5}$$

III. PATHWAYS

A. If there is evidence of migration of hazardous contaminants, assign maximum factor subscore of 100 points for direct evidence or 80 points for indirect evidence. If direct evidence exists then proceed to C. If no evidence or indirect evidence exists, proceed to B.

Subscore ND

B. Rate the migration potential for 3 potential pathways: surface water migration, flooding, and ground-water migration. Select the highest rating, and proceed to C.

1. Surface water migration

Rating Factor	Factor Rating (0-3)	Multiplier	Factor Score	Maximum Possible Score
Distance to nearest surface water	1	8	8	24
Net precipitation	1	6	6	18
Surface erosion	0	8	0	24
Surface permeability	1	6	6	18
Rainfall intensity	3	8	24	24

Subtotals 44 108

Subscore (100 X factor score subtotal/maximum score subtotal) 41

2. Flooding	0	1	0	3
-------------	---	---	---	---

Subscore (100 x factor score/3) 0

3. Ground-water migration

Depth to ground water	2	8	16	24
Net precipitation	1	6	6	18
Soil permeability	2	8	16	24
Subsurface flows	1	8	8	24
Direct access to ground water	0	8	0	24

Subtotals 46 114

Subscore (100 x factor score subtotal/maximum score subtotal) 40

C. Highest pathway subscore.

Enter the highest subscore value from A, B-1, B-2 or B-3 above.

Pathways Subscore 41

IV. WASTE MANAGEMENT PRACTICES

A. Average the three subscores for receptors, waste characteristics, and pathways.

Receptors	<u>44</u>
Waste Characteristics	<u>14</u>
Pathways	<u>41</u>
Total <u>99</u> divided by 3 =	<u>33</u>
	Gross Total Score

B. Apply factor for waste containment from waste management practices

Gross Total Score X Waste Management Practices Factor = Final Score

33 x 0.95 = 31

APPENDIX I

REFERENCES

APPENDIX I

REFERENCES

- Chow, V. T., 1964, Handbook of Applied Hydrology, McGraw-Hill Book Company, New York, New York.
- Fenn, D. G., Hanley, K. J., and DeGeare, T. V., 1975, Use of the Water Balance Method for Predicting Leachate Generation from Solid Waste Disposal Sites, U. S. Environmental Protection Agency publication EPA/530/SW-168.
- Georgia Department of Natural Resources, 1976, Geologic Map of Georgia.
- Georgia Game and Fish Division, Department of Natural Resources, 1982, Telephone conversation with Ken Grahl, Fort Valley office, March 30, 1982.
- Giger, W. and Molnar-Kubica, E., 1978, Tetrachloroethylene in Contaminated Ground and Drinking Waters, Bulletin Environ. Contamination Toxicol. Vol. 19, No. 4, April, pp. 475-480.
- Herrick, Stephen M., 1961, Well Logs of the Coastal Plain of Georgia, Georgia Geological Survey Bulletin Number 70.
- Herrick, Stephen M., 1965, A Subsurface Study of Pleistocene Deposition Coastal Georgia, Georgia Geological Survey Information Circular 31.
- Herrick, Stephen M. and Vorhis, Robert C., 1963, Subsurface Geology of the Georgia Coastal Plain, Georgia Geological Survey Information Circular 25.
- Law Engineering Testing Co., 1980, Final Report, Ground Water Monitoring Program, Landfill Closure, Robins Air Force Base, Warner Robins, Georgia.
- LeGrand, H. E., 1962, Geology and Ground-Water Resources of the Macon Area, Georgia, Georgia Geological Survey Bulletin Number 72.
- Mitchell, Gail D., 1979, Potentiometric Surface of the Principal Artesian Aquifer in Georgia, Georgia Geological Survey Hydrologic Atlas Number 4.
- Pollard, L. D. and Vorhis, R. C., The Geohydrology of the Cretaceous Aquifer System in Georgia, Georgia Geological Hydrologic Atlas Number 3.
- Robins Air Force Base, TAB A-1, Environmental Narrative, Updated 1976.

Roberts, P.V., McCarty, P.L., Reinhard, M. and Schreiner, J., 1980, Organic Contaminant Behavior During Ground-Water Recharge, Journal Water Poll. Control Fed., Vol. 52, No. 1, January, pp. 161-171. SGB/Bioenvironmental Engineers Office, Stabilization of DDT Spill. January 4, 1980. Robins AFB, Georgia.

Sonderegger, J. L., Pollard, L. D., and Cressler, C. W., 1978, Quality and Availability of Groundwater in Georgia, Georgia Geological Survey Information Circular 48.

Talley, et al., Non-Potable Water Chemical Testing 1978-1979. Bio-environmental Engineering Services Division, U.S. Air Force. Robins AFB, Georgia.

Thomson, M. T., Herrick, S. M., and Brown, E., 1956, The Availability and Use of Water in Georgia, Georgia Geological Survey Bulletin 65.

APPENDIX J

GLOSSARY

APPENDIX J

GLOSSARY OF TERMINOLOGY AND ABBREVIATIONS

AF: Air Force

AFB: Air Force Base

AFFF: Aqueous Film Forming Foam

AFLC: Air Force Logistics Command

AFR: Air Force Regulation

AFSC: Air Force Systems Command

AG: Adjutant General

Ag: Chemical symbol for silver

AGE: Aircraft Ground Equipment

Al: Chemical symbol for aluminum

ALIPHATIC SOLVENTS: Those solvents derived from straight chain hydrocarbon compounds.

AROMATIC SOLVENTS: Those solvents derived from benzene whose molecule contains one or more carbon rings.

ARTESIAN: Ground water contained under hydrostatic pressure

AQUICLUDE: Poorly permeable formation that impedes ground-water movement and does not yield water to a well or spring

AQUIFER: A geologic formation, group of formations, or part of a formation that is capable of yielding water to a well or spring

AQUITARD: A soils formation which impedes groundwater flow

AVGAS: Aviation Gasoline

Ba: Chemical symbol for barium

BESD: Bioenvironmental Engineering Services Division

Cd: Chemical symbol for cadmium

CERCLA: Comprehensive Environmental Response, Compensation and Liability Act

CES: Civil Engineering Squadron

CIRCA: About; used to indicate an approximate date

CLOSURE: The completion of a set of rigidly defined functions for a hazardous waste facility no longer in operation

CN: Chemical symbol for cyanide

COD: Chemical Oxygen Demand, a measure of the amount of oxygen required to oxidize organic and oxidizable inorganic compounds in water

COE: Corps of Engineers

CONFINED AQUIFER: An aquifer bounded above and below by impermeable beds or by beds of distinctly lower permeability than that of the aquifer itself

CONTAMINATION: The degradation of natural water quality to the extent that its usefulness is impaired; there is no implication of any specific limits since the degree of permissible contamination depends upon the intended end use or uses of the water

Cr: Chemical symbol for chromium

Cu: Chemical symbol for copper

DASC: Direct Air Support Center

DET: Detachment

DISPOSAL FACILITY: A facility or part of a facility at which hazardous waste is intentionally placed into or on land or water, and at which waste will remain after closure

DISPOSAL OF HAZARDOUS WASTE: The discharge, deposit, injection, dumping, spilling, or placing of any hazardous waste into or on land or water so that such waste or any constituent thereof may enter the environment or be emitted into the air or discharged into any waters, including ground water

DOD: Department of Defense

DOWNGRAIENT: In the direction of decreasing hydraulic static head; the direction in which ground water flows

DPDO: Defense Property Disposal Office - previous designation R&M, Redistribution and Marketing

DUMP: An uncovered land disposal site where solid and/or liquid wastes are deposited with little or no regard for pollution control or aesthetics; dumps are susceptible to open burning and are exposed to the elements, disease vectors and scavengers

EOD: Explosive Ordnance Disposal

ECM: Electronic Countermeasures

EFFLUENT: A liquid waste discharge from a manufacturing or treatment process, in its natural state, or partially or completely treated, that discharges into the environment

EPA: U. S. Environmental Protection Agency

EROSION: The wearing away of land surface by wind or water

EPHEMERAL AQUIFER: An aquifer usually near the surface which is only temporary in nature

FAA: Federal Aviation Administration

FACILITY: Any land and appurtenances thereon and thereto used for the treatment, storage and/or disposal of hazardous wastes

Fe: Chemical symbol for iron

FLOOD PLAIN: The lowland and relatively flat areas adjoining inland and coastal areas of the mainland and off-shore islands, including, at a minimum, areas subject to a one percent or greater chance of flooding in any given year

FLOW PATH: The direction or movement of ground water and any contaminants that may be contained therein, as governed principally by the hydraulic gradient

GROUND WATER: Water beneath the land surface in the saturated zone that is under atmospheric or artesian pressure

GROUND WATER RESERVOIR: The earth materials and the intervening open spaces that contain ground water

HALF-LIFE: The time required for half the atoms present in radioactive substance to disintegrate

HARDFILL: Disposal sites receiving construction debris, wood, miscellaneous spoil material

HAZARDOUS WASTE: A solid waste, or combination of solid wastes, which because of its quantity, concentration, or physical, chemical or infectious characteristics may cause or significantly contribute to an increase in mortality or an increase in serious, irreversible, or incapacitating reversible illness; or pose a substantial present or potential hazard to human health or the environment when improperly treated, stored, transported, or disposed of, or otherwise managed

HAZARDOUS WASTE GENERATION: The act or process of producing a hazardous waste

HEAVY METALS: Metallic elements, including the transition series, which include many elements required for plant and animal nutrition in trace concentrations but which become toxic at higher concentrations

Hg: Chemical symbol for mercury

HQ: Headquarters

INCOMPATIBLE WASTE: A waste unsuitable for commingling with another waste or material because the commingling might result in generation of extreme heat or pressure, explosion or violent reaction, fire, formation of substances which are shock sensitive, friction sensitive, or otherwise have the potential for reacting violently, formation of toxic dusts, mists, fumes, and gases, volatilization of ignitable or toxic chemicals due to heat generation in such a manner that the likelihood of contamination of ground water or escape of the substance into the environment is increased, any other reaction which might result in not meeting the Air, Human Health, and Environmental Standard

INFILTRATION: The flow of liquid through pores or small openings

IRP: Installation Restoration Program

KETONE SOLVENTS: Organic solvents containing a ketone functional group

LEACHATE: A solution resulting from the separation or dissolving of soluble or particulate constituents from solid waste or other man-placed medium by percolation of water

LEACHING: The process by which soluble materials in the soil, such as nutrients, pesticide chemicals or contaminants, are washed into a lower layer of soil or are dissolved and carried away by water

LETCO: Law Engineering Testing Company, Marietta, Georgia

LINER: A continuous layer of natural or man-made materials beneath or on the sides of a surface impoundment, landfill, or landfill cell which restricts the downward or lateral escape of hazardous waste, hazardous waste constituents or leachate

LOX: Liquid Oxygen

LYSIMETERS: A thimble or cup device used for extracting ground water samples at various depths

MAC: Military Airlift Command

MAS: Military Air Service

MGD: million gallons per day

MOA: Military Operating Area

Mn: Chemical symbol for manganese

MONITORING WELL: A well used to measure ground-water levels and to obtain samples

Mr/hr: millirem/hour; a measure of radioactivity

MSL: Mean Sea Level

Ni: Chemical symbol for nickel

OEHL: Occupational and Environmental Health Laboratory

ORGANIC: Being, containing or relating to carbon compounds, especially in which hydrogen is attached to carbon

O&G: Symbols for oil and grease

OT&E: Operations, Training and Evaluation

Pb: Chemical symbol for lead

PCB: Polychlorinated Biphenyls are highly toxic to aquatic life; they persist in the environment for long period and are biologically accumulative

PERCOLATION: Movement of moisture by gravity or hydrostatic pressure through interstices of unsaturated rock or soil

PD-680: Cleaning solvent, safety solvent, Stoddard's solvent

pH: Negative logarithm of hydrogen ion concentration, measurement of acids and bases

PL: Public Law

POL: Petroleum, Oils and Lubricants

POLLUTANT: Any introduced gas, liquid or solid that makes a resource unfit for a specific purpose

RCRA: Resource Conservation and Recovery Act

RECHARGE AREA: An area in which water is absorbed that eventually reaches the zone of saturation in one or more aquifers

RECHARGE: The addition of water to the ground-water system by natural or artificial processes

RECON: Reconnaissance

SANITARY LANDFILL: A land disposal site using an engineered method of disposing solid wastes on land in a way that minimizes environmental hazards

SATURATED ZONE: That part of the earth's crust in which all voids are filled with water

SLUDGE: The solid residue resulting from a manufacturing or wastewater treatment process which also produces a liquid stream

SOLID WASTE: Any garbage, refuse, or sludge from a waste treatment plant, water supply treatment, or air pollution control facility and other discarded material, including solid, liquid, semi-solid, or contained gaseous material resulting from industrial, commercial, mining, or agricultural operations and from community activities, but does not include solid or dissolved materials in domestic sewage; solid or dissolved materials in irrigation return flows; industrial discharges which are point source subject to permits under Section 402 of the Federal Water Pollution Control Act, as amended (86 USC 880); or source, special nuclear, or by-product material as defined by the Atomic Energy Act of 1954 (68 USC 923)

SPILL: Any unplanned release or discharge of a hazardous waste onto or into the air, land, or water

STORAGE OF HAZARDOUS WASTE: Containment, either on a temporary basis or for a longer period, in such a manner as not to constitute disposal of such hazardous waste

TAC: Tactical Air Command

TOXICITY: The ability of a material to produce injury or disease upon exposure, ingestion, inhalation, or assimilation by a living organism

TRANSMISSIVITY: The rate at which water is transmitted through a unit width under a unit hydraulic gradient

TREATMENT OF HAZARDOUS WASTE: Any method, technique, or process including neutralization designed to change the physical, chemical, or biological character or composition of any hazardous waste so as to neutralize the waste or so as to render the waste nonhazardous

UPGRADIENT: In the direction of increasing hydraulic static head; the direction opposite to the prevailing flow of groundwater

USAF: United States Air Force

V: Chemical symbol for vanadium

WATER TABLE: Surface of a body of unconfined ground water at which the pressure is equal to that of the atmosphere

Zn: Chemical symbol for zinc