

MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
	AD-A127961	
4. TITLE (and Subtitle) INTEGRATED MULTIPLE PROJECT SCHEDULING SYSTEM.		5. TYPE OF REPORT & PERIOD COVERED
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Douglas D. Gransberg		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS U.S. Army Engineer District, St. Paul 1135 USPO & Custom House St. Paul, MN 55101		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE 1 April 1983
		13. NUMBER OF PAGES 42
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report)
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) COMPUTER APPLICATIONS DATA MANAGEMENT MANAGEMENT INFORMATION SYSTEMS		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The problem of simultaneous scheduling of multiple projects within the Engineering Division of the St. Paul District, Corps of Engineers, is addressed using a decision-making algorithm in conjunction with a computer software package (IMPSS). This report details the capabilities and limitations of the software, outlines theories used in development and use of IMPSS, and illustrates the IMPSS decision-making algorithm by example.		

AD A 127961

DTIC FILE COPY

DTIC
COLLECTED
MAY 11 1983
H

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

INTEGRATED MULTIPLE PROJECT

SCHEDULING SYSTEM

By CPT Douglas D. Gransberg

DTIC
ELECTR
MAY 14 1983
S H D

St. Paul District, Corps of Engineers
1135 U.S. Post Office and Custom House
St. Paul, Minnesota 55101
1 April 1983

83 05 09 051

TABLE OF CONTENTS

<u>Item</u>	<u>Page</u>
Purpose	1
Background	2
Software Support Package	4
The Algorithm and Its Theory	11
Example of IMPSS Use	18
Conclusions	37
Recommendations	38
 Appendix A - Abbreviations and Definitions	 39
Appendix B - Sample Form for Input and Updating	40
 Bibliography	 42

FIGURES

Figure 3.3-1: Sample Gantt Chart	7
Figure 3.3-2: Sample Resource Histogram	8
Figure 3.3-3: Sample Printout of Resource Histogram Totals	9
Figure 4.1-1: IMPSS Algorithm Flow Chart	12
Figure 5.1-1: Network for Project AAA	19
Figure 5.1-2: Network for Project BBB	20
Figure 5.1-3: Network for Project CCC	21
Figure 5.1-4: Master Network for All Projects	22
Figure 5.1-5: Initial IMPSS Output from *CPM	23
Figure 5.2-1: Output of Second *CPM Run with Milestones and Actual Start Dates Included	25
Figure 5.2-2: Output After Durations Have Been Changed to Allow Milestones to Be Met	26
Figure 5.2-3: (Page 1) Gantt Chart	27
Figure 5.2-3: (Page 2) Gantt Chart	28
Figure 5.2-3: (Page 3) Gantt Chart	29
Figure 5.2-3: (Page 4) Gantt Chart	30
Figure 5.2-3: (Page 5) Gantt Chart	31
Figure 5.2-4: Resource Histogram	32
Figure 5.4-1: Resource Histogram After First Attempt at Leveling	34
Figure 5.4-2: Resource Histogram After Second Attempt at Leveling	35

1. Purpose


The purpose of this report is to present the author's solution to the problem of simultaneous scheduling of multiple projects within the Engineering Division of the St. Paul District. This solution involves using a decision-making algorithm in conjunction with a computer software package. The algorithm/software package will hereafter be referred to as the Integrated Multiple Project Scheduling System (IMPSS). This report will do the following:

- a. Detail the capabilities and limitations of the software developed to support IMPSS.
- b. Outline and explain the theories used to develop and use IMPSS.
- c. Illustrate the IMPSS decision-making algorithm by example.

It is important that one point be made and understood at the outset of the report. IMPSS relies heavily on the human element (i.e., the experience and knowledge of executives and managers) to set priorities and allocate resources. The computer will not resource level for all projects. It will show required resource levels at any time and will allow shifting of those levels as management decisions are made.

Responsible For	
DRAB	<input checked="" type="checkbox"/>
TAB	<input type="checkbox"/>
Reviewed	<input type="checkbox"/>
Classification	
Distribution/	
Availability Codes	

A



2. Background

2.1 Problem Description:

The author was assigned this project by the Chief of the Engineering Division in January 1983. At that time, there was no method for determining actual, total resource requirements without resorting to tedious, time-consuming, manual calculations. The level of detail in the Resource Allocation/Project Management (RA/PM) system not only inundates the manager with a lot of output that requires a great deal of analysis time, but also forces project managers to spend an inordinate amount of time (about one day per week) to keep the data current. Additionally, the development of input for RA/PM requires the same "stubby-pencil" calculations referred to earlier in this paragraph. Consequently, there is no advantage to using RA/PM in its present form.

2.2 Milestone Determinations:

The second part of the problem involves the means by which individual project milestones are determined. Essentially, project managers break down each of their projects into its component activities. Then, through the use of bar charting, critical path method (CPM), and personal estimating techniques, they assign a set of milestones to each project. The project managers are generally operating in a vacuum and assigning milestones without any knowledge of how their projects relate to other projects. This knowledge gap forces projects and project managers to compete for resources. At the functional level, it also causes workload bottlenecks to form which can only be relieved by slipping milestones (a weak and unpopular solution at best). As a result, the amount of crisis management required to meet individual milestones is higher than what would normally be found if project resource interrelationships were known prior to assigning milestones.

2.3 Workload Determination and Contracting-Out:

The last component of the problem is finding a method of accurately determining the total workload in the Engineering Division over the fiscal year. A lead time of 4 to 6 months is required to identify functional area overloads so that they may be relieved by sending the excess work to other districts or by contracting for architect/engineer (A/E) services. Under the current system, branch and section chiefs annually determine their projected workloads, which are then manually assembled to find the total workload of the Division. This not only requires a great deal of time, but it is virtually impossible to manipulate the end product to allow separate courses of action to be developed, analyzed, and the best course selected. In fact, the current procedure is to make policy and priority decisions during the data development and to accept the final product as the best solution.

2.4 Explanation:

It must be noted that the above discussion is not meant to be critical of the individual abilities of managers at any level within the District. Rather, it is meant to point out the pressing need for an automated system of dealing with the minutiae of project management which is currently handcuffing the District's ability to intelligently allocate internal resources. The development of IMPSS or a similar system is indeed necessary.

2.5 Conduct of the Project:

The project was divided into three phases: study, software development, and algorithm development. The study phase consisted of interviews and literature research. The purpose of the interviews was to define the scope and magnitude of the problem and to obtain guidance on the type of output required. Individuals at all levels, from project managers to division chief, were interviewed. The information gathered during those interviews is presented in the preceding paragraphs. Literature research was done to determine which analytical scheduling methods are best suited to the situation. Initially, it appeared that precedence networking would be the best method. However, the cost of obtaining and fielding the required software seemed to be unjustified during the initial stage of the project. The decision was made to modify an existing CPM software package, write a bar charting/resource load program, and combine the two with an external problem-solving algorithm. The software and algorithm development phases of the project resulted from this decision. These will be explained in detail in the following sections of this report.

3. Software Support Package

3.1 Composition:

The IMPSS software support package consists of the following major components:

- a. "*CPM": a canned program for the Harris 500 which performs critical path method calculations.
- b. "*CPM Option 6": a graphic illustration program for the Tech-tronix plotter which converts the output from "*CPM" into a Gantt Chart (a bar chart which shows slack by activity) and plots a resource loading histogram based on the Gantt Chart.

If this report is accepted and IMPSS is found to be a satisfactory system, a third component could easily be added which would convert IMPSS final output into RA/PM input. This would relieve project managers of the need to prepare input for two systems.

3.2 Capabilities of "*CPM":

"*CPM" is an interactive, canned program originally developed by Mobile District and modified and improved by St. Paul District. It consists of six subroutines which are used iteratively to compute start, finish, and slack times and to update the input network. "*CPM" will compute the following elements from the network input data (see Appendix A for definition):

- a. Early start date (ES)
- b. Early finish date (EF)
- c. Late start date (LS)
- d. Late finish date (LF)
- e. Total slack (TS)
- f. Remaining slack (RS)
- g. Total project cost

From updated input data, the program can perform the following functions:

- a. Compute total cost to date for each project activity and show total project cost to date.
- b. Show percentage of completion for each project activity.
- c. Replace ES and LS dates with actual start date and alter slack calculations to show how critical the activities are.

d. Replace LF date with milestone date, alter slack calculations, and determine if milestone can be met.

e. If a milestone cannot be met, a warning statement is printed, and TS is shown as a negative number which indicates the number of days that the activity will be late if neither the duration nor the milestone is changed.

The program has the ability to sort the output and list it in several orders. The various sorts and their management uses are as follows:

a. I-J Sort - Activities are listed in numerical order of their I-J (event) numbers. Analysis of this sort allows the logic of the total network to be checked and the level of input accuracy to be quickly determined.

b. Early Start Sort - Activities are listed in chronological order by their ES dates. This sort shows which activities can be started chronologically if resources are available.

c. Early Finish Sort - Activities are listed chronologically by their EF dates. This sort shows how soon activities can be finished if resources are available.

d. Late Start Sort - Activities are listed chronologically by their LS dates. This sort shows when activities must be started to remain on schedule.

e. Late Finish Sort - Activities are listed chronologically by their LF date. This is one of the most important sorts from a management standpoint. It shows which activities must be completed to avoid missing milestones. In the final IMPSS output, the LF dates will be replaced by the activity milestone date. Therefore, this sort could be labeled the milestone sort.

f. Total slack sort - Activities are listed in ascending numerical order by their amounts of total slack. This is the most important management sort because it shows the critical activities and near-critical activities.

g. Project Sort - Activities are listed in the order specified by any of the above five basic sorts for one specific project. This allows project managers to get information on a particular project.

h. Organization Sort - All the activities of a specific organization are listed in the order specified by any of the five basic sorts. This provides specific information on the work schedule of a particular organization to allow evaluation of bottlenecks and analysis of staffing levels.

3.3 Capabilities of "*CPM" Graphics Options:

There are two primary graphics options: a Gantt Chart (Figure 3.3-1) and a resource histogram (Figure 3.3-2). The Gantt Chart is simply a bar chart for all activities which graphically shows available slack. The resource histogram is a graph which shows the total daily cost for each activity scheduled for that day. The resource histogram option has an additional feature which prints out daily totals for both ES and LF schedules (Figure 3.3-3). These numbers correspond to the peak amounts registered on the graph for both the ES and LF plots.

3.4 Limitations of "*CPM":

"*CPM" and its graphics options are limited both by program capacity and the inherent constraints of using critical path method theory. The program capacity limitations follow.

a. The maximum number of activities is 3,000. This includes dummies.

b. Every activity must have a unique I-J (event) number. Therefore, projects with a great number of parallel paths will have a large number of dummies and may reduce the total usable capacity for real activities.


c. The program can only calculate closed networks. Therefore, individual project networks must be linked together at the beginning and end by dummies. This creates false start and stop events and makes output interpretation on a project-by-project basis somewhat tricky. However, some familiarity with the output makes accurate analysis possible. Additionally, use of the project sort can expedite this process.

d. Assembly of a large initial calendar file is required to ensure that the available "time window" is great enough for the network to occupy. The calendar file can be reduced after the initial run.

e. Strict coding of activity descriptions is required to allow project and organizational sorting.

f. Activity durations must be in calendar days.

g. The amount of output requires a 132-character display. However, a cathode ray tube (CRT) can only display 96 characters. This causes the output to be "wrapped" on the screen, making data interpretation somewhat tedious. If totally interactive CRT use is found to be important, additional search and sort subroutines can be added to make the CRT output display less confusing.



TEST DATA
 MEU FORRYAT
 FEBRUARY 1983
 2 MAR 83

Figure 3.3-1: Sample Gantt Chart




Figure 3.3-2: Sample Resource Histogram

TEST DATA
NEW FORMAT
FEBRUARY 1983

2 MAR 83

AVERAGE DAILY COST SUMMARY

DATE	EARLY START/FINISH COST	LATE START/FINISH COST
010283	20.	20.
010383	20.	20.
010483	20.	20.
010583	20.	20.
010683	20.	20.
010783	20.	20.
010883	20.	20.
010983	20.	20.
011083	20.	20.
011183	20.	20.
011283	50.	20.
011383	50.	20.
011483	50.	20.
011583	50.	20.
011683	50.	20.
011783	50.	50.
011883	50.	50.
011983	50.	50.
012083	50.	50.
012183	50.	50.
012283	20.	50.
012383	20.	50.
012483	20.	50.
012583	20.	50.
012683	20.	50.
012783	0.	0.

MAXIMUM DAILY EARLY START/FINISH COST IS \$ 50. ON 11283.
MAXIMUM DAILY LATE START/FINISH COST IS \$ 50. ON 11783.
EOT..

Figure: 3.3-3: Sample Printout of Resource Histogram Totals

h. Size limitations of the plotter will necessitate some cutting and taping to produce an overall bar chart and resource histogram.

Limitations imposed by the inherent weakness of CPM follow.

a. True project logic is difficult to diagram because CPM does not allow overlapping with preceding activities. This can be partially overcome by using actual start dates and the Gantt Chart option.

b. Converting task activity project networks to organizational activity project networks will require a good deal of thought. A training program for project managers will be necessary.

c. A CPM network must be converted to a Gantt Chart before heuristic resource leveling techniques can be applied.

One final limitation of CPM is the impossibility of mathematically modeling the political climate and the desires, plans, and feelings of the executive group. The computer will not produce an optimal, resource-constrained schedule because to do so would be a waste of time and money. First, the activity durations are estimates, and CPM does not allow use of a mechanism that demonstrates the potential variation of those times within the system. That makes the entire schedule an estimate and degrades the true value of a resource-leveled schedule. Secondly, factors such as flood emergencies and unscheduled resource losses affect the actual schedule and cannot be included in the network input. Most importantly, to use an optimal, resource-constrained schedule as a factor in the decision-making process is to run the risk of letting the computer set the priorities for the corporate body. Therefore, IMPSS is designed only to illustrate total workload requirements in the best and worst possible cases, ensuring that project priorities are set by the appropriate decision makers.

4. The Algorithm and Its Theory

4.1 IMPSS Decision-making Algorithm:

Figure 4.1-1 graphically illustrates the decision-making algorithm, which consists of five stages. The following paragraphs describe each stage and its corresponding theoretical basis. Assumptions will be discussed as they appear within the algorithm.

4.2 Stage I, Network Development:

The first stage consists of assembling the items necessary for the integrated multiple-project network. Individual project networks must first be developed, and this will be the responsibility of individual project managers. Contrary to normal CPM and RA/PM practice, activities will be defined by organization rather than by task. (For purposes of this report, organization is defined as a functional element (within a Branch) such as Interior Drainage, Geotechnical Design, or Estimating). The duration of the activity will be the amount of time required by an organization to complete all the tasks for which it is responsible on a particular project. The total cost of the activity will be the amount of money allocated to the organizations to do those tasks. Restricting activities to established organizational codes is desirable, but organizational codes which represent more than one functional element can be broken down if necessary.

For example, the Structural Section of the Design Branch may have to complete the following three tasks on a certain project: (1) Prepare architectural design concepts, (2) Design structural steel, and (3) Design structural concrete. Each task's duration would take 2 weeks at a budget of \$1,000.00, \$2,000.00 and \$3,000.00, respectively. These tasks would be combined into one activity labeled "Structural Design," with a 6-week duration and a total cost of \$6,000.00. (Note: The activity description must receive a coded prefix prior to input).

Once a list of activities with durations and costs is assembled, the individual project network can be constructed using standard CPM theory. At this point, it may be necessary to subdivide certain activities to preserve important precedence relationships within the project. This is allowable, but must be kept to a minimum to avoid unnecessary detail within the output. Additionally, it may be found that a project network consists of nothing but parallel paths. Although this is theoretically possible, it is unlikely, and the logic should be reviewed to determine if a satisfactory technological precedence relationship exists.

The next step is to combine the individual networks into one master network. This is done by first assigning unique I-J numbers for each project (i.e., one project may have numbers starting with 01 while another's numbers may start with 19). There is no theoretical basis for this requirement, but it will be of substantial aid in the analysis and interpretation of the output. The individual projects are now linked together at their initial and final nodes by dummies which emanate from and converge into master start and finish nodes. A comprehensive table of all activities in the master network is then assembled which shows the I-J number, duration, cost, and description for each activity. This





FIGURE 4.1-1:



RE 4.1-1: IMPSS ALGORITHM FLOW CHART

1

2

table becomes the initial input to "*CPM". Finally, an initial run of "*CPM" is made, and its output used to check the accuracy of the input. Once the above steps have been completed satisfactorily, the user can move to Stage II of IMPSS.

4.3 Stage II, Project Constraints:

The second stage involves constraining the theoretical network built in Stage I with actual milestones, start dates, and percentages of completion. This is done by using the update option of "*CPM". The information required is provided by project managers as a part of their initial input. After this information has been entered, a second computer run can be made and the output checked for accuracy. Next, it must be determined if the output is realistic. If it is not, the entire system must be reviewed and the fallacies in the logic identified and corrected before going on. If everything is in order, the graphics options of "*CPM" should be run, generating the following output:

- a. ES bar chart.
- b. LF (milestone) bar chart.
- c. ES resource histogram.
- d. LF resource histogram.
- e. TS sort for master network.

The above information and the output generated by Step 1 should provide all the information required for Stage III.

4.4. Stage III, Resource Leveling:

The goal of Stage III is to distribute the total workload as evenly as possible across the selected period of time. This is done by comparing the ES and LF resource histograms with the ES bar chart. Before this operation can be explained in detail, the comparison criteria must be understood. The resource requirement is measured in dollars per day and is determined for an individual activity by dividing the activity's total cost (the organization's project budget) by its duration. This operation assumes that the money allocated for a single activity is uniformly expended throughout its duration. Consequently, the total resource requirement for any one day will be the sum of the individual activity resource requirements that are scheduled for that day. That sum can then be compared to the maximum amount of dollars that the parent organization can expend on any given day to determine if the parent organization will be over or under committed on that particular day. For purposes of this report, parent organization is defined as the aggregate of functional elements over which it has control. This theory can be reduced to the following equations:

$$r_x = \frac{c_x}{d_x} \dots \dots \dots \text{Equation 1}$$

$$R_i = \sum_{x=1}^n r_x(i) \dots \dots \text{Equation 2}$$

Where: r_x = Resource requirement for activity "x" (\$/day)

c_x = Total cost for activity "x" (\$)

d_x = Duration of activity "x" (Days)

And: R_i = Total resource requirement
on day "i" (\$)

i = Day

R_{max} = Maximum daily resource capacity for parent organization

Therefore:

If: $R_{max} < R_i \dots \dots \dots \text{Equation 3}$

Then: The parent organization is over committed

If: $R_{max} = R_i \dots \dots \dots \text{Equation 4}$

Then: The parent organization is fully committed

If: $R_{max} > R_i \dots \dots \dots \text{Equation 5}$

Then: The parent organization is under committed

Resource leveling can now begin, using this theory and the updating option of "*CPM". A simple heuristic program is used iteratively until a satisfactory solution is reached. The program is based on four rules (heuristics):

- a. Allocate resources serially in time (i.e., start with ES schedule).
- b. Give preference to activities with the least slack.
- c. Reschedule non-critical activities to free resources for critical activities.
- d. Schedule activities by project priority as determined by executive group.

The heuristic program is applied using the following sequence of events:

- a. Locate times in which $R_i > R_{\max}$ on ES resource histogram.
- b. Check corresponding times on ES Gantt Chart to determine which activities have slack and which activities do not (i.e., critical activities).
- c. Add the resource requirement for those activities with no slack. If this amount is greater than R_{\max} , the parent organization will be over committed unless a means to shorten the duration of critical activities can be found.
- d. Attempt to schedule activities with slack at a point between their ES and LS date where $R_i < R_{\max}$. Call these dates tentative actual start dates.
- e. Using the LF Gantt Chart, LF resource histogram and the TS sort, identify which milestones are most heavily limiting the overall system. Select tentative new milestones, if possible, for super-critical activities. A super-critical activity is defined as one which cannot meet its milestone.
- f. Update the master file with newly determined tentative actual start dates, tentative new milestones, revised durations, and other changes.
- g. Run newest update. Analyze that output and repeat the process until a satisfactory solution is reached.

It is doubtful that a level resource histogram can be derived. Therefore, the best possible solution will contain times when the parent organization is both over committed and under committed. This is dealt with in Stage IV.

4.5 Stage IV, Project Assignment:

The fourth stage of IMPSS involves a number of crucial management decisions. These include:

- a. Which projects and activities will be done internally.
- b. Which projects and activities should be sent to other districts.
- c. Which projects and activities should be contracted out.
- d. If there are small projects and other activities not included in the master file which could fill the times when the parent organization is under committed.
- e. If personnel staffing levels should change.
- f. How much overtime should be authorized and where it should occur.

These decisions can be made with the aid of additional iterations of "*CPM" as described below.

- a. Identify times where $R_i > R_{max}$ and the activities that occur during those times.
- b. Determine which activities will be done internally and which will be done externally (contracted or sent out).
- c. Remove the activities which will be done by an external agency. (Note: The I-J numbers and new logic of the modified master file should be checked to ensure that no system limitations are exceeded).
- d. Run "*CPM" and analyze output to determine if R_i is still greater than R_{max} . Make necessary decisions and iterate until $R_i < R_{max}$ in all cases.
- e. Identify times when $R_i < R_{max}$.
- f. Add additional small projects to master file during those times if necessary.
- g. Run "*CPM", analyze output, and make any necessary changes. Iterate until satisfied with output.
- h. Relabel activities to be done by external sources and put them back into the network.
- i. Run final output.

The final output should consist of the graphics and sorts that are most useful to managers.

4.6 Stage V, Output Utilization:

Stage V is an optional stage and is described here only as the author's opinion of how "*CPM" output might be used after all decisions have been made. Once the final output is generated, it should be reviewed to ensure that the corporate body is satisfied with the decisions which the output illustrates. If they are not, then "its back to the old drawing board." Assuming that the final output is satisfactory, the following things can be done to enhance its value as a communications vehicle:

a. Using a special search option of "*CPM", a Gantt Chart and resource histogram can be drawn for each separate organization. Organizational managers (branch and section chiefs) could use these diagrams to aid them in their daily work scheduling and to remind them of critical activities.

b. The same search option will produce like diagrams on an individual project basis for use by project managers.

c. The LF sort could be used as the base document for publishing a consolidated list of milestones.

There are probably a number of other uses for the output. It is specifically designed to allow the interrelationships between projects to be shown in both tabular and graphical form.

5. Example of IMPSS Use

This section consists of an example of how the IMPSS algorithm is used in conjunction with "*CPM". For simplicity, only three projects are used, and decisions will be made about their interrelationships. The computer output for each point in the algorithm is shown to illustrate the information that can be gleaned from it by proper analysis.

5.1 Stage I Example:

The three projects have each been given a three-digit code as required by the "*CPM" search option, and they will be referred to by that code throughout this example. Figures 5.1-1, 5.1-2, and 5.1-3 are the networks associated with each project. Figure 5.1-4 illustrates how the three are integrated by joining them at the start and finish points with dummies and common nodes. The projects have been further identified by assigning each node a four-digit number in which the first two digits are unique throughout the network for each project. Table 5.1-1 is a list of the three-digit activity codes which have been assigned to each functional area within the Engineering Division. Thus, individual activities can be identified by combining their project code and functional area activity code.

Table 5.1-1 Functional Area Activity Codes

<u>Functional Area</u>	<u>Activity Code</u>
G & H Branch:	
Geology & Surveys	EGS
Field Survey Party	EGF
Boring Crew	EGB
Geotechnical Design	EGD
Hydraulics	EHA
Hydrology	EHO
Design Branch:	
General Engineering	EGE
Drafting	EDD
Specifications & Estimating	ESP
Structural Design	EDS
Non-structural Design	EDN
Estimating	EDE
Project Management	EPM

Once the above information has been entered into "*CPM", an initial run can be made and the output can be checked for accuracy before starting Stage II. Figure 5.1-5 illustrates the initial output.




Figure 5.1-1 Network for Project AAA




Figure 5.1-2 Network for Project BBB




Figure 5.1-3 Network for Project CCC




Figure 5.1-4 Master Network for All Projects

01. SAMPLE
1 I-J SORT
1 I-J SORT

UPDATE AS OF 10 383

REPORT EXAMPLE OUTPUT
11 MAR 83

THREE HYPOTHETICAL PROJECTS
ILLUSTRATES USE OF IMPSS ALGORITHM AND SAMPLE OUTPUTS

1 I J ATION

TOTAL COST

CURRENT COST

PCT COMP

EARLIEST START

FINISH

LATEST START

FINISH

SLACK

TOT REM

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
1	1010	0	D	0	0	0	10CT83	10CT83	10CT83	0	0	0	0	0	0	0	0	0	0
1	2010	0	D	0	0	0	10CT83	10CT83	10CT83	0	0	0	0	0	0	0	0	0	0
1	3010	0	D	0	0	0	10CT83	10CT83	10CT83	0	0	0	0	0	0	0	0	0	0
1010	1015	90	AAA-ENO, HYDROLOGY	0	0	0	10CT83	10CT83	10CT83	0	0	0	0	0	0	0	0	0	0
1010	1020	30	AAA-ECB, GEOTECH BORING	0	0	0	30DEC83	30DEC83	30DEC83	0	0	0	0	0	0	0	0	0	0
1015	1020	0	D	0	0	0	10CT83	10CT83	10CT83	0	0	0	0	0	0	0	0	0	0
1020	1025	90	AAA-EMA, HYDRAULIC DESIGN	0	0	0	30DEC83	30DEC83	30DEC83	0	0	0	0	0	0	0	0	0	0
1020	1030	270	AAA-EGD, GEOTECH DESIGN	0	0	0	27JUN84	25SEP84	25SEP84	0	0	0	0	0	0	0	0	0	0
1025	1030	0	D	0	0	0	30DEC83	30DEC83	30DEC83	0	0	0	0	0	0	0	0	0	0
1025	1035	90	AAA-EGE, GENERAL ENGR	0	0	0	29MAR84	29MAR84	25SEP84	0	0	0	0	0	0	0	0	0	0
1030	1035	90	AAA-EDS, STRUCTURAL DESIGN	0	0	0	29MAR84	29MAR84	25SEP84	0	0	0	0	0	0	0	0	0	0
1035	1040	60	AAA-EED, DRAFTING PLANS	0	0	0	24DEC84	24DEC84	24DEC84	0	0	0	0	0	0	0	0	0	0
1035	1045	60	AAA-ESP, SPECS	0	0	0	24DEC84	24DEC84	24DEC84	0	0	0	0	0	0	0	0	0	0
1040	1045	0	D	0	0	0	24DEC84	24DEC84	24DEC84	0	0	0	0	0	0	0	0	0	0
1045	1050	30	AAA-EDE, ESTIMATE	0	0	0	24MAR85	24MAR85	24MAR85	0	0	0	0	0	0	0	0	0	0
1050	5000	0	D	0	0	0	24MAR85	24MAR85	24MAR85	0	0	0	0	0	0	0	0	0	0
2010	2015	30	BBB-ECB, GEOTECH BORING	0	0	0	10CT83	10CT83	10CT83	0	0	0	0	0	0	0	0	0	0
2015	2020	270	BBB-ED, GEOTECH DESIGN	0	0	0	31OCT83	30NOV83	30DEC83	0	0	0	0	0	0	0	0	0	0
2015	2025	30	BBB-EDS, STRUCTURAL DESIGN	0	0	0	31OCT83	30NOV83	30DEC83	0	0	0	0	0	0	0	0	0	0
2020	2025	0	D	0	0	0	27JUL84	27JUL84	25OCT84	0	0	0	0	0	0	0	0	0	0
2020	2030	90	BBB-EGE, GENERAL ENGR	0	0	0	27JUL84	27JUL84	25OCT84	0	0	0	0	0	0	0	0	0	0
2025	2030	60	BBB-EDS, STRUCTURAL DESIGN	0	0	0	27JUL84	27JUL84	25OCT84	0	0	0	0	0	0	0	0	0	0
2025	2035	60	BBB-EDM, NONSTRUCTURAL DESIGN	0	0	0	27JUL84	27JUL84	25OCT84	0	0	0	0	0	0	0	0	0	0
2030	2035	0	D	0	0	0	27JUL84	27JUL84	25OCT84	0	0	0	0	0	0	0	0	0	0
2030	2040	0	D	0	0	0	25SEP84	25SEP84	25SEP84	0	0	0	0	0	0	0	0	0	0
2035	2040	15	BBB-EDN, NONSTRUCTURAL DESIGN	0	0	0	25SEP84	25SEP84	25SEP84	0	0	0	0	0	0	0	0	0	0
2040	2045	60	BBB-EDD, DRAFTING PLANS	0	0	0	25SEP84	25SEP84	25SEP84	0	0	0	0	0	0	0	0	0	0
2040	2050	60	BBB-ESP, SPECS	0	0	0	25OCT84	24DEC84	24DEC84	0	0	0	0	0	0	0	0	0	0
2045	2050	0	D	0	0	0	25OCT84	24DEC84	24DEC84	0	0	0	0	0	0	0	0	0	0
2050	2055	30	BBB-EDE, ESTIMATE	0	0	0	24DEC84	23JAN85	24MAR85	0	0	0	0	0	0	0	0	0	0
2055	5000	0	D	0	0	0	23JAN85	23JAN85	24MAR85	0	0	0	0	0	0	0	0	0	0
3010	3015	90	CCC-ENO, HYDROLOGY	0	0	0	10CT83	30DEC83	30DEC83	0	0	0	0	0	0	0	0	0	0
3010	3020	30	CCC-ECB, GEOTECH BORING	0	0	0	30DEC83	30DEC83	30DEC83	0	0	0	0	0	0	0	0	0	0
3015	3020	0	D	0	0	0	30DEC83	30DEC83	30DEC83	0	0	0	0	0	0	0	0	0	0
3020	3025	270	CCC-EGD, GEOTECH DESIGN	0	0	0	30DEC83	30DEC83	30DEC83	0	0	0	0	0	0	0	0	0	0
3020	3030	90	CCC-EHA, HYDRAULIC DESIGN	0	0	0	27JUN84	25SEP84	25SEP84	0	0	0	0	0	0	0	0	0	0
3025	3030	0	D	0	0	0	25SEP84	25SEP84	25SEP84	0	0	0	0	0	0	0	0	0	0
3030	3035	90	CCC-EGE, GENERAL ENGR	0	0	0	25SEP84	25SEP84	25SEP84	0	0	0	0	0	0	0	0	0	0
3030	3040	60	CCC-EDD, DRAFTING PLANS	0	0	0	24DEC84	22FEB85	24DEC84	0	0	0	0	0	0	0	0	0	0
3035	3040	60	CCC-ESP, SPECS	0	0	0	24DEC84	22FEB85	24DEC84	0	0	0	0	0	0	0	0	0	0
3040	3045	0	D	0	0	0	22FEB85	22FEB85	22FEB85	0	0	0	0	0	0	0	0	0	0
3045	3050	30	CCC-EDE, ESTIMATE	0	0	0	22FEB85	24MAR85	24MAR85	0	0	0	0	0	0	0	0	0	0
3050	5000	0	D	0	0	0	24MAR85	24MAR85	24MAR85	0	0	0	0	0	0	0	0	0	0

TOTAL COST OF WORK: 765000.
TOTAL COST OF WORK COMPLETED: 0.

3 INDICATES ACTUAL START
18 INDICATES MILESTONE DATE
1 LATE START SORT

JOBCTRL PDH1211 AB 15 0 37104 X 3 : OPERATOR PARTED PROGRAM.

Figure 5.1-5: Initial IMPSS Output From *CPM

5.2 Stage II Example:

If the initial output is accurate, the milestones, actual start dates, and percentages of completion for each activity can be added to constrain the network. The next run can then be made and its output analyzed for accuracy. Figure 5.2-1 shows the output of the second run.

If the initial output is accurate, it must then be determined if it is realistic. First, a check is made to ensure that all milestones can be met. Figure 5.2-1 shows that the milestones for activities (3030, 3035) and (3045, 3050) cannot be met. The network for Project CCC (Figure 5.1-3) shows that the duration of either activity (3010, 3015), (3020, 3025), or (3030, 3035) must be altered by a total of at least 54 days to meet the milestone. Discussions with each section chief reveal that the Hydrology Section can probably complete its activity in 80 days, Geotechnical Design can finish in 230 days, and General Engineering can finish in 85 days without adding to the project cost. (In other words, the initial duration estimates for Project CCC were fairly conservative, as would normally be expected.) The durations for these activities are then revised and another "*CPM" run is made. The output from that run, Figure 5.2-2, shows that all milestones can now be met. Because the output appears to be realistic, the graphics options are run, and Figures 5.2-3 and 5.2-4 are produced.

5.3 Stage III Example:

The resource histogram shows three distinct peaks (critical periods). The first occurs from 1 October 1983 to 30 October 1983. The second spans the period from 17 January 1984 to 15 March 1984, and the third runs from 1 August 1984 to 31 October 1984. The first attempt at leveling should be without regard to any particular resource amount (R_{max}). Using the Gantt Chart, activities which are ongoing during each critical period are identified. Those which have slack are listed in following table.

Table 5.3-1 Activities With Slack

<u>Period</u>	<u>Activity</u>	<u>Slack (Days)</u>	<u>Resources (\$/Day)</u>
1 Oct-30 Oct 83	AAA-EGB Geotech Boring	60	833
	BBB-EGB Geotech Boring	60	833
	CCC-EHO Hydrology	55	312
	CCC-EGB Geotech Boring	105	833
17 Jan 84-15 Mar 84	AAA-EHA Hydraulic Design	180	722
	CCC-EHA Hydraulic Design	195	722
1 Aug 84-31 Oct 84	BBB-EGE General Engineering	60	777
	BBB-EDS Struc. Design	75	333
	BBB-EDN Nonstruc. Design	75	166
	BBB-EDN Nonstruc. Design	75	333
	CCC-EGD Geotech. Design	55	174

DI, SAMPLE1

1 I-J SORT

UPDATE AS OF 10 303

REPORT EXAMPLE OUTPUT 11 MAR 83
THREE HYPOTHETICAL PROJECTS
ILLUSTRATES USE OF INPSS ALGORITHM AND SAMPLE OUTPUTS

EVENT	DUR	ACTIVITY DESCRIPTION	TOTAL COST	CURRENT COST	PCT COMP	EARLIEST START	EARLIEST FINISH	LATEST START	LATEST FINISH	SLACK	TOT REM
1010	0	D	0	0	0	10CT83	10CT83	10CT83	10CT83	0	0
1010	0	D	0	0	0	10CT83	10CT83	30NOV83	30NOV83	0	60
1010	0	D	0	0	0	10CT83	10CT83	10CT83	10CT83	0	0
1010	90	AAA-ENO, HYDROLOGY	25000	0	0	30DEC83	30DEC83	10CT83	30DEC83	0	0
1015	1020	D	25000	0	0	10CT83	310CT83	10CT83	30DEC83	0	60
1020	1025	0	0	0	0	30DEC83	30DEC83	30DEC83	30DEC83	0	0
1020	1030	90	65000	0	0	30DEC83	29MAR84	27JUN84	25SEP84	180	180
1025	1030	270	40000	0	0	30DEC83	25SEP84	30DEC83	25SEP84	0	0
1025	1035	0	0	0	0	29MAR84	29MAR84	25SEP84	25SEP84	0	0
1030	1035	90	70000	0	0	29MAR84	27JUN84	25SEP84	25SEP84	180	180
1030	1035	90	30000	0	0	25SEP84	24DEC84	25SEP84	24DEC84	0	0
1035	1040	60	10000	0	0	24DEC84	24DEC84	24DEC84	24DEC84	0	0
1035	1045	60	20000	0	0	24DEC84	22FEB85	24DEC84	22FEB85	0	0
1040	1045	0	0	0	0	22FEB85	22FEB85	22FEB85	22FEB85	0	0
1045	1050	30	5000	0	0	22FEB85	24MAR85	22FEB85	24MAR85	0	0
1050	5000	0	0	0	0	24MAR85	24MAR85	24MAR85	24MAR85	0	0
2010	2015	30	25000	0	0	10CT83	310CT83	10CT83	30DEC83	0	60
2015	2020	270	40000	0	0	310CT83	27JUL84	30DEC83	25SEP84	0	60
2015	2025	30	10000	0	0	310CT83	30NOV83	10CT83	25SEP84	0	0
2020	2025	0	0	0	0	27JUL84	27JUL84	10CT83	10CT83	0	0
2020	2040	90	70000	0	0	27JUL84	25OCT84	25SEP84	10CT83	315	315
2025	2030	60	20000	0	0	27JUL84	25SEP84	25SEP84	10CT83	0	0
2025	2035	60	10000	0	0	27JUL84	25SEP84	25SEP84	10CT83	0	0
2030	2035	0	0	0	0	25SEP84	25SEP84	10CT83	10CT83	0	0
2030	2040	15	5000	0	0	25SEP84	25SEP84	10CT83	10CT83	0	0
2040	2045	60	10000	0	0	25OCT84	10CT84	24DEC84	24DEC84	0	0
2040	2050	60	20000	0	0	25OCT84	24DEC84	24DEC84	24DEC84	0	0
2045	2050	0	0	0	0	24DEC84	24DEC84	24DEC84	24DEC84	0	0
2050	2055	30	5000	0	0	24DEC84	24DEC84	24DEC84	24DEC84	0	0
2055	5000	0	0	0	0	23JAN85	23JAN85	24MAR85	24MAR85	0	0
3010	3015	90	25000	0	0	10CT83	30DEC83	10CT83	30DEC83	0	0
3015	3020	30	25000	0	0	10CT83	310CT83	10CT83	30DEC83	0	0
3020	3025	0	0	0	0	30DEC83	30DEC83	30DEC83	30DEC83	0	0
3020	3030	270	40000	0	0	30DEC83	29MAR84	30DEC83	25SEP84	0	0
3025	3030	90	65000	0	0	30DEC83	29MAR84	27JUN84	25SEP84	180	180
3030	3030	0	0	0	0	25SEP84	25SEP84	25SEP84	25SEP84	0	0
3030	3035	90	70000	0	0	25SEP84	310CT84	25SEP84	310CT84	-54	0
3035	3040	60	10000	0	0	24DEC84	22FEB85	24DEC84	22FEB85	0	0
3035	3045	60	20000	0	0	24DEC84	22FEB85	24DEC84	22FEB85	0	0
3040	3045	0	0	0	0	22FEB85	22FEB85	22FEB85	22FEB85	0	0
3045	3050	30	5000	0	0	22FEB85	31JAN85	22FEB85	31JAN85	-52	0
3050	5000	0	0	0	0	24MAR85	24MAR85	24MAR85	24MAR85	0	0


TOTAL COST OF WORK: 765000.
TOTAL COST OF WORK COMPLETED: 0.

8 INDICATES ACTUAL START DATE
18 INDICATES MILESTONE DATE
EOT..

Figure 5.2-1: Output of Second *CPM Run With Milestones And Actual Start Date Included


DI. SAMPLE		UPDATE AS OF 10 383		REPORT EXAMPLE OUTPUT		11 MAR 83		THREE HYPOTHETICAL PROJECTS		ILLUSTRATES USE OF IMPSS ALGORITHM AND SAMPLE OUTPUTS		CURRENT PCT		EARLIEST		LATEST		SLACK	
I	J	I	J	EVENT	DUR	ACTIVITY DESCRIPTION	TOTAL COST	CURRENT COST	COMP	START	FINISH	START	FINISH	START	FINISH	TOT	REM		
1	1	1010	0	D	0	0	0	0	0	10CT83	10CT83	10CT83	10CT83	0	0	0	0	0	0
1	1	2010	0	D	0	0	0	0	0	10CT83	10CT83	10CT83	10CT83	0	0	0	0	0	0
1	1	3010	0	D	0	0	0	0	0	10CT83	10CT83	10CT83	10CT83	0	0	0	0	0	0
1010	1015	90	0	AAA-ENG, HYDROLOGY	0	25000.	25000.	0	0	10CT83	30DEC83	10CT83	30DEC83	0	0	0	0	0	0
1010	1020	30	0	AAA-EGD, GEOTECH BORING	0	25000.	25000.	0	0	10CT83	30DEC83	10CT83	30DEC83	0	0	0	0	0	0
1015	1020	0	0	D	0	0	0	0	0	10CT83	10CT83	10CT83	10CT83	0	0	0	0	0	0
1020	1025	90	0	AAA-ENH, HYDRAULIC DESIGN	0	65000.	65000.	0	0	30DEC83	29MAR84	30DEC83	29MAR84	0	0	0	0	0	0
1020	1030	270	0	AAA-EGD, GEOTECH DESIGN	0	40000.	40000.	0	0	30DEC83	25SEP84	30DEC83	25SEP84	0	0	0	0	0	0
1025	1030	0	0	D	0	0	0	0	0	29MAR84	29MAR84	29MAR84	29MAR84	0	0	0	0	0	0
1025	1035	90	0	AAA-EGE, GENERAL ENGR	0	70000.	70000.	0	0	29MAR84	24DEC84	29MAR84	24DEC84	0	0	0	0	0	0
1030	1035	90	0	AAA-EDS, STRUCTURAL DESIGN	0	30000.	30000.	0	0	25SEP84	24DEC84	25SEP84	24DEC84	0	0	0	0	0	0
1035	1040	60	0	AAA-EDD, DRAFTING PLANS	0	10000.	10000.	0	0	24DEC84	22FEB85	24DEC84	22FEB85	0	0	0	0	0	0
1035	1045	60	0	AAA-ESP, SPECS	0	20000.	20000.	0	0	24DEC84	22FEB85	24DEC84	22FEB85	0	0	0	0	0	0
1040	1045	0	0	D	0	0	0	0	0	22FEB85	22FEB85	22FEB85	22FEB85	0	0	0	0	0	0
1045	1050	30	0	AAA-EDE, ESTIMATE	0	5000.	5000.	0	0	24MAR85	24MAR85	24MAR85	24MAR85	0	0	0	0	0	0
1050	5000	0	0	D	0	0	0	0	0	24MAR85	24MAR85	24MAR85	24MAR85	0	0	0	0	0	0
2010	2015	30	0	BBB-EGD, GEOTECH BORING	0	25000.	25000.	0	0	10CT83	31OCT83	10CT83	31OCT83	0	0	0	0	0	0
2010	2020	30	0	BBB-EGD, GEOTECH DESIGN	0	40000.	40000.	0	0	10CT83	27JUL84	10CT83	27JUL84	0	0	0	0	0	0
2015	2025	30	0	BBB-EDS, STRUCTURAL DESIGN	0	10000.	10000.	0	0	31OCT83	30NOV83	31OCT83	30NOV83	0	0	0	0	0	0
2020	2025	0	0	D	0	0	0	0	0	10CT83	10CT83	10CT83	10CT83	0	0	0	0	0	0
2020	2040	90	0	BBB-EGE, GENERAL ENGR	0	70000.	70000.	0	0	10CT83	27JUL84	10CT83	27JUL84	0	0	0	0	0	0
2025	2030	60	0	BBB-EDS, STRUCTURAL DESIGN	0	20000.	20000.	0	0	27JUL84	25OCT84	27JUL84	25OCT84	0	0	0	0	0	0
2025	2035	60	0	BBB-EDM, NONSTRUCTURAL DESIGN	0	10000.	10000.	0	0	27JUL84	25SEP84	27JUL84	25SEP84	0	0	0	0	0	0
2030	2035	0	0	D	0	0	0	0	0	25SEP84	25SEP84	25SEP84	25SEP84	0	0	0	0	0	0
2030	2040	0	0	D	0	0	0	0	0	25SEP84	25SEP84	25SEP84	25SEP84	0	0	0	0	0	0
2035	2040	15	0	BBB-EDN, NONSTRUCTURAL DESIGN	0	5000.	5000.	0	0	25SEP84	25SEP84	25SEP84	25SEP84	0	0	0	0	0	0
2040	2045	60	0	BBB-EDD, DRAFTING PLANS	0	10000.	10000.	0	0	25OCT84	24DEC84	25OCT84	24DEC84	0	0	0	0	0	0
2040	2050	60	0	BBB-ESP, SPECS	0	20000.	20000.	0	0	25OCT84	24DEC84	25OCT84	24DEC84	0	0	0	0	0	0
2045	2050	0	0	D	0	0	0	0	0	24DEC84	24DEC84	24DEC84	24DEC84	0	0	0	0	0	0
2050	2055	30	0	BBB-EDE, ESTIMATE	0	5000.	5000.	0	0	24DEC84	23JAN85	24DEC84	23JAN85	0	0	0	0	0	0
2055	5000	0	0	D	0	0	0	0	0	23JAN85	23JAN85	23JAN85	23JAN85	0	0	0	0	0	0
3010	3015	80	0	CCC-ENG, HYDROLOGY	0	25000.	25000.	0	0	10CT83	20DEC83	10CT83	20DEC83	0	0	0	0	0	0
3010	3020	30	0	CCC-EGD, GEOTECH BORING	0	40000.	40000.	0	0	10CT83	31OCT83	10CT83	31OCT83	0	0	0	0	0	0
3015	3025	230	0	CCC-EGD, GEOTECH DESIGN	0	65000.	65000.	0	0	20DEC83	20DEC83	20DEC83	20DEC83	0	0	0	0	0	0
3020	3030	90	0	CCC-ENH, HYDRAULIC DESIGN	0	70000.	70000.	0	0	20DEC83	19MAR84	20DEC83	19MAR84	0	0	0	0	0	0
3025	3030	0	0	D	0	0	0	0	0	19MAR84	19MAR84	19MAR84	19MAR84	0	0	0	0	0	0
3030	3035	85	0	CCC-EGE, GENERAL ENGR	0	10000.	10000.	0	0	19MAR84	30OCT84	19MAR84	30OCT84	0	0	0	0	0	0
3035	3040	60	0	CCC-EDD, DRAFTING PLANS	0	20000.	20000.	0	0	30OCT84	29DEC84	30OCT84	29DEC84	0	0	0	0	0	0
3035	3045	60	0	CCC-ESP, SPECS	0	5000.	5000.	0	0	29DEC84	29DEC84	29DEC84	29DEC84	0	0	0	0	0	0
3040	3045	0	0	D	0	0	0	0	0	29DEC84	29DEC84	29DEC84	29DEC84	0	0	0	0	0	0
3045	3050	30	0	CCC-EDC, ESTIMATE	0	765000.	765000.	0	0	29DEC84	28JAN85	29DEC84	28JAN85	0	0	0	0	0	0
3050	5000	0	0	D	0	0	0	0	0	28JAN85	28JAN85	28JAN85	28JAN85	0	0	0	0	0	0

Figure 5.2-2: Output After Durations Have Been Changed to Allow Milestones to be Met




REPORT EXAMPLE OUTPUT 11 MAR 83
 THREE HYPOTHETICAL PROJECTS
 ILLUSTRATES USE OF IMPSS ALGORITHM
 PLOT FILE IS BARGPARR2

Figure 5.2-3 (Page 1): Gantt Chart




REPORT EXAMPLE OUTPUT 11 MAR 83
 THREE HYPOTHETICAL PROJECTS
 ILLUSTRATES USE OF IMPSS ALGORITHM
 PLOT FILE IS BAPGRAM2

Figure 5.2-3 (Page 2): Gantt Chart



REPORT EXAMPLE OUTPUT : 1 MAR 83
 THREE HYPOTHETICAL PROJECTS
 ILLUSTRATES USE OF IMPSS ALGORITHM
 PLOT FILE IS BAPGRAN2

Figure 5.2-3 (Page 3): Gantt Chart



REPORT EXAMPLE OUTPUT 11 MAR 83
 THREE HYPOTHETICAL PROJECTS
 ILLUSTRATES USE OF IMPSS ALGORITHM
 PLOT FILE IS BARGRAM2

Figure 5.2-3 (Page 4): Gantt Chart

100183	112483	11784	31184	50484	62784	82084	101384	120684	12985	32485
DATE (NO-DAY-YR)										
							<u>CCC-EGE, GENERAL ENGR</u>			
								<u>CCC-EDD DRAFTING PLANS</u>		
								<u>CCC-ESP SPECS</u>		
									<u>CCC-EDF ESTIMATE</u>	

REPORT EXAMPLE OUTPUT 11 MAR 83
THREE HYPOTHETICAL PROJECTS
ILLUSTRATES USE OF IMPSS ALGORITHM
PLOT FILE IS BARGRAM2

Figure 5.2-3 (Page 5): Gantt Chart




Figure 5.2-4: Resource Histogram

At this point, a system limitation concerning slack must be remembered. Because the projects are tied together with artificial dummies at the beginning and end, the criterion for determining critical activities within a single project changes from activities with zero slack to those with the least amount of slack within the project. Therefore, activities BBB-EGE, CCC-EGD, CCC-EHO, and CCC-EGB are critical and should be removed from initial consideration during resource leveling.

On the basis of analysis of the output, the following changes will be made during the first attempt to level resource requirements:

- a. Schedule activity CCC-EGB, Geotech Boring (3010, 3020) to start on 31 Oct 83.
- b. Schedule activity AAA-EGB, Geotech Boring, (1010, 1020) to start on 30 Nov 83.
- c. Schedule activity AAA-EHA, Hydraulic Design (1020, 1025) to start on 1 Apr 84.
- d. Schedule activity BBB-EDS, Structural Design, (2025, 2030) to start on 10 Oct 84.
- e. Schedule activity BBB-EDN, Nonstructural Design, (2025, 2035) to start on 10 Oct 84.
- f. Schedule activity BBB-EDN, Nonstructural Design (2025-2040) to start on 9 Dec 84.

5.4 Stage IV Example:

After entering these changes, another run can be made and another Gantt Chart and resource histogram produced. The histogram, Figure 5.4-1, shows that, while the resource requirements are more level, there are still two critical periods--31 October 1983 to 30 December 1983 and 27 July 1984 to 30 October 1984. Again using the Gantt Chart to identify activities with slack during those critical periods, a decision to schedule activity BBB-EDS, Structural Design (2015, 2025) to start on 19 March 1984 is made to flatten the first peak. The second peak is caused by a bottleneck in the General Engineering Section. The decision to contract out activities AAA-EGE (1025-1035) and AAA-EDS (1030-1035) is made. These changes produce Figure 5.4-2.

Setting $R_{max} = \$1,750/\text{day}$ and plotting that line on the histogram reveals two new critical periods. The first is from 20 December 1983 to 30 December 1983. Analysis of the Gantt Chart shows that the peak is caused by a bottleneck in the Hydrology Section. Because the period is only 10 days long, it can probably be discounted or a decision could be made to shift funds to allow overtime to be worked during that period. The second peak is from 25 September 1984 to 25 October 1984 and is primarily the result of the General Engineering Section's workload. This problem can only be solved by allowing the completion date for either Project BBB or




Figure 5.4-1: Resource Histogram After First Attempt at Leveling




Figure 5.4-2: Resource Histogram After Second Attempt at Leveling

Project CCC to be slipped by 60 days.

5.5 Stage V Example:

Further iterations of the system must be made until the corporate body is satisfied with the output. Additionally, iterations can be made to illustrate various alternatives for decision making. Once a satisfactory product is achieved, a final run of "*CPM" can be made to produce the graphics required to illustrate the wishes of the decision-makers. This is the point in the process where the search options of "*CPM" would most likely be used to produce charts and tables for each functional area and project.

6. Conclusions:

The example in section 5 and a similar test of IMPSS using three real projects demonstrated this system's potential for providing a viable solution to the problem of integrated, multiple-project scheduling. The key to maximizing the value of this system is the human factor in the decision-making process. If project managers do a reasonable job of developing project networks and input data, the mathematical model built by IMPSS will be of sufficient quality to allow the executive group to make intelligent decisions. The system's ability to handle 30 projects (the anticipated load for IMPSS) is yet to be demonstrated. However, the system does have the capacity for that number of projects, and though analysis will no doubt become tedious, there is no reason why it cannot be properly carried out. Therefore, the system as presented in this report should be considered as the best available solution to the problem of scheduling multiple projects within the St. Paul District.

7. Recommendations:

The following recommendations are made:

a. Consider adopting IMPSS as the base for making project scheduling decisions for fiscal year 1984.

b. Schedule a short course on IMPSS input development for project managers no later than 1 May 1983.

c. Schedule a short course on IMPSS output interpretation for functional area managers and their supervisors no later than 1 July 1983.

d. Establish and support a suspense date of 1 June 1983 for completion of all input for the first full-scale run of IMPSS.

Appendix A

Abbreviations and Definitions

A/E: Architect/Engineer

Algorithm: A set of rules for solving a problem in a finite number of steps.

Bar Chart: A scaled, graphical representation of a schedule.

CPM: Critical Path Method.

CRT: Cathode Ray Tube.

EF: Early Finish - The earliest time an activity can be completed.

ES: Early Start - The earliest time an activity can be started.

Gantt Chart: A bar chart which shows slack.

Heuristics: A set of rules which serve to indicate the arrival at a desired solution.

Histogram: A graph of frequency distribution.

I Number: The event number at the tail of an activity arrow.

IMPSS: Integrated Multiple Project Scheduling System.

J Number: The event number at the head of an activity arrow.

LF: Late Start - the latest time an activity can be finished.

LS: Late Start - the latest time an activity can be started.

Milestone: The date on which an activity must be completed.

Precedence Networking: A system of networking, similar to CPM, which allows activities to overlap.

RA/PM: Resource Allocation/Project Management.

RS: Remaining Slack - the amount of slack remaining in an activity after it has actually been started.

Software: A computer program.

Sort: An organization of data in a specific format.

TS: Total Slack, the difference between the LF and EF of an activity.

"*CPM": A canned program used with IMPSS.

Appendix B

Sample Form for Input and Updating

The following page is a sample form which can be used to organize the required input for each individual project. These forms could constitute the bulk of a periodic report from project managers which would be used to update the master network.

Project Input for IMPSS

Project: _____

Project Manager: _____

				(Network Sketch)	As of Date:		
I	J	Cost (\$)	Dur (Days)	Description Codes (Proj-Org)	Milestone (MMDDYY)	Actual Start (MMDDYY)	% Complete

Bibliography

- Department of the Army, 1982. Network Analysis Systems Course, Corps of Engineers Training Center, Huntsville, Alabama.
- Hoare, H. R., 1973. Project Management Using Network Analysis, McGraw-Hill, New York.
- Meredith, D. D., et al., 1973. Design and Planning of Engineering Systems, Prentice-Hall, Englewood Cliffs, N.J.
- Rekow, E. D., 1982. Project Management Guidelines, St. Paul District, St. Paul, MN.
- Riggs, J. L., 1976. Production System: Planning Analysis, and Control, John Wiley and Sons.
- Shaffer, L. R., et al., 1965. The Critical Path Method, McGraw Hill, New York.
- Wiest, J. D. and F. K. Levy, 1977. A Management Guide to PERT/CPM, Prentice-Hall, Englewood Cliffs, N.J.

END

FILMED

6-83

DTIC