

AD-A133 039


COPES - A FORTRAN CONTROL PROGRAM FOR ENGINEERING
SYNTHESIS(U) NAVAL POSTGRADUATE SCHOOL MONTEREY CA
L E MADSEN ET AL. MAR 82 NPS69-81-003


1/2

UNCLASSIFIED

F/G 9/2

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AD-A133039

NPS69-81-003

2

NAVAL POSTGRADUATE SCHOOL

Monterey, California



DTIC
ELECTED
SEP 28 1983
S D
B

COPES - A FORTRAN CONTROL PROGRAM
FOR ENGINEERING SYNTHESIS

BY
LEROY E. MADSEN
AND
GARRET N. VANDERPLAATS

March 1982

Approved for public release; distribution unlimited.

Prepared for:
Naval Postgraduate School
Monterey, California
93940

DTIC FILE COPY

83 09 00 16

NAVAL POSTGRADUATE SCHOOL
Monterey, California

Rear Admiral J. J. Ekelund
Superintendent

D. A. Schrady
Acting Provost

This project was unfunded.

Reproduction of all or part of this report is authorized.

This report was prepared by:

GARRET N. VANDERPLAATS
GARRET N. VANDERPLAATS
Associate Professor of Mechanical
Engineering

Reviewed by:

P. J. Mario
P. J. MARIO, Chairman
Department of Mechanical
Engineering

Released by:

W. M. Tolles
W. M. TOLLES
Dean of Research

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NPS69-81-003	2. GOVT ACCESSION NO. AD-A133039	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) COPES - A Fortran Control Program for Engineering Synthesis		5. TYPE OF REPORT & PERIOD COVERED Research Report - 1981
7. AUTHOR(s) Leroy E. Madsen Garret N. Vanderplaats		6. PERFORMING ORG. REPORT NUMBER NPS69-81-003
8. PERFORMING ORGANIZATION NAME AND ADDRESS Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93940		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Postgraduate School Monterey, Ca 93940		12. REPORT DATE March 1982
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)		13. NUMBER OF PAGES 124
		15. SECURITY CLASS. (of this report) Unclassified
		16e. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Optimization, Design, Mathematical Programming, Computer aided design.		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A FORTAN COntrol Program for Engineering Synthesis (COPES) has been developed for solving engineering design problems. The program maximizes or minimizes a numerically defined objective function subject to a set of inequality constraint functions. COPES uses the optimization program, CONMIN, which includes the conjugate direction method of Fletcher and Reeves for unconstrained function minimization and a modification of		

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE/When Data Entered:

Item #20 continued:

Zoutendijk's method of feasible directions for constrained function minimization. Additionally, approximation techniques are available for use in optimization, and trade-off studies may be performed. A simple design example demonstrates the program capabilities. Programming guidelines are presented followed by sample input data and output for each program option.

TABLE OF CONTENTS

LIST OF FIGURES -----	4
I. INTRODUCTION -----	6
II. PROGRAMMING GUIDELINES -----	14
III. DATA MANAGEMENT -----	20
IV. COPES TERMINOLOGY -----	22
V. COPES DATA -----	25
VI. UNFORMATTED DATA INPUT -----	26
VII. SAMPLE COMPUTER SOLUTIONS -----	55
VIII. REFERENCES -----	105
APPENDIX A - GLOBAL CATALOG FORMS -----	106
APPENDIX B - COPES DATA FORMS -----	108

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification _____	
By _____	
Distribution/ _____	
Availability Codes	
Dist	Avail and/or Special
A	

LIST OF FIGURES

1.	Cantilevered Beam -----	8
2.	Analysis Only -----	57
3.	Optimization -----	60
4.	Sensitivity Study -----	67
5.	Two-Variable Function Space Study -----	72
6.	Optimum Sensitivity -----	78
7.	Optimization Using Approximation Techniques -----	86
8.	Combined Data Input -----	100
9.	Simplified Data Input -----	102
10.	Simplified Data Input Without Comment Cards -----	104

ABSTRACT

A FORTRAN COntrol Program for Engineering Synthesis (COPES) has been developed for solving engineering design problems. The program maximizes or minimizes a numerically defined objective function subject to a set of inequality constraint functions. COPES uses the optimization program, CONMIN, which includes the conjugate direction method of Fletcher and Reeves for unconstrained function minimization and a modification of Zoutendijk's method of feasible directions for constrained function minimization. Additionally, approximation techniques are available for use in optimization, and trade-off studies may be performed. A simple design example demonstrates the program capabilities. Programming guidelines are presented followed by sample input data and output for each program option.

I. INTRODUCTION

Most design processes require the minimization or maximization of some parameter which may be called the design objective. For the design to be acceptable, it must satisfy a variety of physical, aesthetic, economic and, on occasion, political limitations which are referred to here as design constraints. While part of the design problem may not be easily quantified, most of the design criteria can be described in numerical terms.

To the extend that the problem can be stated in numerical terms, a computer program can be written to perform the necessary calculations. For this reason, computer analysis is commonplace in most engineering organizations. For example, in structural design, the configuration, materials and loads may be defined and a finite element analysis computer code is used to calculate stresses, deflections and other response quantities of interest. If any of these parameters are not within the prescribed bounds, the engineer may change the structural member sizes and re-run the program. The computer code therefore provides only the analysis of a proposed design, with the engineer making the actual design decisions. This approach to design, which may be called computer-aided design, is commonly used today.

Another common use of analysis codes is in trade-off studies. For example, an aircraft trajectory analysis code may be run repetitively for several payloads, calculating the aircraft range, to determine the range-payload sensitivity.

A logical extension to computer-aided design is fully automated design, where the computer makes the actual design decisions, or to perform trade-off studies with a minimum of man-machine interaction. The purpose of the COPES program is to provide this automated design and trade-off capability. The user must provide a FORTRAN analysis program for analysis of the particular problem being considered. This analysis program is written according to a simple set of guidelines so that it can be easily coupled to the COPES program for automated design synthesis.


This document describes the capabilities of the COPES program and its usage. A simple design example is first presented to demonstrate the program capabilities. Guidelines are given for writing analysis codes which can be coupled directly to COPES. Finally the data organization is outlined and sample data is presented.

The most commonly used option of the COPES program will be for design optimization. Two approaches are available for this purpose. The first ($NCALC = 2$) is direct optimization of the function by the CONMIN optimization sub-program [Ref. 1]. An alternative to this is through the use of approximation techniques ($NCALC = 6$, Ref. 2). This second

option is usually more efficient for problems of under 6 design variables but which requires costly analysis, especially when multiple optimizations are to be performed.

DESIGN EXAMPLE

Assume it is required to design the cantilevered beam shown in Fig. 1. The objective is to find the minimum volume of material which will support the concentrated load. That is;



$$\text{Minimize Volume} = B \cdot H \cdot L \quad (1) \quad \text{Figure 1 - Cantilevered Beam}$$

The bending stress in the beam must not exceed 20,000 psi;

$$\sigma_b = \frac{Mc}{I} = \frac{6PL}{BH^2} \leq 20,000 \quad (2)$$

The shear stress must not exceed 10,000 psi;

$$v = \frac{3}{2} \frac{P}{A} = \frac{3P}{2BH} \leq 10,000 \quad (3)$$

and the deflection under the load must not exceed one inch;

$$\delta = \frac{PL^3}{3EI} = \frac{4PL^3}{EBH^3} \leq 1.0 \quad (4)$$

Additionally, geometric limits are imposed on the beam size so that;

$$0.5 \leq B \leq 5.0 \quad (5)$$

$$1.0 < H \leq 20.0 \quad (6)$$

$$H/B \leq 10.0 \quad (7)$$

Equation (1), the design objective, provides a measure of the efficiency of the design, while Eqs. (2-7) define the criteria which the structure must satisfy, and are referred to as constraints.

This design problem may be stated in general form;

Minimize $F(\bar{X})$

Subject to:

$$G_j(\bar{X}) \leq 0 \quad i = 1, m$$

$$x_i^l \leq x_i \leq x_i^u$$

where \bar{X} is a vector containing the design variables B and H and $G_j(\bar{X})$ are the constraints defined by Equations (2-7). There are eight constraints on the design. The objective and constraints are functions of the design variables.

While this problem is straightforward, its solution is not trivial because it is not known which constraints will be critical (i.e. which $G_j(\bar{X}) = 0$) at the optimum.

One design approach is to assume that the bending and the displacement constraints are critical, so that Equations (2) and (4) are equalities, and then solve the two simultaneous equations for the design variables B and H. The remaining constraints are then checked to be sure they are satisfied, and if not, they are used to obtain a new design satisfying all constraints. When a design is obtained where two $G_j(\bar{X}) = 0$ and the remaining $G_j(\bar{X}) \leq 0$, it is an acceptable design.

The design obtained here yields a volume of 6750 and satisfies all constraints. Note, however, that the objective function of Equation (1) played no part in the choice of design variables so that, using this approach, there is no assurance that a minimum volume design will be produced [Ref. 3]. More importantly, it is desirable to devise techniques for optimum design of systems which may be defined by more than two variables and by much more complex analysis, where the optimum design cannot be determined by inspection.

The COPES program provides this general capability by the use of the optimization program CONMIN [Ref. 1]. To use this design capability, a FORTRAN code must be provided which will calculate the various parameters. In writing the analysis code; 1) it is written in subroutine form with SUBROUTINE ANALIZ (ICALC) as the main routine, 2) it is segmented into INPUT, EXECUTION AND OUTPUT and 3) all parameters which may be design variables, object functions or constraints are contained in a single labeled common block called GLOBCM.

To demonstrate the simplicity with which a design-oriented analysis code can be written, the following FORTRAN subroutine was produced for the analysis of the cantilevered beam in Figure 1.

```

SUBROUTINE ANALIZ (ICALC)
COMMON /GLOBCM/ B,H,VOL,BSTRES,SHRSTR,DELTA,HB,E,AL
IF (ICALC.GT.1) GO TO 10
C --- INPUT OR INITIALIZATION.
B=2.5
H=10.
P=10,000.
E=30.E+6
AL=200.
WRITE (6,30)AL,P,E,B,H
RETURN
C --- EXECUTION.
10 CONTINUE
VOL=AL*B*H
BSTRES=6.*P*AL/(B*H*H)
SHRSTR=1.5*P/(B*H)
DELTA=4.*P*(AL**3)/(E*B*(H**3))
HB=H/B
IF (ICALC.LT.3) RETURN
C --- PRINT RESULTS.
20 WRITE (6,30)AL,P,E,B,H
WRITE (6,40)VOL,BSTRES,SHRSTR,DELTA,HB
30 FORMAT(////5X,17HCANTILEVERED BEAM//5X,8HAL = ,F9.3/5X,
* 8HP    = ,E12.5/5X,8HE    = ,E12.5//5X,8HB    = ,F9.3/5X,
* 8HH    = ,F9.3)
40 FORMAT(/5X,8HVOL    = ,F9.3//5X,8HBSTRES=,E12.5/5X,
8HSHRSTR=
* E12.5/5X,8HDELTA=,E12.5/5X,8HH/B    = ,F9.3)
RETURN
END

```

This routine may be executed as a simple analysis program by the following main program;

```

C     MAIN PROGRAM TO EXECUTE SUBROUTINE ANALIZ.
DO 10 I = 1,3
10 CALL ANALIZ (I)
STOP
END

```

Moreover, ANALIZ can be coupled directly to the COPES program to perform this same function, or to perform optimization or trade-off studies.

This subroutine was coupled to COPES and an optimization

was performed (NCALC = 2) to yield the following design;

CANTILEVERED BEAM

L	= 200.00
P	= .10000E+05
E	= .30000E+08
B	= 1.82
H	= 18.16
VOL	= 6607.61
BSTRES	= .20002E+05
SHRSTR	= .45402E+03
DELTA	= .97906E+00
H/B	= 9.98

The parameters L, P, E, B and H were input to the program and the remaining parameters were calculated. The design variables B and H were changed during the optimization process to obtain this design.

This design was achieved with 45 calls to ANALIZ with ICALC = 2 (45 analyses). This design could surely have been found with fewer analyses were it performed by hand calculations. However, once having written the analysis subroutine, numerous other designs may be obtained for different materials, loading, or design stresses with only minimal effort. Furthermore, the design obtained here of volume = 6607.6 is very near the theoretical optimum of 6603.9, while that which satisfied stress and displacement constraints simultaneously was not.

This very simple design example underscores the power of numerical optimization techniques and the ease with which they may be applied. The key to efficient use of the COPES program is the requirement that the ANALIZ code be written in a standard

format so that it may be coupled to COPES without modification. The following section contains guidelines for writing a design-oriented analysis code.

II. PROGRAMMING GUIDELINES

In developing any computer code for engineering analysis, it is prudent to write the code in such a way that it is easily coupled to a general synthesis program such as COPES. Therefore, a general programming practice is outlined here which in no way inhibits the use of the computer program in its traditional role as an analytic tool, but allows for simple adaptation to COPES. This approach is considered good programming practice and provides considerable flexibility of design options. Only five basic rules must be followed:

- I. Write the code in subroutine form with the primary routine called as; SUBROUTINE ANALIZ (ICALC) The name ANALIZ is compatible with the COPES program and ICALC is a calculation control. Note that subroutine ANALIZ may call numerous other subroutines as required to perform the necessary calculations.
- II. Segment the program into INPUT, EXECUTION and OUTPUT. The calculation control, ICALC, will determine the portion of the analysis code to be executed.
ICALC = 1; the program reads all data required to perform the analysis. Also, any initialization of constants which will be used repetitively during execution is done here. This initial input information is printed here for later reference and for program debugging.

ICALC = 2: the program performs the execution phase of the analysis task. No data reading or printing is done here, except on user-defined scratch disc. Data may be printed here during program debugging, in which case it should be controlled by a print control parameter which is read during input. In this way, this print may be turned off after the program is debugged, but may be used again during future program expansion and debugging. The reason that printing is not normally allowed during execution is that when optimization is being done, the code will be called many times with ICALC = 2, resulting in voluminous print.

ICALC = 3: the results of the analysis are printed. Also the essential input parameters which may have been changed during optimization should be printed here for easy reference. In some cases, so much information is generated when ICALC = 2 that it would be inefficient to store it internally or on disc for printing when ICALC = 3. In this case, it may be desirable to actually execute when ICALC = 3 with a print code turned on to print his intermediate information. However, this approach should be avoided because it requires an additional complete execution of the program.

In summary, when;

ICALC = 1 Read input data.

ICALC = 2 Execute the analysis.

ICALC = 3 Print the results.

- III. Store all parameters which may be design variables, objective functions or constraints in a single labeled common block called GLOBCM. The order in which they are stored is arbitrary. A listing of the COPES program should be checked to see how many parameters may be stored in GLOBCM (the dimension of ARRAY). Initial distribution of COPES allows for 1500 parameters.
- IV. During execution or output, no parameters which are read during input should be updated. For example, if variable X is initialized during input, the execution segment must not update X such as $X = X + 3.2$. Instead a new variable, $Y = X + 3.2$ should be defined.
- V. Write all programs in standard language, avoiding machine dependent capabilities such as multiple entry point (IBM), DEFINE statements (UNIVAC) and seven letter FORTRAN names (CDC). While this guideline is not essential to the use of the analysis code within the COPES program, it makes the analysis code much more transportable between different computer systems, a capability which easily justifies a slight reduction in efficiency on a given machine.

Adherence to these guidelines not only leads to a more readable and machine independent computer code, but allows

this code to be coupled to the COPES program without
modification.

Having written the analysis code, it may be executed either with a simple main program or within the COPES program to perform the analysis. To insure that guideline IV is followed, the following main test program is recommended. Note that this program calls ANNALIZ twice with ICALC = 2 and ICALC = 3, to show that the same result is obtained repetitively

```
C MAIN PROGRAM TO CHECK SUBROUTINE ANALIZ,  
C READ, EXECUTE AND PRINT.  
    DO 10 ICALC = 1, 3  
10  CALL ANALIZ (ICALC)  
C EXECUTE AND PRINT AGAIN TO BE SURE THE RESULTS  
C DO NOT CHANGE.  
    DO 20 ICALC = 2, 3  
20  CALL ANALIZ (ICALC)  
    STOP  
    END
```

This program was executed with the ANALIZ subroutine for the cantilevered beam example to yield the following result:

CANTILEVERED BEAM

AL	=	200.00
P	=	.10000E+05
E	=	.30000E+08
B	=	2.00
H	=	5.00

CANTILEVERED BEAM

AL	= 200.00
P	= .10000E+05
E	= .30000E+08
B	= 2.00
H	= 5.00
VOL	= 2000.00
BSTRES	= .24000E+06
SHRSTR	= .15000E+04
DELTA	= .42667E+02
H/B	= 2.50

CANTILEVERED BEAM

AL	= 200.00
P	= .10000E+05
E	= .30000E+08
B	= 2.00
H	= 5.00
VOL	= 2000.00
BSTRES	= .24000E+06
SHRSTR	= .15000E+04
DELTA	= .42667E+02
H/B	= 2.50

This design was used as the initial design for the optimization presented previously. Note that, while the volume here is lower than the optimum, the bending stress and displacement each exceed the imposed limits by more than an order of magnitude.

Once the analysis code has been written, it can be coupled to the COPES program without modification. If it is desired to perform a simple analysis using COPES, only three data

cards are required for the COPES program, namely a TITLE card, a control parameter, NCALC = 1, and an END card. If the optimization or parametric analysis (sensitivity) capabilities of COPES are to be used, additional data must be read. This data will identify which parameters in the global common block, GLOBCM, are used. To set up the COPES data, the user must have a basic understanding of how the data in the global common block is accessed by COPES. This is outlined in the following section.

III. DATA MANAGEMENT

In order to perform design operations, the COPES program must access the data in common block GLOBCM. This is done by defining the location in GLOBCM where a specified parameter resides. For example, consider the common block for the cantilevered beam;

```
COMMON/GLOBCM/B,H,VOL,BSTRES,SHRSTR,DELTA,HB,E,AL
```

The volume of material, VOL, is the third parameter in the common block; that is, it resides in location 3, referred to as the global location number. Similarly the bending stress, BSTRES, is in global location 4 and the beam width is in global location 1. Thus, the parameters are referred to by their respective location numbers in global common.

For convenience in preparing data for the COPES program, a simple "CATALOG" of parameters may be defined. For the cantilevered beam, this catalog would be;

GLOBAL LOCATION	FORTRAN NAME	DEFINITION
1	B	Beam width
2	H	Beam height
3	VOL	Volume of Material
4	BSTRES	Maximum bending stress
5	SHRSTR	Maximum shear stress
6	DELTA	Deflection under the load
7	HB	Ratio, H/B

<u>GLOBAL LOCATION</u>	<u>FORTRAN NAME</u>	<u>DEFINITION</u>
8	E	Young's modulus
9	AL	Length of beam

As another example, consider a global common block containing arrays;

COMMON/GLOBCM/A, Y(10), Q, C(2,2), H

The variable catalog for this common block is;

<u>GLOBAL LOCATION</u>	<u>FORTRAN NAME</u>	<u>DEFINITION</u>
1	A	Area
2	Y(10)	Vector of y-coordinates
12	Q	.
13	C(2,2)	.
17	H	etc.

The dimensions are given with the FORTRAN name as a reminder that the parameter is an array. In this case, the third parameter in the Y array is in global location 4. Remembering that arrays are stored column by column the C(1,2) array location is in global location 15.

It will be seen that identifying parameters according to their location in GLOBCM provides a great deal of flexibility in using the COPES program for design.

Appendix A contains blank forms for writing the variable catalog for the user's particular problem.

IV. COPES TERMINOLOGY

The copes program currently provides six specific capabilities;

1. Simple analysis, just as if COPES was not used.
2. Optimization - Minimization or maximization of one calculated function with limits imposed on other functions using the CONMIN subprogram.
3. Sensitivity analysis - the effect of changing one or more design variables on one or more calculated functions.
4. Two-variable function space - analysis for all specified combinations of two design variables.
5. Optimum sensitivity - same as sensitivity analysis except at each step, the design optimized with respect to the remaining independent design variables.
6. Approximate optimization - optimization using approximation techniques. Usually more efficient than standard optimization for up to 6 design variables or if multiple optimizations are to be performed.

In defining the data required to execute the COPES program, the following definitions are useful:

Design Variables - Those parameters which the optimization program is allowed to change in order to improve the design. Design variables appear only on the right hand side

of equations in the analysis program. COPES considers two types of design variables, independent and dependent. If two or more variables are always required to have the same value or be in a constant ratio, one is the independent variable while the remaining are dependent variables. For example, if the height is required to be 10 times the width of the cantilever beam, B would be the independent variable while H would be the dependent variable.

Objective Function - The parameter which is to be minimized or maximized during optimization. Also the parameters calculated as functions of specified design variables during a sensitivity or two-variable function space study. Objective functions always occur on the left side of equations, unless the objective function is also a design variable (the beam height may be minimized as an objective function if it is also a design variable. In this case the minimum height is found for which no constraints are violated). An objective function may be linear or non-linear, implicit or explicit, but must be a function of the design variables to be meaningful.

Constraint - Any parameter which must not exceed specified bounds for the design to be acceptable. Constraint functions, always appear on the left side of equations. Just as for objective functions, constraints may be linear or non-linear, implicit or explicit, but must be functions of the design variables.

Constraint Set - A group of constraints which appear consecutively in the global common block and which all have the same limits imposed. This is a convenience which allows several constraints to be identified with a minimum of data.

Global Common - Common block GLOBCM containing design information.

Global Location - Location of a particular parameter in GLOBCM.

V. COPES DATA

The COPES program reads data from unit 5 and writes output on unit 6. Units 20 and 40 are used as scratch files. The scratch file numbers may be changed by changing two cards at the beginning of the COPES program.

In order to execute the COPES program it is necessary to provide formatted data for COPES, followed by data for the ANALIZ program which is coupled to COPES. This section defines the data which is required by COPES. The data is segmented into "BLOCKS" for convenience. All formats are alphanumeric for TITLE, and END cards, F10 for real data and I10 for integer data.

The COPES data begins with a TITLE card and ends with an END card. This is followed by data to be read by the user supplied subroutine ANALIZ or when ICALC = 1.

Comment cards may be inserted anywhere in the COPES data stack prior to the END card, and are identified by a dollar sign (\$) in column 1.

Data coding forms are provided in Appendix B.

VI. UNFORMATTED DATA INPUT

While the user's sheet defines COPES data in formatted fields of ten, the data may actually be read in a simplified fashion by separating data by commas or one or more blanks. If more than one number is contained on an unformatted data card, a comma must appear somewhere on the card. If exponential numbers such as $2.5+10$ are read on an unformatted card, there must be no embedded blanks. Unformatted cards may be intermingled with formatted cards. Real numbers on an unformatted card should have a decimal point.

Examples:

Unformatted data;

5,7,1.3,1.0+20,0,-5.1

5,7,1.3,1.0+20,,,-5.1

5 7 1.3 1.0+20,, -5.1

5 7 1.3, 1.0+20 0 -5.1

Equivalent formatted data;

col+	10	20	30	40	50	60	70	80
	5	7	1.3	1.0+20	0	-5.1		

Unformatted data;

2

2,3

2 3

Equivalent formatted data;

col+ 10 20 30

2

Note: This data has been right justified.

2 3

Note: This data contains no commas, so it is assumed to be formatted already.

Unformatted data;

1,2,3,4,5,6,7,8,9,10,11

Equivalent formatted data;

col+ 10 20 30 40 50 60 70 80

1

2

3

4

5

6

7

8

9

10

11

Note that two formatted data cards are created here.

Unformatted data;

1,2,3,4,5,6,

7,8,9,10,11

Equivalent formatted data;

col+ 10 20 30 40 50 60 70 80

1

2

3

4

5

6

7

8

7

8

9

10

11

Note that the above two examples do not produce the same formatted data cards.

DATA BLOCK A

DESCRIPTION: Title card.

FORMAT AND EXAMPLE

	1	2	3	4	5	6	7	8	FORMAT
TITLE									
CANTILEVERED BEAM DESIGN									

FIELD

1-8 Any 80 character title may be given on this card.

CONTENTS

DATA BLOCK B

DESCRIPTION: Program Control Parameters

FORMAT AND EXAMPLE

FORMAT						
1	2	3	4	5	6	7
NCALC	NDV	NSV	N2VAR	NXAPRX	IPNPUT	IPDBG
2	2	3	5	2	0	0

FIELD

- | FIELD | CONTENTS |
|-------|--|
| 1 | NCALC: Calculation Control
0 - Read input and stop. Data of blocks A, B and V is required.
Remaining data is optional. |
| 1 | - One cycle through program. The same as executing ANALIZ stand-alone.
Data of blocks A, B and V is required. Remaining data is optional. |
| 2 | - Optimization. Data of blocks A-I and V is required. Remaining data is optional. |
| 3 | - Sensitivity analysis. Data of blocks A, B, P, Q and V is required.
Remaining data is optional. |
| 4 | - Two variable function space. Data of blocks A, B, and R-V is required.
Remaining data is optional. |

CONTENTS

<u>FIELD</u>	<u>CONTENTS</u>
1 - cont. NCALC:	
5	- Optimum Sensitivity. Data of blocks A-I, P, Q, and V is required. Remaining data is optional.
6	- Optimization using approximation techniques. Data of blocks A-0 and V is required. Remaining data is optional.
2	NDV: Number of independent design variables in optimization.
3	NSV: Number of variables on which sensitivity analysis will be performed.
4	N2VAR: Number of objective functions in a two variable function space study.
5	NXAPRX: Number of X-variables for approximate analysis/optimization.
6	IPNPUT: Input print control. 0 - Print card images of data plus formatted print of input data. 1 - Formatted print only of input data. 2 - No print of input data.
7	IPDBG: Debug print control.

DATA BLOCK C OMIT IF NDV = 0 IN BLOCK B

DESCRIPTION: Integer optimization control parameters.

FORMAT AND EXAMPLE

	1	2	3	4	5	6	7	8	FORMAT
FIELD	IPRINT	ITMAX	ICNDIR	NSCAL	ITRM	LINOBJ	NACMX1		
	5	0	0	0	0	0	0		7110

FIELD CONTENTS

1 IPRINT: Print control used in optimization.

- 0 - No print during optimization.
- 1 - Print initial and final optimization information.
- 2 - Print above plus objective function value and design variable values at each iteration.
- 3 - Print above plus constraint values, direction vector and move parameter at each iteration.
- 4 - Print above plus gradient information.
- 5 - Print above plus each proposed design vector, objective function and constraint values during the one-dimensional search.

<u>FIELD</u>	<u>CONTENTS</u>
2 ITMAX:	Maximum number of optimization iterations allowed. DEFAULT = 20.
3 ICNDIR:	Conjugate direction restart parameter. DEFAULT = NDV + 1.
4 NSCAL:	Scaling parameter. GT.0 - Scale design variable to order of magnitude one every NSCAL iterations. LT.0 - Scale design variables according to user-input scaling values. Suggested values are 0 or NDV + 1.
5 ITRM:	Number of consecutive iterations which must satisfy relative or absolute convergence criterion before optimization process is terminated. DEFAULT = 3.
6 LINOBJ:	Linear objective function identifier. If the optimization objective is known to be a linear function of the design variables, set LINOBJ = 1. DEFAULT = Nonlinear.
7 NACMX1:	One plus the maximum number of active constraints anticipated. DEFAULT = NDV + 2. If CONMIN writes an error message that the number of active and violated constraints exceeds N3-1, then NACMX1 must be increased (Note that NACMX1 = N3).

DATA BLOCK D OMIT IF NDV = 0 IN BLOCK B

DESCRIPTION: Floating point optimization program parameters.

FORMAT AND EXAMPLE

								FORMAT
1	FDCH	FDCHM	CT	CTMIN	CTL	CTLMIN	THETA	7F10
0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
DELFUN	DABFUN	ALPHAX	ABOBJI					4F10

NOTE: TWO CARDS ARE READ HERE.

FIELD CONTENT

- 1 FDCH: Relative change in design variables in calculating finite difference gradients. DEFAULT = 0.01.
- 2 FDCHM: Minimum absolute step in finite difference gradient calculations. DEFAULT = 0.01.

<u>FIELD</u>	<u>CONTENTS</u>
3	CT: Constraint thickness parameter. DEFAULT = -0.1.
4	CTMIN: Minimum absolute value of CT considered in the optimization process. DEFAULT = 0.004.
5	CTL: Constraint thickness parameter for linear constraints. DEFAULT = -0.01.
6	CTLMIN: Minimum absolute value of CTL considered in the optimization process. DEFAULT = 0.001.
7	THETA: Mean value of the push-off factor in the Method of Feasible Directions. DEFAULT = 1.0.
1	DELFUN: Minimum relative change in objective function to indicate convergence of the optimization process. DEFAULT = 0.001.
2	DABFUN: Minimum absolute change in objective function to indicate convergence of the optimization process. DEFAULT = 0.001 times the initial objective value.
3	ALPHAX: Maximum fractional change in any design variable for first estimate of the step in the one-dimensional search. DEFAULT = 0.1.
4	ABOBJI: Expected fractional change in the objective function for first estimate of the step in the one-dimensional search. DEFAULT = 0.1.

REMARKS:

- 1) The DEFAULT values for these parameters usually work well.

DATA BLOCK E OMIT IF NDV = 0 IN BLOCK B

DESCRIPTION: Total number of design variables, design objective identification and sign.

FORMAT AND EXAMPLE

	1	2	3	FORMAT
NDVTOT	I0BJ	SIGNOPT		2I10,F10
0	3	-1.0		

FIELD CONTENTS

- 1 NDVTOT: Total number of variables linked to the design variables. This option allows two or more parameters to be assigned to a single design variable. The value of each parameter is the value of the design variable times a multiplier, which may be different for each parameter. DEFAULT = NDV.
- 2 I0BJ: Global variable location associated with the objective function in optimization.
- 3 SIGNOPT: Sign used to identify whether function is to be maximized or minimized. +1.0 indicates maximization. -1.0 indicates minimization. If SIGNOPT is not unity in magnitude, it acts as a multiplier as well, to scale the magnitude of the objective.

DATA BLOCK F OMIT IF NDV = 0 IN BLOCK B

DESCRIPTION: Design variable bounds, initial values and scaling factors.

FORMAT AND EXAMPLE

				FORMAT
1	2	3	4	
VLB	VUB	X	SCAL	
.5	5.	0.0	0.0	

NOTE: READ ONE CARD FOR EACH OF THE NDV INDEPENDENT DESIGN VARIABLES.

FIELD

CONTENTS

- 1 VLB: Lower bound on the design variable. If VLB.LT.-1.0E+15, no lower bound.
- 2 VUB: Upper bound on the design variable. If VUB.GT.1.0E+15, no upper bound.
- 3 X: Initial value of the design variable. If X is non-zero, this will supercede the value initialized by the user-supplied subroutine ANALIZ.
- 4 SCAL: Design variable scale factor. Not used if NSCAL.GE.0 in Block C.

DATA BLOCK G OMIT IF NDV = 0 IN BLOCK B

DESCRIPTION: Design variable identification.

FORMAT AND EXAMPLE

FORMAT		
1	2	3
NDSGN	IDSGN	AMULT
1.	1	1.0

NOTE: READ ONE CARD FOR EACH OF THE NDVTOT DESIGN VARIABLES.

FIELD

CONTENTS

- 1 NDSGN: Design variable number associated with this parameter.
- 2 IDSGN: Global variable number associated with this parameter.
- 3 AMULT: Constant multiplier on this parameter. The value of the parameter will be the value of the design parameter, NDSGN, times AMULT. DEFAULT = 1.0.

DATA BLOCK H OMIT IF NDV = 0 IN BLOCK B

DESCRIPTION: Number of constraint sets.

FORMAT AND EXAMPLE

FORMAT	
1	NCONS
	4

FIELD

- 1 NCONS: Number of constraint sets in the optimization problem.

REMARKS

- 1) If two or more adjacent parameters in the global common block have the same limits imposed, these are part of the same constraint set.

DATA BLOCK I OMIT IF NDV = 0 IN BLOCK B, OR NCNS = 0 IN BLOCK H

DESCRIPTION: Constraint identification and constraint bounds.

FORMAT AND EXAMPLE

FORMAT			
1	2	3	4
ICON	JCON	LCON	
4	0	0	
BL	SCAL1	BU	SCAL2
-1.0 +20	0.0	20000.	0.0

NOTE: READ TWO CARDS FOR EACH OF THE NCNS CONSTRAINT SETS.

FIELD CONTENTS

- 1 ICON: First global number corresponding to the constraint set.
- 2 JCON: Last global number corresponding to the constraint set.
 DEFAULT = ICON.
- 3 LCON: Linear constraint identifier for this constraint set.
 LCON = 1 indicates linear constraints.

<u>FIELD</u>	<u>CONTENTS</u>
1	BL: Lower bound on the constrained variables. If BL.LT.-1.0E+15, no lower bound.
2	SCAL1: Normalization factor on lower bound. DEFAULT = MAX of ABS(BL), 0.1.
3	BU: Upper bound on the constrained variables. IF BU.GT.1.0E+15, no upper bound.
4	SCAL2: Normalization factor on upper bound. DEFAULT = MAX of ABS(BU), 0.1.

REMARKS

- 1) The normalization factor should usually be defaulted.
- 2) The constraint functions sent to CONMIN are of the form;

$$(BL - 'VALUE)/SCAL1 .LE. 0.0 \text{ and } (VALUE - BU)/SCAL2 .LE. 0.0.$$
- 3) Each constrained parameter is converted to two constraints in CONMIN unless ABS(BL) or ABS(BU) exceeds 1.0E+15, in which case no constraint is created for that bound.

DATA BLOCK J OMIT IF NXAPRX = 0 IN BLOCK B

DESCRIPTION: Approximate analysis/optimization control parameters.

FORMAT AND EXAMPLE

FORMAT				
1	2	3	4	5
NG	NXS	NXFS	NXA	INOM
5	1	1	1	0
KMIN	KMAX	NPMAX	JNOM	INXLOC
0	0	0	0	0

FIELD CONTENTS

- 1 NF: Number of functions to be approximated, Default = number of optimization objective and constraint functions.
- 2 NXS: Number of X-vectors read as data.
- 3 NXFS: Number of X-F pairs read as data.
- 4 NXA: If non-zero, the design variables read by SUBROUTINE ANALIZ form an X-vector.
- 5 INOM: Nominal X-vector. Default = best available.

FIELD

CONTENTS

6	ISCRX:	File from which NXS X-vectors are read. Default = 5.
7	ISCRXF:	File from which NXFS X-F pairs of data are read. Default = 5.
8	IPAPRX:	Print Control. Values of 0-4 with increasing amounts of print for larger IPAPRX.
1	KMIN:	Minimum number of approximation iterations. Default = 2 * NDV + 1 - NXS - NXFS - NXA.
2	KMAX:	Maximum number of approximation iterations. Default = 3 * NXAPRX + 3 * (NXAPRX + NXAPRX**2)/2 + 1 - NXS - NXFS - NXA.
3	NPMAX:	Maximum number of designs retained for Taylor series expansion.
4	JNOM:	Number of iterations after which the best design is picked as nominal. Default = 2 * NXAPRX + (NXAPRX + NXAPRX**2).
5	INXLOC:	X-variable global location identifier. If INXLOC = 0, the Taylor series expansion is on the design variables listed in BLOCK G.
6	INFLOC:	Function global location identifier. If INFLOC = 0, the objective and constraint functions identified in BLOCKS E AND I are the functions on which the Taylor series expansion is performed.
7	MAXTRM:	Terms retained in Taylor series expansion. 1 - Linear only. 2 - Linear plus diagonal elements of Hessian Matrix. 3 - Full 2nd order expansion. DEFAULT = 3.

REMARKS

- 1) If ISCRX and/or ISCRXF file number is other than 5, the data read from that file is assumed to be binary data.
- 2) If NXS = NXFS = 0, NXA is defaulted to NXA = 1, even if it is read as zero. Also, a second vector of design variables is automatically defined by COPEs to yield two independent designs to start the optimization.

DATA BLOCK K OMIT IF NXAPRX = 0 IN BLOCK B

DESCRIPTION: Bounds and multipliers for approximate optimization.

FORMAT AND EXAMPLE

		1				2		3		4		5		6		7		8		FORMAT
		DX1		DX2		DX3		DX4		DX5			8F10
.5			2.																	
XFACT1		XFACT2																		2F10
0.		0.																		

NOTE: TWO OR MORE CARDS ARE READ HERE.

FIELD

CONTENTS

1-8 DXI : Allowable change (in magnitude) of the *I*th design variable during each approximate optimization.

1 XFACT1 : Multiplier on DXI when the diagonal elements of the H matrix are available. Default = 1.5.

2 XFACT2 : Multiplier on DXI when all elements of the H matrix are available.

DATA BLOCK L OMIT IF NXAPRX = 0 IN BLOCK B OR INXLOC = 0 IN BLOCK J

DESCRIPTION: Global locations of approximating variables.

FORMAT AND EXAMPLE:

FORMAT							
1	2	3	4	5	6	7	8
LOCK1	LOCK2	LOCK3	LOCK4	8I10
1							

NOTE: MORE THAN ONE CARD MAY BE READ HERE.

FIELD CONTENTS
1-8 LOCX1: Global location of Ith approximating variable.

REMARKS

- 1) If INXLOC = 0 in BLOCK J, this data is not read. In this case, the data is defaulted to be the global locations of the design variables (IDSGN values in BLOCK G).

DATA BLOCK M OMIT IF NXAPRX = 0 IN BLOCK B OR INFLOC = 0 IN BLOCK J

DESCRIPTION: Global locations of functions to be approximated.

FORMAT AND EXAMPLE

	1	2	3	4	5	6	7	8	FORMAT
LOCF1	LOCF2	LOCF3	LOCF4	
3	5	6	4						8I10

NOTE: MORE THAN ONE CARD MAY BE READ HERE.

FIELD
1-8 LOCFI: Global location of Ith function to be approximated.

CONTENTS

REMARKS

- 1) If INFLOC = 0 in BLOCK J, this data is not read. In this case, the data is defaulted to be the global locations of the objective function (IOBJ in BLOCK E) followed by the global locations of the constrained parameters (ICON-JCON in BLOCK I).

DATA BLOCK N OMIT IF NXAPRX = 0 in BLOCK B OR NXS = 0 IN BLOCK J

DESCRIPTION: X-Vectors for approximate optimization.

FORMAT AND EXAMPLE

1	2	3	4	5	6	7	8	FORMAT
XI1	XI2	XI3	XI4	8F10
4.	15.							

NOTE: NX SETS OF DATA ARE READ HERE.

NOTE: MORE THAN ONE CARD MAY BE READ FOR EACH SET OF DATA.

FIELD

CONTENTS

1-8 XIJ: Jth value of Ith X-vector, J = 1, NXAPRX.

DATA BLOCK 0 OMIT IF NXAPRX = 0 IN BLOCK B OR NXFS = 0 IN BLOCK J

DESCRIPTION: X-F pairs of information for approximate optimization.

FORMAT AND EXAMPLE

1	2	3	4	5	6	7	8	FORMAT
X1	X2	X3	X4	...	1	8F10
2.	18.							
Y1	Y2	Y3	Y4	Y5	8F10
7200.	416.667	.914495	18518.519					

NOTE: NXFS SETS OF DATA ARE READ HERE.

NOTE: MORE THAN ONE CARD MAY BE REQUIRED FOR XI OR YI.

NOTE: NXAPRX VALUES OF X AND NF VALUES OF Y ARE READ FOR EACH SET OF DATA.

FIELD CONTENTS

1- 8 XI: I th value of X, I = 1,NXAPRX.

1- 8 YI: I th value of Y, I = 1,NF.

DATA BLOCK P OMIT IF NSV = 0 IN BLOCK B

DESCRIPTION: Sensitivity objectives.

FORMAT AND EXAMPLE

	1	2	3	4	5	6	7	8	FORMAT
NSOBJ		IPSENS							2I10
5		0							
NSN1	NSN2	NSN3	NSN4	NSN5	8I10
3	4	5	6	7					

NOTE: TWO OR MORE CARDS ARE READ HERE.

- | <u>FIELD</u> | <u>CONTENTS</u> |
|--------------|--|
| 1 | NSOBJ: Number of separate objective functions to be calculated as functions of the sensitivity variables. |
| 2 | IPSENS: Print control. If IPSENS.GT.0, detailed print will be called at each step in the sensitivity analysis. DEFAULT = No print. |
| 1-8 | NSNI: Global variable number associated with the i-th sensitivity function. |

REMARKS

- 1) More than eight sensitivity objectives are allowed. Add data cards as required to contain data.

DATA BLOCK Q OMIT IF NSV = 0 IN BLOCK B

DESCRIPTION: Sensitivity variables.

FORMAT AND EXAMPLE

		1	2	3	4	5	6	7	8	FORMAT
ISENS	NSENS									
9	4									
SNS1	SNS2	SNS3	SNS4	8F10	
200.	100.	150.	250.							

NOTE: READ ONE SET OF DATA FOR EACH OF THE NSV SENSITIVITY VARIABLES.

NOTE: TWO OR MORE CARDS ARE READ FOR EACH SET OF DATA.

FIELD CONTENTS

- 1 ISENS: Global variable number associated with the sensitivity variable.
- 2 NSENS: Number of values of this sensitivity variable to be read on the next card.
- 1-8 SENSI: Values of the sensitivity variable. I = 1, NSENS. I = 1 corresponds to the nominal value.

REMARKS

- 1) More than eight values of the sensitivity variable are allowed. Add data cards as required to contain the data.

DATA BLOCK R OMIT IF N2VAR = 0 IN BLOCK B

DESCRIPTION: Two variable function space control parameters.

FORMAT AND EXAMPLE

	1	2	3	4	5		FORMAT
N2VX	M2VX	N2VY	M2VY	IP2VAR			
1	4		2	5	9		5I10

FIELD

- 1 N2VX: Global location of the X-variable in the two variable function space.
- 2 M2VX: Number of values of X to be considered.
- 3 N2VY: Global location of the Y-variable in the two variable function space.
- 4 M2VY: Number of values of Y to be considered.
- 5 IP2VAR: Print control. If IP2VAR.GT.0, detailed print will be called at each step (each X-Y combination). DEFAULT = No print.

DATA BLOCK S OMIT IF N2VAR = 0 IN BLOCK B

DESCRIPTION: Functions to be evaluated in the two variable function space study.

FORMAT AND EXAMPLE

1	2	3	4	5	6	7	8	FORMAT
NZ1	NZ2	NZ3	NZ4	NZ5	8I10
3	4	5	6	7				

FIELD

1-8 NZI: Global location corresponding to the Ith function of X and Y to be calculated. N2VAR values are read here.

CONTENTS

REMARKS

- 1) More than eight functions are allowed. Add data cards as required to contain the data.

DATA BLOCK T OMIT IF N2VAR = 0 IN BLOCK B

DESCRIPTION: Values of the X-variable in a two variable function space study.

FORMAT AND EXAMPLE

	1	2	3	4	5	6	7	8	FORMAT
X1		X2	X3	X4	8F10
0.5	1.0	1.5	2.0						

FIELD

1-8 XI: Values of the X-variable in the two variable function space. M2VX
values are read here.

REMARKS

- 1) More than eight values are allowed. Add data cards as required to contain the data.

DATA BLOCK U OMIT IF N2VAR = 0 IN BLOCK B

DESCRIPTION: Values of the Y-variable in a two variable function space study.

FORMAT AND EXAMPLE

1	2	3	4	5	6	7	8	FORMAT
Y1	Y2	Y3	Y4	Y5	8F10
4.0	8.0	12.0	16.0	20.0				

FIELD

1-8 YI: Values of the Y-variable in the two variable function space. M2VY
values are read here.

CONTENTS

REMARKS

- 1) More than eight values are allowed. Add data cards as required to contain the data.

DATA BLOCK V

DESCRIPTION: COPIES data 'END' card.

FORMAT AND EXAMPLE

FORMAT	
	3A1
END	
END	

FIELD

CONTENTS

- 1 The word 'END' in columns 1-3.

REMARKS

- 1) This card MUST appear at the end of the COPIES data.
- 2) This ends the COPIES input data.
- 3) Data for the user-supplied routine, ANALIZ, follows this.

VII. SAMPLE COMPUTER SOLUTIONS

Sample solutions are presented here for the various COPES program options defined by the parameter NCALC in DATA BLOCK B. The ANALIZ routine given in the design example section was used to produce the results given here. Note that SUBROUTINE ANALYZ does not read data, so only COPES data is required here. In the usual case where data is read as input to the analysis routine, this data would follow directly after the COPES 'END' card.

The output from a COPES program execution includes a title page followed by a copy of the input data. Then the required program executions are performed and final output information is printed. Figures 2-7 contain output for all options of COPES as follows:

<u>NCALC</u>	<u>FIGURE</u>	<u>PROBLEM SOLVED</u>
1	2	Analysis only
2	3	Optimization by CONMIN
3	4	Sensitivity study
4	5	Two-variable function space study
5	6	Optimum sensitivity
6	7	Optimization using approximation techniques

Note that data for the COPES program is read depending on the value of the parameters NDV, NSV, N2VAR and NXAPRX in DATA BLOCK B. The actual program execution is determined by the value of NCALC. Therefore, data may be read for all program options even though only one option of the program is to be executed. Figure 8 is a copy of the combined data for all the previous examples. This data may be used for any program option simply by changing the value of NCALC. Figure 9 is a copy of this same data using the simplified data input mode and Figure 10 is the same data without the comment cards.

CCCCCCC CCCCCGG PPPPP
CCCCC GGGGG PPPP
CCCCC GGGGG PPPP
CCCCC GGGGG PPPP
CCCCC GGGGG PPPP

EEEEEEE SSSSSSS
EEEEE SSSSSSS
EEEEE SSSSSSS
EEEEE SSSSSSS

CONTROL PROGRAM
FOR
ENGINEERING SYNTHESIS

TITLE
CANTILEVERED BEAM ANALYSIS AND DESIGN

CARD IMAGE
1) CANTILEVERED BEAM ANALYSIS AND DESIGN
2) FNC

FIG. 2 - ANALYSIS ONLY

CANTILEVERED BEAM ANALYSIS AND DESIGN

CANTILEVERED BEAM ANALYSIS AND DESIGN
 CALCULATICN CONTROL PARAMETERS:
 NUMBER OF GLOBAL DESIGN VARIABLES, NCALC = 1000
 NUMBER OF GENETIVY VARIABLES, NCV = 1000
 NUMBER OF FUNCTIONS IN TWO-SPACE, N2VAR = 1000000
 NUMBER OF APPROXIMATING VARS, NXAPRX = 1000000
 INPUT INFORMATION PRINT CODE, IPNPRT = 1000
 DEBUG PRINT CODE, IPDBG = 0

CALCULATION CONTROL, NCALC
 1 SINGLE ANALYSIS
 2 OPTIMIZATION
 3 SENSITIVITY
 4 SEC-VARIABLE FUNCTION SPACE
 5 CFTIMUM SENSITIVITY
 6 APPROXIMATE OPTIMIZATION

* * ESTIMATED DATA STORAGE REQUIREMENTS

INPUT EXECUTION	REAL AVAILABLE	INTEGER	AVAILABLE
₉	_{5CCC}	₁	_{10CC}

CANTILEVERED BEAM

AL	=	200.000	05
P	=	0.10000E	05
E	=	0.3CCCCCE	06
B	=	2.500	
F	=	10.000	

FIG. 2 - CONT.

FIG. 2 - CONCLD.

ICALC CALLS
1
2
3

PROGMAP CALLS TO ANALIZ

CANTILEVERED BEAM
AL = 200.000
P = 0.10000E 05
E = 0.3000E 06
B = 2.500
H = 10.000
VCL = 5000.000
BSTRESS = C.48000E 05
SHASTR = C.60000E 03
DEF1A = C.42667E 01
H/E =

CCCCCCC CCCCCCC PPPPPP
C C P EEEEEEE
C C P EEEE
C C P EEEE
CCCCCCC CCCCCC P SSSSSS

CONTROL PROGRAM
FOR
ENGINEERING SYNTHESIS

TITLE
CANTILEVERED BEAM ANALYSIS AND DESIGN

CARD IMAGES OF CONTROL DATA
CARD IMAGE

1) CANTILEVERED BEAM ANALYSIS AND DESIGN
2) \$ CITA BLOCK E NDY
3) \$ ACALC
4) \$ CITA BLOCK 2
5) \$ CITA BLOCK C - CEFAULT ALL BUT PRINT CONTROL
6) \$ IPRINT
7) \$

FIG. 3 - OPTIMIZATION

\$ DATA BLOCK C - ALL DEFAULTS

```
0.  
C.  
$ DATA BLOCK E 108J 3 SGKOPT  
$ DATA BLOCK F 000 -1.  
$ DIVISOR 4 4  
$ WIDTH 8 5.  
$ HEIGHT H 20.  
$ DATA BLOCK G 1CSGN APUT  
$ NDIGN 1 1.  
$ WIDTH E 1.  
$ HEIGHT I H 2.  
$ DATA BLOCK H 1.  
$ NCOKS 4  
$ DATA BLOCK I 1CON SCAL1 BUICON  
$ ELICN SCAL1 ON ESTRES SCAL2  
$ CONSTRAINT 4 0 0 0.  
-1.0 +20 0 SHRSTR 20000. 0.  
$ CONSTRAINT 5 0 0 0.  
-1.0 +22 0 0 0.  
$ CONSTRAINT 6 0 0 0.  
-1.0 +20 0 0 0.  
$ CONSTRAINT 7 0 0 0.  
-1.0 +20 0 0 0.  
$ DATA BLOCK S J-L ARE NOT REQUIRED.  
$ DATA BLOCK V  
$ REQUIRED END CARD  
END
```

CART FLIEVERED BEAM ANALYSIS AND DESIGN

CONTROL PARAMETERS:

CALCULATE GLOBAL DESIGN VARIABLES, NCALC = 2
 NUMBER OF SENSITIVITY VARIABLES, NOV = 2000000
 NUMBER OF FUNCTIONS IN TWO-SPACE, NSV = N2VAR =
 NUMBER OF APPROXIMATING VARS, NXAPRX =
 INPUT INFORMATION PRINT CODE, IPNPUT =
 DEBUG PRINT CODE, IPCBG =

CALCULATION CONTROL, NCALC
 VALUE MEANING
 1 SINGLE ANALYSIS
 2 OPTIMIZATION
 3 SENSITIVITY
 4 TAC-VARIABLE FUNCTION SPACE
 5 OPTIMUM SENSITIVITY
 6 APPROXIMATE OPTIMIZATION

* * OPTIMIZATION INFORMATION

GLCB AL VARIABLE NUMBER OF OBJECTIVE FUNCTION MINIMIZATION = -0.1000E 01

CONSTRAINT PARAMETERS (IF ZERO, COMM IN DEFAULT WILL OVER-RIDE)

IPRINT	ITMAX	ICDIR	NSCL	ITRN	LINOBJ	NACMX1	NFDG
1	0	0	0	0	CT	0	0
FDCH	0.0	0.0	0.0	0.0	CTMIN	0.0	0.0
CTL	0.0	0.0	0.0	0.0	THETA	0.0	PHI
DEFUN	0.0	0.0	0.0	0.0	ALPHAX	0.0	0.0

FIG. 3 - CONT.

DESIGN VARIABLE INFORMATION		MODULUS INPUT	
NON-ZERO ID.	INITIAL VALUE	UPPER BOUND	INITIAL VALUE
1	6.5E+00	6.0	6.0
2	0.10000E+01	0.20000E+02	0.0

DESIGN VARIABLES		MULTIPLYING	
ID	GLOBAL NO.	GLOBAL NO.	FACTOR
1	1	1	0.10000E+01
2	2	2	0.10000E+01

CONSTRAINT INFORMATION

THERE ARE 4 CONSTRAINTS		GLOBAL LINEAR		NORMALIZATION	
ID	VAR.	LOWER BOUND	UPPER BOUND	FACTOR	FACTOR
1	1	0	-0.11000E+16	0.11000E+16	0.20000E+05
2	5	0	-0.11000E+16	0.11000E+16	0.10000E+05
3	6	0	-0.11000E+16	0.11000E+16	0.10000E+01
4	7	0	-0.11000E+16	0.11000E+16	0.10000E+02

TOTAL NUMBER OF CONSTRAINED PARAMETERS = 4

* * ESTIMATED DATA STORAGE REQUIREMENTS

INPUT EXECUTION AVAILABLE		INPUT EXECUTION AVAILABLE	
REAL	129	5CCC	41

CANTILEVER BEAM

	AL	=	200.000
	F	=	6.10000E+05
	E	=	2.0000E+06
	F	=	2.500
	F	=	10.000

CANTILEVEREC BEAM

AL	=	200.000
P	=	C.1CCCCC E C8
E	=	0.30CCCC E C8
B	=	2.500
F	=	1C.CCC
VOL	=	5CCC.CCC
ESTRESS	=	C.48CCCC E C5
SHRSTR	=	C.600000 E C3
DELTA	=	0.42667E C1
H/B	=	4.000

```
*****
*          C O M P I L A
*          FCRTRAN PROGRAM FOR
*          CONSTRAINED FUNCTION MINIMIZATION
*****
INITIAL FUNCTION INFORMATION
DRJ = 0.500000E 04
DECISION VARIABLE'S (X-VECTORS)
1) 0.25000E C1 0.15000E 02
CONSTRAINT VALUES (E-VECTCR)
1) C.14CCCC E 01 -C.94CCCC E 00 0.32667E 01 -0.60000E 00
```

FIG. 3 - CONT.

FINAL OPTIMIZATION INFORMATION

OBJ = C.660538E 04
DECISION VARIABLES (X-VECTOR)
C1) 0.18179E 02
CONSTRAINT VALUES (G-VECTOR)
C1) -0.12367E-02 -0.95461E 00 -0.23254E-01 -0.31548E-04
THERE ARE 2 ACTIVE CONSTRAINTS
CONSTRAINT NUMBERS ARE
1 4
THERE ARE 0 VIOLATED CONSTRAINTS
THERE ARE 0 ACTIVE SIDE CONSTRAINTS
TERMINATION CRITERION
 $\frac{ABS((OBJ(i)-OBJ(i-1))/OBJ(i-1))}{ABS(CBJ(i)-CBJ(i-1))}$ LESS THAN DELFUN FOR 3 ITERATIONS
NUMBER OF ITERATIONS = 9
OBJECTIVE FUNCTION WAS EVALUATED 35 TIMES
CONSTRAINT FUNCTIONS WERE EVALUATED 35 TIMES

OPTIMIZATION RESULTS

OBJECTIVE FUNCTION 3 FUNCTION VALUE 0.66094E 04
 GLOBAL LOCATION 3

DESIGN VARIABLES

ID	C. V.	GLOBAL VAR. NO.	LOWER BOUND	VALUE	UPPER BOUND
1	R0.	1	0.50000E 00	0.18179E C1	0.50000E 01
2	R1.	2	0.10000E C1	0.18179E C2	0.20000E C2

DESIGN CONSTRAINTS

ID	GLOBAL VAR. NO.	LOWER BOUND	VALUE	UPPER BOUND
1	4	-0.10000E 16	0.19975E 05	0.20000E 05
2	5	-0.10000E 16	0.45390E 03	0.10000E 05
3	6	-0.10000E 16	0.97675E 00	0.10000E 01
4	7	-0.10000E 16	0.99997E 01	0.10000E 02

CANTILEVERED BEAM

AL_P	=	2.00000E 05
E	=	0.30000E 08
B	=	1.0E18
H	=	18.179
VCL	=	6609.375
BSTRESS	=	0.19975E 05
SHRSTR	=	0.45390E 03
DELTA	=	0.97675E 00
H/B	=	10.000

PROGRAM CALLS TO ANALIZ

ICPLC CALLS
1
2
36

FIG. 3 - CONCLUDED

CCCCCCC CCCCCCO PPPPPPP EEEEEE
C COOCC P E
C COOC P EEE
C COOC P ESSS
E COOOOO P EEEEEE
CCCCCCC COOOOOO SSSSSSS

C O N T R O L P R O G R A M
F C R
E A C H I N E E R I N G S Y N T H E S I S

T I T L E
CANTILEVERED BEAM ANALYSIS AND DESIGN

FIG. 4 - SENSITIVITY STUDY

CARD IMAGES OF CONTROL DATA

CARD IMAGE

CARD	IMAGE
1)	CANTILEVERED BEAM ANALYSIS AND DESIGN
2)	\$ DATA BLOCK B NDV NSV
3)	\$ NCALC 0 3
4)	\$ DATA BLOCKS C-C ARE NOT REQUIRED
5)	\$ DATA BLOCK P 0
6)	\$ DATA BLOCK R-U ARE NOT REQUIRED
7)	\$ DATA BLOCK S NSOEJ
8)	\$ NSN1 5
9)	\$ NSN2 4
10)	\$ NSN3 5
11)	\$ NSN4 6
12)	\$ DATA BLOCK Q NSENS
13)	\$ ISENS SNS3 SN S4
14)	\$ BEAM LENGTH 9
15)	\$ BEAM LENGTH 100. 4
16)	\$ BEAM WIDTH 1 1.5 3
17)	\$ BEAM WIDTH 2 1.5 3
18)	\$ BEAM HEIGHT 1 2.5
19)	\$ BEAM HEIGHT 2 2
20)	\$ BEAM HEIGHT 2 2.5
21)	\$ BEAM HEIGHT 2 2.5
22)	\$ BEAM HEIGHT 2 2.5
23)	\$ BEAM HEIGHT 2 2.5
24)	\$ BEAM HEIGHT 2 2.5
25)	\$ BEAM HEIGHT 2 2.5
26)	\$ REQUIRED END CARD
	END

FIG. 4 - CONT.

TITLE: CANTILEVERED BEAM ANALYSIS AND DESIGN

CONTROL PARAMETERS:
 CALCULATION OF GLOBALE DESIGN VARIABLES, NCALC = 3
 NUMBER OF SENSITIVITY VARIABLES, NSV = 3
 NUMBER OF FUNCTIONS IN TWO-SPACE, N2VAR = 300
 NUMBER OF APPROXIMATING VAR., NXAPRX = 3000
 INPUT INFORMATION PRINT CODE, IPNPLT = 0
 DEBUG PRINT CODE, IPDBG = 0

CALCULATION CONTROL, NCALC
 VALUE PEGGING ANALYSIS
 SENSITIVITY OPTIMIZATION
 THE VARIABLE FUNCTION SPACE
 OPTIMUM SENSITIVITY APPROXIMATE OPTIMIZATION

* * SENSITIVITY INFORMATION

PRINT CONTROL IPSENS = 5
 NUMBER OF SENSITIVITY OBJECTIVES = 5

GLOBAL NUMBERS ASSOCIATED WITH SENSITIVITY OBJECTIVES

NUMBER	GLOBAL VARIABLE	MINIMAL VALUE	OFF-MINIMAL VALUES	03	0.2500E 03
1		C.2000E 03	0.1000E 03	C.1500E 03	0.2500E 01
2		C.2000E 01	0.1500E 01	C.2500E 01	0.2000E 02
3		0.5000E 01	0.2000E 02		

* * ESTIMATED DATA STORAGE REQUIREMENTS
 INPUT EXECUTION 16 23 5000 AVAILABLE 12 12 1000 INTEGER EXECUTION AVAILABLE 1000

FIG. 4 - CONT.

CANTILEVERED BEAM

AL	=	200.000
P	=	C.10000E 05
E	=	C.30000E C8
B	=	2.500
F	=	10.000

STANDARD SENSITIVITY ANALYSIS RESULTS (INCALC=3)

CANTILEVERED BEAM ANALYSIS AND DESIGN

NUMBER OF SENSITIVITY VARIABLES, NSV = 3
 NUMBER OF SENSITIVITY OBJECTIVES, NSOBJ = 5

GLOBAL NUMBERS ASSOCIATED WITH SENSITIVITY VARIABLES
₁⁹ ₂

GLOBAL NUMBERS ASSOCIATED WITH SENSITIVITY OBJECTIVES
₃⁷ ₄⁶

NOMINAL DESIGN INFORMATION

VALUES OF SENSITIVITY VARIABLES
₀⁰.20000E 01 ₁⁰.50000E 01
 VALUES OF SENSITIVITY OBJECTIVE FUNCTIONS
₀⁰.26667E 04 ₁⁰.15000E 04 ₂⁰.42667E 02 ₃⁰.25000E 01

FIG. 4 - CONT.

SENSITIVITY ANALYSIS RESULTS

GLOBAL VARIABLE S	X	F(X)	
C.1000E 03	0.1500E 04 0.2500E 01	0.1200E 06 0.1500E 04	0.1500E 04 0.5333E 01
C.1500E 03	0.1500E 04 0.2500E 01	0.1800E 06 0.3000E 04	0.1500E 04 0.1800E 02
C.2500E 03	0.2500E 04 0.2500E 01	0.3000E 06 0.1500E 04	0.3000E 04 0.8333E 02
GLOBAL VARIABLE 1	X	F(X)	
C.1500E C1	0.1500E 04 0.3333E 01	0.3200E 06 0.2000E 04	0.2000E 04 0.5689E 02
C.2500E 01	0.2500E 04 0.2600E 01	0.1920E 06 0.1200E 04	0.1200E 04 0.3413E 02
GLOBAL VARIABLE 2	X	F(X)	
C.2000E 02	0.8000E 04 0.1000E 02	0.1500E 05 0.3750E 03	0.1500E 05 0.6667E 00

PROGRAM CALLS TC ANALIZ
 ICALC CALLS
 1 1
 2 7
 3 0

FIG. 4 - CONCLUDED

CCCCCCC	0000000	PPPPP P P	EEEEEE E E E E E	SSSSSS S S S S S S
CCCCC	0000000	PPPPP P P	EEEEEE E E E E E	SSSSSS S S S S S S
CCCCC	0000000	PPPPP P P	EEEEEE E E E E E	SSSSSS S S S S S S

CONTROL PROGRAM
FOR
ENGINEERING SYNTHESIS

TITLE
CANTILEVERED BEAM ANALYSIS AND DESIGN

FIG. 5 - TWO-VARIABLE FUNCTION SPACE STUDY

CARD IMAGES OF CONTROL DATA

CARD	IMAGE
1	CANTILEVERED BEAM ANALYSIS AND DESIGN
2	S DATA BLOCK B
3	NCALC ADV
4	DATA BLOCK C-C ARE NOT REQUIRED
5	DATA BLOCK F O
6	DATA BLOCK G
7	N2VX M2VX
8	N2VY M2VY
9	DATA BLOCK S
10	N21 N22
11	N23 N24
12	N25 N26
13	DATA BLOCK T
14	VALUES OF WIDTH, B
15	X1 X2
16	X3 X4
17	DATA BLOCK U
18	VALUES OF HEIGHT, H
19	Y1 Y2
20	Y3 Y4
21	DATA BLOCK V
22	VALUES OF WEIGHT, H
23	Y5 Y6
24	DATA BLOCK W
25	REQUERED END CARD
END	

CNTFILEVEREC CEAH ANALYSIS AND DESIGN

```

CNCAT FILE PARAMETERS:
CALCULATE CCNTRL DESIGN VARIABLES, NCALC = 4
NUMBER OF GLOBAL DESIGN VARIABLES, NNDV = 0
NUMBER OF FUNCTIONS IN TWO-SPACE, NSV = 0
NUMBER OF APPROXIMATING VAR, N2VAR = 5
INPUT INFORMATION PRINT CODE, NXAPRX = 0
INPUT INFORMATION PRINT CODE, IPINPUT = 0
INPUT INFORMATION PRINT CODE, IPDBG = 0

CALCULATIONAL CONTROL, NCALC
VALUE MEANING
1 SINGLE ANALYSIS
2 OPTIMIZATION
3 TWO-VARIABLE FUNCTION SPACE
4 OPTIMUM SENSITIVITY
5 APPROXIMATE OPTIMIZATION
6

* * TWO-VARIABLE FUNCTION SPACE MAPPING INFORMATION
PRINT CONTROL, IP2VAR = 0

GLOBAL VARIABLE NUMBERS ASSOCIATED WITH F(X,Y), N2VZ
3 4 5 6

GLOBAL VARIABLE NUMBER CORRESPONDING TO X, N2VX = 1
VALUES OF X-VARIABLE
0.5000E 01 0.1000E 01 C.1500E 01 0.2000E 01

GLOBAL VARIABLE NUMBER CORRESPONDING TO Y, N2VY = 2
VALUES OF Y-VARIABLE
C.4000E 01 0.8000E 01 0.1200E 02 0.1600E 02 0.2000E 02

* * ESTIMATED DATA STORAGE REQUIREMENTS
INPUT REAL EXECUTION AVAILABLE INPUT INTEGER EXECUTION AVAILABLE
18 23 5000 6 1000 6 1000

```

FIG. 5 - CONT.

CANTILEVERED BEAM

A _L	=	2000000
F	=	0.10000E 05
E	=	0.30000E 08
B	=	2.500
H	=	1C.000

TWO-VARIABLE FUNCTION SPACE RESULTS

TITLE CANTILEVERED BEAM ANALYSIS AND DESIGN

GLOBAL NUMBER ASSOCIATED WITH X-VARIABLE, N2VX = 1
 GLOBAL NUMBER ASSOCIATED WITH Y-VARIABLE, N2VY = 2

GLOBAL NUMBERS ASSOCIATED WITH F(X,Y)
 4 5 6 7

X	Y	F(X,Y)
0.5000E 30	0.4000E 01	C.4000E 03 0.8000E 01
C.8000E 31	0.8000E 02 C.1600E 02	0.3750E 06 C.3750E 06
0.1200E 32	C.1200E 04 0.2400E 02	0.1667E 06 C.2500E 04
C.1600E 32	0.1600E 04 0.3200E 02	0.9375E 05 C.1875E 04
0.2000E 32	0.2000E 04 0.4000E 02	0.6000E 05 C.1500E 04
		0.2667E 01

FIG. 5 - CONT.

X	Y	F(X,Y)
C.1000E 01	0.2000E 02	C.4000E 04 0.2000E 02
0.1600E 02	0.3200E 02	0.4698E 05 0.1600E 02
0.1200E 02	0.2400E 04 0.1200E 02	0.8333E 05 0.1250E 04
C.8000E 01	0.1600E 04 C.8000E 01	0.1875E 06 0.1875E 04
0.4000E 01	0.8000E 03 0.4000E 01	C.7500E 06 0.3750E 04
X	Y	F(X,Y)
C.1500E 01	0.4000E 01	C.1200E 04 C.2667E 01
0.8000E 01	0.2400E 04 0.5333E 01	0.5000E 06 0.1250E 06
C.1200E 02	0.3600E 04 0.8000E 01	0.5556E 05 C.8333E 03
0.1600E 02	0.4800E 04 C.1067E 02	0.3125E 05 C.6250E 03
C.2000E 02	0.6000E 04 0.1333E 02	C.2000E 05 C.5000E 03

FIG. 5 - CONT.

X	Y	F(X, Y)
0.2000E C1	0.2000E C2	6.80C0E 04
0.1600E 02	6.10C0E 02	0.1500E 05
0.1600E 02	0.64C0E 01	0.2344E 05
0.8000E 01	0.8000E 01	0.4688E 03
0.1200E C2	0.48C0E 01	0.1302E 01
0.1200E C2	0.6000E 01	0.4167E 05
0.8000E 01	0.32C0E 01	0.6250E 03
0.8000E 01	0.4000E 01	0.9375E 05
C.4CCCE C1	0.16C0E 01	0.9375E 03
C.4CCCE C1	0.2000E 01	0.1C42E 02
		0.1875E 04
		0.8333E 02

PROGRAM CALLS TO ANALYZE
 ICALC CALLS
 1 2 3
 2 3 4

FIG. 6 - OPTIMUM SENSITIVITY

CCCCCCC CCCCCCG PFFFFPPP EEEEEEE SSSSSSS
C C C Q Q P P P P P P P P P P P P P P P P P
C C C Q
C
C C

C O N T R O L P R O G R A M
F C R

E N G I N E E R I N G S Y N T H E S I S

T I T L E

CANTILEVERED BEAM ANALYSIS AND DESIGN

CARD IMAGES OF CONTROL DATA

CARD	IMAGE
1)	CANTILEVERED BEAM ANALYSIS AND DESIGN
2)	DATA BLOCK B NOV NSV
3)	NCALC 5
4)	DATA BLOCK C - DEFAULT ALL BUT PRINT 3
5)	IPRINT 1
6)	DATA BLOCK E - ALL DEFAULTS
7)	0.
8)	0.
9)	
10)	S DATA BLOCK E 10B J
11)	NDYTOT 3 SGACPT -1.
12)	S DATA BLOCK F VUB
13)	YLB 16 S WIDTH, B 5.
14)	S HEIGHT, H 2G.
15)	S DATA BLOCK G 17SGN AMULT
16)	ENDSGN 20 S HEIGHT, I 1.
17)	WICHT, B 21 S HEIGHT, H 2.
18)	22 S HEIGHT, 1 1.
19)	23 S HEIGHT, 2 1.
20)	24 S HEIGHT, H 2.
21)	25

```

26) $ DATA BLOCK NCON4
27)   1 DATA BLOCK I JCON BU LCON SCAL2
28)   $ IICON SCAL1 ESTRES 0.0.0.0.
29)   $ BL CONSTRAINT CN 0.0.0.0.
30)   $ -1.0 C 420 0.0.0.0.
31)   $ CONSTRAINT CN STRSTR 20000.0.0.
32)   $ -1.0 C 420 0.0.0.0.
33)   $ CONSTRAINT CN 0.0.0.0.
34)   $ -1.0 C 420 0.0.0.0.
35)   $ CONSTRAINT CN 0.0.0.0.
36)   $ -1.0 C 420 0.0.0.0.
37)   $ CONSTRAINT CN 0.0.0.0.
38)   $ -1.0 C 420 0.0.0.0.
39)   $ CONSTRAINT CN 0.0.0.0.
40)   $ -1.0 C 420 0.0.0.0.
41)   $ CONSTRAINT CN 0.0.0.0.
42)   $ -1.0 C 420 0.0.0.0.
43)   $ DATA BLOCKS 0.0.0.0.
44)   $ DATA BLOCK p j-c ARE NOT REQUIRED.
45)   $ DATA BLOCK p NSCBY
46)   $ NSN1 NSN2 NSN3 NSN4 NSN5 NSN6 NSN7
47)   $ NSN1 NSN2 NSN3 NSN4 NSN5 NSN6 NSN7
48)   $ DATA BLOCK C NSENS NSNS1 NSNS2 NSNS3 NSNS4
49)   $ ISENS NSNS1 NSNS2 NSNS3 NSNS4
50)   $ BEAM LENGTH 9 4 150. 250.
51)   $ BEAM WIDTH 100. 4 150. 250.
52)   $ BEAM HEIGHT 1.5 3 2.5 2
53)   $ BEAM HEIGHT 2 2
54)   $ CINIT DATA BLOCKS R-U BECAUSE N2VAR = 0
55)   $ DATA BLOCK Y
56)   $ REQUIRE ENE CARD
57) END
58)
59)
60)
61)
62)
63)
64)
65)

```

TITLE F: EVEREED BEAM ANALYSIS AND DESIGN

CCNT POLATIION CONTROL PARAMETERS:
CACULL CF CREAL DESIGN VARIABLES, NCALC = 52
NUMBER OF SENSITIVITY VARIABLES, NDV = 3
NUMBER OF FUNCTIONS IN TWO-SPACE, NSV = 3
NUMBER OF APPROXIMATING VAR, N2VAR = 00000
INPLT INFORMATION PRINT CODE, IPNPLT = 1
DEBLG PRINT CODE, IPDEG = 0

CACULAT ICA CCNTROL, NCALC
VALUE MEANING
1 SINGLE ANALYSIS
2 SENSITIZATION
3 SENSITIVITY FUNCTION SPACE
4 TAC-VARIABLE SENSITIVITY
5 OPTIMUM SENSITIVITY
6 APPROXIMATE OPTIMIZATION

*** * OPTIMIZATION INFORMATION**

GLOBAL VARIABLE NUMBER OF OBJECTIVE MINIMIZATION = -0.1000E 31
MULTIPLIER (NEGATIVE INDICATES MINIMIZATION) = -0.1000E 31
COND IN PARAMETERS (IF ZERO, CCAMIN DEFAULT WILL OVER-RIDE)

IPRINT	ITAX	ICACIR	NSCAL	ITRM	LINOBJ	NACMX1	NFDG
1	0	0	0	0	0	4	0
FCCH	FCCH			CT			
0.0	0.0			0.0			
CTL	CTL			THETA			
0.0	0.0			0.0			
CFUN	DABFUN			ALPHAX			
0.0	0.0			0.0			

FIG. 6 - CONT.

DESIGN VARIABLE INFORMATION					
NON-ZERO INITIAL VALUE WILL OVER-RIDE MODULE INPUT		INITIAL		MODULE INPUT	
DO.	V.	LLCNER	UPPER	BOUND	SCALE
1	0.5000E 01	0.5000E 01	0.0	0.0	0.0
2	C.1CCCCCE 01	C.20000E 02	0.0	0.0	0.0

DESIGN VARIABLES		
ID	NO.	GLOEAL NO.
1	1	MULTIPLYING FACTOR 01
2	2	0.1000E 01

CONSTRAINT INFORMATION

THERE ARE 4 CONSTRAINT SETS

GLOBAL		LINEAR		NORMALIZATION	
ID	VAR:	10	10	FACTOR	FOUND
1	1	0	-C.1100CE 16	0.1100CE 16	0.2000E 05
2	2	0	-C.1100CE 16	0.1100CE 16	0.1000E 05
3	6	0	-0.1100CE 16	0.1100CE 16	0.1000E 01
4	7	C	-C.11000E 16	0.1100CE 16	0.1000E 02

TOTAL NUMBER OF CONSTRAINED PARAMETERS = 4

***** SENSITIVITY INFORMATION

PRINT CONTROL IP SENS = 0
 NUMBER OF SENSITIVITY OBJECTIVES = 7
 GLOBAL NUMBERS ASSOCIATED WITH SENSITIVITY OBJECTIVES

FIG. 6 - CONT.

NUMBER	GLOBAL VARIABLE	ACMINAL VALUE	OFF-NOMINAL VALUES
1		C.20000E 03	0.1000E 03
2		C.20000E 01	0.1500E 01
3		C.500CCCE 01	0.2500E 01
			0.2000E 02

* * ESTIMATED DATA STORAGE REQUIREMENTS

INPUT	REAL EXECUTION 161	AVAILABLE 5000	INPUT 34	INTEGER 58	EXECUTION 58	AVAILABLE 1000
-------	--------------------	----------------	----------	------------	--------------	----------------

CANTILEVERED FEAM

AL	=	200.000
P	=	C.100.000E 05
E	=	C.30000E 08
B	=	2.500
H	=	1C.000

OPTIMUM SENSITIVITY ANALYSIS RESULTS (ACALC=5)

TITLE
CANTILEVERED BEAM ANALYSIS AND DESIGN

NUMBER OF SENSITIVITY VARIABLES: NSV = 3
NUMBER OF SENSITIVITY OBJECTIVES: NSOBJ = 7

GLOBAL NUMBERS ASSOCIATED WITH SENSITIVITY VARIABLES
 $\begin{matrix} 1 & 2 \\ 3 & 4 \end{matrix}$

GLOBAL NUMBERS ASSOCIATED WITH SENSITIVITY OBJECTIVES
 $\begin{matrix} 5 & 6 \\ 7 & 1 \end{matrix}$

INITIAL DESIGN INFORMATION

VALUES OF SENSITIVITY VARIABLES
0.2CCCC0E 03 0.2CCCC0E 01 0.50000E 01

VALUES OF SENSITIVITY OBJECTIVE FUNCTIONS
0.2CCCC0E 04 0.24000E 06 0.15000E 04 0.42667E 02 0.25000E 01
0.2CCCC0E 01 0.50000E 01

SENSITIVITY ANALYSIS RESULTS

GLOBAL VARIABLE 9		F(X)	
X		X	
0.1000E 03	0.2C82E 04	0.1997E 05	0.7205E 03
	0.1CC0E 02	0.1443E 01	0.1443E 02
C.1500E 03	0.4096E 04	0.1554E 05	0.5493E 03
	0.1000E 02	0.1652E 01	0.1652E 02
0.2500E 03	0.1303E 05	0.1439E 05	0.2878E 03
	0.7674E 01	0.2606E 01	0.2000E 02

GLOBAL VARIABLE 1		F(X)	
X		X	
C.1500E 01	0.6000E 04	0.2000E 05	0.5000E 03
	0.1333E 02	0.1500E 01	0.2000E 02
C.2500E C1	0.6137E 04	0.1812E 05	0.3687E 03
	0.6510E 01	0.2500E 01	0.1627E 02

GLOBAL VARIABLE 2		F(X)	
X		X	
0.2000E 02	0.7042E 05	0.1151E 05	0.2878E 03
	0.7674E 01	0.2606E 01	0.2000E 02

PROGRAM CALLS TC ANALIZ
 ICALC CALLS
 1 1
 2 103
 3 C

FIG. 6 - CONCLUDED

CCCCCCC	CCCCCC	PPPPP P P P P P P	EEEEEE E E E E E E	SSSSSS S S S S S S
CCCCCCC	CCCCC	PPPPP P P P P P P	EEEEEE E E E E E E	SSSSSS S S S S S S

C C T R C L P R O G R A M
F O R
E N G I N E E R I N G S Y N T H E S I S

T I T L E
 CANTILEVERED BEAM ANALYSIS AND DESIGN

CARD IMAGES OF CONTROL DATA

CARD **IMAGE**

111	CANTILEVERED BEAM ANALYSIS AND DESIGN
111	\$ DATA BLOCK 8
111	NCALC 6
111	NDV 0
111	NXVAR 0
111	NXAPRX 1
111	DATA BLOCK C - DEFAULT ALL BUT PRINT 0
111	IPRIINT 1
111	DATA BLOCK C - ALL DEFAULTS 1
101	C.
101	0.
101	C.
111	\$ DATA BLOCK E
111	NDV 0
111	IOBY 3
111	SGNDOPT -1.

FIG. 7 - OPTIMIZATION USING APPROXIMATION TECHNIQUES

```

150      $ DATA BLOCK F VJB
151      $ WIDTH, B 5.
152      $ HEIGHT, H 5.
153      $ DATA BLOCK G I DSGN  AMULT
154      $ WIDTH, B 2C.
155      $ HEIGHT, H 2C.
156      $ DATA BLOCK H 1 1.
157      $ HEIGHT, R 1 1.
158      $ DATA BLOCK I 2 1.
159      $ ACCESS 4
160      $ DATA BLOCK J 1 JCCN BU LCN SCAL2
161      $ CCONSTRAINT SCN ESTRES 0 0.
162      $ CCONSTRAINT SCN SFRSTR 200C. 0.
163      $ CCONSTRAINT SCN 0 0.
164      $ CCONSTRAINT SCN DELTA 0 0.
165      $ CCONSTRAINT SCN 0 0.
166      $ CCONSTRAINT SCN 1/B 0 0.
167      $ CCONSTRAINT SCN 0 0.
168      $ DATA BLOCK K NXS POSSIBLE EXCEPT PRINT CONTROL AND CANDIDATE DESIGNS IPAPRX
169      $ USE DEFAULTS WHERE NSFS NXA INCM ISCRX INFLCC MAXTRM
170      $ NF 0 0 0 0 0 0
171      $ KMIN 4 NPMAX JNOM INXLCC
172      $ KMAX 0 0 0 0
173      $ DATA BLOCK L DX2 XFACT2
174      $ D5 0. 2FACT
175      $ XFACT1 0. 2FACT
176      $ DATA BLOCK M ACT REQUIRED INXLOC = 0
177      $ DATA BLOCK N ACT REQUIRED INFLOC = 0
178      $ DATA BLOCK N READ 4 CANDIDATE DESIGNS X1 X2
179      $ 1. 1C.
180      $ 2. 2C.
181      $ 4. 1C.
182      $ 3. 12C.
183      $ DATA BLOCKS CAN'T REQUIRE INXFS = 0
184      $ DATA BLOCKS P-L ARE NOT REQUIRED.
185      $ DATA BLOCK Y REQUIRED END CARD
186      $ END

```

FIG. 7 - CONT.

CANTILEVERED BEAM ANALYSIS AND DESIGN

CNT FOLIATE PARM CONTROL:
 CALCULATE GLOBAL DESIGN VARIABLES, NCALC = 6
 NUMBER OF GENERATIVE VARIABLES, NNV = 200
 NUMBER OF FUNCTIONS IN TWO-SPACE, N2VAR = 100
 NUMBER OF APPROXIMATING VAR, NXAPRX = 100
 INPUT INFORMATION PRINT CODE,
 DEBUG PRINT CODE, IPDEC = 1

CALCULATION CONTROL, NCALC
 VALUE MEANING
 1 SINGLE ANALYSIS
 2 OPTIMIZATION
 3 SENSITIVITY
 4 TWO-VARIABLE FUNCTION SPACE
 5 OPTIMUM SENSITIVITY
 6 APPROXIMATE OPTIMIZATION

* * OPTIMIZATION INFORMATION

GLOBAL VARIABLE NUMBER OF OBJECTIVE MINIMIZATION = -0.1000E 01
 MULTIPLIER (NEGATIVE INDICATES OVER-RIDE)

CONMIN PARAMETERS (IF ZERO, CONMIN DEFAULT WILL OVER-RIDE)

IPRINT	ITMAX	ICNDIR	NSCAL	ITRM	LINOBJ	NFCM X1	NFDG
1	C	0	0	0	0	6	0
FCCR		FCCHM		CT		CTMIN	
0.0		0.C		0.0		0.0	
CTL		CTLMIN		THETA		PHI	
0.0		0.0		0.0		0.0	
DEFFUN		DABFUN		ALPHAX		ABOBJ1	
0.0		0.C		0.0		0.0	

DESIGN VARIABLE INFORMATION
 NC-ZERO INITIAL VALUE IS 1, OVER-RIDE MODULE INPUT
 NO. V. LOWER BOUND UP, ER
 NO. 1 0.5000E 01 0.5000E 01 0.2000E C2 0.0 0.0
 NO. 2 0.1000E 01 0.1000E 01 0.2000E C2 0.0 0.0

FIG. 7 - CONT.

DESIGN VARIABLES		MULTIPLYING	
ID	NO.	GLOBAL	FACTCR
1	1	VAR 1	0.1000E 01
2	2	VAR 2	C.1000E 01

CONSTRAINT INFORMATION

THERE ARE 4 CONSTRAINT SETS

GLOBAL LINEAR		LOWER	NORMALIZATION	UPPER	NORMALIZATION
ID	VAR	BOUND	FACTCR	BOUND	FACTCR
1	1	0	-C.11000E 16	0.11000E 16	0.20000E 05
1	4	0	-0.11000E 16	0.11000E 16	0.10000E 05
2	5	0	-0.11000E 16	0.11000E 16	0.10000E 05
3	6	0	-0.11000E 16	0.11000E 16	0.10000E 01
4	7	0	-0.11000E 16	0.11000E 16	0.10000E 02

TOTAL NUMBER OF CONSTRAINED PARAMETERS = 4

* APPROXIMATE ANALYSIS/OPTIMIZATION INFORMATION

```

NUMBER OF FUNCTIONS APPROXIMATED, NF = 4
NUMBER OF INPUT X-VECTORS, NPS = 4
NUMBER OF INPUT X-F PAIRS, NPFS = 0
X-VECTOR FROM ANALIZ,
ACMINAL DESIGN, INOM = 0
READ UNIT FOR X-VECTORS, ISCRX = 5
READ UNIT FOR X-F PAIRS, ISCRXF = 5
PRINT COUNTFILE, IPAPRX = 1
MINIMUM APPROXIMATING CYCLES, KMIN = 1
MAXIMUM APPROXIMATING CYCLES, KMAX = 12
MAXIMUM DESIGN USED IN FIT, NPMAX = 10
ACMINAL DESIGN PARAMETER, JNOW = 100
X-LOCATION INPUT PARAMETER, INXLOC = 0
F-LOCATION INPUT PARAMETER, INFLOC = 0
TAYLOR SERIES I.D. CODE, MATRM = 3

```

DELTA-X SECUNDS FOR APPROXIMATE OPTIMIZATION
0.5000E 00 0.2000E 01

MULTIPLIER ON CELX,
MULTIPLIER ON CELX,

XFACT1 = 0.1500E 01
XFACT2 = 0.2000E 01

FIG. 7 - CONT.

GLOBAL LOCATIONS OF X-VARIABLES

SIMULATED LOCATIONS OF FLACTIONS

X-VECTORS INPUT FROM UNIT 5

NUMBER 01 1 DESIGN 1
C.1000E 01 0.15GCE C2

NUMBER 01 2 DESIGN 2
C.2000E 01 0.2000E C2

NUMBER 01 3 DESIGN 3
C.4000E 01 0.1000E 02

NUMBER 01 4 DESIGN 4
C.3000E C1 C.12GCE C2

* * ESTIMATED DATA STORAGE REQUIREMENTS

INPUT EXECUTION REAL AVAILABLE INPUT INTEGER EXECUTION AVAILABLE
27 212 500 26 60 1000

CANTILEVERED BEAM

A _L	=	2CC.000
P	=	C.1000E C5
E	=	C.3000E C8
B	=	2.500
F	=	1.C.00

APPROXIMATE OPTIMIZATION ITERATION HISTORY
APPROXIMATING FUNCTION 1 IS THE OBJECTIVE
APPROXIMATING FUNCTIONS ASSOCIATED WITH CONSTRAINTS
2 3 4 5

DESIGN VARIABLE NUMBERS ASSOCIATED WITH APPROXIMATING VARIABLES
1 2

BEGIN ITERATION NUMBER 1
NOMINAL DESIGN NUMBER = 2
X-VECTOR
0.20000E C1 0.20000E 02
FUNCTION VALUES
0.80000E 04 0.15000E 05 0.37500E 03 0.66667E 00 C.10000E 02

RESULTS OF APPROXIMATE OPTIMIZATION
DELTA-X VECTOR
-0.61480E-01 -0.11224E 01
X-VECTOR
0.15285E C1 0.18878E 02
APPROXIMATE FUNCTION VALUES
0.73964E 04 0.15745E 05 0.44117E 03 0.10002E 01 C.99918E 01
PRECISE FUNCTION VALUES
C.72189E C4 0.17371E 05 0.40990E 03 0.81794E 00 C.97381E 01

BEGIN ITERATION NUMBER 2
NOMINAL DESIGN NUMBER = 5
X-VECTOR
0.19285E C1 C.1E818E 02
FUNCTION VALUES
0.73189E 04 0.17271E 05 0.40990E 03 0.81794E 00 C.97381E C1

FIG. 7 - CONT.

RESULTS OF APPROXIMATE OPTIMIZATION

DELTA-X VECTOR
C.21965E-01 -0.13725E 01
X-VECTOR
0.19605E 01 0.17505E 02
APPROXIMATE FUNCTION VALUES
0.67872E C4 0.19684E 05 0.43322E 03 C.10001E 01 C.90402E 01
PRECISE FUNCTION VALUES
C.68637E 04 0.19975E 05 C.43708E 03 0.10143E 01 0.89289E C1

BEGIN ITERATION NUMBER 3
NOMINAL DESIGN NUMBER = 6
X-VECTOR
C.15655E C1 0.17505E 02
FUNCTION VALUES
0.68637E 04 0.15575E 05 0.43708E 03 0.10143E 01 0.89289E 01

RESULTS OF APPROXIMATE OPTIMIZATION
DELTA-X VECTOR
-0.10136E CC C.77532E 00
X-VECTOR
C.18591E C1 C.18280E 02
APPROXIMATE FUNCTION VALUES
C.67980E 04 0.19598E 05 0.45218E 02 0.98844E CC C.10000E 02
PRECISE FUNCTION VALUES
C.67970E C4 C.19316E 05 0.44137E 03 C.93927E 00 C.98326E C1

```

BEGIN ITERATION NUMBER 4
NOMINAL DESIGN NUMBER = 7
X-VECTOR C1 0.18280E 02
FUNCTION VALUES 0.67970E 04 0.19316E 05 C.44137E 03 0.93927E 00 C.98326E 01

RESULTS OF APPROXIMATE OPTIMIZATION
DELTA-X VECTOR -0.524669E-01
C.18242E 01 0.18188E 02
APPROXIMATE FUNCTION VALUES
C.66354E C4 0.20001E 05 0.45387E 03 C.98035E 00 C.99933E 01
PRECISE FUNCTION VALUES
C.66354E C4 0.15871E 05 0.45212E 03 0.97195E 00 C.99704E 01

BEGIN ITERATION NUMBER 5
NOMINAL DESIGN NUMBER = 8
X-VECTOR 0.18242E 01 C.18188E 02
FUNCTION VALUES
0.66354E C4 0.19887E 05 0.45212E 03 0.97195E 00 C.99704E 01

RESULTS OF APPROXIMATE OPTIMIZATION
DELTA-X VECTOR -0.59226E-02 -0.87478E-02
X-VECTOR C.18182E 01 0.16179E 02
APPROXIMATE FUNCTION VALUES
C.66117E 04 0.19933E 05 0.45399E 02 0.97747E 00 C.10000E 02
PRECISE FUNCTION VALUES
C.66117E 04 0.19971E 05 0.45381E 03 C.97652E 00 C.99981E 01

```

FIG. 7 - CONT.

```

BEGIN ITERATION NUMBER 6
NOMINAL DESIGN NUMBER = 9
X-VECTOR
C.18182E 01 0.18168E C2
FUNCTION VALUES
0.66067E 04 0.19971E 05 0.45381E 03 0.97652E 00 C.99981E 01

RESULTS OF APPROXIMATE OPTIMIZATION N

DELTA-X VECTOR
-0.15702E-04 -C.1C826E-01

X-VECTOR
C.18182E C1 0.18168E 02
APPROXIMATE FUNCTION VALUES
0.66067E 04 0.20000E C5 0.45417E 03 0.97861E 00 C.99935E 01
PRECISE FUNCTION VALUES
C.6667E C4 C.15995E 05 0.45409E 03 0.97828E 00 C.99922E 01

BEGIN ITERATION NUMBER 7
NOMINAL DESIGN NUMBER = 10
X-VECTOR
C.18182E C1 C.18168E 02
FUNCTION VALUES
0.66067E 04 0.19995E 05 0.45409E 03 0.97828E 00 C.99922E C1

RESULTS OF APPROXIMATE OPTIMIZATION N

OPTIMIZATION HAS PREDICTED AN X-VECTOR WHICH IS THE SAME AS A PREVIOUS DESIGN
DELTA-X VECTOR
0. C 0. 0
X-VECTOR
0.18182E 01 0.18168E 02

```

KD-A133 039

COPES - A FORTRAN CONTROL PROGRAM FOR ENGINEERING
SYNTHESIS(U) NAVAL POSTGRADUATE SCHOOL MONTEREY CA
L E MADSEN ET AL. MAR 82 NPS69-81-003


2/2

UNCLASSIFIED

F/G 9/2

NL

END



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

THE FOLLOWING DESIGN IS NOT THE APPROXIMATE OPTIMUM

DELTAX VECTOR
0.50000E-02 0.20000E-01

X-VECTOR
0.18232E 01 0.18188E 02

APPROXIMATE FUNCTION VALUES
0.66321E C4 C.15881E 05 0.45210E 03 C.97124E 00 C.99727E C1

PRECISE FUNCTION VALUES
C.66321E C4 0.19836E 05 0.45234E 03 0.97238E 00 C.99758E 01

BEGIN ITERATION NUMBER 8

ADMISSIBLE DESIGN NUMBER = 10

X-VECTOR
0.18182E 01 0.18168E 02

FUNCTION VALUES
0.66671E C4 0.19995E 05 0.45409E 03 0.97828E 00 C.99922E 01

RESULTS OF APPROXIMATE OPTIMIZATION

DELTAX VECTOR
0.0 0.0

X-VECTOR
0.18182E C1 0.18168E 02

APPROXIMATE FUNCTION VALUES
C.66067E 04 0.15555E C5 0.45409E 03 0.97828E 00 C.99922E 01

THE CONSECUTIVE APPROXIMATE OPTIMIZATIONS HAVE PRODUCED THE SAME DESIGN
OPTIMIZATION TERMINATED

FINAL RESULT OF APPROXIMATE OPTIMIZATION
NOMINAL DESIGN NUMBER = 10
X-VECTOR
C.1E182E 01 0.18168E 02
FUNCTION VALUES
0.66067E 04 0.15595E 05 0.45409E 03 0.97828E 00 C.99922E 01

RESULTS OF APPROXIMATE ANALYSIS/OPTIMIZATION

TITLE FILE NEEDED FOR ANALYSIS AND DESIGN

GLOBAL LOCATIONS OF X-VARIABLES

GLOBAL LOCATIONS OF FUNCTIONS, F(X)

APPROXIMATION IS BASED ON 11 DESIGNS
NOMINAL DESIGN IS DESIGN NUMBER 10

VALUES OF X-VARIABLES
0.1E182E 01 C.1A17E 02

VALUES OF FUNCTIONS F(X)
0.6607E 04 0.2C0E 05 0.4541E 03 0.9783E 00 0.9992E 01

FIG. 7 - CONT.

COEFFICIENTS OF TAYLOR SERIES EXPANSION

PARAMETER 1 = GLOBAL VARIABLE 3

LINEAR TERMS DEL F
0.3633E 04 -0.3637E 03

NON-LINEAR TERMS, R, BEGINNING WITH DIAGONAL ELEMENT

RO¹
-0.6992E 00 0.1999E 03
RCW 0.2882E-01

PARAMETER 2 = GLOBAL VARIABLE 4

LINEAR TERMS DEL F
-0.1231E 05 -0.26663E 04

NON-LINEAR TERMS, R, BEGINNING WITH DIAGONAL ELEMENT

RCW 0.1481E 05 C.2444E C4
RO¹
0.7C24E 03

PARAMETER 3 = GLOBAL VARIABLE 5

LINEAR TERMS DEL F
-0.2C74E C3 -0.3274E 02

NON-LINEAR TERMS, R, BEGINNING WITH DIAGONAL ELEMENT

RCW 0.2492E 03 0.3669E 02
RO¹
0.8920E 01

FIG. 7 - CONT.

PARAMETER 4 = GLOBAL VARIABLE 6

LINEAR TERMS, H, BEGINNING WITH DIAGONAL ELEMENT
-0.6454E 01 DEL F

00

NCN-LINEAR TERMS, H, BEGINNING WITH DIAGONAL ELEMENT

ROW 0.1C21E 01 0.1589E 00

RCW 0.5775E-C1

PARAMETER 5 = GLOBAL VARIABLE 7

LINEAR TERMS, H, BEGINNING WITH DIAGONAL ELEMENT
-0.5611E Q1 DEL F

00

NCN-LINEAR TERMS, H, BEGINNING WITH DIAGONAL ELEMENT

ROW 0.2661E 01 0.1113E 00

RCW 0.1162E 00

OPTIMIZATION RESULTS

OBJECTIVE FUNCTION 3
GLOBAL LOCATION 3

FUNCTION VALUE 0.66067E 04

DESIGN VARIABLES

ID	D _{NO.}	V _{NO.}	GLOBAL VAR. NO.	LOWER BOUND	UPPER BOUND
1	1	1	1	0.50000E 01	0.18182E 01
2	2	2	2	0.10000E 01	0.18168E 02

DESIGN CONSTRAINTS

ID	GLOBAL VAR. NO.	LOWER BOUND	UPPER BOUND
1	4	-0.11000E 16	0.19955E 05
2	5	-0.11000E 16	0.45409E 03
3	6	-0.11000E 16	0.97828E 00
4	7	-0.11000E 16	0.99922E 01

CANTILEVERED FEAM

A _L	=	200.000
E	=	6.10000E 05
E	=	3.00000E 08
B	=	1.818
H	=	18.168
VCL	=	6606.660
S _{STRESS}	=	6.19995E 05
S _{SHRSTR}	=	0.4549E C3
DELT _A	=	0.97828E 00
F/G	=	6.992

PROGRAM CALLS TO ANALIZ

I _{CALC}	CALLS
1	1
2	1
3	1

```

CANTILEVERED BEAM ANALYSIS AND DESIGN
S DATA BLOCK E NDY NSV N2VAR NMAX
S NCALC 4 2 3 2
S DATA BLOCK C - DEFAULT ALL BUT PRINT CONTROL
S IPRINT 1
S DATA BLOCK D - ALL DEFAULTS
0.0.

S DATA BLOCK E 1083 SCACPT -1.
S DATA BLOCK F
S VELS
S MDTF, B
S HEIGHT, F 5.
S HEIGHT, F 20.
S DATA BLOCK G IDSEN APULT
S MDTF, B 1. 1.
S HEIGHT, F 2 1.
S DATA BLOCK H 2 1.

S DATA BLOCK I JCCN BU LCIN SCAL2
S BLCRNT SCL BSTRS 0.
S CONSTRAINT OF SHRSTR 20000. 0.
S CONSTRAINT OF DELTA 10000. 0.
S CONSTRAINT OF 1/B 0. 0.
S CONSTRAINT OF 1/B 0. 0.
S CONSTRAINT OF 1/B 0. 0.
S DATA BLOCK J 10. 0.
S USE DEFALLS WHERE POSSIBLE EXCEPT PRINT CONTROL AND CANDIDATE DESIGNS
S NXA 0 ISCRX 0 IPAPRX 1
S NF 0 INLOC 0 MAXTRN 0
S KMIN 0 NPMAG 0 JNDW 0 INFLOC 0

```

FIG. 8 - COMBINED DATA INPUT

```

S DATA BLOCK K
S DX1 DX2
S XSFACT1 XSFACT2
S CATA BLOCK L NOT REQUIRED (INXLOC = 0)
S CATA BLOCK M NOT REQUIRED (INFLLOC = 0)
S DATA BLOCK N READ 4 CANDIDATE DESIGNS
S X1 X2
S 1. 15.
S 2. 20.
S 3. 10.
S 4. 12.

S CATA BLOCK P NOT REQUIREC (NXFS = 0)
S DATA BLOCK Q NOT REQUIREC (NXFS = 0)

S NSN1 ASN2 ASN3 ASN4 ASN5 ASN6 ASN7
S CATA BLOCK C NSENS SNS2 SNS3 SNS4
S ISEN1 SNS1
S BEAM LENGTH
S BEAM LENGTH
S 200. 100. 4 150. 250.

S BEAM WIDTH
S BEAM1 1.5 3 2.5
S BEAM2 1.5 2
S BEAM3 20.

S CATA BLOCK R M2VX M2VY
S CATA NZ1 M2VX M2VY
S CATA NZ2 M2VY M2VY
S CATA NZ3 M2VY M2VY
S CATA NZ4 M2VY M2VY
S CATA NZ5 M2VY M2VY
S CATA NZ6 M2VY M2VY
S CATA NZ7 M2VY M2VY

S DATA BLOCK T
S VALUES OF WIDTH, B
S X1 X2 X3 X4
S X5 1. 1.5 2.
S CATA BLOCK U
S VALUES OF HEIGHT, H
S Y1 Y2 Y3 Y4 Y5
S Y6 8. 12. 16. 20.

S DATA BLOCK V
S RE CUREDEC ENC CARD
END

```

CANTILEVERED BEAM ANALYSIS AND DESIGN

DATA BLOCK 1	NDV	NSV	N2VAR	NXA PRX
DATA BLOCK C - DEFAULT ALL BUT PRINT CONTROL				
DATA BLOCK D - ALL DEFAULTS				
DATA BLOCK E	I0BJ	SNOPT		
DATA BLOCK F	YUB			
DATA BLOCK G	IDSGN	AMULT		
DATA BLOCK H	YDTH.			
DATA BLOCK I	JCON	BUICON	SCAL2	
CONSTRAINT ON STRES				
-1.0+2.91E+000	SHRSTR			
-1.0+2.61E+000	CONSTRAINT ON DELTA			
-1.0+2.91E+000	H/E			
-1.0+2.61E+000	CLOCK 10.			
USE DEFAULTS WHERE POSSIBLE EXCEPT NXA	NSFS	PRINT	CONTROL	AND CANDIDATE DESIGNS
FOR KMIN	KMAX	INOM	INXLOC	IPAPRX
FOR KMAX	NFMAX	INOM	INFLOC	MAXT FM

FIG. 9 - SIMPLIFIED DATA INPUT

```

S DATA BLOCK K
S DX1   EX2
S 5.2 FACT1  XFACT2
Q. DATA BLOCK L NOT REQUIRED (INXLOC = 0)
S DATA BLOCK M NOT REQUIRED (INLOC = 0)
S DATA BLOCK N READ 4 CARD IDATE DESIGNS
S X1   X2
S 15.0
S 12.0
S 10.0
S 8.0
S 6.0
S 4.0
S 2.0
S 1.0
S 0.5
S DATA BLOCK P NOT REQUIRED (NXFS = 0)
S DATA BLOCK Q
S DATA BLOCK R
S DATA BLOCK S
S DATA BLOCK T
S DATA BLOCK U
S DATA BLOCK V
S DATA BLOCK W
S DATA BLOCK X
S DATA BLOCK Y
S DATA BLOCK Z
S NSN1   NSN2   NSN3   NSN4   NSN5
S NSENS1  NSENS2  NSNS3  NSNS4  NSNS5
S BEAR LENGTH
S BEAM WIDTH
S BEAM HEIGHT
S BEAM WIDTH, B
S BEAM HEIGHT, H
S BEAM HEIGHT, M
S BEAM HEIGHT, N
S BEAM HEIGHT, P
S BEAM HEIGHT, Q
S BEAM HEIGHT, R
S BEAM HEIGHT, S
S BEAM HEIGHT, T
S BEAM HEIGHT, U
S BEAM HEIGHT, V
S BEAM HEIGHT, W
S BEAM HEIGHT, X
S BEAM HEIGHT, Y
S BEAM HEIGHT, Z
S X1   X2   X3   X4
S Y1   Y2   Y3   Y4
S Y5
END

```

CANTILEVERED BEAM ANALYSIS AND DESIGN

```
6.2.3.1.  
100.  
05.5.  
120.  
1.1.  
2.1.  
4 -1.0+20.0.,20000.  
5 -1.0+20.0.,10000.  
6 -1.0+20.0.,10.  
7 -1.0+20.0.,10.  
0.4.,0.4.,1  
05.2.  
20.0.,10.  
10.0.  
10.0.  
10.0.  
10.0.  
4.5.6.7  
0.,100.,150.,250.  
1.5.2.5  
2.0.  
1.4.3.5  
1.4.3.5  
1.4.3.5  
1.4.3.5  
END  
0.8.12.0.20.0.20.
```

FIG. 10 - SIMPLIFIED DATA INPUT WITHOUT COMMENT CARDS

VIII. REFERENCES

1. Vanderplaats, G. N., CONMIN - A Fortran Program for Constrained Function Minimization. User's Manual. NASA Technical Memorandum TMX-62282. Ames Research Center, August, 1973.
2. Vanderplaats, G. N., Approximation Concepts for Numerical Airfoil Design, NASA Technical Paper 1370, Ames Research Center, March, 1979.
3. Schmit, L. A., "Structural Design by Systematic Synthesis," Proc. 2nd Conference on Electronic Computation, ASCE, New York, 1960, pp. 105-122.

APPENDIX A
GLOBAL CATALOG FORMS

GLOBAL CATALOG

GLOBAL LOCATION	FORTRAN NAME	DEFINITION

APPENDIX B
COPES DATA FORMS

COPES DATA

DATA BLOCK A

TITLE		FORMAT
*		20A4

DATA BLOCK B

+	\$					COMMENT
NCALC	NDV	NSV	N2VAR	NXAPRX	I PNPUT	IPDBG
*						7I10

DATA BLOCK C - OMIT IF NDV = 0

+	\$					COMMENT
IPRINT	ITMAX	ICNDIR	NSCAL	ITRM	LINOBJ	NACMX1
*						NRDG

COPES DATA

DATA BLOCK D - OMIT IF NDV = 0

COPES DATA						COMMENT			
+	\$	FDCH	FDCHM	CT	CTMIN	CTL	CTLMIN	THETA	FORMAT
*	*								7F10
DEL.FUN	DABFUN	ALPHAX	ABOBJ1						FORMAT
*	*								4F10

DATA BLOCK E - OMIT IF NDV = 0

DATA BLOCK E				COMMENT	
+	\$	NDVTOT	I0BJ	SIGNOBJ	FORMAT
					2I10,F10

DATA BLOCK F - OMIT IF NDV = 0

DATA BLOCK F				COMMENT		
+	\$	VLB	VUB	X	SCAL	FORMAT
						4F10

COPES DATA

DATA BLOCK F - CONT.

COPES DATA

DATA BLOCK G - OMIT IF NDV = 0

\$	NDSGN	IDSGN	AMULT																	COMMENT
*																				
*																				
*																				
*																				
*																				
*																				
*																				
*																				
*																				
*																				
*																				
*																				
*																				
*																				

COPES DATA

DATA BLOCK H - OMIT IF NDV = 0

+				COMMENT
	NCONS			FORMAT
*				I 10

DATA BLOCK I - OMIT IF NDV = 0 OR NCONS = 0

+				COMMENT
\$	ICON	JCON	LCON	FORMAT
*				3I 10
+				COMMENT
	BL	SCAL1	BU	SCAL2
*				
*				
\$	ICON	JCON	LCON	FORMAT
				4F10

COPES DATA

DATA BLOCK I - CONT.

\$	BL	SCAL1	BU	SCAL2																				
\$	ICON	JCON	LCON																					
\$	BL	SCAL1	BU	SCAL2																				
\$	ICON	JCON	LCON																					
\$	BL	SCAL1	BU	SCAL2																				
\$	ICON	JCON	LCON																					
\$	BL	SCAL1	BU	SCAL2																				

COPIES DATA

DATA BLOCK J - OMIT IF NXAPRX = 0

+ \$	NF	NXS	NXFS	NXA	INOM	ISCRX	ISCRXF	IPAPRX	FORMAT	COMMENT
*									8I10	
KMIN	KMAX	NPMAX	JNOM	INXLOC	INFLOC	MAXTRM			FORMAT	
*									7110	

DATA BLOCK K - OMIT IF NXAPRX = 0

+ \$	DX1	DX2	DX3	DX4	DX5	DX6	DX7	DX8	FORMAT	COMMENT
*									8F10	
*	XFACT1	XFACT2							8F10	
*									2F10	

COPES DATA

DATA BLOCK L - OMIT IF NXAPRX = 0 OR INXLOC = 0

+	\$									COMMENT
LOCX1	LOCX2	LOCX3	LOCX4	LOCX5	LOCX6	LOCX7	LOCX8		FORMAT	
*										8110
*										8110
*										8110

DATA BLOCK M - OMIT IF NXAPRX = 0 OR INFLOC = 0

+	\$									COMMENT
LOCF1	LOCF2	LOCF3	LOCF4	LOCF5	LOCF6	LOCF7	LOCF8		FORMAT	
*										8110
*										8110
*										8110

COPES DATA

DATA BLOCK N - OMIT IF NXS = 0

+ \$	XI1	XI2	XI3	XI4	XI5	XI6	XI7	XI8	FORMAT	COMMENT
*									8F10	
*									8F10	
\$									COMMENT	
XI1	XI2	XI3	XI4	XI5	XI6	XI7	XI8	FORMAT		
								8F10		
								8F10		
\$								COMMENT		
XI1	XI2	XI3	XI4	XI5	XI6	XI7	XI8	FORMAT		
								8F10		
								8F10		
\$								COMMENT		
XI1	XI2	XI3	XI4	XI5	XI6	XI7	XI8	FORMAT		
								8F10		
								8F10		
\$								COMMENT		
XI1	XI2	XI3	XI4	XI5	XI6	XI7	XI8	FORMAT		
								8F10		
								8F10		

COPES DATA

DATA BLOCK 0 - OMIT IF NXFS = 0

\$	X1	X2	X3	X4	X5	X6	X7	X8	COMMENT
*									FORMAT 8F10
									8F10
									FORMAT 8F10
									FORMAT 8F10
									COMMENT
\$	X1	X2	X3	X4	X5	X6	X7	X8	FORMAT 8F10
*									8F10
									FORMAT 8F10
									FORMAT 8F10
									COMMENT
\$	X1	X2	X3	X4	X5	X6	X7	X8	FORMAT 8F10
*									8F10
									FORMAT 8F10
									FORMAT 8F10
									FORMAT 8F10

COPES DATA

DATA BLOCK P - OMIT IF NSV = 0

\$	NSOBJ		IPSENS		COMMENT	
*					FORMAT	
*					2110	
+	\$				COMMENT	
*					FORMAT	
*					8110	

NSN1	NSN2	NSN3	NSN4	NSN5	NSN6	NSN7	NSN8	FORMAT	COMMENT
*									
*									
*									
*									
*									
*									
*									

COPES DATA

DATA BLOCK Q - OMIT IF NSV = 0

+	\$										
ISENS	NSENS										
*											
+	\$										
SNS1	SNS2	SNS3	SNS4	SNS5	SNS6	SNS7	SNS8				
*											
*											
*											
*											

+	\$										
ISENS	NSENS										
*											
+	\$										
SNS1	SNS2	SNS3	SNS4	SNS5	SNS6	SNS7	SNS8				
*											
*											
*											
*											

COPES DATA

DATA BLOCK Q - CONT.

+		\$	COMMENT	
ISENS	NSNES		FORMAT	
*			2110	
		+	COMMENT	
SNS1	SNS2	SNS3	SNS4	SNS5
*				
SNS6	SNS7	SNS8		
*			8F10	

DATA BLOCK R - OMIT IF N2VAR = 0

+		\$	COMMENT	
N2VX	M2VX	N2VY	M2VY	FORMAT
*				4110

COPES DATA

DATA BLOCK S - OMIT IF N2VAR = 0

\$									COMMENT
+	NZ1	NZ2	NZ3	NZ4	NZ5	NZ6	NZ7	NZ8	FORMAT
*									8110

DATA BLOCK T - OMIT IF N2VAR = 0

\$									COMMENT
+	X1	X2	X3	X4	X5	X6	X7	X8	FORMAT
*									8F10

COPES DATA

DATA BLOCK U - OMIT IF N2VAR = 0

*	\$	Y1	Y2	Y3	Y4	Y5	Y6	Y7	Y8	COMMENT
*										8F10
*										
*										
*										
*										
*										
*										
*										
*										
*										

DATA BLOCK V - COPES END OF DATA CARD

*	END	FORMAT	3A1
*	END		

DISTRIBUTION LIST

- | | | |
|----|--|-----|
| 1. | Library
Naval Postgraduate School
Monterey, California 93940 | 1 |
| 2. | Research Administration
Code 012A
Naval Postgraduate School
Monterey, California 93940 | 1 |
| 3. | Defense Documentation Center
Cameron Station
Alexandria, Virginia 22314 | 2 |
| 4. | Dr. Garret N. Vanderplaats
Code 69Vn
Department of Mechanical Engineering
Naval Postgraduate School
Monterey, California 93940 | 300 |
| 5. | Dr. Paul J. Marto, Chairman
Code 69Mx
Naval Postgraduate School
Monterey, California 93940 | 1 |

END

FILMED

10-83

DTIC