


AD-A133 448


APPROPRIATE LENGTHS BETWEEN PHALANGES OF MULTIJOINTED
FINGERS FOR STABLE GRASPING(U) CARNEGIE-MELLON UNIV
PITTSBURGH PA ROBOTICS INST T OKADA ET AL. 22 JUL 83
CMU-RI-TR-83-13 F/G 6/4

1/1

UNCLASSIFIED

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

ADA 133 448

Appropriate Lengths Between Phalanges
of Multijointed Fingers for Stable Grasping

Tokuji Gkeda and Takeo Kanade

CMU-RI-TR-83-13

(13)

REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS BEFORE COMPLETING FC

1. REPORT NUMBER CMU-RI-TR-83-13		2. GOVT ACCESSION NO. AD-A133448		3. RECIPIENT'S CATALOG NUMBER	
4. TITLE (and Subtitle) APPROPRIATE LENGTHS BETWEEN PHALANGES OF MULTIJOINTED FINGERS FOR STABLE GRASPING			5. TYPE OF REPORT & PERIOD COVERED Interim		
7. AUTHOR(s) Tokuji Okada and Takeo Kanade			8. CONTRACT OR GRANT NUMBER(s)		
9. PERFORMING ORGANIZATION NAME AND ADDRESS Carnegie-Mellon University The Robotics Institute Pittsburgh, PA. 15213			10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS		
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research Arlington, VA 22217			12. REPORT DATE 22 July 1983		13. NUMBER OF PAGES 14
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)			15. SECURITY CLASS. (of this report) UNCLASSIFIED		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)					
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) Approved for public release; distribution unlimited					
18. SUPPLEMENTARY NOTES					
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)					
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)					

AD-A133448

100-254-001

DTIC
SELECTED
OCT 11 1983
E

Appropriate Lengths Between Phalanges of Multijointed Fingers for Stable Grasping

Tokuji Okada and Takeo Kanade

CMU-RI-TR-83-13

Robotics Institute
Carnegie-Mellon University
Pittsburgh, Pennsylvania 15213

22 July 1983

Copyright © 1983 Carnegie-Mellon University

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	



- 2 -

↓

Abstract

An appropriate arrangement of finger joints is very important since the stability of grasping an object greatly depends on that arrangement. Multijointed fingers can grasp an object with many points of contact each of which is pressed against the object as if wrapping up that object. The amount of the wrapped up area and the form of the finger when an object is grasped are therefore important factors for determining the stability of grasping. ^{The authors} We propose the wrapping factor to be used for the evaluation of the stability of grasping by using these factors. ^{They} We consider twenty eight models for the finger having three joints, and perform a simulation of their ability to grasp various shapes stably. Based on the simulation results, an appropriate arrangement of lengths between phalanges for a multijointed finger is presented.

↑

Table of Contents

1. Introduction	1
2. Evaluation of Grasping by a Form of Fingers	1
2.1. Relationships Between Sizes of Fingers and an Object	2
2.2. Definition of Wrapping Factor	3
3. Simulation for Finding Appropriate Lengths between Phalanges	3
3.1. Control Sequence of Finger	3
3.2. Finger Models	4
3.3. Dimensions of Objects for Grasping	5
3.4. Simulation Process	5
3.5. Simulated Results	6
4. Conclusions	7
Acknowledgements	7

List of Figures and Tables

Figure 1: Finger structure.

Figure 2: Relationships between the sizes of fingers and objects.

Figure 3: Illustration of the amount of wrap-up.

Figure 4: Unstable grasping in general.

Table 1: Finger models.

Figure 5: Classification of finger models into five types.

Figure 6: Finger configurations to explain tactual conditions for circles.

Figure 7: Finger configurations to explain tactual conditions for rectangles.

Figure 8: Simulated results of graspings under $(W_r)_i > 0.8$, $0 < \theta_0 < \pi/2$ and $0 < \theta_1 < \pi/2$.

Figure 9: Simulated results of graspings under $(W_r)_i > 0.8$, $0 < \theta_0 < \pi$ and $0 < \theta_1 < \pi$.

Figure 10: Appropriate finger lengths between phalanges for grasping circles, squares and rectangles.

$$(a): (\theta_0)_{max} = (\theta_1)_{max} = \pi/2,$$

$$(b): (\theta_0)_{max} = \pi/2 \text{ and } (\theta_1)_{max} = \pi,$$

$$(c): (\theta_0)_{max} = \pi \text{ and } (\theta_1)_{max} = \pi/2,$$

$$(d): (\theta_0)_{max} = (\theta_1)_{max} = \pi.$$

1. Introduction

Two kinds of end effectors for grasping an object have been developed: One is the gripper and the other is the multijointed finger. Most grippers have simple mechanisms and grasp an object by pinching it since the grippers can only close and open. Although grippers are useful for grasping objects of limited shape and size, controlling the pressing force of the fingers against the object would make those grippers more versatile [1,2]. Multijointed fingers exhibit this versatility since they have increased mechanical flexibility and are able to grasp objects of a wider variety of shapes and sizes [3,4]. While these are desirable features, the main requirement for grasping objects is that the grip is stable. One way of determining this stability in both types of end effectors is by measuring the force exerted between the fingers and an object. Asada[2] and Chen[5] studied the problem of achieving a stable grip from this point of view. Multijointed fingers, however, grasp an object in a complex manner and this complexity makes it difficult to determine the stability of grasping based solely on the force between the fingers and object. We propose another method for assessing the stability of grip in multijointed fingers based on their inherent ability to wrap around an object. In a previous paper [6] we used the amount of wrapped up area as a guide to assessing the stability of the grip. However, we considered neither the number of points of contact between the fingers and the object nor the position of the fingers where that contact occurs. Salisbury treated contact configurations for designing a most suitable articulated hand (Stanford/JPL Hand), his treatment, however, was limited to mobilities and connectivities for acceptable hand mechanisms and did not include stability of grasping [4].

In this paper we examine the role of these additional factors in evaluating the stability of grasping. Since the number of points of contact between fingers and object depend on the arrangement of the joints and the lengths between the phalanges, two criteria are important to the stability of grasping: the amount of the wrapped up area and the form of the fingers including tactual conditions when the object is grasped. Thus, by taking notice of these two criteria, we will evaluate the stability of grasping by multijointed fingers having three joints. The results are applied to the problem of design of multijointed fingers.

2. Evaluation of Grasping by a Form of Fingers

The size of the fingers is determined depending on the sizes of the objects to be handled. After quantifying sizes of fingers and objects, we evaluate the stability of the graspings in the relationships between the objects and the fingers relatively. We will present the criteria which use the configuration of the fingers and tactual conditions.

2.1. Relationships Between Sizes of Fingers and an Object

The total length of a finger is determined mainly by the size of an object to be grasped. For our purposes, most objects are assumed to be lumps except for pillar-shaped objects. In order to express the size of the lumps, let the maximum width of an object be W_d , and the minimum width be W_s . When the object is not considered to be a lump, these are measured in the perpendicular plane to the longitudinal axis of the object.

The structure of the multijointed fingers we will consider is shown in Figure 1. In the figure, the multijointed finger moves in one plane and has k links, $L_1, L_2, L_3, \dots, L_k$ which are connected to joint $J_1, J_2, J_3, \dots, J_k$, respectively. The angular values of each joints are denoted by $\theta_1, \theta_2, \theta_3, \dots, \theta_k$. The horizontal link at the bottom is a palm and L_p stands for its length. L_0 is the length of the link which plays an auxiliary role for grasping an object with the multijointed finger. The angular value of the joint J_0 is expressed by θ_0 . The palm L_p is fixed, but the links L_0, L_i ($i=1, 2, \dots, k$) rotate about the corresponding joints. The ranges of angular rotation of proximal joints J_0 and J_1 are $0 < \theta_0 < \pi$ and $0 < \theta_1 < \pi$, and those for other joints are $0 < \theta_i < \pi/2$ ($i=2, 3, \dots, k$). Let us denote the total length of the finger as $L_T (= \sum_{i=1}^k L_i)$. It seems reasonable to impose the following three conditions on the relations of L_T, L_p and L_0 :

$$(L_p^2 + L_0^2)^{1/2} < L_T < L_p + L_0, \quad (1)$$

$$W_d < L_T, \quad (2)$$

$$W_s > 2(L_T - L_p)/3. \quad (3)$$

The first condition states that the total length L_T is longer than the length between the tip of L_0 and the joint J_1 when L_1 and the palm make a right angle, and shorter than that when the joint stretches. The total length of the finger should be longer than the maximum width of an object by the second condition. The third condition is understood by considering the case of $k = 3$; the minimum size of an object W_s is larger than the diameter of the circle which touches the links L_0, L_p, L_2 and L_3 (fingertip) when $\theta_0 = \theta_1 = \theta_2 = \theta_3 = \pi/2$.

As the size of the object increases, so the length of the fingers must also increase. Intuitively, the reverse must also be true. The length L_0 would be determined therefore depending on the length of L_p . We quantify this relationship by using μ which is the ratio of L_T to L_p ($\mu = L_T/L_p$). We will investigate the case when $\mu = 1.8$, and $L_0 = L_p$. Figure 2 illustrates the size of the finger relative to that of the objects which satisfy the inequality conditions (1-3). Given the three-jointed finger shown in the lower right, the maximum and minimum sizes that can be handled by the finger are illustrated for each shape. The rectangle and ellipse

show the longest and slenderest figures that can be handled.

2.2. Definition of Wrapping Factor

In the previous paper [6], the value $\Theta = \theta_0 + \sum_{i=1}^m \theta_i$ was used to evaluate the stability of grasping, where m was the maximum number of link where there was a contact between the object and the finger ($m \leq k$). The point of contact in the fingertip was treated in the same way as the point of contact in the middle point of the link. Also the position of the point of contact on the link L_0 was not considered.

In order to take these factors into account, we define a new measure named a *wrapping factor* W_r , which can be expressed as follows:

$$W_r = \frac{2\pi - (\theta_l - \theta_r)}{2\pi} \quad (4)$$

The concept of wrapping factor is illustrated in Figure 3. In this definition, θ_l is the angular displacement of the point at which the link L_0 touches the object, and θ_r is the angular displacement of the joint J_1 to the most distal position at which the finger touches the object. When $\theta_l = \theta_r$, the finger wraps the object completely and the value W_r becomes equal to 1. At this value the grip is considered to be most stable. The larger the value of W_r becomes, the more stable grasping the finger provides.

A finger having large values of L_f and k tends to wrap the finger around the object more than one turn. Under the conditions that $k=3$, $2^{1/2} < \mu < 2$, and equations (1), (2) and (3) are valid, the maximum value of W_r is $1 + \tan^{-1}(L_0/L_f)/2\pi$, which occurs when $\theta_l = \pi - \tan^{-1}(L_0/L_f)$ and $\theta_r = \pi$. If $L_p = L_0$, this maximum value of W_r is 1.125.

3. Simulation for Finding Appropriate Lengths between Phalanges

In order to find appropriate finger constructions for the stable grasping of objects having various shapes and sizes, we simulate the graspings and evaluate them by using the wrapping factor. Various constructions of a finger are considered and various objects are grasped by each construction. The results depend not only on finger constructions but also on the size and shape of the objects. Mutual relationships among these factors are investigated.

3.1. Control Sequence of Finger

Grasping an object by a finger is realized by the following control sequence. It is important to have the palm L_p touch the object since this contact enables the finger to grasp the object stably. In our sequence of grasping, this contact is required. The control sequence is:

1. Stretch the finger so that $\theta_i = 0$ ($i = 1, 2, \dots, k$). An object is placed on the palm link.
2. Starting with joint J_0 , bend the joints in turn from proximal to distal. Joint J_{i+1} begins to bend when a contact occurs with the object on the link L_i , or when the angular displacement of joint J_i reaches its maximum.
3. Finger control ends either when the final link L_k touches the object or when its angular displacement reaches its maximum while joint J_k bends.

Application of these rules to the finger control results in various types of finger configurations. Configurations of unstable graspings are included too. For instance, those graspings shown in Figure 4 are considered as unstable. The configuration in Figure 4(a) is $\theta_1 = \theta_2 = \pi/2$ [rad], and the object does not touch L_1 and L_2 . Figure 4 (b) shows the unstable grasping which occurs when the amount of $\theta_0 + \sum_{i=1}^m \theta_i$ is less than π [rad]. This configuration is not stable since the object has a tendency to move out from the palm area. We exclude these unstable graspings before we calculate the wrapping factor W_r described in Section 2.2.

3.2. Finger Models

The finger we consider has three joints whose rotational axes are all parallel. Table 1 shows the twenty eight models we considered each of which has different combinations of the lengths of L_1 , L_2 and L_3 . Each number in the table expresses the proportion of the length of a link to the sum of L_1 , L_2 and L_3 . These models are classified into 5 categories.

1. I-type; distal lengths are larger than those of the proximal,
2. D-type; distal lengths are less than those of the proximal,
3. M-type; middle link (i.e. L_2) is longer than the others,
4. V-type; middle link is shorter than the others,
5. K-type; three links are the same length.

Figure 5 illustrates this classification by segmenting the plane whose horizontal and vertical axes represent proportions of L_2 and L_3 , respectively. This figure makes it easy to see which type a model belongs to.

3.3. Dimensions of Objects for Grasping

If we were considering the grasping of objects in three-dimensional space, we would use objects like a ball, a cylinder and a four-cornered pillar. However, since our finger moves in one plane, we can simulate calculations for the stability of the grip reliably by using two-dimensional shapes. For simplicity, we exclude rhomboids and ellipses and restrict ourselves to considering circles, squares and rectangles. The ratio of the long side to the short side of the rectangles is set as $3^{1/2}$. Dimensions of the finger are $L_0 = L_p = 80\text{mm}$ and $\mu = 1.8$. The radii of the circles are chosen from 25mm to 70mm in increments of 2.5mm. The diagonal lengths of the squares and rectangles are from 50mm to 140mm in increments of 10mm. All of these shapes satisfy the conditions of equations (2) and (3) in Section 2.1. Under these conditions, graspings of circles, squares and rectangles are simulated.

3.4. Simulation Process

This section explains in detail how the simulation of grasping circles is performed. At first, a circle is placed at the left side of the palm to touch the link L_p . Then, the auxiliary link L_0 closes to find the angular displacement θ_0 at which link L_0 touches the circle. When contact is made between the object and link L_0 , link L_1 is driven next, and then L_2 and L_3 , according to the rules described in Section 3.1. For stable grasping we impose a tactual condition that the total number of points of contact on L_1 , L_2 and L_3 is greater than or equal to two. Figure 6 shows an example of finger configurations satisfying the tactual conditions for circles. When this condition is satisfied, the wrapping factor W_p is calculated. The grasping is then evaluated by the magnitude of the wrapping factor; that is, the grasping is regarded as a stable grasping when the magnitude is greater than a threshold value $(W_p)_t$. In our simulation we set $(W_p)_t = 0.8$.

The same circle is then shifted to the right by $dl = 2\text{mm}$ along L_p and the next check is performed in the same manner. When the contact is made on the tip of L_0 , or the tactual conditions are not satisfied, the data are not taken into consideration and we examine the next grasping. When the circle is moved to the right end of the palm, the next circle having a different size is tested. Many circles of different sizes are tested in different positions relative to the palm, and the total number of graspings which are regarded as stable graspings are obtained.

For other shapes, simulations of grasping are performed in ways similar to those for circles. The only difference is that rotations of those figures are also considered by rotating the shapes about their centers as well as moving the position along the palm L_p . The range of rotation is $\pi/2$ and π for squares and rectangles, respectively, and the increment of rotation is $d\rho = 2$ degrees. Finger configurations shown in Figure 7 illustrate the stable tactual conditions for rectangles.

3.5. Simulated Results

Figure 8 summarizes the simulation results for the case in which we limit the rotational range of the proximal joints to half way, i.e., $0 < \theta_0 < \pi/2$ and $0 < \theta_1 < \pi/2$. Figure 8(a) shows the score of stable graspings for circles. In the figure, horizontal and vertical axes are proportions of L_2 and L_3 , respectively, and thus each grid position corresponds to each finger model in Table 1. The size of the circle is proportional to the number of stable graspings. The threshold of the stable wrapping factor we used is $(W_r)_t = 0.8$. Triple circles indicate the finger model with the most stable graspings: Double circles indicate the model with the second most stable graspings. Similarly, Figure 8(b) and (c) show the simulated results for the squares and rectangles, respectively. Figure 8(d) shows the result when the score of stable graspings for both squares and rectangles are combined. The results shown in Figure 8 imply that the most stable finger model for circles and rectangles is the M-type (refer to Figure 5).

Figure 9 shows similar simulation results for the case in which $0 < \theta_0 < \pi$ and $0 < \theta_1 < \pi$. Here the link and the joint can bend completely, unlike the case of Figure 8 in which the auxiliary link L_0 and the proximal joint can bend only half way. Notice that the stable graspings are found by different models from those in Figure 8.

By selecting two models with high stability for both circles and rectangles, those finger constructions shown in Figure 10 are extracted for stable grasping of various shapes. In the figure, (a) shows the result where $(\theta_0)_{max} = (\theta_1)_{max} = \pi/2$, (b) shows the result where $(\theta_0)_{max} = \pi/2$ and $(\theta_1)_{max} = \pi$, (c) shows the result where $(\theta_0)_{max} = \pi$ and $(\theta_1)_{max} = \pi/2$, and (d) shows the result where $(\theta_0)_{max} = (\theta_1)_{max} = \pi$. The left finger is the auxiliary link used in the simulations. The next two couples from the left to the right correspond to the appropriate fingers for circles and rectangles, in this order. Hatched and dotted areas show the most proximal and the most distal links (L_1 and L_3), respectively.

By comparing the four finger constructions in Figure 10, it is observed that the lengths of L_3 are not very different from each other, but the lengths of L_1 in (a) are much smaller than in the other three. Also, L_2 in (a) and L_1 in (b) are longer than any other three. Figure 8(a) implies that the M-type model is the most suitable for grasping circles, squares and rectangles when $0 < \theta_0 < \pi/2$ and $0 < \theta_1 < \pi/2$. However, when the auxiliary link or the proximal joint can be bent extensively (that is, the range of θ_0 and θ_1 is enlarged from $\pi/2$ to π), the D-type model is useful for circles as shown in Figure 9 and the V-type for squares and rectangles. In general, when the ranges of motion of θ_0 and θ_1 become large at the same rate, the appropriate length of L_1 becomes larger without changing the lengths of L_3 .

Simulations have also been carried out with different tactual conditions such those under which the finger makes contact with the object only on L_3 (except the tip) and only on L_2 . However, no significant difference has been observed between the results for these conditions and those for the ones previously

discussed.

4. Conclusions

We have proposed the wrapping factor as a criterion for evaluating the stability of grasping by multijointed fingers. In the simulation of grasping, a multijointed finger having three joints is used and circles, squares and rectangles are considered as possible shapes of an object. Positions and orientations of these two-dimensional shapes are changed systematically to examine various graspings. From the simulation, we have found that appropriate finger lengths between phalanges depend on the angular ranges of proximal joints. The results obtained from the simulation would be useful for determining the lengths between phalanges of multijointed fingers.

Acknowledgements

We thank D.R. Reddy for encouraging us to do this research.

1. A. Rovetta and I. Franchetti, "On a General Prehension Multipurpose System", Proc. of 10th ISIR, March 1980, pp.191-201.
2. H. Asada, "Studies on Prehension and Handling by Robot Hands with Elastic Fingers", D.E. Thesis, Kyoto Univ., April 1979.
3. T. Okada, "Computer Control of Multijointed Finger System for Precise Object-Handling", IEEE Trans. on Systems, Man, and Cybernetics, Vol.SMC-12 No.3, May/June 1982, pp.289-299.
4. J.K. Salisbury, "Kinematic and Force Analysis of Articulated Hands", Ph. D. Thesis, Stanford Univ., July, 1982.
5. F.Y. Chen, "Force Analysis and Design Considerations of Grippers", Journal of Industrial Robot, Vol.9 No.4, December 1982, pp.243-249.
6. T. Okada, "An Artificial Finger Equipped with Adaptability to an Object", Bul. Electrotech. Lab., Vol.37 No.12, December 1973, pp.1078-1090.




Figure 1: Finger structure.




Figure 2: Relationships between the sizes of fingers and objects.




Figure 3: Illustration of the amount of wrap-up.




Figure 4: Unstable grasplings in general.

TYPE	I	I	I	I	M	M	M	V	I	I	M	M	M	V	V	K	M	M	V	V	D	D	V	D	D	V	D	D
L_1	1	1	1	1	1	1	1	2	2	2	2	2	2	3	3	3	3	3	4	4	4	4	5	5	5	6	6	7
L_2	1	2	3	4	5	6	7	1	2	3	4	5	6	1	2	3	4	5	1	2	3	4	1	2	3	1	2	1
L_3	7	6	5	4	3	2	1	6	5	4	3	2	1	5	4	3	2	1	4	3	2	1	3	2	1	2	1	1

Table 1: Finger models.




Figure 5: Classification of finger models into five types.




Figure 6: Finger configurations to explain tactual conditions for circles.




Figure 7: Finger configurations to explain tactual conditions for rectangles.




Figure 8: Simulated results of graspings under $(W_r)_1 > 0.8$, $0 < \theta_0 < \pi/2$ and $0 < \theta_1 < \pi/2$.




Figure 9: Simulated results of grasplings under $(W_r)_r > 0.8$, $0 < \theta_0 < \pi$ and $0 < \theta_1 < \pi$.




Figure 10: Appropriate finger lengths between phalanges for grasping circles, squares and rectangles.

(a); $(\theta_0)_{max} = (\theta_1)_{max} = \pi/2$,

(b); $(\theta_0)_{max} = \pi/2$ and $(\theta_1)_{max} = \pi$,

(c); $(\theta_0)_{max} = \pi$ and $(\theta_1)_{max} = \pi/2$,

(d); $(\theta_0)_{max} = (\theta_1)_{max} = \pi$.

END

FILMED

10-83

DTIC