

AD-A134 209 COL A J BO BAKER AAF GERMANY (WEST) LIMITED SURFACE
OBSERVATIONS CLIMATIC.. (U) AIR FORCE ENVIRONMENTAL
UNCLASSIFIED TECHNICAL APPLICATIONS CENTER SCOTT A.. 03 AUG 83
USAFETAC/DS-83/034 SBI-AD-E850 427 F/G 4/2

COL A J BO BAKER AAF GERMANY (WEST) LIMITED SURFACE
OBSERVATIONS CLIMATIC..(U) AIR FORCE ENVIRONMENTAL
TECHNICAL APPLICATIONS CENTER SCOTT A.. 03 AUG 83
USAFETAC/DS-83/034 SBI-AD-E850 427 F/G 4/2


1/3

UNCLASSIFIED

USAFETAC/DS-83/034 SBI-AD-E850 427

F/G 4/2

NI



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AD-A134209

①

DATA PROCESSING DIVISION
USAFETAC
Air Weather Service (MAC)

ASST TECHNICAL LIBRARY
PL 4414
SCOTT AFB, IL 62220

"LIMITED SURFACE OBSERVATIONS"
CLIMATIC SUMMARY "LISOCs"

08 AUG 1983

AUG 03 1983

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

FEDERAL BUILDING
ASHEVILLE, N. C.

DTIC
ELECTE
S OCT 6 1983 D

DTIC FILE COPY

83 10 05 169

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER USAFETAC/DS-83/034	2. GOVT ACCESSION NO. ADA B4-209	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Limited Surface Observations Climatic Summary (LISOCs) - COL A J BO BAKER AAF, GERMANY (WEST)		5. TYPE OF REPORT & PERIOD COVERED Final Rept
7. AUTHOR(s)		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS USAFETAC/OL-A Air Force Environmental Technical Appl. Center Scott AFB IL 62225		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS USAFETAC/TS Air Weather Service (MAC) Scott AFB IL 62225		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE AUG 83
		13. NUMBER OF PAGES 270
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES Limited-duty weather observation site.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		
*LISOCs	Climatology	Weather conditions
*RUSSWO	Surface winds	Relative humidity
*Climatological data	Sea-level pressure	Station pressure
Psychrometric summary	Atmospheric pressure	Ceiling versus Visibility
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report is similar to a Revised Uniform Summary of Surface Weather Observations (RUSSWO) except the summary generated is from data observed at limited-duty observation sites. This summary is blocked based on the normal hours of observation and only those tables using hourly data are presented. Caution must be exercised when using these summaries as the data reflect conditions occurring only during limited duty hours of operation. This report is a five-part statistical summary of surface weather observations for COL A J BO BAKER AAF, GERMANY (WEST)		

19. Percentage frequency of distribution tables
 Dry-bulb temperature versus wet-bulb temperature
 Cumulative percentage frequency of distribution tables

*GERMANY (WEST) DL109711
 *COL A J BO BAKER AAF
 *BAKER
 *BAKER AAF
 *BO BAKER
 *A J BO BAKER
 *A J BAKER

20. It contains the following parts: (A) Weather Conditions; (C) Surface Winds; (D) Ceiling Versus Visibility; (E) Psychrometric Summaries (psychrometric summary of wet-bulb temperature depression versus dry-bulb temperature, means and standard deviations of dry-bulb, wet-bulb and dew point temperatures and relative humidity); and (F) Pressure Summary (means, standard deviations and observation counts of station and/or sea-level pressure). Summaries in this report are presented in tabular form, in most cases in percentage frequency of occurrence or cumulative percentage frequency of occurrence tables.

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

Since Col A.J. Bo Baker AAF, DL is a part time observing station, we partitioned the data to use only those observations from 0500Z to 1900Z. The hourly data 2000Z to 0400Z were not used in the production of this summary. This is done to reduce any bias in the summaries which could result from using those infrequent observations outside the normal operating hours.

The remaining summaries contain serious misleading values that if used would present gross inaccurate climatology for the station, therefore the "ALL ALL" summaries were removed (because they do not represent the "ALL" hours summaries):

SECTION A Weather Conditions

SECTION C Surface Winds

SECTION D Ceiling Versus Visibility

SECTION E Psychrometric Summary and Relative Humidity

The remaining Hourly Summaries must be used with caution and the following values NOT USED: TOTALS, MEANS AND STANDARD DEVIATIONS. (The values are for 1900Z only and not for a 24 Hour period).

The number that identifies the station in this summary is an AWS Master Station Catalog number. This number is comprised of the WHO number with the addition of a suffix zero; or, in cases where there is no designated WHO number, a 5-digit number created in agreement with WHO rules, plus a sixth qualifying digit. These numbers (also referred to as DATSAV or USAFETAC numbers) uniquely identify each of more than 15,000 reporting stations around the world. This is the provenance of the number (e.g., MSC 999999) which will appear on future OL-A standard products.

USAFETAC

LIMITED SURFACE OBSERVATIONS
CLIMATIC SUMMARIES (LISOCs)
HOURLY OBSERVATIONS

Hourly observations are defined as those record or record-special observations recorded at established hourly intervals.

SUMMARY OF THE DAY OBSERVATIONS

Summary of the day observations are selected from all data recorded on reporting forms and combined into these observations (records, record-specials, locals, summary of day, remarks, etc.).

DESCRIPTION OF SUMMARIES

Preceding each section is a brief description of the data comprising each part of the LISOCs and the manner of presentation. Tabulations are prepared from observations recorded by stations operated by the US Services and some foreign stations using similar reporting practices.

Unless otherwise noted, the following summaries are included in this LISOCs:

PART A: WEATHER CONDITIONS	PART E: DAILY HIGH, LOW, AND MEAN TEMPERATURES
PART B: NO OR INSUFFICIENT DATA AVAILABLE*	MAX HIGH AND MIN LOW TEMPERATURES
PART C: SURFACE WINDS	PSYCHROMETRIC: DRY VS WET BULB
PART D: CEILING VERSUS VISIBILITY	MEAN AND STD DEV. (DRY BULB, WET BULB, AND DEW POINT TEMPERATURES)
SKY COVER DATA NOT AVAILABLE	RELATIVE HUMIDITY
*PRECIPITATION, SNOWFALL AND SNOW DEPTH	PART F: STATION PRESSURE
	SEA LEVEL PRESSURE DATA NOT AVAILABLE

STANDARD 3-HOUR GROUPS

All summaries requiring diurnal variations are summarized in eight 3-hour periods corresponding to the following sets of hourly observations: 0000-0200, 0300-0500, 0600-0800, 0900-1100, 1200-1400, 1500-1700, 1800-2000, 2100-2300 local standard time (LST).

STATION NO ON SUMMARY		STATION NAME		LATITUDE		LONGITUDE		STATION ELEV (FT)		CALL SIGN		WMO NUMBER	
109711		Col A J BO BAKER AAF, DL		N 42 46		E 011 36		2350		EDOV		10971	
STATION LOCATION AND INSTRUMENTATION HISTORY													
NUMBER OF LOCATION	GEOGRAPHICAL LOCATION & NAME	TYPE OF STATION	AT THIS LOCATION		LATITUDE	LONGITUDE	ELEVATION ABOVE MSL		OBS PER DAY				
			FROM	TO			STATION (FT)	ROPE BAROMETER					
1	Bad Tolz Germany	AAF	Sep 64	Feb 66	N 47 46	E 011 36	2360	2355	9 to 14				
2	No change	AAF	Mar 66	Jun 66	No chge	No chge	No chge	2351	14				
3	No change	AAF	Jul 66	Feb 68	No chge	No chge	No chge	2354	17				
4	No change	AAF	Mar 68	Dec 70	No chge	No chge	No chge	2353	13 to 17				
5	No change	AAF	Jan 71	Oct 76	No chge	No chge	No chge	2353	14				
6	No change	AAF	Nov 76	Nov 80	No chge	No chge	2350	2354	0-14				
7	Col A J BO BAKER AAF, DL	AAF	Dec 80	Jul 81	No chge	No chge	2350	2354	14				
8	Same	AAF	Jul 81	Mar 83	Same	Same	Same	Same	14				

NUMBER OF LOCATION	DATE OF CHANGE	SURFACE WIND EQUIPMENT INFORMATION				REMARKS, ADDITIONAL EQUIPMENT, OR REASON FOR CHANGE
		LOCATION	TYPE OF TRANSMITTER	TYPE OF RECORDER	HT ABOVE GROUND	
1	Sep 64 to Feb 65	Located on top of operations bldg.	AN/GNQ-11	None	46 ft	
2	Mar 65 to Feb 66	No change	No chge	None	76 ft	
3	Mar 66 to Feb 68	Located on top of control tower.	No chge	None	79 ft	
4	Mar 68 to Dec 70	No change	No chge	None	50 ft	

(OVER)

NUMBER OF LOCATION	DATE OF CHANGE	SURFACE WIND EQUIPMENT INFORMATION				REMARKS, ADDITIONAL EQUIPMENT, OR REASON FOR CHANGE
		LOCATION	TYPE OF TRANSMITTER	TYPE OF RECORDER	HT ABOVE GROUND	
5	Jan 71 to Oct 76	No change	No chge	None	50 ft	
6	Nov 76 to Mar 83	Located near midpoint rwy 03/21	No chge	RO-362	10 ft	

U S AIR FORCE
ENVIRONMENTAL TECHNICAL
APPLICATIONS CENTER

A

PART A

WEATHER CONDITIONS

This summary is a percentage frequency occurrence of various atmospheric phenomena and obstructions to vision, derived from hourly observations, and is presented in two tables as follows:

1. By month and annual, all hours and years combined.
2. By month, all years combined, by standard 3-hour groups.

A percent value of ".0" in these tables indicates less than .05 percent, which is usually only one occurrence. The various phenomena included in each category on the forms are listed below:

Thunderstorms - All reported occurrences of thunderstorm, tornado, and waterspout.

Rain and/or drizzle - All liquid precipitation, falling to the ground, not freezing.

Freezing rain and/or freezing drizzle (glaze) - Precipitation falling in liquid form, but freezing on contact with an unheated surface.

Snow and/or sleet (ice pellets) - Included are snow, snow pellets, sleet, snow grains, ice crystals, and ice pellets from Jan 68 and later. (Snow pellets also known as soft hail)

Hail - Occurrences of hail and small hail are included.

Percentage of observations with precipitation - Included in this category are the observations when one or more of the above phenomena occurred. Since more than one type of precipitation may be reported in the same observation, the sums of the individual categories may exceed the percentages of the observations with precip.

Fog - Included are fog, ice fog, and ground fog.

Smoke and/or haze - Occurrences of smoke, haze, or combinations of smoke and haze are included.

Blowing snow - Occurrences of blowing snow (also drifting snow when reported from non-WBAN sources).

Dust and/or sand - Included are blowing dust, blowing sand, and dust.

Continued on Reverse

Blowing spray - This item if reported, is not shown in a separate category on this form but is included in the computation Percentage of Observations with Obstructions to Vision, below.

Percentage of observations with obstructions to vision - Included in this category are the observations when one or more of the above obstructions to vision occurred. Since more than one type of obstruction may be reported in the same observation, the sums of the individual categories may exceed the percentage total columns. Also, although precipitation may reduce visibility, it is not considered an obstruction to vision for purposes of this summary; therefore, the percentage total of obstructions to vision need not reflect the total observations with reduced visibility.

2

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIP WEATHER SERVICE/MAC

WEATHER CONDITIONS

109710
STATION

COL A J BO BAKER AAF DL
STATION NAME

73-78,80-82
YEARS

JAN
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER
CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS (LST)	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND/OR SLEET	HAIL	% OF OBS WITH PRECIP.	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS
JAN	00-02												
	03-05												
	06-08		9.2	1.0	17.9		26.4	20.3				20.3	587
	09-11		7.0	.3	21.0		27.7	16.2	.7			16.7	599
	12-14		7.7		21.9		28.6	13.0	3.2			15.6	507
	15-17		10.0		18.6		26.7	15.2	3.4			18.4	408
	18-20		12.5		17.5		28.8	23.7	.8			24.5	257
	21-23												
TOTALS			9.3	.3	19.4		27.6	17.7	1.6			19.1	2358

2

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

WEATHER CONDITIONS

10-710
STATION

COL A J 20 BAKER AAF DL
STATION NAME

73-78,82-82
YEARS

FEB
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER
CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS 1-24	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HALE	% OF OBS WITH PRECIP	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS
FEB	00-02												
	03-05												
	06-08		8.3		20.7		27.5	25.9	.3			26.3	579
	09-11		6.6		21.5		26.1	19.7	1.2			20.9	578
	12-14		7.6		18.0		23.8	15.3	5.7			23.6	529
	15-17		7.1		18.4		23.8	13.3	7.1			20.4	407
	18-20		5.9		16.4		21.5	21.9	3.9			25.8	256
	21-23												
TOTALS			7.1		19.0		24.5	19.2	3.6			22.6	2349

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

WEATHER CONDITIONS

100710
STATION

COL A J BO BAKER AAF DL
STATION NAME

73-78, 80-82

YEARS

4A2
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS LST	THUNDER STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIL	% OF OBS WITH PRECIP	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO OF OBS
MAR	00-02												
	03-05												
	06-08		10.7		16.5		26.0	18.3	1.4			19.7	638
	09-11		9.7		16.6		25.0	10.6	6.7			17.2	639
	12-14		9.5		16.0	.2	24.0	6.6	11.8			18.2	592
	15-17		8.4		15.5		22.5	6.8	13.7			19.9	453
	18-20		7.4		15.8	.4	22.5	8.5	13.0			21.5	284
	21-23												
TOTALS			9.1		16.1	.1	24.0	10.2	9.3			19.3	2606

2

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

WEATHER CONDITIONS

19710
STATION

COL A J BO BAKER AAF DL
STATION NAME

73-78,80-82
YEARS

APR
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER
CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS LST	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIL	% OF OBS WITH PRECIP	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS
APR	00-02												
	03-05												
	06-08		10.6		22.8		32.3	16.2	1.3			17.5	606
	09-11		11.4		18.4		28.8	9.9	3.1			12.9	604
	12-14		12.2		17.0		28.3	3.2	6.8			10.0	558
	15-17		14.2		14.0		27.7	5.5	3.0			8.2	437
	18-20		18.4		13.0		31.4	3.1	3.1			6.1	261
	21-23												
TOTALS			13.4		17.0		29.7	7.6	3.5			10.9	2466

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

11

1 9710	COL A J BO BAKER AAF DL	73-78,80-82	MAY
STATION	STATION NAME	YEARS	MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER
CONDITIONS FROM HOURLY OBSERVATIONS

[illegible]

USAFETAC FORM 0-10-51 (OL A), PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
NAFETAC
A.2 WEATHER SERVICE/MAC

三

JUN
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER
CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS LST	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIL	% OF OBS WITH PRECIP	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO OF OBS
JUN	00-02												
	03-05												
	06-08	.6	21.3				21.3	10.2	1.4			11.6	629
	09-11	1.0	22.6			.2	22.6	3.1	4.3			7.9	610
	12-14	2.8	19.3				19.3	1.9	3.2			5.1	571
	15-17	4.6	25.1		.2	.2	25.3	1.8	3.2			5.0	438
	18-20	4.3	23.0			.4	23.5	2.6	2.2			4.8	230
	21-23												
TOTALS		2.7	22.3		.2	.2	22.4	3.9	3.0			6.9	2477

USAFETAC FORM 0-10-5101 A. PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

包

2

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AF WEATHER SERVICE/MAC

WEATHER CONDITIONS

109710
STATION

COL A J BO BAKER AAF DL
STATION NAME

73-78, 80-82
YEARS

JUL
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER
CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS LIST	THUNDER STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIR	% OF OBS WITH PRECIP	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS
JUL	00-02												
	03-05												
	06-08	.5	18.8				18.8	6.5	1.3			7.8	612
	09-11	.7	17.1				17.1	3.3	3.2			6.3	601
	12-14	2.0	19.3				19.3	.9	4.4			5.1	549
	15-17	4.1	18.6				18.6	1.4	2.3			3.5	488
	18-20	5.5	19.6				19.6		2.7			2.7	255
	21-23												
TOTALS		2.6	18.7				16.7	2.4	2.8			5.1	2505

2

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

WEATHER CONDITIONS

109710
STATION

COL A J BO BAKER AAF DL
STATION NAME

73-78,80-82

YEARS

AUG
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER
CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS LST	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIL	% OF OBS WITH PRECIP	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS
AUG	00-02												
	03-05												
	06-08	1.0	18.8		.2		18.9	17.1	3.0			20.1	608
	09-11	.9	16.6				16.6	8.7	7.5			15.6	577
	12-14	2.4	14.6				14.6	5.3	7.8			12.4	548
	15-17	5.1	17.0				17.0	3.8	7.7			11.3	470
	18-20	7.3	24.3				24.3	5.7	6.9			12.6	247
	21-23												
TOTALS		3.3	18.3		.0		18.3	8.1	6.6			14.4	2450

2

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

WEATHER CONDITIONS

1 9710 COL A J BO BAKER AAF DL 73-78,80-82 SEP
STATION STATION NAME YEARS MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER
CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS UT	THUNDER STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIL	% OF OBS WITH PRECIP	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO OF OBS
SEP	00-01												
	03-05												
	06-08	.2	16.9				16.9	20.4	1.5			21.9	603
	09-11	.5	17.8				17.8	10.6	3.9			14.4	596
	12-14		14.6				14.6	4.6	7.3			11.8	549
	15-17	1.3	14.3				14.3	4.3	7.4			11.7	462
	18-20	2.5	14.8				14.8	5.9	7.2			13.1	237
	21-23												
TOTALS		.9	15.7				15.7	9.2	5.5			14.6	2447



2

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

WEATHER CONDITIONS

1 4710 COL A J 80 BAKER AAF DL 73-78,80-82 OCT
STATION STATION NAME YEARS MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER
CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS LST	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIL	% OF OBS WITH PRECIP	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS
OCT	00-02												
	03-05												
	06-08		16.3	.2	3.3		18.8	23.6	.3			24.0	584
	09-11		17.6		4.2		20.8	16.8	.4			16.9	567
	12-14		12.4		3.6		15.9	12.4	1.8			14.1	548
	15-17	.2	10.4		5.6		14.2	13.3	4.5			17.6	443
	18-20	.7	12.7		5.1		16.4	21.2	4.8			26.0	292
	21-23												
TOTALS		.2	13.9	.0	4.4		17.2	17.5	2.4			19.7	2434

2

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

WEATHER CONDITIONS

159710
STATION

COL A J D BAKER AAF DL
STATION NAME

73-78,80-82

YEARS

NOV
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS LIST	THUNDER STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN & OR DRIZZLE	SNOW AND OR SLEET	HAIL	% OF OBS WITH PRECIP	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO. OF OBS
NOV	00-02												
	03-05												
	06-08		9.6	.2	15.5		23.8	20.5	.4			20.8	562
	09-11		10.8		17.3		26.6	15.5				15.5	548
	12-14		9.8		16.6		24.9	15.6	1.2			16.6	518
	15-17		15.9		16.9		29.5	15.7	2.1			17.8	421
	18-20		16.5		15.0		28.6	18.7	1.8			20.5	273
	21-23												
TOTALS			12.5	.0	16.3		26.7	17.2	1.1			18.2	2322



2

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

WEATHER CONDITIONS

109710
STATION

COL A J BO BAKER AAF DL
STATION NAME

73-78,80-82
YEARS

DEC
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE OF WEATHER
CONDITIONS FROM HOURLY OBSERVATIONS

MONTH	HOURS (LST)	THUNDER- STORMS	RAIN AND OR DRIZZLE	FREEZING RAIN 5. OR DRIZZLE	SNOW AND OR SLEET	HAIL	% OF OBS WITH PRECIP	FOG	SMOKE AND OR HAZE	BLOWING SNOW	DUST AND OR SAND	% OF OBS WITH OBST TO VISION	TOTAL NO OF OBS
DEC	00-02												
	03-05												
	06-08		6.9	.2	23.0		28.0	18.8				18.8	547
	09-11		6.3	.2	22.2		27.2	10.3	.2			10.5	591
	12-14		7.5	.4	21.2		27.3	9.6	.4			9.9	523
	15-17		11.7	.5	20.1		28.6	15.9	.3			16.1	384
	18-20		10.0	1.0	20.4		28.9	25.4	.5			25.9	201
	21-23												
TOTALS			6.5	.5	21.4		28.0	16.0	.3			16.2	2246

U S AIR FORCE
ENVIRONMENTAL TECHNICAL
APPLICATIONS CENTER

PART C

SURFACE WINDS

Presented in this part are various tabulations of surface winds as follows:

- *1. Extreme Values - Peak Gusts: Derived from daily observations and presented by individual year and month for the entire period of record available. Speeds are presented in knots, while directions are given in 16 compass points from the beginning of record through June 1968, and in tens of degrees starting in July 1968. The extreme is selected and printed from available peak gusts for each year-month, however an asterisk (*) is printed in the data block if less than 90% (3 or more missing observations) of the peak gusts are available for the month. An ALL MONTHS value is presented when every month of the year has valid observations. Means and standard deviations are also computed when four or more values are present for any column. A total raw count of valid observations is presented for each month and ALL MONTHS.

NOTE: According to Federal Meteorological Handbook No. 1 specifications (formerly Circular N), "peak gust data are recorded only at stations with continuous instantaneous wind-speed recorders."

- *2. Bivariate percentage frequency tabulations: Derived from hourly observations, these tabulations are a percentage frequency of wind directions to 16 compass points and calm by wind speeds (knots) in increments of Beaufort classifications. Percentages are shown by both directions and speed, and in addition the mean wind speed is given for each direction.

A separate category is provided on the form for variable winds, which are reported in some data sources. In these data where light and variable winds are reported with no directions but with speeds given, the speeds will be summarized in the appropriate groups opposite the column headed VRBL.

- a. Three tables are prepared for ALL WEATHER surface winds, all years combined, by: (1) Annual - all hours combined, (2) By month - all hours combined, and (3) By month - by standard 3-hour groups.
- b. A separate annual table is also presented for surface winds meeting INSTRUMENT CLASS conditions as follows: Ceiling 200 through 1400 feet inclusive with visibility equal to or greater than 1/2 mile, and/or visibility 1/2 through 2-1/2 miles inclusive with ceiling equal to or greater than 200 feet.

NOTE: A percentage frequency of ".0" in these tables represents one or more occurrences amounting to less than ".05" percent.

*Values for means and standard deviations do not include measurements from incomplete months.

GLOBAL CLIMATOLOGY BRANCH
USAFET-C
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1-710 COL A J BO BAKER AAF DL STATION NAME 77-78,82-82 YEARS JAN NORTH
ALL WEATHER CLASS 5677-2807 HOURS (LST)
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.2		.2									.7	2.5
NNE	.5											.5	2.5
NE	.2	.2										1.5	2.5
ENE	1.1	1.2	.3									3.1	3.6
E	3.4	.9	1.9									6.1	4.4
ESE	1.7	.3										2.2	2.2
SE	.7											.7	2.2
SSE	1.9	.3										2.2	2.2
S	2.4	2.4	.9		.7							6.2	4.9
SSW	1.2	3.3	2.0	.5								9.5	5.3
SW	2.7	4.3	2.9	.7								11.4	5.6
WSW	1.9	2.5	2.2	.7	.3							7.7	6.6
W	1.4	2.9	4.9	3.2	.7							13.1	9.2
WNW	.2	1.4	.7									2.5	4.5
NW	.2		.2									1.2	2.3
NNW	.7	.2										.9	2.2
VARBL		.2	1.5	1.4	1.2							4.1	13.2
CALM												28.3	
	2.1	20.5	17.7	6.3	2.4							112.2	4.3

TOTAL NUMBER OF OBSERVATIONS 566

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1 711 CEL A J 30 BAKER AAF CL STATION NAME 71-78,83-62 YEARS JA
ALL WEATHER CLASS 0900-1100
 CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.1											.1	1.0
NNE	.1	.2										1.3	2.2
NE	1.0	.3										1.3	2.4
ENE	1.0	1.0	1.0									3.4	4.6
E	1.0	1.3	1.0									4.2	4.2
ESE	2.3	.3										3.2	2.5
SE	1.0											1.3	1.8
SSE	1.0	.7	.3									2.0	3.7
S	2.8	2.0	.7	.3								5.9	4.3
SSW	1.0	1.2	1.8	.5	.2							5.5	6.5
SW	1.0	3.0	2.7	.2								7.7	5.5
WSW	.0	2.7	4.7	.7								8.5	7.2
W	2.0	2.8	5.7	2.8	.8	.3						16.1	6.5
WNW	.3	1.3	.0	.2	.2							3.2	5.3
NW	.3	1.0	.2									1.8	4.3
NNW	.5	.5		.7								1.2	4.4
VARBL			1.7	1.5	1.3							4.5	13.5
CALM												27.5	
	21.0	10.9	20.4	6.4	2.5	.3						100.0	4.4

TOTAL NUMBER OF OBSERVATIONS 578

CLIMATE CLIMATOLOGY BRANCH
 USAFETAC
 AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
 DIRECTION AND SPEED
 (FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 71 STATION NAME COLA WIND BAKE 2 AAF CL YEARS 71-72, 80-82 NORTH 122-142
 CLASS ALL WEATHER HOURS (L & T)
 CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.2											2.4	2.2
NNE	.6	1.0	.3									2.4	3.1
NE	.5	1.0	.6									2.2	4.3
ENE	2.2	2.5	1.9	.4								6.9	3.3
E	4.2	2.4	1.7	.2								7.4	3.9
ESE	1.6											1.4	2.0
SE	1.4											1.4	1.9
SSE	1.7											1.2	1.6
S	2.7	1.7	.6	1.0								4.5	6.2
SSW	1.4	1.0	1.8	.2								4.3	5.6
SW	1.5	2.5	1.4									5.5	4.8
WSW	1.2	4.2	2.4	1.5	.2							5.9	6.7
W	3.4	4.5	5.1	3.2	.2							16.4	7.1
WNW	1.0	2.4	.6	.6								4.7	5.5
NW	1.4	1.2	.2	.2								3.2	4.3
NNW	1.2	.4										1.5	2.6
VARBL			1.7	2.6	1.6	.2	.2					5.5	14.6
CALM												3.9	
	20.1	24.9	17.4	9.3	2.7	.2	.2					122.2	4.5

TOTAL NUMBER OF OBSERVATIONS 526

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION 11710 COL A JSC BAKER AAF DL 73-75, 82 YEARS JAN MONTH 1900-1900 HOURS (LST) CLASS ALL WEATHER CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.7	.2										1.9	2.8
NNE	1.7	.7	.2									2.6	2.9
NE	1.7	.7	1.2									3.7	4.6
ENE	2.7	3.2	1.6	.6								7.9	4.9
E	2.7	5.7	2.2	.7								10.7	5.5
ESE	.		.2									.7	4.3
SE	1.2											1.2	2.6
SSE	1.7			.7								1.7	3.4
S	1.7	1.7										2.7	3.3
SSW	1.7	1.7	.6	.2								4.2	4.7
SW	2.7	3.2	1.6	.2								5.1	4.5
WSW	2.7	3.2	3.7	.7	.2							10.3	6.2
W	2.7	3.2	4.7	1.6								11.1	6.6
WNW	.7	2.7	1.0	.2								5.4	4.6
NW	1.2	1.7										3.2	3.6
NNW	.7	.2	.2									1.0	3.8
VARBL		.2	3.7	3.2	1.2							6.4	12.1
CAIM												17.5	
	20.6	27.8	2.0	6.7	1.5							100.0	4.8

TOTAL NUMBER OF OBSERVATIONS 476

CENTRAL CLIMATOLOGY BRANCH
AFETAC
AIR WEATHER SERVICE/AFAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 711 WIL A WOOD LAKE AAF IL 73-70.00 YEARS 1A
STATION NAME ALL WEATHER MONTH 1000-2000
CLASS ALL WEATHER HOURS (L & T)
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.2											1.2	2.3
NNE	.	.										1.2	2.7
NE		1.2										1.2	3.2
ENE	2.7	.	.4	.4								4.7	4.6
E	3.2	.4	2.7									9.4	4.6
ESE	1.2											1.6	2.6
SE	.											.3	2.2
SSE	2.3											2.3	1.2
S	.3	1.6	.4	.4	.4							2.1	5.5
SSW	1.2	1.2	1.2	.4								4.3	5.9
SW	2.0	3.7	.6									6.3	4.9
WSW	3.2	5.8	2.7	.6								12.3	6.3
W	2.0	4.7	4.7	2.3								13.7	7.4
WNW	.4	1.6	.4									2.3	4.5
NW	.	.4										1.2	3.2
NNW	.4		.4									.5	5.5
VARBL			3.6	3.6	.6							6.8	11.7
CALM												2.3	
	27.0	23.0	17.2	6.6	1.2							100.0	4.6

TOTAL NUMBER OF OBSERVATIONS 251

GENERAL CLIMATOLOGY BRANCH
USAFETAC
ATTN: WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 710 COL A J CO BAKER AAF CL STATION NAME 73-76, 80-42 YEARS JAN MONTH ALL DAY HOUR

ALL WEATHER CLASS

CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.0	.0	.0									.7	3.1
NNE	.0	.4	.2									1.4	3.4
NE	.0	.7	.3									1.1	3.9
ENE	.1	1.7	1.0	.7								.1	4.6
E	.0	2.4	1.7	.1								7.1	4.5
ESE	1.6	.3	.7									1.9	2.4
SE	1.0											1.0	2.0
SSE	1.0	.3	.1	.0								2.0	2.3
S	.3	1.7	.6	.3	.1							5.0	4.9
SSW	.0	1.7	1.6	.4	.0							5.9	5.6
SW	.1	3.4	2.9	.2								7.8	5.2
WSW	1.7	3.0	3.1	.8	.2							9.1	6.5
W	.3	3.4	5.1	2.6	.4	.1						14.0	7.9
WNW	1.1	1.7	.7	.2	.0							3.7	5.1
NW	.0	.7	.1	.0								1.0	3.9
NNW	.7	.7	.1	.0								1.1	3.4
VARBL		.1	2.1	2.3	1.2	.0	.0					5.7	13.0
CALM												24.4	
	24.7	22.7	18.7	7.3	2.0	.1	.0					122.0	4.6

TOTAL NUMBER OF OBSERVATIONS 2352

U.S. AIR FORCE
 AIRCRAFT
 WEATHER SERVICE

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION NAME LAKE AAF DL YEARS 73-78, 80-82 ELEVATION 5000-5000
 STATION ALL WEATHER CLASS BOB (LST)
 CONDITION

SPEED KNTS D/R	1-3	4-6	7-10	11-16	17-21	22-27	28-33	34-40	41-47	48-55	≥56	%	MEAN WIND SPEED
N	.											1.2	1.5
NNE	.											1.2	2.1
NE	.			.7								1.7	6.4
ENE	.1	1.1	1.4									2.2	4.4
E	.	2.1	2.9	.7								3.7	5.2
ESE	.	.										1.1	2.2
SE	1.1	.										1.9	2.7
SSE	.	.	.2									2.1	2.9
S	.	1.2	.7									2.2	3.1
SSW	1.7	4.7	1.1	1.2								5.7	6.7
SW	.	2.4	2.4	1.2	.2							3.1	6.6
WSW	1.1	3.2	1.3	.9								4.2	5.4
W	1.1	2.7	4.7	.7	.2							12.4	6.9
WNW	.	1.4	.9	.2								2.3	5.6
NW	.	.										.3	1.5
NNW	.	.										.3	2.5
VARBL				.7	.2							1.0	14.7
CALM												1.0	
		1.3	7.5	5.4	.5							12.2	1.8

TOTAL NUMBER OF OBSERVATIONS 577

CENTRAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAL

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

71. COL A J L BAKER AAF DL 77-76.62-92
STATION STATION NAME YEARS
ALL WEATHER CLASS
1940-1990
HOURS (L & T)
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.1	.2										.3	2.2
NNE	.1	.1	.5									.7	4.0
NE	1.3	2.6	2.8	.5								6.2	4.3
ENE	.3	2.6	2.8	.5								6.2	5.5
E	.2	1.9	2.1	.7								5.9	4.2
ESE	1.8	.5	.2									2.5	2.8
SE	1.4											1.4	2.0
SSE	.3	.2	.2									.9	4.0
S	.3	1.4	.2									1.8	5.1
SSW	2.1	.1	1.2	.9	.2							5.6	7.4
SW	.9	2.3	2.1	.2								5.4	5.9
WSW	1.4	2.1	2.6	1.6								7.1	5.5
W	1.2	3.0	4.5	2.8	.5							12.0	5.5
WNW	.9	1.9	1.0	.2								4.7	6.2
NW	.3	1.0	.2									1.4	4.5
NNW	.5											.7	1.7
VARBL			.5	.2								1.2	5.0
CALM												2.1	
	23.1	1.9	19.4	6.4	.9	.2						100.0	4.0

TOTAL NUMBER OF OBSERVATIONS 576

CENTRAL CLIMATOLOGY BRANCH
AFETAC
AIR WEATHER SERVICE/PAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1710 ALL A W 2 BAKER AAF CL STATION NAME 73-76,82-82 YEARS 1900-1952 MONTH ALL
CLASS EAT-EP
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.1	.7										1.7	2.1
NNE	.5	.5	.2									2.1	4.1
NE	1.1	1.7	.6	.2								3.1	4.9
ENE	1.3	5.1	3.2	1.7	.2							14.2	5.9
E	4.1	2.1	4.2	1.9								12.3	4.3
ESE	1.1		.2									1.3	2.1
SE		.1										.2	4.2
SSE	.1	.4										.5	2.7
S	.6	.7	.2		.2							1.5	4.9
SSW	.1	.2	.6		.4	.2						2.1	2.5
SW	.1	1.7	1.5	.2								4.2	6.2
WSW	.1	1.7	1.1	.2								3.5	5.7
W	1.1	4.1	6.6	2.6	1.3	.2						17.2	6.6
WNW	.3	3.4	1.1	.6								7.4	5.2
NW	.1	1.7	.8									3.3	3.7
NNW	1.2	.1	.2									2.3	3.3
VARBL			.2	.4								1.1	1.5
CALM												19.1	
	24.2	25.7	21.2	7.4	2.1	.4						100.2	5.2

TOTAL NUMBER OF OBSERVATIONS 527

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AF WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 14710 COL A J DO BAKER AAF DL 77-76,80-22 FEH
STATION NAME YEARS MONTHS (L.Y.)
ALL WEATHER
CLASS
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	MEAN WIND SPEED
N	1.2	1.5									2.7	3.5
NNE	1.2	1.2	.2								2.7	4.3
NE	1.2	3.2	.5								5.9	4.1
ENE	5.7	6.2	5.4	1.2	.2						18.9	5.8
E	7.7	3.7	7.9	7.2							17.5	7.4
ESE	.5	.5									1.0	2.8
SE	.7										.7	1.7
SSE		.5									.2	4.5
S	.2	.7		.5	.2						1.7	9.4
SSW	.7	.5	.5	.5	.2						2.0	8.5
SW	.7		.7	.5							2.0	7.5
WSW	1.7	2.7		.5							3.2	4.5
W	1.7	4.4	3.7	2.0	.5						12.3	7.5
WNW	1.7	2.7	.2	.5							4.9	4.8
NW	3.2	1.5	1.0								5.7	3.9
NNW	3.2	.7	.2								4.2	2.8
VARBL			.5	.2	.2	.2					1.2	14.4
CALM											13.1	
	20.7	29.1	21.0	8.4	1.5	.2					100.0	5.2

TOTAL NUMBER OF OBSERVATIONS 405

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 00210 COL A J 00 JAFET AAF DL STATION NAME 73-76,65-32 YEARS 1960-1969 NORTH
CLASS ALL DATA HOURS (LST) 1800-2500
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	2.2											1.2	2.3
NNE	.1											1.2	2.3
NE	.1	3.1										4.3	2.9
ENE	2.7	6.6	2.7	.8								12.9	5.5
E	2.7	6.6	6.6	2.0								18.1	6.6
ESE		.4	.4									1.7	2.9
SE												.1	1.0
SSE	1.1											1.2	2.2
S	.4	.4		.4		.4						1.2	11.3
SSW		1.0										2.3	4.2
SW	1.1	2.3	.4									4.3	4.2
WSW	.3	3.1	1.6	1.2								8.2	5.7
W	1.2	2.7	3.1	.8								7.8	7.2
WNW	1.2		.4									2.3	4.7
NW				.4								1.2	5.3
NNW		.4	.4									1.0	4.3
VARBL			.4		.4							.2	14.0
CALM												25.4	
	23.4	28.5	16.1	5.5	.4	.4						120.2	4.1

TOTAL NUMBER OF OBSERVATIONS 256

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 710 STATION NAME COL A JCS BAKER AAF DL YEARS 77-78, 80-82 MONTH ALL
CLASS ALL WEATHER
CONDITION ALL
HOURS (L & T) ALL

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.7	.5										1.2	3.1
NNE	.5	.5	.1									1.4	3.5
NE	1.4	1.5	.5	.1								3.5	4.4
ENE	5.3	4.7	3.0	.7	.1							11.1	5.6
E	4.3	2.3	4.2	1.5								12.5	6.0
ESE	1.5	.3	.1									1.9	2.6
SE	.7	.5										1.1	2.3
SSE	.7	.3	.1									1.1	3.1
S	1.7	.7	.5	.1	.1	.7						3.5	4.4
SSW	1.2	1.7	.8	.5	.2	.1						4.5	6.9
SW	1.2	1.7	1.7	.4	.7							5.1	6.1
WSW	1.4	2.4	1.9	.7								5.3	6.2
W	1.5	3.6	4.7	1.9	.6	.7						12.4	6.0
WNW	1.5	2.1	.8	.3								4.5	5.3
NW	1.4	.5	.4	.0								2.7	3.9
NNW	1.1	.4	.1									1.5	3.0
VARBL			.7	.3	.1	.7						.9	11.9
CALM												24.6	
	24.5	23.9	19.1	6.6	1.1	.7						100.0	4.4

TOTAL NUMBER OF OBSERVATIONS 2343

CENTRAL CLIMATOLOGY BRANCH
AFETAC
AIR WEATHER SERVICE/PAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1 710 STATION NAME DEL A J 30 BAKER AAF DL YEARS 73-74, 80-82 MONTH MAY
CLASS ALL - FEATHERED HOURS (LST) 0600-2000
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.1	.3										.4	3.6
NNE	.1		.5									.7	5.2
NE	.1	.7	.5									1.4	4.4
ENE	1.1	.7	.5	.3								2.6	5.1
E	.2	1.6	1.9	.9								6.6	6.2
ESE	1.4	.2										1.6	2.2
SE	.1	.2	.2									1.3	3.3
SSE	.3	.5	.2									1.0	2.5
S	2.4	1.4	.3	1.1								5.2	5.4
SSW	1.3	3.5	.9	.7	.3	.2						5.9	5.3
SW	3.1	4.4	3.5	1.4								12.9	6.0
WSW	1.7	4.6	1.6	.9	.2							6.9	5.9
W	2.4	3.4	2.4	1.6	.3							10.2	5.7
WNW	.1	.1	.8	.3	.2							2.3	5.8
NW	.5	.3	.3									1.4	3.9
NNW	.1	.5	.3									1.4	4.3
VARBL			.6	.8								1.4	11.6
CALM												71.0	
	24.2	22.9	14.3	7.7	.9	.2						120.2	4.5

TOTAL NUMBER OF OBSERVATIONS 437

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

STATION 710 STATION NAME 01L A J 80 AKES BAF FL YEARS 73-78, 81-92 MAP NORTH
CLASS ALL WEATHER
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.0	.2										1.2	2.4
NNE	.2	.2										1.7	5.5
NE	.2	1.1	1.3									2.7	6.6
ENE	1.0	1.0	1.4	.3								5.5	5.1
E	2.7	1.3	2.5	1.6								1.3	7.2
ESE	1.0											1.0	2.0
SE	.2											.2	2.0
SSE	1.0	.0	.2									2.4	3.3
S	.2	1.1	.2	.9								4.4	5.3
SSW	1.0	1.6	.9	.5								4.7	5.3
SW	1.4	3.6	2.5	1.3	.2							9.0	6.0
WSW	1.7	3.3	.9	.6	.5							7.4	6.3
W	2.7	4.7	4.6	1.6	.9	.3						15.0	7.7
WNW	1.4	2.2	.9	.2	.3							5.0	5.7
NW	1.0	1.7	.5	.2								3.5	4.5
NNW	.2	.5	.3									1.0	4.3
VARBL			.2	.0								1.7	11.0
CALM												23.5	
	22.3	24.7	17.8	8.3	1.0	.3						170.2	4.7

TOTAL NUMBER OF OBSERVATIONS 635

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/HAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 100710 011700 000000 BAKES AAF DL 73-76.81-62 73-76.81-62 73-76.81-62
STATION NAME CLASS MONTH
ALL WEATHER
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.1	2.2	.7									4.2	4.3
NNE	.2	.5	.7									3.4	3.5
NE	1.1	1.7	1.2	1.0								4.1	4.6
ENE	3.2	3.7	2.2	1.0								12.2	5.6
E	.2	4.4	5.1	2.9								14.6	7.5
ESE		.										.3	5.5
SE		.											4.2
SSE		.											4.2
S	.	1.2	.3	.3								2.2	2.4
SSW	.7	.7	1.2	.3								2.3	7.4
SW	.7	1.2	2.2	.7								4.1	7.2
WSW	.7	2.2	1.0	.5	.2							4.5	6.8
W	3.7	5.3	3.4	3.0	.7	.2						15.7	7.6
WNW	1.2	2.7	1.9	1.4	.3							7.6	7.4
NW	2.7	2.7	2.4	.5								3.3	6.5
NNW	1.5	1.0	.2	.2								2.7	4.2
VARBL			1.2	.5	.7							2.7	12.6
CALM												1.0	
	10.0	31.1	23.5	12.4	1.9	.2						100.0	5.9

TOTAL NUMBER OF OBSERVATIONS 501

GENERAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION 171 COL A J B BAKER AAF DL STATION NAME 77-78,80-92 YEARS MAC MONTH 1500-1700 HOURS (LST)

CLASS ALL EATHER

CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.5	2.2	.4									4.2	4.1
NNE	1.5	1.5	.4	.2								3.8	4.4
NE	1.5	1.6	2.2									5.1	5.9
ENE	2.6	5.7	4.4	1.6	.2							14.9	6.4
E	1.5	5.3	5.7	2.7								17.8	7.7
ESE	.4	.2	1.1									1.8	6.3
SE	.2											.2	2.5
SSE	.2											.2	3.7
S	.4	.2	1.3	.7								2.7	5.1
SSW	.7	.9	.7	.7								2.9	6.7
SW	.7	.9	.2	.4								2.2	6.2
WSW	.4	2.7	2.0	.7	.2							3.3	7.4
W	1.7	4.4	2.0	1.6	.7							11.0	7.7
WNW	1.6	4.7	1.8	2.0								13.0	6.9
NW	2.2	2.9	2.7	.2								7.1	5.5
NNW	1.5	1.8	1.1	.4								5.1	5.3
VARBL		.7	1.3	.4	.2							2.2	10.8
CALM												4.2	
	17.1	34.7	29.1	11.6	1.3							100.0	6.4

TOTAL NUMBER OF OBSERVATIONS 450

GLOBAL CLIMATOLOGY BRANCH
SAFETAC
AIR WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION 1-712 COL A W B BAKER AAF DL STATION NAME 73-78,80-92 YEARS 1977-2000
CLASS ALL WEATHER HOURS (L S Y) 1977-2000
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.4	.4										2.3	2.7
NNE	.4	1.1	.4									1.5	4.6
NE	1.4	2.5	.4									4.2	4.3
ENE	.7	4.6	1.4	.4								11.7	4.4
E	4.4	7.4	4.2	2.8								19.1	6.2
ESE	1.4	.4	.4									2.1	4.2
SE			.4									.4	5.2
SSE	.7	.7										1.4	3.3
S	.7	.4	.7									2.2	5.2
SSW	1.1	3.2	.4									4.6	5.2
SW	2.1	1.4	2.1	.4								5.4	5.6
WSW	1.4	3.2	.7									5.2	4.6
W	2.1	2.1	2.5	1.4	.7							8.8	7.8
WNW	1.2	3.2	1.1									7.4	4.3
NW	1.4	1.6	2.1									5.7	5.5
NNW	1.4	.7		.4								2.2	4.4
VARBL			1.4									1.4	9.4
CALM												13.4	
	20.3	33.2	16.0	5.3	.7							100.0	4.7

TOTAL NUMBER OF OBSERVATIONS 283

U.S. AIR FORCE
 CLIMATE DIVISION
 AFETAC
 WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
 DIRECTION AND SPEED
 (FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1001 1001 A J 10 1001 AAF 11 71-78, 60-12 YEARS
 STATION NAME NORTH
 ALL WEATHER CLASS
 ALL
 HOURS (L & T)
 CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.2	1.1	.2									2.5	3.2
NNE	1.1	.5	.6	.7								3.1	4.4
NE	.3	1.2	1.1	.7								3.4	5.2
ENE	2.7	3.7	1.9	.7	.7							1.2	5.6
E	2.5	3.4	4.1	2.1								12.1	7.1
ESE	.	.2	.2									1.2	3.7
SE	.4	.2	.1									.7	3.2
SSE	1.7	.4	.1									1.2	3.8
S	1.7	1.2	.5	.7								3.2	5.3
SSW	1.2	1.2	.2	.4	.1	.						4.2	5.7
SW	1.7	2.6	.2	.6	.2							7.4	6.4
WSW	1.2	3.2	1.2	.6	.2							3.2	6.2
W	.3	4.4	3.1	1.2	.7	.1						12.4	7.5
WNW	1.7	2.5	1.3	.6	.2							3.2	6.2
NW	1.7	1.2	1.3	.2								1.2	5.2
NNW	1.1	1.2	.4	.2								2.7	4.2
VARBL		.	1.2	.7	.2							1.2	11.4
CALM												17.8	
	22.7	28.4	20.2	9.3	1.4	.2						100.0	5.1

TOTAL NUMBER OF OBSERVATIONS 7506

CENTRAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1 725 STATION NAME 77-76 MC-52 YEARS 77-76 MC-52
CLASS ALL WEATHER
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	MEAN WIND SPEED
N												1.0
NNE	1.2											1.2
NE	1.3											1.2
ENE	1.1	1.7										1.2
E	1.7	1.5	2.3	1.0								1.2
ESE												1.2
SE												1.2
SSE												1.2
S												1.2
SSW	5.7	3.5										1.2
SW	1.1	3.1	3.3									1.2
WSW	1.1	3.1	1.5									1.2
W	1.1	4.0	5.3									1.2
WNW	1.7	2.2										1.2
NW	1.1	1.1										1.2
NNW	1.2											1.2
VARBL			1.1									1.2
CALM												1.2
	25.2	26.2	15.8	3.7								1.2

TOTAL NUMBER OF OBSERVATIONS 500

U.S. AIR CLIMATOLOGY BRANCH
 AFMPC
 AIR WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION 1011 UPL AFB - BAKER AAF FL 77-7E, 60-02 AP
 STATION NAME YEARS MONTH
ALL WEATHER
 CLASS
1950-1970
 HOURS (L & T)
 CONDITION

SPEED (KNTS) DIR	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	3.0	1.7	.7									6.2	3.4
NNE	1.7	.5	.3	.2								3.0	4.2
NE	1.2	3.5	.7	.7								5.7	5.4
ENE	.7	2.5	2.5	.7								7.7	6.0
E	1.0	2.7	5.5	.3								12.0	7.6
ESE	.7	.3										1.3	2.7
SE	.7											.8	2.0
SSE	.7	.7										1.2	2.7
S	.7	.3	.3	.7								2.3	7.6
SSW	1.2	1.2	.5									2.3	4.4
SW	1.7	1.5	2.2	.5								6.5	5.7
WSW	1.0	3.0	2.2	.2								6.0	5.7
W	.7	4.5	6.2	1.3								15.0	6.7
WNW	1.7	2.5	3.8	.3								7.3	6.0
NW	1.0	2.6	.7	.2								5.2	4.6
NNW	1.0	1.2	.3									3.3	3.7
VARBL			.7	1.5	.2							2.7	12.2
CALM												10.0	
	24.1	31.1	26.1	8.5	.2							100.0	5.4

TOTAL NUMBER OF OBSERVATIONS 601

JOINT CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION 711 STATION NAME COL A JESSE BAKER AAF DL YEARS 77-78, 80-82 MONTH AP
CLASS ALL WEATHER HOURS (LST) 1200-1400
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.2	2.4	.5	.2								3.1	4.5
NNE	1.1	1.4	1.1									3.6	4.7
NE	1.1	2.2	2.7	.4								4.5	6.1
ENE	1.4	2.3	6.5	2.1								12.3	7.7
E	2.2	3.4	5.4	4.3								12.4	6.1
ESE	.7	.4										1.1	3.3
SE	.1	.2										.1	3.0
SSE	.1	.2										.1	3.0
S	.1	.3	.4									1.1	5.2
SSW	.4	1.6	1.6									3.6	6.2
SW		.7	.9									1.6	7.1
WSW	.4	1.6	1.1	.7								2.1	7.2
W	2.2	4.7	5.8	2.0	.2							14.3	7.4
WNW	2.9	3.8	3.4	1.3								11.4	6.3
NW	.6	1.4	1.3	.4								5.2	5.7
NNW	1.2	1.3	1.4									4.0	5.2
VARBL		.1	4.3	.9								2.4	9.3
CALM												.2	
	17.7	30.7	37.1	12.1	.2							100.0	6.7

TOTAL NUMBER OF OBSERVATIONS 553

CENTRAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAF

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1717 COL AFB D FAKA AAF DL 77-77,80-92 AP NORTH
STATION NAME YEARS
ALL WEATHER CLASS 1972-1990
HOURS (LST)
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	MEAN WIND SPEED
N	.2	1.0	.6									2.7
NNE	.7	.2	1.4	.2								2.3
NE	1.4	2.1	2.2	.7								7.4
ENE	.2	3.0	6.9	2.7	.2							14.0
E	.3	2.5	5.3	3.6								14.0
ESE	.2		.5									.7
SE	.2	.2										.7
SSE												
S	1.0	.7	.2	.2								3.9
SSW		2.0	1.4									3.9
SW	.7	2.3	.7									3.7
WSW	.2	1.1	.2									2.3
W	2.0	6.9	5.1	2.1								16.8
WNW	1.4	2.5	2.8	.6								7.6
NW	1.1	3.0	2.8	.2								7.1
NNW	.7	1.4	.7	.7								3.0
VARBL			3.0	2.1								6.0
CALM												4.4
	14.0	32.3	26.6	13.6	.2							120.2

TOTAL NUMBER OF OBSERVATIONS 435

U.S. AIR FORCE
 USAFETAC
 AIR WEATHER SERVICE / IAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION IAC STATION NAME CLAUDE BAKER AAF DL YEARS 77-77, 81-82 MONTH APR

CLASS ALL WEATHER MOVER (L E Y) 18.0-2000

CONDITION _____

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.2	1.2	1.2									3.2	4.5
NNE	.4	.4										.2	3.5
NE		1.2	1.5									4.2	5.7
ENE	1.2	4.6	5.5	.8								12.4	6.7
E	1.2	.6	12.0	1.9								15.1	7.6
ESE	.6											.4	2.2
SE		.4										.4	4.2
SSE													
S	1.2	.4	1.2									3.1	4.5
SSW	1.1	3.6	1.2									5.1	4.3
SW	.4	3.6	.4									4.5	4.6
WSW	1.2	4.2	.6									5.2	4.4
W	2.3	5.0	3.9	1.5								8.7	6.3
WNW	.4	2.7	2.3	.4								5.2	6.4
NW	1.2	1.2	1.2									4.2	4.7
NNW	2.7	.4	.9									3.5	2.1
VARBL			2.3	.8								3.1	2.5
CALM												7.7	
	11.3	35.1	32.4	5.4								100	5.5

TOTAL NUMBER OF OBSERVATIONS 200

GENERAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION 1710 COL A J SO BAKER AFB DL STATION NAME 71-78,80-2 YEARS APR
 MONTH BORTH
 CLASS ALL WEATHER
 HOURS (LST) ALL
 CONDITION

SPEED (KNTS) DIR	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.0	1.0	.6	.0								3.6	4.1
NNE	1.2	.7	.6	.1								2.6	4.5
NE	1.0	2.1	1.5	.3								4.4	5.9
ENE	1.0	2.7	4.1	1.3	.0							9.7	7.1
E	1.0	2.6	5.1	2.7								12.4	7.6
ESE	.0	.0	.1									.3	3.2
SE	.4	.2										.5	2.6
SSE	.0	.2										.3	2.9
S	1.7	.9	.4	.4								3.3	4.0
SSW	1.1	2.4	1.0									5.4	4.5
SW	1.0	2.7	1.9	.1								5.7	5.7
WSW	1.0	2.7	1.4	.2								5.3	5.6
W	2.3	5.0	5.4	1.5	.0							14.3	6.0
WNW	1.0	2.7	3.3	.6								7.4	6.0
NW	1.2	2.1	1.2	.2								5.2	5.2
NNW	1.4	.0	.6	.0								2.9	4.3
VARBL		.0	2.4	1.1	.0							3.6	10.0
CALM												11.5	
	11.0	30.1	28.6	8.6	.1							120.9	5.5

TOTAL NUMBER OF OBSERVATIONS 2486

U.S. AIR FORCE CLIMATOLOGY BRANCH
AF-TAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 711 COL A W L C BAKER AAF DL STATION NAME 73-78.67-52 YEARS 1950-1955 DAY 1800-0000
CLASS ALL-WEATHER HOURS (L & T)
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.1	.5										.2	3.5
NNE	.1	.3		.1								.2	5.2
NE	1.4	.2	.5									2.2	3.6
ENE	1.1	2.0	1.1									4.4	4.9
E	1.1	1.7	2.5	.6								6.4	6.9
ESE	.1	.3		.2								.2	5.0
SE	.1	.7										1.1	4.7
SSE	1.7	.2										1.3	2.3
S	3.1	1.4	.8		.2							5.7	3.5
SSW	1.1	2.7	.8	.6	.2							7.4	2.2
SW	3.4	4.7	1.6	.3								12.2	4.7
WSW	3.1	4.4	.6									5.2	3.9
W	4.7	5.3	2.8	.2								12.1	4.7
WNW	1.0	1.1	1.3									3.9	5.0
NW	.7	.5	.3									1.5	5.1
MNW	.5		.2									.9	5.2
VARBL			.7									.3	5.0
CALM												29.7	
	29.2	25.8	12.9	2.2	.2							100.7	3.3

TOTAL NUMBER OF OBSERVATIONS 436

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1 710 COL A J C RAKE AAF DL STATION NAME 77-78.87-82 YEARS DAY MONTH 1233-1400 HOURS (LST)

ALL WEATHER CLASS

CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.1	2.5	.8	.2								5.5	4.7
NNE	1.1	2.3	.3									3.3	4.1
NE	1.1	3.4	1.1	.5								7.2	5.1
ENE	1.1	4.6	7.2	.8	.7							14.3	6.9
E	1.1	3.2	6.4	2.6	.7							14.3	5.5
ESE		.2	.7	.3								1.1	7.3
SE		.5	.2									1.1	4.7
SSE		.7	.7									1.2	4.3
S		.3	.3									1.1	4.6
SSW	1.0	.7	1.0	.2	.2							1.1	6.1
SW	.7	1.5	1.0									2.2	5.7
WSW	.1	2.3	1.7									5.7	4.5
W	1.1	4.1	3.8	.7								12.4	6.2
WNW	1.1	4.6	3.1	.8	.7							12.5	6.4
NW	1.1	2.6	1.5	.5								5.7	5.6
NNW	1.1	2.5	.2									4.1	3.9
VARBL			3.3	.8								4.1	7.2
CALM												3.1	
	10.5	36.4	33.6	7.4	1.1							120.2	4.1

TOTAL NUMBER OF OBSERVATIONS 610

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 10710 COL A J B O BAKER AAF DL STATION NAME 73-77,80-82 YEARS 44
MONTH 1500-1700
CLASS ALL WEATHER
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.7	2.4	.9									4.3	4.7
NNE	1.7	1.7	.9	.4								4.5	5.1
NE	.6	2.4	1.9									4.9	5.6
ENE	2.4	3.0	4.9	1.7								12.7	6.0
E	1.7	4.7	6.9	7.0	.2							16.6	7.9
ESE	.4	.4	.6									1.5	5.0
SE		.4										.6	4.0
SSE	.7	.4	.6	.2								1.5	7.1
S	1.1	1.7	.9	.2								3.9	5.1
SSW	.7	2.4	2.2	.2								5.6	6.2
SW	.7	1.7	.4	.2								2.5	5.9
WSW	2.2	1.0	.9									4.9	4.3
W	1.7	3.7	3.4	.6								9.5	6.1
WNW	1.7	3.2	2.2	1.1								3.0	5.4
NW	1.7	2.4	.9									5.2	4.8
NNW	1.7	1.7	.9									4.1	4.6
VARBL			3.7	1.3								4.9	9.6
CALM												4.1	
	10.1	35.5	32.0	9.0	.2							100.0	5.0

TOTAL NUMBER OF OBSERVATIONS 465

CLIMATOLOGY BRANCH
METAC
AIR WEATHER SERVICE / MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 717 COL A J SO BAKER AAF DL STATION NAME 73-77, 81-82 YEARS MAY MONTH 1900-2000 HOURS (L.S.T.)
ALL WEATHER CLASS
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.2	.4	1.2									2.1	4.3
NNE		1.2	.6									2.7	5.9
NE	2.3	1.2	1.6									5.2	4.7
ENE	2.7	7.8	5.2									16.7	5.9
E	.6	6.6	6.6	1.2								22.2	5.7
ESE	1.2	.4	.4									3.3	3.7
SE	1.2		.4									1.2	4.3
SSE	.4	.4	.4									1.2	2.3
S	1.3	2.3	.6									2.4	4.4
SSW	1.2	3.9	2.7	.8								1.9	6.2
SW	1.2	1.2	.4									3.2	4.7
WSW	.6	3.6	.4									4.7	5.5
W	1.2	7.1	3.1	.4								6.6	6.2
WNW	.6	1.2	2.3									4.3	6.2
NW	2.7	1.6	.8									5.1	4.4
NNW	.6	.6	1.2									6.7	5.4
VARBL			.6	1.2								1.9	10.5
CALM												6.6	
	21.2	38.1	3.2	3.5								122.2	5.3

TOTAL NUMBER OF OBSERVATIONS 257

CLIMATOLOGY BRANCH
USAFETAC
AF WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1 710 COL A J D BAKER AAF DL STATION NAME 73-76,80-62 YEARS MAY NORTH ALL HOURS (LST)

ALL WEATHER CLASS

CONDITION

SPEED (KNTS) DIR.	1-3	4-6	7-10	11-16	17-21	22-27	28-33	34-40	41-47	48-55	≥56	%	MEAN WIND SPEED
N	1.4	1.5	.5	.7								3.8	4.3
NNE	1.0	1.5	.4	.1								3.3	4.6
NE	1.2	1.4	1.5	.2								4.7	5.5
ENE	.3	4.3	5.7	.7	.1							11.3	5.4
E	1.4	3.1	4.9	1.6	.3							11.3	7.8
ESE	.7	.5	.4	.7								1.8	6.3
SE	.7	.2	.2									.3	4.2
SSE	.7	.3	.2	.6								1.2	4.3
S	1.7	1.2	.5	.7								3.3	4.2
SSW	1.7	2.1	1.4	.4	.1							5.9	5.7
SW	1.7	2.4	1.0	.1								5.0	5.1
WSW	.2	3.1	1.2									6.3	4.5
W	2.7	4.8	3.3	.5								11.4	5.6
WNW	2.4	2.3	2.0	.5	.7							7.3	5.6
NW	1.2	1.7	.8	.2								4.0	5.1
NNW	1.1	1.3	.3	.7								2.6	4.2
VARBL		.7	2.0	.6								2.6	9.3
CALM												12.1	
	23.2	32.0	25.8	5.3	.5							100.0	5.1

TOTAL NUMBER OF OBSERVATIONS 2606

OFFICIAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/AFAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 15710 COL A J D BAKER AAF DL STATION NAME 73-76.5-62 YEARS 1953-1962 MONTHS 12
CLASS ALL WEATHER HOURS (LST) 1432-0000
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.1											.3	1.8
NNE	1.0											1.0	2.2
NE	.5											.5	2.7
ENE	1.5	.2	.2									1.9	2.9
E	1.1	1.0	1.4									3.5	3.2
ESE	.1	.2										1.3	2.0
SE	.8	.2										.8	2.2
SSE	.2											.5	1.3
S	4.3	.6										5.0	2.1
SSW	4.5	3.7	1.1	.3								10.0	4.2
SW	4.5	4.5	1.3	.3								12.6	4.4
WSW	5.6	4.5	1.0	.2								11.3	3.8
W	4.2	7.2	2.1	.3								13.8	4.5
WNW	1.9	1.3	.2									3.4	3.1
NW		.1	.2									.3	0.5
NNW	1.1		.3									1.4	3.6
VARBL		.2	.3	.2								.5	9.8
CALM												3.5	
	33.5	23.7	8.1	1.3								100.0	2.7

TOTAL NUMBER OF OBSERVATIONS 621

JOINT CLIMATE LOGISTICS BRANCH
AFETAC
AF WEATHER SERVICE/AFAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 71 OL A D D BAKER AAF FL 77-78.8 - 92 71
STATION NAME YEARS MONTH
CLASS ALL WEATHER 1977-1978
HOURS (LST) 0000-2359
CONDITION

SPEED (KNTS) DIR	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	2.0	1.0	0.2									2.0	4.8
NNE	2.0	2.3	0.2									2.3	3.7
NE	1.0	1.2	1.0									4.0	4.5
ENE	1.0	2.0	2.9	0.2								7.0	6.3
E	3.0	7.0	3.6	1.7								12.2	5.7
ESE	0	0.2	0.7	0.2								1.2	5.7
SE	0											0	2.0
SSE													
S	0	0.2										0.7	3.2
SSW	0	1.0	0.7									2.1	5.2
SW	2.1	3.1	1.2									5.4	4.4
WSW	2.1	3.5	0.2									7.0	4.2
W	2.4	6.6	4.6	0.2								17.1	5.2
WNW	3.0	4.0	1.2	0.2								10.3	4.5
NW	1.0	4.0	0.5	0.2								6.4	4.6
NNW	2.3	2.0	0.3									4.0	3.9
VARBL		0	1.3									1.0	5.0
CALM												9.7	
	22.3	34.2	19.6	3.1								11.0	4.4

TOTAL NUMBER OF OBSERVATIONS 607

U.S. AIR FORCE
AFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1710 STATION NAME WILLOW BAKE AAF DL YEARS 73-78 MONTH JULY
CLASS ALL WEATHER 1200-1400
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.0	3.7	.4									7.2	4.0
NNE	1.0	2.0	.5	.7								5.4	5.4
NE	.0	2.3	1.1	.2								4.4	5.6
ENE	1.1	3.7	3.5	.7								3.0	6.6
E	1.0	3.0	7.7	2.5								14.5	7.8
ESE	.0	.4	.4									.9	5.8
SE	.0	.4										.5	4.3
SSE	.0											.0	4.0
S	.7	.9	.4									1.2	4.5
SSW	1.2	2.3	.2									3.7	4.3
SW	.7	1.0	.5									2.2	4.7
WSW	1.0	3.3	1.2	.5								6.7	5.6
W	2.0	.0	3.7	.4								12.7	5.5
WNW	1.0	4.4	2.3	.4								9.7	5.7
NW	1.0	2.3	1.9									6.2	5.0
NNW	1.7	3.5	.7									7.9	3.9
VARBL		.0	1.8	.2								2.5	6.4
CALM												4.0	
	22.7	41.7	26.2	5.4								100.0	5.4

TOTAL NUMBER OF OBSERVATIONS 555

CENTRAL CLIMATOLOGY BRANCH
AFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 17-710 STATION NAME COL A JO BAKER AAF CL YEARS 77-78, 80-82 MONTHS JUL
CLASS ALL WEATHER HOURS 1500-1700
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	2.0	1.0	1.1									5.7	3.9
NNE	1.1	2.3	.5									4.4	3.9
NE	1.4	1.0	1.4									4.5	5.3
ENE	.9	3.9	5.1	.6								11.5	7.0
E	1.1	3.7	7.6	2.1								15.4	7.5
ESE	.7	.7	.2									.7	5.0
SE	.7	.7										.7	3.5
SSE	.7	.5										.7	3.7
S	.7	.7	.7									1.6	4.3
SSW	.7	1.0	.9	.7								3.4	6.7
SW	1.1	2.5	1.4									5.1	5.5
WSW	1.0	3.2	1.1	.7								6.7	5.9
W	1.4	4.1	3.2									9.2	5.7
WNW	1.0	4.1	3.2	.7								9.4	5.8
NW	.1	4.1	1.6	.2								5.0	4.9
NNW	1.0	2.1	2.3									6.2	5.3
VARBL		.7	2.3	.7								3.2	8.9
CALM												5.9	
	21.1	37.2	32.2	5.5								100.0	5.7

TOTAL NUMBER OF OBSERVATIONS 435

LOCAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 710 WIL A W 40 BAKE AAF DL STATION NAME 73-75.81-82 YEARS 1973-74
CLASS ALL WEATHERED
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.2	2.2										3.5	3.6
NNE	.2											.7	1.5
NE	.2	2.2	.4									3.5	4.9
ENE	.2	5.2	.2	1.7								13.9	6.1
E	3.7	1.7	7.8	.9								22.2	5.8
ESE	.2	.4	.4									1.7	4.5
SE		.4	.4									.9	5.5
SSE		.4										.4	4.2
S	1.7	.4										2.7	5.2
SSW	.2	1.7	1.7									4.3	5.4
SW	2.2	1.7	2.6	.4								7.4	5.6
WSW	.2	3.0	.9	.9								7.2	5.3
W	1.0	3.1	2.2	.4								9.1	5.4
WNW	.2		1.7	.4								2.9	7.2
NW	1.7	2.6	.9									5.2	4.7
NNW	1.7	3.0										4.6	3.8
VARBL		.2	1.7									2.2	7.4
CALM												5.7	
	23.7	37.8	25.7	4.3								170.0	4.9

TOTAL NUMBER OF OBSERVATIONS 270

U.S. AIR FORCE CLIMATE BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 717 COLA J. D. RAMEY AAF CL STATION NAME 73-78,80-92 YEARS J. D. RAMEY
CLASS ALL WEATHER MONTH ALL
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.1	1.7	.3									4.1	3.6
NNE	1.7	1.6	.2	.2								3.7	4.1
NE	1.1	1.7	.6	.7								3.2	5.0
ENE	1.7	2.4	2.0	.6								7.5	6.7
E	.2	3.4	5.1	1.7								12.1	6.7
ESE	.4	.3	.2	.7								1.3	4.6
SE	.	.7	.6									.5	3.3
SSE	.7	.1										.3	2.6
S	1.6	.5	.1									2.3	2.9
SSW	1.7	2.2	.8	.2								4.9	4.7
SW	.3	3.	1.2	.1								6.6	4.7
WSW	2.4	3.7	1.	.4								8.0	4.7
W	3.7	5.4	3.3	.3								13.1	5.2
WNW	.3	3.3	1.5	.2								7.3	5.1
NW	1.7	2.6	1.	.1								5.0	4.8
NNW	2.2	1.	.7									4.9	4.2
VARBL		.	1.4	.7								1.9	6.5
CALM												13.3	
	27.6	34.6	20.8	3.7								100.0	4.5

TOTAL NUMBER OF OBSERVATIONS 2462

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

1-710 STATION C L A J 30 BAKER AAF DL STATION NAME 73-74.80-82 YEARS JUL MONTH 0600-2400 HOURS (L S T)
ALL WEATHER SS
CONDITION

SPEED (KNTS) DIR	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.2		.2									.3	5.0
NNE	.2	.2										.5	3.3
NE	.2	.3										.5	4.0
ENE	.2	.2										1.3	4.1
E	.2	.2										1.7	2.6
ESE	.2											.5	2.2
SE	.7											.7	1.8
SSE	.1											.2	1.2
S	3.2	1.2										4.9	2.4
SSW	4.4	5.1	.7	.3	.3							15.9	4.0
SW	4.3	4.7	1.8	.3								11.3	4.7
WSW	4.5	8.1	2.1	.2								15.1	4.6
W	.4	6.2	2.0									13.7	4.4
WNW	1.2	1.4	.5									3.3	4.4
NW	.5	.8	.2									1.5	4.2
NNW	.7	.3	.2									.8	4.0
VARBL		.1	.3	.7								1.2	7.8
CALM												31.0	
	2.6	30.4	7.9	1.2	.3							100.0	2.9

TOTAL NUMBER OF OBSERVATIONS 628

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AF WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

1971 COL A J AND BAKER AAF OL 77-78, 80-82 JUL
STATION STATION NAME YEARS MONTH

ALL WEATHER
CLASS

CONDITION

900-1100
HOURS (L & T)

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.1	1.1	.3									1.4	4.2
NNE	.1	.5										1.3	3.4
NE	.7	.7	.7									2.0	4.5
ENE	.5	4.4	1.7	.2								6.8	4.8
E	2.7	2.3	.5	.2								6.0	4.2
ESE	.7	.3	.2									1.2	3.9
SE	.2											.2	1.0
SSE	.1	.3										.5	2.6
S	.5	.3	.2									1.3	3.1
SSW	1.7	1.3	1.0	.5								4.5	5.6
SW	1.7	3.5	.7	.3								6.2	4.5
WSW	.3	4.0	1.3	.2								7.9	4.9
W	.4	7.0	3.0	.7								16.1	5.7
WNW	3.7	5.2	2.0	.2								11.1	4.5
NW	2.2	3.0	2.2	.2								7.4	5.1
NNW	2.7	2.3	.3									5.4	3.8
VARBL			2.3									2.3	6.2
CALM												13.9	
	30.1	36.3	16.8	2.3								100.0	4.1

TOTAL NUMBER OF OBSERVATIONS 597

U.S. AIR FORCE
CLIMATE DIVISION
AFETAC
A. WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 710 U.S. AIR FORCE BAKER AAF DL STATION NAME 73-78.80-82 YEARS 1971
 ALL WEATHER CLASS 1222-1400
 HOURS (L.S.T.)
 CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	2.4	2.3	.6									5.4	3.9
NNE	2.4	2.4		.2								5.2	3.9
NE	1.1	1.5	.6									3.1	4.6
ENE	2.6	3.5	2.6	.4								9.2	5.4
E	1.7	5.7	3.9	.9								11.5	6.1
ESE	.7	.2	.4	.2								1.5	4.9
SE													
SSE	.2											.2	2.5
S	.7	.7	.2									1.7	3.5
SSW	1.1	1.1	.2	.7								3.9	5.2
SW	.6	1.1	1.1									2.9	3.6
WSW	1.5	2.9	1.5	.7								6.4	4.9
W	1.7	5.5	3.5	.6			.2					11.4	6.5
WNW	2.0	5.7	3.5	.2								11.4	5.6
NW	1.3	5.1	2.0	.4								8.8	5.7
NNW	1.1	5.0	1.5	.2								9.7	4.7
VARBL			2.6	.4								2.9	9.2
CALM												4.4	
	23.7	43.7	23.9	4.2			.2					100.0	5.2

TOTAL NUMBER OF OBSERVATIONS 505

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 710 COL A J 12 BAKER AAF DL 73-76, 80-82 YEARS JUL MONTH
CLASS ALL WEATHER 1600-1700 HOURS (LST)
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	4.1	3.1	.2	.2								7.6	3.6
NNE	1.0	1.0	.2									2.9	4.1
NE	1.0	1.2	2.7									4.9	5.8
ENE	.3	5.1	1.4	.4								9.2	5.2
E	2.7	5.7	5.7	1.2								14.8	6.3
ESE	.4		.2	.2								.6	5.3
SE	.2											.2	2.0
SSE	.2	.2										.4	3.0
S	.4	.2	.6	.4								1.6	7.8
SSW	1.0	1.0	1.2	.2								4.3	5.6
SW	.6	1.6	1.4									3.7	5.9
WSW	1.2	3.0	1.0									6.2	5.1
W	2.5	5.7	2.7	.2	.2							10.7	5.5
WNW	1.0	3.3	2.1	.2								6.6	5.7
NW	1.0	.1	3.9	.2								1.3	5.0
NNW	.3	4.3	1.2	.2								9.0	4.5
VARBL		.2	2.5	.2								2.9	5.7
CALM												3.7	
	42.5	42.5	27.1	3.7	.2							120.2	5.3

TOTAL NUMBER OF OBSERVATIONS 407

JOINT CLIMATE BRANCH
USAFETAC
AIR FORCE SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 710 STATION NAME 73-78.82 YEARS 1970-2000
CLASS ALL WEATHER CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	2.4	3.1										5.5	3.6
NNE	1.0											1.0	2.0
NE	.4	1.5	.4									2.4	4.5
ENE	2.0	4.3	2.0									5.2	4.9
E	3.5	.6	5.9	1.6								19.6	5.8
ESE		.4		.4								.8	1.0
SE		.4										1.2	3.7
SSE			.4									.4	7.0
S	.4	.7	.4	.8								2.4	7.3
SSW	1.2	1.6	.8	.4								3.9	5.6
SW	1.7	3.1	2.7	.4								7.8	5.6
WSW	2.4	5.1	1.6									9.2	4.7
W	2.4	5.5	2.0									9.8	5.0
WNW	3.0	3.9	2.0	.4								10.2	5.1
NW	2.7	1.2	1.2									5.1	4.2
NNW	2.4	.7										3.1	2.8
VARBL		.7	.4	.4								1.2	9.3
CALM												7.8	
	27.5	47.8	19.6	4.3								100.0	4.7

TOTAL NUMBER OF OBSERVATIONS 255

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

1 0710 COL A J CO BAKER AAF DL 73-78, 81-82 JUL
STATION STATION NAME YEARS MONTHS
ALL WEATHER CLASS ALL
CONDITION HOURS (L & T)

SPEED (KNTS) DIR	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	2.1	1.0	.3	.0								4.3	3.6
NNE	1.2	1.0	.0	.0								2.2	3.7
NE	.7	1.0	.0									2.0	5.1
ENE	.0	3.5	1.4	.2								7.1	5.1
E	1.1	3.7	2.8	.6								7.2	5.7
ESE	.0	.2	.2	.1								1.0	4.0
SE	.3	.0										.4	2.3
SSE	.4	.1	.0									.6	2.6
S	1.4	.6	.2	.2								3.4	3.9
SSW	2.0	2.5	.8	.4	.1							5.3	5.2
SW	1.0	2.9	1.4	.2								6.4	5.1
WSW	2.6	4.9	1.5	.1								9.1	4.8
W	3.7	6.0	2.7	.3	.0		.0					12.0	5.2
WNW	2.2	3.0	2.0	.2								6.3	5.1
NW	1.4	3.2	1.0	.2								6.5	5.4
NNW	2.3	2.6	.7	.1								5.7	4.3
VARBL		.0	1.7	.2								2.1	0.7
CALM												13.6	
	26.0	38.2	16.5	2.9	.1		.0					100.0	4.3

TOTAL NUMBER OF OBSERVATIONS 2492

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/HAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1471 COL A J SO BAKER AAF IL STATION NAME 73-78.62-82 YEARS ALL WEATHER CLASS 600-7800 HOURS (L & T) CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.7											.5	1.3
NNE	.7		.2									.8	3.8
NE	.7											.7	2.3
ENE	1.0											1.0	1.6
E	.7	1.2	.7	.3								3.2	6.4
ESE	.7		.7									.9	4.6
SE	1.7	.3										1.7	3.2
SSE	.7	.3										.3	2.6
S	.3	.3	.2	.2								4.5	3.1
SSW	5.6	3.7	1.0	.2								9.7	3.7
SW	4.7	5.0	1.0	.2								10.9	4.0
WSW	7.4	5.0	1.3									11.7	4.1
W	3.9	4.9	1.5	.5								10.5	4.6
WNW	1.2	.7										1.6	3.5
NW	.7	.2	.2									1.0	3.7
NNW	.3											.5	1.7
VARBL		.7	.3									.5	2.0
CALM												10.5	
	21.2	21.3	6.6	1.3								100.0	2.4

TOTAL NUMBER OF OBSERVATIONS 626

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

1 4710 COL A J 60 BAKER AAF FL 73-78, 81-82
STATION MONTH
ALL WEATHER CLASS 200-1100
HOURS (LST)
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.1	1.7										3.8	3.2
NNE	1.7	.7										2.4	2.4
NE	.1	1.6										2.7	3.5
ENE	1.0	1.4	.9									4.2	4.3
E	1.3	2.6	1.7	1.7								6.4	5.8
ESE	.4		.7	.2								.9	5.4
SE	.7											.3	2.0
SSE	.7											.5	2.3
S	.7	.2	.7									1.5	5.0
SSW	1.3	2.3	.9									5.4	4.1
SW	2.4	3.2	.5	.3								6.5	4.4
WSW	3.4	4.4	.5	.3								9.1	4.2
W	5.0	5.4	2.8	.2								14.3	4.5
WNW	4.0	3.1	.5	.2								7.5	4.0
NW	2.4	1.9	.3		.2							4.9	4.2
NNW	2.4	1.4										3.5	2.9
VARBL			.9									.5	6.4
CALM												2.4	
	36.6	30.0	9.9	3.1	.2							100.0	3.4

TOTAL NUMBER OF OBSERVATIONS 574

GENERAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 4710 STATION NAME CIL A J 20 TAKER AAF CL YEARS 77-78-8-52 MONTH AUG
CLASS ALL WEATHERED HOURS (L & T) 1200-1400
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	4.7	2.7	.2									7.5	3.2
NNE	1.7	2.0										2.3	3.6
NE	2.2	3.3	.9									6.4	4.6
ENE	2.4	3.5	2.9	.7								9.0	5.7
E	1.8	3.8	3.5	3.3	.4							13.2	6.5
ESE	.7		.5									.7	7.0
SE	.4	.2										.2	2.7
SSE	.7	.2										.4	2.5
S	.1	.4	.4									1.3	4.7
SSW	.7	.5	.5	.2								2.2	5.2
SW	1.4	1.5	1.3									4.4	5.1
WSW	1.7	1.5	.4	.7								3.3	4.6
W	2.8	5.1	2.6	.9	.7							11.4	6.5
WNW	4.0	6.7	1.1	.9	.2							12.3	5.0
NW	1.7	6.6	.9									9.0	4.6
NNW	3.7	3.3	.5									7.5	3.8
VARBL			1.1	.7								1.8	9.4
CALM												5.9	
	28.0	41.0	17.2	6.4	.7							100.0	5.7

TOTAL NUMBER OF OBSERVATIONS 596

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 10010 COL AFB D BAKER AAF DL 77-76,81-92
STATION NAME YEARS
ALL WEATHER CLASS 1500-1700
CONDITION HOURS (LST)

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.5	1.7										2.2	2.7
NNE	2.8	1.7										3.5	3.1
NE	2.8	2.2	.4	.2								4.8	4.1
ENE	2.4	3.2	1.1									5.5	4.5
E	2.2	3.4	6.2	3.7	1.1							15.8	7.8
ESE	.4		.4									.9	4.5
SE													
SSE	.4											.4	1.6
S	.4	.4	.3	.7								1.7	5.5
SSW	1.5	1.0	.6	.4								4.7	5.6
SW	.1	1.0	.9	.7								7.0	5.1
WSW	1.7	3.0	1.5	.4								6.6	5.4
W	7.4	3.6	.6	.6								12.2	4.5
WNW	7.2	3.0	2.8	.1								13.3	5.1
NW	3.2	4.7	1.5									9.4	4.4
NNW	3.0	1.0	1.5									6.4	4.5
VARBL		.7	1.5	.2								1.9	5.9
CALM												3.5	
	32.1	32.1	19.2	5.6	1.1							100.0	4.5

TOTAL NUMBER OF OBSERVATIONS 452

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1710 COL A WIND BAKER AAF DL STATION NAME 73-7E, 81-52 MONTH ALL
CLASS ALL WEATHER 1800-2000
HOURS (LST) 1800-2000
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.0	2.0										2.0	4.0
NNE	.0	.4										1.2	2.7
NE	1.0	2.4										4.0	3.7
ENE	4.0	3.6	.4									8.1	3.5
E	4.0	4.7	5.3	3.6								22.7	6.6
ESE	.0	.4										1.2	2.7
SE	.4	1.2	.4									2.0	4.4
SSE													
S	1.2	.0	.4									2.0	4.0
SSW	2.4	1.2	.8									4.5	4.2
SW	2.4	4.0	2.0	.4								9.7	2.3
WSW	2.0	1.5	.4									4.5	3.5
W	1.2	6.5	.4									10.1	4.2
WNW	2.0	1.6	.4									4.0	3.3
NW	.0	1.2	1.2	.0								4.0	6.6
NNW	1.0		.4									2.0	2.5
VARBL			1.2	.4								1.6	9.3
CALM												13.8	
	22.6	37.7	13.8	5.3								100.0	4.3

TOTAL NUMBER OF OBSERVATIONS 247

CLIMATOLOGY BRANCH
USAFETAC
AFWETHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

1 710 COL A GORDON BAKER AAF DL 73-75,80-82
STATION STATION NAME YEARS
ALL WEATHER
CLASS
ALL
HOURS (LST)

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	2.5	1.5	.5									4.2	3.2
NNE	1.4	.5	.5									3.3	3.1
NE	1.6	1.6	.3									4.0	4.0
ENE	.1	2.1	1.1	.5								5.3	4.6
E	2.4	3.4	3.2	2.2	.3							11.4	7.1
ESE	.5	.5	.5	.5								.9	5.0
SE	.5	.5	.5									.5	3.2
SSE	.4	.1										.5	2.4
S	1.7	.5	.4	.1								2.3	4.1
SSW	2.5	2.5	.8	.2								5.4	4.3
SW	2.5	3.2	1.0	.2								6.9	4.6
WSW	3.5	3.3	.9	.2								7.4	4.3
W	3.0	5.5	1.8	.5	.0							11.1	4.9
WNW	3.0	3.0	.9	.3	.0							7.3	4.6
NW	1.5	3.5	.7	.1	.0							5.6	4.6
NNW	2.3	1.4	.5									4.1	3.7
VARBL		.1	.0	.2								1.3	5.9
CALM												15.0	
	32.7	31.6	12.9	4.1	.4							100.0	3.5

TOTAL NUMBER OF OBSERVATIONS 2441

CLERICAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION 1710 COL A W D BAKER AAF DL STATION NAME 73-75, 80-82 YEARS 1973-1982 GED 1973-1982
 CLASS ALL WEATHER
 HOURS (LST) 0600-1800
 CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.2	.3										.7	3.0
NNE	.2											.2	2.0
NE	.2	.2										1.0	2.8
ENE	1.2	.5										1.7	2.6
E	.2	.7	.3									3.0	3.1
ESE	.2											.7	1.5
SE	.2											.2	1.0
SSE	.3	.3										2.7	2.2
S	4.5	1.0	.3	.2								5.5	3.2
SSW	4.5	3.8	1.2	.7								10.2	4.6
SW	.2	5.7	1.5	.7								17.2	5.7
WSW	4.5	4.3	1.2	.2								11.2	4.1
W	3.5	4.9	1.5	.7								10.5	5.0
WNW	.2	1.0	.3	.2								1.8	2.2
NW	.2	.2	.2									.8	4.8
NNW	.7	.3	.2									1.2	3.7
VARBL			.5	.2								.7	10.5
CALM												19.1	
	27.5	23.2	7.2	2.7								100.0	4.5

TOTAL NUMBER OF OBSERVATIONS 499

GLOBAL CLIMATOLOGY BRANCH
AFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

1 710 COL A JUD BAKER AAF DL 73-78,80-82
STATION MONTH YEARS
ALL EATHER
CLASS
CONDITION
0900-1100
HOURS (L.S.T.)

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.5	.3										1.2	2.6
NNE	.5	.7	.2									1.3	3.6
NE	1.5	1.7	.5									3.7	4.0
ENE	.5	2.4	1.5									5.9	4.7
E	1.2	1.7	2.0									6.9	4.2
ESE	.5											.5	2.3
SE	.5	.5										.8	3.8
SSE	1.2	.5	.2									1.9	3.4
S	2.5	.5	.2									3.2	2.7
SSW	1.5	2.2	1.5	.5								6.1	5.6
SW	3.0	2.5	1.5									7.1	4.8
WSW	1.4	4.4	1.5									11.3	4.1
W	4.5	4.7	1.2	.7								11.1	4.6
WNW	4.2	2.5	.5	.5								8.1	4.5
NW	1.2	1.3	.2									2.7	3.5
NNW	1.5	1.5	.2									3.2	3.5
VARBL				.5								.8	12.5
CALM												24.1	
	34.4	27.8	11.1	2.5								100.0	3.3

TOTAL NUMBER OF OBSERVATIONS 503

GLOBAL CLIMATOLOGY BRANCH
AFETAC
AIR WEATHER SERVICE/AFAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

14710 STATION COL A J 60 BAKER AAF DL STATION NAME 73-78,82-82 YEARS SEP
BIRTH
ALL WEATHER CLASS 1200-1400
HOURS (L & T)
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	0.2	2.0	0.2									5.1	3.8
NNE	1.0	1.5	0.2									4.1	3.7
NE	0.5	2.0	1.3									5.0	5.3
ENE	2.5	4.6	3.3									10.5	5.4
E	2.4	2.0	5.5									10.5	6.2
ESE	0.1	0.1	0.2									0.9	5.2
SE	0.4											0.4	2.5
SSE		0.1										0.2	4.0
S	1.0	0.6	0.1	0.2								2.2	4.0
SSW	1.0	1.3	0.7	0.2								3.5	4.8
SW	0.7	1.3	0.7									2.3	2.4
WSW	1.0	1.1	2.2	0.2								5.3	5.9
W	2.0	5.5	2.4	0.7								11.2	5.7
WNW	0.3	5.1	1.7	0.2	0.4							12.7	4.7
NW	2.0	4.2	0.7									7.9	4.1
NNW	4.0	1.5	0.7	0.2								6.4	3.9
VARBL			1.1	0.2								1.5	0.6
CALM												10.0	
	30.1	35.2	21.1	1.8	0.4							100.0	4.5

TOTAL NUMBER OF OBSERVATIONS 545

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AF WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

1 4711 COL A J 60 BAKER AFB TX 73-78,81-92
STATION MONTH
ALL WEATHER CLASS
CONDITION
1500-1700 HOURS (LST)

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	2.2	1.1	.2	.2								2.7	3.6
NNE	1.5	1.3	.7									3.3	4.1
NE	1.7	3.3	1.3									6.3	4.8
ENE	4.4	3.5	2.4									10.2	4.7
E	2.4	6.1	9.4									17.9	6.4
ESE		.7	.7									1.3	7.3
SE	.2											.2	2.0
SSE	.2		.2									.4	4.0
S	.9	.2		.2								1.3	4.5
SSW	1.5	2.7	.7	.4								4.6	5.2
SW	1.7	2.2	1.1									5.0	4.4
WSW	1.3	2.0	1.3	.2								4.3	5.3
W	2.8	3.5	.9									7.2	4.1
WNW	2.4	6.1	1.1	.2								9.8	4.8
NW	3.1	3.1	.6									7.0	4.1
NNW	4.1	2.2										5.3	3.0
VARBL		.2	.9									1.1	7.8
CALM												9.5	
	3.3	37.3	21.6	1.3								100.0	4.4

TOTAL NUMBER OF OBSERVATIONS 459

CENTRAL CLIMATOLOGY BRANCH
 USAFETAC
 AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
 DIRECTION AND SPEED
 (FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1071 STATION NAME COL A J 50 BAKER AAF TX YEARS 73-78, 81-82 SEP
ALL WEATHER 1800-2000
 CLASS MOUSE (L.S.T.)
 CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.0											.9	2.5
NNE	1.0											1.3	1.7
NE	2.1	1.7										1.4	3.3
ENE	4.3	3.0	.4									5.5	3.8
E	4.7	13.2	3.0									20.9	4.6
ESE	.4	1.3										1.7	4.0
SE													
SSE	.0											.2	2.0
S	.4			.4								.0	7.5
SSW	2.6	1.7	2.1	.4								6.2	4.9
SW	.1	3.0	1.3									5.4	3.5
WSW	1.3	3.4	1.7									5.4	4.9
W	1.7	2.6	1.3									5.6	4.7
WNW	2.6	2.6										5.1	3.1
NW		.4										.4	4.0
NNW	.0		.4									1.3	3.3
VARBL			.0									.9	7.5
CALM												25.6	
	29.1	33.3	11.1	.9								100.0	3.1

TOTAL NUMBER OF OBSERVATIONS 234

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

11-710 STATION CCL A J 80 BAKER AAF DL 73-78,80-82 YEARS SEP MONTH
STATION NAME CLASS ALL WEATHER
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.7	1.7	.1	.0								2.4	3.5
NNE	.9	.7	.2									1.8	2.7
NE	1.3	1.7	.7									3.8	4.5
ENE	2.6	2.8	1.6									7.0	4.7
E	2.7	3.7	3.9									10.2	5.4
ESE	.4	.4	.2									.7	4.5
SE	.2	.1										.4	3.0
SSE	1.7	.2	.1									1.3	2.8
S	3.1	.6	.2	.2								3.0	3.4
SSW	2.4	2.8	1.2	.5								6.3	5.0
SW	2.3	3.7	1.2	.2								6.7	4.8
WSW	3.2	3.1	1.6	.1								6.2	4.6
W	3.3	4.5	1.5	.5								9.7	4.9
WNW	3.7	3.5	.8	.2	.1							7.6	4.5
NW	1.6	1.9	.4									4.0	4.1
NNW	2.3	1.2	.3	.0								3.8	3.5
VARBL		.1	.6	.3								.9	9.6
CALM												2.2	
	30.5	30.8	14.4	2.0	.1							100.0	3.6

TOTAL NUMBER OF OBSERVATIONS 2430

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AT WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION 0710 STATION NAME 01 A W H BAKER AAF DL YEARS 73-78, 80-82 GORTS 017
CLASS ALL WEATHER HOUSE (L.S.T.) 0600-0800
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	N	MEAN WIND SPEED
N	1.0											1.0	1.5
NNE													
NE	.2	.3										1.0	2.7
ENE	2.6	.2	.2	.3								3.3	3.9
E	2.1	.2										2.2	2.2
ESE	.7	.5	.2									1.5	3.7
SE	.7	.3										1.0	2.0
SSE	2.1	.2										2.2	2.0
S	4.0	2.6	.2									7.4	3.0
SSW	4.3	2.6	1.4	.2								1.4	4.2
SW	.7	4.1	1.4	.3								3.5	4.8
WSW	2.6	3.6	1.9									1.1	4.8
W	2.3	3.4	1.5									2.2	4.6
WNW	1.5		.2									1.7	3.2
NW	1.9	.5										2.4	2.2
NNW	.3											.3	1.5
VARBL		.7	.3	.5								1.7	13.2
CALM												1.5	
	31.2	10.7	7.2	1.4								120.3	2.3

TOTAL NUMBER OF OBSERVATIONS 503

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 14717 COL A JED BAKER AAF DL STATION NAME 73-78,80-P2 YEARS 667 MONTHS 1933-1938 HOURS (L.S.T.) ALL WEATHER CLASS CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.2											1.2	1.9
NNE	1.1	.5										1.6	3.1
NE	1.2	.2										1.4	2.9
ENE	1.5	1.4	1.4	.7								5.3	5.6
E	2.5	1.1	1.4									5.3	4.3
ESE	1.4	.4	.2									1.9	3.0
SE	.7		.2									.9	2.6
SSE	.7											2.7	1.7
S	1.4	1.6	.7	.2								4.1	4.7
SSW	2.1	2.1	2.1	.7								7.8	5.9
SW	2.1	3.5	1.8	.2								7.6	5.2
WSW	2.7	3.9	1.6	.2								5.3	4.9
W	3.4	5.1	2.1	.2								10.5	4.9
WNW	1.4	2.5	.4	.2								4.5	4.8
NW	2.7	.5										3.5	2.6
NNW	1.6	.2										1.3	2.1
VARBL			.7	.4								1.1	10.3
CALM												24.9	
	31.7	24.0	12.7	2.7								100.0	3.2

TOTAL NUMBER OF OBSERVATIONS 566

GENERAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/HAL

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 1-710 COL A J MC BAKER AAF DL 73-76.80-E2 CGT
STATION NAME YEARS NORTH
CLASS ALL WEATHER
1200-1400
HOURS (L & T)
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	0.2	.4										2.6	2.9
NNE	1.1	1.1										3.2	3.3
NE	2.6	3.9	.6									7.0	4.0
ENE	3.5	2.6	3.1	.4								9.6	5.2
E	3.7	2.2	2.4	1.1								9.2	5.7
ESE	.4	.2	.2	.2								.9	5.2
SE													
SSE	.2		.2									.4	4.5
S	.2	1.1	.7									2.3	5.9
SSW	1.3	2.8	1.3	.4								6.3	5.1
SW	.7	2.1	.9									3.7	5.4
WSW	1.7	3.5	.9	.6								6.3	5.4
W	2.9	5.3	2.8	1.3								12.0	6.4
WNW	3.5	4.8	.7	.4								9.4	4.4
NW	3.3	4.2	.4									7.9	3.8
NNW	3.3	1.7	.2									5.2	3.1
VARBL			2.4	.2								2.6	6.7
CALM												11.2	
	30.6	36.1	16.8	4.4								100.0	4.4

TOTAL NUMBER OF OBSERVATIONS 243

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

1. 710 COL A J. D. PAKER AAF DL 73-78,81-82 667
STATION STATION NAME YEARS MONTH
ALL WEATHER
CLASS
CONDITION
1980-1980
HOURS (L.S.T.)

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	2.4	.5	.2									1.1	2.4
NNE	1.1	1.4										2.5	3.0
NE	3.1	2.9										6.0	3.6
ENE	4.5	5.3	3.6	.2								13.3	4.9
E	1.1	4.7	5.9	.9								12.1	6.5
ESE	.2	.5										.7	1.7
SE	.5											.9	2.0
SSE	.2											.1	1.0
S	1.4	.5	.7	.2								2.2	4.9
SSW	.5	.2	1.1	.2								1.2	5.9
SW	1.4	2.1	.5									3.5	4.6
WSW	.7	2.5	1.6									4.7	5.6
W	3.4	4.3	3.6	.7								12.2	5.7
WNW	4.1	4.1	.9	.5								9.5	4.4
NW	2.9	2.0	.5									5.4	3.3
NNW	2.7	1.6										4.3	3.3
VARBL			1.1	1.1								2.3	10.7
CALM												9.9	
	23.2	33.7	19.9	3.1								100.0	4.4

TOTAL NUMBER OF OBSERVATIONS 443

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AF WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 10710 COL AFB BASED AAF DL STATION NAME 73-74.81-82 YEARS 1971-1972
CLASS ALL WEATHER HOURS (LST) 1800-2000
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.7		.3									.7	3.0
NNE													
NF	.7	1.7	.7									3.1	4.9
ENE	6.7	2.1	2.4									11.4	3.6
E	5.7	4.7	3.1									13.5	4.4
ESE	1.0	.3										1.4	2.3
SE	.7											.7	3.0
SSE	1.4											1.4	3.0
S	1.0	.7										1.7	3.4
SSW	1.0	2.0	1.0									4.0	4.6
SW	2.1	2.1	.3									4.5	3.5
WSW	3.1	4.0	2.1									10.0	4.7
W	1.2	3.8	2.4									10.4	4.4
WNW	.7	.7	1.4	.3								2.5	7.4
NW	.3	.3	.3	.3								1.4	6.5
NNW	.7											.7	2.0
VARBL			2.7	.3								3.1	9.0
CALM												20.4	
	29.4	24.2	17.0	1.0								10.0	3.2

TOTAL NUMBER OF OBSERVATIONS 289

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
ALL-WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION 1-710 COL A J 90 BAKER AAF DL 77-78, 80-92 2-1
STATION NAME YEARS MONTH
CLASS ALL-WEATHER
HOURS (L.E.T.) ALL
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.0	.2	.1									1.5	2.5
NNE	.0	.0										1.4	3.1
NE	1.5	1.7	.7									3.5	3.8
ENE	3.1	2.1	2.0	.4								5.5	4.8
E	1.5	3.2	2.3	.4								7.7	5.2
ESE	.0	.4	.1	.1								1.5	3.5
SE	.1	.1	.0									.7	2.6
SSE	1.4	.0	.0									1.4	1.9
S	.0	1.6	.5	.1								4.1	4.1
SSW	.0	2.4	1.4	.3								6.4	5.1
SW	1.5	2.9	1.1	.1								5.9	4.9
WSW	.0	3.6	1.6	.2								7.3	5.1
W	.3	4.5	2.5	.5								10.6	5.3
WNW	.3	2.6	.6	.2								5.7	4.6
NW	2.1	1.6	.2	.0								4.3	3.3
NNW	1.1	.7	.0									2.0	3.0
VARBL		.0	1.3	.5								1.9	9.6
CALM												24.9	
	11.1	27.1	14.1	2.8								100.0	3.1

TOTAL NUMBER OF OBSERVATIONS 2424

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 10710 STATION NAME COL A JCC BAKER AAF DL YEARS 77-78.62-82 MONTH NOV
CLASS ALL WEATHER HOURS 1600-2800
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.0	.4	.5									1.4	5.6
NNE	.4											.4	2.0
NE	1.1	.0										1.2	2.4
ENE	1.4	1.6	.7									3.7	4.4
E	1.2	1.4	1.2									4.1	4.8
ESE	.0	.7	.4									3.0	3.2
SE	1.1	.0										1.2	2.3
SSE	1.1											1.1	1.9
S	2.7	1.6		.5								5.0	4.3
SSW	.4	2.1	1.6	1.2	.2							5.0	6.3
SW	.3	4.3	3.6	.4								10.0	5.8
WSW	.0	4.6	4.1	.4								10.0	6.2
W	1.0	3.4	3.7	1.6	.2							10.9	7.1
WNW	.7	1.4	.7	.4								3.2	6.3
NW	.0	.4	.2									1.1	4.3
NNW	.0	.2										.4	3.5
VARBL		.0	.4	1.6		.2						2.3	13.2
CALM												11.6	
	21.4	23.0	17.1	6.1	.4	.2						100.0	4.0

TOTAL NUMBER OF OBSERVATIONS 560

JOINT CLIMATE BRANCH
AFETAC
AIR WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION 717 STATION NAME COL A J BAKER AAF DL YEARS 77-78, 80-82 NO. 1007-1100
STATION 717 STATION NAME COL A J BAKER AAF DL YEARS 77-78, 80-82 NO. 1007-1100
CLASS ALL WEATHER
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N		.4										.2	4.2
NNE	.7	.4	.6									1.7	4.6
NE	.4	.3	.2									.7	3.6
ENE	1.7	3.0	.4									4.6	4.2
E	1.0	1.7	1.5	.2								1.2	5.1
ESE	.6	.2										1.1	2.5
SE	.5	.4	.2									1.3	3.0
SSE	1.7	.6	.2									2.4	2.9
S	2.4	1.1	1.7									5.9	4.6
SSW	1.0	1.5	2.0	.7								6.1	6.3
SW	.2	4.6	2.0	.4								9.2	5.3
WSW	.2	4.6	2.4									9.2	5.1
W	1.0	5.5	4.1	4.1	.4							15.5	8.2
WNW	.4	1.7	.2									1.2	5.0
NW	.1	1.1	.4									2.3	4.7
NNW	.4	.4	.2									.9	4.4
VARBL			1.7	1.1								2.5	10.4
CALM												9.3	
	17.2	27.7	17.3	6.5	.4							100.2	4.1

TOTAL NUMBER OF OBSERVATIONS 1007-1100

CLIMATE CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 10710 STATION NAME COL A J SO BAKER AAF DL YEARS 72-76, 82-82 MONTH ALL
CLASS ALL WEATHER HOURS (LST) 1200-1400
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.2	.2										1.2	2.6
NNE	2.5	1.2	.2									3.9	3.0
NE	.6	1.7	.2									1.7	4.0
ENE	1.2	1.6	1.4	.2								4.3	5.6
E	1.6	2.9	3.3									7.8	5.7
ESE	.4	.6										1.0	3.6
SE	1.2	.2										1.4	2.7
SSE	.2	.4	.2									1.4	3.6
S	1.7	1.4	.8	.6	.2							3.9	6.7
SSW	1.6	1.7	1.0	.8								5.2	6.2
SW	.2	1.5	1.0									3.3	5.5
WSW	1.0	2.7	1.7	.2								6.6	5.4
W	2.5	6.6	6.2	6.0	.4	.2						21.9	3.2
WNW	2.1	1.7	1.0	.4								6.2	5.1
NW	2.3	4.1	.2									6.6	4.0
NNW	2.2	1.2		.2								4.2	3.3
VARBL			.5	1.4								2.1	12.6
CALM												17.8	
	24.0	20.8	17.8	9.7	.6	.2						120.0	4.9

TOTAL NUMBER OF OBSERVATIONS 516

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION 710 COL A J 50 BAKER AAF DL 73-78, 80-82 NOV
STATION NAME YEARS MONTH
CLASS ALL WEATHER 1500-1700
HOURS (L & T)
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.2	1.0	.2									2.4	3.6
NNE	.7	.5	.2									1.4	3.5
NE	1.2	.5	.7									2.4	4.1
ENE	1.7	2.4	1.4									5.5	4.8
E	2.1	4.0	3.8									10.0	5.6
ESE	.5	.2										.5	3.0
SE	.7	.2										1.0	2.8
SSE	.5	.5	.2									1.2	4.4
S	.7	1.7	.2									2.6	5.0
SSW	.7	1.4	3.1	.2	.2							5.7	7.3
SW	1.7	2.4	1.0									5.0	4.8
WSW	1.0	5.7	3.1	1.4								11.2	6.7
W	2.1	2.6	6.4	2.4	1.4							15.0	8.7
WNW	3.3	2.4	1.2	.2								7.1	4.6
NW	1.7	1.2	1.0									3.8	4.4
NNW	2.1	.7	.5									3.3	3.4
VARBL		.1		.7	.2							1.2	12.3
CALM												20.9	
	21.6	27.6	23.0	5.0	1.9							100.0	4.7

TOTAL NUMBER OF OBSERVATIONS 421

CENTRAL CLIMATOLOGY BRANCH
 USAF ETAC
 AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
 DIRECTION AND SPEED
 (FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 10710 COL A J CO BAKER AAF DL STATION NAME 73-73,81-82 YEARS 1977-2000
 MONTH ALL CLASS ALL WEATHER HOURS (LST) 1800-2000
 CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	1.1	.4										1.2	2.3
NNE													
NE	1.1	1.1										2.2	3.7
ENE	1.1	1.5	1.5									4.0	5.4
E	1.1	1.1	1.5									4.4	4.8
ESE	.7	1.1	.4									2.2	4.0
SE													
SSE	.7											.7	2.0
S	1.1	.7										1.8	3.4
SSW	2.2	1.7	1.5	.4	.4							6.2	9.2
SW	2.6	5.5	2.6									10.6	5.2
WSW	2.7	3.3	3.3	1.1								10.6	6.1
W	1.1	7.9	7.3	2.2	.4							17.2	7.8
WNW	.4	2.7	1.1	.4								4.6	5.8
NW	.4											.4	3.0
NNW	.7	.7	.4									1.6	4.2
VARBL			.4	1.8	.4							2.6	13.3
CALM												28.9	
	17.0	25.7	19.8	5.9	1.1							120.0	4.3

TOTAL NUMBER OF OBSERVATIONS 273

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 100710 STATION NAME COL A J B O BAKER AAF DL YEARS 73-78, 80-82
CLASS ALL WEATHER
CONDITION

NAV
NORTH
ALL
HOURS (LST)

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.1	.4	.2									1.2	3.9
NNE	1.1	.4	.2									1.6	3.4
NE	.1	.4	.2									1.6	3.6
ENE	1.7	2.1	1.0	.1								4.4	4.8
E	1.8	2.4	2.2	.1								6.3	5.3
ESE	.1	.1	.1									1.5	3.3
SE	.1	.1	.0									1.1	3.0
SSE	1.1	.3	.1									1.4	3.0
S	1.7	1.6	.6	.3	.1							4.2	4.9
SSW	.1	1.7	1.1	.7	.1							6.4	6.4
SW	1.9	3.5	2.1	.2								7.6	5.4
WSW	1.7	4.2	2.9	.5								9.3	5.9
W	1.9	4.8	5.3	3.4	.5	.0						16.9	8.1
WNW	1.4	2.1	.8	.3								4.5	5.2
NW	1.1	1.5	.3									2.9	4.3
NNW	1.3	.6	.2	.0								2.1	3.6
VARBL		.1	.1	1.3	.1	.0						2.2	12.3
CALM												25.7	
	21.1	26.1	18.7	6.7	.8	.1						100.0	4.4

TOTAL NUMBER OF OBSERVATIONS 2312

CENTRAL CLIMATE CLOUDY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

10710 STATION C L A U 80 BAKER AAF OL STATION NAME 73-78.60-82 YEARS DEC MONTH 0600-0800 HOURS (L S T.)
ALL-WEATHER CLASS
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.0											.2	3.0
NNE	.4	.4										.7	4.0
NE	.0	.4										.2	3.6
ENE	.0	2.4	.7									3.7	5.1
E	1.8	.7	1.3									3.8	4.3
ESE	1.3	.4										1.7	2.4
SE	.0											.9	2.0
SSE	2.4	.4										2.8	2.5
S	3.7	2.4	.4		.2							6.6	3.8
SSW	1.8	3.7	1.8	1.5								8.4	6.8
SW	1.8	5.1	4.2	.0	.2							10.1	6.5
WSW	.0	3.3	3.9	.9		.2						10.3	6.9
W	1.8	2.4	5.7	1.8	.6							12.7	5.0
WNW	.0	1.5	.4	.6								2.9	6.2
NW	.6	.2										.7	2.0
NNW	.2		.2									.4	4.5
VARBL			1.8	2.6	.6	.2						5.1	12.6
CALM												76.1	
	20.6	22.9	20.4	8.3	1.5	.4						100.0	4.7

TOTAL NUMBER OF OBSERVATIONS 545

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

100710 STATION 001 A J 80 BAKER AAF DL 73-78,80-82 YEARS DEC MONTH 0000-1100 HOURS (L.S.T.)

ALL WEATHER CLASS

CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.2	.3										.2	2.8
NNE	.2											.2	3.0
NE	.2	.7	.3									1.2	5.7
ENE	1.2	1.0	.5									3.9	5.0
E	1.7	1.9	1.5	.5								5.6	5.2
ESE	1.5	.2										1.7	2.3
SE	.5	.3										1.2	2.4
SSE	1.9	.3										2.2	2.5
S	2.0	1.0	.3	.2								4.9	4.0
SSW	1.1	3.1	1.9	.3								5.3	5.1
SW	1.7	3.6	4.6	.3	.3							9.7	6.6
WSW	2.0	3.7	3.9	1.5	.3							11.5	7.1
W	1.2	2.0	6.3	1.5								11.9	7.7
WNW	.5		.2	.3								1.0	7.2
NW	.3	.2		.2								.7	5.5
NNW	.3	.2										.5	2.3
VARBL		.2	.5	2.2	.3							3.5	12.6
CALM												1.1	
	10.0	21.2	20.7	7.1	.8							100.0	4.3

TOTAL NUMBER OF OBSERVATIONS 589

U.S. AIR FORCE CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION 100710 COL A J D BAKER AAF DL STATION NAME 73-76.80-82 YEARS D.C.
NORTH
CLASS ALL WEATHER 1277-1420
NOV (L.S.T.)
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.6	.2										.8	2.5
NNE	.2	.2										.4	3.0
NE	.2		.4									1.1	3.6
ENE	.2	3.1	1.0	.4								6.7	6.1
E	1.0	.0	1.9	.4								4.2	6.5
ESE	3.1											1.1	2.5
SE	.0											.2	2.5
SSE	.4	.4										.8	3.0
S	2.9	.0	.2									3.8	2.7
SSW	1.7	1.7	1.1									4.6	5.7
SW	2.7	3.4	2.7									8.8	5.1
WSW	.0	3.4	2.5	.8								6.9	7.3
W	1.0	4.8	7.1	2.5	.4							16.3	7.9
WNW	1.3	1.4	1.3	.6								5.2	6.1
NW	1.0	1.0	.4									2.3	4.1
NNW	1.0	.2										1.1	2.3
VARBL			1.7	2.1								3.4	11.6
CALM												72.4	
	17.8	21.8	20.9	6.7	.4							120.2	4.2

TOTAL NUMBER OF OBSERVATIONS 222

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION: 1710 COL A J BAKER AAF DL STATION NAME: 73-78,80-R2 YEARS: 1970 MONTH: 1970-1970
CLASS: ALL WEATHER HOURS (LST):
CONDITION:

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.5											1.5	1.5
NNE	.5											1.5	2.7
NE	.5	.5										1.3	3.4
ENE	1.0	1.5	2.1	.5								5.8	6.7
E	1.0	2.5	1.3	.5								6.3	6.1
ESE	.5	.5										1.0	2.5
SE	.5	.5										1.0	3.1
SSE	1.0	.5	.3									1.5	2.9
S	1.0	.5										2.1	2.4
SSW	1.0	3.5	1.6	.3	.3							6.3	6.2
SW	.5	2.5	.8	.5								4.5	6.1
WSW	1.0	2.2	1.8	.3								5.4	5.7
W	1.5	5.5	7.9	2.6	.8	.5						15.9	6.2
WNW	1.5	1.5	1.0									4.5	4.6
NW	1.5	1.5	.8	.5								4.2	5.3
NNW	1.0	.3										1.6	2.3
VARBL		.5	2.4	1.3	.3							4.2	11.4
CALM												26.2	
	16.8	28.1	19.9	7.1	1.3	.5						100.0	4.7

TOTAL NUMBER OF OBSERVATIONS 351

GENERAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

PERCENTAGE FREQUENCY OF WIND
DIRECTION AND SPEED
(FROM HOURLY OBSERVATIONS)

SURFACE WINDS

STATION 14710 COL A J E O BAKER AAF DL STATION NAME 72-78.81--2 YEARS 72 MONTH 1972-1972 HOURS (L.S.T.)

ALL WEATHER CLASS

CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.5	.5										1.0	4.0
NNE													
NE	.5											.5	2.0
ENE	1.0	3.0	1.0	2.0								7.0	7.4
E	.5	3.0	.5									4.0	5.4
ESE	1.0	.5										1.5	2.3
SE	1.0	.5										1.5	2.3
SSE	1.0											1.5	2.3
S	1.0	1.0	1.0									3.0	4.4
SSW	.5	3.0	3.0									6.0	6.2
SW	.5	6.0	2.0									8.5	5.7
WSW	1.0	6.5	2.5	1.5								11.5	6.4
W	1.0	4.0	5.0	4.0								14.0	5.4
WNW	1.0		1.0									3.0	4.0
NW	.5	1.0										3.0	3.0
NNW		1.0										1.0	5.0
VARBL			2.0	2.0	.5							5.0	11.0
CALM												23.4	
	16.0	3.0	16.9	9.5	.5							100.0	4.9

TOTAL NUMBER OF OBSERVATIONS 201

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
WEATHER SERVICE/MAC

SURFACE WINDS

PERCENTAGE FREQUENCY OF WIND DIRECTION AND SPEED (FROM HOURLY OBSERVATIONS)

STATION 710 COL A J BO BAKER AAF DL STATION NAME 77-78.60-82 YEARS 1977-1982 NORTH 000
CLASS ALL WEATHER HOURS (LST) 24
CONDITION

SPEED (KNTS) DIR.	1 - 3	4 - 6	7 - 10	11 - 16	17 - 21	22 - 27	28 - 33	34 - 40	41 - 47	48 - 55	≥ 56	%	MEAN WIND SPEED
N	.4	.2										.4	2.6
NNE	.7	.1										.4	2.3
NE	.7	.4	.2									1.1	4.3
ENE	1.1	2.3	1.3	.4								5.3	6.0
E	1.4	1.6	1.4	.4								4.8	5.6
ESE	1.2	.2										1.4	2.4
SE	.9	.3										1.2	2.4
SSE	1.5	.4	.2									1.9	2.7
S	2.5	1.4	.3	.6	.2							4.5	3.6
SSW	2.0	3.0	1.7	.5	.2							7.3	5.4
SW	1.5	4.0	3.2	.4	.1							9.1	6.1
WSW	1.3	4.1	3.1	1.0	.1	.2						9.5	6.8
W	1.7	3.3	6.5	2.2	.4	.1						14.5	5.0
WNW	1.0	1.1	.8	.4								3.2	4.1
NW	.6	.7	.2	.1								1.4	4.3
NNW	.6	.3	.2									.5	1.3
VARBL		.1	1.6	2.1	.7	.2						4.2	12.1
CALM												25.5	
	15.5	23.4	20.4	7.5	.9	.2						17.0	4.4

TOTAL NUMBER OF OBSERVATIONS 227

U S AIR FORCE
ENVIRONMENTAL TECHNICAL
APPLICATIONS CENTER

PART D

CEILING VERSUS VISIBILITY

This summary is a bivariate percentage frequency distribution by classes of ceiling from zero to equal to or greater than 20,000 feet and as a separate class "no ceiling", versus visibility in 16 classes from zero to equal to or greater than 10 miles. Data are derived from hourly observations, and three sets of tables are presented as follows:

1. Annual - all years and all hours combined
2. By month - all years and all hours combined
3. By month - by standard 3-hour groups

Due to the cumulative nature of this presentation, it is possible to determine the percentage frequency of occurrence for any given limit of ceiling or visibility separately, or in combination of ceiling and visibility. The totals progress to the right and downward. Ceiling may be determined independently by referring to totals in the extreme right hand column. Also, visibility may be determined independently by reference to the horizontal row of totals at the bottom of the page. The percentage frequency for which the station was meeting or exceeding any given set of minima may be determined from the figure at the intersection of the appropriate ceiling column and visibility row. Several examples in the use of these tables are shown on pages 2 and 3 below.

U. S. Weather Bureau and Navy stations did not report ceilings within the range 10,000 feet and higher prior to January 1949. Summaries prepared from data for these stations using the earlier period and data subsequent to January 1949 will be modified to limit ceilings to 10,000 feet. Short periods of record prior to 1949 for these stations will be eliminated from the summary. For Air Force stations, the "no ceiling" category includes clear and scattered conditions, and ceilings above 20,000 feet for period through June 1948. Beginning in July 1948 for Air Force stations and January 1949 for USWB and U. S. Navy stations the "no ceiling" category consists of observations with less than 6/10 total sky cover and those cases where total sky cover is 6/10 or more, but not more than 1/2 of the sky cover is opaque.


Beginning in January 1968, METAR stations report visibilities to 6 miles and then greater than 6 miles. Thus, for METAR stations, the category equal to or greater than 10 miles is not printed in the tables, unless the summary was for a period ending before January 1968.


Continued on Reverse Side

AD-A134 209 COL A J BD BAKER AAF GERMANY (WEST) LIMITED SURFACE
OBSERVATIONS CLIMATIC..(U) AIR FORCE ENVIRONMENTAL
TECHNICAL APPLICATIONS CENTER SCOTT A... 03 AUG 83
UNCLASSIFIED USAFETAC/DS-83/034 SBI-AD-EB50 427 F/G 4/2

2/3

NI





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

EXAMPLES FOR USE OF CEILING VERSUS VISIBILITY TABLES IN THIS TABULATION

CEILING (FEET)	VISIBILITY (STATUTE MILES)															
	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	$\geq 2\frac{1}{2}$	≥ 2	$\geq 1\frac{1}{2}$	$\geq 1\frac{1}{4}$	≥ 1	$\geq \frac{3}{4}$	$\geq \frac{1}{2}$	$\geq \frac{1}{4}$	$\geq \frac{1}{8}$	$\geq \frac{1}{16}$	≥ 0
NO CEILING																
1800																
1500					91.0											92.6
1200																
1000																
900																
800																
700																
600																
500										97.4						98.1
400																
300																
200																
100																
0					95.4		96.9			98.3						100.0

EXAMPLE # 1 Read ceiling values independently of visibility under column at right headed ≥ 0 .
For instance, from the table: Ceiling ≥ 1500 feet = 92.6%.
Ceiling ≥ 500 feet = 98.1%.

EXAMPLE # 2 Read visibilities independently of ceilings on bottom line opposite ≥ 0 . From the table:
Visibility ≥ 3 miles = 95.4%.
Visibility ≥ 2 miles = 96.9%.
Visibility ≥ 1 mile = 98.3%.

EXAMPLE # 3 To obtain combinations of ceiling with visibility, read figure at intersection of the two categories; i.e.: Ceiling ≥ 1500 feet with visibility ≥ 3 miles = 91.0%.

ADDITIONAL EXAMPLES

EXAMPLE # 4 Values below minimums stated in the table may be obtained by subtracting the value given in the table from 100%.
Thus, to obtain the percentage of observations with ceiling < 1500 feet and/or visibility < 3 miles, subtract the value read from the table at the intersection, which is 91.0, from 100.0. The answer 9.0 is the percentage of observations with ceiling < 1500 feet and/or visibility < 3 miles.

Likewise, the percentage of observations with ceiling < 500 feet and/or visibility < 1 mile is 2.6, obtained by subtracting 97.4 from 100.0.

EXAMPLE # 5 To find the percentage of observations falling within the two categories given in example above, subtract the value read from the table for the first set of limits from the value in the table for the second set of limits. The difference will be the percentage of observations meeting the lower set of limits, but not meeting the higher set of limits.

The value 91.0 read from the table at the intersection of ≥ 1500 feet with ≥ 3 miles, subtracted from 97.4 read from the table at the intersection of ≥ 500 feet with ≥ 1 mile is equal to 6.4%. Thus; 6.4 percent of the observations meet the criteria: "ceiling ≥ 500 feet with visibility > 1 mile, but < 3 miles; or ceiling ≥ 500 feet, but < 1500 feet with visibility ≥ 1 mile."

Since these tabulations are prepared in several ways including by month, by 3-hour groups it is possible to determine diurnal variations of ceiling and visibility limits as well as probabilities of various ceiling-visibility combinations.

JOINT CLIMATE BRANCH
USAF ETAC
ALL WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

124710
STATION

COL A J BO BAKER AAF DL
STATION NAME

73-78,80-82
YEAR

JAN
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1600-2300
HOURS

CEILING FEET	VISIBILITY STATUTE MILES															
	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2.5	≥ 2	≥ 1.5	≥ 1	≥ .75	≥ .5	≥ .25	≥ .1	≥ .05	≥ .01	≥ .00
NO CEILING	15.3	28.5	28.7	29.6	29.7	29.7	30.1	30.3	30.3	30.3	30.4	31.3	31.5	32.3	32.5	33.2
≥ 20000	22.2	34.7	34.9	35.9	36.4	36.6	36.9	37.1	37.1	37.4	37.6	38.5	39.0	39.8	40.0	40.7
≥ 18000	22.2	34.7	34.9	35.9	36.4	36.6	36.9	37.1	37.1	37.4	37.6	38.5	39.0	39.8	40.0	40.7
≥ 16000	22.2	34.7	34.9	35.9	36.4	36.6	36.9	37.1	37.1	37.4	37.6	38.5	39.0	39.8	40.0	40.7
≥ 14000	22.2	34.7	34.9	35.9	36.4	36.6	36.9	37.1	37.1	37.4	37.6	38.5	39.0	39.8	40.0	40.7
≥ 12000	22.2	34.7	34.9	35.9	36.4	36.6	36.9	37.1	37.1	37.4	37.6	38.5	39.0	39.8	40.0	40.7
≥ 10000	22.2	34.7	34.9	35.9	36.4	36.6	36.9	37.1	37.1	37.4	37.6	38.5	39.0	39.8	40.0	40.7
≥ 9000	23.4	36.4	36.6	37.6	38.1	38.3	38.6	38.8	38.8	39.1	39.3	40.2	40.7	41.7	41.9	42.6
≥ 8000	24.3	38.5	38.6	39.7	40.2	40.3	40.7	40.9	40.9	41.2	41.4	42.2	42.7	43.5	43.9	44.6
≥ 7000	25.1	39.3	39.5	40.5	41.0	41.2	41.5	41.7	41.7	42.1	42.2	43.1	43.6	44.6	44.8	45.5
≥ 6000	25.3	39.5	39.7	41.7	41.2	41.4	41.7	41.9	41.9	42.2	42.4	43.2	43.8	44.8	45.0	45.6
≥ 5000	26.1	40.3	40.5	41.5	42.1	42.2	42.6	42.7	42.7	43.1	43.2	44.1	44.6	45.6	45.8	46.5
≥ 4500	26.3	40.9	41.3	42.1	42.6	42.7	43.1	43.2	43.2	43.6	43.8	44.6	45.1	46.2	46.3	47.0
≥ 4000	27.9	44.3	44.4	45.5	46.0	46.2	46.5	46.7	46.7	47.0	47.2	48.0	48.5	49.6	49.7	50.4
≥ 3500	31.4	47.4	47.5	48.5	49.1	49.2	49.6	49.7	49.7	50.1	50.3	51.1	51.6	52.6	52.8	53.5
≥ 3000	32.3	50.6	50.9	52.0	52.5	52.6	53.0	53.2	53.2	53.5	53.7	54.5	55.0	56.1	56.2	56.9
≥ 2500	34.9	53.3	53.7	54.9	55.4	55.6	55.9	56.1	56.1	56.4	56.6	57.4	57.9	59.0	59.1	59.8
≥ 2000	35.4	54.9	55.6	57.4	58.6	58.8	59.8	60.0	60.0	60.3	60.5	61.4	61.9	62.9	63.1	63.8
≥ 1800	36.8	56.8	57.6	60.2	61.5	61.7	62.7	62.9	62.9	63.2	63.4	64.3	64.8	65.8	66.0	66.7
≥ 1600	36.5	60.5	61.5	64.4	66.0	66.5	68.2	68.4	68.4	68.7	68.9	69.7	70.3	71.3	71.5	72.1
≥ 1400	38.8	62.1	63.1	66.7	68.4	69.6	71.6	72.5	72.5	73.0	73.2	74.0	74.7	75.7	75.9	76.6
≥ 1200	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4
≥ 1000	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4
≥ 900	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4
≥ 800	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4
≥ 700	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4
≥ 600	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4
≥ 500	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4
≥ 400	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4
≥ 300	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4
≥ 200	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4
≥ 100	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4
≥ 50	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4
≥ 20	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4
≥ 10	38.8	62.4	63.4	67.7	69.4	71.3	74.0	75.0	75.0	76.6	77.6	78.6	79.5	80.5	80.7	81.4

TOTAL NUMBER OF OBSERVATIONS

585

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AF WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

100710 COL A J BO BAKER AAF DL

73-78,80-82

JAN

STATION

STATION NAME

YEARS

MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

0900-1100

HOURLY

CEILING FEET	VISIBILITY, STATUTE MILES															
	≥10	≥6	≥5	≥4	≥3	≥2	≥2	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1
NO CEILING	19.1	29.3	29.3	30.0	30.3	30.3	30.7	31.2	31.3	31.8	31.8	31.8	32.0	32.2	32.3	32.5
≥ 2000	12.1	33.3	33.3	34.0	34.5	34.5	34.8	35.3	35.7	36.2	36.2	36.2	36.3	36.5	36.7	37.2
≥ 1800	22.9	34.2	34.2	34.8	35.3	35.3	35.7	36.2	36.5	37.2	37.2	37.2	37.4	37.5	37.7	38.2
≥ 1600	23.3	34.5	34.5	35.2	35.7	35.7	36.0	36.5	36.9	37.5	37.5	37.5	37.7	37.9	38.0	38.5
≥ 1400	23.3	34.5	34.5	35.2	35.7	35.7	36.0	36.5	36.9	37.5	37.5	37.5	37.7	37.9	38.0	38.5
≥ 1200	23.3	34.5	34.5	35.2	35.7	35.7	36.0	36.5	36.9	37.5	37.5	37.5	37.7	37.9	38.0	38.5
≥ 1000	23.3	34.5	34.5	35.2	35.7	35.7	36.0	36.5	36.9	37.5	37.5	37.5	37.7	37.9	38.0	38.5
≥ 900	24.3	37.2	37.2	37.9	38.4	38.4	38.9	39.5	39.9	40.5	40.5	40.5	40.7	40.9	41.0	41.5
≥ 800	26.3	40.4	40.4	41.0	41.5	41.5	42.0	42.7	43.0	43.7	43.7	43.7	43.9	44.1	44.2	44.7
≥ 700	27.5	41.7	41.7	42.4	42.9	42.9	43.4	44.1	44.4	45.1	45.1	45.1	45.2	45.4	45.5	46.1
≥ 600	28.1	42.4	42.4	43.4	43.9	43.9	44.4	45.1	45.4	46.1	46.1	46.1	46.2	46.4	46.5	47.1
≥ 500	28.8	43.4	43.4	44.4	44.9	44.9	45.4	46.1	46.4	47.1	47.1	47.1	47.2	47.4	47.6	48.1
≥ 4500	29.3	44.2	44.2	45.2	45.7	45.7	46.2	46.9	47.2	47.9	47.9	47.9	48.1	48.2	48.4	48.9
≥ 4000	31.5	47.9	47.9	48.9	49.4	49.4	49.9	50.6	50.9	51.6	51.6	51.6	51.8	51.9	52.1	52.6
≥ 3500	34.3	51.9	51.9	52.9	53.4	53.4	53.9	54.6	54.9	55.6	55.6	55.6	55.8	55.9	56.1	56.6
≥ 3000	37.2	56.3	56.3	57.8	58.5	58.5	59.0	59.8	60.1	60.8	60.8	60.8	61.0	61.1	61.3	61.9
≥ 2500	39.0	59.1	59.3	61.0	61.6	61.6	62.3	63.3	63.7	64.3	64.3	64.3	64.5	64.7	64.8	65.3
≥ 2000	39.9	61.3	61.5	63.8	64.7	65.2	66.0	67.2	67.5	68.2	68.2	68.2	68.3	68.5	68.7	69.2
≥ 1800	40.2	61.8	62.5	65.2	66.2	66.7	67.8	69.2	69.5	70.2	70.2	70.2	70.4	70.5	70.7	71.2
≥ 1600	40.5	63.3	64.3	67.3	68.5	69.0	70.7	72.4	72.7	73.7	73.7	73.7	73.9	74.0	74.2	74.7
≥ 1400	40.9	64.0	65.7	69.0	70.4	71.0	73.0	75.2	76.0	77.2	77.6	77.6	77.7	77.9	78.1	78.5
≥ 1200	40.9	64.5	65.7	69.8	71.4	72.5	75.0	77.7	78.7	81.1	81.9	82.1	82.2	82.9	83.1	83.6
≥ 1000	40.9	64.5	65.7	69.8	71.5	72.7	75.2	77.9	78.9	81.6	82.6	82.7	82.9	83.6	83.8	84.7
≥ 900	40.9	64.5	65.7	69.8	71.5	72.7	75.2	77.9	78.9	81.6	82.6	82.7	82.9	83.6	83.8	84.7
≥ 800	40.9	64.5	65.7	69.8	71.5	72.7	75.2	77.9	78.9	81.6	82.6	82.7	82.9	83.6	83.8	84.7
≥ 700	40.9	64.5	65.7	69.8	71.5	72.7	75.2	77.9	78.9	81.6	82.6	82.7	82.9	83.6	83.8	84.7
≥ 600	40.9	64.5	65.7	69.8	71.5	72.7	75.2	77.9	78.9	81.6	82.6	82.7	82.9	83.6	83.8	84.7
≥ 500	40.9	64.5	65.7	69.8	71.5	72.7	75.2	77.9	78.9	81.6	82.6	82.7	82.9	83.6	83.8	84.7
≥ 400	40.9	64.5	65.7	69.8	71.5	72.7	75.2	77.9	78.9	81.6	82.6	82.7	82.9	83.6	83.8	84.7
≥ 300	40.9	64.5	65.7	69.8	71.5	72.7	75.2	77.9	78.9	81.6	82.6	82.7	82.9	83.6	83.8	84.7
≥ 200	40.9	64.5	65.7	69.8	71.5	72.7	75.2	77.9	78.9	81.6	82.6	82.7	82.9	83.6	83.8	84.7
≥ 100	40.9	64.5	65.7	69.8	71.5	72.7	75.2	77.9	78.9	81.6	82.6	82.7	82.9	83.6	83.8	84.7
≥ 0	40.9	64.5	65.7	69.8	71.5	72.7	75.2	77.9	78.9	81.6	82.6	82.7	82.9	83.6	83.8	84.7

TOTAL NUMBER OF OBSERVATIONS

557

USAF ETAC

FORM

0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 9710
STATION

COL A J RO BAKER AAF DL
STATION NAME

73-79, EC-52
YEAR

JAN
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1200-1400
HOURS

CEILING FEET		VISIBILITY STATUTE MILES															
		≥10	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12
NO.	FILLS	17.4	26.7	26.9	28.3	28.9	28.9	28.9	29.1	29.1	29.1	29.1	29.1	29.1	29.1	29.3	29.3
2	2000	23.2	34.7	34.9	36.4	37.0	37.0	37.2	37.4	37.4	37.4	37.4	37.4	37.4	37.4	37.6	37.6
2	1800	23.0	35.1	35.2	36.8	37.4	37.4	37.6	37.8	37.8	37.8	37.8	37.8	37.8	37.8	38.0	38.0
2	1600	23.4	35.0	35.2	36.8	37.4	37.4	37.6	37.8	37.8	37.8	37.8	37.8	37.8	37.8	38.0	38.0
2	1400	23.4	35.2	35.4	37.0	37.6	37.6	37.8	38.0	38.0	38.0	38.0	38.0	38.0	38.2	38.2	38.2
2	1200	25.0	36.6	36.8	38.4	39.0	39.0	39.2	39.4	39.4	39.4	39.4	39.4	39.4	39.6	39.6	39.6
2	1000	25.4	38.6	38.8	40.6	41.2	41.2	41.6	41.8	41.8	41.8	41.8	41.8	41.8	42.0	42.0	42.0
2	900	27.2	40.0	40.2	42.0	42.6	42.6	43.0	43.2	43.2	43.2	43.2	43.2	43.2	43.4	43.4	43.4
2	800	28.7	42.8	43.2	45.1	45.7	45.7	46.1	46.3	46.3	46.3	46.3	46.3	46.3	46.5	46.5	46.5
2	700	30.3	44.8	45.1	46.9	47.7	47.7	48.1	48.3	48.3	48.3	48.3	48.3	48.3	48.5	48.5	48.5
2	600	31.1	45.5	45.4	47.7	48.5	48.5	48.9	49.1	49.1	49.1	49.1	49.1	49.1	49.3	49.3	49.3
2	500	32.9	47.5	47.9	49.7	50.5	50.5	50.9	51.1	51.1	51.1	51.1	51.1	51.1	51.3	51.3	51.3
2	450	33.4	49.5	49.9	51.7	52.5	52.5	52.9	53.1	53.1	53.1	53.1	53.1	53.1	53.3	53.3	53.3
2	400	35.4	51.9	52.3	54.1	54.9	54.9	55.6	55.8	55.8	55.8	55.8	55.8	55.8	56.0	56.0	56.0
2	350	37.2	54.5	54.9	56.6	57.4	57.4	58.2	58.4	58.4	58.4	58.4	58.4	58.4	58.6	58.6	58.6
2	300	41.2	61.0	61.8	64.4	65.1	65.1	65.9	66.1	66.1	66.1	66.1	66.1	66.1	66.3	66.3	66.3
2	250	43.0	63.2	64.2	66.7	67.5	67.5	68.7	69.1	69.1	69.1	69.1	69.1	69.1	69.3	69.3	69.3
2	200	44.2	65.5	66.9	69.7	70.5	71.1	72.9	73.5	73.5	73.7	73.7	73.7	73.7	73.9	73.9	73.9
2	180	45.0	67.1	68.5	72.1	72.9	73.7	75.4	76.4	76.4	76.6	76.6	76.6	76.6	76.8	76.8	76.8
2	150	45.0	67.9	69.3	73.3	74.5	75.4	77.8	79.0	79.0	79.2	79.2	79.2	79.2	79.6	79.6	79.6
2	120	45.1	68.3	69.7	74.7	75.8	76.8	79.6	81.0	81.0	81.2	81.2	81.2	81.4	82.0	82.2	82.2
2	100	45.1	69.5	70.9	76.0	77.4	78.4	81.6	83.4	83.6	84.2	84.4	84.6	84.8	86.3	86.5	86.5
2	90	45.1	69.5	70.9	76.0	77.4	78.4	82.0	84.0	84.2	85.3	85.5	85.7	85.9	87.5	87.7	87.7
2	80	45.1	69.5	70.9	76.0	77.6	78.6	83.2	85.1	85.5	87.3	87.5	87.7	87.9	89.5	89.7	89.7
2	70	45.1	69.7	71.1	76.2	77.8	79.0	83.8	86.1	86.7	89.1	89.3	89.5	89.9	91.5	91.7	91.7
2	60	45.1	69.7	71.1	76.4	78.0	79.2	84.2	87.1	87.9	91.9	92.3	92.5	92.9	94.9	95.4	95.4
2	50	45.1	69.7	71.1	76.4	78.0	79.2	84.4	87.3	88.3	92.9	93.3	94.1	94.5	96.4	97.0	97.0
2	40	45.1	69.7	71.1	76.4	78.0	79.2	84.4	87.3	88.5	93.7	94.5	95.2	96.0	98.6	99.2	99.2
2	30	45.1	69.7	71.1	76.4	78.0	79.2	84.4	87.3	88.5	93.7	94.5	95.2	96.6	99.2	99.9	99.8
2	20	45.1	69.7	71.1	76.4	78.0	79.2	84.4	87.3	88.5	93.9	94.7	95.4	96.8	99.4	100.0	100.0
2	10	45.1	69.7	71.1	76.4	78.0	79.2	84.4	87.3	88.5	93.9	94.7	95.4	96.8	99.4	100.0	100.0
2	0	45.1	69.7	71.1	76.4	78.0	79.2	84.4	87.3	88.5	93.9	94.7	95.4	96.8	99.4	100.0	100.0

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

104710
STATION

CPL A J 30 BAKER AAF DL
STATION NAME

73-78,82
YEAR

JAN
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1430-1730
HOURS

CEILING FEET	VISIBILITY STATUTE MILES															
	≥10	≥6	≥5	≥4	≥3	≥2.5	≥2	≥1.5	≥1	≥0.5	≥0.25	≥0.15	≥0.1	≥0.05	≥0.025	≥0.01
NO CEILING	17.2	22.7	22.9	24.1	24.4	24.9	25.1	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4	25.4
≥20000	22.7	31.8	31.7	32.3	32.5	33.0	33.3	33.5	33.5	33.5	33.5	33.5	33.5	33.5	33.5	33.5
≥18000	23.2	31.3	31.5	32.8	33.0	33.5	33.7	34.0	34.0	34.0	34.0	34.0	34.0	34.0	34.0	34.0
≥16000	23.2	31.3	31.5	32.8	33.0	33.5	33.7	34.0	34.0	34.0	34.0	34.0	34.0	34.0	34.0	34.0
≥14000	23.2	31.3	31.5	32.8	33.0	33.5	33.7	34.0	34.0	34.0	34.0	34.0	34.0	34.0	34.0	34.0
≥12000	23.2	31.3	31.5	32.8	33.0	33.5	33.7	34.0	34.0	34.0	34.0	34.0	34.0	34.0	34.0	34.0
≥10000	24.1	33.5	33.7	35.0	35.2	35.7	36.0	36.2	36.2	36.2	36.2	36.2	36.2	36.2	36.2	36.2
≥9000	25.9	35.2	35.5	36.7	36.9	37.4	37.7	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
≥8000	28.6	39.2	39.4	40.6	40.9	41.4	41.6	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9
≥7000	30.0	40.9	41.1	42.9	43.1	43.6	43.8	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.1
≥6000	30.5	41.9	42.1	43.8	44.1	44.6	44.8	45.1	45.1	45.1	45.1	45.1	45.1	45.1	45.1	45.1
≥5000	31.3	43.3	44.1	45.8	46.1	46.6	46.8	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0
≥4500	32.5	46.1	46.3	48.0	48.3	48.8	49.0	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
≥4000	35.5	49.5	49.8	51.7	52.0	52.5	52.7	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0
≥3500	36.2	52.2	52.5	54.4	54.7	55.2	55.4	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7
≥3000	40.9	59.1	59.4	62.3	62.6	63.1	63.5	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8
≥2500	41.1	60.1	60.3	63.3	64.0	64.5	65.3	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8
≥2000	41.4	62.3	62.6	66.0	67.5	68.0	68.7	69.2	69.2	69.7	69.7	69.7	69.7	70.0	70.0	70.0
≥1800	42.1	64.8	65.1	68.7	70.2	70.7	71.4	71.9	71.9	72.4	72.4	72.4	72.7	72.7	72.7	72.7
≥1600	42.4	65.8	66.3	70.7	72.7	73.2	74.6	75.1	75.1	75.9	75.9	75.9	76.1	76.1	76.1	76.1
≥1400	42.4	67.0	67.5	72.7	74.9	75.9	77.6	78.1	78.1	79.1	79.3	79.3	79.6	80.0	80.0	80.0
≥1200	42.9	68.2	68.7	74.4	76.8	78.1	80.3	81.0	81.0	82.5	83.7	84.7	85.2	86.7	86.7	86.7
≥1000	42.9	68.2	68.7	74.4	76.8	78.1	80.3	81.0	81.0	82.5	83.7	84.7	85.2	86.7	86.7	86.7
≥900	42.9	68.2	68.7	74.4	76.8	78.1	80.3	81.0	81.0	82.5	83.7	84.7	85.2	86.7	86.7	86.7
≥800	43.1	68.5	69.0	74.6	77.8	79.3	82.0	83.5	83.5	86.0	87.2	88.2	89.7	90.1	90.1	90.1
≥700	43.1	68.5	69.0	74.6	77.8	79.3	82.0	83.5	83.5	86.0	87.2	88.2	89.7	90.1	90.1	90.1
≥600	43.1	68.5	69.0	74.6	77.8	79.3	82.0	83.5	83.5	86.0	87.2	88.2	89.7	90.1	90.1	90.1
≥500	43.1	68.5	69.0	74.6	77.8	79.3	82.0	83.5	83.5	86.0	87.2	88.2	89.7	90.1	90.1	90.1
≥400	43.1	68.5	69.0	74.6	77.8	79.3	82.0	83.5	83.5	86.0	87.2	88.2	89.7	90.1	90.1	90.1
≥300	43.1	68.5	69.0	74.6	77.8	79.3	82.0	83.5	83.5	86.0	87.2	88.2	89.7	90.1	90.1	90.1
≥200	43.1	68.5	69.0	74.6	77.8	79.3	82.0	83.5	83.5	86.0	87.2	88.2	89.7	90.1	90.1	90.1
≥100	43.1	68.5	69.0	74.6	77.8	79.3	82.0	83.5	83.5	86.0	87.2	88.2	89.7	90.1	90.1	90.1
≥50	43.1	68.5	69.0	74.6	77.8	79.3	82.0	83.5	83.5	86.0	87.2	88.2	89.7	90.1	90.1	90.1
≥20	43.1	68.5	69.0	74.6	77.8	79.3	82.0	83.5	83.5	86.0	87.2	88.2	89.7	90.1	90.1	90.1
≥10	43.1	68.5	69.0	74.6	77.8	79.3	82.0	83.5	83.5	86.0	87.2	88.2	89.7	90.1	90.1	90.1

TOTAL NUMBER OF OBSERVATIONS

436

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 9710

COL A J BO BAKER AAF DL

73-79,82

JAN

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1970-2000

CEILING FEET	VISIBILITY - STATUTE MILES															
	≥10	≥6	≥5	≥4	≥3	≥2.5	≥2	≥1.5	≥1	≥0.5	≥0.25	≥0.1	≥0.05	≥0.025	≥0.01	≥0.005
NO. CEILING	14.1	21.5	21.5	22.7	23.4	23.4	24.6	25.0	25.0	25.0	25.0	25.0	25.0	25.4	25.4	26.2
≥ 20000	19.1	29.7	29.7	30.9	31.6	31.6	32.8	33.2	33.2	33.2	33.2	33.2	33.2	33.6	33.6	34.4
≥ 18000	19.1	30.5	30.5	31.6	32.4	32.4	33.6	34.0	34.0	34.0	34.0	34.0	34.0	34.4	34.4	35.2
≥ 16000	19.1	30.5	30.5	31.6	32.4	32.4	33.6	34.0	34.0	34.0	34.0	34.0	34.0	34.4	34.4	35.2
≥ 14000	19.1	30.5	30.5	31.6	32.4	32.4	33.6	34.0	34.0	34.0	34.0	34.0	34.0	34.4	34.4	35.2
≥ 12000	19.1	30.5	30.5	32.0	32.8	32.8	34.0	34.4	34.4	34.4	34.4	34.4	34.4	34.8	34.8	35.6
≥ 10000	19.1	31.3	31.3	32.4	33.2	33.2	34.4	34.8	34.8	34.8	34.8	34.8	34.8	35.2	35.2	35.9
≥ 8000	21.1	33.6	33.6	34.8	35.5	35.5	36.7	37.1	37.1	37.1	37.1	37.1	37.1	37.5	37.5	38.3
≥ 6000	22.7	35.5	35.5	37.1	38.3	38.3	39.5	39.8	39.8	39.8	39.8	39.8	39.8	40.2	40.2	41.0
≥ 4000	23.4	36.7	37.1	38.3	39.5	39.5	40.6	41.0	41.0	41.0	41.0	41.0	41.0	41.4	41.4	42.2
≥ 3000	24.2	37.5	37.9	39.1	40.2	40.2	41.4	41.8	41.8	41.8	41.8	41.8	41.8	42.2	42.2	43.0
≥ 2000	25.8	39.1	39.5	40.6	41.8	41.8	43.0	43.4	43.4	43.4	43.4	43.4	43.4	43.8	43.8	44.6
≥ 1800	27.3	41.0	41.4	42.6	43.8	43.8	44.9	45.3	45.3	45.3	45.3	45.3	45.3	45.7	45.7	46.5
≥ 1600	29.3	44.9	45.3	46.5	47.7	47.7	48.8	49.2	49.2	49.2	49.2	49.2	49.2	49.6	49.6	50.4
≥ 1400	30.1	47.7	48.1	49.2	50.4	50.4	51.6	52.0	52.0	52.0	52.0	52.0	52.0	52.3	52.3	53.1
≥ 1200	32.8	51.2	51.6	53.5	54.7	54.7	56.6	57.0	57.0	57.0	57.0	57.0	57.0	57.4	57.4	58.2
≥ 1000	33.2	52.0	52.3	54.3	55.5	55.5	57.4	57.8	57.8	58.2	58.2	58.2	58.2	58.6	58.6	59.4
≥ 800	33.6	54.7	55.5	57.4	58.6	58.6	60.5	60.9	60.9	61.3	61.3	61.3	61.3	61.7	61.7	62.5
≥ 600	34.4	56.3	57.4	59.8	60.9	60.9	62.9	63.3	63.3	63.7	63.7	63.7	63.7	64.1	64.1	64.8
≥ 400	35.2	59.8	61.7	66.0	67.6	67.6	69.9	70.3	70.3	70.7	70.7	70.7	70.7	71.9	71.9	72.7
≥ 300	35.9	60.9	62.9	68.0	69.5	69.5	71.9	72.3	72.3	73.8	73.8	73.8	73.8	75.0	75.0	75.8
≥ 200	35.9	61.7	63.7	70.3	73.0	73.0	76.6	77.0	77.0	78.5	78.5	78.5	78.5	80.5	80.5	81.4
≥ 100	36.3	62.1	64.1	70.7	73.4	73.4	77.0	77.7	77.7	79.3	79.3	79.3	79.3	81.3	81.3	82.2
≥ 80	36.7	62.5	64.5	71.1	75.0	75.0	78.9	79.7	79.7	81.3	81.3	81.3	81.3	83.2	83.2	84.1
≥ 60	36.7	62.5	64.5	71.1	75.0	75.0	78.9	79.7	79.7	81.3	81.3	81.3	81.3	83.2	83.2	84.1
≥ 40	36.7	62.5	64.5	71.1	75.0	75.0	78.9	79.7	79.7	81.3	81.3	81.3	81.3	83.2	83.2	84.1
≥ 30	36.7	62.5	64.5	71.1	75.0	75.0	78.9	79.7	79.7	81.3	81.3	81.3	81.3	83.2	83.2	84.1
≥ 20	36.7	62.5	64.5	71.1	75.0	75.0	78.9	79.7	79.7	81.3	81.3	81.3	81.3	83.2	83.2	84.1
≥ 10	36.7	62.5	64.5	71.1	75.0	75.0	78.9	79.7	79.7	81.3	81.3	81.3	81.3	83.2	83.2	84.1
≥ 5	36.7	62.5	64.5	71.1	75.0	75.0	78.9	79.7	79.7	81.3	81.3	81.3	81.3	83.2	83.2	84.1
≥ 2	36.7	62.5	64.5	71.1	75.0	75.0	78.9	79.7	79.7	81.3	81.3	81.3	81.3	83.2	83.2	84.1

TOTAL NUMBER OF OBSERVATIONS 256

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 4715 COL A J BO BAKER AAF DL

73-78,80-82

JAN

STATION

STATION NAME

YEAR

ALL

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

CEILING FEET	VISIBILITY: STATUTE MILES															
	≥10	≥6	≥5	≥4	≥3	≥2.5	≥2	≥1.5	≥1	≥0.75	≥0.5	≥0.25	≥0.15	≥0.1	≥0.05	≥0.01
NO. CEILING	17.7	20.6	26.7	27.7	28.1	28.2	28.5	28.8	28.9	29.0	29.0	29.2	29.4	29.6	29.8	30.1
≥ 20000	22.1	33.1	33.2	34.4	34.9	35.0	35.4	35.7	35.8	36.0	36.0	36.2	36.4	36.7	35.8	37.2
≥ 18000	22.4	33.6	33.7	34.6	35.3	35.5	35.8	36.1	36.2	36.5	36.5	36.7	37.0	37.2	37.3	37.7
≥ 16000	22.6	33.7	33.8	34.9	35.4	35.5	35.9	36.2	36.3	36.6	36.6	36.8	37.0	37.3	37.4	37.8
≥ 14000	22.6	33.7	33.8	35.0	35.5	35.6	36.0	36.3	36.4	36.6	36.7	36.9	37.1	37.3	37.5	37.8
≥ 12000	23.7	34.1	34.3	35.4	35.9	36.0	36.4	36.7	36.8	37.0	37.1	37.3	37.5	37.8	37.9	38.3
≥ 10000	23.0	35.6	35.8	36.9	37.4	37.5	38.0	38.4	38.4	38.7	38.7	39.0	39.2	39.4	39.5	39.9
≥ 9000	24.6	36.9	37.0	38.1	38.7	38.8	39.3	39.6	39.7	39.9	40.0	40.2	40.4	40.7	40.8	41.2
≥ 8000	26.3	39.7	39.9	41.0	41.6	41.6	42.2	42.6	42.7	42.9	43.0	43.2	43.4	43.7	43.8	44.2
≥ 7000	27.5	41.1	41.3	42.5	43.1	43.3	43.7	44.1	44.1	44.4	44.4	44.7	44.9	45.2	45.3	45.7
≥ 6000	28.1	41.7	41.9	43.3	43.8	44.0	44.4	44.8	44.9	45.1	45.2	45.4	45.6	45.9	46.0	46.4
≥ 5000	29.1	43.1	43.3	44.7	45.3	45.4	45.8	46.2	46.7	46.5	46.6	46.8	47.0	47.3	47.4	47.8
≥ 4500	29.9	44.5	44.7	46.0	46.6	46.7	47.2	47.6	47.6	47.9	47.9	48.1	48.4	48.7	48.8	49.2
≥ 4000	31.9	47.8	48.0	49.4	50.0	50.1	50.7	51.0	51.1	51.3	51.4	51.6	51.8	52.1	52.2	52.6
≥ 3500	33.3	50.9	51.1	52.5	53.1	53.2	53.8	54.1	54.2	54.4	54.5	54.7	54.9	55.2	55.3	55.7
≥ 3000	37.1	55.8	56.2	58.1	58.7	58.8	59.5	59.9	60.0	60.2	60.3	60.5	60.7	61.0	61.1	61.5
≥ 2500	38.6	57.9	58.4	60.4	61.1	61.2	62.1	62.6	62.7	63.0	63.0	63.2	63.4	63.7	63.9	64.2
≥ 2000	39.3	60.0	60.7	63.2	64.2	64.6	65.8	66.4	66.5	66.9	67.0	67.2	67.4	67.7	67.9	68.2
≥ 1800	40.7	61.6	62.5	65.4	66.6	67.0	68.3	69.0	69.1	69.5	69.6	69.8	70.0	70.3	70.5	70.8
≥ 1500	40.7	63.6	64.8	68.3	69.8	70.3	72.2	73.1	73.1	73.7	73.7	73.9	74.3	74.6	74.9	75.1
≥ 1200	41.1	64.6	65.8	70.2	71.7	72.6	74.8	75.9	76.2	77.0	77.1	77.4	77.8	78.3	78.4	78.8
≥ 1000	41.1	65.4	66.5	71.5	73.3	74.5	77.3	78.8	79.1	80.6	81.4	82.0	82.8	83.6	83.9	84.3
≥ 900	41.1	65.4	66.5	71.5	73.4	74.6	77.5	79.1	79.4	81.3	82.2	82.9	83.7	84.6	84.8	85.1
≥ 800	41.2	65.5	66.7	71.6	73.9	75.2	78.5	80.2	80.6	82.8	83.7	84.4	85.4	86.3	86.5	86.8
≥ 700	41.2	65.6	66.7	71.7	74.1	75.4	79.0	81.2	81.6	84.1	85.2	86.0	87.3	88.2	88.4	88.8
≥ 600	41.2	65.6	66.7	71.8	74.1	75.4	79.3	81.7	82.4	85.7	87.0	88.1	89.5	90.8	91.2	91.7
≥ 500	41.2	65.6	66.7	71.8	74.2	75.5	79.5	82.5	83.2	87.2	89.0	90.3	91.8	93.2	93.7	94.2
≥ 400	41.2	65.6	66.7	71.8	74.2	75.5	79.7	82.7	83.7	88.2	90.2	91.7	94.0	96.1	96.7	97.2
≥ 300	41.2	65.6	66.7	71.8	74.2	75.5	79.7	82.8	83.8	88.4	90.4	92.0	94.6	97.1	98.0	98.5
≥ 200	41.2	65.6	66.7	71.8	74.2	75.5	79.7	82.8	83.8	88.5	90.6	92.2	94.8	97.7	98.9	99.5
≥ 100	41.2	65.6	66.7	71.8	74.2	75.5	79.7	82.8	83.8	88.5	90.6	92.2	94.8	97.7	99.1	99.8
≥ 0	41.2	65.6	66.7	71.8	74.2	75.5	79.7	82.8	83.8	88.5	90.6	92.2	94.8	97.7	99.1	100.0

TOTAL NUMBER OF OBSERVATIONS 2349

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 4710
STATION

COL A J 30 BAKER AAF DL
STATION NAME

73-78,80-82
YEAR

FEET
DOCS

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

0622-2520
DATE

CEILING FEET	VISIBILITY, STATUTE MILES															
	≥10	≥6	≥5	≥4	≥3	≥2	≥2	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1
NO CEILING	23.1	28.8	29.6	31.4	31.7	31.9	32.9	32.9	33.1	34.0	34.7	34.5	34.7	35.2	35.9	36.2
≥ 20000	25.4	31.9	32.8	34.7	35.2	35.4	36.6	36.6	36.7	37.6	37.6	38.3	39.6	39.2	39.9	40.2
≥ 18000	25.4	31.9	32.8	34.7	35.2	35.5	36.9	36.9	37.1	38.0	38.0	38.6	39.0	39.5	40.2	40.6
≥ 16000	25.4	31.9	32.8	34.7	35.2	35.5	36.9	36.9	37.1	38.0	38.0	38.6	39.0	39.5	40.2	40.6
≥ 14000	25.4	31.9	32.8	34.7	35.2	35.5	36.9	36.9	37.1	38.0	38.0	38.6	39.0	39.5	40.2	40.6
≥ 12000	25.4	31.9	32.8	34.7	35.2	35.5	36.9	36.9	37.1	38.0	38.0	38.6	39.0	39.5	40.2	40.6
≥ 10000	25.4	32.1	32.9	34.6	35.4	35.9	37.3	37.3	37.4	38.3	38.3	39.0	39.3	39.9	40.6	40.9
≥ 9000	25.4	32.2	33.1	35.0	35.5	36.0	37.4	37.4	37.6	38.5	38.5	39.2	39.5	40.0	40.7	41.1
≥ 8000	27.6	35.0	35.9	37.8	38.3	38.8	40.2	40.2	40.4	41.2	41.2	41.9	42.3	42.8	43.5	43.8
≥ 7000	28.4	36.6	37.6	39.5	40.0	40.6	41.9	41.9	42.1	43.0	43.0	43.7	44.0	44.5	45.2	45.6
≥ 6000	28.4	36.7	37.8	39.7	40.2	40.7	42.1	42.1	42.3	43.2	43.2	43.8	44.2	44.7	45.4	45.8
≥ 5000	29.1	37.8	38.9	41.1	41.6	42.1	43.5	43.5	43.7	44.5	44.5	45.2	45.6	46.1	46.8	47.1
≥ 4500	30.2	39.2	40.2	42.5	43.0	43.5	45.1	45.1	45.2	46.1	46.1	46.8	47.1	47.7	48.4	48.7
≥ 4000	31.5	41.7	41.8	44.0	44.5	45.1	46.8	46.8	47.0	47.8	47.8	48.5	48.9	49.4	50.1	50.4
≥ 3500	34.5	44.0	45.2	48.2	48.7	49.2	51.0	51.0	51.1	52.0	52.0	52.7	53.0	53.6	54.2	54.6
≥ 3000	36.0	47.0	48.4	52.2	53.2	53.7	55.6	56.0	56.2	57.0	57.0	57.7	58.1	58.6	59.3	59.6
≥ 2500	37.3	49.9	51.3	55.6	57.0	57.5	59.4	59.8	60.1	61.0	61.0	61.9	62.4	62.9	63.5	64.0
≥ 2000	38.6	51.6	53.7	58.6	60.3	60.8	63.3	63.6	64.1	65.2	65.2	66.0	66.6	67.1	67.8	68.1
≥ 1800	39.3	52.5	54.6	59.8	62.0	62.6	65.0	65.3	66.0	67.2	67.2	68.1	68.6	69.2	69.8	70.2
≥ 1600	40.2	53.7	56.2	61.7	64.3	64.5	67.2	67.9	68.6	69.8	69.8	70.7	71.2	71.8	72.4	72.8
≥ 1400	40.2	53.9	56.3	62.4	65.2	65.7	68.5	69.5	70.4	71.8	71.8	72.6	73.5	74.0	74.7	75.0
≥ 1200	40.4	54.2	56.7	63.6	66.7	67.4	70.7	72.4	73.3	75.2	75.7	76.6	77.3	78.5	79.2	79.5
≥ 1000	40.4	54.4	56.9	63.8	67.1	67.8	71.2	73.0	74.2	76.1	76.6	77.5	78.7	79.4	80.1	80.4
≥ 900	40.4	54.4	56.9	63.8	67.1	67.8	71.4	74.0	75.7	78.5	79.2	80.1	81.3	82.0	82.7	83.0
≥ 800	40.4	54.4	56.9	63.8	67.1	67.8	71.4	74.0	75.7	78.5	79.2	80.1	81.3	82.0	82.7	83.0
≥ 700	40.4	54.4	56.9	63.8	67.1	67.8	71.4	74.0	75.7	78.5	79.2	80.1	81.3	82.0	82.7	83.0
≥ 600	40.4	54.4	56.9	63.8	67.1	67.8	71.4	74.0	75.7	78.5	79.2	80.1	81.3	82.0	82.7	83.0
≥ 500	40.4	54.4	56.9	63.8	67.1	67.8	71.4	74.0	75.7	78.5	79.2	80.1	81.3	82.0	82.7	83.0
≥ 400	40.4	54.4	56.9	63.8	67.1	67.8	71.4	74.0	75.7	78.5	79.2	80.1	81.3	82.0	82.7	83.0
≥ 300	40.4	54.4	56.9	63.8	67.1	67.8	71.4	74.0	75.7	78.5	79.2	80.1	81.3	82.0	82.7	83.0
≥ 200	40.4	54.4	56.9	63.8	67.1	67.8	71.4	74.0	75.7	78.5	79.2	80.1	81.3	82.0	82.7	83.0
≥ 100	40.4	54.4	56.9	63.8	67.1	67.8	71.4	74.0	75.7	78.5	79.2	80.1	81.3	82.0	82.7	83.0
≥ 50	40.4	54.4	56.9	63.8	67.1	67.8	71.4	74.0	75.7	78.5	79.2	80.1	81.3	82.0	82.7	83.0
≥ 0	40.4	54.4	56.9	63.8	67.1	67.8	71.4	74.0	75.7	78.5	79.2	80.1	81.3	82.0	82.7	83.0

TOTAL NUMBER OF OBSERVATIONS 577

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 5710
STATION

COL A J 80 BAKER AAF DL
STATION NAME

73-78,60-82
YEARS

FEB
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

0900-1100
HOURS

CEILING FEET	VISIBILITY: STATUTE MILES															
	≥10	≥8	≥6	≥4	≥3	≥2	≥2	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1
NO CEILING	22.6	30.7	31.1	33.7	34.0	34.4	34.7	35.2	35.2	35.6	35.6	35.6	35.6	35.6	35.6	35.6
≥20000	24.5	33.9	34.2	36.8	37.2	37.5	37.8	38.4	38.4	38.9	38.9	39.1	39.1	39.1	39.1	39.1
≥18000	24.8	34.2	34.5	37.2	37.7	38.0	38.4	38.9	38.9	39.4	39.4	39.6	39.6	39.6	39.6	39.6
≥16000	24.8	34.5	34.9	37.5	38.0	38.4	38.7	39.2	39.2	39.8	39.8	39.9	39.9	40.1	40.1	40.1
≥14000	25.0	34.7	35.1	37.7	38.2	38.5	38.9	39.4	39.4	39.9	39.9	40.1	40.1	40.3	40.3	40.3
≥12000	25.2	34.9	35.2	37.8	38.4	38.7	39.1	39.6	39.6	40.1	40.1	40.3	40.3	40.5	40.5	40.5
≥10000	26.0	35.9	36.3	38.9	39.4	39.6	40.1	40.6	40.6	41.1	41.1	41.3	41.3	41.5	41.5	41.5
≥9000	26.4	36.8	37.2	39.8	40.3	40.6	41.0	41.5	41.5	42.0	42.0	42.2	42.2	42.4	42.4	42.4
≥8000	29.7	40.8	41.1	43.8	44.3	44.6	45.0	45.5	45.5	46.0	46.0	46.2	46.2	46.4	46.4	46.4
≥7000	30.6	42.5	42.9	45.5	46.0	46.3	46.7	47.2	47.2	47.7	47.7	48.0	48.0	48.2	48.2	48.2
≥6000	30.6	43.1	43.4	46.0	47.0	47.4	47.7	48.3	48.3	48.8	48.8	49.0	49.0	49.1	49.1	49.1
≥5000	31.1	43.9	44.3	46.9	47.9	48.3	48.6	49.1	49.1	49.6	49.6	50.0	50.0	50.2	50.2	50.2
≥4500	32.1	45.5	45.8	48.4	49.5	49.8	50.2	50.7	50.7	51.4	51.4	51.6	51.6	51.7	51.7	51.7
≥4000	33.5	47.4	47.7	50.3	51.4	51.7	52.1	52.6	52.6	53.3	53.3	53.5	53.5	53.6	53.6	53.6
≥3500	37.3	52.3	52.6	55.6	56.6	56.9	57.3	57.8	57.8	58.5	58.5	58.7	58.7	58.9	58.9	58.9
≥3000	39.4	54.7	55.2	59.4	60.4	60.8	61.3	61.8	62.0	62.6	62.6	63.0	63.0	63.2	63.2	63.2
≥2500	40.5	57.1	57.6	61.8	63.0	63.4	63.9	64.6	64.9	66.1	66.1	66.3	66.3	66.5	66.5	66.5
≥2000	42.7	60.2	61.1	66.8	68.6	69.1	69.6	70.7	71.2	72.4	72.4	72.6	72.6	72.9	72.9	72.9
≥1800	43.2	60.8	61.6	67.4	69.1	69.8	70.3	71.4	71.9	73.1	73.1	73.3	73.3	73.4	73.4	73.4
≥1500	43.6	61.3	62.2	67.9	70.0	70.7	71.4	73.1	73.6	75.5	75.5	75.9	75.9	76.2	76.2	76.2
≥1200	43.6	61.3	62.3	68.4	71.7	71.5	72.4	75.0	75.9	78.0	78.0	78.5	78.5	79.2	79.2	79.2
≥1000	43.6	61.3	62.3	69.6	72.7	74.0	75.5	78.8	79.9	82.6	83.3	84.0	84.0	84.7	84.9	85.1
≥900	43.6	61.3	62.3	69.8	73.3	74.5	76.2	79.7	80.7	83.9	84.5	85.2	85.2	85.9	86.1	86.3
≥800	43.6	61.3	62.3	69.8	73.6	74.8	76.7	80.2	81.6	84.9	85.6	86.3	86.3	87.0	87.2	87.3
≥700	43.6	61.3	62.3	69.8	73.6	75.0	77.1	80.6	81.9	86.5	87.2	87.8	87.8	88.7	89.2	89.4
≥600	43.8	61.5	62.5	70.3	74.1	75.5	78.1	81.9	83.3	88.2	89.2	90.1	90.1	91.1	91.7	91.8
≥500	43.8	61.5	62.5	70.3	74.3	75.7	78.6	83.0	84.4	90.5	91.7	92.5	92.5	93.8	94.4	94.6
≥400	43.8	61.5	62.5	70.3	74.3	75.7	78.6	83.2	84.7	90.8	92.0	92.9	92.9	94.3	95.0	95.5
≥300	43.8	61.5	62.5	70.3	74.3	75.7	78.6	83.2	84.7	91.7	93.2	94.3	94.3	95.7	96.7	97.7
≥200	43.8	61.5	62.5	70.3	74.3	75.7	78.6	83.2	84.7	91.7	93.4	94.6	94.6	96.0	97.2	98.8
≥100	43.8	61.5	62.5	70.3	74.3	75.7	78.6	83.2	84.7	91.7	93.4	94.6	94.6	96.0	97.2	98.8
≥50	43.8	61.5	62.5	70.3	74.3	75.7	78.6	83.2	84.7	91.7	93.6	94.8	94.8	96.2	97.4	99.0

TOTAL NUMBER OF OBSERVATIONS 576

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 4710
STATION

COL A J BO BAKER AAF DL
STATION NAME

73-79,80-82
YEAR

FEET
MOON

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1200-1400
TIME

CEILING FEET	VISIBILITY STATUTE MILES															
	≥10	≥8	≥6	≥4	≥3	≥2	≥2	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1
NO CEILING	20.1	30.9	32.6	34.3	35.6	36.0	36.9	37.5	37.5	37.7	37.7	37.7	37.7	37.7	37.7	37.7
≥20000	23.3	35.8	37.7	39.8	41.1	41.7	42.6	43.2	43.2	43.9	43.9	44.1	44.1	44.1	44.1	44.1
≥18000	23.3	36.0	37.9	40.0	41.5	42.2	43.4	43.9	43.9	44.7	44.7	44.9	44.9	44.9	44.9	44.9
≥16000	23.7	36.2	38.1	40.2	41.7	42.4	43.6	44.1	44.1	44.9	44.9	45.1	45.1	45.1	45.1	45.1
≥14000	23.9	36.6	38.4	40.5	42.0	42.8	43.9	44.5	44.5	45.3	45.3	45.5	45.5	45.5	45.5	45.5
≥12000	25.7	37.7	39.6	41.7	43.2	43.9	45.1	45.6	45.6	46.4	46.4	46.6	46.6	46.6	46.6	46.6
≥10000	26.3	39.4	41.3	43.6	45.1	45.6	47.0	47.5	47.5	48.3	48.3	48.5	48.5	48.5	48.5	48.5
≥9000	26.7	40.3	42.2	44.7	46.2	47.0	48.1	48.7	48.7	49.4	49.4	49.6	49.6	49.6	49.6	49.6
≥8000	29.2	44.3	46.2	48.7	50.2	50.9	52.1	52.7	52.7	53.4	53.4	53.6	53.6	53.6	53.6	53.6
≥7000	30.1	45.8	47.7	50.4	51.9	52.7	53.8	54.4	54.4	55.1	55.1	55.3	55.3	55.3	55.3	55.3
≥6000	30.3	46.4	48.3	50.9	52.5	53.2	54.4	54.9	54.9	55.7	55.7	55.9	55.9	55.9	55.9	55.9
≥5000	30.5	47.0	48.9	51.5	53.0	53.6	54.9	55.5	55.5	56.3	56.3	56.4	56.4	56.4	56.4	56.4
≥4500	31.1	47.5	49.4	52.1	53.6	54.4	55.5	56.3	56.3	57.0	57.0	57.2	57.2	57.2	57.2	57.2
≥4000	31.7	48.7	50.6	53.4	54.9	55.7	56.8	57.6	57.6	58.3	58.3	58.5	58.5	58.5	58.5	58.5
≥3500	35.1	52.3	54.2	57.2	58.7	59.5	60.6	61.4	61.4	62.1	62.1	62.3	62.3	62.3	62.3	62.3
≥3000	36.9	54.9	57.1	61.0	62.5	63.3	64.4	65.2	65.2	66.1	66.3	66.5	66.5	66.5	66.5	66.5
≥2500	39.0	58.9	61.1	65.0	66.5	67.2	68.6	69.3	69.3	70.3	70.5	70.6	70.6	70.6	70.6	70.6
≥2000	40.3	62.7	65.2	71.6	73.9	75.0	76.3	77.3	77.3	78.4	79.0	79.2	79.4	79.4	79.4	79.4
≥1800	40.5	62.9	65.3	72.0	74.2	75.4	76.7	77.7	77.7	78.8	79.4	79.5	79.7	79.7	79.7	79.7
≥1600	40.9	63.8	66.3	73.7	76.3	77.8	79.5	80.7	80.7	81.8	82.4	82.6	83.0	83.0	83.0	83.0
≥1400	40.7	63.8	66.3	74.4	79.6	80.3	82.2	83.9	84.7	86.4	87.1	87.5	87.9	87.9	87.9	87.9
≥1200	41.1	64.6	67.7	76.3	81.6	83.5	85.6	87.9	89.2	91.9	92.8	93.2	93.6	93.6	93.6	93.6
≥1000	41.1	64.6	67.7	76.3	81.6	83.5	85.6	87.9	89.2	92.0	93.2	93.9	94.3	94.3	94.3	94.3
≥900	41.3	64.8	67.2	76.5	81.8	83.7	85.8	88.3	89.8	92.6	93.8	94.5	94.9	94.9	94.9	94.9
≥800	41.3	64.8	67.2	76.5	81.8	83.7	85.8	88.6	90.2	93.0	94.1	94.9	95.3	95.3	95.3	95.3
≥700	41.3	65.0	67.4	77.3	82.8	84.7	86.9	89.4	91.1	94.3	95.5	96.2	96.6	96.6	96.6	96.6
≥600	41.3	65.0	67.4	77.3	82.8	84.7	86.9	89.4	91.1	94.9	96.6	97.3	97.7	97.7	97.7	97.7
≥500	41.3	65.0	67.4	77.3	82.8	84.7	86.9	89.4	91.5	95.5	97.2	97.9	98.3	98.9	98.9	98.9
≥400	41.3	65.0	67.4	77.3	82.8	84.7	86.9	89.4	91.5	96.0	97.9	98.9	99.2	99.8	99.8	99.8
≥300	41.3	65.0	67.4	77.3	82.8	84.7	86.9	89.4	91.5	96.0	97.9	98.9	99.2	100.0	100.0	100.0
≥200	41.3	65.0	67.4	77.3	82.8	84.7	86.9	89.4	91.5	96.0	97.9	98.9	99.2	100.0	100.0	100.0
≥100	41.3	65.0	67.4	77.3	82.8	84.7	86.9	89.4	91.5	96.0	97.9	98.9	99.2	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 528

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 5710 CCL A J LO BAKER AAF DL

73-78, BD-62

FEET

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1960-1970

CEILING FEET	VISIBILITY, STATUTE MILES															
	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2.5	≥ 2	≥ 1.5	≥ 1	≥ .75	≥ .5	≥ .25	≥ .1	≥ .05	≥ .01	≥ .00
NO FIRMING	23.1	34.9	35.1	36.1	37.3	37.6	38.1	38.1	38.6	38.8	38.8	33.8	34.9	38.9	34.9	38.8
≥ 20000	28.7	42.8	43.7	44.0	45.2	45.5	45.9	46.2	46.7	47.4	47.4	47.4	47.4	47.4	47.4	47.4
≥ 18000	28.7	43.2	43.5	44.5	45.7	45.9	46.4	46.7	47.2	47.9	47.9	47.9	47.9	47.9	47.9	47.9
≥ 16000	28.7	43.2	43.5	44.5	45.7	45.9	46.4	46.7	47.2	47.9	47.9	47.9	47.9	47.9	47.9	47.9
≥ 14000	29.7	43.5	43.7	44.7	45.9	46.2	46.7	46.9	47.4	48.2	48.2	48.2	48.2	48.2	48.2	48.2
≥ 12000	29.9	44.1	44.2	45.2	46.4	46.7	47.2	47.4	47.9	48.6	48.6	48.6	48.6	48.6	48.6	48.6
≥ 10000	31.2	47.9	48.2	49.1	50.4	50.6	51.1	51.4	51.8	52.6	52.6	52.6	52.6	52.6	52.6	52.6
≥ 9000	31.2	48.2	48.4	50.1	51.4	51.6	52.1	52.3	52.8	53.6	53.6	53.6	53.6	53.6	53.6	53.6
≥ 8000	32.4	50.7	50.4	52.1	53.3	53.6	54.1	54.3	54.8	55.5	55.5	55.5	55.5	55.5	55.5	55.5
≥ 7000	33.4	51.6	51.9	53.6	55.3	56.3	56.8	57.0	57.5	58.2	58.2	58.2	58.2	58.2	58.2	58.2
≥ 6000	33.4	51.6	51.9	53.6	55.3	56.3	56.8	57.0	57.5	58.2	58.2	58.2	58.2	58.2	58.2	58.2
≥ 5000	33.4	51.6	52.1	53.8	55.5	56.5	57.0	57.2	57.7	58.5	58.5	58.5	58.5	58.5	58.5	58.5
≥ 4500	33.7	52.1	52.3	54.1	55.3	56.6	57.2	57.5	58.0	58.7	58.7	58.7	58.7	58.7	58.7	58.7
≥ 4000	34.2	52.8	53.1	54.8	56.5	57.5	58.0	58.2	58.7	59.5	59.5	59.5	59.5	59.5	59.5	59.5
≥ 3500	36.1	55.5	56.0	58.5	60.4	61.4	61.9	62.2	62.7	63.4	63.4	63.4	63.4	63.4	63.4	63.4
≥ 3000	36.4	56.3	56.9	59.5	61.4	62.9	63.9	64.1	64.6	65.4	65.4	65.4	65.4	65.4	65.4	65.4
≥ 2500	37.6	59.2	59.7	62.7	64.6	66.1	67.1	67.6	68.1	68.8	68.8	68.8	68.8	68.8	68.8	68.8
≥ 2000	38.3	61.2	61.9	67.1	69.0	70.5	72.0	72.5	73.0	74.0	74.0	74.0	74.0	74.0	74.0	74.0
≥ 1800	38.6	61.7	62.4	68.1	70.0	71.7	73.2	73.7	74.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2
≥ 1600	38.6	62.9	63.5	71.3	74.0	76.4	77.9	78.4	79.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1
≥ 1400	39.1	64.1	64.9	73.7	76.4	79.1	80.6	81.8	82.6	83.5	83.5	83.5	83.5	83.5	83.5	83.5
≥ 1200	39.3	64.6	65.4	75.2	78.1	81.8	83.5	85.3	86.5	87.7	88.0	88.5	89.4	89.4	89.4	89.4
≥ 1000	39.3	64.6	65.4	75.4	78.4	82.1	84.3	86.5	87.7	89.2	89.4	89.9	91.2	91.2	91.2	91.2
≥ 900	39.3	64.6	65.4	75.4	78.4	82.1	84.3	87.0	88.2	89.7	89.9	90.4	91.6	91.6	91.6	91.6
≥ 800	39.3	64.6	65.4	75.7	78.6	82.3	84.5	87.7	88.9	90.7	90.9	91.4	92.6	93.1	93.4	93.4
≥ 700	39.3	64.6	65.4	75.7	78.6	82.3	85.0	88.9	90.7	93.1	94.1	94.6	95.8	96.6	97.1	97.1
≥ 600	39.3	64.6	65.4	75.7	78.6	82.3	85.0	88.9	90.7	93.4	94.6	95.3	96.6	97.5	98.0	98.0
≥ 500	39.3	64.6	65.4	75.7	78.6	82.3	85.0	88.9	90.7	94.3	95.6	96.8	98.0	99.3	99.8	99.8
≥ 400	39.3	64.6	65.4	75.7	78.6	82.3	85.0	88.9	90.7	94.3	95.6	96.8	98.0	99.5	100.0	100.0
≥ 300	39.3	64.6	65.4	75.7	78.6	82.3	85.0	88.9	90.7	94.3	95.6	96.8	98.0	99.5	100.0	100.0
≥ 200	39.3	64.6	65.4	75.7	78.6	82.3	85.0	88.9	90.7	94.3	95.6	96.8	98.0	99.5	100.0	100.0
≥ 100	39.3	64.6	65.4	75.7	78.6	82.3	85.0	88.9	90.7	94.3	95.6	96.8	98.0	99.5	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 407

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CENTRAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 5710
STATION

COL A J SC BAKER AAF DL
STATION NAME

73-7A, PD-82
PILOT

FEB
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
FROM HOURLY OBSERVATIONS

1952-2-20
DATE

CEILING FEET		VISIBILITY STATISTICS															
		≥10	26	31	34	37	40	43	46	49	52	55	58	61	64	67	≥70
NO. OF OBS.	21000	21.3	35.2	36.3	37.1	39.1	39.6	40.2	40.2	40.2	40.6	40.6	40.6	40.6	40.6	40.6	40.6
1	2000	24.9	40.2	41.4	42.2	44.5	45.3	46.5	46.5	46.5	47.3	47.3	47.3	47.3	47.3	47.3	47.3
2	1800	24.9	40.6	41.8	42.6	44.9	45.7	46.9	46.9	47.3	48.0	48.0	48.0	48.0	48.0	48.0	48.0
3	1600	24.9	40.6	41.8	42.6	44.9	45.7	46.9	46.9	47.3	48.0	48.0	48.0	48.0	48.0	48.0	48.0
4	1400	24.9	40.6	41.8	42.6	44.9	45.7	46.9	46.9	47.3	48.0	48.0	48.0	48.0	48.0	48.0	48.0
5	1200	24.9	41.7	42.7	43.0	45.3	46.1	47.3	47.3	47.7	48.4	48.4	48.4	48.4	48.4	48.4	48.4
6	1000	25.1	43.0	44.5	45.3	47.7	48.4	49.6	49.6	50.0	50.8	50.8	50.8	50.8	50.8	50.8	50.8
7	800	25.4	43.4	44.9	45.1	47.8	49.6	50.8	50.8	51.2	52.0	52.0	52.0	52.0	52.0	52.0	52.0
8	600	27.0	46.9	48.4	49.6	52.3	53.1	54.3	54.3	54.7	55.5	55.5	55.5	55.5	55.5	55.5	55.5
9	400	27.7	46.4	50.0	51.2	53.9	55.5	56.6	56.6	57.0	57.8	57.8	57.8	57.8	57.8	57.8	57.8
10	200	28.5	49.2	51.8	52.0	54.7	56.3	57.4	57.4	57.8	58.6	58.6	58.6	58.6	58.6	58.6	58.6
11	100	28.5	49.2	51.8	52.0	54.7	56.3	57.4	57.4	57.8	58.6	58.6	58.6	58.6	58.6	58.6	58.6
12	50	28.5	49.2	51.8	52.0	54.7	56.3	57.4	57.4	57.8	58.6	58.6	58.6	58.6	58.6	58.6	58.6
13	25	30.5	51.5	53.1	54.3	57.4	59.0	60.2	60.2	60.5	61.3	61.3	61.3	61.3	61.3	61.3	61.3
14	10	31.5	54.7	56.6	57.8	60.9	62.5	63.7	64.5	64.8	65.6	65.6	65.6	65.6	65.6	65.6	65.6
15	5	32.4	57.0	59.0	60.2	63.3	64.8	66.0	66.8	67.2	68.0	68.0	68.0	68.0	68.0	68.0	68.0
16	2	33.2	59.9	62.1	63.3	66.6	68.4	69.5	70.3	70.7	71.9	71.9	71.9	71.9	71.9	71.9	71.9
17	1	34.1	60.5	62.9	64.5	68.0	69.5	70.7	71.5	71.9	73.0	73.0	73.0	73.0	73.0	73.0	73.0
18	0.5	34.1	61.3	63.7	67.2	70.7	73.0	74.6	75.8	76.2	77.7	77.7	77.7	77.7	77.7	77.7	77.7
19	0.2	34.1	61.3	63.7	67.6	71.1	73.4	75.0	77.0	77.3	78.9	78.9	78.9	78.9	78.9	78.9	78.9
20	0.1	34.1	61.3	63.7	67.6	71.9	74.2	75.8	77.7	78.1	82.0	82.8	82.8	82.8	82.8	82.8	82.8
21	0.05	34.0	61.3	63.7	67.6	71.9	74.2	76.2	78.9	79.3	83.2	84.0	84.0	84.0	84.0	84.0	84.0
22	0.02	34.0	61.3	63.7	67.6	71.9	74.2	76.2	78.9	79.3	83.6	84.4	84.4	84.4	84.4	84.4	84.4
23	0.01	34.1	61.3	63.7	67.6	71.9	74.2	76.2	79.3	79.7	84.8	86.3	86.3	86.7	87.0	87.9	87.9
24	0.005	34.1	61.3	63.7	68.8	73.0	76.2	79.3	82.0	82.5	87.9	89.5	89.5	89.5	89.8	91.0	91.4
25	0.002	34.1	61.3	63.7	68.8	73.0	76.2	79.3	82.6	83.6	89.1	91.0	91.5	92.0	94.9	95.3	95.7
26	0.001	34.0	61.3	63.7	68.8	73.0	76.2	79.3	82.8	83.6	89.1	91.0	91.5	92.0	94.9	95.3	95.7
27	0.0005	34.0	61.3	63.7	68.8	73.0	76.2	79.3	82.8	83.6	89.1	91.0	91.5	92.0	94.9	95.3	95.7
28	0.0002	34.0	61.3	63.7	68.8	73.0	76.2	79.3	82.8	83.6	89.1	91.0	91.5	92.0	94.9	95.3	95.7
29	0.0001	34.0	61.3	63.7	68.8	73.0	76.2	79.3	82.8	83.6	89.1	91.0	91.5	92.0	94.9	95.3	95.7
30	0.00005	34.0	61.3	63.7	68.8	73.0	76.2	79.3	82.8	83.6	89.1	91.0	91.5	92.0	94.9	95.3	95.7

TOTAL NUMBER OF OBSERVATIONS 256

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AND WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1-710

COL A J D BAKER AAF DL

73-78, PC-50

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

ELEVATION FEET	VISIBILITY STATUTE MILES																			
	20	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8
NO CEILING	22.1	31.5	37.3	34.0	34.9	35.3	36.0	36.2	36.3	36.8	36.8	36.9	36.9	37.1	37.1	37.1	37.1	37.1	37.1	37.4
1-20000	25.3	36.0	36.9	38.8	39.8	40.1	41.0	41.3	41.4	42.1	42.1	42.4	42.5	42.7	42.9	43.0	43.2	43.4	43.6	43.7
1-8000	25.4	36.3	37.2	39.0	40.1	40.6	41.5	41.8	41.9	42.7	42.7	42.9	43.0	43.2	43.4	43.5	43.7	43.9	44.1	44.2
1-6000	25.5	36.4	37.3	39.2	40.2	40.7	41.6	41.9	42.1	42.8	42.8	43.0	43.2	43.3	43.5	43.7	43.9	44.1	44.3	44.4
1-4000	25.6	36.6	37.5	39.3	40.4	40.9	41.8	42.1	42.2	43.0	43.0	43.2	43.3	43.5	43.7	43.9	44.1	44.3	44.5	44.6
1-2000	26.7	37.0	37.9	39.8	40.8	41.3	42.2	42.5	42.7	43.4	43.4	43.6	43.8	43.9	44.2	44.4	44.6	44.8	45.0	45.1
1-1000	26.8	38.6	39.5	41.4	42.5	43.0	43.9	44.2	44.4	45.1	45.1	45.3	45.5	45.6	45.9	46.1	46.3	46.5	46.7	46.8
1-500	27.0	39.2	40.1	42.2	43.3	43.6	44.7	45.0	45.2	45.9	45.9	46.2	46.3	46.5	46.7	46.9	47.1	47.3	47.5	47.6
1-250	29.2	42.4	43.4	45.5	46.6	47.1	48.1	48.3	48.5	49.2	49.2	49.4	49.6	49.7	50.0	50.1	50.2	50.3	50.4	50.5
1-100	30.1	44.3	45.0	47.1	48.5	49.2	50.1	50.4	50.6	51.3	51.3	51.6	51.7	51.9	52.1	52.2	52.3	52.4	52.5	52.6
1-50	30.2	44.4	45.4	47.5	48.8	49.6	50.5	50.8	50.9	51.7	51.7	52.0	52.1	52.3	52.5	52.6	52.7	52.8	52.9	53.0
1-25	30.6	45.1	46.3	48.3	49.6	50.3	51.2	51.5	51.7	52.4	52.4	52.7	52.8	53.0	53.2	53.3	53.4	53.5	53.6	53.7
1-10	31.3	45.9	46.9	49.1	50.5	51.2	52.1	52.5	52.6	53.4	53.4	53.7	53.8	54.0	54.2	54.3	54.4	54.5	54.6	54.7
1-5	32.2	47.2	48.2	50.4	51.7	52.5	53.5	53.8	54.0	54.7	54.7	55.0	55.1	55.3	55.5	55.6	55.7	55.8	55.9	56.0
1-2	35.2	50.7	51.6	54.5	55.9	56.6	57.6	57.9	58.1	58.9	58.9	59.1	59.3	59.4	59.6	59.8	59.9	60.0	60.1	60.2
1-1	36.6	53.1	54.4	57.8	59.3	60.2	61.3	61.8	62.0	62.9	63.0	63.2	63.4	63.5	63.7	63.9	64.0	64.1	64.2	64.3
1-0.5	38.0	56.1	57.3	61.0	62.6	63.4	64.6	65.2	65.5	66.5	66.5	66.9	67.0	67.2	67.4	67.5	67.6	67.7	67.8	67.9
1-0.25	39.4	58.8	60.5	65.5	67.6	68.6	70.0	70.7	71.1	72.2	72.4	72.7	73.0	73.1	73.3	73.5	73.6	73.7	73.8	73.9
1-0.1	39.8	59.3	61.0	66.3	68.6	69.6	71.0	71.7	72.1	73.3	73.5	73.8	74.1	74.2	74.4	74.6	74.7	74.8	74.9	75.0
1-0.05	40.2	60.3	62.0	68.2	70.7	72.0	73.7	74.7	75.2	76.6	76.8	77.1	77.6	77.7	77.9	78.1	78.2	78.3	78.4	78.5
1-0.025	40.3	60.5	62.3	69.1	72.1	73.6	75.3	77.0	77.8	79.4	79.7	80.1	80.6	80.8	81.0	81.1	81.2	81.3	81.4	81.5
1-0.01	40.4	60.9	62.7	70.4	74.1	75.9	78.0	80.3	81.3	83.7	84.3	84.9	85.7	85.9	86.1	86.2	86.3	86.4	86.5	86.6
1-0.005	40.4	60.9	62.7	70.5	74.4	76.2	78.5	81.0	82.1	84.6	85.3	86.0	86.8	87.0	87.2	87.3	87.4	87.5	87.6	87.7
1-0.0025	40.5	61.0	62.8	70.6	74.5	76.3	78.7	81.5	82.9	85.8	86.5	87.1	87.9	88.1	88.4	88.5	88.6	88.7	88.8	88.9
1-0.001	40.5	61.0	62.8	70.7	74.7	76.6	79.2	82.2	83.5	87.1	87.9	88.5	89.4	89.9	90.2	90.3	90.4	90.5	90.6	90.7
1-0.0005	40.5	61.0	62.8	71.2	75.3	77.3	80.3	84.1	85.6	90.1	91.5	92.4	93.6	94.2	94.6	94.7	94.8	94.9	95.0	95.1
1-0.00025	40.5	61.0	62.8	71.2	75.4	77.4	80.5	84.3	86.0	90.7	92.1	93.2	94.5	95.4	95.8	95.9	96.0	96.1	96.2	96.3
1-0.0001	40.5	61.0	62.8	71.2	75.4	77.4	80.5	84.6	86.2	91.5	93.3	94.7	96.1	97.3	98.0	98.2	98.3	98.4	98.5	98.6
1-0.00005	40.5	61.0	62.8	71.2	75.4	77.4	80.5	84.6	86.2	91.5	93.6	95.2	96.8	98.2	99.1	99.4	99.5	99.6	99.7	99.8
1-0.000025	40.5	61.0	62.8	71.2	75.4	77.4	80.5	84.6	86.2	91.5	93.6	95.2	96.8	98.4	99.3	99.6	99.7	99.8	99.9	100.0

TOTAL NUMBER OF OBSERVATIONS 2344

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CLIMATOLGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 5710 COL A J 30 BAKER AAF DL

73-78,00-87

MA

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1622-0822

CEILING FEET	VISIBILITY STATUTE MILES															
	≥10	≥8	≥6	≥4	≥3	≥2	≥2	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1
NO CEILING ≥20000	18.9	26.0	29.8	30.7	31.0	31.0	31.3	31.5	31.7	31.7	32.0	32.0	32.3	32.6	32.8	33.4
≥18000	23.9	33.2	34.7	36.2	36.7	36.7	37.0	37.2	37.3	37.3	37.6	37.6	38.0	38.6	38.7	39.4
≥16000	23.6	33.4	34.2	36.4	36.9	36.9	37.2	37.3	37.5	37.5	37.8	37.8	38.1	38.7	38.9	39.5
≥14000	23.6	33.4	34.2	36.4	36.9	36.9	37.5	37.6	37.8	37.8	38.1	38.1	38.4	39.1	39.2	39.8
≥12000	23.6	33.4	34.2	36.4	36.9	36.9	37.5	37.5	37.8	37.8	38.1	38.1	38.4	39.1	39.2	39.8
≥10000	24.1	34.0	34.8	37.0	37.5	37.5	38.1	38.3	38.4	38.4	38.7	38.7	39.1	39.7	39.8	40.5
≥8000	26.1	36.7	37.5	39.7	41.2	40.2	40.8	40.9	41.1	41.1	41.4	41.4	41.7	42.4	42.5	43.1
≥7000	27.1	38.1	38.9	41.1	41.6	41.6	42.2	42.4	42.5	42.5	42.8	42.8	43.1	43.8	43.9	44.6
≥6000	32.3	43.9	44.7	47.1	47.9	47.9	48.5	48.7	48.9	48.8	49.1	49.1	49.4	50.2	50.4	51.0
≥5000	33.4	45.0	45.8	48.2	49.4	49.9	50.6	50.7	50.9	50.9	51.2	51.2	51.5	52.3	52.4	53.1
≥4500	33.5	45.4	46.1	48.5	49.8	50.2	50.9	51.0	51.2	51.2	51.5	51.5	51.8	52.6	52.8	53.4
≥4000	34.8	46.6	47.4	49.8	51.0	51.5	52.1	52.3	52.4	52.4	52.9	52.9	53.1	53.9	54.0	54.6
≥3500	35.0	46.8	47.6	49.9	51.2	51.7	52.3	52.4	52.6	52.6	52.9	52.9	53.2	54.0	54.2	54.8
≥3000	37.1	49.3	50.1	52.6	53.9	54.3	55.0	55.1	55.3	55.3	55.6	55.6	55.9	56.7	56.9	57.5
≥2500	38.4	51.2	52.1	54.6	55.9	56.4	57.2	57.3	57.5	57.5	57.8	57.8	58.1	58.9	59.1	59.7
≥2000	40.5	54.0	54.9	57.5	58.9	59.8	60.4	61.1	61.3	61.3	61.6	61.7	62.0	62.8	63.1	63.8
≥1800	41.9	55.7	56.9	59.5	61.1	62.0	63.0	63.6	63.9	63.9	64.3	64.4	64.7	65.5	65.8	66.5
≥1600	43.1	58.1	59.4	63.0	65.0	66.0	67.6	68.6	69.3	69.6	69.9	70.1	70.6	71.3	71.7	72.3
≥1400	43.6	58.7	60.0	63.8	66.0	66.9	68.7	69.9	70.6	70.9	71.2	71.3	71.8	72.6	72.9	73.5
≥1200	43.8	59.5	60.8	64.0	66.8	69.6	72.3	73.5	74.2	74.8	75.1	75.3	75.7	76.5	76.9	77.5
≥1000	44.3	60.3	61.9	67.1	69.9	71.2	74.2	75.7	76.5	78.3	78.7	78.9	79.4	80.2	80.5	81.1
≥900	44.4	60.8	62.5	68.0	71.2	72.4	75.7	77.5	78.4	81.3	82.0	82.2	82.8	83.6	83.9	84.6
≥800	44.6	60.8	62.5	68.0	71.2	72.4	75.7	77.5	78.4	81.3	82.0	82.2	82.8	83.6	83.9	84.6
≥700	44.7	61.1	62.8	69.4	72.6	73.9	77.6	79.5	80.6	84.1	85.5	85.7	86.3	87.1	87.4	88.1
≥600	44.9	61.3	63.1	70.1	73.4	74.6	78.9	80.9	82.4	86.1	87.7	87.9	88.5	89.4	89.8	90.4
≥500	44.9	61.3	63.1	70.1	73.4	74.6	78.9	81.9	83.6	87.6	89.3	89.4	90.1	91.0	91.3	92.0
≥400	44.9	61.3	63.1	70.2	73.5	75.0	79.2	82.4	84.4	89.9	91.9	92.1	94.0	95.1	95.4	96.1
≥300	44.9	61.3	63.1	70.2	73.5	75.0	79.5	83.1	85.2	90.9	92.9	93.5	95.9	97.0	97.3	98.0
≥200	44.9	61.3	63.1	70.2	73.5	75.0	79.5	83.3	85.4	91.2	93.4	94.0	97.2	98.7	99.1	100.0
≥100	44.9	61.3	63.1	70.2	73.5	75.0	79.5	83.3	85.4	91.2	93.4	94.0	97.2	98.7	99.1	100.0
≥50	44.9	61.3	63.1	70.2	73.5	75.0	79.5	83.3	85.4	91.2	93.4	94.0	97.2	98.7	99.1	100.0

TOTAL NUMBER OF OBSERVATIONS 635

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CLIMATE CLIMATOLOGY BRANCH
USAF ETAC
AF WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 710 COL A J DO BAKER AAF DL

73-75,50-82

WA

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1 03-1100

CEILING FEET	VISIBILITY STATUTE MILES															
	20	26	21	24	23	22	27	2	24	21	24	21	2	23	24	21
1000	20.0	30.9	31.4	33.5	34.3	34.3	35.7	35.1	36.1	35.4	35.4	35.4	35.4	35.4	35.4	35.4
900	26.1	35.2	39.7	41.7	42.5	42.5	43.1	43.3	43.3	43.6	43.6	43.6	43.6	43.6	43.6	43.6
800	26.5	39.0	40.4	42.6	43.6	43.6	44.2	44.4	44.4	44.7	44.7	44.7	44.7	44.7	44.7	44.7
700	26.4	39.0	40.4	42.6	43.6	43.6	44.2	44.4	44.4	44.7	44.7	44.7	44.7	44.7	44.7	44.7
600	26.6	39.3	40.9	42.9	43.6	43.6	44.5	44.7	44.7	45.0	45.0	45.0	45.0	45.0	45.0	45.0
500	26.8	39.3	40.9	43.1	44.0	44.0	44.7	44.6	44.6	45.1	45.1	45.1	45.1	45.1	45.1	45.1
400	27.7	40.9	42.7	44.5	45.5	45.5	46.1	46.2	46.2	46.6	46.6	46.6	46.6	46.6	46.6	46.6
300	29.0	42.5	43.7	46.1	47.0	47.0	47.6	47.8	47.8	48.1	48.1	48.1	48.1	48.1	48.1	48.1
200	32.4	46.6	49.0	50.8	52.2	52.2	53.0	53.1	53.1	53.4	53.4	53.4	53.4	53.4	53.4	53.4
100	33.1	47.6	49.1	52.0	53.9	53.9	54.7	54.9	54.9	55.2	55.2	55.2	55.2	55.2	55.2	55.2
50	33.4	48.5	49.4	52.4	54.4	54.4	55.2	55.3	55.7	55.6	55.6	55.6	55.6	55.6	55.6	55.6
25	33.5	48.6	50.0	53.0	55.0	55.0	55.8	56.0	56.0	56.3	56.3	56.3	56.3	56.3	56.3	56.3
15	33.9	48.9	50.3	53.4	55.5	55.5	56.3	56.4	56.4	56.7	56.7	56.7	56.7	56.7	56.7	56.7
10	36.2	52.2	53.5	56.7	58.9	58.9	59.7	59.9	59.9	60.2	60.2	60.2	60.2	60.2	60.2	60.2
5	37.5	54.1	55.5	58.6	61.0	61.0	61.8	62.4	62.4	62.7	62.7	62.7	62.7	62.7	62.7	62.7
2	40.8	57.8	59.2	62.9	65.2	65.2	66.1	66.8	66.8	67.1	67.1	67.1	67.1	67.1	67.1	67.1
1	42.5	59.9	61.3	64.9	67.4	67.4	68.5	69.1	69.1	69.4	69.4	69.4	69.4	69.4	69.4	69.4
0	44.4	62.4	64.7	68.8	71.3	71.3	72.9	73.7	73.7	74.5	74.5	74.5	74.5	74.5	74.5	74.5
0.5	45.3	63.5	65.8	70.2	72.7	72.7	74.6	75.4	75.4	76.2	76.2	76.2	76.2	76.2	76.2	76.2
0.25	45.5	64.4	66.8	71.9	75.2	75.4	77.6	78.4	78.5	79.6	79.6	79.6	79.6	79.6	79.6	79.6
0.1	45.5	64.7	67.1	72.3	75.5	75.5	78.2	79.3	79.5	81.2	81.7	81.7	81.7	81.7	81.7	81.7
0.05	45.6	65.4	67.9	73.8	77.7	78.1	81.0	82.6	83.5	85.9	86.7	86.8	87.0	87.5	87.5	87.5
0.025	45.8	65.7	68.2	74.5	78.7	79.0	82.8	85.0	86.1	88.9	89.7	89.8	90.0	90.4	90.4	90.4
0.01	45.8	65.7	68.2	74.8	79.3	79.6	83.5	85.7	86.8	89.8	91.1	91.2	91.4	92.7	92.7	92.7
0.005	45.8	65.7	68.3	75.1	79.6	79.9	84.2	86.4	87.6	91.7	92.9	93.1	93.4	94.2	94.2	94.2
0.0025	45.8	65.7	68.3	75.1	79.6	80.3	84.6	86.2	87.7	95.5	97.5	97.5	97.6	98.5	98.5	98.5
0.001	45.8	65.7	68.3	75.1	79.6	80.3	84.6	86.2	87.7	96.6	98.1	98.4	98.7	99.7	99.7	99.7
0.0005	45.8	65.8	68.5	75.2	79.8	80.4	84.8	86.4	87.8	96.7	98.3	98.6	98.9	100.0	100.0	100.0
0.00025	45.8	65.8	68.5	75.2	79.8	80.4	84.8	86.4	87.8	96.7	98.3	98.6	98.9	100.0	100.0	100.0
0.0001	45.8	65.8	68.5	75.2	79.8	80.4	84.8	86.4	87.8	96.7	98.3	98.6	98.9	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 678

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

U.S. AIR FORCE
 CLIMATE BRANCH
 AFETAC
 AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

710 COL A J LO BAKER AAF DL

73-78,80-92

MAC

PERCENTAGE FREQUENCY OF OCCURRENCE
 (FROM HOURLY OBSERVATIONS)

1222-1400

CEILING (FEET)	VISIBILITY (STATUTE MILES)															
	20	26	24	22	20	18	16	14	12	10	8	6	4	2	1/2	0
1000	22.1	31.1	31.4	32.6	34.0	34.5	34.8	34.8	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0
800	28.7	40.5	41.7	42.2	43.8	44.3	44.5	44.6	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
600	29.2	41.0	41.6	42.7	44.3	44.6	45.1	45.1	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3
400	29.4	41.2	41.7	42.9	44.4	44.9	45.3	45.3	45.4	45.4	45.4	45.4	45.4	45.4	45.4	45.4
200	29.9	41.9	42.6	43.8	45.3	45.6	46.1	46.1	46.3	46.3	46.3	46.3	46.3	46.3	46.3	46.3
100	32.3	45.1	45.9	47.1	48.6	49.2	49.5	49.5	49.7	49.7	49.7	49.7	49.7	49.7	49.7	49.7
50	32.9	45.5	46.6	47.8	49.3	49.6	50.2	50.2	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
25	35.3	47.3	50.2	51.7	53.7	54.2	54.6	54.6	54.7	54.7	54.7	54.7	54.9	54.9	54.9	54.9
15	35.8	49.5	50.3	52.0	54.1	54.6	54.9	54.9	55.1	55.1	55.1	55.1	55.2	55.2	55.2	55.2
10	35.6	50.0	50.9	52.5	54.8	55.1	55.4	55.4	55.6	55.6	55.6	55.6	55.7	55.7	55.7	55.7
5	36.1	50.5	51.4	53.2	55.1	55.6	55.9	55.9	56.1	56.1	56.1	56.1	56.3	56.3	56.3	56.3
2	36.1	50.7	51.5	53.2	55.2	55.7	56.1	56.1	56.3	56.3	56.3	56.3	56.4	56.4	56.4	56.4
1	37.7	52.7	53.9	55.7	57.9	58.4	58.8	58.8	59.0	59.0	59.0	59.0	59.1	59.1	59.1	59.1
0	37.7	54.6	55.7	57.9	60.1	60.6	61.0	61.0	61.1	61.3	61.3	61.3	61.5	61.5	61.5	61.5
1000	41.4	59.3	60.5	63.2	65.4	65.9	66.2	66.2	66.4	66.6	66.6	66.6	66.7	66.7	66.7	66.7
800	42.7	61.1	62.7	66.2	68.4	69.3	69.6	69.6	69.8	69.9	69.9	69.9	70.1	70.1	70.1	70.1
600	45.1	64.7	66.4	71.4	74.0	75.0	75.5	75.5	75.7	76.0	76.2	76.2	76.4	76.4	76.4	76.4
400	45.3	66.4	68.9	73.6	76.5	77.5	78.4	78.5	78.7	79.1	79.2	79.4	79.4	79.4	79.4	79.4
200	46.5	67.4	69.7	76.7	79.7	80.7	82.1	82.4	82.6	83.3	83.4	83.6	83.6	83.6	83.6	83.6
100	46.5	67.6	70.3	77.2	80.6	81.6	83.8	84.1	84.3	85.8	86.0	86.1	86.1	86.1	86.1	86.1
50	46.5	67.7	70.5	78.2	82.6	83.6	86.3	87.2	87.7	89.4	89.7	90.0	90.0	90.0	90.0	90.0
25	46.5	68.2	71.1	79.6	84.1	85.3	88.0	89.2	89.4	91.6	91.9	92.2	92.2	92.2	92.2	92.2
15	46.5	68.2	71.1	80.1	84.6	86.0	89.0	90.7	91.2	93.8	94.1	94.4	94.6	95.1	95.1	95.1
10	46.5	68.2	71.1	80.1	84.6	86.0	89.0	91.2	91.7	94.6	94.9	95.3	95.4	95.9	95.9	95.9
5	46.5	68.2	71.1	80.2	85.0	86.3	89.5	92.4	92.9	95.5	96.5	96.8	97.0	97.5	97.5	97.5
2	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	96.8	97.5	97.8	98.0	98.5	98.5	98.5
1	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
0	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
1000	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
800	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
600	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
400	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
200	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
100	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
50	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
25	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
15	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
10	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
5	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
2	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
1	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8
0	46.5	68.4	71.3	80.4	85.3	86.7	89.9	92.9	93.4	97.0	98.0	98.3	99.2	99.8	99.8	99.8

TOTAL NUMBER OF OBSERVATIONS 592

CLIPAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 4710 COL A J ED BAKER AAF DL

73-73,80-82

MA

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1500-1700

CEILING FEET	VISIBILITY - STATUTE MILES															
	30	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12
1000	17.9	29.6	37.7	31.6	33.8	34.1	34.1	34.1	34.1	34.1	34.1	34.1	34.1	34.1	34.1	34.1
900	24.8	41.6	42.3	43.8	46.0	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2
800	25.7	42.7	43.4	44.9	47.1	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3
700	25.7	42.7	43.4	44.9	47.1	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3
600	25.9	42.9	43.6	45.1	47.7	47.6	47.6	47.6	47.6	47.6	47.6	47.6	47.6	47.6	47.6	47.6
500	25.9	43.4	44.7	46.2	48.5	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7
400	26.8	44.7	46.3	47.6	49.8	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0
300	27.2	45.4	46.7	48.2	50.4	50.7	50.7	50.7	50.7	50.7	50.7	50.7	50.7	50.7	50.7	50.7
200	29.2	48.5	50.2	52.7	55.8	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0
100	29.9	49.8	51.5	54.4	57.5	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7
50	29.9	50.0	51.8	54.6	57.7	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0
25	30.1	50.4	52.2	55.1	58.2	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4
15	30.1	50.7	52.4	55.3	58.4	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6
10	31.0	52.9	55.1	58.0	61.1	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
5	31.4	53.5	55.8	58.6	62.2	62.4	62.4	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6
2	36.3	60.0	62.8	65.9	69.5	69.7	69.7	69.9	69.9	69.9	70.1	70.1	70.1	70.1	70.1	70.1
1	37.4	61.5	64.6	68.4	71.9	72.1	72.1	72.3	72.3	72.3	72.6	72.6	72.6	72.6	72.6	72.6
0.5	38.5	64.2	67.9	73.0	77.2	77.9	77.9	78.1	78.1	78.5	78.5	78.5	78.5	78.5	78.5	78.5
0.25	39.2	65.3	69.0	74.6	79.0	79.6	79.9	80.1	80.1	80.8	80.8	80.8	81.0	81.0	81.0	81.0
0.1	40.3	67.9	71.7	78.1	83.2	84.1	84.3	84.5	84.5	85.4	85.6	85.6	85.8	85.8	85.8	85.8
0.05	40.3	68.1	71.9	78.3	83.4	84.7	85.4	85.6	85.6	86.7	86.9	86.9	87.2	87.2	87.2	87.2
0.025	40.3	68.4	72.1	79.2	85.2	86.5	88.1	89.4	89.4	91.6	91.8	91.8	92.0	92.0	92.0	92.0
0.01	40.3	68.4	72.1	79.6	86.7	88.1	89.6	91.2	91.2	93.4	93.6	93.6	93.8	93.8	93.8	93.8
0.005	40.3	68.6	72.3	79.9	86.9	88.3	90.3	92.5	92.7	95.1	95.4	95.6	95.8	95.8	95.8	95.8
0.0025	40.3	68.6	72.3	79.9	86.9	88.3	90.3	92.5	92.7	95.4	95.6	95.8	96.0	96.0	96.0	96.0
0.001	40.3	68.6	72.3	79.9	86.9	88.3	90.3	92.5	92.7	95.4	95.6	95.8	96.0	96.0	96.0	96.0
0.0005	40.3	68.6	72.3	79.9	86.9	88.3	90.3	92.5	92.7	95.4	95.6	95.8	96.0	96.0	96.0	96.0
0.00025	40.3	68.6	72.3	79.9	86.9	88.3	90.3	92.5	92.7	95.4	95.6	95.8	96.0	96.0	96.0	96.0
0.0001	40.3	68.6	72.3	79.9	86.9	88.3	90.3	92.5	92.7	95.4	95.6	95.8	96.0	96.0	96.0	96.0
0.00005	40.3	68.6	72.3	79.9	86.9	88.3	90.3	92.5	92.7	95.4	95.6	95.8	96.0	96.0	96.0	96.0
0.000025	40.3	68.6	72.3	79.9	86.9	88.3	90.3	92.5	92.7	95.4	95.6	95.8	96.0	96.0	96.0	96.0
0.00001	40.3	68.6	72.3	79.9	86.9	88.3	90.3	92.5	92.7	95.4	95.6	95.8	96.0	96.0	96.0	96.0

TOTAL NUMBER OF OBSERVATIONS 452

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

JOINT CLIMATOLOGY BRANCH
WAFETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 0710 COL A J 60 BAKER AAF DL

73-79,80-82

MAC

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

15-2-2828

CEILING FEET	VISIBILITY - STATUTE MILES															
	210	20	25	24	23	22	21	20	19	18	17	16	15	14	13	12
2000	17.3	31.4	32.2	33.9	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0
1800	25.4	42.4	44.5	46.3	47.7	47.7	47.7	47.7	47.7	48.1	48.1	48.1	48.1	48.1	48.1	48.1
1600	25.4	42.8	45.2	47.3	48.8	48.8	48.8	48.8	48.8	49.1	49.1	49.1	49.1	49.1	49.1	49.1
1400	25.4	42.8	45.2	47.3	48.8	48.8	48.8	48.8	48.8	49.1	49.1	49.1	49.1	49.1	49.1	49.1
1200	25.8	42.8	45.2	47.3	48.8	48.8	48.8	48.8	48.8	49.1	49.1	49.1	49.1	49.1	49.1	49.1
1000	26.1	43.1	45.6	47.7	49.1	49.1	49.1	49.1	49.1	49.5	49.5	49.5	49.5	49.5	49.5	49.5
800	27.6	44.9	47.3	49.5	50.9	50.9	50.9	50.9	50.9	51.2	51.2	51.2	51.2	51.2	51.2	51.2
600	27.7	45.2	47.7	50.5	51.9	51.9	51.9	51.9	51.9	52.3	52.3	52.3	52.3	52.3	52.3	52.3
400	31.1	49.1	51.6	54.4	56.2	56.5	56.5	56.5	56.5	56.9	56.9	56.9	56.9	56.9	56.9	56.9
200	33.2	51.9	54.4	58.0	59.7	60.4	60.4	60.4	60.4	60.8	60.8	60.8	60.8	60.8	60.8	60.8
100	33.2	51.9	54.4	58.0	59.7	60.4	60.4	60.4	60.4	60.8	60.8	60.8	60.8	60.8	60.8	60.8
50	33.9	53.1	55.5	59.0	60.8	61.5	61.5	61.5	61.5	61.8	61.8	61.8	61.8	61.8	61.8	61.8
25	33.9	53.0	55.5	59.0	60.8	61.5	61.5	61.5	61.5	61.8	61.8	61.8	61.8	61.8	61.8	61.8
10	35.0	55.5	58.0	61.8	63.6	64.3	64.3	64.3	64.3	64.7	64.7	64.7	64.7	64.7	64.7	64.7
5	37.1	58.0	60.8	64.7	67.1	67.8	67.8	67.8	67.8	68.5	68.5	68.5	68.5	68.5	68.5	68.5
2	38.2	61.5	64.3	68.6	71.0	71.7	71.7	71.7	71.7	72.4	72.4	72.4	72.4	72.4	72.4	72.4
1	38.5	61.8	64.7	68.9	71.7	72.4	72.4	72.4	72.4	73.1	73.1	73.1	73.1	73.1	73.1	73.1
0.5	39.9	64.0	67.1	72.8	76.7	77.4	77.4	77.4	77.4	78.1	78.1	78.1	78.1	78.1	78.1	78.1
0.25	40.3	65.0	68.2	74.2	78.1	78.6	78.6	78.6	78.6	79.5	79.5	79.5	79.5	79.5	79.5	79.5
0.1	40.3	66.8	70.0	77.7	82.3	83.4	83.4	83.4	83.4	84.6	84.6	84.6	84.6	84.6	84.6	84.6
0.05	40.3	66.8	70.0	77.7	82.3	83.7	83.7	83.7	83.7	85.2	85.2	85.2	85.2	85.2	85.2	85.2
0.025	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	86.9	86.9	86.9	86.9	86.9	86.9	86.9
0.01	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	87.6	87.6	87.6	87.6	87.6	87.6	87.6
0.005	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	89.4	89.4	89.4	89.4	89.4	89.4	89.4
0.0025	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	90.1	90.1	90.1	90.1	90.1	90.1	90.1
0.001	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	91.5	91.5	91.5	91.5	91.5	91.5	91.5
0.0005	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	92.9	92.9	92.9	92.9	92.9	92.9	92.9
0.00025	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	94.7	94.7	94.7	94.7	94.7	94.7	94.7
0.0001	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	96.5	96.5	96.5	96.5	96.5	96.5	96.5
0.00005	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2
0.000025	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	97.5	97.5	97.5	97.5	97.5	97.5	97.5
0.00001	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	97.9	97.9	97.9	97.9	97.9	97.9	97.9
0.000005	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	99.3	99.3	99.3	99.3	99.3	99.3	99.3
0.0000025	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.000001	40.3	66.8	70.0	78.4	83.7	85.2	85.2	85.2	85.2	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 293

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AFS WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 0710 COL A J 30 BAKER AAF DL

73-78, PC-62

MAC

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

ALL

CEILING FEET	VISIBILITY STATUTE MILES															
	≥10	≥6	≥5	≥4	≥3	≥2	≥2	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1
NO CEILING	19.3	30.1	30.4	32.3	33.4	33.6	33.9	34.0	34.0	34.1	34.2	34.2	34.3	34.3	34.4	34.5
≥ 20000	25.7	38.6	39.6	41.3	42.5	42.7	43.0	43.1	43.2	43.3	43.3	43.3	43.4	43.6	43.5	43.8
≥ 18000	26.2	39.2	40.2	42.0	43.3	43.4	43.7	43.8	43.9	44.0	44.1	44.1	44.2	44.3	44.3	44.5
≥ 16000	26.2	39.2	40.2	42.0	43.3	43.4	43.7	43.8	43.9	44.0	44.1	44.2	44.2	44.4	44.4	44.6
≥ 14000	26.3	39.3	40.3	42.2	43.4	43.6	44.0	44.0	44.1	44.2	44.3	44.3	44.4	44.5	44.5	44.7
≥ 12000	26.6	39.8	41.0	42.6	44.0	44.2	44.6	44.7	44.7	44.8	44.9	44.9	45.0	45.2	45.2	45.3
≥ 10000	28.2	41.9	43.2	45.0	46.2	46.4	46.8	46.8	46.9	47.0	47.1	47.1	47.2	47.4	47.4	47.6
≥ 9000	29.0	43.0	44.2	46.1	47.3	47.5	47.9	48.0	48.0	48.2	48.2	48.2	48.3	48.5	48.5	48.7
≥ 8000	32.3	47.2	48.5	50.8	52.5	52.7	53.2	53.2	53.3	53.4	53.5	53.5	53.6	53.8	53.9	54.0
≥ 7000	33.2	48.3	49.6	52.2	54.1	54.5	54.9	55.0	55.0	55.2	55.2	55.3	55.3	55.6	55.6	55.8
≥ 6000	33.3	48.6	49.9	52.5	54.5	54.8	55.2	55.3	55.4	55.5	55.6	55.6	55.7	55.9	55.9	56.1
≥ 5000	33.9	49.3	50.7	53.2	55.2	55.6	56.0	56.1	56.2	56.3	56.3	56.4	56.5	56.7	56.7	56.9
≥ 4500	34.0	49.5	50.8	53.5	55.5	55.8	56.2	56.3	56.4	56.5	56.6	56.6	56.7	56.9	57.0	57.1
≥ 4000	35.7	52.1	53.5	56.3	58.3	58.7	59.1	59.2	59.3	59.4	59.5	59.5	59.6	59.8	59.9	60.0
≥ 3500	36.9	53.8	55.3	58.2	60.4	60.8	61.2	61.5	61.5	61.8	61.8	61.9	62.0	62.2	62.3	62.4
≥ 3000	39.8	58.0	59.6	62.8	65.1	65.5	66.1	66.3	66.4	66.7	66.7	66.8	66.9	67.2	67.3	67.4
≥ 2500	41.2	59.7	61.5	64.9	67.3	67.9	68.5	68.8	68.9	69.2	69.2	69.3	69.4	69.7	69.8	69.9
≥ 2000	42.7	62.3	64.7	69.2	72.0	72.7	73.5	74.2	74.3	74.6	74.9	75.0	75.2	75.4	75.5	75.7
≥ 1800	43.4	63.5	65.9	70.6	73.6	74.3	75.4	76.0	76.2	76.8	77.0	77.0	77.2	77.5	77.6	77.7
≥ 1600	43.3	64.8	67.3	73.3	76.8	77.6	79.1	79.9	80.1	81.1	81.2	81.3	81.5	81.8	81.9	82.0
≥ 1400	43.9	65.1	67.7	73.8	77.4	78.5	80.4	81.3	81.6	83.2	83.5	83.6	83.9	84.2	84.2	84.4
≥ 1200	44.1	65.5	68.2	74.8	79.2	80.2	82.8	84.3	84.8	87.3	87.8	88.0	88.2	88.7	88.7	88.9
≥ 1000	44.1	65.7	68.3	75.4	80.0	81.1	83.9	85.7	86.3	89.0	89.6	89.7	90.0	90.4	90.5	90.7
≥ 900	44.1	65.8	69.5	76.0	80.7	81.8	85.0	87.0	87.7	90.7	91.5	91.7	92.0	92.5	92.6	92.7
≥ 800	44.2	65.8	68.6	76.2	81.0	82.1	85.4	87.6	88.4	92.0	92.8	93.0	93.3	93.9	94.0	94.1
≥ 700	44.2	65.8	68.6	76.2	81.0	82.2	85.7	88.4	89.3	93.1	94.1	94.4	94.7	95.3	95.4	95.6
≥ 600	44.2	65.8	68.6	76.3	81.2	82.3	85.9	89.0	90.1	94.7	95.8	96.2	96.8	97.7	97.7	97.9
≥ 500	44.2	65.8	68.6	76.3	81.2	82.3	86.0	89.2	90.3	95.4	96.7	97.1	98.0	98.9	99.1	99.3
≥ 400	44.2	65.9	68.7	76.3	81.2	82.4	86.0	89.3	90.3	95.5	96.8	97.2	98.3	99.5	99.7	99.9
≥ 300	44.2	65.9	68.7	76.3	81.2	82.4	86.0	89.3	90.3	95.5	96.8	97.2	98.3	99.5	99.7	100.0
≥ 200	44.2	65.9	68.7	76.3	81.2	82.4	86.0	89.3	90.3	95.5	96.8	97.2	98.3	99.5	99.7	100.0
≥ 100	44.2	65.9	68.7	76.3	81.2	82.4	86.0	89.3	90.3	95.5	96.8	97.2	98.3	99.5	99.7	100.0
≥ 0	44.2	65.9	68.7	76.3	81.2	82.4	86.0	89.3	90.3	95.5	96.8	97.2	98.3	99.5	99.7	100.0

TOTAL NUMBER OF OBSERVATIONS 2600

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CLIPAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 4710
STATION

COL A J 30 BAKER AAF DL
STATION NAME

73-78,80-82
YEAR

AP
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

600-2600
FOOT

CEILING FEET	VISIBILITY - STATUTE MILES															
	≥10	≥6	≥5	≥4	≥3	≥2.5	≥2	≥1.5	≥1	≥0.75	≥0.5	≥0.25	≥0.15	≥0.1	≥0.05	≥0
NO. CEILING	24.1	35.0	35.6	36.3	37.0	37.1	37.1	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5
≥ 20000	26.4	39.1	39.9	40.8	41.4	41.6	41.6	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9
≥ 18000	26.4	39.1	39.9	40.8	41.4	41.6	41.6	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9
≥ 16000	26.4	39.1	39.9	40.8	41.4	41.6	41.6	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9
≥ 14000	26.4	39.1	39.9	40.8	41.4	41.6	41.6	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9
≥ 12000	26.4	39.1	39.9	40.8	41.4	41.6	41.6	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9
≥ 10000	26.4	39.1	39.9	40.8	41.4	41.6	41.6	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9
≥ 9000	27.9	42.2	43.1	43.9	44.6	44.7	44.7	45.0	45.0	45.2	45.2	45.2	45.2	45.5	45.5	46.2
≥ 8000	28.5	43.7	44.6	45.9	47.2	47.4	47.4	47.7	47.7	48.0	48.0	48.0	48.0	48.3	48.8	49.5
≥ 7000	30.5	46.0	47.2	48.5	49.8	50.0	50.0	50.3	50.3	50.7	50.7	50.7	50.7	51.0	51.5	52.1
≥ 6000	30.7	46.2	47.4	48.7	50.0	50.2	50.2	50.5	50.5	50.8	50.8	50.8	50.8	51.2	51.7	52.3
≥ 5000	32.0	48.3	49.5	51.0	52.3	52.5	52.5	52.8	52.8	53.3	53.3	53.3	53.3	53.6	54.3	55.0
≥ 4500	32.2	48.7	50.0	51.7	53.0	53.1	53.1	53.5	53.5	54.0	54.0	54.0	54.0	54.3	55.0	55.6
≥ 4000	34.3	51.2	52.5	54.1	55.4	55.8	55.8	56.1	56.1	56.8	56.8	56.8	56.8	57.1	57.8	58.4
≥ 3500	35.3	53.0	54.5	56.1	57.4	57.8	57.8	58.1	58.1	58.7	58.7	58.7	58.7	59.1	59.7	60.4
≥ 3000	36.1	54.8	56.3	58.9	60.4	60.9	60.9	61.2	61.2	61.9	61.9	61.9	61.9	62.2	62.9	63.5
≥ 2500	37.5	56.6	58.1	61.9	63.5	64.0	64.0	64.4	64.4	65.2	65.2	65.3	65.3	65.7	66.3	67.0
≥ 2000	38.3	57.6	59.6	64.4	66.5	67.3	68.6	69.5	69.5	70.3	70.3	70.5	70.5	70.8	71.5	72.1
≥ 1800	38.4	57.8	59.7	64.7	66.8	67.7	69.0	69.8	69.8	70.6	70.6	70.8	70.8	71.1	71.8	72.4
≥ 1600	38.4	57.9	60.1	65.5	68.3	69.1	71.3	72.4	72.4	73.6	74.3	74.8	75.1	75.7	76.7	76.4
≥ 1400	38.8	58.4	60.6	67.0	70.0	71.0	73.4	74.9	75.1	76.2	76.9	77.4	77.7	78.4	79.4	79.0
≥ 1200	38.9	58.7	60.9	67.7	70.8	71.9	75.2	77.4	78.4	80.5	81.5	82.2	83.0	83.7	84.6	84.5
≥ 1000	39.3	59.2	61.6	68.3	71.6	72.9	76.4	78.5	79.9	82.5	83.9	84.7	85.6	86.3	87.3	87.1
≥ 900	39.3	59.4	61.7	68.6	71.9	73.3	77.1	79.7	81.2	84.5	86.1	87.0	88.0	89.1	89.3	90.3
≥ 800	39.3	59.4	61.7	68.8	72.1	73.6	78.1	81.0	82.7	86.3	88.8	89.6	90.9	92.6	92.7	93.7
≥ 700	39.3	59.4	61.7	69.1	72.4	73.9	78.4	81.8	84.0	88.1	90.9	91.6	93.6	95.4	95.7	96.7
≥ 600	39.3	59.4	61.7	69.1	72.4	73.9	78.4	81.8	84.0	88.4	91.4	92.2	94.4	96.7	97.0	98.0
≥ 500	39.3	59.4	61.7	69.1	72.4	73.9	78.4	81.8	84.0	89.3	92.2	93.1	95.4	98.0	99.0	100.0
≥ 400	39.3	59.4	61.7	69.1	72.4	73.9	78.4	81.8	84.0	89.3	92.2	93.1	95.4	98.0	99.0	100.0
≥ 300	39.3	59.4	61.7	69.1	72.4	73.9	78.4	81.8	84.0	89.3	92.2	93.1	95.4	98.0	99.0	100.0
≥ 200	39.3	59.4	61.7	69.1	72.4	73.9	78.4	81.8	84.0	89.3	92.2	93.1	95.4	98.0	99.0	100.0
≥ 100	39.3	59.4	61.7	69.1	72.4	73.9	78.4	81.8	84.0	89.3	92.2	93.1	95.4	98.0	99.0	100.0

TOTAL NUMBER OF OBSERVATIONS 606

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 5710 COL A J SO BAKER AAF DL

73-78,80-82

APP

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

5900-1100
HOURS

CEILING FEET	VISIBILITY STATUTE MILES															
	≥10	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12
25000	25.5	35.5	35.8	36.3	36.7	36.7	36.7	36.7	36.7	36.7	36.7	36.7	36.7	36.7	36.7	36.7
20000	26.4	42.0	42.3	42.6	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
18000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
16000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
14000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
12000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
10000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
9000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
8000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
7000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
6000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
5000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
4500	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
4000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
3500	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
3000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
2500	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
2000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
1800	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
1600	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
1400	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
1200	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
1000	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
900	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
800	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
700	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
600	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
500	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
400	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
300	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
200	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
100	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
0	26.7	42.6	43.0	43.4	43.6	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8

TOTAL NUMBER OF OBSERVATIONS 603

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
JAFETAC
AIF WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 9710 COL A J SO BAKER AAF DL

73-78,80-82

APR

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1200-1400

CEILING FEET	VISIBILITY - STATUTE MILES															
	≥10	≥6	≥5	≥4	≥3	≥2	≥2	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1
NO CEILING	20.7	30.0	30.2	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6
≥ 20000	24.1	37.4	37.6	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5
≥ 18000	25.2	40.1	40.6	41.2	41.2	41.2	41.2	41.2	41.2	41.2	41.2	41.2	41.2	41.2	41.2	41.2
≥ 16000	25.2	40.5	40.6	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5
≥ 14000	25.2	40.6	40.8	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7
≥ 12000	25.2	40.6	40.8	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7
≥ 10000	25.9	42.3	42.6	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
≥ 9000	25.9	42.8	43.2	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.1
≥ 8000	29.3	46.9	47.3	48.2	48.2	48.2	48.2	48.2	48.2	48.2	48.2	48.2	48.2	48.2	48.2	48.2
≥ 7000	29.2	47.8	48.2	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1
≥ 6000	30.2	47.8	48.2	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1
≥ 5000	31.1	49.6	50.0	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9
≥ 4500	31.9	50.0	50.4	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3
≥ 4000	32.9	52.7	53.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
≥ 3500	35.1	55.4	55.9	57.4	57.4	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6
≥ 3000	38.9	60.4	61.3	63.7	63.7	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8
≥ 2500	41.0	63.5	64.6	67.1	67.4	67.8	68.0	68.0	68.0	68.2	68.2	68.2	68.2	68.2	68.2	68.2
≥ 2000	43.5	66.9	68.0	71.6	72.8	73.2	73.7	73.7	73.7	74.1	74.1	74.3	74.5	74.5	74.5	74.5
≥ 1800	44.6	69.4	70.7	75.2	77.0	77.3	77.9	78.1	78.1	78.4	78.4	78.6	78.8	78.8	78.8	78.8
≥ 1600	45.9	71.6	73.1	78.4	80.8	81.3	82.2	82.6	82.6	83.3	83.3	83.5	83.6	83.8	83.8	83.8
≥ 1400	45.0	72.3	73.7	80.2	82.6	83.5	85.4	85.8	85.8	86.5	86.9	87.1	87.2	87.4	87.4	87.4
≥ 1200	46.3	73.2	74.6	81.7	84.2	85.3	87.8	88.1	88.5	90.1	90.3	91.0	91.2	91.4	91.5	91.5
≥ 1000	46.9	73.4	74.8	81.8	84.4	85.4	87.9	88.5	88.8	90.5	91.2	91.4	91.5	91.9	92.1	92.1
≥ 900	46.9	73.4	74.8	81.8	84.4	85.4	88.1	88.8	89.2	91.0	91.7	91.9	92.1	92.4	92.5	92.6
≥ 800	46.9	73.4	75.2	82.2	84.9	86.0	89.4	90.6	91.0	94.2	95.0	95.1	95.3	95.7	95.9	95.9
≥ 700	46.9	73.4	75.2	82.4	85.1	86.2	89.6	91.2	91.5	95.1	95.9	96.0	96.4	97.1	97.3	97.3
≥ 600	46.9	73.4	75.2	82.4	85.1	86.2	89.9	91.5	91.9	95.9	96.9	97.1	97.7	98.6	98.7	98.7
≥ 500	46.9	73.4	75.2	82.4	85.1	86.2	89.9	91.9	92.3	96.2	97.3	97.5	98.0	99.6	99.8	99.8
≥ 400	46.9	73.4	75.2	82.4	85.1	86.2	89.9	91.9	92.3	96.2	97.3	97.5	98.0	99.6	99.8	99.8
≥ 300	46.9	73.4	75.2	82.4	85.1	86.2	89.9	91.9	92.3	96.2	97.3	97.5	98.0	99.6	99.8	99.8
≥ 200	46.9	73.4	75.2	82.4	85.1	86.2	89.9	91.9	92.3	96.2	97.3	97.5	98.0	99.6	99.8	99.8
≥ 100	46.9	73.4	75.2	82.4	85.1	86.2	89.9	91.9	92.3	96.2	97.3	97.5	98.0	99.6	99.8	99.8
≥ 0	46.9	73.4	75.2	82.4	85.1	86.2	89.9	91.9	92.3	96.2	97.3	97.5	98.0	99.6	99.8	99.8

TOTAL NUMBER OF OBSERVATIONS 556

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 0710

COL A J BO BAKER AAF DL

73-77,80-82

APT
DOGT

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1522-1700

CEILING FEET	VISIBILITY - STATUTE MILES															
	≥ 10	≥ 5	≥ 3	≥ 2.5	≥ 2	≥ 1.5	≥ 1	≥ .75	≥ .5	≥ .25	≥ .1	≥ .05	≥ .025	≥ .01	≥ .005	≥ .001
NO FLOORING	21.3	32.6	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8
≥ 20000	25.2	39.4	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
≥ 18000	25.2	39.9	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4
≥ 16000	25.2	40.1	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
≥ 14000	25.2	40.1	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
≥ 12000	25.9	40.8	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3
≥ 10000	26.4	42.3	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4
≥ 9000	27.3	43.6	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0
≥ 8000	29.8	48.2	48.6	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
≥ 7000	30.7	49.5	50.2	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5
≥ 6000	30.7	50.3	50.7	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9
≥ 5000	31.2	50.9	51.6	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8
≥ 4500	32.4	52.8	53.4	53.7	53.7	53.7	53.7	53.7	53.7	53.7	53.7	53.7	53.7	53.7	53.7	53.7
≥ 4000	34.2	54.6	55.3	55.5	55.5	55.5	55.5	55.5	55.5	55.5	55.5	55.5	55.5	55.5	55.5	55.5
≥ 3500	36.9	57.8	58.5	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1
≥ 3000	41.3	65.1	66.3	67.9	67.9	68.1	68.1	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3
≥ 2500	43.3	69.5	70.9	73.2	73.2	73.4	73.4	73.9	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1
≥ 2000	44.7	72.2	73.6	77.1	77.5	77.6	78.2	78.9	79.1	79.1	79.1	79.4	79.4	79.4	79.4	79.4
≥ 1800	45.2	73.2	75.3	79.6	80.3	80.5	81.2	81.9	82.1	82.6	82.6	82.8	82.8	82.8	82.8	82.8
≥ 1600	45.2	73.4	75.7	80.3	81.7	82.1	82.8	83.5	83.7	84.6	84.9	85.1	85.1	85.1	85.1	85.1
≥ 1400	46.1	75.2	78.3	83.5	85.6	86.2	86.9	88.1	88.3	89.2	89.4	89.7	89.7	89.7	89.7	89.7
≥ 1200	46.1	75.5	78.2	84.2	86.2	86.9	87.8	89.2	89.4	90.8	91.1	91.3	91.5	91.7	92.0	92.0
≥ 1000	46.1	75.5	78.2	84.4	86.7	87.4	88.3	89.9	90.4	92.4	92.7	92.9	93.1	93.3	93.6	93.6
≥ 900	46.1	75.5	78.2	84.4	86.7	87.6	88.8	90.8	91.3	93.8	94.5	94.7	95.0	95.2	95.4	95.4
≥ 800	46.1	75.5	78.2	84.4	86.9	87.6	89.0	91.1	91.5	94.5	95.4	96.1	96.3	96.6	96.8	96.8
≥ 700	46.1	75.5	78.2	84.4	86.9	87.8	89.4	91.7	92.7	95.9	96.8	97.7	98.9	99.5	100.0	100.0
≥ 600	46.1	75.5	78.2	84.4	86.9	87.8	89.4	91.7	92.7	95.9	96.8	97.7	98.9	99.5	100.0	100.0
≥ 500	46.1	75.5	78.2	84.4	86.9	87.8	89.4	91.7	92.7	95.9	96.8	97.7	98.9	99.5	100.0	100.0
≥ 400	46.1	75.5	78.2	84.4	86.9	87.8	89.4	91.7	92.7	95.9	96.8	97.7	98.9	99.5	100.0	100.0
≥ 300	46.1	75.5	78.2	84.4	86.9	87.8	89.4	91.7	92.7	95.9	96.8	97.7	98.9	99.5	100.0	100.0
≥ 200	46.1	75.5	78.2	84.4	86.9	87.8	89.4	91.7	92.7	95.9	96.8	97.7	98.9	99.5	100.0	100.0
≥ 100	46.1	75.5	78.2	84.4	86.9	87.8	89.4	91.7	92.7	95.9	96.8	97.7	98.9	99.5	100.0	100.0
≥ 50	46.1	75.5	78.2	84.4	86.9	87.8	89.4	91.7	92.7	95.9	96.8	97.7	98.9	99.5	100.0	100.0
≥ 0	46.1	75.5	78.2	84.4	86.9	87.8	89.4	91.7	92.7	95.9	96.8	97.7	98.9	99.5	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 476

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CEILING VERSUS VISIBILITY

AP -

1300-2400

TOTAL NUMBER OF OBSERVATIONS 260

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GENERAL CLIMATOLOGY BRANCH
 USAF ETAC
 AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1-710
 STATION

COL A J DO BAKER AAF DL
 STATION NAME

73-79,80-82
 YEAR

PERCENTAGE FREQUENCY OF OCCURRENCE
 (FROM HOURLY OBSERVATIONS)

1-710
 STATION

ALL
 MONTH

CEILING FEET	VISIBILITY STATUTE MILES															
	210	20	25	24	23	22	21	20	19	18	17	16	15	14	13	12
20000	22.7	33.3	37.7	34.1	34.3	34.3	34.3	34.4	34.4	34.4	34.4	34.4	34.4	34.5	34.5	34.7
18000	26.1	39.9	47.7	40.6	41.0	41.1	41.1	41.2	41.2	41.2	41.2	41.2	41.2	41.3	41.3	41.5
16000	26.5	40.9	41.4	41.9	42.1	42.2	42.2	42.3	42.3	42.3	42.3	42.3	42.3	42.4	42.4	42.6
14000	26.5	41.0	41.4	41.9	42.2	42.2	42.2	42.3	42.3	42.3	42.3	42.3	42.3	42.5	42.5	42.6
12000	26.7	41.1	41.5	42.1	42.3	42.4	42.4	42.5	42.5	42.5	42.5	42.5	42.5	42.6	42.6	42.8
10000	27.3	42.5	43.7	43.5	43.8	43.8	43.8	43.9	43.9	43.9	43.9	43.9	43.9	44.0	44.0	44.2
8000	28.3	44.0	44.5	45.1	45.3	45.3	45.3	45.4	45.4	45.5	45.5	45.5	45.5	45.6	45.6	45.8
6000	30.3	47.2	47.8	48.6	49.0	49.1	49.1	49.2	49.2	49.2	49.2	49.2	49.2	49.4	49.5	49.7
4000	31.4	48.6	49.3	50.1	50.5	50.6	50.6	50.7	50.7	50.8	50.8	50.8	50.8	50.9	51.0	51.2
2000	31.5	48.8	49.5	50.4	50.8	50.9	50.9	51.0	51.0	51.0	51.0	51.0	51.0	51.2	51.3	51.4
1000	32.4	50.3	51.0	51.9	52.3	52.4	52.4	52.5	52.5	52.6	52.6	52.6	52.6	52.7	52.9	53.1
500	32.9	51.0	51.9	52.7	53.1	53.2	53.2	53.3	53.3	53.4	53.4	53.4	53.4	53.6	53.7	53.9
200	34.5	53.2	54.7	55.0	55.4	55.6	55.6	55.7	55.7	55.8	55.8	55.8	55.8	56.0	56.1	56.3
100	36.0	55.3	56.2	57.7	58.1	58.4	58.4	58.5	58.5	58.6	58.6	58.6	58.6	58.8	58.9	59.1
50	38.9	59.5	60.5	62.7	63.3	63.6	63.6	63.7	63.7	63.9	63.9	63.9	63.9	64.0	64.2	64.3
25	40.7	62.5	63.8	66.7	67.4	67.9	67.9	68.1	68.1	68.4	68.4	68.4	68.4	68.5	68.7	68.9
15	42.1	64.6	66.1	70.0	71.3	71.6	72.7	73.1	73.3	73.7	73.7	73.9	74.0	74.2	74.2	74.4
10	42.6	65.6	67.2	72.0	73.5	74.0	75.0	75.4	75.6	76.1	76.1	76.3	76.4	76.6	76.6	76.8
5	43.1	66.7	68.5	74.1	76.2	76.8	78.1	78.7	78.9	79.8	80.0	80.3	80.6	80.8	80.8	80.9
2	43.5	67.5	69.5	76.1	78.6	79.4	81.2	82.0	82.2	83.2	83.6	83.9	84.1	84.3	84.3	84.5
1	43.7	67.8	70.0	77.1	79.7	80.7	83.2	84.3	84.8	86.4	87.0	87.3	87.8	88.0	88.1	88.3
0.5	43.4	67.9	70.1	77.2	79.9	80.9	83.5	84.6	85.2	86.9	87.5	87.9	88.4	88.7	88.8	89.0
0.25	43.8	68.0	70.2	77.7	80.7	81.6	84.5	85.8	86.6	88.7	89.5	89.8	90.4	90.5	90.9	91.1
0.1	43.9	68.1	70.4	78.0	81.0	82.1	85.2	86.9	87.8	90.7	91.7	92.0	92.7	93.3	93.5	93.7
0.05	43.9	68.1	70.4	78.1	81.2	82.4	85.6	87.6	88.5	91.8	93.1	93.6	94.4	95.4	95.6	95.9
0.025	43.9	68.1	70.4	78.2	81.3	82.5	85.9	88.1	89.2	93.0	94.5	95.0	96.3	97.4	97.7	98.0
0.01	43.9	68.1	70.4	78.2	81.4	82.6	86.1	88.4	89.6	93.5	95.1	95.6	96.9	98.3	98.7	99.0
0.005	43.9	68.1	70.4	78.2	81.4	82.6	86.1	88.4	89.6	93.8	95.4	95.9	97.3	98.9	99.5	99.8
0.0025	43.9	68.1	70.4	78.2	81.4	82.6	86.1	88.4	89.6	93.8	95.4	95.9	97.3	98.9	99.7	100.0
0.001	43.9	68.1	70.4	78.2	81.4	82.6	86.1	88.4	89.6	93.8	95.4	95.9	97.3	98.9	99.7	100.0

TOTAL NUMBER OF OBSERVATIONS 2461

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

OFFICIAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1-710
STATION

CAL A JLD PAKER AAF DL
STATION NAME

73-79,80-82
YEAR

MAC
MOON

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1500-2500
TIME

ELEVATION FEET	VISIBILITY - STATUTE MILES																
	20	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11
10000	25.7	33.5	34.1	34.7	35.2	35.2	35.2	35.5	35.5	35.5	35.5	35.5	35.5	35.5	35.5	35.5	35.5
9000	25.1	32.7	33.4	33.1	33.5	33.5	33.5	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6
8000	23.9	39.5	40.0	40.6	41.1	41.1	41.1	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
7000	28.9	39.5	40.0	40.6	41.1	41.1	41.1	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
6000	29.4	40.0	40.5	41.1	41.6	41.6	41.6	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9
5000	29.5	40.3	40.8	41.4	41.9	41.9	41.9	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2
4000	31.4	42.5	43.1	43.6	44.1	44.1	44.1	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4
3000	34.2	45.3	46.3	46.9	47.3	47.3	47.3	47.7	47.7	47.7	47.7	47.7	47.7	47.7	47.7	47.7	47.7
2000	37.5	50.0	50.5	51.3	51.7	51.7	51.9	52.3	52.3	52.3	52.3	52.3	52.3	52.3	52.3	52.3	52.3
1000	40.4	53.8	54.4	55.2	55.6	55.6	55.8	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3
0000	41.4	54.7	55.3	56.1	56.6	56.6	56.7	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2
4500	42.1	56.4	57.5	58.3	58.8	58.8	58.9	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4
4000	43.4	59.5	60.5	61.6	62.0	62.0	62.2	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7
3500	44.1	61.9	63.3	64.1	64.5	64.5	64.7	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2
3000	47.3	65.9	67.2	68.3	68.9	68.9	69.1	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5
2500	49.4	69.5	70.9	72.7	73.4	73.4	73.6	73.8	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4
2000	51.9	72.5	74.5	76.6	78.0	78.3	78.4	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1
1500	52.1	74.8	77.3	79.2	80.6	80.9	81.1	81.5	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0
1000	53.5	76.1	78.4	81.3	82.7	83.0	83.1	83.9	84.1	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5
0500	54.2	77.3	79.7	82.6	84.4	84.7	85.5	86.3	86.4	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9
0000	54.2	78.1	80.5	83.8	85.1	85.4	87.7	88.6	88.9	89.5	89.7	89.7	89.7	89.7	89.7	89.7	89.7
4500	54.2	78.3	80.6	84.1	86.4	86.7	88.3	90.0	90.3	91.4	91.6	91.7	91.9	92.5	92.5	92.5	92.5
4000	54.2	78.4	80.9	84.5	86.9	87.3	88.9	90.9	91.3	92.7	93.0	93.4	93.6	94.2	94.2	94.2	94.2
3500	54.4	79.1	81.4	85.3	87.7	88.1	89.7	92.0	92.3	93.9	94.2	94.7	94.8	95.5	95.5	95.5	95.5
3000	54.4	79.1	81.4	85.6	88.0	88.4	90.2	92.7	93.0	95.0	95.5	95.9	96.1	96.7	96.7	96.7	96.7
2500	54.4	79.1	81.4	85.6	88.0	88.4	90.2	93.0	93.3	95.5	95.9	96.7	97.0	97.7	97.7	97.7	97.7
2000	54.4	79.1	81.4	85.6	88.0	88.4	90.2	93.3	93.4	95.9	96.4	97.2	97.5	98.1	98.1	98.1	98.1
1500	54.4	79.1	81.4	85.6	88.0	88.4	90.2	93.3	93.6	96.4	96.9	97.7	98.0	98.9	98.9	98.9	98.9
1000	54.4	79.1	81.4	85.6	88.0	88.4	90.2	93.3	93.6	96.4	96.9	97.7	98.0	99.1	99.1	99.1	99.1
0500	54.4	79.1	81.4	85.6	88.0	88.4	90.2	93.3	93.6	96.4	96.9	97.7	98.0	99.1	99.1	99.1	99.1
0000	54.4	79.1	81.4	85.6	88.0	88.4	90.2	93.3	93.6	96.4	96.9	97.7	98.0	99.1	99.1	99.1	99.1

TOTAL NUMBER OF OBSERVATIONS 64

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 0710

COL A J 50 RAKE AAF DL

73-7A, 50-62

MAY

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

0500-1100

ELEVATION FEET	VISIBILITY, STATUTE MILES															
	20	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12
20000	28.3	32.5	39.5	36.1	35.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4
18000	30.5	39.8	39.8	40.5	40.9	40.9	40.9	40.9	40.9	40.9	40.9	40.9	40.9	40.9	40.9	40.9
16000	31.9	42.0	42.0	42.7	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
14000	31.4	42.0	42.0	42.7	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
12000	31.4	42.0	42.0	42.7	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
10000	32.1	42.0	42.0	43.4	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9
8000	34.5	45.9	45.9	46.6	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0
6000	35.5	48.3	48.3	48.9	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4
4000	38.8	52.7	52.7	53.4	53.9	53.9	53.9	53.9	53.9	53.9	53.9	53.9	53.9	53.9	53.9	53.9
2000	43.1	57.3	57.3	58.1	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6
0000	43.3	58.7	58.7	58.8	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2
20000	44.2	60.5	60.5	61.3	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7
18000	45.5	62.7	62.7	63.6	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1
16000	47.5	65.9	65.9	66.9	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3
14000	50.2	69.8	69.8	71.2	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9	71.9
12000	52.7	74.5	74.5	76.3	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0
10000	54.7	77.2	77.2	79.7	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6
8000	57.2	80.5	80.5	83.3	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2
6000	57.7	81.7	81.7	84.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8
4000	59.1	84.2	84.2	87.8	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4
2000	59.4	85.2	85.2	89.2	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3
0000	59.4	85.2	85.2	89.6	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3
20000	59.4	85.2	85.2	89.8	92.7	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1
18000	59.4	85.2	85.2	90.0	93.0	93.4	93.4	93.4	93.4	93.4	93.4	93.4	93.4	93.4	93.4	93.4
16000	59.4	85.2	85.2	90.6	94.2	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
14000	59.4	85.6	85.6	90.8	94.2	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
12000	59.4	85.6	85.6	90.8	94.2	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
10000	59.4	85.6	85.6	90.8	94.2	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
8000	59.4	85.6	85.6	90.8	94.2	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
6000	59.4	85.6	85.6	90.8	94.2	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
4000	59.4	85.6	85.6	90.8	94.2	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
2000	59.4	85.6	85.6	90.8	94.2	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
0000	59.4	85.6	85.6	90.8	94.2	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7

TOTAL NUMBER OF OBSERVATIONS 640

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 7710 COL A J ED BAKER AAF DL

73-77, EC-62

467

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

15-2-1700

CEILING (FEET)	VISIBILITY (STATUTE MILES)															
	20	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12
NO CEILING	22.7	29.6	29.6	29.6	29.6	29.6	29.6	29.6	29.6	29.6	29.6	29.6	29.6	29.6	29.6	29.6
1-2000	27.3	36.2	36.2	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4
2-3000	27.8	37.7	37.7	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
3-4000	27.8	37.7	37.7	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
4-5000	27.8	37.7	37.7	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
5-6000	29.1	38.1	38.1	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3
6-7000	29.6	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3
7-8000	31.0	42.5	42.5	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0
8-9000	37.3	49.4	49.4	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1
9-10000	38.1	52.9	52.9	53.3	53.3	53.3	53.3	53.3	53.3	53.3	53.3	53.3	53.3	53.3	53.3	53.3
10-11000	38.3	54.2	54.2	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54.6
11-12000	39.0	56.1	56.1	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5
12-13000	40.7	60.3	60.3	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4
13-14000	43.5	64.0	64.0	64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5
14-15000	46.3	70.7	70.7	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1
15-16000	53.1	78.4	78.4	80.3	80.7	80.7	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9
16-17000	56.3	82.9	83.1	85.7	86.5	86.5	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7
17-18000	58.7	86.3	86.9	89.5	90.6	90.6	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2
18-19000	60.1	87.8	88.7	91.2	92.5	92.7	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6
19-20000	60.2	88.2	89.1	92.1	94.2	94.4	95.3	95.7	95.7	95.7	95.9	95.9	95.9	95.9	95.9	95.9
20-21000	60.4	88.7	89.7	93.8	95.9	96.4	97.2	97.6	97.6	97.9	97.9	97.9	97.9	97.9	97.9	97.9
21-22000	60.4	88.7	89.9	94.4	96.6	97.0	98.1	98.5	98.5	98.7	98.7	98.7	98.7	98.7	98.7	98.7
22-23000	60.4	88.7	89.9	94.6	96.8	97.2	98.5	98.9	98.9	99.1	99.1	99.1	99.1	99.1	99.1	99.1
23-24000	60.4	88.7	89.9	94.6	96.8	97.2	98.7	99.1	99.1	99.4	99.4	99.4	99.4	99.4	99.4	99.4
24-25000	60.4	88.7	89.9	94.6	96.8	97.2	98.7	99.1	99.1	99.6	99.6	99.6	99.6	99.6	99.6	99.6
25-26000	60.4	88.7	89.9	94.6	96.8	97.2	98.7	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0
26-27000	60.4	88.7	89.9	94.6	96.8	97.2	98.7	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0
27-28000	60.4	88.7	89.9	94.6	96.8	97.2	98.7	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0
28-29000	60.4	88.7	89.9	94.6	96.8	97.2	98.7	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0
29-30000	60.4	88.7	89.9	94.6	96.8	97.2	98.7	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 467

CLIMATE CLIMATOLOGY BRANCH
AFETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

STATION COL A JCS BAKER AAF DL

73-77, 81-82

WAV

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1322-1325

CEILING FEET	VISIBILITY STATUTE MILES															
	20	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12
20	22.4	31.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9
26	28.6	41.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
25	30.1	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6
24	30.1	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6
23	30.1	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6	43.6
22	30.1	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4
21	32.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1
20	32.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9
19	40.5	57.5	57.5	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3
18	43.2	61.4	61.4	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2
17	43.6	61.8	61.8	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5
16	45.2	64.1	64.1	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3
15	48.3	65.0	65.0	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1
14	50.6	71.0	71.0	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2
13	53.7	75.7	75.7	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6
12	57.5	81.9	81.9	83.8	83.8	83.8	83.8	83.8	83.8	84.2	84.2	84.2	84.2	84.2	84.2	84.2
11	57.8	86.1	86.1	88.4	88.8	88.8	88.8	88.8	88.8	89.2	89.2	89.2	89.2	89.2	89.2	89.2
10	60.2	86.9	87.6	90.7	92.3	92.3	92.7	92.7	92.7	93.1	93.1	93.1	93.1	93.1	93.1	93.1
9	60.2	86.9	87.6	91.1	92.7	92.7	93.1	93.1	93.1	93.4	93.4	93.4	93.4	93.4	93.4	93.4
8	60.6	88.0	88.9	93.1	95.4	95.4	95.8	95.8	95.8	96.1	96.1	96.1	96.1	96.1	96.1	96.1
7	60.6	88.0	88.9	94.2	96.5	96.5	96.9	96.9	96.9	97.3	97.3	97.3	97.3	97.3	97.3	97.3
6	60.6	88.0	88.9	94.2	96.5	96.5	97.3	97.3	97.3	97.7	97.7	97.7	97.7	97.7	97.7	97.7
5	60.6	88.0	88.9	94.2	96.5	96.5	98.1	98.1	98.1	98.8	98.8	98.8	98.8	98.8	98.8	98.8
4	60.6	88.0	88.9	94.2	96.5	96.5	98.1	98.1	98.1	98.8	98.8	98.8	98.8	98.8	98.8	98.8
3	60.6	88.0	88.9	94.2	96.5	96.5	98.1	98.1	98.1	99.5	99.5	99.5	99.5	99.5	99.5	99.5
2	60.6	88.0	88.9	94.2	96.5	96.5	98.1	98.1	98.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0
1	60.6	88.0	88.9	94.2	96.5	96.5	98.1	98.1	98.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0	60.6	88.0	88.9	94.2	96.5	96.5	98.1	98.1	98.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 200

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AFW WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 710 COL A J BO BAKER AAF DL

73-78, 80-82

MAY

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

ALL

		VISIBILITY - STATUTE MILES															
		2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0
1000	FEET	24.7	22.1	31.2	32.6	33.8	32.8	32.9	32.9	32.9	32.9	32.9	32.9	32.9	32.9	32.9	32.9
900	FEET	27.9	37.6	37.9	38.2	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5
800	FEET	21.9	39.4	39.6	41.0	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3
700	FEET	25.9	39.4	39.6	40.0	40.2	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3
600	FEET	29.0	37.5	39.7	40.1	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4
500	FEET	29.2	40.0	40.1	40.6	40.9	40.9	40.9	40.9	40.9	40.9	40.9	40.9	40.9	40.9	40.9	40.9
400	FEET	31.3	42.5	43.7	43.2	43.4	43.4	43.4	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
300	FEET	32.7	45.1	45.1	45.6	45.8	45.8	45.8	45.9	45.9	45.9	45.9	45.9	45.9	45.9	45.9	45.9
200	FEET	35.7	50.4	50.5	51.2	51.5	51.5	51.5	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6
100	FEET	39.8	54.4	54.6	55.3	55.5	55.5	55.5	55.6	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7
0	FEET	40.2	55.2	55.4	56.1	56.3	56.3	56.4	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5
100	FEET	41.1	57.3	57.6	58.4	58.6	58.6	58.6	58.8	58.8	58.8	58.8	58.8	58.8	58.8	58.8	58.8
200	FEET	42.7	60.2	60.5	61.4	61.6	61.6	61.6	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7
300	FEET	44.3	63.3	63.5	64.5	64.7	64.7	64.8	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9
400	FEET	46.5	67.7	67.9	69.1	69.4	69.4	69.4	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5
500	FEET	48.4	74.7	75.3	77.1	77.6	77.6	77.8	78.0	78.0	78.1	78.1	78.1	78.1	78.1	78.1	78.1
600	FEET	50.4	78.7	79.5	81.8	82.6	82.6	82.8	83.0	83.0	83.1	83.1	83.1	83.1	83.1	83.1	83.1
700	FEET	52.1	81.3	82.5	85.1	86.0	86.1	86.4	86.6	86.6	86.8	86.8	86.8	86.8	86.8	86.8	86.8
800	FEET	53.8	82.5	83.8	86.7	87.7	87.8	88.3	88.5	88.5	88.7	88.7	88.7	88.7	88.7	88.7	88.7
900	FEET	55.4	83.5	85.2	88.8	90.3	90.5	91.2	91.6	91.6	91.9	91.9	91.9	91.9	91.9	91.9	91.9
1000	FEET	56.6	84.4	85.7	89.8	91.7	92.0	93.0	93.5	93.6	93.9	93.9	93.9	93.9	93.9	93.9	93.9
1100	FEET	58.7	84.6	86.1	90.7	92.8	93.1	94.3	95.1	95.2	95.6	95.6	95.7	95.7	95.7	95.7	95.7
1200	FEET	59.7	84.6	86.1	90.9	93.0	93.4	94.8	95.7	95.8	96.2	96.3	96.3	96.4	96.5	96.5	96.5
1300	FEET	59.7	84.6	86.2	91.1	92.2	93.5	95.1	96.2	96.3	96.8	96.8	96.9	97.7	97.1	97.1	97.2
1400	FEET	59.8	84.9	86.5	91.5	93.8	94.2	95.9	97.1	97.2	97.7	97.8	98.0	98.0	98.2	98.2	98.2
1500	FEET	59.8	84.9	86.5	91.6	93.9	94.3	96.1	97.4	97.6	98.3	98.4	98.6	98.6	98.8	98.8	98.8
1600	FEET	59.8	85.0	86.5	91.6	93.9	94.3	96.2	97.7	97.8	98.7	98.9	99.1	99.2	99.2	99.3	99.4
1700	FEET	59.8	85.0	86.5	91.6	93.9	94.3	96.3	97.7	97.9	98.9	99.0	99.2	99.2	99.4	99.5	99.5
1800	FEET	59.8	85.0	86.5	91.6	93.9	94.3	96.3	97.8	97.9	99.0	99.1	99.4	99.5	99.7	99.9	100.0
1900	FEET	59.8	85.0	86.5	91.6	93.9	94.3	96.3	97.8	97.9	99.0	99.1	99.4	99.5	99.7	99.9	100.0
2000	FEET	59.8	85.0	86.5	91.6	93.9	94.3	96.3	97.8	97.9	99.0	99.1	99.4	99.5	99.7	99.9	100.0

TOTAL NUMBER OF OBSERVATIONS 7616

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
AFETAC
AF WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

STATION 710 COL A J L BAKER AAF DL

73-72,60-52

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

422-2222

CEILING FEET	VISIBILITY, STATUTE MILES															
	20	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12
12000	34.1	41.3	41.5	41.9	42.1	42.1	42.1	42.3	42.3	42.3	42.3	42.4	42.6	42.9	42.9	42.9
10000	37.8	46.3	46.4	47.2	47.4	47.4	47.4	47.5	47.5	47.5	47.5	47.7	47.8	48.2	48.2	48.2
8000	38.3	47.4	47.5	48.3	48.5	48.5	48.5	48.6	48.6	48.6	48.6	48.8	49.0	49.3	49.3	49.3
6000	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
4000	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
2000	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
1000	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
500	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
200	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
100	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
50	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
25	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
12	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
6	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
3	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
1	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
0	38.3	47.4	47.5	48.5	48.6	48.6	48.6	48.8	48.8	48.8	48.8	49.0	49.1	49.4	49.4	49.4
12000	42.9	53.7	53.7	55.0	55.2	55.2	55.2	55.5	55.5	55.7	55.7	55.8	56.0	56.5	56.5	56.5
10000	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
8000	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
6000	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
4000	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
2000	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
1000	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
500	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
200	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
100	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
50	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
25	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
12	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
6	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
3	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
1	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
0	45.7	59.0	59.3	61.4	61.7	61.7	61.7	62.0	62.0	62.2	62.2	62.4	62.5	63.2	63.2	63.2
12000	56.3	69.4	69.9	72.7	73.2	73.2	73.2	73.5	73.5	73.7	73.7	73.8	74.0	74.5	74.5	74.5
10000	59.5	74.3	74.9	78.5	78.8	79.1	79.1	79.4	79.4	79.5	79.5	79.7	79.9	80.4	80.4	80.4
8000	61.2	77.5	78.1	81.8	82.8	83.1	83.1	83.4	83.4	83.6	83.6	83.7	83.9	84.4	84.4	84.4
6000	62.8	80.1	80.5	85.5	86.4	86.8	86.9	87.4	87.4	87.6	87.6	87.7	87.9	88.4	88.4	88.4
4000	63.1	80.9	81.3	86.8	87.7	88.0	88.2	88.7	88.7	88.8	88.8	89.0	89.2	89.6	89.6	89.6
2000	64.1	83.1	83.7	90.0	91.9	92.3	92.7	93.1	93.1	93.3	93.3	93.5	93.6	94.1	94.1	94.1
1000	64.4	83.6	84.3	91.4	92.7	93.1	93.5	94.1	94.1	94.3	94.3	94.4	94.6	95.1	95.1	95.1
500	64.6	84.4	85.0	91.5	93.8	94.4	95.4	96.2	96.2	96.3	96.3	96.5	96.7	97.1	97.1	97.1
200	64.6	84.4	85.0	91.5	93.8	94.4	95.4	96.2	96.2	96.3	96.3	96.5	96.7	97.1	97.1	97.1
100	64.6	84.4	85.0	91.5	93.8	94.4	95.4	96.2	96.2	96.3	96.3	96.5	96.7	97.1	97.1	97.1
50	64.6	84.4	85.0	91.5	93.8	94.4	95.4	96.2	96.2	96.3	96.3	96.5	96.7	97.1	97.1	97.1
25	64.6	84.4	85.0	91.5	93.8	94.4	95.4	96.2	96.2	96.3	96.3	96.5	96.7	97.1	97.1	97.1
12	64.6	84.4	85.0	91.5	93.8	94.4	95.4	96.2	96.2	96.3	96.3	96.5	96.7	97.1	97.1	97.1
6	64.6	84.4	85.0	91.5	93.8	94.4	95.4	96.2	96.2	96.3	96.3	96.5	96.7	97.1	97.1	97.1
3	64.6	84.4	85.0	91.5	93.8	94.4	95.4	96.2	96.2	96.3	96.3	96.5	96.7	97.1	97.1	97.1
1	64.6	84.4	85.0	91.5	93.8	94.4	95.4	96.2	96.2	96.3	96.3	96.5	96.7	97.1	97.1	97.1
0	64.6	84.4	85.0	91.5	93.8	94.4	95.4	96.2	96.2	96.3	96.3	96.5	96.7	97.1	97.1	97.1

TOTAL NUMBER OF OBSERVATIONS 627

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AFW LEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 5715 CCL A J 80 BAKER AAF DL

73-79,60-52

JUN

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1950-11-10

CEILING FEET	VISIBILITY, STATUTE MILES															
	210	20	25	24	23	22	21	20	19	18	17	16	15	14	13	12
21000	33.7	45.2	45.7	45.7	45.7	45.7	45.7	45.7	45.7	45.7	45.7	45.7	45.7	45.7	45.7	45.7
20000	36.7	49.5	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
18000	37.1	49.8	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
16000	37.0	49.5	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
14000	37.2	50.0	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5
12000	37.2	50.0	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5
10000	38.3	51.5	52.1	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0
9000	38.8	52.5	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1
8000	41.3	55.3	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9
7000	44.7	59.4	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0
6000	44.7	59.4	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0
5000	46.1	61.5	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2
4500	47.4	63.3	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0
4000	51.0	67.6	68.4	68.4	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6
3500	54.3	71.5	72.4	72.4	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5
3000	55.1	77.8	78.6	78.8	79.6	79.6	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8
2500	60.0	81.9	83.1	84.2	85.0	85.5	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7
2000	61.2	83.4	84.5	86.2	87.0	88.3	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5
1800	61.3	83.9	85.0	86.8	87.8	89.0	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1
1600	62.9	87.5	88.7	91.3	92.6	93.8	94.1	94.6	94.6	94.9	94.9	94.9	94.9	94.9	94.9	94.9
1400	62.8	88.0	89.1	91.6	93.6	94.7	95.1	95.7	95.7	96.1	96.1	96.1	96.1	96.1	96.1	96.1
1200	63.2	88.5	89.6	92.4	94.2	95.7	96.7	97.4	97.4	97.7	97.7	97.7	97.7	97.7	97.7	97.7
1000	63.2	89.1	90.3	93.3	95.1	96.5	97.7	98.4	98.4	98.8	98.8	98.8	98.8	98.8	98.8	98.8
900	63.2	89.1	90.3	93.3	95.1	96.5	97.9	98.5	98.5	99.0	99.0	99.0	99.0	99.0	99.0	99.0
800	63.2	89.1	90.3	93.3	95.1	96.5	97.9	98.8	98.8	99.3	99.3	99.3	99.3	99.3	99.3	99.3
700	63.2	89.1	90.3	93.3	95.1	96.5	97.9	99.0	99.0	99.5	99.5	99.5	99.5	99.5	99.5	99.5
600	63.2	89.1	90.3	93.3	95.1	96.5	97.9	99.0	99.0	99.7	99.7	99.7	99.7	99.7	99.7	99.7
500	63.2	89.1	90.3	93.3	95.4	96.9	98.2	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0
400	63.2	89.1	90.3	93.3	95.4	96.9	98.2	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0
300	63.2	89.1	90.3	93.3	95.4	96.9	98.2	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0
200	63.2	89.1	90.3	93.3	95.4	96.9	98.2	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0
100	63.2	89.1	90.3	93.3	95.4	96.9	98.2	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 60F

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

STATION 14710 COL A J H BAKER AAF DL STATION NAME

73-79, 80-82 YEAR

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

100-1400

CEILING FEET	VISIBILITY STATUTE MILES															
	≥10	20	25	24	23	22	21	20	19	18	17	16	15	14	13	12
NO REPORT	30.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
≥2000	53.4	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
≥1800	33.9	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3
≥1600	33.9	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3
≥1400	33.9	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3
≥1200	34.3	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0
≥1000	35.1	47.8	47.8	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0
≥800	36.0	49.2	49.2	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4
≥600	40.1	53.6	53.6	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8
≥400	41.5	55.7	55.7	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9
≥200	42.0	56.2	56.2	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4
≥100	43.1	57.8	57.8	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0
≥50	44.6	59.4	59.4	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6
≥25	48.0	64.9	64.9	65.0	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2
≥12	54.5	72.4	72.4	72.6	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8	72.8
≥6	60.3	81.9	81.9	82.6	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1
≥3	61.9	84.9	84.9	86.1	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5
≥1	62.6	85.9	86.3	88.8	90.2	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7
≥0.5	63.4	87.2	87.5	90.2	91.6	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1
≥0.25	64.9	89.1	89.7	93.3	94.9	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4
≥0.1	65.1	89.5	89.8	94.0	96.0	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
≥0.05	65.2	89.8	90.2	94.6	96.7	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5
≥0.025	65.3	90.0	90.3	94.9	97.0	97.9	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
≥0.01	65.2	90.0	90.3	94.9	97.0	97.9	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
≥0.005	65.2	90.0	90.3	94.9	97.0	97.9	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
≥0.0025	65.2	90.0	90.3	94.9	97.0	97.9	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
≥0.001	65.2	90.0	90.3	94.9	97.0	97.9	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
≥0.0005	65.2	90.0	90.3	94.9	97.0	97.9	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
≥0.00025	65.2	90.0	90.3	94.9	97.0	97.9	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
≥0.0001	65.2	90.0	90.3	94.9	97.0	97.9	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
≥0.00005	65.2	90.0	90.3	94.9	97.0	97.9	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
≥0.000025	65.2	90.0	90.3	94.9	97.0	97.9	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
≥0.00001	65.2	90.0	90.3	94.9	97.0	97.9	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1

TOTAL NUMBER OF OBSERVATIONS 569

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CEILING VERSUS VISIBILITY

١٢٦

1500-1700

TOTAL NUMBER OF OBSERVATIONS 437

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AF WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 0710 CCL A J 60 BAKER AAF DL

73-73,P1-62

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1992-12-22

CEILING (FEET)	VISIBILITY STATISTICAL															
	≥10	≥6	≥5	≥4	≥3	≥2.5	≥2	≥1.5	≥1	≥0.75	≥0.5	≥0.25	≥0.15	≥0.1	≥0.05	≥0.01
NO. CEILING	28.7	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6
20000	34.3	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0
18000	34.3	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0
16000	34.3	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0
14000	34.3	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0
12000	34.3	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0
10000	35.7	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3
9000	37.0	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6
8000	40.2	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8
7000	42.6	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4
6000	43.0	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3
5000	43.9	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6
4500	45.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2
4000	43.3	67.0	67.0	67.0	67.0	67.0	67.0	67.0	67.0	67.0	67.0	67.0	67.0	67.0	67.0	67.0
3500	54.3	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5
3000	60.4	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9
2500	61.3	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5
2000	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
1800	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
1600	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
1400	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
1200	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
1000	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
900	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
800	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
700	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
600	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
500	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
400	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
300	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
200	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
100	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
0	62.6	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8

TOTAL NUMBER OF OBSERVATIONS 230

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 710
STATION

COL A J 30 BAKER AAF DL
STATION NAME

73-79,60-82
YEAR

JUN
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

ALL
PERIOD

CEILING FEET	VISIBILITY, STATUTE MILES															
	≥10	≥6	≥5	≥4	≥3	≥2.5	≥2	≥1.5	≥1	≥0.5	≥0.25	≥0.15	≥0.1	≥0.05	≥0.025	≥0.01
≥20000	31.4	41.2	41.4	41.5	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6
≥18000	35.4	46.2	46.4	46.6	46.7	46.7	46.7	46.7	46.7	46.7	46.7	46.7	46.7	46.7	46.7	46.7
≥16000	35.9	46.8	47.0	47.2	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3
≥14000	35.9	46.8	47.0	47.2	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3
≥12000	35.9	46.8	47.0	47.2	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3
≥10000	36.3	47.0	47.2	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
≥8000	36.3	48.4	48.6	48.8	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
≥6000	37.7	49.5	49.7	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1
≥4000	40.9	53.6	53.9	54.2	54.3	54.3	54.3	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4
≥2000	43.2	56.6	56.9	57.2	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3
≥1000	43.5	57.0	57.3	57.8	57.8	57.8	57.8	57.9	57.9	58.0	58.0	58.0	58.0	58.0	58.0	58.0
≥500	44.6	56.8	59.1	59.8	59.9	59.9	59.9	59.9	60.1	60.1	60.1	60.1	60.2	60.2	60.3	60.3
≥250	45.9	60.3	60.7	61.4	61.4	61.4	61.4	61.5	61.7	61.7	61.7	61.7	61.7	61.7	61.9	61.9
≥150	49.9	65.8	66.2	67.0	67.1	67.1	67.1	67.2	67.4	67.4	67.4	67.4	67.5	67.5	67.6	67.6
≥100	54.5	71.2	71.6	72.6	72.8	72.8	72.8	72.8	73.0	73.0	73.0	73.0	73.1	73.1	73.2	73.2
≥75	59.2	79.0	79.5	81.0	81.5	81.7	81.7	81.8	82.0	82.0	82.0	82.0	82.0	82.1	82.2	82.2
≥50	60.9	82.2	82.9	85.2	86.1	86.4	86.4	86.6	86.7	86.8	86.8	86.8	86.8	86.8	87.0	87.0
≥25	62.7	83.8	84.6	88.1	89.2	89.6	89.6	90.0	90.2	90.2	90.2	90.2	90.3	90.3	90.4	90.4
≥15	62.5	84.7	85.6	89.4	90.5	91.1	91.2	91.4	91.6	91.6	91.6	91.6	91.7	91.7	91.8	91.8
≥10	63.4	86.8	87.8	92.3	93.8	94.5	94.7	95.1	95.2	95.3	95.3	95.4	95.4	95.5	95.5	95.5
≥7.5	63.6	87.1	88.1	92.7	94.5	95.2	95.4	95.8	96.0	96.2	96.2	96.2	96.3	96.4	96.4	96.4
≥5	63.7	87.5	88.5	93.4	95.2	96.1	96.6	97.1	97.4	97.5	97.5	97.6	97.6	97.7	97.7	97.7
≥2.5	63.7	87.7	88.7	93.7	95.7	96.6	97.2	97.7	97.9	98.1	98.1	98.2	98.2	98.3	98.3	98.3
≥1.5	63.7	87.7	88.7	93.7	95.7	96.6	97.2	97.9	98.1	98.3	98.3	98.3	98.3	98.4	98.5	98.5
≥1	63.7	87.7	88.7	93.7	95.7	96.6	97.2	98.0	98.3	98.5	98.5	98.5	98.5	98.7	98.7	98.7
≥0.5	63.7	87.7	88.7	93.7	95.7	96.6	97.3	98.3	98.6	98.8	98.8	98.8	98.8	98.9	99.0	99.0
≥0.25	63.7	87.7	88.7	93.7	95.7	96.6	97.6	98.5	99.0	99.5	99.5	99.6	99.6	99.7	99.8	99.8
≥0.15	63.7	87.7	88.7	93.7	95.8	96.8	97.7	98.7	99.2	99.7	99.7	99.8	99.8	99.9	100.0	100.0
≥0.1	63.7	87.7	88.7	93.7	95.8	96.8	97.7	98.7	99.2	99.7	99.7	99.8	99.8	99.9	100.0	100.0
≥0.05	63.7	87.7	88.7	93.7	95.8	96.8	97.7	98.7	99.2	99.7	99.7	99.8	99.8	99.9	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 2471

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 4710
STATION

COL A J BO BAKER AAF DL
STATION NAME

73-78,80-82
YEAR

JUL
DATE

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1600-2000
TIME

CEILING FEET	VISIBILITY - STATUTE MILES															
	≥10	≥6	≥5	≥4	≥3	≥2.5	≥2	≥1.5	≥1	≥0.5	≥0.25	≥0.1	≥0.05	≥0.025	≥0.01	≥0.005
NO. CEILING 2 2000	33.1	36.6	39.1	41.1	43.2	40.2	40.6	40.6	40.7	40.7	40.7	41.1	41.1	41.1	41.1	41.1
2 1800	37.8	43.3	44.3	45.3	45.5	45.5	46.0	46.0	46.1	46.5	46.5	46.8	46.8	46.8	46.8	46.8
2 1600	38.4	44.5	45.0	46.0	46.1	46.1	46.6	46.6	46.8	47.1	47.1	47.5	47.5	47.5	47.5	47.5
2 1400	38.4	44.5	45.0	46.0	46.1	46.1	46.6	46.6	46.8	47.1	47.1	47.5	47.5	47.5	47.5	47.5
2 1200	38.4	44.5	45.0	46.0	46.1	46.1	46.6	46.6	46.8	47.1	47.1	47.5	47.5	47.5	47.5	47.5
2 1000	38.9	45.6	46.1	47.1	47.3	47.3	47.8	47.8	47.9	48.3	48.3	48.6	48.6	48.6	48.6	48.6
2 800	40.7	48.6	49.1	50.1	50.2	50.2	50.7	50.7	50.9	51.2	51.2	51.6	51.6	51.6	51.6	51.6
2 600	45.6	54.7	55.2	56.2	56.3	56.3	56.8	56.8	57.0	57.3	57.3	57.6	57.6	57.6	57.6	57.6
2 400	47.6	57.0	57.5	58.6	58.8	58.8	59.3	59.3	59.4	59.8	59.8	60.1	60.1	60.1	60.1	60.3
2 200	47.7	57.8	58.3	59.4	59.6	59.6	60.1	60.1	60.3	60.6	60.6	60.9	60.9	60.9	60.9	61.1
2 1000	51.1	61.7	62.2	63.9	64.0	64.0	64.5	64.5	64.7	65.0	65.0	65.4	65.4	65.4	65.4	65.6
2 4500	63.2	63.9	64.4	66.0	66.2	66.2	66.7	66.7	66.8	67.7	67.7	67.9	67.9	67.9	67.9	67.9
2 4000	57.3	66.8	69.3	71.4	71.6	71.6	72.4	72.4	72.6	72.9	72.9	73.2	73.2	73.2	73.2	73.4
2 3500	60.3	73.2	73.7	75.9	76.0	76.0	76.8	76.8	77.0	77.3	77.3	77.8	77.8	77.8	77.8	78.0
2 3000	63.4	77.0	77.7	80.0	80.1	80.1	81.0	81.0	81.1	81.4	81.4	81.9	81.9	81.9	81.9	82.1
2 2500	64.4	79.0	80.0	82.6	82.8	82.8	83.6	83.6	83.7	84.1	84.1	84.6	84.6	84.6	84.6	84.7
2 2000	65.9	81.1	82.1	85.1	85.2	85.4	86.2	86.2	86.4	86.9	86.9	87.7	87.7	87.7	87.7	87.8
2 1800	66.7	82.4	83.4	86.5	86.9	87.0	88.2	88.2	88.3	88.8	88.8	89.7	89.7	89.7	89.7	89.6
2 1600	66.8	84.7	85.7	89.5	89.8	90.5	92.0	92.3	92.4	92.9	92.9	93.8	93.8	93.8	93.8	93.9
2 1400	69.0	84.9	85.9	90.6	91.0	91.6	93.1	93.4	93.6	94.1	94.1	94.9	94.9	94.9	94.9	95.1
2 1200	69.1	85.4	86.4	91.5	92.0	92.6	94.4	95.1	95.2	96.4	96.4	97.2	97.2	97.2	97.2	97.4
2 1000	69.1	85.4	86.4	91.5	92.0	92.6	94.4	95.1	95.2	96.4	96.4	97.2	97.2	97.2	97.2	97.4
2 800	69.1	85.4	86.4	91.5	92.0	92.6	94.4	95.2	95.4	97.0	97.0	97.9	97.9	97.9	97.9	98.0
2 600	69.1	85.4	86.4	91.5	92.1	92.9	94.9	95.7	95.9	97.7	97.7	98.5	98.5	98.5	98.5	98.7
2 400	69.1	85.4	86.4	91.5	92.3	93.1	95.2	96.6	97.0	98.9	98.9	99.7	99.7	99.7	99.7	99.8
2 200	69.1	85.4	86.4	91.5	92.3	93.1	95.4	96.7	97.2	99.0	99.0	99.8	99.8	99.8	99.8	99.9
2 1000	69.1	85.4	86.4	91.5	92.3	93.1	95.4	96.7	97.2	99.0	99.0	99.8	99.8	99.8	99.8	99.9
2 400	69.1	85.4	86.4	91.5	92.3	93.1	95.4	96.7	97.2	99.0	99.0	99.8	99.8	99.8	99.8	99.9
2 300	69.1	85.4	86.4	91.5	92.3	93.1	95.4	96.7	97.2	99.0	99.0	99.8	99.8	99.8	99.8	99.9
2 200	69.1	85.4	86.4	91.5	92.3	93.1	95.4	96.7	97.2	99.0	99.0	99.8	99.8	99.8	99.8	99.9
2 100	69.1	85.4	86.4	91.5	92.3	93.1	95.4	96.7	97.2	99.0	99.0	99.8	99.8	99.8	99.8	99.9
2 50	69.1	85.4	86.4	91.5	92.3	93.1	95.4	96.7	97.2	99.0	99.0	99.8	99.8	99.8	99.8	99.9

TOTAL NUMBER OF OBSERVATIONS 620

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AF WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 710 COL A J E BAKER AAF DL

73-7P, PD-62

JUL

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

0000-1100

		VISIBILITY - STATUTE MILES															
		30	28	26	24	22	20	18	16	14	12	10	8	6	4	2	0
1	3000	33.7	44.9	44.9	46.4	46.4	46.4	46.4	46.4	46.4	46.4	46.4	46.4	46.4	46.4	46.4	46.4
2	2500	37.7	45.1	45.1	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6
3	2000	37.9	45.1	45.1	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6
4	1500	36.2	45.9	45.9	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4
5	1000	35.9	47.1	47.1	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6
6	800	41.7	50.9	50.9	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4
7	600	46.7	57.8	57.8	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6
8	400	49.2	61.3	61.3	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1
9	200	49.6	61.8	61.8	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6
10	100	51.4	64.9	64.9	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8
11	50	52.3	65.9	65.9	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8
12	20	54.4	69.6	69.6	72.0	72.0	72.0	72.0	72.0	72.0	72.0	72.0	72.0	72.0	72.0	72.0	72.0
13	10	58.8	75.1	75.1	77.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5
14	5	60.6	79.1	79.1	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5
15	2	63.1	82.8	82.8	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3
16	1	63.9	84.6	84.6	88.8	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0
17	0.5	65.3	86.3	86.3	90.7	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8
18	0.2	65.6	87.5	87.5	92.7	93.0	93.0	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
19	0.1	65.8	88.7	88.7	93.5	94.2	94.2	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5
20	0.05	65.8	88.7	88.7	93.8	94.5	94.5	95.7	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8
21	0.02	65.8	88.7	88.7	94.2	94.8	94.8	96.0	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
22	0.01	65.8	88.7	88.7	94.2	95.0	95.0	96.3	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0
23	0.005	65.8	88.7	88.7	94.2	95.7	95.7	97.0	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
24	0.002	65.8	88.7	88.7	94.2	96.0	96.0	97.5	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
25	0.001	65.8	88.7	88.7	94.2	96.0	96.0	97.5	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
26	0.0005	65.8	88.7	88.7	94.2	96.0	96.0	97.5	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
27	0.0002	65.8	88.7	88.7	94.2	96.0	96.0	97.5	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
28	0.0001	65.8	88.7	88.7	94.2	96.0	96.0	97.5	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
29	0.00005	65.8	88.7	88.7	94.2	96.0	96.0	97.5	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
30	0.00002	65.8	88.7	88.7	94.2	96.0	96.0	97.5	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
31	0.00001	65.8	88.7	88.7	94.2	96.0	96.0	97.5	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2

TOTAL NUMBER OF OBSERVATIONS 509

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
AFETAC
AIR WEATHER SERVICE/AFAC

CEILING VERSUS VISIBILITY

1 710 CPL A J BO BAKER AAF DL

73-79,50-60

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1000-1400

ELEVATION FEET	VISIBILITY - STATUTE MILES															
	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
0-100	31.7	41.7	41.4	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3
101-200	30.1	40.5	47.3	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2
201-300	36.3	46.7	47.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4
301-400	36.3	46.7	47.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4
401-500	36.3	46.7	47.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4
501-600	36.4	47.1	47.3	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7
601-700	37.5	48.5	49.3	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2
701-800	38.6	51.5	52.2	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1
801-900	41.1	55.7	56.4	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3
901-1000	45.5	59.7	61.4	61.4	61.4	61.4	61.4	61.4	61.4	61.4	61.4	61.4	61.4	61.4	61.4	61.4
1001-1100	45.4	59.9	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5
1101-1200	46.1	62.3	63.2	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1	64.1
1201-1300	47.6	63.7	64.7	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6
1301-1400	50.4	67.2	68.1	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4
1401-1500	57.1	75.3	76.7	77.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5
1501-1600	59.1	79.5	80.4	81.7	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9
1601-1700	82.6	82.8	84.2	85.9	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1
1701-1800	84.1	85.7	87.4	89.4	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6
1801-1900	84.5	86.6	88.3	90.7	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8
1901-2000	85.2	87.9	89.9	93.2	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0
2001-2100	85.4	88.5	91.5	94.5	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4
2101-2200	85.4	88.5	91.5	95.4	96.3	96.5	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
2201-2300	85.4	88.5	90.5	95.4	96.3	96.5	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1
2301-2400	85.4	88.5	90.5	95.4	96.7	96.9	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
2401-2500	85.4	88.5	90.5	95.4	96.7	96.9	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
2501-2600	85.4	88.5	90.5	95.4	97.3	97.4	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
2601-2700	85.4	89.0	91.1	96.0	97.4	98.0	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7
2701-2800	85.4	89.0	91.1	96.0	97.4	98.0	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7
2801-2900	85.4	89.0	91.1	96.0	97.4	98.0	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7
2901-3000	85.4	89.0	91.1	96.0	97.4	98.0	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7

TOTAL NUMBER OF OBSERVATIONS 546

OFFICIAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 1710 01L A 3 30 3400 AAF DL
STATION NAME

73-74, 80-82

JUL

PERCENTAGE FREQUENCY OF OCCURRENCE
FROM HOURLY OBSERVATIONS

1900-1999

CEILING FEET	VISIBILITY - STATUTE MILES															
	> 10	20	30	40	50	60	70	80	90	100	120	140	160	180	200	> 200
1000	33.0	41.5	41.5	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1
900	34.6	47.8	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7
800	37.8	48.0	48.7	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
700	38.8	48.0	48.7	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
600	38.8	48.0	48.7	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
500	38.8	48.0	48.7	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
400	38.8	48.0	48.7	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
300	38.8	48.0	48.7	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
200	38.8	48.0	48.7	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
100	38.8	48.0	48.7	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
0	41.0	53.2	53.5	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4
900	46.6	60.9	61.2	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0
800	48.7	64.5	64.7	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9
700	48.7	64.7	65.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1
600	48.7	66.9	67.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4
500	48.7	68.4	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8
400	48.7	73.5	73.9	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2
300	58.5	79.7	80.1	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7
200	58.5	83.2	83.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6
100	62.1	84.6	85.4	88.3	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5
0	63.0	86.9	87.4	91.2	91.4	91.6	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8
900	63.7	88.1	88.9	93.2	93.4	93.6	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8
800	64.3	88.7	89.9	94.9	95.5	95.7	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
700	64.3	88.7	89.9	95.3	96.1	96.3	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
600	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
500	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
400	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
300	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
200	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
100	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
0	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
900	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
800	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
700	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
600	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
500	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
400	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
300	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
200	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
100	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2
0	64.3	88.7	90.1	95.5	96.3	96.5	97.3	97.5	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2

TOTAL NUMBER OF OBSERVATIONS 497

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

LOCAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 717
STATION

COL A J 30 PAKED AAF DL
STATION NAME

73-72,82
DATE

JUL
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1300-2000
TIME

CEILING FEET	VISIBILITY STATUTE MILES															
	≥ 10	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12
NO CEILING	31.7	30.2	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6
12000	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
10000	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
8000	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
6000	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
4000	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
3000	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2000	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
1000	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
800	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
600	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
400	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
300	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
200	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
100	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
80	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
60	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
40	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
30	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
20	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
10	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
8	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
4	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
3	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
1	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6

TOTAL NUMBER OF OBSERVATIONS 254

U.S. AIR FORCE
 CLIMATE CLIMATOLOGY BRANCH
 AFETAC
 AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 710 COL A J D BAKER AAF DL

73-72,90-80

40

PERCENTAGE FREQUENCY OF OCCURRENCE
 FROM HOURLY OBSERVATIONS

1-22-22

CEILING FEET	VISIBILITY STATUTE MILES																			
	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44
1000	24.5	38.1	38.5	38.9	39.8	39.6	40.6	40.9	41.1	41.4	41.5	41.6	41.7	42.8	42.5	42.7				
900	32.3	41.9	42.6	43.6	44.4	44.4	45.2	45.5	45.7	46.7	46.2	46.2	46.2	46.9	47.7	47.9	47.9	47.9	47.9	47.9
800	33.7	42.6	43.2	44.2	45.0	45.0	45.9	46.2	46.4	46.7	46.7	46.9	46.9	47.7	47.9	47.9	47.9	47.9	47.9	47.9
700	33.7	42.6	43.2	44.2	45.0	45.0	45.9	46.2	46.4	46.7	46.7	46.9	46.9	47.7	47.9	47.9	47.9	47.9	47.9	47.9
600	33.1	42.5	43.2	44.2	45.0	45.0	45.9	46.2	46.4	46.7	46.7	46.9	46.9	47.7	47.9	47.9	47.9	47.9	47.9	47.9
500	33.3	42.9	43.6	44.6	45.4	45.4	46.2	46.5	46.7	47.0	47.2	47.2	47.4	48.2	48.2	48.2	48.2	48.2	48.2	48.2
400	33.1	44.7	45.4	46.4	47.2	47.2	48.2	48.3	48.5	48.8	49.0	49.0	49.2	50.0	50.0	50.0	50.0	50.0	50.0	50.0
300	36.5	46.4	47.1	48.3	48.8	48.6	49.7	50.0	50.7	50.5	50.7	50.7	50.9	51.7	51.7	51.7	51.7	51.7	51.7	51.7
200	39.9	50.2	50.3	51.8	52.6	52.6	53.5	53.8	54.1	54.5	54.5	54.6	54.8	55.6	55.6	55.6	55.6	55.6	55.6	55.6
100	42.5	53.3	53.1	54.8	55.6	55.6	56.4	56.6	56.6	56.6	57.4	57.6	57.6	57.6	57.8	58.6	58.6	58.6	58.6	58.6
000	42.5	53.3	53.6	54.8	55.6	55.6	56.4	56.6	56.6	56.6	56.6	57.4	57.6	57.6	57.6	57.8	58.6	58.6	58.6	58.6
000	44.7	55.4	56.3	57.6	58.4	58.4	59.2	59.6	59.7	60.2	60.4	60.4	60.6	61.4	61.4	61.4	61.4	61.4	61.4	61.4
000	46.2	57.1	57.9	59.2	60.1	60.1	60.9	61.2	61.4	61.9	62.1	62.1	62.2	63.0	63.0	63.0	63.0	63.0	63.0	63.0
000	49.8	60.6	61.4	63.0	63.9	63.9	64.7	65.0	65.2	65.7	65.8	65.8	66.7	66.8	66.8	66.8	66.8	66.8	66.8	66.8
000	50.7	62.5	63.4	65.7	66.5	66.5	67.3	67.7	67.8	68.3	68.5	68.5	68.5	68.5	68.5	68.5	68.5	68.5	68.5	68.5
000	53.7	66.3	67.3	71.6	71.5	71.5	72.3	72.8	72.9	73.6	73.8	73.8	73.8	73.9	74.3	74.8	74.8	74.8	74.8	74.8
000	56.4	71.1	71.1	74.8	75.7	75.7	76.6	77.1	77.2	77.9	78.1	78.1	78.1	78.2	79.0	79.0	79.0	79.0	79.0	79.0
000	58.7	72.9	74.6	79.4	80.9	80.9	81.8	82.3	82.5	83.7	83.8	83.8	83.8	84.0	84.8	84.8	84.8	84.8	84.8	84.8
000	59.0	73.4	75.1	80.4	81.8	81.8	82.8	83.3	83.5	84.7	85.0	85.0	85.0	85.1	86.0	86.0	86.0	86.0	86.0	86.0
000	60.1	75.1	76.9	82.5	84.5	84.5	86.5	87.0	87.1	88.3	88.6	88.6	88.6	88.8	89.6	89.6	89.6	89.6	89.6	89.6
000	60.2	75.4	77.7	83.3	85.5	85.5	86.5	87.6	88.1	89.3	89.6	89.6	89.6	89.9	90.1	90.1	90.1	90.1	90.1	90.1
000	60.4	75.6	77.4	83.8	86.0	86.0	86.6	88.4	89.1	89.3	91.1	91.4	91.4	91.4	91.6	92.4	92.4	92.4	92.4	92.4
000	60.4	75.6	77.4	84.7	87.0	87.0	87.6	89.6	90.4	90.6	92.9	93.2	93.4	93.6	94.4	94.4	94.4	94.4	94.4	94.4
000	60.4	75.6	77.6	84.7	87.1	87.1	87.8	90.1	90.9	91.1	93.6	93.9	94.1	94.4	95.4	95.4	95.4	95.4	95.4	95.4
000	60.4	75.6	77.6	84.7	87.3	87.3	88.3	90.6	91.4	91.4	94.2	94.6	94.7	95.0	96.0	96.0	96.0	96.0	96.0	96.0
000	60.4	75.6	77.7	85.3	88.0	88.0	88.9	91.3	92.6	92.7	95.7	96.1	96.2	96.5	97.7	97.7	97.7	97.7	97.7	97.7
000	60.4	75.6	77.7	85.3	88.0	88.0	88.9	91.3	92.9	93.1	96.0	96.4	96.5	96.5	96.9	98.1	98.1	98.1	98.1	98.1
000	60.4	75.6	77.7	85.3	88.0	88.0	88.9	91.3	93.1	93.2	96.2	96.5	96.7	97.7	98.3	99.0	99.0	99.0	99.0	99.0
000	60.4	75.6	77.7	85.3	88.0	88.0	88.9	91.3	93.1	93.2	96.2	96.5	96.7	97.7	98.3	99.0	99.0	99.0	99.0	99.0
000	60.4	75.6	77.7	85.3	88.0	88.0	88.9	91.3	93.1	93.2	96.2	96.5	96.7	97.7	98.3	99.0	99.0	99.0	99.0	99.0
000	60.4	75.6	77.7	85.3	88.0	88.0	88.9	91.3	93.1	93.2	96.2	96.5	96.7	97.7	98.3	99.0	99.0	99.0	99.0	99.0

TOTAL NUMBER OF OBSERVATIONS 606

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GENERAL CLIMATOLOGY BRANCH
AFETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 0710 COL A J BO BAKER AAF DL

73-7P, 60-67

405

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1200-1400

CEILING FEET	VISIBILITY, STATUTE MILES															
	30	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12
NO CEILING	34.1	41.1	41.3	42.4	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6
20000	37.7	45.5	45.7	47.2	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3
18000	35.0	46.3	46.4	47.9	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1
16000	35.1	46.3	46.4	47.9	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1
14000	35.2	46.4	46.6	48.1	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3
12000	35.4	47.0	47.2	48.6	48.8	48.8	48.8	48.8	48.8	48.8	48.8	48.8	48.8	48.8	48.8	48.8
10000	39.1	47.9	48.1	49.5	49.9	49.9	49.9	49.9	49.9	49.9	49.9	49.9	49.9	49.9	49.9	49.9
9000	41.1	50.6	50.8	52.5	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8
8000	45.7	50.1	56.3	58.0	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3
7000	46.8	57.8	58.1	59.6	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0
6000	47.1	58.0	58.1	60.0	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3
5000	48.3	59.6	59.8	61.6	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0
4500	49.0	60.7	60.9	62.7	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3
4000	50.6	62.7	62.1	65.1	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6
3500	55.1	68.2	68.4	70.6	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1
3000	59.6	73.1	73.5	77.0	77.7	77.7	77.7	77.7	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9
2500	64.9	79.5	80.3	84.1	84.8	84.8	84.8	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0
2000	66.0	80.5	81.7	86.5	87.4	87.4	87.4	88.1	88.3	88.5	88.5	88.5	88.5	88.5	88.5	88.5
1800	66.7	81.7	82.1	88.3	89.2	89.2	89.2	89.6	89.9	90.1	90.3	90.3	90.3	90.3	90.3	90.3
1600	67.5	83.4	84.6	91.4	92.7	92.7	93.2	93.6	93.8	94.0	94.0	94.0	94.0	94.0	94.0	94.0
1400	67.5	83.7	85.1	92.3	94.0	94.0	94.5	94.9	95.1	95.2	95.2	95.2	95.2	95.2	95.2	95.2
1200	67.6	84.1	85.4	93.1	94.9	95.2	96.3	97.3	97.4	97.8	97.8	97.8	97.8	97.8	97.8	97.8
1000	67.6	84.1	85.4	93.1	95.2	95.6	96.7	97.6	97.8	98.2	98.2	98.2	98.2	98.2	98.2	98.2
900	67.6	84.1	85.4	93.1	95.2	95.6	96.7	97.6	97.8	98.2	98.2	98.2	98.2	98.2	98.2	98.2
800	67.6	84.1	85.4	93.1	95.2	95.6	96.7	97.6	97.8	98.2	98.2	98.2	98.2	98.2	98.2	98.2
700	67.6	84.1	85.4	93.1	95.2	95.6	96.7	97.6	97.8	98.2	98.2	98.2	98.2	98.2	98.2	98.2
600	67.6	84.1	85.4	93.1	95.2	95.6	96.7	97.6	97.8	98.2	98.2	98.2	98.2	98.2	98.2	98.2
500	67.6	84.1	85.4	93.1	95.2	95.6	96.7	97.6	97.8	98.2	98.2	98.2	98.2	98.2	98.2	98.2
400	67.6	84.1	85.4	93.1	95.2	95.6	96.7	97.6	97.8	98.2	98.2	98.2	98.2	98.2	98.2	98.2
300	67.6	84.1	85.4	93.1	95.2	95.6	96.7	97.6	97.8	98.2	98.2	98.2	98.2	98.2	98.2	98.2
200	67.6	84.1	85.4	93.1	95.2	95.6	96.7	97.6	97.8	98.2	98.2	98.2	98.2	98.2	98.2	98.2
100	67.6	84.1	85.4	93.1	95.2	95.6	96.7	97.6	97.8	98.2	98.2	98.2	98.2	98.2	98.2	98.2
0	67.6	84.1	85.4	93.1	95.2	95.6	96.7	97.6	97.8	98.2	98.2	98.2	98.2	98.2	98.2	98.2

TOTAL NUMBER OF OBSERVATIONS 547

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CLIMATE CLIMATOLOGY BRANCH
 SAFETAC
 AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 710 COL A J ED BAKER AAF DL

73-78,80-82

400

PERCENTAGE FREQUENCY OF OCCURRENCE
 (FROM HOURLY OBSERVATIONS)

1500-1700

CEILING FEET	VISIBILITY - STATUTE MILES															
	20	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12
2000	26.9	35.0	36.7	38.2	39.2	38.2	36.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2
1800	29.9	39.9	40.1	42.0	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2
1600	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
1400	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
1200	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
1000	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
800	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
600	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
400	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
200	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
100	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
50	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
25	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
12	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
6	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
3	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
1	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
0	30.7	40.7	40.9	42.9	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1

TOTAL NUMBER OF OBSERVATIONS 459

GENERAL CLIMATOLOGY BRANCH
AFETAC
AIR WEATHER SERVICE/MAG

CEILING VERSUS VISIBILITY

1-710 COL A J BO BAKER AAF DL

73-72,51-82

80

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1-710-0000

CEILING FEET	VISIBILITY STATISTICAL VALUES															
	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	10.0
2000	27.9	36.1	35.1	37.2	35.1	36.1	36.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1
1800	33.2	42.5	42.6	44.5	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3
1600	33.1	42.9	43.3	45.3	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2
1400	33.1	42.9	43.3	45.3	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2
1200	33.1	42.9	43.3	45.3	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2
1000	34.1	43.3	43.7	45.7	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6
800	34.1	44.5	44.7	47.0	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
600	35.2	45.7	46.2	48.6	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4
400	36.9	50.6	51.0	53.4	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3
200	41.7	53.8	54.3	57.1	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9
100	41.7	53.8	54.3	57.1	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9
50	43.7	55.9	56.3	59.1	59.9	59.9	59.9	59.9	59.9	59.9	59.9	59.9	59.9	59.9	59.9	59.9
25	44.7	57.1	57.5	60.3	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5
10	47.8	60.7	61.1	64.8	66.0	66.0	66.0	66.0	66.0	66.0	66.0	66.0	66.0	66.0	66.0	66.0
5	53.4	66.4	67.2	71.9	72.5	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9
2	61.9	76.5	78.1	82.6	84.2	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6
1	64.7	79.4	81.1	86.2	86.7	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1
0.5	64.4	79.8	81.4	87.0	91.1	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
0.25	64.4	80.8	82.6	87.9	91.9	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3
0.1	65.2	81.4	83.4	89.5	93.5	93.9	93.9	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
0.05	65.2	81.4	83.4	89.9	93.9	94.3	94.3	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
0.025	65.6	82.2	84.2	90.7	94.7	95.1	95.1	97.2	97.2	97.6	97.6	97.6	97.6	97.6	97.6	97.6
0.01	65.6	82.2	84.2	91.5	95.5	96.0	96.0	98.0	98.0	98.8	98.8	98.8	98.8	98.8	98.8	98.8
0.005	65.6	82.2	84.2	91.5	95.5	96.0	96.0	98.0	98.4	99.2	99.2	99.2	99.2	99.2	99.2	99.2
0.0025	65.6	82.2	84.2	91.5	95.5	96.0	96.4	98.8	99.2	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.001	65.6	82.2	84.2	91.5	95.5	96.0	96.4	98.8	99.2	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.0005	65.6	82.2	84.2	91.5	95.5	96.0	96.4	98.8	99.2	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.00025	65.6	82.2	84.2	91.5	95.5	96.0	96.4	98.8	99.2	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.0001	65.6	82.2	84.2	91.5	95.5	96.0	96.4	98.8	99.2	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.00005	65.6	82.2	84.2	91.5	95.5	96.0	96.4	98.8	99.2	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.000025	65.6	82.2	84.2	91.5	95.5	96.0	96.4	98.8	99.2	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.00001	65.6	82.2	84.2	91.5	95.5	96.0	96.4	98.8	99.2	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 247

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 0710 COL A J ED BAKER AAF DL

73-78,83-82

ALL

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

ALL

CEILING FEET	VISIBILITY - STATUTE MILES															
	20	20	25	24	23	22	21	20	19	18	17	16	15	14	13	12
20000	37.4	34.3	32.6	40.7	41.2	41.2	41.4	41.5	41.5	41.6	41.7	41.7	41.7	41.9	41.9	42.0
18000	34.3	43.8	44.2	45.6	46.1	46.1	46.3	46.4	46.5	46.5	46.6	46.6	46.6	46.8	46.8	46.9
16000	34.3	44.5	44.7	46.3	46.5	46.6	47.0	47.1	47.2	47.2	47.3	47.3	47.3	47.5	47.5	47.6
14000	34.3	44.5	44.7	46.3	46.6	46.6	47.0	47.1	47.2	47.2	47.3	47.3	47.3	47.5	47.5	47.6
12000	34.4	44.5	44.9	46.4	46.9	46.9	47.1	47.2	47.2	47.3	47.4	47.4	47.4	47.6	47.6	47.6
10000	35.2	45.1	45.5	46.9	47.4	47.4	47.6	47.7	47.8	47.9	47.9	47.9	47.9	48.1	48.1	48.2
8000	36.4	46.6	47.1	48.4	49.0	49.0	49.2	49.3	49.3	49.4	49.4	49.4	49.5	49.7	49.7	49.7
6000	37.7	46.6	49.1	50.6	51.2	51.2	51.4	51.5	51.5	51.6	51.7	51.7	51.7	51.9	51.9	51.9
4000	41.2	52.7	53.1	54.7	55.3	55.3	55.5	55.6	55.6	55.8	55.8	55.8	55.8	56.0	56.0	56.1
2000	43.3	55.3	55.7	57.5	58.0	58.0	58.2	58.3	58.4	58.5	58.5	58.5	58.5	58.6	58.6	58.6
1000	43.4	55.5	55.9	57.6	58.3	58.3	58.5	58.6	58.7	58.8	58.8	58.8	58.8	58.9	59.1	59.1
500	45.1	57.4	57.9	59.8	61.3	60.3	60.5	60.7	60.7	60.8	60.9	60.9	60.9	61.1	61.1	61.2
200	46.3	58.8	59.7	61.2	61.9	61.9	62.1	62.2	62.3	62.4	62.4	62.4	62.5	62.7	62.7	62.7
100	48.5	61.4	61.9	64.3	65.0	65.0	65.2	65.3	65.4	65.5	65.5	65.5	65.5	65.6	65.8	65.8
50	52.4	66.1	66.5	69.2	70.0	70.0	70.2	70.3	70.4	70.5	70.5	70.5	70.5	70.6	70.8	70.8
25	56.7	71.7	72.4	75.9	76.8	76.8	77.0	77.4	77.4	77.6	77.6	77.6	77.7	77.9	77.9	77.9
12	59.4	76.5	77.7	81.2	82.2	82.3	82.5	82.8	82.8	83.0	83.1	83.1	83.1	83.3	83.3	83.3
6	61.6	78.2	79.3	84.1	85.6	85.6	86.0	86.4	86.5	86.9	86.9	86.9	86.9	87.1	87.1	87.2
3	62.1	79.2	80.4	85.8	87.3	87.4	87.8	88.2	88.3	88.7	88.8	88.8	88.8	89.0	89.0	89.1
1	62.8	80.5	81.8	87.9	90.0	90.1	90.8	91.3	91.4	91.8	91.9	91.9	91.9	92.1	92.1	92.2
0.5	63.7	80.8	82.2	88.6	91.1	91.3	92.0	92.5	92.7	93.1	93.2	93.2	93.2	93.5	93.5	93.5
0.25	63.3	81.2	82.5	89.2	91.8	92.2	93.1	94.2	94.4	95.3	95.3	95.3	95.4	95.6	95.6	95.6
0.125	63.3	81.2	82.5	89.3	92.1	92.6	93.6	94.8	95.0	96.0	96.1	96.1	96.1	96.3	96.3	96.4
0.0625	63.4	81.3	82.7	89.6	92.6	93.0	94.1	95.5	95.7	96.8	96.9	96.9	97.0	97.2	97.2	97.2
0.03125	63.4	81.3	82.7	89.9	93.0	93.4	94.7	96.2	96.4	97.6	97.7	97.7	97.7	97.8	98.0	98.1
0.015625	63.4	81.3	82.7	90.0	93.2	93.7	95.1	96.6	96.8	98.0	98.1	98.2	98.3	98.5	98.5	98.6
0.0078125	63.4	81.3	82.7	90.2	93.4	93.9	95.3	97.1	97.3	98.7	98.8	98.9	99.0	99.3	99.3	99.3
0.00390625	63.4	81.4	82.9	90.2	93.4	93.9	95.3	97.2	97.4	98.8	98.9	99.0	99.1	99.4	99.4	99.4
0.001953125	63.4	81.4	82.9	90.2	93.4	93.9	95.3	97.2	97.5	98.9	99.0	99.1	99.1	99.5	99.7	99.8
0.0009765625	63.4	81.4	82.9	90.2	93.4	93.9	95.3	97.2	97.5	98.9	99.0	99.1	99.1	99.6	99.8	99.9
0.00048828125	63.4	81.4	82.9	90.3	93.5	94.0	95.4	97.3	97.5	98.9	99.0	99.1	99.2	99.7	99.9	100.0

TOTAL NUMBER OF OBSERVATIONS 2443

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CENTRAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 4710 COL A J BO BAKER AAF DL

73-78, PD-62

SEP

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1600-2600

		VISIBILITY STATUTE MILES																	
CEILING FEET		2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	
2.0	2000	27.1	32.4	32.4	33.9	34.1	34.1	34.7	35.4	35.4	35.9	36.5	36.7	37.2	38.4	35.9	39.7		
2.5	2000	30.5	36.4	36.4	37.9	38.2	38.2	38.9	39.5	39.5	40.0	40.7	40.9	41.4	43.7	43.5	44.4		
3.0	2000	31.1	37.4	37.4	38.9	39.2	39.2	39.9	40.5	40.5	41.0	41.7	41.9	42.4	44.7	44.5	45.3		
3.5	2000	31.5	37.4	37.4	38.9	39.2	39.2	39.9	40.5	40.5	41.0	41.7	41.9	42.4	44.7	44.5	45.3		
4.0	2000	31.6	37.4	37.4	38.9	39.2	39.2	39.9	40.5	40.5	41.0	41.7	41.9	42.4	44.7	44.5	45.3		
4.5	2000	31.7	37.9	37.4	39.4	39.7	39.7	40.4	41.0	41.0	41.5	42.2	42.4	42.9	44.5	45.0	45.5		
5.0	2000	33.4	40.0	40.0	42.0	42.4	42.4	43.0	43.7	43.7	44.2	44.7	45.0	45.5	47.2	47.7	48.7		
5.5	2000	34.4	40.7	40.7	42.9	43.2	43.2	43.9	44.5	44.5	45.0	45.8	46.0	46.5	48.2	48.7	49.7		
6.0	2000	37.4	44.0	44.0	46.2	46.6	46.6	47.5	48.2	48.2	48.7	49.5	49.7	50.2	51.6	52.3	53.3		
6.5	2000	38.9	46.0	46.0	48.3	49.0	49.0	49.7	50.3	50.3	50.5	51.7	51.8	52.3	54.7	54.6	55.6		
7.0	2000	39.0	46.2	46.2	48.5	49.2	49.2	49.8	50.5	50.5	51.0	51.8	52.0	52.5	54.2	55.0	56.0		
7.5	2000	41.4	49.2	49.2	51.5	52.5	52.5	53.5	54.2	54.2	54.8	55.6	56.0	56.6	58.3	59.1	60.1		
8.0	2000	42.5	50.3	50.3	53.0	53.7	53.7	54.7	55.3	55.3	56.0	56.8	57.1	57.8	59.6	60.5	61.5		
8.5	2000	45.5	54.2	54.2	57.0	57.8	57.8	59.0	59.6	59.6	60.3	61.1	61.5	62.1	64.7	64.9	65.8		
9.0	2000	48.3	57.3	57.3	60.3	61.1	61.1	62.5	63.1	63.1	63.6	64.5	65.0	65.6	67.4	68.3	69.3		
9.5	2000	52.2	63.5	63.5	66.6	67.8	67.8	69.1	69.5	69.9	70.9	71.8	72.1	73.3	75.1	75.9	76.9		
10.0	2000	53.2	65.4	65.4	69.4	70.9	71.1	72.4	73.1	73.3	74.3	75.1	75.6	76.7	78.6	79.9	80.9		
10.5	2000	56.3	69.3	69.3	74.4	76.4	76.6	77.9	78.6	78.7	79.7	80.6	81.1	82.2	84.1	85.4	86.4		
11.0	2000	57.5	71.3	71.3	76.4	78.4	78.6	79.9	80.6	80.7	81.7	82.6	83.1	84.2	86.7	87.4	88.4		
11.5	2000	58.3	72.3	72.3	78.2	80.7	80.9	82.7	83.6	83.7	84.7	85.5	86.0	87.2	89.7	90.4	91.4		
12.0	2000	58.3	72.3	72.3	78.4	81.2	81.6	83.9	84.7	84.9	86.0	86.9	87.4	88.5	90.4	91.7	92.7		
12.5	2000	58.3	72.3	72.3	79.2	82.2	82.7	85.4	86.2	86.4	87.7	88.7	89.2	90.4	92.2	93.5	94.5		
13.0	2000	58.3	72.3	72.3	79.2	82.4	82.9	85.9	86.9	87.0	88.5	89.5	90.0	91.2	93.7	94.4	95.3		
13.5	2000	58.3	72.4	72.4	79.7	83.2	83.7	86.7	87.7	87.9	89.5	90.5	91.0	92.2	94.2	95.5	96.5		
14.0	2000	58.3	72.4	72.4	79.7	83.2	83.7	86.7	87.7	87.9	89.9	91.0	91.5	93.7	95.7	96.3	97.3		
14.5	2000	58.3	72.4	72.4	79.7	83.2	83.7	86.7	87.7	87.9	89.9	91.0	91.5	93.7	95.7	96.3	97.3		
15.0	2000	58.3	72.4	72.4	79.7	83.4	83.9	86.9	87.9	88.0	90.0	91.5	92.0	93.7	95.8	97.2	98.2		
15.5	2000	58.3	72.4	72.4	79.7	83.4	83.9	86.9	87.9	88.0	90.5	92.2	92.7	94.4	96.5	98.0	99.0		
16.0	2000	58.3	72.4	72.4	79.7	83.4	83.9	86.9	87.9	88.0	90.5	92.2	93.0	94.7	97.0	98.5	99.5		
16.5	2000	58.3	72.4	72.4	79.7	83.4	83.9	86.9	87.9	88.0	90.5	92.2	93.0	94.7	97.0	98.5	99.5		
17.0	2000	58.3	72.4	72.4	79.7	83.4	83.9	86.9	87.9	88.0	90.5	92.2	93.0	94.7	97.0	98.5	99.5		
17.5	2000	58.3	72.4	72.4	79.7	83.4	83.9	86.9	87.9	88.0	90.5	92.2	93.0	94.7	97.0	98.5	99.5		

TOTAL NUMBER OF OBSERVATIONS 602

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 0710
STATION

01L A J 30 BAKER AAF DL
STATION NAME

73-75,80-82
YEAR

SEP
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

0900-1100
HOURS

CEILING FEET	VISIBILITY - STATUTE MILES															
	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2.5	≥ 2	≥ 1.5	≥ 1	≥ .5	≥ .3	≥ .2	≥ .1	≥ .05	≥ .03	≥ .01
NO CEILING	32.3	41.1	41.5	43.8	44.4	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6
≥ 2000	37.4	46.1	46.5	49.7	50.3	50.5	50.7	50.7	50.7	50.7	50.7	50.7	50.7	50.7	50.7	50.7
≥ 1800	37.9	46.6	47.1	50.2	50.8	51.0	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2
≥ 1600	37.9	46.6	47.1	50.2	50.8	51.0	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2
≥ 1400	37.9	46.6	47.1	50.2	50.8	51.0	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2
≥ 1200	38.2	47.3	47.8	50.8	51.5	51.7	51.9	51.9	51.9	51.9	51.9	51.9	51.9	51.9	51.9	51.9
≥ 1000	39.1	48.1	48.7	52.0	52.7	52.9	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0
≥ 900	39.7	49.0	49.5	52.9	53.5	53.7	53.9	53.9	53.9	53.9	53.9	53.9	53.9	53.9	53.9	53.9
≥ 800	44.5	54.5	55.1	59.1	59.8	59.9	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1
≥ 700	45.6	56.1	56.1	60.6	61.3	61.4	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6
≥ 600	45.3	56.4	56.9	61.9	61.6	61.8	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0
≥ 500	47.9	58.9	59.4	63.8	64.5	64.6	64.8	64.8	64.8	64.8	64.8	64.8	64.8	64.8	64.8	64.8
≥ 400	48.7	59.9	60.4	64.8	65.5	65.7	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8
≥ 300	52.4	64.8	65.3	69.7	70.4	70.5	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7
≥ 200	55.2	68.4	69.2	73.0	74.4	74.6	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7
≥ 100	56.1	71.2	72.4	76.9	77.9	78.1	78.5	78.6	78.6	78.6	78.6	78.6	78.6	78.6	78.6	78.6
≥ 50	58.2	73.4	75.6	80.8	81.8	82.0	82.3	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5
≥ 30	59.3	76.3	78.6	85.5	87.2	87.4	87.7	88.0	88.0	88.0	88.0	88.0	88.0	88.0	88.0	88.0
≥ 20	60.1	77.1	79.6	86.9	88.6	88.7	89.1	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4
≥ 10	60.3	77.4	80.1	88.9	90.7	90.9	91.6	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9
≥ 5	60.3	77.6	80.3	89.6	91.6	91.8	92.6	92.9	93.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1
≥ 3	60.4	78.3	81.1	91.4	93.6	93.8	94.9	95.5	95.6	97.0	97.0	97.0	97.0	97.0	97.0	97.0
≥ 2	60.4	78.3	81.1	91.4	93.6	93.8	94.9	95.5	95.6	97.1	97.3	97.3	97.3	97.3	97.3	97.3
≥ 1	60.4	78.3	81.1	91.9	94.1	94.3	95.5	96.5	96.8	98.7	98.8	98.8	98.8	96.5	98.9	98.8
≥ .5	60.4	78.3	81.1	91.9	94.1	94.3	95.5	96.8	97.1	99.0	99.2	99.2	99.2	99.2	99.2	99.2
≥ .3	60.4	78.3	81.1	91.9	94.1	94.3	95.5	96.8	97.1	99.0	99.2	99.2	99.2	99.2	99.2	99.2
≥ .2	60.4	78.3	81.1	91.9	94.1	94.3	95.5	96.8	97.1	99.0	99.2	99.2	99.2	99.2	99.2	99.2
≥ .1	60.4	78.3	81.1	91.9	94.1	94.3	95.5	96.8	97.1	99.0	99.2	99.2	99.2	99.2	99.2	99.2
≥ .05	60.4	78.3	81.1	91.9	94.1	94.3	95.5	96.8	97.1	99.0	99.2	99.2	99.2	99.2	99.2	99.2
≥ .03	60.4	78.3	81.1	91.9	94.1	94.3	95.5	96.8	97.1	99.0	99.2	99.2	99.2	99.2	99.2	99.2
≥ .01	60.4	78.3	81.1	91.9	94.1	94.3	95.5	96.8	97.1	99.0	99.2	99.2	99.2	99.2	99.2	99.2

TOTAL NUMBER OF OBSERVATIONS 594

JOINT MILITARY CLIMATOLOGY BRANCH
 WASHINGTON, D.C.
 AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 4710

COL A J BO BAKER AAF DL

73-79,80-82

SET

PERCENTAGE FREQUENCY OF OCCURRENCE
 (FROM HOURLY OBSERVATIONS)

1220-1420

CEILING FEET	VISIBILITY - STATUTE MILES															
	20	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12
NO CEILING	34.2	42.8	47.1	44.6	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0
20000	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
18000	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
16000	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
14000	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
12000	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
10000	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
8000	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
6000	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
4000	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
2000	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
1000	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
800	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
600	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
400	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
200	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
100	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
80	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
60	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
40	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
20	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
10	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
8	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
6	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
4	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
2	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
1	37.7	50.1	50.3	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2

TOTAL NUMBER OF OBSERVATIONS 549

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 9710
STATION

COL A J SO BAKER AAF DL
STATION NAME

73-75,91-82
YEAR

SEP
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1900-1700
HOURS

CEILING FEET	VISIBILITY STATUTE MILES															
	≥10	≥6	≥5	≥4	≥3	≥2	≥2	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1
NO CEILING	31.6	41.1	42.7	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4
≥20000	37.4	50.9	51.9	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8
≥18000	37.7	51.3	52.4	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2
≥16000	37.7	51.5	52.6	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4
≥14000	38.3	51.9	53.7	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8
≥12000	38.5	52.6	53.7	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5
≥10000	39.2	53.5	54.5	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4
≥9000	39.8	54.8	55.4	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7
≥8000	42.2	58.2	59.3	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6
≥7000	43.9	60.8	61.9	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4
≥6000	43.9	60.8	61.9	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4
≥5000	44.2	61.3	62.3	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8
≥4500	46.1	63.4	64.5	68.0	68.0	68.0	68.0	68.0	68.0	68.0	68.0	68.0	68.0	68.0	68.0	68.0
≥4000	48.3	66.0	67.1	70.8	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0
≥3500	52.4	70.6	71.5	75.5	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8
≥3000	57.8	77.7	79.0	83.3	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5
≥2500	60.3	81.0	82.3	87.2	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4
≥2000	61.5	82.9	84.2	90.3	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5
≥1800	62.3	84.0	85.3	92.4	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6
≥1500	62.6	84.8	86.4	93.9	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4
≥1200	62.6	85.1	86.8	95.0	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7
≥1000	62.6	85.5	87.2	95.5	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1
≥900	62.6	85.5	87.2	95.5	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1
≥800	62.8	85.7	87.4	95.7	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
≥700	62.8	85.7	87.4	95.7	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
≥600	62.8	85.7	87.4	95.7	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
≥500	62.8	85.7	87.4	95.7	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
≥400	62.8	85.7	87.4	95.7	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
≥300	62.8	85.7	87.4	95.7	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
≥200	62.8	85.7	87.4	95.7	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
≥100	62.8	85.7	87.4	95.7	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
≥	62.8	85.7	87.4	95.7	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3

TOTAL NUMBER OF OBSERVATIONS 462

U.S. AIR FORCE
 CLIMATE BRANCH
 AFETAC
 AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1-4717 COL A J. SO RAKER AAF CL

33-74, 91-52

PERCENTAGE FREQUENCY OF OCCURRENCE
 (FROM HOURLY OBSERVATIONS)

13-2-1950

CEILING FEET	VISIBILITY STATUTE MILES															
	30	26	24	22	20	18	16	14	12	10	8	6	4	2	1	0
NO. OF	31.0	41.4	47.6	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2000	36.0	43.1	49.4	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1
1800	38.0	45.1	49.4	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1
1600	38.4	46.5	49.8	51.5	51.5	51.5	51.5	51.5	51.5	51.5	51.5	51.5	51.5	51.5	51.5	51.5
1400	38.4	48.5	49.8	51.5	51.5	51.5	51.5	51.5	51.5	51.5	51.5	51.5	51.5	51.5	51.5	51.5
1200	38.8	50.2	51.5	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
1000	38.8	50.6	51.9	54.0	54.0	54.0	54.0	54.0	54.0	54.0	54.0	54.0	54.0	54.0	54.0	54.0
800	39.2	51.5	52.7	54.9	54.9	54.9	54.9	54.9	54.9	54.9	54.9	54.9	54.9	54.9	54.9	54.9
600	43.1	56.5	57.8	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3
400	44.3	57.8	59.1	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6
200	44.3	57.8	59.1	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6
100	45.1	58.6	59.9	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4
50	46.4	59.9	61.2	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7
25	47.7	61.2	62.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4
12.5	53.5	67.1	68.4	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0
6.25	62.1	78.1	79.7	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8
3.125	64.1	80.6	82.3	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
1.5625	64.6	81.4	83.1	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5
0.78125	64.6	81.4	83.1	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5
0.390625	64.6	82.3	84.4	92.8	93.2	93.2	94.1	94.1	94.1	94.9	94.9	94.9	94.9	94.9	94.9	94.9
0.1953125	64.6	82.3	84.4	94.5	94.9	94.9	97.0	97.0	97.0	98.3	98.3	98.3	98.3	98.3	98.3	98.3
0.09765625	65.1	82.7	84.8	94.9	95.4	95.4	97.5	97.5	97.5	98.7	98.7	98.7	98.7	98.7	98.7	98.7
0.048828125	65.4	83.1	85.2	95.4	95.8	95.8	97.9	97.9	97.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.0244140625	65.4	83.1	85.2	95.4	95.8	95.8	97.9	97.9	97.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.01220703125	65.4	83.1	85.2	95.4	95.8	95.8	97.9	97.9	97.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.006103515625	65.4	83.1	85.2	95.4	95.8	95.8	97.9	97.9	97.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.0030517578125	65.4	83.1	85.2	95.4	95.8	95.8	97.9	97.9	97.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.00152587890625	65.4	83.1	85.2	95.4	95.8	95.8	97.9	97.9	97.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.000762939453125	65.4	83.1	85.2	95.4	95.8	95.8	97.9	97.9	97.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
0.0003814697265625	65.4	83.1	85.2	95.4	95.8	95.8	97.9	97.9	97.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 237

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CEILING CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1-717 COL A J L BAKER AAF DL
STATION NAME

73-75, FD-82

SEP

PERCENTAGE FREQUENCY OF OCCURRENCE
FROM HOURLY OBSERVATIONS

ALL

CEILING FEET	VISIBILITY - STATUTE MILES																							
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
1-100	31.4	37.4	38.4	41.7	41.9	41.9	42.1	42.2	42.3	42.4	42.5	42.6	42.7	43.1	47.1	43.3								
101-200	35.1	40.7	45.2	45.6	48.9	48.9	49.1	49.3	49.3	49.4	49.5	49.6	49.8	50.2	50.3	50.5								
201-300	36.3	46.2	46.5	49.1	49.3	49.4	49.6	49.8	49.9	49.9	50.0	50.1	50.2	50.6	50.7	50.9								
301-400	36.3	46.2	46.7	49.1	49.4	49.5	49.7	49.8	49.9	50.0	50.1	50.2	50.3	50.7	50.9	51.0								
401-500	36.5	46.4	46.5	49.3	49.5	49.6	49.8	50.0	50.1	50.1	50.2	50.3	50.4	50.8	50.9	51.1								
501-600	36.7	47.1	47.5	50.0	50.2	50.3	50.5	50.7	50.7	50.8	50.9	51.0	51.1	51.5	51.6	51.8								
601-700	36.1	48.5	49.1	51.6	52.1	52.2	52.4	52.5	52.6	52.7	52.8	52.9	53.0	53.4	53.5	53.6								
701-800	38.7	49.6	51.1	53.0	53.3	53.5	53.7	53.7	53.8	54.0	54.1	54.2	54.6	54.7	55.0									
801-900	42.5	54.1	54.5	57.7	58.1	58.1	58.3	58.5	58.6	58.6	58.8	58.9	59.0	59.4	59.5	59.8								
901-1000	43.7	55.9	56.4	59.6	60.0	60.0	60.2	60.4	60.4	60.5	60.7	60.8	60.9	61.3	61.5	61.7								
1001-1100	43.7	56.1	56.7	59.8	60.2	60.2	60.4	60.6	60.6	60.7	60.9	61.0	61.1	61.5	61.7	61.9								
1101-1200	45.4	57.9	58.4	61.8	62.2	62.2	62.5	62.7	62.7	62.8	63.1	63.1	63.3	63.7	63.9	64.2								
1201-1300	47.4	59.2	59.7	63.1	63.5	63.5	63.8	64.0	64.1	64.1	64.3	64.4	64.6	65.0	65.2	65.5								
1301-1400	49.3	62.9	63.4	66.9	67.3	67.4	67.7	67.9	67.9	68.1	68.7	68.4	68.5	69.0	69.2	69.4								
1401-1500	52.8	66.9	67.5	71.2	71.7	71.8	72.1	72.3	72.3	72.5	72.7	72.8	73.0	73.4	73.5	73.9								
1501-1600	56.8	72.4	73.0	77.1	77.7	77.8	78.2	78.4	78.5	78.8	79.1	79.1	79.3	79.4	80.0	80.0								
1601-1700	58.3	74.8	76.1	80.5	81.2	81.3	81.8	82.0	82.0	82.4	82.7	82.7	83.0	83.4	83.8	84.0								
1701-1800	60.2	77.7	78.9	84.6	85.6	85.7	86.2	86.5	86.5	87.0	87.2	87.4	87.5	88.1	88.4	88.7								
1801-1900	61.0	78.8	80.2	86.1	87.2	87.2	87.8	88.1	88.2	88.7	88.9	89.0	89.3	89.7	90.1	90.3								
1901-2000	61.4	79.6	81.0	88.3	89.7	89.8	90.9	91.2	91.3	91.9	92.1	92.2	92.5	92.9	93.2	93.5								
2001-2100	61.5	79.7	81.2	88.9	90.5	90.7	92.0	92.3	92.5	93.2	93.4	93.5	93.8	94.2	94.4	94.8								
2101-2200	61.7	80.2	81.3	90.0	91.7	91.9	93.6	94.0	94.0	95.3	95.5	95.6	95.9	96.4	96.7	96.9								
2201-2300	61.7	80.2	81.5	90.0	91.9	92.0	93.9	94.4	94.5	95.7	96.1	96.2	96.4	96.9	97.2	97.5								
2301-2400	61.8	80.3	82.0	90.4	92.3	92.5	94.4	95.1	95.3	96.6	96.9	97.0	97.3	97.8	98.1	98.4								
2401-2500	61.8	80.4	82.1	90.5	92.4	92.6	94.4	95.2	95.5	97.1	97.4	97.5	97.9	98.4	98.7	98.9								
2501-2600	61.8	80.4	82.1	90.5	92.4	92.6	94.4	95.3	95.5	97.1	97.4	97.5	97.9	98.4	98.7	98.9								
2601-2700	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.3	97.7	97.9	98.3	98.9	99.2	99.4								
2701-2800	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
2801-2900	61.8	80.4	82.1	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
2901-3000	61.8	80.4	82.1	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
3001-3100	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
3101-3200	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
3201-3300	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
3301-3400	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
3401-3500	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
3501-3600	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
3601-3700	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
3701-3800	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
3801-3900	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
3901-4000	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
4001-4100	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
4101-4200	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
4201-4300	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
4301-4400	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
4401-4500	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
4501-4600	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
4601-4700	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
4701-4800	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
4801-4900	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								
4901-5000	61.8	80.4	82.0	90.5	92.4	92.7	94.6	95.4	95.7	97.5	98.0	98.2	98.5	99.1	99.5	99.7								

TOTAL NUMBER OF OBSERVATIONS 2444

CLIMATE CLIMATOLOGY BRANCH
USAF ETAC
AIR LEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 7710 COL A J BO BAKER AAF DL

73-78,80-82

CLT

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1000-2800

ELEVATION FEET	VISIBILITY - STATUTE MILES															
	≥10	≥6	≥5	≥4	≥3	≥2	≥2	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1
NO. OF LINE 20000	23.4	31.0	30.1	30.3	30.3	30.5	30.7	30.8	30.8	31.3	31.8	31.8	32.2	32.9	33.9	34.4
20000	26.4	33.4	33.5	33.7	33.7	33.9	34.1	34.2	34.2	34.3	35.3	35.3	35.6	36.3	37.3	37.8
20000	27.1	34.1	34.2	34.4	34.4	34.6	34.8	34.9	34.9	35.4	36.0	36.0	36.3	37.0	38.0	38.6
20000	27.2	34.2	34.4	34.6	34.6	34.8	34.9	35.1	35.1	35.6	36.1	36.1	36.5	37.2	38.2	38.7
20000	27.2	34.2	34.4	34.6	34.6	34.8	34.9	35.1	35.1	35.6	36.1	36.1	36.5	37.2	38.2	38.7
20000	27.2	34.2	34.4	34.6	34.6	34.8	34.9	35.1	35.1	35.6	36.1	36.1	36.5	37.2	38.2	38.7
20000	28.4	35.4	35.6	35.8	35.8	36.0	36.1	36.3	36.3	36.8	37.3	37.3	37.7	38.4	39.4	39.9
20000	28.9	36.1	36.3	36.5	36.5	36.6	36.8	37.0	37.0	37.5	38.0	38.0	38.4	39.2	40.2	40.6
20000	31.0	37.0	37.2	37.4	37.4	37.6	37.7	37.9	37.9	38.5	39.0	39.0	39.4	40.2	41.2	41.6
20000	33.1	41.3	41.4	41.6	41.6	41.8	42.0	42.1	42.1	42.6	43.1	43.1	43.5	44.2	45.2	45.6
20000	34.2	42.8	43.1	43.2	43.2	43.3	43.5	43.7	43.7	44.3	44.8	44.8	45.2	46.1	47.3	47.8
20000	35.4	44.2	44.3	44.5	44.5	44.7	44.9	45.0	45.0	45.7	46.2	46.2	46.6	47.4	48.6	49.1
20000	37.3	46.2	46.4	46.5	46.6	46.7	46.9	47.1	47.1	47.8	48.3	48.3	48.6	49.5	50.7	51.2
20000	38.4	48.8	49.0	49.1	49.1	49.3	49.5	49.7	49.7	50.3	50.8	50.8	51.2	52.1	53.3	53.8
20000	41.1	51.9	52.1	52.4	52.4	52.6	52.7	52.9	52.9	53.6	54.1	54.1	54.5	55.3	56.5	57.0
20000	42.1	55.0	55.3	55.8	55.8	56.0	56.2	56.5	56.5	57.2	57.7	57.7	58.0	58.9	60.1	60.6
20000	45.7	57.7	58.4	59.2	59.2	59.4	59.6	59.9	59.9	60.6	61.1	61.1	61.5	62.3	63.5	64.0
20000	46.7	59.8	60.6	63.2	63.2	63.4	63.7	64.2	64.2	65.1	65.6	65.6	65.9	66.8	68.0	68.5
20000	47.6	60.4	61.3	63.9	64.0	64.2	64.7	65.2	65.2	66.1	66.6	66.6	67.0	67.8	69.0	69.5
20000	49.9	63.9	64.9	68.3	69.2	69.7	71.4	72.1	72.1	73.1	73.6	73.6	74.1	75.0	76.2	76.7
20000	50.5	65.9	67.1	72.1	73.3	73.6	75.7	76.5	76.5	77.7	78.3	78.3	78.8	79.6	80.8	81.3
20000	51.0	66.6	67.8	73.0	75.2	75.7	78.4	79.5	79.5	80.8	81.5	81.5	82.2	83.6	84.8	85.3
20000	51.0	66.6	67.8	73.6	75.2	75.7	78.4	79.6	79.6	81.1	82.0	82.2	82.9	84.2	85.4	86.1
20000	51.4	67.1	68.3	74.1	75.7	76.2	79.5	80.8	80.8	82.4	83.4	83.6	84.4	85.8	87.0	87.7
20000	51.4	67.1	68.3	74.3	75.9	76.4	80.0	81.3	81.3	83.0	84.1	84.2	85.3	86.6	87.9	88.5
20000	51.4	67.1	68.3	74.3	75.9	76.4	80.1	81.7	81.7	83.7	85.1	85.3	86.3	88.5	89.7	90.4
20000	51.4	67.1	68.3	74.3	75.9	76.4	80.1	81.8	81.8	85.1	86.6	86.8	88.0	90.2	91.4	92.1
20000	51.4	67.1	68.3	74.3	75.9	76.4	80.1	82.0	82.0	85.8	87.3	87.5	88.7	92.0	93.7	94.2
20000	51.4	67.1	68.3	74.3	75.9	76.4	80.1	82.0	82.0	86.6	88.4	88.5	89.9	94.2	96.2	97.1
20000	51.4	67.1	68.3	74.3	75.9	76.4	80.1	82.0	82.0	86.6	88.4	88.5	90.1	94.9	97.9	99.8
20000	51.4	67.1	68.3	74.3	75.9	76.4	80.1	82.0	82.0	86.6	88.4	88.5	90.1	94.9	97.9	99.8
20000	51.4	67.1	68.3	74.3	75.9	76.4	80.1	82.0	82.0	86.6	88.4	88.5	90.1	94.9	97.9	99.8

TOTAL NUMBER OF OBSERVATIONS 524

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CLIMATOLGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

STATION 1710 COL A J BO BAKER AAF DL

73-75, FD-52

DOT

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

822-1100

CEILING FEET	VISIBILITY - STATUTE MILES															
	210	20	25	24	23	22	21	20	19	18	17	16	15	14	13	12
10000	29.3	35.5	35.9	28.2	36.5	36.5	36.7	36.9	36.9	37.0	37.2	37.2	37.2	37.2	37.2	37.2
8000	31.9	40.0	40.0	40.4	40.7	40.7	40.9	41.1	41.1	41.3	41.4	41.4	41.4	41.4	41.4	41.4
6000	31.4	40.2	40.2	40.6	40.9	40.9	41.1	41.3	41.7	41.4	41.5	41.5	41.5	41.5	41.5	41.5
4000	32.3	40.6	40.6	40.9	41.3	41.3	41.4	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6
3000	32.5	40.7	40.7	41.1	41.4	41.4	41.6	41.6	41.6	41.6	42.0	42.2	42.2	42.2	42.2	42.2
2000	32.5	41.9	40.9	41.3	41.6	41.6	41.8	42.0	42.0	42.2	42.3	42.3	42.3	42.3	42.3	42.3
1800	33.3	41.6	41.6	42.0	42.3	42.3	42.5	42.7	42.7	42.9	43.0	43.0	43.0	43.0	43.0	43.0
1600	35.4	43.9	43.5	44.3	44.6	44.6	44.8	45.0	45.0	45.1	45.7	45.3	45.3	45.3	45.3	45.3
1400	36.4	48.5	48.5	48.9	49.2	49.2	49.4	49.6	49.6	49.7	49.9	49.9	49.9	49.9	49.9	49.9
1200	39.7	50.1	50.1	50.4	50.8	50.8	51.0	51.1	51.1	51.3	51.5	51.5	51.5	51.5	51.5	51.5
1000	40.7	51.3	51.3	51.7	52.0	52.0	52.2	52.4	52.4	52.6	52.7	52.7	52.7	52.7	52.7	52.7
800	41.4	52.6	52.6	52.9	53.3	53.3	53.6	53.8	53.8	54.0	54.1	54.1	54.1	54.1	54.1	54.1
600	42.5	53.4	53.4	54.1	54.5	54.5	54.9	55.0	55.0	55.2	55.4	55.4	55.4	55.4	55.4	55.4
400	44.1	55.2	55.2	55.9	56.3	56.3	56.6	56.8	56.8	57.1	57.1	57.1	57.1	57.1	57.1	57.1
300	46.9	58.9	58.9	59.6	60.0	60.0	60.3	60.5	60.5	60.7	60.8	60.8	60.8	60.8	60.8	60.8
200	49.1	62.1	62.3	63.1	63.5	63.5	63.8	64.0	64.0	64.2	64.4	64.4	64.4	64.4	64.4	64.4
180	50.3	63.7	64.4	65.3	65.6	65.6	66.0	66.1	66.1	66.3	66.5	66.5	66.5	66.5	66.5	66.5
160	51.5	66.5	67.4	69.5	70.5	70.5	71.1	71.6	71.8	72.1	72.3	72.3	72.3	72.3	72.3	72.3
140	52.2	67.2	69.1	70.7	71.8	72.1	72.5	73.0	73.2	73.5	73.7	73.7	73.7	73.7	73.7	73.7
120	54.3	70.4	71.7	74.4	76.5	77.6	78.7	79.9	80.1	81.0	81.1	81.1	81.1	81.1	81.1	81.1
100	54.7	71.3	72.1	76.2	78.3	79.4	80.8	82.7	82.9	83.8	84.0	84.0	84.0	84.0	84.0	84.0
80	55.4	72.3	73.7	78.1	80.2	81.7	84.0	86.2	86.4	88.0	88.4	88.5	88.5	89.1	89.1	89.2
60	55.4	72.0	73.0	78.5	80.6	82.0	84.3	86.6	86.9	88.5	89.2	89.4	89.4	89.9	89.9	90.1
40	55.4	72.0	73.0	78.5	80.6	82.0	84.8	87.1	87.5	89.4	90.3	90.5	90.7	91.2	91.2	91.4
30	55.4	72.0	73.0	78.5	80.8	82.2	85.2	87.7	88.0	90.3	91.4	91.5	91.7	92.4	92.4	92.6
20	55.4	72.0	73.0	78.5	80.8	82.2	85.4	87.8	88.4	91.0	92.2	92.4	92.6	93.3	93.3	93.5
10	55.4	72.0	73.0	78.5	81.3	82.9	86.1	88.5	89.2	92.6	93.9	94.0	94.5	95.4	95.4	95.6
5	55.4	72.0	73.0	78.5	81.5	83.2	86.8	89.4	90.1	93.7	94.9	95.1	95.6	97.2	97.2	97.5
3	55.4	72.0	73.0	78.5	81.5	83.2	86.0	89.6	90.2	94.2	95.6	95.8	96.6	99.1	99.1	99.5
2	55.4	72.0	73.0	78.5	81.5	83.2	86.0	89.6	90.3	94.2	95.6	95.8	96.6	99.3	99.3	99.8
1	55.4	72.0	73.0	78.5	81.5	83.2	87.1	89.8	90.6	94.4	95.8	95.9	96.8	99.5	99.5	100.0
0	55.4	72.0	73.0	78.5	81.5	83.2	87.1	89.8	90.6	94.4	95.8	95.9	96.8	99.5	99.5	100.0

TOTAL NUMBER OF OBSERVATIONS 567

U.S. AIR FORCE
U.S. AIR FORCE
U.S. AIR FORCE

CEILING VERSUS VISIBILITY

1 0010 COL A J B BAKER AAF DL

73-78,50-52

001

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1000-1400

ELEVATION FEET	VISIBILITY - STATUTE MILES															
	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
100	31.1	37.4	37.4	37.5	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1
200	33.4	40.5	40.5	40.5	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6
300	34.1	41.2	41.2	41.6	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3
400	34.1	41.2	41.2	41.6	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3
500	34.2	41.4	41.4	41.8	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5
600	34.3	41.8	41.8	42.1	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
700	37.1	44.9	44.9	45.2	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0
800	38.3	46.9	46.9	47.3	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0
900	41.0	50.7	50.9	51.3	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0
1000	41.3	52.4	52.4	52.7	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
1100	43.0	54.6	54.6	54.9	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7
1200	45.2	56.2	56.2	56.6	57.3	57.3	57.5	57.5	57.5	57.5	57.5	57.5	57.5	57.5	57.5	57.5
1300	45.1	57.3	57.3	57.9	58.6	58.6	58.8	58.8	58.8	58.8	58.8	58.8	58.8	58.8	58.8	58.8
1400	45.5	60.4	60.4	61.0	61.7	61.7	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9
1500	46.6	63.5	63.5	64.1	64.8	64.8	65.0	65.0	65.0	65.0	65.0	65.0	65.0	65.0	65.0	65.0
1600	48.1	67.8	67.8	68.5	69.2	69.2	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4	69.4
1700	50.6	71.2	71.4	72.0	72.7	72.7	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9
1800	50.6	74.7	74.9	76.0	77.1	77.8	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0
1900	59.3	75.8	76.3	77.5	78.6	79.3	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5
2000	61.5	78.1	78.2	81.7	83.0	83.9	84.1	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4
2100	62.3	79.1	79.3	83.9	85.7	86.6	87.0	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4
2200	62.3	79.7	79.9	84.6	87.4	88.8	89.7	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3
2300	62.3	79.9	80.0	85.0	87.9	89.4	90.3	91.2	91.6	92.5	93.0	93.0	93.0	93.0	93.0	93.0
2400	62.3	79.9	80.1	85.0	88.8	90.3	91.4	92.3	92.7	93.6	94.1	94.1	94.1	94.1	94.1	94.1
2500	62.3	79.9	80.2	85.2	89.0	90.5	92.1	93.6	94.0	95.2	96.2	96.2	96.2	96.2	96.2	96.2
2600	62.3	79.9	80.2	85.2	89.2	90.7	92.3	94.0	94.3	96.2	97.1	97.1	97.1	97.1	97.1	97.1
2700	62.3	79.9	80.2	85.2	89.9	91.6	93.4	95.1	95.4	97.6	98.5	98.5	98.5	98.5	98.5	98.5
2800	62.3	79.9	80.2	85.5	90.3	91.9	93.8	95.6	96.0	98.2	99.1	99.1	99.1	99.1	99.1	99.1
2900	62.3	79.9	80.2	85.5	90.3	91.9	93.8	95.6	96.0	98.4	99.3	99.3	99.3	99.3	99.3	99.3
3000	62.3	79.9	80.2	85.5	90.3	91.9	93.8	95.6	96.0	98.4	99.3	99.3	99.3	99.3	99.3	99.3
3100	62.3	79.9	80.2	85.5	90.3	91.9	93.8	95.6	96.0	98.4	99.3	99.3	99.3	99.3	99.3	99.3
3200	62.3	79.9	80.2	85.5	90.3	91.9	93.8	95.6	96.0	98.4	99.3	99.3	99.3	99.3	99.3	99.3

TOTAL NUMBER OF OBSERVATIONS 596

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GENERAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 4710 COL A J SO BAKER AAF DL

73-78, 81-82

CC

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1500-1700

CEILING FEET	VISIBILITY, STATUTE MILES															
	≥ 10	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12
≥ 10000	28.9	37.5	38.1	38.8	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0
9000	32.3	41.3	42.2	42.7	43.8	43.8	43.8	43.8	43.8	43.8	44.0	44.0	44.0	44.0	44.0	44.0
8000	32.3	41.5	42.2	42.9	44.0	44.0	44.0	44.0	44.0	44.0	44.2	44.2	44.2	44.2	44.2	44.2
7000	32.3	41.5	42.2	42.9	44.0	44.0	44.0	44.0	44.0	44.0	44.2	44.2	44.2	44.2	44.2	44.2
6000	32.3	41.5	42.2	42.9	44.0	44.0	44.0	44.0	44.0	44.0	44.2	44.2	44.2	44.2	44.2	44.2
5000	33.1	42.2	42.9	43.6	44.7	44.7	44.7	44.7	44.7	44.7	44.9	44.9	44.9	44.9	44.9	44.9
4000	34.1	44.0	44.7	45.4	46.5	46.5	46.5	46.5	46.5	46.5	46.7	46.7	46.7	46.7	46.7	46.7
3000	35.2	45.6	46.3	47.0	48.1	48.1	48.1	48.1	48.1	48.1	48.3	48.3	48.3	48.3	48.3	48.3
2000	36.4	46.1	46.9	47.6	48.6	48.6	48.6	48.6	48.6	48.6	48.8	48.8	48.8	48.8	48.8	48.8
1000	38.8	50.9	51.0	52.1	53.3	53.3	53.3	53.3	53.3	53.3	53.5	53.5	53.5	53.5	53.5	53.5
800	38.8	50.9	51.0	52.1	53.3	53.3	53.3	53.3	53.3	53.3	53.5	53.5	53.5	53.5	53.5	53.5
600	40.2	52.1	52.1	53.5	54.6	54.6	54.6	54.6	54.6	54.6	54.9	54.9	54.9	54.9	54.9	54.9
400	41.1	53.5	54.2	54.9	56.0	56.0	56.0	56.0	56.0	56.0	56.2	56.2	56.2	56.2	56.2	56.2
300	45.4	58.9	59.6	60.5	61.6	61.6	61.6	61.6	61.6	61.6	61.9	61.9	61.9	61.9	61.9	61.9
200	47.1	61.4	62.1	63.0	64.1	64.1	64.1	64.1	64.1	64.1	64.3	64.3	64.3	64.3	64.3	64.3
100	51.2	67.0	67.7	68.8	70.0	70.0	70.0	70.0	70.0	70.0	70.4	70.4	70.4	70.4	70.4	70.4
80	53.5	72.2	71.1	72.9	74.3	74.3	74.3	74.3	74.3	74.3	74.7	74.7	74.7	74.7	74.7	74.7
60	55.3	72.9	73.8	76.5	78.1	78.3	78.3	78.3	78.3	78.3	78.8	78.8	78.8	78.8	78.8	78.8
40	55.5	73.6	74.5	77.2	79.5	79.7	79.7	79.7	79.7	79.7	80.1	80.1	80.1	80.1	80.1	80.1
30	56.7	75.2	76.4	80.1	83.3	83.5	83.5	83.5	83.5	83.5	84.0	84.0	84.0	84.0	84.0	84.0
20	56.7	75.8	77.4	82.2	87.1	87.4	87.4	87.4	87.4	87.4	87.8	87.8	87.8	87.8	87.8	87.8
10	56.9	76.5	78.1	83.3	88.5	88.7	89.2	89.8	90.1	91.2	91.4	91.6	91.9	91.9	91.9	91.9
8	56.9	77.0	78.5	83.7	89.4	89.6	90.1	90.7	91.0	92.1	92.3	92.8	93.0	93.0	93.0	93.0
6	57.1	77.2	79.0	84.2	89.8	90.3	91.0	91.6	91.9	93.0	93.2	93.7	93.9	93.9	93.9	93.9
4	57.1	77.2	79.0	84.4	90.3	91.0	92.3	93.2	94.4	95.3	95.5	95.9	96.2	96.2	96.2	96.2
3	57.1	77.2	79.0	84.7	90.5	91.2	92.6	93.5	94.6	97.1	97.5	98.0	98.2	98.2	98.2	98.2
2	57.1	77.2	79.0	84.7	90.5	91.2	92.6	93.5	94.6	97.7	98.2	98.6	99.3	99.5	99.5	99.5
1	57.1	77.2	79.0	84.7	90.5	91.2	92.6	93.5	94.6	97.7	98.2	98.6	99.3	99.5	99.5	99.5
0	57.1	77.2	79.0	84.7	90.5	91.2	92.6	93.5	94.6	97.7	98.2	98.6	99.3	99.5	99.5	99.5

TOTAL NUMBER OF OBSERVATIONS 483

CLIMATE CLIMATOLOGY BRANCH
 AFETAC
 AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1-710
 STATION

COL A J ED BAKER AAF DL
 STATION NAME

75-75,81-82
 YEARS

307
 DAYS

PERCENTAGE FREQUENCY OF OCCURRENCE
 (FROM HOURLY OBSERVATIONS)

1840-2000
 DATE

CEILING FEET	VISIBILITY STATUTE MILES																
	20	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	10
20000	28.9	35.6	36.6	36.6	35.0	36.4	38.4	35.7	39.0	39.4	39.7	39.7	39.7	39.7	39.7	39.7	39.7
18000	31.1	39.7	40.8	40.8	42.1	42.5	42.5	42.8	43.2	43.5	43.8	43.8	43.8	43.8	43.8	43.8	43.8
16000	31.1	39.7	40.8	40.8	42.1	42.5	42.5	43.2	43.5	43.8	44.2	44.2	44.2	44.2	44.2	44.2	44.2
14000	31.1	39.7	40.8	40.8	42.1	42.5	42.5	43.2	43.5	43.8	44.2	44.2	44.2	44.2	44.2	44.2	44.2
12000	31.1	39.7	40.8	40.8	42.1	42.5	42.5	43.2	43.5	43.8	44.2	44.2	44.2	44.2	44.2	44.2	44.2
10000	32.2	40.4	41.4	41.4	42.8	43.5	43.5	43.8	44.2	44.5	44.9	44.9	44.9	44.9	44.9	44.9	44.9
9000	33.2	41.4	42.5	42.5	43.8	44.5	44.5	44.9	45.2	45.5	45.9	45.9	45.9	45.9	45.9	45.9	45.9
8000	36.3	44.5	45.5	45.5	46.9	47.6	47.6	47.9	48.3	48.6	49.0	49.0	49.0	49.0	49.0	49.0	49.0
7000	37.3	46.6	47.6	47.6	49.0	49.7	49.7	50.0	50.3	50.7	51.0	51.0	51.0	51.0	51.0	51.0	51.0
6000	37.3	46.6	47.6	47.6	49.0	49.7	49.7	50.0	50.3	50.7	51.0	51.0	51.0	51.0	51.0	51.0	51.0
5000	38.3	48.3	49.3	49.3	50.7	51.4	51.4	51.7	52.1	52.4	52.7	52.7	52.7	52.7	52.7	52.7	52.7
4500	39.7	50.7	51.7	51.7	53.1	53.8	53.8	54.1	54.5	54.8	55.1	55.1	55.1	55.1	55.1	55.1	55.1
4000	42.1	54.1	55.1	55.1	56.5	57.2	57.2	57.5	57.9	58.2	58.6	58.6	58.6	58.6	58.6	58.6	58.6
3500	44.1	56.5	57.5	57.5	58.9	59.6	59.6	59.9	60.3	60.6	61.0	61.0	61.0	61.0	61.0	61.0	61.0
3000	47.9	60.6	62.3	62.3	63.7	64.4	64.4	64.7	65.1	65.4	65.8	65.8	65.8	65.8	65.8	65.8	65.8
2500	50.3	63.7	65.4	65.4	67.1	67.8	67.8	68.2	68.5	68.8	69.2	69.2	69.2	69.2	69.2	69.2	69.2
2000	52.1	65.8	67.5	67.5	70.9	71.6	71.6	71.9	72.3	73.3	73.6	73.6	73.6	73.6	73.6	73.6	73.6
1800	52.4	66.8	68.5	68.5	72.6	73.3	73.3	73.6	74.0	75.0	75.3	75.3	75.3	75.3	75.3	75.3	75.3
1600	52.4	66.8	68.5	68.5	71.9	74.7	75.3	76.0	76.4	76.7	77.7	78.1	78.1	78.1	78.1	78.1	76.1
1400	52.4	67.5	69.2	69.2	73.6	77.1	78.1	79.8	80.8	81.2	82.2	82.5	82.5	82.5	82.5	82.5	82.5
1200	53.1	68.2	69.9	69.9	75.3	79.1	80.1	81.8	83.2	84.2	86.3	86.6	86.6	86.6	87.3	87.3	87.3
1000	53.1	68.2	70.5	70.5	76.7	80.5	81.5	83.2	84.6	85.6	87.7	88.0	88.0	88.0	88.7	88.7	88.7
900	53.1	68.2	70.5	70.5	76.7	80.5	82.2	84.6	86.0	87.0	89.0	89.4	89.4	89.4	90.1	90.1	90.1
800	53.1	68.2	70.5	70.5	76.7	80.5	82.5	85.6	87.3	89.0	91.8	92.5	92.5	93.5	93.5	93.5	93.5
700	53.1	68.2	70.5	70.5	76.7	80.5	82.5	85.6	87.3	89.7	92.8	93.5	93.5	94.5	94.5	94.5	94.5
600	53.4	68.5	70.9	70.9	77.1	80.8	82.9	86.0	87.7	90.4	94.9	95.5	95.5	96.6	96.9	97.3	97.3
500	53.4	68.5	70.9	70.9	77.1	80.8	82.9	86.0	88.0	90.8	95.2	96.6	96.6	97.6	98.3	98.6	98.6
400	53.4	68.5	70.9	70.9	77.1	80.8	82.9	86.0	88.4	91.1	95.5	96.9	96.9	97.6	98.6	99.3	99.7
300	53.4	68.5	70.9	70.9	77.1	80.8	82.9	86.0	88.4	91.1	95.5	96.9	96.9	97.6	98.6	99.7	100.0
200	53.4	68.5	70.9	70.9	77.1	80.8	82.9	86.0	88.4	91.1	95.5	96.9	96.9	97.6	98.6	99.7	100.0
100	53.4	68.5	70.9	70.9	77.1	80.8	82.9	86.0	88.4	91.1	95.5	96.9	96.9	97.6	98.6	99.7	100.0

TOTAL NUMBER OF OBSERVATIONS 292

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 9710
STATION

COL A J GO BAKER AAF DL
STATION NAME

73-73,80-82
YEAR

201
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

ALL
HOURS

CEILING FEET	VISIBILITY STATUTE MILES															
	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2	≥ 2	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1
NO CEILING	28.1	35.0	35.3	35.6	36.2	36.3	36.3	36.5	36.5	36.7	36.9	36.9	37.7	37.2	37.4	37.5
≥ 20000	31.1	39.7	39.7	39.4	40.0	40.0	40.1	40.3	40.3	40.5	40.7	40.7	40.8	41.0	41.2	41.4
≥ 18000	31.3	39.1	39.4	39.8	40.4	40.5	40.6	40.7	40.7	40.7	41.0	41.2	41.2	41.3	41.4	41.8
≥ 16000	31.5	39.3	39.6	39.9	40.5	40.6	40.7	40.8	40.9	41.1	41.3	41.3	41.4	41.6	41.8	41.9
≥ 14000	31.5	39.4	39.6	40.0	40.6	40.7	40.8	40.9	41.0	41.2	41.4	41.4	41.5	41.7	41.9	42.0
≥ 12000	31.7	39.6	39.9	40.2	40.8	41.0	41.0	41.2	41.2	41.4	41.7	41.7	41.7	41.9	42.1	42.3
≥ 10000	33.1	41.2	41.4	41.6	42.4	42.5	42.6	42.7	42.8	43.0	43.2	43.2	43.3	43.5	43.7	43.8
≥ 9000	34.2	42.7	43.7	43.3	44.0	44.1	44.2	44.3	44.3	44.6	44.8	44.8	44.9	45.1	45.3	45.4
≥ 8000	36.3	46.2	46.5	46.8	47.5	47.6	47.7	47.8	47.8	48.1	48.3	48.3	48.4	48.6	49.8	49.0
≥ 7000	38.2	48.2	48.5	48.8	49.4	49.5	49.6	49.8	49.8	50.1	50.3	50.3	50.4	50.6	50.9	51.0
≥ 6000	39.1	49.3	49.6	50.0	50.6	50.7	50.8	50.9	50.9	51.2	51.4	51.4	51.5	51.7	52.0	52.1
≥ 5000	40.3	50.8	51.1	51.4	52.0	52.1	52.3	52.4	52.5	52.8	53.0	53.0	53.0	53.2	53.5	53.7
≥ 4500	41.4	52.3	52.5	53.0	53.6	53.7	53.9	54.0	54.1	54.4	54.6	54.6	54.6	54.8	55.1	55.3
≥ 4000	44.0	55.4	55.7	56.2	56.8	56.9	57.1	57.2	57.2	57.5	57.7	57.7	57.8	58.0	58.3	58.4
≥ 3500	46.5	58.4	58.7	59.3	59.9	60.0	60.2	60.3	60.3	60.6	60.8	60.8	60.9	61.1	61.4	61.5
≥ 3000	49.2	62.4	62.9	63.5	64.1	64.3	64.4	64.6	64.6	65.0	65.2	65.2	65.3	65.5	65.7	65.9
≥ 2500	51.2	65.1	65.9	66.8	67.4	67.6	67.7	67.9	67.9	68.3	68.5	68.5	68.5	68.8	69.0	69.2
≥ 2000	52.8	67.8	68.6	70.7	71.7	72.0	72.2	72.5	72.6	73.1	73.3	73.3	73.4	73.6	73.9	74.0
≥ 1800	53.3	68.6	69.4	71.8	72.9	73.4	73.6	73.9	74.0	74.5	74.7	74.7	74.8	75.0	75.2	75.4
≥ 1600	55.1	71.0	71.9	75.3	77.2	77.9	78.7	79.3	79.4	80.0	80.2	80.2	80.3	80.6	80.8	81.0
≥ 1400	55.5	72.1	73.1	77.7	80.2	81.0	82.0	82.9	83.0	83.7	83.9	83.9	84.0	84.2	84.5	84.7
≥ 1200	55.9	72.8	73.8	79.1	82.0	82.9	84.6	85.8	86.1	87.4	87.9	88.0	88.2	88.7	89.0	89.2
≥ 1000	55.9	72.9	74.1	79.5	82.5	83.5	85.2	86.5	86.8	88.2	88.8	88.9	88.9	89.2	89.7	90.2
≥ 900	56.0	73.1	74.3	79.7	82.9	84.0	86.1	87.5	87.8	89.3	89.9	90.1	90.5	91.0	91.2	91.4
≥ 800	56.0	73.1	74.3	79.6	83.1	84.3	86.7	88.2	88.8	90.7	91.6	91.7	92.2	92.7	93.0	93.2
≥ 700	56.0	73.1	74.3	79.9	83.2	84.3	87.0	88.7	89.4	91.7	92.7	92.9	93.3	94.1	94.4	94.6
≥ 600	56.0	73.1	74.3	79.9	83.6	84.8	87.5	89.2	90.0	93.1	94.2	94.3	95.1	96.0	96.3	96.5
≥ 500	56.0	73.1	74.3	80.0	83.7	85.0	87.7	89.6	90.4	93.7	94.8	95.0	95.8	97.1	97.5	97.7
≥ 400	56.0	73.1	74.3	80.0	83.7	85.0	87.7	89.7	90.7	94.2	95.4	95.6	96.5	98.3	98.8	99.1
≥ 300	56.0	73.1	74.3	80.0	83.7	85.0	87.7	89.7	90.7	94.2	95.4	95.7	96.6	98.6	99.4	100.0
≥ 200	56.0	73.1	74.3	80.0	83.7	85.0	87.8	89.7	90.7	94.2	95.4	95.7	96.6	98.6	99.4	100.0
≥ 100	56.0	73.1	74.3	80.0	83.7	85.0	87.8	89.7	90.7	94.2	95.4	95.7	96.6	98.6	99.4	100.0

TOTAL NUMBER OF OBSERVATIONS 2432

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CENTRAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 9710 COL A J BO BAKER AAF DL

73-79,80-82

NOV

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1970-1972

CEILING FEET	VISIBILITY - STATUTE MILES															
	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2.5	≥ 2	≥ 1.5	≥ 1	≥ .5	≥ .3	≥ .2	≥ .1	≥ .05	≥ .03	≥ .01
NO CEILING	24.1	23.5	28.5	29.0	29.0	29.0	29.0	29.0	29.0	29.0	29.0	29.0	29.0	29.0	29.0	29.0
≥ 20000	29.2	34.4	34.6	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1
≥ 18000	29.2	34.6	34.6	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1
≥ 16000	29.2	34.6	34.6	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1
≥ 14000	29.4	34.8	34.9	35.3	35.3	35.3	35.3	35.3	35.3	35.3	35.3	35.3	35.3	35.3	35.3	35.3
≥ 12000	29.9	35.3	35.3	35.8	35.8	35.8	35.8	35.8	35.8	35.8	35.8	35.8	35.8	35.8	35.8	35.8
≥ 10000	30.1	35.5	35.5	36.0	36.0	36.0	36.0	36.0	36.0	36.0	36.0	36.0	36.0	36.0	36.0	36.0
≥ 9000	31.5	37.1	37.1	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
≥ 8000	32.3	41.4	41.4	41.9	41.9	41.9	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1
≥ 7000	36.9	43.3	43.3	43.5	43.5	43.5	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7
≥ 6000	36.9	43.7	43.7	43.5	43.5	43.5	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7
≥ 5000	38.0	44.3	44.3	44.8	44.8	44.8	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0
≥ 4000	39.1	45.3	45.3	46.1	46.1	46.1	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2
≥ 3000	41.4	46.0	46.0	46.1	46.1	46.1	46.3	46.3	46.3	46.3	46.3	46.3	46.3	46.3	46.3	46.3
≥ 2000	43.4	50.4	50.4	51.4	51.6	51.6	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8
≥ 1000	44.3	51.6	51.6	53.2	53.6	53.6	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8
≥ 500	47.5	55.6	55.7	57.5	57.9	57.9	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1
≥ 200	48.9	57.2	57.7	60.2	60.9	60.9	61.3	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5
≥ 100	49.6	57.9	58.4	61.8	62.9	63.1	63.4	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6
≥ 50	50.5	59.3	60.7	65.6	67.7	67.9	68.8	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0
≥ 20	51.4	60.6	61.5	67.4	69.5	69.9	71.9	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6
≥ 10	51.4	60.6	61.5	69.0	71.7	73.3	76.2	77.8	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3
≥ 5	51.4	60.6	61.5	69.4	72.4	74.0	78.0	79.6	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1
≥ 2	51.4	60.6	61.5	69.4	72.9	74.6	78.9	80.8	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4
≥ 1	51.4	60.6	61.5	69.7	73.5	75.1	79.6	81.5	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1
≥ .5	51.6	60.8	61.8	69.9	73.7	75.8	80.6	82.6	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7
≥ .3	51.6	60.8	61.8	70.1	73.8	76.2	81.2	83.3	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4
≥ .2	51.6	60.8	61.8	70.1	73.8	76.2	81.2	83.3	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4
≥ .1	51.6	60.8	61.8	70.1	73.8	76.2	81.2	83.3	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4
≥ .05	51.6	60.8	61.8	70.1	73.8	76.2	81.2	83.3	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4
≥ .03	51.6	60.8	61.8	70.1	73.8	76.2	81.2	83.3	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4
≥ .01	51.6	60.8	61.8	70.1	73.8	76.2	81.2	83.3	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4

TOTAL NUMBER OF OBSERVATIONS 558

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
 USAF ETAC
 AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 0710 COL A J SO BAKER AAF DL

73-78,80-82

NGV

PERCENTAGE FREQUENCY OF OCCURRENCE
 (FROM HOURLY OBSERVATIONS)

900-1170

CEILING (FEET)	VISIBILITY - STATUTE MILES															
	2.0	2.6	2.5	2.4	2.3	2.2	2.1	2.0	1.9	1.8	1.7	1.6	1.5	1.4	1.3	1.2
20000	26.5	30.3	30.5	30.7	30.7	30.7	30.7	30.7	30.7	30.7	30.7	30.9	30.9	30.9	30.9	31.4
18000	31.1	36.3	36.4	36.6	36.6	36.6	36.6	36.7	36.7	36.7	36.7	37.1	37.1	37.1	37.1	37.7
16000	31.1	36.3	36.4	36.6	36.6	36.6	36.6	36.7	36.7	36.7	36.7	37.1	37.1	37.1	37.1	37.7
14000	31.4	36.4	36.7	36.9	36.9	36.9	37.1	37.1	37.3	37.5	37.5	37.5	37.5	37.5	38.0	38.0
12000	32.3	36.9	37.3	37.5	37.5	37.5	37.7	37.7	37.8	38.0	38.0	38.0	38.0	38.0	38.6	38.6
10000	32.9	36.6	38.0	39.1	39.1	39.1	39.3	39.3	39.5	39.7	39.7	39.7	39.7	40.2	40.2	40.2
8000	32.9	38.9	39.3	39.5	39.5	39.5	39.7	39.7	39.9	40.0	40.0	40.0	40.0	40.6	40.6	40.6
6000	37.7	43.9	44.2	44.4	44.4	44.4	44.6	44.6	44.8	45.0	45.0	45.0	45.0	45.6	45.6	45.6
4000	39.7	46.6	47.2	47.3	47.3	47.3	47.5	47.5	47.7	47.9	47.9	47.9	47.9	48.4	48.4	48.4
2000	40.2	47.5	47.6	48.1	48.1	48.1	48.3	48.3	48.4	48.6	48.6	48.6	48.6	49.2	49.2	49.2
1000	40.8	49.0	49.4	49.5	49.5	49.5	49.7	49.7	49.9	50.1	50.1	50.1	50.1	50.6	50.6	50.6
500	42.1	50.5	50.8	51.0	51.0	51.0	51.2	51.2	51.4	51.6	51.6	51.6	51.6	52.1	52.1	52.1
250	45.0	53.9	54.3	54.5	54.5	54.5	54.7	54.7	54.8	55.0	55.0	55.0	55.0	55.6	55.6	55.6
100	47.7	57.2	57.8	58.5	58.5	58.5	58.7	58.7	58.9	59.0	59.0	59.0	59.0	59.6	59.6	59.6
50	48.6	58.7	59.2	60.1	60.1	60.1	60.3	60.3	60.7	60.9	60.9	60.9	60.9	61.4	61.4	61.4
25	49.5	60.1	60.7	61.8	61.8	61.8	62.0	62.0	62.3	62.5	62.5	62.5	62.5	63.1	63.1	63.1
10	51.2	62.9	63.6	66.4	66.5	66.7	66.9	67.1	67.5	67.6	67.6	67.6	67.6	68.2	68.2	68.2
5	51.9	63.6	64.9	68.4	68.6	69.1	69.5	69.7	70.0	70.2	70.2	70.2	70.2	70.7	70.7	70.7
2	52.7	64.7	66.7	71.7	72.8	73.3	74.0	74.6	75.1	75.5	75.7	75.7	75.7	76.2	76.2	76.2
1	53.0	65.1	67.1	72.9	74.0	74.8	76.4	77.1	77.5	78.1	78.2	78.2	78.2	78.8	78.8	78.8
0.5	53.0	65.4	67.5	74.6	75.7	76.4	78.1	80.1	80.4	81.9	82.3	82.3	82.3	82.8	82.8	82.8
0.25	53.0	65.4	67.8	75.1	76.4	77.9	80.6	82.6	83.4	85.2	85.6	85.6	85.6	86.1	86.1	86.1
0.1	53.0	65.4	67.8	75.1	76.4	77.9	80.8	83.4	83.9	86.1	86.8	86.8	86.8	87.4	87.4	87.4
0.05	53.0	65.4	68.1	75.5	77.0	78.4	81.5	84.6	85.2	87.6	88.3	88.5	88.5	89.0	89.0	89.0
0.025	53.0	65.4	68.1	75.5	77.3	78.8	82.1	86.3	87.2	90.5	91.6	92.5	93.8	94.9	94.9	95.1
0.01	53.0	65.4	68.1	75.9	77.3	78.8	82.4	86.7	87.6	91.4	92.7	93.6	94.9	96.2	96.2	96.3
0.005	53.0	65.4	68.0	75.9	77.3	78.8	82.4	86.7	87.6	91.6	93.1	94.1	95.6	98.4	98.4	99.1
0.0025	53.0	65.4	68.0	75.9	77.3	78.8	82.4	86.7	87.6	91.6	93.1	94.1	95.6	98.7	99.1	99.8
0.001	53.0	65.4	68.0	75.9	77.3	78.8	82.4	86.7	87.6	91.6	93.1	94.1	95.6	98.7	99.3	100.0

TOTAL NUMBER OF OBSERVATIONS 547

GLOBAL CLIMATOLOGY BRANCH
CAPETAC
AF-WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 4710
STATION

COL A J 50 BAKER AAF DL
STATION NAME

73-75,80-52
YEAR

NOV
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

12,22-1422
NO. OF

CEILING FEET	VISIBILITY - STATUTE MILES															
	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2	≥ 2	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1
20000	27.4	31.7	31.2	32.8	33.0	33.2	33.4	33.6	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8
18000	31.3	36.7	36.9	38.0	38.2	38.4	38.6	39.0	39.0	39.0	39.0	39.0	39.0	39.0	39.0	39.0
16000	31.7	37.5	37.6	38.8	39.0	39.2	39.4	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
14000	31.9	37.5	37.6	38.8	39.0	39.2	39.4	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
12000	33.0	38.6	38.8	40.0	40.2	40.3	40.5	40.9	40.9	40.9	40.9	40.9	40.9	40.9	40.9	40.9
10000	34.0	40.0	40.2	41.3	41.5	41.7	41.9	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3
9000	34.2	40.2	40.3	41.5	41.7	41.9	42.1	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5
8000	37.5	44.2	44.4	45.6	45.8	45.9	46.1	46.5	46.5	46.5	46.5	46.5	46.5	46.5	46.5	46.5
7000	39.3	46.5	46.7	47.9	48.1	48.3	48.5	48.8	48.8	48.8	48.8	48.8	48.8	48.8	48.8	48.8
6000	40.9	47.7	47.9	49.0	49.2	49.6	50.2	50.6	50.6	50.6	50.6	50.6	50.6	50.6	50.6	50.6
5000	42.3	49.2	49.4	50.6	50.8	51.4	51.7	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1
4500	42.9	49.8	50.0	51.2	51.4	51.9	52.3	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7
4000	45.7	53.5	53.7	55.0	55.2	55.6	56.2	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6
3500	47.3	56.4	56.6	57.9	58.1	58.7	59.1	59.5	59.5	59.5	59.5	59.5	59.5	59.5	59.5	59.5
3000	45.5	57.5	57.7	59.8	60.0	60.6	61.4	61.8	61.8	61.8	61.8	61.8	61.8	61.8	61.8	61.8
2500	51.0	60.4	61.1	64.7	64.9	65.4	66.2	66.6	66.6	66.6	66.6	66.6	66.6	66.6	66.6	66.6
2000	52.7	62.9	63.7	69.1	69.9	70.5	71.2	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6
1800	53.1	63.5	64.5	71.0	72.2	73.0	73.7	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1
1600	54.1	65.4	67.2	73.9	75.9	76.8	78.0	79.3	79.3	79.7	79.9	79.9	79.9	79.9	79.9	79.9
1400	54.4	66.6	68.3	75.7	78.2	79.5	81.3	82.6	82.6	83.0	83.2	83.2	83.2	83.2	83.2	83.2
1200	54.8	67.0	68.9	77.2	79.7	81.1	82.8	84.6	84.6	85.3	85.5	85.7	85.7	85.7	85.7	85.7
1000	54.3	67.0	68.9	77.2	79.7	81.1	83.0	84.9	84.9	85.7	85.9	86.1	86.1	86.1	86.1	86.1
900	54.4	67.2	69.5	78.4	81.3	82.8	85.7	88.0	88.0	89.2	89.4	89.6	89.6	89.6	89.6	89.6
800	54.4	67.2	69.5	78.4	81.5	83.0	86.1	88.6	88.6	90.2	90.5	90.7	90.7	91.3	91.3	91.3
700	54.4	67.2	69.5	78.4	81.5	83.0	86.3	89.0	89.0	92.1	92.5	92.7	92.7	93.2	93.2	93.2
600	54.3	67.2	69.5	78.6	81.7	83.4	86.9	90.5	91.1	94.4	95.0	95.2	95.4	95.9	95.9	95.9
500	54.5	67.2	69.5	78.6	81.7	83.4	86.9	90.5	91.7	95.8	96.7	96.9	97.1	97.7	97.9	97.9
400	54.3	67.2	69.5	78.6	81.7	83.4	86.9	90.5	91.7	96.1	97.1	97.3	97.5	98.1	98.8	98.8
300	54.3	67.2	69.5	78.6	81.7	83.4	86.9	90.5	91.7	96.3	97.3	97.7	97.9	98.8	100.0	100.0
200	54.3	67.2	69.5	78.6	81.7	83.4	86.9	90.5	91.7	96.3	97.3	97.7	97.9	98.8	100.0	100.0
100	54.3	67.2	69.5	78.6	81.7	83.4	86.9	90.5	91.7	96.3	97.3	97.7	97.9	98.8	100.0	100.0
0	54.3	67.2	69.5	78.6	81.7	83.4	86.9	90.5	91.7	96.3	97.3	97.7	97.9	98.8	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 518

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 5710 COL A J ED BAKER AAF DL

73-79,80-82

NOV

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1500-1700

CEILING FEET	VISIBILITY STATUTE MILES															
	≥10	≥8	≥6	≥4	≥3	≥2	≥2	≥2	≥2	≥2	≥2	≥2	≥2	≥2	≥2	≥2
NO CEILING	20.1	25.4	25.4	27.0	27.5	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
≥20000	24.9	31.1	31.1	32.6	33.3	33.5	33.5	33.5	33.5	33.5	33.5	33.5	33.5	33.5	33.5	33.5
≥18000	25.4	31.8	31.8	33.5	34.0	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2
≥16000	25.4	31.8	31.8	33.5	34.0	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2
≥14000	25.4	31.8	31.8	33.5	34.0	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2
≥12000	25.4	31.8	31.8	33.5	34.0	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2
≥10000	27.5	34.4	34.4	36.1	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6
≥9000	27.5	34.7	34.7	36.4	36.8	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1
≥8000	29.9	37.8	37.8	39.5	40.0	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
≥7000	31.1	39.3	39.3	40.7	41.1	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
≥6000	31.9	39.7	39.7	41.4	41.9	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1
≥5000	32.1	40.7	40.7	42.3	42.8	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
≥4500	33.3	42.1	42.1	43.8	44.3	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5
≥4000	35.6	45.0	45.0	46.7	47.1	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4
≥3500	38.8	49.3	49.3	50.7	51.4	51.9	51.9	51.9	51.9	51.9	51.9	51.9	51.9	51.9	51.9	51.9
≥3000	41.1	51.9	51.9	55.3	56.2	56.7	57.2	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4
≥2500	45.2	56.5	56.5	60.3	61.2	61.7	62.2	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4
≥2000	49.8	60.8	61.0	66.0	67.5	68.4	69.1	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6
≥1800	49.8	61.7	62.1	67.7	69.9	70.8	71.5	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2
≥1600	50.2	62.9	63.9	71.5	74.6	75.6	76.6	78.2	78.2	79.2	79.2	79.2	79.2	79.2	79.2	79.2
≥1400	50.7	63.9	65.1	74.4	77.5	78.7	80.1	82.1	82.1	83.3	83.3	83.3	83.3	83.3	83.3	83.3
≥1200	51.4	64.8	66.0	76.3	79.4	81.1	83.0	85.2	85.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3
≥1000	51.4	64.8	66.0	76.3	79.4	81.1	83.0	85.2	85.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3
≥900	51.4	64.8	66.0	76.3	79.4	81.1	83.0	85.2	85.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3
≥800	51.4	64.8	66.0	76.3	79.4	81.1	83.0	85.2	85.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3
≥700	51.4	64.8	66.0	76.3	79.4	81.1	83.0	85.2	85.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3
≥600	51.4	64.8	66.0	76.3	79.4	81.1	83.0	85.2	85.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3
≥500	51.4	64.8	66.0	76.3	79.4	81.1	83.0	85.2	85.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3
≥400	51.4	64.8	66.0	76.3	79.4	81.1	83.0	85.2	85.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3
≥300	51.4	64.8	66.0	76.3	79.4	81.1	83.0	85.2	85.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3
≥200	51.4	64.8	66.0	76.3	79.4	81.1	83.0	85.2	85.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3
≥100	51.4	64.8	66.0	76.3	79.4	81.1	83.0	85.2	85.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3
≥50	51.4	64.8	66.0	76.3	79.4	81.1	83.0	85.2	85.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3
≥20	51.4	64.8	66.0	76.3	79.4	81.1	83.0	85.2	85.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3

TOTAL NUMBER OF OBSERVATIONS 418

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AF WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 4710
STATION

COL A J CO BAKER AAF DL
STATION NAME

73-78,81-82
YEAR

NOV
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1980-2000
PERIOD

CEILING FEET	VISIBILITY, STATUTE MILES															
	≥10	≥8	≥5	≥4	≥3	≥2.5	≥2	≥1.5	≥1	≥0.5	≥0.25	≥0.1	≥0.05	≥0.025	≥0.01	≥0
NO CEILING	23.4	26.4	26.4	27.1	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6
2 2000	28.6	31.9	31.9	32.6	34.1	34.1	34.1	34.1	34.1	34.1	34.1	34.1	34.1	34.1	34.1	34.1
2 1800	28.6	32.6	32.6	33.3	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2
2 1600	28.6	32.6	32.6	33.3	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2
2 1400	28.6	32.6	32.6	33.3	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2
2 1200	29.3	33.3	33.3	34.1	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2 1000	29.7	33.7	33.7	34.4	36.3	36.3	36.3	36.3	36.3	36.3	36.3	36.3	36.3	36.3	36.3	36.3
2 900	29.7	33.7	33.7	34.4	36.3	36.3	36.3	36.3	36.3	36.3	36.3	36.3	36.3	36.3	36.3	36.3
2 800	31.5	36.3	36.3	37.0	38.8	38.8	38.8	38.8	38.8	38.8	38.8	38.8	38.8	38.8	38.8	38.8
2 700	32.2	37.0	37.0	37.7	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6
2 600	32.4	37.7	37.7	38.5	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3
2 500	33.7	38.8	38.8	39.6	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2 450	34.4	39.6	39.6	40.3	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1
2 400	37.0	42.9	42.9	44.0	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8
2 350	39.6	45.8	45.8	47.3	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5
2 300	43.2	50.9	50.9	53.8	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0
2 250	45.4	55.3	55.3	59.0	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2
2 200	48.0	59.3	59.3	65.2	67.4	67.4	67.4	67.4	67.4	67.4	67.4	67.4	67.4	67.4	67.4	67.4
2 180	48.7	60.1	60.1	66.3	68.5	68.5	68.5	68.5	68.5	68.5	68.5	68.5	68.5	68.5	68.5	68.5
2 150	50.2	62.3	62.3	71.1	74.0	74.0	74.0	74.0	74.0	74.0	74.0	74.0	74.0	74.0	74.0	74.0
2 120	50.2	62.3	62.3	72.5	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8
2 100	50.2	62.3	62.3	73.6	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9
2 900	50.2	62.3	62.3	73.6	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9
2 800	50.2	62.3	62.3	73.6	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9
2 700	50.2	62.3	62.3	73.6	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9
2 600	50.2	62.3	62.3	73.6	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9
2 500	50.2	62.3	62.3	73.6	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9
2 400	50.2	62.3	62.3	73.6	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9
2 300	50.2	62.3	62.3	73.6	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9
2 200	50.2	62.3	62.3	73.6	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9
2 100	50.2	62.3	62.3	73.6	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9
2 000	50.2	62.3	62.3	73.6	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9

TOTAL NUMBER OF OBSERVATIONS 273

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 710
STATION

COL A J CO BAKER AAF DL
STATION NAME

73-78,80-82
YEAR

NOV
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

ALL
HOURLY

CEILING FEET	VISIBILITY STATUTE MILES															
	210	20	25	24	23	22	21	20	19	18	17	16	15	14	13	12
NO CEILING	24.6	25.6	29.9	29.7	30.0	30.1	30.1	30.2	30.2	30.3	30.3	30.3	30.4	30.7	30.8	30.9
2 20000	29.3	34.4	34.6	35.4	35.7	35.8	35.9	36.0	36.0	36.1	36.1	36.1	36.2	36.5	36.6	36.6
2 8000	29.5	34.5	35.0	35.8	36.1	36.2	36.3	36.4	36.4	36.5	36.5	36.6	36.6	36.9	37.0	37.0
2 6000	29.5	34.8	35.0	35.8	36.1	36.2	36.3	36.4	36.4	36.5	36.5	36.6	36.6	36.9	37.0	37.0
2 4000	29.6	35.0	35.1	35.9	36.3	36.3	36.4	36.5	36.6	36.6	36.7	36.7	36.7	37.1	37.1	37.1
2 2000	30.4	35.8	35.9	36.7	37.1	37.2	37.3	37.3	37.4	37.5	37.5	37.5	37.6	37.9	37.9	37.9
2 2000	31.1	36.5	36.9	37.8	38.1	38.2	38.3	38.4	38.4	38.5	38.5	38.5	38.6	38.9	39.0	39.0
2 1800	31.5	37.4	37.5	38.3	38.7	38.8	38.9	39.0	39.0	39.1	39.2	39.2	39.2	39.5	39.6	39.6
2 1600	34.9	41.4	41.5	42.3	42.7	42.7	42.9	43.0	43.0	43.1	43.1	43.1	43.2	43.5	43.6	43.6
2 1400	36.6	43.3	43.4	44.2	44.6	44.6	44.8	44.9	44.9	45.0	45.0	45.0	45.1	45.4	45.5	45.5
2 1200	37.2	43.9	44.0	44.9	45.2	45.4	45.5	45.6	45.7	45.8	45.8	45.8	45.9	46.2	46.2	46.2
2 1000	38.2	45.2	45.2	46.2	46.5	46.7	46.8	46.9	47.0	47.1	47.1	47.1	47.1	47.5	47.5	47.5
2 800	39.1	46.3	46.4	47.3	47.6	47.8	48.0	48.1	48.1	48.2	48.2	48.2	48.3	48.6	48.7	48.7
2 600	41.5	49.5	49.5	50.6	51.0	51.2	51.3	51.4	51.5	51.6	51.6	51.6	51.6	52.0	52.0	52.0
2 400	44.0	52.5	52.7	53.9	54.4	54.6	54.8	54.9	55.0	55.1	55.1	55.1	55.1	55.5	55.5	55.5
2 200	45.5	54.5	54.6	56.8	57.3	57.6	58.0	58.2	58.3	58.3	58.4	58.4	58.4	58.8	58.8	58.8
2 1800	48.1	57.9	58.2	60.8	61.4	61.6	62.0	62.2	62.3	62.4	62.4	62.4	62.4	62.8	62.8	62.8
2 1600	50.2	60.7	61.4	65.3	66.2	66.6	67.2	67.6	67.7	67.8	67.8	67.8	67.8	68.2	68.2	68.2
2 1400	50.7	61.5	62.4	67.0	68.2	68.8	69.4	69.9	70.0	70.1	70.2	70.2	70.2	70.6	70.6	70.6
2 1200	51.7	63.0	64.5	70.6	72.7	73.4	74.5	75.6	75.7	76.4	76.5	76.5	76.6	77.0	77.0	77.0
2 1000	52.2	63.8	65.4	72.4	74.7	75.6	77.5	78.9	79.0	79.7	79.9	79.9	80.0	80.3	80.4	80.4
2 800	52.4	64.2	65.9	73.9	76.4	77.5	79.7	81.7	82.0	83.6	83.8	83.9	84.0	84.7	84.4	84.4
2 600	52.4	64.2	66.1	75.1	77.8	79.3	82.4	84.6	85.0	86.8	87.0	87.1	87.3	87.6	87.6	87.6
2 400	52.4	64.2	66.1	75.1	78.0	79.6	82.9	85.4	85.7	87.8	88.4	88.5	88.7	89.4	89.5	89.5
2 200	52.4	64.2	66.2	75.2	78.3	79.6	83.3	86.0	86.3	89.1	89.8	90.1	90.2	90.9	91.0	91.1
2 1800	52.5	64.3	66.2	75.3	78.4	80.1	83.9	87.2	88.0	91.5	92.6	93.0	93.6	94.6	94.8	94.9
2 1600	52.5	64.3	66.2	75.5	78.5	80.3	84.1	87.7	88.8	92.8	94.1	94.6	95.2	96.5	96.6	96.7
2 1400	52.5	64.3	66.2	75.5	78.5	80.3	84.1	87.7	88.8	93.2	94.6	95.2	95.8	97.8	98.4	98.9
2 1200	52.5	64.3	66.2	75.5	78.5	80.3	84.1	87.7	88.8	93.3	94.6	95.3	96.0	98.3	99.2	99.7
2 1000	52.5	64.3	66.2	75.5	78.5	80.3	84.1	87.7	88.8	93.3	94.6	95.4	96.0	98.4	99.4	99.9
2 800	52.5	64.3	66.2	75.5	78.5	80.3	84.1	87.7	88.8	93.3	94.7	95.4	96.1	98.5	99.5	100.0

TOTAL NUMBER OF OBSERVATIONS 2514

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
USAF ETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 710
STATION

COL A J CO BAKER AAF DL
STATION NAME

73-7960-82
YEAR

DLC
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1972-1972
NO. OF

CEILING FEET	VISIBILITY - STATUTE MILES															
	≥10	20	25	24	23	22	21	20	19	18	17	16	15	14	13	12
≥20000	22.7	26.7	27.1	27.8	28.4	28.8	29.3	29.3	29.3	29.6	30.0	30.0	30.0	30.0	30.9	30.8
15000	26.2	30.5	31.1	32.4	33.0	33.3	33.9	33.9	34.0	34.5	34.8	34.8	35.5	35.5	35.5	35.5
10000	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
7500	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
5000	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
3000	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
1500	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
1000	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
750	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
500	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
300	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
150	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
100	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
75	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
50	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
30	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
15	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
10	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
7.5	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
5	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
3	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
1.5	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7
1	26.4	31.0	31.3	32.6	33.2	33.5	34.1	34.1	34.1	34.8	35.0	35.0	35.0	35.7	35.7	35.7

TOTAL NUMBER OF OBSERVATIONS 546

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CENTRAL CLIMATOLOGY BRANCH
AFSLTAC
AIR WEATHER SERVICE/AFAC

CEILING VERSUS VISIBILITY

1 0710
STATION

COL A J BAKER AAF DL
STATION NAME

73-78,80-82
YEAR

DEC
MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

1000-1400
HOURS

CEILING FEET	VISIBILITY STATUTE MILES															
	≥ 10	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12
NO CEILING	20.2	25.0	25.4	26.0	26.2	26.2	26.7	26.7	26.7	26.7	26.7	26.7	26.7	26.7	26.7	26.7
≥ 2000	24.4	30.2	30.2	31.2	31.3	31.3	31.9	31.9	31.9	31.9	31.9	31.9	31.9	31.9	31.9	31.9
≥ 1800	25.2	31.0	31.3	31.9	32.1	32.1	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7
≥ 1600	26.2	31.9	32.3	32.9	33.1	33.1	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7
≥ 1400	26.2	31.9	32.3	32.9	33.1	33.1	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7
≥ 1200	26.5	32.3	32.7	33.3	33.5	33.5	34.0	34.0	34.0	34.0	34.0	34.0	34.0	34.0	34.0	34.0
≥ 1000	27.3	33.1	33.7	34.0	34.2	34.2	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8
≥ 900	30.2	36.2	36.5	37.1	37.3	37.3	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
≥ 800	33.0	40.2	40.5	41.3	41.5	41.5	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1
≥ 700	36.0	43.3	44.7	44.8	45.0	45.0	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6
≥ 600	36.9	44.2	45.1	45.8	46.0	46.0	46.7	46.7	46.7	46.7	46.7	46.7	46.7	46.7	46.7	46.7
≥ 500	38.5	45.8	46.5	47.3	47.5	47.5	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3
≥ 400	40.5	48.1	48.9	49.6	49.8	49.8	50.6	50.6	50.6	50.6	50.6	50.6	50.6	50.6	50.6	50.6
≥ 300	44.0	51.7	52.5	53.3	53.5	53.5	54.2	54.2	54.2	54.2	54.2	54.2	54.2	54.2	54.2	54.2
≥ 200	47.7	56.2	56.7	57.7	57.9	57.9	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7
≥ 100	51.9	61.5	62.3	63.5	63.8	63.8	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6
≥ 50	53.3	63.8	64.8	66.5	66.9	66.9	68.1	68.1	68.1	68.1	68.1	68.1	68.1	68.1	68.1	68.1
≥ 20	55.6	65.6	67.3	69.2	70.0	70.2	71.5	71.5	71.7	71.7	71.7	71.9	71.9	71.9	71.9	71.9
≥ 10	56.7	67.7	69.2	71.3	72.1	72.3	74.0	74.0	74.2	74.2	74.2	74.4	74.4	74.4	74.4	74.4
≥ 5	58.8	70.6	72.1	74.2	75.4	75.6	77.5	77.5	77.7	77.7	77.7	77.9	78.1	78.3	78.3	78.3
≥ 2	59.6	72.3	73.8	76.3	77.7	77.9	80.8	80.8	81.0	81.0	81.0	81.2	81.3	81.5	81.5	81.5
≥ 1	60.0	72.9	74.4	77.7	79.2	79.4	83.3	83.8	84.7	84.2	84.4	84.6	85.0	85.0	85.0	85.0
≥ 0.5	60.0	73.1	74.6	78.7	80.2	80.4	84.2	84.6	85.0	85.2	85.4	85.6	86.0	86.0	86.0	86.0
≥ 0.2	60.0	73.1	75.0	79.6	81.2	81.9	86.2	86.9	87.1	87.5	88.1	88.3	88.8	89.0	89.0	89.0
≥ 0.1	60.2	73.5	75.4	80.2	81.7	82.5	86.7	87.9	88.1	88.5	89.0	89.2	89.8	90.0	90.0	90.0
≥ 0.05	60.2	73.5	75.4	80.4	81.9	82.7	88.3	89.6	90.4	90.8	91.3	91.5	92.1	92.3	92.3	92.3
≥ 0.02	60.2	73.5	75.8	80.8	82.7	83.5	89.4	91.0	91.7	92.7	94.2	94.4	95.4	95.6	95.6	95.6
≥ 0.01	60.2	73.5	75.8	80.8	82.7	83.5	89.4	91.2	91.9	93.1	94.8	95.0	96.5	97.3	97.3	97.3
≥ 0.005	60.2	73.5	75.8	80.8	82.7	83.5	89.4	91.5	92.3	93.8	95.6	96.0	97.7	99.2	99.2	99.2
≥ 0.002	60.2	73.5	75.8	80.8	82.7	83.5	89.4	91.5	92.3	93.8	95.6	96.0	97.7	99.4	99.8	99.8
≥ 0.001	60.2	73.5	75.8	80.8	82.7	83.5	89.4	91.5	92.3	93.8	95.6	96.0	97.7	99.4	99.8	100.0

TOTAL NUMBER OF OBSERVATIONS 520

GLOBAL CLIMATOLOGY BRANCH
AFETAC
AFR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 710

COL A J BO BAKER AAF DL

73-78,81-82

DEC

PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

1500-2000

CEILING FEET	VISIBILITY - STATUTE MILES															
	≥10	≥6	≥5	≥4	≥3	≥2	≥2	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1	≥1
25000	10.0	14.0	14.0	17.0	17.0	17.0	18.0	18.0	18.0	18.0	18.5	18.5	18.5	19.5	20.5	21.5
22000	13.5	18.0	18.0	21.0	21.0	21.0	22.0	22.0	22.0	22.0	22.5	22.5	22.5	22.5	24.5	25.5
2000	13.5	18.0	18.0	21.0	21.0	21.0	22.0	22.0	22.0	22.0	22.5	22.5	22.5	22.5	24.5	25.5
2500	13.5	18.0	18.0	21.0	21.0	21.0	22.0	22.0	22.0	22.0	22.5	22.5	22.5	22.5	24.5	25.5
2400	13.5	18.0	18.0	21.0	21.0	21.0	22.0	22.0	22.0	22.0	22.5	22.5	22.5	22.5	24.5	25.5
2300	14.5	19.0	19.0	22.0	22.0	22.0	23.0	23.0	23.0	23.0	23.5	23.5	23.5	23.5	25.5	26.5
2200	15.0	19.5	19.5	22.5	22.5	22.5	23.5	23.5	23.5	23.5	24.0	24.0	24.0	24.0	26.0	27.0
2100	15.5	21.0	21.0	24.0	24.0	24.0	25.0	25.0	25.0	25.0	25.5	25.5	25.5	25.5	27.5	28.5
2000	21.0	26.0	26.0	31.0	31.0	31.0	32.0	32.0	32.0	32.0	32.5	32.5	32.5	32.5	34.5	35.5
1900	22.5	27.5	27.5	32.5	32.5	32.5	33.5	33.5	33.5	33.5	34.0	34.0	34.0	34.0	36.0	37.0
1800	22.5	27.5	27.5	32.5	32.5	32.5	33.5	33.5	33.5	33.5	34.0	34.0	34.0	34.0	36.0	37.0
1700	22.5	30.0	30.0	33.0	33.0	33.0	34.0	34.0	34.0	34.0	34.5	34.5	34.5	34.5	36.5	37.5
1600	27.0	30.0	30.0	33.0	33.0	33.0	34.0	34.0	34.0	34.0	34.5	34.5	34.5	34.5	36.5	37.5
1500	24.0	31.0	31.0	34.0	34.0	34.0	35.0	35.0	35.0	35.0	35.5	35.5	35.5	35.5	37.5	38.5
1400	30.0	37.5	37.5	40.5	40.5	40.5	41.5	41.5	41.5	41.5	42.0	42.0	42.0	42.0	44.0	45.0
1300	34.5	42.5	42.5	45.5	45.5	45.5	46.5	46.5	46.5	46.5	47.0	47.0	47.0	47.0	49.0	50.0
1200	38.0	46.0	46.0	51.0	51.0	51.0	52.0	52.0	52.0	52.0	52.5	52.5	52.5	52.5	54.5	55.5
1100	39.5	49.0	49.0	55.0	55.0	55.0	56.0	56.0	56.0	56.0	56.5	56.5	56.5	56.5	58.5	59.5
1000	39.5	49.5	50.0	56.0	56.0	56.0	57.0	57.0	57.0	57.0	57.5	57.5	57.5	57.5	59.5	60.5
900	39.5	50.0	50.5	56.5	59.0	59.0	61.0	61.0	61.0	61.0	61.5	61.5	61.5	61.5	63.5	64.5
800	40.5	52.0	52.5	61.0	61.5	61.5	64.5	65.5	66.0	66.5	66.5	66.5	66.5	66.5	68.5	69.5
700	41.5	55.0	55.5	64.0	66.0	67.0	70.5	73.0	73.5	74.0	74.0	74.0	74.0	74.0	76.0	77.0
600	41.5	55.0	55.5	65.5	67.5	68.5	73.5	78.0	78.5	81.0	81.0	81.0	81.0	81.0	83.0	84.0
500	41.5	55.0	55.5	65.5	67.5	68.5	73.5	78.5	79.0	81.5	81.5	81.5	81.5	81.5	83.5	84.5
400	41.5	55.0	56.5	66.5	68.5	70.0	75.0	80.5	81.0	83.5	83.5	83.5	83.5	83.5	86.0	87.0
300	41.5	55.0	56.5	67.5	69.5	71.0	77.5	83.0	83.5	86.5	86.5	86.5	86.5	86.5	88.0	89.0
200	41.5	55.0	56.5	67.5	69.5	71.0	77.5	83.0	83.5	86.5	86.5	86.5	86.5	86.5	88.0	89.0
100	41.5	55.0	56.5	67.5	69.5	71.0	77.5	83.0	84.0	87.0	87.0	87.0	87.0	87.0	89.0	90.0
0	41.5	55.0	56.5	67.5	69.5	71.0	77.5	83.0	84.0	87.0	87.0	87.0	87.0	87.0	89.0	90.0

TOTAL NUMBER OF OBSERVATIONS 200

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

CEILING VERSUS VISIBILITY

1 710 COL A J 80 BAKER AAF DL

73-79, ED-62

DEC

STATION

STATION NAME

YEAR

MONTH

PERCENTAGE FREQUENCY OF OCCURRENCE (FROM HOURLY OBSERVATIONS)

ALL

HOURS

CEILING FEET	VISIBILITY - STATUTE MILES															
	≥ 10	≥ 6	≥ 5	≥ 4	≥ 3	≥ 2.5	≥ 2	≥ 1.5	≥ 1	≥ .5	≥ .3	≥ .2	≥ .1	≥ .05	≥ .03	≥ .01
NO CEILING	20.3	24.1	24.3	24.9	25.1	25.2	25.7	25.7	25.7	25.9	26.0	26.0	26.0	26.0	26.0	26.6
≥ 20000	24.2	28.9	29.1	29.9	30.1	30.2	30.7	30.7	30.7	31.0	31.1	31.1	31.1	31.1	31.7	31.7
≥ 18000	24.7	29.4	29.6	30.4	30.6	30.7	31.2	31.2	31.2	31.5	31.5	31.5	31.5	31.6	32.1	32.2
≥ 16000	25.1	29.8	30.0	30.8	31.0	31.1	31.6	31.6	31.6	31.9	31.9	31.9	31.9	32.0	32.5	32.6
≥ 14000	25.1	29.8	30.0	30.8	31.0	31.1	31.6	31.6	31.6	31.9	31.9	31.9	31.9	32.0	32.5	32.6
≥ 12000	25.5	30.2	30.4	31.3	31.5	31.5	32.1	32.1	32.1	32.3	32.4	32.4	32.4	32.4	32.9	33.1
≥ 10000	26.6	31.6	31.9	32.8	32.9	33.0	33.6	33.6	33.6	33.9	33.9	33.9	33.9	33.9	34.4	34.5
≥ 9000	28.7	33.6	33.9	34.7	34.9	34.9	35.5	35.5	35.5	35.7	35.8	35.8	35.8	35.8	36.3	36.5
≥ 8000	31.4	37.1	37.3	38.3	38.4	38.5	39.1	39.1	39.1	39.3	39.4	39.4	39.4	39.4	39.9	40.0
≥ 7000	33.7	39.5	39.9	40.8	41.0	41.1	41.6	41.6	41.6	41.9	41.9	42.0	42.0	42.0	42.5	42.6
≥ 6000	34.7	40.1	40.5	41.4	41.6	41.7	42.3	42.3	42.3	42.6	42.6	42.7	42.7	42.7	43.2	43.3
≥ 5000	35.4	41.3	41.7	42.6	42.8	42.9	43.5	43.5	43.5	43.8	43.8	43.8	43.8	43.8	44.3	44.4
≥ 4500	37.1	42.9	43.3	44.2	44.4	44.5	45.1	45.1	45.1	45.4	45.4	45.5	45.5	45.5	46.0	46.1
≥ 4000	39.8	46.2	46.5	47.5	47.7	47.8	48.4	48.4	48.4	48.7	48.7	48.7	48.7	48.7	49.3	49.4
≥ 3500	43.5	50.4	50.8	51.9	52.1	52.2	52.8	52.8	52.8	53.1	53.2	53.2	53.2	53.2	53.7	53.8
≥ 3000	47.2	55.6	56.2	57.4	57.9	58.0	58.7	58.7	58.7	59.0	59.0	59.0	59.0	59.0	59.6	59.7
≥ 2500	49.9	59.1	59.9	62.1	62.7	62.9	63.7	63.7	63.7	64.0	64.1	64.1	64.1	64.1	64.7	64.8
≥ 2000	51.3	61.7	62.6	65.5	66.3	66.5	67.5	67.6	67.7	68.2	68.3	68.3	68.3	68.3	68.9	69.0
≥ 1800	52.2	62.9	63.4	66.9	67.8	68.1	69.1	69.3	69.4	70.0	70.1	70.1	70.1	70.1	70.6	70.8
≥ 1600	53.4	64.8	65.8	69.4	70.7	71.1	72.9	73.2	73.3	74.0	74.1	74.2	74.2	74.2	74.8	74.9
≥ 1400	54.1	66.5	67.5	71.5	73.2	73.6	76.2	76.6	77.0	77.7	77.9	78.1	78.1	78.1	78.7	78.8
≥ 1200	54.4	67.2	68.3	72.8	75.1	75.6	79.1	80.6	80.9	81.9	82.4	82.6	82.7	82.7	83.3	83.4
≥ 1000	54.5	67.4	68.5	73.3	75.7	76.4	79.8	81.3	81.7	82.8	83.4	83.5	83.6	83.6	84.2	84.3
≥ 900	54.5	67.5	68.6	74.0	76.7	77.7	81.6	83.6	84.1	85.9	86.6	86.8	86.9	86.9	87.6	87.7
≥ 800	54.5	67.7	68.9	74.3	77.0	78.0	81.9	84.2	84.7	86.9	87.6	87.8	87.8	87.8	88.1	88.8
≥ 700	54.5	67.7	68.9	74.4	77.2	78.3	82.8	85.1	85.9	88.4	89.3	89.5	89.5	89.5	90.5	90.6
≥ 600	54.5	67.7	69.1	74.9	77.8	79.0	84.2	86.6	87.4	90.7	92.0	92.5	93.1	93.9	94.0	94.1
≥ 500	54.5	67.7	69.1	74.9	77.8	79.0	84.2	86.6	87.4	91.0	92.5	93.1	94.2	95.4	95.6	95.7
≥ 400	54.5	67.7	69.1	74.9	77.8	79.2	84.4	86.9	87.9	91.5	93.1	93.7	95.3	97.2	97.6	97.7
≥ 300	54.5	67.7	69.1	74.9	77.8	79.2	84.4	86.9	88.0	91.7	93.3	94.0	96.0	98.3	99.3	99.4
≥ 200	54.5	67.7	69.1	74.9	77.8	79.2	84.4	86.9	88.0	91.7	93.3	94.0	96.0	98.3	99.3	99.9
≥ 100	54.5	67.7	69.1	74.9	77.8	79.2	84.4	86.9	88.0	91.7	93.3	94.0	96.0	98.3	99.3	100.0

TOTAL NUMBER OF OBSERVATIONS

2235

USAF ETAC 0-14-5 (OL A) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

U S AIR FORCE
ENVIRONMENTAL TECHNICAL
APPLICATIONS CENTER

PART E

PSYCHROMETRIC SUMMARIES

In this section are presented various summaries of dry- and wet-bulb temperatures, dew points, and relative humidity. The order and manner of presentations follows:

1. Cumulative percentage frequency of occurrence - derived from daily observations and presented by month and annual for all years combined. These tabulations provide the cumulative percentage frequency to tenths of temperature by 5-degree Fahrenheit increments, plus mean temperature, standard deviations, and total number of observations in three separate tables as follows:
 - a. Daily maximum temperatures
 - b. Daily minimum temperatures
 - c. Daily mean temperatures

NOTE: Beginning in January 1964, daily maximum and minimum temperatures are routinely selected from hourly observations recorded on surface observing forms or from automated data collections for all Air Force operated stations. For those stations observing less than 24 hours per day, and where maximum and minimum temperatures are required but not recorded, these are also selected from hourly data from as early as January 1949 and later. Please refer to notations on summary pages and Station History for further information on reporting practices of individual stations.

2. Extreme values - derived from daily observations with the extreme value selected for each year and month of record available. An annual (ALL MONTHS) value is selected when all months for a year have valid extremes. Means and standard deviations are computed for months and annual when four or more values are present for any column. Two tables of daily extremes are prepared:
 - a. Extreme maximum temperature
 - b. Extreme minimum temperature

NOTE: The following symbols are used in the extreme data blocks:

- (1) * indicates the extreme was selected from a month with one or more days missing.
- (2) # indicates the extreme was selected from a month in which hourly temperatures were available for less than 24 hours for at least one day in the month.

() Values for means and standard deviations do not include measurements for incomplete months.

Continued on Reverse

3. Bivariate percentage frequency distribution and computations of dry-bulb versus wet-bulb temperature. This tabulation is derived from hourly observations and is presented by month and annual, all hours and years combined. The following information is provided:

a. The main body of the summary consists of a bivariate percentage frequency distribution of wet-bulb depression in 17 classes spread horizontally; by 2-degree intervals of dry-bulb temperature spread vertically. Also provided for each of the dry-bulb intervals is the percentage of observations with dry-bulb and wet-bulb temperature combined; and again for dry-bulb, wet-bulb, and dew-point temperatures separately. Total observations for these four items is also provided in two lines at end of each tabulation table, which may be continued on several pages.

NOTE: A percentage frequency in this table of ".0" represents one or more occurrences amounting to less than .05 percent.

b. Statistical data for the individual elements of relative humidity, dry-bulb, wet-bulb, and dew-point temperatures are shown in the section at the bottom left of the forms. These consist of the sum of squares ($\sum X^2$), sums of values ($\sum X$), means ($\bar{X}$), and standard deviations (σ_x). The number of observations used in the computation for each element is also shown.

c. At the lower right of the form are given the mean number of hours of occurrence for six ranges of dry-bulb, wet-bulb, and dew-point temperatures, and total number of hours possible in the period represented. Mean number of hours is shown to tenths and indicates mean number of hours per year in the annual summary, or mean number of hours per month in the tabulation by month.

NOTE: Wet-bulb temperature usually was not reported prior to 1946. Relative humidity usually was not reported prior to 1949, nor subsequent to June 1958; and was computed by machine methods for observations recorded during these periods. All values of dew-point temperature and relative humidity are with respect to water, unless otherwise indicated.

4. Means and standard deviations - These tabulations are derived from hourly observations and present the mean, standard deviation, and total number of observations for the eight standard 3-hour groups, by month and annual and again at the bottom for all hours combined. Records for all years combined are presented in the following three tables; DRY-BULB TEMPERATURE, WET-BULB TEMPERATURE, and DEW-POINT TEMPERATURE.
5. Cumulative percentage frequency of occurrence of relative humidity - This summary is derived from hourly observations and presents the cumulative percentage frequency of occurrence of relative humidity by increments of 10% classes, plus the mean relative humidity and total number of observations in two tables.
- a. Table 1 is prepared by month and annual, all years combined, with month being the vertical argument.
- b. Table 2 is prepared by month by standard 3-hour groups, with the hour groups being the vertical argument and a separate page for each month. All years are also combined for this summary.

PSYCHROMETRIC SUMMARY

73-78, E-2-2?

۱۵۸

PAGE 1

7073-0300

HOURS (L, S, T,)

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																				TOTAL D.B./W.B.	TOTAL		
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	Dry Bulb	Wet Bulb	Dew Point				
7 / 4																		3	7					
7 / 47																		1	1					
47 / 47																		5	5	7				
47 / 43			1.4		.2	.2	.2											14	14	7				
7 / 41			1.0		.7	.7	.8											17	17	4				
7 / 37			1.4	1.2														15	15	9				
7 / 37			.2	4.5	.8													30	30	19				
7 / 35			1.0	5.1	.7													40	40	46				
37 / 35			3.5	4.5	.5													47	47	57				
7 / 31			2.1	3.3	.2													32	32	49				
7 / 27			2.4	6.3	.3													43	43	51				
7 / 27			7.4	3.1														65	65	64				
7 / 25			6.1	1.5														44	44	47				
7 / 23			3.1	3.4														30	30	41				
23 / 21			5.5	1.7														42	42	44				
7 / 17			1.7	.3														12	12	24				
7 / 17			1.7															10	10	12				
7 / 1			1.0	.3														8	8	7				
7 / 13			1.2	.3														9	10	10				
7 / 11			2.7	.3														19	20	18				
7 / 7			5.9	.3														31	31	30				
7 / 7			1.7															10	10	10				
7 / 5			.2															1	1	1				
7 / 3			.2															1	1	1				
7 / 1			.7															4	4	4				
7 / -1			.1															10	10	10				
7 / -3			.7															1	1	1				
-3 / -15			.3															2	2	2				
TOTAL	52.73	9.6	5.1	1.2	.9	.2	.3											503	503	503				

Element (X)	Σx^2	Σx	$\bar{x}$	σ_x	No. Obs.	Mean No. of Hours with Temperature						
Rel. Hum.	4875534	52770	97.9	10.470	583	≤ 0 F	≤ 32 F	≥ 67 F	≥ 73 F	≥ 80 F	≥ 93 F	Total
Dry Bulb	455647	15280	26.1	10.719	583	3.3	55.7					93
Wet Bulb	430944	14744	25.3	9.989	583	3.3	69.6					93
Dew Point	377248	13758	23.6	9.505	583	3.3	80.4					93

2

YEARS

73-74, 82-82

182

STATION

STATION NAME

YEARS

MONTH

PAGE 1

0900-1100
HOURS (L. S. T.)

[illegible]

PSYCHROMETRIC SUMMARY

11.

STATION

STATION NAME

YEARS

MONTH

PAGE 1

1270-1450

HOURS (L, S, T)

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																				TOTAL D.B./W.B.	TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	Dry Bulb	Wet Bulb	Dew Point			
57/55																		1	1				
47/5																		3	3				
77/51																		10	10				
7/4																		4	4	1			
7/47																		12	12				
6/40																		25	25	6			
47/40																		29	29				
7/41																		33	33	2			
77/37																		40	40	23			
7/37																		34	34	18			
7/35																		34	34	31			
7/33																		45	45	52			
77/31																		36	36	52			
7/31																		50	50	75			
77/27																		44	44	78			
7/27																		31	31	43			
77/25																		21	22	35			
7/25																		7	7	24			
77/21																		8	8	15			
7/21																		5	5	5			
77/17																		7	7	10			
7/17																				2			
77/15																				5			
7/15																				1			
77/11																				5			
7/11																				1			
TOT	25.537	521.1	9.8	3.6	1.2	.8	.4											512	502	502			

Element (X)	Σx'	Σx	X̄	s _x	No. Obs.	Mean No. of Hours with Temperature					Total	
						≤ 0 F	≤ 32 F	≥ 67 F	≥ 73 F	≥ 80 F	≥ 93 F	
Rel. Hum.	3431.6	40750	81.3	15.260	502							
Dry Bulb	233154	17578	34.5	8.218	504		39.5					53
Wet Bulb	5411.8	16156	32.2	6.511	507		46.7					93
Dew Point	432254	14444	28.8	5.773	502		59.5					93

2

44

STATION

STATION NAME

YEAR

1000000

PAGE 1

1550-2000

HOURS 11. 5. 7.

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																															TOTAL D.B./W.B.	TOTAL			
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	Dry Bulb	Wet Bulb	Dew Point																
1 / 47			.4																1	1																
4 / 45																			2	2																
4 / 43		1.2		.4															4	4																
1 / 41		2.0	4.7	.4	.6														23	23	5	1														
4 / 39		.4	2.7	4.7	.8														11	11	8	6														
1 / 37		5.9	2.7	.4															21	21	14	5														
7 / 35	1.2	5.5	2.3																27	23	32	16														
2 / 33	4.7	.5	.9																23	23	33	25														
7 / 31	3.1	7.7	.5																28	27	37	35														
1 / 29	2.7	5.5	.5																23	23	28	31														
7 / 27	8.7	1.2																	24	24	25	39														
1 / 25	6.5	2.7																	24	24	23	32														
7 / 23	3.1	7.0																	13	13	15	14														
2 / 21	2.0	.4																	6	6	6	17														
7 / 19	1.2																		7	7	4	6														
1 / 17	2.3																		6	6	6	7														
1 / 15	1.5																		4	4	4	6														
1 / 13	1.2																		3	3	3	2														
1 / 11	1.5																		4	4	4	6														
1 / 9	.4																		1	1	1	1														
1 / 7	.4																		1	1	1	1														
1 / 5	.4																		1	1	1	1														
Total	41.2	39.5	16.2	2.0	1.5														256	256	256	256														

Element (X)	Σx^1	Σx	$\bar{x}$	s_x	No. Obs.	Mean No. of Hours with Temperature						
						≤ 0 F	≤ 32 F	≥ 67 F	≥ 73 F	≥ 80 F	≥ 93 F	Total
Rel. Hum.	14.63	22.31	68.	11.163	256							
Dry Bulb	261.21	7947	31.	7.761	256		51.2					93
Wet Bulb	237.474	7619	29.8	6.796	256		57.8					97
Dew Point	206.139	7079	27.7	6.383	256		73.4					93

PSYCHROMETRIC SUMMARY

73-75, 80-82

YEARS

PAGE 7

Temp (F)	WET BULB TEMPERATURE DEPRESSION (F)																				TOTAL D.B./W.B.	TOTAL		
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	Dry Bulb	Wet Bulb	Dew Point				
5 / 55																		1	1					
4 / 53			.3	.3	.3	.3	.3	.3										6	6					
3 / 51			.6	.6	.6	.6	.6	.6										13	13					
2 / 49			.9	.9	.9	.9	.9	.9										15	15					
1 / 47			1.2	1.2	1.2	1.2	1.2	1.2										27	27	3				
0 / 45		.1	.7	.5	.4	.1	.											43	43	1				
47 / 43		1.3	1.4	1.1	.7	.1												57	57	2				
37 / 41	.1	1.7	3.3	1.2	.7													154	164	71				
27 / 39	.1	3.2	3.0	.3														153	153	112				
17 / 37	.3	4.2	2.5	.3														169	169	147				
7 / 35	.7	4.8	1.5	.3														171	171	293				
3 / 33	3.6	4.5	.6	.5														197	197	290				
7 / 31	2.1	4.6	.4															156	166	234				
7 / 29	2.3	6.2	.4															224	224	244				
7 / 27	3.3	2.5	.2															222	223	251				
7 / 25	4.7	2.3	.1															159	159	141				
7 / 23	3.7	2.5																144	144	191				
27 / 21	2.1	.8																44	15	50				
7 / 19	1.4	.3																41	42	41				
7 / 17	1.4	.1																34	35	41				
7 / 15	1.7	.2																44	44	44				
7 / 13	1.1	.2																28	29	32				
7 / 11	1.5	.1																41	44	41				
7 / 9	1.5	.1																44	44	44				
7 / 7	.7																	16	16	16				
7 / 5	.1																	5	5	5				
7 / 3	.1																	2	2	2				
7 / 1	.2																	5	6	6				
7 / -1	.5																	25	25	25				
7 / -3	.																	1	1	1				
-17 / -15	.1																	2	2	2				
TOTAL	3.8	56.0	15.7	4.6	1.3	.6	.4	.1										2339	2347	2339				

Element (X)	Σx²	Σx	X̄	s²	No. Obs.	Mean No. of Hours with Temperature						Total
Rel. Hum.	17621391	201775	85.2	13.326	2339	≤ 0 F	≤ 32 F	≥ 67 F	≥ 73 F	≥ 80 F	≥ 93 F	
Dry Bulb	24274711	71981	31.7	9.680	2347	7.7	409.2					744
Wet Bulb	2157163	68223	29.2	8.458	2339	7.7	452.6					744
Dew Point	1805798	62410	26.7	7.753	2339	7.3	595.5					744

CELESTIAL CLIMATOLOGY BRANCH
OF METAC
A. W. FATHEN SERVICE/HAC

PSYCHROMETRIC SUMMARY

1 717 COL A J C BAKER AAF PL
STATION STATION NAME

44-77,60-52

YEARS

15.
MONTH

Page 1

2021-09-01
HOURS 11.5. T.

PSYCHROMETRIC SUMMARY

73-75,90-100

55 -

YEARS

MONTH

2451

927-11

HOURS 11 5 7

[illegible]

U.S. NATIONAL CLIMATOLOGY BRANCH
WASHDC
A WEATHER SERVICE/NAO

PSYCHROMETRIC SUMMARY

1 717	COL A J BO PAKE- AAF DL
STATION	STATION NAME

73-72, 80-42

134

STATION

STATION NAME

YEARS

PAGE 1

MONTH

1570-1700

HOURS 11 5 7

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																					TOTAL		TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point				
7 50																		2	3						
7 57																		1	1						
5 7 55																		1	1						
4 7 53							1.7	.7	.5									12	12						
7 7 51					.2	.7	.7	.2										8	4						
7 7 4					.2		.2											4	4		2				
7 7 47					.7		1.2											14	14						
4 7 46		.2		.5	2.7	.2	1.7	.5										29	29		3				
4 7 43				2.7	4.2	.7	.7											22	22		16				
7 7 41		1.2		2.2	.7		.2											18	18		15				
7 7 3		.2	1.7	4.9	1.2	.7												31	31		42				
7 7 37	1.7	3.4	3.4	1.	.2													40	40		46				
7 7 35	.5	3.2	2.7	.5														28	24		43				
3 7 33	4.4	3.7	.7															36	36		42				
7 7 31	2.7	4.4	.2	.7														29	29		42				
7 7 28	1.2	6.2	.7	.2														34	34		46				
7 7 27	5.4	5.7	.2															46	45		44				
7 7 25	3.	.7	.2															16	16		27				
7 7 23	2.7	1.5																14	14		12				
7 7 21	1.2	.2																6	6		11				
7 7 19	1.2																	4	4		5				
7 7 17																									
7 7 15																									
7 7 13																									
7 7 11																									
TOTAL	22.7	31.5	19.	11.6	6.9	5.9	1.7	.7										456		456					

Element (X)	Σ X ¹	Σ X	Σ	Σ _s	No. Obs.	Mean No. of Hours with Temperature						Total
Rel. Hum.	2011222	31.46	76.5	18.4	406	≤ 0 F	≤ 32 F	≤ 67 F	≤ 73 F	≤ 80 F	≤ 93 F	
Dry Bulb	559445	14691	36.2	8.2	406		30.2					64
Wet Bulb	457855	13423	33.1	5.8	406		38.3					64
Dew Point	342667	11597	28.6	5.3	406		66.2					84

U.S. NAVAL CLIMATOLOGY BRANCH
METEC
WEATHER SERVICE/NAO

PSYCHROMETRIC SUMMARY

1 710	COL A J C BAKER AAF DL
STATION	STATION NAME

73-72, 20-52

YEARS

553
MONTH

PAGE 9

18-0-2000
HOURS (L.S.T.)

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																														TOTAL	TOTAL		
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	a 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point													
/ 51						.4	.4											2	2															
/ 4						.4												1	1															
/ 41						.4												1	1															
/ 41					.4	.4												2	2															
/ 41					.4	.4												3	3															
/ 41			.4	.4	.4	.4												14	14	3														
/ 3			1.6	4.7	.8													16	16	7														
/ 37	1.6	6.3	2.6															24	25	18	6													
/ 35	.4	5.5	6.7		.4													33	33	32	13													
/ 33	7.1	4.7	1.2															25	25	35	19													
/ 31	1.2	7.1	.8															23	23	36	29													
/ 29	2.4	5.5	2.6															25	25	32	22													
/ 27	7.5	1.2	.4															23	23	36	65													
/ 25	1.6	2.4	.4															21	22	19	26													
/ 23	2.6	1.6	.4															16	15	19	16													
/ 21	2.7	2.4																13	13	5	17													
/ 19	3.5																	9	7	10	11													
/ 17	.4	.4																2	2	1	11													
/ 15																				1														
/ 13																																		
/ 11																					1													
/																					1													
TOTAL	32	39	22	4	2.4	1.2	1.2	.8										255	256	255	255													

SURFAL CLIMATOLOGY BRANCH
 LAFAYETTE
 AIR WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

1710	COL A J O BAKE AAF DL
STATION	STATION NAME

17-78, 80-82

YEARS

FEB
MONTH

FILE :

ALL
HOURS (L. S. T.)

Temp (F)	WET BULB TEMPERATURE DEPRESSION (F)																											TOTAL		TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point										
50						.1		.1										4	4												
57					.		.	.										3	7												
55				.	.		.1											4	4												
52				.	.	.5	.2	.1										19	19												
51				.	.	.3	.2											19	19												
47			.	.	.	.3	.1											25	24	4											
47			.	.	.	.5	.1											44	44	1											
46		.1	.5	1.4	1.	.6	.1											57	67	7											
45		.1	1.5	1.5	.4	.2												90	90	42	2										
41	.1	1.	2.4	.	.1	.1												99	98	67	12										
37	.	1.6	3.2	.7	.7													140	147	133	23										
37	1.2	3.5	1.8	.9	.1													166	166	172	65										
37	1.2	4.9	2.8	.3														214	214	271	132										
33	4.7	3.8	1.2															229	229	350	223										
31	2.	3.7	.6	.														153	153	251	264										
27	3.5	1.2	1.3	.1														220	220	242	277										
27	6.9	3.5	.9	.														256	256	265	365										
25	4.6	1.8	.2	.														157	158	175	238										
25	3.7	2.0	.2															141	141	143	257										
21	2.	.9																91	91	104	144										
18	2.2	.4																62	63	74	105										
17	1.3	.3																37	37	43	71										
15	1.3	.																32	32	35	63										
13	.4	.																11	11	12	39										
11	.	.2																23	23	23	25										
9	.6	.3																16	16	16	69										
7	.1																	5	3	3	12										
5																					1										
3																					1										
TOTAL	37.6	33.2	15.9	6.0	3.6	2.5	.	.2										2343		2343											
																		2343		2343											

Element (X)	Σx²	Σx	X̄	s²	No. Obs.	Main No. of Hours with Temperature						
Rel. Hum.	168	2547	1553.5	83.4	6340	≤ 0 F	≤ 32 F	≤ 64 F	≤ 72 F	≤ 80 F	≤ 93 F	Total
Dry Bulb	260	1570	75434	32.2								

USAFETAC
FORM
0-26-5 (OL A)
REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

USAFETAC

2

GENERAL CLIMATOLOGY BRANCH
AFETAC
AIR WEATHER SERVICE/AFAC

PSYCHROMETRIC SUM

STATION 1710 COL A J. N. BAKER AAF FL
STATION NAME

73-78, 80-82

YEARS

MAR

MONTH

PAGE 1 7600-0900

HOURS (L. S. T.)

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																					TOTAL D.B./W.B.	TOTAL		
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	Dry Bulb	Wet Bulb	Dew Point					
7 57																		1	1						
7 55																		1	3						
7 53																		2	2						
7 51																		2	2						
7 49																		4	4						
7 47																		6	6						
7 45			1.1	.5	.5	.3												10	20	11	6				
7 43		.5	.3	1.3	.7													15	19	19	9				
7 41		1.1	1.9	2.4														34	34	20	13				
7 39		1.5	3.3	1.9														43	43	37	22				
7 37		1.7	4.6	1.4	.3													71	51	44	31				
7 35		2.1	5.4	1.7														58	58	55	43				
7 33		4.6	4.6	1.3														61	66	60	70				
7 31		4.1	4.7	.3														59	59	78	73				
7 29		3.8	6.5	.3														61	61	72	62				
7 27		3.4	3.6	.3														79	79	83	38				
7 25		3.9	1.7	.2														37	37	43	69				
7 23		1.3	2.2	.2														23	23	19	42				
7 21		1.1	1.5															17	17	14	23				
7 19		1.5	.6															9	9	16	17				
7 17		1.1	.2															6	8	11	12				
7 15		.7	.2															7	8	7	11				
7 13		.2	.2															2	2	3	5				
7 11		.5	.5															7	7	7	5				
7 9		.2	.2															2	2	2	3				
7 7		.2																1	1	1	4				
7 5																					1				
7 3																					1				
7 1																					1				
TOTAL	25.6	43.8	12.3	7.1	.6	.9	.5	.2										634	634	634	634				
																					634	634	634		
Element (X)	Z ₁	Z ₂	X	%	No. Obs.	Mean No. of Hours with Temperature						Total													
Rel. Hum.	75.75	55.68	83.1	12.21	634	≤ 0 F	≤ 32 F	≥ 67 F	≥ 73 F	≥ 80 F	≥ 93 F	Total													
Dry Bulb	75.75	55.68	83.1	12.21	634		45.8					63													
Wet Bulb	67.0390	70.770	31.7	7.441	634		51.8					93													
Dew Point	59.608	18.732	29.5	7.662	634		62.5					93													

USAFET, C FORM 0-26-5 (OL A) REVISED EDITIONS OF THIS FORM ARE OBSOLETE

2

PSYCHROMETRIC SUMMARY

1	712	COL A J LO PAKER AAF DL
	STATION	STATION NAME

13-73, 20-62

YEARS

4 A 4
MONTH

PAGE 1 2900-1140
HOURS (L.S.T.)

[illegible]

2

PSYCHROMETRIC SUMMARY

502

YEARS

PAGE 1

MONTH

1200-1400

HOURS (L. S. T.)

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																															TOTAL D.B./W.B.	TOTAL		
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	Dry Bulb	Wet Bulb	Dew Point															
47/72																		1	1																
47/71																		3	3																
47/69																		2	2																
47/67																		4	2																
57/65																		5	5	1															
47/63																		11	11	1	1														
47/61			.3	.7					1.0	1.7	.3							25	25		1														
47/59			.7	.7				.7	.7	1.5	1.0							24	24	3															
47/57		.7	.2	.7	.2	.7	.7	.5	.5									17	17	7	3														
57/55		.5	.3	.2		1.0	.3	.5	.3									17	17	4	5														
47/53		.5	.3	.2	.2	1.0	1.2		.7									31	31	11	3														
47/51		.7			.7	2.5	1.4	.8										36	36	24	4														
47/49		.7		.7	.5	1.2	2.0											25	25	11	4														
47/47		.7	.3	.5	1.7	.7	1.4											29	29	32	7														
47/45		.7	1.2	1.7	2.5	4.4												63	63	72	11														
47/43		.3	.3	1.7	2.0	1.0	.2	.2										34	34	43	11														
47/41		.5	3.6	1.5	1.7	.7												43	43	52	29														
47/39		.3	1.9	2.0	.5	.2												40	32	59	32														
47/37		.5	2.2	2.9	.5	.3												40	43	56	53														
47/35		2.4	2.4	2.0		.2												41	41	56	83														
47/33		2.2	3.0	1.0														37	37	53	67														
47/31		.7	4.1	.5	.3													23	33	40	43														
47/29		1.4	2.9	.7														25	39	45	79														
47/27		.5	1.0	.2														10	10	18	72														
47/25																				4	34														
47/23		1.0	.2															7	7	7	31														
47/21		.2																1	1	1	6														
47/19																					2														
47/17																					1														
47/15																					1														
47/13																					1														
TOTAL	12.4	25.0	16.9	11.2	14.2	7.8	5.6	4.2	2.2	.3	.2							591	591	591	591														

Element (X)

2

YEARS

MA 2
MONT

PAGE 1 1500-1700
HOURS (L. S. T.)

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																														TOTAL	TOTAL		
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	>31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point													
4 / 73										.4								2	2															
4 / 71										.4								1	1															
4 / 69				.2						.4								3	3															
4 / 67																		1	1															
6 / 65		.2	.2	.2					.4	.2								6	6	2														
4 / 63			.4					.2	.7	.9								10	12	1	2													
4 / 61			.4	.4				.2	2.2									23	23	1	1													
4 / 59		.4					1.6	2.2	.2									20	20	2														
4 / 57		.2		.2	.2	.7			.7	.2								9	9	4	3													
5 / 55		.4	.2	.2	.4	1.3	.2	.2										14	14	5	5													
4 / 53		.2	.2	.2	1.3	1.1												16	17	6														
2 / 51		.2		1.3	1.2	.7	.4											20	22	13	5													
4 / 49		.7	1.1	.7	1.6	1.1	.7											26	26	18	2													
4 / 47			.7	1.6	1.6	.9	.2											22	22	16	4													
4 / 45		.4	.4	2.2	1.9	.4												24	24	27	4													
4 / 43		1.6	1.6	1.8	1.8		.2											31	31	27	1													
4 / 41		2.7	2.4	2.	.2	.2												37	37	31	22													
80 / 39		.2	1.6	2.4														19	19	43	42													
3 / 37	1.3	3.8	3.1	.2														38	36	46	51													
4 / 35	1.6	2.2	1.3	1.3														29	29	49	44													
3 / 33	2.	3.8	1.8	.4														36	36	38	44													
2 / 31	.4	5.3	.4															28	28	39	34													
4 / 29	.4	3.3	.4															19	19	34	54													
4 / 27	2.2	.7	.2															13	13	21	64													
4 / 25	.2	.2																2	2	5	28													
4 / 23	.7																	3	2	3	22													
2 / 21																					5													
4 / 19																					6													
1 / 17																					3													
1 / 15																					1													
4 / 7																					1													
TOTAL	1.9	27.9	17.5	13.1	11.0	6.0	6.2	4.2	1.1	1.3								451	452		451													

Element (X)	Z _X ¹	Z _X	X	%	No. Obs.	Mean No. of Hours with Temperature						Total
Rel. Hum.	2303708	36970	68.719	233	451	± 0 F	± 32 F	± 67 F	± 73 F	± 80 F	± 93 F	
Dry Bulb	434227	19963	44.210	794	452		13.4	1.4	.4			93
Wet Bulb	717399	17637	39.1	7.843	451		21.0					93
Dew Point	521071	14965	33.2	7.379	451		45.6					93

0.26.5 (31 A) REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

USAFETAC

GLOBAL CLIMATOLOGY BRANCH
JLSTAC
AIR MAILER SERVICE/MAC

PSYCHROMETRIC SUMMARY

1 71	COL A J L O BAKER AAF EL
STATION	STATION NAME

73-78, 50-27

445

YEARS

MONTH

PAGE 1 100-2720

HOURS (L, S, T.)

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																												TOTAL		TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point											
60																		1	1													
67									.4									1	1													
57				.4														1	1													
61			.4															1	1	1												
56						.7	.7											4	4													
57		.4			.4	2.1												5	5	1												
55		.4	.4		.7	1.1												14	14	1												
53			.7	1.1		.4												6	6	3	1											
51		.7		.7	1.1		.4											5	5	4	1											
49		.4	1.4	.7	.7	.7												11	11	4												
47			1.4			.4												5	5	2	5											
45	.4	2.1	1.4	1.4	2.1	.4												23	23	15	5											
42		.4	1.4	1.4	1.4													14	14	14	1											
41	.4	3.9	4.3	1.4														29	29	15	22											
39		1.4	5.3	.4														21	21	23	27											
37	2.1	3.5	1.1	.7														21	21	70	23											
35	1.4	4.3	1.4															21	21	42	26											
33	2.1	3.5	.7															15	15	1	28											
31		2.9	1.4															29	29	29	23											
29	1.1	5.7	1.4															27	27	73	34											
27		1.4	1.4	.4														9	9	13	42											
25	1.1	1.4																7	7	7	21											
23	1.1	1.4																7	7	9	17											
21																					6											
19																					5											
17																					4											
15																					3											
TOTAL	11.4	123.4	8.9	8.9	5.7	1.1			.7									282	282	282	757											

Element (X)	Σx ²	Σx	X̄	s _x	No. Obs.	Mean No. of Hours with Temperature						
Rel. Hum.	1726843	21611	76.6	15.861	282	≤ 0 F	2 F	≥ 67 F	≥ 73 F	≥ 80 F	≥ 93 F	Total
Dry Bulb	475065	11275	40.3	9.296	282		24.7	.7				93
Wet Bulb	343988	10340	36.7	7.271	282		30.5					93
Dew Point	311563	9181	32.6	6.712	282		49.5					93

USAFETAC
FORM
HH 04
0-26-5 (OL A)
REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

USAFETAC

GLOBAL CLIMATOLOGY BRANCH
METAC
AIR WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

14710	COL A J JO PAKER AAF DL
STATION	STATION NAME

73-70, 86-87

YEARS

542

MONTH

PAGE 1

43.

HOURS (L, S, T)

[illegible]

CLIMAT CLIMATOLOGY BRANCH
SAFETAC
AIR WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

171.	CPL A J JOHNSON	AAF DL
STATION	STATION NAME	

73-70, 80-02

YEARS

4 A L
MONTH

PAGE 2

ALL
HOURS (L. S. T.)

[illegible]

2

3

197

STATION

STATION NAME

YEARS

MONTH

PAGE 1

7623-0800

HOURS (L. S. T.)

0-26-5 (01 A) REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

USAFETAC


AD-A134 209

COL A J BO BAKER AAF GERMANY (WEST) LIMITED SURFACE
OBSERVATIONS CLIMATIC..(U) AIR FORCE ENVIRONMENTAL
TECHNICAL APPLICATIONS CENTER SCOTT A.. 03 AUG 83
UNCLASSIFIED USAFETAC/DS-83/034 SBI-AD-E850 427 F/G 4/2

3/9

NI

END
DATE
FORM
1287
6-2



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

GLOBAL CLIMATOLOGY BRANCH
 MS/FETAC
 AT WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

1	710	COL A J SO PAKE	AAF DL
	STATION	STATION NAME	

13-78, 60-62

YEARS

APP

MONTH

PAGE 1

2912-1110
HOURS (L, S, T)

[illegible]

2

3

435

STATION

STATION NAME

YEARS

MONTH

PAGE 1

MONTH

1270-1450

HOURS (L, S, T,)

0-26.5 (OL A)

USAFETAC

GLOBAL CLIMATOLOGY BRANCH
SACDETAC
AIR WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

1	715	COL A J SO BAKER AAF DL
STATION		STATION NAME

73-77, 80-82

YEARS

ADL
MONITOR

PAGE 1 150-1700
MAY 11 1964

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																														TOTAL	TOTAL
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	= 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point											
/ 71										.1								1	1													
/ 69				.2	.2					.5								4	4													
/ 67				.2					.5	.2								5	5													
/ 65								1.1	.2	.2								11	11	3												
/ 63				.7				3.4	.2	.2								22	22													
/ 61					.2			.7	.5	1.1	.2							12	12													
/ 59			.2		.5	.5	3.7	1.8	.5									20	20	3												
/ 57		.2	.2		.7	2.5	1.6	.5										25	25													
/ 55					1.4	1.6	2.5	.2										28	28	4	1											
/ 53			.5	.5	1.1	2.5	.2	.5										22	22	11												
/ 51				.5	1.4	.7	.7											20	20	26												
/ 49		1.1	.2	.2	.2	.2	.7											12	12	16												
/ 47		1.4	.7	1.8	.7	.9												24	24	57	4											
/ 45	.5	.7	2.5	2.5	1.1	.2												36	36	36												
/ 43	.5	.5	.5	.5	1.4													16	16	45	15											
/ 41		2.1	3.	1.1	1.4													23	23	36	24											
/ 39		3.4	1.4	2.5														32	32	72	26											
/ 37	.2	2.3	1.4	.7	.2													21	21	41	61											
/ 35	1.5	3.4	1.4	.2														28	28	73	51											
/ 33	3.2	5.3																37	37	84	46											
/ 31	2.1	1.4																15	15	88	34											
/ 29																				6	26											
/ 27																					43											
/ 25																					2											
/ 23																					23											
/ 21																					1											
/ 19																					3											
TOTAL	1.7	2.1	8.1	4.4	15.5	10.5	9.9	14.4	5.7	2.5	1.6							476	436	436	436											

Element (X)	Z _X ¹	Z _X	F	F _z	No. Obs.	Mean No. of Hours with Temperature						
Rel. Hum.	1789219	27.77	63.42	1.805	436	≤ 0 F	≤ 32 F	≤ 67 F	≤ 73 F	≤ 80 F	≤ 93 F	Total
Dry Bulb	1230767	28789	47.71	0.452	436		3.1	2.1				9.3
Wet Bulb	768797	19053	41.4	6.797	36		9.1					9.1
Dew Point	534514	14976	34.4	6.776	436		38.2					9.3

4. LEATHER SERVICE/MAN

PSYCHROMETRIC SUMMARY

SIGNATURE

12-2-2000

HOURS 11.5 - 2.0

[illegible]

Element (X)	$\Sigma x'$	Σx	$\bar{x}$	s_x	No. Obs.	Mean No. of Hours with Temperature						Total
						$\leq 0^\circ\text{F}$	$\leq 32^\circ\text{F}$	$\leq 67^\circ\text{F}$	$\leq 73^\circ\text{F}$	$\leq 80^\circ\text{F}$	$\leq 93^\circ\text{F}$	
Rel. Hum.	14161.4	18528	71.0	19.732	261							
Dry Bulb	53636.9	11585	44.4	9.229	261		8.3					8.3
Wet Bulb	42311.6	10774	39.7	6.430	261		15.4					15.4
Dew Point	31795.1	8073	34.4	6.034	261		39.0					39.0

USAFETAC FORM 0-26-5 (OL A) REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

USAFETAC

2

AP-

MONTM

NOV 11 1951

0-26-5 (OL A) REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

USAFETAC

PSYCHROMETRIC SUMMARY

1	710	COL A J JO BAKER AAF DL
	STATION	STATION NAME

73-79, 80-82

YEARS

DAY
MONTH

PAGE 1

0600-0800
HOURS (L. S. T.)

[illegible]

PSYCHROMETRIC SUMMARY

1 - 717	COL A J JO BAKER AAF DL
STATION	STATION NAME

73-76, 80-c2

484

YEARS

MONTH

PAGE 1

7900-1140

HOURS (L, S, T,)

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																												TOTAL		TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point											
77																		1	1													
76									.3									2	2													
75										.2								5	5													
74											.2							9	9													
73												.2						18	18													
72													.2					20	20													
71														.2				26	26													
70															.2			56	56													
69																.2		55	55													
68																	.2	51	51													
67																		50	50													
66																		45	45													
65																		44	44													
64																		36	36													
63																		48	48													
62																		49	49													
61																		61	61													
60																		24	24													
59																		18	18													
58																		10	10													
57																		6	6													
56																		7	7													
55																		1	1													
54																																
53																																
52																																
51																																
50																																
49																																
48																																
47																																
46																																
45																																
44																																
43																																
42																																
41																																
40																																
39																																

PSYCHROMETRIC SUMMARY

1-716	COL A J SO BAKER AAF DL
STATION	STATION NAME

73-79,90-82

YEARS

4 A Y
MONTH

1220-1400
HOURS (L. S. T.)

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																															TOTAL		TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point														
7 / 7																		2	7																
7 / 77																		7	7																
47 / 75				.2	.2					.2	.2							7	7																
47 / 73			.3	.2				.7	1.1	1.2	.2	.7						26	28																
47 / 71			.3				.2	.7	1.1	.5		.2						17	17																
47 / 69					.2	1.0	1.2	2.3	.2	.3								15	35	4															
47 / 67			.2	.2	.2	1.1	.2	1.5	.7									24	24	3	3														
47 / 65			.3			.7	1.3	2.3	1.5	.2								21	31																
47 / 63		.2	1.7	2.5	1.4	2.6	1.6	2.1	.3									25	25	2															
47 / 61		.3	1.1	.7	.8	2.3	1.3	.7	.2									46	46	14	3														
47 / 59		.3	.7	1.2	3.1	2.9	1.7	.2										55	59	27	2														
47 / 57		.3	.2	1.6	1.3	1.5	.7											34	34	62	5														
47 / 55		.5	.8	1.3	2.7	1.5	.2											38	39	57	14														
47 / 53		.3	1.1	2.3	.5	1.1	.2											34	34	62	22														
47 / 51		.7	1.5	2.3	1.3	.2												33	33	74	27														
47 / 49		1.7	1.5	1.2	.7													25	25	65	30														
47 / 47	.3	1.6	1.6	.7	.3													26	29	58	57														
47 / 45	1.1	3.6	.8	.2	.2													36	36	76	97														
47 / 43	.3	2.1	.3															17	17	46	80														
47 / 41	.5	2.5	.3															20	20	27	84														
47 / 39	.2	.7																5	5	14	57														
47 / 37	1.1	.3																9	9	12	51														
47 / 35	.5																	2	2	4	3														
37 / 33																					21														
37 / 31																					3														
37 / 29																					2														
37 / 27																					2														
TOTAL	3.6	14.7	11.6	14.2	12.2	15.9	10.1	10.6	3.3	1.6	2.0								611	611	611														

Element (X)	Σx²	Σx	X̄	s²	No. Obs.	Mean No. of Hours with Temperature						Total
Rel. Hum.	2595879	38085	62.3	19.75	611	≥ 0 F	≥ 32 F	≥ 67 F	≥ 73 F	≥ 80 F	≥ 93 F	
Dry Bulb	2128137	35593	58.3	9.471	611			18.3	6.7	.2		53
Wet Bulb	1592438	30958	57.7	6.255	611			1.1				63
Dew Point	1213157	26937	44.1	6.477	611		1.2	.5				9

FATHER SERVICE / RAC

PSYCHROMETRIC SUMMARY

1 710 COL A J LO BAKER AAF DL

73-77, 80-82

RAY

STATION

STATION NAME

YEARS

PAGE 1

MONT H

1529-1703

HOURS (L. S. T.)

2

 YEARS MAY
MONTH

YEARS

May
MONTH

1800-2000
HOURS (L. S. T.)

USAFETAC

GLOBAL CLIMATOLOGY BRANCH
JAFETAC
AIR WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

STATION	STATION NAME
710	COL A J LO BAKER AAF DL

73-75, cc-32

YEARS

10 MAY 1964

5 A C 1 }

ALL

HOURS (L, S, Y,)

[illegible]

0.26-5 (OL A)

USAFETAC

GLOBAL CLIMATOLOGY BRANCH
METAC
WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

STATION	STATION NAME
1717	COL A J NO BAKE AAF PL

73-75, 80-82

YEARS

444

545

2014-2000

HOURS: L, S, T, *

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																														TOTAL		TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point													
7 / 75																																		
7 / 73																																		
7 / 71																																		
7 / 69																																		
7 / 67																																		
7 / 65																																		
7 / 63																																		
7 / 61																																		
7 / 59																																		
7 / 57																																		
7 / 55																																		
7 / 53																																		
7 / 51																																		
7 / 49																																		
7 / 47																																		
7 / 45																																		
7 / 43																																		
7 / 41																																		
7 / 39																																		
7 / 37																																		
7 / 35																																		
7 / 33																																		
7 / 31																																		
7 / 29																																		
7 / 27																																		
7 / 25																																		
7 / 23																																		
7 / 21																																		
7 / 19																																		
7 / 17																																		
7 / 15																																		
7 / 13																																		
7 / 11																																		
7 / 9																																		
7 / 7																																		
7 / 5																																		
7 / 3																																		
7 / 1																																		
Tot																																		

REVISED PREVIOUS EDITIONS OF THIS WORK ARE OBSOLETE

0-26-5 (OL A)

USAFETAC

CENTRAL CLIMATOLOGY BRANCH
 METAC
 U.S. WEATHER SERVICE/HAC

PSYCHROMETRIC SUMMARY

1. <u>1010</u>	<u>COL A J MC SAKEN AAF DL</u>
STATION	STATION NAME

73-72, EC-82

YEARS

2020

7-1-1 1900-1111
HOURS (L. S. T.)

YEARS _____ MONTH _____
 PAGE 1 120-1400
 HOURS (L. S. T.) _____

1715	COL A J D BAKER AAF DL
STATION	STATION NAME

73-78, 85-82

YEAR:

39
MONT

PAGE 1 125-1400
HOURS 11.5.11

CLIMATE CLIMATOLOGY BRANCH
METEOR
METEOROLOGICAL SERVICE/MAC

PSYCHROMETRIC SUMMARY

1 717 COL A J. DAVE DAF IL
STATION STATION NAME

73-74, 80-87

YEARS

JUN
MONTH

PAGE 1 1500-1700
HOURS (L. S. T.)

[illegible]

2

•

۱۹۸۵

STATION	STATION NAME
---------	--------------

YEARS

MON T W

PAGE 2

1370-2000
HOURS 11.5.70

REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

D-26.5 (OL A)

FORM 44-100 (Rev. 1-60)

UŠAFETAC

PSYCHROMETRIC SUMMARY

1	710	COL A J D BAKE	AAF DL
	STATION		STATION NAME

73-7-150-12

YEARS

11

SECTION 10

241

311

— *Journal of the American Medical Association*, 1997

[illegible]

2

U.S. AIR FORCE CLIMATE DIVISION
 AFMTC
 WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

STATION: 21001 A U TAPE AAF DL
 STATION NAME: 12-71, 01-01

YEARS

JUL
MONTH

PAGE 1

15000-1900
HOURS (L.S.T.)

Temp (F)	WET BULB TEMPERATURE DEPRESSION (F)																															TOTAL		TOTAL		
	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	D.B. W.B.	Dry Bulb	Wet Bulb	Dew Point
71										1.																							5	5		
70																																	4	4		
69																																	19	19		
68																																	15	15		
67																																	44	64	5	
66																																	22	22	29	5
65																																	20	20	5	18
64																																	79	79	9	57
63																																	78	78	91	66
62																																	72	72	110	102
61																																	47	47	77	86
60																																	43	43	71	57
59																																	31	31	46	37
58																																	26	26	25	14
57																																	4	4	11	13
56																																			15	
55																																			2	
54																																				
53																																				
52																																				
51																																				
50																																				
49																																				
48																																				
47																																				
46																																				
45																																				
44																																				
43																																				
42																																				
41																																				
40																																				
39																																				
38																																				
37																																				

USAFETAC FORM 026-5 (OL A) 01-60 PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Element (X)	ΣX	ΣX^2	ΣX^3	ΣX^4	No. Obs.	Mean No. of Hours with Temperature						
Rel. Hum.	4223446	50350	62.3	11.620	612	≤ 0 F	≤ 32 F	≤ 67 F	≤ 73 F	≤ 80 F	≤ 93 F	Total
Dry Bulb	198165	34791	56.8	5.773	612			9.9				5.5
Wet Bulb	177538	32852	53.7	4.4.8	612							4.3
Dew Point	1619290	31370	51.2	4.305	612							3.5

PSYCHROMETRIC SUMMARY

1-715	COL A J O BAKE : AAF DL
STATION	STATION NAME

13-70, 60-62

444

STATION

STATION NAME

YEARS

PAGE 1

MONTH

7922-11.2

MOUSE (1-5-7)

[illegible]

GLOBAL CLIMATOLOGY BRANCH
NO. 2202
PO BOX 308
WASHINGTON, DC 20543-0308

PSYCHROMETRIC SUMMARY

1 0710	07L A J 10 BAKER AAF DL
STATION	STATION NAME

73-79, 80-97

YEARS

July

MONTH

PAGE 1

1570-1750

HOURS (1, 5, 9, ...)

[illegible]

REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

0-26-5 (OL A)

USAFETAC

2

PSYCHROMETRIC SUMMARY

YEARS

JUL
MONTH

PAGE: 1 100-200
MOUSE 11-5-71

0.26.5 (OLA)

USAFETAC

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

U.S. AIR FORCE
CLIMATE BRANCH
AFETAC
WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

STATION 71 COL A J O PAKE AAF CL 73-7P, 80-90 JIL
STATION NAME YEARS MONTH

PAGE 1 ALL
HOURS (L. S. T.)

Temp. (F)	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	31	TOTAL D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point
67																		2	2		
68																		0	0		
69																		14	14		
70																		45	45		
71																		89	89		
72																		123	123		
73																		156	156		
74																		142	142		
75																		156	156	0	
76																		165	165	9	
77																		117	117	77	4
78																		129	129	126	2
79																		243	243	243	15
80																		173	173	364	57
81																		180	180	350	140
82																		157	157	318	704
83																		175	175	258	367
84																		141	141	244	376
85																		88	88	196	325
86																		101	101	1-4	225
87																		84	84	170	279
88																		23	23	45	233
89																		5	5	15	78
90																					42
91																					4
92																					1
93																					1
TOTAL	4.2	16.0	15.3	12.7	11.2	10.5	10.0	9.1	4.4	2.3	1.1	.1						2500	2500	2500	2500
Element (X)																					
Rel. Hum.	12373871										109951										
Dry Bulb	10746363										160724										
Wet Bulb	252428										143000										
Dew Point	6411433										130923										
No. Obs.	2500										2500										
Mean No. of Hours with Temperature																					
± 0 F																					
± 32 F																					
± 67 F																					
± 73 F																					
± 80 F																					
± 93 F																					
Total																					

CLIMATE CLIMATOLOGY BRANCH
TACETAC
AIR LEATHER SERVICE/HAC

PSYCHROMETRIC SUMMARY

1710	COL A J LO BAKE BAF DL
STATION	STATION NAME

73-70, PG-52

At 17,

STAT-2B

STATION NAME

YEARS

MON T W

Page 1

7500-0500

HOURS 11. 5. 7.

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																				TOTAL		TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	D.B.-W.B.	Dry Bulb	Wet Bulb	Dew Point			
77 75																		1	1					
77 71																		1	1					
77 69																		1	1					
77 67																		1	1					
77 65																		1	1					
77 63																		1	1					
77 61																		1	1					
77 59																		1	1					
77 57																		1	1					
77 55																		1	1					
77 53																		1	1					
77 51																		1	1					
77 49																		1	1					
77 47																		1	1					
77 45																		1	1					
77 43																		1	1					
77 41																		1	1					
77 39																		1	1					
77 37																		1	1					
TOTAL	11.3	47.1	22.6	9.4	1.5	.6	.3											6.7	6.7	6.7	6.7			

Element (X)	Σ x ²	Σ x	$\bar{x}$	s _x	No. Obs.	Mean No. of Hours with Temperature						Total
Rel. Hum.	4692560	52466	57.3	9.684	607	≤ 0 F	≤ 32 F	≥ 67 F	≥ 73 F	≥ 80 F	≥ 93 F	
Dry Bulb	1556264	33532	55.7	5.829	607			2.6	.2			93
Wet Bulb	1755717	42507	55.6	4.949	607							93
Dew Point	1549568	31504	51.9	4.862	607							93

YEARS

73-72, FD-302

A 1.2

PAGE 1 12-6-1400
HOURS 11.3.11

[illegible]

CENTRAL CLIMATOLOGY BRANCH
USAFETAC
WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

STATION: OHL A J RO BAKER AAF DL
STATION NAME

73-76, 90-82

YEARS

AUG
MONTH

PAGE 1

15, 0-1700
HOURS (L. S. Y.)

Temp (F)	WET BULB TEMPERATURE DEPRESSION (F)																																	TOTAL		TOTAL	
	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point	
7/ 89																																	1	1			
5/ 87																																	1	1			
5/ 85																																	4	4			
4/ 83																																	5	5			
4/ 81																																	5	5			
4/ 79																																	24	2			
7/ 77																																	12	12			
6/ 75																																	26	26			
4/ 73																																	45	45			
4/ 71																																	52	52			
4/ 69																																	37	37		4	
4/ 67																																	25	25		25	
6/ 65																																	47	47		1	
4/ 63																																	15	48	79	13	
4/ 61																																	21	21	69	17	
4/ 59																																	25	25	62	29	
4/ 57																																	24	24	55	59	
4/ 55																																	17	17	39	74	
4/ 53																																	24	24	23	71	
4/ 51																																	0	0	25	67	
4/ 49																																	7	7	11	43	
4/ 47																																				34	
4/ 45																																	1	1		10	
4/ 43																																	1	1		4	
4/ 41																																				1	
4/ 39																																				5	
TOTAL	1.01	.91	12.61	2.61	5.15	11.5	11.6	3	7.5	4.1	2.1	.9	.6																				459	460	460		

Element (X)	ΣX^2	ΣX	$\bar{X}$	σ^2	No. Obs.	Mean No. of Hours with Temperature					Total	
Rel. Hum.	2.49401	30385	64.11	5.962	460	$\leq 0 F$	$\leq 32 F$	$\geq 67 F$	$\geq 73 F$	$\geq 80 F$	$\geq 93 F$	Total
Dry Bulb	2149450	31711	67.2	5.319	460			43.5	26.6	5.4		92
Wet Bulb	164.637	27715	59.1	4.815	460			4.0				92
Dew Point	1365235	25213	53.6	4.578	460							92

USAFETAC FORM 34-64 0-26-5 (OL A) REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

GLOBAL CLIMATOLOGY BRANCH
METAC
AIR WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

1	711	COL A J D BAKE	AAF DL
	STATION	STATION NAME	

73-75,80-82

YEARS

4.15

PAGE 1

MONTH

A11

HOURS L. S. T.

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																															TOTAL		TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	= 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point														
7 66																		1	1																
7 67											.1	.1						3	3																
7 68										.1	.1	.1						6	6																
7 69									.2	.3	.1	.1						14	14																
7 70								.2	.4	.3								26	26																
7 71							.4	.4	.6	.2	.1							53	53																
7 72						.5	.6	.6	.7	.1								85	85																
7 73					.7	1.0	1.0	.7	.3									89	89																
7 74					.7	1.5	1.9	.4	.4									109	109																
7 75					.6	1.2	2.0	1.4	.7	.1								149	149	1															
7 76				.1	1.7	2.7	1.7	1.2	.7									164	164	11															
7 77				.3	.7	1.5	1.3	.5										180	180	6	1														
7 78			.1	1.2	1.1	1.6	1.8	.3	.									174	174	145	3														
7 79		.1	1.0	1.0	3.7	2.2	.8	.4	.									240	240	276	50														
7 80		.1	1.3	2.3	2.1	.7	.3											171	171	327	96														
7 81		.1	3.4	2.8	1.8	.7	.4											222	222	391	256														
7 82		.1	4.3	2.7	.6													173	173	379	713														
7 83	1.0	1.2	1.4	.7														176	176	298	373														
7 84	1.7	4.7	1.8	.7														185	185	215	343														
7 85	1.1	2.6	.6															106	106	1.9	316														
7 86	1.1	1.3	.2															66	66	168	751														
7 87	.7	.9	.4															49	49	57	266														
7 88	.9	.9																2	2	37	124														
7 89	.1	.4																17	17	17	50														
7 90	.1	.2																5	5	12	55														
7 91	.																	1	1	3	7														
7 92	.																	1	1	1	4														
7 93	7.122	9.166	13.612	112.0	5.1	3.8	2.6	1.1	.4	.2								2445	2445	2445															
																		2445	2445	2445															

Element (X)

Ref. Hum.

Dry Bulb

Wet Bulb

Dew Point

Zx²

1356327

955932

115470

7028732

Zx

177453

164756

140740

130562

I

72.0

63.2

57.4

53.4

%

17.10

8.793

5.413

4.318

No. Obs.

2445

2445

2445

2445

Mean No. of Hours with Temperature

= 0 F

= 32 F

= 67 F

= 73 F

= 80 F

= 93 F

Total

35.4.4

1.2.6

23.7

21.9

.3

744

744

744

744

01. PAL CLIMATOLOGY BRANCH
 02. METAC
 03. WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

STATION	STATION NAME
1 217	1 217
2 217	2 217
3 217	3 217
4 217	4 217
5 217	5 217
6 217	6 217
7 217	7 217
8 217	8 217
9 217	9 217
10 217	10 217
11 217	11 217
12 217	12 217
13 217	13 217
14 217	14 217
15 217	15 217
16 217	16 217
17 217	17 217
18 217	18 217
19 217	19 217
20 217	20 217
21 217	21 217
22 217	22 217
23 217	23 217
24 217	24 217
25 217	25 217
26 217	26 217
27 217	27 217
28 217	28 217
29 217	29 217
30 217	30 217
31 217	31 217
32 217	32 217
33 217	33 217
34 217	34 217
35 217	35 217
36 217	36 217
37 217	37 217
38 217	38 217
39 217	39 217
40 217	40 217
41 217	41 217
42 217	42 217
43 217	43 217
44 217	44 217
45 217	45 217
46 217	46 217
47 217	47 217
48 217	48 217
49 217	49 217
50 217	50 217
51 217	51 217
52 217	52 217
53 217	53 217
54 217	54 217
55 217	55 217
56 217	56 217
57 217	57 217
58 217	58 217
59 217	59 217
60 217	60 217
61 217	61 217
62 217	62 217
63 217	63 217
64 217	64 217
65 217	65 217
66 217	66 217
67 217	67 217
68 217	68 217
69 217	69 217
70 217	70 217
71 217	71 217
72 217	72 217
73 217	73 217
74 217	74 217
75 217	75 217
76 217	76 217
77 217	77 217
78 217	78 217
79 217	79 217
80 217	80 217
81 217	81 217
82 217	82 217
83 217	83 217
84 217	84 217
85 217	85 217
86 217	86 217
87 217	87 217
88 217	88 217
89 217	89 217
90 217	90 217
91 217	91 217
92 217	92 217
93 217	93 217
94 217	94 217
95 217	95 217
96 217	96 217
97 217	97 217
98 217	98 217
99 217	99 217
100 217	100 217

73-76,64-2

YEARS

350

MONTH

Case 2

2020-262
MOORE, S. T.

2

U.S. AIR FORCE
 AIR FORCE
 AIR FORCE

PSYCHROMETRIC SUMMARY

STATION NAME
 STATION NAME

73-74, 80-82

YEARS

MONTH

1-5-14

HOURS

Temp (F)	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	TOTAL D.B. W.B. Dry Bulb	TOTAL Wet Bulb Dew Point
7																																	1	1
8																																	2	2
9																																	3	3
10																																	4	4
11																																	5	5
12																																	6	6
13																																	7	7
14																																	8	8
15																																	9	9
16																																	10	10
17																																	11	11
18																																	12	12
19																																	13	13
20																																	14	14
21																																	15	15
22																																	16	16
23																																	17	17
24																																	18	18
25																																	19	19
26																																	20	20
27																																	21	21
28																																	22	22
29																																	23	23
30																																	24	24
31																																	25	25
TOTAL																																	548	548

USAFETAC FORM 0-26.5 (OL A) REVISIONS EDITIONS OF THIS FORM ARE OBSOLETE

Element (X)	Σx^2	Σx	Σ	σ_x	No. Obs.	Mean No. of Hours with Temperature						
Rel. Hum.	24533.6	35522	64.8	16.664	548	$\pm 0^\circ\text{F}$	$\pm 32^\circ\text{F}$	$\pm 67^\circ\text{F}$	$\pm 73^\circ\text{F}$	$\pm 80^\circ\text{F}$	$\pm 93^\circ\text{F}$	Total
Dry Bulb	2412510	34415	62.3	9.686	548			32.0	16.4	2.6		50
Wet Bulb	16593.2	50314	55.3	6.400	548			8				9
Dew Point	1360975	27303	49.8	6.145	548							4

1. GENERAL CLIMATOLOGY BRANCH
 2. CAFETAC
 3. WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

711 COL A J C BAKE AAF CL
STATION STATION NAME

73-74, 1-2

YF009

55 MONTH

15-1-2020
HOURS 11:50-1:00

GENERAL CLIMATOLOGY BRANCH
AFMAC
C. LEATH & SERVICE / MAC

PSYCHROMETRIC SUMMARY

STATION	STATION NAME
1	COL A J CRANE AAF IL

73-75, 80-82

YEARS

U C T
MONTH

2455 1

5670-0900
HOURS 11, 5, 7

PSYCHROMETRIC SUMMARY

71	C L A J U C PAKET PAT PL
STATION	STATION NAME

13-70, 61-67

YEARS

...

MONTH

08-05-1

1570-1700
HOURS (L.S.T.)

Temp (F)	WET BULB TEMPERATURE DEPRESSION (F)																															TOTAL		TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	D.B. W.B.	Dry Bulb	Wet Bulb	Dew Point														
71																		2	2																
72																		2	2																
73																		2	2																
74																		6	6																
75																		6	6																
76																		9	9																
77																		27	27																
78																		27	27																
79																		28	28																
80																		18	18																
81																		28	28																
82																		2	52	57	11														
83																		29	29	49	22														
84																		34	34	56	35														
85																		21	21	42	35														
86																		39	39	40	34														
87																		41	43	42	41														
88																		27	27	53	75														
89																		10	17	27	43														
90																		21	21	17	22														
91																		15	15	17	42														
92																		14	14	25	39														
93																		3	2	15	13														
94																				1	0														
95																					0														
96																					1														
97																					1														
98																					1														
99																					1														
100																					1														
TOTAL	7.27	223.11	6.81	1.1	7.7	4.3	1.0	1.1										441	441	441	641														

Element (X)	Σx²	Σx	̄x	σx	No. Obs.	Mean No. of Hours with Temperature						Total
						≤ 0 F	≤ 32 F	≤ 67 F	≤ 73 F	≤ 80 F	≤ 93 F	
Rel. Hum.	2426646	32393	73.515	250	441							
Dry Bulb	1169100	22294	50.6	9.766	441		6	4.8	1.0	0.4		93
Wet Bulb	54112	20755	46.8	7.215	441		2.3					93
Dew Point	784012	18767	41.0	6.781	441		8.0					93

JOINT CLIMATEOLOGY BRANCH
METAC
AIR WEATHER SERVICE / JNC

PSYCHROMETRIC SUMMARY

STATION	STATION NAME
0 71	0 L A J 0 NAME / AAF EL

73-79, 81-82

451

YEARS

MONITOR

PAGE 1

1470-2048

HOURS: L. S. T.

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																															TOTAL		TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point														
67																		2	7																
68																		1	1																
69																		3	3	1															
70																		2	2		1														
71				1.7	1.0	1.0												12	12	1															
72			.7	.3	.3													4	4		1														
73			2.7	1.4	.7	.7												16	16	10															
74			1.7	1.0	1.7													13	13	14	7														
75		.7	2.1	2.4	1.7													12	12	15	13														
76		.3	2.4	3.0	.7													21	21	18	9														
77		1.0	3.1	2.1	1.7													11	21	30	20														
78		2.7	6.3	1.7	.3													34	34	26	34														
79		.7	7.2	1.7														26	26	35	33														
80		3.1	8.2	4.5	.7													46	46	70	45														
81		1.4	3.4	1.5														17	17	11	24														
82			4.1	.3														13	13	16	15														
83		.3	4.8															15	15	22	24														
84		2.1	1.7	.7														13	13	17	12														
85		.7	1.7															7	7	15	11														
86		.7	.7															4	4	6	14														
87																					2														
88																					0														
TOTAL	13.75	1.42	3.3	7.5	1.7	1.4	.7	.3										242	242	242	242														

Element (X)	Σ x ²	Σ x	$\bar{x}$	σ _x	No. Obs.	Mean No. of Hours with Temperature						Total
Ref. Num.						≤ 0 F	≤ 32 F	≤ 67 F	≤ 73 F	≤ 80 F	≤ 93 F	
Dry Bulb	616961	13229	84.5	11.06	292		3.5	.6				53
Wet Bulb	552674	12554	43.0	6.66	292		5.7					93
Dew Point	495405	11273	40.7	6.59	292		10.5					93

NATIONAL CLIMATOLOGY BRANCH
 METEAC
 WEATHER SERVICE/HAC

PSYCHROMETRIC SUMMARY

1	71	COL 2	NAME	AAF DL
STATION		STATION NAME		

73-79, 80-82

YEARS

258

MONTH

Page

ALL

HOURS (L, S, T)

Temp (F)	WET BULB TEMPERATURE DEPRESSION (F)																														TOTAL	TOTAL				
	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	= 31	D.B.-W.B.	Dry Bulb	Wet Bulb	Dew Point
L	10.7	37.3	31.9	51	1.7	7.0	4.5	0.9	1.1	.8	.7																							2426	2426	2426

CLIMATE CLIMATOLOGY BRANCH
METEOR
AIR WEATHER SERVICE/ASAC

PSYCHROMETRIC SUMMARY

1 70- CIL A J 3 RARE AAF CL
STATION STATION NAME

73-70, 80-62

MONTH

YEARS

74-111

26.5-12.5
HOURS 15.0

Temp. (F)		WET BULB TEMPERATURE DEPRESSION (F)																															TOTAL D.B./W.B.		TOTAL Wet Bulb Dew Point	
		0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31			
7	51																																	1	1	
7	50																																	1	1	
7	57																																	1	1	
7	53																																	1	1	
7	52																																	1	1	
7	41																																	1	1	
7	47																																	1	1	
7	45																																	1	1	
7	40																																	1	1	
7	41																																	1	1	
7	41																																	1	1	
7	37																																	1	1	
7	35																																	1	1	
7	33																																	1	1	
7	31																																	1	1	
7	27																																	1	1	
7	25																																	1	1	
7	22																																	1	1	
7	21																																	1	1	
7	17																																	1	1	
7	15																																	1	1	
7	13																																	1	1	
7	11																																	1	1	
7	9																																	1	1	
7	5																																	1	1	
7	3																																	1	1	
7	1																																	1	1	
7	0																																	1	1	
7	0																																	1	1	
7	0																																	1	1	
7	0																																	1	1	
7	0																																	1	1	
7	0																																	1	1	
7	0																																	1	1	
7	0																																			

4. HEALTH SERVICE / ABC

PSYCHROMETRIC SUMMARY

YEARS

NOV
MONTH

PAGE 1 - 92-11-3

HOURS (L, S, T)

[illegible]

USAFETAC FORM 0.26.5 (OL A) REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

USAFETAC

YEARS _____ MONTH _____
 PAGE 1 12-10-1961
 HOURS (L. S. T.) _____

1710	COLAJ GRAPE AAF FL
STATION	STATION NAME

11-75, 11-76

YEAR:

422

MONITOR

24-5

15-18.

HOURS L S T

Temp (F)	WET BULB TEMPERATURE DEPRESSION (F)																															TOTAL		TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	31	D.B.-W.B.	Dry Bulb	Wet Bulb	Dew Point														
67 67																		7	7																
67 63																		17	17																
67 61																		13	13																
67 59																		14	14																
67 57																		20	20																
57 55																		17	17	5															
47 53																		27	27	11															
57 51																		16	16	13															
67 49																		17	17	10															
67 47																		27	27	21	4														
67 45																		29	29	35	22														
47 43																		24	24	15	12														
67 41																		41	41	34	41														
67 39																		32	32	27	44														
67 37																		44	44	40	57														
67 35																		49	49	50	57														
67 33																		32	32	28	53														
67 31																		16	16	24	51														
67 29																		16	16	19	41														
67 27																		24	24	26	47														
67 25																		13	13	13	22														
67 23																		6	6	7	17														
67 21																		9	9	3	7														
67 19																		4	4	8	5														
67 17																				1	6														
67 15																					3														
TTL	16.	33.	716.	41	6.	6.2	7.7	4.	2.9	1.4									517		517														
																			517		517														

Element (X)	Σx^1	Σx	Σ	σ_s	No. Obs.	Mean No. of Hours with Temperature					Total	
Rel. Hum.	3113671	78435	75.31	7.55	517	≤ 0 F	≤ 32 F	≤ 67 F	≤ 73 F	≤ 80 F	≤ 93 F	
Dry Bulb	2953.3	21673	42.51	6.99	517		15.1	3				90
Wet Bulb	31607	19955	38.7	7.80	517		17.6					90
Dew Point	622265	17651	34.1	6.16	517		35.9					90

USAFETAC FORM 026-5 (OL A) REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE JUL 64

GLOBAL CLIMATOLOGY BRANCH
METAC
WEATHER SERVICE / IAC

PSYCHROMETRIC SUMMARY

STATION	STATION NAME
71	CAL A J D BAKE AAF DL

73-75,80-82

422

MONTH

YEARS

565-1

£ 1 1

MOVAS 11. S. T. 1

[illegible]

GLOBAL CLIMATOLOGY BRANCH
AFETAC
AIR WEATHER SERVICE/MAC

PSYCHROMETRIC SUMMARY

STATION _____ STATION NAME _____ YEARS _____ MONTH _____
ALL
HOURS U.S.T.

[illegible]

PSYCHROMETRIC SUMMARY

YEARS

655

FALL 1

NOV 20 - 68

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																															TOTAL		TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point														
77-81			.4															1	1																
77-84			.4															2	2	3															
77-87																																			
77-90			.6	.7	.6													10	10																
77-94																		1	1	3															
77-97			1.1	.7	.2													11	11	9	1														
77-100		.2	3.5	1.7														10	11	7	5														
77-103		.2	2.4	4.8	.6	.2												47	47	35	11														
77-106		1.1	3.9	.7														31	31	46	27														
77-109		4.4	5.1	.2														52	52	41	43														
77-112		6.1	3.1															50	50	77	59														
77-115		3.5	5.4	.4														50	51	49	55														
77-118		5.2	1.5															36	36	47	50														
77-121		2.2	.7	.2														17	17	15	23														
77-124		5.7	2.8															42	40	75	47														
77-127		2.1	.7															19	19	21	25														
77-130		4.4	.2															25	25	75	27														
77-133		5.2	.2															19	29	79	33														
77-136		3.7	.4															18	18	17	24														
77-139		2.2																12	12	14	11														
77-142		3.7																11	11	11	10														
77-145		5.7	.4															12	22	72	23														
77-148		.5																3	3	3	5														
77-151		.7																1	1	1	4														
77-154		.7																4	4	4	2														
77-157		1.1																5	5	5	5														
77-160		1.1																5	5	5	5														
77-163		.7																4	4	4	7														
77-166		.4																2	2	2	5														
TOTAL	51.3	34.5	5.5	1.7														541		541	541														

Element (X)	Σx^2	Σx	$\bar{x}$	σ_x	No. Obs.	Mean No. of Hours with Temperature						
Rel. Hum.	467.896	40024	92.6	9.68	541	≤ 0 F	≤ 32 F	≥ 67 F	≥ 73 F	≥ 80 F	≥ 93 F	Total
Dry Bulb	452.025	14599	26.9	10.425	542	2.1	61.3					93
Wet Bulb	424450	14132	26.2	9.877	541	2.1	66.5					93
Dew Point	384710	13461	24.9	9.652	541	2.6	74.4					93

PSYCHROMETRIC SUMMARY

DEC
MONTH

PAGE 1 10.0-17.0
HOURS (L. S. T.)

[illegible]

NO. 1 AL CLIMATOLOGY BRANCH
AFETAC
A. WEATHER SERVICE/HAC

PSYCHROMETRIC SUMMARY

1 71	COL A J LO BAKE AAF DL
STATION	STATION NAME

12-73, #1-23

YEARS

DEC
MONTH

PAGE : 1800-2000
HOURS (L. S. T.)

Temp. (F)	WET BULB TEMPERATURE DEPRESSION (F)																												TOTAL		TOTAL		
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	≥ 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point												
4 / 41			1.5	1.0														4	4														
4 / 43			2.0															5	5														
4 / 41			3.5	.5														6	6	8	7												
4 / 39			5.0	3.0														15	15	5	5												
4 / 37		3.0	7.5	1.5														24	24		14												
4 / 35		2.5	8.0															1	21	28	15												
3 / 33		4.5	5.0															19	19	32	19												
3 / 31		1.5	4.5															12	12	11	31												
3 / 29		4.5	6.0															1	31	44	23												
3 / 27		8.5																17	17	19	24												
2 / 25		3.5	1.5															10	10	5	17												
2 / 23		6.0	2.5															17	17	17	20												
2 / 21		3.0																5	5	7	11												
1 / 19		2.0																4	4	4	4												
1 / 17		1.0																2	2	2	4												
1 / 15		1.0	.5															3	3	3	7												
1 / 13		2.0																4	4	4	2												
1 / 11		2.0																4	4	4	5												
1 / 9		1.0																2	2	2	3												
1 / 7		.5																1	1	1	1												
TOTAL	45.546	20	5.0	1.5														200	100	200	200												

Element (X)	Σx^2	Σx	$\bar{x}$	s_x	No. Obs.	Mean No. of Hours with Temperature						
						≤ 0 F	± 32 F	≥ 67 F	≥ 73 F	≥ 80 F	≥ 93 F	Total
Rel. Hum.	1602620	18265	91.3	8.559	200							
Dry Bulb	203162	6175	30.9	7.931	200		47.9					93
Wet Bulb	190368	5992	30.0	7.280	200		49.8					93
Dew Point	172267	5703	28.5	6.962	200		67.0					93

CLIMATE CLIMATOLOGY BRANCH
METAC
WEATHER SERVICE/AC

PSYCHROMETRIC SUMMARY

STATION	STATION NAME
710	STL 4 J 0 PAVEN BAF DL

15-72, 66-23

250

STAY ON

STATION NAME

YEARS

24-1

MONTH

511

MOUSE (L. S. T.)

[illegible]

U. S. AIR FORCE
METAC
AIR FORCE SERVICE/MAO

PSYCHROMETRIC SUMMARY

2 711 JUL A J C BAKER AAF DL 73-72, RC-37 GFC
STATION STATION NAME YEARS MONTH

PAGE: ALL
HOURS (L, S, T):

Temp (F)	WET BULB TEMPERATURE DEPRESSION (F)																															TOTAL		TOTAL	
	0	1-2	3-4	5-6	7-8	9-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26	27-28	29-30	> 31	D.B./W.B.	Dry Bulb	Wet Bulb	Dew Point														
1	41.6	40.9	31.6	4.2	1.8	.2	.	.	.	.	.	.	.	.	.	.	.	2235	2237	2.35	2238														
																						2235	2237	2.35	2238										
																							</												

FORM 0-26.5 (OL A) REVISED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE JUL 64

USAFETAC

2

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

MEANS AND STANDARD DEVIATIONS

DRY-BULB TEMPERATURES DEG F FROM HOURLY OBSERVATIONS

100710 COL A J 80 BAKER AAF DL
STATION

73-78,80-82

YEARS

MEASUREMENT	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
MEAN	26.1	26.7	32.9	36.1	47.3	54.1	56.8	55.7	50.3	40.3	33.6	26.9	40.9
S.D.	10.719	7.757	8.240	6.600	6.910	7.234	5.773	5.829	6.647	7.361	8.519	10.425	13.698
TOTAL OBS	586	579	635	624	637	626	612	607	603	583	561	542	7175
MEAN	29.1	30.9	39.3	43.9	55.0	61.1	64.5	63.7	58.2	46.7	37.8	29.4	46.8
S.D.	9.258	7.280	9.366	9.112	8.618	9.277	8.059	7.515	8.406	8.721	9.266	9.419	15.604
TOTAL OBS	594	576	639	602	639	609	599	576	593	565	545	590	7127
MEAN	34.5	36.6	44.4	47.7	58.3	64.2	67.9	67.4	62.8	51.8	42.5	34.1	51.3
S.D.	8.218	8.158	10.430	10.183	9.471	10.055	9.144	8.291	9.686	9.836	10.999	8.433	15.425
TOTAL OBS	504	528	591	556	611	571	588	547	548	547	517	522	6590
MEAN	34.6	36.2	44.2	47.7	58.7	64.2	68.6	67.2	62.2	50.6	41.1	34.2	51.5
S.D.	7.916	8.293	10.794	10.452	9.456	10.897	9.427	8.319	9.880	9.766	10.387	8.047	15.635
TOTAL OBS	407	406	452	436	467	436	488	469	458	441	420	383	5263
MEAN	31.0	31.8	40.0	44.4	55.7	61.4	65.4	63.6	56.8	45.3	37.7	30.9	46.9
S.D.	7.701	6.654	9.496	9.229	8.371	10.241	8.661	7.762	8.527	7.782	8.299	7.931	14.893
TOTAL OBS	254	256	282	261	258	230	258	246	237	292	273	200	3045
MEAN													
S.D.													
TOTAL OBS													
MEAN													
S.D.													
TOTAL OBS													
MEAN													
S.D.													
TOTAL OBS													
ALL HOURS	30.7	32.2	39.8	43.6	54.6	60.6	64.3	63.2	57.9	46.8	38.4	30.8	47.2
S.D.	9.680	8.639	10.587	10.160	9.639	10.232	9.330	8.793	9.887	9.784	10.158	9.569	15.603
TOTAL OBS	2347	2345	2599	2459	2612	2472	2501	2445	2439	2428	2316	2237	29200



USAFETAC FORM 0-89-3 (OLA)

2

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AF WEATHER SERVICE/MAC

MEANS AND STANDARD DEVIATIONS

WET-BULB TEMPERATURES DEG F FROM HOURLY OBSERVATIONS

1 5710 COL A J BO BAKER AAF DL
STATION

73-78,80-82

YEARS

HR	CT	AN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
6-08	MEAN	25.3	26.0	31.7	34.6	44.5	50.9	53.7	53.6	48.5	39.0	32.3	26.2	39.1
	S.D.	9.989	7.227	7.441	5.576	5.648	5.892	4.408	4.949	5.915	6.638	7.557	9.877	12.567
	TOTAL OBS	583	579	634	604	637	626	612	607	603	582	560	541	7168
9-11	MEAN	27.0	29.5	36.2	39.8	46.9	54.6	57.4	57.9	53.3	43.4	35.4	28.2	42.8
	S.D.	8.296	6.315	7.282	6.768	6.049	6.686	4.953	4.946	6.097	6.758	7.366	8.587	12.879
	TOTAL OBS	591	575	639	611	639	608	598	576	593	564	544	589	7117
12-14	MEAN	32.2	33.5	39.4	41.8	50.7	56.1	58.8	59.4	55.3	46.4	38.6	32.1	45.6
	S.D.	6.510	5.925	7.537	7.203	6.255	7.138	5.220	4.890	6.400	6.792	7.806	7.019	11.927
	TOTAL OBS	502	528	591	556	611	571	588	547	548	547	517	522	6588
15-17	MEAN	32.4	33.1	39.1	41.4	50.9	56.5	59.3	59.1	55.1	46.0	37.9	32.5	45.8
	S.D.	6.465	5.894	7.843	6.997	6.111	7.801	5.239	4.815	6.758	7.215	7.744	6.806	12.094
	TOTAL OBS	407	406	451	436	466	436	488	469	457	441	420	383	5260
18-20	MEAN	29.8	30.1	36.7	39.7	49.2	54.7	57.6	57.6	52.6	43.0	35.8	30.0	43.0
	S.D.	6.796	5.454	7.271	6.439	5.603	7.307	5.184	5.013	6.606	6.668	7.069	7.280	12.100
	TOTAL OBS	256	255	282	261	258	230	258	246	237	292	273	200	3084
	MEAN													
	S.D.													
	TOTAL OBS													
	MEAN													
	S.D.													
	TOTAL OBS													
	MEAN													
	S.D.													
	TOTAL OBS													
ALL HOURS	MEAN	29.2	30.2	36.4	39.3	48.6	54.4	57.2	57.4	52.8	43.4	35.9	29.5	43.1
	S.D.	8.458	6.947	8.040	7.172	6.464	7.189	5.398	5.413	6.840	7.361	7.899	8.559	12.636
	TOTAL OBS	2339	2343	2597	2458	2611	2471	2500	2445	2438	2426	2318	2235	29177

USAFETAC FORM 0 80 5 (OLA)

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

MEANS AND STANDARD DEVIATIONS

DEW-POINT TEMPERATURES DEG F FROM HOURLY OBSERVATIONS

1 5710 COL A J BO BAKER AAF DL

73-78,80-82

HR	MEAN	AN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
6-8	23.6	24.4	29.5	32.4	41.7	48.4	51.3	51.9	46.9	37.5	30.5	24.9	37.2	
	9.505	7.294	7.662	5.541	5.788	5.720	4.305	4.802	5.953	6.678	7.444	9.602	12.364	
	583	579	634	604	637	626	612	607	603	582	560	541	7168	
9-11	25.7	26.9	32.1	35.1	43.5	49.7	52.6	54.0	49.5	40.1	32.4	26.2	39.0	
	7.819	6.312	6.986	6.638	6.267	6.728	4.537	4.780	5.901	6.340	6.650	8.329	12.080	
	591	575	639	601	639	608	598	576	593	564	544	589	7117	
12-14	26.8	29.1	33.5	35.2	44.1	50.2	52.8	54.1	49.8	41.3	34.1	29.2	40.4	
	5.773	5.614	7.318	7.415	6.477	7.475	4.787	4.759	6.145	6.169	6.169	6.353	11.181	
	502	528	591	556	611	571	548	547	548	547	517	522	6588	
15-17	29.3	28.6	33.2	34.4	44.1	50.9	53.1	53.8	49.8	41.6	34.1	30.0	40.7	
	5.808	5.308	7.379	6.776	6.641	8.063	4.891	4.578	6.455	6.581	6.494	6.214	11.311	
	407	406	451	436	466	436	488	469	457	441	420	383	5260	
18-20	27.7	27.1	32.6	34.4	43.3	49.6	52.3	53.5	49.5	40.7	33.3	28.5	39.3	
	6.383	5.506	6.712	6.034	5.859	7.315	4.943	4.773	6.411	6.590	6.712	6.962	11.300	
	252	255	282	261	256	230	254	246	237	292	273	220	3044	
MEAN														
S.D.														
TOTAL OBS														
MEAN														
S.D.														
TOTAL OBS														
MEAN														
S.D.														
TOTAL OBS														
ALL HOURS	26.7	27.1	32.0	34.3	43.3	49.7	52.4	53.4	49.0	40.1	32.7	27.4	39.2	
	7.753	6.420	7.418	6.629	6.303	7.030	4.696	4.818	6.241	6.640	6.878	8.048	11.811	
	2339	2343	2597	2458	2611	2471	2500	2445	2438	2426	2314	2235	29177	

2

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

RELATIVE HUMIDITY

1 710
STATION

COL A J EO BAKER AAF DL
STATION NAME

73-78,80-82

PERIOD

JAN
MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

MONTH	HOURS (LST)	PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN									MEAN RELATIVE HUMIDITY	TOTAL NO OF OBS
		10%	20%	30%	40%	50%	60%	70%	80%	90%		
JAN	00-02											
	03-05											
	06-08	100.0	100.0	99.6	99.5	98.8	98.5	94.9	88.0	61.9	90.9	593
	09-11	100.0	100.0	100.0	99.3	98.8	97.0	89.8	78.2	52.6	87.9	591
	12-14	100.0	100.0	99.4	98.4	96.2	89.2	74.3	58.2	35.3	81.3	502
	15-17	100.0	100.0	100.0	99.3	97.5	92.6	76.9	58.2	39.8	82.4	477
	18-20	100.0	100.0	100.0	100.0	98.8	97.3	91.0	77.3	53.5	88.0	256
	21-23											
TOTALS		100.0	100.0	99.4	99.3	98.0	94.9	85.4	72.0	48.6	86.1	2339

USAFETAC

FORM
JUL 64

0-87-5 (OL A)

GENERAL CLIMATOLOGY BRANCH
METAC
AIR WEATHER SERVICE/MAC

10471
STATION

COL A J BO BAKER AAF DL
STATION NAME

73-78,90-42

PERIOD

F E O
MONTH

MONTH	HOURS (LST)	PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN									MEAN RELATIVE HUMIDITY	TOTAL NO. OF OBS
		10%	20%	30%	40%	50%	60%	70%	80%	90		
FEB	00-02											
	03-05											
	06-08	100.0	100.0	100.0	100.0	100.0	99.0	95.0	88.3	67.5	91.4	579
	09-11	100.0	100.0	100.0	99.8	98.6	94.8	84.3	71.8	50.3	86.1	575
	12-14	100.0	100.0	99.6	96.0	87.7	77.8	63.1	48.9	31.3	76.6	528
	15-17	100.0	100.0	99.6	96.1	88.4	77.1	62.8	49.8	31.5	76.5	476
	18-20	100.0	100.0	100.0	98.8	97.3	94.5	80.4	65.9	42.7	83.9	255
	21-23											
TOTALS		100.0	100.0	99.9	96.1	94.4	88.6	77.1	64.9	44.7	82.9	2343

USAFETAC FORM 0-87-5 (OL A)

RELATIVE HUMIDITY

MAR
MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

MONTH	HOURS (LST)	PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN									MEAN RELATIVE HUMIDITY	TOTAL NO OF OBS
		10%	20%	30%	40%	50%	60%	70%	80%	90		
MAR.	0-02											
	03-05											
	06-08	100.0	100.0	99.8	99.4	98.1	97.2	90.5	78.5	54.1	88.1	634
	09-11	100.0	100.0	99.1	96.7	92.2	82.9	64.8	49.8	32.7	77.8	639
	12-14	100.0	100.0	97.8	90.2	76.3	61.4	47.7	36.2	19.1	69.0	591
	15-17	100.0	99.8	98.7	90.7	76.9	60.8	49.0	36.1	17.5	69.7	451
	18-20	100.0	100.0	100.0	98.6	92.9	81.9	66.3	48.9	23.8	76.6	282
	21-23											
TOTALS		100.0	100.0	99.1	95.1	87.3	76.8	63.7	49.9	29.4	76.0	2597

GENERAL CLIMATOLOGY BRANCH
NAFETAC
AIR WEATHER SERVICE/MAC

1 4710
STATION

COL A J SO BAKER AAF DL
STATION NAME

73-78, 80-82

APR
MONTH

MONTH	HOURS (LST)	PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN									MEAN RELATIVE HUMIDITY	TOTAL NO OF OBS
		10%	20%	30%	40%	50%	60%	70%	80%	90%		
APR	00-03											
	03-05											
	05-08	100.0	100.0	100.0	99.5	98.2	96.2	88.1	77.2	51.7	47.2	624
	09-11	100.0	100.0	99.5	95.7	85.9	71.2	59.6	45.1	25.1	74.0	631
	12-14	100.0	100.0	97.3	86.7	67.4	55.6	45.3	32.2	17.4	65.9	556
	15-17	100.0	100.0	95.9	84.9	63.5	50.5	39.9	31.4	16.5	63.9	436
	18-20	100.0	100.0	98.5	94.6	79.7	66.3	50.2	39.5	23.0	71.0	261
	21-23											
TOTALS		100.0	100.0	98.2	92.3	78.9	68.0	56.6	45.1	26.7	72.4	2458

USAFETACFORM
JUL 64

0-87-5 (OL A)

1 9710	COL A J BO BAKER AAF DL	73-76,80-62	MAY
STATION	STATION NAME	PERIOD	MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

MONTH	HOURS (LST)	PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN								MEAN RELATIVE HUMIDITY	TOTAL NO. OF OBS.	
		10%	20%	30%	40%	50%	60%	70%	80%			90%
MAY	00-02											
	03-05											
	06-08	100.0	100.0	100.0	99.7	97.8	92.0	79.6	59.0	34.7	81.9	637
	09-11	100.0	100.0	99.5	95.6	78.9	61.3	45.9	27.5	13.5	67.5	639
	12-14	100.0	100.0	97.7	86.6	68.6	49.8	34.0	21.9	9.7	62.3	611
	15-17	100.0	100.0	96.8	86.9	65.2	46.1	34.8	24.5	9.4	61.8	466
	18-20	100.0	100.0	99.6	93.0	79.5	55.0	41.5	24.0	10.9	65.7	258
	21-23											

RELATIVE HUMIDITY

1 710
STATION

COL A J SO BAKER AAF DL
STATION NAME

73-78, 80-92

PERIOD

JUN
MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

MONTH	HOURS TEST	PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN									MEAN RELATIVE HUMIDITY	TOTAL NO. OF OBS.
		10%	20%	30%	40%	50%	60%	70%	80%	90%		
JUN	1-5-00											
	6-10											
	11-15	100.0	100.0	100.0	100.0	99.2	93.1	83.9	59.3	30.7	82.0	626
	16-20	100.0	100.0	100.0	97.7	81.7	61.7	43.1	29.6	13.8	68.3	608
	21-25	100.0	100.0	99.6	91.2	69.2	47.1	35.4	24.0	8.4	63.0	571
	26-30	100.0	100.0	99.1	90.4	72.7	52.5	41.1	28.2	12.8	65.0	436
	1-5	100.0	100.0	100.0	96.1	79.1	60.9	45.2	29.6	10.9	67.6	230
	6-10											
	11-15											
	16-20											
	21-25											
	26-30											
TOTALS		100.0	100.0	99.7	95.1	80.4	63.1	49.7	34.1	15.2	69.2	2471

1 9710
STATION

COL A J BO BAKER AAF DL
STATION NAME

73-7c, 80-82

PERIOD

JUL
MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

MONTH	HOURS (LST)	PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN									MEAN RELATIVE HUMIDITY	TOTAL NO. OF OBS.
		10%	20%	30%	40%	50%	60%	70%	80%	90%		
JUL	00-02											
	03-05											
	06-08	100.0	100.0	100.0	100.0	99.5	94.9	85.1	57.8	28.3	62.3	612
	09-11	100.0	100.0	100.0	97.3	84.8	62.5	39.6	22.1	10.2	67.2	598
	12-14	100.0	100.0	99.8	91.8	63.7	42.0	27.6	16.2	8.8	60.9	548
	15-17	100.0	100.0	99.4	89.3	60.7	43.0	30.7	18.0	9.2	60.5	488
	18-20	100.0	100.0	99.6	94.9	75.6	52.8	40.6	22.0	8.7	64.9	254
	21-23											
TOTALS		100.0	100.0	99.8	94.7	76.9	59.0	44.7	27.6	13.0	67.2	2500

109710	COL A J EO BAKER AAF DL	73-78,80-82	AUG
STATION	STATION NAME	PERIOD	MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

MONTH	HOURS (LST)	PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN									MEAN RELATIVE HUMIDITY	TOTAL NO. OF OBS.
		10%	20%	30%	40%	50%	60%	70%	80%	90%		
AUG	1-0-02											
	3-05											
	6-08	100.0	100.0	100.0	100.0	100.0	98.8	94.9	75.0	43.8	37.3	607
	9-11	100.0	100.0	100.0	99.1	92.4	75.9	55.2	30.9	12.5	72.2	576
	12-14	100.0	100.0	99.6	94.3	78.6	53.2	34.4	18.8	7.9	64.4	547
	15-17	100.0	100.0	100.0	94.7	76.3	53.5	35.6	18.6	6.8	64.1	469
	18-20	100.0	100.0	100.0	98.6	90.7	73.2	54.1	29.3	13.4	71.4	246
	21-23											
TOTALS		100.0	100.0	99.9	97.4	87.6	70.9	54.8	34.5	16.9	71.9	2445

GLOBAL CLIMATOLOGY BRANCH
SAFETAC
AIR WEATHER SERVICE/MAC

RELATIVE HUMIDITY

1 - 713
STATION

COL A J EO BAKER AAF DL
STATION NAME

73-78, 80-82

SEP
MON

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

MONTH	HOURS (LST)	PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN								MEAN RELATIVE HUMIDITY	TOTAL NO. OF OBS	
		10%	20%	30%	40%	50%	60%	70%	80%			90%
JULY	00-02											
	03-05											
	06-08	100.0	100.0	100.0	99.8	99.2	97.3	94.7	81.4	49.6	86.5	603
	09-11	100.0	100.0	100.0	99.3	93.8	80.6	60.4	35.9	18.2	74.2	593
	12-14	100.0	100.0	99.1	94.0	80.5	55.1	35.8	20.4	9.3	64.8	548
	15-17	100.0	100.0	99.0	95.8	84.0	60.4	38.1	19.3	9.2	65.9	457
	18-20	100.0	100.0	100.0	98.7	96.2	89.9	75.9	43.0	17.7	77.8	237
	21-23											
TOTALS		100.0	100.0	99.8	97.5	90.7	76.7	61.0	40.0	20.8	74.2	2438

2

CLICAL CLIMATOLOGY BRANCH
USAFETAC
AF WEATHER SERVICE/MAC

RELATIVE HUMIDITY

1 9710
STATIONCGL A J ED BAKER AAF DL
STATION NAME

73-78,80-82

PERIOD

JCT
MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

MONTH	HOURS (LST)	PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN									MEAN RELATIVE HUMIDITY	TOTAL NO OF OBS
		10%	20%	30%	40%	50%	60%	70%	80%	90%		
JCT	00-02											
	03-05											
	06-08	100.0	100.0	100.0	100.0	99.7	97.9	95.7	85.6	58.4	90.1	582
	09-11	100.0	100.0	100.0	99.1	96.1	87.4	72.7	50.0	23.5	79.2	564
	12-14	100.0	100.0	99.1	95.6	86.5	66.7	49.2	31.4	14.1	69.7	547
	15-17	100.0	100.0	99.8	98.9	90.9	76.2	58.0	37.4	17.2	73.5	441
	18-20	100.0	100.0	100.0	99.7	98.3	96.6	88.7	66.1	37.7	84.5	292
	21-23											
TOTALS		100.0	100.0	99.8	98.7	94.3	85.0	72.9	54.1	31.2	79.4	2426

USAFETAC

FORM
JUL 64

0-87-5 (OL A)

1 0710 COL A J ED BAKER AAF DL 73-78,80-82 NOV
STATION STATION NAME PERIOD MONTH

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE
(FROM HOURLY OBSERVATIONS)

MONTH	HOURS (LST)	PERCENTAGE FREQUENCY OF RELATIVE HUMIDITY GREATER THAN									MEAN RELATIVE HUMIDITY	TOTAL NO. OF OBS.
		10%	20%	30%	40%	50%	60%	70%	80%	90%		
Nº.	0-02											
	03-05											
	06-08	100.0	100.0	100.0	100.0	98.8	96.8	95.0	83.8	55.9	89.1	560
	09-11	100.0	100.0	100.0	98.5	95.6	89.5	77.6	63.2	40.3	82.4	544
	12-14	100.0	100.0	99.4	94.6	87.2	76.2	63.4	50.3	27.9	75.3	517
	15-17	100.0	100.0	99.8	96.2	91.0	84.3	72.4	53.6	28.8	78.6	420
	18-20	100.0	100.0	100.0	100.0	97.4	97.4	89.7	69.2	40.7	85.0	273
	21-23											
TOTALS		100.0	100.0	99.8	97.9	94.0	88.8	79.6	64.0	38.7	80.1	2314

2

DEC
MONTH

95-2007

6

U S AIR FORCE
ENVIRONMENTAL TECHNICAL
APPLICATIONS CENTER

PART F


PRESSURE SUMMARY

Presented in this part are two tables giving the means, standard deviations, and total number of observations of station pressure and sea-level pressure by month and annual for the local hourly observations corresponding to the eight 3-hourly synoptic times GCT. The same computations are also provided at the bottom of the page for all hours combined. All years of data available are combined in both of these tables, although the overall period is limited by service as indicated below.

NOTES: Station pressure not reported for all services until late in 1945.
Station pressure reported only at 6-hourly times for Air Force stations from Jan 64 - Jul 65.
METAR stations do not report Sea-level pressure for the period Jan 68 - Dec 70.

1. Station pressure is presented in the table in inches of mercury.
2. Sea-level pressure is presented in millibars.

Provided below is a scale to convert station pressure values in inches of mercury or millibars to pressure-altitude in 1000's of feet. This scale is an enlarged model of the pressure-altitude scale in the Smithsonian Meteorological Tables.



2

GLOBAL CLIMATOLOGY BRANCH
USAFETAC
AIR WEATHER SERVICE/MAC

MEANS AND STANDARD DEVIATIONS

STATION PRESSURE IN INCHES HG FROM HOURLY OBSERVATIONS

1 5710 COL A J BO BAKEP AAF DL
STATION STATION NAME

73-78,80-82

YEARS

HRS	ST	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
1	MEAN													
	S.D.													
	TOTAL OBS.													
05	MEAN													
	S.D.													
	TOTAL OBS.													
07	MEAN	27.550	27.502	27.492	27.488	27.509	27.584	27.586	27.624	27.628	27.541	27.594	27.498	27.550
	S.D.	.268	.289	.219	.170	.174	.127	.118	.117	.166	.250	.248	.329	.219
	TOTAL OBS.	192	193	215	203	212	211	205	202	203	195	187	175	2393
10	MEAN	27.571	27.514	27.502	27.499	27.517	27.592	27.593	27.624	27.638	27.550	27.623	27.504	27.559
	S.D.	.270	.294	.223	.173	.175	.128	.117	.121	.165	.259	.239	.360	.228
	TOTAL OBS.	189	187	210	200	210	194	190	172	194	188	175	192	2301
15	MEAN	27.562	27.501	27.498	27.484	27.505	27.574	27.581	27.619	27.625	27.523	27.631	27.470	27.547
	S.D.	.265	.292	.216	.170	.172	.131	.117	.119	.164	.260	.297	.349	.229
	TOTAL OBS.	149	161	182	184	193	177	169	167	171	166	163	159	2041
16	MEAN	27.544	27.505	27.487	27.474	27.513	27.575	27.572	27.610	27.602	27.523	27.607	27.425	27.538
	S.D.	.252	.301	.214	.172	.160	.126	.108	.115	.170	.255	.237	.338	.218
	TOTAL OBS.	128	124	146	141	147	134	154	150	159	140	131	124	1682
19	MEAN	27.563	27.521	27.509	27.473	27.502	27.575	27.561	27.603	27.614	27.542	27.618	27.465	27.545
	S.D.	.256	.308	.217	.182	.145	.131	.106	.112	.172	.255	.238	.310	.221
	TOTAL OBS.	128	124	136	120	117	101	117	102	107	145	137	99	1437
22	MEAN													
	S.D.													
	TOTAL OBS.													
ALL HOURS	MEAN	27.558	27.508	27.498	27.485	27.510	27.581	27.581	27.616	27.623	27.537	27.615	27.477	27.549
	S.D.	.263	.295	.218	.173	.168	.128	.114	.117	.167	.255	.253	.341	.223
	TOTAL OBS.	784	793	889	848	879	817	835	793	834	834	793	753	9854



USAFETAC FORM 0 89 5 (OLA)

DATE
ILME