



MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAG OF STANDARD (1995) A



FILE COPY

j

SHORT-RANGE LOCAL FORECASTING OF IAVENVPREDRSCHFAC TR 83-0 590 COASTAL SUMMER STRATUS BY STATISTICAL TECHNIQUES - A PILOT STUDY A134

Wayne A. Sweet vironmental Prediction Research Facility

SEPTEMBER 1983



AL PREDICTION RESEARCH FACILITY **MONTEREY, CALIFORNIA 93940**

004 0.1 83 **1**

NVPREDRSCHFAC

TECHNICAL REPORT

TR 83-06

QUALIFIED REQUESTORS MAY OBTAIN ADDITIONAL COPIES FROM THE DEFENSE TECHNICAL INFORMATION CENTER. ALL OTHERS SHOULD APPLY TO THE NATIONAL TECHNICAL INFORMATION SERVICE.

4

.

Ŧ

UNCLASSIFIED	
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)	
REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
T. REPORT NUMBER NAVENUPREDRSCHFAC 2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
Technical Report TR 83-06	9()
4. TITLE (and Sublitio)	5. TYPE OF REPORT & PERIOD COVERED
Short-Range Local Forecasting of Coastal	Final
Summer Stratus by Statistical Techniques	
- A Pilot Study	NEPRETR 83-06
7. AUTHOR()	S. CONTRACT OR GRANT NUMBER(+)
Wayne A. Sweet	
	IN PROSPAN PLEMENT PROJECT TARK
). PERFORMING ORGANIZATION NAME AND ADDRESS Neural Environmental Deceintion Deceanch Excility	AREA & WORK UNIT NUMBERS
Monterey CA 93943	PE 62759N PN WF59-551
	TA_2 NEPRF WU 6.2-18
I. CONTROLLING OFFICE NAME AND ADDRESS	12. AEPORT DATE
Naval Air Systems Lommand	September 1983
Washington, DC 20361	13. NUMBER OF FACES
TA. MONITORING AGENCY NAME & ADDRESS(II dillerent from Controlling Office)	18. SECURITY CLASS. (of this report)
	UNCLASSIFIED
	SCHEDULE
7. DISTRIBUTION STATEMENT (of the obstract entered in Block 20, if different fre	un Report)
B. SUPPLEMENTARY NOTES B. KEY WORDS (Continue on reverse eide if necessary and identify by block number)
Chatiatical formoscing	
Short range forecasting	
Regression technique	
Local forecasting	
0. ABSTRACT (Continue on reverse side il necessary and identify by block number)	
Two different regression techniques applied to forecasting are examined at four naval air station: Regression estimates of event probabilities (REEP) regression (LR) in forecasting summer stratus at M evaluated operationally at Moffett during the summ LR technique was examined at North Island, Miramar Southern California for the stratus ceiling foreca	o short range (24 hr or less) s on the California coast. was compared to logistic offett NAS; REEP also was er of 1982. The skill of the and San Nicolas NAS in st.—(Continued on reverse)
D 1 JAN 73 1473 EDITION OF I NOV 68 IS OBSOLETE	UNCLASSIFIED
5/N 0102-014-6601 :	ASSIFICATION OF THIS PAGE (Then Date Anter

UNCLASSIFIED

SCURITY CLASSIFICATION OF THIS PAGE (Then Data Entered)

Block 20, Abstract, continued.

The results of these evaluations indicated equal skills for REEP and LR. The REEP operational evaluation at Moffett NAS showed a level of skill equivalent to that possessed by the most experienced forecasters.

equivalent to that possessed by the most experienced forecasters. Either of these techniques would provide valuable forecasting capability for certain forecast parameters when applied to remote areas where archived data are available but little or no local forecasting experience exists.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

CONTENTS

1.	Intro	duc	:t1	on		•	٠		٠	٠		•	•		•		•	•	•	•	•	•	•	٠	1
	1.1 1.2	Foc The	:us e F	or	f ec	th as	e t	Pi Pr	10 05	t S len	Sti n .	נףו י	'.		•	•	•	•	•	•	•	•	•	•	1 2
2.	Descr	ript	ci c	ns	0	f	th	e	RE	EP	ar	bd	L	R	Te	cl	hni	qu	es	•	•	•	•	•	4
	2.1 2.2	Reg Log	ire iis	ss ti	io c	n Re	Es gr	ti es	ma si	tes on	; (([of _R)	E	ve	nt •	1	Pro •	bai •	bil •	itie	es	(RE •	EP) ·	•	4 6
3.	Resul	ts	•	•		•	•		•	•		,	•				•	•	•	•	•	•	•	•	7
	3.1 3.2		ipa P Ra	ri Op	s0 er 1+	ns at	0 10 10	f na r	RE 1	EP Eva	ar 11	nd Jat	L ; 1	R on nd	at a) t Mi	Mof Mo ira	fe ff(tt i ett	NAS NAS	•	•	•	•	7 11
	J.J	and	IS	an	Ň	ic	01	a s	N	AS	• •	, .	•		•			•	•	•	•	•	•	•	12
4.	Conc1	usi	on	S	an	d	Re	co	mm	end	la t	;10	n	S	•		•	•	•	•	•	•	•	•	14
	4.1 4.2	Con Rec	cl om	u s me	io nd	ns at	10	n s	•	•	•	r 1	•		•	•	•	•	•	•	•	•	•	•	15 16
Refe	rence	S	•	•		•	•		•	•		,	•		•		•	•	•	•	•	•	•	•	16
Арре	ndix	A -	-	Εv	a 1	ua	ti	0 n	0	f R	EE	P	E	qu	at	10	ons	a	t Me	offe	ett	NA	S	•	17
Appe	ndix	B -	-	Lo	gi	st	ic	R	eg	res	s i	or		Eq	ua	ti	ion	s t	for	Mot	ffe	tt	NAS	•	37
Арре	ndix	C -	-	Lo No	gi rt	st h	ic Is	R 1 a	egi nd	res NA	s 1 S	or	•	Eq	ua •	ti	ion	s 1 •	for	•	•	•	•	•	41
Арре	ndix	D -	-	Lo Mi	gi ra	st ma	ic r	R	egi S	res	:s1 •	or	•	Εq	ua •	ti	ion	s 1 •	for •	•	•	•	•	•	45
Appe	ndix	Ε-	-	Lo Sa	gi n	st Ni	ic co'	R 1 a	egi s l	res NAS	s 1	an	•	Eq	ua •	ti	ion	s 1 •	for •	•	•	•	•	•	49
Dist	ribut	ion	l			•					_									•		_	_		52



1. INTRODUCTION

1.1 FOCUS OF THE PILOT STUDY

Short range forecasts for periods of 24 hours or less usually are based on both the objective guidance provided by large scale models and the individual forecaster's experience gained over time at a particular location. The forecaster who lacks this personal experience, however, often must rely on "textbook" interpretation of a model's objective guidance, and thus possibly be handicapped in forecasting primarily mesoscale situations.

This study examines the skill, usefulness and applicability of two techniques that have been applied to short range forecasting as substitutes for local experience. They are known as regression estimates of event probability (REEP), and logistic regression (LR) probabilities.

These techniques are based on conditional climatologies (see Miller, 1979). They use surface observations coupled with forecast equations based on regression techniques, to produce probability forecasts.

The skills of the techniques in forecasting summer stratus ceilings at four naval air stations in California -- Moffett NAS, North Island NAS, Miramar NAS, and San Nicolas NAS -- were evaluated in this study. Both REEP and LR were used at Moffett; only LR was used at the other three stations. (REEP equations also were used operationally at Moffett NAS during the summer of 1982; see Appendix A for results of this evaluation.) Skill scores of each technique were compared to those of climatology, a readily quantifiable technique, to assess performance.

1.2 THE FORECAST PROBLEM

Summer stratus along the California coast presents a daily forecast problem. Depending on the location, stratus with ceilings as low as 500 ft can develop during the late afternoon or evening, dissipating sometime the following morning. A series of days with stratus occurring typically is followed by one to several clear days; California summer is typically either coastal stratus or clear.

Since the mid-latitude Pacific anticyclone is a persistent feature in the summer, and the large scale synoptic pattern does not change much, the forecast problem therefore is associated with subtle changes in the mesoscale features. Predictors such as surface winds, dew point depression, etc., are strong candidates.

Topographical features also play a major role since the stratus deck is confined to the marine layer. Cool sea surface temperatures along the California coast in summer cause a low level temperature inversion and an associated moist marine layer. The predominant on-shore pressure gradient forces this marine layer on shore, with diurnal modification from the sea breeze gradient. Coastal terrain features modify, or dam up this inland intrusion.

Moffett NAS, for example, is located on the southern edge of the San Francisco Bay, with the Santa Cruz range to the west (Figure 1). These hills cause the stratus to approach Moffett from the north, along the bay. The cool and moist marine layer must slide through the Golden Gate and push down the bay, so the stratus deck that occurs at Moffett is really a combination advection-formation event.



Figure 1. Locations of air stations and airports, with mountain elevations to the west and east, in the San Francisco Bay Region of Northern California. At the three air stations in Southern California, the stratus deck has a clear path inland; field elevation and distance inland are the primary differences (see Figure 2). The lower latitude and much warmer sea surface temperatures along the southern coast also have an effect, causing thicker stratus decks with higher bases.

2. DESCRIPTIONS OF THE REEP AND LR TECHNIQUES

2.1 REGRESSION ESTIMATES OF EVENT PROBABILITIES (REEP)

The REEP technique (described in detail in Miller, 1964) uses surface observations from the forecast station and other surrounding stations. Each predictor variable is divided into subranges; these are then assigned values of 0 or 1, depending on the observed values.

(Lists of candidate predictors for both REEP and LR (logistic regression) techniques used in this pilot study are given for Moffett, North Island, Miramar and San Nicolas Naval Air Stations in Appendixes A-E respectively.)

As an example, the predictor variable "surface dew point depression" is divided into five subranges for Moffett NAS data:

Dummy Variable No.	<u>Range (°F)</u>
1	-8.0
2	8.1-10.0
3	10.1-12.0
4	12.1-14.0
5	>14.1

The dew point depression variable can now be represented by a vector,

D = (1, 0, 0, 0, 0),

which indicates the value is in the 0-8.0°F range. All the other predictor variables are categorized similarly, and the resulting single surface observation for any given day and time becomes simply a string of 0's and 1's.





Using linear regression methods, forecast indices are found for each forecast category from the regression equations, one for each forecast category:

 $F_i = a_{0i} + a_{1i} x_1 + \dots + a_{ni} x_n; i = 1, 2$

The F_i 's are the forecast indices for each ceiling category: F1 for ceilings less than or equal to 1000 ft and F2 for ceilings greater than 1000 ft, for example. The a_i represent the regression coefficients and the x_i represent the 0,1 dummy variables. Although more than two ceiling categories can be selected, greater skill results when only two are used.

 F_i resembles a probability in two ways: $F_1+F_2 = 1$; and a larger F_i means that state i is more likely. However individu F_i are not bounded by 0 and 1. Therefore F_i is not rigorousl probability and will be referred to as a forecast index.

An additional characteristic of REEP is that since the x equal 0 or 1, the magnitude of the aij directly show the pred. tors relative influence on the index value.

2.2 LOGISTIC REGRESSION (LR)

Consideration of a forecast parameter which has the properties of a probability leads to the following (logistic) transformation;

$$\theta_{i} = \frac{e^{\lambda_{i}}}{1 + e^{\lambda_{i}}} \qquad i = 1, 2$$

where

 $\lambda_{i} = \sum_{j=1}^{N} a_{ij} x_{j}; N = No. of predictors$

and

$$\ln \left(\frac{\theta_{i}}{1-\theta_{i}}\right) = \lambda_{i}$$

is called the log-odds ratio.

Now $0 \le \theta_1 \le 1$ and $\theta_1 + \theta_2 = 1$, therefore θ satisfies the probability properties.

The coefficients a_{ij} are found from applying regression techniques to the dependent data sample (see Dixon, 1981). The advantage of LR is that continuous variables can be used without first categorizing; also, categorical variables can be used directly without transformation. However, only binomial predictands are allowed.

Predictor selection is based on a statistical stepwise procedure called asymptotic covariance estimate. An explanation of this procedure is beyond the scope of this report, and the reader is referred to Dixon, 1981, for information.

3. RESULTS

3.1 COMPARISONS OF REEP AND LR AT MOFFETT NAS

The REEP and LR equations are given in Appendices A and B, respectively, for ceilings 1000 ft and 2000 ft.

Five forecast valid times (VT) were selected for this pilot study; a common forecast generation time of 1800 LST allowed use of the 0000 GMT Oakland radiosonde data, and also was a time prior to stratus formation. The equations for REEP were generated from ten years of data; the equations for LR were generated from seven years of data.

Tables 1 and 2 show percent correct and threat scores for REEP, LR, and climatology for the dependent and independent data samples, respectively.

Threat score is defined as

TS = A/(A+B+C) where

A is the number of correct stratus forecasts, B is the number of incorrect non-stratus forecasts, and C is the number of incorrect stratus forecasts.

	Table	1.	Dependent	data	comparisons.
--	-------	----	-----------	------	--------------

a. Ceiling <2000 Ft

Per	rcent Co	rrect	Th	reat Sco	re
REEP	LR	CLIMU	REEP	LR	CLIMO

.47

.46

.04

.08

.13

.16

.16

VT	REEP	LR	CLIMO	REEP	LR	CLIMO
2200	88	83	88	.34	.37	.06
2400	77	83	72	.24	•55*	.16
0200	77	82	67	.57	.59	.20
0400	75	78	50	.61	.57	.28
0600	78	77	56	.64	•58	.28

b. Ceiling <1000 Ft

78

0600

Percent Correct Threat Score CLIMO REEP LR CLIMO REEP LR VΤ 2200 92 92 .25 .23 82 .32 .46* 85 2400 85 85 .51 .55 77 0200 84 84 .48 .51 73 0400 81 80

72

77

	lable 2	• Inde	Penden			JU UDSEI	vacions)
a.	Ceili	ng <u><</u> 2000	Ft				
		Pe	rcent	Correct	Т	hreat Sc	ore
	VΤ	REEP	LR	CLIMO	REEP	LR	CLIMU
	2200	88	82	87 ,	.34	.37	.07
	2400	78	82	75	.27	.57*	.14
	0200	76	80	63	.54	.60	.22
	0400	75	68	57	.62	.42	.27
	0600	74	76	52	.57	.62	.32
ь.	Ceili	ng <u><</u> 1000	Ft				
		Ре	rcent	Correct	T	hreat Sc	ore
	VT	REEP	LR	CLIMO	REEP	LR	CLIMO
	2200	91	90	92	.24	.09*	.04
	2400	86	84	86	.24	.47*	.07
	0200	72	78	76	.38	.50	.14
	0400	75	62	70	.38	.43	.18
	0600	70	70	69	.38	.47	.18

Independent data comparisons (200 observations). Table 2

Given this relationship, $0 \le TS \le 1$ with TS = 1 represents a perfect score while TS = 0 indicates a no-skill score.

For ceilings ≤ 2000 the percent correct comparisons show both REEP and LR are better than climatology for the last four valid times (VT). LR also seems to be slightly better than REEP. For ceilings ≤ 1000 ft, however, no clear advantage can be seen for either method.

The threat score comparisons show both REEP and LR have definite skill over climatology*, with the exception of the 2200 VT LR in Table 2b. A contingency table for 2200 VT LR can be shown as

Forecast

Ceiling Ceiling

Observat	ion		<u><</u> 1000 Ft	>1000 Ft	Tota]
Ceiling	<u><</u> 1000	Ft	2	14	16
Ceiling	<u>></u> 1000	Ft	6	178	184
Total			8	192	200

With the exception of the LR threat score for the 2200 VT in Table 2b, the only LR scores significantly better than REEP (5% chi square test) are for the 2400 VT forecast. This exception is easily explained: the above tabulation shows a small number of observed ceilings ≤ 1000 ft; therefore, a small fluctuation in the number of correct low ceiling forecasts can account for the low threat score for the 2200 VT LR forecast in Table 2b.

^{*}Climatology threat score = P/(2-P) where P is the climatological probability.

The explanation for the universally better 2400 VT LR threat scores is not so clear. With the exception of Table 2b, the REEP 2400 VT scores seem inconsistent with the other REEP threat scores. As the valid time increases, the frequency of low ceilings increases. The threat scores characteristically become larger with increasing relative frequency. This trend in REEP threat score is not followed at the 2400 VT, even though the relative frequencies are nearly double those of 2200 VT.

It must be assumed that the data used for REEP equations had some anomalous characteristic at the 2400 observation; the 2400 VT equations therefore will not be considered in this comparison.

The following conclusions can be drawn for the REEP/LR comparison at Moffett NAS:

(1) Percent correct scores show that both REEP and LR are better than climatology, except for the 2200 VT forecasts.

(2) Threat scores are clearly better for both REEP and LR as compared to climatology.

(3) After the 2400 VT forecast is eliminated, REEP and LR show about the same skill scores.

3.2 REEP OPERATIONAL EVALUATION AT MOFFETT NAS

REEP operational evaluation results are given in Appendix A. REEP was used since Moffett did not have the LR program available at the time of the study. The subjective conclusions of the evaluation were (1) Reep was easy to use; (2) REEP has a skill about equal to that of an experienced forecaster; and (3) REEP does not improve a good forecaster's skill. (Close data examination reveals inconsistencies which cannot be completely resolved with the existing data; see Appendix 1.)

3.3 LR RESULTS FOR NORTH ISLAND, MIRAMAR AND SAN NICOLAS NAS

Appendices C, D, E give the LR equations for North Island, Miramar, and San Nicolas NAS.

Tables 3 through 5 give the dependent, independent and climatology skill scores for the three NAS.

	Tab	le 3a	. North	Island -	ceili	ng <u>≺</u> 3500	Ft.
	Percent	Correct		Thr			
LST	DEP	IND	CLIMO	DEP	IND	CLIMO	Relative Frequency
1900	67	72	62	.49	.52	.23	.38
0100	75	79	67	.73	.76	• 50 [.]	.67
0700	84	74	76	.83	.74	.61	.76

Table 3a shows that (1) threat scores are better than climatology; (2) threat scores increase with lead time; (3) percent correct is not significantly better than climatology; and (4) relative frequency increases with lead time.

Table 3b reveals the same information as Table 3a, with the exception of point 3). In fact, percent correct overall is not as high as climatology, which clearly diminishes the forecast's worth despite of the better threat scores.

Table 3b. North Island - ceiling <1000 Ft.

	Percent	Corr	ect	Threat Score						
LST	DEP	IND	CLIMO	DEP	IND	CLIMO	Relative Frequency			
1900	90	80	93	.29	.10	.04	.07			
0100	73	57	76	.38	.34	.14	.24			
0700	69	64	70	.43	.36	.18	.30			

Tables 4a and 4b show that (1) threat scores are better than climatology; (2) percent correct about the same as climatology; (3) relative frequencies for the 0100 LT and 0700 LT forecasts are about the same; and (4) threat scores for 0100 LT and 0700 LT forecast are about the same.

Table 4a. Miramar - ceiling <3500 ft.

	Percent	Corre	ect	Threat Score						
LST	DEP	IND	CLIMO	DEP	IND	CLIMO	Relative Frequency			
1900	76	82	72	.46	.58	.16	.28			
0100	76	76	64	.71	.72	.47	.64			
0700	79	75	69	.77	.72	.53	.69			

Table 4b. Miramar - ceiling <u><</u>1000 ft.

	Percent	Corre	ect		Threa	at Score	
LST	DEP	IND	CLIMO	DEP	IND	CLIMO	Relative Frequency
1900	86	90	92	.17	.26	.04	.08
0100	66	65	61	.51	.52	.24	.39
0700	61	56	62	.50	.47	.23	.38

In Tables 4a and 4b the scores for the LR again shows considerable skill over climatology. However, the similar percent correct for the two LR samples and climatology points out a weak overall forecast skill.

Tables 5a and 5b show that (1) threat scores are consistently higher than climatology; (2) percent correct is better than climatology, but lower than for the other three NAS; and (3) relative frequencies are higher for San Nicolas than for North Island or Miramar.

Table 5a. San Nicolas - ceiling ≤3500 ft.

Percent Correct			Threat Score			
DEP	IND	CLIMO	DEP	IND	CLIMO	Relative Frequency
73	71	61	.69	.68	.43	.61
76	73	68	.73	.70	.51	.68
81	80	76	.80	.80	.61	.76
	Percent DEP 73 76 81	Percent Corro DEP IND 73 71 76 73 81 80	Percent Correct DEP IND CLIMO 73 71 61 76 73 68 81 80 76	Percent CorrectDEPINDCLIMODEP737161.69767368.73818076.80	Percent Correct Three DEP IND CLIMO DEP IND 73 71 61 .69 .68 76 73 68 .73 .70 81 80 76 .80 .80	Percent Correct Threat Score DEP IND CLIMO DEP IND CLIMO 73 71 61 .69 .68 .43 76 73 68 .73 .70 .51 81 80 76 .80 .80 .61

Table 5b. San Nicolas - ceiling <1000 ft.

Percent Correct				Threa	at Score		
LST	DEP	IND	CLIMO	DEP	IND	CLIMO	Relative Frequency
1900	69	69	58	.52	.59	.27	.42
0100	68	68	53	.56	.60	.31	.47
0700	67	64	52	.55	.55	.32	.48

Because of point (3) relative to Tables 5a and 5b, very little variation occurs between the dependent and independent samples scores. This fact suggests that the equation's skill merely reflect the underlying climatology, and that differences between dependent and independent samples imply climatological differences in the samples themselves.

4. CONCLUSIONS AND RECOMMENDATIONS

Short-range stratus ceiling forecast equations were generated at four naval air stations on the California coast using logistic regression (LR) probabilities. A second statistical technique -- regression estimates of event probabilities (REEP) -- was used to develop Moffett NAS forecast equations. These equations were evaluated operationally at Moffett; when the logistic program became available later, they were compared to LR.

4.1 CONCLUSIONS

The REEP operational evaluation at Moffett indicated that although the technique has definite skill, the experienced forecaster could do as well not using it as an inexperienced forecaster could do using it. The concensus at Moffett was that REEP would be helpful to new duty forecasters, but that they would place less reliance on REEP after they gained more experience. The primary shortfall of both REEP and experienced forecasters lay in forecasting the transition from stratus to non-stratus sequence, and vice versa.

The REEP-LR comparison at Moffett showed essentially no difference in the two skill scores. Both were significantly better than climatology in the th Bat score comparisons, but only marginally better in most percent-correct comparisons.

The LR equations for the three Southern California stations -- given in Appendices C, D and E -- yield unimpressive results. The threat scores were universally better than climatology, but the percent-correct scores were marginal, with some better and some worse than climatology.

Overall, the study's results indicate that the statistical forecast techniques are only marginally useful as forecasting tools in the particular applications investigated here. Certainly climatology can not be viewed as wholly valid competition, insofar as the actual competition for any forecast procedure would be the operational forecaster's skill scores (none available for this pilot study).

The stations do not have a universal forecast verification procedure; each office sets its own, and apparently can revise it at will. It becomes very difficult, therefore, to test a forecast procedure for operational usefulness when no long-term and rigorous skill scores exist for comparison.

At locations such as foreign coastal regions where there is archived data but no U.S. forecast experience, techniques like REEP or LR obviously would be useful. Two criteria must be met, however: (1) the location must have about 10 years of data available, and (2) the selected forecast parameters must have a significant dependency on local surface conditions. If the desired forecast parameter were rainfall intensity, then clearly these procedures would be useless. Parameters such as surface winds and visibility, however, would conceivably be candidates for such autonomous statistical procedures.

4.2 RECOMMENDATIONS

Based on the information and experience developed during the pilot study, the following are recommended:

(1) Establish universal forecast verification procedures at each NAS forecast office. These procedures should not be based only on simple percent correct (since such scores can be very misleading by themselves), but upon threat scores, Heidke skill scores, and meaningful forecast parameters such as ceiling height.

(2) Compile and archive verification statistics so that prospective forecast techniques can be compared prior to operational evaluation. The operational evaluation should be performed mainly to iron out any implementation problems and special situation difficulties.

(3) After a period of time, conduct a survey to determine areas of potential improvement in forecasts.

REFERENCES

Miller R. G., 1979: Conditional climatology given the local observation, <u>Nat. Wx. Digest</u>. 4, 4.

______, 1964: Regression estimates of event probabilities. Tech. Report 7411-121 Contract Pub. 10704, Travelers Research Center, Inc., Hartford, CT.

Dixon, W. J. (Ed.), 1981: BMDP statistical software. Dept. of Biomath, UCLA, Los Angeles, CA.

APPENDIX A

EVALUATION OF REEP EQUATIONS AT MOFFETT NAS

A.1 RESULTS

Ceiling forecasts for 2200, 2400, 0200, 0400 and 0600 local time (LT) were developed for Moffett using regression estimates of event probabilities (REEP). The complete set of equations is given in Section A.2. Forecasts for ceilings above or below 1000 ft are generated using 1800 LT observations and Oakland 0000 GMT (1600 LT) radiosonde data. The ceiling forecasts are limited to the June-September period of summer coastal stratus occurrence at this location.

The evaluation began in June 1982 and used the forecast packet reproduced as Section A.3. Beginning in July with the arrival of a HP-41CV calculator and printer, the forecast procedure was automated and run on the calculator. An output example appears in Figure A-1.

Each day the duty forecaster recorded these forecasts and verifications for the previous day. Also noted was whether REEP was used alone or with additional guidance, or the forecast was based solely on other guidance. Tables A-1 and A-2 provide these records.

Table A-1. Moffett stratus forecast.

Forecast Made	REEP Alone	REEP and Other	Other
A11	99%	83%	57%
Stratus	*	46%	44%
*None obse	rved		

NEPRONT FORECAST FOF 2000FT 15 0.04 VERIFY PERCENT 15 95. 0600GHT FOFECPET FOR 1000FT IS 0.05 VERIFY PERCENT IS SE. 0800GHT FORECAST FOR 2000FT IS -0.08 VERIFY PERCENT 18 92. 0800CMT FORFCAST FOR 1000FT 19 8.0-VERIFY PEPCENT 13 97. 1000GMT FORECAST FOF 2000FT 18 0.21 VERIFY PERCENT IS 89. 1000GHT FORECAST FOR 1000FT IS 0.11 VERIFY PERCENT 15 98. 1200GMT FORESAST FOR 2000FT 15 0.52 VERIFY PERCENT 15 44. 1200GMT FORECAST FOR 1000FT IS -0.04 VERIFY PERCENT 15 93. 1400GMT FORTCHET FOR 2000FT 11 2.23 VERIFY PERCENT IS 74. 1400GMT FORECRET FOR 1000FT 15 0.22 VERIFY PERCENT 19 94.

Figure A-1. HP-41CV output for 13 August 1982 giving \leq 2000 ft and \leq 1000 ft forecasts for all five forecast times.

Table A-2. Percent correct forecasts (forecaster "agreed" or "disagreed" with REEP).

Forecast Made	Agreed	Disagreed
Non-stratus	99.5%	*
Stratus	83%	24%
*None observed		

Table A-1 gives the verification summary for the two types of forecasts. For "all" forecasts, REEP apparently was superior. For the non-stratus, no clear advantage resulted. The low score for the "stratus" forecasts compared to the "all" forecasts results from the difficulty of forecasting the stratus event. Long periods of clear weather were followed by short periods of stratus, and the initiation of such stratus periods is difficult to forecast.

Due to the long-running clear sequence, the persistence factor tends to influence the forecaster. During obvious clear spells, the forecaster is more likely to go with REEP alone. There also seemed to be some forecasters during the study who never trusted REEP and always indicated that they used additional guidance. This could easily contribute to the 83%-57% advantage over the "other" category.

The results in Table A-2 are a little harder to explain in the light of the unenthusiastic response related verbally by forecasters. The somewhat small sample size may have had some effect, but a complete explanation is unknown.

A.2 MOFFETT REEP EQUATIONS

The equations are functions of binary predictor variables X_i , whose values are "1" if the variable is in the given range and "0" otherwise. The X_i are listed at the end of this section.

Forecast Equations - Ceiling <1000'

Valid Time

```
2200 LT
```

 $F = .469 + .183 \times - .254 \times 15 - .141 \times 4$

2400 LT

 $F = .245 + .325 \times - .245 \times 4 + .107 \times 19$

+ .096X20+.075X23-.146X15-.104X9

0200 LT

 $F = .379 + .352 \times - .272 \times 6 + .173 \times 20 - .141 \times 24 - .099 \times 22$

0400 LT

 $F = .325 + .414 \times - .240 \times 7 + .230 \times 20$

-.257X24-.095X22-.153X18-.121X26

-.248X₂₅

0600 LT

 $F = .476 - .257X_{8} + .273X_{8} - .071X_{22}$

+.212X20-.167X24

Forecast Equations - Ceiling $\leq 2000^{\circ}$ 2200 LT F = .542+.301X.-.348X₁₆-.155X₁₀ 2400 LT F = .165+.508X.-.338X₁₆+.220X₂ -.129X₁₁+.110X₁₇+.131X₁₉ 0200 LT F = .224+.694X.+.212X₂₀-.200X₁₂+.185X₂ 0400 LT F = .311+.544X.+.286X₂₀+.248X₂ -.130X₁₃-.121X₃+.089X₂₁+.116X₁₉ 0600 LT F = .316+.685X.+.186X₂₀-.162X₁₄

```
-.100X13-.124X22+.132X2
```

List of Predictors (1800 LT observation unless specified) At Moffett

\mathbf{x}_{1}	Ħ	Dew point depression (O-8°F)	
X 2	Ŧ	Dew point depression (8-10°F)	
x ₃	=	Dew point depression (<u>></u> 14°F)	
X 4	=	Previous Day's Ceiling (\geq 1000') at 2200 LT	
×5	=	Previous Day's Ceiling (≥1000') at 2400 LT	
X 6	z	Previous Day's Ceiling (\geq 1000') at 0200 LT	
X ₇	=	Previous Day's Ceiling (\geq 1000') at 0400 LT	
X8	z	Previous Day's Ceiling (\geq 1000') at 0600 LT	
X9	=	Wind Speed (O-6 kt)	
X10	=	Previous Day's Ceiling (≥2000°) at 2200 LT	
\mathbf{x}_{11}	=	Previous Day's Ceiling (≥2000°) at 2400 LT	
X12	2	Previous Day's Ceiling (\geq 2000°) at 0200 LT	
× ₁₃	=	Previous Day's Ceiling (≥2000°) at 0400 LT	
X14	2	Previous Day's Ceiling (≥2000°) at 0600 LT	

At Alameda

 X_{15} = Ceiling (\geq 1000') X_{16} = Ceiling (\geq 2000') X_{17} = Dew Point Depression (0-8°F) X_{18} = Dew Point Depression (\geq 14°F) X_{19} = Wind Speed (12-15 kt)

At San Francisco

 X_{20} = Dew Point Depression (0-8°F) X_{21} = Wind Direction (282-326) X_{22} = Wind Direction (237-281) Oakland Radiosonde (0000 GMT)

· · ·

. 7

· •

4 **4** 1

۰.

. ·

. •

X₂₃ = Temperature, 950 mb (20-25°C)
X₂₄ = Temperature, 950 mb (10.1-15.5°C)
X₂₅ = Temperature, 950 mb (<10°C)
X₂₆ = Temperature, 950 mb (15.6-20°C)

A.3 SAMPLE FORECAST PACKET USED AT MOFFETT NAS

MOFFETT STRATUS FORMATION FORECAST AID (SUMMER)

The following computation is meant as a forecast aid for a summer stratus formation forecast. It provides guidance for the stratus formation forecast which should then, at the forecaster's discretion, be supplemented by other information.

The computation uses the 0200GMT observations of Moffett, Alameda and San Francisco, and the 0000 GMT Oakland 950mb temperature data. Also used are "persistence" ceilings from the previous day at Moffett. Five forecast valid times (VT) are 0600GMT, 0800GMT, 1000GMT, 1200GMT, 1400GMT, which are referred to as computations A through E.

Each computation produces a number index, which falls ideally in an interval 0.0 to 1.0, however, negative numbers and numbers larger than 1.0 do occur. The forecast index, therefore, extends below 0.0 and above 1.0, which indicates lower and higher "probabilities" respectively. Two forecast indices are computed for each valid time, one for ceilings $\angle 2000$ ' and one for ceilings $\angle 1000$ '.*

Following the computation for each forecast valid time is a suggested use of the indices and the interface with satellite and synoptic information. Forecasters may develop their own interface with such subjective factors.

The percentages appearing on the right of the "Forecast" column are the verification frequencies (i.e., the percentage of the time the forecast was incorrect in the developmental data).

* SYMBOLS			
∠- Less than			
∠- Less than or equal to			
➤ - Greater than			
7 - Greater than or equal to			

The following data will be needed.

Moffett (surface)

Dew point depression	(0200GMT)
Wind Speed	(0200GMT)
Previous day's ceiling	(0600, 0800, 1000, 1200, & 1400GMT)

San Francisco (SFO) (surface)

Wind	l direc	tion	(0200GMT)
Dew	point	depression	(0200GMT)

Alameda (surface)

Dew point depression	(0200GMT)
Wind speed	(0200GMT)
Ceiling	(0200GMT)

Oakland (upper air)

Temperature 950mb (0000GMT)

SHEET A

MOFFETT STRATUS FORMATION FORECAST VALID TIME: 0600 GMT

Computation for ceiling < 2000'

If the following parameters fall within the indicated ranges, add or subtract the number appearing on the right.

1.	Start with	.542
2.	Moffett dew. pt. dep. (0.0-8.0°F) (0200 GMT) .301	
3.	Alameda ceiling (≥2000?) (0200GMT)348	
4.	Moffett previous days ceiling: 0600GMT (≥2000')155	
	Index (TOTAL)	

If index is:

Forecast

≤ .30	Do <u>not</u> forecast stratus (<2000')	2%
.31 to .40	Do <u>not</u> forecast stratus unless other indications strongly differ	24%
.41 to .80	Need additional guidance from other indications	438
> .80	Forecast stratus (<2000')	164

Enter the forecast category (stratus/no stratus) on the final forecast sheet P.

MOFFETT STRATUS FORMATION VALID TI	ME: 0600GMT	
Computation for: Ceilings 41000'		
If the following parameters fall w	ithin the indicated rang	es, add or
subtract the numbers appearing on	the right.	
1. Start with		.469
2. Moffett dew. pt. dep. (0.0-8.0	°F) (0200GMT) .183	
3. Alameda ceiling 21000' (0200	GMT)253	
4. Moffett previous days ceiling:	0600GMT (Z1000')141	
	Index (TOTAL)	
If index is:	Forecast	

<u>4</u> . 30	Do not forecast stratus (<1000') 4	ŝ
.31 to .40	Do not forecast stratus unless other indicators differ 28	è
.41 to .70	Need additional guidance 54	È
7.70	None occurred	

Enter forecast on sheet F.

Cont. A

Sheet B

MOFFETT STRATUS FORMATION FORECAST VALID TIME: 0800GMT

Computation for ceilings 22000'

If the following parameters fall within the indicated ranges, add or subtract the number appearing on the right.

1.	Start with	.165
2.	Moffett dew. pt. dep. (0.0-8.0°F) (0200GMT) .508	•
3.	Moffett dew. pt. dep. (8.1-10.0°F) (0200GMT) .220	•••••
4.	Alameda ceilings (22000') (0200GMT)338	
5.	Moffett previous days ceilings at 0800GMT (≥2000')129	
6.	Alameda dew. pt. dep. (0.0-8.0°F) (0200GMT) .110	
7.	Alameda wind speed: (12-15kts) (0200GMT) .131	
	Index (TOTAL)	

If index is:	Forecast	
∠.10	Do <u>not</u> forecast stratus (<2000')	88
.11 to .60	Need additional guidance	52%
.61 to .70	Forecast stratus (4 2000') unless other indications strongly differ	248
7.70	Forecast stratus (22000')	78
Paken ferrerah an abaah	P	

Enter forecast on sheet F.

COLC. D	Con	t.	B
---------	-----	----	---

MOFFETT STRATUS FORMATION FORECAST VALID TIME: 0800GMT Computation for ceiling <1000' If the following parameters fall within the indicated ranges, add or subtract the numbers appearing on the right.

1. Start with

2.	Moffett dew. pt. dep. (0.0-8.0°F) (0200GMT)	.325	
3.	Moffett previous days ceiling at 0800GMT (21000	')244	
4.	SFO wind direction (282° - 8.0°F) (0200GMT)	.107	
5.	SFO dew. pt. dep. (0.0-8.0°F) (0200GMT)	.096	
6.	Oakland 950mb temp. (20-25°F) (0000GMT)	.075	
7.	Alameda ceiling (Z 1000') (0200GMT)	146	
8.	Moffett wind speed (0-6kts) (0200GMT)	104	

.245

If index is:	Forecast	
∠. 20	Do <u>not</u> forecast stratus (<1000')	3%
.21 to .49	Do not forecast stratus (<1000') other indicators differs	unless 34%
.50 to .60	Need addition guidance	498
.61 to .80	Forecast stratus (41000') unless indicators differ	other 35%
7.80	Forecast stratus (21000') (O	for 4)

Enter forecast on sheet F.

Sheet C

MOFFETT STRATUS FORMATION FORECAST VALID TIME: 1000GMT

Computation for ceilings 42000'

If the following parameters fall within the indicated ranges, add or subtract the numbers on the right.

1.	Start with	.224
2.	SFO dew. pt. dep. (0.0-8.0°F) (0200GMT) .212	
3.	Moffett previous days ceiling at 1000GMT (22000')200	
4.	Moffett dew. pt. dep. (8.1-10.0°F) (0200GMT) .185	
5.	Moffett dew. pt. dep. (0.0-8.0°F) (0200GMT) .694	
	Index (TOTAL)	

If index is: Forecast ∠.30 Do not forecast stratus (2000') 118 .31 to .40 None occurred .41 to .50 Do not forecast unless other indicators differ 381 .51 to .70 Forecast stratus unless other indicators differ 391 Forecast stratus (22000') unless other 7.70 indicators strongly differ 261

Enter forecast on sheet P.

Cont.	С	
-------	---	--

 MOFFETT STRATUS FORMATION FORECAST VALID TIME: 1000GMT

 Computation for ceilings <1000'</td>

 If the following parameters fall within the indicated ranges, add or

 subtract the numbers on the right.

 1. Start with

 2. Moffett dew. pt. dep. (0.0-8.0°F) (0200GMT)

 3. Moffett 1000GMT ceiling previous day \$1000')

 -.272

 4. SFO dew. pt. dep. (0.0-8.0°F) (0200GMT)

 5. Oakland 950mb temp. (10.1-15.5°F) (0000GMT)

 6. SFO wind direction (237°-281°) (0200GMT)

Index (TOTAL)

If index is:

Forecast

≰.20	Do <u>not</u> forecast stratus <1000'	28
.21 to .40	Do not forecast stratus <1000' unless other indicators strongly differ	20%
.41 to .50	Do not forecast stratus <1000' unless other indicators differ	248
.51 to .60	Forecast stratus <1000' unless other indicators differ	418
.61 to .80	Need additional guidance	498
>.80	Forecast stratus <1000' unless other indicators differ	23%

Enter forecast on sheet F.

SHEET D

MOFFETT STRATUS FORMATION FORECAST VALID TIME: 1200GMT

Computation for ceilings <2000'

If the following parameters fall within the indicated ranges, add or subtract the numbers on the right.

Start with 1. .311 2. Moffett dew. pt. dep. (0.0-8.0°F) (0200GMT) .544 3. Moffett dew. pt. dep. (>14.0°F) (0200GMT) -.121 Moffett dew.pt. dep. (8.1-10.0°F) (0200GMT) 4. .248 Moffett previous days ceiling at 1200GMT (≥2000') -.130 5. SFO wind direction (282°-326°) (0200GMT) 6. +.089 SFO dew. pt. dep. (0.0-8.0°F) (0200GMT) 7. .286 8. Alameda wind speed (12-15kts) (0200GMT) .116 Index (TOTAL) If index is: Forecast

≤.30 Do not forecast stratus <2000' 81 .31 to .40 Do not forecast stratus unless other 16% indicators strongly differ .41 to .49 Do not forecast stratus unless other 261 indicators differ .50 to .90 Additional guidance needed 56% >.90 Forecast stratus (< 2000') 15%

Enter forecast on sheet F.

Cont. D

MOFFETT STRATUS FORMATION FORECAST VALID TIME: 1200GMT Computation for ceiling <1000'

If the following parameters fall within the indicated ranges, add or subtract the number on the right.

1.	Start with		.325
2.	Moffett dew. pt. dep. (0.0-8.0°F) (0200GMT)	.414	
3.	Moffett previous days 1200GMT ceiling: (21000')	240	·····
4.	SFO dew.pt.dep. (0.0-8.0°F) (0200GMT)	.230	
5.	SFO wind direction (237°-281°) (0200GMT)	095	
6.	Alameda dew.pt. dep. (>14.0°F) (0200GMT)	153	
7.	Oakland 950mb temp. (15.6-20.0°F) (0000GMT)	121	
8.	Oakland 950mb temp. (<10.0°F) (0000GMT)	248	
9.	Oakland 950mb temp. (10.1-15.5) (0000GMT)	257	
	Index (TOTAL)		

If index is:	Forecast	
<u>≤</u> .30	Do not forecast stratus <1000'	7 %
.31 to .40	Do not forecast stratus <1000' unless other indicators differ	36%
.41 to .70	Additional guidance needed	498
.71 to .90	Forecast stratus <1000' unless other indicators differ	338
>.90	Forecast stratus <1000'	15%

Enter forecast on sheet F.

Sheet E

MOFFETT STRATUS FORECAST VALID TIME: 1400GMT

Computation for ceilings <2000'

If the following parameters fall within the indicated ranges, add or subtract the number on the right.

1.	Start with		.316
2.	SFO dew. pt. dep. (0.0-8.0°F) (0200GMT)	.186	
3.	Moffett previous days ceilings: 1400GMT (≥2000')	162	
4.	SFO wind direction (237°-281°) (0200GMT)	124	
5.	Moffett dew. pt. dep. (8.0-10.0°F) (0200GMT)	.132	
6.	Moffett dew. pt. dep. (0.0-8.0°F) (0200GMT)	.685	
7.	Moffett dew. pt. dep. (>14.0°F) (0200GMT)	100	
	Index (TOTAL)		

If index is:	Forecast	
≤.20	Do <u>not</u> forecast stratus <2000'	12%
.21 to .30	Do not forecast stratus <2000' unless other indicators <u>strongly</u> differ	26%
.31 to .60	Additional guidance needed	488
.61 to .80	Forecast stratus <2000' unless other indicators strongly differ	208
.81 to .90	Additional guidance needed	52%
>.90	Forecast stratus <2000'	15%

Enter forecast on sheet F.

Cont. E

MOFFETT STRATUS FORMATION FORECAST VALID TIME: 1400GMT Computation for ceilings <1000' If the following parameters fall within the indicated ranges, add or subtract the number on the right. .476 Start with 1. 2. Moffett previous days ceiling, 1400GMT (≥1000') -.257 _____ 3. Moffett dew. pt. dep. (0.0-8.0°F) (0200GMT) .273 4. SFO wind direction (237°-281°) (0200GMT) -.071 ____. 5. SFO dew. pt. dep. (0.0-8.0°F) (0200GMT) .212 _____ 6. Oakland 950mb temp. (10.1-15.5°F) (0000GMT) -.167 Index (TOTAL)

If index is:	Forecast	
≤ .40	Do <u>not</u> forecast stratus <1000'	68
.41 to .49	Do not forecast stratus <1000' unless other indicators differ	33%
.50 to .89	Additional guidance needed	4 6%
> .90	Forecast stratus <1000'	20%

Enter forecast on sheet F.

Sheet F

VALID TIMES	FORECAST (< 2000')	FORECAST (< 1000')
0600GMT	······································	
0800GMT		
1000GMT	·	
1200GMT		
1400GMT		

REMARKS:

- 1. Check continuity of ceiling forecast throughout the period.
- Check for ridiculous results, example: Do not forecast ceiling <1000', without also forecasting ceiling <2000' for the same valid time.

APPENDIX B

LOGISTIC REGRESSION EQUATIONS FOR MOFFETT NAS

The logistic transformation is

$$\theta_{i} = \frac{e^{s_{i}}}{1+e^{s_{i}}} \quad i = 1, 2$$

where θ_1 is the probability of low ceilings and $\theta_2 = (1 - \theta_1)$ is the probability of higher ceilings.

$$s_{i} = \sum_{j=1}^{N} A_{ij} X_{j}$$

 χ_j are the predictor variables and the Aij are the constants found by using regression on the dependent data sample. The list of candidate predictors and forecast equations are given on succeeding pages.

List of Variables

Xl	=	East-west component, Moffett wind (kt)
×2	=	North-south component, Moffett wind (kt)
X3	=	Moffett air temperature (°F)
x ₄	=	Moffett dew point depression (°F)
X 5	=	Ceiling (F.T. minus 24 hrs) Moffett (Ft)
× ₆	=	Alameda Ceiling (Ft)
X 7	=	East-west component, Alameda wind (kt)
x ₈	=	North-south component, Alameda wind (kt)
X 9	=	Alameda air temperature (°F)
x_{10}	=	Alameda dew point depression (°F)
X11	=	San Francisco (SFU) ceiling (Ft)
x_{12}	=	East-west component, SFO wind (kt)
X13	=	North-south component, SFO wind (kt)
× ₁₄	=	SFO air temperature (°F)
X15	=	SFO dew point depression (°F)
X ₁₀	=	Marine layer thickness (m)
X 1 7	=	Marine layer strength *
× ₁₈	=	700 mb temperature (°C)
X19	=	700 mb wind direction (0-90°)
× ₂₀	=	700 mb wind direction (90-180°) Binary variables
X21	=	700 mb wind direction (180-270°)
× ₂₂	=	700 mb wind direction (270-360°)
X23	=	700 mb wind speed (kt)
x_{24}	=	850 mb temperature (°C)

^{*}Defined as the average relative humidity from the surface to the marine layer top.

Forecast lquations Ceiling <u><</u>1000′

Valid Time 2200 LT $S = 15.319 + .134X_1 - .096X_{2} - .167X_3$ $-.100 \times 4 - .634 \times 10^{-3} \times 5^{-} .816 \times 10^{-3} \times 6$ +.068X7-.105X8-.471X9+.243X10 +.056X12+.416X14-.615X15+.010X18 $-.651X_{19}+.038X_{20}+.526X_{21}-.069X_{23}$ 2400 LT $S = 6.210 + .113X_1 - .058X_{2-}.296X_4$ $-.846 \times 10^{-3} \times 5^{-} \cdot 592 \times 10^{-3} \times 6^{+} \cdot 068 \times 7$ -.170Xg+.109X11-.194X15+.006X17 0200 LT $S = 7.461 + .083X_{1} - .196X_{4} - .510X_{10} - 3X_{5}$ +.086X7-.343X9+.191X10+.241X14 $-.499X_{15}-.633X_{19}+.023X_{20}+.320X_{21}$ $+.013X_{24}$ 0400 LT $S = 6.093 + .061 X_{1} - .196 X_{4} - .510 X_{10} - 3 X_{5}$ $+.086 \times 7 - .343 \times 9 + .191 \times 10 + .241 \times 14$ $-.499 \times 15 - .633 \times 19 + .023 \times 20 + .320 \times 21$ +.013X24 0600 LT $S = 6.137 - .099 X_{4} - .717 X_{10} - 3 X_{5}$ +.079X7-.071X9-.056X12-.045X13 $-.199X_{15} - .623X_{19} - .239X_{20} + .656X_{21}$ +.007X24

Forecast Equations Ceiling <2000'

2200 LT $S = .801 - .133X_2 - .331X_4 - .603X_{10}^{-3}X_6$ -.112X8-.356X15+.008X24 2400 LT $S = .510 + .150X_1 - .073X_2 - .500X_4$ $-.797 \times 10^{-3} \times 5^{+} \cdot 104 \times 7^{-} \cdot 176 \times 8$ -.245X₁₅-.020X18-.154X23+.025X24 0200 LT $S = 2.045 + .126X_1 - .339X_4 - .645X_{10}^{-3}X_5$ -.151X8-.236X15-.563X19-.124X20 +.522X21-.077X23+.012X24 0400 LT $S = .993 + .091 X_1 - .283 X_4 - .487 X_{10} - 3 X_5$ -.076X8+.8898X10-3X11-.239X15 $-.529X_{19}-.088X_{20}+.605X_{21}-.069X_{23}$ +.014X240600 LT $S = -.100 - .185 X_{4} - .098 X_{13} - .172 X_{15}$

+.012X24

APPENDIX C

5

LUGISTIC REGRESSION EQUATIONS FOR NURTH ISLAND NAS

The regression equations for S follow from the list of candidate predictors below. Observation time is 1200 LT unless otherwise stated. See Appendix B for definition and use of S.

List of Predictors

м.	=	East-west component North Island wind (kt)
X 1	-	Last-west component, north Israna wind (kt)
×2	=	North-south component, North Island wind (kt)
X 3	=	North Island air temperature (°F)
x ₄	=	North Island dew point depression (°F)
X 5	=	Ceiling (FT minus 24 hrs) North Island (Ft)
× ₆	=	East-west component, Miramar wind (kt)
X 7	2	North-south component, Miramar wind (kt)
X ₈	=	Miramar air temperature (°F)
X 9	=	Miramar dew point depression (°F)
X ₁₀	=	East-west component. San Nicolas wind (kt)
10 X11	=	North-south component, San Nicolas wind (kt)
X12	-	San Nicolas air temperature (°F)
12	-	
X13	=	San Nicolas dew point depression (°F)
x_{14}	=	Marine layer height (m)
X15	=	Marine layer strength *
X ₁₆	=	700 mb temperature (°C)
X17	=	700 mb wind direction (degrees)

^{*}Defined as the average relative humidity from the surface to the marine layer top.

 χ_{18} = 700 mb wind speed (kt)

 $X_{19} = 850$ mb temperature (°C)

 χ_{20} = 850 mb wind direction (degrees)

 $X_{21} = 850$ mb wind speed (kt)

 χ_{22} = Marine layer height (Ft minus 24 hr) (m)

X₂₃ = Surface pressure difference, San Nicolas -North Island (mb)

```
X<sub>24</sub> = Surface pressure difference, Pt.Mugu -
North Island (mb)
```

Forecast Equations

Ceiling <1000′

Valid Time

1900 LT

 $S = -4.713 - .197X_{4} + .513X_{10} - 3X_{14}$

+.022X19

0100 LT

 $S = 1.624 + .080X_{1} - .091X_{3} - .107X4$ $- .005X_{15} + .026X_{19} - .325X_{10} - 3X_{22}$

0700 LT

```
S = 2.783 - .106X_{4} - .985X_{10} - ^{3}X_{5}- .003X_{15} + .015X_{19} + .295X_{10} - ^{3}X_{22}+ .046X_{24}
```

Forecast Equations

Ceiling <u>≺</u>3500'

Valid Time

1900 LT

 $S = 10.58 - .074X_1 - .122X_3 - .164X_4$

 $-.840 \times 10^{-3} \times 5^{+} \cdot 002 \times 15^{-} \cdot 043 \times 18$

0100 LT

 $S = 11.379 - .141 X_{3} - .081 X_{4}$

-.645X10-3X5+.013X16-.092X18

0700 LT

1

 $S = 9.817 + .055 X_1 - .140 X_{3} - .732 X_{10} - 3 X_5$

+.012X16-.087X18+.005X19

APPENDIX D

LOGISTIC REGRESSION EQUATIONS FOR MIRAMAR NAS

The regression equations for S (see Appendix B for details) follow from the list of predictors below. Observation time is 1200 LT unless otherwise stated.

 X_1 = East-west component, Miramar wind (kt) = North-south component, Miramar wind (kt) X 2 Xz = Miramar air temperature (°F) = Miramar dew point depression (°F) X۵ X۲ = Ceiling (FT minus 24 hrs) Míramar (Ft) = East-west component, North Island wind (kt) X 6 X_7 = North-south component, North Island wind (kt) = North Island air temperature (°F) X8 χ_9 = North Island dew point depression (°F) χ_{10} = East-west component, San Nicolas wind (kt) X_{11} = North-south component. San Nicolas wind (kt) X_{12} = San Nicolas air temperature (°F) X_{13} = San Nicolas dew point depression (°F) X_{14} = Marine layer height (m) X_{15} = Marine layer strength * χ_{16} = 700 mb temperature (°C) $X_{17} = 700$ mb wind direction (degrees)

*Defined as the average relative humidity throughout the marine layer.

PRECEDING PAGE BLANK-NOT FILMED

 χ_{18} = 700 mb wind speed (kt)

 $\chi_{19} = 850 \text{ mb temperature (°C)}$

 χ_{20} = 850 mb wind direction (degrees)

 $\chi_{21} = 850 \text{ mb wind speed (kt)}$

 χ_{22} = Marine layer height (Ft minus 24 hr) (m)

- X₂₃ = Surface pressure difference, San Nicolas -North Island (mb)
- X₂₄ = Surface pressure difference, Pt.Mugu -North Island (mb)

Forecast Equations

```
Ceiling <1000'
```

Valid Time

1900 LT

 $S = -1.608 - .201X_{4} - .018X_{16}$

+.020X19

0100 LT

 $S = 1.978 - .085 X_{4} - .465 X_{10} - 3 X_{5}$

 $+.043X_{18}+.016X_{19}+.053X_{24}$

0700 LT

 $S = -.553 - .077 X_{4} - .003 X_{15}$ $-.003 X_{15} P V + .015 X_{19} + .295 X_{10} - 3 X_{22}$ $+.046 X_{24}$

Forecast Equations

Ceiling <u>≺</u>3500'

1900 LT $S = 8.532 - .079X_{1} - .073X^{3}$ $-.217X^{4} - .850x1C - 3X5$ 0100 LT

$$S = 7.723 - .071X_{1} - .0713^{3} - .074X^{4}$$
$$- .667X10 - 3X5 + .010X16 - .101X18 - .296X22$$
$$+ .043X_{24}$$

0700 LT

$$S = 10.273 - .136X_{3} - .745X_{10} - 3X_{5}$$

-.102X18+.011X19

APPENDIX F

LUGISTIC REGRESSION EQUATIONS FOR SAN NICOLAS NAS

The regression equations for S (see Appendix B for details) follow the list of predictor variables. Observation times are 1200 LT unless otherwise stated.

 X_1 = East-west component, San Nicolas wind (kt) = North-south component, San Nicolas wind (kt) X2 χ_3 = San Nicolas air temperature (°F) = San Nicolas dew point depression (°F) X 4 X₅ = Ceiling (FT minus 24 hrs) Miramar (Ft) X6 = East-west component, Miramar wind (kt) X_7 = North-south component, Miramar wind (kt) χ_8 = Miramar air temperature (°F) χ_9 = Miramar dew point depression (°F) x_{10} = East-west component, North Island wind (kt) X_{11} = North-south component, North Island wind (kt) χ_{12} = North Island air temperature (°F) χ_{13} = North Island dew point depression (°F) χ_{14} = Marine layer height (m) X_{15} = Marine layer strength * χ_{16} = 700 mb temperature (°C) $X_{17} = 700$ mb wind direction (degrees)

*Defined as the average relative humidity throughout the marine layer.

FRECEDING PAGE BLANK-NOT FILMED

 $x_{18} = 700 \text{ mb wind speed (kt)}$

 $X_{19} = 850$ mb temperature (°C)

 χ_{20} = 850 mb wind direction (degrees)

 $X_{21} = 850$ mb wind speed (kt)

 χ_{22} = Marine layer height (Ft minus 24 hr) (m)

X₂₃ = Surface pressure difference, San Nicolas -North Island (mb)

X₂₄ = Surface pressure difference, Pt.Mugu -North Island (mb)

Forecast Equations

Ceiling <1000'

Valid Time

1900 LT

 $S = 8.924 - .227 X_{3} + .028 X_{19}$

0100 LT

 $S = 6.282 - .137 \times 3 - .001 \times 5 - .001 \times 14$

+.018X19

0700 LT

 $S = 8.434 - .163 X_3 - .001 X_{14}$

+.014X20+.432X23

Forecast Equations

```
Ceiling <3500'
```

1900 LT $S = 14.130 - .152 X_{16} - .249 X_8$ -.001X5+.001X14+.014X19+.047X24 0100 LT $S = 13.242 - .175 X_{3-.001 X_{5}}$ +.009X16-.167X18-.588X33 0700 LT $S = 8.970 - .093 X_{3} - .001 X_{5}$ -.118X18-.048X24 -.217X4-.850x10-3X5 0100 LT $S = 7.723 - .071X_{1} - .0713_{3} - .074X_{4}$ -.667X10-3X5+.010X16-.101X18-.296X²² +.043X24 0700 LT $S = 10.273 - .136 \times 3 - .745 \times 10 - 3 \times 5$

 $-.102 \times 18 + .011 \times 19$

DISTRIBUTION

ATTN: NSAP SCIENCE ADVISOR

ATTN: NSAP SCIENCE ADVISOR

CINCLANTFUT

NERFOLK, VA 23511

LODE NO4E

COMTHIRDFLT

COMMANDING OFFICER

U.S. ATLANTIC FLEET

NORFOLK, VA 23511

COMSEVENTHELT

ATTN: FLT METEOROLOGIST

COMSECONDFLT

COMSEVENTHELT

FPO NEW YORK 09501

ATTN: NSAP SCIENCE ADVISOR

ATTN: NSAP SCIENCE ADVISOR

SILVER SPRING, MD 20910 WASHINGTON, DC 20505

4 i

ł.

ATTN: FLT METEOROLOGIST, N304 CODE N702/01T BOX 167 FPO SAN FRANCISCO 96601 PEARL HARBOR, HI 96860 FPO SEATTLE 98762 COMSIXTHFLT/COMFAIRMED COMMANDER NAVAL AIR FORCE COMSIXTHFLT ATTN: FLT METEOROLOGIST SCIENCE ADVISORS OFFICE (032) U.S. ATLANTIC FLEET (30F) ATTN: NSAP SCIENCE ADVISOR FPO NEW YORK 09501 FPO NEW YORK 09501 NORFOLK, VA 23511 OFFICER IN CHARGE COMFLTAIR, MEDITERRANEAN COMNAVSURFPAC OPTEVFOR, SUNNYVALE NAVAL AIR STATION (005/N6N) ATTN: NSAP SCIENCE ADVISOR CODE 03A ATTN: NSAP SCIENCE ADVISOR FPO NEW YORK 09521 SAN DIEGO, CA 92155 MOFFETT FIELD, CA 94035 NAVAL DEPUTY TO THE OFFICER IN CHARGE OFFICER IN CHARGE ADMINISTRATOR, NOAA ROOM 200, PAGE BLDG. #1 NAVOCEANCOMDET NAVOCEANCOMDET U.S. NAVAL AIR FACILITY NAVAL STATION 3300 WHITEHAVEN ST. NW FPO SEATTLE 98791 FPO SEATTLE 98767 WASHINGTON, DC 20235 OFFICER IN CHARGE OFFICER IN CHARGE OFFICER IN CHARGE NAVOCEANCOMDET NAVOCEANCOMDET NAVOCEANCOMDET NAVAL AIR STATION NAVAL AIR STATION NAVAL AIR STATION MOFFETT FIELD, CA 94035 SAN DIEGO, CA 92145 ALAMEDA, CA 94501 COMMANDER (2)COMMANDER COMMANDER NAVAIRSYSCOM NAVAIRSYSCOM (AIR-330) PACMISTESTCEN ATTN: LIBRARY (AIR-00D4) WASHINGTON, DC 20361 GEOPHYSICS OFFICER PT. MUGU, CA 93042 WASHINGTON, DC 20361 DIRECTOR DIRECTOR USAFETAC/TS (12)DEFENSE TECH. INFORMATION TECHNIQUES DEVELOPMENT LAB SCOTT AFB, IL 62225 CENTER, CAMERON STATION GRAMAX BLUG. ALEXANDRÍA, VA 22314 8060 13TH ST.

