



5

MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAU OF STANDARDS-1963 A

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS
REPORT NUMBER	GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
		5. TYPE OF REPORT & RERIOD COVERED
Transonic Shock Interaction with a	Tangentially-	AIAA Paper 84-0094
Injected forbulent Boundary Layer		6. PERFORMING ORG. REPORT NUMBER
AUTHOR(a)		8. CONTRACT OR GRANT NUMBER(+)
		N00014-81-K-0633
G. R. Inger and A. Deane		ONR NR-061-274
PERFORMING ORGANIZATION NAME AND ADDRESS		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
West Virginia University		
Morgantown, WV 26506		
CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE .
		Jan., 1984
		13. NUMBER OF PAGES
		16
MONITORING AGENCY NAME & ADDRESS(II dillerent fr	om Controlling Office)	15. SECURITY CLASS. (of this report)
Office of Naval Research		
800 N. Quincy Street		Unclassified
Ariington, VA		SCHEDULE
DISTRIBUTION STATEMENT (of this Report)		
ſ	DISTRIBUTION ST	ATEMENT A
Distribution Unlimited	Approved for pul	blic releases
-		
DISTRIBUTION STATEMENT (of the abetract entered in I	Block 20, 11 dillerent from	n Report)
DISTRIBUTION STATEMENT (of the abstract entered in a	Block 20, 11 different from	n Report)
DISTRIBUTION STATEMENT (of the abstract entered in ,	Block 20, 11 different from DISTRIBUTION	Report)
DISTRIBUTION STATEMENT (of the abetract entered in p Distribution Unlimited	Block 20, 11 different from DISTRIBUTION Approved for p	TATEMENT A
DISTRIBUTION STATEMENT (of the abetract entered in p Distribution Unlimited	Block 20, 11 different from DISTRIBUTION Approved for p Distribution	TATEMENT A STATEMENT A public released Unlimited
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited	Block 20, 11 different from DISTRIBUTION Approved for p Distribution	n Report) STATEMENT A public released Unlimited
DISTRIBUTION STATEMENT (of the abetract entered in Distribution Unlimited	Block 20, 11 different from DISTRIBUTION Approved for p Distribution	n Report) STATEMENT A public released Unlimited
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited	Block 20, 11 different from DISTRIBUTION Approved for p Distribution	TATEMENT A public released Unlimited ====================================
DISTRIBUTION STATEMENT (of the abetract entered in Distribution Unlimited SUPPLEMENTARY NOTES	Block 20, 11 different from DISTRIBUTION Approved for p Distribution	TATEMENT A public released Unlimited ELECTE
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and in	Block 20, 11 dillerent from DISTRIBUTION Approved for p Distribution	TATEMENT A public released Unlimited ====================================
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and to Transonic Shock	Block 20, 11 different from DISTRIBUTION Approved for g Distribution	TATEMENT A public released Unlimited DTIC ELECTE JUN 2 1 1984
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse eide if necessary and to Transonic Shock Interaction Turbulopt	Block 20, 11 different from DISTRIBUTION ( Approved for g Distribution	TATEMENT A public released Unlimited SUDJUN 2 1 1984
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse eide if necessary and ic Transonic Shock Interaction Turbulent Tangential Injection	Block 20, 11 different from DISTRIBUTION 1 Approved for g Distribution	TATEMENT A public released Unlimited SUN 2 1 1984
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and in Transonic Shock Interaction Turbulent Tangential Injection	Block 20, 11 different from DISTRIBUTION Approved for p Distribution	TATEMENT A public released Unlimited SUN 2 1 1984 B
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and in Transonic Shock Interaction Turbulent Tangential Injection ABSTRACT (Continue on reverse side if necessary and id	Block 20, 11 dillerent from DISTRIBUTION Approved for g Distribution	TATEMENT A public released Unlimited SUN 2 1 1984 B
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and in Transonic Shock Interaction Turbulent Tangential Injection ABSTRACT (Continue on reverse side if necessary and id -A non-asymptotic triple deck theory	Block 20, 11 dillerent from DISTRIBUTION Approved for g Distribution dentify by block number) entify by block number) of transonic s	Report) STATEMENT A public released Unlimited DTIC ELECTE JUN 2 1 1984 B shock/turbulent boundary
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and in Transonic Shock Interaction Turbulent Tangential Injection ABSTRACT (Continue on reverse side if necessary and id "A non-asymptotic triple deck theory layer interaction is described whice	Block 20, 11 dillerent from DISTRIBUTION Approved for g Distribution dentify by block number) entify by block number) of transonic so the takes into ac	Report) STATEMENT A public releases Unlimited DTIC SUN 2 1 1984 B shock/turbulent boundary count the influence of up-
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and ic Transonic Shock Interaction Turbulent Tangential Injection ABSTRACT (Continue on reverse side if necessary and id A non-asymptotic triple deck theory layer interaction is described whic stream tangential injection on a cu	Block 20, 11 different from DISTRIBUTION Approved for p Distribution dentify by block number) entify by block number) of transonic so the takes into ac	Report) STATEMENT A public releases Unlimited Unlimited SUB State of up- addition to Reynolds number
DISTRIBUTION STATEMENT (of the obstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse eide II necessary and to Transonic Shock Interaction Turbulent Tangential Injection ABSTRACT (Continue on reverse eide II necessary and Id "A non-asymptotic triple deck theory layer interaction is described whice stream tangential injection on a cu and the shock strength, the theory	Block 20, 11 different from DISTRIBUTION Approved for g Distribution dentify by block number) entify by block number) of transonic so the takes into ac irved wall. In is parameterize	A Report) STATEMENT A public releases Unlimited Unlimited State of up- addition to Reynolds number addition to Reynolds number
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse eide II necessary and in Transonic Shock Interaction Turbulent Tangential Injection ABSTRACT (Continue on reverse eide II necessary and Id -A non-asymptotic triple deck theory layer interaction is described which stream tangential injection on a cu and the shock strength, the theory incoming boundary layer shape factor	Block 20, 11 different from DISTRIBUTION Approved for p Distribution dentify by block number) r of transonic s th takes into ac irved wall. In is parameterize or, wall jet may	Report) STATEMENT A public releases Unlimited Unlimited State Stat
DISTRIBUTION STATEMENT (of the obstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse oide II necessary and it Transonic Shock Interaction Turbulent Tangential Injection ABSTRACT (Continue on reverse oide II necessary and id -A non-asymptotic triple deck theory layer interaction is described whice stream tangential injection on a cu and the shock strength, the theory incoming boundary layer shape facto nondimensional height of this ratio	Block 20, 11 different from DISTRIBUTION Approved for p Distribution dentify by block number) r of transonic s thakes into ac irved wall. In is parameterized or, wall jet may o; results of a	A Report) STATEMENT A public released Unlimited Unlimited State of the state of up- addition to Reynolds number addition to R
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and in Transonic Shock Interaction Turbulent Tangential Injection ABSTRACT (Continue on reverse side if necessary and id "A non-asymptotic triple deck theory layer interaction is described whice stream tangential injection on a cu and the shock strength, the theory incoming boundary layer shape factor nondimensional height of this ratio study are then presented. It is sh	entify by block number) r of transonic s that the wall of a cover wall jet may by that the wall	Report) STATEMENT A public released Unlimited Unlimited Unlimited DTIC ELEECTE JUN 2 1 1984 B Shock/turbulent boundary count the influence of up- addition to Reynolds number ed by arbitrary values of the cimum velocity ratio and the comprehensive parametric all jet effects significantly thiskeping of the intermet
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and it Transonic Shock Interaction Turbulent Tangential Injection ABSTRACT (Continue on reverse side if necessary and id A non-asymptotic triple deck theory layer interaction is described whic stream tangential injection on a cu and the shock strength, the theory incoming boundary layer shape factor nondimensional height of this ratio study are then presented. It is sh reduce both the streamwise scale an	entify by block number) of transonic s the takes into ac in year and the takes of a proved for g Distribution dentify by block number) of transonic s the takes into ac inved wall. In is parameterized or, wall jet may o; results of a nown that the wall and displacement	A Report) STATEMENT A public releases Unlimited Unlimited State of the second sec
DISTRIBUTION STATEMENT (of the abstract entered in Distribution Unlimited SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse eide II necessary and it Transonic Shock Interaction Turbulent Tangential Injection ABSTRACT (Continue on reverse eide II necessary and id -A non-asymptotic triple deck theory layer interaction is described which stream tangential injection on a cu and the shock strength, the theory incoming boundary layer shape factor nondimensional height of this ratio study are then presented. It is sh reduce both the streamwise scale an form 1473	entify by block number) r of transonic so inved wall. In is parameterize or, wall jet may or, results of a hown that the wall and displacement	A Report) STATEMENT A public releases Unlimited Unlimited States States States States States States States States States States States States States States States States States

ومكافر وترجيس والمتاطلة فالمعتم شريستنا محكمتك بالكليم فليلامين

The second the second the

1.

· - -

•

zone. While increasing the upstream and downstream skin friction levels, these effects also reduce the minimum interactive Cf and thus hasten the onset of incipient separation at the shock foot.

ب <del>ن</del> ا
Accession For NTIS GRA&I
Unannounced Justification PER By
Distribution/ Availability Codes Avail and/or
A-1

SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered)

AIAA-84-0094 Transonic Shock Interaction with a

- **Tangentially-Injected Turbulent Boundary** 77
- <sup>\*</sup> Layer
- G.R. Inger and A. Deane, West Virginia
   Univ., Morgantown, WV

# **AIAA 22nd Aerospace Sciences Meeting**

January 9-12, 1984/Reno, Nevada

For permission to copy or republish, contact the American Institute of Aeronautics and Astronautics 1633 Broadway, New York, NY 10019 15 008

06

## TRANSONIC SHOCK INTERACTION WITH A TANGENTIALLY-INJECTED TURBULENT BOUNDARY LAYER

G. R. Inger and A. Deane West Virginia University, Morgantown, W. Va.

÷

• \*

mi

SL.

#### Abstract

A non-asymptotic triple deck theory of transonic shock turbulent boundary layer interaction is described which takes into account the influence of upstream tangential injection on a curved wall. In addition to Reynolds number and the shock strength, the theory is parameterwed by arbitrary values of the incominy boundary layer shape factor, wall jet maximum velocity ratio and the nondimensional height of this ratio; results of a comprehensive par metric study are then presented. It is shown that the wall jet effects significantly reduce both the streamwise scale and displacement thickening of the interaction zone. While increasing the upstream and downstream skin friction levels, these effects also reduce the minimum interactive of and thus hasten the onset of incipient separation at the shock foot.

#### Nomenclature

A	Van Driest-Cebeci wall turbulence imping
	parameter
C.	skin friction coefficient, $2\pi = \frac{2}{3}$
1.Cf	skin friction increment due to wall jet
$c_{\rm p}$	pressure coefficient, 2 p' 2 U 2 e e e
с.	literal spreading factor of wall let
н <sup>ж</sup>	boundary layer shape factor, it it
H.	incompressible shape factor
к	curvature of wall in interaction region
<u>N</u> .	Mach number
Р	static pressure
r'	interactive pressure perturbation, p-p,
11	pressure jump across incident shock
Re , Re∛	Reynolds numbers based on length ( and
•	boundary layer thickness, respectively
5	non-dimensional wall shear function of
W	wall jet
'i'	absolute temperature
	basic interactive wall-turbulence
	parameter
ut,vt	streamwise and normal interactive distur-
	hance velocity components, respectively
	wall jet component of total velocity
	profile
	undisturbed incoming boundary layer
0	velocity in x-direction
х,∵	streamwise and normal distance coordin-
	ates (origin at the inviscid shock in-
	tersection with the wall)
Y.,	effective wall shift seen by interactive
"eff	inviscid flow
Υ <sub>m ix</sub>	Location of AU max

\*Professor and Associate Chairman, Dept. of
\_\_\_Mechanical and Aerospace Engineering

Graduate student.

Copyright @ American Institute of Aeronautics and Astronautics, Inc., 1984. All rights reserved.

	$\sqrt{\frac{M_1^2-1}{specific}}$ heat ratio	
	boundary layer thickness	
	poundary layer displacement thickness	
	wall jet mixing thickness	
х	inner deck sublayer thickness	
	kinematic turbulent eddy viscosity	
	interactive perturbation of turbulent eddy viscosity	
	Y 52	
	ordinary coefficient of viscosit;	
	<b>.</b> ć	
	<pre>viscosity-temperature dependence expon- ent, usT</pre>	
	density	
	boundary layer momentum thickness	

- total shear stress
- interactive perturbation of total shear stress

#### Subscripts

AD

1

e

1

- adiabatic wall
  - undisturbed inviscid values shead of incident shock
- conditions at the boundary layer edge
- inc incompressible value
- inv inviscid disturbance solution value
- max velocity profile maximum due to wall jet o undisturbed incoming boundary layer properties

#### 1. Introduction

The use of tangential slot-injection to influence and control turbulent boundary layer behavior has been extensively studied in various types of lowspeed external and internal aerodynamic flow fields (e. g., on circulation-controlled airfoils, slotted slaps, in film cooling applications and for separation control in inlets and diffusers). in recent years, many applications of such injection have arisen in supercritical transonic flow fields where local shock wave is present; however, little is presently available to provide a basic understanding of how the resulting shock-boundary interaction ("SBLI") alters the influence of tangential injection. Conversely, in such supercritical flows it may be of interest to know how the effects of SBLI may be altered by the use of injection. The present paper addresses these questions for the case of steady non-separating 2-D turbulent boundary layers on adiabatic surfaces of small-to-moderate longitudinal curvature.

The primary objectives of our work are to develop a fundamental theory of a transonic SBLI region occurring downstream of a tangentiallyinjected turbulent boundary layer on a curved wall (Fig. 1) and then to present the results of a parametric study of this theory showing the

relationship between the dominant physical parameters, the injection and the physics of the SBLI zone. In Section 2, we briefly outline the nonasymptotic triple deck theory of a SBLI zone on a curved surface without tangential injection. Then by taking the SBLI zone sufficiently far downstream of the injection slot for mixing of the wall jet and overlying turbulent boundary layer to have produced a well-defined "jet-bulged" boundary layer profile, the interactive perturbation field caused by normal shock interaction with this profile is analyzed in Section 3 by an extension of the aforementioned SBLI theory. This is followed in Section 4 by presentation and discussion of the results of a parametric study of this extended solution for the interactive pressure, displacement thickness and skin friction effects.

#### 2. Brief Outline of the Basic SBLI Theory

#### 2.1) The Triple-Deck Model

It is well-known experimentally that when separation occurs, the disturbance flow pattern associ ted with normal shock-boundary layer interaction is a very complicated one involving a bifurcated shock pattern<sup>1</sup>, whereas the unseparated case pertaining to turbulent boundary layers up to 1.3 has instead a much simpler type of interaction pattern which is more amenable to analytical treatment (Fig. 2). The flow consists of a known incoming isobaric turbulent boundary layer profile M\_(y) subjected to small transonic perturbations due to an impinging weak normal shock. In the practic -1 Peynolds number rand of interest here (Re 10 to  $10^8$ ) we purposely employ a non-asymptotic trible-deck flow model <sup>2</sup> in the turbulent boundary layer patterned after the Lighthill-Stratford-Hond, approach that has proven highly successful in treating a variety of other problems involving turbulent boundary layer response to strong rapid adverse pressure gradients and which is supported by a large body of transonic and supersonic interaction data. The resulting flow model, Fig. 2, consists of an inviscid boundary value problem surrounding a shock discontinuity and underlaid by a thin shear stress-disturbance sublayer that contains the upstream influence and skin friction perturbations. An approximate analytic solution is further achieved by assuming small linearized disturbances ahead of and behind the nonlinear shock jump plus neglect of the detailed shock structure within the boundary layer, which give accurate predictions for all the properties of engineering interest when M > 1.05. The resulting equations can be solved by operational methods yielding the interactive pressure rise, displacement thickness growth and the skin friction behavior upstream and downstream of the shock foot. This solution contains all the escential global features of the mixed transonic viscous interaction flow and detailed comparisons with experiment **3.4** and Navier-Stokes numerical solutions have shown that it gives a very good account of all the important engineering features of non-separating interactions over a wide range of Mach-Reynolds number conditions.

An important and unique feature of this interaction theory is that it employs for the incoming turbulent boundary layer velocity profile a very general Composite Law of the Wall-Law of the Wake profile model due to Walz<sup>5</sup>, which is characterized not only by the shock Mach numbe. Mg and the boundary layer thickness Reynolds number Reg. but also by arbitrary nonequilibrium values of the incompressible shape factor  $H_{11}$ . The resulting predictions, such as typically Illustrated in Fig. 3, show that  $H_{11}$  has a very large effect on the local and downstream interactive properties that is important to account for in practical applications. By thereby accomodating a wide range of possible upstream histories of pressure gradient, heat and mass transfer, the theory has found wide-spread success as an interactive module in global composite viscous-inviscid flow field analysis programs on supercritical arrioils and projectiles, while also proving adaptable to the accomodation of new effects.

#### 2.2) Wall Curvature and Shock Obliquity Effects

Since SBLI with tangential injection often arises in flows on curved surfaces, it is desireable to account for wall curvature effects in the foregoing interaction theory. For the small to moderate curvatures usually encountered (KS < .02,, details analysis<sup>6</sup> of the transonic small disturbance flow in the outer deck shows that while the explicit new curvature terms in the perturbation equations are of the negligible order KS , the interactive viscous displacement effect from the underlying decks eliminates the well-known 7 inviccid shock cingularity while clightly altering the shock into an oblique configuration. Detailed examination of the middle+deck region shows that any new terms in the inviscid rotational distinbance equations are of the negligible order  $\mathbb{M}_{\mathbb{Q}^2}$ : only the curvature effect on the undistanced boundary-layer velocity and eddy viscosity profile are of possible significance. Here again, the explicit Ké, terms in the governing equations of this incoming flow are all negligible; however, curvature can moderately influence (10-20+) the eddy viscosity terms, with a consequent effect on the boundary-layer profile in the form of a skin described approximately by the relationships<sup>8</sup>

$$C_{f_{O}} \sim (1 + 10K_{O}^{3}) (C_{f_{O}}) flat$$
(1)

$$H_{i_1} = (1 + 5K_{i_0}) [H_{i_1}]_{flat}$$
 (2)

where to this order of accuracy the corresponding effect on  $G_{1}$  is negligibly small. Note, for example, that the typical value  $k\delta = 0.01$  yields a reduction and increase in Cf and  $H_{11}$  of 10 and 5, respectively. The use of Eqs. (1) and (2) with the Walz velocity profile model and  $k\delta_{1}$  as an additional input parameter provides a good engineering account of the moderate curvature effects on the middle-deck interaction solution. Within the very thin <u>inner</u> disturbance shear stress deck it is found yet again that the explicit curvature effects on the various inertia, pressure gradient, and laminar viscous terms in the disturbance flow equations are altogether negligible. Moreover, because of the extreme inner-deck thinness, the eddy viscosity curvature effect therein can also be safely neglected for the high Reynolds number conditions typifying most practical external aerodynamic flows.

Predictive results for the typical influence of K3 on SBLI properties, which agree with experimental observations, may be found in Ref. 6; they show that the curvature effect alightly spreads out the interaction, weakening the idverse pressure gradient along the wall, due primarily to the increased shape factor. Since the carvature effect slightly reduces the incoming bound ry-layer velocity profile fullness and spreads out the interaction, it further acts to thicken the downstream boundary layer while slightly increasing the local C\_around the shock foor owing to the reduced interactive pressure analient. As retards the slight shock obliquity at the boundary layer. elie caused by the interactive displacement thick-near effect, detailed investigation<sup>0</sup> has established that it corresponds with a good approximation to a condition of Caximum deflection. Hence the pressure rise is equivalent to a normal snock at the effective lower shock Mach number

$$\mathbb{M}_{1} = \mathbb{M}_{1} \sin^{-1}(90^{\circ} - 3^{\circ}, 3\sqrt{\mathbb{M}_{1} - 1})$$
(3)

thereby allowing the obligatty effect to be accurstely accommisted in the present theory "(Fri. 4).

#### 4. Extension to Include Tinjential Injection

We recall that the aforementioned interaction theory feeds agon a known shock strength and an assumed incoving turbulent velocity profile model characterized by the overall parameters  $H_{i_{1}}$  , cfo

and  $\operatorname{Re}_{3,*}$ . In the problem at hand we have  $\frac{1}{4}$  new unique shape of velocity profile that exists due to tangential blowing. In this section we will be concerned with modeling such a profile and its associated wall-region eddy videosity behavior by a convenient set of parameters that characterize the essential new physical features and yet are flexible enough to accomodate later specific data and to allow parametric sensitivity studies.

When air is tangentially injected through a slot of height h into an overlying boundary layer it forms a jet which is entrained by the surrounding flow (Fig. 5a). Immediately downstream of the slot, strong mixing of these flows occurs in a complicated canner which may not be validly treated by boundary layer theory; in any event, the resulting composite velocity profile assumes a unique coaracter with a maximum and a minimum (Fig. 5b). As the flow proceeds further downstream, expericental studies<sup>2</sup> have shown that the minimum is rapidly eliminated by further mixing so that when  $x \gg h$ , the profile attains a fully-developed "et-bulged" shape (Fig. 5c) composed of an unblowntype of tarbulent boundary layer profile plus a will jet component containing a velocity maximum near the wall. As this fully-developed shape convects downstreic, further mixing gradually decreases and spreads out the jet maximum (Fig. 5d) until the boundary layer ultimately tends toward in ordinary monotone profile shape in which the let component has been completely eliminated by entrainment. In the present study of weak transomic norgal shock interaction with the boundary layer downstream of a tangential injection slot, we will deal with the case where the shock interacts with a jet-bulged type of profile (Fig. 5c); this is the most interesting encountered in

prictice.\*

While possessing a boundary layer profile shape that can be analytically modeled in a manner appropriate to the SBLI solution (see below), this case also permits a simplified treatment of the eddy viscosity aspects of the interactive decks in the boundary layer, as follows. Experimental studies<sup>12-14</sup> have shown that the usual Law of the Wall behavior and its associated mixing length eddy viscosity model applies to the lower portion below the jet maximum when the injection effect is smill-to-moderate ( $\Delta u = u \ge 1.0$ ). Since the thin disturbance-snear stress inner deck of the SBLI region lies well within this Law of the Wall region, while there are no eddy viscosity-associated perturbation terms in the overlying middle deck owing to the inviscid frozen-turbulence nature of its disturbance flow, height, it can be shown that the form of all the basic triple-deck Equations in the aforementioned SBLI theory can be carried over to the present protlem provided that one fully accounts for the wall jet effects on the undisturied flow skin friction  $C_{f_{i,j}}$ , displacement

thickness Reynolds number Re , and (especially, incompressible shape factor  $\hat{R}_{i}$  as well as the pro-file distribution itself. file distribution itself.

An appropriate analytical model of the incomint boundary layer profile was developed which accounts for the essential new wall-jet features of the flow while also being well-suited to the Lighthill pressure disturbance equation that is involved in the middle deck solution. It is constructed as the sum of a wall-jet component and in "unblown" component, where to be consistent with earlier work the latter is represented by Wild's Law of the Wall Law of the Wake composite profile characterized by the three parameters Re-C, and  $B_{11}$  see Appendix A). Thus if  $y_{max}$  denotes the height of the maximum velocity u with Au max denoting the corresponding difference between  $u_{\max}$ and the unflown velocity due to the wall jet effect (see Fig. 6), the total profile is expressed AB

$$(\gamma = \alpha \frac{1}{walz}(\gamma) + \Delta u(\gamma)$$
 (4)

where the wall jet component Ju(y) varies from zero at  $\gamma = 0$  (no slip) to its maximum value Lumax at  $y = y_{max}$  and then decays outwardly towards zero, becoming negligible beyond some characteristic het-spread height  $\delta$  above y max (we presume  $\frac{1}{mix} + \frac{y}{max} \le \delta$ ). Above y max, we have followed the experimentally-based work of Carrierre et al  $^{15}\!\!$  and represented  $\Delta u$  by a modified Sech function whose slope at  $y_{max}$  equals  $-(dU_{walz} - dy)_y$  such that the <u>total</u> composite profile correctly has a maximum at  $y_{max}$ :

$$\frac{\Delta u}{u_{e}} = \frac{\Delta u_{max}}{u_{e}} \left\{ \frac{\operatorname{SECH}^{2} \left\{ \frac{y - y_{max}}{\delta_{mix}} + \delta \right\}}{\operatorname{SECH}^{2} \delta} \right\}$$
(5)

\*The regions upstream of the slot and very far downstream where the profile maximum has disappeared can of course be handled by the existing "unblown" version of the present SBLI theory.

where

$$b = 5 \left[ \ln \left( 1 + \frac{c_x}{2} \right) - \ln \left( 1 - \frac{c_x}{2} \right) \right]$$
 (5B)

is a phasing factor insuring the maximum in total velocity it  $y_{\max}$  and

$$C_{\mathbf{x}} = \left( \frac{\delta_{\text{mix}}}{\max} \right) \left[ \frac{\partial \Delta u}{\partial \mathbf{y}} \right]_{\text{max}}$$

is a lateral spreading constant (typically = .15 to avoid secondary profile maxima above  ${\rm y}_{\rm max})$  .

Below  $y_{max}$ , on the other hand, we require a functional representation that gives a reasonable monotonic shape and matches smoothly to Eq. (5) at  $y_{max}$ . Furthermore, we desire some control over the wall slope in order to represent injection effects on the local skin friction  $\Delta Cf$ . The specific constraints on this functional choice are (a) only one maximum in the total composite profile at  $y = y_{max}$ , (b) a match with the value and slope of the upper  $\Delta u(y)$  function at  $y_{max}$ , and (c) positive values of the non-dimensional slope

$$s = \left[\frac{d(\Delta u/ue)}{d(\Delta u/ue)}\right]$$

$$S_{w} \equiv \left\{ \frac{d(y, y_{max})}{d(y, y_{max})} \right\}_{y=0}$$

leading to physically reasonable skin friction increments

$$C_{\mathbf{f}} = S_{\mathbf{w}} \left( \mu_{\mathbf{w}} \delta / \mu_{\mathbf{e}} \operatorname{Re}_{\mathbf{f}} \right) \Delta U_{\max} / \gamma_{\max} , \qquad (6)$$

Now condition (a) so severely restricts the class of monotone functions it admits that no general solution can be generated to accommodate a completely arbitrary combination of conditions (b) and (c); whit can be found, however, are functions which allow either an arbitrary choice of all three parameters  $S_{w}$ ,  $\Delta U_{max}$ ,  $y_{max}$  within a restrictive range or the choice of a wide range of values for the two key parameters  $\Delta U_{max}$ ,  $y_{max}$  with  $S_{w}$ then consequently determined (but still within an interesting range of resulting values). One such function which has proven quite satisfactory for the purposes of this investigation is

$$\frac{\Delta u}{ue} = C_1 \frac{Y}{Y_{max}} - C_3 [exp(C_2 \frac{Y}{Y_{max}}) - 1]$$

$$(y < y_{max})$$
(7A)

where the aforementioned matching conditions are fulfilled if the constants  $C_{1,2,3}$  satisfy the three simultaneous relations

$$C_1 - C_3 (\exp C_2 - 1) = u_{max}$$
 (7B)

$$C_1 = C_3 C_2 \exp C_2 \approx -y_{max}$$
(7C)

$$C_1 - C_3 = S_w$$
(7D)

This trio is readily solved numerically during the implementation of the velocity profile model by using a standard non-linear simultaneous root-finder subroutine.

The aforementioned provides a smooth, piecewise-continuous and physically realistic analytical model of a fully-turbulent boundary layer downstream of a tangential injection slot; it captures the velocity overshoot and negative vorticity region features unique to this kind of flow (Fig. 6) while containing sufficient basic parameterization to permit sensitivity studies of how the jet-bulge effect influences the SBLI zone. Moreover, it has the advantage of allowing current and later experimental data on turbulent wall-jet boundary layer behavior to be incorporated into the interaction study without tying the present research down to the much more difficult and lengthy effort of such experimental studies. The weak boundary layer compressibility effects on this profile for adiabatic transonic flow are guite satisfactorily accounted for by the reference temperature method.

#### 3.2) Implementation of the Extended Theory

The foregoing approach may be implemented by several straightforward modifications to the existing computer program for the zero-blowing SBLI theory, as follows. To include small-tomoderate wall curvature effects (K6 < .01), we add K6 as an independent input variable and accordingly modify the input values of H and Cf according to Eqs. (1) and (2); furthermore, we eliminate the inviscid curvature singularity, altering the normal shock to a slightly oblique one at the boundary layer edge, by modifying the input effective normal shock Mach number according to Eq. (3). The influence of tangential injection is accomodated by introducing the two new input parameters  $\Delta U_{max} \neq 0$  and  $y_{max} \neq 0$ , characterizing the magnitude and height, respectively, of the wall jet component effect; in addition, values of the auxillary parameters C and S can be set within certain restricted ranges. The program subroutine which evaluates the Walz turbulent boundary layer velocity profile model is modified to add the matched upper and lower wall jet-component increments pertaining to these inputs (Eqs. 4-7), using a Reference Temperature-Method compressibility correction of the appropriate parameters. Figure 7 illustrates some typical boundary layer velocity profiles containing these tangential injection effects. Using the adiabatic temperature-velocity relationship

$$T \approx T_{W,AD} + (T_e - T_{W,AD}) U^2 / U_e^2$$
(8)

the associated Mach number profile M (y) and its derivative dM/dy (which are both needed in the subsequent SBLI solution routine) are calculated, the corresponding mass flow and momentum defect distributions  $1 - \frac{\partial U}{\rho e U e}$  and  $(1 - \frac{c U}{\rho e U e})^{-\frac{U}{Ue}}$  are also integrated across the boundary layer to obtain the values of  $\delta^*/\delta$  and  $0^*/\delta$ , respectively, associated with the wall jet effect. The resulting values of the displacement thickness and shape factor are shown in Figs. 8A and 8B, to illustrate how the mass and momentum addition to the boundary layer from the wall jet substantially decreases  $\delta^*$  and produces a greater profile "fullness" reflected in a significantly reduced shape factor.

<sup>†</sup> It is formally possible to obtain negative  $\delta^*$  and  $\Theta^*$  for sufficiently large injection rates  $(\Delta U_{max}, say)$ ; consistent with our other assumptions, however, we exclude such cases from this study.

the height of the jet maximum is seen to have a similar effect, because this enhances the effective strength of the injection effect on the boundary layer profile. Awareness of these overall integral property effects proves helpful in interpreting the predicted interaction properties given below.

Implementation of these wall jet-modifications is quite straightforward, except to note that feedback of the aforementioned modified integral properties into the solution sequence must be properly phased: since the wall jet effect on the incoming boundary layer profile shape is already included in the M (y) distribution used in solving the Lighthill interactive pressure equation, the feedback must be done after this pressure disturbance solution is carried out. Subsequent use of the jet-altered values of  $\delta^{\star}$  and  $\mathrm{Cf}_{O}$  then further influences the local interactive displacement thickening and skin friction solution results. To illustrate the importance of this proper feedback of the jet-influenced profile integral properties a typical set of interactive pressure, displacement thickness and skin friction distributions predicted by the aforeme tioned extended theory are presented in Fig. 9, showing the various relative effects of tangential injection compared to the zero blowing case. It is seen that the increased boundary layer profile fullness and shape factor reduction due to injection causes a significant streamwise contraction of the interactive pressure rise; this is in agreement with experimental observations (see, e.g., Fig. 116, p. 1323 of Ref. 17). Accompanying this contraction of the interaction zone, the two main effects of injection on the ratio 35\* 5 \* are seen to act with opposite and nearly
equal influence: while the profile shape-factor effect of injection reduces as\*, the corresponding reduction of So\* is approximately of the same magnitude so that the overall change in  $\Delta \delta^* / \delta_0^*$  is small. This implies that the net injection effect on 15\* scales approximately with the corresponding effect on  $\delta$  \*. Turning to the interactive skin friction behavior typified in Fig. 9c, it can be seen that the increased Cf level due to the wall jet effect dominates most of the interaction zone both fore and aft of the shock except in the vicinity of the shock foot; in this foot region, the Cf reduction due to the steepened interactive pressure gradient caused by injection becomes the dominant effect and the local value of Cf is actually reduced. Stated another way, the SBLI effect adversely counteracts the otherwise favorable Cf increase due to injection.

The offerementioned tangential injection effects on SBLI may be readily understood from the overall shape factor and displacement thickness effects shown in Fig. 8: the reduced H and  $\delta^*$ imply a thinner incoming turbulent boundary layer with a somewhat higher Mach number deep in the layer and a fuller profile shape typical of a favorable upstream pressure gradient history, which in view of the demonstrated sensitivity of SBLI to the shape factor (Fig. 3) have the effect of reducing the streamwise scale and interactive thickening while increasing the corresponding local pressure gradient.

#### 3.3) Imbedded Regions of Negative Vorticity and Supersonic Flow in the Boundary Layer

It has been seen that the wall jet effect

results in a strata of negative vorticity flow above the maximum deep down in the incoming boundary layer profile (Fig. 6). Now, some earlier basic studies of shock interaction with idealized shear flows (simple velocity discontinuities) suggest that such a strata of vorticity sign reversal might significantly alter the character of the shock transmission and reflection across it, in turn implying possible difficulty with the numeri cal solution across this strata of the Lighthill<sup>18</sup> interactive pressure disturbance equation in the present SBLI theory (which involves a term  $- \partial p / \partial y + d U_0 / d y$ ). We therefore examined this point carefully, with the following reassuring conclusion: provided that reasonable care is taken to insure high numerical accuracy with an appropriately smaller step size Av, the Lighthill equation solution is quite regular for any smooth albeit rapid variation in sign  $(dM_0/dy)$  across the strata. Hence the overall interaction solution is modified, but not fundamentally altered, by the presence of the negative vorticity due to the wall jet effect and this is straightforwardly accounted for by our modified velocity profile model in the Lighthill equation and by the associated change of the integral parameters. The underlying reason for this lack of difficulty with rapid local variations in either magnitude or sign of  $dM_{\Omega}^{\prime}/dy$  may be found from an analysis of the large scale features of Lighthill's equation, which reveals that its solution essentially depends only on integrals, rather than on local details, of the  $M_{0}(y)$  distribution across the boundary layer.

The presence of a local velocity maximum deep within the boundary layer also raises another possible difficulty, when the wall jet effect is sufficiently large, associated with the existence of a strata of locally supersonic flow astride the velocity maximum (Fig. 10). When this occurs, it is seen that there are two special cases where  $dM_{O}/dy$  vanishes at a sonic point within the boundary layer and where a local transonic singularity in the Lighthill pressure equation solution therefore will occur: (a) at a tangential injection rate where  $\textbf{U}_{max}$  just goes sonic, and (b) at a slightly higher rate where the local minimum U goes sonic higher up in the boundary layer. In these two isolated cases, there is a local breakdown of the linearization underlying the Lighthill equation and the resulting transonic singularity which causes fundamental difficulties with the numerical solution of this equation that can only be cured by restoring (at least locally) the appropriate non-linear transonic correction term. For all other maximum wall jet velocities (including, interestingly enough, the so-called "overblown" cases where  $M_{max} > M_{e}$ ), the boundary layer contains only one local sonic point that is well $dM_0/dy = 0$ removed from (for subsonic  $U_{\text{max}}$  it lies above  $y_{\text{max}}$  while for supersonic  $U_{\text{max}}$  it lies below). In such normal cases, no fundamental difficulties were discerned.

#### 4. Discussion of Parametric Study Results

The present theory has been used to carry out a systematic study of how the key tangential injection parameters influence the essential properties of a subsequent SBLI zone. We now present and discuss the results.

#### 4.1) Interactive Pressure and Displacement Thickening

Typical pressure distributions, showing the strong systematic contraction of the streamwise interactive scale with increasing strength of the wall jet component-effect, are illustrated in Figure 11. A comprehensive summary of such results showing the upstream and downstream influence distances (the distance ahead and behind the shock where the pressure rise is 5% and 95%. respectively, of the overall shock jump value) are presented in Figures 12 and 13 as a function of both the magnitude and location of the jet velocity maximum for a typical supercritical flow of M  $_{\rm H}$  = 1.20. Additional plots showing the influence of the incoming (unblown) shape factor, shock strength and Reynolds number on the wall jet effects are presented in Figures 14-17. Taken overall, these results show that tangential injection can significantly reduce the over (11) upstream influence, and strongly reduce the downstream streamwise scale of the interaction to a degree comparable to, or greater than, the unblown shape factor and/or Mach number effects. When non-dimensionalized in terms of 5, the results are not very sensitive to Reynolds number.

The corresponding systematic influence of injection on the relative interactive displacement thickness distribution  $55^*(x)/\delta_0^+$  is illustrated in Figure 18, where we see that the effect on  $55^*(x)$  and  $50^+$  largely cancel over a wide range of wall jet strengths when presented in this ratioed manner. However, there is a significant injection effect on the streamwise slope of  $\Delta^+(x)$  at the shock foot, which relates to the effective "viscous wedge" angle sensed by the outer inviscid flow; this effect is illustrated in Fig. 19, where the strong increase of this slope with wall jet strength may be clearly seen.

#### 4.2) Incipient Separation

The present theory, although it breaks down at separation, does yield a useful indication of incipient separation where  $C_{f_{\min}} \rightarrow 0$ , owing to the particular attention paid to the treatment of the local interactive skin friction behavior. Since this indication is of great practical interest, a parametric study of incipient separation conditions inherent in the present theory was carried out.

As a basis for comparison, the results for flow without any tangential injection are shown in Fig. 20a where the shock Mach number above which incipient separation occurs is plotted as a function of the Reynolds number with the shape factor as a parameter; also shown in the figure is the approximate experimental boundary determined by a careful examination of a large number of transonic interaction tests, besides Nussdorfer's 19

 $M \sim 1.30$  criterion for turbulent flow. It is seen that the theoretical prediction of a gradual increase in the incipient separation Mach number value with Revnolds number is in agreement with the trend of this data. The theoretical prediction of only a small influence of shape factor on the incipient separation conditions is also borne out by more recent data as indicated in Fig. 20b. We note here that the absolute values of the incipient separation Mach number predicted on the basis of a normal shock are consistently underpredicted slightly (Fig. 20a): when the shock obligatiy effect is modeled as described above, it is seen that the present theory and experiment are in good greenent over a wide range of Reynolds numbers.

Turning to the effect of injection, we first note from the typical behavior of the interactive Of distribution around the shock foot (see, e.g., Fig. 9c; that the net effect is expected to deare see  ${\mathbb C} f_{\text{cln}}$  (notwithstanding the overall upstream and downstreas increase in Cf otherwise due to injection). As shown in Fig. 21, this is indeed found to be the case: the wall jet effect of increasing the local interactive pressure gradient is seen to hasten the onset of incipient separation at the shock foot for a given Reynolds number flow; in the sense that separation occurs at a slightly lower shock number as  $\mathbb{M}_{max}^{*}/\mathbb{U}_{e}$  is increased. This is of course in sharp contrast to the well-known  $^{17}$ favorable effect of injection in <u>delaying</u> separation observed for purely subsonic 21 flows with a prescribed adverse pressure gradient, and is due to the fact that the interactive pressure gradient enhancement effect of tangential injection in locally reducing Cf is absent in the latter flows.

#### 4.3) Downstre g Effects

The SBLI effect has been shown in several comprehensive studies<sup>11,22</sup> of supercritical airfoil flow fields to have an appreciable influence on both shock location and downstream boundary layer behavior, and hence a significant global aerodynamic influence, when the shock occurs downstream of 65-70% chord (Fig. 22). Therefore, the predicted influence of tangential injection on the post-interactive boundary layer properties would be of interest, as would the extent to which SBLI alters the injected boundary layer behavior that otherwise exists downstream.

Now, we have seen above that tangential injection reduces the SBLI displacement thickness growth while increasing the downstream post-interactive Cf (Fig. 9c). Alternatively, we may view SBLI as increasing the downstream  $d^*$ , and hence counteracting the thinning effect otherwise obtained by the wall jet, while reducing the injection-produced Cf enhancement; both these SBLI effects make the boundary layer less resistant to separation in any subsequent adverse pressure gradient region it may encounter, and hence diminish the effectiveness of injection in otherwise delaying downstream separation. Regarding the skin friction, these conclusions are summarized in Fig. 23, where there is shown the typical influence of increasing wall jet strength on the postinteractive Cf: it is seen that while weak injection at first increases it slightly due to the corresponding increase in Cfo, stronger injection rates have the opposite effect of lowering it (as well as  $Cf_{\min}$ ) because of the intensified adverse pressure gradient effect.

### 5. Concluding Remarks

Viewed overall, the present study has shown that the usual favorable tangential injection effects of thinning out and delaying the separation of turbulent boundary layers in subsonic flow can be significantly compromised by transonic

shock, boundary layer interaction. Conversely, such injection was seen to appreciably reduce the streamwise extent of an SBLI zone albeit with the allied consequence of intensifying the local interactive adverse pressure gradient and onset of shock foot separation. It has further been established that a fundamentally-based triple-deck theory of SBLI with injection is now available to treat these effects in either external or internal supercritical flow fields; moreover, this theory has been constructed to serve as a locally insertatle interactive module (stride the inviscid shock location, driven by the attendant local boundary layer properties including an arbitrary nonequilibrium shape factor. Consequently it would re possible to investigate in the future interesting problems of plowing in supercritical flow :ields, including the use of tangential injection to codify the influence of SBLT upon the viscous trailing edge effect of supercritical airfoils $^{22,23}$ and the inclusion of SBLI effects in viscousinviscid flow field analysis programs for circulation-controlled airfoils and wings flying at supercritical flight speeds.

#### Acknowledgement

This work was carried out under the suspices of Office of Naval Research Contract NR-361-274; the resulting support and encouragement of Dr. Robert Whitehead of CNR is sincerely appreciated.

### Appendix

Because of its convenient analytical form, accurate blended representation of the comined Law of the Wall - Law of the Wake behavior and generality, we have adopted Walz's model<sup>2</sup> for the incoming turbulent coundary layer upstream of the intersection. For the low Mach number small heat transfer conditions appropriate to transonic interactions, it may be satisfactorily corrected for permeasibility effects by the Eckert Reference Temper iture setted which ander these conditions is, in fact, comparable in accuracy to, but fur pressibility transformation approach.

Let - be Coles' (incompressible) Wake Function - y ' and denote for convenience R = .41 Re<sup>3</sup>\*  $((1 + \cdots + (T_{n-1})^{1+1}))$  with z = .76 and y < 1.4 for a perfect das; then the compressible form of Walz's composite profile may be written

$$\frac{V_{O}}{V_{e}} = 1 + \frac{1}{-41} \sqrt{\frac{c_{f,O}}{2} \frac{T_{X}}{T_{V}} \int (\frac{R}{1+R}) (n^{2}(1-n) - 2n + 2n - n^{2}) (3-2n)}$$

+ 
$$in(\frac{1+R^{-}}{1+R}) = (.215 + .655R^{-})e^{-3R^{-}}$$
 (A-1

subject to the following condition linking  $\pmb{\Pi}$  to  $\mathcal{C}_{\underline{f}}$  and Ref. :

$$2^{-1} + 2\Gamma_{2}^{-1} + n(1+R) = \frac{.41}{\sqrt{\frac{c_{1}}{c_{1}} - \frac{T_{W}}{T_{e}}}}$$
(A-2)

Eqs. (A-1) and (A-2) have the following desirable properties: (a) for  $n\geq 10$  or so  $U_0$   $U_0$  is domin-

ated by a Law of the Wake behavior which correctly satisfied both the outer limit conditions U\_U\_+1 and dU\_dy +0 as n + 1; (b) on the other hand, for very small  $\Re$  values, U\_ assumes a Law of the Wall - type behavior consisting of a logarithmic term that is exponentially damped out extremely close to the wall into a linear laminar sublayer profile U\_U\_= Rn as n + 0; (c) Eq. (A-1) may be differentiated w.r.t. n to yield an analytical expression for dU\_dy also, which proves advantageous in solving the middle and inner deck interaction problems (see text) where dM\_dy must be known and vanish at the boundary layer edge.

The use of the incompressible form of Eq. (A-1) in the defining integral relations for '\* and  $\theta_1^*$  yields the following relationship that links the wake parameter to the resulting incompressible chape factor  $H_{11} = -\frac{(*_1^* + \theta_1^*)}{(*_1^* + \theta_1^*)}$ :

$$\frac{\mathbb{H}_{1} - 1}{\mathbb{E}_{1}} = \frac{1}{41} \sqrt{\frac{\mathbb{T}_{W}}{(\frac{\mathbb{T}_{W}}{\mathbb{T}_{e}})} \frac{\mathbb{C}_{f}}{2}} \frac{(1 + 1 \cdot 59^{-1} + 75^{-2})}{(1 + 1 \cdot 59^{-1})}$$
 (A-3)

Eqs. (A-2) and (A-3) together with the defining relation for R enable a rather general and convenlent parameterization of the profile (and hence the interaction that depends on it! in terms of three important physical quantities: the shock strength (Me\_1), the displacement thickness Reynolds number Res<sup>4</sup>, the wall temperature ratio T<sub>o</sub> T and the shape factor H<sub>i</sub> that reflects the prior upstream history of the incoming boundary layer including possible pressure gradient and surface mass transfer effects. With these parameters prescribed, the aforementioned three equations may be solved simultaneously for the attendant skin friction C<sub>fo</sub>, the value of R and, if desired, the - value appropriate to these flow conditions.

#### References

- Ackeret, J. F. Foldman and N. Rott, "Investigation of Compression Shocks and Boundary Layers in Gases Moving at High Speed," <u>NACA TN-1113</u>, 1947.
- Inger, G. R., "Upstream Influence and Skin Friction in Non-Separating Shock Turbulent Boundary Layer Interactions," AIAA Paper 80-1411, Snowmass, Colo., July 1980.
- Inger, G. R., "Some Features of a Shock-Turbulent Boundary Layer Interaction Theory in Transonic Flow Field," <u>AGARD CP-291, Symposium</u> on Computation of Viscous-Inviscid Interactions, Colorado Springs, Colo., Sept. 1980, pp. 18-1 to 18-66.
- Inger, G. R., "Application of a Shock-Turbulent Boundary Layer Interaction Theory in Transonic Flowfield Analysis", Ch. 17 of <u>Transonic Aerodynamics</u>, Vol. 81, Progress in Astronautics and Aeronautics, AIAA, 1982.
- Walz, A., "Boundary Layers of Flow and Temperature," M.I.T. Press, Cambridge, Mass., 1969, pp. 113.
- Inger, G. R., "Transonic Shock-Turbulent Boundary Layer Interaction and Incipient Separation on Curved Surfaces," AIAA Paper 81-1244, Palo Alto, June, 1981. Jour. of Aircraft 20, June 1983, pp. 571-74.
- 7. Oswatitsch, K., and J. Zierep, "Das Problem

des senkrechten Stosses an einer gekrummten Wand," <u>2AMM 40</u>, 1960, pp. 143-147.

- Bradshaw, P., "Effects of Streamline Curva-8. ture on Turbulent Flow," Agardograph 169, Aug. 1973.
- 9. Cebeci, T. "Wall Curvature and Transition Effects in Turbulent Boundary Layers", AIAA Jour. 9, Sept. 1971, 1868-1870.
- 10. Inger, G. R., and H. Sobieczky, "Shock Obliduity Effect on Transonic Shock-Boundary Layer Interaction," ZAMM 58T, 1978.
- 11. Nandanan, M., Stanewsky, E. and Inger, G. R., "A Computational Procedure for Transonic Airfoil Flow Including a Special Solution for Shock-Boundary Layer Interaction," AIAA Paper 80-1389, Snowmass, Colo., July 1980. AIAA J. Dec. '81, January 1982.
- 12. M. P. Escudier, W. B. Nicoll, D. B. Spalding, and J. M. Whitelaw, "Decay of a Velocity Maximum in a Turbulent Boundary Layer," Aero Quart. Vol. XVIII, Pt. 2, May 1967, pp. 121-132.
- 13. Dvorak, F. A., "Calculation of Turbulent Boundary Layers and Wall Jets Over Curved Surfaces," AIAA Jour. 11, April 1973, pp. 517-22.
- 14. Hubbartt, J. E. and D. H. Neale, "Wall Layer of Plane Turbulent Wall Jets Without Pressure Gradients", J. of Aircraft 9, March 1972, pp. 195-196.
- 15. Carriere, P., E. Eichelbrenner and Ph. Poisson-Quinton, "Contribution Theoretique et Experimentale a L'Etude du Controle de la Couche Limite par Soufflage," in Advances in Aeronautical Sciences, Vol. 2, Pergamon Press, 1959.

- 16. Burggrif, J. R., "The Compressibility Transformation and the Turbulent Boundary Layer Equation," Jour. of the Aerospace Sci. 29, 19(2, pp. 434-439.
- 17. Chang, P. Control of Flow Separation, Pergamon Press, N.Y. 1972; p. 330-375, plus 1323.
- 18. Lightnill, M. J., "On Boundary Layers and Upstream Influence, II. Supersonic Flow with Separation," Proceedings of the Royal Society A, Vol. 217, 1953, pp. 478-507.
- 19. Nussdorfer, T. J., "Some Observations of Shock Induced Turbulent Separation on Supersonic Diffusors," <u>NACA RM E51L26</u>, May 1956.
- Sirieix, M., J. Delery and E. Staneswky, 2J. "High Reynolds Number Boundary Layer-Shock Wave Interaction in Transonic Flow", Lecture Notes in Physics, Springer-Verlag, 1982.
- Burley, R. R., and D. P. Huang, "Experimental and Analytical Results of Tangential Blowin: Applied to a Subsonic V STOL Inlet," AIAA Paper 82-1084, June 1982.
- Lekoudic, S. G., G. R. Inger and M. Khan, 22. "Computation of the Viscous Transonic Flow Around Airfoils with railing Edge Effects and Proper Treatmen , the Shock-Boundary Layer Interaction ATAA Puper 82-0989, St. Louis, June, 1982
- 23. Melnick, R. E., <sup>1</sup> new and H. P. Mead, "Theory of Visco foils at High Re 77-68), June 197
  - ansonic Flow Over Air-" Number," AIAA Paper
- Van Driest, E. R. 24. libulent Boundary Layers in Compressible Fluids," Jour. of the Aeronaut. Sci. 18, March 1951, pp. 145-160.



Fig. 1 Interaction Problem Configuration



average in a please to the draw of the USG Come







 Fig. 3 Shape and Factor Effect on on Interactive Properties too [Nol] Pressure d Displacement Threemers

St. Skin Priction



14.4

does **bl**ighty Offert doe to Mission Difects

.....



9

INTERACTION THEORY WITH HUGONIOT SHOCK JUMP RELATIONS

INTERACTION THEORY WITH SHOCK JUMP RELATIONS FOR MAXIMUM STREAM DEFLECTION

12.02



Fij. 5

Schematic of Turbulent Boundary Layer Development Downstream of a Wall Jot





INCIDENT SHOCK



(d.)



WEIR DW LNDIAL R. WIN

F14. 6

Model for the Wall Jet-Effect on the Turbulent Boundary Layer Velocity Fromile



10



Fig. 8 Blowing Diffect on Integral Properties of the Boundary Layer



Interactive Property Distributions

-

22 F



Fig. 9 (Continuea)

(c) Skin Friction



12

12 4 C







14

. **.** 



File 20. Mich Number for Incision Separation at Shock Foot



Fig. 21

Blowing Effect on Predicted Incipient Separation



