

AD-A148 699

A FREE SHEAR LAYER PREDICTION OF THE TURBULENT WAKE OF 1/1
A FLAT PLATE TOWED BELOW A FREE SURFACE(U) NAVAL
RESEARCH LAB WASHINGTON DC R A SKOP 18 DEC 84

UNCLASSIFIED


NRL-MR-5476

F/G 20/4

NL



| | | | | | |
|--|--|--|--|--|--------|
| | | | | | END |
| | | | | | FILMED |
| | | | | | DTIC |



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

2

NRL Memorandum Report 5476

A Free Shear Layer Prediction of the Turbulent Wake of a Flat Plate Towed Below a Free Surface

R. A. SKOP

*Fluid Dynamics Branch
Marine Technology Division*

December 18, 1984

DTIC
ELECTE
DEC 18 1984
S B D



NAVAL RESEARCH LABORATORY
Washington, D.C.

Approved for public release; distribution unlimited.

84 12 07 007

AD-A148 699

DTIC FILE COPY

AD-A148699

SECUR CLASSIFICATION OF THIS PAGE

| REPORT DOCUMENTATION PAGE | | | | |
|--|--|---|--|---|
| 1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED | | 1b. RESTRICTIVE MARKINGS | | |
| 2a. SECURITY CLASSIFICATION AUTHORITY | | 3. DISTRIBUTION / AVAILABILITY OF REPORT | | |
| 2b. DECLASSIFICATION / DOWNGRADING SCHEDULE | | Approved for public release; distribution unlimited. | | |
| 4. PERFORMING ORGANIZATION REPORT NUMBER(S) NRL Memorandum Report 5476 | | 5. MONITORING ORGANIZATION REPORT NUMBER(S) | | |
| 6a. NAME OF PERFORMING ORGANIZATION Naval Research Laboratory | 6b. OFFICE SYMBOL (if applicable) Code 5840 | 7a. NAME OF MONITORING ORGANIZATION Office of Naval Research | | |
| 6c. ADDRESS (City, State, and ZIP Code) Washington, DC 20375-5000 | | 7b. ADDRESS (City, State, and ZIP Code) Arlington, VA 22217 | | |
| 8a. NAME OF FUNDING / SPONSORING ORGANIZATION Office of Naval Research | 8b. OFFICE SYMBOL (if applicable) | 9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER | | |
| 8c. ADDRESS (City, State, and ZIP Code) Arlington, VA 22217 | | 10. SOURCE OF FUNDING NUMBERS | | |
| | | PROGRAM ELEMENT NO. 61153N | PROJECT NO. | TASK NO. RR023-01-41 WORK UNIT ACCESSION NO. DN280-006 |
| 11. TITLE (Include Security Classification) A Free Shear Layer Prediction of the Turbulent Wake of a Flat Plate Towed Below a Free Surface | | | | |
| 12. PERSONAL AUTHOR(S) Skop, R.A. | | | | |
| 13a. TYPE OF REPORT Interim | 13b. TIME COVERED FROM 9/83 TO 8/84 | 14. DATE OF REPORT (Year, Month, Day) 1984 December 18 | 15. PAGE COUNT 18 | |
| 16. SUPPLEMENTARY NOTATION | | | | |
| 17. COSATI CODES | | 18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) | | |
| FIELD | GROUP | SUB-GROUP | Turbulent wake | |
| | | | Free shear layers | |
| 19. ABSTRACT (Continue on reverse if necessary and identify by block number) The turbulence modeled, parabolic Navier-Stokes equations are used to predict the wake of a flat plate towed below a free surface. Prandtl's free shear layer approximation is employed to represent the turbulent kinematic viscosity. The agreement between the predicted and measured velocity profiles is found to be excellent. | | | | |
| 20. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS | | 21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED | | |
| 22a. NAME OF RESPONSIBLE INDIVIDUAL Richard A. Skop | | 22b. TELEPHONE (Include Area Code) (202) 767-2858 | 22c. OFFICE SYMBOL Code 5840 | |

DD FORM 1473, 84 MAR

83 APR edition may be used until exhausted
All other editions are obsolete.

SECURITY CLASSIFICATION OF THIS PAGE

CONTENTS

INTRODUCTION 1

GOVERNING EQUATIONS 1

SOLUTION OF THE GOVERNING EQUATIONS 2

EVALUATION OF γ AND x_0 3

COMPARISON WITH SWEAN'S EXPERIMENTS 5

THE SURFACE PROXIMITY FACTOR 6

CONCLUSIONS 7

REFERENCES 14

S DTIC ELECTE **D**
 DEC 18 1984
 B

Accession For

| | |
|---------------|-------------------------------------|
| NTIS GRA&I | <input checked="" type="checkbox"/> |
| DTIC TAB | <input type="checkbox"/> |
| Unannounced | <input type="checkbox"/> |
| Justification | |

By _____

Distribution/

Availability Codes

| | | |
|------|--------------|--|
| Dist | Avail and/or | |
| | Special | |
| A-1 | | |

A FREE SHEAR LAYER PREDICTION OF THE TURBULENT WAKE OF A FLAT PLATE TOWED BELOW A FREE SURFACE

Introduction

Recently, Swaan and Keramidas [1] have reported experimental results for the turbulent wake of a flat plate towed below a free surface. We employ, here, the turbulence modeled Navier-Stokes equations to predict the experimental results. Prandtl's free shear layer approximation is used to model the turbulent kinematic viscosity.

The agreement between the predicted and measured velocity profiles is found to be excellent.

Governing Equations

We consider a flat plate (of infinite width) towed horizontally at a velocity U and a depth d beneath the free surface of a fluid. Figure 1 is a schematic of the situation. The z coordinate increases upwards with $z = 0$ corresponding to the undisturbed free surface. The x coordinate increases downstream of the plate with $x = 0$ corresponding to the trailing edge of the plate.

Far enough downstream, the plate induced axial flow velocity u must satisfy [2]

$$U \frac{\partial u}{\partial x} = \frac{\partial}{\partial z} \left(\nu_t \frac{\partial u}{\partial z} \right) \quad (1a)$$

together with the boundary conditions

$$\frac{\partial u}{\partial z} = 0 \quad \text{at } z = 0 \quad (1b)$$

$$u \rightarrow 0 \quad \text{as } z \rightarrow -\infty \quad (1c)$$

and the momentum constraint [3]

$$\rho U \int_{-\infty}^0 u \, dz = -D_v \quad (1d)$$

Here, ν_t and ρ denote, respectively, the turbulent kinematic viscosity and the density of the fluid; while D_v represents the viscous drag per unit width on the plate. To model ν_t , we use Prandtl's free shear layer approximation [4]. For the two-dimensional flow problem under consideration, this approximation specifies that

$$\nu_t = \kappa U \quad (2)$$

where κ is a constant.

Solution of the Governing Equations

The solution of equation (1) with ν_t given by equation (2) is a standard problem in heat conduction [5, Chapter 6]. We find

$$\frac{u(x, z)}{U} = \frac{H(x-x_0)}{2U[\pi\kappa(x-x_0)]^{1/2}} \times \int_{-\infty}^0 u_0(z') \left\{ e^{-\frac{(z-z')^2}{4\kappa(x-x_0)}} + e^{-\frac{(z+z')^2}{4\kappa(x-x_0)}} \right\} dz' \quad (3a)$$

where $u_0(z)$ must satisfy

$$\rho U \int_{-\infty}^0 u_0(z) \, dz = -D_v \quad (3b)$$

Here, $H(\xi)$ is the Heaviside unit step function defined by

$$H(\xi) = \begin{cases} 0, & \xi < 0 \\ 1, & \xi > 0 \end{cases} \quad (4)$$

and $u_0(z)$ is an input velocity profile specified at the axial location $x = x_0$ or

$$u_0(z) = u(x_0, z) \quad (5)$$

Because equation (1d) represents a diffusion process, the far downstream structure of the wake is independent of the details of $u_0(z)$. Hence, we assume $u_0(z)$ is given by a Dirac delta function, $\delta(\xi)$, at the plate depth d . Specifically, we set

$$u_0(z) = -U \theta_0 \delta(z+d) \quad (6)$$

where

$$\theta_0 = D_v / \rho U^2 \quad (7)$$

is the total momentum thickness. Equation (6) clearly satisfies equation (3b) as required.

Substituting equation (6) into equation (3a) and redefining κ as

$$\kappa = \gamma \theta_0 \quad (8)$$

we obtain

$$\frac{u(x, z)}{U} = - \frac{H(x-x_0)}{2} \left[\frac{\theta_0}{\pi \gamma (x-x_0)} \right]^{\frac{1}{2}} \times \left\{ e^{-\frac{(z+d)^2}{4\gamma \theta_0 (x-x_0)}} + e^{-\frac{(z-d)^2}{4\gamma \theta_0 (x-x_0)}} \right\} \quad (9)$$

Evaluation of γ and x_0

The velocity field $u_w(x, z)$ behind a flat plate in an infinite fluid is given by 1/2 of equation (9) with $d = 0$ or

$$\frac{u_{\infty}(x, z)}{U} = - \frac{H(x-x_0)}{2} \left[\frac{\theta_0}{\pi\gamma(x-x_0)} \right]^{\frac{1}{2}} e^{-\frac{z^2}{4\gamma\theta_0(x-x_0)}} \quad (10)$$

Schlichting [4] notes from experimental observations that, for proper values of γ and x_0 , equation (10a) provides a valid description of the velocity field for

$$x/\theta_0 > 100 \quad (11)$$

In particular, along the plate centerline $z = 0$, we find

$$\frac{u_{\infty}(\tilde{x}, 0)}{U} = - \frac{H(\tilde{x}-\tilde{x}_0)}{2} \frac{1}{[\pi\gamma(\tilde{x}-\tilde{x}_0)]^{\frac{1}{2}}} \quad (12a)$$

where we have introduced the dimensionless axial coordinates

$$\tilde{x} = x/\theta_0, \quad \tilde{x}_0 = x_0/\theta_0 \quad (12b)$$

In Table 1, the experimental results of Swean and Keramidas [1] and of Chevray and Kovaszny [6] for a flat plate in an infinite fluid are tabulated. Also tabulated is the value of $\gamma(\tilde{x}-\tilde{x}_0)$ required in equation (12a) to produce the experimentally observed centerline velocity. From Table 1, six values of $\Delta\tilde{x}$ and the corresponding six values of $\gamma\Delta\tilde{x}$ can be obtained. These are given in Table 2 as is the resultant value of γ . Averaging the values of γ in Table 2 gives a best fit value for γ as

$$\gamma = 0.0209 \quad (13)$$

Using this value for γ , we tabulate in Table 3 the calculated value of $\tilde{x}-\tilde{x}_0$ from Table 1. Also given is the value of \tilde{x}_0 . Averaging the values of \tilde{x}_0 in Table 3 gives a best fit value for \tilde{x}_0 as

$$\tilde{x}_0 = x_0/\theta_0 = 12.3 \quad (14)$$

Comparison with Swean's Experiments

In Figure 2, the velocity profiles predicted by equation (10) are compared with the results of Swean and Keramidas for a flat plate towed in an infinite fluid. The comparisons are made for their two most downstream measuring stations $x/\theta_0 = 95.8$ and $x/\theta_0 = 172.1$ which correspond, respectively, to $x = 61.7$ cm and $x = 110.8$ cm. In general, the agreement is seen to be excellent.

In Figure 3, the velocity profiles predicted by equation (9) are compared with the results of Swean and Keramidas for a flat plate towed at a depth $d = 5$ cm. Again, the comparisons are made at this two most downstream measuring stations $x = 61.7$ cm and $x = 110.8$ cm. The agreement is seen to be not nearly as satisfactory as for the infinite fluid case. Essentially, the model substantially underpredicts the observed spread of the wake and the observed free surface velocity.

It is apparent from Figures (3a) and (3b), however, that the measured velocity profiles of Swean and Keramidas do not satisfy the momentum constraint of equation (1d) if their value of $\theta_0 = 0.644$ for the towed flat plate in an infinite fluid is used. That is

$$-\int_{-\infty}^0 \frac{u}{U} dz = \theta_0 > 0.644 \quad (15)$$

Unfortunately, Swean and Keramidas did not measure directly the viscous drag on the plate. Thus, the appropriate value of θ_0 for the near free surface towing condition can only be estimated by using their measured velocity profiles.

For simplicity, we approximate each of the measured profiles by a two straight line fit. In Figure (3a), we find the three

$(z, 1+u/U)$ endpoints as $(0, 1)$, $(-4.75, 0.75)$ and $(-8.5, 1)$. The area subtended by this approximation and the vertical axis $1 + u/U = 1$ gives

$$\theta_0 = 1.06 \text{ cm for } x = 61.7 \text{ cm}$$

In Figure (3b), we find the three $(z, 1+u/U)$ endpoints as $(0, 0.965)$, $(-4.5, 0.8)$ and $(-9.75, 1)$. The subtended area gives

$$\theta_0 = 1.05 \text{ cm for } x = 110.8 \text{ cm}$$

In Figure (4), the velocity profiles predicted by equation (9) using the estimated value $\theta_0 = 1.05$ are plotted. As can be seen, the agreement with the measured profiles is improved considerably as compared to Figure 3. However, the predicted profiles tend to be shifted downward in z compared to the measured ones and the free surface velocities are somewhat in error.

The Surface Proximity Factor

If we assume that, because of the proximity of the free surface, the origin of $u_0(z)$ shifts from $z = -d$ to $z = -\alpha d$, equation (9) becomes

$$\frac{u(x, z)}{U} = - \frac{H(x-x_0)}{2} \left[\frac{\theta_0}{\pi \gamma (x-x_0)} \right]^{\frac{1}{2}} \times \left\{ e^{-\frac{(z+\alpha d)^2}{4\gamma\theta_0(x-x_0)}} + e^{-\frac{(z-\alpha d)^2}{4\gamma\theta_0(x-x_0)}} \right\} \quad (16)$$

We term α the surface proximity factor. For a deeply towed plate $\alpha = 1$.

To evaluate α for the near free surface experiment of Swean and Keramidas their measured free surface velocity for $x = 110.8$ cm is used. In particular, referring to Figure (4b), we require $u(110.8, 0)/U = -0.05$ which provides the value $\alpha = 0.85$.

In Figure 5, the velocity profiles predicted by equation (16) with $\theta_0 = 1.05$ and $\alpha = 0.85$ are shown. The agreement with the measured profiles is excellent.

Conclusions

Prandtl's free shear layer model has been used to predict the turbulent wake of a flat plate towed below a free surface. When appropriate account is taken of the apparent increase in viscous drag on the plate as it approaches the free surface, excellent agreement between predicted and measured velocity profiles is obtained.

These results validate the applicability of Prandtl's model for the turbulent kinematic viscosity for this complex wake development problem.

Table 1. Calculated value of $\gamma(\tilde{x}-\tilde{x}_0)$ necessary to match experimental results

| Ref | Experimental* | | Calculated $\gamma(\tilde{x}-\tilde{x}_0)$ |
|-----|---------------|---------------------------|---|
| | \tilde{x} | $u_\infty(\tilde{x},0)/U$ | |
| [1] | 95.8 | -0.21 | 1.80 |
| [6] | 129.3 | -0.19 | 2.20 |
| [1] | 172.1 | -0.15 | 3.54 |
| [6] | 206.9 | -0.14 | 4.06 |

*Ref. [1], $\theta_0 = 0.644$ cm

Ref. [2], $\theta_0 = 1.16$ cm

Table 2. Evaluation of γ

| Experimental $\Delta\tilde{x}$ | Calculated | |
|-----------------------------------|-------------------------|----------|
| | $\gamma\Delta\tilde{x}$ | γ |
| 33.5 | 0.40 | 0.0119 |
| 34.8 | 0.52 | 0.0149 |
| 42.8 | 1.34 | 0.0313 |
| 76.3 | 1.74 | 0.0228 |
| 77.6 | 1.86 | 0.0240 |
| 111.1 | 2.26 | 0.0203 |

Table 3. Evaluation of \tilde{x}_0

| Experimental \tilde{x} | Calculated | |
|-----------------------------|-------------------------|---------------|
| | $\tilde{x}-\tilde{x}_0$ | \tilde{x}_0 |
| 95.8 | 86.1 | 9.7 |
| 129.3 | 105.3 | 24.0 |
| 172.1 | 169.4 | 2.7 |
| 206.9 | 194.3 | 12.6 |




Figure 1. Schematic and notation for the turbulent wake of a flat plate towed below a free surface.




Figure 2. Free shear layer prediction from eq. (10) of the turbulent wake behind a flat plate in an infinite fluid. The assumed momentum thickness was $\theta_0 = 0.644$ cm. — predicted, ooo measured [1]. (a) $x = 61.7$ cm, (b) $x = 110.8$ cm.




Figure 3. Free shear layer prediction from eq. (9) of the turbulent wake behind a flat plate towed 5 cm below a free surface. The assumed momentum thickness was $\theta_0 = 0.644$ cm. — predicted, ooo measured [1]. (a) $x = 61.7$ cm, (b) $x = 110.8$ cm.




Figure 4. Free shear layer prediction from eq. (9) of the turbulent wake behind a flat plate towed 5 cm below a free surface. The assumed momentum thickness was $\theta_0 = 1.05$ cm. — predicted, ooo measured [1]. (a) $x = 61.7$ cm, (b) $x = 110.8$ cm




Figure 5. Free shear layer prediction from eq. (16) of the turbulent wake behind a flat plate towed 5 cm below a free surface. The assumed momentum thickness was $\theta_0 = 1.05$ cm and the assumed surface proximity factor was $\alpha = 0.85$. — predicted, ooo measured [1]. (a) $x = 61.7$ cm, (b) $x = 110.8$ cm.

References

1. T.F. Swean, Jr. and G.A. Keramidas, 1984: The Turbulent Wake of a Flat Plate Near a Free Surface. Proceedings of the 2nd International Conference on Computational Methods and Experimental Mechanics, Computational Mechanics Centre, Southampton, England.
2. R.A. Skop, 1984: The Hydrodynamic Wake of a Surface Ship: Theoretical Foundations. Naval Research Laboratory Report 8833, Washington, DC. AD B084604L DTT June 28, 1984
3. R.A. Skop, 1984: The Development of Plane and Initially Axisymmetric Laminar Wakes Generated by Bodies Moving Beneath a Free Surface. Proceedings of the 2nd International Conference on Computational Methods and Experimental Mechanics, Computational Mechanics Centre, Southampton, England.
4. H. Schlichting, 1960: Boundary Layer Theory, Fourth Edition. McGraw-Hill, New York, NY.
5. B.A. Boley and J.H. Weiner, 1960: Theory of Thermal Stresses. John Wiley & Sons, New York, NY.
6. R. Chevray and L.S.G. Kovasznay, 1969: Turbulence Measurements in the Wake of a Thin Flat Plate. AIAA Journal, Vol. 7, No. 8, pp. 1641-1643.

END

FILMED

1-85

DTIC