

AD-A148 932

INTERNAL FORCED CONVECTION TO LOW PRANDTL NUMBER GAS  
MIXTURES(U) ARIZONA UNIV TUCSON ENGINEERING EXPERIMENT  
STATION M F TAYLOR ET AL. 15 JUL 84 1248-10


1/2


UNCLASSIFIED

N00014-75-C-0694

F/G 20/13

NL





MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS 1963 A

AD-A148 932

Interim Report

Contract No. N00014-75-C-0694

INTERNAL FORCED CONVECTION TO LOW  
PRANDTL NUMBER GAS MIXTURES*Prepared for*Office of Naval Research  
Code 431  
Arlington, Virginia 22217*Prepared by*M. F. Taylor  
K. E. Bauer  
D. M. McEligot

30 JUNE 1984

DTIC  
ELECTE  
DEC 31 1984  
S D E

THIS FILE COPY

This document has been approved  
for public release and sale; its  
distribution is unlimited.ENGINEERING EXPERIMENT STATION  
COLLEGE OF ENGINEERINGTHE UNIVERSITY OF ARIZONA  
TUCSON, ARIZONA 85721

84 12 18 064

*Interim Report*

INTERNAL FORCED CONVECTION TO  
LOW PRANDTL NUMBER  
GAS MIXTURES

*by*

M. F. Taylor, K. E. Bauer and D. M. McEligot  
Aerospace and Mechanical Engineering Department  
University of Arizona  
Tucson, Arizona 85721

*Research sponsored by*

Office of Naval Research

ONR Contract No. N00014-75-C-0694

ONR Contract Authority NR-097-395

30 JUNE 1984

Approved for public release; distribution unlimited. Reproduction in whole or in part is permitted for any purpose of the United States Government.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE


A148 932


## REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION Unclassified		1b. RESTRICTIVE MARKINGS	
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION/AVAILABILITY OF REPORT Unlimited	
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE		5. MONITORING ORGANIZATION REPORT NUMBER(S) 1248-	
PERFORMING ORGANIZATION REPORT NUMBER(S) 1248-10		5. MONITORING ORGANIZATION REPORT NUMBER(S) 1248-	
4a. NAME OF PERFORMING ORGANIZATION Engineering Experiment Station University of Arizona	4b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION Office of Naval Research Bandolier Hall West - Room 204	
6a. ADDRESS (City, State and ZIP Code) College of Engineering Tucson, Arizona 85721		7b. ADDRESS (City, State and ZIP Code) University of New Mexico Albuquerque, NM 87131	
4a. NAME OF FUNDING/SPONSORING ORGANIZATION Office of Naval Research	4b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER N00014-75-C-0694	
6a. ADDRESS (City, State and ZIP Code) Code 431 Arlington, VA 22217		10. SOURCE OF FUNDING NOS.	
1. TITLE (Include Security Classification) INTERNAL FORCED CONVECTION TO LOW PRANDTL NUMBER GAS MIXTURES		PROGRAM ELEMENT NO. NR 097-395	PROJECT NO.
2. PERSONAL AUTHOR(S) M. F. Taylor, K. E. Bauer and D. M. McEligot		TASK NO.	WORK UNIT NO.
13a. TYPE OF REPORT Interim Technical	13b. TIME COVERED FROM 7/15/82 TO 7/15/84	14. DATE OF REPORT (Yr., Mo., Day) 15 July 1984	15. PAGE COUNT
3. SUPPLEMENTARY NOTATION			
7. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB. GR.	Heat Transfer - Forced Convection - Variable Properties - Tubes - Ducts - Turbulent - Gas Flow - Gas Mixtures
1. ABSTRACT (Continue on reverse if necessary and identify by block number)			
<p>At a Prandtl number of about 0.2, the predictions of accepted correlations for heat transfer in fully established tube flow differ by a factor more than two. Since gas turbine systems proposed for propulsion utilize working fluids with the Prandtl number in this range, it was necessary to resolve the discrepancy. By mixing helium with xenon or hydrogen with xenon, the range of <math>0.16 \leq Pr \leq 0.7</math> can be obtained. Measurements with these mixtures in a vertical tube showed that the Colburn analogy and Dittus-Boelter substantially overpredict the Nusselt number for constant property conditions; best agreement was provided by relations suggested by Petukhov and by Kays. For moderate variation of gas properties (<math>1 &lt; T_w/T_b \leq 2.2</math>) the correlation for average friction factor by Taylor was verified; the exponent on the Prandtl number in his equation for heat transfer was modified to 0.65 in order to accommodate these new data.</p>			
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT Unclassified/Unlimited <input type="checkbox"/> SAME AS RPT. <input checked="" type="checkbox"/> DTIC USERS <input type="checkbox"/>		21. ABSTRACT SECURITY CLASSIFICATION Unclassified	
22a. NAME OF RESPONSIBLE INDIVIDUAL M. Keith Ellingsworth		22b. TELEPHONE NUMBER (Include Area Code) (202) 696-4403	22c. OFFICE SYMBOL Code 431

# ABSTRACT

At a Prandtl number of about 0.2, the predictions of accepted correlations for heat transfer in fully established tube flow differ by a factor more than two. Since gas turbine systems proposed for propulsion utilize working fluids with the Prandtl number in this range, it was necessary to resolve the discrepancy. By mixing helium with xenon or hydrogen with xenon, the range  $0.16 < Pr < 0.7$  can be obtained. Measurements with these mixtures in a vertical tube showed that the Colburn analogy and Dittus-Boelter substantially overpredict the Nusselt number for constant property conditions; best agreement was provided by relations suggested by Petukhov and by Kays. For moderate variation of gas properties ( $1 < T_w/T_b < 2.2$ ) the correlation for average friction factor by Taylor was verified; the exponent on the Prandtl number in his equation for heat transfer was modified to 0.65 in order to accommodate these new data.






## TABLE OF CONTENTS

	<u>Page</u>
ABSTRACT . . . . .	iii
NOMENCLATURE . . . . .	v
INTRODUCTION . . . . .	1
TRANSPORT PROPERTIES OF THE MIXTURE . . . . .	4
THE EXPERIMENT . . . . .	17
Apparatus . . . . .	17
Procedures and Preliminary Measurements . . . . .	20
Experimental Uncertainties . . . . .	23
Reproducibility . . . . .	24
EXPERIMENTAL RESULTS . . . . .	27
Heat Transfer with Constant Properties . . . . .	27
Heating with Property Variation . . . . .	31
CONCLUSION . . . . .	38
ACKNOWLEDGEMENTS . . . . .	40
APPENDICES:	
A. Uncertainty Analysis . . . . .	42
B. Experimental Data with Heat Addition . . . . .	50
REFERENCES . . . . .	106
DISTRIBUTION LIST . . . . .	110





## NOMENCLATURE

A	Flow area of test section;
c	Velocity of sound;
$c_p$	Specific heat at constant pressure;
$c_v$	Specific heat at constant volume;
D	Inside diameter
g	Acceleration due to gravity;
$g_c$	Dimensional conversion factor;
G	Average mass flux, $\dot{m}/A$ ;
h	Heat transfer coefficient;
i	Specific enthalpy;
k	Thermal conductivity;
$\dot{m}$	Mass flow rate;
L	Distance from start of heating to PT #2;
$\tilde{M}$	Molal mass;
p	Pressure;
$q''$	Heat flux;
R	Gas constant for a particular gas;
$R$	Universal gas constant;
T	Temperature ;
x	Axial distance from start of heating;

## NOMENCLATURE (continued)

### *Greek Symbols*

$\epsilon/k$	Force constant in Lennard-Jones potential;
$\gamma$	Ratio of specific heats, $c_p/c_v$ ;
$\mu$	Absolute viscosity;
$\nu$	Kinematic viscosity;
$\rho$	Density;
$\sigma$	Force constant in Lennard-Jones potential;


### *Nondimensional Parameters*

$f$	Friction factor, $g_c \rho_{b,av} D \Delta p_{fr} / 2 L G^2$ ;
$G_r$	Grashof number based on wall heat flux, $g D^4 q_w'' / (\nu^2 k T)_i$
$Nu$	Nusselt number, $h D / k$ ;
$\bar{p}$	Pressure drop, $\rho_i g_c (p_i - p) / G^2$ ;
$Pr$	Prandtl number, $c_p \mu / k$ ;
$q^+$	Heat flux parameter, $q_w'' / G c_{p,i} T_i$ ;
$Re$	Reynolds number, $G D / \mu$ ;

## NOMENCLATURE (continued)

### *Subscripts*

av	Lengthwise average;
b	Evaluated at bulk temperature;
cp	Constant property condition;
DB	Dittus-Boelter;
fr	Frictional;
H <sub>2</sub>	Hydrogen gas;
i	Inlet; an index;
mod	Modified;
ref	Reference;
w	Wall;
Xe	Xenon gas;
1	At start of heating;
2	At pressure tap 2.



## INTRODUCTION

The use of gas mixtures has been proposed for use in closed cycle gas turbines with applications in power systems undersea and in space as well as for propulsion of ships, aircraft, buses and rail units. Helium and hydrogen both possess excellent heat transfer properties but require many stages of turbomachinery in closed cycle gas turbines. The addition of higher molecular weight gases to helium or hydrogen to form binary mixtures can reduce the number of stages in turbomachinery but increases heat exchanger surface area because of the lower thermal conductivity of the heavier gases. The Prandtl number can be as low as 0.16 for these mixtures. In the past, most designs utilizing these gas mixtures were made by using correlations of the Colburn [1933] or Dittus-Boelter [1930] type which had resulted from tests using gases with a Prandtl number around 0.7, or with liquids.

In fact, some well-known texts do not recognize that a Prandtl number less than 0.6 can occur for gas mixtures. Several relations have been reported which differ considerably from Colburn and are suggested for use over a wide range of Prandtl numbers, some as low as 0.1 [Kays, 1966; Petukhov, 1970; Sleicher and Rouse, 1975; Gnielinski, 1975; and Churchill, 1977]. The relations recommended by these investigators are tabulated in Table 1. The large variations in Nusselt number resulting from these relations are shown in Fig. 1 as a function of Prandtl number. At a Prandtl number of 0.2 there is a factor of 2.2 between the lowest and

Table 1. Equations Proposed to Predict Nusselt Number over a Range of Prandtl Number.

Investigator	Correlation Equations for Constant Properties	Suggested Pr Range	Eq
Dittus-Boelter [1930]	$Nu = 0.021 Re^{0.8} Pr^{0.4}$	0.7 to 1.0	1
Colburn [1933]	$Nu = 0.023 Re^{0.8} Pr^{1/3}$	0.5 to 100	2
Kays [1966]	$Nu = 0.022 Re^{0.8} Pr^{0.6}$	0.5 to 1.0	3
Petukhov [1970]	$Nu = \frac{(\xi/8) Re Pr}{K_1(\xi) + K_2(Pr) \sqrt{\xi/8} (Pr^{2/3} - 1)}$ $\xi = (1.82 \log_{10} Re - 1.64)^{-2}$ $K_1(\xi) = 1.3.4\xi \quad K_2(Pr) = 11.7 + 1.8 Pr^{-1/3}$	0.5 to 200	4
Sleicher and Rouse [1975]	$Nu = 5.0 + 0.015 Re^a Pr^b$ $a = 0.88 - 0.24/(4 + Pr)$ $b = 1/3 + 0.5 \exp(-0.6 Pr)$	0.1 to $10^5$	5
Gniefinski [1975]	$Nu = 0.0214 (Re^{0.8} - 100) Pr^{0.4} (T_v/T_b)^{0.45} \left[ 1 + \left( \frac{D}{x} \right)^{2/3} \right]$	0.6 to 1.5	6
Churchill [1977]	$Nu = 6.3 \frac{0.079 Re \sqrt{f} Pr}{[1 + Pr^{4/5}]^{5/6}}$ $\frac{1}{\sqrt{f}} = 2.21 \ln \left( \frac{Re}{7} \right)$	all	7




Figure 1. Comparison of correlation equations recommended by several investigators.



highest value recommended! The danger of extrapolating heat transfer correlations based on data at  $Pr \approx 0.7$  is emphasized by Pierce [1981] in an application to the closed gas turbine cycle.

The authors of this paper have used a number of binary mixtures of light and heavy gases to test the correlations shown in Fig. 1; for later reference, equation numbers are listed on the table. Pickett, Taylor and McEligot [1979] employed mixtures of helium and argon in order to obtain  $Pr \approx 0.42$  and  $0.49$  while Serksnis, Taylor and McEligot [1978] conducted measurements at  $Pr \approx 1/3$  by using a mixture of hydrogen and carbon dioxide. In the present investigation, additional data have been obtained in the range  $0.18 \lesssim Pr \lesssim 0.3$  by mixing hydrogen with xenon and helium with xenon. Table 2 summarizes the range of data obtained in this investigation.

#### TRANSPORT PROPERTIES OF THE MIXTURES

The properties needed for this study were compressibility, viscosity, thermal conductivity, specific heat, enthalpy, speed of sound, and the gas constant. The properties of air have been studied extensively; for the comparison data the NBS tables of Hilsenrath et al. [1955] were used in this investigation. The properties of helium-xenon mixtures were calculated theoretically. For all gases the viscosity and thermal conductivity were assumed to be independent of pressure.

The helium-xenon mixtures were assumed to be ideal gases, thus making the compressibility equal to unity. This assumption is reasonable for the range of pressures (260 - 1000 kPa or 2.6 - 9.9 atm) and

Table 2. Range of Variables in the Present Investigation.

Gas	Air	He-Xe	He-Xe	He-Xe	He-Xe	H <sub>2</sub> -Xe
Molecular Weight	28.97	83.8	40	28.3	14.5	29
Inlet Bulk Prandtl Number	0.717	0.251	0.214	0.231	0.301	0.181 (0.196)
Experimental Runs	16	10	10	4	5	4
Inlet Bulk Reynolds Number	33,900 - 85,800	32,600 - 87,400	34,300 - 61,800	48,400 - 55,400	34,000 - 40,900	71,100 - 73,900
Exit Bulk Reynolds Number	21,600 - 77,900	16,500 - 74,300	19,200 - 51,800	26,200 - 43,000	19,500 - 36,700	43,400 - 66,700
Maximum $T_w/T_b$	2.38	2.22	1.99	2.06	2.04	1.78
Maximum $T_w$ (°K)	974	962	941	982	972	832
Maximum $q^+$	0.0044	0.0069	0.0053	0.0051	0.0047	0.0034
Maximum $Gr/Re_1^2$	$1.40 \times 10^{-2}$	$1.44 \times 10^{-2}$	$9.34 \times 10^{-3}$	$6.67 \times 10^{-3}$	$3.05 \times 10^{-3}$	$3.29 \times 10^{-3}$ ( $3.04 \times 10^{-3}$ )
Maximum Mach Number	0.109	0.123	0.079	0.90	0.075	0.103
x/D for Local Bulk Nusselt Numbers	2.2 - 52.4	2.2 - 52.4	2.2 - 52.4	2.2 - 52.4	2.2 - 52.4	2.2 - 52.4

Values in parentheses are for calculated thermal conductivities of H<sub>2</sub> - Xe

temperatures (290 - 980°K or 62 - 1310°F) used in this experiment. Since helium and xenon are monatomic and the temperature range in this study was not too large, the relation [Reynolds, 1968]

$$c_p = (5/2) R = (5/2) R/\bar{M} \quad (8)$$

was used to calculate the specific heat.

Using the ideal gas and constant specific heat assumptions, one may derive simple equations for the enthalpy and speed of sound [Reynolds and Perkins, 1968]

$$\begin{aligned} i &= c_p (T - T_{\text{ref}}) \\ \text{and} \quad c &= \sqrt{\gamma RT} = \sqrt{(5/3)RT} \end{aligned} \quad (9)$$

The Lennard-Jones (6-12) potential can be employed in the Chapman-Enskog kinetic theory to predict thermal conductivity, viscosity and Prandtl number of binary mixtures of inert gases [Hirschfelder, Curtiss and Bird, 1964]. There has been considerable experimental study of the pure gases but, unfortunately, few data exist on the mixtures.

With force constants,  $\epsilon/k$  and  $\sigma$ , suggested by Hirschfelder, Curtiss and Bird [1964], the predicted viscosity for pure helium falls about eight percent below the data of Clarke and Smith [1968], Dawe and Smith [1970] and Kalelkar and Kestin [1970] at temperatures around 900°C (1650°F). Likewise, the predicted thermal conductivity is about nine percent lower than the measurements of Saxena and Saxena [1968] up to 1100°C (2011°F). In contrast, using the force constants suggested by DiPippo and Kestin

[1969] leads to essential agreement with the values recommended by the Thermophysical Properties Research Center [Touloukian and Ho, 1970].

For pure xenon, force constants from Hirschfelder, Curtiss and Bird [1964] predicted viscosity that falls about five percent below the data of Dawe and Smith [1970] and Kestin, Ro and Wakeham [1972]. The predicted thermal conductivity is about twelve percent lower than measurements of Saxena and Saxena [1969] up to 1200°C (2191°F). DiPippo and Kestin did not report force constants for xenon, but Kestin, Ro and Wakeham suggested force constants that predicted values of viscosity that are in very good agreement with the experimental data and predicted values of thermal conductivity that are about four percent lower than the reported measurements.

The properties of the helium-xenon mixtures are shown in Fig. 2. The solid curves were calculated using the force constants recommended by DiPippo and Kestin [1969] for helium:  $\sigma = 2.158 \text{ \AA}$  and  $\epsilon/k = 86.2^\circ\text{K}$  and those recommended by Kestin, Ro and Wakeham [1972] for xenon:  $\sigma = 2.858 \text{ \AA}$  and  $\epsilon/k = 285.2^\circ\text{K}$ .

The viscosity of the mixtures varies considerably with the molecular weight of the mixture. At 277°C (530°F) the maximum viscosity of the mixture is 41% higher than that of helium and five percent higher than xenon. Viscosity predicted using constants from DiPippo and Kestin [1969] and Kestin, Ro and Wakeham [1972] agrees to within three percent of the data of Trautz and Heberling [1923] and Thornton [1960]. As with pure gases the viscosity increases with temperature.




Figure 2a. Transport properties of helium-xenon mixtures.  
Pressure = 1 atm.




Figure 2b. Transport properties of helium-xenon mixtures.  
Pressure = 1 atm.




Figure 2c. Transport properties of helium-xenon mixtures.  
Pressure = 1 atm.

The mixture thermal conductivity decreases by a factor of 23 as the molecular weight increases from pure helium to pure xenon over the range of mixture temperature in this investigation, and mixture conductivity also increases with temperature. Agreement with the data of Thornton [1960], Gandhi and Saxena [1968] and Mason and von Ubish [1960] is good for temperatures ranging from 18° to 90°C (65° to 194°F). The only data available at higher temperatures are those of Mason and von Ubish at 520°C (968°F) and these are almost 10% higher than the predictions; however, in a critical review Gandhi and Saxena [1968] have observed that the measurements of Mason and von Ubish appear to be systematically higher than others they reviewed.

As a consequence of the variation of thermal conductivity and specific heat vs. molecular weight the Prandtl number decreases to a minimum of about 0.21 at  $\tilde{M} \sim 50$  from about 0.667 for the pure gases. It is about 0.23 at the molecular weight of air.

It is interesting to note that even though the force constants of Hirschfelder, Curtiss and Bird [1964] did not adequately predict thermal conductivity and viscosity for pure helium and xenon, their predictions for the mixtures did not differ greatly from the ones used in this investigation.

The hydrogen-xenon mixtures were also assumed to be ideal gases, making the compressibility equal to unity. This assumption is also reasonable for the range of pressures (750 - 800 kPa or 7.4 - 7.9 atm) and temperatures (290 - 830°K or 62 - 1040°F) used in this experiment. The specific heat of this mixture was calculated by the relation



$$c_{p,mixture} = (\text{mass fraction}_{H_2}) c_{p,H_2} + (\text{mass fraction}_{Xe}) c_{p,Xe}$$

The enthalpy and speed of sound were calculated in the same manner as with the helium-xenon mixture.

The hydrogen-xenon mixture properties are shown in Fig. 3. The solid lines for viscosity were calculated using the viscosities of hydrogen and xenon and the method recommended by Hirschfelder, Curtiss and Bird [1964] for calculating mixtures of monatomic gases. Hydrogen is, of course, polyatomic and predicting its properties is more complex than predicting those of monatomic gases. The solid lines for thermal conductivity were calculated using the method of Lindsay and Bromley [1965].

The only measurements of viscosity of hydrogen-xenon mixtures found in the literature were those of Trautz and Heberling [1934] which are in good agreement with these predictions, especially at the mole fraction of xenon (0.21) in the mixture used in the present investigation. The viscosity of the mixture increases with temperature and the increase in viscosity from pure hydrogen to pure xenon is threefold.

The mixture thermal conductivity decreases by a factor of 30 as the molecular weight increases from pure hydrogen to pure xenon over the temperature range of this investigation. Only two investigations of thermal conductivity of hydrogen-xenon mixtures have been reported. Barua [1960] measured conductivities for mixtures of eight volume-percentages of xenon from 0 to 100% at temperatures of 30°C (85°F) and 45°C (111°F).




Figure 3a. Transport properties of hydrogen-xenon mixtures.  
Pressure = 1 atm.




Figure 3b. Transport properties of hydrogen-xenon mixtures.  
Pressure = 1 atm.




Figure 3c. Transport properties of hydrogen-xenon mixtures.  
Pressure - 1atm.

Saxena and Tondon [1971] measured conductivities for five mole fractions of xenon from 0 to 1.0 at 40°, 65° and 93°C (104°, 149° and 199°F). The measurements of the two investigations are in good agreement with each other, particularly near the mixture concentration (mole fraction of Xe = 0.21) used in this investigation, but are as much as fifteen percent higher than predicted values at 93°C (199°F).

For the present concentration, the experimental values of thermal conductivity were extrapolated to the maximum mixture temperature used, and it was found that the measured conductivity was twenty percent higher than the predicted value. A method recommended by Kestin [personal communication, 1983], but not with complete confidence, is described by Clifford et al. [1980]. The thermal conductivities calculated by this method are closer to the experimental values than those predicted by the method of Lindsay and Bromley, but are still fifteen percent lower at 283°C. As a consequence of this discrepancy in thermal conductivity, the heat transfer data of this investigation were reduced twice, once using the lower predicted values and once using the values obtained by extrapolating the experimental values. The normalized Nusselt number was found to be six to ten percent higher when the calculated thermal conductivity was used rather than the extrapolated experimental value.

As a result of the variations of the calculated thermal conductivity, viscosity and specific heat versus the molecular weight, the calculated Prandtl number decreases to a minimum of about 0.18 at  $\tilde{M} = 47$  from 0.707 for hydrogen and 0.667 for xenon. It is about 0.20 at  $\tilde{M} = 29$  which is the molecular weight of both air and the hydrogen-xenon mixture

used in this investigation. When based on the experimental thermal conductivity a value of 0.18 is predicted for this mixture.

## **THE EXPERIMENT**

### **Apparatus**

The experimental apparatus, arrangement and procedure were similar to those used by Park, Taylor and McEligot [1982]. In the present investigation the loop was a closed circuit, as shown in Fig. 4, due to the extremely high cost of the xenon gas. A single-acting "Gas Booster Pump" from Haskel Manufacturing Company circulated the gas mixtures through two pressure regulators, a plenum, a cooler which removed the heat of compression, a tubular flowmeter, the instrumented test section, another cooler to remove the energy added in the heated test section, a UGC densitometer, another plenum, a control valve and then back into the pump. The two pressure regulators and plenum were installed to remove the pressure fluctuations in the flow created by the pump. Two pressure transducers were used to measure the pressure fluctuations; a Model SCD 147 from Data Instruments, Inc. was located just beyond the first cooler and a Kulite Model XT-140-100G subminiature pressure transducer was mounted flush with the inside of the tube immediately beyond the elbow at the entry of the test section to measure the pressure fluctuations of the flow entering the test section.

The vertical test section was a circular tube of Inconel 600 with an inside diameter of 5.87 mm (0.231 in) and a wall thickness of 0.28 mm




Figure 4. Schematic diagram of experimental apparatus.

(0.011 in). It consisted of a heated section 60 diameters in length preceded by an unheated section of 56 diameters which insured that the flow approached a fully developed velocity profile prior to heating. The test section itself served directly as an electrical resistance heater. Alternating current from a line voltage stabilizer was supplied via variable transformers to the test section through thin stainless steel electrodes brazed to the tube. The current was measured using a Weston current transformer and a Weston Model 370 ammeter. A high impedance Fluke differential voltmeter measured the voltage across the test section to serve as a check on power measurements. Three pressure taps, with holes of about 0.30 mm (0.012 in.) were used. One was located 5 diameters below the lower electrode and the other two were 50 and 54 diameters above it, near the upper electrode. The static pressure at the test section inlet was measured with a Heise bourdon tube gauge and the pressure drop between taps was measured with an MKS Baratron Type 77 Pressure Meter and Head. The fluctuating signals from the Kulite pressure transducer were recorded on a Hewlett-Packard x-y recorder.

Twenty-one premium grade Chromel-Alumel thermocouples, 0.13 mm (0.005 in.) in diameter were spot welded to the heated section of the tube using the parallel junction technique suggested by Moen [1960]. Thermal conduction error was calculated from the heat loss calibration data and a relation developed by Hess [1965]; the thermocouple conductance was estimated from the emissivity of the bare wire and a natural convection correlation for small Rayleigh numbers [Kreith, 1973]. The correction was of the order of 1% of the difference between the tube temperature and the



environmental temperature; at  $Re \sim 3 \times 10^4$  this correction was equivalent to 1-1/2 to 2% in the Nusselt number.

#### Procedures and Preliminary Measurements

The test section was a bare tube surrounded by a draft shield so the heat loss was by radiation and natural convection. The heat loss was calibrated as a function of axial position and temperature from measurements with a vacuum on the inside of the test section. the uncertainty of the heat loss measurements was estimated to be about 1%. The heat loss data were represented by cubic equations that deviated no more than three percent except at very low test section temperatures  $121^\circ\text{C}$  ( $250^\circ\text{F}$ ) where the deviation might be as much as ten percent. For tests with gas flow the heat loss was usually less than 10% of the heat generated. A few runs with inlet Reynolds number less than 36000 and maximum wall temperatures greater than  $650^\circ$  ( $1200^\circ\text{F}$ ) had heat losses exceeding 20% of the heat generated. The worst case was a heat loss of 41% for helium-xenon ( $M \sim 83.8$ ) with an inlet Reynolds number of 34000 and a maximum wall temperature of  $680^\circ\text{C}$  ( $1256^\circ\text{F}$ ). The electrical resistance of the test section was also measured as a function of temperature during the heat loss runs; the estimated uncertainty was also about 1%.

The closed loop was pressurized with gases and gas mixtures from high pressure cylinders. A cylinder of helium-xenon gas mixture with a molecular weight of 83.8 was obtained from the NASA-Lewis Research Center. Helium-xenon mixtures of lesser molecular weight were obtained in the loop by adding helium to the existing gas mixture. On the other hand, the

hydrogen-xenon mixture was obtained by mixing high purity hydrogen directly with high purity xenon. The partial pressures of the gases in a mixture were used to calculate the quantity of helium needed to reduce the molecular weight of the helium-xenon mixture and also to determine the amounts of hydrogen and xenon needed to obtain the particular mixture for a given run.

The UGC gas densitometer was calibrated with air, argon, helium and the helium-xenon gas mixture ( $\bar{M} = 83.8$ ) over the pressure range of this investigation. The densitometer was used to verify the procedures for mixing the gases to predetermined concentrations in situ and also for checking the concentrations after a series of runs. This was done by comparing the measured density with the density calculated using the measured temperature and pressure and the perfect gas law. The measured and calculated densities usually agreed within one percent and the mixture molecular weight did not change measurably during the runs. Mass flow rate was determined with the tubular flowmeter, which was itself calibrated over the range of interest using several positive displacement meters in parallel. The mass flow rate could be determined within an uncertainty of 1.5% or better.

Park, Taylor and McEligot [1982] reported the results of an experiment on the effects of pulsating flow on heat transfer with air with the same apparatus modified to an open loop configuration, so that the mass flow rate could be measured directly with positive displacement meters at the exit of the loop. The static pressure fluctuations were as large as could be attained with the gas booster pump in this system (9 to 35%).

Frequency ranged from 2.1 to 3.6 Hertz,  $q^+$  from zero to 0.0034 and Reynolds numbers from 18,000 to 102,000. For the range of conditions in the present investigation the effect of pressure fluctuations from 26 to 35% had less than a 2% effect on the Nusselt number [Park, Taylor and McEligot, 1982]. The pressure fluctuations in the gas mixtures were never more than 0.6% (usually less than 0.2%) and had a frequency no greater than 2.0 Hertz. Thus, any effect of pressure fluctuations on the Nusselt number of the present gas mixture experiments is believed to be negligible. Results from runs made with air pulsating at the present levels in the closed loop compared closely with those from similar runs conducted with the loop open and no pressure fluctuations.

The procedure for the experimental runs was to introduce the proper amounts of the gases into the closed loop and then circulate the mixture until the density of the gas reached steady state as measured by the densitometer. The mass flow rate was set to give the required Reynolds number, and then the electrical power to the test section was adjusted to give a series of maximum wall temperatures of approximately 120°C (250°F), 260°C (500°F), 400°C (750°F), 540°C (1000°F) and 680°C (1250°F). After covering the range of wall temperature the mass flow rate could be changed to give the next required Reynolds number. Once the range of Reynolds number was covered, the power was shut down and the gas flow stopped. At this time the density was again measured to determine whether the molecular weight had changed due to preferential leakage of the hydrogen or helium. No change in molecular weight could be detected at any time during the experiment.

During each run the wall temperatures along the heated and unheated test section were recorded along with the inlet static pressure and the pressure difference across both the tubular flow meter and the heated test section. The current through the test section and the voltage drop were recorded. The bulk temperature of the gas entering the tubular flow meter was measured and the temperature of the gas entering the heated test section was deduced from this measured temperature and the wall temperatures of the unheated section just downstream of the start of heating.

The data were reduced to give local heat transfer and fluid flow parameters. As described later in the Experimental Results, the ratio of measured Nusselt number to the Nusselt number predicted by Dittus and Boelter [1930] was plotted as a function of the ratio of wall-to-bulk gas temperature and was then extrapolated to  $T_w/T_b = 0$  to deduce a constant property Nusselt number versus position for each gas mixture and Reynolds number. This constant property Nusselt number was compared to the predicted values suggested by several investigators mentioned earlier. The heat transfer and friction data with property variation were reduced and compared with existing correlations.

#### Experimental Uncertainties:

The experimental uncertainties were estimated by the method of Kline and McClintock [1953]. Typical uncertainties for the Nusselt number were about 8% at  $x/D \sim 1.3$  decreasing to 5% at  $x/D > 24$  for low heating rates, and about 1.4% at  $x/D \sim 1.3$  increasing to 4% at  $x/D < 24$  for the

higher heating rates. These estimates are in good agreement with the estimates made by Serksnis [1977] for  $H_2 - CO_2$  experiments and by Pickett [1976] for He-Ar experiments, both in open loop configurations. For the low heating rates, the dominant uncertainties are provided by the inlet bulk gas temperature and the wall temperatures. For higher heating rates, the uncertainty increases with  $x/D$  because the uncertainties in tube wall temperature and, therefore, temperature difference increase significantly with temperature level, while the contributions of uncertainties in mass flow rate, electrical power and inlet gas temperature remain small. Typical uncertainties for air, He-Xe ( $\tilde{M} \approx 40$ ) and  $H_2$ -Xe ( $\tilde{M} \approx 29$ ) data are shown in Table A2 in Appendix A.

#### Reproducibility

The reproducibility of the measurement technique was checked in two ways. Air data in steady flow had been obtained previously in two other test sections by Serksnis, Taylor and McEligot [1978] and Pickett, Taylor and McEligot [1979]. It was found that each had a series of runs at  $Re_i$  near 80,000 and various heating rates, so these were compared to present measurements at the same conditions. For the three sets of data which spanned a five-year period, it was found that in the downstream region the normalized Nusselt number,  $Nu/(0.021Re^{0.8} Pr^{0.4})$ , agreed to within three percent at low heating rates ( $T_w/T_b \approx 1.2$ ) and within two percent at higher heating rates ( $1.4 < T_w/T_b < 1.8$ ).

Secondly, the reproducibility of the present measurements was tested at the end of the experiments by duplicating one of the first runs

with  $Re_i \sim 60,000$ ,  $q^+ = 0.0014$  (maximum  $T_w/T_b \sim 1.5$ ) and steady conditions. The mass flow rate could be reproduced to better than 0.2%, the test section inlet pressure to within less than 0.1% and the electrical current within the accuracy of ammeter ( $\sim 0.25\%$ ). The resulting values of  $(T_w - T_{b,in})_{max}$  differed by 2.1%, leading to agreement of the fully developed Nusselt numbers within less than 3% again.

### EXPERIMENTAL RESULTS

The ranges of the present data have been previously presented as Table 2. Tabulations of these data are provided in Appendix B. Data for helium-argon mixtures are tabulated in the report by Pickett [1976] and for hydrogen-carbon dioxide mixtures by Serksnis [1977].

#### Heat Transfer with Constant Properties

To compare experimental data with constant property correlations the measurements were extrapolated to the constant property idealization by an approach like that of Malina and Sparrow [1964]. For this method, a series of experimental runs was taken with the same inlet Reynolds number and gas composition but with successively higher heating rates. At each thermocouple location the normalized value of the measured Nusselt number,  $Nu/Nu_{DB}$ , was plotted versus the local ratio of wall to bulk temperature,  $T_w/T_b$ . An extrapolation to  $T_w/T_b = 1$  yielded the deduced Nusselt number for constant property conditions,  $Nu_{cp}$ .

For fully developed conditions with air as the fluid, the ratio of  $Nu_{cp}/Nu_{DB}$  was about 0.94 for Reynolds numbers from about 34,000 to 85,000 without any apparent dependence on Reynolds number. The variations of  $Nu_{cp}/Nu_{DB}$  with  $T_w/T_b$  for several thermocouple locations are shown in Figure 5 for air and three binary gas mixtures. It can readily be seen that the extrapolated values of  $Nu_{cp}/Nu_{DB}$  decrease from 0.94 for a Prandtl number of 0.72 to 0.86 at  $Pr = 0.42$ , 0.76 at  $Pr = 0.21$  and 0.66 at the lowest Prandtl number. This reduction in the normalized value corresponds to the trend predicted by an analysis by Pickett, Taylor and McEligot [1979].

The constant property Nusselt numbers for Prandtl numbers from 0.18 to 0.72 for three Reynolds numbers are compared to various correlations from references from Dittus-Boelter [1930] through Churchill [1977] in Figure 6. The solid symbols denote data from the present investigation. The air data from Pickett [1976] and Serksnis [1977] and the present investigation agreed to within less than 3% and are represented by a single solid symbol. As the Reynolds number increases, the deviation between the predictions of various correlations also increases. At Reynolds numbers of 34,000 and 60,000 there is little difference between the values predicted by Kays [1966] and Petukhov and Popov [Petukhov, 1970], and both are in reasonably good agreement with the experimental data for Prandtl numbers from about 0.2 to 0.72. However, for a Reynolds number of 84,000, the difference between the Petukhov and Popov and Kays' correlations widens and the Petukhov relation agrees more closely with experiments at the lower Prandtl number.




Figure 5. Technique for determining constant property Nusselt number.






Figure 6a. Comparison between measured Nusselt number and Nusselt number predicted by correlations proposed by other investigators for constant properties.




Figure 6b. Comparison between measured Nusselt number and Nusselt number predicted by correlations proposed by other investigators for constant properties.




Figure 6c. Comparison between measured Nusselt number and Nusselt number predicted by correlations proposed by other investigators for constant properties.

There could be concern about the possibility of thermo-diffusion at high temperatures with the high ratios of molecular weights of the gases used in the binary mixtures. However, any effect of thermo-diffusion should reduce to zero as the data are extrapolated to a  $T_w/T_b = 1$ .

#### Heating with Property Variation

If power densities are to be increased, or the weight of systems such as the closed cycle gas turbine reduced, moderately high heating rates must be employed. Then, the temperature-dependence of the fluid transport properties will cause significant variation in properties appearing in the correlation equations for both heat transfer and friction coefficients. The results and correlations based on the constant properties idealizations become invalid. In this section the proposed modifications accounting for property variations are examined.

Since pressure taps were installed only near the entrance and exit of the test section, local friction factors could not be determined in this investigation. Overall average friction factors with heat addition were compared to the correlation proposed by Taylor [1967]

$$f_{av} = (0.0014 + 0.125Re_w^{-0.32})(T_{w,av}/T_{b,av})^{-0.5} \quad (10)$$

for the data of a wide variety of experiments with gas flow with  $0.62 \lesssim Pr \lesssim 0.81$ . Most previous measurements agreed within 10%. For

evaluation of this expression, integrated averages of both the local wall and local bulk gas temperature were used along with the average pressure to determine average density and viscosity. The overall friction factor was determined from the frictional pressure drop,

$$\Delta p_{fr} = p_1 - p_2 - \frac{G^2 R}{g_c} \left( \frac{T_{b2}}{p_2} - \frac{T_{b1}}{p_1} \right) \quad (11)$$

and the modified wall Reynolds number was defined as

$$Re_w = (GD/\mu_w) (T_{b,av}/T_{w,av}) \quad (12)$$

In the present study correlation (10) predicted most of the data within 5%. These measurements are presented in Figure 7. The few data deviating more than -5% from the correlation were mixture runs with maximum wall temperatures in excess of 668°C (1234°F) and  $T_w/T_b > 1.8$  and with modified wall Reynolds numbers in the low range between 8,000 and 20,000. The data deviating more than +5% were all air runs with modified wall Reynolds numbers between 8,500 and 17,500. There appeared to be no effect of Prandtl number.

Experimental local Nusselt numbers were compared to Nusselt numbers predicted by modified forms of the prediction equations recommended by Pickett, Taylor and McEligot [1979]

$$Nu_b = 0.021 Re_b^{0.8} Pr_b^{0.55} [(T_w/T_b)^{0.4} + 0.85 D/x] \quad (13)$$

and by Taylor [1968]

$$Nu_b = 0.023 Re_b^{0.8} Pr_b^{0.4} (T_w/T_b)^{-a} \quad (14)$$

	$\hat{M}$	Pr
○	29	0.72
□	29	0.18
●	84	0.25
△	40	0.21
✱	28.3	0.23
◇	14.5	0.30




Figure 7. Comparison of average friction factors to Taylor [1967] correlation for variable gas properties.

where  $a = (0.57 - \frac{1.59}{x/D})$

For the present comparisons a value of 0.65 was finally taken as the exponent of the Prandtl number in both of these equations.

Figure 8 shows the ratios of the measured Nusselt number to the Nusselt number predicted from Equation (13) and (14) as functions of  $x/D$  for two heating rates of air, He - Xe ( $\tilde{M} = 14.5$ ,  $Pr = 0.30$ ) and  $H_2$  - Xe ( $\tilde{M} = 29$ ,  $Pr = 0.18$ ). The data shown here are typical of all the data measured in this investigation. Both of the correlation equations appear to predict downstream Nusselt numbers with acceptable accuracy for all three Prandtl numbers. Both equations predict entrance effects better for the low heating rate than for the higher rate and are in close agreement with each other, even though the methods of handling entrance effects are different. A better understanding of entrance effects is needed.

Increasing the exponent of the Prandtl number to 0.65 yielded considerable improvement and promise in the predictions using Equations (13) and (14) for all Prandtl numbers. The value of  $Pr^{0.65}/Pr^{0.4}$  is 0.65 for  $Pr = 0.181$ , 0.74 for  $Pr = 0.30$  and 0.92 for air; it is obvious that determining the correct exponent for Prandtl number is far more difficult for values of Prandtl number near 1 than in the lower Prandtl number cases, where the sensitivity of the Nusselt number to the Prandtl number exponent is much greater.

He-Xe,  $\hat{M}=14.5$ ,  $Pr=0.30$ ,  $Re=38\,000$   
 Modified Eq (13) Modified Eq (14)  $(T_w/T_b)_{max}$  Run





Figure 8a. Comparison to correlations for heat transfer with gas property variation.



Modified Eq (13) · Modified Eq (14)  $(T_w/T_b)_{\max}$  Run

Air,  $\hat{M}=28.97$ ,  $Pr=0.72$ ,  $Re=84700$

Modified Eq (13) Modified Eq (14)  $(T_w/T_b)_{max}$  Run

● 1.19 724H  
 ▲ 2.00 734H




Figure 8c. Comparison to correlations for heat transfer with gas property variation.

Examination of air data with Reynolds numbers of  $\sim 34,000$ ,  $65,000$  and  $85,000$  showed less than 3% variation of  $Nu/Nu_p$  with Reynolds number for a particular heating rate for all  $x/D$  greater than 2.2. The same held true for the gas mixtures when two Reynolds numbers were available for comparison at the same mixture concentration.

### CONCLUSION

From experiments with heated flow of helium-xenon and hydrogen-xenon mixtures with Prandtl numbers in the range 0.18 to 0.30, the following major conclusions may be drawn. The Colburn analogy and the Dittus-Boelter correlation based on measurements for  $Pr > 0.7$ , greatly overpredict Nusselt numbers for fully established conditions with constant properties in this range. The correlation equation of Sleicher and Rouse and also that of Churchill underpredict the Nusselt number in this range. Of the correlations examined, that of Petukhov [1970] best represents the data the constant property Nusselt number at  $0.18 < Pr < 0.72$  in fully established conditions.

The friction coefficients for flow with property variation were predicted within  $\pm 5\%$  by the correlation proposed by Taylor [1967], Equation (10), for modified wall Reynolds numbers greater than 20,000.

Nusselt numbers for flow with property variation were predicted using the correlation recommended by Pickett, Taylor and McEligot [1979], Equation (13), and Taylor [1968], Equation (14), but with the exponent of Prandtl number increased 0.65 in both cases. The predictions of both

correlations are in good agreement with each other. For low heating rates the measured and predicted values agreed within  $\pm 10\%$  for axial distances from 4.3 to 52.3 diameters. For the higher heating rates both equations failed to predict the effects of the entrance region adequately at  $x/D$  less than about 20. Most of the data at  $x/D$  greater than 20 was predicted within  $\pm 10\%$ .

#### ACKNOWLEDGEMENTS

We appreciate the help of Dr. William G. Harrach of AiResearch Manufacturing Company of Arizona, who originally suggested this topic and also supplied the programs for the calculation of the fluid properties. Thanks are due also to Ms. Elmira Reavis and Mrs. Margaret F. Wheeler for changing our rough draft into a finished manuscript and to Mrs. Alison Habel for drawing the figures in this report.

**APPENDICES**

## APPENDIX A

### Uncertainty Analysis

To determine the validity of the deduced results it is necessary to determine their estimated experimental uncertainties. An analysis has been conducted in accordance with recognized procedures to estimate the percent uncertainty in the important heat transfer and friction characteristics along the test section. Doebelin [1966] considers the problem of computing a quantity  $N$ , where  $N$  is a known function of the  $n$  independent variables,  $u_1, u_2, u_3, \dots, u_n$ . That is,

$$N = \text{fn} (u_1, u_2, u_3, \dots, u_n) \quad (\text{A1})$$

The  $u$ 's are the measured quantities (instrument or component outputs) and are uncertain by  $\pm \Delta u_1, \pm \Delta u_2, \pm \Delta u_3, \dots, \pm \Delta u_n$ , respectively. These uncertainties will cause an uncertainty  $\Delta N$  in the computed result  $N$ . We are concerned with experimental uncertainties here rather than systematic errors, like the thermocouple conduction error which can be corrected. The  $u$ 's may be considered as absolute limits on the uncertainties, as statistical bounds such as  $3\sigma$  limits, or as uncertainties on which we are willing to give certain odds as including the actual error. However, the method of computing  $\Delta N$  and the interpretation of its meaning are different for the first case as compared with the second and third. After calculating the limits on the uncertainty in  $N$ , then  $N \pm \Delta N$  and the

percentage uncertainty is known. In all cases, systematic errors (bias) were removed by calibration where they were known to exist.

If the individual errors are thought of as  $\pm 3\sigma$  limits, then, as shown by Kline and McClintock [1953], the general equation used is

$$\Delta N = E_{\text{arss}} = \sqrt{(\Delta u_1 \frac{\partial f}{\partial u_1})^2 + (\Delta u_2 \frac{\partial f}{\partial u_2})^2 + \dots + (\Delta u_n \frac{\partial f}{\partial u_n})^2} \quad (\text{A2})$$

where  $E_{\text{arss}}$  represents a  $\pm 3\sigma$  limit on  $N$  and 99.7 percent of the values of  $N$  can be expected to fall within these limits (arss = absolute root-sum square).

An analysis was performed to determine the uncertainty of local bulk Nusselt number,  $Nu$ , as calculated from the measured experimental data. Table A1 lists the uncertainties of the instruments ( $\Delta u$ 's) used in this investigation. The uncertainties of the directly measured quantities were determined from manufacturers' specifications and experience. The uncertainties of the gas properties were not included.

The estimated uncertainty in the experimental Nusselt number which results from the uncertainty in a measured variable is shown in Table A2. The measured variables included mass flow rate, current, inlet bulk temperature of the gas, wall temperature, inlet static pressure, and the resistance per unit length of the test section. Uncertainties,  $\Delta u$ , in these measurements were assigned from Table A1 and their values are shown in Table A2. An uncertainty in mass flow rate of 1.5 percent was used in Table A2. The values of  $\partial Nu / \partial u$  in Table A2 were attained by changing the variable by an amount equal to its estimated uncertainty and rerunning the



Table A1. Uncertainties of Measured Values

Measured Quantity	Instrument	Uncertainty (Based on Manufacturer's Specification Unless Otherwise Stated)	Notes
Current	Weston Ammeter Model 370 No. 13605	0.0 to 2.0 amp range, $\pm 0.17\%$ of full scale 2.0 to 5.0 amp range, $\pm 0.25\%$ of full scale	
Voltage	Fluke Voltmeter Model 883AB	$\pm 0.1\%$ of input voltage	Voltmeter used as a check on test section voltage
Mass Flow Rate	Calibrated tubular flow meter	$\pm 1.5\%$ of flow rate measured with positive displacement meter	Tubing for test section and flow meter from same manufacturer shipment
Wall and Inlet Bulk Temperature	Keithley Model 179 Digital Multimeter	$\pm 0.004\%$ of reading (200mV range = 0.014mV)	
	Premium Grade Chromel - Alumel Thermocouples	$\pm 2$ F, 3/8% of reading above 553K (535F)	For relative measurements, uncertainty can be considered better as same spool of wire was used
Thermocouple Location Pressure Tap Location	Gaertner Cathetometer	$\pm 0.1\%$ of distance from datum	(Estimate of uncertainty)

Table A1. Uncertainties of Measured Values (continued)

Measured Quantity	Instrument	Uncertainty (Based on Manufacturer's Specification Unless Otherwise Stated)	Notes
Test section I.D. and O.D.	Starret Micrometer and small hole gage	$\pm 0.001$ inch	Uncertainty based on calibrated tubular flow meter uncertainty
Static Pressure	Heise bourdon tube gage	$\pm 0.15$ psia	
	Kulite XT-140-100G Pressure Transducer	$\pm 0.1\%$ of full scale (100 psig)	
Atmospheric Pressure	Welch Mercury Barometer	$\pm 0.05$ psia ( $\pm 0.03$ in Hg)	(Estimate of uncertainty)
Pressure Drop	MKS Baratron Pressure Meter	Accuracy of $\pm 0.02\%$ of full range plus $0.15\%$ of dial reading. Repeatability of $\pm 0.005$ to $0.02\%$ of full range (Full range = 1000 mmHg)	

Table A2. Percentage Uncertainties in the Measured Nusselt Number.

	x/d	Variable, u										E <sub>arsa</sub>	% Uncertainty
		m		I		T <sub>b</sub> , in		T <sub>w</sub>					
		$\frac{\partial \text{Nu}}{\partial u}$	$\Delta u$	$\frac{\partial \text{Nu}}{\partial u}$	$\Delta u$	$\frac{\partial \text{Nu}}{\partial u}$	$\Delta u$	$\frac{\partial \text{Nu}}{\partial u}$	$\Delta u$				
Run 704 He-Xe $\dot{M} \approx 40$	1.3	0.04	1.5%	0.58	0.25% of full scale	2.13	2.0°F	2.28	2.1°F	6.240	8.14		
	2.2	.05	0.83 $\frac{\text{lbm}}{\text{hr}}$	.54	0.25 amp	1.77		1.93		5.239	7.45		
	4.3	.08		.50		1.38		1.53		4.123	6.60		
	10.9	.14		.47		1.06		1.20		3.207	5.86		
	23.9	.25		.50		.91		1.04		2.774	5.55		
	43.6	.45		.58		.87		.98		2.65	5.61		
	52.6	.52		.61		.83		.95		2.564	5.58		
Run 701 He-Xe $\dot{M} \approx 40$	1.3	0.02	1.5%	0.63	0.25% of full scale	0.22	2.0°F	0.44	2.0°F	1.033	1.40		
	2.2	.02	0.81 $\frac{\text{lbm}}{\text{hr}}$	.57	0.5 amp	.16		.35	2.0	.821	1.24		
	4.3	.03		.48		.10		.28	2.2	.691	1.22		
	10.9	.05		.40		.07		.24	2.6	.671	1.48		
	23.9	.08		.36		.06		.23	3.2	.770	2.13		
	43.6	.18		.40		.07		.25	3.7	.968	3.07		
	52.6	.23		.41		.07		.28	3.9	1.135	3.77		
Run 701 He-Xe $\dot{M} \approx 40$ $\text{Re}_{\text{in}} = 58900$ $\left(\frac{T_w}{T_b}\right) = 1.83$ $\left(\frac{T_w}{T_b}\right)_{\text{max}}$													

Table A2. Percentage Uncertainties in the Measured Nusselt Number (continued)

	x/D	Variable, u										E <sub>ass</sub>	Z Uncertainty
		■		I		T <sub>b</sub> in		T <sub>w</sub>					
		$\frac{\partial Nu}{\partial u}$	$\Delta u$	$\frac{\partial Nu}{\partial u}$	$\Delta u$	$\frac{\partial Nu}{\partial u}$	$\Delta u$	$\frac{\partial Nu}{\partial u}$	$\Delta u$				
Run 722 H <sub>2</sub> -Xe H = 29.0 Re <sub>in</sub> = 73800	1.3	0.05	1.5%	0.48	0.25% of full scale	2.99	2.0°F	3.05	2.0°F	8.54	11.21		
	2.2	.06	0.84 $\frac{\text{lbm}}{\text{hr}}$	.43	0.25 amp	2.60		2.68		7.49	10.49		
$\frac{T_w}{T_b} = 1.13$	4.3	.09		.36		2.02		2.13		5.87	9.26		
T <sub>b</sub> max	10.9	.16		.30		1.51		1.63		4.45	8.09		
	23.9	.29		.27		1.27		1.39		3.77	7.55		
	43.6	.48		.26		1.16		1.27		3.46	7.39		
	52.6	.55		.29		1.11		1.22		3.33	7.32		
Run 720 H <sub>2</sub> -Xe	1.3	0.01	1.5%	0.64	0.25% of full scale	0.21	2.0°F	0.36	2.0°F	0.797	1.10		
	2.2	.01		.61		.15		.32	2.0	.770	1.18		
H = 29.0	4.3	.02		.55		.09		.28	2.1	.674	1.21		
Re <sub>in</sub> = 71200	10.9	.04	0.82 $\frac{\text{lbm}}{\text{hr}}$	.53	0.5 amp	.05		.23	2.6	.663	1.48		
$\frac{T_w}{T_b} = 1.78$	23.9	.05		.55		.05		.22	3.1	.743	2.06		
	43.6	.13		.61		.05		.23	3.7	.916	2.95		
	52.6	.18		.64		.06		.24	3.9	1.007	3.37		

Table A2. Percentage Uncertainties in the Measured Nusselt Number (continued)

	x/D	Variable, u										E <sub>arss</sub>	% Uncertainty
		m		I		T <sub>b</sub> in		T <sub>n</sub>					
		$\frac{\partial \text{Nu}}{\partial u}$	$\Delta u$	$\frac{\partial \text{Nu}}{\partial u}$	$\Delta u$	$\frac{\partial \text{Nu}}{\partial u}$	$\Delta u$	$\frac{\partial \text{Nu}}{\partial u}$	$\Delta u$				
Run 727 II Air  Re <sub>In</sub> = 66100	1.3	0.02	1.5%	1.37	0.25% of full scale	3.11	2.0°F	3.53	2.0°F	9.415	6.35		
	2.2	.04		1.30		2.77		3.19		8.456	5.96		
	4.3	.07		1.22		2.33		2.73		7.185	5.49		
	10.9	.16	0.68 $\frac{\text{lbm}}{\text{hr}}$	1.16	0.25 amp	1.92		2.31		6.015	5.05		
	23.9	.32		1.19		1.71		2.07		5.382	4.84		
	43.6	.54		1.29		1.60		1.93		5.038	4.77		
	52.6	.62		1.31		1.54		1.86		4.859	4.74		
Run 738H Air  Re <sub>In</sub> = 64200	1.3	0.00	1.5	0.99	0.25% of full scale	0.01	2.0°F	0.66	2.8°F	1.913	1.32		
	2.2	.01	0.66 $\frac{\text{lbm}}{\text{hr}}$	.89	0.5 amp	.05		.60	3.1	1.915	1.44		
	4.3	.02		.78		.06		.53	3.5	1.899	1.62		
	10.9	.01		.68		.02		.49	3.9	1.941	1.93		
	23.9	.01		.60		.01		.50	4.4	2.220	2.70		
	43.6	.16		.63		.06		.56	4.7	2.656	3.57		
	52.6	.23		.65		.05		.59	4.9	2.915	4.06		

computer program for data reduction at the experimental conditions. It was found that a change of 0.2 psia to the inlet static pressure did not change the experimental Nusselt number noticeably. Also, an uncertainty of 0.00008  $\Omega/\text{in}$  in the measurement of resistance per unit length had an insignificant effect on the percentage uncertainty in the experimental Nusselt number.

Three types of comparisons can be made from Table A2. A comparison between the two runs shows that the percentage uncertainty for a relatively low heating rate run to be higher than a high heating rate run at about the same Reynolds number. The result is due to the relatively high percentage uncertainties in the inlet bulk and wall temperatures being much more dominant in the lower heating rate case. Secondly, the change in the percentage uncertainty along the axial length of the test section can be examined. For the low heating rates the major uncertainties in the Nusselt number are provided by the inlet bulk gas temperature and the wall temperatures; they decrease with  $x/D$ . For higher heating rates, the uncertainty increases with  $x/D$  because the uncertainties in tube wall temperature and, therefore, temperature difference increase significantly with temperature level, while the contributions of uncertainties in mass flow rate, electrical power and inlet gas temperature remain small. Thirdly, the individual variables can be compared to each other for the two different heating rates as well as for the range of  $x/D$ .

# APPENDIX B

## EXPERIMENTAL DATA WITH HEAT ADDITION

Table B1. Summary of Experimental Data

Run	Gas	M	$Pr_i$	$Re_i$	$(T_w/T_b)_{max}$	$q^+_{max}$
686H	He-Xe	83.8	0.25	85147	1.18	0.0007
687H				85802	1.42	.0016
688H				86740	1.65	.0026
689H				87373	1.89	.0035
690H				86063	2.17	.0049
691H				32646	1.16	.0009
692H				32647	1.39	.0022
693H				33513	1.62	.0034
694H				33328	1.88	.0051
695H				33947	2.22	.0069
696H	He-Xe	40.0	0.21	36183	1.99	.0053
697H				34994	1.75	.0041
698H				34280	1.59	.0032
699H				34686	1.36	.0018
700H				34865	1.15	.0007
701H				58657	1.83	.0039
702H				58525	1.59	.0027
703H				61534	1.38	.0017
704H				59851	1.17	.0008
705H				61772	1.77	.0037
707H	He-Xe	28.3	0.23	53390	1.67	.0030
708H				55449	1.38	.0017
709H				48411	2.06	.0051
710H				49001	1.16	.0007
711H	He-Xe	14.5	0.30	40869	1.15	.0006
712H				40554	1.32	.0013
713H				35374	1.61	.0027
714H				38962	1.84	.0034
715H				34042	2.04	.0047
719H	H <sub>2</sub> -Xe	29.0	0.18	73916	1.48	0.0021
720H				71174	1.78	.0034
721H				72531	1.30	.0013
722H				73803	1.13	.0005

Table B1. Summary of Experimental Data  
(continued)

Run	Gas	M	Pr <sub>i</sub>	Re <sub>i</sub>	(T <sub>w</sub> /T <sub>b</sub> ) <sub>max</sub>	q <sub>+</sub> max
723H	Air	28.97	0.72	84169	1.20	.0005
724H				84455	1.19	.0005
725H				84778	1.46	.0012
726H				64990	1.40	.0012
727H				66076	1.19	.0005
728H				34149	1.74	.0023
729H				34946	1.45	.0014
730H				34765	1.20	.0006
731H				33882	2.03	.0033
732H				34777	2.35	.0044
733H				84294	1.74	.0019
734H				84742	2.00	.0026
735H				85824	2.30	.0033
736H				64311	1.90	.0024
737H				66215	1.73	.0019
738H				64199	2.38	.0038

The headings and their definitions used in the listing of the heated flow data are below.

Heading	Definition
TIN	Inlet gas temperature, °F
TOUT	Calculated outlet gas temperature, °F
I	Alternating current, amperes
E	Voltage drop between voltage taps, volts
PR,IN	Inlet Prandtl number, $c_p \mu/k$
GR/RESQ	Ratio of Grashof number $g D^4 q_w / (\nu^2 k T)_i$ to the square of the inlet Reynolds number, $GD/\mu_i$
MACH (2)	Mach number at thermocouple 2
MACH (16)	Mach number at thermocouple 16



Heading	Definition
TSURR	Temperature of surroundings inside draft shield, °F
Q+(8)	Nondimensional turbulent heat flux parameter. Corresponds to $q^+$ in text at thermocouple 8, $q^+ = q''_w / (G c_{p,i} T_i)$
TC	Thermocouple number
X/D	Axial position, corresponds to x/D in text
HL/QGAS	Ratio of heat loss to heat flux to gas
TW	Inside tube wall temperature, °F
TW/TB	Wall to bulk temperature ratio
QGAS	Heat flux to gas, Btu/hr-ft <sup>2</sup>
HTCOEF	Heat transfer coefficient, Btu/hr-ft <sup>2</sup> -°F
BULK REYNOLDS	Reynolds number evaluated at bulk temperature, $GD/\mu_b$
BULK NUSSELT	Nusselt number evaluated at bulk temperature, $hD/k_b$
PT	Pressure tap: 1-near inlet, 2-near outlet
TB	Bulk static temperature °F
PRESS DEFECT	Pressure defect, $\rho_i g_c (p_i - p)/G^2$
TW,AV(F)	Average inside tube wall temperature °F
TB,AV(F)	Average bulk gas temperature °F
TW,AV/TB,AV	Average wall to average bulk temperature ratio
DELTA P(PSI)	Pressure drop from start of heating to pressure tap #2
RE,B,AV	Average value of bulk Reynolds number from start of heating to pressure tap #2, $GD/\mu_{b,av}$
RE,W,MOD,AV	Average value of modified wall Reynolds number, $GD/\mu_{w,av} (T_{b,av}/T_{w,av})$
F,B,AV	Friction factor through heated section of tube, $g_c \rho_{b,av} D P_{fr} / 2LG^2$

RUN 686H, DATE 4/20/61, GAS HE XC, MOLECULAR WT. = 83.60  
 TIN = 73.7 F, TOUT = 153.8 F, MASS FLOW RATE = 74.8 LB/HR, I = 42.5 AMPS, L = 2.782 VOLT  
 PR,IN = .251, GR/RESQ = .167E-02, MACH(2) = .098, MACH(10) = .105, T,50KR = 83.0 F, J+(d) = .000073

TC	X/D	HL/QGAS	TW (F)	TW/TB	Q/GAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK MUSSELT
2	.1	-.162	107.6	1.067	6731.2	194.61	82147.	273.00
3	.3	.692	119.5	1.089	3322.6	71.88	82103.	101.03
4	.5	.186	126.3	1.105	4737.4	86.46	82053.	121.47
5	.6	.094	134.6	1.116	5144.7	84.72	84999.	110.90
6	1.3	.056	143.1	1.130	5335.3	77.91	84683.	109.29
7	2.2	.038	151.5	1.144	5431.9	71.75	84697.	100.47
8	4.3	.033	163.5	1.159	5461.1	84.54	84223.	89.97
9	7.6	.035	174.6	1.170	5456.3	80.00	83512.	55.05
10	10.6	.037	182.5	1.175	5447.8	57.76	82844.	74.42
11	17.3	.042	196.5	1.180	5424.8	54.77	81510.	74.27
12	23.8	.049	207.0	1.180	5393.2	53.72	80247.	71.91
13	30.4	.053	216.3	1.177	5379.4	53.80	79014.	70.83
14	37.0	.057	226.7	1.176	5360.8	52.79	77624.	68.87
15	43.5	.051	235.8	1.174	5346.8	52.69	76080.	67.90
16	47.9	.064	242.6	1.173	5334.8	52.30	75931.	66.84
17	52.3	.067	249.4	1.172	5321.4	51.83	75200.	65.70
18	56.5	.144	254.9	1.170	4962.8	48.43	74551.	60.94
19	58.5	1.006	244.6	1.149	2826.8	31.37	74317.	59.55
20	59.1	-.113	210.7	1.093	6362.9	115.10	74251.	144.25

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.8	88.5	1.00	72.0	-.550E-01
2	54.0	87.7	1.17	147.8	.718E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	197.5	TW,AV/TB,AV	1.17	DELTA P(PSI)	.786E+00	RE,B,AV	80034.	REYNOLDS,AV	29405.	F,50,AV	83.00
IB,AV(F)	103.8										

RUN 687H, DATE 4/20/81, GAS HE XF, MOLECULAR WT. = 83.80  
 TIN = 72.8 F, TOUT = 265.0 F, MASS FLOW RATE = 75.3 LB/HR, I = 65.5 AMPS, I = 4.327 VOLTS  
 PR,IN = .251, GR/RESO = .404E-02, MACH(2) = .097, MACH(16) = .111, T,SURP = 58.0 F, T+(8) = .001602

TC	X/D	HL/OGAS	TW (F)	TW/IB	QGAS BTU/HRFT2	H T COFF BTU/HRFT2F	BULK RFYNOLLS	BULK NUSSFLT
2	.1	-.171	155.8	1.160	16160.5	192.55	85802.	271.74
3	.3	.725	183.8	1.211	7778.8	70.01	85095.	93.52
4	.5	.164	204.5	1.249	11549.6	88.05	85276.	123.80
5	.8	.106	220.1	1.276	12169.0	83.39	85445.	147.13
6	1.5	.055	241.3	1.312	12731.6	76.98	85160.	107.84
7	2.2	.041	263.5	1.346	12969.0	70.15	84726.	97.00
8	4.3	.036	295.8	1.387	13060.6	62.26	83620.	85.45
9	7.6	.038	324.2	1.410	13060.2	57.58	81946.	78.19
10	10.8	.041	343.5	1.417	13044.2	55.43	80445.	74.12
11	17.4	.048	377.6	1.422	12984.1	52.52	77574.	68.11
12	23.8	.056	404.7	1.416	12912.9	51.17	74939.	64.47
13	30.4	.063	427.8	1.403	12858.1	50.77	72479.	62.16
14	37.0	.069	449.6	1.389	12797.8	50.58	70213.	60.30
15	43.5	.076	469.6	1.374	12736.0	50.69	68136.	58.92
16	48.0	.081	483.6	1.365	12691.5	50.67	66794.	57.91
17	52.4	.086	498.1	1.358	12639.0	50.48	65530.	56.77
18	56.6	.202	512.1	1.352	11433.9	42.51	64447.	55.46
19	58.6	1.263	482.2	1.302	6048.0	27.51	64088.	50.78
20	59.2	.083	447.6	1.252	12634.0	69.98	63907.	77.00

PT	X/D	STATIC PRESS. (PSIA)	TW/IB	IB (F)	PPFS DEFFCT
1	-5.9	64.6	1.00	71.1	-.550E-01
2	54.1	68.5	1.36	251.7	.980E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TE,AV	DELTA P (PSI)	RF,B,AV	RF,W,MOD,AV	F,R,AV
379.4	144.7	1.39	.107E+01	75456.	40326.	.00402

RUN 688H, DATE 4/20/81, GAS HE XE, MOLECULAR WT. = 83.60  
 TIN = 72.8 F, IOUT = 372.3 F, MASS FLOW RATE = 76.2 LB/HR, I = 32.9 AMPS, E = 3.203 VULIS  
 PR,IN = .251, GR/RESQ = .661E-02, MACH(2) = .096, MACH(16) = .116, T,SURR = 121.0 F, W(8) = .002222

IC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK MUSSELLI
2	.1	-.180	205.8	1.254	26256.8	196.26	86740.	276.31
3	.3	.705	251.8	1.338	12105.9	87.04	86507.	95.27
4	.2	.178	282.4	1.399	18387.2	87.01	86573.	122.24
5	.8	.107	309.9	1.441	19606.3	83.57	86168.	117.26
6	1.3	.002	344.4	1.498	20480.5	76.90	85720.	107.48
7	2.2	.043	380.3	1.552	20906.2	70.22	85018.	77.31
8	4.3	.034	433.2	1.615	21074.8	62.17	83268.	84.84
9	7.7	.043	460.9	1.648	21059.9	57.15	80717.	70.00
10	10.8	.048	512.9	1.654	21017.4	54.85	78440.	71.27
11	17.4	.058	556.4	1.646	20885.2	52.07	74221.	54.24
12	23.9	.070	610.5	1.626	20575.0	50.12	70570.	34.00
13	30.5	.084	643.7	1.592	20404.6	44.93	67288.	37.02
14	37.1	.103	676.5	1.562	20144.4	44.66	64371.	34.01
15	43.6	.116	704.4	1.530	20004.0	44.92	61742.	33.02
16	48.1	.127	725.4	1.512	19839.3	44.76	60172.	31.84
17	52.5	.135	742.0	1.490	19714.8	50.14	56880.	30.97
18	56.0	.274	761.8	1.478	17590.4	44.84	57410.	44.70
19	58.7	3.123	713.6	1.404	5417.1	16.03	57074.	15.88
20	54.3	-.117	507.7	1.254	25066.1	119.55	50490.	116.01

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	70.9	1.00	71.1	-.548E-01
2	54.2	69.6	1.48	322.7	.120E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MUD,AV	F,B,AV
567.2	187.3	1.59	.131E+01	72450.	30434.	.00473

RUN 689H, DATE 4/20/81, GAS HE XE, MOLECULAR WT. = 83.80  
 TIN = 72.3 F, TOUT = 407.3 F, MASS FLOW RATE = 76.7 LB/HR, I = 90.4 AMPS, E = 0.490 VOLTS  
 PK,IN = .201, GR/RESQ = .8YLE-02, MACH(2) = .046, MACH(16) = .123, I, SUKR = 150.0 F, W+(8) = .000347

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.191	229.3	1.356	30142.1	192.21	67373.	271.23
3	.3	.804	321.0	1.469	10279.6	65.58	67136.	92.37
4	.5	.166	366.5	1.550	25281.1	86.52	86878.	121.64
5	.8	.120	400.9	1.610	26384.3	81.19	86291.	113.69
6	1.3	.064	448.9	1.668	27048.0	75.41	85992.	105.24
7	2.2	.049	501.0	1.705	28373.2	68.35	85032.	91.23
8	4.3	.046	578.4	1.854	28609.7	60.00	82695.	81.15
9	7.7	.053	645.8	1.891	28548.2	54.93	79360.	71.02
10	10.9	.060	689.1	1.890	28450.7	52.74	70454.	60.09
11	17.4	.077	763.0	1.866	28144.9	49.75	71232.	59.43
12	23.9	.120	823.3	1.829	27180.4	46.89	66890.	53.12
13	30.5	.141	860.5	1.775	26744.0	46.35	63170.	50.02
14	37.1	.168	909.6	1.729	26221.9	45.59	59960.	47.04
15	43.7	.191	944.1	1.681	25766.7	45.55	57184.	45.11
16	48.1	.212	970.5	1.654	25304.8	45.08	55486.	43.51
17	52.5	.229	990.8	1.622	25058.4	45.19	53958.	42.57
18	56.8	.393	1012.7	1.603	22139.0	40.19	52671.	37.06
19	58.8	*****	941.1	1.515	1128.0	2.36	52408.	2.19
20	59.4	-.121	772.0	1.328	34491.0	114.55	52320.	104.09

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	71.4	1.00	70.7	-.548E-01
2	54.3	69.8	1.61	444.7	.142E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	761.5	TB,AV(F)	225.5	TW,AV/TB,AV	1.78	DELTA P(PSI)	.156E+01	RE,B,AV	70411.	RE,W,MUD,AV	24136.	F,B,AV	.00470
----------	-------	----------	-------	-------------	------	--------------	----------	---------	--------	-------------	--------	--------	--------

RUN 690H, DATE 4/20/81, GAS HE XE, MOLECULAR WT. = 83.00  
 TIN = 73.2 F, IOUT = 613.0 F, MASS FLOW RATE = 75.7 LB/HR, I = 113.2 AMPS, C = 7.009 VULID  
 PR,IN = .251, GR/RESQ = .144E-01, MACH(2) = .069, MACH(16) = .121, I,SURK = 204.0 F, W(3) = .004342

IC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	REYNOLDS	BULK NUSSLEI
2	.1	-.197	335.0	1.496	50490.7	192.33	66063.	271.01
3	.3	.780	415.9	1.643	22914.8	67.07	65735.	94.31
4	.5	.157	476.4	1.749	35412.9	88.52	65376.	124.10
5	.8	.115	522.8	1.826	36854.8	83.00	64978.	110.04
6	1.3	.070	589.5	1.933	38595.1	70.35	64153.	102.90
7	2.2	.053	660.8	2.033	39418.4	69.37	62847.	95.11
8	4.3	.052	765.9	2.137	39742.5	61.04	79720.	81.14
9	7.7	.065	859.9	2.170	39524.1	55.64	75364.	70.62
10	10.9	.077	921.2	2.155	39245.5	53.13	71721.	64.70
11	17.4	.102	1014.3	2.084	38606.8	50.47	65442.	50.90
12	24.0	.178	1081.1	1.999	36273.9	47.22	60547.	49.84
13	30.6	.208	1126.2	1.905	35477.5	47.25	56532.	47.00
14	37.2	.242	1169.3	1.825	34601.2	47.17	53198.	44.55
15	43.8	.270	1201.5	1.746	33905.0	47.96	50390.	43.10
16	48.3	.297	1228.1	1.704	33258.5	47.92	46701.	41.87
17	52.7	.317	1247.7	1.661	32767.6	48.52	47202.	41.25
18	56.9	.463	1270.2	1.628	29560.4	44.54	42935.	30.90
19	58.9	****	1184.2	1.537	-3627.6	-6.71	42730.	-5.53
20	59.6	-.114	975.6	1.336	47875.4	133.38	42694.	109.60

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	2.2	76.2	1.00	71.9	-.250E-01
2	54.4	74.5	1.65	563.9	.163E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,M,MUD,AV	F,B,AV
996.5	1.95	.164E+01	60398.	19274.	.00410
286.3					

RUN 091H, DATE 4/21/01, GAS HE XE, MOLECULAR WT. = 83.00  
 TIN = 70.5 F, TOUT = 169.4 F, MASS FLOW RATE = 26.6 LB/HR, I = 30.0 AMPS, E = 1.950 VULIS  
 PR,IN = .251, GR/KESQ = .170E-02, MACH(2) = .066, MACH(10) = .071, I,SURR = 60.7 F, Q+(0) = .000052

TC	X/D	HL/QGAS	TW (F)	TW/To	QGAS BTU/HRFT2	H T LUEF BTU/HRFT2F	BULK KEYNOLDS	BULK NUSSLEI
2	.1	-.260	90.3	1.054	3769.3	134.09	32640.	189.14
3	.3	2.174	108.5	1.073	879.0	23.13	32620.	32.01
4	.5	.269	116.5	1.087	2200.5	48.19	32607.	67.92
5	.8	.183	122.7	1.098	2361.4	45.81	32582.	64.53
6	1.3	.108	131.7	1.113	2523.3	42.32	32528.	59.53
7	2.2	.073	141.1	1.128	2607.1	38.58	32439.	54.16
8	4.3	.066	155.3	1.146	2626.8	33.71	32212.	47.05
9	7.0	.068	167.8	1.156	2622.7	31.09	31867.	43.01
10	10.8	.075	177.1	1.161	2608.0	29.65	31548.	40.67
11	17.3	.087	191.6	1.163	2583.6	28.45	30914.	38.58
12	23.8	.103	203.5	1.161	2540.5	27.90	30328.	37.03
13	30.4	.112	213.6	1.155	2529.4	28.15	29757.	36.70
14	37.0	.122	224.4	1.151	2508.2	28.08	29215.	36.11
15	43.5	.131	234.4	1.147	2490.1	28.28	28704.	35.82
16	47.9	.138	241.6	1.144	2474.9	28.23	28307.	35.40
17	52.3	.144	248.0	1.141	2463.2	28.45	28046.	35.34
18	56.5	.304	253.9	1.138	2067.8	24.04	27775.	29.01
19	58.5	****	256.3	1.108	-97.5	-1.45	27721.	-1.79
20	59.1	-.277	195.9	1.042	3863.4	150.57	27697.	104.92

PT	X/D	STATIC PRESS.(PSIA)	TW/To	TB (F)	PRESS DEFECT
1	-5.8	38.6	1.00	69.8	-.689E-01
2	54.0	38.4	1.14	163.7	.900E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/To,AV	DELTA P(PSI)	RE,B,AV	RE,W,MUD,AV	F,0,AV
192.9	108.1	1.15	.254E+00	30266.	23118.	.00009

RUN 692H, DATE 4/21/81, GAS HE XE, MOLECULAR WT. = 83.80  
 TIN = 71.0 F, TOUT = 320.1 F, MASS FLOW RATE = 28.6 LB/HR, I = 47.0 AMPS, E = 3.122 VOLT  
 PR,IN = .251, GR/KESQ = .434E-02, MACH(2) = .060, MACH(16) = .078, I,SURK = 94.0 F, J+(8) = .002104

IC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H I COEF BTU/HRFT2F	BULK KEYNULUS	BULK NUSSLEI
2	.1	-.263	139.5	1.131	9589.4	139.23	32647.	170.33
3	.3	2.142	104.5	1.176	2252.1	24.19	32597.	34.07
4	.5	.274	104.5	1.212	5561.0	49.49	32544.	67.03
5	.6	.189	200.2	1.240	5908.6	46.94	32480.	82.97
6	1.3	.105	223.3	1.278	6430.8	43.46	32549.	83.88
7	2.2	.083	249.2	1.317	6576.4	38.57	32120.	53.07
8	4.3	.069	286.0	1.361	6680.2	33.89	31507.	40.52
9	7.6	.075	319.8	1.384	6657.8	30.68	30738.	41.48
10	10.8	.082	342.9	1.389	6625.2	29.56	30000.	50.90
11	17.4	.099	380.3	1.383	6545.2	28.23	28608.	52.71
12	23.8	.117	408.7	1.364	6452.7	27.90	27584.	54.01
13	30.4	.130	431.4	1.339	6387.9	28.41	26271.	53.43
14	37.0	.145	453.6	1.316	6313.2	28.93	25208.	52.93
15	43.5	.160	474.0	1.293	6240.2	29.62	24504.	52.73
16	48.0	.172	488.6	1.279	6180.8	30.02	23801.	52.47
17	52.4	.184	501.6	1.265	6126.7	30.57	23281.	52.42
18	56.0	.519	513.5	1.255	4778.2	24.31	22824.	52.40
19	58.0	****	401.9	1.184	-1113.8	-7.82	22801.	-8.14
20	59.2	-.213	371.0	1.065	9134.7	183.37	22772.	190.52

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	5.9	38.9	1.00	70.2	-.089E-01
2	54.1	38.0	1.26	307.2	.125E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MUD,AV	F,8,AV
374.2	166.3	1.34	.349E+00	27871.	15950.	.00001



RUN 693H, DATE 4/21/81, GAS HE XE, MOLECULAR WT. = 83.80  
 TIN = 71.9 F, TOUT = 444.7 F, MASS FLOW RATE = 29.4 LB/HR, I = 60.2 AMPS, E = 4.020 VOLTS  
 PR,IN = .251, GR/RESQ = .633E-02, MACH(2) = .068, MACH(16) = .068, T,SURK = 115.0 F, Q+(6) = .003309

IC	X/D	HL/GGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T CDEF BTU/HRFT2F	BULK REYNOLDS	BULK MUSSELT
2	.1	-.281	185.1	1.215	15762.6	138.84	33213.	172.33
3	.3	2.026	224.5	1.287	3750.9	24.73	33430.	34.74
4	.5	.299	257.6	1.346	8777.4	47.74	33353.	67.00
5	.8	.211	283.2	1.390	9433.8	45.32	33254.	63.22
6	1.3	.117	321.3	1.452	10250.7	42.26	33038.	50.94
7	2.2	.088	363.3	1.513	10553.4	37.88	3282.	22.38
8	4.3	.077	425.2	1.583	10709.8	32.93	31812.	44.22
9	7.7	.088	481.1	1.614	10647.9	29.81	30501.	34.00
10	10.8	.099	518.1	1.615	10507.6	28.44	29472.	30.11
11	17.4	.125	577.1	1.592	10368.5	26.96	27519.	32.20
12	23.9	.169	619.8	1.522	10004.9	26.13	25894.	24.74
13	30.2	.192	651.3	1.502	9810.0	26.40	24444.	28.74
14	37.1	.225	681.3	1.459	9591.0	26.62	23297.	27.87
15	43.6	.252	706.2	1.415	9399.2	27.57	22253.	27.24
16	48.1	.278	725.9	1.392	9220.6	27.72	21814.	27.01
17	52.2	.298	741.1	1.367	9088.2	28.31	21039.	26.42
18	56.6	.756	756.7	1.351	8720.7	24.40	20542.	14.44
19	58.7	*****	674.0	1.262	-4113.7	-17.25	20571.	-16.32
20	59.3	-.192	540.0	1.102	14394.4	123.58	20552.	142.72

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	5.9	38.6	1.00	71.0	-.085E-01
2	54.2	38.1	1.36	428.0	.154E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
270.2	218.8	1.22	.462E+00	27160.	12437.	.00599

RUN 694H, DATE 4/21/81, GAS HE XE, MOLECULAR WT. = 83.80  
 TIN = 72.3 F, TOUT = 598.2 F, MASS FLOW RATE = 29.3 LB/HR, I = 74.0 AMPS, E = 3.030 VOLTS  
 PR,IN = .251, GR/KESQ = .984E-02, MACH(2) = .068, MACH(16) = .093, T,SURK = 149.0 F, W(8) = .000117

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H I COEF BTU/HRFT2F	BULK KEYNULUS	BULK NUSSLEIT
2	.1	-.289	243.7	1.325	24188.4	140.70	33328.	175.22
3	.3	2.143	301.8	1.429	5497.9	24.10	33203.	33.87
4	.2	.272	349.3	1.513	13633.8	49.77	33080.	39.79
5	.8	.189	387.1	1.577	14621.1	47.27	32933.	38.06
6	1.3	.126	444.9	1.608	15505.7	42.87	32600.	39.45
7	2.2	.097	508.8	1.757	15993.1	38.39	32081.	32.50
8	4.3	.090	603.0	1.850	16206.0	33.24	30810.	44.05
9	7.7	.109	686.3	1.876	16014.3	29.97	29062.	37.83
10	10.9	.128	738.9	1.858	15808.2	28.80	27610.	34.59
11	17.4	.168	817.7	1.789	15350.2	27.29	25143.	30.49
12	23.9	.274	672.2	1.711	14125.7	25.57	23257.	28.73
13	30.5	.321	909.3	1.629	13658.2	25.90	21753.	25.55
14	37.1	.373	543.8	1.560	13172.4	26.24	20479.	24.57
15	43.7	.451	985.8	1.511	12494.1	25.84	19438.	22.99
16	48.2	.507	1010.5	1.480	12053.3	25.38	18825.	22.00
17	52.8	.536	1023.9	1.442	11835.4	26.15	18285.	22.10
18	56.8	1.132	1039.9	1.418	8535.5	19.41	17070.	18.12
19	58.8	*****	908.0	1.295	-11228.4	-36.24	17911.	-30.11
20	59.5	-.179	736.5	1.131	21705.9	159.39	17912.	132.55

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	5.9	38.5	1.00	71.5	-.686E-01
2	54.3	37.9	1.43	552.1	.192E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,8,AV	RE,9,NUSS,AV	RE,9,AV
801.1	290.5	1.68	.571E+00	25721.	9895.	19.54V .00004

RUN 69DH, DATE 4/21/81, GAS HE XE, MOLECULAR WT. = 85.80  
 TIN = 72.8 F, TOUT = 735.5 F, MASS FLOW RATE = 29.9 LB/HR, I = 87.2 AMPS, C = 5.923 VOLTS  
 PRIN = .251, GR/RESQ = .129E-01, MACH(2) = .070, MACH(10) = .101, T,SURR = 203.0 F, Q(10) = .000004

IC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T CUEF BTU/HRFT2F	BULK RLYNULDS	BULK MUSSELT
2	.1	-.304	327.6	1.482	34519.7	135.11	33947.	190.37
3	.3	2.480	408.6	1.627	6944.3	20.79	33711.	29.20
4	.2	.259	475.2	1.744	19291.3	48.42	33010.	67.82
5	.8	.208	529.4	1.833	20172.2	44.94	33547.	62.04
6	1.3	.146	612.2	1.961	21396.4	40.77	32949.	50.23
7	2.2	.113	703.9	2.082	22172.2	36.71	32234.	49.79
8	4.3	.120	841.8	2.204	22248.6	31.33	30226.	40.69
9	7.7	.161	960.5	2.222	21638.7	27.74	28339.	33.80
10	10.9	.193	1027.0	2.172	21154.8	26.41	26290.	30.23
11	17.2	.256	1117.3	2.036	20218.1	22.24	23768.	26.24
12	24.0	.488	1169.2	1.902	17120.4	22.17	21778.	21.62
13	30.6	.536	1192.2	1.778	16613.4	23.04	20277.	21.11
14	37.2	.585	1212.6	1.671	16118.0	24.08	19042.	20.87
15	43.8	.821	1226.9	1.576	15772.1	25.68	18019.	21.20
16	48.3	.873	1244.4	1.527	15301.2	26.14	17409.	20.92
17	52.7	.708	1256.1	1.479	15004.5	27.15	16869.	21.12
18	56.9	1.227	1271.8	1.446	11517.8	21.67	16421.	16.49
19	59.0	***	1117.7	1.522	-17929.9	-46.97	16216.	-32.77
20	59.6	-.169	911.6	1.147	30122.2	173.91	16220.	151.98

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	5.9	38.3	1.00	71.9	-.683E-01
2	54.4	37.7	1.40	717.2	.212E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,AV	RE,WMU,AV	T,AV
1068.2	355.2	1.87	.626E+00	23330.	0115.	.00220

RUN 636H, DATE 4/29/81, GAS HE XE, MOLECULAR WT. = 39.95  
 TIN = 74.6 F, TOUT = 634.3 F, MASS FLOW RATE = 33.6 LB/HR, I = 114.4 AMPS, E = 7.766 VOLTS  
 PR,IN = .214, CR/RESO = .760E-02, MACH(2) = .053, MACH(16) = .074, T,SURR = 195.3 F, Q+(8) = .005320

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HPFT2	H T CDEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.168	291.7	1.403	49639.1	230.46	36183.	125.35
3	.3	.521	357.6	1.520	27263.8	97.62	36044.	52.97
4	.5	.127	407.9	1.606	36934.4	112.51	35583.	61.08
5	.8	.061	445.5	1.667	38625.3	106.69	35711.	57.51
6	1.3	.046	501.1	1.751	40053.9	97.28	35354.	52.03
7	2.2	.037	565.4	1.836	40612.9	87.07	34790.	49.57
8	4.5	.038	671.5	1.942	40857.5	74.51	33453.	38.10
9	7.7	.050	777.3	1.991	40694.5	64.14	31599.	32.25
10	10.9	.061	848.2	1.585	40460.7	62.27	30060.	29.11
11	17.4	.087	960.9	1.942	39812.5	57.83	27426.	25.00
12	23.9	.154	1038.5	1.867	37694.8	54.24	25360.	21.90
13	30.6	.182	1087.0	1.774	36912.5	54.77	23696.	20.84
14	37.2	.212	1129.4	1.691	36118.4	55.71	22310.	20.11
15	43.7	.237	1162.4	1.613	35455.3	57.63	21144.	19.83
16	48.2	.262	1189.8	1.571	34832.4	58.23	20442.	19.44
17	52.6	.280	1210.2	1.528	34376.0	59.71	19618.	19.39
18	56.8	.399	1233.9	1.496	31503.5	56.23	19290.	17.82
19	58.9	*****	1181.2	1.439	-3022.3	-6.11	19193.	-1.93
20	54.5	-.098	1002.0	1.278	48123.6	152.20	19174.	47.70

PT	X/D	STATIC PRESS. (PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	82.6	1.00	76.3	-.673E-01
2	54.4	81.8	1.51	650.8	.195E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TP,AV	DELTA P (PSI)	RE,B,AV	RE,M,MOD,AV	F,B,AV
941.2	213.6	1.81	.756E+00	27847.	9702.	.00545

RUN 197H, DATE 4/29/81, GAS HE XE, MOLECULAR WT. = 39.95  
 TTN = 76.3 F, TOUT = 560.2 F, MASS FLOW RATE = 32.4 LB/HR, I = 99.1 AMPS, E = 6.642 VOLTS  
 PR, IN = .214, GR/PESC = .534E-02, MACH(2) = .055, MACH(16) = .073, T, SURR = 146.5 F, Q+(6) = .004104

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	F T CUEF BTU/HRFT2F	RULK REYNOLDS	RULK NUSSELT
2	.1	-.160	233.9	1.296	36663.6	232.02	34994.	126.21
3	.3	.525	284.7	1.367	20284.9	97.86	34891.	53.15
4	.5	.125	322.6	1.452	27564.4	113.32	34771.	61.39
5	.8	.081	351.1	1.499	28746.9	106.60	34643.	57.59
6	1.3	.047	392.5	1.563	29766.8	97.10	34376.	52.14
7	2.2	.034	438.3	1.625	30245.1	87.66	33953.	46.60
8	4.3	.034	513.5	1.703	30425.2	71.75	32928.	39.27
9	7.7	.042	550.2	1.747	30357.7	67.70	31476.	33.79
10	10.5	.043	635.6	1.746	30280.5	64.43	30230.	31.01
11	17.4	.064	723.3	1.724	29997.1	60.46	28024.	27.31
12	23.9	.098	785.0	1.677	29207.5	58.20	26217.	24.85
13	30.5	.117	831.2	1.618	28795.6	58.49	24662.	23.67
14	37.1	.139	874.6	1.565	26330.2	58.50	23355.	22.73
15	43.7	.152	911.2	1.514	27895.1	60.10	22236.	22.22
16	48.1	.178	939.6	1.486	27501.2	60.25	21552.	21.67
17	52.5	.194	962.5	1.456	27183.1	61.18	20937.	21.45
18	56.7	.324	986.9	1.435	24547.3	56.17	20417.	19.26
19	58.8	*****	945.1	1.382	2706.7	6.59	20298.	2.38
20	59.4	-.097	602.9	1.238	35611.0	147.47	20269.	50.07

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	77.4	1.00	75.8	-.678E-01
2	54.2	76.7	1.45	531.3	.174E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TR,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,M,MOD,AV	F,B,AV
719.4	260.9	1.64	.675E+00	27656.	11493.	.00586

RUN 698H, DATE 4/29/81, GAS HE XE, MOLECULAR WT. = 39.95  
 TIN = 76.3 F, INOUT = 454.6 F, MASS FLOW RATE = 31.8 LB/HR, I = 87.2 AMPS, E = 5.833 VOLTS  
 PR, IN = .214, GF/RESO = .389E-02, MACH(2) = .057, MACH(16) = .072, T, SUKR = 129.5 F, O+(b) = .003232

TC	X/D	HL/OGAS	TW (F)	TW/TB	OGAS BTU/HRFT2	H T COFF BTU/HRFT2F	BULK REYNOLDS	BULK MUSSELT
2	.1	-.156	199.5	1.232	28226.9	227.78	34280.	123.88
3	.3	.519	239.6	1.303	15727.5	96.83	34200.	52.59
4	.5	.139	270.0	1.356	21018.6	109.81	34108.	59.52
5	.8	.082	292.2	1.393	22153.7	104.53	34010.	56.53
6	1.3	.045	323.7	1.442	22997.6	95.85	33803.	51.60
7	2.2	.033	358.7	1.451	23329.0	86.69	33474.	46.30
8	4.3	.031	415.6	1.552	23463.1	75.43	32666.	39.48
9	7.7	.037	472.8	1.589	23434.4	67.91	31504.	34.48
10	10.6	.041	511.1	1.594	23396.1	64.76	30487.	31.98
11	17.4	.053	576.8	1.584	23243.4	60.89	28632.	28.51
12	23.9	.072	626.4	1.555	22912.7	55.20	27060.	26.40
13	30.5	.085	664.5	1.514	22710.2	54.62	25674.	25.41
14	37.1	.099	702.2	1.476	22470.0	60.09	24456.	24.54
15	43.6	.114	736.2	1.440	22222.2	60.93	23395.	23.94
16	48.1	.127	761.9	1.421	21998.8	60.91	22742.	23.35
17	52.5	.137	783.3	1.400	21813.4	61.61	22150.	23.00
18	56.7	.263	805.3	1.384	19687.6	56.22	21645.	20.64
19	58.7	3.828	774.9	1.340	5140.4	16.47	21509.	6.01
20	59.3	-.098	660.1	1.212	27306.9	140.41	21475.	51.05

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.5	73.7	1.00	75.6	-.681E-01
2	54.2	73.0	1.39	439.9	.154E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW, AV(F)	IN, AV(F)	TW, AV/TP, AV	DELTA P(PSI)	RE, D, AV	RE, W, MOD, AV	F, R, AV
577.0	222.4	1.52	.601E+00	28108.	13147.	.00596

RUN 699H, DATE 4/29/81, GAS HE XE, MOLECULAR WT. = 39.95  
 TIN = 75.9 F, TOUT = 299.1 F, MASS FLOW RATE = 32.1 LB/HR, I = 66.2 AMPS, E = 4.423 VOLTS  
 DP,IN = .214, GR/REFSO = .207E-02, MACH(2) = .059, MACH(16) = .069, T,SLRR = 103.0 F, Q+(3) = .001829

TC	X/D	HL/OGAS	TW (F)	TW/TB	OGAS BTU/HRFT2	F T COEF BTU/HRFT2F	REYNOLDS	BULK NUSSELT
2	.1	-.142	147.3	1.135	15924.6	221.82	34686.	120.66
3	.3	.453	169.9	1.176	9170.5	97.91	34640.	53.22
4	.5	.135	186.5	1.205	12076.3	110.01	34587.	59.73
5	.9	.070	199.1	1.226	12826.6	105.54	34530.	57.40
6	1.3	.041	216.7	1.254	13194.7	96.55	34410.	52.21
7	2.2	.031	236.2	1.282	13352.0	87.34	34219.	47.02
8	4.3	.028	267.5	1.320	13411.8	76.31	33741.	40.60
9	7.6	.032	299.2	1.345	13394.1	61.89	33033.	36.01
10	10.8	.035	319.8	1.352	13384.7	66.06	32394.	33.57
11	17.4	.042	357.1	1.357	13326.6	62.17	31169.	30.93
12	23.8	.049	385.7	1.348	13262.1	60.93	30063.	29.40
13	30.4	.055	409.5	1.332	13213.1	61.07	29035.	26.60
14	37.0	.061	433.9	1.318	13154.6	61.18	28095.	27.80
15	43.5	.069	457.9	1.305	13087.7	61.15	27239.	27.10
16	48.0	.074	474.3	1.297	13037.5	61.12	26659.	26.62
17	52.4	.080	490.1	1.289	12982.9	61.10	26176.	26.17
18	56.5	.111	504.1	1.282	11885.3	56.26	25730.	23.74
19	58.6	1.623	487.1	1.251	5342.6	28.26	25587.	11.66
20	59.2	-.094	420.1	1.159	15390.2	128.05	25548.	53.63

PT	X/D	STATIC PRESS. (PSIA)	TW/TB	TR (F)	PRESS DEFFCT
1	5.9	71.4	1.00	75.3	-.679E-01
2	54.1	70.8	1.29	283.6	.118E+01

AVFPAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F) 359.8 TB,AV(F) 158.7 TW,AV/TR,AV 1.33 DELTA P(PSI) .485E+00 RE,B,AV 30334. RE,W,POD,AV 18028. F,B,AV .00608

RUN 70CH, DATE 4/29/81, GAS HF XE, MOLECULAR WT. = 39.95  
 TIN = 75.4 F, TOUT = 165.2 F, MASS FLOW RATE = 32.2 LB/HR, I = 42.3 AMFS, F = 2.787 VOLTS  
 OK, IN = .014, GP/RESO = .754E-03, MACH(2) = .062, MACH(16) = .067, T, SURR = 87.5 F, Q+(6) = .00073F

TC	X/D	IN/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	F T CDEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.136	104.8	1.056	6423.0	216.16	34865.	117.63
3	.3	.482	114.0	1.073	3747.6	97.20	24846.	52.87
4	.5	.122	120.6	1.085	4953.8	110.46	34824.	60.06
5	.6	.072	125.5	1.093	5187.4	105.02	34801.	57.07
6	1.3	.039	132.2	1.104	5351.9	96.79	34752.	52.54
7	2.2	.029	139.4	1.115	5410.4	86.48	34674.	47.54
8	4.3	.026	150.5	1.128	5430.0	76.66	34476.	42.53
9	7.6	.029	162.5	1.139	5416.6	71.68	34175.	36.37
10	10.8	.031	170.4	1.143	5410.1	68.88	33694.	36.62
11	17.3	.037	185.0	1.148	5386.3	65.02	33335.	34.08
12	23.8	.044	195.9	1.147	5354.4	63.98	32810.	33.08
13	30.4	.047	206.0	1.144	5339.0	63.52	32295.	32.61
14	37.0	.052	217.0	1.143	5320.1	63.05	31799.	31.74
15	43.5	.056	227.5	1.142	5303.6	62.60	31331.	31.12
16	47.9	.060	235.2	1.141	5289.8	61.83	31018.	30.48
17	52.3	.063	242.4	1.141	5277.1	61.31	30716.	29.97
18	56.5	.132	249.8	1.140	4956.6	57.50	30447.	27.89
19	58.5	.617	243.1	1.126	3085.9	39.53	30347.	19.12
20	59.1	-.081	216.4	1.062	6092.5	120.52	30319.	56.23

P1	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.8	67.5	1.00	74.7	-.678E-01
2	54.0	67.5	1.14	158.6	.846E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW, AV(F)	TB, AV(F)	TW, AV/TB, AV	DELTA P (PSI)	RE, B, AV	RE, W, MFD, AV	F, B, AV
184.8	108.7	1.14	.370E+00	32732.	25701.	.00588



RUN 701H, DATE 5/13/81, GAS HE XL, MOLEFCULAR WT. = 39.95  
 TIN = 76.0 F, IOUT = 541.1 F, MASS FLOW RATE = 54.2 LB/HR, I = 123.6 AMPS, E = 8.300 VOLTS  
 PR, IN = .214, GR/RESQ = .714E-02, MACH(2) = .060, MACH(16) = .079, T, SURR = 141.0 F, Q+(8) = .003372

TC	X/D	HL/QCAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.122	255.3	1.339	54755.0	302.93	58657.	165.16
3	.3	.354	314.9	1.447	35651.1	149.22	58487.	81.22
4	.5	.104	356.8	1.520	43847.3	157.23	58285.	85.38
5	.8	.056	386.2	1.569	45938.9	150.00	58079.	81.24
6	1.3	.033	427.9	1.633	47120.1	137.07	57650.	73.82
7	2.2	.025	474.6	1.698	47635.4	124.21	56975.	66.26
8	4.3	.025	551.1	1.779	47890.8	108.31	55341.	56.42
9	7.7	.031	627.7	1.825	47881.9	97.53	53016.	49.01
10	10.9	.036	677.7	1.827	47835.2	93.00	51006.	45.24
11	17.4	.047	762.0	1.806	47594.5	87.43	47422.	39.97
12	23.9	.074	829.3	1.766	46605.0	83.45	44452.	35.10
13	30.5	.089	879.2	1.710	46128.5	83.11	41886.	34.14
14	37.1	.106	926.5	1.659	45572.8	82.91	39683.	32.48
15	43.7	.121	964.9	1.606	45071.6	84.01	37801.	31.54
16	48.2	.135	995.6	1.579	44599.9	83.79	36644.	30.62
17	52.5	.147	1020.3	1.549	44208.1	84.54	35603.	30.12
18	56.8	.219	1041.6	1.521	41676.0	81.28	34702.	28.31
19	58.8	2.432	1013.0	1.477	14768.1	31.16	34436.	10.77
20	59.4	-.050	874.8	1.333	52889.2	159.18	34380.	54.81

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	117.8	1.00	74.3	-.600E-01
2	54.3	116.6	1.54	510.2	.158E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TA, AV(F)	762.2	TB, AV(TB, AV)	1.72	RE, B, AV	46948.	RE, W, MOD, AV	17701.	F, H, AV	.00509

RUN 702H, DATE 5/13/81, GAS HE XE, MOLECULAR WT. = 39.95  
 T<sub>IN</sub> = 76.3 F, TOUT = 407.7 F, MASS FLOW RATE = 55.2 LB/HR, I = 104.4 AMPS, E = 7.016 VOLTS  
 PR.IN = .214, GR/RESO = .470E-02, MACH(2) = .062, MACH(16) = .076, T,SLRR = 124.0 F, Q+(8) = .002689

TC	X/D	HL/CGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	F T COEF BTU/HRFT2F	BULK KEYNOLDS	BULK NUSSELT
2	.1	-.110	208.6	1.249	38378.1	269.27	19602.	157.35
3	.3	.338	250.4	1.324	25605.6	147.62	59483.	60.20
4	.5	.097	279.1	1.374	31317.2	155.97	59339.	84.60
5	.8	.057	299.4	1.409	32544.2	141.10	59193.	80.15
6	1.3	.029	326.9	1.452	33502.5	137.17	58889.	73.57
7	2.2	.022	357.7	1.455	33797.9	125.07	58407.	67.00
8	4.3	.021	408.1	1.552	33946.9	110.12	57219.	58.00
9	7.7	.025	459.0	1.588	33960.1	99.95	55500.	51.32
10	10.8	.027	492.5	1.596	33958.1	95.69	53968.	47.99
11	17.4	.034	550.9	1.593	33876.3	90.23	51124.	43.22
12	23.9	.044	596.0	1.572	32641.7	87.78	48649.	40.29
13	30.5	.052	632.7	1.540	33497.8	87.64	46421.	38.04
14	37.1	.060	669.9	1.512	33308.1	87.22	44443.	37.04
15	43.6	.069	701.3	1.481	33128.0	86.02	42672.	36.07
16	48.1	.076	724.4	1.464	32966.2	81.09	41555.	35.26
17	52.4	.081	743.6	1.444	32834.1	89.03	40546.	34.86
18	56.6	.150	763.8	1.429	30923.6	84.45	39663.	32.48
19	58.7	1.102	746.2	1.395	16692.0	49.66	39359.	18.99
20	60.3	-.034	651.8	1.282	36513.6	150.23	39288.	57.16

PT	X/D	STATIC PRESS.(PSIA)	TW/TR	TB (F)	PRESS DEFECT
1	-5.9	117.3	1.00	75.6	-.597F-C1
2	54.2	116.3	1.44	384.0	.128E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

T <sub>IN</sub> ,AV(F)	T <sub>B</sub> ,AV(F)	T <sub>W</sub> ,AV/T <sub>B</sub> ,AV	DELTA P(PFSI)	RE,P,AV	RE,W,MCO,AV	F,B,AV
553.2	158.9	1.54	.951E+00	45891.	22782.	.00509

RUN 703H, DATE 5/13/81, GAS HE AE, MOLECULAR WT. = 39.95  
 TIN = 74.8 F, INOUT = 287.4 F, MASS FLOW RATE = 57.0 LB/HP, I = 84.6 AMPS, F = 5.602 VOLTS  
 PR, IN = .214, GR/RESQ = .296E-02, MACH(2) = .064, MACH(16) = .074, T, SURR = 99.5 F, O+(8) = .001696

TC	X/D	HL/OGAS	TA (F)	TW/TB	OGAS BTU/HRFT2	F T CEEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.096	158.8	1.155	24716.2	295.79	61534.	162.90
3	.3	.309	184.9	1.202	17104.3	156.64	61457.	86.14
4	.5	.095	202.2	1.232	20480.5	164.81	61362.	89.35
5	.8	.042	214.0	1.252	21535.1	159.30	61266.	86.30
6	1.2	.026	230.7	1.279	21902.1	145.98	61067.	73.89
7	2.2	.020	249.3	1.306	22058.0	132.25	60750.	71.70
8	4.3	.019	279.2	1.342	22131.0	117.94	59962.	62.79
9	7.6	.021	309.2	1.366	22132.9	107.72	58787.	56.43
10	10.8	.022	328.5	1.372	22135.5	103.83	57726.	53.53
11	17.4	.025	363.0	1.375	22102.7	98.72	55677.	49.36
12	23.8	.031	390.6	1.367	22052.9	96.77	53809.	47.00
13	30.4	.034	413.8	1.353	22018.8	96.53	52067.	45.77
14	37.0	.038	437.3	1.340	21972.7	96.84	50462.	44.51
15	43.5	.042	459.0	1.326	21925.3	97.40	48987.	43.64
16	48.0	.045	474.0	1.317	21888.1	97.74	48034.	43.06
17	52.4	.048	488.5	1.309	21843.9	97.90	47148.	42.44
18	56.5	.102	501.5	1.300	20785.7	94.04	46353.	40.17
19	58.6	.625	490.7	1.275	14095.0	69.00	46052.	29.30
20	59.2	-.021	434.1	1.156	23284.8	159.68	45975.	67.65

PT	X/D	STATIC PRESS. (PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	117.3	1.00	76.0	-.593E-01
2	54.1	116.5	1.30	271.6	.997E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TA, AV(F)	TB, AV(F)	TW, AV/TB, AV	DELTA P (PSI)	RE, B, AV	RE, W, MND, AV	F, B, AV
366.0	154.1	1.35	.750F+00	54172.	31318.	.00492

RUN 704H, DATE 5/13/81, GAS HE XE, MOLECULAR WT. = 39.95  
 TIN = 75.4 F, TOUT = 148.3 F, MASS FLOW RATE = 55.3 LB/HR, I = 55.7 AMPS, E = 3.684 VOLTS  
 PR,IN = .214, GR/RESQ = .125E-02, MACH(2) = .065, MACH(16) = .069, T,SURR = 67.5 F, O+(8) = .000754

TC	X/D	HL/OGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.094	113.5	1.073	10652.1	277.14	59851.	150.83
3	.3	.312	124.9	1.093	7363.0	146.64	59817.	80.86
4	.5	.073	132.0	1.106	9008.0	160.23	59776.	87.13
5	.8	.052	137.4	1.115	9194.5	150.24	59735.	81.65
6	1.3	.023	144.0	1.126	9460.8	141.16	59646.	76.63
7	2.2	.019	151.5	1.137	9504.2	125.85	59510.	70.36
8	4.3	.018	163.5	1.153	9518.9	115.90	59163.	62.49
9	7.6	.020	176.4	1.164	9512.3	106.69	58635.	57.10
10	10.8	.021	184.7	1.168	9507.0	102.93	58142.	54.69
11	17.3	.024	198.7	1.171	9469.9	98.99	57162.	51.84
12	23.8	.028	210.9	1.172	9458.1	96.77	56237.	49.98
13	30.4	.030	221.7	1.169	9444.9	96.42	55329.	49.12
14	37.0	.033	233.0	1.167	9428.7	95.47	54457.	47.98
15	43.5	.035	243.4	1.165	9414.7	95.32	53630.	47.26
16	47.9	.037	250.7	1.163	9405.1	95.11	53078.	46.76
17	52.3	.039	258.4	1.162	9391.8	94.29	52548.	45.50
18	56.5	.080	264.7	1.160	9041.8	90.94	52067.	43.98
19	58.5	.388	260.8	1.149	7032.1	75.88	51668.	36.57
20	59.1	-.013	236.5	1.108	9869.4	146.22	51814.	70.39

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.8	112.5	1.00	74.7	-.597E-01
2	54.0	111.9	1.16	161.1	.748E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,M,MOD,AV	F,B,AV
201.2	109.6	1.16	.581E+00	56095.	42399.	.00498

RUN 705H, DATE 5/20/81, GAS HE XE, MOLECULAR WT. = 39.95  
 T<sub>IN</sub> = 79.0 F, T<sub>OUT</sub> = 527.0 F, MASS FLOW RATE = 57.5 LB/HR, I = 124.0 AMPS, E = 8.332 VOLTS  
 PR<sub>IN</sub> = .215, GR/RESQ = .943E-02, MACH(2) = .052, MACH(16) = .068, T<sub>SURR</sub> = 142.0 F, Q+(8) = .003650

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.113	253.0	1.325	54486.5	312.44	61772.	169.32
3	.3	.326	309.8	1.426	36629.7	159.42	61603.	80.25
4	.5	.096	348.4	1.493	44435.5	166.68	61400.	89.98
5	.8	.051	375.5	1.538	46410.5	159.07	61194.	85.65
6	1.3	.031	413.6	1.596	47466.3	145.60	60768.	77.95
7	2.2	.022	455.5	1.653	48018.8	132.98	60096.	70.54
8	4.3	.023	525.9	1.727	48231.7	116.35	58471.	60.39
9	7.7	.027	595.3	1.767	48255.6	105.47	56144.	52.91
10	10.9	.031	640.9	1.769	48235.4	100.93	54121.	49.09
11	17.4	.040	718.7	1.749	48064.2	95.37	50488.	43.72
12	23.9	.061	779.4	1.710	47342.9	92.12	47446.	40.04
13	30.5	.072	826.5	1.658	46979.4	92.13	44795.	38.10
14	37.1	.087	874.2	1.615	46513.5	91.74	42491.	36.21
15	43.7	.099	912.1	1.567	46101.8	93.09	40522.	35.26
16	48.1	.111	942.2	1.542	45705.9	92.56	39304.	34.28
17	52.5	.120	964.6	1.512	45416.5	94.37	38205.	33.94
18	56.7	.167	989.0	1.489	42919.2	90.35	37249.	31.76
19	58.8	1.674	964.1	1.448	19019.8	43.26	36946.	15.10
20	59.4	-.038	839.2	1.317	52415.8	166.40	36880.	58.55

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	144.9	1.00	78.5	-.593E-01
2	54.2	143.8	1.50	496.2	.153E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MJD,AV	F,B,AV
720.0	246.0	1.67	.100E+01	45795.	19748.	.00515

RUN 707H, DATE 5/23/81, GAS HF XE, MOLECULAR WT. = 28.30  
 TIN = 76.1 F, TOUR = 451.3 F, MASS FLOW RATE = 49.2 LB/HR, I = 123.6 AMPS, E = 8.255 VOLTS  
 PR,IN = .231, CR/RESO = .448E-02, MACH(2) = .056, MACH(16) = .070, T,SURR = 126.0 F, Q+(E) = .003006

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.095	227.6	1.280	52989.7	353.66	53390.	147.52
3	.3	.271	277.3	1.369	37877.7	190.92	53272.	79.54
4	.5	.084	310.1	1.426	44506.5	193.79	53129.	80.55
5	.8	.044	332.6	1.464	46280.7	184.71	52986.	76.65
6	1.3	.023	363.3	1.511	47342.8	170.32	52692.	70.37
7	2.2	.019	398.7	1.560	47664.2	154.80	52226.	63.49
8	4.3	.018	456.3	1.624	47890.5	136.22	51087.	54.65
9	7.7	.022	515.9	1.666	47929.1	123.07	49436.	48.18
10	10.8	.024	554.0	1.672	47947.1	117.83	47988.	44.96
11	17.4	.031	620.4	1.665	47871.0	111.14	45306.	40.35
12	23.9	.043	673.4	1.641	47486.6	107.46	43004.	37.28
13	30.5	.050	715.3	1.603	47281.4	107.15	40945.	35.60
14	37.1	.060	758.5	1.572	46999.9	106.25	39123.	33.91
15	43.6	.069	793.8	1.535	46736.3	107.16	37496.	32.91
16	48.1	.075	818.2	1.513	46523.9	107.65	36500.	32.28
17	52.5	.082	841.4	1.491	46306.4	106.28	35589.	31.75
18	56.7	.137	863.6	1.473	44138.5	104.07	34790.	29.90
19	58.7	.971	848.8	1.441	25427.5	63.63	34507.	18.14
20	59.4	-.019	747.2	1.325	50728.5	172.06	34443.	48.89

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	135.7	1.00	77.6	-.613E-01
2	54.2	134.7	1.48	424.3	.141E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
623.9	215.9	1.6C	.100E+01	44326.	19069.	.00540

RUN 708H, DATE 5/23/61, GAS HE XE, MOLECULAR WT. = 28.30  
 T<sub>IN</sub> = 79.9 F, T<sub>OUT</sub> = 289.0 F, MASS FLOW RATE = 51.2 LB/HR, I = 94.4 AMPS, E = 6.263 VCLTS  
 P<sub>R,IN</sub> = .231, GR/RESQ = .232E-02, MACH(2) = .059, MACH(16) = .068, T<sub>SURR</sub> = 109.0 F, Q+(8) = .001663

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	P-T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.078	168.6	1.166	30184.4	339.24	55449.	141.09
3	.3	.229	194.0	1.212	22697.6	199.52	55382.	62.92
4	.5	.076	210.8	1.241	25956.0	200.02	55298.	83.04
5	.8	.032	222.1	1.260	27088.1	193.36	55216.	80.18
6	1.3	.020	237.9	1.284	27449.8	178.19	55045.	73.71
7	2.2	.015	255.5	1.310	27606.9	163.66	54774.	67.42
8	4.3	.015	285.0	1.345	27679.0	145.35	54100.	54.25
9	7.6	.016	314.6	1.368	27695.9	133.14	53098.	53.41
10	10.8	.018	334.8	1.376	27701.9	127.77	52187.	50.50
11	17.4	.021	369.3	1.380	27685.2	121.54	50429.	46.63
12	23.8	.024	396.9	1.373	27647.4	115.14	48823.	44.44
13	30.4	.027	419.5	1.358	27625.5	119.58	47315.	43.40
14	37.0	.030	444.0	1.346	27587.3	118.96	45926.	42.06
15	43.5	.033	466.1	1.333	27549.1	119.39	44646.	41.17
16	48.0	.035	481.5	1.325	27517.1	115.55	43814.	40.55
17	52.4	.038	496.8	1.318	27479.3	119.57	43041.	39.93
18	56.6	.080	510.3	1.310	26437.9	115.63	42342.	38.06
19	58.6	.445	503.0	1.289	19751.5	91.79	42065.	30.03
20	59.2	.000	452.7	1.219	28424.4	174.52	41994.	56.97

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	133.9	1.00	79.3	-.607E-01
2	54.1	133.0	1.31	272.9	.105E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P (PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
372.3	156.4	1.35	.823E+00	49098.	28428.	.00538

RUN 709H, DATE 5/23/81, GAS HE XE, MOLECULAR WT. = 28.30  
 TIN = 80.3 F, TOUT = 691.8 F, MASS FLOW RATE = 44.8 LB/HR, I = 152.4 AMPS, E = 10.270 VOLTS  
 PR,IN = .231, GF/RESQ = .667E-02, MACH(2) = .057, MACH(16) = .078, T,SURR = 196.5 F, Q+(E) = .005064

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	F T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.111	326.2	1.457	82585.8	335.29	48411.	139.55
3	.3	.290	402.7	1.594	57251.7	178.41	48232.	74.10
4	.5	.077	454.3	1.681	68837.5	186.12	48016.	77.06
5	.6	.045	492.2	1.742	71170.3	175.67	47798.	72.48
6	1.3	.030	548.7	1.827	72435.9	158.85	47351.	65.06
7	2.2	.023	611.1	1.908	73310.2	143.98	46655.	58.26
8	4.3	.024	714.5	2.008	73752.5	125.22	44998.	49.17
9	7.7	.032	821.6	2.061	73723.9	111.85	42687.	41.99
10	10.9	.038	889.7	2.055	73624.1	106.38	40746.	38.37
11	17.4	.054	1004.2	2.010	73115.0	99.52	37378.	33.31
12	24.0	.095	1085.2	1.935	70724.3	94.64	34665.	29.68
13	30.6	.113	1138.9	1.842	69852.3	95.73	32449.	28.25
14	37.2	.133	1190.7	1.763	68846.8	96.59	30585.	27.04
15	43.8	.150	1230.2	1.684	68001.8	99.23	29007.	26.48
16	48.3	.165	1259.9	1.640	67285.1	100.50	28049.	26.02
17	52.7	.176	1282.6	1.594	66735.1	102.59	27192.	25.92
18	56.9	.224	1308.0	1.559	64219.7	101.61	26448.	24.93
19	58.9	3.050	1287.1	1.523	19378.3	32.40	26234.	7.86
20	59.6	-.037	1125.0	1.376	80650.9	186.92	26195.	45.29

PT	X/D	STATIC PRESS. (PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	122.5	1.00	79.8	-.627E-01
2	54.4	121.3	1.58	651.6	.186E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,M,MND,AV	F,B,AV
990.2	311.7	1.86	.122E+01	37661.	12445.	.00505



RUN 710H, DATE 5/23/81, GAS HE XE, MOLECULAR WT. = 28.30  
 TIN = 80.3 F, IOUT = 168.3 F, MASS FLOW RATE = 45.3 LB/HR, I = 58.0 AMPS, E = 3.786 VOLTS  
 PR,IN = .231, GR/RESQ = .806E-03, MACT(2) = .062, MACH(16) = .066, I,SURR = 103.7 F, Q+(8) = .000705

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.079	119.5	1.074	11374.0	286.42	49001.	119.83
3	.3	.227	129.0	1.091	8539.4	175.31	48976.	72.81
4	.5	.088	135.7	1.103	9635.9	175.21	48945.	72.74
5	.8	.027	139.7	1.109	10209.0	174.14	48914.	72.25
6	1.3	.016	145.4	1.118	10324.6	162.39	48850.	67.31
7	2.2	.014	152.1	1.128	10355.4	150.22	48748.	62.16
8	4.3	.013	162.7	1.141	10375.5	136.00	48491.	56.02
9	7.6	.015	174.6	1.152	10364.7	124.61	48100.	50.97
10	10.8	.015	182.5	1.156	10360.9	120.12	47734.	48.82
11	17.3	.018	196.1	1.160	10344.3	115.06	47009.	46.14
12	23.8	.022	206.2	1.158	10317.6	114.45	46319.	45.31
13	30.4	.023	215.4	1.154	10307.1	115.26	45638.	45.04
14	37.0	.026	225.8	1.152	10292.8	114.49	44986.	44.19
15	43.5	.027	235.3	1.149	10281.4	114.77	44365.	43.76
16	47.9	.029	242.1	1.147	10273.1	114.60	43950.	43.34
17	52.3	.030	249.3	1.147	10262.1	113.65	43550.	42.63
18	56.5	.060	255.7	1.146	9976.1	110.31	43184.	41.08
19	58.5	.261	253.0	1.137	8385.8	96.61	43026.	36.60
20	59.1	.010	234.3	1.105	10459.2	159.86	42983.	59.27

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.8	113.7	1.00	75.7	-.625E-01
2	54.0	113.1	1.15	161.3	.781E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
197.3	112.6	1.15	.566E+00	46197.	35809.	.00538

RUN 711H, DATE 6/2/81, GAS HE XE, MOLECULAR WT. = 14.50  
 TIN = 85.3 F, TOUT = 162.7 F, MASS FLOW RATE = 36.0 LB/HR, I = 67.6 AMPS, E = 4.392 VOLTS  
 PR, IN = .301, GR/RESQ = .503E-03, MACH(2) = .054, MACH(16) = .057, T, SURR = 82.5 F, O+(8) = .000612

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	T T CDEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.068	118.7	1.062	15263.6	453.56	40869.	132.07
3	.3	.201	130.5	1.084	11649.2	261.86	40851.	76.23
4	.5	.082	138.1	1.097	13165.4	250.98	40829.	73.03
5	.8	.027	142.5	1.104	13677.2	245.42	40808.	71.39
6	1.3	.016	148.2	1.113	14030.7	227.81	40764.	66.20
7	2.2	.013	154.4	1.123	14077.6	211.18	40694.	61.28
8	4.3	.013	164.6	1.135	14094.6	190.52	40520.	55.08
9	7.6	.014	175.2	1.145	14090.5	175.79	40252.	50.51
10	10.8	.014	182.2	1.149	14089.1	169.89	40002.	48.54
11	17.3	.016	194.5	1.153	14077.6	162.78	39508.	45.99
12	23.8	.019	204.5	1.153	14052.0	159.82	39033.	44.66
13	30.4	.020	212.4	1.150	14045.8	161.36	38562.	44.59
14	37.0	.021	220.9	1.147	14036.9	161.61	38108.	44.18
15	43.5	.022	229.5	1.145	14028.8	161.59	37675.	43.71
16	47.9	.024	236.3	1.145	14020.4	159.88	37383.	42.94
17	52.3	.025	242.7	1.145	14013.2	158.82	37102.	42.36
18	56.5	.048	248.1	1.143	13706.3	155.41	36840.	41.18
19	58.5	.198	247.3	1.137	11991.3	141.27	36725.	37.33
20	59.1	.016	230.3	1.109	14119.3	210.13	36694.	55.47

PT	X/D	STATIC PRESS. (PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.8	144.7	1.00	84.7	-.653E-01
2	54.0	144.1	1.14	156.4	.774E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW, AV(F)	TB, AV(F)	TW, AV/TB, AV	DELTA P (PSI)	RE, B, AV	RE, W, MOD, AV	F, B, AV
195.5	113.6	1.14	.548E+00	38925.	30649.	.00555

RUN 712H, DATE 6/2/81, GAS HE XE, MOLECULAR WT. = 14.50  
 TIN = 63.9 F, TOUT = 254.1 F, MASS FLOW RATE = 35.6 LB/HK, I = 95.0 AMPS, E = 6.398 VOLTS  
 PR,11 = .301, GR/RESQ = .109E-02, MACF(2) = .054, MACH(16) = .061, T,SURR = 94.5 F, O+(8) = .001337

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	F T CCEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.062	157.2	1.136	32623.3	443.59	40554.	129.57
3	.3	.184	180.5	1.179	25897.2	267.76	40515.	78.10
4	.5	.063	195.6	1.204	28859.3	260.70	40468.	75.97
5	.8	.028	205.2	1.220	29859.6	245.75	40422.	72.71
6	1.3	.015	217.6	1.239	30288.0	232.22	40327.	67.47
7	2.2	.012	231.6	1.259	30397.2	214.05	40177.	62.00
8	4.3	.012	255.2	1.268	30459.5	191.21	39802.	54.92
9	7.6	.013	279.6	1.309	30473.8	175.11	39243.	49.66
10	10.8	.014	295.0	1.314	30488.4	165.24	38732.	47.43
11	17.4	.016	322.4	1.319	30483.8	161.69	37729.	44.24
12	23.8	.018	343.6	1.313	30465.2	159.66	36802.	42.71
13	30.4	.020	360.5	1.300	30460.0	161.51	35917.	42.25
14	37.0	.022	378.5	1.290	30445.8	162.11	35082.	41.50
15	43.5	.023	395.9	1.279	30432.1	163.76	34308.	41.07
16	48.0	.025	408.1	1.272	30419.4	164.37	33798.	40.65
17	52.3	.026	420.8	1.267	30400.5	164.33	33321.	40.12
18	56.5	.055	431.2	1.260	29596.0	161.35	32883.	38.92
19	58.6	.262	427.3	1.246	24725.1	141.91	32696.	34.04
20	59.2	.015	392.4	1.154	30667.0	222.73	32648.	53.33

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	143.2	1.00	83.4	-.654E-01
2	54.1	142.5	1.26	240.6	.977E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
323.6	145.9	1.29	.664E+00	36845.	23353.	.00555

RUN 713H, DATE 6/2/81, GAS HE XE, MOLECULAR WT. = 14.50  
 T<sub>IN</sub> = 63.9 F, T<sub>OUT</sub> = 432.9 F, MASS FLOW RATE = 31.1 LB/HR, I = 131.9 AMPS, E = 8.620 VOLTS  
 PP<sub>IN</sub> = .301, GF/RESQ = .181E-02, MACH(2) = .056, MACH(16) = .069, T<sub>SURR</sub> = 121.5 F, Q+(8) = .002749

TC	X/D	HL/QGAS	TW (F)	TW/TB	CGAS BTU/HRFT2	P T CEEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.077	225.5	1.262	59181.9	417.00	35374.	121.77
3	.3	.215	272.9	1.347	45102.1	239.62	35306.	69.90
4	.5	.068	303.3	1.399	51443.0	236.62	35222.	68.96
5	.8	.045	324.5	1.434	52657.5	222.30	35140.	64.61
6	1.3	.015	349.2	1.471	54303.8	210.07	34973.	60.81
7	2.2	.015	360.9	1.515	54390.1	190.71	34706.	54.84
8	4.3	.015	431.0	1.568	54636.1	165.47	34060.	47.94
9	7.7	.017	482.7	1.603	54708.4	154.54	33114.	42.62
10	10.8	.019	516.4	1.608	54748.7	148.54	32279.	40.03
11	17.4	.023	574.3	1.600	54736.4	141.37	30714.	36.41
12	23.9	.031	618.6	1.574	54512.8	136.88	29345.	34.31
13	30.5	.035	651.3	1.533	54415.8	141.08	28109.	33.50
14	37.1	.040	682.9	1.496	54287.1	143.63	27000.	32.86
15	43.6	.044	711.6	1.459	54152.4	147.22	25963.	32.45
16	48.1	.049	734.3	1.440	54017.9	148.44	25345.	32.00
17	52.5	.052	754.3	1.420	53896.9	150.59	24776.	31.79
18	56.7	.092	774.4	1.403	52019.4	147.13	24270.	30.47
19	58.7	.551	765.5	1.377	36598.7	105.36	24673.	22.48
20	59.3	.007	689.2	1.287	56061.5	219.66	24027.	45.00

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	121.2	1.00	83.4	-.676E-01
2	54.2	120.2	1.41	406.4	.142E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P (PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
573.1	211.6	1.54	.892E+00	29972.	14150.	.00589

RUN 714H, DATE 6/2/81, GAS HE XE, MOLECULAR WT. = 14.50  
 TIN = 85.3 F, TOUT = 564.9 F, MASS FLOW RATE = 30.3 LB/HR, I = 152.7 AMPS, E = 10.300 VELTS  
 PR,IN = .301, GP/RESQ = .245E-02, MACF(2) = .056, MACH(16) = .073, T,SLRR = 159.0 F, Q+(8) = .003799

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	F T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.062	279.5	1.358	80061.3	411.42	34429.	119.98
3	.3	.209	339.9	1.465	61044.5	240.80	34338.	70.11
4	.5	.064	379.9	1.533	69564.6	238.63	34225.	69.32
5	.8	.038	408.1	1.579	71460.3	224.93	34115.	65.17
6	1.3	.020	446.6	1.636	72902.2	207.19	33890.	59.70
7	2.2	.015	489.6	1.692	73486.5	169.46	33537.	54.10
8	4.3	.016	562.8	1.767	73832.4	166.58	32689.	46.51
9	7.7	.020	637.4	1.809	73960.9	150.95	31474.	40.74
10	10.9	.022	686.3	1.810	74008.1	144.47	30419.	37.81
11	17.4	.029	767.4	1.784	73943.2	137.24	28509.	33.86
12	23.9	.046	838.6	1.751	73095.7	131.46	26899.	30.71
13	30.5	.054	884.6	1.689	72762.7	132.82	25456.	29.51
14	37.1	.065	933.4	1.639	72293.8	133.29	24243.	28.31
15	43.7	.073	970.5	1.584	71688.1	136.51	23190.	27.82
16	48.2	.082	1000.7	1.555	71483.7	137.43	22534.	27.27
17	52.6	.086	1016.7	1.515	71308.5	142.44	21940.	27.57
18	56.8	.126	1042.2	1.490	68842.4	139.67	21415.	26.43
19	58.8	.882	1030.7	1.461	41162.3	87.84	21226.	16.48
20	59.4	-.002	918.6	1.345	77021.2	216.60	21187.	40.65

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	118.7	1.00	84.7	-.681E-01
2	54.3	117.6	1.50	529.7	.172E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
770.7	262.2	1.70	.106F+01	28082.	11185.	.00605

RUN 715H, DATE 6/2/81, GAS HE XE, MOLECULAR WT. = 14.50  
 TIN = 85.7 F, TOUT = 673.7 F, MASS FLOW RATE = 30.0 LB/HK, I = 168.7 AMPS, E = 11.420 VCLTS  
 PR,IN = .301, GP/RESO = .305E-02, MACH(2) = .055, MACH(16) = .075, T,SURR = 202.0 F, Q+(8) = .004717

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.092	331.3	1.452	99157.1	403.12	34042.	117.54
3	.3	.219	405.4	1.583	74236.1	233.27	33930.	67.89
4	.5	.067	457.0	1.670	85175.0	231.88	33792.	67.28
5	.8	.038	493.5	1.729	87774.0	216.70	33657.	63.26
6	1.3	.023	545.5	1.806	89373.2	199.29	33380.	57.26
7	2.2	.017	603.5	1.881	90310.1	181.44	32954.	51.56
8	4.3	.019	704.6	1.982	90787.0	157.51	31927.	43.54
9	7.7	.024	806.1	2.034	90937.7	141.42	30487.	37.52
10	10.9	.029	875.2	2.037	90909.1	132.89	29261.	34.23
11	17.4	.040	978.8	1.585	90647.1	126.86	27102.	30.25
12	23.9	.069	1059.8	1.924	88619.7	121.58	25311.	27.22
13	30.6	.082	1113.4	1.837	87889.1	122.81	23819.	25.99
14	37.2	.097	1167.7	1.764	86972.7	123.58	22559.	24.87
15	43.8	.110	1207.6	1.689	86229.9	127.02	21478.	24.41
16	48.2	.122	1240.7	1.649	85508.4	128.04	20813.	23.90
17	52.7	.130	1264.7	1.606	84985.9	130.98	20215.	23.79
18	56.9	.167	1290.1	1.570	82470.7	130.12	19691.	23.05
19	58.9	1.437	1268.9	1.532	39428.0	65.51	19518.	11.57
20	59.6	-.009	1126.7	1.400	96053.1	212.86	19485.	37.22

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	118.3	1.00	85.1	-.683E-01
2	54.4	117.1	1.59	632.5	.193E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
970.3	305.1	1.87	.116E+01	27030.	9226.	.00589

(EXPERIMENTAL K) RUN 719H, DATE 6/23/81, GAS H2 XE, MOLECULAR WT. = 28.97  
 TIN = 69.3 F, TOUT = 350.8 F, MASS FLOW RATE = 56.2 LB/HP, I = 124.8 AMPS, E = 3.120 VOLTS  
 PR,IN = .161, GR/RESC = .187E-02, MACH(2) = .061, MACH(16) = .096, T,SLRR = 110.7 F, Q+(6) = .002051

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HPFI2	T COEF BTU/HPFI2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.062	199.3	1.202	51994.1	470.52	73916.	145.75
3	.3	.172	235.2	1.266	41727.3	286.63	73799.	88.70
4	.5	.056	257.1	1.303	46375.9	278.73	73652.	80.11
5	.8	.029	272.0	1.328	47663.5	264.56	73510.	61.60
6	1.3	.014	291.5	1.357	48430.0	245.54	73218.	75.46
7	2.2	.012	314.2	1.389	48616.5	224.82	72756.	68.69
8	4.3	.012	353.3	1.434	48758.1	198.47	71632.	59.73
9	7.7	.014	394.2	1.468	48816.4	179.76	69967.	52.84
10	10.8	.015	420.1	1.476	48861.1	172.61	68467.	49.65
11	17.4	.018	468.1	1.483	48672.2	162.00	65617.	44.66
12	23.9	.022	503.3	1.471	48808.2	158.61	63064.	42.00
13	30.5	.025	533.3	1.452	48771.8	156.26	60706.	40.31
14	37.0	.028	562.0	1.432	48717.9	156.48	58562.	39.01
15	43.6	.032	589.2	1.413	48650.9	159.25	56621.	37.91
16	48.0	.034	607.3	1.395	48598.6	160.04	55382.	37.31
17	52.4	.037	625.5	1.388	48532.3	160.32	54231.	36.00
18	56.6	.070	642.7	1.378	47079.8	156.31	53196.	34.99
19	58.7	.389	639.7	1.360	36275.2	124.57	52775.	27.75
20	59.3	.013	585.3	1.289	49526.6	212.09	52669.	46.97

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	115.4	1.00	88.5	-.569E-01
2	54.1	114.2	1.38	330.5	.109E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DFLIA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
469.7	185.1	1.44	.119E+01	63858.	32729.	.00486

(EXPERIMENTAL K) RUN 720H, DATE 6/23/81, CAS H2 XF, MOLECULAR WT. = 29.97  
 TIN = 57.3 F, TOUT = 540.0 F, MASS FLOW RATE = 54.9 LB/HR, I = 160.0 AMPS, E = 4.000 VOLTS  
 PR,IN = .161, GP/RESQ = .304E-02, MACH(2) = .080, MACH(16) = .103, T,SURR = 165.5 F, Q+(6) = .00344

TC	X/D	HL/OGAS	TW (F)	TW/TB	OGAS BTU/HRFT2	F T CDEF BTU/HRFT2F	RULK REYNOLDS	BULK NUSSELT
2	.1	-.071	282.7	1.335	86902.3	467.60	71174.	143.11
3	.3	.177	341.2	1.427	68837.7	283.26	70964.	86.55
4	.5	.054	378.5	1.499	77103.0	276.97	70747.	84.39
5	.8	.033	404.9	1.541	78799.5	260.13	70521.	79.04
6	1.3	.016	440.2	1.592	80341.9	240.39	70062.	72.59
7	2.2	.013	481.4	1.646	80818.6	215.03	69339.	65.48
8	4.3	.014	552.4	1.721	81190.2	191.73	67571.	55.89
9	7.7	.017	625.7	1.769	81366.2	172.70	65043.	46.49
10	10.9	.019	674.4	1.777	81451.7	164.46	62838.	44.62
11	17.4	.025	758.6	1.770	81434.2	153.92	58830.	39.08
12	23.9	.037	815.8	1.728	80802.4	150.59	55447.	36.10
13	30.5	.045	865.3	1.681	80502.4	150.23	52463.	34.14
14	37.1	.054	914.6	1.640	80102.8	149.60	49894.	32.34
15	43.7	.062	956.5	1.597	79703.1	150.93	47642.	31.02
16	48.1	.069	986.3	1.571	79357.7	151.34	46244.	30.27
17	52.5	.074	1010.1	1.542	79080.9	153.45	44978.	29.85
18	56.8	.110	1037.0	1.521	76669.6	145.90	43866.	28.39
19	58.8	.740	1031.5	1.497	48904.0	99.03	43453.	18.56
20	59.4	.008	935.5	1.396	83866.5	212.65	43360.	39.73

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	114.9	1.00	96.5	-.574E-01
2	54.3	113.3	1.53	507.2	.143E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
756.2	260.7	1.69	.152E+01	57855.	22657.	.00473



(EXPERIMENTAL K) RUN 721H, DATE 6/23/81, GAS H2 XE, MOLECULAR WT. = 28.97  
 TIN = 89.7 F, TOUT = 252.1 F, MASS FLOW RATE = 55.2 LB/HR, I = 47.8 AMPS, E = 4.890 VOLTS  
 PR,IN = .181, GR/RESQ = .110E-02, MACH(2) = .083, MACH(16) = .092, T,SURR = 104.5 F, Q+(6) = .001273

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T CDEF BTU/HRFT2F	BULK KEYNOLDS	BULK NUSSELT
2	.1	-.057	158.4	1.127	31674.2	458.63	72531.	141.92
3	.3	.162	179.0	1.163	25743.6	288.64	72461.	89.26
4	.5	.058	192.0	1.185	28291.3	278.84	72371.	86.14
5	.8	.022	200.2	1.199	29299.3	268.72	72285.	82.93
6	1.3	.013	211.6	1.216	29594.6	248.86	72106.	76.63
7	2.2	.011	224.7	1.235	29668.0	228.98	71823.	70.25
8	4.3	.011	247.3	1.262	29740.0	203.31	71117.	61.79
9	7.6	.012	270.8	1.283	29756.3	185.39	70075.	55.52
10	10.8	.013	286.7	1.290	29767.6	177.76	69111.	52.49
11	17.4	.015	314.4	1.298	29764.3	168.17	67224.	48.30
12	23.6	.017	335.6	1.294	29748.5	165.22	65483.	46.22
13	30.4	.019	353.5	1.285	29743.4	165.17	63820.	45.02
14	37.0	.021	373.2	1.279	29731.0	164.20	62253.	43.63
15	43.5	.022	391.1	1.271	29716.4	164.29	60800.	42.61
16	48.0	.024	403.9	1.267	29705.6	163.90	59845.	41.83
17	52.3	.025	416.1	1.262	29689.4	163.75	58950.	41.20
18	56.5	.053	425.6	1.255	28936.5	161.32	58131.	40.05
19	58.6	.241	421.7	1.241	24543.1	144.07	57777.	31.56
20	59.2	.010	391.4	1.196	30079.5	217.27	57684.	53.51

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	111.2	1.00	88.9	-.571E-01
2	54.0	110.2	1.26	239.2	.867E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RF,B,AV	RF,W,MOD,AV	F,R,AV
316.7	149.1	1.28	.971E+00	65567.	41801.	.00493

(EXPERIMENTAL K) RUN 722H, DATE 6/23/81, GAS H2 XF, MOLECULAR WT. = 28.97  
 T<sub>IN</sub> = 90.6 F, T<sub>OUT</sub> = 155.2 F, MASS FLOW RATE = 56.2 LB/HK, I = 62.8 AMFS, F = 3.140 VOLTS  
 P<sub>R</sub>, IN = .181, G<sub>R</sub>/RESQ = .411E-03, MACT(2) = .087, MACH(16) = .091, T, SLRR = 95.3 F, Q+(6) = .000511

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	F T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.056	120.0	1.055	13010.8	437.08	73803.	135.03
3	.3	.167	128.2	1.070	10523.6	276.73	73775.	60.00
4	.5	.057	133.0	1.078	11626.5	274.65	73738.	84.79
5	.8	.018	136.1	1.083	12075.5	267.38	73703.	62.51
6	1.3	.015	140.6	1.090	12116.8	247.08	73629.	76.18
7	2.2	.010	145.0	1.096	12162.6	232.00	73513.	71.42
8	4.3	.011	153.9	1.107	12179.0	206.62	73220.	63.37
9	7.6	.012	163.1	1.117	12174.2	184.79	72771.	57.56
10	10.8	.012	169.3	1.121	12171.8	181.36	72355.	54.98
11	17.3	.014	179.9	1.125	12161.0	172.76	71527.	51.77
12	23.8	.017	188.7	1.126	12136.2	166.79	70726.	50.00
13	30.4	.018	196.1	1.124	12129.3	168.52	69932.	49.32
14	37.0	.020	204.8	1.125	12118.3	165.11	69158.	47.81
15	43.5	.021	212.7	1.125	12109.9	163.59	68421.	46.86
16	47.9	.022	218.1	1.125	12103.9	162.54	67925.	46.23
17	52.3	.023	223.5	1.125	12097.9	161.23	67446.	45.53
18	56.5	.044	229.0	1.125	11861.3	156.33	66998.	43.82
19	58.5	.163	228.1	1.120	10638.1	145.92	66746.	40.81
20	59.1	.024	216.7	1.100	12076.4	198.51	66740.	55.46

PT	X/D	STATIC PRESS. (PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.8	108.1	1.00	65.7	-.569E-01
2	54.0	107.3	1.12	145.9	.656E+00

AVERAGE PARAMETERS FROM STAFF OF HEATING TO PT2

TW, AV (F)	TB, AV (F)	TW, AV/TB, AV	DELTA P (PSI)	RE, B, AV	RE, W, MOD, AV	F, B, AV
181.5	114.4	1.12	.768E+00	70529.	57310.	.00473

✓ AD-A148 932

INTERNAL FORCED CONVECTION TO LOW PRANDTL NUMBER GAS  
MIXTURES(U) ARIZONA UNIV TUCSON ENGINEERING EXPERIMENT  
STATION M F TAYLOR ET AL. 15 JUL 84 1248-18


2/2


UNCLASSIFIED

N00014-75-C-0694

F/G 20/13

NL





MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS 1963-A

(CALCULATED K) RUN 7104, DATE 6/23/81, GAS H2 XF, MOLECULAR WT. = 28.97  
 TIN = 85.3 F, TOUT = 350.9 F, MASS FLOW RATE = 56.2 LB/HR, I = 124.8 AMPS, F = 3.120 VOLTS  
 PR, IN = .166, GR/REFCO = .202F-02, MACH(?) = .081, MACH(16) = .096, T, SURR = 110.7 F, Q+(R) = .002050

TC	X/D	HL/OGAS	TW (F)	TW/TR	OGAS RTU/HRFT2	F T COFF BTU/HRFT2F	BULK PFYNOLDS	BULK NUSSELT
2	.1	-.062	199.2	1.202	51904.1	470.57	73916.	157.60
3	.3	.172	235.2	1.266	41727.3	286.66	73799.	95.52
4	.5	.056	257.1	1.303	46375.9	278.75	73652.	93.15
5	.6	.029	272.0	1.328	47663.5	264.58	73510.	88.29
6	1.3	.014	291.5	1.357	46430.0	245.56	73218.	81.70
7	2.2	.012	314.3	1.389	48616.5	224.43	72756.	74.43
8	4.3	.012	353.2	1.424	48758.1	198.48	71632.	64.91
9	7.7	.014	394.3	1.468	48816.4	175.77	69947.	57.69
10	10.8	.015	420.1	1.476	48861.1	172.62	68467.	54.44
11	17.4	.018	468.1	1.483	48872.2	162.01	65617.	49.38
12	23.9	.022	503.3	1.471	48808.2	158.62	63064.	46.84
13	30.5	.025	533.3	1.452	48771.8	156.27	60706.	45.34
14	37.0	.028	562.0	1.432	48717.9	158.50	58562.	44.12
15	43.6	.032	589.2	1.413	48650.9	155.27	56621.	43.16
16	48.0	.034	607.3	1.399	48598.6	160.06	55382.	42.82
17	52.4	.037	625.6	1.388	48532.3	160.35	54231.	42.00
18	56.4	.070	642.7	1.378	47079.6	156.34	53196.	40.33
19	68.7	.389	620.7	1.360	36275.2	124.59	52775.	32.04
20	69.3	.013	585.3	1.289	49526.6	212.14	52669.	54.24

PT	X/D	STATIC PRESS.(PSIA)	TW/TR	TR (F)	PRESS DEFECT
1	-5.0	115.4	1.00	88.5	-.569E-01
2	54.1	114.2	1.38	330.5	.109E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TR,AV(F)	TW,AV/TR,AV	DELTA P(PSI)	RE,B,AV	RE,W,MND,AV	F,R,AV
463.7	185.1	1.44	.119E+01	6385F.	32729.	.00456

(CALCULATED K) RIM 7204, DATE 6/23/41, GAS H2 XE, MOLECULAR WT. = 28.97  
 TIN = 97.3 F, TOUT = 540.0 F, MASS FLOW RATE = 54.9 LB/HR, I = 160.0 AMPS, F = 4.000 VOLTS  
 DR,IN = .164, CR/REFSO = .329E-02, MACH(2) = .080, MACH(16) = .103, T,SHRP = 165.5 F, O+(8) = .003445

TC	X/D	YI/OGAS	TW (F)	TW/TR	OGAS BTU/HRFT2	H-T COEF BTU/HRFT2F	RULK PFYNOLDS	RULK NUSSFLT
2	.1	-.071	282.7	1.335	84902.3	467.63	71174.	155.03
3	.3	.177	341.2	1.437	68837.7	263.29	70984.	93.78
4	.5	.054	378.5	1.459	77103.0	276.98	70747.	91.49
5	.5	.033	404.0	1.541	78799.5	260.14	70521.	85.73
6	1.3	.016	440.2	1.592	80341.9	240.40	70062.	74.85
7	2.2	.013	481.4	1.646	80818.6	219.03	69339.	71.27
8	4.3	.014	552.4	1.721	81190.2	191.74	67571.	61.14
9	7.7	.017	625.7	1.769	81266.2	172.71	65043.	53.44
10	10.0	.019	674.4	1.777	81451.7	164.49	62838.	49.52
11	17.4	.025	759.6	1.770	81434.2	153.02	58830.	43.99
12	23.9	.027	815.8	1.728	80802.4	150.60	55447.	41.07
13	30.5	.045	865.2	1.681	80502.4	150.24	52483.	39.23
14	37.1	.054	914.8	1.640	80102.8	145.61	49894.	37.54
15	43.7	.062	956.5	1.567	79703.1	150.95	47642.	36.51
16	48.1	.069	986.3	1.571	79357.7	151.36	46244.	35.75
17	52.5	.074	1010.1	1.542	79080.9	153.47	44978.	35.44
18	56.8	.110	1037.0	1.521	78669.6	145.53	43666.	33.52
19	58.8	.740	1031.5	1.457	48904.0	99.05	43453.	22.23
20	59.4	.063	935.5	1.396	83866.5	212.69	43360.	47.62

PT	X/D	STATIC PRESS. (PSIA)	TW/TR	TB (F)	PRESS DEFECT
1	-.9	114.0	1.00	96.5	-.574E-01
2	54.3	113.2	1.53	507.2	.143E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TR,AV(F)	TW,AV/TR,AV	DELTA P (PSI)	RE,AV	RE,W,MNO,AV	F,AV
756.2	260.7	1.66	.152E+01	57655.	22657.	.00473

(CALCULATED K) RUN 7214, DATE 6/23/81, GAS H2 XE, MOLFCULAP WT. = 28.97  
 TIN = 89.7 F, TOUT = 252.1 F, MASS FLOW RATE = 55.2 LB/HR, I = 97.8 AMPS, E = 4.890 VOLTS  
 P2,IN = .196, GP/2FSC = .119E-02, MACH(2) = .083, MACH(16) = .092, T,SUPR = 104.5 F, Q+(R) = .001273

TC	X/D	HL/OCAS	TW (F)	TW/TB	OCAS RTU/HRFT2	H T CFFF RTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.057	158.4	1.127	31674.2	458.71	72531.	153.48
3	.3	.162	170.0	1.163	25743.6	288.68	72461.	96.54
4	.5	.058	192.0	1.185	28291.3	278.87	72371.	93.18
5	.8	.022	200.2	1.199	29290.3	268.75	72295.	89.72
6	1.1	.013	211.6	1.216	29594.6	248.89	72106.	82.93
7	2.2	.011	224.7	1.235	29688.0	225.00	71823.	70.07
8	4.2	.011	247.3	1.262	29740.0	203.33	71117.	67.01
9	7.6	.012	270.8	1.283	29756.3	185.41	70075.	60.39
10	10.8	.013	286.7	1.290	29767.6	177.78	69111.	57.26
11	17.4	.015	314.4	1.208	29764.3	168.19	67229.	52.97
12	22.8	.017	335.6	1.264	29748.5	165.23	65483.	50.94
13	30.4	.019	353.5	1.285	29743.4	165.19	63820.	49.89
14	37.0	.021	373.2	1.279	29731.0	164.22	62253.	48.62
15	43.5	.022	391.1	1.271	29718.4	164.31	60800.	47.74
16	48.0	.024	403.9	1.267	29705.6	163.93	59845.	47.03
17	52.3	.025	416.1	1.262	29689.4	163.78	58950.	46.43
18	56.5	.053	425.6	1.255	29636.5	161.35	58131.	45.23
19	58.6	.241	421.7	1.241	24543.1	144.09	57777.	40.19
20	59.2	.010	391.4	1.156	30079.5	217.32	57684.	60.51

DT	X/D	STATIC PRESS. (PSIA)	TW/TB	TB (F)	PRESS DEFFECT
1	-5.9	111.2	1.00	88.5	-.571E-01
2	54.0	110.2	1.26	235.2	.887E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	T3,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,8,AV	RF,W,MDD,AV	F,8,AV
216.7	149.1	1.28	.971E+00	65567.	41801.	.00453

(CALCULATED K) RUN 7224, DATE 6/23/81, GAS H2 XE, MOLECULAR WT. = 28.97  
 TIN = 50.6 F, TOUT = 155.2 F, MASS FLOW RATE = 56.2 LB/HK, I = 62.8 AMPS, F = 3.140 VOLTS  
 22, IN = .166, CP/DECO = .445F-03, MACH(2) = .097, MACH(16) = .091, T, SURR = 95.3 F, O+(F) = .000511

TC	X/D	ML/CCAS	TW (F)	TW/TR	8TU/HRFT2	F T COFF BTU/HRFT2F	BULK PEYMDLDS	BULK NUSSFLT
2	.1	-.056	120.0	1.055	12010.8	437.28	73803.	146.10
3	.3	.167	128.2	1.070	10523.6	278.83	73775.	93.14
4	.5	.057	123.0	1.078	11626.5	274.74	73738.	91.74
5	.8	.018	136.1	1.063	12075.5	267.46	73703.	89.28
6	1.3	.015	140.6	1.060	12116.8	247.15	73629.	82.44
7	2.2	.010	145.0	1.056	12182.6	232.06	73513.	77.31
8	4.3	.011	153.5	1.107	12179.0	206.67	73220.	68.63
9	7.6	.012	163.1	1.117	12174.2	186.83	72771.	62.39
10	10.8	.012	169.3	1.121	12171.6	181.40	72355.	59.66
11	17.3	.014	170.5	1.125	12161.0	172.80	71527.	56.30
12	23.8	.017	188.7	1.126	12136.2	168.83	70726.	54.51
13	30.4	.018	166.1	1.124	12129.3	168.56	69532.	53.92
14	37.0	.020	204.8	1.125	12118.3	165.15	69158.	52.35
15	43.5	.021	212.7	1.125	12109.9	163.63	68421.	51.42
16	47.9	.022	218.1	1.125	12103.9	162.59	67925.	50.80
17	52.3	.023	223.5	1.125	12097.9	161.28	67446.	50.10
18	56.5	.044	229.0	1.125	11861.3	156.38	66938.	48.31
19	58.5	.163	228.1	1.120	10638.1	145.96	66796.	44.96
20	59.1	.024	216.7	1.100	12076.4	198.58	66740.	61.15

PT	X/D	STATIC PRESS. (PSIA)	TW/TR	TR (F)	PRESS DEFECT
1	5.8	108.1	1.00	89.7	-.569E-01
2	54.0	107.3	1.12	145.9	.656F+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TR,AV(F)	TW,AV/TR,AV	DELTA P (PSI)	RE,AV	RE,WMMD,AV	F,3,AV
151.5	114.6	1.12	.768E+00	70.25	57310.	.00473



RUN 723H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 TIN = 86.6 F, TOUT = 146.8 F, MASS FLOW RATE = 57.3 LB/HR, I = 64.0 AMPS, E = 4.219 VOLTS  
 PR,IN = .717, GR/RESQ = .164E-02, MACH(2) = .089, MACH(16) = .094, T,SURR = 82.0 F, Q+(8) = .000480

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.095	133.1	1.067	14080.2	302.03	84169.	380.56
3	.3	.350	149.9	1.117	9449.8	145.53	84137.	188.36
4	.5	.122	159.5	1.135	11385.4	155.93	84103.	196.38
5	.8	.051	166.1	1.146	12155.4	154.01	84069.	193.89
6	1.3	.027	173.2	1.158	12444.3	145.62	84000.	183.18
7	2.2	.020	179.8	1.168	12536.2	137.48	83892.	172.70
8	4.3	.018	189.0	1.180	12568.0	128.08	83621.	160.31
9	7.6	.019	198.2	1.189	12563.9	121.01	83206.	150.62
10	10.8	.020	203.8	1.192	12563.2	116.31	82816.	146.49
11	17.3	.021	213.9	1.156	12552.4	114.73	82056.	140.53
12	23.8	.024	223.0	1.197	12525.8	112.15	81323.	135.92
13	30.4	.025	228.8	1.193	12522.9	113.15	80593.	135.67
14	37.0	.027	238.4	1.196	12508.3	110.36	79876.	130.56
15	43.5	.028	245.1	1.193	12502.0	110.32	79181.	129.56
16	47.9	.029	250.1	1.192	12495.8	105.95	78712.	128.22
17	52.3	.030	255.1	1.192	12488.6	109.49	78257.	126.81
18	56.5	.060	259.2	1.150	12132.5	106.56	77833.	122.64
19	58.5	.287	251.6	1.174	9989.1	95.71	77653.	109.63
20	59.1	-.012	221.4	1.123	12981.3	176.34	77613.	202.14

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	107.5	1.00	85.7	-.552E-01
2	54.0	106.7	1.19	142.0	.656E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
214.8	108.8	1.19	.798E+00	81126.	60191.	.00460

RUN 724H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 TIN = 87.5 F, TOUT = 147.4 F, MASS FLOW RATE = 57.6 LB/HR, I = 63.8 AMPS, E = 4.214 VOLTS  
 PR,IN = .717, GR/RESO = .198E-02, MACH(2) = .081, MACH(16) = .065, T,SURR = 84.3 F, Q+(8) = .000474

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	F T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.093	134.4	1.087	13984.4	297.42	84455.	374.13
3	.3	.347	151.1	1.117	9429.8	148.32	84423.	186.54
4	.5	.121	160.8	1.135	11334.8	155.37	84389.	195.34
5	.8	.043	166.5	1.145	12190.5	155.45	84356.	195.36
6	1.3	.028	173.6	1.156	12371.1	145.62	84287.	182.86
7	2.2	.019	179.7	1.166	12489.2	138.38	84180.	173.54
8	4.3	.018	188.5	1.178	12512.9	128.71	83910.	160.85
9	7.6	.019	198.1	1.167	12508.7	121.51	83498.	151.01
10	10.8	.019	203.6	1.190	12507.7	118.75	83110.	146.60
11	17.3	.021	213.4	1.193	12497.5	115.53	82360.	141.30
12	23.6	.024	221.6	1.193	12472.6	113.80	81632.	137.74
13	30.4	.024	227.4	1.189	12469.0	114.76	80906.	137.44
14	37.0	.026	236.5	1.191	12455.3	112.31	60193.	133.10
15	43.5	.027	242.8	1.188	12448.6	112.65	79502.	132.15
16	47.9	.028	246.4	1.185	12448.9	113.66	79036.	132.44
17	52.3	.029	253.2	1.188	12433.4	111.22	78582.	128.71
18	56.5	.059	257.3	1.166	12087.9	108.30	78160.	124.53
19	58.5	.273	249.3	1.169	10051.5	98.86	77581.	113.35
20	59.1	-.007	220.5	1.120	12855.3	177.79	77541.	203.64

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	118.8	1.00	86.8	-.552E-01
2	54.0	118.1	1.19	142.6	.632E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P (PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
213.9	109.5	1.18	.703E+00	81434.	60685.	.00462

RUN 725H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 T<sub>IN</sub> = 88.4 F, T<sub>OUT</sub> = 236.3 F, MASS FLOW RATE = 57.9 LB/HR, I = 99.5 AMPS, E = 6.740 VOLTS  
 PR, IN = .717, GR/RESQ = .469E-02, MACH(2) = .082, MACH(16) = .091, T, SURR = 99.0 F, Q+(8) = .001156

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.091	203.6	1.212	34125.1	295.95	84778.	371.96
3	.3	.327	242.4	1.282	23436.5	152.50	84700.	191.58
4	.5	.108	265.6	1.323	28121.1	159.45	84616.	200.16
5	.8	.056	280.5	1.349	29536.3	154.92	84534.	194.31
6	1.3	.026	297.3	1.376	30443.9	147.75	84367.	184.95
7	2.2	.020	314.2	1.401	30662.6	138.86	84104.	173.24
8	4.3	.018	338.1	1.430	30770.2	128.59	83450.	159.06
9	7.7	.019	361.1	1.449	30762.3	121.29	82501.	148.05
10	10.8	.020	375.4	1.454	30790.7	118.46	81620.	142.78
11	17.4	.023	400.1	1.455	30774.8	114.80	79873.	134.91
12	23.9	.025	417.8	1.445	30737.5	114.17	78217.	130.90
13	30.4	.027	433.2	1.430	30720.7	114.70	76604.	128.34
14	37.0	.029	450.9	1.421	30692.0	114.19	75105.	124.99
15	43.5	.031	467.6	1.411	30662.0	113.99	73700.	122.25
16	48.0	.033	478.5	1.403	30642.5	114.12	72779.	120.72
17	52.4	.035	490.2	1.398	30611.0	113.72	71930.	118.71
18	56.6	.073	498.8	1.389	29546.6	110.53	71151.	113.97
19	58.6	.374	479.2	1.352	23037.7	94.70	70835.	97.11
20	59.2	-.007	412.0	1.252	31721.0	181.66	70771.	185.68

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	118.6	1.00	87.6	-.551E-01
2	54.1	117.6	1.39	224.7	.850E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW, AV(F)	TB, AV(F)	TW, AV/TB, AV	DELTA P(PSI)	RE, B, AV	RE, W, MOD, AV	F, B, AV
398.8	142.5	1.43	.959E+00	78205.	42556.	.00488

RUN 726H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 T<sub>IN</sub> = 87.0 F, T<sub>OUT</sub> = 243.5 F, MASS FLOW RATE = 44.3 LB/HR, I = 89.8 AMPS, E = 5.930 VOLTS  
 PR<sub>IN</sub> = .717, GP/RESO = .476E-02, MACH(2) = .073, MACH(16) = .081, T<sub>SURR</sub> = 103.5 F, Q+(8) = .001231

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.114	199.0	1.206	28503.4	254.36	64990.	320.30
3	.3	.427	235.9	1.273	17741.5	119.49	64930.	150.40
4	.5	.139	260.5	1.316	22280.6	129.16	64864.	162.44
5	.8	.071	276.3	1.344	23712.5	126.35	64798.	156.76
6	1.3	.034	294.8	1.374	24598.1	120.10	64663.	150.59
7	2.2	.024	313.1	1.401	24861.5	112.59	64448.	140.69
8	4.3	.022	338.6	1.433	24966.7	103.69	63916.	128.39
9	7.7	.024	363.7	1.454	24970.9	97.30	63143.	118.79
10	10.8	.025	378.9	1.459	24974.5	94.88	62428.	114.30
11	17.4	.028	405.5	1.460	24945.9	91.67	61014.	107.50
12	23.9	.031	424.0	1.449	24899.7	91.13	59678.	104.12
13	30.4	.033	439.9	1.433	24877.5	91.69	58380.	102.10
14	37.0	.037	461.2	1.427	24828.1	90.30	57187.	98.32
15	43.5	.039	476.6	1.413	24797.4	90.89	56063.	96.85
16	48.0	.041	487.9	1.405	24768.5	91.00	55344.	95.57
17	52.4	.044	499.1	1.397	24737.6	91.05	54666.	94.31
18	56.6	.094	509.5	1.390	23619.1	87.12	54048.	89.09
19	58.6	.509	486.0	1.348	17093.6	70.33	53809.	71.52
20	59.2	-.024	413.6	1.242	26280.9	155.28	53760.	157.53

PT	X/D	STATIC PRESS. (PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	101.6	1.00	86.5	-.586E-01
2	54.1	100.9	1.39	231.5	.686E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW, AV(F) 404.1	TB, AV(F) 144.3	TW, AV/TB, AV 1.43	DELTA P (PSI) .682E+00	RE, B, AV 55709.	RE, W, MOD, AV 32326.	F, B, AV .00204
--------------------	--------------------	-----------------------	---------------------------	---------------------	--------------------------	--------------------

RUN 727H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 TIN = 86.6 F, TOUT = 148.8 F, MASS FLOW RATE = 45.0 LB/HR, I = 57.6 AMPS, E = 3.690 VOLTS  
 PR,IN = .717, GR/RESO = .177E-02, MACH(2) = .077, MACH(16) = .081, T,SURR = 89.5 F, Q+(8) = .000494

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFI2	I T CDEF BTU/HRFI2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.110	133.1	1.086	11614.2	249.15	66079.	313.82
3	.3	.423	148.5	1.114	7274.1	117.61	66054.	148.11
4	.5	.135	158.2	1.132	9123.0	128.09	66027.	161.25
5	.8	.054	164.3	1.142	9832.4	127.47	66000.	160.42
6	1.3	.039	172.3	1.156	9975.7	117.59	65945.	146.36
7	2.2	.022	178.5	1.165	10150.8	113.01	65858.	141.90
8	4.3	.021	188.1	1.178	10167.9	104.68	65638.	130.95
9	7.6	.022	197.3	1.187	10164.9	98.95	65303.	123.07
10	10.8	.023	203.4	1.190	10161.1	96.38	64987.	119.23
11	17.3	.025	213.5	1.193	10149.1	93.58	64375.	114.48
12	23.8	.028	222.1	1.194	10122.4	91.97	63784.	111.29
13	30.4	.029	228.9	1.191	10115.6	92.15	63195.	110.30
14	37.0	.031	237.5	1.191	10102.8	90.76	62618.	107.46
15	43.5	.033	245.2	1.190	10093.0	90.10	62058.	105.55
16	47.9	.034	250.6	1.190	10085.6	89.51	61680.	104.11
17	52.3	.036	256.1	1.190	10075.8	88.83	61314.	102.61
18	56.5	.072	259.7	1.187	9735.4	86.41	60975.	99.17
19	58.5	.359	251.2	1.169	7672.5	75.03	60834.	85.85
20	59.1	-.023	220.6	1.118	10648.0	149.92	60802.	171.36

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	97.6	1.00	85.9	-.583E-01
2	54.0	97.0	1.19	143.9	.675E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MDD,AV	F,B,AV
214.2	109.5	1.18	.558E+00	63628.	47366.	.00496

RUN 728H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 TIN = 79.5 F, IDUT = 365.3 F, MASS FLOW RATE = 23.1 LB/HR, I = 89.5 AMPS, E = 5.990 VOLTS  
 PR,IN = .719, GR/RESQ = .415E-02, MACH(2) = .078, MACH(16) = .094, T,SURR = 107.0 F, Q+(6) = .002358

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.188	233.6	1.288	30925.2	200.33	34149.	255.55
3	.3	.905	291.1	1.392	13244.0	62.79	34093.	80.02
4	.5	.210	332.6	1.467	20918.9	83.18	34035.	105.86
5	.8	.129	362.5	1.519	22466.6	80.17	33971.	101.87
6	1.3	.074	402.4	1.565	23680.5	74.56	33838.	94.38
7	2.2	.050	441.0	1.643	24299.9	69.04	33627.	86.82
8	4.3	.044	493.6	1.705	24520.3	62.29	33104.	77.00
9	7.7	.049	539.5	1.735	24485.9	57.96	32358.	69.76
10	10.8	.053	567.4	1.734	24445.1	56.32	31681.	66.14
11	17.4	.063	613.7	1.716	24303.1	54.36	30384.	60.80
12	23.9	.082	648.3	1.664	23915.3	53.26	29256.	57.16
13	30.5	.091	673.5	1.641	23764.5	53.83	28247.	55.55
14	37.1	.103	701.9	1.606	23559.2	53.87	27325.	53.38
15	43.6	.114	726.3	1.571	23374.0	54.37	26499.	51.91
16	48.1	.124	746.4	1.553	23190.3	54.14	25977.	50.52
17	52.5	.131	760.8	1.530	23071.0	54.71	25490.	50.08
18	56.7	.255	776.6	1.514	20817.7	49.75	25071.	44.72
19	58.7	2.212	716.1	1.429	6098.5	23.02	24958.	20.55
20	59.3	-.109	580.1	1.260	28908.9	135.44	24937.	120.48

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	49.3	1.00	78.8	-.682E-01
2	54.2	48.7	1.52	346.4	.137E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
607.9	186.5	1.65	.577E+00	29736.	12709.	.00642

RUN 729H, DATE 6/29/81, GAS AIF, MOLECULAR WT. = 28.97  
 TIN = 80.8 F, TOUT = 253.9 F, MASS FLOW RATE = 23.6 LB/HR, I = 70.0 AMPS, E = 4.656 VOLTS  
 PR,IN = .719, GR/RESQ = .212E-02, MACH(2) = .085, MACH(16) = .096, T,SURR = 59.0 F, Q+(6) = .001400

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.175	176.9	1.180	18560.3	192.83	34946.	245.36
3	.3	.796	210.4	1.241	6549.2	66.13	34912.	64.10
4	.5	.215	235.6	1.286	12660.6	82.16	34876.	104.40
5	.8	.122	253.5	1.317	13731.6	80.28	34837.	101.91
6	1.3	.064	276.1	1.355	14508.5	75.50	34756.	95.62
7	2.2	.042	297.9	1.389	14830.0	70.15	34627.	88.49
8	4.3	.036	326.8	1.425	14955.1	63.96	34304.	79.86
9	7.6	.039	353.5	1.447	14943.5	55.67	33825.	73.33
10	10.8	.040	369.6	1.451	14936.4	58.14	33394.	70.36
11	17.4	.046	397.3	1.449	14888.9	56.24	32546.	66.05
12	23.8	.052	418.1	1.437	14824.7	55.72	31751.	63.56
13	30.4	.056	435.4	1.419	14786.5	56.12	30985.	62.23
14	37.0	.061	454.9	1.406	14731.7	55.96	30289.	60.54
15	43.5	.067	473.0	1.393	14678.1	56.04	29639.	59.20
16	48.0	.070	485.3	1.364	14638.4	56.11	29226.	58.35
17	52.4	.074	497.0	1.375	14596.5	56.23	28834.	57.58
18	56.6	.170	506.9	1.366	13412.2	52.06	28484.	52.53
19	58.6	1.168	472.1	1.309	7221.7	33.05	28369.	33.16
20	59.2	-.094	390.6	1.192	17178.9	126.76	28343.	126.84

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	46.5	1.00	80.0	-.678E-01
2	54.1	45.9	1.37	241.6	.107E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
396.1	144.8	1.42	.506E+00	31819.	17524.	.00614

RUN 730H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 TIN = 81.2 F, TOUT = 153.2 F, MASS FLOW RATE = 23.5 LB/HR, I = 45.4 AMPS, E = 2.992 VOLTS  
 PR, IN = .718, GR/RESO = .756E-03, MACH(2) = .092, MACH(16) = .097, T, SURR = 85.0 F, Q+(8) = .CC0586

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	F T COEF BTU/HRFT2F	BULK REYNOLDS	BULK MUSSELT
2	.1	-.171	120.5	1.074	7736.4	196.66	34765.	249.98
3	.3	.812	135.1	1.101	3544.0	65.91	34751.	83.76
4	.5	.203	145.7	1.120	5343.4	83.38	34736.	105.92
5	.8	.118	153.2	1.133	5753.0	80.66	34720.	102.43
6	1.3	.060	162.5	1.149	6074.7	75.96	34686.	96.36
7	2.2	.041	171.3	1.163	6188.6	70.50	34632.	89.29
8	4.3	.035	182.8	1.179	6230.7	64.54	34496.	81.39
9	7.6	.036	192.9	1.186	6228.7	60.83	34266.	76.19
10	10.6	.038	199.9	1.192	6221.2	59.04	34093.	73.47
11	17.3	.041	211.3	1.195	6204.3	57.17	33709.	70.22
12	23.6	.047	220.7	1.194	6174.0	56.24	33347.	68.20
13	30.4	.049	228.4	1.191	6163.4	56.44	32987.	67.57
14	37.0	.053	237.5	1.189	6147.8	55.88	32637.	66.06
15	43.5	.056	246.1	1.188	6133.7	55.51	32298.	64.82
16	47.9	.058	252.0	1.186	6124.0	55.26	32071.	63.99
17	52.3	.061	257.9	1.186	6112.4	54.93	31851.	63.10
18	56.5	.132	262.5	1.183	5727.7	51.70	31650.	58.95
19	58.5	.820	248.1	1.156	3559.0	37.67	31577.	42.82
20	59.1	-.095	212.3	1.096	7142.6	123.01	31559.	139.67

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.8	42.7	1.00	80.3	-.679E-01
2	54.0	42.2	1.18	147.9	.834E+00

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
211.8	108.0	1.18	.425E+00	33266.	24799.	.00607



RUN 731H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 TIN = 81.2 F, TOUT = 475.3 F, MASS FLOW RATE = 22.9 LB/HR, I = 106.0 AMPS, E = 7.180 VOLTS  
 PR, IN = .718, GR/RESQ = .566E-02, MACH(2) = .079, MACH(16) = .10C, T, SURR = 147.5 F, Q+(E) = .003333

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.195	311.6	1.428	44063.6	191.12	33882.	243.25
3	.3	.878	388.2	1.566	19002.7	62.11	33803.	78.44
4	.5	.201	444.7	1.666	29830.4	82.62	33721.	104.81
5	.8	.132	486.0	1.737	31741.8	75.22	33631.	100.27
6	1.3	.076	541.6	1.827	33533.9	74.07	33445.	93.25
7	2.2	.055	598.0	1.909	34324.2	66.23	33148.	65.10
8	4.3	.053	676.5	1.996	34603.2	61.10	32443.	74.40
9	7.7	.061	742.9	2.026	34485.4	56.71	31426.	66.56
10	10.9	.068	781.0	2.012	34373.5	55.17	30521.	62.59
11	17.4	.082	842.2	1.962	34053.9	53.44	28882.	57.06
12	23.9	.126	889.0	1.902	32824.6	51.42	27534.	51.97
13	30.5	.142	920.8	1.830	32445.0	51.51	26342.	49.68
14	37.2	.161	954.0	1.770	31987.6	52.12	25298.	47.74
15	43.7	.177	980.5	1.711	31600.4	52.92	24394.	46.44
16	48.2	.194	1004.2	1.681	31211.2	52.79	23826.	45.02
17	52.6	.206	1021.5	1.647	30933.0	53.31	23301.	44.35
18	56.8	.337	1040.3	1.622	27932.0	46.71	22852.	39.65
19	58.8	5.347	958.6	1.522	5852.3	12.08	22753.	9.76
20	59.5	-.103	778.0	1.324	40891.6	135.66	22740.	109.29

PT	X/D	STATIC PRESS. (PSIA)	TW/TR	TB (F)	PRESS DEFECT
1	-5.9	48.5	1.00	80.6	-.684E-01
2	54.3	47.8	1.64	451.1	.162E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW, AV(F)	TB, AV(F)	TW, AV/TB, AV	DELTA P (PSI)	RF, B, AV	RE, W, MOD, AV	F, B, AV
830.7	231.5	1.87	.690E+00	28509.	10036.	.00643

RUN 732H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 TIN = 82.1 F, TOUT = 589.4 F, MASS FLOW RATE = 23.6 LB/HR, I = 123.4 AMPS, E = 8.331 VOLTS  
 PR,IN = .718, GR/RESQ = .727E-02, MACH(2) = .081, MACH(16) = .109, T,SURR = 200.5 F, Q+(8) = .0064406

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.202	401.6	1.592	60646.8	189.68	34777.	241.28
3	.3	.867	500.6	1.770	26113.9	62.61	34669.	79.50
4	.5	.200	575.6	1.902	40845.7	83.33	34556.	105.54
5	.8	.135	630.5	1.995	43376.1	79.89	34433.	100.87
6	1.3	.083	705.7	2.113	45674.8	74.48	34179.	93.37
7	2.2	.062	781.3	2.218	46826.3	68.78	33781.	85.18
8	4.3	.064	888.0	2.323	47102.9	61.43	32846.	73.72
9	7.7	.079	978.8	2.350	46721.6	56.60	31510.	64.77
10	10.9	.088	1025.2	2.311	46485.6	55.25	30369.	60.66
11	17.5	.108	1098.1	2.211	45850.4	53.81	28398.	54.83
12	24.0	.183	1144.1	2.101	43106.2	51.36	26607.	48.79
13	30.6	.203	1176.3	1.993	42455.4	52.20	25470.	46.88
14	37.2	.223	1204.1	1.896	41841.5	53.33	24333.	45.29
15	43.8	.240	1226.7	1.809	41326.9	54.94	23336.	44.50
16	48.3	.259	1249.0	1.763	40755.4	55.26	22732.	43.37
17	52.7	.272	1263.8	1.715	40400.0	56.38	22179.	43.05
18	56.9	.386	1284.1	1.681	37119.3	52.71	21707.	39.28
19	59.0	****	1186.3	1.574	3363.5	5.66	21616.	4.19
20	59.6	-.098	967.2	1.360	55843.9	148.75	21610.	109.54

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	48.5	1.00	81.4	-.679E-01
2	54.4	47.6	1.70	555.7	.183E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F) 1069.2	TB,AV(F) 279.6	TW,AV/TB,AV 2.07	DELTA P(PSI) .825E+00	RE,B,AV 26400.	RE,W,MOD,AV 8512.	F,B,AV .00611
--------------------	-------------------	---------------------	--------------------------	-------------------	----------------------	------------------

RUN 733H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 TIN = 87.5 F, TOUT = 325.0 F, MASS FLOW RATE = 57.6 LB/HR, I = 125.2 AMPS, E = 8.230 VULTS  
 PR,IN = .717, GR/RESQ = .786E-02, MACH(2) = .080, MACH(16) = .093, T,SURR = 122.0 F, Q+(d) = .0C1666

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.100	278.2	1.351	54874.7	287.44	84294.	362.00
3	.3	.339	339.6	1.461	37041.0	147.25	84170.	185.33
4	.5	.115	377.8	1.528	44627.4	154.52	84035.	194.24
5	.8	.059	402.0	1.570	47071.8	150.56	83903.	164.37
6	1.3	.029	430.9	1.616	48510.4	143.16	83636.	179.14
7	2.2	.023	460.8	1.660	48939.6	133.96	83214.	166.74
8	4.3	.021	503.8	1.710	49157.6	123.06	82202.	151.09
9	7.7	.024	542.5	1.737	49182.7	115.77	80713.	134.17
10	10.8	.025	563.5	1.734	49208.8	113.61	79352.	134.11
11	17.4	.028	601.8	1.721	49166.2	110.78	76698.	125.46
12	23.9	.036	632.3	1.697	48912.1	109.23	74301.	119.38
13	30.5	.039	655.3	1.664	48831.5	110.03	72088.	116.34
14	37.1	.043	680.0	1.635	48718.4	110.31	70092.	113.00
15	43.6	.047	699.6	1.603	48625.5	111.85	68228.	110.80
16	48.1	.050	714.8	1.564	48536.9	112.38	67021.	108.88
17	52.5	.053	728.3	1.565	48459.9	113.30	65926.	107.68
18	56.7	.095	741.9	1.549	46621.1	105.78	64931.	102.52
19	58.7	.497	712.3	1.498	34030.9	87.68	64547.	81.33
20	59.3	-.005	606.5	1.359	50851.0	181.20	64477.	167.60

PT	X/D	STATIC PRESS. (PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	120.4	1.00	86.8	-.552E-01
2	54.2	119.3	1.56	306.9	.103E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P (PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
598.8	174.6	1.67	.113E+01	74932.	31448.	.00462

RUN 734H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 TIN = 89.7 F, TOUT = 418.2 F, MASS FLOW RATE = 58.1 LB/HR, I = 148.0 AMPS, E = 9.910 VOLTS  
 PR, IN = .717, GR/RESQ = .107E-01, MACH(2) = .081, MACH(16) = .099, T, SURR = 157.7 F, Q+(6) = .002597

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	T COEF BTL/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.107	355.1	1.465	77704.3	292.54	84742.	367.35
3	.3	.339	436.5	1.631	52154.5	150.60	84570.	188.93
4	.5	.112	489.7	1.723	63054.6	158.48	84379.	198.49
5	.8	.063	524.2	1.782	66112.2	153.40	84194.	191.75
6	1.3	.033	565.5	1.647	68223.7	145.25	83819.	180.77
7	2.2	.025	608.1	1.907	68978.1	136.02	83243.	168.05
8	4.3	.024	669.7	1.973	69305.3	124.57	81860.	151.03
9	7.7	.028	724.3	2.002	69332.9	117.18	79819.	137.98
10	10.9	.030	753.5	1.990	69347.0	115.00	77977.	131.78
11	17.4	.035	807.7	1.958	69232.2	111.83	74524.	121.80
12	23.9	.053	855.7	1.922	68326.6	108.44	71554.	112.96
13	30.5	.059	887.1	1.867	68079.9	105.08	68861.	108.51
14	37.1	.067	922.4	1.822	67740.0	108.85	66446.	103.70
15	43.7	.076	960.3	1.787	67317.1	107.91	64276.	99.20
16	48.2	.083	985.9	1.764	66989.1	107.26	62906.	96.31
17	52.6	.088	1003.6	1.734	66779.9	108.05	61668.	94.68
18	56.8	.136	1028.4	1.718	64034.3	103.24	60552.	88.49
19	58.8	.776	974.5	1.640	40827.6	73.17	60159.	62.15
20	59.5	-.015	822.0	1.460	72871.7	181.19	60103.	153.24

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	120.3	1.00	89.0	-.551E-01
2	54.3	118.9	1.73	394.1	.121E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
806.6	211.4	1.89	.135E+01	7302C.	25172.	.00476

RUN 735H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 TIN = 90.6 F, TOUT = 506.0 F, MASS FLOW RATE = 58.9 LB/HR, I = 166.0 AMPS, E = 11.340 VOLTS  
 PR, IN = .717, GR/RESO = .136E-01, MACH(2) = .081, MACH(16) = .103, T, SLRR = 198.0 F, Q+(8) = .003317

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.114	432.7	1.624	101592.7	296.81	85824.	372.43
3	.3	.356	537.3	1.810	66820.0	149.94	85599.	187.91
4	.5	.101	606.6	1.930	82729.6	161.20	85349.	201.60
5	.6	.076	656.2	2.014	84943.9	151.41	85105.	188.90
6	1.3	.039	714.2	2.104	88309.3	143.51	84620.	178.07
7	2.2	.029	771.0	2.182	89572.1	134.51	83891.	165.35
8	4.3	.030	856.1	2.269	89955.3	122.35	82113.	146.84
9	7.7	.036	928.6	2.297	89930.6	114.66	79524.	132.89
10	10.9	.040	970.5	2.278	89858.4	112.13	77218.	125.40
11	17.5	.048	1040.7	2.220	89536.3	106.76	73109.	114.61
12	24.0	.079	1093.1	2.146	87309.2	105.37	69636.	104.83
13	30.6	.088	1127.7	2.062	86791.8	106.35	66588.	100.27
14	37.2	.098	1163.3	1.988	86164.9	107.02	63886.	96.57
15	43.8	.103	1180.7	1.903	85675.9	110.57	61553.	95.30
16	48.3	.111	1204.6	1.864	85382.8	110.97	60054.	92.96
17	52.7	.118	1224.2	1.824	84981.3	112.01	58679.	91.46
18	56.9	.155	1241.7	1.788	82322.4	110.08	57501.	87.60
19	59.0	1.003	1184.2	1.709	47298.5	69.59	57102.	54.87
20	59.6	-.015	999.5	1.511	95027.5	193.33	57059.	151.74

PT	X/D	STATIC PRESS. (PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	122.2	1.00	85.9	-.550E-01
2	54.4	120.6	1.81	476.3	.136E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW, AV(F) 1025.4	TB, AV(F) 245.8	TW, AV/TB, AV 2.1C	DELTA P (PSI) .154E+01	RE, B, AV 72075.	RE, W, MOD, AV 20887.	F, R, AV .00455
---------------------	--------------------	-----------------------	---------------------------	---------------------	--------------------------	--------------------

RUN 736H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 TIN = 84.8 F, TOUT = 385.0 F, MASS FLOW RATE = 43.8 LB/HR, I = 123.6 AMPS, E = 8.210 VOLTS  
 PR, IN = .718, GR/RESQ = .893E-02, MACH(2) = .075, MACH(16) = .090, T, SURR = 139.5 F, Q+(8) = .002400

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	H T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.129	307.4	1.411	55358.9	246.48	64311.	314.35
3	.3	.459	378.6	1.539	33237.8	113.41	64194.	143.34
4	.5	.147	426.4	1.623	42438.5	124.93	64067.	157.67
5	.8	.062	457.1	1.676	45912.9	124.37	63939.	156.69
6	1.3	.050	500.5	1.747	46602.2	113.70	63675.	142.68
7	2.2	.029	537.3	1.759	47682.6	107.81	63267.	134.38
8	4.3	.029	595.0	1.866	47857.7	97.92	62282.	119.93
9	7.7	.033	646.0	1.897	47848.8	91.65	60845.	109.26
10	10.9	.035	673.4	1.890	47845.5	89.81	59544.	104.40
11	17.4	.041	721.5	1.863	47723.4	87.35	57060.	96.67
12	23.9	.057	760.3	1.827	47128.2	85.47	54902.	90.74
13	30.5	.064	788.7	1.779	46934.4	86.03	52975.	87.71
14	37.1	.071	817.1	1.735	46704.2	86.49	51191.	84.44
15	43.6	.078	842.3	1.653	46484.4	87.38	49624.	82.25
16	48.1	.085	863.6	1.672	46265.6	87.21	48612.	80.33
17	52.5	.090	881.3	1.648	46088.9	87.63	47672.	79.07
18	56.7	.152	900.3	1.630	43682.0	83.30	46867.	73.61
19	58.8	.909	852.2	1.558	26269.7	56.08	46589.	49.15
20	59.4	-.038	710.4	1.385	51591.8	159.17	46547.	138.96

PT	X/D	STATIC PRESS. (PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	97.9	1.00	64.2	-.587E-01
2	54.2	96.9	1.64	363.3	.121E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,AV	RE,W,MOD,AV	F,8,AV
716.4	195.9	1.79	.940E+00	55851.	20866.	.00517

RUN 737H, DATE 6/29/81, GAS AIR, MOLECULAR WT. = 28.97  
 TIN = 85.3 F, TOUT = 329.2 F, MASS FLOW RATE = 45.1 LB/HR, I = 112.8 AMPS, E = 7.492 VOLTS  
 PR,IN = .716, GR/RESQ = .680E-02, MACH(2) = .077, MACH(16) = .091, T,SURR = 131.5 F, Q+(8) = .001934

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.117	271.6	1.344	45394.5	243.15	66215.	307.31
3	.3	.425	329.4	1.448	28242.6	115.97	66118.	145.46
4	.5	.127	366.6	1.514	35794.3	127.90	66012.	161.34
5	.8	.075	391.9	1.557	37618.8	123.70	65905.	155.61
6	1.3	.038	422.7	1.607	39034.0	117.30	65689.	147.28
7	2.2	.027	453.1	1.652	39550.1	109.99	65348.	137.33
8	4.3	.025	497.0	1.703	39744.8	100.77	64518.	124.05
9	7.7	.027	537.0	1.731	39756.2	94.60	63310.	113.93
10	10.8	.029	560.3	1.731	39760.3	92.44	62205.	109.07
11	17.4	.034	600.5	1.719	39697.6	89.71	60059.	101.59
12	23.9	.043	631.9	1.695	39443.6	88.33	58127.	96.43
13	30.5	.047	654.9	1.659	39354.5	89.07	56353.	94.00
14	37.1	.052	680.0	1.630	39230.0	89.29	54751.	91.21
15	43.6	.056	701.4	1.598	39123.4	90.26	53259.	89.05
16	48.1	.062	721.9	1.566	38986.1	89.54	52302.	86.41
17	52.5	.065	737.6	1.549	38888.3	89.62	51428.	84.99
18	56.7	.121	751.6	1.553	36982.2	85.99	50640.	79.58
19	58.7	.660	712.6	1.490	24908.2	64.79	50351.	59.66
20	59.3	-.029	599.3	1.342	42260.9	157.21	50300.	144.63

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	97.3	1.00	84.6	-.563E-01
2	54.2	96.4	1.56	311.1	.109E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,8,AV	RE,W,MOD,AV	F,8,AV
596.8	175.0	1.66	.902E+00	58679.	24733.	.00516

RUN 738H, DATE 6/29/61, GAS AIR, MOLECULAR WT. = 28.97  
 TIN = 85.7 F, TOUT = 550.6 F, MASS FLOW RATE = 43.8 LB/HR, I = 155.2 AMPS, E = 10.500 VOLTS  
 PR, IN = .718, GR/RESO = .140E-01, MACH(2) = .074, MACH(16) = .097, T, SURR = 201.0 F, Q+(6) = .003816

TC	X/D	HL/QGAS	TW (F)	TW/TB	QGAS BTU/HRFT2	F T COEF BTU/HRFT2F	BULK REYNOLDS	BULK NUSSELT
2	.1	-.142	435.9	1.645	89521.5	255.44	64199.	323.05
3	.3	.482	544.4	1.839	52207.5	114.13	64012.	144.13
4	.5	.140	620.1	1.971	68221.1	128.38	63809.	161.76
5	.8	.086	672.3	2.059	71884.6	123.61	63604.	155.32
6	1.3	.052	739.4	2.164	74581.5	115.74	63188.	144.52
7	2.2	.038	805.3	2.255	75909.4	107.93	62551.	133.35
8	4.3	.041	903.0	2.353	76223.1	97.37	61035.	117.03
9	7.7	.050	984.3	2.378	76000.4	90.91	58848.	104.60
10	10.9	.052	1014.6	2.326	76001.1	90.53	56940.	100.48
11	17.5	.064	1086.9	2.246	75503.3	88.11	53580.	91.49
12	24.0	.108	1142.9	2.161	72753.4	84.62	50770.	82.29
13	30.6	.120	1175.1	2.058	72179.4	86.02	48376.	79.27
14	37.2	.133	1209.9	1.973	71464.4	86.95	46300.	76.15
15	43.8	.144	1235.6	1.690	70922.2	89.02	44467.	74.35
16	48.3	.157	1262.3	1.649	70261.7	89.06	43327.	72.22
17	52.7	.162	1275.3	1.798	69976.0	91.06	42313.	71.72
18	56.9	.212	1292.9	1.760	67174.7	86.99	41408.	68.43
19	59.0	1.717	1220.5	1.669	29826.9	44.41	41135.	33.84
20	59.6	-.040	1017.2	1.462	83267.3	179.19	41107.	135.90

PT	X/D	STATIC PRESS.(PSIA)	TW/TB	TB (F)	PRESS DEFECT
1	-5.9	98.1	1.00	85.1	-.588E-01
2	54.4	96.9	1.78	519.1	.150E+01

AVERAGE PARAMETERS FROM START OF HEATING TO PT2

TW,AV(F)	TB,AV(F)	TW,AV/TB,AV	DELTA P(PSI)	RE,B,AV	RE,W,MOD,AV	F,B,AV
1071.3	261.5	2.12	.116E+01	53119.	15219.	.00476



## REFERENCES

- Barua, A. K., 1960. Thermal Conductivity and Eucken-type Factor for the Binary Mixtures H-He, H-Ne, H-Kr and H-Xe. Indian J. Phys., **34**, pp. 169-183.
- Churchill, S. W., 1977. Comprehensive Correlating Equations for Heat, Mass and Momentum Transfer in Fully Developed Flow in Smooth Tubes. Ind. Eng. Chem., Fundam., **16**, No.1, pp. 109-116.
- Clarke, A. G. and E. B. Smith, 1968. Low-temperature Viscosities of Argon, Krypton, and Xenon. J. Chem. Phys., **48**, pp. 3988-3991.
- Clifford, A. A., R. D. Fleeter, J. Kestin and W. A. Wakeham, 1980. Thermal Conductivity of Mixtures of Hydrogen and Helium at 27.5°C and Pressures up to 14 MPa. Berichte der Bunsen-Gesellschaft für Physikalische Chemie, **84**, pp. 18-23.
- Colburn, A. P., 1933. Method of Correlating Forced Convection Heat Transfer Data and a Comparison with Liquid Friction. Trans. AIChE, **29**, pp. 174-210.
- Dawe, R. A., and E. B. Smith, 1970. Viscosities of the Inert Gases at High Temperature, J. Chem. Phys., **52**, pp. 693-703.
- DiPippo, R. and J. Kestin, 1968. The Viscosity of Seven Gases up to 500°C and Its Statistical Interpretation. Fourth Symposium on Thermal Physical Properties, New York, pp. 304-313.
- Dittus, F. W. and L. M. K. Boelter, 1930. Heat Transfer in Automobile Radiators of the Tubular Type. Univ. Calif. Publ. in Engrg., **2**, pp. 443-461.
- Doebelin, E. O., 1966. Measurement Systems: Application and Design. McGraw-Hill, New York.
- Gandhi, J. M. and S. C. Saxena, 1968. Correlated Thermal Conductivity Data of Rare Gases and Their Binary Mixtures at Ordinary Pressures. J. Chem. Engng., **13**, pp. 357-361.
- Gnielinski, V., 1975. Neue Gleichungen für den Wärme-und den Stoffübergang in Turbulent Durchströmten Rohren und Kanälen. Sonderdruck aus Forschung im Ingenieurwesen, **1**, pp. 8-16. Also Int. Chem. Engr., **16**, pp. 359-368.

#### REFERENCES (continued)

- Hess, W. G., 1965. Thermocouple Conduction Error with Radiation Heat Loss. M.S.E. Thesis, University of Arizona.
- Hilsenrath, J. C., W. Beckett, W. S. Benedict, L. Fano, H. J. Hoge, J. F. Masi, R. L. Nuttall, Y. S. Touloukian and H. W. Wooley, 1955. Tables of Thermal Properties of Gases. NBS Circular 564.
- Hirschfelder, J. O., C. F. Curtiss and R. B. Bird, 1964. Molecular Theory of Gases and Liquids, John Wiley, New York.
- Kalelkar, A. S. and J. Kestin, 1970. Viscosity of He-Ar and He-Kr Binary Gaseous Mixtures in the Temperature Range 25-720°C. J. Chem. Phys., 52, pp. 4248-4261.
- Kays, W. M., 1966. Convective Heat and Mass Transfer. McGraw-Hill, New York.
- Kestin, J., 1983. Personal Communication, Brown Univ., Providence, R. I., 3 March, 1983.
- Kestin, J., S. T. Ro and W. A. Wakeham, 1972. Viscosity of the Noble Gases in the Temperature Range 25-700°C. J. Chem. Phys., 56, pp. 4119-4124.
- Kline, S. J. and F. A. McClintock, 1953. The Description of Uncertainties in Single Sample Experiments. Mech. Engng., 75, No. 1, pp. 3-8.
- Lindsay, A. L. and L. A. Bromley, 1950. Thermal Conductivity of Gas Mixtures. Ind. Eng. Chem., 42, pp. 1508-1511.
- Malina, J. A. and E. M. Sparrow, 1964. Variable-property, Constant-property, and Entrance-region Heat Transfer Results for Turbulent Flow of Water and Oil in a Circular Tube. Chem. Engng. Sci., 19, pp. 953-961.
- Mason, E. A. and H. von Ubish, 1960. Thermal Conductivity of Rare Mixtures. Phys. Fluids, 3, pp. 355-361.
- Moen, W. K., 1960. Surface Temperature Measurements. Inst. Control Syst., 33, pp. 70-73.
- Park, J. S., M. F. Taylor and D. M. McEligot, 1982. Heat Transfer to Pulsating, Turbulent Gas Flow. Proc., Seventh Int. Heat Transfer Conf., Munchen, 3, pp. 105-110.

## REFERENCES (continued)

- Petukhov, B. S., 1970. Heat Transfer and Friction in Turbulent Pipe Flow with Variable Physical Properties, Adv. Heat Transfer, 6, pp. 503-564.
- Pickett, P. E., 1976. Heat and Momentum Transfer to Internal, Turbulent Flow of Helium-Argon Mixtures in Circular Tubes. M.S.E. Report, University of Arizona.
- Pickett, P. E., M. F. Taylor and D. M. McEligot, 1979. Heated Turbulent Flow of Helium-Argon Mixtures in Tubes. Int. J. Heat Mass Transfer, 22, pp. 705-719.
- Pierce, B. L., 1981. The influence of Recent Heat Transfer Data on Gas mixtures (He-Ar, H<sub>2</sub>-CO<sub>2</sub>) on Closed Cycle Gas Turbines, ASME J. Eng. Power, 103, pp. 114-117.
- Reynolds, W. C., 1968. Thermodynamics, 2nd Edition, p. 228, McGraw-Hill, New York.
- Reynolds, W. C. and H. C. Perkins, 1968. Engineering Thermodynamics, McGraw-Hill, New York.
- Saxena, V. K. and S. C. Saxena, 1968. Measurements of the Thermal Conductivity of Helium Using a Hot-wire-Type of Thermal Diffusion Column. Br. J. Appl. Phys., (J. Phys. D.), 1, 1341-1351.
- Saxena, V. K. and S. C. Saxena, 1969. Thermal Conductivity of Krypton and Xenon in the Temperature Range 350-1500°K. J. Chem. Phys., 51, pp.3361-3368.
- Saxena, S. C. and P. K. Tondon, 1971. Experimental Data and Procedures for Predicting Thermal Conductivity of Binary Mixtures of Nonpolar Gases. J. Chem. and Eng. Data, 16, pp. 212,220.
- Serksnis, A. W., 1977. Turbulent Flow of Hydrogen-Carbon Dioxide Mixtures in Heated Tubes. M.S.E. Report, University of Arizona.
- Serksnis, A. W., M. F. Taylor and D. M. McEligot, 1978. Heat Transfer to Turbulent Flow of Hydrogen-Carbon Dioxide Mixtures, Proc., 6th Int. Heat Transfer Conf., Toronto, 2, pp. 163-168.
- Sleicher, C. A. and M. W. Rouse, 1975. A Convenient Correlation for Heat Transfer to constant and variable property fluids in turbulent pipe flow, Int. J. Heat Mass Transfer, 18, pp. 677-683.

#### REFERENCES (continued)

Taylor, M. F., 1967. A Method of Correlating Local and Average Friction Coefficients for Both Laminar and Turbulent Flow of Gases Through a Smooth Tube with Surface to Fluid Bulk Temperature Ratios from 0.35 to 7.35, Int. J. Heat Mass Transfer, 10, pp. 1123-1128.

Taylor, M. F., 1968. Correlation of Local Heat Transfer Coefficients for Single-Phase Turbulent Flow of Hydrogen in Tubes with Temperature Ratios to 23. NASA TN D-4332.

Thornton, E., 1960. Viscosity and Thermal Conductivity of Binary Gas Mixtures: Xenon-Krypton, Xenon-Argon, Xenon-Neon and Xenon-Helium. Proc. Phys. Soc., 76, pp. 104-112.

Touloukian, Y. S. and C. Y. Ho, 1970. Thermophysical Properties of Matter, Plenum Press, London.

Trautz, M. and R. Heberling, 1934. Viscosity, Thermal Conductivity and Diffusion in Gas Mixtures, XXV Internal Viscosity of Xenon and Its Mixtures with Hydrogen and Helium. Ann. Physik, 20, pp. 118-120.

Tsederberg, N. V. T., 1965. Thermal Conductivity of Gases and Liquids, M.I.T. Press, Cambridge.

DISTRIBUTION LIST

HEAT TRANSFER

One copy except  
as noted

Mr. M. Keith Ellingsworth 5  
Materials and Mechanics Program (Code 431)  
Office of Naval Research  
800 N. Quincy Street  
Arlington, VA 22203

Defense Documentation Center 12  
Building 5, Cameron Station  
Alexandria, VA 22314

Technical Information Division 6  
Naval Research Laboratory  
4555 Overlook Avenue SW  
Washington, DC 20375

Professor Paul Marto  
Department of Mechanical Engineering  
US Naval Post Graduate School  
Monterey, CA 93940

Professor Bruce Rankin  
Naval Systems Engineering  
US Naval Academy  
Annapolis, MD 21402

Office of Naval Research Eastern/  
Central Regional Office  
Bldg 114, Section D  
666 Summer Street  
Boston, Massachusetts 02210

Office of Naval Research Branch Office  
536 South Clark Street  
Chicago, Ill. 60605

Office of Naval Research  
Western Regional Office  
1030 East Green Street  
Pasadena, CA 91106

Mr. Charles Miller, Code 05R13  
Crystal Plaza #6  
Naval Sea Systems Command  
Washington DC 20362

Steam Generators Branch, Code 5222  
National Center #4  
Naval Sea Systems Command  
Washington, DC 20362

Heat Exchanger Branch, Code 5223  
National Center #3  
Naval Sea Systems Command  
Washington, DC 20362

Mr. Ed Ruggiero, NAVSEA 08  
National Center #2  
Washington, DC 20362

Dr. Earl Quandt Jr., Code 272  
David Taylor Ship R&D Center  
Annapolis, MD 21402

Mr. Wayne Adamson, Code 2722  
David Taylor Ship R&D Center  
Annapolis, MD 21402

Dr. Win Aung  
Heat Transfer Program  
National Science Foundation  
1800 G St. NW  
Washington, DC 20550

Mr. Michael Perlswieg  
Department of Energy  
Mail Station E-178  
Washington, DC 20545

Dr. W.H. Thielbahr  
Chief, Energy Conservation Branch  
Dept. of Energy, Idaho Operations Office  
550 Second Street  
Idaho Falls, Idaho 83401

Professor Ephriam M. Sparrow  
Department of Mechanical Engineering  
University of Minnesota  
Minneapolis, Minnesota 55455

Professor J.A.C. Humphrey  
Department of Mechanical Engineering  
University of California, Berkeley  
Berkeley, California 94720

Professor Brian Launder  
Thermodynamics and Fluid Mechanics Division  
University of Manchester  
Institute of Science & Technology  
PO88 Sackville Street  
Manchester M601QD England

Professor Shi-Chune Yao  
Department of Mechanical Engineering  
Carnegie-Mellon University  
Pittsburgh, PA 15213

Professor Charles B. Watkins  
Chairman, Mechanical Engineering Department  
Howard University  
Washington, DC 20059

Professor Adrian Bejan  
Department of Mechanical Engineering  
University of Colorado  
Boulder, Colorado 80309

Professor Donald M. McEligot  
Department of Aerospace and Mechanical Engineering  
University of Arizona  
Tucson, AZ 85721

Professor Paul A. Libby  
Department of Applied Mechanics and Engineering Sciences  
University of California San Diego  
Post Office Box 109  
La Jolla, CA 92037

Professor C. Forbes Dewey Jr.  
Fluid Mechanics Laboratory  
Massachusetts Institute of Technology  
Cambridge, Massachusetts 02139

Professor William G. Characklis  
Dept. of Civil Engineering and Engineering Mechanics  
Montana State University  
Bozeman, Montana 59717

Professor Ralph Webb  
Department of Mechanical Engineering  
Pennsylvania State University  
208 Mechanical Engineering Bldg.  
University Park, PA 16802

Professor Warren Rohsenow  
Mechanical Engineering Department  
Massachusetts Institute of Technology  
77 Massachusetts Avenue  
Cambridge, Massachusetts 02139

Professor A. Louis London  
Mechanical Engineering Department  
Bldg. 500, Room 501B  
Stanford University  
Stanford, CA 94305

Professor James G. Knudsen  
Associate Dean, School of Engineering  
Oregon State University  
219 Covell Hall  
Corvallis, Oregon 97331

Professor Arthur E. Bergles  
Mechanical Engineering Department  
Iowa State University  
Ames, Iowa 50011

Professor Kenneth J. Bell  
School of Chemical Engineering  
Oklahoma State University  
Stillwater, Oklahoma 74074

Dr. James J. Lorenz  
Component Technology Division  
Argonne National Laboratory  
9700 South Cass Avenue  
Argonne, Illinois 60439

Dr. David M. Eissenberg  
Oak Ridge National Laboratory  
P.O. Box Y, Bldg. 9204-1, MS-0  
Oak Ridge, Tennessee 37830

Dr. Jerry Taborek  
Technical Director  
Heat Transfer Research Institute  
1000 South Fremont Avenue  
Alhambra, CA 91802

Dr. Simion Kuo  
Chief, Energy Systems  
Energy Research Laboratory  
United Technology Research Center  
East Hartford, Connecticut 06108

Mr. Jack Yampolsky  
General Atomic Company  
P.O. Box 81608  
San Diego, CA 92138

Mr. Ted Carnavos  
Noranda Metal Industries, Inc.  
Prospect Drive  
Newtown, Connecticut 06470

Dr. Ramesh K. Shah  
Harrison Radiator Division  
General Motors Corporation  
Lockport, New York 14094

Dr. Ravi K. Sakhuja  
Manager, Advanced Programs  
Thermo Electron Corporation  
101 First Avenue  
Waltham, Massachusetts 02154



Mr. Robert W. Perkins  
Turbotec Products, Inc.  
533 Downey Drive  
New Britain, Connecticut 06051

Dr. Keith E. Starner  
York Division, Borg-Warner Corp.  
P.O. Box 1592  
York, PA 17405

Mr. Peter Wishart  
C-E Power Systems  
Combustion Engineering, Inc.  
Windsor, Connecticut 06095

Mr. Henry W. Braum  
Manager, Condenser Engineering Department  
Delaval  
Front Street  
Florence, New Jersey 08518

Dr. Thomas Rabas  
Steam Turbine-Generator Technical Operations Division  
Westinghouse Electric Corporation  
Lester Branch  
P.O. Box 9175 N2  
Philadelphia, PA 19113

Dr. Albert D. Wood  
Director, Mechanics Program (Code 432)  
Office of Naval Research  
800 N. Quincy Street  
Arlington, VA 22203

Mr. Walter Ritz  
Code 033C  
Naval Ships Systems Engineering Station  
Philadelphia, Pa 19112

Mr. Richard F. Wyvill  
Code 5232  
NC #4  
Naval Sea Systems Command  
Washington, DC 20362

Mr. Doug Marron  
Code 5231  
NC #4  
Naval Sea Systems Command  
Washington, DC 20362

Mr. T. M. Herder  
Bldg. 46462  
General Electric Co.  
1100 Western Avenue  
Lynn, MA 01910

Mr. Ed Strain  
AiResearch of Arizona  
Dept. 76, Mail Stop 301-2  
P. O. Box 5217  
Phoenix, AZ 85010  
(Tel. 602-267-2797)

Mr. Norm McIntire  
Solar Turbines International  
2200 Pacific Highway  
San Diego, CA 92101

Prof. Darryl E. Metzger  
Chairman, Mechanical and Aerospace  
Engineering Dept.  
Arizona State University  
Tempe, AZ 85281

The Study Center  
National Maritime Research Center  
Kingspoint, N. Y. 11024  
Attn: Ms. Shirley Rose

**END**

**FILMED**

**2-85**

**DTIC**